

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396496
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Davis; Angela Louise

Garment for facilitating urination

Abstract

A garment for facilitating urination includes two leg openings, and an access panel between the two leg openings. The access panel extends from a front of the garment to a back of the garment, wherein the access panel is coupled to the front of the garment with an attachment. The garment is configurable between an initial, closed configuration and a second, open configuration in which the access panel is at least partially detached from the garment.

Inventors:	Davis; Angela Louise (St. Peters, MO)
Applicant:	Davis; Angela Louise (St. Peters, MO)
Family ID:	1000008782942
Appl. No.:	16/999190
Filed:	August 21, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210052021 A1	Feb. 25, 2021

Related U.S. Application Data

us-provisional-application US 62891245 20190823

Publication Classification

Int. Cl.: A41D1/06 (20060101)

U.S. Cl.:

CPC A41D1/065 (20130101); A41D2300/32 (20130101); A41D2300/33 (20130101)

Field of Classification Search

CPC: A41B (9/004); A41B (9/005); A41B (9/007); A41D (1/065)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1179159	12/1915	Buley	2/407	A41B 9/04
1270190	12/1917	Morris	2/237	A41F 9/02
1469287	12/1922	Torchia	2/408	A41B 9/04
2014802	12/1934	Gulke	2/237	A41F 9/02
2256884	12/1940	Boysen	2/404	A41B 9/14
2281872	12/1941	Donnelly	2/237	A41F 9/025
2334144	12/1942	Bono	D2/742	A41D 1/21
3279469	12/1965	Schustack	2/408	A41C 1/003
3793646	12/1973	Tempelhof	2/DIG.1	A41D 1/06
3974836	12/1975	Carlson	2/408	A41C 1/003
4280230	12/1980	LaFleur	2/408	A61F 13/70
4389733	12/1982	Boykins, Jr.	2/466	A41D 1/08
4961234	12/1989	Leibman	2/408	A41D 1/06
5926851	12/1998	Kovalik	2/114	A41D 13/1254
6324699	12/2000	Cosmah	2/408	A41B 11/14
6412119	12/2001	Robles	2/400	A41B 9/026
7100214	12/2005	Murray	2/408	A41C 1/003
7727218	12/2009	Lavon et al.	N/A	N/A
8087098	12/2011	Kimberly	2/403	A41B 9/001
8088116	12/2011	Kline et al.	N/A	N/A
8479320	12/2012	Swafford	2/78.2	A41D 1/065
9089173	12/2014	Krishnan	N/A	A41D 1/06
9125440	12/2014	Guerrero	N/A	A41D 1/06
9522088	12/2015	Ashton et al.	N/A	N/A
9750287	12/2016	Cohen Larren	N/A	A41C 1/00
9872527	12/2017	Boillat-Macon	N/A	A41D 13/1254
10034504	12/2017	Boyle	N/A	A41D 27/204
10687570	12/2019	Strange	N/A	A41D 1/06
11357266	12/2021	Connors	N/A	A41B 9/005
2006/0230503	12/2005	Shterenberg	2/309	A41F 9/00
2013/0125293	12/2012	Stearns	2/227	A41D 1/06
2014/0273735	12/2013	Cohen Larren	450/92	A41C 1/00
2015/0313302	12/2014	Boyle	2/227	A41D 27/28
2016/0345642	12/2015	Brothers	N/A	A41D 13/065
2016/0360806	12/2015	Thomas	N/A	A41D 13/1254
2017/0006925	12/2016	Priest	N/A	A41C 1/06
2018/0206561	12/2017	Moran	N/A	A41D 1/065
2018/0228665	12/2017	Relekar	N/A	A41B 9/04
2019/0021416	12/2018	Lai	N/A	A41D 13/1254
2019/0320737	12/2018	Kiuchi	N/A	A41D 17/02

2021/0100681	12/2020	Miles	N/A	A41B 9/14
2021/0352970	12/2020	Monaco	N/A	A41B 9/005
2022/0133527	12/2021	Brown	128/844	A41B 9/005

Primary Examiner: Haden; Sally

Attorney, Agent or Firm: Armstrong Teasdale LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application Ser. No. 62/891,245, filed on Aug. 23, 2019, the disclosure of which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE DISCLOSURE

(1) The present disclosure relates generally to garments, and more specifically, to a garment for facilitating urination.

(2) In typical pant-like garments, the garments have to be taken completely off or unbuttoned and unzipped before a wearer of the garment can urinate. These actions may be very difficult to achieve for elderly wearers and/or disabled wearers, and therefore, urination may be especially difficult for the wearers and any caretakers assisting the wearers.

(3) Additionally, some wearers may not be able to urinate in a typical bathroom setting. For example, the wearers may need to urinate in a urination bottle or a bed pan. Typical pant-like garments do not provide privacy or cover for these unique circumstances.

SUMMARY OF THE DISCLOSURE

(4) In one aspect, a garment for facilitating urination is provided. The garment includes two leg openings, and an access panel between the two leg openings. The access panel extends from a front of the garment to a back of the garment, wherein the access panel is coupled to the front of the garment with an attachment. The garment is configurable between an initial, closed configuration and a second, open configuration in which the access panel is at least partially detached from the garment.

(5) In another aspect, a method of operating a garment is provided. The method includes providing a garment for facilitating urination. The garment includes two leg openings, and an access panel between the two leg opening. The access panel extends from a front of the garment to a back of the garment, wherein the access panel is coupled to the garment with an attachment. The garment is configurable between an initial, closed configuration and a second, open configuration in which the access panel is at least partially detached from the garment. The method also includes detaching, using an attachment, the access panel from the garment before a wearer of the garment urinates.

(6) These other and features, aspects and advantages of the present disclosure will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a front view of an exemplary garment in a closed or initial configuration.

(2) FIG. 2 is a back view of a first embodiment of the garment of FIG. 1.

- (3) FIG. 3 is a back view of a second embodiment of the garment of FIG. 1.
- (4) FIG. 4 is a bottom view of a bottom panel of the garment of FIG. 1.
- (5) FIG. 5 is a front view of the garment of FIG. 1 with a first type of attachment.
- (6) FIG. 6 is a front view of the garment of FIG. 1 with a second type of attachment.
- (7) FIGS. 7-9 are front perspective views of the garment of FIG. 1 being positioned into an open or second configuration.
- (8) FIG. 10 is a back view of a blanket that may be used in association with the garment of FIG. 1.
- (9) Corresponding reference characters indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION OF THE DISCLOSURE

- (10) The present disclosure relates generally to garments, and more specifically, to a garment for facilitating urination.
- (11) FIG. 1 is a front view of an exemplary garment **100** for facilitating urination in a closed or initial configuration. FIG. 2 is one embodiment of a back view of the garment **100**, and FIG. 3 is another embodiment of a back view of the garment **100**. FIG. 4 shows a bottom view of a bottom panel (e.g., bottom panel **120**, shown in FIG. 1) of the garment **100**. FIGS. 5 and 6 show two embodiments of the garment **100** with different attachments (e.g., attachment **118**, shown in FIG. 1), and FIGS. 7-9 show an exemplary garment substantially similar to the garment **100** being positioned from a closed configuration to an open configuration. Although the garment **100** is described and shown herein as being a pant, specifically long pants, it should be understood that the garment **100** is not limited to a pant, and may instead be any garment **100** with leg openings including, for example and without limitation, shorts, underwear, boxers, briefs, long underwear, and pajamas.
- (12) In the exemplary embodiment, the garment **100** is constructed from a flexible cloth or textile material. For example, the garment **100** may be constructed of wool, cotton, silk, linen, crepe, polyester, velvet, chenille, fleece, chiffon, flannel terry cloth and any/all fabrics used in making any garment. In other embodiments, the garment **100** may be constructed from any other suitable material such that the garment **100** may function as described herein. Moreover, the garment **100** is constructed from several pieces of material that are coupled or secured together. The difference pieces may be made of the same material or different materials.
- (13) The garment **100** has a front **101** that is generally worn on a front of a user (not shown) when the garment **100** is worn by the user and a back **103** that is generally worn on a back of the user when the garment **100** is worn by the user. The garment **100** includes a first leg opening **102**, a second leg opening **104**, a waistband **106**, and an access panel **108**, also referred to herein as a panel **108**. The leg openings **102**, **104** extend from a top end **110** of the garment **100** to a bottom end **112** of the garment **100**. The waistband **106** is located at the top end **110** of the garment **100**. The panel **108** is located near the top end **110** of the garment **100**. The panel **108** extends vertically from the front **101** of the garment **100** to the back **103** of the garment **100**, and the panel **108** extends horizontally from a first end **114** of the panel **108** to a second end **116** of the panel **108**. The panel **108** is removably coupled to the garment **100**, and more specifically, to the first and second leg openings **102**, **104**, by attachments **118** (e.g., rope, buttons, snaps, hook-and-loop fasteners, etc.). That is, when the garment **100** is in the closed configuration (shown in FIG. 1), the first end **114** of the panel **108** is coupled to the first leg opening **102** with the attachment **118** and the second end **116** of the panel **108** is coupled to the second leg opening **104** with the attachment **118**. When the garment **100** is in the open configuration (shown in FIGS. 7-9) and moved in the direction of X, the first end **114** of the panel **108** is decoupled from the first leg opening **102** using attachment **118**, and the second end **116** of the panel **108** is decoupled from the second leg opening **104** using attachment **118**.
- (14) The panel **108** includes a bottom panel **120** in a crotch region **121** of the garment **100**. In the exemplary embodiment, the bottom panel **120** is a distinct panel that is coupled to the panel **108**

(e.g., through stitching or other attachment means). In other embodiments, the bottom panel **120** is not distinct from the panel **108** and is the portion of the panel **108** that is in the crotch region **121** of the garment **100**. The panel **108**, and more specifically, the bottom panel **120** includes a first front panel edge **122** and a second front panel edge **124**. The first front panel edge **122** and the second front panel edge **124** meet generally in the middle of the panel **108**. In the exemplary embodiment, the front panel edges **122**, **124** are slanted such that the front panel edges **122**, **124** form a generally triangular shape in the crotch region **121** of the garment **100** and such that the bottom panel **120** is generally hexagonal in shape (as shown in FIG. 4). In other embodiments, the panel **108** may include any number of panel edges such that the crotch region **121**, the panel **108**, and/or the bottom panel **120** may be any suitable shape.

(15) In the exemplary embodiment, the garment **100** includes a first leg extension **126** of first leg opening **102** and a second leg extension **128** of second leg opening **104**. The first leg extension **126** extends from the first end **114** of the panel **108** through at least a partial length of the first leg opening **102**. The second leg extension **128** extends from the second end **116** of the panel **108** through a partial length of the second leg opening **104**. In the exemplary embodiment, the leg extensions **126**, **128** are generally triangular in shape (as shown in FIG. 4). In other embodiments, the leg extensions **126**, **128** may be any suitable shape. In the exemplary embodiment, the leg extensions **126**, **128** are configured to give a user of the garment **100** extra space in the crotch region **121** and the leg openings **102**, **104** when the user wears the garment **100**. For example, the extra space due to the leg extensions **126**, **128** may be especially useful when the user is wearing a diaper underneath the garment **100**. In other embodiments, the garment **100** may not include leg extensions **126**, **128**.

(16) FIG. 2 shows a first embodiment of the back **103** of the garment **100**. The back **103** includes a first back panel edge **150** of the panel **108**, shown in FIG. 1, (and more specifically, the bottom panel **120**) and a second back panel edge **152** of the panel **108** (and more specifically, the bottom panel **120**). In the exemplary embodiment, the back panel edges **150**, **152** are slanted such that the back panel edges **150**, **152** meet at an end **158**. Further, the back panel edges **150**, **152** are configured to form a generally triangular shape in the crotch region **121** (shown in FIG. 1) of the garment **100** and such that the bottom panel **120** is generally hexagonal in shape (as shown in FIG. 4). The back **103** also shows a first extension **156** and a second extension **158** that come from the first leg extension **126** and the second leg extension **128**, respectively.

(17) In the exemplary embodiment, the panel **108** and the bottom panel **120** extend from the front **101** of the garment **100** to the end **154**. When the garment **100** is positioned to the open configuration (shown in FIGS. 7-9), the panel **108** and the bottom panel **120** move in the direction of Y. The panel **108** and the bottom panel **120** stop moving at the end **154** (e.g., when the garment **100** is fully in the open configuration).

(18) FIG. 3 shows a second embodiment of the back **103** of the garment **100**. The back **103** includes a first back panel edge **160** of the panel **108** (and more specifically, the bottom panel **120**) and a second back panel edge **162** of the panel **108** (and more specifically, the bottom panel **120**). In the exemplary embodiment, the back panel edges **160**, **162** are generally curved in shape and are connected by an ending edge **164** of the panel **108** and the bottom panel **120**. Further, the back panel edges **160**, **162** are configured such that the bottom panel **120** is polygonal in shape, and more specifically, heptagonal in shape.

(19) In the exemplary embodiment, the panel **108** and the bottom panel **120** extend from the front **101** of the garment to the ending edge **164**. When the garment **100** is positioned to the open configuration (shown in FIGS. 7-9), the panel **108**/the bottom panel **120** move in the direction of Y. The panel **108** and the bottom panel **120** stop moving at the ending edge **164** (e.g., when the garment **100** is fully in the open configuration).

(20) FIG. 4 shows a simplified bottom view of the crotch region **121** of the garment **100** (shown in FIGS. 1 and 2). Specifically, FIG. 4 shows a bottom view of the bottom panel **120** and the leg

extensions **126**, **128** of the garment **100**. As explained with respect to FIGS. **1** and **2**, the front **101** of the bottom panel **120** includes front panel edges **122**, **124**, and the back **103** of the bottom panel **120** includes back panel edges **150**, **152**. The bottom panel **120** also includes a first side panel edge **170** and a second side panel edge **172**. The first leg extension **126** includes a first extension edge **174** coupled to the front **101** of the first leg opening **102** (shown in FIG. **1**) and a second extension edge **175** coupled to the back **103** of the first leg opening **102** (shown in FIG. **2**). The second leg extension **128** includes a third extension edge **176** coupled to the front **101** of the second leg opening **104** (shown in FIG. **1**) and a fourth extension edge **177** coupled to the back **103** of the second leg opening **104** (shown in FIG. **2**). The extensions edges **174**, **175**, **176**, **177** may be coupled to the respective first and second leg openings **102**, **104** by any suitable means, including, but not limited to, stitching.

(21) The first leg extension **126** extends from the first side panel edge **170** down a length of the first leg opening **102**, and the second leg extension **128** extends from the second side panel edge **172** down a length of the second leg opening **104**. In the exemplary embodiment, the leg extensions **126**, **128** are triangular in shape to maximize the amount of space the leg extensions **126**, **128** provide without compromising the comfort of the garment **100**. For example, if the leg extensions **126**, **128** were square in shape, the leg extensions may provide more space, but the corners of the square-shaped leg extensions may irritate the skin of the user and be uncomfortable for the user.

(22) In the exemplary embodiment, the bottom panel **120** is hexagonal in shape. The hexagonal shape of the bottom panel **120** allows for easy access to a crotch region of the user (e.g., when the user urinates) such that the user can urinate in any position (e.g., standing up, sitting down, laying down, etc.). The hexagonal shape also allows for flexibility of the garment **100** and the bottom panel **120** without the garment **100** or the bottom panel **120** bunching up. Furthermore, the hexagonal and triangular shapes allow for the extra fabric between the legs and inseams to use a urine bottle quickly, pull out a soiled diaper, and solve the problem of waiting on assistance to urinate while in a seated position. The extra fabric will also eliminate tight fabric being caught up in the buttock and crotch areas of both men and women. Although the bottom panel **120** is shown as having a hexagonal shape in the exemplary embodiment, the bottom panel **120** can have any polygonal shape. For example, in other embodiments, the bottom panel **120** may have a pentagonal shape, a heptagonal shape, an octagonal shape, etc.

(23) FIG. **5** shows an exemplary embodiment of the garment **100** with a first exemplary attachment **118** (shown in FIG. **1**) of buttons or snaps. Specifically, the garment **100** includes a plurality of buttons **180** or snaps **180** near the first end **114** of the panel **108** and a plurality of buttons **182** or snaps **182** near the second end **116** of the panel **108** to secure the panel **108** to the first and second leg openings **102**, **104** when the garment **100** is in the closed configuration. In the exemplary embodiment, the buttons **180** are coupled to the first leg opening **102** (e.g., through stitching), and the panel **108** includes a plurality of holes (not shown) near the first end **114** configured to receive the buttons **180**. The buttons **182** are coupled to the second leg opening **104** (e.g., through stitching), and the panel **108** includes a plurality of holes (not shown) near the second end **116** configured to receive the buttons **182**. The garment **100** is in the closed configuration when the buttons **180**, **182** secure the corresponding holes of the panel **108**.

(24) When the garment **100** is positioned into the open configuration, the buttons **180**, **182** are undone (e.g., the buttons **180**, **182** release the corresponding holes) from the top **110** (shown in FIG. **1**) of the garment **100** to the bottom panel **120** (shown in FIG. **1**) of the garment **100** in the direction of X. When the garment **100** is positioned into the closed configuration from the open configuration, the buttons **180**, **182** are redone (e.g., the buttons **180**, **182** are received in the corresponding holes) from the bottom panel **120** of the garment **100** to the top **110** of the garment **100** in a direction opposite of X, such that the panel **108** is secured to the leg openings **102**, **104** by the buttons **180**, **182**.

(25) If the buttons are snaps, one part of the snaps **180** is coupled to the leg opening **102**, and the

other part of the snaps **180** is coupled near the first end **114** of the panel **108**. Further, one part of the snaps **182** is coupled to the leg opening **104**, and the other part of the snaps **182** is coupled near the second end **116** of the panel **108**. The one part of the snaps **180**, **182** on the leg openings **102**, **104** are each configured to align with the other part of the snaps **180**, **182** on the panel **108**.

(26) When the garment **100** is positioned into the open configuration, the snaps **180**, **182** are undone (e.g., the one part and the other part are decoupled) from the top **100** of the garment **100** to the bottom panel **120** of the garment in the direction of X. When the garment **100** is positioned into the closed configuration from the open configuration, the snaps **180**, **182** are re-snapped (e.g., the one part of the snaps **180**, **182** receives the other part of the snaps **180**, **182**) from the bottom panel **120** of the garment **100** to the top **110** of the garment **100** in a direction opposite X, such that the panel **108** is secured to the leg openings **102**, **104** by the snaps **180**, **182**.

(27) FIG. **6** shows an exemplary embodiment of the garment **100** with a second exemplary attachment **118** (shown in FIG. **1**) of hook-and-loop fasteners (e.g., VELCRO). Specifically, the garment **100** includes a hook-and-loop fastener strip **190** near the first end **114** of the panel **108** and a hook-and-loop fastener strip **192** near the second end **116** of the panel **108** to secure the panel **108** to the first and second leg openings **102**, **104** when the garment **100** is in the closed configuration. A first part of the hook-and-loop fastener strips **190**, **192** (e.g., either the “hook” or the “fastener”) is coupled (e.g., through stitching) to the first and second leg openings **102**, **104**, respectively. Another part of the hook-and-loop fastener strips **190**, **192** (e.g., the other of the “hook” or the “fastener”) is coupled to the first and second ends **114**, **116**, respectively, such that both parts of the hook-and-loop fastener strips line up when the garment **100** is in the closed configuration. That is, the garment **100** is in the closed configuration when the hook-and-loop fastener strips **190**, **192** secure the panel **108** to the leg openings **102**, **104**.

(28) When the garment **100** is positioned into the open configuration, the two parts of the hook-and-loop fastener strips **190**, **192** are decoupled (e.g., through pulling the two parts away from each other) from the top **110** (shown in FIG. **1**) of the garment **100** to the bottom panel **120** (shown in FIG. **1**) of the garment **100** in the direction of X. When the garment **100** is positioned into the closed configuration from the open configuration, the hook-and-loop fastener strips **190**, **192** are coupled together (e.g., by sticking the parts of the strips **190**, **192** back together) from the bottom panel **120** of the garment **100** to the top **100** of the garment in a direction opposite of X, such that the panel **108** is secured to the leg openings **102**, **104** by the hook-and-loop fastener strips **190**, **192**.

(29) Although the attachments **118** (shown in FIG. **1**) are shown as being buttons, snaps, or hook-and-loop fastener strips, the attachments **118** can be any other suitable attachment that is removable and/or non-permanent. For example, the attachments **118** may be a rope, as shown in FIGS. **7-9**. Further, the attachments **118** may include, for example, fabric tape or elastic. The removable attachments **118** that secure the panel **108** to the first and second leg openings **102**, **104** ensure that users are easily able to access a crotch region of the user without the user having to take off the garment **100**. This is especially useful when, for example, the user needs to urinate.

(30) FIGS. **7-9** show an exemplary garment **200** being positioned from a closed configuration to an open configuration. The garment **200** is substantially similar to the garment **100** (shown in FIG. **1**) and includes substantially similar parts. FIG. **7** shows the panel **108** in a first intermediate configuration between the closed configuration and the open configuration, FIG. **8** shows the panel **108** in a second intermediate configuration between the first intermediate configuration and the open configuration, and FIG. **9** shows the panel **108** (and the garment **200**) in the open configuration.

(31) In the illustrated embodiment, the attachment **118** of the garment **200** is rope **118**. Specifically, the rope **118** wraps around the garment **200** and is placed in a first passageway **201** (shown in FIG. **8**) defined in the waistband **106**. The rope **118** is also coupled to the panel **108** and extends through a second passageway **203** (shown in FIG. **8**) defined in the panel **108**. The rope **118** ties, as shown as **202**, on one side of the garment **200** between the panel **108** and the waistband **106**. When the

garment **200** is in the closed configuration (not shown), the rope **118** is pulled taut throughout the panel **108** and tied **202** at one end of the panel **108** such that the panel **108** and the waistband **106** are flush at the top of the garment **200**. As shown in FIG. 7, the tie **202** is untied such that the panel **108** can be lowered into the open configuration (e.g., toward the crotch region **121** of the garment **200** in the direction of X).

(32) FIG. 8 shows the garment **200** in the second intermediate position (e.g., as the panel **108** is further lowered in the direction of X from the first intermediate position shown in FIG. 7). The bottom panel **120** is visible in the second intermediate position, as are the back panel edges **150**, **152** and the ending **154**. As the panel **108** is pulled lower, the tie **202** gets smaller as the rope **118** needs more slack to stay coupled to the panel **108**.

(33) FIG. 9 shows the garment **200** in the open configuration. In the open configuration, the panel **108** is pulled completely down to the crotch region **121** (e.g., adjacent leg openings **102**, **104**). In the open configuration, since the panel **108** is completely lowered, the user of the garment **200** can easily urinate without having to take off the garment **200** completely. Further, the bottom panel **120** is configured to make the garment **200** flexible without bunching up and allows the user to urinate from any position (e.g., standing up, sitting down, laying down, etc.). When the user has finished urinating, the panel **108** can easily be pulled up to be flush with the waistband **106** again, and the panel **108** is secured by tying the rope **118**.

(34) FIG. 10 shows a blanket **300** that may be used in association with the garment **100** (shown in FIG. 1). The blanket **100** has a back side **302**, which is shown in FIG. 10, and a front side **304**. The back side **302** includes a plurality of fasteners **306** configured to hold a bottle **308** or other urination-assist device **308**. The fasteners **306** may be constructed of elastic and/or hook-and-loop fasteners.

(35) When a user of the garment **100** needs to urinate and the garment **100** is in the open configuration, the user may use the blanket **300** to discreetly urinate. Specifically, the user may urinate into the bottle **308** fastened in place by the fasteners **306** of the blanket **300**. That is, the back side **302** of the blanket **300** is in contact with the user such that the front side **304** of the blanket hides the urine and urination of the user.

(36) As described above, the garment **100** facilitates urination by providing an access panel (e.g., panel **108**) such that a user of the garment can easily access a crotch area of the user when the user has to urinate. The access panel ensures that the user does not have to completely take off the garment **100** when the user has to urinate. Further, by providing a bottom panel (e.g., bottom panel **120**) of the access panel, the garment **100** is more flexible without bunching up, and the user can urinate from any position (e.g., standing up, sitting down, laying down, etc.). In some embodiments, the garment **100** also provides leg extensions (e.g., leg extensions **126**, **128**) that are configured to provide more space in a crotch region of the user and down the legs of the user. The leg extensions may accordingly be especially useful for users who wear diapers or other bulky underwear underneath the garment **100**.

(37) Accordingly, the garment **100** is especially useful in facilitating urination for users who are elderly, incontinent, or disabled due to the garment **100** not having to be taken off to urinate. Further, the garment **100** is also useful to caretakers of the users of the garment **100**, as the caretakers can easily assist the users in urinating because garment **100** can stay on while the user is urinating, and the caretakers do not have to take the garment **100** on and off.

(38) Although the embodiments and examples disclosed herein have been described with reference to particular embodiments, it is to be understood that these embodiments and examples are merely illustrative of the principles and applications of the present disclosure. It is therefore to be understood that numerous modifications can be made to the illustrative embodiments and examples and that other arrangements can be devised without departing from the spirit and scope of the present disclosure as defined by the claims. Thus, it is intended that the present application cover the modifications and variations of these embodiments and their equivalents.

(39) This written description uses examples to disclose the disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

Claims

1. A garment for facilitating urination, the garment comprising: a front side; a back side; a first leg opening and a second leg opening each defined by the front side and the back side; a waistband at a top end of the garment defining a first passageway; an access panel assembly between the first leg opening and the second leg opening and extending from the front side of the garment to the back side of the garment, the access panel assembly comprising: an access panel positioned on the front side and defining a second passageway at a top of the access panel, the access panel extending horizontally from a first free edge to a second free edge; and a bottom panel in a crotch region of the garment coupled to the access panel, wherein the first free edge of the access panel extends from the bottom panel and to the second passageway at the first leg opening and the second free edge of the access panel extends from the bottom panel to the second passageway at the second leg opening; a first back panel edge and a second back panel edge on the bottom panel coupling the access panel assembly to the back side of the garment; a first front panel edge and a second front panel edge on the bottom panel coupling the access panel to the bottom panel, the first front panel edge intersecting the second front panel edge, and wherein the first front panel edge is oriented obliquely relative to the second front panel edge; and an attachment coupling the access panel to the front side of the garment, the attachment including a tightening rope extending through the first passageway in the waistband and the second passageway in the access panel, wherein the garment is configurable by the tightening rope to an open configuration in which the access panel is at least partially detached from the garment, wherein the tightening rope wraps around the circumference of the top end of the garment through the waistband and the access panel, and wherein loosening the tightening rope lowers the second passageway on the garment relative to the first passageway, moves the first free edge away from the first leg opening, and moves the second free edge away from the second leg opening, to lower the access panel on the front side and allow for maintaining the waistband in position on a wearer.
2. The garment of claim 1, wherein the first and second front panel edges meet in a center region of the access panel.
3. The garment of claim 1, wherein the bottom panel has a polygon shape, and wherein the polygon shape has at least five sides.
4. The garment of claim 3, wherein the bottom panel has a hexagon shape.
5. The garment of claim 1, wherein the first leg opening and the second leg opening each extend to a bottom of the garment, and wherein the first leg opening and the second leg opening each have a same length.
6. The garment of claim 1 further comprising: leg extensions extending from the bottom panel to at least a partial length of each of the first leg opening and the second leg opening.
7. The garment of claim 6, wherein the leg extensions have a triangular shape.
8. The garment of claim 1, wherein the waistband is configured to change a size of the top end of the garment.
9. The garment of claim 1, wherein the garment is configured to the open configuration by untying the tightening rope to release the access panel from the garment.
10. The garment of claim 1, wherein the garment is composed of a textile material including at

least one of cotton and polyester.

11. The garment of claim 1, wherein the tightening rope is configured to be pulled taut through the access panel and tied with a tie at one end of the access panel.

12. The garment of claim 11, wherein the garment is configurable to an intermediate configuration by loosening the tie to provide slack to the tightening rope within the waistband and allowing the top of the access panel to lower relative to the waistband, and wherein, in the open configuration, the access panel is positioned downward from the intermediate configuration and adjacent the crotch region and the two leg openings.

13. The garment of claim 1, wherein the first back panel edge and the second back panel edge intersect at an ending of the bottom panel, the first back panel edge and the second back panel edge each slanting outward relative to one another from the ending such that the first back panel edge and the second back panel edge collectively define a triangular shape in the crotch region, wherein the bottom panel further includes: a first side panel edge and a second side panel edge, the first side panel edge extending from the first back panel edge to the first front panel edge, the second side panel edge extending from the second back panel edge to the second front panel edge, the second side panel edge being oriented parallel to the first side panel edge, and wherein the garment further includes a first leg extension extending from the first side panel edge down the first leg opening and a second leg extension extending from the second side panel edge down the second leg opening.

14. The garment of claim 13, wherein the bottom panel has a hexagon shape defined by the first back panel edge, the second back panel edge, the first side panel edge, the second side panel edge, the first front panel edge, and the second front panel edge.

15. The garment of claim 13, wherein the first leg extension includes a first extension edge coupled to the front side of the garment at the first leg opening and a second extension edge coupled to the back side of the garment at the first leg opening.

16. The garment of claim 15, wherein the first leg extension has a triangular shape defined by the first extension edge, the second extension edge, and the first side panel edge.

17. The garment of claim 16, wherein the first side panel edge extends from a first end to a second end, the first extension edge extending from the first end of the first side panel edge and the second extension edge extending from the second end of the first side panel edge.

18. The garment of claim 17, wherein the first front panel edge extends to the first end of the first extension edge and the first back panel edge extends to the second end of the first extension edge.

19. The garment of claim 18, wherein the first front panel edge is oriented parallel to the second back panel edge and the second front panel edge is oriented parallel to the first back panel edge.
