

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397172
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lin; Li-Chi et al.

Chip pad decompression structure

Abstract

A chip pad decompression structure includes a pad, a protective ring, a chip, and an upper lid. A middle of one side of the pad has a raised portion. Another side of the pad has a recess. The protective ring is disposed in the recess of the pad. The protective ring has a through hole. The chip is disposed in the through hole of the protective ring and located in the recess of the pad. The upper lid is configured to cover the protective ring and the chip. The protective ring is disposed between the pad and the chip, which can disperse the force, improve a force-cushioning effect and protect the chip, so as to reduce a foreign body sensation and prolong the service life of the chip.

Inventors: Lin; Li-Chi (Changhua County, TW), Lin; Yi-Ying (Changhua County, TW)

Applicant: Ghi Fu Technology Co, Ltd. (Changhua County, TW)

Family ID: 1000008782988

Appl. No.: 18/151472

Filed: January 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230226371 A1	Jul. 20, 2023

Foreign Application Priority Data

TW	111102024	Jan. 18, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: A61N5/06 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: A61N (5/0625); A61N (2005/0645); A61N (2005/066); A61N (5/06-2005/073)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11837513	12/2022	Meier	N/A	G01N 27/28
2006/0235346	12/2005	Prescott	602/2	A43B 3/36
2014/0303692	12/2013	Pignatelli	607/90	A61N 5/0613
2018/0304094	12/2017	Hicks	N/A	A61N 5/0616
2021/0020528	12/2020	Meier	N/A	G01N 27/283
2021/0069489	12/2020	Lawson	N/A	A61N 1/0484

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2022036518	12/2021	WO	N/A

Primary Examiner: Kuo; Jonathan T

Attorney, Agent or Firm: Bruce Stone LLP

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a chip pad, and more particularly to a chip pad decompression structure.

BACKGROUND OF THE INVENTION

(2) The wrapping and retaining structure of a conventional chip unit comprises a retaining film. The retaining film is configured to wrap a plurality of chips to form a chip unit, so that the chip unit is completed. When in use, the chip unit cooperates with a close-fitting accessory, such as a belt. When the close-fitting accessory is attached to the user's body, the chip unit will emit far-infrared rays to the user's body. Far-infrared rays radiate a small amount of energy to the user's body and are resonantly absorbed by water molecules in the user's body, thereby generating deformation vibrations to promote blood circulation and enhance metabolism.

(3) However, if the chip unit is used, in cooperation with a foot pad, on the foot of the user, the weight of the user will be concentrated on the chip. When the user moves or walks, he/she may have a foreign body sensation. The user feels uncomfortable. Besides, it will cause deformation or damage to the chip unit, which will reduce the effect of the product greatly. Accordingly, the inventor of the present invention has devoted himself based on his many years of practical experiences to solve these problems.

SUMMARY OF THE INVENTION

(4) The primary object of the present invention is to provide a chip pad decompression structure, which can improve a force-cushioning effect and protect a chip, so as to reduce a foreign body sensation and prolong the service life of the chip.

(5) In order to achieve the above object, the chip pad decompression structure provided by the present invention comprises a pad, a protective ring, a chip, and an upper lid. The pad has a recess. The protective ring is disposed in the recess of the pad. The protective ring has a through hole. The chip is disposed in the through hole of the protective ring. The upper lid is configured to cover the protective ring and the chip.

(6) In the chip pad decompression structure provided by the present invention, the protective ring is disposed between the pad and the chip, which can disperse the force, improve a force-cushioning effect and protect the chip, so as to reduce a foreign body sensation and prolong the service life of the chip.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view in accordance with a preferred embodiment of the present invention;

(2) FIG. 2 is an exploded view in accordance with the preferred embodiment of the present invention;

(3) FIG. 3 is a schematic view in accordance with the preferred embodiment of the present invention, illustrating that the chip pad decompression structure is joined to the strap; and

(4) FIG. 4 is a schematic view in accordance with the preferred embodiment of the present invention when in use.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(5) Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings.

(6) FIG. 1 is a perspective view in accordance with a preferred embodiment of the present invention. FIG. 2 is an exploded view in accordance with the preferred embodiment of the present invention. FIG. 3 is a schematic view in accordance with the preferred embodiment of the present invention. The present invention discloses a chip pad decompression structure **100**, comprising a pad **10**, a protective ring **20**, a chip **30**, and an upper lid **40**.

(7) In this embodiment of the present invention, the material of the pad **10** is silicone. The pad **10** has a hardness of Shore A 28. The shape of the pad **10** may be round or oval, but not polygonal with acute angles. In this embodiment, the shape of the pad **10** is oval. The middle of one side of the pad **10** has a raised portion **11**. As shown in FIG. 4, the thickness of the middle of the raised portion **11** is greater than the thickness of the periphery of the raised portion **11**, so that the cross-section of the raised portion **11** has a trapezoid-like shape. The other side of the pad **10** has a recess **12**. The recess **12** is a round recess. The bottom of the recess **12** corresponds in position to the raised portion **11**.

(8) The protective ring **20** is disposed in the recess **12** of the pad **10**. The protective ring **20** has a through hole **21**. The hardness of the protective ring **20** is greater than that of the pad **10**. In this embodiment of the present invention, the material of the protective ring **20** is silicone. The protective ring **20** has a hardness of Shore A 50. The shape of the protective ring **20** may be round or oval, but not polygonal with acute angles. In this embodiment, the shape of the protective ring **20** is round.

(9) The chip **30** is disposed in the through hole **21** of the protective ring **20** and is located in the recess **12** of the pad **10**. The chip **30** includes a metal substrate. The metal substrate may be one of iron, zinc and aluminum, and has thermal conductivity. The surface of the metal substrate is sprayed with a coating. The coating is composed of materials such as germanium, carbon, calcium, silica, oxygen and adhesives mixed in proportion, enabling the chip **30** to increase in temperature due to the body temperature and to emit far-infrared radiation energy. The shape of the chip **30** may

be round or oval, but not polygonal with acute angles. In this embodiment, the shape of the chip **30** is round.

(10) The upper lid **40** is configured to cover the protective ring **20** and the chip **30**. In this embodiment of the present invention, the material of the upper lid **40** is silicone. The upper lid **40** has a hardness of Shore A 28. The shape of the upper lid **40** may be round or oval, but not polygonal with acute angles. In this embodiment, the shape of the upper lid **40** is round.

(11) The chip pad decompression structure **100** is arranged on a strap **50**. The strap **50** includes a first connecting portion **51** and a second connecting portion **52** at both ends thereof. In this embodiment of the present invention, the first connecting portion **51** and the second connecting portion **52** are hook-and-loop fasteners, so that the first connecting portion **51** and the second connecting portion **52** can be adhered to the opposing surfaces to be fastened. The strap **50** further includes a fabric **53**. The fabric **53** is suede fabric. The fabric **53** is configured to cover the chip pad decompression structure **100**. The fabric **53** is joined to the strap **50** by high frequency welding, so that the chip pad decompression structure **100** is secured to the strap **50**.

(12) Referring to FIG. 2 and FIG. 3, when the chip pad decompression structure **100** of the present invention is to be assembled, the pad **10** is first turned upside down so that the recess **12** of the pad **10** faces upward. The protective ring **20** is placed into the recess **12**, and then the chip **30** is placed into the through hole **21**, so that both the protective ring **20** and the chip **30** are located in the recess **12**. The upper lid **40** is glued to cover the protective ring **20** and the chip **30**, so that the protective ring **20**, the chip **30** and the upper lid **40** are secured to the pad **10** to complete the assembly of the chip pad decompression structure **100**. The chip pad decompression structure **100** is joined to the strap **50**. The strap **50** is on one side of the pad **10** opposite to the upper lid **40**. The fabric **53** is configured to cover one side of the pad **10** opposite to the raised portion **11**. The fabric **53** is joined to the strap **50** by high frequency welding. The strap **50** may be worn on the neck, hand, wrist, or arch of the foot, forefoot, and heel of the feet and other body parts of the user.

(13) FIG. 4 is a schematic view in accordance with the preferred embodiment of the present invention when in use. In this embodiment, the chip pad decompression structure **100** is used on the arch of the user's foot. The chip **30** increases in temperature due to the body temperature and emits far-infrared rays. Far-infrared rays can penetrate the skin of the user and resonate with the water that accounts for 65%-70% of the user's body, making the water change from large molecules to small molecules and generating heat via intermolecular friction. The subcutaneous temperature rises via the heat reaction, which can promote the expansion of microvessels, accelerate blood circulation, promote metabolism, and remove harmful substances and heavy metals in the user's body. Thus, new enzymes are rapidly produced to activate cells, such that the physiological functions of the user's body are more active, and the immunity is improved to resist diseases.

(14) It is worth mentioning that when the user's foot treads on the chip pad decompression structure **100**, the raised portion **11** will cushion the force. The protective ring **20** is disposed between the pad **10** and the chip **30**, which can further disperse the force to the whole pad **10**, reduce the phenomenon of uneven distribution of the force, and improve a force-cushioning effect. The compressive force can be reduced and the chip **30** can be protected when in use, so as to reduce a foreign body sensation and prolong the service life of the chip **30**.

Claims

1. A chip pad decompression structure, comprising: a pad, the pad having a recess; a protective ring, disposed in the recess of the pad, the protective ring having a through hole; a chip, disposed in the through hole of the protective ring; an upper lid, configured to cover the protective ring and the chip; wherein the pad, the protective ring, and the upper lid are made of silicone: wherein the pad and the upper lid each have a hardness of Shore A 28; and wherein the protective ring has a hardness of Shore A 50.

2. The chip pad decompression structure as claimed in claim 1, wherein the protective ring has a hardness greater than that of the pad.
 3. The chip pad decompression structure as claimed in claim 1, wherein the pad, the protective ring, the chip and the upper lid each have a round or oval shape.
 4. The chip pad decompression structure as claimed in claim 1, wherein the pad has an oval shape, and the protective ring, the chip and the upper lid each have a round shape.
 5. The chip pad decompression structure as claimed in claim 1, wherein a middle of one side of the pad has a raised portion, another side of the pad has the recess, and a bottom of the recess corresponds in position to the raised portion.
 6. The chip pad decompression structure as claimed in claim 1, wherein the pad is connected to a strap, the strap includes a first connecting portion and a second connecting portion at two ends thereof, the first connecting portion and the second connecting portion are fastened to each other.
-