

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397402
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Yuan; Jianming

Staple gun

Abstract

The present disclosure relates to a staple gun. The staple gun includes a staple gun shell with a fixed handle and a movable handle, and provided with a staple storage mechanism with a staple outlet. The staple gun shell is internally and slidably provided with a staple striking assembly through an elastic sliding mechanism. A pry bar type linkage reset mechanism, arranged between the movable handle and the staple striking assembly, is capable of driving one end of the staple striking assembly to get away from the staple outlet when the movable handle moves toward the fixed handle under an external force, or when the external force disappears, the pry bar type linkage reset mechanism is capable of making the movable handle move far away from the fixed handle, and one end of the staple striking assembly slides into the staple outlet under the action of the elastic sliding mechanism.

Inventors:	Yuan; Jianming (Ningbo, CN)
Applicant:	Yuyao Tangwen Tools Co., Ltd. (Zhejiang, CN)
Family ID:	1000008782852
Assignee:	Yuyao Tangwen Tools Co., Ltd. (Ningbo, CN)
Appl. No.:	18/642731
Filed:	April 22, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240269814 A1	Aug. 15, 2024

Foreign Application Priority Data

CN	202310465264.3	Apr. 24, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: B25C5/11 (20060101); B25C5/16 (20060101)

U.S. Cl.:

CPC B25C5/11 (20130101); B25C5/1617 (20130101);

Field of Classification Search

CPC: B25C (5/11); B25C (5/1617)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2268102	12/1940	Attula	227/126	B25C 5/16
4025031	12/1976	Chi	227/132	B25C 5/0285
5165587	12/1991	Marks	227/132	B25C 5/11
5407118	12/1994	Marks	227/132	B25C 5/085
5497932	12/1995	Brewer	227/132	B25C 5/11
5505362	12/1995	Marks	227/120	B25C 5/1606
5664722	12/1996	Marks	227/132	B25C 5/085
6145728	12/1999	Marks	227/120	B25C 5/11
6789719	12/2003	Shor	227/120	B25C 5/11
7464845	12/2007	Chou	227/127	B25C 5/11
8322010	12/2011	Boswinkel	227/151	B25C 5/06
9808923	12/2016	Hu	N/A	B25C 5/1606
11305410	12/2021	Yeh	N/A	B25C 5/11
11472014	12/2021	Marks	N/A	B25C 5/11
2011/0297725	12/2010	Huang	227/140	B25C 5/11
2013/0228605	12/2012	Wang	227/8	B25C 5/11
2014/0231486	12/2013	Burch	227/63	B25C 5/0285
2017/0057071	12/2016	Pelletier	N/A	B25C 5/1696
2023/0068249	12/2022	Yeh	N/A	B25C 5/11
2024/0286259	12/2023	Fedrigon	N/A	B25C 5/11

Primary Examiner: Kinsaul; Anna K

Assistant Examiner: Shutty; David G

Attorney, Agent or Firm: IPGentleman Intellectual Property Services, LLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure belongs to the technical field of staple gun equipment, and particularly

relates to a staple gun.

BACKGROUND

(2) Staple guns are widely used in the decoration industry. Based on different driving sources, staple guns are divided into electric staple guns, pneumatic staple guns, gas-powered staple guns, manual staple guns, etc. The pneumatic staple guns and the electric staple guns use electric power or air compressors as power sources to drive striking pins in air cylinders of the staple guns to do striking motion to drive staples in a staple magazine into objects or shoot staples out. Although operations are easy, a fixed power supply or a set of air compressor equipment is required, which can consume more electric energy and is extremely unsafe and inconvenient because of a long power cord.

(3) In the prior art, a multifunctional nailing gun disclosed in the Chinese patent document with the application number 201020136417.8, comprising a nailing gun shell, a handle body and a grip, a nailing mechanism, an automatic nail feeding device and a driving structure of the nailing mechanism are arranged in the nailing gun shell, the automatic nail feeding device comprises an outer grooved rail and an inner grooved rail in sliding fit within the outer grooved rail, the tail of the inner grooved rail is provided with a through hole, an adjusting pin is arranged in the through hole, the adjusting pin is in clearance fit with the through hole, the nailing gun shell is provided with two adjusting holes that allow two ends of the adjusting pin to extend out of the nailing gun shell, the sectional area of the adjusting hole is greater than that of the adjusting pin, one end of the adjusting pin is provided with an adjusting step, and the sectional area of the adjusting step is slightly smaller than that of the adjusting hole; the nailing gun shell is further internally provided with a spring, one free end of the spring abuts against an inner wall of the tail of the nailing gun shell, and the other free end of the spring abuts against the adjusting pin.

(4) The aforementioned solution solves the problem of the inconvenience brought by existing electric staple guns or pneumatic staple guns to some extent. However, the solution still has the problem that a staple gun is too complex in structure, a staple outlet warps upward easily to affect normal use, and the like.

SUMMARY

(5) To solve the aforementioned problems, the present disclosure provides a staple gun.

(6) To achieve the goal, the present disclosure adopts the following technical solution: a staple gun, comprising a staple gun shell with a fixed handle and a movable handle, the staple gun shell is provided with a staple storage mechanism, one end of the staple storage mechanism is provided with an opening that extends into one end of the staple gun shell to form a staple outlet, the staple gun shell is internally and slidably provided with a staple striking assembly through an elastic sliding mechanism, one end of the staple striking assembly is capable of penetrating into the staple outlet, a pry bar type linkage reset mechanism, arranged between the movable handle and the staple striking assembly, is capable of driving one end of the staple striking assembly to get away from the staple outlet when the movable handle moves toward the fixed handle under an external force, or when the external force disappears, the pry bar type linkage reset mechanism is capable of making the movable handle move far away from the fixed handle, and one end of the staple striking assembly slides into the staple outlet under the action of the elastic sliding mechanism. When the movable handle moves toward the fixed handle under the external force, the pry bar type linkage reset mechanism follows the movable handle to start running. The pry bar type linkage reset mechanism runs to drive the staple striking assembly to move in an elastic sliding mechanism to enable the staple striking assembly to get away from the staple outlet. When the external force disappears, the pry bar type linkage reset mechanism is reset, and the staple striking assembly moves toward the staple outlet through the elastic sliding mechanism and is in contact with the staple storage mechanism at the same time.

(7) In the aforementioned staple gun, the staple striking assembly comprises a staple striking plate slidably arranged in the staple outlet, and one end, far away from the staple outlet, of the staple

striking plate is connected to a sliding plate. The staple striking plate with a thickness equal to or less than that of a staple is used for pushing the staple out. One end of the staple striking plate is connected to the sliding plate so that the staple striking plate can be pushed out or tightened by moving the sliding plate. Moreover, the thickness of the sliding plate is more than that of the staple striking plate, thereby being capable of prolonging the service life of the staple striking plate.

(8) In the aforementioned staple gun, the elastic sliding mechanism comprises a sliding groove arranged on one side inside the staple gun shell, the sliding plate is slidably arranged in the sliding groove, one end of the sliding groove is provided with a staple output base, the staple outlet is formed on one side of the staple output base in an axial direction, a bending part extending downward is arranged between the staple striking plate and the sliding plate, a staple striking torsion spring is arranged in the staple gun shell, one end of the staple striking torsion spring acts on the bending part, and the other end of the staple striking torsion spring acts on the staple gun shell or the movable handle. The staple output base has a limiting and protecting effect on the staple striking plate so that the staple striking plate can operate normally without deviation or without causing the staple outlet to get jammed. The bending part of the sliding plate has the effect of pushing the staple striking plate out. The staple striking torsion spring is tightened through the backward movement of the sliding plate. When the sliding plate is released, the staple striking torsion spring returns to drive the bending part of the sliding plate to move forward, thereby generating a push force.

(9) In the aforementioned staple gun, the pry bar type linkage reset mechanism comprises a pry bar linkage assembly and a pry bar reset assembly which are arranged in the staple gun shell.

(10) In the aforementioned staple gun, the pry bar linkage assembly comprises a linkage base movably arranged in the staple gun shell, one end of the linkage base is inserted into a sliding hole at one end, far away from the staple striking plate, of the sliding plate, and a linkage structure, arranged between the linkage base and the movable handle, is capable of making the linkage base move synchronously to enable the sliding plate to move far away from the staple striking plate when the movable handle moves toward the fixed handle under an external force. One end of the linkage base is arranged in the sliding hole of the sliding plate, and the movable handle drives the linkage base to move through the linkage structure, thereby enabling the sliding plate to move backward.

(11) In the aforementioned staple gun, the linkage structure comprises a linkage plate arranged between the linkage base and the movable handle, one end of the linkage plate is connected to the movable handle through a first movable shaft, one end, far away from the sliding hole, of the linkage base is provided with a strip-shaped hole that extends in an axial direction, a fixed shaft pin that is fixedly arranged in the staple gun shell penetrates into one end of the strip-shaped hole, a second movable shaft that is connected to one end, far away from the movable handle, of the linkage plate slidably penetrates into the other end of the strip-shaped hole, the staple gun shell is internally provided with a movable groove, and an end part of the second movable shaft is movably arranged in the movable groove. The linkage plate plays a role of a pry bar and moves between the linkage base and the movable handle through the first movable shaft and the second movable shaft. When the movable handle is under stress, the linkage plate moves toward the linkage base, and the linkage base enables an upper end of the linkage base to move backward through the fixed shaft pin, thereby driving the sliding plate to move.

(12) In the aforementioned staple gun, the pry bar reset assembly comprises a return spring arranged in the staple gun shell, one end of the return spring acts on an outer side of one end, far away from the strip-shaped hole, of the linkage base, and the other end of the return spring acts on an inner side of the staple gun shell. The return spring mainly plays a role in helping the linkage base to return and also has the effect of pushing the sliding plate.

(13) In the aforementioned staple gun, the fixed handle is integrally formed on the staple gun shell, the movable handle has a handle gripping part and a handle connecting part, the handle connecting

part is hinged to the interior of the staple gun shell through a hinge shaft, the movable handle is located on one side, close to the staple outlet, of the fixed handle, the hinge shaft is arranged at one end, far away from the handle gripping part, of the handle connecting part, the second movable shaft is arranged between the hinge shaft and the handle gripping part, the linkage base is movably arranged on one side, far away from the staple outlet, of the movable handle and located on an inner side of an upper end of the fixed handle, and the return spring is obliquely arranged; or the movable handle is located on one side, far away from the staple outlet, of the fixed handle, the hinge shaft is arranged at one end, close to the handle gripping part, of the handle connecting part, the second movable shaft is arranged on one side, far away from the handle gripping part, of the hinge shaft, the linkage base is movably arranged on one side, close to the staple outlet, of the movable handle and located on an inner side of an upper end of the fixed handle, and the return spring and the sliding plate extend in the same direction.

(14) In the aforementioned staple gun, the staple storage mechanism comprises a staple storage aluminum section detachably arranged on the staple gun shell through a first connecting bolt, one end of the staple storage aluminum section corresponds to the staple outlet, one side of the staple storage aluminum section is provided with an elastic buffer part that abuts against the bending part, one end, far away from the staple outlet, of the staple storage aluminum section is provided with a staple groove base through a second connecting bolt, the staple groove base is provided with a staple feeding base body that penetrates into the staple storage aluminum section and extends to the staple outlet, and a staple feeding block, which is connected to a tension spring located in the staple feeding base body and corresponds to the staple outlet, is slidably arranged in the staple feeding base body. When the staple striking torsion spring returns to drive the sliding plate to move forward, the bending part of the sliding plate abuts against the elastic buffer part, and the elastic buffer achieves a buffering effect, thereby prolonging the service life of the staple gun.

(15) In the aforementioned staple gun, both the fixed handle and the movable handle are curved, an open space is formed between the fixed handle and the movable handle, and the open space can release a gripping space and improve the applicability. When the movable handle is located on one side, far away from the staple outlet, of the fixed handle, a handle locking block is rotationally arranged on the staple gun shell, and the handle locking block is connected to a stop block that is located in the staple gun shell and is capable of abutting against a notch at one end, far away from the sliding hole, of the linkage base.

(16) Compared with the prior art, the present disclosure has the following advantages: 1. The device adopts an open-type handle structure, and the handle and the staple storage mechanism are separated to release the gripping space. 2. In the device, the movable handle is arranged between the staple storage mechanism and the fixed handle to form a lift-type staple gun, thereby solving the problem that a staple outlet warps upward during the use of an existing staple gun. 3. In the device, the movable handle is arranged on one side, far away from the staple storage mechanism, of the fixed handle, a pressing type staple gun is formed, and an internal structure is reduced to be compact so that an acting force of the handle faces toward the staple outlet, thereby preventing the staple outlet from warping upward.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a structural schematic view of embodiment 1 according to the present disclosure.

(2) FIG. 2 is a structural explosive view of a staple storage mechanism in embodiment 1 according to the present disclosure.

(3) FIG. 3 is a schematic view of an internal structure according to embodiment 1 of the present disclosure.

(4) FIG. 4 is a partial enlarged view of a part A in FIG. 3 according to embodiment 1 of the present disclosure.

(5) FIG. 5 is a structural schematic view of a staple gun shell in embodiment 1 according to the present disclosure.

(6) FIG. 6 is a structural schematic view of embodiment 2 according to the present disclosure.

(7) FIG. 7 is a schematic view of an internal structure of embodiment 2 according to the present disclosure.

(8) FIG. 8 is a partial enlarged view of a part B in FIG. 6 according to embodiment 2 of the present disclosure.

(9) FIG. 9 is a structural schematic view of a staple gun shell in embodiment 2 according to the present disclosure.

DETAILED DESCRIPTION OF EMBODIMENTS

(10) The present disclosure will be further described in detail in combination with the accompanying drawings and the specific embodiments.

Embodiment 1

(11) As shown in FIGS. 1 to 5, a staple gun includes a staple gun shell 1 with a fixed handle 11 and a movable handle 12, wherein the staple gun shell 1 is provided with a staple storage mechanism 2, one end of the staple storage mechanism 2 is provided with an opening which extends into one end of the staple gun shell 1 to form a staple outlet 21, the staple gun shell 1 is internally and slidably provided with a staple striking assembly 4 through an elastic sliding mechanism 3, and one end of the staple striking assembly 4 is capable of penetrating into the staple outlet 21, a pry bar type linkage reset mechanism 5, arranged between the movable handle 12 and the staple striking assembly 4, is capable of driving one end of the staple striking assembly 4 to get away from the staple outlet 21 when the movable handle 12 moves toward the fixed handle 11 under an external force, or when the external force disappears, the pry bar type linkage reset mechanism 5 is capable of driving the movable handle 12 to move far away from the fixed handle 11, and one end of the staple striking assembly 4 slides into the staple outlet 21 under the action of the elastic sliding mechanism 3. When the movable handle 12 moves toward the fixed handle 11 under the external force, the pry bar type linkage reset mechanism 5 follows the movable handle 12 to start running. The pry bar type linkage reset mechanism 5 runs to drive the staple striking assembly 4 to move in an elastic sliding mechanism 3 to enable the staple striking assembly 4 to get away from the staple outlet 21. When the external force disappears, the pry bar type linkage reset mechanism 5 is reset, and the staple striking assembly 4 moves toward the staple outlet 21 through the elastic sliding mechanism 3 and is in contact with the staple storage mechanism 2 at the same time.

(12) As shown in FIG. 3, the staple striking assembly 4 includes a staple striking plate 41 slidably arranged in the staple outlet 21, and one end, far away from the staple outlet 21, of the staple striking plate 41 is connected to a sliding plate 42. The staple striking plate 41 with a thickness equal to or less than that of a staple is used for pushing the staple out. One end of the staple striking plate 41 is connected to the sliding plate 42 so that the staple striking plate 41 can be pushed out or tightened by moving the sliding plate 42. Moreover, the thickness of the sliding plate 42 is more than that of the staple striking plate 41, thereby being capable of prolonging the service life of the staple striking plate 41.

(13) The elastic sliding mechanism 3 includes a sliding groove 31 arranged on one side inside the staple gun shell 1, the sliding plate 42 is slidably arranged in the sliding groove 31, one end of the sliding groove 31 is provided with a staple output base 32, the staple outlet 21 is formed on one side of the staple output base 32 in an axial direction, a bending part 43 extending downward is arranged between the staple striking plate 41 and the sliding plate 42, a staple striking torsion spring 33 is arranged in the staple gun shell 1, one end of the staple striking torsion spring 33 acts on the bending part 43, and the other end of the staple striking torsion spring acts on the staple gun shell 1 or the movable handle 12. The staple output base 32 has a limiting and protecting effect on

the staple striking plate **41** so that the staple striking plate **41** can operate normally without deviation or without causing the staple outlet **21** to get jammed. The bending part **43** of the sliding plate **42** has the effect of pushing the staple striking plate **41** out. The staple striking torsion spring **33** is tightened through the backward movement of the sliding plate **42**. When the sliding plate **42** is released, the staple striking torsion spring **33** returns to drive the bending part **43** of the sliding plate **42** to move forward, thereby generating a push force.

(14) Specifically, the pry bar type linkage reset mechanism **5** includes a pry bar linkage assembly **6** and a pry bar reset assembly **7** which are arranged in the staple gun shell **1**.

(15) Further, the pry bar linkage assembly **6** includes a linkage base **61** movably arranged in the staple gun shell **1**, one end of the linkage base **61** is inserted into a sliding hole **44** at one end, far away from the staple striking plate **41**, of the sliding plate **42**, and a linkage structure **8**, arranged between the linkage base **61** and the movable handle **12**, is capable of making the linkage base **61** move synchronously to enable the sliding plate **42** to move far away from the staple striking plate **41** when the movable handle **12** moves toward the fixed handle **11** under an external force. One end of the linkage base **61** is arranged in the sliding hole **44** of the sliding plate **42**, and

(16) the movable handle **12** drives the linkage base **61** to move through the linkage structure **8**, thereby enabling the sliding plate **42** to move backward.

(17) As shown in FIG. **4** and FIG. **5**, the linkage structure **8** includes a linkage plate **81** arranged between the linkage base **61** and the movable handle **12**, one end of the linkage plate **81** is connected to the movable handle **12** through a first movable shaft **82**, one end, far away from the sliding hole **44**, of the linkage base **61** is provided with a strip-shaped hole **83** that extends in an axial direction, a fixed shaft pin **13** that is fixedly arranged in the staple gun shell **1** penetrates into one end of the strip-shaped hole **83**, a second movable shaft **84** that is connected to one end, far away from the movable handle **12**, of the linkage plate **81** slidably penetrates into the other end of the strip-shaped hole **83**, the staple gun shell **1** is internally provided with a movable groove **85**, and an end part of the second movable shaft **84** is movably arranged in the movable groove **85**. The linkage plate **81** plays a role of a pry bar and moves between the linkage base **61** and the movable handle **12** through the first movable shaft **82** and the second movable shaft **84**. When the movable handle **12** is under stress, the linkage plate **81** moves toward the linkage base **61**, and the linkage base **61** enables an upper end of the linkage base **61** to move backward through the fixed shaft pin **13**, thereby driving the sliding plate **42** to move.

(18) As shown in FIG. **3**, the pry bar reset assembly **7** includes a return spring **71** arranged in the staple gun shell **1**, one end of the return spring **71** acts on an outer side of one end, far away from the strip-shaped hole **83**, of the linkage base **61**, and the other end of the return spring **71** acts on an inner side of the staple gun shell **1**. The return spring **71** mainly plays a role in helping the linkage base **61** to return and also has the effect of pushing the sliding plate **42**.

(19) The fixed handle **11** is integrally formed on the staple gun shell **1**, the movable handle **12** has a handle gripping part **14** and a handle connecting part **15**, the handle connecting part **15** is hinged to the interior of the staple gun shell **1** through a hinge shaft **16**, the movable handle **12** is located on one side, close to the staple outlet **21**, of the fixed handle **11**, the hinge shaft **16** is arranged at one end, far away from the handle gripping part **14**, of the handle connecting part **15**, the second movable shaft **84** is arranged between the hinge shaft **16** and the handle gripping part **14**, the linkage base **61** is movably arranged on one side, far away from the staple outlet **21**, of the movable handle **12** and located on an inner side of an upper end of the fixed handle **11**, and the return spring **71** is obliquely arranged.

(20) As shown in FIG. **1** and FIG. **2**, the staple storage mechanism **2** includes a staple storage aluminum section **23** detachably arranged on the staple gun shell **1** through a first connecting bolt **22**, one end of the staple storage aluminum section corresponds to the staple outlet **21**, one side of the staple storage aluminum section **23** is provided with an elastic buffer part **17** that abuts against the bending part **43**, one end, far away from the staple outlet **21**, of the staple storage aluminum

section **23** is provided with a staple groove base **25** through a second connecting bolt **24**, the staple groove base **25** is provided with a staple feeding base body **26** that penetrates into the staple storage aluminum section **23** and extends to the staple outlet **21**, and a staple feeding block **28**, which is connected to a tension spring **27** located in the staple feeding base body **26** and corresponds to the staple outlet **21**, is slidably arranged in the staple feeding base body **26**. When the staple striking torsion spring **33** returns to drive the sliding plate **42** to move forward, the bending part **43** of the sliding plate **42** abuts against the elastic buffer part **17**, and the elastic buffer part **17** achieves a buffering effect, thereby prolonging the service life of the staple gun. During use, the tension spring **27** is in a U-shaped structure. When the staple feeding block **28** moves downward to enable the tension spring **27** to start stretching to feed a staple into the staple feeding base body **26**, the staple feeding block **28** is released, and the tension spring **27** starts to return to feed the staple to the staple outlet **21**.

(21) Both the fixed handle **11** and the movable handle **12** are curved, an open space is formed between the fixed handle **11** and the movable handle **12**, and the open space can release the gripping space to improve the applicability.

(22) The principle of the embodiment lies in: one end of the linkage plate **81** is movably connected to the handle connecting part **15** of the movable handle **12** through the first movable shaft **82**, and the other end of the linkage plate **81** is movably connected to the linkage base **61** through the second movable shaft **84**; when the movable handle **12** is under stress, the movable handle **12** moves backward through the hinge shaft **16**, the linkage plate **81** also moves to push the linkage base **61** to move backward, the linkage base **61** drives the staple striking plate **41** and the sliding plate **42** to move at the same time, and the staple striking torsion spring **33** under the sliding plate **42** starts to be tightened; when the force applied to the movable handle **12** disappears, the staple striking torsion spring **33** starts to return to drive the sliding plate **42** to move forward so that the staple striking plate **41** goes into the staple outlet **21** to complete staple outputting, and the movable handle **12**, the linkage plate **81** and the linkage base **61** return through the return spring **71**.

Embodiment 2

(23) As shown in FIGS. **6** to **9**, the principle of the embodiment and the embodiment steps are similar to those of embodiment 1. The difference is that in embodiment 1, the movable handle **12** is located on one side, close to the staple outlet **21**, of the fixed handle **11**, and the return spring **71** is obliquely arranged. However, in the embodiment, the movable handle **12** is located on one side, far away from the staple outlet **21**, of the fixed handle **11**, the hinge shaft **16** is arranged at one end, close to the handle gripping part **14**, of the handle connecting part **15**, the second movable shaft **84** is arranged on one side, far away from the handle gripping part **14**, of the hinge shaft **16**, the linkage base **61** is movably arranged on one side, close to the staple outlet **21**, of the movable handle **12** and located on an inner side of an upper end of the fixed handle **11**, and the return spring **71** and the sliding plate **42** extend in the same direction.

(24) As shown in FIG. **8**, when the movable handle **12** is located on one side, far away from the staple outlet **21**, of the fixed handle **11**, a handle locking block **18** is rotationally arranged on the staple gun shell **1**, and the handle locking block **18** is connected to a stop block **19** that is located in the staple gun shell **1** and is capable of abutting against a notch at one end, far away from the sliding hole **44**, of the linkage base **61**.

(25) The specific embodiments described herein are only for example illustrations of the spirit of the present disclosure. Those skilled in the art to which the present invention pertains may make various modifications or additions to the specific embodiments described herein or replace them in a similar manner without departing from the spirit of the present disclosure or going beyond the scope defined in the appended claims.

(26) Although relative terms are used more frequently herein, the possibility of using other terms is not excluded. These terms are only used to describe and explain the nature of the present disclosure

more conveniently; it is to be construed that any additional limitation is inconsistent with the spirit of the present disclosure.

Claims

1. A staple gun, comprising: a staple gun shell (1) with a fixed handle (11) and a movable handle (12); wherein the staple gun shell (1) is provided with a staple storage mechanism (2), wherein one end of the staple storage mechanism (2) is provided with an opening which extends into one end of the staple gun shell (1) to form a staple outlet (21); wherein the staple gun shell (1) is internally and slidably provided with a staple striking assembly (4) through an elastic sliding mechanism (3), and a first end of the staple striking assembly (4) is capable of penetrating into the staple outlet (21) wherein a pry bar type linkage reset mechanism (5), arranged between the movable handle (12) and the staple striking assembly (4), is capable of driving the first end of the staple striking assembly (4) to get away from the staple outlet (21) when the movable handle (12) moves toward the fixed handle (11) under an external force, or, when the external force disappears, the pry bar type linkage reset mechanism (5) is capable of driving the movable handle (12) to move away from the fixed handle (11), and wherein the first end of the staple striking assembly (4) slides into the staple outlet (21) under an action of the elastic sliding mechanism (3); wherein the staple striking assembly (4) comprises a staple striking plate (41) slidably arranged in the staple outlet (21), and one end, away from the staple outlet (21), of the staple striking plate (41) is connected to a sliding plate (42); wherein the elastic sliding mechanism (3) comprises a sliding groove (31) arranged on one side inside the staple gun shell (1), the sliding plate (42) is slidably arranged in the sliding groove (31), and one end of the sliding groove (31) is provided with a staple output base (32), wherein the staple outlet (21) is formed on one side of the staple output base (32) in an axial direction, wherein a bending part (43) extending downward is arranged between the staple striking plate (41) and the sliding plate (42), a staple striking torsion spring (33) is arranged in the staple gun shell (1), one end of the staple striking torsion spring (33) acts on the bending part (43), and the other end of the staple striking torsion spring acts on the staple gun shell (1) or the movable handle (12).
2. The staple gun according to claim 1, wherein the pry bar type linkage reset mechanism (5) comprises a pry bar linkage assembly (6) and a pry bar reset assembly (7) which are arranged in the staple gun shell (1).
3. The staple gun according to claim 2, wherein the pry bar linkage assembly (6) comprises a linkage base (61) movably arranged in the staple gun shell (1), one end of the linkage base (61) is inserted into a sliding hole (44) at one end, away from the staple striking plate (41), of the sliding plate (42), and a linkage structure (8), arranged between the linkage base (61) and the movable handle (12), is capable of making the linkage base (61) move synchronously to enable the sliding plate (42) to move away from the staple striking plate (41) when the movable handle (12) moves toward the fixed handle (11) under the external force.
4. The staple gun according to claim 3, wherein the linkage structure (8) comprises a linkage plate (81) arranged between the linkage base (61) and the movable handle (12), one end of the linkage plate (81) is connected to the movable handle (12) through a first movable shaft (82), one end, away from the sliding hole (44), of the linkage base (61) is provided with a hole (83) that extends in an axial direction, a fixed shaft pin (13) that is fixedly arranged in the staple gun shell (1) penetrates into one end of the hole (83), a second movable shaft (84) that is connected to one end, away from the movable handle (12), of the linkage plate (81) slidably penetrates into the other end of the hole (83), the staple gun shell (1) is internally provided with a movable groove (85), and an end part of the second movable shaft (84) is movably arranged in the movable groove (85).
5. The staple gun according to claim 3, wherein both the fixed handle (11) and the movable handle (12) are curved, an open space is formed between the fixed handle (11) and the movable handle (12), and a handle locking block (18) is rotationally arranged on the staple gun shell (1), and the

handle locking block (18) is connected to a stop block (19) that is located in the staple gun shell (1) and is capable of abutting against a notch at one end, away from the sliding hole (44), of the linkage base (61).

6. The staple gun according to claim 3, wherein the pry bar reset assembly (7) comprises a return spring (71) arranged in the staple gun shell (1), one end of the return spring (71) acts on an outer side of one end, away from the hole (83), of the linkage base (61), and the other end of the return spring (71) acts on an inner side of the staple gun shell (1).

7. The staple gun according to claim 6, wherein the fixed handle (11) is integrally formed on the staple gun shell (1), the movable handle (12) has a handle gripping part (14) and a handle connecting part (15), the handle connecting part (15) is hinged to the interior of the staple gun shell (1) through a hinge shaft (16), the movable handle (12) is located on one side, close to the staple outlet (21), of the fixed handle (11), the hinge shaft (16) is arranged at one end, away from the handle gripping part (14), of the handle connecting part (15), the second movable shaft (84) is arranged between the hinge shaft (16) and the handle gripping part (14), the linkage base (61) is movably arranged on one side, away from the staple outlet (21), of the movable handle (12) and located on an inner side of an upper end of the fixed handle (11), and the return spring (71) is obliquely arranged; or the movable handle (12) is located on one side, away from the staple outlet (21), of the fixed handle (11), the hinge shaft (16) is arranged at one end, close to the handle gripping part (14), of the handle connecting part (15), the second movable shaft (84) is arranged on one side, away from the handle gripping part (14), of the hinge shaft (16), the linkage base (61) is movably arranged on one side, close to the staple outlet (21), of the movable handle (12) and located on an inner side of an upper end of the fixed handle (11), and the return spring (71) and the sliding plate (42) extend in the same direction.

8. The staple gun according to claim 1, wherein the staple storage mechanism (2) comprises a staple storage aluminum section (23) detachably arranged on the staple gun shell (1) through a first connecting bolt (22), one end of the staple storage aluminum section corresponds to the staple outlet (21), one side of the staple storage aluminum section (23) is provided with an elastic buffer part (17) that abuts against the bending part (43), one end, away from the staple outlet (21), of the staple storage aluminum section (23) is provided with a staple groove base (25) through a second connecting bolt (24), the staple groove base (25) is provided with a staple feeding base body (26) that penetrates into the staple storage aluminum section (23) and extends to the staple outlet (21), and a staple feeding block (28), which is connected to a tension spring (27) located in the staple feeding base body (26) and corresponds to the staple outlet (21), is slidably arranged in the staple feeding base body (26).
