

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12400292
B2
August 26, 2025
Kim; Jaehwan et al.

Apparatus and method for performing artificial intelligence encoding and artificial intelligence decoding on image by using pre-processing

Abstract

An artificial intelligence (AI) decoding apparatus includes a memory storing one or more instructions; and a processor configured to execute the one or more instructions to obtain image data generated through first encoding on a first image; obtain a second image corresponding to the first image by performing first decoding on the image data; perform pre-processing of changing a resolution of the second image, according to a pre-determined output resolution; and obtain a fourth image having the pre-determined output resolution by applying AI up-scaling based on an up-scaling deep neural network (DNN) to a third image obtained as a result of the pre-processing.

Inventors: Kim; Jaehwan (Suwon-si, KR), Park; Youngo (Suwon-si, KR), Yang; Heechul (Suwon-si, KR), Lee; Chaeun (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008782834

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 17/500672

Filed: October 13, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220036508 A1	Feb. 03, 2022

Foreign Application Priority Data

KR	10-2020-0022379	Feb. 24, 2020
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **G06T3/4046** (20240101); **G06T9/00** (20060101)

U.S. Cl.:

CPC **G06T3/4046** (20130101); **G06T9/00** (20130101);

Field of Classification Search

CPC: G06T (3/4046); G06T (9/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7308031	12/2006	Yamaguchi et al.	N/A	N/A
8385406	12/2012	Cho et al.	N/A	N/A
9602814	12/2016	Bhagavathy et al.	N/A	N/A
9679213	12/2016	Yang et al.	N/A	N/A
9749580	12/2016	Suh et al.	N/A	N/A
9936208	12/2017	Brailovski et al.	N/A	N/A
10148723	12/2017	Falvo	N/A	N/A
10218971	12/2018	Dong et al.	N/A	N/A
10225607	12/2018	Bai et al.	N/A	N/A
10423843	12/2018	Biemer	N/A	G06V 20/63
10623775	12/2019	Theis et al.	N/A	N/A
10817989	12/2019	Kim et al.	N/A	N/A
10817990	12/2019	Yang	N/A	G06T 3/4053
10825141	12/2019	Park	N/A	G06T 9/002
10832447	12/2019	Jeon et al.	N/A	N/A
10950009	12/2020	Dinh et al.	N/A	N/A
10986356	12/2020	Kim et al.	N/A	N/A
2005/0129306	12/2004	Wang et al.	N/A	N/A
2005/0195900	12/2004	Han	N/A	N/A
2007/0189392	12/2006	Tourapis et al.	N/A	N/A
2008/0140594	12/2007	Tannhof et al.	N/A	N/A
2009/0141809	12/2008	Visharam et al.	N/A	N/A
2009/0148054	12/2008	Kim et al.	N/A	N/A
2011/0026819	12/2010	Lee	N/A	N/A
2011/0090950	12/2010	Bush et al.	N/A	N/A
2012/0026288	12/2011	Tourapis et al.	N/A	N/A
2012/0275511	12/2011	Shemer et al.	N/A	N/A

2014/0037015	12/2013	Ye et al.	N/A	N/A
2014/0177706	12/2013	Fernandes et al.	N/A	N/A
2014/0247890	12/2013	Yamaguchi et al.	N/A	N/A
2015/0042878	12/2014	Jeon et al.	N/A	N/A
2015/0256828	12/2014	Dong et al.	N/A	N/A
2015/0334416	12/2014	Holcomb et al.	N/A	N/A
2015/0371132	12/2014	Gemello	706/20	H01L 29/785
2016/0323583	12/2015	Kadoto et al.	N/A	N/A
2016/0328630	12/2015	Han et al.	N/A	N/A
2016/0360155	12/2015	Civanlar et al.	N/A	N/A
2017/0039456	12/2016	Saberian et al.	N/A	N/A
2017/0208345	12/2016	Jeong et al.	N/A	N/A
2017/0287109	12/2016	Tasfi	N/A	N/A
2017/0344808	12/2016	El-Khamy	N/A	G06T 7/70
2017/0345130	12/2016	Wang et al.	N/A	N/A
2017/0347061	12/2016	Wang	N/A	G06N 3/04
2017/0347110	12/2016	Wang et al.	N/A	N/A
2017/0357871	12/2016	Zhai et al.	N/A	N/A
2018/0014022	12/2017	Cho et al.	N/A	N/A
2018/0063549	12/2017	Amer et al.	N/A	N/A
2018/0075343	12/2017	van den Oord	N/A	G06F 40/44
2018/0107925	12/2017	Choi et al.	N/A	N/A
2018/0131953	12/2017	Wang et al.	N/A	N/A
2018/0139458	12/2017	Wang	N/A	G06T 3/4053
2018/0174275	12/2017	Bourdev et al.	N/A	N/A
2018/0176576	12/2017	Rippel et al.	N/A	N/A
2018/0239972	12/2017	Biemer	N/A	G06V 20/582
2018/0249158	12/2017	Huang et al.	N/A	N/A
2018/0293706	12/2017	Viswanathan et al.	N/A	N/A
2018/0302456	12/2017	Katsavounidis et al.	N/A	N/A
2018/0352233	12/2017	Alshina et al.	N/A	N/A
2019/0013822	12/2018	Marpe et al.	N/A	N/A
2019/0075301	12/2018	Chou et al.	N/A	N/A
2019/0147296	12/2018	Wang et al.	N/A	N/A
2019/0166379	12/2018	Navarrete Michellini et al.	N/A	N/A
2019/0180189	12/2018	Biesemann et al.	N/A	N/A
2019/0230354	12/2018	Kim	N/A	N/A
2020/0053408	12/2019	Park et al.	N/A	N/A
2020/0126186	12/2019	Kim	N/A	G06N 3/084
2020/0143194	12/2019	Hou et al.	N/A	N/A
2020/0162751	12/2019	Kim et al.	N/A	N/A
2020/0162789	12/2019	Ma et al.	N/A	N/A

2020/0184685	12/2019	Kim	N/A	H04N 19/59
2020/0193647	12/2019	Jeon	N/A	G06T 5/70
2020/0258197	12/2019	Tai et al.	N/A	N/A
2020/0382792	12/2019	Gao et al.	N/A	N/A
2020/0382793	12/2019	Gao et al.	N/A	N/A
2021/0073947	12/2020	Park	N/A	G06N 3/045
2021/0125380	12/2020	Lee	N/A	H04N 19/117
2021/0160556	12/2020	Jang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101878649	12/2009	CN	N/A
104754357	12/2014	CN	N/A
104902273	12/2014	CN	N/A
107431805	12/2016	CN	N/A
2009-540625	12/2008	JP	N/A
100286443	12/2000	KR	N/A
100657280	12/2005	KR	N/A
101375663	12/2013	KR	N/A
101425602	12/2013	KR	N/A
1020140145560	12/2013	KR	N/A
1020150041098	12/2014	KR	N/A
1020150060906	12/2014	KR	N/A
10-2015-0087103	12/2014	KR	N/A
10-2015-0135637	12/2014	KR	N/A
1020160131848	12/2015	KR	N/A
1020160132331	12/2015	KR	N/A
1020170059040	12/2016	KR	N/A
1020170100045	12/2016	KR	N/A
1020180001428	12/2017	KR	N/A
1020180043154	12/2017	KR	N/A
1020180052651	12/2017	KR	N/A
101885855	12/2017	KR	N/A
1020180100976	12/2017	KR	N/A
1020180108288	12/2017	KR	N/A
102022648	12/2018	KR	N/A
10-2019-0130479	12/2018	KR	N/A
10-2020-0009118	12/2019	KR	N/A
1020200016943	12/2019	KR	N/A
1020200044661	12/2019	KR	N/A
2012058394	12/2011	WO	N/A
2015/104963	12/2014	WO	N/A
2016132148	12/2015	WO	N/A
2016132152	12/2015	WO	N/A
WO-2016132145	12/2015	WO	G06K 9/46
2017036370	12/2016	WO	N/A

WO-2017144881	12/2016	WO	G06T 3/4053
2019220095	12/2018	WO	N/A
WO-2020080709	12/2019	WO	G06N 3/04
WO-2020080765	12/2019	WO	G06N 20/10

OTHER PUBLICATIONS

Communication dated Jan. 14, 2021 issued by the Korean Patent Office in application No. 10-2020-7000378. cited by applicant

Communication dated Aug. 19, 2019 issued by the European Patent Office in application No. 19183429.0. cited by applicant

Tao, W., et al., “An End-to-End Compression Framework Based on Convolutional Neural Networks”, 2017 Data Compression Conference, IEEE, 2017, p. 463. cited by applicant

Theis, L., et al., “Lossy Image Compression With Compressive Autoencoders”, ICLR 2017, arXiv:1703.00395v1 [stat.ML] Mar. 1, 2017, pp. 1-19. cited by applicant

Jiang, F., et al., “An End-to-End Compression Framework Based on Convolutional Neural Networks”, IEEE Transactions on Circuits and Systems for Video Technology, arXiv:1708.00838v1 [cs.CV] Aug. 2, 2017, pp. 1-13. cited by applicant

Nguyen, V.-A., et al., “Adaptive Downsampling/Upsampling for Better Video Compression at Low Bit Rate”, IEEE 2008, pp. 1624-1627. cited by applicant

Communication dated Apr. 28, 2020 issued by the European Patent Office in application No. 19183429.0. cited by applicant

Yahia, H., “Frame Interpolation using Convolutional Neural Networks on 2D animation”, Universiteit Van Amsterdam Bachelor Thesis, Jun. 24, 2016, XP055558906. cited by applicant

Skoneczny, S., et al., “Classical and neural methods of image sequence interpolation”, SPIE—International Society for Optical Engineering Proceedings, vol. 4535, Aug. 24, 2001, XP 055688092, pp. 190-204. cited by applicant

Communication dated Dec. 11, 2020 issued by the European Patent Office in application No. 19183429.0. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 & PCT/ISA/237) dated Aug. 6, 2019 issued by the International Searching Authority in International Application No. PCT/KR2019/004171. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 and PCT/ISA9237) dated Dec. 4, 2019 issued by the International Searching Authority in International Application No. PCT/KR2019/010645. cited by applicant

Communication dated Dec. 16, 2020 issued by the Korean Patent Office in application No. 10-2019-0062583. cited by applicant

Cho, S., et al., “A Technical Analysis on Deep Learning based Image and Video Compression”, Journal of Broadcast Engineering Society, Korean Institute of Broadcast and Media Engineers, May 2018, pp. 383-394. cited by applicant

Johnston, N., et al., “Improved Lossy Image Compression with Priming and Spatially Adaptive Bit Rates for Recurrent Networks”, Cornell University, Mar. 29, 2017, 9 pages. cited by applicant

Communication dated Dec. 22, 2020 issued by the Korean Patent Office in application No. 10-2019-0066057. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 and PCT/ISA237) dated Jan. 30, 2020 issued by the International Searching Authority in International Application No. PCT/KR2019/013421. cited by applicant

Nick Johnston et al., “Improved Lossy Image Compression with Priming and Spatially Adaptive Bit Rates for Recurrent Networks”, Proceedings of the IEEE Conference on CVPR, Computer

Vision Foundation, Jun. 23, 2018, pp. 4385-4393, 9 total pages. cited by applicant

Li et al., "Learning a Convolutional Neural Network for Image Compact-Resolution," IEEE Transactions on Image Processing, vol. 28, No. 3, pp. 1092-1107, Mar. 2019, XP011703593. cited by applicant

Li et al., "Convolutional Neural Network-Based Block Up-Sampling for Intra Frame Coding," IEEE Transactions on Circuits and Systems for Video Technology, vol. 28, No. 9, pp. 2316-2330, Sep. 2018, XP055610817. cited by applicant

Communication dated Jun. 1, 2021, issued by the International Searching Authority in counterpart International Application No. PCT/KR2021/002204 (PCT/ISA/220, 210, 237). cited by applicant

Communication dated Jul. 27, 2021, issued by the Korean Patent Office in counterpart Korean Patent Application No. 10-2020-22379. cited by applicant

Communication dated Jun. 7, 2021, issued by the India Intellectual Property Office in Indian Patent Application No. 201924041670. cited by applicant

Communication dated Aug. 9, 2021, issued by the Korean Patent Office in counterpart Korean Patent Application No. 10-2019-0062583. cited by applicant

Communication dated Apr. 27, 2021 issued by the Korean Intellectual Property Office in application No. 10-2020-0022379. cited by applicant

Communication dated Mar. 8, 2021 issued by the Intellectual Property India Patent Office in application No. 201927038419. cited by applicant

Communication dated Jun. 21, 2021, issued by the Korean Patent Office in counterpart Korean Patent Application No. 10-2019-0062583. cited by applicant

Communication dated Jun. 21, 2021, issued by the Korean Patent Office in counterpart Korean Patent Application No. 10-2019-0066057. cited by applicant

Communication dated Aug. 9, 2021, issued by the Korean Patent Office in counterpart Korean Patent Application No. 10-2019-0066057. cited by applicant

Communication dated Jun. 29, 2021, issued by the European Patent Office in counterpart European Application No. 19872393.4. cited by applicant

Kim, H., et al., "Task-Aware Image Downscaling", Computer Vision-ECCV 2018, Oct. 6, 2018, pp. 1-16. cited by applicant

Park, W.-S., et al., "CNN-Based In-Loop Filtering For Coding Efficiency Improvement", IEEE, 2016, 5 pages. cited by applicant

Dai, Y., et al., "A Convolutional Neural Network Approach for Post-Processing in HEVC Intra Coding", arXiv:1608.06690v2 [cs.MM] Oct. 29, 2016, 12 pages. cited by applicant

Rastegari, M., et al., "XNOR-Net: ImageNet Classification Using Binary Convolutional Neural Networks", Allen Institute for AI, University of Washington, 17 pages, Sep. 17, 2016. cited by applicant

Courbariaux, M., et al., "BinaryConnect: Training Deep Neural Networks with binary weights during propagations", 1 arXiv:1511.00363v3 [cs.LG] Apr. 18, 2016, pp. 1-9. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 and PCT/ISA/237) dated Apr. 5, 2018 issued by the International Searching Authority in International Application No. PCT/KR2017/007258. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 and PCT/ISA/237) dated Jul. 11, 2018 issued by the International Searching Authority in International Application No. PCT/KR2018/001542. cited by applicant

Mao, X.J., et al., "Image Restoration Using Convolutional Auto-encoders with Symmetric Skip Connections", arXiv:1606.08921v3 [cs.CV] Aug. 30, 2016, Corne II University Library, pp. 1-17. cited by applicant

Communication dated Oct. 4, 2021, issued by the European Patent Office in counterpart European Application No. 19873223.2. cited by applicant

Sajjadi et al., "EnhanceNet: Single Image Super-Resolution Through Automated Texture

Synthesis,” 2017 IEEE International Conference on Computer Vision, pp. 4501-4510, Oct. 2017, XP033283324. cited by applicant

Guo et al., “Deep Learning Based Image Super-Resolution With Coupled Backpropagation,” 2016 IEEE Global Conference on Signal and Information Processing (GlobalSIP 2016), pp. 237-241, Dec. 2016, XP033087061. cited by applicant

Communication dated Apr. 6, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/570,057. cited by applicant

Communication dated Oct. 23, 2019 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/570,057. cited by applicant

Kim, J., et al. “Dynamic frame resizing with convolutional neural network for efficient video compression.” Applications of Digital Image Processing XL. vol. 10396. International Society for Optics and Photonics, 2017. (Year: 2017), pp. 103961R-1-103961R-13 (14 pages). cited by applicant

Afonso, M., et al. “Spatial resolution adaptation framework for video compression.” Applications of Digital Image Processing XU. vol. 10752. International Society for Optics and Photonics, 2018. (Year: 2018), pp. 107520L-1-107520L-10 (11 pages). cited by applicant

“several, adj., adv. and n.” OED Online, Oxford University Press, Mar. 2020, oed.com/view/Entry/176914. Accessed Mar. 27, 2020. (Year: 2020), pp. 1-21. cited by applicant

Gorodilov, A., et al., “Neural Networks for Image and Video Compression.” 2018 International Conference on Artificial Intelligence Applications and Innovations (IC-AIAI). IEEE. (Year: 2018), pp. 37-41. cited by applicant

Zhang, X., et al., “Can lower resolution be better?.” Data Compression Conference (Dec. 2008). IEEE, 2008. (Year: 2008), pp. 302-311. cited by applicant

Communication dated Mar. 24, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/793,605. cited by applicant

Cai, B., et al., “Deep Sampling Networks”, arXiv:1712.00926v2 (2018), pp. 1-17. cited by applicant

Communication dated Jun. 29, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/821,609. cited by applicant

Chen, H., et al., “Low bit rates image compression via adaptive block downsampling and super resolution”, Journal of Electronic Imaging, vol. 25, No. 1, Jan./Feb. 2016, pp. 013004-1-013004-10 (11 pages). cited by applicant

Hosking, B., et al., “An Adaptive Resolution Rate Control Method For INTRA Coding in HEVC”, 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 1486-1490. cited by applicant

Hou, X., et al., “Learning Based Image Transformation Using Convolutional Neural Networks”, IEEE Access, vol. 6, 2018, pp. 49779-49792. cited by applicant

Communication dated Aug. 24, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/821,686. cited by applicant

Colic, A., et al., “Exploring NVIDIA-CUDA for Video Coding”, Proceedings of the first annual ACM SIGMM Conference on Multimedia systems, 2010, pp. 13-22. cited by applicant

Communication dated Apr. 27, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/821,686. cited by applicant

Deshpande, A., “A Beginner's Guide to Understanding Convolutional Neural Networks”, <https://adeshpande3.github.io/A-Beginner%27s-Guide-To-Understanding-Convolutional-Neural-Networks>, Jul. 20, 2016, pp. 1/31-17/31. cited by applicant

Communication dated Nov. 5, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/821,686. cited by applicant

Communication dated Feb. 17, 2021 issued by the United States Patent and Trademark Office in U.S. Appl. No. 17/082,848. cited by applicant

Communication dated Sep. 29, 2022 issued by the United States Patent and Trademark Office in U.S. Appl. No. 17/383,533. cited by applicant

Communication dated Oct. 16, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/468,338. cited by applicant

Communication dated Dec. 4, 2019 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/656,812. cited by applicant

Aklson, Alex. "Shallow Versus Deep Neural Networks." Introduction to Deep Learning & Neural Networks with Keras, Coursera. <https://www.coursera.org/lecture/introduction-to-deep-learning-with-keras/shallow-versus-deep-neural-networks-3pKHn>. Accessed Nov. 26, 2019. (Year: 2019). cited by applicant

Communication dated Jan. 12, 2021 issued by the United States Patent and Trademark Office in U.S. Appl. No. 17/079,773. cited by applicant

Communication dated Oct. 14, 2022 issued by the United States Patent and Trademark Office in U.S. Appl. No. 17/575,691. cited by applicant

Communication dated Mar. 13, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/781,083. cited by applicant

Communication dated Dec. 18, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/750,615. cited by applicant

Communication dated Aug. 17, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/750,615. cited by applicant

Communication dated Jul. 30, 2020 issued by the United States Patent and Trademark Office in U.S. Appl. No. 16/656,812. cited by applicant

Communication issued on Jun. 27, 2024 by the European Patent Office for EP Patent Application No. 19183429.0. cited by applicant

Communication issued on May 27, 2024 by the Indian Patent Office in corresponding IN Patent Application No. 201944042227. cited by applicant

Communication issued by the United States Patent and Trademark Office on Jan. 19, 2023 for U.S. Appl. No. 17/383,533. cited by applicant

Communication issued by the United States Patent and Trademark Office on Feb. 10, 2023 for U.S. Appl. No. 17/575,691. cited by applicant

Communication dated May 24, 2022, issued by the Korean Intellectual Property Office in Korean Patent Application No. 10-2021-0119183. cited by applicant

Communication dated Nov. 8, 2021 issued by the Korean Patent Office in counterpart Korean Application No. 10-2021-0119183. cited by applicant

Communication issued Sep. 20, 2023 by National Intellectual Property Administration, PRC in Chinese Application No. 201980068867.1. cited by applicant

Communication dated Feb. 21, 2022, issued by the Korean Intellectual Property Office in Korean Patent Application No. 10-2019-0066057. cited by applicant

Communication dated Jan. 12, 2022, issued by the China National Intellectual Property Administration in counterpart Chinese Application No. 201880013752.8. cited by applicant

Communication dated Feb. 22, 2024, issued by the National Intellectual Property Administration, PRC, in Chinese Application No. 201980061966.7. cited by applicant

Communication dated Aug. 29, 2022, issued by the Korean Intellectual Property Office in Korean Patent Application No. 10-2019-0062583. cited by applicant

Communication dated Sep. 22, 2022, issued by the Korean Intellectual Property Office in Korean Patent Application No. 10-2019-0062583. cited by applicant

Communication dated Aug. 25, 2022, issued by the National Intellectual Property Administration of P.R. China in counterpart Chinese Application No. 201880013752.8. cited by applicant

Communication issued Oct. 21, 2024 by the European Patent Office in European Patent Application No. 19872393.4. cited by applicant

Communication issued Oct. 28, 2024 by the European Patent Office for EP Patent Application No. 19183429.0. cited by applicant
Communication issued Sep. 4, 2024 by the European Patent Office for EP Patent Application No. 19183429.0. cited by applicant
Communication dated Dec. 19, 2024 issued by the European Patent Office in European Patent Application No. 19873223.2. cited by applicant
Communication issued Jun. 12, 2025 by the European Intellectual Property Office in counterpart European Patent Application No. 19873223.2. cited by applicant

Primary Examiner: Shedrick; Charles T

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. application Ser. No. 17/184,250 dated Feb. 24, 2021, which is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2020-0022379, filed on Feb. 24, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to image processing. More particularly, the disclosure relates to a method and apparatus for performing artificial intelligence (AI) encoding and AI decoding on an image.

2. Description of the Related Art

(2) Images are encoded by a codec following a designated data compression standard, e.g., a moving picture expert group (MPEG) compression standard, and are then stored in a recording medium or are transmitted via a communication channel in the form of bit streams.

(3) As hardware for reproducing and storing high-resolution/high-quality images is being developed and supplied, a need for a codec capable of effectively encoding and decoding high-resolution/high-quality images is increasing.

SUMMARY

(4) Provided are an artificial intelligence (AI) encoding method based on pre-processing, an AI decoding method based on pre-processing, an AI encoding apparatus based on pre-processing, and an AI decoding apparatus based on pre-processing, in which an image is encoded and decoded based on AI to attain a low bitrate.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments of the disclosure.

(6) According to an embodiment of the disclosure, an AI decoding apparatus includes a memory storing one or more instructions; and a processor configured to execute the one or more instructions stored in the memory, wherein the processor is configured to: obtain image data generated through first encoding on a first image; obtain a second image corresponding to the first image by performing first decoding on the image data; perform pre-processing of changing a resolution of the second image, according to a pre-determined output resolution; and obtain a fourth image having the pre-determined output resolution by applying AI up-scaling based on an up-scaling deep neural network (DNN) to a third image obtained as a result of the pre-processing.

(7) The processor may be further configured to change the resolution of the second image via a

legacy scaling method.

(8) The processor may be further configured to: determine, as a target resolution of the third image, a value obtained by dividing the pre-determined output resolution by a scaling factor of the up-scaling DNN; and change the resolution of the second image to have the determined target resolution.

(9) The processor may be further configured to: obtain AI data related to AI down-scaling of an original image to the first image; and select DNN setting information corresponding to the AI data from among a plurality of DNN setting information previously stored in the AI decoding apparatus. The up-scaling DNN may operate according to the selected DNN setting information.

(10) The processor may be further configured to determine the output resolution according to performance information of a display that reproduces the fourth image.

(11) According to another embodiment of the disclosure, an AI encoding apparatus includes a memory storing one or more instructions; and a processor configured to execute the one or more instructions stored in the memory, wherein the processor is configured to: perform pre-processing of changing a resolution of a first original image according to a pre-determined output resolution; obtain a first image having the pre-determined output resolution by applying AI down-scaling based on a down-scaling DNN to a second original image obtained as a result of the pre-processing; generate image data by performing first encoding on the first image; and transmit the image data.

(12) The processor may be further configured to change the resolution of the first original image via a legacy scaling method.

(13) The processor may be further configured to: determine, as a target resolution of the second original image, a value obtained by dividing the pre-determined output resolution by a scaling factor of the down-scaling DNN; and change the resolution of the first original image to have the determined target resolution.

(14) The down-scaling DNN may be trained based on first quality loss information corresponding to a difference between a fourth training image obtained by performing AI up-scaling on an original training image through an up-scaling DNN and an enlarged training image obtained by performing legacy up-scaling on the original training image.

(15) The down-scaling DNN may be trained based on second quality loss information corresponding to a difference between a first training image obtained by performing AI down-scaling on the fourth training image through the down-scaling DNN and the original training image.

(16) The processor may be further configured to transmit AI data related to the AI down-scaling, and the AI data may be used to select DNN setting information to be set for an up-scaling DNN for AI up-scaling from among a plurality of DNN setting information previously stored in an AI decoding apparatus.

(17) The processor may be further configured to determine the output resolution, based on performance information of a display that reproduces a second image obtained through first decoding on the image data.

(18) The processor may be further configured to determine the output resolution, based on a scaling factor of an AI decoding apparatus that performs AI up-scaling on a second image obtained through first decoding on the image data and performance information of a display that reproduces a fourth image obtained through AI up-scaling on the second image.

(19) The processor may be further configured to execute at least one of the one or more instructions to, when an AI decoding apparatus is able to perform pre-processing of changing resolution of a second image obtained through first decoding on the image data, determine the output resolution based on the state of a network that connects the AI encoding apparatus to the AI decoding apparatus.

(20) According to another embodiment of the disclosure, an AI decoding method includes

obtaining image data generated through first encoding on a first image; obtaining a second image corresponding to the first image by performing first decoding on the image data; performing pre-processing of changing resolution of the second image, according to a pre-determined output resolution; and obtaining a fourth image having the pre-determined output resolution by applying AI up-scaling based on an up-scaling DNN to a third image obtained as a result of the pre-processing.

(21) According to another embodiment of the disclosure, an AI encoding method includes performing pre-processing of changing resolution of a first original image according to a pre-determined output resolution; obtaining a first image having the pre-determined output resolution by applying AI down-scaling based on a down-scaling deep neural network (DNN) to a second original image obtained as a result of the pre-processing; generating image data by performing first encoding on the first image; and transmitting the image data.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1A is a diagram for describing an artificial intelligence (AI) encoding process and a first AI decoding process, according to an embodiment of the disclosure;

(3) FIG. 1B is a diagram for describing an AI encoding process and a second AI decoding process, according to an embodiment of the disclosure;

(4) FIG. 10 is a diagram for describing an AI encoding process and a general decoding process, according to an embodiment of the disclosure;

(5) FIG. 2 is a block diagram of a structure of an AI decoding apparatus according to an embodiment of the disclosure;

(6) FIG. 3 is a diagram showing a second deep neural network (DNN) for performing AI up-scaling on a third image;

(7) FIG. 4 is a diagram for describing a convolution operation in a convolution layer;

(8) FIG. 5 is a table showing a mapping relationship between several pieces of image-related information and several DNN setting information;

(9) FIG. 6 is a diagram showing a third image including a plurality of frames;

(10) FIG. 7 is a block diagram of a structure of an AI encoding apparatus according to an embodiment of the disclosure;

(11) FIG. 8 is a diagram showing a first DNN for performing AI down-scaling on a second original image;

(12) FIG. 9 is a diagram for describing a method of training a first DNN and a second DNN;

(13) FIG. 10 is a diagram for describing training processes of a first DNN and a second DNN, performed by a training apparatus;

(14) FIG. 11 is a diagram for explaining another method of training a first DNN;

(15) FIG. 12 is a diagram for explaining another method of training a second DNN;

(16) FIG. 13 is a diagram for describing training processes of a first DNN and a second DNN by a training apparatus; and

(17) FIG. 14 is a diagram of an apparatus for performing AI down-scaling and an apparatus for performing AI up-scaling.

DETAILED DESCRIPTION

(18) As the disclosure allows for various changes and numerous embodiments of the disclosure, exemplary embodiments of the disclosure will be illustrated in the drawings and described in detail

in the written description. However, this is not intended to limit the disclosure to particular modes of practice, and it is to be appreciated that all changes, equivalents, and substitutes that do not depart from the spirits and technical scopes of several embodiments of the disclosure are encompassed in the disclosure.

(19) In the description of embodiments of the disclosure, certain detailed explanations of the related art are omitted when it is deemed that they may unnecessarily obscure the essence of the disclosure. While such terms as “first,” “second,” etc., may be used to describe various components, such components must not be limited to the above terms. The above terms are used only to distinguish one component from another.

(20) When an element (e.g., a first element) is “coupled to” or “connected to” another element (e.g., a second element), the first element may be directly coupled to or connected to the second element, or, unless otherwise described, a third element may exist therebetween.

(21) In the present specification, regarding an element represented as a “unit” or a “module”, two or more elements may be combined into one element or one element may be divided into two or more elements according to subdivided functions. In addition, each element described hereinafter may additionally perform some or all of functions performed by another element, in addition to main functions of itself, and some of the main functions of each element may be performed entirely by another component.

(22) Throughout the disclosure, the expression “at least one of a, b or c” indicates only a, only b, only c, both a and b, both a and c, both b and c, all of a, b, and c, or variations thereof.

(23) Also, in the present specification, an ‘image’ or a ‘picture’ may denote a still image, a moving image including a plurality of consecutive still images (or frames), or a video.

(24) Also, in the present specification, a deep neural network (DNN) is a representative example of an artificial neural network model simulating brain nerves, and is not limited to an artificial neural network model using a specific algorithm. In the present specification, a DNN may be referred to as a neural network (NN).

(25) Also, in the present specification, a ‘parameter’ is a value used in an operation process of each layer forming a neural network, and for example, may include a weight used when an input value is applied to a certain operation expression. Here, the parameter may be expressed in a matrix form. The parameter is a value set as a result of training, and may be updated through separate training data when necessary.

(26) Also, in the present specification, a ‘first DNN’ indicates a DNN used for artificial intelligence (AI) down-scaling an image, and a ‘second DNN’ indicates a DNN used for AI up-scaling an image.

(27) Also, in the present specification, ‘DNN setting information’ includes information related to an element constituting a DNN. ‘DNN setting information’ includes the parameter described above as information related to the element constituting the DNN. The first DNN or the second DNN may be set by using the DNN setting information, and may operate according to the set DNN setting information.

(28) Also, in the present specification, a ‘first original image’ denotes an image to be an object of AI encoding, a ‘second original image’ denotes an image obtained as a result of pre-processing during an AI encoding process, and a ‘first image’ denotes an image obtained as a result of performing AI down-scaling during the AI encoding process. A ‘second image’ denotes an image obtained via first decoding during an AI decoding process, a ‘third image’ denotes an image obtained as a result of pre-processing during the AI decoding process, and a ‘fourth image’ denotes an image obtained by performing AI up-scaling during the AI decoding process.

(29) Also, in the present specification, ‘AI down-scale’ denotes a process of decreasing resolution of an image according to a predetermined scaling factor, based on AI, and ‘first encoding’ denotes an encoding process according to an image compression method based on frequency transformation. Also, ‘first decoding’ denotes a decoding process according to an image

reconstruction method based on frequency transformation, and 'AI up-scale' denotes a process of increasing resolution of an image according to a predetermined scaling factor, based on AI. The scaling factor could be referred to scaling magnification.

(30) FIG. 1A is a diagram for describing an AI encoding process and a first AI decoding process, according to an embodiment of the disclosure.

(31) As described above, when resolution of an image remarkably increases, the throughput of information for encoding and decoding the image is increased, and accordingly, a method for improving efficiency of encoding and decoding of an image is required.

(32) As shown in FIG. 1A, according to an embodiment of the disclosure, a first image **125** is obtained by performing pre-processing **110** and AI down-scaling **120** on a first original image **105** having high resolution. Then, first encoding **130** and first decoding **140** are performed on the first image **125** having relatively low resolution, and thus a bitrate may be largely reduced compared to when the first encoding **130** and the first decoding **140** are performed on the first original image **105**.

(33) In detail, referring to FIG. 1A, during the AI encoding process, a second original image **115** is obtained by performing the pre-processing **110** to change the resolution of the first original image **105**, and the first image **125** is obtained by performing the AI down-scaling **110** on the second original image **115**. The first image **125** undergoes the first encoding **130**.

(34) During the AI decoding process, AI encoding data including AI data and image data, which are obtained as a result of AI encoding, is received, a second image **145** is obtained via the first decoding **140**, and a third image **155** is obtained by performing pre-processing **150** to change the resolution of the second image **145**. A fourth image **165** is obtained by performing AI up-scaling **160** on the third image **155**. The fourth image **165** is post-processed as necessary and then is reproduced by a display (not shown).

(35) Referring to the AI encoding process in detail, when the first original image **105** is received, the pre-processing **110** and the AI down-scaling **120** are performed on the first original image **105** to obtain the first image **125** of certain resolution or certain quality.

(36) The pre-processing **110** includes a legacy scaling process, and the resolution of the first original image **105** may be changed to an arbitrary resolution via the pre-processing **110**. The resolution of the first original image **105** is changed to an arbitrary resolution to diversify the resolution of the first image **125** as a target of the first encoding **130**. By diversifying the resolution of the first image **125**, the size of image data that is transmitted via a network or stored in a storage medium may be adjusted according to circumstances.

(37) The AI down-scaling **120** is performed based on AI, and AI for the AI down-scaling **120** needs to be trained jointly with AI for the AI up-scaling **160**. This is because, when the AI for the AI down-scaling **120** and the AI for the AI up-scaling **160** are separately trained, a difference between the first original image **105**, which is an object of AI encoding, and the fourth image **165** reconstructed through AI decoding is increased.

(38) In an embodiment of the disclosure, the AI data may be used to maintain such a joint relationship during the AI encoding process and the AI decoding process. Accordingly, the AI data obtained through the AI encoding process may include information indicating an up-scaling target, and during the AI decoding process, the AI up-scaling **160** needs to be performed on the third image **155** according to the up-scaling target verified based on the AI data.

(39) The AI for the AI down-scaling **120** and the AI for the AI up-scaling **160** may be embodied as a DNN. As will be described later with reference to FIGS. 9, 11, and 12, because a first DNN and a second DNN are jointly trained under a certain target, an AI encoding apparatus may provide target information used during joint training of the first DNN and the second DNN to an AI decoding apparatus, and the AI decoding apparatus may perform the AI up-scaling **160** on the third image **155** to target resolution or quality based on the provided target information.

(40) Regarding the first encoding **130** of FIG. 1A, information amount of the first image **125**

obtained by performing the AI down-scaling **120** on the second original image **115** may be reduced through the first encoding **130**. The first encoding **130** may include a process of generating prediction data by predicting the first image **125**, a process of generating residual data corresponding to a difference between the first image **125** and the prediction data, a process of transforming the residual data of a spatial domain component to a frequency domain component, a process of quantizing the residual data transformed to the frequency domain component, and a process of entropy-encoding the quantized residual data. Such first encoding **130** may be performed via one of image compression methods using frequency transformation, such as MPEG-2, H.264 Advanced Video Coding (AVC), MPEG-4, High Efficiency Video Coding (HEVC), VC-1, VP8, VP9, and AOMedia Video 1 (AV1).

(41) The AI encoding data obtained through the AI encoding process may include the image data obtained as a result of performing the first encoding **130** on the first image **125**, and the AI data related to the AI down-scaling **120** of the second original image **115**. The image data may be used during the first decoding **140** and the AI data may be used during the AI up-scaling **160**.

(42) The image data may be transmitted in a form of a bitstream. The image data may include data obtained based on pixel values in the first image **125**, for example, residual data that is a difference between the first image **125** and prediction data of the first image **125**. Also, the image data includes pieces of information used during the first encoding **130** performed on the first image **125**. For example, the image data may include prediction mode information, motion information, and information related to quantization parameter used during the first encoding **130**. The image data may be generated according to a rule, for example, according to a syntax, of an image compression method used during the first encoding **130**, among MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1.

(43) The second image **145** corresponding to the first image **125** may be reconstructed by performing the first decoding **140** on the image data. The first decoding **140** may include a process of generating the quantized residual data by entropy-decoding the image data, a process of inverse-quantizing the quantized residual data, a process of transforming the residual data of the frequency domain component to the spatial domain component, a process of generating the prediction data, and a process of reconstructing the second image **145** by using the prediction data and the residual data. Such first decoding **140** may be performed via an image reconstruction method corresponding to one of the image compression methods using frequency transformation, such as MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1, which is used in the first encoding **130**.

(44) The resolution of the second image **145** obtained by performing the first decoding **140** on the image data is changed via the pre-processing **150**. The pre-processing **150** includes a legacy scaling process, and the resolution of the second image **145** may be changed to an arbitrary resolution via the pre-processing **150**. The resolution of the second image **145** is changed to an arbitrary resolution to diversify the resolution of the fourth image **165**, which is to be reproduced, or the resolution of a pre-processed fourth image. In other words, because the resolution of an image that may be reproduced by the display may vary according to the performance of the display, the display may reproduce the fourth image **165** without errors by diversifying the resolution of the fourth image **165**.

(45) The AI data is used in the AI up-scaling **160** based on the second DNN. As described above, because the first DNN and the second DNN are jointly trained, the AI data includes information enabling the AI up-scaling **160** to be performed accurately on the third image **155** through the second DNN. During the AI decoding process, the AI up-scaling **160** may be performed on the third image **155** to have targeted resolution and/or quality, based on the AI data.

(46) The AI data may be transmitted together with the image data in a form of a bitstream. Alternatively, according to an embodiment of the disclosure, the AI data may be transmitted separately from the image data, in a form of a frame or a packet. The AI data and the image data obtained as a result of the AI encoding may be transmitted through the same network or through

different networks.

(47) FIG. 1B is a diagram for describing an AI encoding process and a second AI decoding process, according to an embodiment of the disclosure.

(48) FIG. 1B is a diagram for describing a case where an AI decoding apparatus that receives AI encoding data does not perform pre-processing. Referring to FIG. 1B, during the AI decoding process, a second image **145** is obtained by performing the first decoding **140** on image data, and a fourth image **165** is obtained by performing the AI up-scaling **160** on the second image **145**. The fourth image **165** or a fourth image post-processed as necessary may be reproduced by the display.

(49) The AI down-scaling **120** and the AI up-scaling **160** are performed based on AI, and AI for the AI down-scaling **120** needs to be trained jointly with AI for the AI up-scaling **160** on the second image **145**. This is because, when the AI for the AI down-scaling **120** and the AI for the AI up-scaling **160** are separately trained, a difference between the first original image **105**, which is an object of AI encoding, and the fourth image **165** reconstructed through AI decoding is increased.

(50) Because the resolution of the second image **145** may not be changed to an arbitrary resolution during the AI decoding process of FIG. 1B, the resolution of the first image **125** may be determined based on at least one of a network state, the performance of the display reproducing the fourth image **165**, or a scaling factor of the AI up-scaling **160** during the AI encoding process.

(51) FIG. 10 is a diagram for describing an AI encoding process and a general decoding process, according to an embodiment of the disclosure.

(52) FIG. 10 is a diagram for describing a case where a general decoding apparatus that receives AI encoding data does not perform an AI decoding process. Referring to FIG. 10, the general decoding apparatus performs only the first decoding **140**.

(53) AI encoding data including image data and AI data generated via the AI encoding process is transmitted toward the general decoding apparatus. Because the general decoding apparatus may not process the AI data, the general decoding apparatus outputs the second image **145** by performing the first decoding **140** on only the image data. The second image **145** or a second image post-processed as necessary may be reproduced by the display.

(54) Because the resolution of the second image **145** is not changed during the general decoding process of FIG. 10, the resolution of the first image **125** may be determined based on a network state and/or the performance of the display reproducing the fourth image **165** during the AI encoding process.

(55) FIG. 2 is a block diagram of a configuration of an AI decoding apparatus **200** according to an embodiment of the disclosure.

(56) Referring to FIG. 2, the AI decoding apparatus **200** may include a receiver **210** and an AI decoder **230**. The receiver **210** may include a communication interface **212**, a parser **214**, and an output interface **216**. The AI decoder **230** may include a first decoder **232**, a pre-processor **234**, and an AI up-scaler **236**.

(57) The receiver **210** receives and parses AI encoding data obtained as a result of AI encoding, and distinguishably outputs image data and AI data to the AI decoder **230**.

(58) In detail, the communication interface **212** receives the AI encoding data obtained as the result of AI encoding through a network. The AI encoding data includes the image data and the AI data. The image data and the AI data may be received through a same type of network or different types of networks.

(59) The parser **214** receives the AI encoding data received through the communication interface **212** and parses the AI encoding data to distinguish the image data and the AI data. For example, the parser **214** may distinguish the image data and the AI data by reading a header of data obtained from the communication interface **212**. According to an embodiment of the disclosure, the parser **214** distinguishably transmits the image data and the AI data to the output interface **216** via the header of the data received through the communication interface **212**, and the output interface **216** transmits the image data and the AI data respectively to the first decoder **232** and the AI up-scaler

236. At this time, the parser **214** may verify that the image data included in the AI encoding data is image data generated via a certain codec (for example, MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, or AV1). In this case, the parser **214** may transmit corresponding information to the first decoder **232** through the output interface **216** such that the image data is processed via the verified codec.

(60) According to an embodiment of the disclosure, the AI encoding data parsed by the parser **214** may be obtained from a data storage medium including a magnetic medium (such as a hard disk, a floppy disk, or a magnetic tape), an optical recording medium (such as CD-ROM or DVD), or a magneto-optical medium (such as a floptical disk).

(61) The first decoder **232** reconstructs the second image **145** corresponding to the first image **125**, based on the image data. The second image **145** obtained by the first decoder **232** is provided to the pre-processor **234**. According to an embodiment of the disclosure, first decoding related information, such as prediction mode information, motion information, quantization parameter (QP) information, or the like included in the image data may be provided to the AI up-scaler **236**.

(62) The pre-processor **234** performs pre-processing of changing the resolution of the second image **145** based on an output resolution. The pre-processor **234** changes the resolution of the second image **145** via legacy scaling. Here, the legacy scaling is scaling not using a neural network, and may include, for example, at least one of bilinear scaling, bicubic scaling, lanczos scaling, or stair step scaling.

(63) AI-based scaling changes the resolution of an image with a parameter optimized based on training, whereas the legacy scaling changes the resolution of an image according to a pre-determined rule. The legacy scaling is different from the AI-based scaling in that a formula or weight used in the legacy scaling is not updated according to training based on training data.

(64) The pre-processor **234** determines the output resolution. The output resolution indicates the resolution of the fourth image **165** obtained by the AI up-scaler **236**.

(65) The pre-processor **234** may determine the output resolution according to an input from a user. Alternatively, the pre-processor **234** may determine the output resolution according to the performance of the display that reproduces the fourth image **165** or the post-processed fourth image. The performance of the display may indicate a minimum resolution or maximum resolution expressible by the display. In other words, the pre-processor **234** may determine, as the output resolution, resolution equal to or greater than the maximum resolution or resolution selected among the minimum resolution to the maximum resolution so that the fourth image **165** may be smoothly reproduced by the display.

(66) When the output resolution is determined, the pre-processor **234** obtains a target resolution of the third image **155**, based on the output resolution. Because the resolution of the fourth image **165** obtained via AI up-scaling needs to be equal to the output resolution, the pre-processor **234** may calculate the target resolution of the third image **155** based on a scaling factor of the AI up-scaler **236** and the output resolution. In detail, when the output resolution is $a \times b$ and the scaling factor is s (where s is a rational number equal to or greater than 1), the pre-processor **234** may calculate the target resolution of the third image **155** as $(a/s) \times (b/s)$. The pre-processor **234** may receive information about the scaling factor of the AI up-scaler **236** from the AI up-scaler **236** or may previously store information about the scaling factor of the AI up-scaler **236**.

(67) The pre-processor **234** may change the resolution of the second image **145** according to a ratio between the resolution of the second image **145** and the target resolution such that the third image **155** may have the target resolution.

(68) As described above, the pre-processor **234** changes the resolution of the second image **145** via legacy scaling that may change the resolution of an image at an arbitrary factor in contrast with the AI-based scaling. In detail, because a DNN used in the AI-based scaling scales an image according to a pre-trained parameter, the DNN may not scale an image at various factors. However, the legacy scaling may reduce (e.g., sampling) or increase (e.g., interpolation) the number of pixels within an

image according to a pre-determined rule, thereby generating an image of desired resolution.

(69) The third image **155** is provided from the pre-processor **234** to the AI up-scaler **236**. Upon receiving the AI data, the AI up-scaler **236** performs AI up-scaling on the third image **155**, based on the AI data. According to an embodiment of the disclosure, the AI up-scaler **236** may perform the AI up-scaling on the third image **155** by further using the first decoding related information, such as the prediction mode information, the quantization parameter information, or the like included in the image data.

(70) The receiver **210** and the AI decoder **230** according to an embodiment of the disclosure are described as individual devices, but may be implemented through one processor. In this case, the receiver **210** and the AI decoder **230** may be implemented through a dedicated processor or through a combination of software and a general-purpose processor such as an application processor (AP), a central processing unit (CPU), or a graphic processing unit (GPU). The dedicated processor may be implemented by including a memory for implementing an embodiment of the disclosure or by including a memory processor for using an external memory.

(71) Also, the receiver **210** and the AI decoder **230** may be configured by a plurality of processors. In this case, the receiver **210** and the AI decoder **230** may be implemented through a combination of dedicated processors or through a combination of software and a plurality of general-purpose processors such as an AP, a CPU, or a GPU. Similarly, the pre-processor **234**, the AI up-scaler **236**, and the first decoder **232** may be implemented as different processors.

(72) The AI data provided to the AI up-scaler **236** includes pieces of information enabling the second image **155** to undergo AI up-scaling according to an up-scaling target. Here, the up-scaling target should correspond to a down-scaling target of a first DNN. Accordingly, the AI data should include information for verifying the down-scaling target of the first DNN.

(73) Examples of the information included in the AI data include difference information between resolution of the second original image **115** and resolution of the first image **125**, and/or information related to the first image **125**.

(74) The difference information may be expressed as information about a resolution conversion degree of the first image **125** compared to the second original image **115** (for example, resolution conversion rate information). Also, because the resolution of the first image **125** is ascertained through the resolution of the reconstructed second image **145** and the resolution conversion degree is verified accordingly, the difference information may be expressed only as resolution information of the second original image **115**. Here, the resolution information may be expressed as vertical/horizontal sizes or as a ratio (16:9, 4:3, or the like) and a size of one axis. Also, when there is pre-set resolution information, the resolution information may be expressed in a form of an index or flag.

(75) The information related to the first image **125** may include information about at least one of a bitrate of the image data obtained as the result of performing first encoding on the first image **125** or a codec type used during the first encoding of the first image **125**.

(76) The AI up-scaler **236** may determine the up-scaling target of the third image **155**, based on at least one of the difference information or the information related to the first image **125**, which are included in the AI data. The up-scaling target may indicate, for example, to what degree resolution is to be up-scaled for the third image **155**, namely, a scaling factor. When the up-scaling target is determined, the AI up-scaler **236** performs AI up-scaling on the third image **155** through a second DNN to obtain the fourth image **165** corresponding to the up-scaling target.

(77) FIG. 2 illustrates that the AI decoder **230** includes the pre-processor **234**, in order to perform the first AI decoding process of FIG. 1A. To perform the second AI decoding process of FIG. 1B, the AI decoding apparatus **200** does not include the pre-processor **234**. Accordingly, the second image **145** obtained by the first decoder **232** may be provided to the AI up-scaler **236**, and the AI up-scaler **236** may perform AI up-scaling on the second image **145** through a second DNN to obtain the fourth image **165** corresponding to the up-scaling target.

(78) Processes related with the third image **155**, which will be described below, for example, AI up-scaling and DNN setting information selection, are also applicable to the second image **145**.

(79) Before describing a method, performed by the AI up-scaler **236**, of performing AI up-scaling on the third image **155** according to the up-scaling target, an AI up-scaling process through the second DNN will be described with reference to FIGS. **3** and **4**.

(80) FIG. **3** is a diagram showing a second DNN **300** for performing AI up-scaling on the third image **155**, and FIG. **4** is a diagram for describing a convolution operation in a first convolution layer **310** of FIG. **3**.

(81) As shown in FIG. **3**, the second image **155** is input to the first convolution layer **310**. $3 \times 3 \times 4$ indicated in the first convolution layer **310** shown in FIG. **3** indicates that a convolution process is performed on one input image by using four filter kernels having a size of 3×3 . Four feature maps are generated by the four filter kernels as a result of the convolution process. Each feature map indicates inherent characteristics of the third image **155**. For example, each feature map may represent a vertical direction characteristic, a horizontal direction characteristic, or an edge characteristic of the third image **155**.

(82) A convolution operation in the first convolution layer **310** will be described in detail with reference to FIG. **4**.

(83) One feature map **450** may be generated through multiplication and addition between parameters of a filter kernel **430** having a size of 3×3 used in the first convolution layer **310** and corresponding pixel values in the third image **155**. Because four filter kernels are used in the first convolution layer **310**, four feature maps may be generated through the convolution operation using the four filter kernels.

(84) I1 through I49 indicated in the third image **155** in FIG. **4** indicate pixels in the third image **155**, and F1 through F9 indicated in the filter kernel **430** indicate parameters of the filter kernel **430**. Also, M1 through M9 indicated in the feature map **450** indicate samples of the feature map **450**.

(85) In FIG. **4**, the third image **155** includes 49 pixels, but the number of pixels is only an example. When the third image **155** has a resolution of 4 K, the third image **155** may include, for example, 3840×2160 pixels.

(86) During a convolution operation process, pixel values of I1, I2, I3, I8, I9, I10, I15, I16, and I17 of the third image **155** and F1 through F9 of the filter kernels **430** are respectively multiplied, and a value of combination (for example, addition) of result values of the multiplications may be assigned as a value of M1 of the feature map **450**. When a stride of the convolution operation is 2, pixel values of I3, I4, I5, I10, I11, I12, I17, I18, and I19 of the third image **155** and F1 through F9 of the filter kernels **430** are respectively multiplied, and the value of the combination of the result values of the multiplications may be assigned as a value of M2 of the feature map **450**.

(87) While the filter kernel **430** is moving along the stride to the last pixel of the third image **155**, the convolution operation is performed between the pixel values in the third image **155** and the parameters of the filter kernel **430**, and thus the feature map **450** having a certain size may be generated.

(88) According to the present disclosure, values of parameters of a second DNN, for example, values of parameters of a filter kernel used in convolution layers of the second DNN (for example, F1 through F9 of the filter kernel **430**), may be optimized through joint training of a first DNN and the second DNN. As described above, the AI up-scaler **236** may determine an up-scaling target corresponding to a down-scaling target of the first DNN, based on AI data, and determine parameters corresponding to the determined up-scaling target as the parameters of the filter kernel used in the convolution layers of the second DNN.

(89) Convolution layers included in the first DNN and the second DNN may perform processes according to the convolution operation process described with reference to FIG. **4**, but the convolution operation process described with reference to FIG. **4** is only an example and is not

limited thereto.

(90) Referring back to FIG. 3, the feature maps output from the first convolution layer **310** may be input to a first activation layer **320**.

(91) The first activation layer **320** may assign a non-linear feature to each feature map. The first activation layer **320** may include a sigmoid function, a Tanh function, a rectified linear unit (ReLU) function, or the like, but is not limited thereto.

(92) The first activation layer **320** assigning the non-linear feature indicates that some sample values of the feature map, which is an output of the first convolution layer **310**, is changed. Here, the change is performed by applying the non-linear feature.

(93) The first activation layer **320** determines whether to transmit sample values of the feature maps output from the first convolution layer **310** to a second convolution layer **330**. For example, some of the sample values of the feature maps are activated by the first activation layer **320** and transmitted to the second convolution layer **330**, and some of the sample values are deactivated by the first activation layer **320** and not transmitted to the second convolution layer **330**. The intrinsic characteristics of the third image **155** represented by the feature maps are emphasized by the first activation layer **320**.

(94) Feature maps **325** output from the first activation layer **320** are input to the second convolution layer **330**. One of the feature maps **325** shown in FIG. 3 is a result of processing the feature map **450** described with reference to FIG. 4 in the first activation layer **320**.

(95) $3 \times 3 \times 4$ indicated in the second convolution layer **330** indicates that a convolution process is performed on the feature maps **325** by using four filter kernels having a size of 3×3 . An output of the second convolution layer **330** is input to a second activation layer **340**. The second activation layer **340** may assign a non-linear feature to input data.

(96) Feature maps **345** output from the second activation layer **340** are input to a third convolution layer **350**. $3 \times 3 \times 1$ indicated in the third convolution layer **350** shown in FIG. 3 indicates that a convolution process is performed to generate one output image by using one filter kernel having a size of 3×3 . The third convolution layer **350** is a layer for outputting a final image, and generates one output by using one filter kernel. According to an embodiment of the disclosure, the third convolution layer **350** may output the fourth image **145** as a result of a convolution operation.

(97) There may be a plurality of DNN setting information indicating the numbers of filter kernels of the first, second, and third convolution layers **310**, **330**, and **350** of the second DNN **300**, parameters of the filter kernels of the first, second, and third convolution layers **310**, **330**, and **350** of the second DNN **300**, and the like, as will be described later, and the plurality of DNN setting information should be connected to a plurality of DNN setting information of a first DNN. The connection between the plurality of DNN setting information of the second DNN and the plurality of DNN setting information of the first DNN may be realized via joint training of the first DNN and the second DNN.

(98) In FIG. 3, the second DNN **300** includes three convolution layers, namely, the first, second, and third convolution layers **310**, **330**, and **350**, and two activation layers, namely, the first and second activation layers **320** and **340**, but this is only an example, and the numbers of convolution layers and activation layers may vary according to an embodiment of the disclosure. Also, according to an embodiment of the disclosure, the second DNN **300** may be implemented as a recurrent neural network (RNN). In this case, a convolutional neural network (CNN) structure of the second DNN **300** according to an embodiment of the disclosure is changed to an RNN structure.

(99) According to an embodiment of the disclosure, the AI up-scaler **236** may include at least one arithmetic logic unit (ALU) for the convolution operation and the operation of the activation layer described above. The ALU may be implemented as a processor. For the convolution operation, the ALU may include a multiplier that performs multiplication between sample values of the third image **155** or the feature map output from a previous layer and sample values of the filter kernel,

and an adder that adds result values of the multiplication. Also, for the operation of the activation layer, the ALU may include a multiplier that multiplies an input sample value by a weight used in a pre-determined sigmoid function, a Tanh function, or an ReLU function, and a comparator that compares a multiplication result and a certain value to determine whether to transmit the input sample value to a next layer.

(100) A method, performed by the AI up-scaler **236**, of performing the AI up-scaling on the third image **155** according to the up-scaling target will now be described.

(101) According to an embodiment of the disclosure, the AI up-scaler **236** may store a plurality of DNN setting information settable in a second DNN.

(102) Here, the DNN setting information may include information about at least one of the number of convolution layers included in the second DNN, the number of filter kernels for each convolution layer, or a parameter of each filter kernel. The plurality of DNN setting information may respectively correspond to various up-scaling targets, and the second DNN may operate based on DNN setting information corresponding to a certain up-scaling target.

(103) The second DNN may have different structures based on the DNN setting information. For example, the second DNN may include three convolution layers according to any piece of DNN setting information, or may include four convolution layers according to another piece of DNN setting information.

(104) According to an embodiment of the disclosure, the DNN setting information may only include a parameter of a filter kernel used in the second DNN. In this case, the structure of the second DNN does not change, but only the parameter of the internal filter kernel may change based on the DNN setting information.

(105) The AI up-scaler **236** may obtain the DNN setting information for performing AI up-scaling on the third image **155**, among the plurality of DNN setting information. Each of the plurality of DNN setting information used at this time is information for obtaining the fourth image **165** of a pre-determined resolution and/or pre-determined quality, and is trained jointly with a first DNN.

(106) For example, one piece of DNN setting information among the plurality of DNN setting information may include pieces of information for obtaining the fourth image **165** of resolution twice higher than resolution of the third image **155**, for example, the fourth image **165** of 4 K (4096×2160) twice higher than 2 K (2048×1080) of the third image **155**, and another piece of DNN setting information may include pieces of information for obtaining the fourth image **165** of resolution four times higher than the resolution of the third image **155**, for example, the third image **165** of 8 K (8192×4320) four times higher than 2 K (2048×1080) of the third image **155**.

(107) Each of the plurality of DNN setting information is obtained jointly with DNN setting information of the first DNN of an AI encoding apparatus **700** of FIG. 7. The AI up-scaler **236** obtains one piece of DNN setting information among the plurality of DNN setting information according to an enlargement factor corresponding to a reduction factor of the DNN setting information of the first DNN. To this end, the AI up-scaler **236** needs to verify information of the first DNN. In order for the AI up-scaler **236** to verify the information of the first DNN, the AI decoding apparatus **200** according to an embodiment of the disclosure receives AI data including the information of the first DNN from the AI encoding apparatus **700**.

(108) In other words, the AI up-scaler **236** may verify information targeted by DNN setting information of the first DNN used to obtain the first image **125** and obtain the DNN setting information of the second DNN trained jointly with the DNN setting information of the first DNN, by using pieces of information received from the AI encoding apparatus **700**.

(109) When DNN setting information for performing the AI up-scaling on the third image **155** is obtained from among the plurality of DNN setting information, input data may be processed based on the second DNN operating according to the obtained DNN setting information.

(110) For example, when any one piece of DNN setting information is obtained, the number of filter kernels included in each of the first, second, and third convolution layers **310**, **330**, and **350** of

the second DNN **300** of FIG. **3**, and the parameters of the filter kernels are set as values included in the obtained DNN setting information.

(111) In detail, parameters of a filter kernel of 3×3 used in any one convolution layer of the second DNN **300** of FIG. **3** are set with {1, 1, 1, 1, 1, 1, 1, 1, 1}, and, when DNN setting information is changed afterwards, the parameters may be replaced by {2, 2, 2, 2, 2, 2, 2, 2, 2} that are parameters included in the changed DNN setting information.

(112) The AI up-scaler **236** may obtain the DNN setting information for AI up-scaling on the third image **155** from among the plurality of DNN setting information, based on information included in the AI data, and the AI data used to obtain the DNN setting information will now be described.

(113) According to an embodiment of the disclosure, the AI up-scaler **236** may obtain the DNN setting information for AI up-scaling on the third image **155** from among the plurality of DNN setting information, based on difference information included in the AI data. For example, when it is verified that the resolution (for example, 4 K (4096×2160)) of the second original image **115** is twice higher than the resolution (for example, 2 K (2048×1080)) of the first image **125**, based on the difference information, the AI up-scaler **236** may obtain the DNN setting information for doubling the resolution of the third image **135**, namely, DNN setting information having a scaling factor of 2.

(114) According to another embodiment of the disclosure, the AI up-scaler **236** may obtain the DNN setting information for AI up-scaling on the third image **155** from among the plurality of DNN setting information, based on information related to the first image **125** included in the AI data. The AI up-scaler **236** may pre-determine a mapping relationship between pieces of image-related information and DNN setting information, and obtain the DNN setting information mapped to the information related to the first image **125**.

(115) FIG. **5** is a table showing a mapping relationship between several pieces of image-related information and several DNN setting information.

(116) Through an embodiment of the disclosure according to FIG. **5**, it will be determined that AI encoding and AI decoding processes according to an embodiment of the disclosure do not only consider a change of resolution. As shown in FIG. **5**, DNN setting information may be selected considering resolution, such as standard definition (SD), high definition (HD), or full HD, a bitrate, such as 10 Mbps, 15 Mbps, or 20 Mbps, and codec information, such as AV1, H.264, or HEVC, individually or collectively. For such consideration of the resolution, the bitrate and the codec information, training in consideration of each element needs to be jointly performed with encoding and decoding processes during an AI training process (see FIGS. **9**, **11**, and **12**).

(117) Accordingly, when a plurality of DNN setting information are provided based on image-related information including a codec type, resolution of an image, and the like, as shown in FIG. **5** according to training, the DNN setting information for AI up-scaling the third image **155** may be obtained based on the information related to the first image **125** received during the AI decoding process.

(118) In other words, the AI up-scaler **236** is capable of using DNN setting information according to image-related information by matching the image-related information at the left of a table of FIG. **5** with the DNN setting information at the right of the table.

(119) As shown in FIG. **5**, when it is verified, from the information related to the first image **125**, that the resolution of the first image **125** is SD, a bitrate of image data obtained as a result of performing first encoding on the first image **125** is 10 Mbps, and the first encoding is performed on the first image **125** via AV1 codec, the AI up-scaler **236** may use A DNN setting information among the plurality of DNN setting information.

(120) Also, when it is verified, from the information related to the first image **125**, that the resolution of the first image **125** is HD, the bitrate of the image data obtained as the result of performing the first encoding is 15 Mbps, and the first encoding is performed on the first image **125** via H.264 codec, the AI up-scaler **236** may use B DNN setting information among the plurality

of DNN setting information.

(121) Also, when it is verified, from the information related to the first image **125**, that the resolution of the first image **125** is full HD, the bitrate of the image data obtained as the result of performing the first encoding on the first image **125** is 20 Mbps, and the first encoding is performed on the first image **125** via HEVC codec, the AI up-scaler **236** may use C DNN setting information among the plurality of DNN setting information. When it is verified, from the information related to the first image **125**, that the resolution of the first image **125** is full HD, the bitrate of the image data obtained as the result of performing the first encoding on the first image **125** is 15 Mbps, and the first encoding is performed on the first image **125** via HEVC codec, the AI up-scaler **236** may use D DNN setting information among the plurality of DNN setting information. One of the C DNN setting information and the D DNN setting information is selected based on whether the bitrate of the image data obtained as the result of performing the first encoding on the first image **125** is 20 Mbps or 15 Mbps. The different bitrates of the image data, obtained when the first encoding is performed on the first image **125** of the same resolution via the same codec, indicates different qualities of reconstructed images. Accordingly, a first DNN and a second DNN may be jointly trained based on a certain image quality, and accordingly, the AI up-scaler **236** may obtain DNN setting information according to a bitrate of image data indicating the quality of the second image **145**.

(122) According to another embodiment of the disclosure, the AI up-scaler **236** may obtain the DNN setting information for performing AI up-scaling on the third image **155** from among the plurality of DNN setting information considering both information (prediction mode information, motion information, quantization parameter information, and the like) provided from the first decoder **232** and the information related to the first image **125** included in the AI data. For example, the AI up-scaler **236** may receive quantization parameter information used during a first encoding process of the first image **125** from the first decoder **232**, verify a bitrate of image data obtained as an encoding result of the first image **125** from AI data, and obtain DNN setting information corresponding to the quantization parameter information and the bitrate. Even when the bitrates are the same, the quality of reconstructed images may vary according to the complexity of an image. A bitrate is a value representing the entire first image **125** on which first encoding is performed, and the quality of each frame may vary even within the first image **125**. Accordingly, DNN setting information more suitable for the third image **155** may be obtained when prediction mode information, motion information, and/or a quantization parameter obtainable for each frame from the first decoder **232** are/is considered together, compared to when only the AI data is used.

(123) Also, according to an embodiment of the disclosure, the AI data may include an identifier of mutually agreed DNN setting information. An identifier of DNN setting information is information for distinguishing a pair of DNN setting information jointly trained between the first DNN and the second DNN, such that AI up-scaling is performed on the third image **155** to the up-scaling target corresponding to the down-scaling target of the first DNN. The AI up-scaler **236** may perform AI up-scaling on the third image **155** by using the DNN setting information corresponding to the identifier of the DNN setting information, after obtaining the identifier of the DNN setting information included in the AI data. For example, an identifier indicating each of the plurality of DNN setting information settable in the first DNN and an identifier indicating each of the plurality of DNN setting information settable in the second DNN may be previously designated. In this case, the same identifier may be designated for a pair of DNN setting information settable in each of the first DNN and the second DNN. The AI data may include an identifier of DNN setting information set in the first DNN for AI down-scaling of the second original image **115**. In response to the AI data, the AI up-scaler **236** may perform AI up-scaling on the third image **155** by using the DNN setting information indicated by the identifier included in the AI data among the plurality of DNN setting information.

(124) Also, according to an embodiment of the disclosure, the AI data may include the DNN setting

information. The AI up-scaler **236** may perform AI up-scaling on the third image **155** by using the DNN setting information included in the AI data, after obtaining the DNN setting information.

(125) According to an embodiment of the disclosure, when pieces of information (for example, the number of convolution layers, the number of filter kernels for each convolution layer, a parameter of each filter kernel, and the like) constituting the DNN setting information are stored in a form of a lookup table, the AI up-scaler **236** may obtain the DNN setting information by combining some values selected from the values in the lookup table, based on information included in the AI data, and perform AI up-scaling on the third image **155** by using the obtained DNN setting information.

(126) According to an embodiment of the disclosure, when a structure of a DNN corresponding to the up-scaling target is determined, the AI up-scaler **236** may obtain the DNN setting information, for example, parameters of a filter kernel, corresponding to the determined structure of the DNN.

(127) The AI up-scaler **236** obtains the DNN setting information of the second DNN through the AI data including information related to the first DNN, and performs AI up-scaling on the third image **155** through the second DNN set with the obtained DNN setting information. In this case, memory usage and throughput may be reduced compared to when features of the third image **155** are directly analyzed for up-scaling.

(128) According to an embodiment of the disclosure, when the third image **155** includes a plurality of frames, the AI up-scaler **236** may independently obtain DNN setting information in units of a certain number of frames, or may obtain common DNN setting information for all of the plurality of frames.

(129) FIG. **6** is a diagram showing the third image **155** including a plurality of frames.

(130) As shown in FIG. **6**, the third image **155** may include frames t_0 through t_n .

(131) According to an embodiment of the disclosure, the AI up-scaler **236** may obtain DNN setting information of a second DNN through AI data, and perform AI up-scaling on the frames t_0 through t_n based on the obtained DNN setting information. In other words, the frames t_0 through t_n may be processed via AI up-scaling based on common DNN setting information.

(132) According to another embodiment of the disclosure, the AI up-scaler **236** may perform AI up-scaling on some of the frames t_0 through t_n , for example, the frames t_0 through t_a , by using 'A' DNN setting information obtained from AI data, and perform AI up-scaling on the frames t_{a+1} through t_b by using 'B' DNN setting information obtained from the AI data. Also, the AI up-scaler **236** may perform AI up-scaling on the frames t_{b+1} through t_n by using 'C' DNN setting information obtained from the AI data. In other words, the AI up-scaler **236** may independently obtain DNN setting information for each group including a certain number of frames among the plurality of frames, and perform AI up-scaling on the frames included in each group by using the independently obtained DNN setting information.

(133) According to another embodiment of the disclosure, the AI up-scaler **236** may independently obtain DNN setting information for each frame forming the third image **155**. In other words, when the third image **155** includes three frames, the AI up-scaler **236** may perform AI up-scaling on a first frame by using DNN setting information obtained in relation to the first frame, perform AI up-scaling on a second frame by using DNN setting information obtained in relation to the second frame, and perform AI up-scaling on a third frame by using DNN setting information obtained in relation to the third frame. DNN setting information may be independently obtained for each frame included in the third image **155**, according to a method of obtaining DNN setting information based on information (prediction mode information, motion information, quantization parameter information, or the like) provided from the first decoder **232** and information related to the first image **125** included in the AI data. This is because the mode information, the quantization parameter information, or the like may be determined independently for each frame included in the third image **155**.

(134) According to another embodiment of the disclosure, the AI data may include information indicating for up to which frame is DNN setting information valid, the DNN setting information

having been obtained based on the AI data. For example, when the AI data includes information indicating that DNN setting information is valid for up to the frame t_a , the AI up-scaler **236** performs AI up-scaling on the frames t_0 through t_a by using DNN setting information obtained based on the AI data. Also, when another piece of AI data includes information indicating that DNN setting information is valid for up to the frame t_n , the AI up-scaler **236** performs AI up-scaling on the frames t_{a+1} through t_n by using DNN setting information obtained based on the other piece of AI data.

(135) The AI encoding apparatus **700** for performing AI encoding on the first original image **105** will now be described with reference to FIG. **7**.

(136) FIG. **7** is a block diagram of a configuration of the AI encoding apparatus **700** according to an embodiment of the disclosure.

(137) Referring to FIG. **7**, the AI encoding apparatus **700** may include an AI encoder **710** and a transmitter **730**. The AI encoder **710** may include a pre-processor **712**, an AI down-scaler **714**, and a first encoder **716**. The transmitter **730** may include a data processor **732** and a communication interface **734**.

(138) In FIG. **7**, the AI encoder **710** and the transmitter **730** are illustrated as separate devices, but the AI encoder **710** and the transmitter **730** may be implemented through one processor. In this case, the AI encoder **710** and the transmitter **730** may be implemented through a dedicated processor or through a combination of software and a general-purpose processor such as an AP, a CPU or a GPU. The dedicated processor may be implemented by including a memory for implementing an embodiment of the disclosure or by including a memory processor for using an external memory.

(139) Also, the AI encoder **710** and the transmitter **730** may be configured by a plurality of processors. In this case, the AI encoder **710** and the transmitter **730** may be implemented through a combination of dedicated processors or through a combination of software and a plurality of general-purpose processors such as an AP, a CPU, or a GPU. The pre-processor **712**, the AI down-scaler **714**, and the first encoder **714** may be implemented through different processors.

(140) The pre-processor **712** performs pre-processing of changing the resolution of the first original image **105** according to an output resolution. The pre-processor **712** may change the resolution of the first original image **105** via legacy scaling. Here, the legacy scaling is scaling not using a neural network, and may include, for example, at least one of bilinear scaling, bicubic scaling, lanczos scaling, or stair step scaling. The legacy scaling may be also referred to as a non-AI scaling.

(141) The pre-processor **712** determines the output resolution. The output resolution indicates or corresponds to the resolution of the first image **125** obtained by the AI down-scaler **714**. The output resolution may refer to a resolution setting value that is applied to the AI down-scaler **714**.

(142) According to an embodiment of the disclosure, the pre-processor **712** may determine the output resolution according to an input from a user. In this embodiment, the input from the user may include a resolution setting value that is set by the user.

(143) According to another embodiment of the disclosure, the pre-processor **712** may determine the output resolution according to the state of a network connected to the communication interface **734**. In detail, the pre-processor **712** may determine the output resolution based on at least one of the bandwidth of the network or the congestion thereof. For example, when it is anticipated from the state of the network that a large capacity of data may be transmitted (e.g., when the available bandwidth is greater than a preset bandwidth), the pre-processor **712** may determine a relatively large output resolution. On the other hand, when it is anticipated from the state of the network that only a small capacity of data may be transmitted (e.g., when the available bandwidth is less than or equal to the preset bandwidth), the pre-processor **712** may determine a relatively small output resolution.

(144) According to another embodiment of the disclosure, the pre-processor **712** may determine the output resolution, based on the performance of a display that reproduces an image. The

performance of the display may include, for example, resolution expressible by the display, whether a decoding apparatus included in the display is able to perform AI up-scaling, a scaling factor of AI up-scaling when the AI up-scaling is possible, and whether the decoding apparatus is able to performing pre-processing.

(145) The pre-processor **712** may receive performance information of the display from the display requesting the first original image **105** through the communication interface **734**.

(146) As described above, a decoding apparatus that receives the AI encoding data may perform the first AI decoding process of FIG. **1A**, the second AI decoding process of FIG. **1B**, or the general decoding process of FIG. **10**. A method, performed by the pre-processor **712**, of determining the output resolution for these decoding apparatuses will now be described in detail.

(147) First, when a decoding apparatus that receives the AI encoding data is able to perform the first AI decoding process of FIG. **1A**, the resolution of the second image **145** may be changed to an arbitrary resolution via pre-processing, and thus the pre-processor **712** may determine the output resolution by considering a network state. Because a decoding apparatus that receives the AI encoding data may arbitrarily change the resolution of the second image **145** according to the performance of a display connected to the decoding apparatus, the pre-processor **712** determines the output resolution by considering only a network state.

(148) Next, when a decoding apparatus that receives the AI encoding data is able to perform the second AI decoding process of FIG. **1B**, the resolution of the second image **145** may be changed according to a pre-determined scaling factor via AI up-scaling, and thus the pre-processor **712** may determine the output resolution by considering a network state, resolution reproducible by the display, and a scaling factor of the AI up-scaling. Because the resolution of the second image **145** is equal to that of the first image **125** and AI up-scaling is performed on the second image **145** according to the pre-determined scaling factor, the pre-processor **712** may set, as a maximum value of the output resolution, a value obtained by dividing maximum resolution reproducible by the display by the scaling factor of the AI up-scaling, and may determine a final output resolution in consideration of a network state within a range that is equal to or greater than the output resolution of the maximum value.

(149) Next, when a decoding apparatus that receives the AI encoding data is able to perform the general decoding process of FIG. **10**, the resolution of the second image **145** is not changed, and thus the pre-processor **712** may determine the output resolution by considering a network state and resolution reproducible by the display. Because the resolution of the second image **145** is equal to that of the first image **125**, the pre-processor **712** may set maximum resolution reproducible by the display as a maximum value of the output resolution, and may determine a final output resolution in consideration of a network state within a range that is equal to or greater than the maximum value of the output resolution.

(150) When the output resolution is determined, the pre-processor **712** obtains a target resolution of the second original image **115**, based on the output resolution. Because the resolution of the first image **125** obtained via AI up-scaling needs to be equal to the output resolution, the pre-processor **712** may calculate the target resolution of the second original image **115** in consideration of a scaling factor of the AI down-scaler **714** and the output resolution. In detail, when the output resolution is $a \times b$ and the scaling factor is s (where s is a rational number smaller than 1), the pre-processor **712** may calculate the target resolution of the second original image **115** as $(a/s) \times (b/s)$.

(151) The pre-processor **712** may change the resolution of the first original image **105** according to a ratio between the resolution of the first original image **105** and the target resolution such that the second original image **115** may have the target resolution.

(152) The AI encoder **710** performs AI down-scaling on the second original image **115** and first encoding on the first image **125**, and transmits AI data and image data to the transmitter **730**. The transmitter **730** transmits the AI data and the image data to the AI decoding apparatus **200**.

(153) The image data includes data obtained as a result of performing the first encoding on the first

image **125**. The image data may include data obtained based on pixel values in the first image **125**, for example, residual data that is a difference between the first image **125** and prediction data of the first image **125**. Also, the image data includes information used during a first encoding process of the first image **125**. For example, the image data may include prediction mode information, motion information, and quantization parameter information used to perform the first encoding on the first image **125**, for example.

(154) The AI data includes pieces of information enabling AI up-scaling to be performed on the third image **155** to an up-scaling target corresponding to a down-scaling target of a first DNN. According to an embodiment of the disclosure, the AI data may include difference information between the second original image **115** and the first image **125**. Also, the AI data may include information related to the first image **125**. The information related to the first image **125** may include information about at least one of resolution of the first image **125**, a bitrate of the image data obtained as the result of performing first encoding on the first image **125** or a codec type used during the first encoding of the first image **125**.

(155) According to an embodiment of the disclosure, the AI data may include an identifier of mutually agreed DNN setting information such that the AI up-scaling is performed on the second image **155** to the up-scaling target corresponding to the down-scaling target of the first DNN.

(156) Also, according to an embodiment of the disclosure, the AI data may include DNN setting information settable in a second DNN.

(157) The AI down-scaler **714** may obtain the first image **125** obtained by performing the AI down-scaling on the second original image **115** through the first DNN. The AI down-scaler **712** may determine the down-scaling target of the second original image **115**, based on a pre-determined standard.

(158) In order to obtain the first image **125** matching the down-scaling target, the AI down-scaler **714** may store a plurality of DNN setting information settable in the first DNN. The AI down-scaler **714** obtains DNN setting information corresponding to the down-scaling target from among the plurality of DNN setting information, and performs the AI down-scaling on the second original image **115** through the first DNN set with the obtained DNN setting information.

(159) Each of the plurality of DNN setting information may be trained to obtain the first image **125** of pre-determined resolution and/or pre-determined quality. For example, any one piece of DNN setting information among the plurality of DNN setting information may include pieces of information for obtaining the first image **125** of resolution that is half resolution of the second original image **115**, for example, the first image **125** of 2 K (2048×1080) that is half of 4 K (4096×2160) of the second original image **115**, and another piece of DNN setting information may include information for obtaining the first image **125** of resolution that is quarter resolution of the second original image **115**, for example, the first image **125** of 2 K (2048×1080) that is quarter of 8 K (8192×4320) of the second original image **115**.

(160) According to an embodiment of the disclosure, when pieces of information (for example, the number of convolution layers, the number of filter kernels for each convolution layer, a parameter of each filter kernel, and the like) constituting the DNN setting information are stored in a form of a lookup table, the AI down-scaler **714** may obtain the DNN setting information by combining some values selected from the values in the lookup table, based on the down-scaling target, and perform AI down-scaling on the first original image **115** by using the obtained DNN setting information.

(161) According to an embodiment of the disclosure, the AI down-scaler **714** may determine a structure of a DNN corresponding to the down-scaling target, and obtain DNN setting information corresponding to the determined structure of the DNN, for example, obtain parameters of a filter kernel.

(162) The plurality of DNN setting information for performing the AI down-scaling on the second original image **115** may have an optimized value as the first DNN and the second DNN are jointly

trained. Here, each piece of DNN setting information includes at least one of the number of convolution layers included in the first DNN, the number of filter kernels for each convolution layer, or a parameter of each filter kernel.

(163) The AI down-scaler **714** may set the first DNN with the DNN setting information selected to perform the AI down-scaling on the second original image **115** to obtain the first image **125** of certain resolution and/or certain quality through the first DNN. When the DNN setting information for performing the AI down-scaling on the second original image **115** is selected from the plurality of DNN setting information, each layer in the first DNN may process input data based on pieces of information included in the DNN setting information.

(164) A method, performed by the AI down-scaler **714**, of determining the down-scaling target will now be described. The down-scaling target may indicate, for example, by how much resolution is decreased from the second original image **115** to obtain the first image **125**.

(165) According to an embodiment of the disclosure, the AI down-scaler **714** may determine the down-scaling target based on at least one of a compression ratio (for example, a resolution difference between the second original image **115** and the first image **125**, a target bitrate, or the like), a compression quality (for example, a type of bitrate), compression history information, or a type of the second original image **115**.

(166) For example, the AI down-scaler **714** may determine the down-scaling target based on the compression ratio, the compression quality, or the like, which is pre-set or input from a user.

(167) As another example, the AI down-scaler **714** may determine the down-scaling target by using the compression history information stored in the AI encoding apparatus **700**. For example, according to the compression history information usable by the AI encoding apparatus **700**, an encoding quality, a compression ratio, or the like preferred by the user may be determined, and the down-scaling target may be determined according to the encoding quality determined based on the compression history information. For example, the resolution, quality, or the like of the first image **125** may be determined according to the encoding quality that has been used most often according to the compression history information.

(168) As another example, the AI down-scaler **714** may determine the down-scaling target based on the encoding quality that has been used more frequently than a certain threshold value (for example, an average quality of the encoding quality that has been used more frequently than the certain threshold value), according to the compression history information.

(169) As another example, the AI down-scaler **714** may determine the down-scaling target, based on the resolution, type (for example, a file format), or the like of the second original image **115**.

(170) According to an embodiment of the disclosure, when the second original image **115** includes a plurality of frames, the AI down-scaler **714** may independently determine a down-scaling target in units of a certain number of frames, or may determine a common down-scaling target for all of the plurality of frames.

(171) According to an embodiment of the disclosure, the AI down-scaler **714** may divide the frames included in the second original image **115** into a certain number of groups, and independently determine the down-scaling target for each group. The same or different down-scaling targets may be determined for each group. The numbers of frames included in the groups may be the same or different according to each group.

(172) According to another embodiment of the disclosure, the AI down-scaler **714** may independently determine a down-scaling target for each frame included in the second original image **115**. The same or different down-scaling targets may be determined for each frame.

(173) An example of a structure of a first DNN **800** on which AI down-scaling is based will now be described.

(174) FIG. **8** is a diagram showing the first DNN **800** for performing AI down-scaling on the second original image **115**.

(175) As shown in FIG. **8**, the second original image **115** is input to a first convolution layer **810**.

The first convolution layer **810** performs a convolution process on the second original image **115** by using 32 filter kernels having a size of 5×5 . 32 feature maps generated as a result of the convolution process are input to a first activation layer **820**. The first activation layer **820** may assign a non-linear feature to the **32** feature maps.

(176) The first activation layer **820** determines whether to transmit sample values of the feature maps output from the first convolution layer **810** to a second convolution layer **830**. For example, some of the sample values of the feature maps are activated by the first activation layer **820** and transmitted to the second convolution layer **830**, and some of the sample values are deactivated by the first activation layer **820** and not transmitted to the second convolution layer **830**. Information represented by the feature maps output from the first convolution layer **810** is emphasized by the first activation layer **820**.

(177) An output **825** of the first activation layer **820** is input to a second convolution layer **830**. The second convolution layer **830** performs a convolution process on input data by using 32 filter kernels having a size of 5×5 . 32 feature maps output as a result of the convolution process are input to a second activation layer **840**, and the second activation layer **840** may assign a non-linear feature to the **32** feature maps.

(178) An output **845** of the second activation layer **840** is input to a third convolution layer **850**. The third convolution layer **850** performs a convolution process on input data by using one filter kernel having a size of 5×5 . As a result of the convolution process, one image may be output from the third convolution layer **850**. The third convolution layer **850** is a layer for outputting a final image, and obtains one output by using one filter kernel. According to an embodiment of the disclosure, the third convolution layer **850** may output the first image **125** as a result of a convolution operation.

(179) There may be a plurality of DNN setting information indicating the numbers of filter kernels of the first, second, and third convolution layers **810**, **830**, and **850** of the first DNN **800**, parameters of the filter kernels of the first, second, and third convolution layers **810**, **830**, and **850** of the first DNN **800**, and the like, and the plurality of DNN setting information needs to be connected to a plurality of DNN setting information of a second DNN. The connection between the plurality of DNN setting information of the first DNN and the plurality of DNN setting information of the second DNN may be realized via joint training of the first DNN and the second DNN.

(180) In FIG. **8**, the first DNN **800** includes three convolution layers, namely, the first, second, and third convolution layers **810**, **830**, and **850**, and two activation layers, namely, the first and second activation layers **820** and **840**, but this is only an example, and the numbers of convolution layers and activation layers may vary according to an embodiment of the disclosure. Also, according to an embodiment of the disclosure, the first DNN **800** may be implemented as a recurrent neural network (RNN). In this case, a convolutional neural network (CNN) structure of the first DNN **800** according to an embodiment of the disclosure is changed to an RNN structure.

(181) According to an embodiment of the disclosure, the AI up-scaler **714** may include at least one ALU for the convolution operation and the operation of the activation layer. The ALU may be implemented as a processor. For the convolution operation, the ALU may include a multiplier that performs multiplication between sample values of the second original image **115** or the feature map output from a previous layer and sample values of the filter kernel, and an adder that adds result values of the multiplication. Also, for the operation of the activation layer, the ALU may include a multiplier that multiplies an input sample value by a weight used in a pre-determined sigmoid function, a Tanh function, or an ReLU function, and a comparator that compares a multiplication result and a certain value to determine whether to transmit the input sample value to a next layer.

(182) Referring back to FIG. **7**, upon receiving the first image **125** from the AI down-scaler **714**, the first encoder **716** may reduce an information amount of the first image **125** by performing first encoding on the first image **125**. The image data corresponding to the first image **125** may be obtained as a result of performing the first encoding by the first encoder **716**.

(183) The data processor **732** processes at least one of the AI data or the image data to be transmitted in a certain form. For example, when the AI data and the image data are to be transmitted in a form of a bitstream, the data processor **732** processes the AI data to be expressed in a form of a bitstream and transmits the image data and the AI data in a form of one bitstream through the communication interface **734**. As another example, the data processor **732** processes the AI data to be expressed in a form of bitstream, and transmits each of a bitstream corresponding to the AI data and a bitstream corresponding to the image data through the communication interface **734**. As another example, the data processor **732** processes the AI data to be expressed in a form of a frame or packet, and transmits the image data in a form of a bitstream and the AI data in a form of a frame or packet through the communication interface **734**.

(184) The communication interface **734** transmits the AI encoding data obtained as the result of AI encoding through a network. The AI encoding data obtained as the result of AI encoding includes the image data and the AI data. The image data and the AI data may be transmitted through a same type of network or different types of networks.

(185) According to an embodiment of the disclosure, the AI encoding data obtained as a result of processes of the data processor **732** may be stored in a data storage medium including a magnetic medium such as a hard disk, a floppy disk, or a magnetic tape, an optical recording medium such as CD-ROM or DVD, or a magneto-optical medium such as a floptical disk.

(186) A method of jointly training the first DNN **800** and the second DNN **300** will now be described with reference to FIG. **9**.

(187) FIG. **9** is a diagram for describing a method of training the first DNN **800** and the second DNN **300**.

(188) In an embodiment of the disclosure, the first original image **105** on which AI encoding is performed through an AI encoding process is reconstructed to the fourth image **165** via an AI decoding process, and, in order to maintain similarity between the fourth image **165** obtained as a result of AI decoding and the first original image **105**, connectivity between the AI encoding process and the AI decoding process is required. In other words, information lost in the AI encoding process needs to be reconstructed during the AI decoding process, and, to this end, the first DNN **800** and the second DNN **300** need to be jointly trained.

(189) For accurate AI decoding, ultimately, quality loss information **930** corresponding to a result of comparing a third training image **904** and an original training image **901** shown in FIG. **9** needs to be reduced. Accordingly, the quality loss information **930** is used to train both of the first DNN **800** and the second DNN **300**.

(190) First, a training process shown in FIG. **9** will be described.

(191) In FIG. **9**, the original training image **901** is an image on which AI down-scaling is to be performed, and a first training image **902** is an image obtained by performing AI down-scaling on the original training image **901**. Also, the third training image **904** is an image obtained by performing AI up-scaling on the first training image **902**.

(192) The original training image **901** includes a still image or a moving image including a plurality of frames. According to an embodiment of the disclosure, the original training image **901** may include a luminance image extracted from the still image or the moving image including the plurality of frames. According to an embodiment of the disclosure, the original training image **901** may include a patch image extracted from the still image or the moving image including the plurality of frames. When the original training image **901** includes the plurality of frames, the first training image **902**, a second training image (not shown), and the third training image **904** also each include a plurality of frames. When the plurality of frames of the original training image **901** are sequentially input to the first DNN **800**, the plurality of frames of the first training image **902**, the second training image, and the third training image **904** may be sequentially obtained through the first DNN **800** and the second DNN **300**.

(193) For joint training of the first DNN **800** and the second DNN **300**, the original training image

901 is input to the first DNN **800**. The original training image **901** input to the first DNN **800** is output as the first training image **902** via the AI down-scaling, and the first training image **902** is input to the second DNN **300**. The third training image **904** is output as a result of performing the AI up-scaling on the first training image **902**.

(194) Referring to FIG. 9, the first training image **902** is input to the second DNN **300**. According to an embodiment of the disclosure, a second training image obtained as first encoding and first decoding are performed on the first training image **902** may be input to the second DNN **300**. In order to input the second training image to the second DNN **300**, any one codec among MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used. In detail, any one codec among MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used to perform first encoding on the first training image **902** and first decoding on image data corresponding to the first training image **902**.

(195) Referring to FIG. 9, separate from the first training image **902** being output through the first DNN **800**, a reduced training image **903** is obtained by performing legacy down-scaling on the original training image **901**. Here, the legacy down-scaling may include at least one of bilinear scaling, bicubic scaling, lanczos scaling, or stair step scaling.

(196) In order to prevent a structural feature of the first image **125** from deviating greatly from a structural feature of the first original image **105** or the second original image **115**, the reduced training image **903** is obtained to preserve the structural feature of the original training image **901**.

(197) Before training is performed, the first DNN **800** and the second DNN **300** may be set with pre-determined DNN setting information. When the training is performed, structural loss information **910**, complexity loss information **920**, and the quality loss information **930** may be determined.

(198) The structural loss information **910** may be determined based on a result of comparing the reduced training image **903** and the first training image **902**. For example, the structural loss information **910** may correspond to a difference between structural information of the reduced training image **903** and structural information of the first training image **902**. Structural information may include various features extractable from an image, such as luminance, contrast, histogram, or the like of the image. The structural loss information **910** indicates how much structural information of the original training image **901** is maintained in the first training image **902**. When the structural loss information **910** is small, the structural information of the first training image **902** is similar to the structural information of the original training image **901**.

(199) The complexity loss information **920** may be determined based on spatial complexity of the first training image **902**. For example, a total variance value of the first training image **902** may be used as the spatial complexity. The complexity loss information **920** is related to a bitrate of image data obtained by performing first encoding on the first training image **902**. It is defined that the bitrate of the image data is low when the complexity loss information **920** is small.

(200) The quality loss information **930** may be determined based on a result of comparing the original training image **901** with the third training image **904**. The quality loss information **930** may include at least one of an L1-norm value, an L2-norm value, an Structural Similarity (SSIM) value, a Peak Signal-To-Noise Ratio-Human Vision System (PSNR-HVS) value, an Multiscale SSIM (MS-SSIM) value, a Variance Inflation Factor (VIF) value, or a Video Multimethod Assessment Fusion (VMAF) value regarding the difference between the original training image **901** and the third training image **904**. The quality loss information **930** indicates how much the third training image **904** is similar to the original training image **901**. The third training image **904** is more similar to the original training image **901** when the quality loss information **930** is small.

(201) Referring to FIG. 9, the structural loss information **910**, the complexity loss information **920**, and the quality loss information **930** are used to train the first DNN **800**, and the quality loss information **930** may be used to train the second DNN **300**. In other words, the quality loss information **930** is used to train both the first and second DNNs **800** and **300**.

(202) The first DNN **800** may update a parameter such that final loss information determined based on the structural loss information **910**, the complexity loss information **920**, and the quality loss information **930** is reduced or minimized. Also, the second DNN **300** may update a parameter such that the quality loss information **930** is reduced or minimized.

(203) The final loss information for training the first DNN **800** and the second DNN **300** may be determined as Equation 1 below.

$$\begin{aligned} \text{LossDS} &= a \times \text{structural loss information} + b \times \text{complexity loss information} + c \times \text{quality loss information} \\ \text{LossUS} &= d \times \text{quality loss information} \end{aligned} \quad [\text{Equation 1}]$$

(204) In Equation 1, LossDS indicates final loss information to be reduced or minimized to train the first DNN **800**, and LossUS indicates final loss information to be reduced or minimized to train the second DNN **300**. Also, a, b, c and d may correspond to pre-determined certain weights.

(205) In other words, the first DNN **800** updates parameters in a direction where LossDS of Equation 1 is reduced, and the second DNN **300** updates parameters in a direction where LossUS is reduced. When the parameters of the first DNN **800** are updated according to LossDS derived during the training, the first training image **902** obtained based on the updated parameters becomes different from a previous first training image **902** obtained during previous training, and accordingly, the third training image **904** also becomes different from a previous third training image **904** obtained during the previous training. When the third training image **904** becomes different from the previous third training image **904**, the quality loss information **930** is also newly determined, and the second DNN **300** updates the parameters accordingly. When the quality loss information **930** is newly determined, LossDS is also newly determined, and the first DNN **800** updates the parameters according to the newly determined LossDS. In other words, updating of the parameters of the first DNN **800** leads to updating of the parameters of the second DNN **300**, and the updating of the parameters of the second DNN **300** leads to updating of the parameters of the first DNN **800**. In other words, because the first DNN **800** and the second DNN **300** are jointly trained by sharing the quality loss information **930**, the parameters of the first DNN **800** and the parameters of the second DNN **300** may be jointly optimized.

(206) Referring to Equation 1, it is verified that LossUS is determined according to the quality loss information **930**, but this is only an example. LossUS may be determined based on at least one of the structural loss information **910** or the complexity loss information **920**, and the quality loss information **930**. It is also verified that LossDS is determined according to the structural loss information **910**, the complexity loss information **920**, and the quality loss information **930**, but this is only an example. LossDS may be determined based on a combination of some of the structural loss information **910**, the complexity loss information **920**, and the quality loss information **930**. For example, LossDS may be determined based on a combination of the structural loss information **910** and the quality loss information **930**.

(207) It has been described above that the AI up-scaler **236** of the AI decoding apparatus **200** and the AI down-scaler **714** of the AI encoding apparatus **700** store the plurality of DNN setting information, and methods of training each of the plurality of DNN setting information stored in the AI up-scaler **236** and the AI down-scaler **714** will now be described.

(208) As described with reference to Equation 1, the first DNN **800** updates the parameters considering the similarity (the structural loss information **910**) between the structural information of the first training image **902** and the structural information of the original training image **901**, the bitrate (the complexity loss information **920**) of the image data obtained as a result of performing first encoding on the first training image **902**, and the difference (the quality loss information **930**) between the third training image **904** and the original training image **901**.

(209) In detail, the parameters of the first DNN **800** may be updated such that the first training image **902** having similar structural information as the original training image **901** is obtained and the image data having a small bitrate is obtained when first encoding is performed on the first training image **902**, and at the same time, the second DNN **300** performing AI up-scaling on the

first training image **902** may obtain the third training image **904** similar to the original training image **901**.

(210) A direction in which the parameters of the first DNN **800** are optimized varies by adjusting the weights a, b, and c of Equation 1. For example, when the weight b is determined to be high, the parameters of the first DNN **800** may be updated by prioritizing a low bitrate over the high quality of the third training image **904**. Also, when the weight c is determined to be high, the parameters of the first DNN **800** may be updated by prioritizing high quality of the third training image **904** over a high bitrate or maintenance of the structural information of the original training image **901**.

(211) Also, the direction in which the parameters of the first DNN **800** are optimized may vary according to a type of codec used to perform first encoding on the first training image **902**. This is because the second training image to be input to the second DNN **300** may vary according to the type of codec.

(212) In other words, the parameters of the first DNN **800** and the parameters of the second DNN **300** may be jointly updated based on the weights a, b, and c, and the type of codec for performing first encoding on the first training image **902**. Accordingly, when the first DNN **800** and the second DNN **300** are trained after determining the weights a, b, and c each to be a certain value and determining the type of codec to be a certain type, the parameters of the first DNN **700** and the parameters of the second DNN **300** connected and optimized to each other may be determined. Also, when the first DNN **700** and the second DNN **300** are trained after changing the weights a, b, and c, and the type of codec, the parameters of the first DNN **700** and the parameters of the second DNN **300** connected and optimized to each other may be determined. In other words, the plurality of DNN setting information jointly trained with each other may be determined in the first DNN **800** and the second DNN **300** when the first DNN **800** and the second DNN **300** are trained while changing values of the weights a, b, and c, and the value of each type of codec.

(213) As described above with reference to FIG. 5, the plurality of DNN setting information of the first DNN **800** and the second DNN **300** may be mapped to the pieces of information related to the first image. To set such a mapping relationship, first encoding may be performed on the first training image **902** output from the first DNN **800** via a certain codec according to a certain bitrate and the second training image obtained by performing first decoding on a bitstream obtained as a result of performing the first encoding may be input to the second DNN **300**. In other words, by training the first DNN **800** and the second DNN **300** after setting an environment such that the first encoding is performed on the first training image **902** of a certain resolution via the certain codec according to the certain bitrate, a DNN setting information pair mapped to the resolution of the first training image **902**, a type of the codec used to perform the first encoding on the first training image **902**, and the bitrate of the bitstream obtained as a result of performing the first encoding on the first training image **902** may be determined. By variously changing the resolution of the first training image **902**, the type of codec used to perform the first encoding on the first training image **902**, and the bitrate of the bitstream obtained according to the first encoding of the first training image **902**, the mapping relationships between the plurality of DNN setting information of the first DNN **800** and the second DNN **300** and the pieces of information related to the first image **125** may be determined.

(214) FIG. 10 is a diagram for describing training processes of the first DNN **800** and the second DNN **300** by a training apparatus **1000**.

(215) The training of the first DNN **800** and the second DNN **300** described above with reference FIG. 9 may be performed by the training apparatus **1000**. The training apparatus **1000** may include the first DNN **800** and the second DNN **300**. The training apparatus **1000** may be, for example, the AI encoding apparatus **700** or a separate server. The DNN setting information of the second DNN **300** obtained as the training result may be stored in the AI decoding apparatus **200**.

(216) Referring to FIG. 10, the training apparatus **1000** initially sets DNN setting information of the first DNN **800** and the second DNN **300**, in operations S1040 and S1045. Accordingly, the first

DNN **800** and the second DNN **300** may operate according to pre-determined DNN setting information. The DNN setting information may include information about at least one of the number of convolution layers included in the first DNN **800** and the second DNN **300**, the number of filter kernels for each convolution layer, the size of a filter kernel for each convolution layer, or a parameter of each filter kernel.

(217) The training apparatus **1000** inputs the original training image **901** into the first DNN **800**, in operation **S1050**. The original training image **901** may include a still image or at least one frame included in a moving image.

(218) The first DNN **800** processes the original training image **901** according to the initially set DNN setting information and outputs the first training image **902** obtained by performing AI down-scaling on the original training image **901**, in operation **S1055**. In FIG. **10**, the first training image **902** output from the first DNN **800** is directly input to the second DNN **300**. However, the first training image **902** output from the first DNN **800** may be input to the second DNN **300** by the training apparatus **1000**. Also, the training apparatus **1000** may perform first encoding and first decoding on the first training image **902** via a certain codec, and then input the second training image to the second DNN **300**.

(219) The second DNN **300** processes the first training image **902** or the second training image according to the initially set DNN setting information and outputs the third training image **904** obtained by performing AI up-scaling on the first training image **902** or the second training image, in operation **S1060**.

(220) The training apparatus **1000** calculates the complexity loss information **920**, based on the first training image **902**, in operation **S1065**.

(221) The training apparatus **1000** calculates the structural loss information **910** by comparing the reduced training image **903** and the first training image **902**, in operation **S1070**.

(222) The training apparatus **1000** calculates the quality loss information **930** by comparing the original training image **901** and the third training image **904**, in operation **S1075**.

(223) According to an embodiment of the disclosure, the training apparatus **1000** may use at least one of the complexity loss information **920**, the structural loss information **910**, or the quality loss information **930** to calculate the final loss information.

(224) The first DNN **800** may update the initially set DNN setting information via a back propagation process based on the final loss information calculated based on at least one of the complexity loss information **920**, the structural loss information **910**, or the quality loss information **930**, in operation **S1080**.

(225) The second DNN **300** updates the initially set DNN setting information via a back propagation process based on the quality loss information **930** or the final loss information, in operation **S1085**.

(226) Then, the training apparatus **1000**, the first DNN **800**, and the second DNN **300** repeat operations **S1050** through **S1085** until pieces of final loss information are minimized, to update the DNN setting information. At this time, during each repetition, the first DNN **800** and the second DNN **300** operate according to the DNN setting information updated in the previous operation.

(227) FIGS. **11** and **12** are diagrams for describing methods of training the first DNN **800** and the second DNN **300**.

(228) In the training method of the first DNN **800** and the second DNN **300** described above with reference to FIG. **9**, updating of the parameter of the first DNN **800** and updating of the parameter of the second DNN **300** are performed simultaneously in one training process. However, in the training methods of FIGS. **11** and **12**, after training of the first DNN **800** is completed, the second DNN **300** is trained.

(229) Referring to FIG. **11**, an original training image **1101** is input to a third DNN **1100**, and a fourth training image **1104** is obtained by performing AI up-scaling on the original training image **1101** by using the third DNN **1100**. The original training image **1101** includes a still image or a

moving image including a plurality of frames. According to an embodiment of the disclosure, the original training image **1101** may include a luminance image extracted from the still image or the moving image including the plurality of frames. According to an embodiment of the disclosure, the original training image **1101** may include a patch image extracted from the still image or the moving image including the plurality of frames. When the original training image **1101** includes the plurality of frames, the fourth training image **1104**, a first training image **1102**, and an enlarged training image **1103** also each include a plurality of frames.

(230) The third DNN **1100** increases the resolution of the original training image **1101**. The third DNN **1100** is used in training the first DNN **800**, and thus may be the same as or different from the second DNN **300** used by the AI decoding apparatus **200** to perform AI up-scaling.

(231) Separate from the fourth training image **1104** being obtained through the third DNN **1100**, the enlarged training image **1103** is obtained by performing legacy down-scaling on the original training image **1101**. Here, the legacy up-scaling may include at least one of bilinear scaling, bicubic scaling, lanczos scaling, or stair step scaling.

(232) In order to prevent a structural feature of the first image **125** from deviating greatly from a structural feature of the first original image **105** or the second original image **115**, the enlarged training image **1103** is obtained to preserve the structural feature of the original training image **1101**.

(233) The fourth training image **1104** is input to the first DNN **800**, and the first training image **1102** is obtained by performing AI down-scaling by using the first DNN **800**.

(234) First quality loss information corresponding to a difference between the enlarged training image **1103** and the fourth training image **1104**, and second quality loss information corresponding to a difference between the original training image **1101** and the first training image **1102** are input to the first DNN **800** and the third DNN **1100**. Each of the difference between the enlarged training image **1103** and the fourth training image **1104** and the difference between the original training image **1101** and the first training image **1102** may include at least one of an L1-norm value, an L2-norm value, an Structural Similarity (SSIM) value, a Peak Signal-To-Noise Ratio-Human Vision System (PSNR-HVS) value, an Multiscale SSIM (MS-SSIM) value, a Variance Inflation Factor (VIF) value, or a Video Multimethod Assessment Fusion (VMAF) value.

(235) The parameters of the first DNN **800** and the third DNN **1100** are updated such that final loss information obtained by combining the first quality loss information with the second quality loss information is reduced or minimized.

(236) When training of the first DNN **800** is completed, the second DNN **300** is trained, as described above with reference to FIG. **12**.

(237) Referring to FIG. **12**, an original training image **1201** is input to the first DNN **800**, and a first training image **1202** is obtained by performing AI down-scaling on the original training image **1201** by using the first DNN **800**. The original training image **1201** of FIG. **12** may correspond to the original training image **1101** or the fourth training image **1104** of FIG. **11**.

(238) The first training image **1202** is input to the second DNN **300**, and a third training image **1204** is obtained by performing AI up-scaling by using the second DNN **300**. According to an embodiment of the disclosure, a second training image obtained by performing first encoding and first decoding on the first training image **1202** may be input to the second DNN **300**. In order to input the second training image to the second DNN **300**, any one codec among MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used. In detail, any one codec among MPEG-2, H.264, MPEG-4, HEVC, VC-1, VP8, VP9, and AV1 may be used to perform first encoding on the first training image **1202** and first decoding on image data corresponding to the first training image **1202**.

(239) Third quality loss information corresponding to a difference between the original training image **1201** and the third training image **1204** is input to the second DNN **300**. Because training of the first DNN **800** has already been terminated, no loss information is input to the first DNN **800**.

The difference between the original training image **1201** and the third training image **1204** may include at least one of an L1-norm value, an L2-norm value, a Structural Similarity (SSIM) value, a Peak Signal-To-Noise Ratio-Human Vision System (PSNR-HVS) value, a Multiscale SSIM (MS-SSIM) value, a Variance Inflation Factor (VIF) value, or a Video Multimethod Assessment Fusion (VMAF) value.

(240) The parameter of the second DNN **300** is updated such the third quality loss information is reduced or minimized.

(241) It has been described above that the AI up-scaler **236** of the AI decoding apparatus **200** and the AI down-scaler **714** of the AI encoding apparatus **700** store the plurality of DNN setting information mapped with each other, and methods of training each of the plurality of DNN setting information stored in the AI up-scaler **236** and the AI down-scaler **714** will now be described.

(242) According to the training methods described with reference to FIGS. **11** and **12**, when the DNN setting information is obtained as a result of training the first DNN **800**, setting information of the second DNN **300** mapped with the DNN setting information of the first DNN **800** may be obtained via the training process of FIG. **12**. Accordingly, when the first DNN **800** is trained while changing a training target during the training of the first DNN **800** and then the second DNN **300** is trained, a pair of DNN setting information mapped with each other could be obtained. For example, when the final loss information is calculated by combining the first quality loss information with the second quality loss information in FIG. **11**, the training target of the first DNN **800** may be set according to adjustment of weights respectively applied to the first quality loss information and the second quality loss information. The pair of DNN setting information mapped with each other may be obtained by training the first DNN **800** according to the training target and then training the second DNN **300**. A pair of DNN setting information corresponding to a training target obtained by changing the former training target and then training the first DNN **800** and the second DNN **300** may be obtained.

(243) As another example, when the first DNN **800** is trained while changing conditions used during the training of the first DNN **800**, for example, the resolution of the original training image **1101**, the type of a subject included in the original training image **1101**, and a legacy scaling method used to obtain the enlarged training image **1103**, and then the second DNN **300** is trained, a pair of DNN setting information mapped with each other could be obtained.

(244) According to another embodiment of the disclosure, to map the plurality of DNN setting information of the first DNN **800** and the second DNN **300** with the pieces of information related to the first image **125**, first encoding may be performed on the first training image **1202** output from the first DNN **800** of FIG. **12** via a certain codec according to a certain bitrate, and the second training image obtained by performing first decoding on a bitstream obtained as a result of performing the first encoding may be input to the second DNN **300**. In other words, by training the second DNN **300** after setting an environment such that the first encoding is performed on the first training image **1202** of a certain resolution via the certain codec according to the certain bitrate, a DNN setting information pair mapped to the resolution of the first training image **1202**, a type of the codec used to perform the first encoding on the first training image **1202**, and the bitrate of the bitstream obtained as a result of performing the first encoding on the first training image **1202** may be determined. By variously changing the resolution of the first training image **1202**, the type of codec used to perform the first encoding on the first training image **1202**, and the bitrate of the bitstream obtained according to the first encoding of the first training image **1202**, the mapping relationships between the plurality of DNN setting information of the first DNN **800** and the second DNN **300** and the pieces of information related to the first image **125** may be determined.

(245) In the training method of the first DNN **800** and the second DNN **300** described above with reference to FIG. **9**, the reduced training image **903** obtained by performing legacy down-scaling on the original training image **901** is used. However, in the training methods of the first DNN **800** and the second DNN **300** described above with reference to FIGS. **11** and **12**, the enlarged training

image **1103** obtained by performing legacy up-scaling on the original training image **1101** is used. Because the enlarged training image **1103** obtained via legacy up-scaling includes the pixels of the original training image **1101** and additionally generated pixels, the enlarged training image **1103** may be favorable to original data preservation compared with legacy down-scaling that omits some of the pixels of the original training image **1101**.

(246) FIG. **13** is a diagram for describing training processes of the first DNN **800** and the second DNN **300** by a training apparatus **1300**.

(247) The training of the first DNN **800** and the second DNN **300** described above with reference FIGS. **11** and **12** may be performed by the training apparatus **1300**. The training apparatus **1300** may include the first DNN **800** and the second DNN **300**. The training apparatus **1300** may be, for example, the AI encoding apparatus **700** or a separate server. The DNN setting information of the second DNN **300** obtained as the training result may be stored in the AI decoding apparatus **200**.

(248) Referring to FIG. **13**, the training apparatus **1300** initially sets DNN setting information of the first DNN **800**, in operation **S1310**. Accordingly, the first DNN **800** may operate according to pre-determined DNN setting information. The DNN setting information may include information about at least one of the number of convolution layers included in the first DNN **800**, the number of filter kernels for each convolution layer, the size of a filter kernel for each convolution layer, or a parameter of each filter kernel.

(249) The training apparatus **1300** inputs, to the first DNN **800**, the fourth training image **1104** obtained by performing up-scaling on the original training image **1101** by using the third DNN **1100**, in operation **S1315**. The original training image **1101** may include a still image or at least one frame included in a moving image. The training apparatus **1300** may obtain the enlarged training image **1103** by performing legacy up-scaling on the original training image **1101**.

(250) The first DNN **800** processes the fourth training image **1104** according to the initially set DNN setting information and outputs the first training image **1102** obtained by performing AI up-scaling on the fourth training image **1104**, in operation **S1320**.

(251) The training apparatus **1300** may calculate the first quality loss information corresponding to the difference between the enlarged training image **1103** and the fourth training image **1104**, and the second quality loss information corresponding to the difference between the original training image **1101** and the first training image **1102**.

(252) The first DNN **800** updates the initially set DNN setting information via a back propagation process based on the final loss information, in operation **S1330**. Then, the training apparatus **1300** and the first DNN **800** repeat operations **S1315** through **S1330** until the final loss information is minimized, to update the DNN setting information. At this time, during each repetition, the first DNN **800** operates according to the DNN setting information updated in the previous operation.

(253) When training of the first DNN **800** is completed, the training apparatus **1300** initially sets DNN setting information of the second DNN **300**, in operation **S1335**. Accordingly, the second DNN **300** may operate according to pre-determined DNN setting information. The DNN setting information may include information about at least one of the number of convolution layers included in the second DNN **300**, the number of filter kernels for each convolution layer, the size of a filter kernel for each convolution layer, or a parameter of each filter kernel.

(254) The training apparatus **1300** inputs, to the second DNN **300**, the first training image **1202** obtained by performing AI down-scaling on the original training image **1201** by using the first DNN **800**, in operation **S1340**. According to an embodiment of the disclosure, the second training image obtained by performing first encoding and first decoding on the first training image **1202** may be input to the second DNN **300**.

(255) The second DNN **300** processes the first training image **1202** according to the initially set DNN setting information and outputs the third training image **1204** obtained by performing AI up-scaling on the first training image **1202**, in operation **S1345**.

(256) The training apparatus **1300** calculates the final loss information corresponding to a

difference between the original training image **1201** and the third training image **1204**, in operation **S1350**.

(257) The second DNN **300** updates the initially set DNN setting information via a back propagation process based on the final loss information, in operation **S1355**. Then, the training apparatus **1300** and the second DNN **300** repeat operations **S1340** through **S1355** until the final loss information is minimized, to update the DNN setting information. At this time, during each repetition, the second DNN **300** operates according to the DNN setting information updated in the previous operation.

(258) FIG. **14** is a diagram of an apparatus **20** for performing AI down-scaling on the first original image **105** and an apparatus **40** for performing AI up-scaling on the second image **145**.

(259) The apparatus **20** receives the first original image **105** and provides image data **25** and AI data **30** to the apparatus **40** by using a pre-processor **1423**, an AI down-scaler **1424**, and a transformation-based encoder **1426**.

(260) According to an embodiment of the disclosure, the image data **25** corresponds to the image data of FIG. **7** and the AI data **30** corresponds to the AI data of FIG. **7**. Also, according to an embodiment of the disclosure, the pre-processor **1423**, the transformation-based encoder **1426**, and the AI down-scaler **1424** correspond to the pre-processor **712**, the first encoder **716**, and the AI down-scaler **714** of FIG. **7**, respectively.

(261) The apparatus **40** receives the AI data **30** and the image data **25** and obtains the fourth image **165** by using a transformation-based decoder **1446**, a pre-processor **1443**, and an AI up-scaler **1444**. According to an embodiment of the disclosure, the transformation-based decoder **1446**, the pre-processor **1443**, and the AI up-scaler **1444** correspond to the first decoder **232**, the pre-processor **234**, and the AI up-scaler **236** of FIG. **2**, respectively.

(262) According to an embodiment of the disclosure, the apparatus **20** includes a CPU, a memory, and a computer program including instructions. The computer program is stored in the memory. According to an embodiment of the disclosure, the apparatus **20** performs functions to be described with reference to FIG. **14** according to execution of the computer program by the CPU. According to an embodiment of the disclosure, the functions to be described with reference to FIG. **14** are performed by a dedicated hardware chip and/or the CPU.

(263) According to an embodiment of the disclosure, the apparatus **40** includes a CPU, a memory, and a computer program including instructions. The computer program is stored in the memory. According to an embodiment of the disclosure, the apparatus **40** performs functions to be described with reference to FIG. **14** according to execution of the computer program by the CPU. According to an embodiment of the disclosure, the functions to be described with reference to FIG. **14** are performed by a dedicated hardware chip and/or the CPU.

(264) In FIG. **14**, a configuration controller **1422** receives at least one input value **10**. According to an embodiment of the disclosure, the at least one input value **10** may include at least one of a target resolution difference for the AI down-scaler **1424** and the AI up-scaler **1444**, a bitrate of the image data **25**, a bitrate type of the image data **25** (for example, a variable bitrate type, a constant bitrate type, or an average bitrate type), a codec type for the transformation-based encoder **1426**, output resolution for the pre-processor **1423**, a network state, or performance of a display. The at least one input value **10** may include a value pre-stored in the apparatus **20** or a value input from a user.

(265) The configuration controller **1422** controls operations of the pre-processor **1423**, the AI down-scaler **1424**, and the transformation-based encoder **1426**, based on the received input value **10**.

(266) According to an embodiment of the disclosure, the configuration controller **1422** determines the output resolution according to the received input value **10**, and sets the pre-processor **1423** with the determined output resolution. According to an embodiment of the disclosure, the configuration controller **1422** may transmit the received input value **10** to the pre-processor **1423**, and the pre-processor **1423** may determine the output resolution for changing the resolution of the first original

image **105**, based on the received input value **10**.

(267) The configuration controller **1422** obtains DNN setting information for the AI down-scaler **1424** according to the received input value **10**, and sets the AI down-scaler **1424** with the obtained DNN setting information. According to an embodiment of the disclosure, the configuration controller **1422** may transmit the received input value **10** to the AI down-scaler **1424** and the AI down-scaler **1424** may obtain the DNN setting information for performing AI down-scaling on the second original image **115** pre-processed by the pre-processor **1423**, based on the received input value **10**. According to an embodiment of the disclosure, the configuration controller **1422** may provide, to the AI down-scaler **1424**, additional information, for example, color format (luminance component, chrominance component, red component, green component, or blue component) information to which AI down-scaling is applied and tone mapping information of a high dynamic range (HDR), together with the input value **10**, and the AI down-scaler **1424** may obtain the DNN setting information in consideration of the input value **10** and the additional information.

(268) According to an embodiment of the disclosure, the configuration controller **1422** transmits at least a part of the received input value **10** to the transformation-based encoder **1426**, and thus the transformation-based encoder **1426** performs first encoding on the first image **125** via a bitrate of a certain value, a bitrate of a certain type, and a certain codec.

(269) The pre-processor **1423** receives the first original image **105**, and performs pre-processing of changing the resolution of the first original image **105** according to the output resolution. The AI down-scaler **1424** receives the second original image **115** and performs an operation described with reference to at least one of FIG. **1A**, **1B**, **10**, **7**, or **8** to obtain the first image **125**.

(270) According to an embodiment of the disclosure, the AI data **30** is provided to the apparatus **40**. The AI data **30** may include at least one of resolution difference information between the second original image **105** and the first image **125**, or information related to the first image **125**. The resolution difference information may be determined based on the target resolution difference of the input value **10**, and the information related to the first image **125** may be determined based on at least one of a target bitrate, the bitrate type, or the codec type. According to an embodiment of the disclosure, the AI data **30** may include parameters used during the AI up-scaling. The AI data **30** may be provided from the AI down-scaler **1424** to the apparatus **40**.

(271) The image data **25** is obtained as the first original image **105** is processed by the transformation-based encoder **1426**, and is transmitted to the apparatus **40**. The transformation-based encoder **1426** may process the first image **125** according to MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, or VA1.

(272) A configuration controller **1442** controls operations of the pre-processor **1443** and the AI up-scaler **1444**. According to an embodiment of the disclosure, the configuration controller **1442** determines an output resolution, and sets the pre-processor **1443** with the determined output resolution. The pre-processor **1443** performs pre-processing of changing the resolution of the second image **145** based on the set output resolution. According to an embodiment of the disclosure, the configuration controller **1442** or the pre-processor **1443** may determine the output resolution, based on the resolution of an image reproducible by a display connected to the apparatus **40**.

(273) The configuration controller **1442** controls the operation of the AI up-scaler **1444**, based on the AI data **30**. According to an embodiment of the disclosure, the configuration controller **1442** obtains DNN setting information for the AI up-scaler **1444** according to the received AI data **30**, and sets the AI up-scaler **1444** with the obtained DNN setting information. According to an embodiment of the disclosure, the configuration controller **1442** may transmit the received AI data **30** to the AI up-scaler **1444**, and the AI up-scaler **1444** may obtain the DNN setting information for performing AI up-scaling on the third image **155**, based on the AI data **30**. According to an embodiment of the disclosure, the configuration controller **1442** may provide, to the AI up-scaler **1444**, additional information, for example, the color format (luminance component, chrominance

component, red component, green component, or blue component) information to which AI up-scaling is applied, and the tone mapping information of an HDR, together with the AI data **30**, and the AI up-scaler **1444** may obtain the DNN setting information in consideration of the AI data **30** and the additional information. According to an embodiment of the disclosure, the AI up-scaler **1444** may receive the AI data **30** from the configuration controller **1442**, receive at least one of prediction mode information, motion information, or quantization parameter information from the transformation-based decoder **1446**, and obtain the DNN setting information based on the AI data **30** and at least one of the prediction mode information, the motion information, or the quantization parameter information.

(274) The transformation-based decoder **1446** processes the image data **25** to reconstruct the second image **145**. The transformation-based encoder **1446** may process the image data **25** according to MPEG-2, H.264 AVC, MPEG-4, HEVC, VC-1, VP8, VP9, or AV1.

(275) The AI up-scaler **1444** obtains the fourth image **165** by performing AI up-scaling on the third image **155** provided from the pre-processor **1443**, based on the set DNN setting information.

(276) The AI down-scaler **1424** includes a first DNN and the AI up-scaler **1444** may include a second DNN. According to an embodiment of the disclosure, DNN setting information for the first DNN and second DNN are trained according to the training method described with reference to FIGS. **9** and **10**. According to an embodiment of the disclosure, the DNN setting information for the first DNN and second DNN may be trained according to the training methods described above with reference to FIGS. **11**, **12**, and **13**.

(277) Table 1 below shows effects when AI encoding and AI decoding are performed on the first original image **105** according to an embodiment of the disclosure and when encoding and decoding are performed on the first original image **105** via HEVC.

(278) TABLE-US-00001 TABLE 1 Information Amount Subjective Image Quality Score (Bitrate) (Mbps) (VMAF) Frame AI Encoding/ AI Encoding/ Content Resolution Number HEVC AI Decoding HEVC AI Decoding Content_01 8K 300 frames 46.3 21.4 94.80 93.54 Content_02 (7680x4320) 46.3 21.6 98.05 98.98 Content_03 46.3 22.7 96.08 96.00 Content_04 46.1 22.1 86.26 92.00 Content_05 45.4 22.7 93.42 92.98 Content_06 46.3 23.0 95.99 95.61 Average 46.11 22.25 94.10 94.85

(279) As shown in Table 1, even when a subjective image quality when AI encoding and AI decoding are performed on content including 300 frames of 8 K resolution according to an embodiment of the disclosure is higher than a subjective image quality when encoding and decoding are performed via HEVC, a bitrate is reduced by at least 50%.

(280) The above-described embodiments of the disclosure can be written as computer-executable programs, and the written computer-executable programs can be stored in a medium.

(281) The medium may continuously store the computer-executable programs, or temporarily store the computer-executable programs for execution or downloading. Also, the medium may be any one of various recording media or storage media in which a single piece or plurality of pieces of hardware are combined, and the medium is not limited to a medium directly connected to a computer system, but may be distributed on a network. Examples of the medium include a magnetic medium (e.g., a hard disk, a floppy disk, or a magnetic tape), an optical medium (e.g., a compact disk-read-only memory (CD-ROM) or a digital versatile disk (DVD)), a magneto-optical medium (e.g., a floptical disk), ROM, RAM, and a flash memory, which are configured to store program instructions. Other examples of the medium include recording media and storage media managed by application stores distributing applications or by websites, servers, and the like supplying or distributing other various types of software.

(282) A model related to the above-described DNN may be implemented by using a software module. When the DNN model is implemented by using a software module (for example, a program module including instructions), the DNN model may be stored in a computer-readable recording medium.

(283) The DNN model may be a part of the above-described AI decoding apparatus **200** or AI encoding apparatus **700** by being integrated in the form of a hardware chip. For example, the DNN model may be manufactured in the form of an exclusive hardware chip for AI, or may be manufactured as a part of an existing general-purpose processor (for example, a CPU or an AP) or a graphic-exclusive processor (for example, a GPU).

(284) The DNN model may be provided in the form of downloadable software.

(285) For example, a computer program product may include a product (e.g., a downloadable application) in the form of a software program that is electronically distributed through a manufacturer or an electronic market. For electronic distribution, at least a portion of the software program may be stored on a storage medium or may be created temporarily. In this case, the storage medium may be a server of the manufacturer or electronic market, or a storage medium of a relay server.

(286) In AI ending and AI decoding methods and AI ending and AI decoding apparatuses all using pre-processing according to an embodiment of the disclosure, an image may be processed at a low bitrate via AI-based image encoding and AI-based image decoding.

(287) However, effects attainable by the AI ending and AI decoding methods and the AI ending and AI decoding apparatuses all using pre-processing according to an embodiment of the disclosure are not limited to the aforementioned effects, and other effects not mentioned above will be clearly understood by one of ordinary skill in the art from the description below,

(288) The foregoing exemplary embodiments are merely exemplary and are not to be construed as limiting. The present teaching can be readily applied to other types of apparatuses. Also, the description of the exemplary embodiments is intended to be illustrative, and not to limit the scope of the claims, and many alternatives, modifications, and variations will be apparent to those skilled in the art.

Claims

1. A server for providing an image by using an artificial intelligence (AI), the server comprising: at least one processor configured to execute one or more instructions stored in the server to cause the server to: receive a first image; change a resolution of the first image to obtain a second image having a target resolution via a non-AI scaling method, wherein the target resolution is determined by applying, to a predetermined equation, a pre-determined output resolution of a third image to be output from a down-scaling neural network (NN) and a scaling factor of the down-scaling NN; after obtaining the second image via the non-AI scaling method, obtain the third image having the pre-determined output resolution by applying AI down-scaling based on the down-scaling NN to the second image; generate image data by performing encoding on the third image; and transmit the image data.

2. The server of claim 1, wherein the server is configured to: determine, as the target resolution of the second image, a value obtained by dividing the pre-determined output resolution by the scaling factor of the down-scaling NN; and change the resolution of the first image to have the determined target resolution.

3. The server of claim 1, wherein the down-scaling NN is trained based on first quality loss information corresponding to a difference between an up-scaled training image obtained by performing AI up-scaling on an original training image through an up-scaling NN and an enlarged training image obtained by performing non-AI up-scaling on the original training image.

4. The server of claim 3, wherein the down-scaling NN is trained based on second quality loss information corresponding to a difference between a down-scaled training image obtained by performing the AI down-scaling on the up-scaled training image through the down-scaling NN and the original training image.

5. The server of claim 1, wherein the server is configured to transmit AI data related to the AI

down-scaling, and the AI data is used to select NN setting information to be set for an up-scaling NN for AI up-scaling from among a plurality of NN setting information previously stored in a display apparatus.

6. The server of claim 1, wherein the server is configured to determine the output resolution, based on performance information of a display that reproduces a decoded image obtained through decoding on the image data.

7. The server of claim 1, wherein the server is configured to determine the output resolution, based on a scaling factor of a display apparatus that performs AI up-scaling on a decoded image obtained through decoding on the image data and performance information of the display apparatus that reproduces an up-scaled image obtained through the AI up-scaling on the decoded image.

8. The server of claim 1, wherein the server is configured to, when a display apparatus is able to perform changing resolution of a decoded image obtained through decoding on the image data, determine the output resolution based on a state of a network that connects the server to the display apparatus.

9. A method for providing an image by using an artificial intelligence (AI), the method comprising: receiving a first image; changing resolution of the first image to obtain a second image having a target resolution via a non-AI scaling method, wherein the target resolution is determined by applying, to a predetermined equation, a pre-determined output resolution of a third image to be output from a down-scaling neural network (NN) and a scaling factor of the down-scaling NN; after obtaining the second image via the non-AI scaling method, obtaining the third image having the pre-determined output resolution by applying AI down-scaling based on the down-scaling NN to the second image; generating image data by performing encoding on the third image; and transmitting the image data.

10. A non-transitory computer-readable recording medium having stored therein instructions for performing the method of claim 9.
