

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400307
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Li; Jisheng et al.

Enhanced automatic cosmetic grading

Abstract

A method for automatically inspecting and grading a device includes generating an artificial intelligence (AI) grading model based on a plurality of grade criteria associated with a plurality of models of devices. The method further includes capturing a set of one or more images of the device; and grading the device based on the set of one or more images of the device using the AI grading model.

Inventors:	Li; Jisheng (Los Altos, CA), Huang; George (Los Altos Hills, CA)
Applicant:	Future Dial, Inc. (Sunnyvale, CA)
Family ID:	1000008782879
Assignee:	Future Dial, Inc. (Sunnyvale, CA)
Appl. No.:	17/555821
Filed:	December 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220114718 A1	Apr. 14, 2022

Related U.S. Application Data

continuation parent-doc US 16774775 20200128 US 11205259 child-doc US 17555821
us-provisional-application US 62797588 20190128

Publication Classification

Int. Cl.: H04N5/235 (20060101); G06N5/02 (20230101); G06N5/04 (20230101); G06N20/00 (20190101); G06T7/00 (20170101); H04N23/74 (20230101); H04N23/90 (20230101);

U.S. Cl.:

CPC **G06T7/0002** (20130101); **G06N5/027** (20130101); **G06N5/04** (20130101); **G06N20/00** (20190101); **H04N23/74** (20230101); **H04N23/90** (20230101); G06T2207/20081 (20130101); H04M1/725 (20130101)

Field of Classification Search

CPC: A61K (31/353); A61K (31/4196); A61K (31/4525); A61K (31/5025); A61K (45/06); A61K (31/352); A61K (2300/00); A61K (31/337); A61K (31/4439); A61K (31/454); A61K (31/4545); A61K (31/53)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6610953	12/2002	Tao	209/11	G01N 21/3563
10386307	12/2018	Morio et al.	N/A	N/A
10548377	12/2019	Weissman	N/A	A44C 17/001
11205259	12/2020	Li et al.	N/A	N/A
2002/0052551	12/2001	Sinclair	128/920	G16H 40/67
2006/0207066	12/2005	Segelke et al.	N/A	N/A
2008/0192129	12/2007	Walker et al.	N/A	N/A
2013/0085387	12/2012	Chen et al.	N/A	N/A
2014/0030686	12/2013	Stambaugh	434/322	G09B 5/00
2018/0224381	12/2017	Vild	N/A	G06V 10/44
2019/0102880	12/2018	Parpara	N/A	B29C 51/46
2019/0392308	12/2018	Bhatnagar	N/A	G06N 20/20
2020/0005422	12/2019	Subramanian	N/A	G06T 7/194
2020/0242751	12/2019	Li et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103743486	12/2013	CN	N/A

OTHER PUBLICATIONS

Enhanced Automatic Cosmetic Grading, U.S. Appl. No. 16/774,775, filed Jan. 28, 2020, Jisheng Li et al. cited by applicant

Primary Examiner: Haque; Md N

Attorney, Agent or Firm: Greenberg Traurig

Background/Summary

RELATED APPLICATIONS (1) The present application is a continuation application of U.S. patent application Ser. No. 16/774,775 filed Jan. 28, 2020, and entitled “ENHANCED

AUTOMATIC COSMETIC GRADING”, which claims priority to and benefit of Prov. U.S. Pat. App. Ser. No. 62/797,588, filed Jan. 28, 2019 and entitled “Automatic Cosmetic Grading,” the entire disclosure of which is incorporated herein by reference. (2) The present application is related to U.S. patent application Ser. No. 16/393,857, filed Apr. 24, 2019, and published as U.S. Pat. App. Pub. No. 2019-0335033 on Oct. 31, 2019, which claims priority to Prov. U.S. Pat. App. Ser. No. 62/662,719, filed Apr. 25, 2018 and entitled “Enhanced System and Method for Fully Automated Reverse Logistics Platform.” The present application is also related to U.S. patent application Ser. No. 16/218,860, filed Dec. 13, 2018, and published as U.S. Pat. App. Pub. No. 2019-0182678 on Jun. 13, 2019, which claims priority to Prov. U.S. Pat. App. Ser. No. 62/598,394, filed Dec. 13, 2017 and entitled “System and Method for Identifying Best Location for 5G In-Residence Router Location.” The present application is also related to U.S. patent application Ser. No. 15/681,233, filed Aug. 18, 2017 and published as U.S. Pat. App. Pub. No. 2018-0089733 on Mar. 29, 2018, which claims priority to Prov. U.S. Pat. App. Ser. No. 62/377,428, filed Aug. 19, 2016 and entitled “System and Method for Enhanced Retail Device Testing and Evaluation.” The present application is also related to U.S. patent application Ser. No. 15/984,286, filed on May 18, 2018 and published as U.S. Pat. App. Pub. No. 2018-0270349, which is a continuation application of U.S. patent Ser. No. 15/162,421, filed May 23, 2016 and issued as U.S. Pat. No. 9,979,817 on May 22, 2018, which is a continuation application of U.S. patent application Ser. No. 13/797,327, filed Mar. 12, 2013 and issued as U.S. Pat. No. 9,363,367 on Jun. 7, 2016 and entitled “Using Automatically Collected Device Problem Information to Route and Guide Users Requests”, which claims priority to Prov. U.S. Pat. App. Ser. No. 61/762,797, filed Feb. 8, 2013. The entire disclosures of the above identified patents/applications are hereby incorporated herein by reference.

BACKGROUND

(1) Often, transferring data in phones can be very cumbersome. In particular, modern phones may hold multiple gigabytes of data comprising pictures and other graphical representations, address records, emails, etc. A lot of overhead going through the applications creates a data bottleneck for service stations and other stores that offer such data transfer services.

(2) FIG. 1 shows two typical telephone/PDA device data transfer stations. In FIG. 1A, transfer station **100** has a phone data transfer machine (PDTM) **110**, typically a PC with USB and Bluetooth connectivity running phone data transfer applications such as PC Suite, PC Tools and other phonebook transfer applications, which typically may connect to two handsets: originating handset **101** and a receiving handset **102**. Said connections are typically made via USB cables **103** or custom cables **104**. Each phone has its own operating system with software **101a** and **102a**, respectively, and data sets **101b1-n** and **102b1-n**, respectively. This data may contain a variety of information, including, but not limited to, address book data, phone numbers, email addresses, pictures, video clips, and other types of data that may be used by cell phones and their applications. In some cases even the applications installed on the phone and/or the application data may be transferable. Typically, machine **110** would have its own operating system **110a**, which has multiple programs **110b**. Often, machine **110** with operating system **110a** and programs **110b** is actually a custom, dedicated PC, and as such it has to contain drivers or DLLs **110c** for all the phones to which it may be connected. As a result of having a large library of DLLs (or drivers, used interchangeably here) almost any data transfers between two different phones can work. The machine can, by using the DLLs, communicate and download the data objects (each item typically comes down as one or more data objects from the phone), which are then stored in machine **110** temporarily and eventually sent on to the other phone, as its data objects, using the matching DLL. Each of these devices has a CPU and memory, both volatile and nonvolatile, and thus each forms a small, distinct computing device.

(3) FIG. 1B shows another type of known data transfer station **120**. Copy machine **121** has only one connector. It is first plugged into the originating machine **101**, using connection **105**, via which

connection the data is transferred into machine **121**. Then the receiving device **102** is connected by a cable connection **106** (dotted) in a second step, and that connection is used to transfer the data from machine **121** to phone **102**. Again, these devices have operating systems, programs, and DLLs, as described above in the discussion of FIG. **1A**.

(4) A large cost is inflicted on cellular network operators by the user practice of returning devices for repair or exchange that are not actually defective. There are several reasons for this problem: some operating intermittencies may not be caught during in store testing of a defective device, or the problem may be caused by peripheral devices that are not returned with the supposedly faulty phone. A large portion of the problem may be attributed to user configuration errors, network configuration errors, or user software add-ons that are installable in the phone but may not be completely compatible with the particular phone set up and its particular network. Only a small fraction of returns are due to actual failure of the hardware. However, efficient and expedient repair of handsets is very important, because the cost of each handset repair affects the final profitability of an operator. One of the most important aspects of handset repair is efficiently achieving a specific level of program and data sets in a repaired handset.

(5) When large numbers of phones are returned or exchanged, often manual handling is required. Also, often, operating systems and software require manual input that can not be automated for security reasons. In large volumes, the costs can easily add up.

(6) When taking returns at point of sales, an objective evaluation system and method is important, as the lack of such a system can quickly lead to losses of a financial nature through overpaying for buybacks, and also to a loss of confidence in customers who exchange information with friends, relatives and acquaintances and can quickly feel treated unfairly if not treated objectively.

(7) In some cases, more thorough diagnostics of devices with problems are needed than the diagnostics that are available currently. These diagnostics should not merely rely on internal functional diagnostics, but they should also include hardware configuration diagnostics, program configuration diagnostics, and network configuration diagnostics; and they should also look for other factors, including but not limited to program compatibility issues.

(8) Often, the exchange of data objects between different phones is desired or required. Some phones do not support such a feature; other phones have a very limited ability in this regard. For example, such phones may allow exchange of an object such as a business card, but do not support exchange of photos, videos or other larger graphic images.

(9) In some cases wired telephone connections may be difficult or impossible due to defective connectors, unavailable infrastructure, etc.

(10) Some telephone devices are notoriously difficult to access with an in-store diagnostic device, be it wirelessly or via wired connection. In the context of universal serial bus (USB) devices, the manufacturers are supposed to use vendor ID (VID) and product ID (PID) numbers to distinctly identify every product.

(11) These VID/PID numbers are often also used in other connectivity schemes, including but not limited to Bluetooth (BT), local area network (LAN) and over the Internet. These access problems occur due to various legitimate or not-so-legitimate reasons, and more frequently, device manufacturers either re-use the same VID/PID numbers for different devices to save money on registration fees, or in other cases, a fly-by-night garage-style manufacturer clandestinely produces a series of few hundred or a few thousand devices and then closes up shop. This is often because such phones infringe copyrights or other intellectual property, pretending to be brand-name manufacturers' phones, but using different components, such as chips. Despite these problems, it is sometimes desirable for an operator, such as, for example, an independent store operator, to provide service nevertheless, doing so to maintain good customer relations, rather than to rebuff or annoy a customer.

(12) In many cases, it is desirable to back up the data on a mobile communication device with a back-up device that does not require a connection to a standard computer, such as, for example, the

exemplary computer of FIG. 7. For example, when a person with a mobile communication device is traveling away from the office, sometimes it is necessary or desirable to travel without a computing device such as a laptop computer; however, a person may still need to back up the data in his or her mobile communication device.

(13) Often in some settings, such as quality control, mass reprogramming, or incoming materials check, it is necessary to run multiple devices, such as smartphones or tablets, at the same time. Depending on the situation, the batteries of these devices may be mostly or completely exhausted. Because many of the newer devices require upwards of 2 amperes (A) of charge current, often as much as up to 3 A, normal hubs or computers can not deliver sufficient power for multiple devices.

(14) Previous co-pending patents (content incorporated above and throughout) describe a system and method in which mobile devices may be collected at sales points or other customer points of access and then shipped to a central facility for processing. However, one undesirable result of this approach is that devices may still be locked when the processing begins, and the user is not available to provide unlocking information. In other cases, the process of receiving, shipping to the processing facility, and processing the device may takes much time that by the time the device is ready for shipping several weeks may have elapsed, and during that time period, the device may have dropped in value (up to 50 percent per week, in some cases). For example, when a new model of a particular device is released, the value of the old model may drop immediately and precipitously. Thus such a prolonged processing time may create substantial damages to the entity holding the inventory.

(15) Various embodiments of the present disclosure may be implemented in computer hardware, firmware, software, and/or combinations thereof. Methods of the present disclosure can be implemented via a computer program instructions stored on one or more non-transitory computer-readable storage devices for execution by a processor. Likewise, various processes (or portions thereof) of the present disclosure can be performed by a processor executing computer program instructions. Embodiments of the present disclosure may be implemented via one or more computer programs that are executable on a computer system including at least one processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. Each computer program can be implemented in any suitable manner, including via a high-level procedural or object-oriented programming language and/or via assembly or machine language. Systems of the present disclosure may include, by way of example, both general and special purpose microprocessors which may retrieve instructions and data to and from various types of volatile and/or non-volatile memory. Computer systems operating in conjunction with the embodiments of the present disclosure may include one or more mass storage devices for storing data files, which may include: magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data (also called the “non-transitory computer-readable storage media”) include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM disks. Any of the foregoing can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits) and other forms of hardware.

(16) In some cases, a system for testing and reprogramming mobile communication devices, such as, for example, cellular phone, tablets, etc., may enable parallel connection of a large number of devices via, typically, USB cables, to connectors in the system box, with indicator lights for communicating to an operator the device status and readiness. Further, in such a system only one step may be required to charge the device to an operational state, without operator interaction.

(17) In other cases, a system for testing and reprogramming mobile communication devices may enable parallel connection of a large number of devices to connectors in the system box, with the system using different sequences to test, verify, securely delete content, and reprogram devices.

Further, the system analyzes problems such as, for example, bricked devices, dead batteries, and unprogrammable and unstable devices, and collects information about the quality of devices based on their different sources. In addition, the system may collect data about the efficiency of the operators connecting and removing devices at any one system box, or about operators at multiple systems in one testing facility. The system may then communicate its collected data to a central server.

(18) In some cases, a system may include with a computer containing software for processing both data and programs on mobile devices. Further, the system may perform a quick evaluation of said mobile device and where feasible, may determine the current commercial value of the mobile device based on make, model, physical condition and other parameters associated with device. Additionally the system includes a tower containing a number of lockable compartments connected to the computer. Each compartment can receive a mobile device, and an application on a mobile device, such as a tablet, of an authorized user can lock the compartment so the device in the compartment can be tested for certain parameters. After a successful test, the system makes an offer to the device owner, and upon legally binding electronic acceptance of the offer, the system locks the drawer of the owner's device and back up into secure local storage the owner's data as needed, with determination of the need based on questions presented to the owner during or immediately after the presentation and/or acceptance of the offer. Then the owner's address book is processed, so it is available as quickly as possible so the owner can then transfer it to a new device without undue delay. Subsequently, large bulk data can be transferred in a throttled mode, on a first-come, first-serve manner. Additionally, the system makes provisions for the onward disposition logistics of the owner's device, based on information supplied by or in conjunction with the entity taking possession of the device.

(19) In some cases, a system for migration of computer content, including but not limited to applications and various types of data, from one computing device, such as, for example, a smartphone, a phablet, a tablet, or other, similar device, and from cloud services to another device and other cloud services may create a map showing what content needs to be migrated, and where to, so that that the content can be transferred to the new device and/or one or more cloud services upon activation of the new device.

(20) In some cases, a system may simulate a human user touching the screen of a device, such as a cell phone or similar, that has a capacitive touch screen, with the device positioned on a touch simulator that has a matrix of individually addressable, electric structures based on an LCD display. In such a system, a camera may photograph the device screen and transmit the resulting images to a computer, where the interactions of the touch simulator and the device are recorded. Additionally, software on a computer can create scripts for future, similar interactions, using the stored images to test similar devices for functionality. Alternatively, the system may simulate human touch on the device screen through a matrix of individually addressable, XY resolved electric structures based on inflatable tubes.

(21) In some cases, an attachment to a mobile device, such as a smart cell phone, may enable a 5G signal to be detected and scanned. This signal and other environmental information, including but not limited to view, GPS, Wi-Fi and other radio signals, etc., may be recorded concurrently to create a map of the environment that could be stored so an application could calculate the optimal location for a gateway type router. Thus a 5G signal from the outside could be fed securely and reliably to all rooms of a unit in a building, enabling the use of 5G communication devices inside buildings with poor or no reception, in some cases by translating the communication to an alternate band such as 4G or Wi-Fi. Such a scan could include also immediate adjacent areas outside a unit. This software could be the primary method to determine the optimal location for such a router. Additionally, the data may be sent to a technician for further review leading to determination of a preferred location, and in some cases, the user's permission must be obtained to share the data before sending the data to the technician for review.

SUMMARY

(22) In one embodiment, the method comprises creating a catalog associated with a mobile device; recording data associated with the mobile device and storing the data in the catalog; creating a profile associated with the mobile device based on the catalog; comparing the profile to one or more peer profiles to determine if at least one new item can be offered to a user of the mobile device; identifying one or more new items to offer to the user of the mobile device; and transmitting an offer to the mobile device, the offer including the one or more new items.

(23) In another embodiment, the apparatus comprises a processor; and a storage medium for tangibly storing thereon program logic for execution by the processor, the stored program logic comprising: logic for creating a catalog associated with a mobile device; logic for recording data associated with the mobile device and storing the data in the catalog; logic for creating a profile associated with the mobile device based on the catalog; logic for comparing the profile to one or more peer profiles to determine if at least one new item can be offered to a user of the mobile device; logic for identifying one or more new items to offer to the user of the mobile device; and logic for transmitting an offer to the mobile device, the offer including the one or more new items

(24) Today large volumes of mobile devices, such as cellular telephones, tablets, etc., are recycled and often refurbished. As part of the process, they need to be inspected, catalogued, cleaned of user personal identifiable information (PII) or user data, and applications installed, as well as updated to the most recent operating system (OS) and applications (apps) as required by the customer. Then these devices can be resold to new users.

(25) Currently, this refurbishing process requires multiple steps on different, specialized workstations, and such a multi-step process requires lots of manual interaction, which is both error-prone and expensive.

(26) In some cases, a mobile device such as a smart phone or smart computing device may be connected to a network, and an operating system, an application for communicating to other devices, and applications are installed. This device may be a wireless device, a smart phone or a tablet, a mobile communication device, and/or a wearable device; and it may be connected to a wireless communication network. These applications may enable a user to pursue additional interests, including but not limited to listening to and/or creating music, viewing and/or editing documents, viewing and/or creating videos, consuming and/or creating video games, participating in social networks, etc. on the device. Additionally, software may be installed to follow user activities on the device and to catalogue and record these activities. Further, based on activities, device accessories used in the activities, and on service plans to which the user has subscribed, a user profile is created. The system may then compare this user profile to other user profiles that match at least in one of the groups of accessories, activities, and service plans and then determines whether the user could benefit from adding one of the other groups that other users have. Thus the system may determine whether an upsell opportunity exists, in which case an offer for additional products and/or services that would enable a user to take advantage of additional offerings to make better use of his device and/or services may be extended to the user.

(27) The system and method described herein is installed at a point of acceptance for devices that may be a store selling new devices, or it may be a dedicated point of acceptance for returns, or any other similar, suitable location. At this point of acceptance the system can test devices for functionality, memory, model, current value, and other characteristics. Importantly, the system can determine a specific value for the returned device and immediately offer the owner that value for the device, to be applied to the purchase of another device, should the owner accept the offer. When, and if, the owner accepts the offer, the system can remove and secure the personal data from the old device and save it to a location from which the owner can load the data onto the selected replacement device. Then, in most cases, the system can process the device so that it is suitable, after being processed, to be offered as a replacement device to subsequent customers, requiring, additionally, only some cleaning and packaging with necessary accessories, such as, for example, a

power supply, a charging cable, etc.

(28) In the 5G phone environment, one of the biggest challenges is that the 5G signal mostly behaves much more like visible light than previous generations of mobile device signals. This characteristic can create all kinds of problems to make phones work inside apartments, homes, etc., as the waves barely work away from windows and also do not spread well inside buildings, even with very light walls or simple furniture.

(29) The system and method disclosed herein utilizes proprietary software known to the inventor to execute certain operations, typically on a previously activated mobile communication device, such as, for example, a smart phone. These operations may include reading the device automatically and delivering an application to the handset, which application identifies the device to a robot throughout the process.

(30) Some of this software, including applications, has been previously disclosed herein, but some other applications are given out by original equipment manufacturers (OEMs) of the handsets under NDA only. While the details of these applications may not be discussed, enough of their characteristics can be incorporated to enable the understanding or even recreation of a full system, without violating any of these NDAs.

(31) One of the applications in the system identifies to the system hardware and other applications the specific make, model and some or all features of the device and the tests that need to be performed via QR code, Bluetooth and/or WiFi. Further, this application can visually grade the cosmetic condition of the device and functionally test and clear the device of all data prior to warehousing the device for resale or repair.

(32) The system and method disclosed herein can integrate with a client's warehouse management and shop floor control system so all information is visible throughout the processing and is recorded properly in the client's operational records. Further, the system digitally certifies device receipt, cosmetic condition, functional test results, and removal of all customer information. All information, other than specific customer information, sometimes also referred to as Personally Identifiable Information or PII, is available for future reference.

(33) In some cases, a system may know all requirements for the Mobile Reverse Logistics process to read, test, classify, and clear a device being returned to a warehouse for processing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1A and 1B show an exemplary conventional telephone/PDA device data transfer station;
- (2) FIG. 2 an example of a typical telephone/personal data assistant ("PDA") device data transfer station which can be utilized with the system and method according to the disclosed subject matter;
- (3) FIG. 3 shows an exemplary process for data transfer;
- (4) FIG. 4 shows an overview of an exemplary transfer station;
- (5) FIG. 5 shows a simplified overview of an exemplary testing system;
- (6) FIG. 6 shows an exemplary process for implementation of system test software;
- (7) FIG. 7 shows an exemplary overview of a computer system as may be used in any of the various locations throughout disclosed system.
- (8) FIG. 8 shows a more detailed overview of an exemplary system similar to typical telephone/PDA device data transfer stations;
- (9) FIG. 9 shows an exemplary process for implementation of enhanced system test software;
- (10) FIG. 10 shows a simplified overview of two phones that are communicating with each other, according to one embodiment of the disclosed system;
- (11) FIG. 11 shows an exemplary process of the interaction between the two phones according to one embodiment of the disclosed system;

(12) FIG. 12 shows a block diagram illustrating a transfer station;

(13) FIG. 13 shows an exemplary process for discovering the actual identity of a telephone device;

(14) FIG. 14 shows an overview of an exemplary table;

(15) FIGS. 15A and 15B illustrate a system and method for exchanging drivers;

(16) FIG. 16 shows an overview of an exemplary device according to one aspect of the system and method disclosed herein;

(17) FIG. 17 shows an overview of device architecture;

(18) FIG. 18 shows a detailed overview of an exemplary system for updating software in a device;

(19) FIG. 19 shows a detailed overview of an exemplary system for updating software in a device;

(20) FIG. 20 shows an exemplary process for backing up data from a mobile communication device;

(21) FIG. 21 shows an enhanced system according to one aspect of the system and method described herein;

(22) FIG. 22 shows a bus and interface system;

(23) FIG. 23 shows an enhanced USB PCI card;

(24) FIG. 24 shows an overview of an exemplary system for enhanced diagnostics;

(25) FIG. 25 shows an exemplary process for implementation of the system according to one aspect of the system and method disclosed herein;

(26) FIG. 26 shows an overview of the data flow as it is analyzed;

(27) FIG. 27 shows an overview of an exemplary screenshot according to one aspect of the system and method disclosed herein;

(28) FIG. 28 shows an overview of an exemplary screenshot according to one aspect of the system and method disclosed herein;

(29) FIG. 29 shows an overview of an exemplary screenshot according to one aspect of the system and method disclosed herein;

(30) FIG. 30 shows an overview of an exemplary screenshot according to one aspect of the system and method disclosed herein;

(31) FIG. 31 shows an overview of an exemplary screenshot according to one aspect of the system and method disclosed herein;

(32) FIG. 32 shows an overview of a system for identifying software-created problems and operational disruptions in smart phone computing devices and other mobile computing devices with cellular connections;

(33) FIG. 33 shows an exemplary process for data retrieval and analysis by system software running on a computer or server;

(34) FIG. 34 shows an overview of an exemplary system for reprogramming phones;

(35) FIG. 35 shows an exemplary process for programming any one of multiple phones; and

(36) FIG. 36 shows an exemplary process for creating a phone reprogramming package.

(37) FIG. 37 shows an exemplary overview of a system for routing calls according to one embodiment;

(38) FIG. 38 shows an overview as an example of use of the system and method disclosed herein according to one embodiment, wherein a customer with a device goes to a customer service location;

(39) FIG. 39 shows an exemplary process for diagnostic services at a call center, according to one embodiment;

(40) FIG. 40 shows an exemplary process for customer service at a telephone diagnostic location, according to one embodiment;

(41) FIG. 41 shows an overview of an exemplary system according to one embodiment;

(42) FIG. 42 shows a simplified view of the interface board of a charger according to one embodiment;

(43) FIG. 43 shows an exemplary overview of the subroutines in a microprocessor, according to

one embodiment;

(44) FIG. **44** shows an exemplary process in an INIT module as it relates to a UART module, according to one embodiment;

(45) FIG. **45** shows an INIT module, according to one embodiment;

(46) FIG. **46** shows a DETECT module, according to one embodiment;

(47) FIG. **47** shows a branch of the DETECT module;

(48) FIG. **48** shows another branch of the DETECT module;

(49) FIG. **49** shows a SYNC module, according to one embodiment;

(50) FIG. **50** shows a CHARGING module **M4**, according to one embodiment;

(51) FIG. **51** shows a UART module, according to one embodiment;

(52) FIG. **52** shows a TIMER module **M6**, according to one embodiment;

(53) FIG. **53** shows an initialization procedure according to one embodiment;

(54) FIG. **54** shows an overview of an exemplary test system, according to one embodiment;

(55) FIG. **55** shows an exemplary process of a typical workflow, according to one embodiment;

(56) FIG. **56** shows a lateral view of an exemplary new testing, charging, and reprogramming unit, according to one embodiment;

(57) FIG. **57** shows a side view of an exemplary new testing, charging, and reprogramming unit, according to one embodiment;

(58) FIG. **58** shows a schematic view of a typical seven-port USB hub;

(59) FIG. **59** shows a schematic view of an exemplary hub system, according to one embodiment;

(60) FIG. **60** is a view of an exemplary USB cable unit; and

(61) FIG. **61** shows three alternative configurations of an exemplary tray;

(62) FIG. **62** shows an overview of an exemplary multi-device tower, according to one embodiment;

(63) FIG. **63** shows a detailed image of an exemplary device drawer, according to one embodiment;

(64) FIG. **64** shows a simplified drawing of exemplary system architecture, according to one embodiment;

(65) FIG. **65** shows an exemplary process for implementation of the system when a user brings in an old device with content already backed up, according to one embodiment;

(66) FIG. **66** shows an exemplary process for implementation of the system when a user brings in an old device with content back-up and transfer required, according to one embodiment.

(67) FIG. **67** shows a typical mobile phone network architecture, as may be currently in use.

(68) FIG. **68** shows an exemplary tabular computer content map.

(69) FIG. **69** shows an exemplary process for migration of computer content when a user moves to a new phone.

(70) FIG. **70** shows an overview of an exemplary testing system **7000**.

(71) FIG. **71** shows an overview of an exemplary stripped LCD **7100**, introduced in the discussion of FIG. **70** as LCD **7004**.

(72) FIG. **72** shows an overview of an exemplary alternative approach **7200** for activating an icon on a device screen, using a cross-hatching of tubes.

(73) FIG. **73** shows exemplary screen **7300** on a computer running software for a system for managing transactions involving testing mobile devices.

(74) FIG. **74** shows exemplary screen **7400** that follows screen **7300**.

(75) FIG. **75** shows an exemplary process **7500** for executing a transaction.

(76) FIG. **76** shows an exemplary process **7600** for generating further sales offers to existing customers.

(77) FIG. **77** shows an exemplary layout of a portion of a simple apartment.

(78) FIG. **78** shows a layout similar to the layout shown in FIG. **77**, with the addition of a router or similar device.

(79) FIG. **79** shows an exemplary means that can help an unskilled user to find the best location for

a router station and its antenna.

(80) FIG. **80** shows an exemplary process of the software and implementation of its commands for locating a router for a 5G signal.

(81) FIG. **81** shows an exemplary process of a typical work flow.

(82) FIG. **82** shows an exemplary process of a typical physical model of the system.

(83) FIG. **83** shows exemplary pseudo-isometric views of a typical physical equipment layout.

(84) FIG. **84** is a Venn diagram of rules and AI range.

(85) FIG. **85** is an exemplary overview showing a flow diagram of a grading process.

(86) FIG. **86** is an exemplary overview of a hardware connectivity system.

(87) FIG. **87** is an exemplary photograph of an early prototype.

(88) FIG. **88** is an enhanced exemplary overview of a hardware connectivity system.

(89) FIG. **89** is a schematic view of an early prototype.

DETAILED DESCRIPTION

(90) What is needed is a system and method for tracking and detecting device failures, and by doing so analyzing the problems and detecting the incorrect return of hardware, thus reducing dramatically the overall cost of network operations.

(91) Additionally needed is an enhanced system and method to collect information about faults and problems mostly created by misbehaving or malicious applications. However, any problems between applications and operating system, driver, hardware, other apps, or any combination thereof due to software incompatibilities of hardware or of software installed in said mobile computing device can be observed and recorded. Also needed is an enhanced system and method that not only takes into account statistical data collected from software recording, but further adds information gleaned from social networking sites, technical forum sites, etc., relevant to the specific models of mobile communication devices.

(92) What is further needed is a system and method that allows data transfer between phones without requiring PDTMs such as **110** or **121**, thus allowing the user to transfer data at his own pace and, if multiple transfers must be done, they can be done concurrently, because limited resources, such as copy machine **110** or **121**, are generally not required.

(93) Further, it is desired, that such a system operates cross-platform. For example currently, a Palm device can beam to another Palm device and a Nokia device can beam to another Nokia device, but currently a Palm device cannot beam to a Nokia device and vice versa, or to phones manufactured by any other manufacturer, by in large. Some exceptions exist within limited groups of some devices by different manufacturers that use same operating systems.

(94) What is further needed is a system and method that, using a small, portable device such as a USB key, can create backups directly from mobile communication and personal computing devices.

(95) What is additionally needed is a system and method for tracking and detecting device failures, and by doing so analyzing the problems and detecting the incorrect return of hardware, thus reducing dramatically the overall cost of network operations.

(96) Additionally needed is a system and method for reducing the number of interactions required to take in, catalog, charge, test, clean of PII, and update OS and apps as needed.

(97) In most cases, manufacturers need to preload client software to at least one if not both devices for a beaming operation to work. In an embodiment, the present invention does not require client software to be pre-installed. In this respect, the device containing the “old” data can be communicated with as if a computer is communicating with the device. This functionality is generally supported on the mobile phone devices, even on older models, in their stock configuration without additional special purpose applications being installed. In an embodiment, the “old” phone is interfaced with using stock interfaces already on the phone, for example by an application installable on a PC that allows the PC to read from devices through a USB cable without first having to pre-install a client. Further, the wireless technology used by the device does

not matter, as it can read from both CDMA and GSM phones, like the PC based tool.

(98) What is clearly needed is a system and method to simulate manual touch on devices such as phones, preferably without requiring movable parts that simulate fingers, as these would wear out quickly.

(99) What is needed is a system and method that enables a returned device to be evaluated in the most objective form and manner possible, with the least personal judgment required by the reviewer. Also needed is a system and method for keeping the reviewer honest by keeping optimal track of all steps of the reviewer.

(100) What is clearly needed is a novel approach that can take those signals from a gateway location in a residence or in rooms of some other type of unit in a building, for example, a window or door, either directly or with a simply attached antenna, and then, for example, redistribute it inside room by room either on different frequencies, such as 4G femto cells, or via an intermediate signal such as Wi-Fi to a device or to a further distribution point in another room.

(101) FIG. 2 shows an example of a system **200** according to one embodiment of this disclosure. In this example, the receiving phone **202** may be connected, either by wired or wireless connection, to the originating phone **101**, as indicated by connection lines **201a-n**. This connection could be via Wi-Fi ad hoc connection, Bluetooth connection, wired connection, or in some embodiments an over-the-air network connection. In an embodiment, the originating phone **101** has, as before, an operating system **101a** and a data set **101b1-n**. The receiving phone **202** has the same software; however, additionally, the operating system **202a** contains applications **212a-n**, at least one of which (referred to herein as **212x**, not shown) is the copying software. This software may be, for example, downloaded from a network provider and installed in the phone or, in some embodiments, pre-installed in the phone by the manufacturer. More than one type of copying software may be required, depending on the various different phones involved in a transfer, but requiring only one application for a given new phone. Copying software **212x** has access to a complete set of drivers and DLLs **213a-n**, which drivers and DLLs may be required for various different phones. The complete library of drivers and DLLs may be pre-installed in the originating phone and updated through the Internet. In some embodiments, these drivers and DLLs **213a-n** may not be downloaded until phones **202** and **101** are paired, so that only the driver(s) and DLL(s) for the specific paired devices are downloaded. In other embodiments, some or all available drivers and DLLs may be downloaded, but some or all drivers and DLLs may be removed later to free up memory in the receiving device **202**. As previously mentioned, devices such as phone **202**, and optionally phone **101**, are generally known as smart phone computing devices or other mobile Internet/computing devices, including, but not limited to, smart phones, tablets, etc. Typically these devices have a very powerful CPU, a relatively large amount of memory of different kinds (including but not limited to RAM, flash, removable media, etc.), input devices, display devices, speaker, microphone, and other such components and a software operating system **202a**, so that they are actually fully functional, hand-held computing platforms, with functionality limited only by their size and sometimes by restrictions of their operating system **202a**. In some embodiments, the copy software and adapted or simulated DLLs may be adapted to run on the phone's operating system ("OS"), and in other embodiments an additional OS that runs within a protected environment (similar to a virtual machine) but allows use of unmodified DLLs may be provided.

(102) What is additionally needed is a system and method for processing devices at the point of acceptance and exchanging the device for another satisfactory, working device, so the customer leaves with the transaction fully executed. Further, a reduction of time spent by customer for the processing of the return device is needed.

(103) FIG. 3 shows an exemplary process **300** for data transfer according to one embodiment of the disclosed system. In step **301** the copy application is downloaded into a receiving phone such as phone **202**. In this example, the download is via network **303** from data repository **305** that resides in server **304** and that contains copy applications for all supported phones. In step **302**, DLLs are

loaded into device **202**, also from data repository **305** in server **304**. As mentioned previously, this step may occur only after connection with an originating phone such as phone **101** is established. In step **306**, the connection is established with originating phone **101**. As previously described, this connection may be made via any of various types of connectivity means that are currently known in the art or that may in the future be developed and made publicly available. In all cases, the connection process would involve a confirmation or pass code, such as the process currently used for the connection of Bluetooth devices. In some cases, this connection would actually be between two Bluetooth devices, but in other cases a similar process could be emulated via the phone number and passwords over the network or over a physical wire. In step **308** the system tests the originating device **101** to determine its specific model. This testing typically requires some user approval **307** or a user action on the originating phone, either of which may also act as a privacy protection (sometimes it may be part of communication protocols, such as pairing of Bluetooth devices. etc.). Then typically the DLL **213x** for that specific model is loaded for use by the copying software **212x**. This DLL could be loaded from the library downloaded in step **302**, or it could be requested from the data repository **305** via over-the-air network or other suitable connections. In step **309**, the system downloads data from device **101**. To the internal intelligence (software and firmware) of device **101**, this process appears to occur just as if the device were connected to a computer. In step **310** the system then converts or adapts the downloaded data objects to the requirements of the receiving phone **202** by means of another DLL, which essentially mimics the process of the download to internal database **202b1-n**. In step **311** the data is then downloaded into database **202b1-n**. In step **312** the user is notified that the data download is complete, and in step **313** the process ends. Progress of the various procedures may be displayed to the user via progress bars on the display device of the receiving phone, showing the progress as a percentage of the overall process or as a percentage of a typical process. Such a progress display is commonly used and well known in computing devices.

(104) FIG. **4** shows an overview of an exemplary station **400** similar to typical telephone/PDA device data transfer stations as are currently in use. In FIG. **4**, phone data transfer machine (PDTM) **410** is typically a PC or other suitable computing device with USB and Bluetooth connectivity running phone data transfer applications such as PC Suite, PC Tools and other phonebook transfer applications, which typically may connect one or two handsets, such as the handset of a device under test (DUT) **401** as shown in FIG. **4**. Said connections are typically made via USB cables **403** or custom cables **404** (not shown). Each phone has its own operating system with software **401a** and data sets **401b1-n**. This data may contain all kinds of information, including, but not limited to, address book data, phone numbers, email addresses, pictures, video clips, and other types of data that may be used by cell phones and their applications. In some cases even the applications or the application data may be transferable. Typically machine **410** would have its own operating system **410a**, which has multiple programs **410b**, including a test application **410b1** (not shown separately). Often machine **410** with operating system **410a** and programs **410b** is actually a custom, dedicated PC, and as such it has to contain drivers or DLLs **410c** for all the phones to which it may be connected. As a result of having a large library of DLLs (or drivers, used interchangeably here) almost any data transfers between two different phones can work. The machine can, by using the DLLs, communicate and download the data objects (each item typically comes down as one or more data objects from the phone), which are then stored in machine **410** temporarily and eventually sent on to the other phone, as its data objects, using the matching DLL. It is clear that each of these devices has a CPU and memory, both volatile and nonvolatile, and thus each forms a small, distinct computing device.

(105) FIG. **5** shows a simplified overview of an exemplary testing system **500**, using the same DUT **401**, according to one aspect. Here, rather than being connected to a hardware testing device, a test application **410b1** (not shown separately) may, for example, be downloaded over the network **502** from a server **504**, or from its data repository **506**. In some cases the PDTM **410** may tell the server

504 which device, identified by its ESN, IMEI, phone number, etc., should receive the application, as the network operator has the ability to send special system messages to remotely install software on devices.

(106) FIG. 6 shows an exemplary process **600** for implementation of the system test software. In step **601** the system downloads a monitoring application onto a target device. In step **602**, the system obtains user permission to run the application. In addition to asking a simple Yes or No question, the system may require the user to enter a password, such an account password or the user password for this device, to verify that this is not an illegal attempt to install software on the device.

(107) In step **603**, the program starts to monitor user and device activities, including but not limited to such as cell changes, roaming table updates, installation and activation of software applications, installation and activation of plug-in software, phone calls, etc. Other monitored data includes a preferred roaming list (PRL), battery operation, temperature control, logging of RF signal in and out during various operations, etc. In some cases, it is also possible to obtain a precrash memory dump, which may be stored in the local storage **401c** of device **401**. Local storage **401c** may be, for example, a segregated section of nonvolatile memory in the device, which would preferably survive a crash without losing data.

(108) The monitoring application preferably repetitively writes a list of applications that were launched or installed to flash memory of the device in multiple consecutively written files. In an embodiment, the monitoring application repetitively writes the list of applications to three consecutively written files in the flash memory in the following manner. A first file is opened, data is written to the file, and the first file is closed. A second file is then opened, data is written to the file, and the file is closed. A third file is then opened, data is written to the file, and the file is closed. The process is then repeated, with the first file being opened, data written to it, the first file closed, and so on. If multiple files are used in this manner in an ongoing monitoring process, then it is much more likely that at least one of the files will be readable and not corrupted after an event such as when the user pulls the battery, when the user performs a hard reset, or the when the device crashes. Furthermore, a snapshot of the state of the device can be reconstructed from a combination of two or more of the multiple files after such event even if one of the files is corrupted by the event. In an embodiment, the monitoring application is configured to selectively upload the data files to a central data repository only when a Wi-Fi connection is available to the device so as not to incur data usage charges. This mode of operation is particularly useful where the user of the device does not have an unlimited data plan, and pays per-megabyte or per-gigabyte charges for data usage.

(109) Also, in step **604** the system monitors the remaining capacity of local storage **401c**. When the storage **401c** reaches a preset threshold of occupied space (yes), it is considered full and the process moves to step **605**, where the system now sends data to data repository **506** on server **504**, from where it can be analyzed either automatically or on demand when a customer comes to a store or repair depot to complain about the phone. From step **605** or, if the local storage is not yet full (no), from step **604**, the process moves to step **606**. There, the system analyzes the data transmitted by the downloaded application and stored either in local storage **401c** or data repository **506**. If the system does not detect a fault, the process loops back to step **603**, where the system continues to monitor the device. If the system detects a fault or other relevant state or event (yes), the process moves to step **607**, where the system sends a fault indication to data repository **506** of server **504**. Server **504** may be running programs to respond to the fault indication by, for example, sending an email to the user of device **401** explaining the problem. A copy of this email may also be sent to the phone number's account log at the network operator's system, or, in other cases, only to the network operator's system. After the email is sent, the process loops back to step **603**, where the system continues to monitor the device. By anonymizing certain data, abuses of the data may be reduced. Also, server **504** may keep a log of who has access to the phone data, who uses the data, and how it

is used. These measures may reduce the incidence of unauthorized employee snooping into the phone usage of certain customers, such as, for example, celebrities. Further, statistical and multivariate analysis may be used to extract useful information, such as the fact(s) that visiting some web-sites, or installing and respectively running some software alone or in combinations, may cause instability. That information can be mined, and also used to alert users, for example by email, SMS or other suitable means, that after installation of a certain applications, for example, their phone may become unstable etc. Also, locations of unusually high frequency of dropped calls may be discovered, and countermeasures may be used, including but not limited to alerting the user that a femtocell at his home may help him avoid those dropped calls, or installing an auxiliary cell in a bend or hollow may solve the problems for cars driving through that location. In yet other cases, end of life of battery, or programs that drain batteries may be found and users alerted either obtain a new battery or turn off power hogging software. This allows the system to do some pre-emptive troubleshooting, reducing costs and making customers more satisfied with the service offerings.

(110) FIG. 7 shows an exemplary overview of a computer system **700** as may be used in any of the various locations throughout system **400**. It is exemplary of any computer that may execute code to process data. Various modifications and changes may be made to the computer system **700** without departing from the broader spirit and scope of the current invention. CPU **701** is connected to bus **702**, to which bus is also connected memory **703**, nonvolatile memory **704**, display **707**, I/O unit **708**, and network interface card (NIC) **713**. I/O unit **708** may, typically, be connected to keyboard **709**, pointing device **710**, hard disk **712**, and real-time clock **711**. NIC **713** connects to network **714**, which may be the Internet or a local network, which local network may or may not have connections to the Internet. Also shown as part of system **700** is power supply unit **705** connected, in this example, to ac supply **706**. Not shown are batteries that could be present, and many other devices and modifications that are well known but are not applicable to the specific cases discussed herein.

(111) FIG. 8 shows a more detailed overview of an exemplary system **800** similar to typical telephone/PDA device data transfer stations as are currently in use and are known to the inventor. In FIG. 8, testing computer **810** is typically a PC with USB and Bluetooth connectivity running phone data transfer applications such as PC Suite, PC Tools and other phonebook transfer applications, which typically may connect one or two handsets, such as the handset of a device under test (DUT) **801** as shown in FIG. 8. These connections are typically made via USB cables **803** (not shown) or custom cables **804** (not shown). Each phone has its own operating system with software **801a** and data sets **801b1-n**. This data may contain various types of information, including, but not limited to, address book data, phone numbers, email addresses, pictures, video clips, and other types of data that may be used by cell phones and their applications. In some cases even the applications or the application data may be transferable. Typically machine **810** would have its own operating system **810a**, which has multiple programs **810b**, including a test application **810b1** (not shown separately). Often machine **810** with operating system **810a** and programs **810b** is actually a custom, dedicated PC, and as such it has to contain drivers or DLLs, data tables, and configuration data **810ca-n** for all the phones to which it may be connected. These data tables and configuration data also contain any known combination of programs and drivers, comprising combinations that are known to be functional, as well as the ones that are known to have problems. Thus the table can indicate the existence of problems. Further, enhanced test functionality is created by downloading an additional diagnostic program **802** that supports additional manipulation and tests beyond factory diagnostic program **801** in the device **401** under test. As a result of having a large library of DLLs (or drivers, used interchangeably here) almost any data transfers between two different phones can work. The machine can, by using the DLLs, communicate and download the data objects (each item typically comes down as one or more data objects from the phone), which are then stored in machine **810** temporarily and eventually sent on

to the other phone, as its data objects, using the matching DLL. It is clear that each of these devices has a CPU and memory, both volatile and nonvolatile, and thus each forms a small, distinct computing device.

(112) FIG. 9 shows an exemplary process 900 for implementation of the additional enhanced system test software. In step 901 the diagnostic program is loaded into a PC, such as PC 810. In step 902 the driver for device under test is loaded, allowing connection between test computer 810 and DUT 401. In step 903 full access to DUT 401 is set up. In step 904 the enhanced diagnostics 802 are downloaded into DUT 401, which diagnostics permit access to data not normally available through previously known access methods for any of various reasons, including but not limited to security restrictions. In step 905 the full data and program map is downloaded into PC 801 from DUT 401. In step 906 the downloaded data is compared to a reference library that may reside in data repository 506 on server 504, or it may be downloaded from a source via the Internet, or via a local intranet. This comparison shows which data from device 401 may be good and which data may have problems. In step 907 results of the comparison of step 906 are flagged with suggested corrections, such as, for example, removing certain programs, or updating or modifying certain configurations, or updating certain of the software or firmware of device 401 to ensure that the configuration of device 110 is functionally compliant with the most recent data stored in the data repository. In step 908, the system may offer an option of automatic reconfiguration. If the option is not offered or not accepted (no), the process moves to step 909, where it ends. If the option is offered and accepted (yes), the process moves to step 910, where the person executing the implementation of the system (process 900) is prompted on a per-item basis to accept updates and modifications. This manual, per-item selection of modifications is necessary because some modifications may cause loss of data and/or applications, which the user may be unwilling to endure. In step 911, the accepted modifications are executed, including configuring data, programs, and tables per user options. In step 912 the modified material is uploaded into DUT 401. Upon completing the uploading, the process moves to step 909, where it ends. These diagnostics with data table comparison capabilities may also have a reminder (“nag”) function that prompts the user to load updates that were not accepted in step 910. For example, a user may have been in a situation, such as a business trip, where he did not trust the connection, or the security, or he did not have time, or for some other reason he preferred to wait until a more convenient time and place. The system may also require an account password or other security mechanism to prevent unauthorized people from changing the DUT configuration. Logs of the functions may be transmitted to a server in the network operation center, allowing review of all past transactions by any technician who is attempting to assist the customer. Additional functionality that may be provided include features such as radio tagging, field strength and GPS tracking, or other add-ons.

(113) It is clear that many modifications and variations of this embodiment may be made by one skilled in the art without departing from the spirit of the novel art of this disclosure. These modifications and variations do not depart from the broader spirit and scope of the invention, and the examples cited here are to be regarded in an illustrative rather than a restrictive sense. For example, the application for determining if a mobile phone device is defective can be loaded onto the device from another computing device either in the store or over the network. Such application analyzes for problems in at least one of hardware, software and configuration. Further, in some cases, such application may be downloaded from a computing device connected with a cable or a local area wireless connection. In other cases, it may be downloaded over the wireless wide area communication network, even at the service location, or anywhere else. In some embodiments, the application continues to run after the local test, and then subsequently transmits information about key events to a server on the communication network. In some embodiments, the application will request a user password to verify the user wishes to have it installed, and is the authorized user of the device. In some embodiments, the data transmitted reflects or describes at least one of the following types of events: crashes of the device, other application crashes or hang-ups, loss of

signal, location, loss of battery power, loss of connection, user configuration changes, user application installation and removals, data synchronization, inserting or removing data cards. Such events are time stamped, and in case of a subsequent crash, the event log can be transmitted after the mobile device regains functionality.

(114) What is needed is a system and method that allows the exchange of any kind of object between two phones, whether exchange is originally supported by these phones or not, in a secure and safe manner. Such an exchange may be accomplished, for example, over Bluetooth, infrared, or other connection types that are well known. As discussed above, the ability to insert diagnostic tools into a phone, and more specifically, the ability to insert software into a phone, is known to the inventors.

(115) FIG. 10 shows a simplified overview of two phones, **1001** and **1011**, that are communicating with each other, according to one embodiment of the current invention. Each phone **1001** and **1011** has its own store **1002a-n** and **1012a-n**, respectively, of software, such as, for example, programs. Similarly, each phone **1001** and **1011** has a set of data objects **1003a-n** and **1013a-n**, respectively. In the manner described above, the phone that is initiating communication, in this case phone **1011**, is sending a diagnostic program, which in this example is a file plan for a utility, to phone **1001**.

(116) FIG. 11 shows an exemplary process **1100** of the interaction between the two phones, according to one embodiment of the current invention. The two communication streams are stream **1111** (for phone **1011**) and stream **1101** (for phone **1001**). In step **1121**, the initializing phone (in this example, phone **1012**) connects to the other phone (in this example, phone **1001**). In step **1122**, phone **1001** identifies phone **1011**. In step **1123**, based on the identification, an application that is suitable for the object phone **1001** is taken from the application store, which forms part of the program store **1012**, and is transferred to phone **1001**. Typically, the phone's security system asks the user to confirm this transfer, and upon acceptance, in step **1124**, phone **1001** accepts and installs the application. That application may contain a key that sets up a trusted relationship between the two phones for the future, similar to the relationship between nodes in a home or workgroup network of computers. Different types of settings may be offered, such as, for example, "Always allow" or "Always ask" in the case of a request to transfer data. In step **1125**, initiating phone **1011** sends a selected object to receiving phone **1001**, and in step **1127**, receiving phone **1001** receives the object. The user may be prompted to accept the object, particularly depending on the nature of the object. This process may continue until all desired objects are transferred. In some cases, the transfers may be bidirectional; in other cases, they are only unidirectional. Both phones end their communications in step **1129** and **1130**, respectively, after which a new session must be started again from step **1121** to send more data. When the application is installed, depending on its permissions settings, it may remain in the phones and permit new connection for data transfers without reinstallation, or it may allow such connections only with user approval. However, in other cases, the application may be deleted after each session for purposes of security.

(117) What is needed is a system and method that can transfer the data of either multiple devices simultaneously or one device on a one-to-one basis in sequence, using wireless connections and thus avoiding connection problems such as defective connectors, unavailable infrastructure, etc.

(118) FIG. 12 shows transfer station **1200**. Station **1200** has a phone data transfer machine (PDTM) **1210**, typically a PC with USB and Bluetooth connectivity running phone data transfer applications such as PC Suite, PC Tools and other phonebook transfer applications, which typically may connect to two handsets: originating handset **1201** and a receiving handset **1202**. These connections are, in some cases, typically made via any suitable wireless connection such as **1203** or **1204**, including, but not limited to, Bluetooth, Wi-Fi, ZigBee, or any other suitable wireless protocol, or over the wireless carrier network and via the Internet (not shown) to device **1210**. For this purpose, device **110** may have one or more additional wireless interfaces (not shown for clarity). In some cases, these interfaces may reside in one or more access points (not shown) connected through a local area network (not shown). Also, device **1210** may, in some cases, support more than two sets

at a time. Thus, a single device could support, for example, transfer between four pairs (i.e., total of eight devices, four old devices and four new devices). Each phone has its own operating system with software **1201a** and **1202a**, respectively, and data sets **1201b1-n** and **1202b1-n**, respectively. This data may contain all kinds of information, including, but not limited to, address book data, phone numbers, email addresses, pictures, video clips, and other types of data that may be used by cell phones and their applications. In some cases even the applications or the application data may be transferable. Typically machine **1210** would have its own operating system **1210a**, which has multiple programs **1210b**. In some embodiments, machine **1210** with operating system **1210a** and programs **1210b** is actually a custom, dedicated PC, and as such it contains drivers or DLLs **1210c** for all the phones to which it may be connected. As a result of having a large library of DLLs (or drivers, used interchangeably here) almost any data transfers between two different phones can work. The machine can, by using the DLLs, communicate and download the data objects (each item typically comes down as one or more data objects from the phone), which are then stored in machine **1210** temporarily and eventually sent on to the other phone, as its data objects, using the matching DLL. In various embodiments, each of these devices has a CPU and memory, both volatile and nonvolatile, and thus each forms a small, distinct computing device.

(119) What is needed is a system and method that allows connection of telephone devices of unknown or questionable origin, with incorrect or spoofed VID/PID, and the ability to provide services such as data transfer, software repair of damaged flash, etc.

(120) FIG. **13** shows an exemplary process **1300**, according to one aspect of the system and method disclosed herein, for discovering the actual identity of a telephone device, which actual identity may differ from the indicated identity of said device, and installing correct drivers for said device. A device under test (DUT) **401** is connected via a wired connection or wirelessly to system **1300**. At step **1303** the system attempts to determine the ID of DUT **401**, typically by determining the VID/PID from the USB or from the wireless plug 'n' plays used. In general, only a few actual distinct platforms of chipsets, symbolized as elements in list **1302a-n**, are widely used. Currently about seven main platforms are in use, including, but not limited to, platforms from chipset manufacturers such as MTK, Infineon, Motorola, Qualcomm, Nokia, etc. However, myriad variations are made in designing telephone or mobile computing devices using those chipsets, both in the chipsets from the chipset manufacturers mentioned above, as well in as custom modifications by handset manufacturers that add additional chips, software, and software modifications, resulting in a complex, vast array of combinations and permutations of the platform elements used in a device, sometimes within the same VID/PID. This VID/PID (referred to as ID here) is then compared to the contents of a look-up table **1304**, where the device may be identified. Table **1304** is a part of a knowledge base (not shown), which contains various tables and data accessed by the system. If the look-up list does not return a conclusive ID result, meaning that more than one model and/or hand set manufacturer (HSM) are using it, the system then queries table **1305**, which has multi-variant content. This is a list of devices that are known to have multiple variants. Also, in some cases, the system may prompt the user to enter additional information, or the system may send a query from server **1306**. This server **1306** may be used, for example, as a common knowledge base for all or a group of service entities, such as, for example, within a certain store network, or provider network, to allow knowledge acquired at one entity to be shared among all entities. Queries to a user may include a request that the user manually enter an International Mobile Equipment Identity (IMEI) number, an electronic serial number (ESN), a serial number, or any other, similar type of marking on the device, as well as a model number from the device. However, as previously noted, some manufacturers may mark a device with a known model number, such as, for example, N95 from Nokia or the Apple iPhone model number, even though the device is not from the indicated manufacturer and is, in fact, a counterfeit device. Once the device has been identified, the system looks up its correct driver from a list of drivers in table **1307**, and then in step **1308** it installs a low-functionality driver that can make additional queries into the

handset's operating system in step **1309** for further identification of a HSM and model number. The results of these queries are applied to a second look-up table **1310** that lists of all the drivers. With the correct driver determined from table **1310**, in step **1311** the system uninstalls the low-functionality driver and, in step **1312**, it installs the correct driver.

(121) FIG. **14** shows an overview of an exemplary table **1400**, typical of tables **1304**, **1307**, or **1310**. Table **1400** shows OEM IDs O1 through On **1402a-n** and model numbers M1 through Mn **1401a-n**. Thus a user or the system as disclosed herein may create a cross reference **1403aa-nn** from the OEM ID and the model numbers appearing within a certain VID/PID of that OEM. Some OEMs, for example, use the same VID/PID for several model numbers as they quickly change chip versions, but do not change the overall device architecture. However, different chip versions may have different functions and features, as well as different internal memory, and thus may need different diagnostic tools and/or different transfer tools to recover and transfer and reinstall the operating system, as well as applications, data, and user information, such as calendar, address book, images, video, etc. By providing this dynamic look-up and problem-management tool, the system can flexibly adapt itself.

(122) FIGS. **15A** and **15B** show an additional aspect of the system and method disclosed here, namely, an innovation to speed up the process as, during the discovery of a device, multiple drivers may need to be exchanged, and that operation can take a long time using the typical plug 'n' play process. A new approach for exchanging drivers is herein proposed:

(123) FIG. **15A** shows an overview of a classic driver model **1500** as is well known in the art, with the application **1501** sitting on top of the driver **1502** and the OS **1503** sitting below, and the driver having the VID/PID and other interfaces to software and hardware plug 'n' play, etc., as indicated by elements **1504a-n**, and interfaces to the applications **1505a-n**.

(124) FIG. **15B** shows a novel approach **1510** for a driver stack layer view, according to one aspect of the system and method disclosed herein. Reinstalling the whole driver every time requires massive changes in the registry. In the novel approach of the system and method disclosed herein, for drivers that have the same VID/PID (or even different VID/PID in some cases), the driver is cut into three sections: application-facing **1511** (with subsections **1505a-n**)” the main body **1512x** (which can be now exchanged without requiring a reboot), and OS-facing section **1513** (with subsections **1514xy** out of **1514aa-nn**). In this embodiment, section **1511**, which contains certain functional elements **1505a-n** of the driver, is now absorbed as part of the application **1501** and, as such, is no longer a part of the driver. Section **1512x** contains the remaining portions of the driver, which, in many applications, can be represented by a uniform driver that has a small footprint and can load relatively quickly. This novel approach no longer requires the loading of all functional elements in **1511** with its subsections **1505a-n** and **1512x**, which may require a long time to load, but only the uniform driver **1512** together with selected functional elements **1505a-n** in **1511** that are necessary to interface to a particular device. Not having to load unnecessary functions can save a significant amount of time. Further, section **1513** interfaces to the OS, and main driver section **1511x** can be easily interchanged with any of **1511a-n** (not shown), without requiring a reboot every time.

(125) In some cases, the VID/PID is exchanged by writing directly into the registry, rather than by a full plug 'n' play installation. This novel approach has the advantage that the typical change time is now in the millisecond or low seconds range, instead of the tens of seconds typically required currently to uninstall and reinstall a driver. Because up to a dozen or two dozen drivers may need to be tested for a single a phone, the total time to test drivers could become a burden to a business if each uninstall and reinstall cycle of a driver takes up to a minute or longer.

(126) FIG. **16** shows an overview of an exemplary device **1600** according to one aspect of the system and method disclosed herein. Device **1600** is, in this example, a USB key **1601**. Device-oriented port **1602** can accept a standard USB interface cable for connection from a small mobile communication device (not shown). Computer-oriented connector **1603** may plug into a computing

device (not shown), such as the exemplary computer of FIG. 7 or any other, similar standard PC. Connector **1603** may, alternatively, plug into a USB power supply (not shown) to supply power to USB key **1601**, if the communication device to which it is attached does not supply enough power. A user may press button **1604** to initiate operation of USB key **1601**. (It is clear that button **1604** is exemplary only, and that any of various types of switches, buttons, toggles, keys, etc. may be used to initiate operation.) In some cases a medium for additional data storage may plug into slot **1605**. USB key **1601** also has a small display **1606**.

(127) FIG. 17 shows an overview of device architecture **1700**, according to one aspect of the system and method disclosed herein. Again, computer-facing USB connector **1603** is connected via USB cable **1711** to a computer **1712**, of the type of complete computer system shown in FIG. 7. The unit **1601** contains, in this example, system on a chip (SOC) **1701**. SOC **1701** contain a processor, some volatile memory, and some nonvolatile memory. The nonvolatile memory contains software **1710a-n** and additional modules described later. It is also used to store and/or to provide information such as address book data, pictures, music, or any other information useable on smart phone **1714**, as well as the embedded operating system, and drivers and tables to communicate with a variety of different devices **1714**. Device-facing interface **1602** is connected via USB cable **1713** to communication device **1714**. Display **1606** may comprise just one LED, a multi-color LED, multiple LEDs, a small LCD, or any other, similar display type. The SOC **1701** has specific interfaces, such as **1706**, to drive and/or interface with respective units, such as, in this case, display **1606** (and/or other output devices, such as OLEDs, LEDs, LCDs, etc.). Port **1705** serves for connecting additional storage, in this example, to slot **1605**, which may accept a micro SD card **1708**. Other interfaces may be supported as well, but are not shown for clarity. Button **1604** is also connected to the SOC via interface **1704**; in a similar manner, computer-facing USB connector **1603** is connected to SOC **1701** through interface **1703**. Internal memory **1706** contains at least a boot-strap software for SOC **1701**. External, additional nonvolatile memory **1707**, may contain additional code, drivers, etc., as described in the discussion of FIG. 18, following. Memory **1707** may or may not be present. In some cases, the system memory **1706** may have minimal capacity, and it may only transfer data between smart phone **1714** and computer **1712**. In other cases, memory **1707** may have limited capacity, requiring the presence of external memory **1708** for full backups. In some cases, for example, without external memory **1708**, device **1600** could back up only, for example, information about 100 contacts; whereas, the addition of external memory **1708** (for example, a flash memory card) would enable backup of all data in the communication device, including even pictures, music, and video. After connecting the device **1601** to phone **1714**, and, if necessary, to a power source, such as computer **1712** (or in lieu, not shown, a USB battery pack) to power it up if no power is available from smart phone **1714**, as indicated by lack of a light on display **1606**, it is then used, as described throughout this disclosure.

(128) FIG. 18 shows a detailed overview of an exemplary system **1800** for updating software in device **1601** to enable connecting it to a mobile communication device **1714** for which it does not have information, according to one embodiment of the system and method disclosed herein. In FIG. 18, computer **1712** is typically a PC with USB and Bluetooth connectivity running phone data transfer applications such as PC Suite, PC Tools and other phonebook transfer applications, which typically may connect one or two handsets, such as the handset of a device under test (DUT) **1714** as shown in FIG. 18. These connections are typically made via USB cables **1711** and **1713**. Computer **1712** has its own operating system **1802** with software **1803a-n** and data sets or embedded operating systems **1804a-n** (not shown) for execution on SOC **1701** in device **1601**. This data may contain all kinds of information, including, but not limited to, address book data, phone numbers, email addresses, pictures, video clips, and other types of data that may be used by cell phones and their applications. In some cases even the applications or the application data may be transferable. Typically computer or machine **1712** would have its own operating system **1802**, which has multiple programs **1803a-n**, including a probing/programming application **1803x** (not

shown separately).

(129) Often computer **1712** with operating system **1802** and programs **1810b** (not shown) is actually a standard PC, and as such it often has lots of other, not relevant software as well. It can combine DLLs, data tables, and configuration data **1804aa-nn** for most phones **1714** to which it may be connected via unit **1601**. These data tables and configuration data also contain an identification of combinations of programs and drivers that are known to be functional, as well as combinations that are known to have problems. Thus the table can indicate the existence of problems. If a driver is not supported, a new configuration is prepared and loaded into device **1601**, as described later in more detail. Operating system **1710a** of unit **1601** is typically an embedded type, such as Unix, Linux or some other, similar embedded, dedicated system. It uses certain programs **1710b a-n**, and they use drivers or driver tables **1710c a-n**. Driver tables, in this example, enable a device to use a formulaic driver, instead of a device-specific driver, said formulaic driver using tables and scripts that provide the actual driver functions for the specific device. Thus a single software instance may offer drivers for a variety of devices. However, no matter how diligently a formulaic driver is designed, the number of drivers in the device may be limited by the capacity limitations of memories **1706** and **1707**. Additionally, as novel smart phones **1714** appear in the market that are not supported by the existing drivers **1710c a-n**. Computer **1712**, which connects via cable **1711** to unit **1601**, has its own operating system **1802**, typically a Windows or Linux operating system, and it has an application **1803x** that contains an enclosed environment **1803y** that can assemble and create new operating environments for unit **1601**, including but not limited to the embedded operating system and its drivers. Thus computer **1712** creates a new image in its internal memory **1810**, and then the image is transferred to a flash memory, such as, for example, external memory **1708** in unit **1601**, and from there the internal memory **1706** (not shown here) can be used to reprogram itself and/or internal memory **1707** (not shown here, but shown in FIG. 17). This image transfer and reprogramming enables the system to very easily reprogram the firmware in USB key **1601** to adapt to new devices that have not previously been supported. Computer **1712**, in turn, can connect via Internet **1801** to expert system as explained in the discussion of FIG. 13, previously, at step **1303**, which has access to all the databases of all the drivers and formats for connecting to devices. To identify new communication devices, such as device **1714**, the system can switch unit **1601** into transparent mode, enabling the more powerful software in computer **1712** to probe device **1714**, to determine its model and possibly the parameters needed to parameterize new drivers. The system can then store those new drivers and/or tables in tables **1804**, report them back to **1303** for its database, and then recreate a new environment in memory **1810** that can be reflashed into key **1601**, which from now on can service device **1714** independently, without connecting to computer **1712**. In some cases, however, key **1601** may still need a power supply device, such as a USB battery, to supply power if the device **1714** cannot supply sufficient power to operate the processor **1701** and other items in key **1601**. Further, in cases where no suitable driver and/or table is present, by downloading an additional diagnostic program **1803z** (not shown separately) that supports additional manipulation and tests beyond programs already present in **1803a-n** and/or drivers and tables in **1804aa-nn**, newer smart phones can be added to the capabilities of device **1601**. As a result of having a large library of DLLs (or drivers, used interchangeably here) almost any data transfers between two different phones can work. The computer **1712** can, by using the available drivers and tables, communicate via device **1601** with smart phone **1714** and test download of data objects (each item typically comes down as one or more data objects from the phone), and thus identify the correct combination, which is then stored in memory **1810** of computer **1712** temporarily and eventually sent on to device **1601**, as described later, enabling it to connect the phone **1714** by itself, for backing up data objects, without use of a computer **1712**. Each of these devices may have a CPU and memory, both volatile and nonvolatile, and thus each can form a small, distinct computing device.

(130) FIG. 19 shows an exemplary process 1900 for updating software in a device 1601. In step 1901, the system switches unit 1601 to transparent mode. In step 1902, computer 1712 probes mobile communication device 1714 (via device 1601, which is now transparent) to determine its model and possibly the parameters needed to parameterize new drivers. In step 1903 the system looks up the identity and drivers of device 1714 on both local computer 1712 and a remote expert system, as explained in the discussion of FIG. 13, previously, at step 1303. In step 1904, the system creates a new embedded operating system for device 1714 with drivers 1710a-n. In step 1905, the system switches unit 1601 to programmable mode, and in step 1906, it then transfers the newly created operating system and drivers to unit 1601. In step 1907, the device 1601 is reflashed, meaning that part or all of the content of the software section of one or more of its nonvolatile memory units (typically, but not always flash memory) is reprogrammed with the downloaded data from step 1906, making the change definitive. In step 1908, the system restarts the operating system of unit 1601, and then the process terminates.

(131) FIG. 20 shows an exemplary process 2000 for backing up data from a mobile communication device, such as device 1714, according to one aspect of the system and method disclosed herein. In step 2001, unit 1601 begins operation. In step 2002, unit 1601 determines whether it contains information about the identity of device 1714. If it does not (no), the process moves to step 2003, where it displays a message indicating that it cannot identify device 1714. In step 2004, unit 1601 checks to determine whether it is connected to a computer, such as computer 1712. If it is not (no), unit 1601 displays an error message and the process moves back to step 2001, as it has no useable input (besides power) or output to perform any tasks. In some cases, it may wait for user input before continuing back to step 2001. If in 2004, unit 1601 detects that it is connected to a computer (yes), the process moves to step 2006, where the system executes process 1900, described above, and the process ends at step 2007. If in step 2002, unit 1601 determines that it does contain information about the identity of device 1714 (yes), the process moves to step 2008, where unit 1601 displays a message asking the user to choose whether to back up data from device 1714 (A) or restore data to device 1714 (B). If the user elects to back up data, in step 2010 unit 1601 backs up data from device 1714 and the process ends at step 2007. If the user elects to restore data, unit 1601 restores data to device 1714 and the process ends at step 2007.

(132) It is clear that many modifications and variations of this embodiment may be made by one skilled in the art without departing from the spirit of the novel art of this disclosure. For example, the device 1601 may be used with computers 1712 that do not have special software installed by mimicking a flash USB drive, and enabling them to exchange information by reading and writing both by the computer 1712 and processor 1701 to and from that drive. In some cases, the drive may present a section with software that can be installed on a guest computer 1714. In yet other cases, the device 1601 may present itself as both a USB drive and a CDROM with auto-launch, to install software, or to connect to a Website, from which software can be downloaded and installed etc. These modifications and variations do not depart from the broader spirit and scope of the invention, and the examples cited here are to be regarded in an illustrative rather than a restrictive sense.

(133) What is needed is a system and method that enables the parallel programming of many handsets. One of the biggest problems is that the USB connection used by most software for reprogramming handsets has largely unknown limitation: At any given time only one USB device is connected to the host controller and thus to the host. Therefore, if a USB device sends a request while the host is talking to another USB device, that request may be lost. Generally, the device is expected to re-transmit by itself, which is not a problem in normal operating mode; however, often during reprogramming only a very reduced, basic I/O system is available, akin to a bootstrap ROM with very limited capabilities. As a result, if multiple handsets or mobile communication devices, both of which in this example are USB devices, are programmed concurrently, often some “hang up” and the process must be restarted. This hang-up and the associated loss of time and productivity is the result of lost communication packets between the host and the (mobile

communication) device being reprogrammed. The way to avoid these frequent packet losses and restarts is to give each USB device its own USB tree with its own USB host controller. The host controller is then dedicated to that device only, and it has the ability to buffer commands before they continue to travel through the PCI bus and into the CPU.

(134) FIG. **21** shows an enhanced system **2100**, according to one aspect of the system and method described herein. System **2100** has a PC **700** (similar to the computing system described in the discussion of FIG. **7**), which has an additional enhanced PCI bus/motherboard. Two PCI bridges **2102a** and **2102b** expand the number of available slots for USB peripheral devices such as mobile communication devices, providing up to 18 such slots. Such computers with up to 18 slots are manufactured for uses such as co-location by telephone companies. For example, 16 USB cards, each of which can handle four phone lines at a time, could be plugged in.

(135) In the case of the system and method disclosed herein, a multitude of PCI cards may be plugged into the available PCI slots **2102a** and **2102b**, such as, for example, PCI card **2206**, shown in FIG. **22**. That PCI card **2206** has a typical PCI USB controller chip **2201**, which on one side connects to the PCI bus **2103**. In this example, PCI card **2206** also has five USB ports, **2205a-n**. Typical for PCI cards are five USB ports, one USB host controller **2202** for USB 2.0, and one or two host controllers for USB 1.0 hubs **2203a**, and in some cases **2203b**. Two USB 1.0 hubs are necessary because in USB 1.0 architecture, each node typically can only address four nodes, and because the card has five ports, at least one port must be addressed by a separate host controller. Cross-matrix **2204** enables the correct connection and selection of the active port(s) to the respective host controllers. Because this exemplary PCI USB controller chip **2201** has two USB 1.0 host controllers, in the case of programming mobile communication devices **2210a-n**, which use USB 1.0, two such devices can be programmed concurrently, as long as each device connects to its own host controller **2203a** or **2203b**. This approach avoids the loss of communication packets. Because in that configuration, once installed and set up, cross matrix **2204** does not change, it therefore maintains a dedicated connection from each device **2210** to each host controller **2201**.

(136) FIG. **23** shows an enhanced USB PCI card **2301**, which has its own PCI-to-PCI bridge **2102**. It creates an internal PCI bus **2303**, on which multiple PCI USB controller chips **2302a-d** are shown. (Typically a PCI segment is limited to four loads.) Each PCI USB controller chip could, using the same architecture described in above in the discussion of FIG. **22**, provide two active ports, **2305a-n**, thus supporting connection of up to eight USB devices (mobile communication devices), such as devices **2210a-n**, to one PCI card. Using this type of card, the capabilities of even a standard office computer, for example, with typically four to six available PCI slots, can be extended. The upper limit of the total number of USB devices in a system is currently **127**. Because the motherboard typically contains three to five USB devices and each USB host controller, such as **2202** or **2203**, count as one as well, each PCI USB controller chip uses three USB identifiers for itself, limiting the total number available for external USB devices. Also, often system peripherals, such as a sound card, web cam, keyboard, mouse, etc. may be connected through a USB hub and therefore further reduce the number of available USB identifiers. All these uses of USB identifiers must be taken into consideration when calculating how many mobile communication devices can be handled simultaneously by one computer.

(137) FIG. **24** shows an overview of an exemplary system **2400** for enhanced diagnostics according to one aspect of the system and method disclosed herein. The devices under test (DUTs) are client devices **2401a** and **2401b**. DUT **2401a** connects to the Internet **2410** via wireless connection (over a network, not shown). DUT **2401b** is connected to a computer **2402**. Software instances **2421a** and **2421b** are testing DUTs **2401a** and **2401b**, respectively. Also, software **2422**, such as interconnectivity software or a special driver, may reside the desktop computer **2402**. Between Internet **2410** and load balancer **2405** is a firewall **2409**. Often the firewall and the load balancer may be combined. Also shown is a main diagnostic server **2406**, which in this case is exemplary of one or more servers. Server **2407** manages a diagnostic database. All servers **2406** and **2407**

contain, respectively, software **2436** and **2437**. Similarly, customer (i.e., carrier) systems **2408a-n** contain software instances **2438a-n**. Diagnostic server **2406** may download diagnostic and background data as well as any other related data into server **2404**, which may be a local server in the domain of a network provider. Server **2404** contains software **2424**, which is a partial or full copy of the system and/or the data downloaded from server **2406**, or any of its connected servers. Administration console **2403** may connect to one or more server(s). Typically, console **2403** would not require special software to connect to said server(s), because web interface software could be used, requiring only a web browser. In some cases, however, special client software (not shown) may be downloaded from one of the servers, or a special browser plug-in may be downloaded to enhance performance and reduce overhead during operations.

(138) FIG. **25** shows an exemplary process **2500** for implementation of the system according to one aspect of the system and method disclosed herein. In step **2501**, the user launches the diagnostic application and screen **2511** opens, wherein the user may select from a list the particular application with which he needs help. In step **2502** the system checks if there is an item in the list on the screen, and may have an “Other” field in the list, or in a different menu for the problem application. If not, in step **2503** the system asks the user what the problem is. If it turns out to be that the application exists, the system branches to step **2505**. If there is no app, the process continues to step **2504**, where it suggests analysis steps outside the automatic venue. The system then continues on to step **2507**, where it performs a soft reset of the device. In step **2505**, the system updates the problem app. If the problem is solved, the process moves to step **2513**, where the system sends the results to the knowledge database. If the problem is not solved, the process moves to step **2506**, where the system deletes the application and checks whether the problem is solved. If yes, the process moves to step **2513**. In those cases, the offending App can be deleted as part of a trial remedy to resolve an error. If after deletion it was found the App was not part of the problem, then the App would need to be restored. Data backup and subsequent restore could for example, and may be employed in several sections and not necessarily as in this exemplary order. If the problem is not solved, the process moves to step **2507**, where the system performs a soft reset of the device. If the problem is solved, the process again moves to step **2513**; if the problem is not solved, the process moves to step **2508**, where the system performs a data backup and then moves to step **2509**, where it updates the device firmware. If the problem is solved, the process moves to step **2511**, where the system restores the data; if the problem is not solved, the process moves to step **2510**, where the system performs a hard reset. If the problem is solved, the process moves to step **2511**, where the system restores the data; if the problem is not solved, system notes the failure but still moves to step **2511** and restores the data. After restoring the data in step **2511**, the system in step **2512** suggests a visit to a repair center, and again in step **2513** sends all results, via either wired or wireless communication means, back through the cloud to the knowledge database.

(139) FIG. **26** shows an overview of the data flow **2600** as it is analyzed. The initial “eTicket” data **2603** (electronic Ticket or error report) is analyzed in the device **2401a** or **2401b** respectively by some local software. If that software cannot determine the nature of the problem, the investigation is escalated to the field knowledge database **2602**. If that examination does not yield a clear conclusion, the device log data **2601** is pulled into the main diagnostic server **2406** and further analyzed there.

(140) FIG. **27** shows an overview of an exemplary typical screenshot **2700**, according to one aspect of the system and method disclosed herein, which screen would appear in response to a user request for troubleshooting assistance or in response to a data analysis software conclusion that a problem exists. Screenshot **2700** offers the user a selection of options **2701a-n** for investigation. For example, if the user selects option **2701a**, the battery issue, another screen opens, as shown in FIG. **28**.

(141) FIG. **28** shows an overview of an exemplary typical screenshot **2800**, according to one aspect of the system and method disclosed herein. At the top of the screen is an array **2801** of basic

information about the device and its functions, such as, for example, its network and its battery. A list **2802** of functions that use battery power and that may be enabled or disabled is presented. Also shown is an option to control brightness level in bar **2803**. Screen timeout selections **2804** let the user select the duration of screen illumination after any activity. One or more button(s) **2805** let the user move to the next step in the process. Additional buttons (not shown) may let the user test new settings or selection other options.

(142) FIG. **29** shows an overview of an exemplary typical screenshot **2900**, according to one aspect of the system and method disclosed herein, which may open if the user selects a GPS option. Screenshot **2900** shows a map of a selected area. Again, array **2901** shows basic information about the device and about this particular function. Map **2902** shows the selected map, with face icon **2903** representing the user's location and star **2904**, the desired destination, typically in this use, the nearest available service location.

(143) FIG. **30** shows an overview of an exemplary typical screenshot **3000**, according to one aspect of the system and method disclosed herein, which shows the user that the diagnostic program recommends a firmware upgrade. Again, array **3001** shows basic information about the device and about this particular function. Message **3002** informs the user of the recommended action and give some of the findings of the diagnostic software, and button **3003** prompts the user to start the recommended action. Starting a firmware upgrade may include such system actions as checking that reception quality is adequate, that the user is not driving or flying, that battery level is adequate to complete the task without crashing during the process, and that there is enough space in the device's flash storage to ensure that user information is not overwritten. In some cases, the system may back up user information over the network before beginning the upgrade.

(144) FIG. **31** shows an overview of an exemplary typical screenshot **3100**, according to one aspect of the system and method disclosed herein, of the type that the system may display to the user on the device during the firmware upgrade. Graphic **3101** indicates that new firmware is moving onto the device, while progress bar **3102** shows the user the progress of the operation.

(145) FIG. **32** shows an overview of a system **3200** for identifying software-created problems and operational disruptions in smart phone computing devices and other mobile computing devices with cellular connections, such as, for example, tablets, etc., according to one aspect of the system and method disclosed herein. However, mobile devices with any type of data connection (cellular, WiFi, bluetooth or other wireless communications) should be considered possible devices upon which to use the systems and methods described herein.

(146) The system comprises social networking sites SNa-SNn **3201a-n** and technical forum sites FSa-FSn **3202a-n**, all of which sites may be searched by a type of web-site scanning software known in the art as a "spider." In this example, two different spiders SN **3203** and FN **3206** search the two types of sites **3201a-n** and **3202a-n**, respectively, because each spider has been optimized to search its respective type of site. Thus spider **3203** is optimized to search social networking sites **3201a-n**, which sites may include, but are not limited to, such social networking sites as Facebook, Twitter, Myspace, LinkedIn, etc. Similarly, spider **3206** is optimized to search technical forum sites. Spider **3203** has a list **3204** of sites to visit and a list of templates **3205**, each template being designed for a particular site or site subset to optimize the extraction of data from each site.

Extracted data is then stored in data store **3210**. Similarly, spiders **3206** and **3209**, which may be copies of essentially the same software running in different specialized configurations, or may be completely different versions, use site list **3207** and template set **3208**, respectively. Both the list and the template set may be amended as needed over time, typically manually, although automatic amending of their data in whole or in part is contemplated within the scope of this invention. When data is collected in data store **3210**, the system applies a filter **3211**, which filter removes irrelevant data and organizes the relevant data by such criteria as phone make, model number, etc., creating a list of harmful combinations of model IDs, OS versions, and other device characteristics that in conjunction with one or more programs negatively impact the user experience. The organized data

is then stored in data store **3212**. In an embodiment, the system then can sort the data into types of faults and problems and try to identify software that users blame for operating faults and unsafe operations.

(147) FIG. **33** shows an exemplary process **3300** for data retrieval and analysis by system software running on a computer or server, as described above and throughout, according to one aspect of the system and method disclosed herein. In step **3301** the system starts the scanning at a specified time. In some cases, the system may continually be scanning web sites; in other cases, the system may scan at preset intervals such as, for example, once a day, once a week, at particular times, or upon the occurrence of a particular event. Some web sites have rules about the specific number, size, and/or frequency of visits or downloads allowed to site scanning software or so-called robots, and these are typically specified in a robots.txt file at the root directory of a site or subsection. Such site-specific rules are recorded in templates **3205** and **3208**. In step **3302**, the system retrieves its lists **3204** and/or **3207** of sites to scan, and in step **3303** it applies the templates **3205** and/or **3208** to the listed sites.

(148) With continued reference to FIG. **33**, in step **3304**, the system retrieves from data store **3350** a list of phones for which it should particularly look on the object sites. In an embodiment, this list is user-generated or based on error reports found at a scanning site, where incoming suspect devices are scanned for trouble. Further, in some cases, the list may be manually extended based on inquiries from field support, for example in stores, as well from reports in call centers, etc. The list may be updated whenever required automatically as reports about phones that are not yet listed as having problems reach a certain level or frequency, or manually when suggestions to add certain phones are made to the system operators. In step **3305** the system reads all the scan logs and extracts all the hits. In step **3306** the system applies filters, such as filter **3311**. Various types of filtering criteria may apply; for example, responses that don't identify the problem phone specifically enough or snide comments and other inappropriate language may be removed. In step **3307** the system flags elements of interest for review. If the issue is clearly of interest (above a certain relevancy level) the system may book it directly. If the relevancy level is not high enough, but above a predetermined relevancy level so as to be of potential interest, in step **3308** the system presents the issue to a technician or other suitable person for manual review. In step **3309** the system operators review and resolve the presented issues, and in the **3310** the process ends, to begin again either immediately or as scheduled.

(149) FIG. **34** shows an overview of a system **3400** for reprogramming phones according to one aspect of the system and method disclosed herein. A mobile computing device or smartphone **3408** initially contains standard code **3409** and a storage **3410**, such as, for example, a micro SD card. Device **3408** is connected to a network **3401** of a carrier. Typically, the phones can be activated by users by dialing a USSD (unstructured supplementary services data) number (or sequence) and entering some codes accordingly. Typically, a single USSD number connects to the carrier's activation number, and then once the connection is established, the USSD essentially establishes a two-way data connection, similar to a USB connection, over the air, enabling the phone to be reprogrammed under control of a server. Because the USSD number is entered like a number, it often is redirected by a DNIS (Dialed Number Identification Service) server, which resolves the destination number, for instance, server **3402**, and then redirected to the USSD server. By using a specially for the purpose described herein setup, nonstandard USSD number or a nonstandard phone number, the initial dialed call or connection can be redirected to an external server such as **3404**. That server contains multiple software applications, including an operating system, such as **3405a-n**, and other programs as described herein. Further, storage **3406** also contains objects **3407a-n**, where the objects are pieces and complete assemblies for over-the-air (OTA) programming of phones, as discussed throughout and later.

(150) FIG. **35** shows an exemplary process **3500** for programming any one of multiple phones, according to one aspect of the system and method disclosed herein. In step **3501**, a phone is turned

on, and in step **3502**, a “need to activate” message appears on the phone display. In step **3503** a user, who may be a technician or even an end user to whom a particular phone is or was assigned, further discussed herein, enters the special service number, which number may be, for example, a USSD number or a special phone number for activating the phone. By calling the number, an activation request is sent via transmission **3504** to USSD gateway **3505** for treatment. USSD gateway **3505** typically may be part of the cellular network DNIS server, such as server **3402** (not shown here). In some cases, USSD gateway **3505** may be a separate server, depending on the configuration of the carrier. The transferred request is then redirected via transmission **3506** to server **3404**, which contains the OTA images, further discussed herein. In step **3507**, the system prompts the user to enter an ID that contains the enterprise customer ID, the user ID, and/or the password. This data is sent via connection **3508**, where the connection is typically as USSD type of connection, to server **3404**. Server **3404** then delivers, via transmission **3509**, the OTA image or package. In step **3510**, the phone receives the OTA package (also referred to as a software module), where the package or module is typically a standard part of the basic phone setup. In step **3511**, the package installation is executed. The type of installation may vary: it may be a simple overwrite of the ROM programming, or it may be a multi-step process that requires more than one reboot of the phone software. In one embodiment, this process continues largely unattended because the package may be put into the storage device of the phone (such as an SD card or other storage device commonly used in such phones), so that the phone may reboot several times without requiring user interaction. In step **3512**, the phone is finally reprogrammed, having rebooted as many times as required, and in step **3513**, the phone is ready for use. It is now programmed for its user, with password, account, etc., all preconfigured. The account may include setups for email, control, internal extensions and other customer phone book entries, and other, similar account data.

(151) FIG. **36** shows an exemplary process **3600** for creating an OTA phone reprogramming package, according to one aspect of the system and method disclosed herein. Process **3600** may be applied to a single phone, multiple phones in one enterprise, or even multiple phones of multiple enterprises. In step **3601**, the system is started. In step **3602**, a user or technician selects a phone model. In step **3603**, the programmer selects group data, which may include any data to be programmed on all the target phones of a group. Typically, such data, for an enterprise customer, could include an IP PBX extension for the enterprise, so the phone is an extension of the IP PBX. Such programming may require installation of additional software, as well as certificates or other credentials to access the particular phone switch. In step **3604**, user data is either entered or selected. Individual user data could, for example, be provided by the technician to that package, often in a table or spreadsheet format that is automatically processed and then applied to the data on a one-package-at-a-time basis for the whole list or table. In step **3605**, for each phone, a combination package is created, where the package contains one or more of the group data, the individual user data, the carrier data, and any other libraries or additional information needed or desired. In step **3606**, that package is stored, with its credentials, in the storage unit of server **3404**. This data in the tables or spreadsheets and thus the package with credentials now includes the ID and password described previously in the description of step **3507** of FIG. **35**. The ID and password are used to identify and to secure access to the package. In step **3607**, one or multiple messages, such as, for example, message **3608**, are sent to a technician who is charged with delivering or setting up the phones. The technician or phone user would then execute the process described in the discussion of FIG. **35**, above. After delivery of the message, the process ends in step **3609**. Both the package describe above, in the discussion of FIG. **36**, and part of the program likewise described previously in the discussion of FIG. **35** are stored on server **3404** as part of the software mentioned in the discussion of FIG. **34**, as programs **3505-x1** through **3505-x2**, within the range a-n.

(152) FIG. **37** shows an exemplary overview of a system **3700** for routing calls according to the system and method discloses herein, based on an automatic diagnosis performed as described earlier. Diagnostic system **2400** was discussed in great detail earlier, in and around the description

of FIG. 24 and in other related parts, and databases 2601 and 2603 contain the results of the data collected by system 2400. Now if a user calls, for example, from any of devices 3711a-n through an Internet and/or phone network connection 3710, such as a standard telephone network, the user ends up getting connected with router/switch 3712 that can route all sorts of phone calls and combinations of phone calls, such as, for example, analog phone calls, wireless phone calls, IP phone calls, and other, similar phone calls. Router/switch 3712 is controlled by processor 3714, which has storage 3715 and programs 3716a-n, some of which are discussed further below. Also present, but not shown for reasons of clarity and simplicity, are a variety of interfaces to couple said router to all networks required to perform its tasks, memory to execute code for programs, operating system, etc., as well as input and output devices, etc. Programs 3716a-n may include such software instances as an operating system, drivers, etc., as may be necessary to control the router/switch. Interactive voice response (IVR) software 3713 may be controlled directly by processor 3714 or through router/switch 3713. When calls arrive they are processed and then routed to call center 3720. There are many different call center topologies, but for purposes of clarity and simplicity in this discussion, any and all call center types are shown here only as exemplary cloud 3720. Call center stations 3712a-n each typically have a workstation with communication and data display devices 3721a1 and 3721a2, and an agent 3721a3.

(153) FIG. 38 shows an exemplary overview 3800 as an example of use of the system and method disclosed herein, wherein a customer 3821 with a device 3822 goes to a customer service location 3820, such as, for example, a store. Said customer may speak to a store agent 3823, who may use a station 3824, which station may be any of a great variety of devices, such as, for example, a kiosk, a pad, a workstation, or any other such device. Alternatively, station 3824 may be designed so that the customer can use the station by himself, without help from any agent 3823, in a manner similar to self-service at, for example, an airport self-check-in station or a grocery self-service check stand. Such an approach may enable one agent 3823 to assist multiple customers, for example, five or even ten customers, at any one time. Station 3824 could typically be a complete computer with its own processor, local storage, memory, input/output subsystem, communication interfaces, etc., said interfaces coupled to a network, so station 3824 can access diagnostic system 2400 and access information stored on databases 2601 and 2603, looking up information for the customer's device 3822 and then delivering remedies.

(154) FIG. 39 shows an exemplary process 3900 for diagnostic services at a call center, according to one aspect of the system and method disclosed herein. Incoming call 3901 is received in step 3902. In step 3903 the system checks for some customer identification. If the system does not detect any ID (-), the call is routed in step 3904 to the IVR system 3713, which queries the customer or the device itself for some identification, such as a phone number, an account number, etc. Upon receiving some ID in step 3904, or if the system receives an ID (+) in step 3903, the process moves to step 3905, where the system checks with main data repository 3920, or it may also pull from repositories 2601 and 2603, the event history of the device. In step 3906 the IVR offers any solution or solutions, based on information about the problem found and identified in the data repositories, or it may connect the caller to a specialist to help resolve the issue. Because each and all problems may have many different possible solutions or outcomes, they are all exemplarily shown as sections 3907a-n, each of which may have multiple steps. At the end of all steps 3907a-n, the call ends in step 3908. Step 3908 may also include a quality and satisfaction survey offered to the caller at the end of the call.

(155) FIG. 40 shows an exemplary process 4000 for customer service at a telephone diagnostic location, according to one aspect of the system and method disclosed herein. Customer 4001 enters the location, and in step 4002, customer identity is determined, typically by his phone number, either by a service agent or technician 3823, or by the customer entering information at a self-service station 3824, as described above in the discussion of FIG. 38. The phone number is transmitted to data repository 3920 and/or databases 2601 and 2603. In step 4003, the phone

number is used to retrieve the international mobile equipment identity (IMEI) of the phone. In step **4004**, the IMEI number is used to retrieve problem solutions, based on known problems of identical or very similar phones. In step **4005**, the system verifies with the user that the problem retrieved from the database is indeed the problem the user identifies. In step **4006**, the system instructs the user to implement the solution(s) for the identified problem or calls an agent for help, in cases such as, for example, where the device needs to be exchanged. Step **4006** may involve one or more of many various solutions, based on the verified problem. In step **4007**, the process ends.

(156) For problem-solving, a server may receive a code from a phone over a wireless connection before the user activates the phone. In response, the server may guide customer requests for service to an appropriate resource. If the customer requests help from a specialist, the customer may be transferred directly to a specialist group. Or the customer may be directed to a self-help resource where he can address the problem by himself. In some cases, the customer may go to a service location, where his phone number may be used to direct him to a local resource. At the service location, a local network may identify the customer, display a greeting on a video output device, and direct the customer to a local resource. The local resource may be a kiosk device connecting to the customer's phone either by wire or wirelessly, or it may be a queue for a local or remote specialist.

(157) What is needed is a system and method by which sufficiently large currents can charge a large number of dead devices concurrently, thus enabling efficient mass processing of such devices in, for example, such situations as described above. Because even high-power hubs and computer boards typically limit the current to 2 A to 5 A total for all ports shared, an additional power source is needed. Further, a smart switch needs to be added, connecting the power leads of a connected device, commonly referred to as a device under test (DUT), to an external source, until the charge level has been reached for sufficient functionality to begin the test or use of said DUT.

(158) FIG. **41** shows an overview of an exemplary system **4100** according to one aspect of the system and method disclosed herein. A smart communication device (DUT) **4105** needs to undergo diagnosis by software on computer **4103**, which may be a standard PC or any other, similar suitable computing device. The system has three modes of operations.

(159) In the first mode, when battery capacity of DUT **4105** is below the power-on threshold, that is, when the user is unable to turn on the device by activating the power switch, a technician first plugs DUT **4105** into iRT (information reading tool) and charger **4101** via cable **4106**, which is typically the standard charger cable for the DUT and has a connector at one end that is compatible with the power charging connector on DUT **4105** and at the other end a standard USB connector for connection to iRT charger **4101**. Charger **4101** performs a fast charge on the DUT (typically using one of the analog USB charge protocols), drawing power via power cable **4104** from a standard ac power adapter **4107**, which adapter **4107** is able to supply a fast charge to the DUT **4105**. After DUT **4105** is able to power on and boot its operating system, iRT charger **4101** connects device **4105** to PC **4103** (or some other suitable device, including a possible intermediate USB switch, not shown for clarity) via standard USB cable **4102**.

(160) In the second operating mode, DUT **4105** is simply in a power-off state, with the battery above the power-on threshold. In this mode, the technician plugs the device into the charger as described above and waits for the device to turn on and boot its operating system. Then iRT charger **4101** connects device **4105** to PC **4103** via standard USB cables **4102** and **4106** and iRT charger **4101** stands by.

(161) In the third operating mode, DUT **4106** is already powered on. In this mode, the technician plugs device **4105** into iRT charger **4101**. The charger then connects the device to the PC as described above.

(162) FIG. **42** shows a simplified view of the interface board **4200** of charger **4101**. Outlet **4201** connects to an external wall charger. It has two low dropout (LDO) regulators **4202** and **4203** to

create internal supply voltages of, respectively, 3 volts and 5 volts. Typically the voltage of LDO **4202** may be 3.3V, but in some cases it may be 3V. Microchip **4204**, such as, for example, PIC16F1782, may be used as a system controller. USB Type A plug **4205** connects to PC **4103**, and USB Type A receptacle **4206** connects to DUT **4105**. A USB switch **4207**, such as, for example, MAX4906, connects the two USB outlets **2405** and **4206**. Signals from microcontroller **4204** control switch **4207**. Also connected to switch **4207** are a digital potentiometer and a digital-to-analog converter (DAC) in Integrated Circuit (IC) **4208**, enabling detection of and response to analog charging signals on the USB channel from the DUT plugged into receptacle **4206**. The signals are sent to the processor, where software is used to control this charging process, etc. as described below in greater detail. Voltage controller **4208**, which may be a dual DAC MCP47A1 or digital potentiometer MCP42xx, can be used to create a controlled voltage and finely adjust the voltage. In some cases, microchip **4204** may be a type that contains an integrated DAC and/or the comparator **4209**, etc.

(163) FIG. **43** shows an exemplary overview **4300** of the subroutines in microprocessor **4204**, according to one aspect of the system and method disclosed herein. In subroutine group **4310**, after the power-up housekeeping process **4307**, in process **4301** module M1 is initialized. Then in process **4302**, module M2 detects the DUT status, that is, whether the DUT is on, off, without battery power, etc. Module M2 then interacts in process **4303** with charging module M3 to charge the DUT, if charging is required. When the device no longer requires charging and is powered up, in process **4304** module M4 attempts to synchronize with the DUT. Group **4310** remains in process **4304** until the DUT is unplugged, when it then returns to process **4301**. Group **4311** contains process **4305**, a UART interrupt module M5 for interaction with processes **4301** through **4304**, to move the processes from one to the next. Also in group **4311** is process **4306**, wherein module M6 supplies a timer tick in case of a timer that needs to be serviced, for example, to look at the time-out in certain USB protocols, etc.

(164) FIG. **44** shows an exemplary process **4400** in module M1 as it relates to process **4305** in module M5, according to one aspect of the system and method disclosed herein. In step **4401** the system attempts to send a character output. The characters are sent on the USB channel to communicate with the DUT when it starts up. In step **4402** the system checks to verify that the character output can be sent. If Yes, then in step **4403** the system starts with outputting a character from the UART and then ends the process in step **4404**. If NO, the process moves directly to step **4404**, where it ends.

(165) FIG. **45** shows an exemplary process **4500**, detailing the steps of process **4301** in module M1, according to one aspect of the system and method disclosed herein. Upon the power-up step **4501**, the LED is turned on in step **4502**. Then in step **4503** the system executes a reset clear to ensure that all the memory is in a set position and all the outputs except the LED are off. In step **4504**, the system checks the start reason to determine if this is a normal start, and which peripherals are connected or not. Then in step **4505** the system is initialized by setting all the parameters in accordance with the findings of step **4504**. In step **4506** the WD (watch dog) is reset. If the WD reset occurs, an "a" is sent in step **4507** just as a check to indicate whether the command went through, and then the process moves to step **4508**, where the CPU app is started. If the WD reset does not occur, the process moves immediately to step **4508**, where the CPU app is started. In step **4509** the system passes control to module M2.

(166) FIG. **46** shows an exemplary process **4600**, detailing the steps of process **4302** in module M2, according to one aspect of the system and method disclosed herein. In step **4601** the process starts, and in step **4602** an E character is output, just as a check to indicate whether the command went through. In step **4603**, the system checks to determine whether the query table is over. If Yes, the process enters fast-charge mode **4604** and then enters charge mode M3 in step **4605**. If No, in step **4606** the system attempts to initialize the DUT, and in step **4607** the system checks to determine whether the DUT has reached minimum charge Dp. If Yes, the process moves to step **4608** where it

outputs an F character. Then in step **4609** it waits for the response, a g character. If no, the process moves to step **4610**, where the system outputs an F character and then in step **4611** sets the USB to a specific setting for an analog charge. Then in step **4612** the system outputs a G character. At the end of the process **4605**, the system moves to charger module M3.

(167) FIG. **47** shows an exemplary process **4700** for the subsection M2-1, which is a branch of the original module M2, discussed above. Process **4700** attempts to determine whether a DUT is connected. It executes continuous loops, with delays, in seeking to make a connection. In step **4701** the system tries to detect a DUT is connected. Upon detection, in step **4702** the system outputs a 3 character and connects to the 5V power source. In step **4703** the system checks the 5V connection and prepares the analog-to-digital converter (ADC). In step **4704** the system sends a 4 character and continues to seek a response. In step **4705** it reads the ADC value to see the load. In **4706** it checks the load value to see a clear voltage drop, which indicates a load. If there is no drop, it branches to step **4707**, starts a delay and retries to connect to a device. If it sees a drop, it goes to break **4708** and then continues to M2_2, starting in FIG. **48**.

(168) FIG. **48** shows exemplary process **4800** for subsection M2-2, which is a branch of the original module M2, discussed above. (M2-1 and M2-2 both belong to M2.)

(169) At step **4801** the system starts the D+ signal for data transmission on the USB port, and then in step **4802** it outputs an 8 character onto the USB channel. In step **4803** the system disconnects the D+ and D- signals and the 5V line and starts a 300 millisecond (ms) delay. In step **4804** the system powers on again and then outputs a 9 character. In step **4805** the system checks the D+ signal and prepares the ADC. In step **4806** it reads the ADC value, and it outputs an A character in step **4807**. In step **4808** the system determines whether the ADC value is greater than 2450, that is, 2.4 A of charge current (ADC value for mode switch). If the charge current is not greater than 2450, the process moves to step **4810**, where the system outputs a D character and returns a FALSE value, meaning the DUT is not connected. If the charge current is greater than 2450, in step **4809** the system outputs a C character and returns a TRUE value, meaning a device is connected. After either step, **4809** or **4810**, the process moves to step **4811**, where a B character is output. Characters are output to a debugging log via UART port.

(170) FIG. **49** shows an exemplary process **4900**, detailing the steps of process **4303** in module M3, according to one aspect of the system and method disclosed herein. In step **4901** module M3, the charging module, starts. In step **4902** the subroutine initializes. In step **4930**, the system seeks a query table. If no query table is found, the process moves to step **4912**, where it outputs a zero and executes a break. After the break, it moves to step **4913** where it charges the DUT. If, in step **4930**, a query table is found, it continues to step **4903** to read the USB value. In step **4904**, the test may be delayed. In step **4905**, it checks to see if the DUT is disconnected. If yes, it moves to step **4913**, where it charges the DUT. If there is no disconnect, in step **4906** a b character is output, and in step **4907** the system detects current. In step **4908** it checks to determine if the current is maximum tested. In step **4910** the system checks to see whether the DUT current is greater than the defined current. Then in step **4911** if the DUT current exceeds the defined current, the process loops back to step **4930**; while if the DUT current does not exceed the defined current, it moves to step **4911**, where the index is received and a “d” is sent back. Once the charge in **4913** is finished, the system will in step **4914** to output a “K” then on top initialize the device in step **4915**. In steps **4916** and **17** it will continuously read the fastIndex, then with a delay **4918** it will go on to a loop consisting of **4919**, **4920**, **4921** and **4922**, where after checking the outcome of the charging it will disconnect the device in **4922**. If it was successful, it will proceed to **4923** and output an “H”, if not it will proceed to **4924** and output an “N”. In both cases the charging is now terminated.

(171) FIG. **50** shows an exemplary process **5000**, detailing the steps of process **4304** in module M4, according to one aspect of the system and method disclosed herein. In step **5001** module M4, the sync module, starts. In step **5002** the system outputs a P character and disconnects the D+ and D- signals and the 5V current. In step **5003**, an I character is output, and in step **5004** the system

connects the D+ and D- signals and the 5V current to computing device **4103**. In step **5005** a Q character is output, and in step **5006** the device connected will be initialized. In step **5007** the power status of the DUT is checked. In step **5008**, the system disconnects if the charging of the DUT has not ended and the process loops back to step **5007** to again check the power status. When the system determines, in step **5008**, that the DUT has completed, the process moves to step **5009**, where it ends.

(172) FIG. **51** shows an exemplary process **5100**, detailing the steps of process **4305** in module M5, according to one aspect of the system and method disclosed herein. In step **5101** module M5, the UART module, starts. In step **5102** the system determines whether incoming data is ready. If No, the process moves directly to step **5107**, where it ends. If Yes, the process continues to step **5104**, where the system checks to see if bit **0** is a 1. If Yes, it moves to step **5106**, where the bit **0** value is saved to g_uart_hi_byte. If the bit **0** value is not 1 (No), in step **5105** the value is saved to g_uart_lo_byte. In either case, after the bit value is saved, the process ends in step **5107**.

(173) FIG. **52** shows an exemplary process **5200**, detailing the steps of process **4306** in module M6, according to one aspect of the system and method disclosed herein. In step **5201** module M6, the timer module, starts. In step **5202** the LED status is updated. In step **5203**, the process ends.

(174) FIG. **53** shows an exemplary process **5300**, for use as initialization procedure according to one aspect of the system and method disclosed herein, as shown as second part in module M1 **4301**. This procedure, composed of steps **5301** thru **5309**, initializes testing and communication parameters.

(175) A system for testing and reprogramming mobile communication devices, such as, for example, cellular phone, tablets, etc., enables parallel connection of a large number of devices via, typically, USB cable, to connectors in the system box, with indicator lights for communicating to an operator the device status and readiness. Further, in such a system only one step is required to charge the device to an operational state, without operator interaction.

(176) In addition, the system uses different sequences to test, verify, securely delete content, and reprogram devices. The system can then analyze problems such as, for example, bricked devices, dead batteries, and unprogrammable and unstable devices, and collect information about the quality of devices based on their different sources. In addition, the system can collect data about the efficiency of the operators connecting and removing devices at any one system box, or about operators at multiple systems in one testing facility. The system can then communicate its collected data to a central server.

(177) FIG. **54** shows an overview of an exemplary test system **5400**, according to one aspect of the system and method disclosed herein. A computer **5401** is, typically, dedicated to a test bench. Screen **5402** shows status tiles **5403a-n**. Computer **5401** may be connected to network **5406**, as indicated by connection **5405**. Computer **5401** also is running software and applications **5404a-n**, as discussed throughout. USB link **5410** connects hub **5411** to computer **5401**. USB cables **5414a-n** connect hub **5411** to devices **5414a-n**, which devices are being reprogrammed, tested, etc. Power supply **5412** connects to power source line **5413**. It is clear that computer **5401** also has access to power. Also, in some cases, when computer **5401** is serving two 21-port hubs and/or two work platforms (using the optional second monitor) simultaneously, a second monitor **5422** is connected to computer **5401** to display additional statuses **5423a-n**.

(178) FIG. **55** shows an exemplary process **5500** of a typical workflow, according to one aspect of the system and method disclosed herein. As each device enters a testing and repair facility in step **5501**, it typically undergoes a visual inspection and is recorded in data repository **5514**. In step **5502** the system tests the device to determine whether it is dead. If yes (+), it goes to a charging station **5503**, where the device is charged at a charging station Unit A **5504**. When the device reaches a certain charge level, it moves (or is moved by an operator) to step **5505**, where its charge status is determined. If the device is still not charged (+), it goes to the “bad” bin **5506**. If the device is charged sufficiently to operate (-), it moves to step **5507**, where the system records the

identification and other specifications, such as, for example, memory size and type, of the device now connected to information reader Unit B **5508**. That Unit B then sends this information to data repository **5514**. In step **5509** the device is connected to Unit C **5511**, which removes user data and all user installed apps from the device. Depending on the customer's security measures and the nature of the data, removing the data may require multiple overwrites to ensure that no data remains, as well as logging the process on data base **5514** for documentation purposes and certifications. In those cases a simple "delete" does not suffice. In step **5510** the device is reflashed. In some cases parts of the operating system are then updated; and in yet other cases, other programs on the device may be replaced or updated. In step **5512** the system does a final quick check of the functionality of the device and, if the system determines that the device is good (+), the system sends the device status to data repository **5514** and the device is deposited into an instance of "good" bin **5513a-n**. If the device does not pass the check of step **5512**, it moves to bad bin **5506**.

(179) FIG. **56** shows a lateral view of an exemplary new testing, charging, and reprogramming unit **5600**, according to one aspect of the system and method disclosed herein. The intention is to be able to perform all steps on one unit rather than on three, as is typical today, and thus simplify the workflow. Use of unit **5600** also reduces the number of manual interactions, thus improving workforce efficiency. The novel unit **5600** has a smooth top **5607** on which devices or trays of devices may be placed, which will be discussed later. On both ends are venting features **5603a-n** and **5604a-n** (not shown) that enable cross flow of air from front to back or back to front, as desired. On one side are connectors and indicators **5605a-n** and **5606a-n**; in some cases more connectors and indicators **5608a-n** and **5609a-n** are on the other side (not shown). In some cases connectors are on top and indicators on the bottom row, while in other cases this order is inverted. Also present but not shown are power and network connections as needed for connecting the unit to the rest of the system, including, but not limited to, data repository **5514**. Since all the data is collected and made available to an MIS system (not shown), many measurements can be obtained, such as, for example the average time for a device to clear the system, which data may be organized by its source, thus enabling determination of quality differences. Also, percentage of dead devices, operator performance, etc., can be obtained by proper analysis of the data collected. By omitting intermediate manual steps, human error can be drastically reduced. Typically unit **5600** contains multiple hubs that can distribute USB connections for, typically, up to 42 devices per unit. In some cases unit **5600** may have a USB cable going to an industrial computer feeding the unit, similar to previous approaches; in other cases, a motherboard may be integrated separately, or the USB ports may be integrated onto the motherboard or a secondary board, inside the unit. In those later cases, often a hard drive or other suitable non volatile data storage unit may also be integrated to store all the data and programs, including the operating system, needed for operation.

(180) FIG. **57** shows a side view of unit **5600**. On the surface is exemplary tray **5700**, according to one aspect of the system and method disclosed herein. Two small guides **5701** and **5702** secure tray **5700** in a saddle on top of unit **5600**. Tray **5700** may have partitions, such as, for example, **5703** and **5704a-n**. In this example the partitioning provides for half side on each side and may have different sizes of slots and short cables **5705a-n** going to connectors on the side of unit **5600**. Under the cables are typically LED indicators, so, in addition to a screen that may or may not be connected, each port has a small LED indicator showing the status of the device attached to that port. Typically red and green LEDs may be used separately or in combination to produce yellow or black, to indicate four different states. Additional information may be indicated by blinks or varying blink speeds of the LEDs. States communicated by the indicators may include, for example, successful (steady green LED), failed (steady red), in process (yellow), starting or shutting down (blinking yellow), etc. Spacing of the partitions must match to some degree the spacing of the connectors below each partition, to limit cable entanglement, and also, there must be enough room for each device to stand up, typically on its side. Typical spacing would be approximately one inch (including partitions), to accommodate a standard smart phone. In some

cases, nonstandard layouts may be offered, to be discussed below.

(181) FIG. **58** shows a schematic view of typical seven-port USB hub **5800**. Hub chips **5810** and **5811** are, typically, daisy chained. Thus with two chips, each of which have four ports, the hub can offer seven external ports, with chip **5810** using one port to connect to chip **5811**. External connectors include Input **5801** and the seven external USB ports **5802a-c** and **5803d-g**. Power supply **5804** may be, typically, a plug-in or a central type PSU.

(182) FIG. **59** shows a schematic view of an exemplary hub system **5900**, according to one aspect of the system and method disclosed herein. Hub system **5900** is composed of existing, off-the-shelf secondary hubs. Secondary hubs **5902b, c**, and **d** are connected to the primary ports of hub **5902a**. This approach reduces the number of levels of the whole system, an important design consideration due to the fact that many types of software do not operate more than three or four levels deep within a system. Adding the root hub in the system and adding the fact that many current smart phones present themselves as internal hubs for various modes and data access types, the number of levels in the system is a concern. In this example, wall plugs **5904a-n** of hubs **5902a-n** plug into power strip **5905**. LED controller **5908** also plugs into power strip **5905**. Controller **5908** controls LEDs **5903** that are mounted above or below the ports on the side of unit **5600** (not shown here). The software in the main system coordinates the transactions and the statuses displayed by the indicators. Essentially, the LEDs mirror the information shown on screen **5402** for the various ports, making it easier for an operator to correlate information, instead of having to count, look up port IDs, etc. The 24 ports **5901** on one side may, for a double-sided unit, be duplicated on the other side, with two connections going to a motherboard in a server. In some cases, rather than using standard hubs, a special board can be made, eliminating the need for the short jump cables **5910a-n** that connect the hubs to the ports **5901**.

(183) FIG. **60** is a view of an exemplary USB cable unit **6000**, showing a typical design of cables **5910a-n**. Unit **6000** has a USB connector **6001**, a female port **6002**, and latches or loops **6003a** and **6003b**, for attaching connector **6002** to the interior of unit **5600**. This design simplifies removing and replacing worn or defective cables as required, on an individual basis.

(184) FIG. **61** shows three alternative configurations of tray **5700**. Configuration **6101** has two tracks **6103a, b**. Dotted lines **6102a, b** indicate the alignment rails that are used to secure the tray on top of unit **5600**. Configuration **6110** has extra-wide overlapped wings **6113a, b** to accommodate larger devices (5 to 8 inches) such as, for example, a small tablet or a large phone. Configuration **6120** has just one set of tracks **6123** across the tray for even larger devices such as, for example, tablets in the 8-inch to 15-inch range.

(185) FIG. **62** shows an overview of an exemplary multi-device tower **6200**, according to one aspect of the system and method disclosed herein. Drawers **6201a-n** accommodate small devices such as, for example, smartphones; small “phablets,” which are mobile devices that combine or straddle a smartphone and tablet. (<http://en.wikipedia.org/wiki/Phablet>); and tablets. Drawers **6202a-n** accommodate larger devices such as, for example, larger phablets and tablets. Computer storage area **6203** holds computer **6204**, in addition to a label printer and cabling, not shown, all of which devices are discussed in detail in the description of FIG. **64**, below. Cables **6205a-n** connect to a standard ac power source and a high-speed network, typically an Ethernet connection for a local area network (LAN) with a router/modem connecting to the Internet. In some cases, rather than using a LAN cable, the system may be connected via a Wi-Fi connection (not shown) or any other, similar suitable connection.

(186) FIG. **63** shows a detailed image of an exemplary device drawer **6300**, according to one aspect of the system and method disclosed herein. Although called a drawer, it may be a simple compartment with a door, similar to a post office box, or in some cases, there may be a slide out tray or box (not shown). For most situations, all designs should be considered functionally the same, but offering different levels of convenience in different aspects, such as ease of insertion, ease of cleaning, etc. For simplicity this compartment is herein referred to as a drawer, but all

variations should be considered interchangeable. A device **6304** may be inserted into drawer **6301**, plugging into one of connection options **6303a-n**, which may include, for example, Apple Lightning cable, micro USB, and Apple 32-pin cable. Internal wiring enables cables **6303a-n** to connect to one or more USB ports (not shown) inside the drawer, and said USB ports are all wired or coupled internally (also not shown) to processor **6404**, discussed further below. After the device is inserted and connected, the attendant closes front cover **6302**. Also, the number of drawers and their distribution may vary in different cases, without impacting the system services performed.

(187) FIG. **64** shows a simplified drawing of exemplary system architecture **6400**, according to one aspect of the system and method disclosed herein. Multi-device tower **6401** houses the device processing hardware and software, although in other cases, the computer and/or storage unit may be separate from the drawer unit, connected by one or more cables. Device drawers **6402a-n** are described in detail in the discussion of FIG. **63**, above. Also shown is exemplary device **6403**, as described in the discussion of FIG. **62**. Computer **6404** is essentially an expanded version of test system **5400**, described above in the discussion of FIG. **54** and throughout, with all the software and additional features, such as, for example, USB hubs, etc. In this case, it has additional software for additional features, such as, for example a system that lets it determine whether a handset is registered as lost or stolen, and hence can not legally be re-activated, etc. More of these additional features are described herein. Depending on the jurisdiction, the OEM, and the carrier(s) involved, one or more such databases (not shown) need to be queried to determine whether a device was reported lost or stolen. In some cases a printer **6406** may be coupled or attached to computer **6404**, for printing labels for devices, including in some cases shipping labels for destinations for processed devices. Exemplary connection **6405x** is one of multiple connections (only one connection shown here, for reasons of clarity and simplicity) from computer **6404** to all drawers **6402a-n**. RAID storage unit **6407** is extended intermediate secure, redundant storage for user data that may take a longer time to transfer into one or more of the respective cloud accounts of said user. The content of each device **6408a-n** is stored in an encrypted temporary location in said storage unit **6407**, from which it may be sent to the designated cloud service of the customer. Storage **6409** contains software support services **6410a-n**, which may comprise, for example, system vendor support, lost or stolen device identification, device information retrieval system (to determine such things as original issuing carrier), whether device is carrier locked, amount of memory and other model characteristics, retrieval of user data into local and cloud storage (including, but not limited to, address book(s), messages, mail and mail accounts, pictures, videos, music, voice recordings and any other media) as well as secure removal of user data and a new image/PRL programming, etc. to be installed on the phone based on its re-use after the digital cleanup. Also contained are, in some cases, software to interact with carrier logistics and destination management **6413**, and in some cases with shipping carriers **6417a-n**, etc. In yet other cases, a lost or stolen check may be included as well. Further, in some cases, one additional software can obtain market pricing for a particular handset and its quality status (for example, rated A, B or C based on mechanical appearance and battery health), enabling, in near real-time, determination of market value for making buy-back offers to owners at the point of collection. Through Internet **6411** the system can access external cloud storage **6412a-n** such as, for example, the Apple iCloud, Google G-Drive, OEM cloud network (OCN) such as Samsung cloud HTC, or carrier cloud network (CCN) such as Verizon cloud storage. Carrier logistics and destination management **6413** determines which destinations need which device models. Also shown is exemplary carrier desk **6415**, which has skilled logistics workers and/or algorithms (at carrier, not shown) to most efficiently dispose of refurbished handsets based on the quality ratings and current market pricing, needs internally etc. Connection **6414** connects carrier desk **6515** to carrier logistics and destination management **6413**, and wi-fi connection **6416a-n** connects destination management **6413** to shipping carriers **6417a-n**, such as, for example, USP, FedEx, OnTrac, etc Arrows **6418a-n** show how devices are sorted into high-grade devices, which are in pristine conditions, ready to kit

and ship; medium-grade devices, in good condition, but need some cosmetic improvements; and low-grade devices, in poor condition, but have salvageable parts. In some cases, kitting may happen at allocation, in others, a mobile service vehicle may be used to service multiple locations in a region, reducing labor costs to the store.

(188) FIG. **65** shows an exemplary process **6500** for implementation of the system when a user brings in an old device with content already backed up, according to one aspect of the system and method disclosed herein. This process assumes that passcodes are all unlocked; debugging mode, such as, for example, Android Debug Bridge mode, is already turned on; the Kill switch is already turned off; and the customer desires to trade in the device for cash or credit. In step **6501**, the customer service representative (CSR) greets the customer, launches the system app on his tablet, and inputs customer ticket information, including the customer's email for notifications and receipts. The CSR or the system then designates a device drawer number. In step **6502**, the CSR places the device into the tower drawer and connects it. The system checks the device for its lost/stolen status and activation readiness. In step **6503**, the CSR leaves the tower to up-sell a new device to the customer. The system transmits the device valuation to the CSR's tablet to discuss with the customer. In step **6504** the customer, on the CSR's tablet, indicates agreement or disagreement with the device valuation. If the customer disagrees (No), in step **6509** the CSR opens the device drawer and returns the device to the customer, and the process ends at step **6510**. If, in step **6504**, the customer agrees with device valuation (Yes), then in step **6505** the customer uses the CSR's tablet to sign an agreement with terms and conditions about content transfer and content erasure liability. In step **6506**, the system sends an agreement notification from the CSR's tablet to the tower. The system then proceeds with device erasure operation. After the system completes device erasure, in step **6507** the CSR's tablet receives a prompt to print a device label for old device disposition. The CSR chooses the "Print Label" button on the tablet. The system also sends a content erasure confirmation receipt to the customer's email address. In step **6508** the CSR opens the tower drawer and retrieves the device. He then affixes the label printed in step **6507** to the device, and places the processed device in the store's out-box for later pickup/delivery. In step **6509**, the system then automatically re-sets to the Start screen on the SCR's tablet for the next customer transaction.

(189) FIG. **66** shows an exemplary process **6600** for implementation of the system when a user brings in an old device with content back-up and transfer required, according to one aspect of the system and method disclosed herein. This process assumes that the customer desires to trade in the device for cash or credit. In step **6601**, the CSR greets the customer; launches the system app on his tablet; inputs customer ticket information, including the customer's email for notifications and receipts; and creates a temporary CCN customer account to store content. The CSR or the system then designates a device drawer number. In step **6602**, CSR has the customer unlock the device's passcode and turn-off the kill switch, and the CSR then turns on the debugging mode. In step **6603**, the CSR places the device in the tower drawer and connects it. The system checks the device for its lost/stolen status and activation readiness. In step **6604**, the CSR leaves the tower to up-sell a new device to the customer. The system transmits the device valuation to the CSR's tablet to discuss with the customer. In step **6605** the customer, on the CSR's tablet, indicates agreement or disagreement with the device valuation. If the customer disagrees (No), in step **6610** the CSR opens the device drawer and returns the device to the customer, and the process ends at step **6611**. If, in step **6605**, the customer agrees with device valuation (Yes), then in step **6606** the customer uses the CSR's tablet to sign an agreement with terms and conditions about content transfer and content erasure liability. In step **6607**, the system sends an agreement notification from the CSR's tablet to the tower. The system then reads and stores the device phonebook information and all the other content into a temporary encrypted file on the tower's internal data storage unit. The system also pushes the stored content to the customer account on the CCN. In step **6608**, after the system completes the processing, the CSR's tablet receives a prompt to load the stored phonebook and

other information into the customer's new device (some sub steps not shown for clarity of diagram) and to print a device label for old device disposition. The CSR chooses the "Print Label" button on the tablet. The system also sends a content erasure confirmation receipt to the customer's email address, with a link to the CCN account and a receipt detailing the device erasure and content transfer operation details. In step **6609** the CSR opens the tower drawer and retrieves the device. He then affixes the label printed in step **6608** to the device, and places the processed device in the store's out-box for later pickup/delivery. In step **6610**, the system then automatically re-sets to the Start screen on the CSR's tablet for the next customer transaction. Also, in some cases, for cross-carrier trade-ins, or for owner's preference, a backing up media contents can be made into a USB thumb drive (not shown).

(190) FIG. **67** shows a typical mobile phone network architecture **6700**, as may be currently in use. Mobile phone **6703** may be used at home or at an office; it may have access through cellular network **6702** to the Internet **6701**, and from there to all kinds of cloud services **6710**, **6711**, and **6712**, each of them potentially with servers and storage **6710a-n**, **6711a-n**, and **6712a-n**. Also in some cases a computer **6705**, for example, a desktop or notebook may be used. It may have additional storage **6706**, where, for example, a user may store additional pictures, music, videos, applications, e-mails, messages, chats etc. For example, if phone **6703** is an iPhone it may have some data and other content synchronized into the iCloud O1 **6710** with Apple, but the user may synchronize some content to the Google cloud O2 **6711**, for example, or to Dropbox, etc. Any services mentioned herein are exemplary only and may be exchanged with functionally equivalent services from any other companies. Also, contacts, for example, may be both in the iCloud and in the Google cloud, in some other proprietary cloud, and/or in the carrier cloud C1 **6712**. Further, most cloud providers offer tools to synchronize applications and data, such as videos and images, automatically to their clouds, since it is in their interest to increase the user's cloud storage so they can charge the user more. Thus, in current usage, content originating from a cellular phone such as, for example, phone **6703**, may be distributed and stored in any or many of a wide variety of local and cloud-based storage.

(191) FIG. **68** shows an exemplary tabular computer content map **6800**, according to one aspect of the system and method disclosed herein. Map **6800** charts locations **6801a-n** of a user's content, so the system can then deduce which content must be migrated when a user moves to a new phone. If, for example, a user is moving from an iPhone to an Android phone, any content the user has in the Apple iCloud must be moved elsewhere, because the Android phone cannot access the iCloud. Or, if the user moves from an Android phone to an iPhone, although content in the Google cloud can be accessed by an iPhone in some cases, the full features/meta data may not be available, so some content should be moved in those cases also. Thus, when notified by a user of migration to a new phone, the system creates a new map of usable and unusable storage locations for the new phone. The system then compares its map of current content locations to the new map, giving new target locations for content according to a user's wishes and within the limits of usable content locations. For example, if the user stores images in Dropbox, the system maps the new content storage so these images can continue to be stored there; but if a user is storing contacts in a carrier's cloud storage, the system maps these contacts to a new location such as, for example, the new phone carrier's cloud storage.

(192) FIG. **69** shows an exemplary process **6900** for migration of data, applications, and other desired content when a user moves to a new phone, according to one aspect of the system and method disclosed herein. In step **6901**, the user installs the system app, typically (but not always) on his current phone. The user then logs on to the system, and, if necessary, he also logs on to or provides credentials for one or multiple cloud storage services, depending on what cloud services he or she uses on what provider(s). In step **6902**, the system communicates with data storage **6903** to identify the user. In step **6907**, the system determines whether the user is new (y) or already an existing user (n). If a new user, in step **6904** the system creates a new account and a new map of

existing content locations. All this information is stored in data storage **6903**. Then, if the user has indicated that he is moving to a new phone, the system in step **6905** creates a target map of new content locations, and in step **6906** the system creates a migration map showing the differences in content locations between the old location map and the new location map. In all these steps, the system stores data in data storage **6903** and also draws stored data as needed. In step **6908**, the system sets up content storage for new locations in various storage services in cloud **6909**. In step **6910**, the system does a full backup of all data, applications, and other content scheduled for migration and then in step **6911** the process ends. By the time the actual content migration is scheduled to occur, the user may have made changes in his storage locations, so he may log on to the system again, as in step **6902**. In step **6907**, if the system determines that the user is already an existing user, in step **6912** the system asks the user if all migration targets are the same. If, in step **6913**, the user indicates that all migration targets are the same (Yes), in step **6914** the system incrementally updates the user information and the process ends. If, in step **6913**, the user indicates that all targets are not the same (No), in step **6915** the system verifies the new targets and then the process loops back to step **6905** to create a new target map and proceed from there. When the user wants to initiate transfer of content from existing locations to new locations, typically, the app provides a means (not shown), such as, typically, a “go” or “confirm” button (or equivalent), after clicking of which the transfer starts, in some cases including creation of new accounts on target clouds.

(193) In some cases, a system may simulate a human user touching the screen of a device, such as a cell phone or similar, that has a capacitive touch screen, with the device positioned on a touch simulator that has a matrix of individually addressable, electric structures based on an LCD display. In such a system, a camera may photograph the device screen and transmit the resulting images to a computer, where the interactions of the touch simulator and the device are recorded. Additionally, software on a computer can create scripts for future, similar interactions, using the stored images to test similar devices for functionality. Alternatively, the system may simulate human touch on the device screen through a matrix of individually addressable, XY resolved electric structures based on inflatable tubes.

(194) FIG. **70** shows an overview of an exemplary testing system **7000**, according to one aspect of the system and method disclosed herein. Phone, tablet, phablet, or similar device **7001**, which is under test, sits with its display screen facing down atop test fixture **7002**. Fixture **7002** is topped by shield **7003**, made, for example, of a transparent material such as glass or acrylic. Underneath is mounted a transparent LCD unit or similar **7004**, which unit can simulate a user's finger moving on the display of device **7001**. Camera **7005** has a wide-angle lens **7006** that can take in the whole display area **7004**, as indicated by view angle **7007**. Shield **7003** may have various different placement markings for various different devices, so an operator knows where to position each type of device so the display is in the view field of the camera. Thus camera **7005** can view and capture what is happening on the display of device **7001**. Computer **7010**, using software **7014a-n**, can manipulate functions on display **7004** to simulate user touches on the display of device **7001**. Most devices use capacitive touchscreens, such as and similar to those discussed in Wikipedia article “Capacitive sensing” (https://en.wikipedia.org/wiki/Capacitive_sensing). Therefore, it is important that shield **7003** be very thin, to allow the touchscreen to sense the activities of LCD **7004**. LCD **7004** is stripped of all accessory or unnecessary features, with no polarizers or other extra features. It is just two panels in series. Even the LCD itself is not necessary; only the active thin-film transistor (TFT) part that enables changes in an electric field is used in this approach. These changes are used to simulate the touch of a human finger (or several fingers). Typically dozens of pixels are activated to represent one finger. Device **7001** is able to detect the change in the field and can be used to simulate a finger touch by moving the active area; i.e., making the display “think” it creates a visible image. However, an image (on LCD **7004**) is not actually visible. Because the polarizers have been removed, the LCD simulates a finger touch. More about this approach is

described in the discussion of FIG. 71, following. Computer 7010, typically, may have a display 7011, keyboard 7012, and a pointing device (not shown). It may be connected to a network 7013 and/or to tablet 7020 through a wireless connection 7024. Tablet 7020 may have software 7025a-n that displays images from camera 7005, in this case, the image of device 7001 as image or outline 7021 on the tablet display. Software 7025a-n is typically used only to set up (and record) new procedures for new software on device under test (DUT) 7001. In this example an icon on the display of device 7001 appears as icon 7022 on the tablet within outline 7021 of the DUT 7001. The operator may now choose from icons 7023a-n what functions he wants to perform on image 7021; that is, for example, he can touch icon 7022 to perform a slide, single-tap, double-tap, multi-tap, squeeze, stretch, etc. Although a tablet 7020 is shown here, the same functions maybe performed on a screen connected to computer 7010, directly or indirectly, using mouse and keyboard, or using a touchscreen or other, similar apparatus or input device. Computer 7010 records and/or stores any functions and following steps, etc. as well as transmitting them to LCD 7004, which then simulates the use of a finger function on device 7001. In this manner, an entire script of operations for a specific type and model of device with its specific software can be created on tablet 7020 and used to test every device of that type. Further, such a test script may be run at variable speeds, that is, real-time speed, faster, slower, etc. Once a set of scripts is created, any script can be recalled from the keyboard 7012, or even by the computer 7010, just by recognizing the device 7001 plugged in, and the whole sequence can be played back without any human interaction. In some cases, the camera 7005 can recognize (based on certain previously made selections during creation of scripts) that additional input is necessary, such as adding a password, etc. and typing that into the screen-based keyboard on device 7001.

(195) FIG. 71 shows an overview of an exemplary stripped LCD 7100, introduced in the discussion of FIG. 70 as LCD 7004, according to one aspect of the system and method of disclosed herein. LCD 7100 has glass 7101; tabs 7102a and 7102b; driver chips 7103a and 7103b; LCD controller 7105; connections 7104a, 7104b, and 7106; video card 7107; and PCI connector 7108. PCI connector 7108 typically plugs into a computer such as a notebook or desktop, depending on the type video card and the bus in the computer. Connector 7108 may be plugged into a computer such as computer 7010, which may then drive the LCD. Active pixels 7109 are shown, for clarity, on glass 7101 as black dots, but in reality they would, in this case, be invisible because all the filters have been removed or not even applied. Pixels 7109 indicate an area of activity applied over an icon on device 7001 to activate the icon. By using LCD pixels that have similar resolution to those on the device 7001 under testing, smooth motions such as, for example, slides or multi-taps may easily be simulated and applied to the device.

(196) FIG. 72 shows an overview of an exemplary alternative approach 7200 for activating an icon on a device screen, using a cross-hatching of tubes, according to one aspect of the system and method disclosed herein. In this approach, rubber tubes with a slightly conductive coating are inflated. Only when two perpendicular tubes inflate does the area at the junction of the two tubes expand enough to touch the device screen. Thus when, at the junction of two inflated tubes, the upper tube touches the screen, it simulates the touch of a user. Tubes 7210a-n and 7211a-n create matrix 7201. At the edges of matrix 7201 are inlet valves 7203a-n and 7205a-n. These valves connect to inlet chambers 7202 and 7204, respectively, which chambers are fed by fan 7214. By controlling the air feed into specific valves of inlet valves 7203a-n and 7205a-n, one or more matrix points may be inflated so the selected points expand enough to touch the screen with the slightly conductive rubber, thus simulating a user touch. Using reduced-flow bleed valves (not shown) on the opposing ends of the tubes would enable the tubes to inflate quickly, but also deflate once the inlet valve is closed. Adjusting the ratio of cross-section between inlet and bleed valves could achieve an optimum balance between speed of inflation and deflation. The problem with this approach is that it would be more difficult than the approach described in the discussion of FIG. 70 to simulate a workable sliding motion, and achieving a workable the resolution would be difficult.

Also, it would be more difficult to achieve enough transparency with those tubes so the screen can be observed to see what's happening where and be responsive to software input. However, software on the computer controlling the matrix could be used to compensate for the sliding difficulties by trying a “soft transition” between matrix points and by erasing/compensating for much of the visual distortion created by the un-transparence of the matrix, thus reducing somewhat the disadvantages. (197) In some cases, a system for reviewing returned smartphones and other computing devices may employ a device-specific protocol for a multistep procedure, with as many of the steps as possible removed from personal judgment. A matching application on the device would support certain steps of the operator and can fill in certain responses. This system may note in a log the steps that were performed without the operator's help, but the operator may override the system with a note and acknowledgement. Further, such a system may require an operator to make a deliberate choice of various status messages when starting to evaluate such a device, starting at a neutral state and actively moving a status report to a yes or a no. In many cases, a script may perform different sets of tests for different devices based on the system owner's preferences.

(198) FIG. 73 shows exemplary screen **7300** on a computer running software for a system for managing transactions involving testing mobile devices, according to one aspect of the system and method disclosed herein. Header section **7301-7304** has a login field with dots representing a login code, followed by a checkmark **7304**, indicating that a system operator has checked in to the system already. Also shown are alphanumeric transaction ID **7305** and bar code **7306**, which in this example is a two-dimensional bar code, such as QR code or similar type of code suitable for scanning by a smart phone, although, alternatively, in some cases, it may be a one-dimensional code. The reason there is both an alphanumeric transaction code and a bar code is because if the camera on the subject phone does not work, either due to physical damage or software malfunction, the user cannot scan the code, so then the user must manually enter the transaction code. If the user scans code **7306** with a phone or similar device, the system downloads the app into the phone. If the bar code cannot be scanned, the system also presents a URL **7307** that can be entered manually on the phone for a link to the app store. This URL can be a tiny URL that brings the user to the app store and allows him to download the app to the phone and then enter transaction ID **7305**.

Although there may be different variations in the process, essentially the phone ends up with an app and a transaction code, so the system an operator can then check and evaluate the phone for acquisition by the retail store.

(199) FIG. 74 shows exemplary screen **7400** that follows screen **7300**, according to one aspect of the system and method disclosed herein. Screen **7400** appears when a mobile device has acquired a new transaction. It shows the interaction offered to the operator doing the transaction. On top **7401** the main header section shows **7402a-d**, the device-specific header section after the (typically) 2-D bar code was scanned, filling in the IMEI and the serial number of the device, and at some point the results of the “stolen/not stolen” and the “kill switch removed” status messages **7402a-d**. In some cases those databases may not be available in all regions, so the operator may have to manually enter that information. All those status messages have special unique switches that, like **7402c**, start in a neutral position **7402c1** and can be moved left to **7402c2** or right to **7402c3**. The operator filling in the screen data thus cannot say, “Oh, the switch was in the wrong position and I didn't notice,” because the system cannot proceed with a transaction unless all the switches are in either put by an operator action to the left (c2) or right (c3) position. The number of status options available can be set or requested by the operator or the enterprise operating the system, and the transaction cannot be completed until all status options have been addressed. Some options may be automatically addressed by the software on the device under test, or by the person operating the device. For example, an operator reviews and then selects “No Water Damage,” thus moving switch **7404a** (top line) to the right, position **7404a3**. Similarly, the operator may select “Glass not cracked” **7404d3**, indicating no observable cracks on the screen that would prevent the device from working properly when the screen is swiped. Other switches, likewise, indicate that the battery is

present, etc. Data fields such as **7403a-n** may populate automatically, mostly when the software is launched on the device. Once all the tests are complete, the system derives the identity of the operator who performed the tests from the ID of the operator who initially logged in. Then typically the device is assigned an SKU **7406**, based on the grade and the answers provided. Also, the system assigns a value, in this example Chinese currency “CNY” **7407**, or any other desired currency or value, for example, store bonus points, etc. Then the device owner can say if he wants to proceed with a trade-in and the operator accordingly selects either the “Trade in” button **74708b** or the “Cancel” button **7408a**.

(200) FIG. **75** shows an exemplary process **7500** for executing a transaction, according to one aspect of the system and method disclosed herein. In step **7502** the transaction is initiated. After login and preparation in step **7503** the system pulls a transaction ID from database **7504**. Typically step **7503** is a web-based transaction on a server **7506** and database **7504** in network **7501**, typically the Internet. Server **7506** also contains a multitude of programs **7507a-n**, some of which are operating system and some of which are the system disclosed herein throughout. The system is typically distributed, with multiple components housed in various different physical and logical locations. Typically the transaction process has some component running as an app on the device under test; it has a component running as a web app in a browser on a tablet or computer in a retail or testing location; and it has a server component that is the main driving software. In step **7508** the initial web application page is created, as described earlier, with, for example, a bar code that enables download of the app to the device under test. It also has the initial transaction ID. In step **7509**, device **7505**, which is typically connected through a wi-fi and/or Internet connection, sends the code to the application, either via server **7506** or the browser through a web interface. Next, in step **7510** the system receives the IMEI and other information from the device under test, depending on the configuration and requirements. In step **7511** the system verifies the received data, such as the theft, lock, and value data. This data verification step may use internal and/or external databases **7512a-n**, in any combination. They are shown here as separate databases. Some may be third-party databases; some may be integrated, or separated, or combined with database **7504**. The actual pulling of this information may be done in any of various steps in the process and is shown here as one separate, unified step solely for purposes of simplicity and clarity. In step **7513** the system ensures that the operator or user runs through all the required step of the script, ensuring that all tests are run properly and completely. Based on the test results, a final value for the device under test is pulled from one of databases **7504** and **7512a-n**. Based on the final value, the operator extends an offer to the device owner. If, in step **7514**, the user accepts the deal (yes), in step **7516** the system finalizes the deal electronically and, in step **7515**, the process terminates. If the user does not accept the deal (no), the process immediately terminates in step **7515**.

(201) In relation with FIGS. **29-40**, FIG. **76** shows an exemplary process **7600** for generating further sales offers for existing customers according to one aspect of the system and method disclosed herein.

(202) In step **7603** the system creates a catalog, typically, from data store **7602** in cloud **7601**. Even though data store **7602** is shown here in a cloud, it may alternatively or additionally be in a local device, on a network server, or in any other accessible location. In one embodiment, a catalog comprises a set of attributes associated with a mobile device operated by a user. As described herein, a catalog may represent a centralized storage mechanism used to store all attributes of a mobile device.

(203) In step **7604** the actual activities of the various apps on the user's mobile device are recorded, so the system can examine the different apps used and so forth. In one embodiment, activities of a user comprise cell changes, roaming table updates, installation and activation of software applications, installation and activation of plug-in software, phone calls, etc. In some embodiments, the actual activities of a mobile device are recorded in the catalog created in step **7603**.

(204) In step **7605** the system records in a log the various mobile device accessories, such as, for

example, the types of headsets and other Bluetooth accessories. In one embodiment, the method updates the catalog with the mobile device accessories recorded in step **7605**. This profile may also be stored in data store **7602** for subsequent use.

(205) In step **7606** the system similarly examines and records in data store **7602** service plans and modules. In one embodiment, this data is extracted from a service module of service provider **7607**. In other cases (not shown) the system could communicate with an app on the mobile device itself and extract this information locally, or it could talk to a dedicated server (not shown) or any other equivalent means could be used.

(206) In step **7608** the system then creates or updates a profile of this specific mobile device associated with a given account. In one embodiment, the method may create separate profiles for the cataloged activities, the cataloged accessories and/or the cataloged service plans/modules. In one embodiment, the method saves the profile(s) to data store **7602** for subsequent use.

(207) In step **7609** the system compares the user of this mobile device to other peers, meaning people who have either the same activity profile, the same accessory profile, or the same service plan profile. For example, if a user has the same activities and the same accessories but not the same service plans, the user may be a candidate for upgrading or changing his service plan. However, if a user has the same service plans and the same activities and apps, but not the same accessories, he may be a candidate for buying different accessories. In another embodiment, the method may recommend an accessory if a profile of cataloged activities and a profile of cataloged service plans or modules matches a given peer and a profile of cataloged accessories does not match the given peer. In another embodiment, the method may recommend an activity if a profile of cataloged accessories and a profile of cataloged service plans or modules matches a given peer and a profile of cataloged activities does not match the given peer.

(208) Thus the system creates several types of peer groups for each device, and then in step **7610** it looks to see if it can propose new items to a user. If no, the process ends in step **7611**.

(209) If yes, the system then checks offering criteria in step **7612**, determining whether the new items meet various criteria to make an offer. The criteria could be set by the carrier, in some cases, so the system checks with service provider **7607**, or in some other cases it could be a filter set by the user in his profile. For example, the user may indicate that he does not want to get certain types of offers because he considers them as spam (and vice versa). In yet other cases both could set rules that are combined. In one embodiment, the offering criteria comprises a list of activities (e.g., applications), accessories, and/or service plans/modules offered by, for example, a carrier.

(210) In step **7613** the system then determines whether it can make an offer to a user, based on the criteria checks. If no, the process terminates in step **7611**. If yes, in step **7614** the system makes an offer. This offer may appear as a pop-up (not shown) on the user's device, or it could be sent via arrow **7615** as an email to the user, or both. In some cases, the offer may have a limited special discount attached. For example, if it's a service offer, if the user takes advantage of the offer within a specified time from the date of the offer, the user may receive an incentive such as, for example, the first month free, or the first three months at a discounted rate, etc. if he signs up immediately, as a way to motivate the user to sign up quickly.

(211) FIG. **77** shows an exemplary layout **7700** of a portion of a simple apartment. Shown are window **7701** whose view includes a transmitter station, low chest **7706**, outlets **7707** and **7708**, a typical metal refrigerator **7704** with its own outlet **7705**, an opening **7702** to another room, another window **7703** in the other room, and part of a wall-mounted flat-screen TV **7709**.

(212) FIG. **78** shows a layout **7800**, similar to layout **7700** shown in FIG. **77**. In FIG. **78**, repeater or router or similar device **7801** is mounted or placed on chest **7706**, with antenna **7802** that can easily receive signals from transmitter station **7805** on the hill visible from window **7701**, as indicated by uninterrupted radio link **7804**. Device **7801**, hereinafter referred to as a router, can transfer signals from one spectrum to another, for example from 5G into a 4G or a Wi-Fi local cell. Router **7801** can then send inside the apartment different frequency signals for different devices,

such as, for example, Wi-Fi signal **7803**, which can easily penetrate interior walls, unlike a 5G signal, which has difficulty penetrating typical interior walls. A 5G signal has difficulty penetrating walls because it is on a very high frequency, akin to the frequency of light, which can penetrate only very thin, translucent material. Signal **7801** could link into an existing Wi-Fi infrastructure, or it could connect with more secure Wi-Fi routers, thus being transmitted into every corner of the residence. Additional router stations, while they could be installed, are not shown for purposes of clarity and simplicity.

(213) FIG. **79** shows an exemplary means **7900** that can help an unskilled user to find the best location for such a station and its antenna, according to one aspect of the system and method disclosed herein. Snapped on to ordinary “smart” telephone **7901** is a special adaptor **7906**. In this case, adaptor **7906** snaps onto the top of the telephone; depending on the model of telephone, the adaptor could snap onto the bottom or some other location, based on the location in the phone of its antenna. In most such phones, the antenna is not externally visible, but these antenna locations are known and can be documented. Additional features of the adaptor may include, for example, funnel **7908** to concentrate signals **7909a-n** radiated from the signal tower, and a snap-on or mounting feature **7907**, such as, for example, an adhesive or an elastic band, or some other feature by which the adaptor can be attached or slipped on or otherwise mounted onto the phone.

(214) Application **7910** running in phone **7901** displays screen images, such as, in this case, exemplary screen images **7902** and **7904**. Within image **7902** is a video image **7903** of the apartment layout such as, for example, layout **7800** shown in FIG. **78**. Image **7904** shows signal density areas **7905a-n** such as, for example, two high-density areas roughly corresponding to the location of windows in the apartment, the windows being where the 5G signals come in. With the help of adaptor **7906** and application **7910**, the user now has a map of his residence and a way to detect the best location for antenna **7802** and the maximum distance from the antenna that he can place router **7801**.

(215) FIG. **80** shows an exemplary process **8000** of the software and implementation of its commands for locating a router for a 5G signal, according to one aspect of the system and method disclosed herein. In step **8001**, the system instructs the user about how to mount the adaptor on the phone, depending on the telephone model. The adaptor and instructions could be supplied to a user in a kit. Some kits could contain multiple adaptors for various phones, in various cases either from different manufacturers or different models from the same manufacturer. Adaptors could be made from any of various materials, many of which may be recyclable; materials may include, but are not limited to, metalized plastic, cardboard, heavy aluminum foil, copper, etc. In step **8002**, the system asks the user for permission to proceed with making a video of the residence interior. This step is to protect the user's privacy and to guard against claims against the system owners of privacy violation, because the system will be recording the interior of the user's residence. In step **8003**, the user makes his decision to grant permission (+) or not (-). Upon being granted permission, the process moves to step **8004**. If the user does not grant permission, the system moves to step **8013**, where the process terminates.

(216) In step **8004**, the system sets a counter to 1, indicating room 1, and then in step **8005** the system instructs the user to move around the first room so the phone can record a video of the entire room and its furnishings, and also record signal strength in various parts of the room. All this data is stored in database **8007**, which can reside in the phone and, optionally, may be uploaded to some other remote data storage unit. In step **8008**, the system asks the user, after recording information about the first room, if the residence has another room. If yes (+) the system increments its room counter in step **8009** and loops back to step **8005**. The system continues to cycle through step **8005** to **8008** until the user indicates no more rooms (-). Then the system moves to step **8010**, where the system analyzes the data in database **8007**. In step **8011**, the system decides whether its analysis has resulted in useful information. If yes (+), the system proposes one or more router locations in in step **8012** and then the process terminates in step **8013**.

(217) If, in step **8011**, the system does not have useful information (–), in step **8014** the system asks the user for permission to share the information in database **8007** with a technician at an online service center. Sharing this information gives the technician permission to view the video of the residence interior so he can suggest router locations. In step **8015**, the user may deny permission (–) to contact a technician, in which case the process terminates in step **8013**. If, in step **8015**, the user gives the system permission to contact a technician (+), then in step **8016** the system sends data to the technician with permission to remotely visit the residence, the technician and the user are put in contact with each other, and the process ends at step **8013**.

(218) FIG. **81** shows an exemplary process **8100** of a typical work flow, according to one aspect of the system and method disclosed herein. On the left side at step **8101** devices come in from any of various acquisition sources. At step **8102** a person executes a “detrash” process on each device, separating out such extraneous material as cases, stickers, batteries, screen protectors, packaging, packing tape, etc. All such material must be removed, and any material that can be recycled or otherwise reused is directed to the proper destination. Reclamation of “trash” where possible is important, because it is often expensive to throw things away, and in some cases and localities, discarding recyclable material is illegal and subject to fines and/or other civil penalties. Then device identifiers, including a tracking number and RMA number are recorded, for example by data entry or scanning into the receiving system software. At step **8103** a person separates devices, including phones and tablets, into operating system categories Apple **8104a** or Android **8104b**. Android devices need additional manual preparation in step **8105**, wherein the ADB mode must be enabled to permit access to the device operating system, and in the case of Apple devices the test application must be trusted. In step **8106**, a subject device is plugged into a reading device that can analyze the device and install appropriate software. In the example shown herein, this reader is an information reading tool (iRT) type, but other, similar reading devices could be used to gain control of the subject device and permit installation of software that can read identifiers of each subject device, such as, for example, make, model, memory, status, any lock status or similar such as FMIP/FMA of OEM specific locking software, etc. Such software can also load a functional test (FT) app into the device that can show information on the device screen, including whether the subject device has a SIM card for iOS. After the subject device is finished with the reception process and is judged to be fit for reuse, in step **8107** it goes through a “car wash,” which physically scrubs the device free of dirt, glue and spill residue, etc. In step **8018**, robots visually inspect the subject device for quality and defect issues, etc. Depending on the condition of the device, it may skip a final functional test via bypass **8109** BER (Beyond Economic Repair), or it may undergo a full functional test in step **8110**. In this test, robots test all usage aspects of the device, simulating not only software use, but also physical use, such as pressing buttons, touching the screen, etc. If the system finds that the device is fully functional, then in step **8111**, the system clears all test data and flashes the latest operating system and associated software into the device, and in step **8112** the device is sent to the warehouse to await resale.

(219) FIG. **82** shows an exemplary process **8200**, which is similar to the process discussed in FIG. **81**, above, but in this case the example is that of a typical physical model of the system, according to one aspect of the system and method disclosed herein. In step **8201**, devices are received and detrashed, and then separated according to type, with iOS devices going to stations **8202a-n** and Android devices going to stations **8203a-n**. At charging station **8204** robotic arm **8211** takes devices off a conveyer belt and plugs them into and removes them from chargers of station **8204**. Once the devices are charged, they go to “car wash” cleaning stations **8205a-n**, which may comprise multiple stations to handle multiple devices, and which may also comprise stations of various types, including washing, rinsing, and drying, etc. (two shown). After being cleaned, the devices are inspected at stations **8206a-n**. More than one inspection station may be needed, because inspection may require from a few seconds to several minutes, and in the latter case, multiple stations may be needed to keep the process moving steadily. At stations **8207a-n**, functional testing

of the devices occurs. At station **8208** a robotic arm **8209** plugs devices into connectors so the devices may be cleared of testing data and flashed with the latest version of its software. Finally, after devices are fully programmed, robots send them to warehouse **8210**.

(220) FIG. **83** shows exemplary pseudo-isometric views **8300** and **8310** of a typical physical equipment layout, according to one aspect of the system and method disclosed herein. View **8300** shows an exemplary layout from the top of typical system equipment, including preparation stations **8302**, test boxes **8301a-n**, conveyer belt **8307**, robot arms **8304**, **8305**, and **8306**, and visual inspection station **8303**. View **8310** presents a 3-D perspective, showing such typical equipment as testing boxes and robot arms.

(221) Enhanced Automatic Cosmetic Grading

(222) Correct grading of returned devices can greatly affect profit loss when buying back large quantities of recent model mobile computing devices (such as tablets, or foremost, smartphones). Resale value greatly depends on “freshness” (how recent a device is), how new/undamaged/unused it looks (cosmetic appearance) and lastly how good its battery is. Currently most of the cosmetic grading is done manually, often overseas, requiring additional shipping and handling of the devices, further potentially degrading them, etc. Further, manual grading carries risk: depending on the training and daily form of the persons performing grading, there may be a variance in the results.

(223) What is needed is a novel approach that will correct, eliminate, or reduce many if not all of these problems. One approach is to use robotic highspeed grading, wherein all aspects of grading are performed robotically at high speed in such a way that per unit costs are very competitive. By eliminating the additional handling risks and travel times, a slightly higher cost per graded unit is still over competitive.

(224) The presented grading technology can use both rule-based and artificial intelligence (AI) solutions. Rule-based solutions include model learning (ML) and rule configuration, image capture, and image processing and grading. AI solutions include convolutional neural networks (CNN), data augmentation/transfer learning, instance segmentation, and incremental learning. Automatic cosmetic grading learns how to grade (grading criteria) using AI and or ML, which allows for an abbreviated, rule-based training. Unlike in a regular AI/ML model, the machine in the demo and production prototypes uses rule-based training to ensure that little to no training is required when the machine encounters a new mobile device model. Another advantage of grading technology is that the machine can detect defects in the mobile device (such as scratches, cracks, discoloration, dent/chips, and hard case scratches) based on its learned grading criteria.

(225) Some goals of automatic cosmetic grading include (but are not limited to) providing an easy setup; being accurate, consistent, efficient, flexible to the new grading criteria, and user friendly; and having a high tolerance to the environment and a low training effort.

(226) FIG. **84** is a Venn diagram for visualizing rules and AI range. Overview **8400** shows how grading criteria V4.2 **8410** and V4.3 **8420** (grading criteria for slightly different mobile devices) contribute to a larger pool of overlapping information **8430** that AI Grading Criteria **8440** can pull from when grading a mobile device. AI Grading Criteria **8410** enables the enhanced automatic cosmetic grading machine to do the following exemplary tasks: analyze discoloration, use optical character recognition (OCR) to determine whether a mobile device is refurbished (and if so, by whom), handle stickers (removing or reading a sticker, etc.), and determine if there are any differences between two mobile devices of the same model (e.g. logo, sensor size, camera, etc.). The advantage of AI Grading Criteria **8440** is that you don't need to spend the time, money, and risk it takes to re-train a machine to learn new grading criteria each time a new mobile device comes out. AI Grading Criteria **8440** can accommodate changes in mobile device models.

(227) FIG. **85** is an exemplary overview showing a flow diagram of a grading process. Overview **8500** shows the process by which mobile device **8510** is graded. The machine learns how to grade via Rule-Based Grading Main Engine **8580**. Rule-Based Grading Engine **8580** learns from the information provided by Grading Criteria **8560** and Training Model Database (DB) **8590**. After the

user puts mobile device **8510** into the machine, the machine captures different images **8520** of said mobile device **8510**. After image capture **8520**, the machine can follow a few exemplary routes. One route option involves the machine augmenting data **8540**, determining the condition of the mobile device (using an AI Incremental Strategy for CNN **8570**), and assigning a grade **8550**. The other route options involves processing the images **8530**, applying Rule-Based Grading Main Engine **8580**, determining the condition of the mobile device (using an AI Incremental Strategy for CNN **8570**), and assigning a grade **8550**. After each mobile device **8510** is graded **8550**, the machine augments data **8540**, thus growing the database and continuing to learn.

(228) FIG. **86** is an exemplary overview of a hardware connectivity system. Overview **8600** shows the Inspection and Grading Central Control and Processing Unit **8610**. The mobile device is placed on Belt Transport Control Unit **8620** and the machine captures multiple images of the mobile device to grade. The machine captures and inspects the top-side **8630**, back-side **8640**, up-side **8650**, down-side **8660**, left-side **8670** and right-side **8680**.

(229) FIG. **87** is an exemplary photograph of an early prototype. Overview **8700** shows a rule-based grading demo. Mobile device **8710** is placed in the machine and said machine captures multiple images of mobile device **8710**. In this example, when the user places mobile device **8710** on fixture **8720** (the starting point of the inspection), mobile device **8710** moves horizontally along Motor Driven Belt Transport Platform **8730** while multiple cameras capture images of five sides of mobile device **8710**: (1) down-side (using area camera **8750a** and lighting module **8750b**), (2) right-side (using area camera set and lighting module **8760**), (3) left-side (using area camera set and lighting module **8770**), (4) top-side (using line camera set **8780a** and lighting module **8780b**), and up-side (using area camera set **8790a** and lighting module **8790b**). Once the machine has captured images of the first five sides of mobile device **8710** in this example—and mobile device **8710** has reached the end of the Motor Driven Belt Transport Platform **8730**—the machine flips mobile device **8710** over on its back and the cameras capture images of the sixth side: the back side (line camera set **8780a** and lighting module **8780b**). The machine returns mobile device **8710** to fixture **8720** (starting point) while simultaneously completing the six-side grading. This entire automatic grading process works with both iOS and Android devices. In this example the device to be inspected travels from the left to the right, gets flipped over, and the “other half” gets inspected on the way back. In other cases, a slightly longer mechanical unit with more cameras might eliminate the need for flipping and two passes (not shown here).

(230) A few important production considerations include (but are not limited to): how to quantify the grading criteria, the processing time, the breadth of coverage (how many devices this machine can process and grade), and the training effort needed to teach the machine.

(231) FIG. **88** an enhanced exemplary overview of a hardware connectivity system. Overview **8800** shows the Inspection and Grading Central Control and Processing Unit **8810**. Unlike in FIG. **86**, which uses a transport belt, in FIG. **88** the mobile device is placed on a Stage Transport **8820**—State Transport **8820** automates the placement and flipping of the mobile device. The machine then captures multiple images of the mobile device, but unlike in FIG. **86**, in FIG. **88** the machine consolidates the down- and up-sides **8830** as well as the top- and back-sides **8840** when capturing images.

(232) FIG. **89** is a simplified schematic view of an early prototype (similar to FIG. **87**). Overview **8900** shows a production system demo. In this exemplary model, Robotic Arm with Vacuum Gripper **8915** automatically places mobile device **8920** in the machine. From there, Stage Transport **8930** moves said mobile device **8920** horizontally through the machine while multiple exemplary cameras and lighting modules **8950a/8950b/8960/8970/8980a/8980b** capture images of the sides. The production system model reduces the number of images required to capture all the sides (compared to the demo system). If flipping is required to capture additional images, Stage Transport **8920** automatically flips mobile device **8920** so the cameras can capture images of the remaining sides.

(233) The demo and production systems differ on their efficiency—the production system is more effective. While the exemplary demo system has two image capture cycles for a total of 5 cameras, the exemplary production system has one 6-side image capture cycle for a total of four cameras—consolidating image captures and cameras reduces processing time and saves on cost. The demo system requires a manual placement and flip of the mobile device, while the production system automatic manual placement and flip of the mobile device—automating the placement and flipping of the mobile devices reduces processing time. The demo system requires a specific fixture based on the phone model, but the production system doesn't require a phone fixture at all—eliminating the phone fixture reduces processing time. The demo system uses a belt transport, while the production system uses screw-driven stages transport (which increases reliability and maintainability). In these exemplary models, the demo system takes two image captures units down- and up-sides, while the production system consolidates the image capture units of down- and up-sides into one unit—this consolidation reduces processing costs. While the demo system captures the left- and right-side images under motion (which results in motion blur in the image), the production system captures a standstill image of left- and right-side so there is no motion blur in the image. The demo system uses fixed focusing image capture which is not able to focus on different focal points, while the production system uses a re-focusing image to increase inspection quality. The demo system uses lighting modules that are not optimized, but the production system will use enhanced lighting modules that increase inspection quality.

(234) In some cases, where a system for visually grading a mobile device is needed, said system will include an artificial intelligence section for grading, and a robotic device for handling and capturing images of the mobile device. Enhanced lighting and dome diffusers ensure that critical areas can be captured for optimal image quality so the AI can accurately determine the correct condition (flawless, lightly-scratched, heavily scratched, etc.) of the mobile device. In some cases the mobile device can be flipped (reversed) to reduce the number of required cameras. The artificial intelligence in this model is trained using a rule-based set and a rule-based algorithm or main engine so the field of training is extra wide, thus eliminating the need for retraining every time there is a minor change in model features.

(235) At least some aspects of the present disclosure will now be described with further reference to the following numbered example aspects.

(236) Example aspect 1. A system for visually grading a mobile device, the system comprising: at least one processor for executing various sections of code, including an artificial intelligence section for performing the actual grading, and a robotic device coupled to the processor for handling and viewing the mobile device and capturing a series of very high quality images of each mobile device under inspection, those images provided to the artificial intelligence section for analysis and grading.

(237) Example aspect 2. The system as in example aspect 1, wherein enhanced lighting for specific areas ensures that critical areas can be captured optimally with very high quality, allowing the AI to distinguish between flawless devices, lightly scratched devices, heavily scratched devices and devices as well as cracks.

(238) Example aspect 3. A system as in any of example aspects 1 and 2, wherein the device is reversed, in order to reduce the number of cameras required.

(239) Example aspect 4. A system as in any of example aspect 1-3, wherein dome diffusers are used to diffuse the light.

(240) Example aspect 5. A system as in example aspect 1, wherein the artificial intelligence is trained using a rule-based set making the field of training extra wide, eliminating the need for retraining every time there is a minor change in model features.

(241) Example aspect 6. A system as in example aspect 1, wherein the artificial intelligence is trained using a rule-based grading algorithm, eliminating the need for retraining every time there is a minor change in model features.

(242) Example aspect 6. A system for visually grading a mobile device, the system having at least one processor for executing various sections of code, including an artificial intelligence section for performing the actual grading, the processor coupled to a robotic device for handling and viewing the mobile device and capturing a series of very high quality images of each mobile device under inspection, those images provided to the artificial intelligence section for analysis and grading.

(243) Various embodiments of the present disclosure may be implemented in computer hardware, firmware, software, and/or combinations thereof. Methods of the present disclosure can be implemented via computer program instructions stored on one or more non-transitory computer-readable storage devices for execution by a processor. Likewise, various processes (or portions thereof) of the present disclosure can be performed by a processor executing computer program instructions. Embodiments of the present disclosure may be implemented via one or more computer programs that are executable on a computer system including at least one processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. Each computer program can be implemented in any suitable manner, including via a high-level procedural or object-oriented programming language and/or via assembly or machine language. Systems of the present disclosure may include, by way of example, both general and special purpose microprocessors which may retrieve instructions and data to and from various types of volatile and/or non-volatile memory. Computer systems operating in conjunction with the embodiments of the present disclosure may include one or more mass storage devices for storing data files, which may include: magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data (also called the “non-transitory computer-readable storage media”) include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM disks. Any of the foregoing can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits) and other forms of hardware.

(244) In some cases, a system for testing and reprogramming mobile communication devices, such as, for example, cellular phone, tablets, etc., may enable parallel connection of a large number of devices via, typically, USB cables, to connectors in the system box, with indicator lights for communicating to an operator the device status and readiness. Further, in such a system only one step may be required to charge the device to an operational state, without operator interaction.

(245) In other cases, a system for testing and reprogramming mobile communication devices may enable parallel connection of a large number of devices to connectors in the system box, with the system using different sequences to test, verify, securely delete content, and reprogram devices. Further, the system analyzes problems such as, for example, bricked devices, dead batteries, and unprogrammable and unstable devices, and collects information about the quality of devices based on their different sources. In addition, the system may collect data about the efficiency of the operators connecting and removing devices at any one system box, or about operators at multiple systems in one testing facility. The system may then communicate its collected data to a central server.

(246) In some cases, a system may include with a computer containing software for processing both data and programs on mobile devices. Further, the system may perform a quick evaluation of said mobile device and where feasible, may determine the current commercial value of the mobile device based on make, model, physical condition and other parameters associated with device. Additionally the system includes a tower containing a number of lockable compartments connected to the computer. Each compartment can receive a mobile device, and an application on a mobile device, such as a tablet, of an authorized user can lock the compartment so the device in the compartment can be tested for certain parameters. After a successful test, the system makes an offer to the device owner, and upon legally binding electronic acceptance of the offer, the system locks

the drawer of the owner's device and back up into secure local storage the owner's data as needed, with determination of the need based on questions presented to the owner during or immediately after the presentation and/or acceptance of the offer. Then the owner's address book is processed, so it is available as quickly as possible so the owner can then transfer it to a new device without undue delay. Subsequently, large bulk data can be transferred in a throttled mode, on a first-come, first-serve manner. Additionally, the system makes provisions for the onward disposition logistics of the owner's device, based on information supplied by or in conjunction with the entity taking possession of the device.

(247) In some cases, a system for migration of computer content, including but not limited to applications and various types of data, from one computing device, such as, for example, a smartphone, a phablet, a tablet, or other, similar device, and from cloud services to another device and other cloud services may create a map showing what content needs to be migrated, and where to, so that that the content can be transferred to the new device and/or one or more cloud services upon activation of the new device.

(248) In some cases, a system may simulate a human user touching the screen of a device, such as a cell phone or similar, that has a capacitive touch screen, with the device positioned on a touch simulator that has a matrix of individually addressable, electric structures based on an LCD display. In such a system, a camera may photograph the device screen and transmit the resulting images to a computer, where the interactions of the touch simulator and the device are recorded. Additionally, software on a computer can create scripts for future, similar interactions, using the stored images to test similar devices for functionality. Alternatively, the system may simulate human touch on the device screen through a matrix of individually addressable, XY resolved electric structures based on inflatable tubes.

(249) In some cases, a system for reviewing returned smartphones and other computing devices may employ a device-specific protocol for a multistep procedure, with as many of the steps as possible removed from personal judgment. A matching application on the device would support certain steps of the operator and can fill in certain responses. This system may note in a log the steps that were performed without the operator's help, but the operator may override the system with a note and acknowledgement. Further, such a system may require an operator to make a deliberate choice of various status messages when starting to evaluate such a device, starting at a neutral state and actively moving a status report to a yes or a no. In many cases, a script may perform different sets of tests for different devices based on the system owner's preferences.

(250) In some cases, a mobile device such as a smart phone or smart computing device may be connected to a network, and an operating system, an application for communicating to other devices, and applications are installed. This device may be a wireless device, a smart phone or a tablet, a mobile communication device, and/or a wearable device; and it may be connected to a wireless communication network. These applications may enable a user to pursue additional interests, including but not limited to listening to and/or creating music, viewing and/or editing documents, viewing and/or creating videos, consuming and/or creating video games, participating in social networks, etc. on the device. Additionally, software may be installed to follow user activities on the device and to catalogue and record these activities. Further, based on activities, device accessories used in the activities, and on service plans to which the user has subscribed, a user profile is created. The system may then compare this user profile to other user profiles that match at least in one of the groups of accessories, activities, and service plans and then determines whether the user could benefit from adding one of the other groups that other users have. Thus the system may determine whether an upsell opportunity exists, in which case an offer for additional products and/or services that would enable a user to take advantage of additional offerings to make better use of his device and/or services may be extended to the user.

(251) In some cases, an attachment to a mobile device, such as a smart cell phone, may enable a 5G signal to be detected and scanned. This signal and other environmental information, including but

not limited to view, GPS, Wi-Fi and other radio signals, etc., may be recorded concurrently to create a map of the environment that could be stored so an application could calculate the optimal location for a gateway type router. Thus a 5G signal from the outside could be fed securely and reliably to all rooms of a unit in a building, enabling the use of 5G communication devices inside buildings with poor or no reception, in some cases by translating the communication to an alternate band such as 4G or Wi-Fi. Such a scan could include also immediate adjacent areas outside a unit. This software could be the primary method to determine the optimal location for such a router. Additionally, the data may be sent to a technician for further review leading to determination of a preferred location, and in some cases, the user's permission must be obtained to share the data before sending the data to the technician for review.

(252) In some cases, a system for handling reverse logistics of mobile devices may, after unpacking a device, check that device for a sufficient charge, and if a sufficient charge is not found, charge the device. Then based on its software platform software, the system installs software that reads and displays on the device screen key parameters such as model, make, memory size, OS version, wipe status, battery status and health, etc. The system may then send that information over the device's network to one or more processors in the system for further processing and control. If the device is judged worthy of further processing, it is cleaned and further prepared for data removal, testing, and reprogramming by robotic devices. Then a robotic visual inspection grades the device, with devices below a certain threshold being removed from the process, to be used as either low-end devices or for spare parts; while devices that successfully pass all tests are reprogrammed and then stored for resale.

(253) Various embodiments of the present disclosure may be implemented in computer hardware, firmware, software, and/or combinations thereof. Methods of the present disclosure can be implemented via a computer program instructions stored on one or more non-transitory computer-readable storage devices for execution by a processor. Likewise, various processes (or portions thereof) of the present disclosure can be performed by a processor executing computer program instructions. Embodiments of the present disclosure may be implemented via one or more computer programs that are executable on a computer system including at least one processor coupled to receive data and instructions from, and to transmit data and instructions to, a data storage system, at least one input device, and at least one output device. Each computer program can be implemented in any suitable manner, including via a high-level procedural or object-oriented programming language and/or via assembly or machine language. Systems of the present disclosure may include, by way of example, both general and special purpose microprocessors which may retrieve instructions and data to and from various types of volatile and/or non-volatile memory. Computer systems operating in conjunction with the embodiments of the present disclosure may include one or more mass storage devices for storing data files, which may include: magnetic disks, such as internal hard disks and removable disks; magneto-optical disks; and optical disks. Storage devices suitable for tangibly embodying computer program instructions and data (also called the “non-transitory computer-readable storage media”) include all forms of non-volatile memory, including by way of example semiconductor memory devices, such as EPROM, EEPROM, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM disks. Any of the foregoing can be supplemented by, or incorporated in, ASICs (application-specific integrated circuits) and other forms of hardware.

(254) Changes and modifications may be made to the disclosed embodiments without departing from the scope of the present disclosure. These and other changes or modifications are intended to be included within the scope of the present disclosure, as expressed in the following claims.

Claims

1. A system comprising: a processor; a camera; and a robotic apparatus having: a transport platform, wherein the transport platform is configured to move a mobile computing device past the camera; and a memory for tangibly storing thereon computer-readable instructions configured to be executed by the processor to: access a grading model, wherein the grading model is configured to:
determine whether a mobile device is refurbished; receive, from the camera, a set of one or more images of the mobile computing device; wherein the set of one or more images comprises a first image of the mobile computing device and a second image of the mobile computing device; wherein the first image of the mobile computing device is captured when the mobile computing device is in a first placement in relation to a grading machine, and the second image of the mobile computing device is captured when the mobile computing device is in a second placement in relation to the grading machine; and grade the mobile computing device based on the set of one or more images of the mobile computing device using the grading model.
2. The system of claim 1, further comprising one or more lighting modules, wherein the one or more lighting modules are controlled to capture the set of one or more images of the mobile computing device in a quality that allows the grading model to distinguish between at least two categories among categories of flawless mobile computing devices, lightly scratched mobile computing devices, heavily scratched mobile computing devices, and mobile computing devices with cracks.
3. The system of claim 1, wherein the grading the mobile computing device based on the set of one or more images comprises using data augmentation in combination with an artificial intelligence (AI) incremental learning feature of the grading model to assign a grade to the mobile computing device.
4. The system of claim 1, wherein the grading the mobile computing device based on the set of one or more images comprises: performing analysis of the set of one or more images; applying the analysis to a rule based engine to generate a result; and grading the mobile computing device based at least in part on the result to assign a grade to the mobile computing device.
5. The system of claim 1, wherein the computer-readable instructions are further configured to: apply a grade generated by the grading of the mobile computing device to a collection of augmentation data; and modify an AI grading model based on the collection of augmentation data.
6. The system of claim 1, comprising a plurality of cameras, wherein an up-side view image of the mobile computing device and a down-side view image of the mobile computing device are captured by the camera, and a top-side view image of the mobile computing device and a back-side view image of the mobile computing device are captured by a second camera.
7. The system of claim 1, further comprising a dome diffuser, wherein the dome diffuser is used to diffuse light for capturing an image of the set of one or more images.
8. A method comprising: accessing an artificial intelligence (AI) grading model generated based on a plurality of grade criteria associated with a plurality of models of mobile computing devices; and capturing a set of one or more images of a mobile computing device, including: moving the mobile computing device past a camera; wherein the set of one or more images comprises a first image of the mobile computing device and a second image of the mobile computing device; wherein the first image of the mobile computing device is captured when the mobile computing device is in a first placement in relation to a grading machine, and the second image of the mobile computing device is captured when the mobile computing device is in a second placement in relation to the grading machine; and grading the mobile computing device based on the set of one or more images of the mobile computing device using the AI grading model, wherein the AI grading model is configured to determine whether a mobile device is refurbished.
9. The method of claim 8, wherein the grading the mobile computing device based on the set of one or more images comprises using data augmentation in combination with an AI incremental learning feature of the AI grading model to assign a grade to the mobile computing device.

10. The method of claim 8, wherein the grading the mobile computing device based on the set of one or more images comprises: performing analysis of the set of one or more images; applying the analysis to a rule based engine to generate a result; and grading the mobile computing device based at least in part on the result to assign a grade to the mobile computing device.
11. The method of claim 8, further comprising: applying a grade generated by the grading of the mobile computing device to a collection of augmentation data; and modifying the AI grading model based on the collection of augmentation data.
12. The method of claim 8, wherein the set of one or more images comprises at least one of: a top-side view image of the mobile computing device, a back-side view image of the mobile computing device, an up-side view image of the mobile computing device, a down-side view image of the mobile computing device, a left-side view image of the mobile computing device, and a right-side view image of the mobile computing device.
13. The method of claim 12, wherein the top-side view image of the mobile computing device, the up-side view image of the mobile computing device, the down-side view image of the mobile computing device, the left-side view image of the mobile computing device, and the right-side view image of the mobile computing device are captured when the mobile computing device is in a first placement in relation to a grading machine, and the back-side view image is captured when the mobile computing device is in a second placement in relation to the grading machine.
14. The method of claim 12, comprising a plurality of cameras, wherein the up-side view image of the mobile computing device and the down-side view image of the mobile computing device are captured by a first of the plurality of cameras, and the top-side view image of the mobile computing device and the back-side view image of the mobile computing device are captured by a second of the plurality of cameras.
15. A non-transitory computer readable storage media for configuring a set of one or more computing devices, the computer readable storage media comprising one or more computer-readable instructions configured to cause one or more computer processors to execute operations comprising: accessing an AI grading model generated based on a plurality of grade criteria associated with a plurality of models of mobile computing devices; and capturing a set of one or more images of a mobile computing device, including: moving the mobile computing device past a camera; and grading the mobile computing device based on the set of one or more images of the mobile computing device using the AI grading model, wherein the AI grading model is configured to determine whether a mobile device is refurbished; wherein the set of one or more images comprises a first image of the mobile computing device and a second image of the mobile computing device; wherein the first image of the mobile computing device is captured when the mobile computing device is in a first placement in relation to a grading machine, and the second image of the mobile computing device is captured when the mobile computing device is in a second placement in relation to the grading machine.
16. The non-transitory computer readable storage media of claim 15, wherein the grading the mobile computing device based on the set of one or more images comprises using data augmentation in combination with an AI incremental learning feature of the AI grading model to assign a grade to the mobile computing device.
17. The non-transitory computer readable storage media of claim 15, wherein the grading the mobile computing device based on the set of one or more images comprises: performing analysis of the set of one or more images; and applying the analysis to a rule based engine to generate a result and grading the mobile computing device based at least in part on results of the analysis to assign a grade to the mobile computing device.
18. The non-transitory computer readable storage media of claim 15, wherein the set of one or more images comprises at least one of: a top-side view image of the mobile computing device, a back-side view image of the mobile computing device, an up-side view image of the mobile

computing device, a down-side view image of the mobile computing device, a left-side view image of the mobile computing device, and a right-side view image of the mobile computing device.
