

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401515
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Constable; Colin et al.

Enhanced login processes using proprietary security and protocol for sharing and managing personal information

Abstract

The present disclosure involves systems, software, and computer implemented methods for enhanced login processes. A first login page of a website is received that includes a field that enables a user to enter a handle for a decentralized resource directory. A handle for the decentralized resource directory is received in the field and provided to a webserver. A second login page is received that includes a challenge code for the handle. A challenge value is generated based on the challenge code. A location in the decentralized resource directory is determined, based on the challenge value. A request is sent to a protocol server that manages the personalized resource directory to store the challenge value in the decentralized resource directory at the location as a login challenge response for logging into the website. A login result page is received that indicates a result of the webserver processing the login challenge response.

Inventors:	Constable; Colin (San Jose, CA), Nickels; Kevin (San Jose, CA)
Applicant:	Atsign, Inc. (San Jose, CA)
Family ID:	1000008782835
Assignee:	Atsign, Inc. (San Jose, CA)
Appl. No.:	18/570187
Filed (or PCT Filed):	June 16, 2022
PCT No.:	PCT/US2022/033854
PCT Pub. No.:	WO2022/266364
PCT Pub. Date:	December 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240146533 A1	May. 02, 2024

Related U.S. Application Data

us-provisional-application US 63211664 20210617

Publication Classification

Int. Cl.: H04L9/32 (20060101); H04L9/30 (20060101)

U.S. Cl.:

CPC H04L9/3226 (20130101); H04L9/3073 (20130101); H04L9/3271 (20130101);

Field of Classification Search

CPC: H04L (9/3226); H04L (9/3073); H04L (9/3271); H04L (63/107); H04L (67/1021); H04L (9/0825); H04L (9/3247); H04L (63/08); H04L (63/0853); H04L (63/101); H04L (63/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6343361	12/2001	Nendell	380/278	H04L 63/0428
8594632	12/2012	Azizi et al.	N/A	N/A
9083531	12/2014	Chenna	N/A	N/A
9258118	12/2015	Roth et al.	N/A	N/A
9571480	12/2016	Asveren	N/A	N/A
11271933	12/2021	Dee	N/A	N/A
11546337	12/2022	Le et al.	N/A	N/A
11849053	12/2022	Nickels et al.	N/A	N/A
2004/0044727	12/2003	Abdelaziz et al.	N/A	N/A
2007/0118879	12/2006	Yeun	N/A	N/A
2008/0091615	12/2007	Choi et al.	N/A	N/A
2015/0178515	12/2014	Cooley et al.	N/A	N/A
2016/0182500	12/2015	Ligatti et al.	N/A	N/A
2017/0257358	12/2016	Ebrahimi et al.	N/A	N/A
2018/0367526	12/2017	Huang et al.	N/A	N/A
2019/0149539	12/2018	Scruby	N/A	N/A
2020/0085408	12/2019	Lemaitre et al.	N/A	N/A
2020/0145451	12/2019	Hansen	N/A	N/A
2020/0252392	12/2019	Mullins et al.	N/A	N/A
2021/0058374	12/2020	Smith et al.	N/A	N/A
2021/0110015	12/2020	McCarty	N/A	G06F 21/32

2021/0272120	12/2020	Murdoch	N/A	G06Q 20/3829
2021/0288973	12/2020	Dimble et al.	N/A	N/A
2023/0015819	12/2022	Nickels et al.	N/A	N/A
2024/0039739	12/2023	Nickels et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO 2019/226115	12/2018	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report in European Appln. No. 22825850.5, mailed on Jun. 27, 2024, 9 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/US2021/040628, dated Jan. 19, 2023, 12 pages. cited by applicant

International Preliminary Report on Patentability in International Appln. No. PCT/US2022/033854, mailed on Dec. 14, 2023, 7 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/US2021/040628, mailed on Dec. 2, 2021, 15 pages. cited by applicant

International Search Report and Written Opinion in International Appln. No. PCT/US2022/033854, mailed on Oct. 25, 2024, 8 pages. cited by applicant

Li et al. "Research on CoAP Resource Directory Based on Blockchain." IEEE 4th Information Technology, Networking, Electronic and Automation Control Conference (ITNEC), May 2020, 1:1730-1735. cited by applicant

Ylonen et al., "Security of interactive and automated access management using Secure Shell (SSH)," National Institute of Standards and Technology, Oct. 2015, 50 pages. cited by applicant

Primary Examiner: Okeke; Izunna

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

CLAIM OF PRIORITY (1) This application claims priority under 35 USC § 119(e) to U.S. Patent Application Ser. No. 63/211,664, filed on Jun. 17, 2021, the entire contents of which are hereby incorporated by reference. CROSS-REFERENCE TO RELATED APPLICATIONS (2) This application is related to PCT Application PCT/US2021/040628, filed Jul. 7, 2021, titled "AUTOMATION OF USER IDENTITY USING NETWORK PROTOCOL PROVIDING SECURE GRANTING OR REVOCATION OF SECURED ACCESS RIGHTS"; the contents of which are hereby incorporated by reference.

TECHNICAL FIELD

(1) The present disclosure relates to computer-implemented methods, software, and systems for enhanced login processes using a proprietary protocol for sharing and managing personal information.

BACKGROUND

(2) Peer-to-peer (P2P) computing or networking is a distributed application architecture that can include partitioning of tasks between peer computing devices. Peers can form a peer-to-peer network of nodes. In a P2P environment, peers can make a portion of their resources, data, and/or metadata, such as processing power, disk storage or network bandwidth, directly available to other

network participants, without requiring central coordination. Peers can be both suppliers and consumers of resources, in contrast to a traditional client-server model in which servers supply resources and clients consume resources.

SUMMARY

(3) The present disclosure involves systems, software, and computer implemented methods for enhanced login processes using a proprietary protocol for sharing and managing personal information.

(4) An example system includes a first user device of a user, a protocol server associated with the user comprising a decentralized resource directory, and a webserver associated with a website. The first user device is configured to send a request to the webserver for a first login page of the website. The webserver is configured to: receive the request for the first login page of the web site; generate the first login page of the web site, wherein the first login page includes a field that enables the user to enter a handle for the decentralized resource directory; and provide the first login page of the website to the first user device. The first user device is further configured to: receive the first login page of the web site; present the first login page of the web site; receive, from the user, the handle for the decentralized resource directory; and provide the handle for the decentralized resource directory to the web server. The web server is further configured to: receive the handle for the decentralized resource directory from the first user device; generate a unique challenge code for the handle; insert the unique challenge code for the handle into a second login page; and provide the second login page that includes the unique challenge code for the handle to the first user device. The first user device is further configured to: receive the second login page that includes the unique challenge code for the handle; present the second login page that includes the unique challenge code for the handle; obtain the unique challenge code for the handle from the second login page; generate a challenge value based on the unique challenge code; determine, based on the challenge value, a location in the decentralized resource directory; and send a request to the protocol server to store the challenge value in the decentralized resource directory at the location. The webserver is further configured to: send a request to the protocol server to obtain the challenge value from the location in the decentralized resource directory; receive the challenge value from the protocol server; generate a server challenge value, using the challenge code sent to the first user device and the handle received from the first user device, to compare to the challenge value received from the protocol server; determine whether the server challenge value matches the challenge value received from the protocol server; log the user into the website in response to determining that the server challenge value matches the challenge value received from the protocol server; and deny a login request to the web site for the user in response to determining that the server challenge value does not match the challenge value received from the protocol server.

(5) An example method includes: receiving a request from a user device of a user for a first login page of a website; generating the first login page of the website, wherein the first login page includes a field that enables the user to enter a handle for a decentralized resource directory; providing the first login page of the website to the user device; receiving the handle for the decentralized resource directory from the user device; generating a unique challenge code for the handle; inserting the unique challenge code for the handle into a second login page; providing the second login page that includes the unique challenge code for the handle to the user device; sending a request to a protocol server to obtain a challenge value stored by the user device at a location in a decentralized resource directory associated with the handle, wherein the challenge value and the location are generated by the user device based on the challenge code; receiving the challenge value from the protocol server; generating a server challenge value, using the challenge code sent to the user device and the handle received from the user device, to compare to the challenge value received from the protocol server; determining whether the server challenge value matches the challenge value received from the protocol server; logging the user into the website in response to determining that the server challenge value matches the challenge value received from the protocol

server; and denying a login request to the website for the user in response to determining that the server challenge value does not match the challenge value received from the protocol server.

(6) Another example method includes: sending a request to a webserver for a first login page of a website; receiving the first login page of the website, wherein the first login page includes a field that enables a user to enter a handle for a decentralized resource directory; presenting the first login page of the website; receiving, from the user, the handle for the decentralized resource directory; providing the handle for the decentralized resource directory to the webserver; receiving, from the webserver, a second login page that includes a unique challenge code for the handle that was generated by the webserver; presenting the second login page that includes the unique challenge code for the handle; obtaining the unique challenge code for the handle from the second login page; generating a challenge value based on the unique challenge code; determining, based on the challenge value, a location in the decentralized resource directory; sending a request to a protocol server to store the challenge value in the decentralized resource directory at the location as a login challenge response for logging into the website; and receiving from the webserver, a login result page that indicates a result of the webserver processing the login challenge response.

(7) Implementations may include one or more of the following features. The first user device can be configured to cryptographically sign the challenge value for the handle using a private key of a public/private key pair for the handle. The webserver can be further configured to: send a request to the protocol server to obtain a public key of the public/private key pair for the handle from the decentralized resource directory; receive, from the protocol server, the public key of the public/private key pair for the handle; and decrypt the challenge value using the public key. The private key of the public/private key pair for the handle can be stored on the first user device. The first user device can be configured to cryptographically sign the challenge value for the handle using a public key of a public/private key pair associated with the website. The webserver can be further configured to decrypt the challenge value using a private key of the public/private key pair associated with the website. The first login page can include a field that allows the user to provide a user-provided code. The first user device can be configured to provide the user-provided code to the web server along with the handle of the user. The web server can be configured to generate the challenge code using the user-provided code. The system can include a second user device of the user. The first login page can be presented on the first user device and the user second device can be configured to generate the challenge value, determine the location in the decentralized resource directory, and send the request to the protocol server to store the challenge value in the decentralized resource directory at the location. The challenge code can be a scannable code that is presented on the first user device and the second user device can be configured to scan the scannable code that is presented on the first user device. The decentralized resource directory can include shared user information for the user that the user has explicitly shared with an entity associated with the website. The webserver can be further configured to: send a request to the protocol server for the shared user information for the user in the decentralized resource directory that has been explicitly shared with the entity associated with the website; receive the shared user information; use the shared user information to generate at least one web page for the user while the user is logged into the website; and provide the at least one web page to the first user device. The first user device can be further configured to generate the challenge value based on the unique challenge code by generating a hash value of a combination of the handle and the unique challenge code. The first user device can be further configured to: generate a nonce value; generate the challenge value based on the challenge code and the nonce value; and send a request to the protocol server to store the nonce value in the decentralized location at a location that is based on the challenge code. The web server is further configured to: send a request to the protocol server to obtain the nonce from the decentralized resource directory; receive the nonce from the protocol server; and use the nonce when generating the server challenge value.

(8) While generally described as computer-implemented software embodied on tangible media that

processes and transforms the respective data, some or all of the aspects may be computer-implemented methods or further included in respective systems or other devices for performing this described functionality. The details of these and other aspects and embodiments of the present disclosure are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the disclosure will be apparent from the description and drawings, and from the claims.

Description

DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a block diagram illustrating an example system for user-controlled access control for user information.
- (2) FIG. 2 is a block diagram illustrating an example system for a public lookup transaction.
- (3) FIG. 3 is a block diagram illustrating an example system for a private lookup transaction.
- (4) FIGS. 4A and 4B are a combined swim lane diagram illustrating an example method for a private lookup transaction.
- (5) FIG. 5 is a block diagram illustrating an example system for a private lookup transaction.
- (6) FIGS. 6A-6B are a combined swim lane diagram illustrating an example method for a private lookup transaction.
- (7) FIG. 7 illustrates an example system for use of encryption keys.
- (8) FIG. 8 illustrates an example system for use of encryption keys.
- (9) FIG. 9 illustrates an example system for key value retrieval.
- (10) FIG. 10 illustrates an example system for P2P applications.
- (11) FIG. 11 illustrates an example system for website login functionality using a protocol for sharing and managing personal information.
- (12) FIG. 12 is a block diagram of an example system for supporting website login functionality.
- (13) FIG. 13 is a block diagram of an example architecture for supporting website login functionality.
- (14) FIGS. 14A-14C illustrate a swim lane diagram for website login scenarios using a protocol for sharing and managing personal information.
- (15) FIG. 15 is a diagram that illustrates example user interfaces for website login scenarios using a protocol for sharing and managing personal information.
- (16) FIG. 16 is a flowchart of an example method for webserver participation in a login process.
- (17) FIG. 17 is a flowchart of an example method for client participation in a login process.

DETAILED DESCRIPTION

(18) As the Internet has grown into every facet of modern life, some of the most problematic issues people face are managing their identities and securing their data. Additionally, website and application developers may have to manage the identity of people thereby assuming an associated risk of managing data of other parties and incurring associated hosting and infrastructure costs. Applications that are monetized through advertising that includes tracking and identifying users can further result in various privacy concerns.

(19) To solve these and other problems, an improved and novel Internet Protocol (IP)-based communication protocol and system can be used to provide robust privacy controls for secure exchanges of information between entities. In particular, the solution provides protocol users with the ability to personally maintain and manage sharing of their personal information and data without reliance on a third-party service or application's settings and restrictions. The system includes a namespace directory, decentralized resource directories with secure key/value persistence, and a protocol (which can be referred to as the “@protocol”) for communication between entities. Information, including both data and services, can be securely and privately

exchanged over the protocol.

(20) As used herein, “users” or “protocol users” refer to users of the @protocol. Each protocol user can be a person, and it follows that multiple users can be “people.” A respective person can use the protocol, with any suitable device, including their own personal device, which can be referred to a “user device,” or “client device.” In general, a computing device that participates in the protocol can be associated with a participating entity, which can be a person, a corporate or other broader entity, or a finer-grained entity such as a specific item or “thing” (such as an IoT (Internet of Things)) device. Each entity that uses the protocol can be represented by a handle, which can be referred to as an “@sign”. Example @signs can include @alice, @bob, sales@amco, and myfurnace@alice. For a corporate or other entity, various handles can be supported, such as a handle for the entity itself (e.g., @amco), a handle for a general role for the entity (e.g., sales@amco), and a handle for specific users associated with the entity (e.g., alice.smith@amco).

(21) The namespace directory can be used for storing a list of unique identifiers (e.g., “@signs”) of protocol users together with routing information for the identifiers. Routing information can include, for example, a DNS (Domain Name System) location and IP port number of individual decentralized resource directory servers (which can be referred to as @sign servers) to which protocol requests can be routed.

(22) A response to a data or service request can be provided by a decentralized resource directory server based on a secure key/value persistence of the decentralized resource directory. A request can include an indication of a requested data item or service, as well as a target entity of the request. For example, a service-related request can have a syntax of a form of “service@entity.” Processing of a protocol request can include operations to ensure that both entities in an exchange are known to each other and that the request is permission checked before an appropriate response is determined and returned. Response information returned for a service@entity request can include or refer to (e.g., by value or by reference) information stored in a secure key/value persistence for the entity.

(23) The @protocol can allow for a person or an entity to configure the person or entity's own data records to be either publicly accessible (e.g., available to anyone who is aware of a corresponding key) or to be private (e.g., with limited, controlled access) and require validation of a requesting entity for access, where only people or entities specified by the person or entity who owns the data records can access the data, or corresponding portions if limited by the person or entity. As described in more detail below, some keys for public data can be discovered/exposed using a scan while other keys may not be discoverable by a scan. Access control for private data can be hard coded into the system rather than as an overlay data structure. To access private data, a requesting entity can be required to first prove, using the @protocol, a claimed identity, so that access rights can be determined. Accordingly, a response to a private data request can be based on a validated identifier of the requestor, and responses can vary between different requesting entities based on their respective level of approved access. For example, a person can configure permissions so that a query sent to the person for the person's location can result in different responses of “USA,” “Minnesota,” or an actual physical address, if sent from an unknown sender, a casual acquaintance, or a close friend, respectively, based on respective grants previously granted to respective entities. The person can also configure permissions for the location data so that no response is given to requests received from unknown senders.

(24) The features of the protocol can form a unique Internet permissioning system for securely controlling access to data and services. Permissioned access can be controlled strictly by an owner of a specific private namespace granting access to data or service(s) of the owner. Access grants can be subject to revocation by the owner.

(25) The permissioning system can provide various advantages. Several advantages relate to an enhanced level of control for people of their own personal information. For example, people are able to specify their own terms and conditions for the use of their data. Specified terms can be

defined in a data-use license and/or terms of service document, for example. A person can specify in a data-use license that a particular data item can be looked up but not stored or replicated, for instance.

(26) The @protocol is designed to only allow connections to occur when permission has been granted by the owner of each respective @sign handle. The response to a query, including whether to respond at all, as well as the payload of a response, is completely under the control of the owner of the @sign, which can allow for fine- or coarse-grained control of responses, which can include different responses to a same query to different users or entities. As a particular example, the protocol can enable a person, such as a person or user associated with the @sign of “@alice,” to share information, such as email, websites, credit card numbers, location data, or preferences, to other people or entities, such as a person “@bob,” under the complete control of and according to the personally-defined rules and permission of @alice alone.

(27) Providing each person or entity control of their own information can improve user experiences in a variety of ways. For example, the described method of directly asking Internet users for their information can allow for new application experiences providing less annoyance for both the requester and the user to whom the request is sent. The @protocol, with a set of predefined verbs, which can be different in (e.g., extended for) particular implementations can provide an ease of use and intuitiveness for protocol users. The system can provide people, entities, and even physical items (e.g., “things”)— or authorized users or persons associated therewith—a single location to manage digital information and a simple mechanism to allow others to request that information. Each protocol user, entity, or physical item can have and share a respective @sign, which can be used by others for future data requests. A simple @sign can be shared (e.g., on or as a business card, via text, email, or verbally, etc.), rather than separate items of information that may become outdated at some point. Sharing an @sign (e.g., @alice or sales@acme) can enable the contacting of Alice @alice or the sales role at AcmeCo, respectively, even if Alice's actual contact details change or if the actual person or people in the sales role at Acme company change.

(28) Generally, the protocol provides a hierarchical and decentralized permissioning system for establishing security and trust as a core part of the Internet, whether between people or between people and entities (e.g., brands). Respective @sign servers can participate in the @protocol without being surveilled or managed by a central entity. Additionally, end-to-end encrypted P2P applications that exchange data using the @protocol can be used without being subject to centralized surveillance, since they do not communicate through centralized and shared backend servers. Rather, protocol-enabled P2P applications can communicate directly with other applications at the edge of the decentralized network after a connection between peers is established.

(29) As another example, data managed by the system can be housed, for instance, in billions of independent @sign servers (which can be implemented as server devices and/or user devices), with each server storing data in a secure and encrypted manner. In contrast to a large database housed on a centralized system that may be vulnerable to a single security attack, any security attack that might be undertaken against the decentralized permissioning system would have to be performed separately against each @sign server, which would be cost and time prohibitive. Decentralized systems can be more trustworthy than a centralized system that has an inherently higher risk (and perhaps history) of data breaches for centrally-stored data. Historical security issues with centralized systems generally result in erosion of trust in the centralized system.

(30) The @protocol is designed as a low-level, real-time Internet permissions protocol. The permissions-based protocol is low-level in that it can prevent a transfer of secured data until permission is verified. Permissions are checked prior to any data transfer, and data is only transferred in response to a successful verification, thereby providing a near real time response that ensures current data, in some cases, without—or with reduced—caching. Application developers (and in some cases, application users) can specify caching parameters for an application, such as

whether caching of data is intended or preferred, for instance.

(31) The system supporting the @protocol is based on a global-scale architecture that is dependable as the system scales. Distributed @sign servers and an addressing scheme can support at least one hundred billion people, entities, and things, for example. Dependability is achieved based on architectural designs for confidentiality, integrity, and availability.

(32) The open-source @protocol has a well-defined architecture and a reference implementation codebase that can be published to third party reviewers to facilitate code review and extensive security testing. The architecture is grounded in fundamental tenets of 1) distributing data when possible and centralizing data when necessary, 2) requiring permission for data access, and 3) empowering ownership of data. The @protocol provides a well-defined set of functionality that is extensible, enabling developers to add useful extensions and take advantage of the security and protection offered by the solution.

(33) Application developers can beneficially leverage various aspects of the @protocol. With protocol-enabled applications, users own and control their own data, so applications can be automatically compliant with GDPR (General Data Protection Regulation), CCPA (California Consumer Privacy Act), and other current and future privacy regulations. With personal data used by an application being stored with the person, the person, and not an application provider, stores keys and other sensitive information, such as personally identifiable information (PII). There is no longer a reason for the developer to add warnings to forms or other areas of an application or site where the user is entering data, as may be required for other applications and prior solutions. Automatic privacy compliance can result in a more empowering, reassuring experience for the user and less effort for a developer, as well as an inherent security to the system from end to end.

(34) User management, particularly of personal information, therefore, can be minimal (or non-existent) for an application developer, and can result in applications not needing an expensive backend infrastructure. Building an infrastructure to house and back up customer data can be a costly and time consuming part of application development. An application being developed to use the @protocol can save costs and time in getting the application to market, as compared to approaches that need development of a backend infrastructure, including security and storage. Fully decentralized P2P apps that have data stored on users' individual @servers may not require any backend infrastructure, for example, which can save substantial costs for the developer.

(35) Liability for data breaches may no longer exist for an application when the application developer does not hold any of the user's data. If the developer chooses to have personal data hosted on personal servers, for example, the individual people can become responsible for their own data, with the developer using best practices and the described @protocol to request and receive access to the personal data. Developers therefore, may avoid a liability for sensitive personal data, and can limit the amount of collected and managed data held by the application.

(36) Additionally, data management can be simplified, both for the developer and for the user. For example, password retrieval and out-of-date email addresses, if managed by the application developer, can create a large support burden for application providers. By using the @protocol, developers no longer have to develop functionality for and support password, login, and other personal data management. Once a user has an @ handle, they do not need to create a username or password for @protocol-compatible sites or applications—instead, they can simply use their @handle, and can verify themselves via the @protocol solution as described herein. Accordingly, the user can get started more easily with a new protocol-enabled application, resulting in a more satisfying user experience, which can benefit the developer as well as the user.

(37) FIG. 1 is a block diagram illustrating an example system **100** for user-controlled access control for user information. Specifically, the illustrated system **100** includes or is communicably coupled with various components that are connected by one or more public network(s) **101**. For example, the system **100** includes a governing body **102**, a protocol provider server **103**, application developers **104**, root servers **105**, backup servers **106**, user devices **107**, an application store **108**,

protocol servers **109** (e.g., @sign servers), and registrar servers **110**. Additionally, in some implementations, the system **100** includes enterprise user devices **111** that might not be directly connected to the public network(s) **101**, but are, for example, on a local area network **112**, behind a firewall in an enterprise, and connected to an enterprise microservice server **113** that is connected to the local area network **112** and the public network **101** that can do protocol exchanges on behalf of the enterprise user devices **111**. Although shown separately, in some implementations, functionality of two or more systems or servers may be provided by a single system or server. In some implementations, the functionality of one illustrated system or server may be provided by multiple systems or servers.

(38) The system **100** provides an ecosystem of compliant applications and services for granting or denying access rights in real time. The protocol, as implemented in the system **100**, can create a network of trust with structured data on a global scale. The protocol can be built upon protocols of TCP/IP (Transmission Control Protocol/Internet Protocol), DNS, HTTP (HyperText Transfer Protocol) (e.g., with future browser enhancements) and SSL/TLS (Secure Sockets Layer/Transport Layer Security). Use of the protocol can result in secure sharing of data and services between @handle owners and applications as specified in @sign servers, if explicitly allowed by both parties of a transaction. The protocol can be used for a large number of use cases that can benefit from user controlled privacy access. The protocol supports both a public lookup (in which the party querying data does not have to prove who they are) and a private lookup that confirms the @sign of the entity asking for information and allows the owner of the data to decide what information to share. Public lookups in general can be used to confirm the existence of an @sign or access specific information that may be set to public access.

(39) The protocol can be provided/developed by a protocol provider (shown interfacing with the system **100** by the protocol provider server **103**). Although a single protocol provider server **103** is shown, the protocol provider can be associated with various types and numbers of servers. And while shown as a single entity, the protocol provider can include or encompass different entities, such as a non-profit organization/foundation tasked with promoting and supporting the protocol and/or a company that provides various services and policies for the protocol.

(40) For example, the protocol provider server **103** can provide a source code distribution **114** and a documentation distribution **116**, include an application certifier **118** that generates application certification information **119**, and include a server configuration component **120** for configuring the root servers **105**. As another example, the protocol provider server **103** can provide secondary user server infrastructure and services, using user containers **122** and user microservices **124**. The components of the protocol provider server **103** are described in more detail below.

(41) In some implementations, the protocol provider server **103** provides governance of the protocol namespace. In other implementations and/or at different points in time, governance can be provided by the governing body **102**. The governing body **102** can be ICANN (Internet Corporation for Assigned Names and Numbers) or some other entity. The governing body **102** (and/or the protocol provider) can include a namespace governor **126** that governs the @sign namespace, including arbitration of namespace conflicts. The governing body **102** (and/or the protocol provider) can also include a registrar accreditor **128** for accreditation of registrars that can sell and maintain @signs and secondary server configurations.

(42) In some implementations, the protocol provider (e.g., as the protocol provider server **103** or other servers or components) can act as a registrar. Other third party registrars can be supported in some implementations. For example, the registrar servers **110** can provide a registration service **130** that maintains @sign data **132** by performing the registering, provisioning, transferring, renewal, and deletion of @sign handles for users.

(43) An @sign, such as @alice, is a unique identifier assigned to a user of the protocol. An @sign can be referred to as a handle, or an @sign handle, and can be a string of characters (e.g., Unicode characters) uniquely identifying a user and that is registered with a registrar. An @sign can serve as

a personal or corporate brand. An expanded Unicode character set can support a wide variety of characters for creative @sign handle creation. Within the system **100**, an @sign serves as an address that is resolvable by the root servers **105** to a secondary server endpoint, as described in more detail below.

(44) The root servers **105** are an implementation of a global namespace directory for the system **100**. The root servers **105** can store a list of unique identifiers (@signs) along with information for how to reach an @sign server that handles requests for a given @sign. For example, the root servers **105** can store and maintain mappings **137** that map @signs to location information for Internet-accessible user protocol microservices. Location information can be a DNS address plus a port number. The user protocol microservices, referred to herein as @sign servers, @servers, or protocol servers, implement individual, distributed, decentralized resource directories to which protocol requests are routed.

(45) The root servers **105** can provide redirection to the @server for a particular @sign. For example, the root servers **105** can offer a centralized lookup service **140** that provides access to a single @sign namespace. Unlike DNS, the @sign namespace can be implemented without Top Level Domains (TLDs) or subdomains. The lookup service **140** can be intentionally minimal for efficiency, offering just two items of information: 1) whether a particular @sign exists; and 2) if the @sign exists, how the server for the @sign can be reached.

(46) The lookup service **140** can support an @exit verb which can disconnect a connection with a requester. All other inputs to the lookup service **140** can be considered to be @sign lookup requests. Location information for @sign servers can be considered public information so the lookup service **140** can be configured to accept requests without requiring authentication. Users can first query the lookup service **140** for an Internet-addressable location of an @sign server before sending protocol requests to that @sign server.

(47) In response to a lookup query, the lookup service **140** can respond with a null value (or simply ignore a request) if a requested @sign does not exist. If the requested @sign does exist, then the lookup service **140** can return the DNS name or address (e.g., a Fully Qualified Domain Name (FQDN)) of the @server and the IP port number for the requested @sign. If a DOS (Denial Of Service) attack is detected, the lookup service **140** can reduce response time for replying to requests and/or terminate connections or restart the lookup service **140**. Other approaches for dealing with DOS attacks can be used. For example, the lookup service **140** can provide the IP address or other identifying information of an entity suspected of a DOS or other attack to upstream (or other) networks or entities, to either slow or delete DOS or other malicious traffic.

(48) TCP ports can be used for scaling @sign server addresses. A TCP port can be used, in general, to identify a service. Port 80 is generally used to identify a web service, for example. Port numbers can generally be a value from 0 to 65535, with only a portion of those values reserved for traditional services. For example, IP version four (IPV4) and IP version six (IPV6) can support port numbers. By using otherwise unassigned or unused port numbers to identify a particular user microservice or @sign server, each unique IP address can be mapped to approximately 65,000 unique microservices, by combining the IP address with a port number. Port numbers thus can allow for scalability at a global scale, since an IP address plus port number scheme can support billions of uniquely-identified microservices.

(49) In general, the root servers **105** can be designed to be cost effectively scaled to handle trillions of requests for billions of records. Root servers **105** can be architected to just provide the single lookup service **140** for the mappings **137**, e.g., to include a minimum amount of information for fulfilling lookup requests. In-memory databases and other performance-improving approaches can be used. For example, multiple read-only copies or replicas (e.g., shards) of the mappings **137** can be used, and a given request can be hashed to identify a particular subset database in which to lookup a given @sign. For instance, a first mappings database can hold @signs starting with the letters “a” through “m” and a second mappings database can hold @signs starting the letters “n”

through “z.” As another example, DNS records for multiple root servers **105** can be used to share an overall load across the multiple root servers **105**. For instance, traffic can be routed to a nearest and/or fastest root server **105**, or a root server **105** with a lightest current load.

(50) As yet another example, the root servers **105** can be configured so that read-only replicas serve the request load and a main root server **105** serves as the master. The main root server **105** can have a preconfigured DNS address (e.g., root.atsign.org). At least some of the root servers **105**, including the master root server, can be configured, operated, and/or provided by the protocol provider. The protocol provider can manage a cluster of root servers, for example. The master root server and/or the protocol provider can maintain IP addresses of the various root servers. In some implementations, third party provider(s) can provide at least some of the read-only replica root servers. In some implementations, a third party representing a particular organization can deploy their own root server(s) for their organization, and maintain internal addressing for their own namespace that may also bridge to the global @sign namespace.

(51) Referring again to the registrar servers **110**, the @sign data **132** maintained by the registrar servers **110** can include information for user provisioned @signs. The @sign data **132** can also include information for reserved @signs, such as for countries, states, or @signs that correspond to registered trademarks. When a user deletes (e.g., gives up) an @sign, the registration service **130** can mark the @sign as available to other users or entities. Similarly, the registration service **130** can periodically determine @signs that have not been renewed, and identify the unrenewed @signs as available. Renewal dates can also be included in the @sign data **132**. The registration service **130** can periodically determine, in general, which free and/or for-fee @signs are available.

(52) The registrar servers **110** can maintain user contact data **134** for sending renewal reminders or other notices. Financial data **136** can include pricing data for vanity @signs and payment records for @sign purchase transactions. Registrars can store a minimum amount of personally identifiable information (PII), if any. In some implementations, registrars can provide some @sign handles for free and charge a fee for certain (e.g., desirable/vanity) @sign handles.

(53) The registration service **130** can provide a registration application **138** to user devices **107**, for example. The registration application **138** can be provided as an application to install on a given user device **107** or as a web site accessed by the user device **107**. The registration application **138** can be used by users to provision @signs. For example, a user can use the registration application **138** to search for available @signs, view a list of available @signs, view a list of suggested @signs, check if a format of a desired @sign is valid, and view which vanity @signs are available and at what cost. Once an available @sign has been selected (or entered), the user can use the registration application **138** to register the @sign.

(54) Registration can include providing payment to secure a particular @sign, such as for premium or otherwise desired or likely-to-be desired @signs, which may be associated with a cost. Payment can include, for example, an agreement to and payment of a yearly subscription fee. Payment information and details provided through the registration application **138** can be stored in the financial data **136**.

(55) Management and maintenance of @signs can be performed using the registration application **138**. For example, users can use the registration application **138** to receive alerts about upcoming @sign renewals (as generated by the registration service **130**), pay for a renewal, view a dashboard of assigned @signs and renewal dates, or delete (e.g., give up) an @sign. As another example, the user can use the registration application **138** to select an @sign to sell, set up advertising for the for-sale @sign (to be displayed to other potential users on a registration website, for example), or to transfer an @sign to another entity.

(56) The registration application **138** can also be used to bind (or rebind) an @sign to server information for an @sign server. For example, @sign registration can include mapping the registered @sign to server information for an @sign server that can handle protocol exchanges for the @sign. The server information can be a single IP address (and possible port number) or a

FQDN and (possible) port number. Using an IP address or a FQDN/port can have advantages and disadvantages.

(57) For example, if a DNS address is used then the IP address mapped to the DNS address can be changed without changing a root entry. However, DNS can cache data meaning migration to a new IP address for an @sign could take hours or possibly days due to the distributed caching nature of DNS. If an IP address is used as the server information for an @sign an IP address update can be completed more quickly, since protocol guidelines can specify that resolvers or applications may cache IP addresses, for example, for up to 10 minutes. However, if an IP address is mapped directly to an @sign, the IP address for the @sign cannot be changed without contacting the registrar to request an update to a root entry. In some implementations, DNS is preferred over use of IP addresses.

(58) The registrar server **110** can store @sign data for registered and bound @signs in the @sign data **132**. The registrar server **110** can send a request to the root server **105** to create a root entry that maps the @sign to the server information for the @sign. In some implementations, @sign to server mapping information is only held in the root servers **105** (and not in the @sign data **132** maintained by the registrar).

(59) Server information for @sign servers can refer to different types of devices and services. Essentially, an @sign server process can run on any device for which an IP address (and possible port number) given by the root server **105** is an Internet-routable address. For example, the protocol server **109** can be a dedicated (e.g., always-on) protocol-enabled device that can handle requests for a particular @sign. The protocol server **109** can execute a user microservice **142** for a particular @sign handle, providing access (based on assigned access rights) to a personal directory **144** that stores information for the @sign handle. The protocol server **109** can be a server device (managed by a third party), a user device (e.g., personal server) that is continuously connected to the network **101**, an IoT (Internet of Things) device, or some other protocol-enabled, network-connected device.

(60) As another example, a protocol service can run on a user device **107** (e.g., as implemented by a settings application **145** or another process). Since some user devices may be occasionally offline, the user device **107** can be mapped to a secondary server. The secondary server can be the protocol server **109** or can be a cloud-based user microservice provided, for example by the registrar, the protocol provider, or another entity. Third party providers can agree to comply with protocol guidelines before being allowed to act as a cloud provider for secondary server infrastructure.

(61) As an example of cloud infrastructure, the protocol provider server **103** can provide the user microservices **124** as @sign server processes for users for access to user-specific user containers **122**. Similarly, additionally, and/or alternatively, the registrar server **110** can provide user microservices **146** as @sign server processes for users for access to user-specific user containers **148**. User containers **122** or **148** may be associated with TLS certificates. The TLS certificates may be associated with, for example, DNS information for the user microservice **124** or **146**. The TLS certificates can be used to provide authentication of both server and client connections to the @protocol microservice and to communicated encrypted traffic. A user microservice **124** or **146**, with its corresponding user container **122** or **148**, respectively, can be uniquely addressable using an assigned IP address and port number, as configured for the associated @sign in a corresponding root server entry.

(62) Container and microservice management, performed by the protocol provider server **103** and/or the registrar server **110**, can include management and deployment of user containers, in a multi-tenant container orchestration system. For example, user container management can include starting, stopping, and restoring user containers, deploying a given user microservice **124** or **146** as part of a user activation/registration process, and monitoring health of user containers, including resource allocation and usage, with automatic resource scaling as necessary. User containers can be reconfigured and redeployed in the event of an outage or hardware failure, for example. Data stored in user containers **122** or **148** can be encrypted for security. Decryption keys are discussed in more

detail below. Users who choose to use a secondary server implemented as a user microservice **124** or **146** can pay fee(s) (e.g., activation, subscription fees) to the protocol provider or the registrar, respectively, as part of a registration process.

(63) Registration can also include a bootstrapping process in which a secondary server instance is cryptographically bound to a user device **107**, such as during activation of the user device **107**, using a shared secret. For example, the registration application **138** can present a code (e.g., a QR (Quick Response) code) that includes the shared secret. The user can use the registration application **138** (or a camera application or similar functionality) to scan the code or otherwise retrieve the secret key from the code. The secret key can be stored on the user device **107** in a keys area **150**, preferably in a hardware trusted root on the user device **107**.

(64) The shared secret can also be provided (e.g., by the registrar server **110**) to the secondary server (e.g., microservice) associated with the user's @sign, for storage in the user's personal directory managed by the secondary server. The shared secret can be used by the user device **107** to authenticate to the secondary server. For example, an authentication process can include a key challenge and a challenge response, using the shared secret (e.g., using a CRAM (Challenge Response Authentication Mechanism) process).

(65) In some implementations, the shared secret is used to establish an authenticated connection between the user device **107** and the secondary server during activation and bootstrapping, with activation also including configuration of a public/private key pairing between the user device **107** and the secondary server. The user device **107** can generate a private key (and store the private key in the keys area **150**) and a corresponding public key, for sharing with the secondary server, such as by using a RSA (Rivest-Shamir-Adleman) algorithm. Once a public/private key pairing has been established, the shared secret can be removed from the secondary server (and in some cases from the keys area **150**). Removal of the shared secret from the secondary server can increase protection of encrypted user data on the secondary server, such as in a scenario where unauthorized access to the secondary server is somehow achieved. The public/private key pairing can be used for post-activation authentications of the user device **107** to the secondary server.

(66) Once the user device **107** is activated and configured, the user device **107** is recorded (e.g., in the @sign data **132**) as a registered device for updating data for the @sign handle to which the device **107** is registered. In some implementations, a given user device **107** can be registered as bound to multiple @signs. The user device **107** can store @sign handle(s) **152** for which the user device **107** is registered and corresponding public/private key pairs for each @sign.

(67) The settings application **145** running on the user device **107** can act as a secondary server for a registered @sign handle, receiving and responding to protocol requests locally on the user device. The settings application **145** can provide access to data stored in a personal directory **154** on the user device **107**, for example. When the user device **107** is bound to a secondary server, the settings application **145** can synchronize the personal directory **154** with a personal directory stored in the secondary server (e.g., in a user container **122** or **148**). When data in the personal directory **154** (or the corresponding personal directory in the secondary server) is updated, a “sync” protocol verb can be automatically invoked that updates the corresponding personal directory, so that user device-based and cloud-based directories are kept synchronized. The user device **107** can be authenticated to the secondary server before a synchronization occurs. The user device **107** can cache secondary server connection information in cached data **156** and/or the user device **107** can obtain secondary server connection information from the root server **105**.

(68) Synchronization can include one or more of sending data from one directory to the corresponding directory, comparing received items to stored items, identifying items in the receiver's directory that may need updating, and identifying changes that may have occurred in the receiver's directory that may in turn need updating in the sender's directory. Comparison processing can use metadata that indicates changes, times of changes, etc.

(69) Event-based synchronization for a network-connected user device **107** can ensure that changes

occurring in one directory copy are reflected in the corresponding directory copy. If the user device **107** is occasionally offline, the user (and locally-installed applications) can still access the personal directory **154** on the user device **107** and any differences between the personal directory **154** and a secondary server directory copy can be automatically synchronized when the user device **107** comes back online.

(70) If the user device **107** is offline, protocol exchanges can be routed to and handled by the secondary server. In some cases, for protocol exchanges that may require user permission, a notification/permission request can be sent by the secondary server to the user device **107**. If the user device **107** is offline, the permission request can be queued and a corresponding application/protocol request can be held until the user device **107** is back online and the user is able to respond to the permission request. In some implementations, the secondary server can be configured to hold a limited number (e.g., one) of permission requests/notifications for the user/user device **107**, so as to prevent a bad actor from overflowing the secondary server (or the user device **107**) with permission requests or other notifications. As another example, the secondary server can utilize a block list to prevent spamming. Such block lists may be device- or user-specific, or may be used across the entire protocol.

(71) The settings application **145** running on the user device **107** can enable a user of the user device **107** to configure access rights to data stored in the user's personal directory (e.g., in the personal directory **154** and in the mirrored secondary server copy). The user can make certain data public, private, or accessible only to certain users, or any other suitable limitations or restrictions. Other permissions applied to data can include whether data can be copied, shared, or used to derive other data. In general, access rights of various kinds can be granted or revoked using the settings application **145**. Access rights can be stored in association with corresponding personal data, such as in the personal directory **154** (and synced with the secondary server copy).

(72) As mentioned, the settings application **145** can serve protocol requests for user data, either from other protocol servers or from an application on the user device **107**. In general, the settings application **145**, along with the corresponding secondary server, can provide @sign server functionality for the user to enable the user device **107**, and the user's @sign, as protocol participants. The settings application **145** can present notifications to the user and enable the user to respond to notifications. Notification responses or other protocol responses can be provided to a sending protocol-enabled participant. Notifications and responses can be sent and received in a P2P fashion, and thus can be free from surveillance by a third party. Notifications can be received by the setting application **145** or the corresponding secondary server automatically, without a need for polling as used in other protocols such as POP3 (Post Office Protocol 3) or IMAP (Internet Message Access Protocol).

(73) In general, an @sign (e.g., protocol) server, whether running on a cloud server, dedicated hardware, or on a user device **107**, can provide an addressable endpoint for protocol-based communication. Along with a first, centralized tier of root servers **105**, protocol servers can provide a second, decentralized tier of the protocol architecture. While the root servers **105** can be configured to respond to simple @sign lookup requests, the more complex handling of protocol requests for data can be distributed to billions of separate decentralized resource directories (e.g., the protocol servers) that are responsible for responding to the requests. In other words, the protocol servers represent a fully decentralized set of personal service directories, with each protocol server configured to respond to lookup and other requests for a particular @sign. The response for a requested data item or service can come from a secure key/value persistence in the respective decentralized resource directory managed by the protocol server receiving the request.

(74) The protocol request received at a protocol server can include a general syntax pattern of "service@entity" that includes both the data or service requested being included in addition to the entity identifier, with the request being directed to a decentralized resource directory instance for processing. The response data for a particular service@entity request can be stored in a secure

key/value persistence for the receiving entity. The value stored for the request can either be stored by value or by reference. The service@entity protocol syntax can be a base for creating Uniform Resource Identifiers (URIs). The service@entity syntax, while forming a simple base pattern, can be extended, such as to include an identity of a requester (e.g., @bob:phone@alice, which can be provided to @bob by @alice in response to a request by @bob for information @alice has shared with @bob).

(75) The decentralized nature of the protocol servers can further increase security. Sensitive data can be stored in, for example, billions of separate, secure decentralized resource directory microservices. Data within a given microservice can be securely stored in an embedded key/value persistence with values strongly encrypted. Accordingly, sensitive data across users is not centralized or stored in one place, which can be security weaknesses for other types of systems. Decentralized distribution of data can support system scaling and can also reduce an attack surface for bad actors to a minimal footprint, as compared to other approaches.

(76) Storing data by reference can further increase data distribution and decentralization. With data being able to be stored either by value or by reference, a user's owned data can be distributed, using by-reference pointers, among various other systems, with access control (including encryption keys) still being stored and managed by the user's protocol server, which remains under the control of the user.

(77) Other than decentralization, various other approaches can be used for securing protocol requests and secured data when implementing the @protocol. For example, secure transport channels, such as TLS over TCP/IP, can be used. As another example, connections can be validated, by servers and/or clients, using SSL certificates. For further security, different protocol messages can be hashed and/or encrypted. Personal data can be encrypted and/or signed cryptographically, and can be decrypted by requesting and obtaining, for example, a public key of the entity. Other examples include use of a blacklist. A blacklist is a list of @signs that is checked when a "from:" verb is received by a protocol server. If the sender of the from: verb is found in the blacklist, the connection is immediately dropped, for example to fulfill a protocol promise of preventing a known blocked @sign from having any interaction whatsoever with the protocol server apart from a public lookup (e.g., which does not use the from: verb). In addition to a blacklist, "allowed list(s)" or "whitelist(s)" can be maintained by a protocol server that are derived from shared data and include @signs to whom the shared data is shared.

(78) Additionally, the protocol servers are designed to prevent outside surveillance. Data stored in a protocol server can only be accessed by the registrant and other users to which the registrant user has explicitly shared access. The protocol servers are specifically designed to control the granting or revoking of access rights to registrant's data and services in real-time, based on the user's permissions. Other tracking or access to a protocol server outside the protocol specification can be prohibited, even from the registrar server **110**, the protocol provider server **103**, or other components of the system **100**.

(79) The personalized decentralized resource directories provided by the various protocol servers can enable various types of applications, including P2P applications. For example, a user device **107** can include various protocol-enabled applications **158**. The protocol-enabled applications **158**, which can include installed and/or web-based applications, can retrieve an @handle from the settings application **145**, request approval for access to data in the personal directory **154**, and expose application data **160** to the settings application **145** (or the secondary server) for the user's protocol server to maintain permissions for the application data **160**. Although shown separately from the personal directory **154**, application data **160** can be stored in the personal directory **154** or linked from the personal directory **154**.

(80) In some implementations, a protocol-enabled application **158** (and/or the settings application **145**) includes a resolver library which can make protocol requests on behalf of the protocol-enabled application **158**. Protocol-enabled applications **158**, through use of the resolver library and/or the

settings application **145**, can be configured to receive user input, translate user input into protocol commands, process protocol verb requests, provide protocol verb responses, and persist data. Data persisted by an application can be data shared by others, and can be stored in the application data **160**, the personal directory **154** and/or the cached data **156**. Data shared by others can have a TTL (Time to Live) setting, which limits how long the data from others may be accessible.

(81) Data in the personal directory **154**, the personal directory **144**, or in secondary server personal directory copies can also have a TTL setting. As described below, a private lookup challenge value can be placed in a personalized directory with a TTL value. As another example, application and/or personalized directory data can have a “TTB” (e.g., Time unTil Birth, Time To Birth) setting, which can represent a duration value. Data with a TTB setting can be configured to become available in the application data or personalized directory after the duration has elapsed (e.g., sharing information with a TTB parameter can provide access to the information only after the TTB time has been reached). For example, important financial information might be stored in an @server that is to become accessible only at a defined time in the future for all recipients. The financial information can be public or private and might also be subject to other time based controls, such as TTL and TTR (Time To Refresh). For instance, data can have both a TTB and a TTL setting, which can result in a data item appearing after a TTB duration has expired, and disappearing after a TTL duration has expired. Data with a TTR setting can be refreshed when the interval value for the TTR setting is reached. TTL, TTB, and TTR settings, whether used separately or in combination(s), can enable flexible and powerful data access and privacy control capabilities.

(82) Applications can present data in a GUI (Graphical User Interface) **162**. As another example, the protocol-enabled applications **158** can include a shell application, in which a user can enter protocol commands, e.g., after connecting to a root server **105**, or a protocol server. The user can enter anonymous commands to access publicly available information, and can authenticate to a given protocol server, to make an authenticated request for information.

(83) A protocol-enabled application **158** can be a standalone application for managing personal data, or can be a P2P application that communicates with other P2P applications, over the network **101**. End-to-end encrypted P2P applications can have an advantage of not being subject to surveillance as they do not need to communicate through backend servers, or send unencrypted information in the clear. Rather, P2P applications can communicate in a distributed fashion, directly between themselves, at the edge of the network **101**.

(84) The protocol provider can support the application developer community, by providing the source code distribution **114** and the documentation distribution **116**. The source code distribution **114** can be an open source code repository, e.g., for reference implementations, and can be made available from the protocol provider server **103** (or another server of the protocol provider) or through another source code repository or channel. The source code distribution **114** can include code for a SDK (Software Development Kit) that can be used by application developers **104** to create protocol-enabled applications. Other source code examples include sample code for protocol exchanges, code for fully-developed sample applications, etc.

(85) The documentation distribution **116** can include protocol specification information and documentation, discussion of example protocol exchanges, tutorials, or other types of documentation. In addition to source code and documentation, the protocol provider can provide binary distributions for development tools, sample applications, etc. In general, an overall repository managed or supported by the protocol provider can include items that can be used, tested, evaluated, contributed to, and extended, by the application developer community.

(86) Application developers **104** can use developer tools **164** provided by the protocol provider (or by other providers) to develop protocol-enabled applications. Application developers **104**, in order to use the protocol, can first agree to terms of conduct published by the protocol provider, which can provide legal recourse. Application developers can review application certification guidelines included in the documentation distribution **116**, to learn requirements for application certification.

When an application is ready for certification, an application developer **104** can provide application code **166** (or another type of packaged application distribution) to the application certifier **118**, for certification.

(87) Application certification can include review and testing (e.g., by the application certifier **118** or by administrator(s)) of the application code **166**, to check for compliance with protocol guidelines. Upon successful certification of an application, application certification information **119** can be stored for the certified application. As another example, certification information can be stored at an @sign server associated with the application. In some implementations, application certification can be validated in real time, such as by using a checksum validation. Upon receiving an application certification result, an application developer **104** (or the application certifier **118**) may update code of the application so that, for example, a user interface of the application presents an indication of certification to a user.

(88) As another example, application information stored for the application in an application repository **168** of the application store **108** can be updated so that prospective users can see the certification status of the application. A user device **107** can connect to an application store service **170** (e.g., using a web site or an installed application provided by the application store **108**), to access various application discovery tools. For example, a user can use the application store service **170** to browse and/or search for protocol-enabled applications. As another example, the application store service **170** can provide application ratings and/or recommendations. Once a user selects an application, the application can be downloaded (e.g., to a user device **107**) from the application repository **168**. The application store **108** can be provided by or otherwise affiliated with the protocol provider. As another example, at least some other application stores can be provided by third party vendors.

(89) In some implementations, the backup server **106** is included in the system **100**, as a separate backup repository for protocol servers. For example, a backup service **171** can provide backup/restore access to personal directory backups **172**. The personal directory backups **172** can hold non-key data, for example. In some implementations, backup services can be provided by secondary server providers (e.g., data may be backed up in the user containers **122** or **148**). If a user chooses to use the backup server **106** or another backup mechanism, the user can be charged a fee for the backup services.

(90) In some implementations, the enterprise user device **111** can be connected over the local area network **112** with the enterprise microservice server **113** that can act as a proxy for the enterprise user device **111** for network connectivity beyond the local area network **112**. The enterprise user device **111** may be behind a corporate or other type of firewall, for example. The enterprise user device **111** can send a “plookup” (e.g., a proxied lookup) protocol verb to the enterprise microservice server **113**, for protocol exchanges. Through use of the plookup verb, the enterprise microservice server **113** can contact other protocol servers for protocol exchanges to be performed on behalf of the enterprise user device **111**. The enterprise microservice server **113** can be useful in large enterprise environments that prefer all lookups going through a single Internet-connected secondary server, or where only a single port (e.g., on the enterprise microservice server **113**) is preferred to be opened through the firewall for protocol use, or for other cases where a minimizing of connections is desired. The enterprise microservice server **113** can support an internal, private @protocol system (that includes the enterprise user device **111** and other devices), that is located internally within the enterprise.

(91) As used in the present disclosure, the term “computer” is intended to encompass any suitable processing device. Indeed, the illustrated devices and systems may be or include any computer or processing device such as, for example, a mobile device, a laptop, a blade server, a general-purpose personal computer (PC), Mac®, workstation, UNIX-based workstation, IoT device, or any other suitable device. In other words, the present disclosure contemplates computers other than general purpose computers, as well as computers without conventional operating systems. Further, the

illustrated devices and systems may be adapted to execute any operating system, including Linux, UNIX, Windows, Mac OS®, Java™, Android™, iOS, Dart, Swift, Kotlin, or any other suitable operating system.

(92) Interfaces **175, 176, 177, 178, 179, 180, 181, 182, 183** and **184** (referred to below as interfaces **175-184**) are used by the governing body **102**, the protocol provider server **103**, the application developers **104**, the root servers **105**, the backup servers **106**, the user devices **107**, the application store **108**, the protocol servers **109**, the registrar servers **110**, and the enterprise microservice server **113**, respectively, for communicating with other systems in a distributed environment—including within the system **100**—connected to the network **101**. Additionally, the interface **185** enables the enterprise user device **111** to communicate on the LAN **112** (e.g., to other enterprise user devices **111** and/or to the enterprise microservice server **113**). Generally, the interfaces **175-184** each comprise logic encoded in software and/or hardware in a suitable combination and operable to communicate with the network **101**. More specifically, the interfaces **175-184** may each comprise software supporting one or more communication protocols associated with communications such that the network **101** or interface's hardware is operable to communicate physical signals within and outside of the illustrated system **100**.

(93) The protocol provider server **103**, the root servers **105**, the backup servers **106**, the user devices **107**, the protocol servers **109**, and the registrar servers **110** may each respectively include one or more processors **186, 187, 188, 189, 190**, or **191**. Each processor **186, 187, 188, 189, 190**, or **191** may be a central processing unit (CPU), a blade, an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or another suitable component. Generally, each processor **186, 187, 188, 189, 190**, or **191** executes instructions and manipulates data to perform the operations of the respective device. Specifically, each processor **186, 187, 188, 189, 190**, or **191** executes the functionality required to receive and respond to requests from another device. Although not illustrated as including processors, the governing body **102**, the application developer **104**, the application store **108**, the enterprise user device **111**, and the enterprise microservice server **113** may each include (or be associated with device(s) that include) one or more processors.

(94) Regardless of the particular implementation, “software” may include computer-readable instructions, firmware, wired and/or programmed hardware, or any combination thereof on a tangible medium (transitory or non-transitory, as appropriate) operable when executed to perform at least the processes and operations described herein. Indeed, each software component may be fully or partially written or described in any appropriate computer language including C, C++, Java™, JavaScript®, Visual Basic, assembler, Perl®, Dart, Swift, Kotlin, Go, Python, any suitable version of 4GL, as well as others. While portions of the software illustrated in FIG. 1 are shown as individual modules that implement the various features and functionality through various objects, methods, or other processes, the software may instead include a number of sub-modules, third-party services, components, libraries, and such, as appropriate. Conversely, the features and functionality of various components can be combined into single components as appropriate.

(95) Each of the devices or systems illustrated in FIG. 1 may include one or more memories (e.g., storage locations). Each memory may include any type of memory or database module and may take the form of volatile and/or non-volatile memory including, without limitation, magnetic media, optical media, random access memory (RAM), read-only memory (ROM), removable media, or any other suitable local or remote memory component. Each memory may store various objects or data, including caches, classes, frameworks, applications, backup data, business objects, jobs, web pages, web page templates, database tables, database queries, repositories storing business and/or dynamic information, and any other appropriate information including any parameters, variables, algorithms, instructions, rules, constraints, or references thereto associated with the purposes of the system **100**.

(96) The user devices **107** may each generally be any computing device operable to connect to or communicate with other devices using a wireline or wireless connection, with different user

devices **107** being similar or different types of devices in a particular implementation. In general, the user device **107** comprises an electronic computer device operable to receive, transmit, process, and store any appropriate data associated with the system **100** of FIG. **1**. The user device **107** can each include one or more client applications, including the registration application **138**, the settings application **145**, and the protocol-enabled applications **158**. A client application is any type of application that allows the user device **107** to request and view content on user device **107**. In some instances, a client application may be an agent or client-side version of the one or more server applications running on a server.

(97) The user device **107** is generally intended to encompass any client computing device such as a laptop/notebook computer, wireless data port, smart phone, personal data assistant (PDA), tablet computing device, one or more processors within these devices, or any other suitable processing device. For example, the user device **107** may comprise a computer that includes an input device, such as a keypad, touch screen, or other device that can accept user information, and an output device that conveys information associated with the operation of the client device itself or the system **100**, including digital data, visual information, or the GUI **162**.

(98) The GUI **162** interfaces with at least a portion of the system **100** for any suitable purpose, including generating a visual representation of the registration application **138**, the settings application **145**, or the protocol-enabled applications **158**. In particular, the GUI **162** may be used to view and navigate various Web pages. Generally, the GUI **162** provides a respective user with an efficient and user-friendly presentation of data provided by or communicated within the system **100**. The GUI **162** may comprise a plurality of customizable frames or views having interactive fields, pull-down lists, and buttons operated by the user. The GUI **162** contemplates any suitable graphical user interface, such as a combination of a generic web browser, intelligent engine, and command line interface (CLI) that processes information and efficiently presents the results to the user visually.

(99) There may be any number of user devices **107** associated with, or external to, the system **100**. Additionally, there may also be one or more additional user devices **107** external to the illustrated portion of system **100** that are capable of interacting with the system **100** via the network **101**. Further, the term “client”, “client device” and “user” may be used interchangeably as appropriate without departing from the scope of this disclosure.

(100) FIG. **2** is a block diagram illustrating an example system **200** for a public lookup transaction. A public lookup can be performed on an @sign server without being authenticated to the @sign server. In this example, a user **201** (“Bob”) wants to do a lookup for a location value for an @alice user. The user **201** can perform the lookup using a device **202** (e.g., Bob's device, configured for or associated with an @bob user). The device **202** can include code for executing @protocol exchanges (e.g., as provided by a resolver library), among other protocol configurations.

(101) In a first stage (e.g., illustrated as a circled “one”), the device **202** sends an “@alice” query **204** to a root server **206**. A public lookup of an @sign can be performed without being authenticated to the root server **206**. The root server **206** looks up server information for the @alice handle and, in stage two, returns server address information **208** to the device **202**. The server address information **208** can include a server address and port number for a protocol server **210** that handles protocol requests for the @alice user.

(102) In a third stage, the device **202** uses the server address information **208** to send a “lookup:location@alice” query **212** to the protocol server **210**. The protocol server **210** can determine whether a “location” value is stored by the protocol server **210** and whether the location value is publicly accessible. The query **212** is an anonymous, unauthenticated (e.g., public) query, so the protocol server **210** can be configured to provide a response to the query **212** only if the protocol server **210** stores a public “location” value. In some implementations, if the protocol server **210** does not store a public location value, the protocol server **210** can provide a null (e.g., empty) response. Alternatively, if no public location value is stored, then the protocol server **210**

can ignore the location@alice query **212** with no response provided.

(103) In a fourth stage, in response to determining that a public location value is stored at the protocol server **210**, the protocol server **210** sends a retrieved public location value of “California” to the device **202**. A note **216** summarizes the transaction (i.e., the device **202** receiving the public location value of “California” **214** in response to the public-lookup “location@alice” query **212**).

(104) The lookup:location@alice query **212** is an example of a lookup protocol verb used to lookup a particular address in a particular @handle's namespace. The protocol server **210** can be configured to assume that any received value that ends with “@alice” is a lookup request, for example. As mentioned, an unauthenticated request is referred to as a public lookup, in which a requesting user does not have to prove who they are. Private, authenticated lookups are also supported, as described below.

(105) FIG. **3** is a block diagram illustrating an example system **300** for a private lookup transaction. The @protocol includes an automated method for ensuring that an entity that is requesting some private information from another entity has proven that they are who they claim to be before the request is presented for processing. Failure of this proof can immediately cause the connection between the entities to be dropped. A “proof of life” or “pol” algorithm can be performed during a private lookup process.

(106) A device **301**, associated here with user @bob, can include a resolver **302**. The resolver **302** can be a library included in (or otherwise used by) a protocol-enabled application. The resolver **302** can be configured to perform (among other tasks) a private lookup of information managed by a user with a handle of @alice. The resolver **302** can be included in an application that is running on the device **301** on behalf of the user @bob.

(107) In a first stage, the resolver **302** sends an “@alice” query **304** and an “@bob” query **306** to a root server **308**. The resolver **302** may or may not currently have access to server information for a protocol server for @bob, for example. To perform the pol algorithm as part of a private lookup for information managed by the @alice user, the resolver **302** can connect to protocol servers for both @alice and @bob.

(108) In response to the @alice query **304** and the @bob query **306**, the root server **308** looks up server information for the @alice and @bob handles and, in a second stage, returns, to the resolver **302**, server address information **310** for a protocol server **311** for @alice and server address information **312** for a protocol server **314** for @bob, respectively.

(109) In a third stage, the resolver **302** submits a “from:@bob” request **316** to the protocol server **311**. The “from:@bob” request **316** is an example use of a from protocol verb that can be used to tell a protocol server what @handle is associated with a request. The pol algorithm can be initiated when a user submits a from verb that includes an @sign of the requester. The “from:@bob” request **316** includes the @sign “@bob” in this example.

(110) In the pol algorithm, upon receiving a “from” request, the requested entity first returns a challenge asking the requestor to publish a defined secret in a defined secret location in the requestor's namespace and notify the requested entity when the defined secret is available at the defined location. For example, in a fourth stage, the protocol server **311**, in response to the request **316**, sends a challenge requesting the resolver **302** to place a cookie **318** at a particular address **320** on the protocol server **314**. That is, proof of a requester's identity can be provided using an ability to place a cookie or other identifier at a specified place in the requester's @handle name space. For the resolver **302** to legitimately act on behalf of @bob, the resolver **302** should be able to authenticate to the protocol server **314** for @bob and place the requested cookie **318** at the requested address **320**. The cookie **318** and the address **320** can be randomly-generated values generated by the protocol server **311** as part of the pol algorithm. The cookie **318** and the address **320** can be UUIDs (Universally Unique IDentifiers) or some other type of random value or identifier.

(111) In a fifth stage, the resolver **302** authenticates to the protocol server **314** for @bob and places

a cookie **322** (corresponding to the requested cookie **318**) at an address **324** (corresponding to the requested address **320**). The resolver **302** authenticates to the protocol server **314** before performing the placement of the cookie **322**. Different approaches can be used for authenticating to the protocol server **314**.

(112) For example, the resolver **302** can first indicate to the protocol server **314** that the resolver **302** is acting on behalf of the @bob user (e.g., using a “from:@bob” command). The protocol server **314** can respond with a challenge for the resolver **302**. The resolver **302** can respond to the challenge, using for example, a CRAM verb or a PKAM (Public Key Authentication Mechanism) verb. The CRAM verb uses a shared secret, while the PKAM verb uses a public/private key approach. Authentication is discussed in more detail below with respect to FIG. 4A.

(113) After successfully authenticating to the protocol server **314**, the resolver **302** can submit an update request to the protocol server **314** to place the cookie **322** at the address **324**. An update verb can be used to place a new value or update an existing value on the protocol server **314**, for example. Placing the cookie **322** at the address **324** can prove to the protocol server **311** that the resolver **302** is in fact acting on behalf of the @bob user.

(114) In a sixth stage, the resolver **302** sends an indication to the protocol server **311** that the requested cookie is in place on the protocol server **314** and available for testing by the protocol server **311**. For example, the resolver **302** can send a pol verb to the protocol server **311**. The pol verb can be used to signal the protocol server **311** to check for (e.g., look up) the cookie **318** on the protocol server **314**.

(115) In a seventh stage, the protocol server **311** sends an “@bob” query **325** to the root server **308** (or to another root server) requesting protocol server information for the @bob handle.

(116) In response to the @bob query **325**, the root server **308** looks up server information for the @bob handle and, in an eighth stage, returns, to the protocol server **311**, server address information **326** for the protocol server **314** for @bob.

(117) In a ninth stage, the protocol server **311** looks for the cookie **318** at the address **320** on the protocol server **314**. Looking for the cookie can include sending a lookup request for a value on the protocol server **314** at the address **320**.

(118) In a tenth stage, the protocol server **314** provides the cookie value **322** stored at the address **324** to the protocol server **311**, in response to the lookup request sent by the protocol server **311**.

(119) In an eleventh stage, the protocol server **311** “tastes” the cookie received from the protocol server **314**. That is, the protocol server **311** compares the cookie **318** sent in the proof challenge to the cookie **322** that was actually stored at the address **320** on the protocol server **314** (and sent to the protocol server **311** by the protocol server **314**). If the cookie **318** does not match the cookie **322**, the protocol server **311** can determine that the resolver **302** has failed the proof of life challenge. The protocol server **311** can drop a connection with the resolver **302**, simply not respond to the pol verb sent by the resolver **302** in the sixth stage, or return an error code to the resolver **302** that indicates a failure of the pol attempt. Similarly, the protocol server **311** can drop a connection, ignore the pol verb, or send an error code to the resolver **302** if the cookie **318** was simply not found on the protocol server **314**.

(120) In a twelfth stage, in response to a successful retrieval and test of the cookie **322**, the protocol server **311** sends an indication of pol success to the resolver **302**, indicating that the resolver **302** has successfully authenticated to the protocol server **311** as the user @bob.

(121) In a thirteenth stage, the resolver **302** sends, using the authenticated connection, a “lookup location@alice” request **327** to the protocol server **311**. The protocol server **311** can determine that a value specific to @bob is stored by the protocol server **311** for the location@alice address.

(122) In a fourteenth stage, the protocol server **311** returns a value of “Home” **328** to the resolver **302**, in response to the lookup request **327**. A note **330** summarizes the private lookup transaction, of the resolver **302** receiving the location value of “Home” **328**, in response to the private (e.g., as @bob) lookup “location@alice” request **327**. That is, the value of “Home” has been shared with

the @bob user and is provided in response to location@alice requests sent by the @bob user or an application acting on behalf of @bob, in contrast to a publicly accessible location value **214** of “California” that is returned in response to location@alice requests sent by unauthorized users (or by users to which a private/custom location value is not shared).

(123) FIGS. **4A** and **4B** are a combined swim lane diagram illustrating an example method **400** for a private lookup transaction. Similar to the private lookup illustrated in FIG. **3**, the method **400** can describe a user “Bob” with a handle of “@bob” performing a private lookup of information maintained by a user “Alice” with a handle of “alice.”

(124) As shown in FIG. **4A** at **402**, a resolver **404** sends a query **406** of “@alice” to a root server **408**. At **410**, the root server **408** sends a response **412** to the query **406** of “alice.alserver.com:6455” that includes a server and port number of Alice's server **413**. Bob can use an application that includes, implements, or accesses the resolver **404** to submit a query for Alice's server information, if Bob (or the application) does not have Alice's server information cached. If Bob (or Bob's application) does not have his own server information cached, the resolver **404** can, at **414**, send a query **416** of “@bob” to the root server **408** to obtain server information for Bob's server **417**. For example, at **418**, the root server **408** sends a response **420** of “bob.bobserver.com:6200” in response to the query **414**.

(125) In general, the root server **408** can respond to a query for an @sign with a single IP address and port or a single fully qualified domain name (FQDN) and port number. The returned port number can identify the @protocol service and a particular user's server. The root server **408** can respond with a null value (or simply ignore a request) if the root server **408** does not have server information for a particular requested @sign.

(126) At **422**, the resolver **404** connects to Alice's server **413** and sends a “from:@bob” message **426** to Alice's server **413**. As discussed above, a “from” request can indicate to a requested entity what @handle the requester claims to be. The message **426** can indicate to Alice's server **413** that the resolver **404** is claiming to be associated with the @bob user.

(127) At **427**, in response to the message **426**, Alice's server **413** generates pol challenge information. For example, Alice's server **413** can generate a first random value and a second random value to be used in a challenge sent to the resolver **404**.

(128) At **428**, Alice's server **413** responds to the message **426** by sending a pol challenge **430**. The pol challenge **430** is a proof challenge that requests the resolver **404** to place a first identifier (e.g., a UUID) “271b7d94-8a31-48e3-9348-da1909349b21” at a randomly-generated address of “86adcd50-9fcb-4e76-a17f-1a572b6a1ee5” on Bob's server **417**. If the resolver **404** is authorized to act on behalf of @bob, the resolver **404** should be able to successfully perform the requested challenge.

(129) At **432**, the resolver **404** sends a “from:@bob” message **434** to Bob's server **417** to attempt to authenticate to Bob's server **417**. Similar to the message **426**, the message **434** is indicating to Bob's server **417** that the resolver **404** is claiming to be acting on behalf of the @bob user.

(130) At **437**, Bob's server **417** generates key challenge information.

(131) At **438**, Bob's server **417** sends a key challenge **440** to the resolver **404**. As shown, if a user, application, or process issues a “from:@bob” verb to the server associated with the @bob user, the server for @bob can issue a key challenge, whereas the server for @bob can issue a proof challenge in response to a from: verb from a user other than the @bob user. As discussed above, the resolver **404** can respond to the key challenge **440** using a CRAM verb, a PKAM verb, or some other type of authentication response.

(132) At **442**, the resolver **404** (or another process, on behalf of the resolver **404**) executes a PKAM command **444** to create a signed version of the key challenge **440** using a private key for the @bob user. If the resolver **404** is legitimately configured to represent the @bob user, the resolver **404** has access to the private key for the @bob user. With the PKAM approach, Bob's server **417** is configured to have access to the public key for the @bob user.

(133) Referring now to FIG. 4B, at **446**, the resolver **404** sends a PKAM message **448** to Bob's server **417**. The PKAM message **448** includes a signed version of the key challenge **440** that was created by the PKAM command **444**.

(134) At **450**, Bob's server **417** tests the PKAM message **448**. For example, Bob's server **417** can check to see if the signed version of the key challenge **440** is accurate by testing the signed version of the key challenge **440** using the public key for the @bob user.

(135) At **452**, in response to a successful test of the PKAM message **448**, Bob's server **417** sends an indication **454** of authentication success to the resolver **404**.

(136) At **456**, the resolver **404** sends, while authenticated on Bob's server **417** as @bob, an update request **458** to Bob's server **417** to place the first random value "271b7d94-8a31-48e3-9348-daf909349b21" included in the pol challenge **430** at the randomly-generated address of "86adcd50-9fcb-4e76-a17f-1a572b6a1ee5" included in the pol challenge **430**.

(137) The update protocol verb enables a user or process authenticated on a given @sign server to update entries in that @sign namespace. A general format of the payload for an update verb is: [public/@sign]:key@[@yourname] value. An example update request is "update:public:email@alice alice.bloggs@emailXXX.com," which can create a public record for an email@alice address with a value of "alice.bloggs@emailXXX.com." An example of updating a value shared to a certain user is "update:@bob:email@alice alice@personalemail.org." A delete verb can be used by an authenticated user or process to delete an entry on an @sign server. For example, "delete:public:email@alice" and "delete:@bob:email@alice" requests can be sent to delete the entries mentioned in the previous two examples.

(138) Continuing with FIG. 4B, at **460**, Bob's server **417** performs an update of Bob's personal directory based on the update request **458**. In some implementations, a cookie placed on Bob's server based on the update request **458** is configured with a timeout value. For example, the cookie can have a TTL (Time To Live) value set to one minute. After one minute has passed, Bob's server **417** can delete the cookie (or mark the cookie as invalid). A timeout value, combined with generation of random values such as UUIDs, can result in a negligible likelihood of a namespace clash (e.g., of another application or user placing a same cookie value at a same location). From a perspective of other entities other than the resolver **404** and Bob's server **417**, the update request **458** essentially results in the placing of an unknowable value at an unknowable location. A likelihood of another user or application knowing (or learning) the random cookie value or the random location can be substantially negligible. In some implementations, Bob's server encrypts the cookie using a private key associated with the @bob user before placing an encrypted cookie at the address requested by Alice's server **413**. Alice's server **413** can decrypt the encrypted cookie, as described below.

(139) At **462**, Bob's server **417** sends an indication **464** of a successful update to the resolver **404**. At **466**, the resolver **404** sends a pol request **468** to Alice's server **413**. The pol request **468** can be used to signal Alice's server **413** that Bob's server **417** is ready for Alice's server **413** to verify the pol challenge **430**.

(140) At **470**, Alice's server **413** sends a query **472** of "@bob" to the root server **408** to obtain server information for Bob's server **417**. At **474**, the root server **408** sends a response **476** of "bob.bobserver.com:6200" in response to the query **472**.

(141) At **478**, Alice's server **413** sends a lookup request **480** to Bob's server **417** to look up the value at the address Alice's server included in the pol challenge **430**.

(142) At **482**, Bob's server **417** sends a value **484** to Alice's server **413** in response to the lookup request **480**. The value **484** is retrieved by Bob's server **417** as the value of the 86adcd50-9fcb-4e76-a17f-1a572b6a1ee5@bob address on Bob's server **417**.

(143) At **486**, Alice's server **413** performs a proof test. Alice's server **413** can compare the value **484** to the value Alice's server **413** included in the pol challenge **430**. In implementations in which Bob's server **417** encrypts the value Alice's server **413** included in the pol challenge **430**, before

storing an encrypted value on Bob's server **417**, Alice's server **413** can decrypt the encrypted value using a public key for the @bob user, before comparing a decrypted value to the value included in the pol challenge **430**. Alice's server **413** can obtain the public key for @bob by doing a lookup for publickey@bob, for example.

(144) At **488**, in response to a successful proof test, Alice's server **413** sends an indication **490** of authentication success to the resolver **404**. The resolver **404** is now authenticated as the @bob user on Alice's server **413**. Alice's server **413** has concluded that the resolver **404** is in fact acting on behalf of the @bob user as claimed by the resolver in the “from:@bob” message **426**.

(145) At **492**, the resolver **404**, while in an authenticated state with respect to Alice's server **413**, sends an authenticated lookup request **494** to Alice's server **413**.

(146) At **496**, Alice's server **413** sends a user-specific value **498** to the resolver **404**, in response to the authenticated lookup request **494**. The user-specific value **498** is an example of a polymorphic response. Alice's server can send different values in response to a same lookup location@alice request, based on whether the sender is anonymous or based on the identity of the sender.

(147) FIG. 5 is a block diagram illustrating an example system **500** for a private lookup transaction. The system **500** is similar to the system **300**, but the system **500** includes a different approach performed by a user's protocol server in contacting another protocol server on behalf of the user (or the user's application). In the example of FIG. 5, a user Bob **502** with a handle of @bob uses a device **504** to initiate an authenticated lookup of a location@alice address.

(148) In a first stage (e.g., denoted with a “1.”), a resolver **506** on the device **504** sends a query of “bob” to a root server **508**, to obtain server information for a protocol server for the @bob handle. In a second stage, the root server **508** returns server information having a pattern of “server2:port”—e.g., a server and port number of a protocol server **510** that is mapped to the @bob handle.

(149) In a third stage, the resolver **506** sends a “from:@bob” query to the protocol server **510**. In a fourth stage, the protocol server **510** responds to the “from:@bob” query with an authentication challenge. In a fifth stage, the resolver **506** (or another program, or Bob using another program) generates a signed challenge response. The signed challenge response is sent by the resolver **506** to the protocol server **510**. In a sixth stage, the protocol server **510** tests the signed challenge response, to determine whether the signed challenge response is valid with respect to the challenge sent to the resolver **506** in the fourth stage.

(150) In a seventh stage, in response to determining that the signed challenge response is valid, the protocol server **510** sends an indication (e.g., “@bob@”) to the resolver **506** to indicate that the resolver **506** has been authenticated to the protocol server **510** (e.g., as @bob). The “@bob@” indicator can correspond to a changing of a connection prompt for a connection between the resolver **506** and the protocol server **510**. A connection prompt of “@” can indicate an unauthenticated connection and a connection prompt of “@bob@” can indicate a connection authenticated as the user @bob.

(151) In an eighth stage, the resolver **506** sends a “lookup:location@alice” query to the protocol server **510**, using the authenticated connection. The protocol server **510** can perform a look up of the “location@alice” address on behalf of the resolver **506** (e.g., on behalf of @bob). The protocol server **510** may first need to obtain server information for a protocol server **512** that is mapped to the @alice handle.

(152) In a ninth stage, the protocol server **510** sends a query of “alice” to the root server **508** (or to another root server). In a tenth stage, the root server **508** (or another root server to which the “alice” query was sent) sends server information for the protocol server **512** (e.g., of a pattern of “server1:port”) to the protocol server **510**, in response to the “alice” query.

(153) In an eleventh stage, the protocol server **510** sends a “from:@bob” message to the protocol server **512**. In a twelfth stage, the protocol server **512** responds to the “from:@bob” request by sending a challenge to the protocol server **510**. The challenge is of a form of “xxx@bob:yyy”,

which represents a challenge/request for the protocol server **510** to set an “xxx@bob” address to a value of “yyy”.

(154) In a thirteenth stage, in response to the challenge from the protocol server **512**, the protocol server **510** updates, on the protocol server **510**, an “xxx@bob” address to the value of “yyy”. In a fourteenth stage, the protocol server **510** sends a proof-of-life (e.g., “poi”) message to the protocol server **512**, to indicate to the protocol server **512** that the requested challenge has been performed. The protocol server **510** is claiming that the protocol server **510** has successfully performed the requested challenge, as the @bob user.

(155) In a fifteenth stage, the protocol server **512** begins a process of validating whether the protocol server **510** successfully performed the requested challenge. The protocol server **512** can perform a public lookup on the protocol server **510** to determine whether the requested address was updated with the requested value. The protocol server **512** may first need to obtain server information for the protocol server **510** before performing the lookup. For example, in the fifteenth stage, the protocol server **512** sends a request to look up server information for the @bob user to the root server **508**. In a sixteenth stage, the root server **508** returns server information for the protocol server **510** (e.g., of a pattern of “server2:port”) to the protocol server **512**.

(156) In a seventeenth stage, the protocol server **512** establishes a separate connection with the protocol server **510** (e.g., different from the connection used in the eleventh, twelfth, thirteenth, and fourteenth stages). The protocol server **512** sends a “lookup:xxx@bob” request, over the separate connection, to the protocol server **510**. In an eighteenth stage, the protocol server **510**, in response to the “lookup:xxx@bob” request, retrieves a “yyy” stored at the “xxx@bob” address and sends a “data:yyy” response to the protocol server **512**.

(157) In a nineteenth stage, the protocol server **512** performs a test to determine whether the “data:yyy” value received from the protocol server **510** matches a requested “yyy” value that was included in the challenge sent to the protocol server **510** in the twelfth stage. If the test fails, the protocol server **512** can drop connection(s) to the protocol server **510**. If the test succeeds, the protocol server **512** can, in a twentieth stage, return an indication (e.g., “@bob@”) to the protocol server **510** over the first connection to indicate to the protocol server **510** that the protocol server **510** has been authenticated as the @bob user on the protocol server **512**.

(158) In a twenty-first stage, the protocol server **510** sends a “lookup:location@alice” request to the protocol server **512** as a request that has been authenticated as corresponding to the @bob user. In a twenty-second stage, the protocol server **512** retrieves a location@alice value (e.g., “SF Bay Area”) that has been specifically shared with the @bob user. The protocol server **512** sends a “data: SF Bay Area” response to the protocol server **510**. In a twenty-third stage, the protocol server **510** forwards the “data: SF Bay Area” response to the resolver **506**, for example, for presentation to the user Bob **502** and/or for use by an application on the device **504**.

(159) FIGS. **6A** and **6B** are a combined swim lane diagram illustrating an example method **600** for a private lookup transaction. The method **600** is similar to the method **400**, but method **600** uses a different approach of a user's protocol server contacting another protocol server, on behalf of the user (or the user's application). In the example of FIGS. **6A-6B**, a user Bob with a handle of @bob can use a device **602** to initiate an authenticated lookup of a location@alice address.

(160) At **604**, the device **602** sends a query of “bob” **606** to a root server **608**, to obtain server information for a protocol server **609** for the @bob handle.

(161) At **610**, the root server **608** returns server and port information **612** of “bobserver:6464” to the device **602**, in response to the query **606**.

(162) At **614**, the device **602** sends a “from:@bob” query **616** to the protocol server **609**.

(163) At **618**, the protocol server **609** responds to the “from:@bob” query **616** with an authentication challenge **620**. The authentication challenge **620** is of a form of “key:xxx@bob:yyy”.

(164) At **622**, the device **602** generates a signed challenge response **624** (e.g., using a PKAM

command) and sends the signed challenge response **624** to the protocol server **609**.

(165) At **626**, the protocol server **609** tests the signed challenge response, to determine whether the signed challenge response **624** is valid with respect to the challenge **618**.

(166) At **628**, in response to determining that the signed challenge response **624** is valid, the protocol server **609** sends an indication **630** (e.g., “@bob@”) to the device **602** to indicate that the device **602** has been authenticated to the protocol server **609** (e.g., as @bob).

(167) At **632**, the device **602** sends a “lookup:location@alice” query **634** to the protocol server **609**, using the authenticated connection. The protocol server **609** can perform a look up of the “location@alice” address on behalf of the device **602** (e.g., on behalf of @bob). The protocol server **609** may first need to obtain server information for a protocol server **635** that is mapped to the @alice handle.

(168) At **636**, the protocol server **609** sends a query **638** of “alice” to the root server **608**.

(169) At **640**, the root server **608** sends server information **642** (e.g., of “aliceserver.com:6455”) for the protocol server **635** to the protocol server **609**, in response to the “alice” query **638**.

(170) At **644**, the protocol server **609** sends a “from:@bob” message **646** to the protocol server **635**.

(171) At **648**, the protocol server **635** responds to the “from:@bob” message **646** by sending a challenge **650** to the protocol server **609**. The challenge **650** has a pattern of “xxx@bob:yyy”, which represents a challenge/request for the protocol server **609** to set an “xxx@bob” address to a value of “yyy”.

(172) Referring now to FIG. 6B, at **652**, in response to the challenge **650** from the protocol server **635**, the protocol server **609** updates, on the protocol server **609**, an “xxx@bob” address to the value of “yyy”.

(173) At **654**, the protocol server **609** sends a proof-of-life (e.g., “pol”) message **656** to the protocol server **635**, to indicate to the protocol server **635** that the requested challenge has been performed. The protocol server **609** is claiming that the protocol server **609** has successfully performed the requested challenge, as the @bob user.

(174) The protocol server **635** can begin a process of validating whether the protocol server **609** performed the requested challenge. The protocol server **635** can perform a public lookup on the protocol server **609** to determine whether the requested address was updated with the requested value. The protocol server **635** may first need to obtain server information for the protocol server **609**. For example, at **658**, the protocol server **635** sends a request **660** to look up server information for the @bob user to the root server **608**.

(175) At **662**, the root server **608** returns server and port information **664** (e.g., “bobserver:6464”) for the protocol server **609** to the protocol server **635**.

(176) At **666**, in a new session **668**, the protocol server **635** sends a “lookup:xxx@bob” request **670** to the protocol server **609**.

(177) At **672**, the protocol server **609**, in response to the “lookup:xxx@bob” request **670**, retrieves a “yyy” value stored at the “xxx@bob” address and sends a “data:yyy” response **674** to the protocol server **635**.

(178) At **676**, the protocol server **635** performs a test to determine whether the “data:yyy” value received from the protocol server **609** matches a requested “yyy” value that was included in the challenge **650**.

(179) At **678**, in response to the test succeeding, the protocol server **635** can return an indication **680** (e.g., “@bob@”) to the protocol server **609** to indicate to the protocol server **609** that the protocol server **609** has been authenticated as the @bob user on the protocol server **635**.

(180) At **682**, the protocol server **609** sends a “lookup:location@alice” request **684** to the protocol server **635** as a request that has been authenticated as corresponding to the @bob user.

(181) At **686**, the protocol server **635** retrieves a location@alice value (e.g., “SF Bay Area”) that has been specifically shared with the @bob user and sends a “data: SF Bay Area” response **688** to

the protocol server **609**.

(182) At **690**, the protocol server **609** send a “data: SF Bay Area” value **692** to the device **602**, for example, for presentation to the user Bob and/or for use by an application on the device **602**.

(183) Data Sharing and Encryption

(184) A major issue historically for the adoption of secure communication systems (e.g. PGP (Pretty Good Privacy)) has been the challenge of distributing signing keys used to encrypt/decrypt information exchanged between entities. The @protocol solves this problem in a unique manner by making it easy to securely share information by permission to some other entity. For example, “publickey@alice” can be a common syntax and approach for sharing a public key, and “atsign://publickey@alice” can be a fully qualified endpoint URL that can be distributed. While a public key used for PKI (Public Key Infrastructure) encryption can be shared publicly, typically a user may securely share a public key only to specified users. The @protocol supports both public and private sharing of encryption keys. The @protocol provides a simple means of creating and distributing PKI keys. Distribution and sharing of public keys can come as a side effect of the fact that the protocol itself relies on key sharing capability to securely share data with others. The result is an Internet-scale directory for billions of @sign owners to easily publish and lookup PKI keys on the Internet. Thus the @protocol provides a means for distributing and managing PKI keys at a massive scale.

(185) The @protocol can also provide a system for distributing and managing PKI keys that can provide different responses based on who is requesting a public key. For instance, in addition to distributing encryption keys as outlined above, the protocol can determine which respective encryption key to provide among multiple encryption keys in response to a request, wherein the respective encryption key to provide depends on an identity of a requestor. That is, the protocol can support polymorphic sharing and distribution of encryption keys. This capability can provide additional assurance that only an intended recipient is able to access shared information.

(186) The @protocol's polymorphism capability can enable providing different responses to a query based on which @sign is requesting the data. Polymorphism can be applicable for public, as well as private, sharing. Polymorphism capabilities can have important implications for managing PKI keys and other types of data. For example, a protocol query such as publickey@alice can be responded to with a public key value that is shared without using the proof of life handshake, as a public value shared with all users or a response can include different values for a same publickey@alice query based on a “from” parameter as part of the pol handshake. A given user can share a different public key with each of multiple different other users, for example. For instance, @alice can share a first public key with @bob and a second public key with @sara, each in response to a lookup by @bob or @sara of a publickey@alice key, respectively, based on a determination by @alice for which public key to share with which user. Polymorphic responses to queries for keys can provide a simple, scalable system for managing public and private PKI keys.

(187) Additionally, the @protocol can provide a system for distributing content to multiple recipients that is encrypted one time such that only the intended recipients can access the content by using those intended recipients' respective personal keys. In further detail, the @server sharing protocol can support encryption of information that is encrypted once with a shared symmetric key, and is then shared with any number of others in such a manner that only the recipient can decrypt the information using their private key with asymmetric decryption. Such sending can be subject to other privacy controls inherent in the @protocol. For example, decrypted information can be set to remain accessible for some defined time period after which it will be automatically deleted.

(188) With the @protocol, a hybrid symmetric/asymmetric encryption scheme can be used wherein the information can be first encrypted using a shared symmetric key set by the sender. The shared symmetric key can then itself be encrypted using asymmetric encryption with the sender's private key and the recipient's public key from the recipient's @server. A result of the hybrid symmetric/asymmetric scheme can be that information that is shared by the sender can only be

retrieved using the recipient's private key which can provide access to the shared symmetric key set by the sender. The recipient can then use the shared symmetric key to decrypt the information shared with the recipient.

(189) FIG. 7 illustrates an example system **700** for use of encryption keys. As indicated by a note **701**, a net result of a security approach can be that only user-encrypted data is stored on secondary servers and only authorized @sign users can access data based on sharing privileges granted by data owners.

(190) As described in a note **702**, during setup for an @sign, a public/private key pair is created and a public key service is populated. For example, for an @alice user **703**, a key pair **704** can be created on Alice's device **704** and a publickey@alice value **705** can be stored on Alice's secondary server **706**. As another example, for an @bob user **707**, a key pair **708** can be created on Bob's device **709** and a publickey@bob value **710** can be stored on Bob's secondary server **711**.

(191) In a first stage **712** of a use case scenario, Alice wants to share a phone@alice value **713** with the @bob user **707**.

(192) In a second stage **714**, Alice's device **704** generates a shared key (e.g., an Advanced Encryption Standard shared key) for the @bob user **707**.

(193) In a third stage **716**, Alice's device **704** requests that Alice's secondary server **706** perform a lookup for the public key **710** for the @bob user **707** that is stored on Bob's secondary server **711**. Alice's device **704** encrypts the shared key with Bob's public key and requests storage of an encrypted shared key **718** on Alice's secondary server **706**.

(194) In a fourth stage **720**, Alice's device **704** encrypts the shared key with Alice's public key **705**, and stores an encrypted shared key **722** on Alice's secondary server **706**.

(195) In a fifth stage **724** corresponding to Bob desiring to access Alice's phone number, Bob's device **709** sends a lookup request to Bob's secondary server **711** for Bob's secondary server **711** to look up the shared encrypted key **718**. Bob's device **709** uses a private key of the key pair **708** to decrypt the encrypted shared key.

(196) In a sixth stage **726**, Bob's device **709** sends a lookup request to Bob's secondary server **711** for Bob's secondary server **711** to look up the phone@alice value **713** from Alice's secondary server **706**. Bob's device **709** receives the phone@alice value **713** as an encrypted phone number. Bob's device **709** uses the shared key obtained from decrypting the encrypted shared key to decrypt the encrypted phone number, to obtain an unencrypted phone number value (e.g., Alice's phone number she has shared with Bob).

(197) FIG. 8 illustrates an example system **800** for use of encryption keys. In step **1.1**, a user Alice (e.g., corresponding to Alice's device **802**) decides to share a phone@alice value with a user Bob (corresponding to Bob's device **804**).

(198) For instance, in step **1.2**, Alice's device **802** generates a shared key **805** for the user Bob.

(199) In step **1.3**, Alice's device initiates a lookup of Bob's public key. Alice's device **802** sends a lookup request **806** to Alice's secondary server **808**. Alice's secondary server **808** sends, on behalf of Alice's device **802**, a lookup request **810** to Bob's secondary server **812**. Bob's secondary server **812** sends a lookup response **814** to Alice's secondary server **808**. Alice's secondary server **808** forwards the lookup response **814** as a forwarded response **816** to Alice's device **802**. Alice's device **802** receives a copy of Bob's public key **818** in the forwarded response **816**.

(200) In step **1.4**, Alice's device **802** encrypts the shared key **805** with the copy of Bob's public key **818** to generate an encrypted shared key **820**.

(201) In step **1.5.1**, Alice's device **802** initiates storing of the encrypted shared key **820** on Alice's device **802**.

(202) For instance, in step **1.5.2**, Alice's device **802** sends an update request **822** to Alice's secondary server **808** to update @bob:key@alice with the encrypted shared key **820**.

(203) In step **1.6.1**, Alice's device **802** encrypts a phone@alice value Alice has shared with Bob (e.g., as @bob:phone@alice), using the shared key **805**, to generate an encrypted phone value **824**.

(204) In step 1.6.2, Alice's device **802** sends an update request **826** to Alice's secondary server **808** to update an @bob:phone@alice key with the encrypted phone value **824**.

(205) At a later time, in step 2.1, Bob wants to look up Alice's phone number.

(206) In step 2.2.1, Bob's device **804** initiates a lookup of the shared key shared between Bob and Alice.

(207) For example, in step 2.2.2, Bob's device **804** sends a lookup request **828** to Bob's secondary server **812** to lookup the shared key shared between Bob and Alice. Bob's secondary server **812** forwards the lookup request **828** to Alice's secondary server **808**, as a forwarded request **830**.

(208) In step 2.2.3, Alice's secondary server **808** sends an encrypted shared key to Bob's secondary server **812**. Bob's secondary server forwards an encrypted shared key **832** to Bob's device **804**.

(209) In step 2.3, Bob's device **804** decrypts the received encrypted shared key **832** using a private key stored on Bob's device **804**, to obtain an unencrypted shared key.

(210) In step 2.4.1, Bob's device **804** sends a lookup request to Bob's secondary server **812** to look up Alice's phone number that Alice has shared with Bob. Bob's secondary server **812** can forward the lookup request to Alice's secondary server **808**.

(211) In step 2.4.2, Alice's secondary server **808** sends an encrypted phone value to Bob's secondary server **812**. Bob's secondary server **812** forwards an encrypted phone value **834** to Bob's device **804**.

(212) In step 2.5, Bob's device decrypts the encrypted phone value **834**, using the shared key, to obtain the phone value for Alice.

(213) FIG. 9 illustrates an example system **900** for key value retrieval.

(214) At a first stage, a user **902** (e.g., user2) desires to obtain a key of a user **904** (e.g., user1). A request for the key can be sent from a device **906** of the user **902** to a secondary server **908** associated with the user **904**.

(215) In a second stage, the user **902** proves that s/he is user2 (e.g., using a pol approach as described herein).

(216) In a third stage, the secondary server **908** locates an entry **910** in a secondary storage **912** that had been encrypted using an encryption key created by a settings application **914** on a device **916** of the user **904**. The entry **910** can include a key code (e.g., Key123), for example.

(217) In a fourth stage, the secondary server **908** can send the entry **910** (or a portion of the entry **910**) with a request to the device **916** for the settings application **914** to decrypt the entry **910**.

(218) In a fifth stage, the settings application **914** can locate, e.g., in local storage **918**, a key for the key code included in the entry **910** and use the key to decrypt the entry **910** (or to decrypt a value associated with the entry **910**). The decrypted value is sent by the device **916** to the secondary server **908**. The secondary server can forward the value to the device **906** so that the user **902** can view the decrypted value (or otherwise use the decrypted value, e.g. in an application on the device **906**).

(219) An ability of the @protocol to locate edge resource endpoints that securely store a user's data gives rise to a new class of applications that can communicate with each other directly (e.g., P2P). This is an important capability in that it removes a scenario for some intermediary (e.g., typically called a server, but could also be a more nefarious man in the middle scenario) being used to store data and manage interactions with other users that want to access stored data. Additionally, end-to-end encryption ensures that all data and traffic only flows between the involved parties and is not susceptible to surveillance. Accordingly, the @protocol can support a new generation of true P2P applications that can securely share information between permitted users without fear of surveillance by intermediaries, infrastructure providers, or others. Additionally, registering for a new protocol-enabled application can be a simple process for users, because a user can register using their @sign which can reduce sign-up/registration steps and can enable user-controlled access of data to application providers/developers, rather than a user having to separately and repeatedly provide multiple specific items of user information each time a user installs or registers

for an application.

(220) FIG. 10 illustrates an example system 1000 for P2P applications. An application 1002 running on a device 1004 of a user @bob can request data for an @alice user stored, e.g., in a personal directory 1006 of a secondary server 1008 and/or a personal directory 1010 on a device 1012 of @alice. Similarly, an application 1014 running on the device 1012 of @alice can request data for the @bob user stored, e.g., in a personal directory 1016 of a secondary server 1018 and/or a personal directory 1020 on the device 1004 of @bob. Specific application examples are described in more detail below.

(221) Data sharing between the device 1004 and the device 1012 (e.g., and/or between the application 1014 and the application 1002) can be conducted without a need of or actual surveillance by a central server. P2P application functionality can be configured with no central server or entity being able to track a user's use of or sharing of data. Data that a user or user application determines to share with another user or application is encrypted, as described above. Also as described above, one client application of one @protocol user can be notified about a change in data for another @protocol user.

(222) Website Login Functionality Using the Protocol

(223) FIG. 11 illustrates an example system 1100 for website login functionality using a protocol for sharing and managing personal information. An @login application that can run, for example, on a mobile device 1102, is a mobile application that can provide authentication for people/entities/things to Internet-connected services through the use of unique @sign/cryptographic key pairs (public/private) and the use of the @protocol. The @login application can be used, for example, to authenticate to a website provided by a web server 1104 to allow a person to login and automatically provide extra information to that website once authenticated.

(224) For example, from a user's perspective, a user can visit a website (e.g., a trusted website) and be given an option (e.g., in a user interface shown on a display 1106) to login using an @sign. The display 1106 can be a display of the mobile device 1102 or can be a display of a different device (e.g., a desktop device) being used by the user. The user can enter their @sign in the user interface and can be presented, for example, a challenge code, such as a graphical code (e.g., a QR (Quick Response) code) 1108 and/or a numeric code (e.g., a PIN (Personal Identification Number) code). The user can enter the numerical code or scan the graphical code using the @login application in order to be logged into the website, without entering any further information. In some cases, the web server 1104 of the trusted website can obtain certain information that the user has shared with the website. If the user changes their mind and no longer trusts the website the user can remove access to the user's data and have confidence that the user's data can no longer be obtained by the web server 1104 of the website.

(225) In further detail, the web server 1104, in response to receiving an @sign corresponding to a login request, can provide a one-time challenge code that can be valid for a short period of time (e.g., a certain number of seconds). In response to the user typing in or scanning a challenge code, the @login application can cryptographically sign the challenge with a private key and post a signature on a secondary server 1110 of the @sign. The web server 1104 of the website can attempt a lookup of the signature on the secondary server 1110 of the @sign and check to see if the signature is correct by using the public key of the @sign (e.g., which can be publicly available for every @sign). If the challenge has been signed correctly, then the web server 1104 can allow the login. If the user has allowed for data sharing with the website (e.g., with an @sign of the website), the web server 1104 of the website can request (e.g., from the secondary server 1110) user information for the user's @sign, which may include the user's name, date of birth, address, phone, etc., without further user interaction (e.g., the user can avoid filling of forms). If the user logging in trusts the website's @sign, then the user can share data with the website, which can provide a fast, secure, and user-friendly login experience.

(226) In some cases, the user can view the website on a first computer (e.g., a desktop computer) and scan or enter the challenge code on the mobile device **1102**. The mobile device **1102** can be used to run the @login application and cryptographically sign the challenge since the mobile device **1102** can store cryptographic keys in a hardware-entrusted root, for example. As another example, the user can view the website using a mobile browser running on the mobile device **1102** and one or more mechanisms, such as deep links or manual entry of a PIN, can be used to provide the challenge to the @login application running on the mobile device **1102**.

(227) The @login application can leverage the @protocol's ability to share data security and privately with known counter parties. As shown in the figures below, the @login application can be used for scenarios in which a web server of a website either is or is not already associated with a unique @sign identifier within the platform. In both scenarios, techniques can be used for allowing secure logins using the underlying identity management platform and encryption challenges of the @protocol.

(228) FIG. **12** is a block diagram of an example system **1200** for supporting website login functionality. A user can use, for example, a web browser **1202** on a desktop device **1204** or a mobile application or browser **1206** on a mobile device **1208** to view web pages provided by a web server **1210**. The user can have an @sign, and personal information for the user can be stored in a personal directory **1212** of a secondary server **1214**. As described above, the mobile device **1208** of the user can include a local personal directory **1216** which can be a cache of some or all information in the personal directory **1212**. In some cases, an entity that manages the web server (e.g., an entity associated with the website itself) can have an @sign and information for the entity that the entity wishes to share with other protocol users can be stored in a directory **1218** that is managed by a secondary server **1220** associated with the entity

(229) Some web page(s) provided by the web server **1210** can require that a user log in to the web server **1210**. The web server **1210** can provide, for example, a login web page or user interface to the desktop device **1204** or the mobile device **1208** that enables the user to enter an @sign and send the @sign to the web server **1204**. The web server **1210** can generate a challenge code and provide the challenge code to the desktop device **1204** or the mobile device **1208**. A login application **1222** running on the mobile device **1204** can obtain the challenge code (e.g., the user can scan the code, enter the code, or select a deep link that enables the login application **1222** to obtain the code). The login application **1222** can sign the challenge code using a private key associated with the @sign and place the signed challenge at a particular location in the personal directory **1212**. The private key can be stored on the mobile device **1208**, for example.

(230) A server application **1224** running on the web server **1210** can look for and retrieve the signed challenge from the particular location in the personal directory **1212**. The server application **1224** can also obtain a public key of the user from the personal directory **1212** and use the public key to determine whether the signed challenge was signed correctly by the login application **1222**. If the login application **1222** correctly signed the challenge code, the server application **1224** can effectively log the user into the web site served by the web server **1210**. Other details and alternatives of a login handshake performed using the protocol are described below.

(231) FIG. **13** is a block diagram of an example architecture **1300** for supporting website login functionality. In a first phase (e.g., labeled "1."), a prompt is displayed in a @login user interface on a device **1302** of the user. The prompt can instruct the user to enter their @sign to log in to a website hosted by a web server **1304**, for example. The @login user interface can enable the user to enter their @sign handle. In some implementations, the @login user interface can prompt the user to enter a PIN of the user's choosing.

(232) In a second phase, the @sign handle entered by the user is sent from the device **1302** to the web server **1304**. If the @login user interface asked the user to enter a PIN of the user's choosing, the PIN of the user's choosing can also be sent from the device **1302** to the web server. The PIN of the user's choosing can also be stored on the device **1302** of the user. In a third phase, the web

server **1304** generates a code challenge and sends the code to the device **1302**. The code challenge can be a PIN (which may be embodied in a QR code), for example. The device **1302** can display the challenge code, in the @login user interface, as a presented code **1308** and/or a presented PIN **1309**, after receiving the code from the web server **1304**. In implementations in which the user has provided a PIN of the user's choosing, the web server **1304** can generate the challenge code based on the PIN of the user's choosing. Basing the challenge code on the PIN of the user's choosing can reduce a chance of a replay attack, for example.

(233) In a fourth phase, the user can use, for example, an @login application running on a mobile device **1310** to scan the presented code **1308**. As another example, the user can use the @login application to enter the PIN **1309**. The mobile device **1310** may be a different device than the device **1302**. For example, the device **1302** can be a desktop device and the user can use the mobile device **1310** to scan the presented code **1308**. In some cases, the device **1302** and the mobile device **1310** are the same device. For instance, the user can view the PIN **1309** in a webpage provided by the web server **1304** that is presented in a web browser on the mobile device **1310**. The user can switch to the @login application on the mobile device **1310** and enter the PIN into the @login application.

(234) In a fifth phase, the @login application can place a challenge value (that is based on the code challenge) at a specified location on an @sign server **1312** that is associated with the @sign of the user. As indicated by a note **1314**, the challenge value can be computed by creating a hash of the user's @sign combined with the code challenge/PIN **1316**. In implementations in which the user had provided a PIN of the user's choosing, the PIN of the user's choosing can be incorporated into the challenge value. As indicated by a note **1318**, the @login application can sign the challenge value with a private key associated with the @sign. In some implementations, a SHA512 hash algorithm can be used to create the challenge value (although other hash functions can be used). As an example, when the user's @sign is @alice, the PIN is GH5J, and the SHA512 algorithm is used, the challenge value can be:

1e1311d473b211796e3d1635079aef297051a2fe6f52decf06a1e28e1b3c2572a796eb51c1a
2b0d7fdb4cdb55cc0ecd040e8c5a3533f888a489d207ba8f0c942.

(235) As indicated by a note **1320**, if the web server **1304** has an associated @sign, the @login application can encrypt the signed challenge value with a public key of the web server. For example, the @login application can query a secondary @sign server associated with the web server **1304** (or associated with the website which the web server **1304** serves) for the public key of the web server **1304**. The @login application can place the signed challenge value at a location **1321** on the @sign server **1312**. The location **1321** is a specified location in the @ namespace on the @sign server **1312** where the signed challenge value can be found by the web server **1304**.

(236) The location **1321** can be based on the challenge value. In some implementations, the location **1321** can be the challenge value with an added “_____” prefix. A “_____” character in the location **1321** can signify that the location can be a key that is hidden (e.g., not returned) by a scan verb. That is, an entity such as the web server **1304** can look up the signed challenge value using the location key but would have to know the value of the location key before performing the look up (i.e., an entity that does not know the location **1321** cannot use the scan verb to discover the location key). As indicated by a note **1322**, the challenge value can be placed in the specified location for a certain amount of time. For instance, a TTL setting can be configured, for example to ten seconds, which means that the web server **1304** has ten seconds to retrieve the signed challenge value before the signed challenge value is removed from the @sign server **1312**.

(237) As described in a note **1322**, in some implementations, the @login application can create a nonce (e.g., a random number) and place the nonce at a particular location in the @sign server **1312**. For example, the @login application can place the nonce at a location value that has a pattern of: _nonce.<PIN>.login<@sign>. For instance, when the user's @sign is @alice, the PIN is GH5J, and the nonce is a random value of 1451, the nonce value of 1451 can be placed in the @sign

server **1312** at a location of “_nonce.GH5J.login@alice”. As described by a note **1324**, when a nonce is used, the nonce value can be combined with the PIN and the user's @sign when creating a challenge value.

(238) In a sixth phase, the web server **1304** obtains a public key associated with the @sign of the user (e.g., by querying the @sign server **1312**). In implementations where a nonce is used, the web server **1304** can retrieve the nonce from the @sign server (e.g., if the PIN is GH5J and the user's @sign is @alice, the web server **1304** can retrieve the nonce from the @sign server **1312** using a lookup of a key of _nonce.GH5J.login@alice). In a seventh phase, the web server **1304** retrieves, from the @sign server **1312**, the signed challenge value placed by the @login application. The web server **1304** can poll the @sign server **1312** for a predetermined period of time (e.g., ten seconds) to attempt to retrieve the signed challenge value, for example.

(239) In an eighth phase, the web server **1304** can perform one or more operations to validate the retrieved signed challenge value. For example, when the web server **1304** has an @sign and @login application had encrypted the signed challenge value using the public key of the @sign of the web server **1304**, the web server **1304** can decrypt an encrypted signed challenge value using a private key of the web server to extract a signed challenge value. The web server **1304** can use a public key of the @sign of the user to decrypt the signed challenge value (e.g., to obtain an extracted challenge value). As described above, the challenge value generated by the @login application can be a hash of a combination of the @sign of the user and the challenge code previously provided to the device **1302** of the user (and possibly a nonce value). Accordingly, to test the extracted challenge value, the web server **1304** can perform a hash operation on a combination of the @sign of the user and the challenge code provided to the device (and possibly a nonce value retrieved from the @sign server **1312**). For example, the web server can perform a SHA512 hash operation on a @alice:GH5J value (with a possible nonce suffix) that is a combination of the @alice handle and a GH5J PIN that the web server **1304** knows was sent to the device **1302** of the user. If a result of the hash operation equals the extracted challenge value, the web server **1304** can determine that the user has successfully performed the requested login procedure using the @protocol. Accordingly, the web server **1304** can allow the user to log in to the website. For example, the web server **1304** can generate another web page to provide to the device **1302** of the user that is a landing page for logged-in users of the web site. If the extracted challenge value does not equal the result of the hash operation performed by the web server **1304**, the web server **1304** can deny the login request. For example, the web server can generate or a login-failed web page and provide the login-failed web page to the device **1302** of the user. The login-failed web page can also be generated and provided to the device **1302** of the user if the web server fails to receive a signed challenge value from the @sign server **1312**, for example. For instance, the web server **1304** may poll the @sign server **1312** for a certain number of seconds or until a signed challenge value is successfully received. In implementations in which the user provided a PIN of the user's choosing, the web server **1304** can perform an algorithm that uses the PIN of the user's choosing to extract the challenge value.

(240) If the web server **1304** has an @sign, a ninth phase can be performed in some implementations (or for some web pages or web servers). For example, the user may have using the @protocol to share certain information with the @sign of the website. The web server **1304** can lookup information at the @sign server **1312** that has been explicitly shared by the user with the @sign of the website. The web server **1304** can use information for the user that has been received from the @sign server for use in one or more web pages generated by the web server **1304** for the user. For example, the web server **1304** can provide a form page that includes pre-filled information that the user has shared with the @sign of the website.

(241) FIGS. **14A-14C** illustrate a swim lane diagram **1400** for website login scenarios using a protocol for sharing and managing personal information. At **1402**, a user device **1404** of a user sends a request **1406** to a web server **1408** for a web page served by the web server **1408**.

(242) At **1410**, the web server **1408** sends web page information **1412** for the requested web page to the user device **1404** in response to the request **1406**.

(243) At **1414**, the user device **1404** uses the received web page information **1412** to display the web page on the user device **1404**. The web page can include a prompt (e.g., and an associated input field) for entering an @sign to login to the website. The web page can also include a “login” button or similar user interface control that the user can select or trigger to request sending of the @sign to the web server **1408** to initiate a login process at the web server **1408**.

(244) At **1416**, the user device **1404** receives an @sign of the user that the user has entered into the web page. The user device **1404** can receive the @sign as part of handling an event related to the user selecting a login button or some other trigger event (e.g., a press of an “enter” key) for requesting initiation of a login process.

(245) At **1418**, the user device **1404** sends an @sign handle **1420** of the user to the web server **1408**.

(246) At **1422**, the web server **1408** generates a code challenge. The code challenge can be a randomly-generated PIN, for example. In some implementations, the code challenge can be represented or incorporated into a QR code image. The web server **1408** can generate a code challenge web page that includes the code challenge.

(247) At **1424**, the web server **1408** sends a generated code challenge **1426** (e.g., as part of the code challenge web page) to the user device **1404**.

(248) At **1428**, the user device **1404** displays the code challenge. For example, the user device **1404** can display the code challenge web page that includes the PIN and/or the QR code image generated by the web server **1408**.

(249) At **1430**, a mobile device **1432** of the user can acquire the a challenge code using one of a variety of approaches. For instance, in some implementations, the mobile device **1432** is a different device than the user device **1404**. For example, the user device **1404** can be a desktop device and the user can use, for example, an @login application on the mobile device **1404** to scan a QR code that is included in the code challenge web page that is displayed on the user device **1404**. As another example, the user can use the @login application on the mobile device **1430** to enter a PIN that is included in the code challenge web page that is displayed on the user device **1404**.

(250) In some implementations, the user device **1404** and the mobile device **1432** are the same device. The mobile device **1432** can acquire the challenge code as a result of a user transitioning from a web browser that is displaying the code challenge web page to the @login application and using the @login application to enter a PIN that is displayed in the code challenge web page. As another example, the code challenge web page can display a deep link that includes the challenge code and a link to the @login application. In response to user selection of the deep link, the @login application can acquire the challenge code.

(251) At **1434**, the mobile device **1432** generates a signed challenge value **1436** and an @protocol command **1438** for placing the signed challenge value at a particular location in a namespace of an @sign server **1440** of the user. As described above with respect to FIG. **14**, the mobile device **1432** can generate the signed challenge value **1436** by signing a challenge value that is based on the challenge code using a private key associated with the @sign of the user. Additionally, if the web server **1408** (e.g., or the website that is served by the web server **1408**) has an @sign, the mobile device **1432** can encrypt the signed challenge value using a public key associated with the @sign of the web server **1408**. For example, the mobile device **1432** can query an @sign server associated with the web server **1408** for the public key associated with the web server **1408** (the @sign server associated with the web server **1408** may reside on the web server **1408** or on a different device than the web server **1408**). Also as described above with respect to FIG. **13**, the location in the namespace of the @sign server **1440** at which to store the signed challenge value can be a particular location value that is determined based on the challenge value.

(252) At **1442**, the mobile device **1432** sends an authentication request **1444** to authenticate the

mobile device **1432** on behalf of the user at the @sign server **1440**.

(253) At **1446**, the @sign server **1440** authenticates the user on the @sign server (e.g., using user protocol authentication processes described above).

(254) Referring now to FIG. **14B**, at **1448**, the mobile device **1432** sends a request **1450** (e.g., that is or includes a previously generated protocol command) to the @sign server **1440** to place the signed challenge value at the particular location.

(255) At **1452**, the @sign server **1440** places the signed challenge value at the particular location in the namespace of the @sign server **1440**.

(256) At **1454**, the web server **1408** sends a lookup request **1456** to the @sign server **1440** for a public key of the user. The public key of the user can be publicly accessible at the @sign server, for example.

(257) At **1458**, the @sign server **1440** can retrieve the requested public key from storage of the @sign server **1440**.

(258) At **1460**, the @sign server **1440** sends a retrieved public key **1462** of the user to the web server **1408**.

(259) At **1464**, the web server **1408** sends a lookup request **1466** to the @sign server **1440** for the signed challenge value at the particular location in the namespace of the @sign server **1440**. The signed challenge value can be publicly accessible at the @sign server, for example, but at a location that is not publicly broadcasted (e.g., using a scan verb). The signed challenge value can have a TTL setting that results in the signed challenge value being available at the particular location only for a predetermined amount of time (e.g., ten seconds).

(260) At **1468**, the @sign server **1440** can retrieve the requested signed challenge value from storage of the @sign server **1440**.

(261) At **1470**, the @sign server **1440** sends a retrieved signed challenge value **1472** to the web server **1408**.

(262) At **1473**, the web server **1408** uses the public key the user's @sign to decrypt the signed challenge value to generate an extracted challenge value.

(263) At **1474**, the web server **1408** compares the extracted challenge value to a challenge value that is based on the challenge code that was previously sent to the user device **1404**. As described above, the web server **1408** can perform one or more operations to generate a challenge value to be compared to the extracted challenge value (e.g., the web server can perform a hash operation on a combination of the user's @sign and the challenge code that was sent to the user device **1404**).

(264) If the extracted challenge value does not equal the challenge value that the web server **1408** generated for comparison, the web server **1408** can deny a login request for the user (e.g., by generating and providing an error page to the user device **1404**). As another example, at **1476**, if the extracted challenge value equals the challenge value that the web server **1408** generated for comparison, the web server **1408** can authenticate the user to the web site. The web server **1408** can generate a landing page for the user, for example.

(265) At **1477**, the web server **1408** provides a landing page **1478** (e.g., for logged-in users) to the user device **1404**. At **1480**, the user device **1404** displays the received landing page.

(266) Referring now to FIG. **14C**, if the user has shared information using the @protocol with an @sign of the web site (or the web server **1408** or an entity associated with the website/the web server **1408**), the web server **1408** can obtain the shared information and use the information in one or more web pages provided to the user device **1404** (or, in general, for one or more processes that the web server **1408** performs on behalf of the user).

(267) At **1482**, the web server **1408** sends a lookup request **1484** to the @sign server **1440** for information that the @sign of the user has shared with an @sign of the website. The lookup request **1484** can correspond to the web server **1408** (or a secondary server corresponding to the website, the web server **1408**, or the entity of the website) authenticating to the @sign server as the @sign of the website (e.g., according to the public lookup protocols described above).

(268) At **1486**, the @sign server **1440** determines if the @sign of the user has shared information with the @sign of the website. If the @sign of the user has shared information with the @sign of the website, the @sign server can retrieve the information shared by the @sign of the user with the @sign of the website.

(269) At **1488**, the @sign server **1440** sends retrieved shared information **1489** to the web server **1408**.

(270) At **1490**, the web server **1408** uses the received shared information. For example, the web server **1408** can use the shared information in one or more server processes. In some cases, the web server **1408** uses the shared information to generate one or more web pages. For some web pages, the shared information is included in the web page (e.g., as pre-filled form fields, for example, or as other webpage content).

(271) At **1492**, the web server **1408** sends a web page **1494** that includes (or was generated based on) the shared information shared by the @sign user with the website.

(272) At **1496**, the user device **1404** displays the received web page that includes (or was generated based on) the shared information shared by the @sign user with the web site.

(273) FIG. **15** is a diagram **1500** that illustrates example user interfaces for website login scenarios using a protocol for sharing and managing personal information. The example user interfaces are described as web pages, but other types of user interfaces, such as screens of a mobile or desktop application may be used.

(274) A web page **1502** includes a prompt **1504** that informs a user that the user can log in to an “ABC” website using an @sign. A web server that served the web page **1502** can be configured to participate in a login scenario using the @protocol, for example, and can generate and provide the web page **1502** to a user device of the user. The web page **1502** includes a field **1506a** that can be used by the user to enter an @sign handle and a login button **1508a** that can be selected to trigger a sending of the @sign handle to the web server.

(275) A web page **1510** that corresponds to the web page **1502** illustrates that the user has entered an @sign handle **1512** of @alice in a field **1506b** that corresponds to the field **1506a**. After entering the @sign handle **1512**, the user can select a login button **1508b** that corresponds to the login button **1508a**. In response to selection of the login button **1508b**, the @sign handle **1512** can be provided to the web server that provided the web page **1510**.

(276) A web page **1520** can be provided the user device by the web server in response to the web server receiving the @sign handle **1512** from the user device. The user device can present the received web page **1520**. The web page **1520** includes a prompt **1522** that informs the user to scan a code **1524** using, for example, an @settings or @login application, to continue the login process. In some cases, the user may use a second device (e.g., a mobile device) to scan the code **1524** when the user device that is displaying the web page **1520** is a desktop device, for example. The code **1524** is shown as a QR code. The QR code can embody a PIN that has been randomly generated by the web server. As another example, the QR code can embody a deep link and a PIN that when scanned by the user device can launch (or open) an @login application that receives the PIN upon being launched or opened.

(277) After the user has scanned the code **1524** (or entered a PIN that is presented along with the code **1524**), the @login application (or @settings application) running on a user device and the web server can each participate in the @login handshake that is described above with respect to FIGS. **13** and **14A-C**. Accordingly, the user can be successfully logged in to the website using features of the @protocol. After the user has been successfully logged in to the website using the @sign of the user, a web page **1530** can be provided to the user device by the web server and the web page **1530** can be presented on the user device.

(278) The web page **1530** includes a label **1532** and a label **1533** that each indicate that the login process using the user's @sign handle completed successfully. In some implementations, the website can be configured to enable the user to use information in their @profile that they have

shared with the website (that is, shared with an @sign associated with the website), for example, for use in filling in forms etc. For instance, the user can have the website use information from their @profile instead of the user having to manually enter the information. For instance, the user can select a link **1534** to start a claim submission process that includes a form that can be filled with at least some information from the user's @profile or from information from a secondary server of the user.

(279) A web page **1540** can be provided to the user device by the web server in response to user selection of the link **1534**. The web page **1540** is a claim form that includes fields **1542a**, **1544a**, and **1546a** for name, phone, and birthday values, respectively. The web page **1540** includes a button **1548** that the user can select to instruct the web server to retrieve information from the user's @profile (or otherwise from the user's secondary server) so that the user does not need to manually provide information for the fields.

(280) A web page **1560** can be provided to the user device in response to selection of the button **1548**. The web page **1560** includes a name value **1562**, a phone value **1564**, and a birthday value **1566** that have been automatically placed into fields **1542b**, **1544b**, and **1546b** (that correspond to the fields **1542a**, **1544a**, and **1546a**). The name value **1562**, the phone value **1564**, and the birthday value **1566** can be information that the user has shared, using the @protocol, with an @sign associated with the website/web server. The web server can authenticate to an @sign server of the user and look up and retrieve information for an @alice handle (e.g., name@alice, phone@alice, and birthday@alice) that the @alice user has explicitly given permission for to the @sign associated with the web site/webserver. The user can select a submit button **1568** (e.g., perhaps after entering other information into other fields of the web page **1560**) and information from the web page **1560** can be provided to the web server.

(281) FIG. **16** is a flowchart of an example method **1600** for webserver participation in a login process. It will be understood that method **1600** and related methods may be performed, for example, by any suitable system, environment, software, and hardware, or a combination of systems, environments, software, and hardware, as appropriate. In some implementations, the method **1600** is executed by one or more components of the system **1200** described above with respect to FIG. **12**. For example, the method **1600** can be executed by the web server **1210**.

(282) At **1602**, a request is received from a user device of a user for a first login page of a web site.

(283) At **1604**, the first login page of the web site is generated. The first login page includes a field that enables the user to enter a handle for a decentralized resource directory.

(284) At **1606**, the first login page of the website is provided to the user device.

(285) At **1608**, the handle for the decentralized resource directory is received from the user device.

(286) At **1610**, a unique challenge code is generated for the handle.

(287) At **1612**, the unique challenge code for the handle is inserted into a second login page.

(288) At **1614**, the second login page that includes the unique challenge code for the handle is provided to the user device.

(289) At **1616**, a request is sent to a protocol server to obtain a challenge value stored by the user device at a location in a decentralized resource directory associated with the handle. The challenge value and the location are generated by the user device based on the challenge code.

(290) At **1618**, the challenge value is received from the protocol server.

(291) At **1620**, a server challenge value code is generated, using the challenge code sent to the first user device and the handle received from the first user device, to compare to the challenge value received from the protocol server. For example, the server challenge value can be generated by creating a hash of a combination of the challenge code sent to the first user device and the handle received from the first user device. In some implementations, the user device has cryptographically signed the challenge value for the handle using a private key of a public/private key pair for the handle. A request can be sent to the protocol server to obtain a public key of the public/private key pair for the handle from the decentralized resource directory and the challenge value can be

decrypted using the public key. In some implementations, the user device has cryptographically signed the challenge value for the handle using a public key of a public/private key pair associated with the website and the challenge value received from the protocol server can be decrypted using a private key of the public/private key pair associated with the website.

(292) At **1622**, a determination is made as to whether the server challenge value matches the challenge value received from the protocol server (e.g., after possible decryption of the received challenge value).

(293) At **1624**, the user is logged into the website in response to determining that the server challenge value matches the received challenge value.

(294) At **1626**, a login request to the website is denied for the user in response to determining that the server challenge value does not match the received challenge value.

(295) In some implementations, the decentralized resource directory includes shared user information for the user that the user has explicitly shared with an entity associated with the website. A request can be sent to the protocol server for the shared user information and the shared user information can be used to generate at least one web page for the user while the user is logged into the website.

(296) FIG. **17** is a flowchart of an example method for client participation in a login process. It will be understood that method **1700** and related methods may be performed, for example, by any suitable system, environment, software, and hardware, or a combination of systems, environments, software, and hardware, as appropriate. In some implementations, the method **1700** is executed by one or more components of the system **1200** described above with respect to FIG. **12**. For example, the method **1700** can be executed by the user device **1208**.

(297) At **1702**, a request is sent to a webserver for a first login page of a website.

(298) At **1704**, the first login page of the website is received. The first login page includes a field that enables a user to enter a handle for a decentralized resource directory.

(299) At **1706**, the first login page of the website is presented to the user.

(300) At **1708**, the handle for the decentralized resource directory is received from the user.

(301) At **1710**, the handle for the decentralized resource directory is provided to the web server.

(302) At **1712**, a second login page that includes a unique challenge code for the handle is received from the webserver. The first login page can also include a field that allows the user to provide a user-provided code and the user-provided code can be provided to the webserver along with the handle. The unique challenge code received from the webserver can be generated by the webserver based on the user-provided code.

(303) At **1714**, the second login page that includes the unique challenge code for the handle is presented.

(304) At **1716**, the unique challenge code for the handle is obtained from the second login page.

(305) At **1718**, a challenge value is generated based on the unique challenge code. The challenge value for the handle can be encrypted using a private key of a public/private key pair for the handle. The private key of the public/private key pair for the handle from can be retrieved from a user device of the user. The challenge value for the handle can be signed using a public key of a public/private key pair associated with the website.

(306) At **1720**, a location in the decentralized resource directory is determined, based on the challenge value.

(307) At **1722**, a request is sent to a protocol server to store the challenge value in the decentralized resource directory at the location as a login challenge response for logging into the website.

(308) At **1724**, a login result page is received from the webserver that indicates a result of the webserver processing the login challenge response. The login result page can indicate that the webserver successfully validated the login challenge response.

(309) The preceding figures and accompanying description illustrate example processes and computer-implementable techniques. But system **100** (or its software or other components)

contemplates using, implementing, or executing any suitable technique for performing these and other tasks. It will be understood that these processes are for illustration purposes only and that the described or similar techniques may be performed at any appropriate time, including concurrently, individually, or in combination. In addition, many of the operations in these processes may take place simultaneously, concurrently, and/or in different orders than as shown. Moreover, system **100** may use processes with additional operations, fewer operations, and/or different operations, so long as the methods remain appropriate.

(310) In other words, although this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of these embodiments and methods will be apparent to those skilled in the art. Accordingly, the above description of example embodiments does not define or constrain this disclosure. Other changes, substitutions, and alterations are also possible without departing from the spirit and scope of this disclosure.

Claims

1. A system comprising: a first user device of a user; a protocol server associated with the user comprising a personal decentralized resource directory of the user; and a webserver associated with a website; wherein the first user device is configured to: send a request to the webserver for a first login page of the website; wherein the webserver is configured to: receive the request for the first login page of the website; generate the first login page of the website, wherein the first login page includes a field that enables the user to enter a handle that uniquely identifies the personal decentralized resource directory of the user; and provide the first login page of the website to the first user device; wherein the first user device is further configured to: receive the first login page of the website; present the first login page of the website; receive, from the user, the handle that uniquely identifies the personal decentralized resource directory of the user; and provide the handle for the personal decentralized resource directory of the user to the webserver; wherein the webserver is further configured to: receive the handle for the personal decentralized resource directory of the user from the first user device; generate a unique challenge code for the handle; insert the unique challenge code for the handle into a second login page; and provide the second login page that includes the unique challenge code for the handle to the first user device; wherein the first user device is further configured to: receive the second login page that includes the unique challenge code for the handle; present the second login page that includes the unique challenge code for the handle; obtain the unique challenge code for the handle from the second login page; generate a challenge value based on the unique challenge code; determine, based on the challenge value, a location in the personal decentralized resource directory of the user; and send a request to the protocol server to store the challenge value in the personal decentralized resource directory of the user at the location; wherein the webserver is further configured to: send a request to the protocol server to obtain the challenge value from the location in the personal decentralized resource directory of the user; receive the challenge value from the protocol server; generate a server challenge value, using the challenge code sent to the first user device and the handle received from the first user device, to compare to the challenge value received from the protocol server; determine whether the server challenge value matches the challenge value received from the protocol server; log the user into the website in response to determining that the server challenge value matches the challenge value received from the protocol server; and deny a login request to the website for the user in response to determining that the server challenge value does not match the challenge value received from the protocol server.

2. The system of claim 1, wherein: the first user device is configured to cryptographically sign the challenge value for the handle using a private key of a public/private key pair for the handle; and the webserver is further configured to: send a request to the protocol server to obtain a public key of the public/private key pair for the handle from the personal decentralized resource directory of

the user; receive, from the protocol server, the public key of the public/private key pair for the handle; and decrypt the challenge value using the public key.

3. The system of claim 2, wherein the private key of the public/private key pair for the handle is stored on the first user device.

4. The system of claim 1, wherein: the first user device is configured to cryptographically sign the challenge value for the handle using a public key of a public/private key pair associated with the website; and the webserver is further configured to decrypt the challenge value using a private key of the public/private key pair associated with the website.

5. The system of claim 1, wherein: the first login page includes a field that allows the user to provide a user-provided code; the first user device is configured to provide the user-provided code to the webserver along with the handle of the user; and the webserver is configured to generate the challenge code using the user-provided code.

6. The system of claim 1, further comprising a second user device of the user, wherein the first login page is presented on the first user device and the user second device is configured to generate the challenge value, determine the location in the personal decentralized resource directory of the user, and send the request to the protocol server to store the challenge value in the personal decentralized resource directory of the user at the location.

7. The system of claim 6, wherein the challenge code is a scannable code that is presented on the first user device and the second user device is configured to scan the scannable code that is presented on the first user device.

8. The system of claim 1, wherein: the personal decentralized resource directory of the user includes shared user information for the user that the user has explicitly shared with an entity associated with the website; and the webserver is further configured to: send a request to the protocol server for the shared user information for the user in the personal decentralized resource directory of the user that has been explicitly shared with the entity associated with the website; receive the shared user information; use the shared user information to generate at least one web page for the user while the user is logged into the website; and provide the at least one web page to the first user device.

9. The system of claim 1, wherein the first user device is further configured to generate the challenge value based on the unique challenge code by generating a hash value of a combination of the handle and the unique challenge code.

10. The system of claim 1, wherein the first user device is further configured to: generate a nonce value; generate the challenge value based on the challenge code and the nonce value; and send a request to the protocol server to store the nonce value in the personal decentralized location of the user at the location that is based on the challenge code; wherein the webserver is further configured to: send a request to the protocol server to obtain the nonce from the decentralized resource directory; receive the nonce from the protocol server; and use the nonce when generating the server challenge value.

11. A computer-implemented method comprising: receiving a request from a user device of a user for a first login page of a website; generating the first login page of the website, wherein the first login page includes a field that enables the user to enter a handle that uniquely identifies a personal decentralized resource directory of the user; providing the first login page of the website to the user device; receiving the handle that uniquely identifies the personal decentralized resource directory of the user from the user device; generating a unique challenge code for the handle; inserting the unique challenge code for the handle into a second login page; providing the second login page that includes the unique challenge code for the handle to the user device; sending a request to a protocol server to obtain a challenge value stored by the user device at a location in the personal decentralized resource directory of the user, wherein the challenge value and the location are generated by the user device based on the challenge code; receiving the challenge value from the protocol server; generating a server challenge value, using the challenge code sent to the user

device and the handle received from the user device, to compare to the challenge value received from the protocol server; determining whether the server challenge value matches the challenge value received from the protocol server; logging the user into the website in response to determining that the server challenge value matches the challenge value received from the protocol server; and denying a login request to the website for the user in response to determining that the server challenge value does not match the challenge value received from the protocol server.

12. The computer-implemented method of claim 11, wherein the user device has cryptographically signed the challenge value for the handle using a private key of a public/private key pair for the handle, the method further comprising: sending a request to the protocol server to obtain a public key of the public/private key pair for the handle from the decentralized resource directory; receiving, from the protocol server, the public key of the public/private key pair for the handle; and decrypting the challenge value using the public key.

13. The computer-implemented method of claim 11, wherein the user device has cryptographically signed the challenge value for the handle using a public key of a public/private key pair associated with the website, the method further comprising decrypting the challenge value received from the protocol server using a private key of the public/private key pair associated with the website.

14. The computer-implemented method of claim 11, wherein: the decentralized resource directory includes shared user information for the user that the user has explicitly shared with an entity associated with the website, the method further comprising: sending a request to the protocol server for the shared user information for the user in the personal decentralized resource directory of the user that has been explicitly shared with the entity associated with the website; receiving the shared user information; using the shared user information to generate at least one web page for the user while the user is logged into the website; and providing the at least one web page to the user device.

15. A computer-implemented method comprising: sending a request to a webserver for a first login page of a website; receiving the first login page of the website, wherein the first login page includes a field that enables a user to enter a handle that uniquely identifies a personal decentralized resource directory of the user; presenting the first login page of the website; receiving, from the user, the handle that uniquely identifies the personal decentralized resource directory of the user; providing the handle that uniquely identifies the personal decentralized resource directory of the user to the webserver; receiving, from the webserver, a second login page that includes a unique challenge code for the handle that was generated by the webserver; presenting the second login page that includes the unique challenge code for the handle; obtaining the unique challenge code for the handle from the second login page; generating a challenge value based on the unique challenge code; determining, based on the challenge value, a location in the personal decentralized resource directory of the user; sending a request to a protocol server to store the challenge value in the personal decentralized resource directory of the user at the location as a login challenge response for logging into the website; and receiving from the webserver, a login result page that indicates a result of the webserver processing the login challenge response.

16. The computer-implemented method of claim 15, wherein the login result page indicates that the webserver successfully validated the login challenge response.

17. The computer-implemented method of claim 15, further comprising cryptographically signing the challenge value for the handle using a private key of a public/private key pair for the handle.

18. The computer-implemented method of claim 17, further comprising retrieving the private key of the public/private key pair for the handle from a user device of the user.

19. The computer-implemented method of claim 15, further comprising cryptographically signing the challenge value for the handle using a public key of a public/private key pair associated with the website.

20. The computer-implemented method of claim 15, wherein the first login page includes a field that allows the user to provide a user-provided code, the method further comprising: receiving,

from the user, the user-provided code; and providing the user-provided code to the webserver along with the handle of the user, wherein the unique challenge code received from the webserver is generated by the webserver based on the user-provided code.
