

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250282401

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Amouie; Mabby Nicholas et al.

---

### RAIL-SIDE INSPECTION ASSEMBLIES AND SYSTEMS

---

#### Abstract

An inspection assembly can comprise a first camera, a second camera, one or more lights, and a housing. The first camera can be angled at least partially in a vertical direction and at least partially in a horizontal direction to thereby be configured to capture images of a target region in a three-dimensional space from a first viewpoint. The second camera can be positioned apart from the first camera, angled at least partially in the vertical direction and at least partially in the horizontal direction, and directed to the target region from a second viewpoint that is different from the first viewpoint. The housing can comprise a base and a shroud and can be configured to attach to one or more rail ties and to at least partially envelop the first camera and the second camera.

---

**Inventors:** Amouie; Mabby Nicholas (Atlanta, GA), Gebhardt; Evan Thomas (Atlanta, GA), Usher; Colin (Atlanta, GA), Samoylov; Alex (Atlanta, GA), Hoang; John (Atlanta, GA), Thomas; Sean (Atlanta, GA), Mandrekar; Parth (Atlanta, GA), Yeager; Brian Thomas (Atlanta, GA), Fox; Thomas Samuel (Atlanta, GA)

**Applicant:** Norfolk Southern Corporation (Atlanta, GA); GEORGIA TECH RESEARCH CORPORATION (Atlanta, GA)

**Family ID:** 94872320

**Appl. No.:** 19/219950

**Filed:** May 27, 2025

#### Related U.S. Application Data

parent US continuation 18829200 20240909 parent-grant-document US 12348880 child US 19219950

us-provisional-application US 63581554 20230908

us-provisional-application US 63582165 20230912

---

## Publication Classification

**Int. Cl.:** **B61L25/02** (20060101); **B61L25/04** (20060101); **B61L27/53** (20220101); **B61L27/57** (20220101); **B61L27/70** (20220101); **G01M17/10** (20060101); **G06T7/00** (20170101); **G06T7/55** (20170101); **G06T7/80** (20170101); **G06V20/52** (20220101); **G06V20/54** (20220101); **G06V20/62** (20220101); **G06V30/10** (20220101); **H04N7/18** (20060101); **H04N23/11** (20230101); **H04N23/51** (20230101); **H04N23/52** (20230101); **H04N23/56** (20230101); **H04N23/60** (20230101); **H04N23/90** (20230101)

## U.S. Cl.:

**CPC** **B61L25/021** (20130101); **B61L25/025** (20130101); **B61L25/04** (20130101); **B61L27/53** (20220101); **B61L27/57** (20220101); **B61L27/70** (20220101); **G01M17/10** (20130101); **G06T7/0002** (20130101); **G06T7/001** (20130101); **G06T7/55** (20170101); **G06T7/80** (20170101); **G06V20/52** (20220101); **G06V20/54** (20220101); **G06V20/63** (20220101); **G06V30/10** (20220101); **H04N7/18** (20130101); **H04N7/188** (20130101); **H04N23/11** (20230101); **H04N23/51** (20230101); **H04N23/52** (20230101); **H04N23/56** (20230101); **H04N23/64** (20230101); **H04N23/90** (20230101); **G06T2207/10024** (20130101); **G06T2207/10048** (20130101); **G06T2207/30252** (20130101); **G06V2201/08** (20220101)

---

## Background/Summary

**CROSS-REFERENCE TO RELATED APPLICATIONS [0001]** This application is a continuation of U.S. patent application Ser. No. 18/829,200, filed on Sep. 9, 2024, and entitled “RAIL-SIDE INSPECTION ASSEMBLIES AND SYSTEMS,” which claims the benefit of, and priority to, U.S. Provisional Patent App. No. 63/581,554, filed on Sep. 8, 2023, and entitled “APPARATUSES, SYSTEMS, AND METHODS FOR MONITORING TRAIN RAILCARS,” and U.S. Provisional Patent App. No. 63/582,165, filed on Sep. 12, 2023, and entitled “APPARATUSES, SYSTEMS, AND METHODS FOR MONITORING TRAIN RAILCARS,” the disclosures of which are incorporated by reference in their entireties as if the same were fully set forth herein.

### TECHNICAL FIELD

[0002] This application generally relates to systems and methods for inspecting passing vehicles and, more specifically, to identify any defects or potential defects in various components and/or systems of a railcar and/or train, such as cross-key systems, as a non-limiting example.

### BACKGROUND

[0003] Trains are vital transportation mediums used to distribute a large quantity of goods around the world. Due to their robust nature and efficiency, trains and their sub-components, such as railcars and locomotives, are commonly used repeatedly throughout their lifetime. Repeated and constant use of a particular train can cause the particular train to experience degradation over time. The trains are traditionally inspected by individuals at rail yards for any particular issue and to prevent safety and functionality hazards. These inspections can be costly due to the manpower necessary to properly complete the inspections, the amount of time it takes to inspect the trains, and the lost revenue associated with keeping the train in the railyard. Additionally, humans can occasionally miss issues that can lead to safety hazards and/or functional issues with the train.

[0004] Further, some existing attempts to automate inspections of moving objects, particularly railcars, can be inadequate because they are unable to capture images that clearly illustrate views necessary to detect certain defects.

[0005] Therefore, there is a long-felt but unresolved need for a system, assembly, and method that

monitors moving objects (e.g., trains), minimizes or otherwise reduces the man-hours necessary for inspecting subject objects, identifies a wide variety of issues associated with the objects, records data associated with the objects, and/or generates insights associated with the objects.

#### BRIEF SUMMARY OF THE DISCLOSURE

[0006] Briefly described, and according to one example, aspects of the present disclosure generally relate to systems, assemblies, and/or devices, and methods thereto, for capturing images of passing railcars (e.g., one or more railcars of a train) or components thereof and/or gathering additional data relating to the railcar and/or the railcar component. As one non-limiting example, the disclosed technology can be used to capture images of a railcar's cross-key. The disclosed technology includes a system comprising two or more rail-side inspection assemblies. For example, a first rail-side inspection assembly can be positioned on a first side of a train track (e.g., outside the rails), and a second rail-side inspection assembly can be positioned on a second side of the train track (e.g., outside the rails and/or opposite the first-rail-side inspection assembly). Each of the rail-side inspection assemblies can include various cameras, sensors, and/or lights to gather data (e.g., images) relating to one or more specific assemblies, sub-assemblies, and/or components of a passing railcar, such as a cross-key component of a passing railcar, as a non-limiting example. The cross-key component can be located on the side of the train coupler. The rail-side inspection assembly can be angled upwardly towards the lower portion of the railcar, such that the rail-side inspection assembly is positioned and oriented to capture images and/or other data from a low vantage of relative to the cross-key component of the train coupler (or any other intended assembly, sub-assembly, and/or component).

[0007] The rail-side inspection assembly can include one or more cameras, such as one or more area-scan cameras and/or one or more line-scan cameras. The cameras can include machine vision cameras with high sensitivity. For example, the cameras can include a highly sensitive sensor, which can be configured to capture, gather, or otherwise obtain images at high speeds and resolution. The rail-side inspection assembly can include one or more lights. The lights and/or the cameras can be arranged in an array (or multiple arrays). For example, the rail-side inspection assembly can include a camera positioned between two adjacent lights. The lights can be oriented so as to illuminate a specific three-dimensional location corresponding to a target region of a passing railcar, with the target assembly, sub-assembly, and/or component (which is referenced herein as the "target component" for simplicity) being located within the target region as a given railcar passes the rail-side assembly). The lights can be configured to illuminate the target region, and the camera can be configured to capture images of the target component with less than 2 mm of blur, as a non-limiting example. Alternatively or in addition, the camera can be configured to capture images of the target component with less than 5 mm of blur, less than 4 mm of blur, less than 3 mm or blur, less than 1 mm of blur, less than 0.5 mm of blur, in a range of between approximately 1 mm of blur and approximately 3 mm of blur, or in a range between approximately 2 mm of blur and approximately 5 mm of blur, as non-limiting examples. The rail-side inspection assembly can be configured to capture images and/or other data from railcars moving at speeds of up to 30 miles per hour (mph), up to 50 mph, up to 70 mph, or even up to 85 mph, as non-limiting examples, with the captured images being of sufficient clarity and focus to accurately and reliably detect defects or potential defects of a given target component.

[0008] The rail-side inspection assembly can include a protective enclosure, which can substantially or wholly envelop the camera(s) of the rail-side inspection assembly. The protective enclosures can protect each particular camera from debris and/or the elements. Alternatively or in addition, the protective enclosure can include an air assembly, which can be configured to generate an air curtain along the lens of the cameras (e.g., in front of the lens and/or a clear, protective material of the enclosure, perpendicular to the focal direction of the lens) to remove debris and other materials that may be present and/or to prevent dust, debris, or other materials from inhibiting the camera's view of the target component. The protective enclosure can fluidly connect to a

compressed air source to provide compressed air for the air curtain. Alternatively or in addition, the protective enclosure can be in communication with a cooling source (e.g., a cooling loop, a heat pump, and/or any other cooling system or device) to cool the camera and/or other components of the rail-side inspection assembly (e.g., to keep the temperature of certain components within a functional and/or desired temperature range). The protective enclosure can be manufactured from steel to protect the various components of the disclosed technology.

[0009] The rail-side inspection assembly can include a dampening system. The dampening system can be configured to reduce the mechanical vibrations, and/or the effect thereof, induced by the passing railcar passes on the rail-side inspection assemblies. The dampening system can connect to the protective enclosure, as a non-limiting example. Alternatively or in addition, the rail-side inspection assembly can be mounted to the ties of a train track, such as by a mounting plate or a mounting enclosure, and the dampening system can be positioned between the mounting plate (or mounting enclosure) and the camera(s).

[0010] The cameras can each be angled such that the cameras and/or sensors are directed towards the target region of a given passing railcar. For example, the one or more cameras, one or more sensors, and/or one or more lights can be angled toward a longitudinal and/or central axis of the train tracks and in an upward direction such that the cameras, sensors, and/or lights are directed towards the target component of passing railcars.

[0011] The rail-side inspection assembly can be installed on (e.g., attached to) existing train tracks. For example, the rail-side inspection assembly can be attached to one or more rail ties. The rail-side inspection assembly can be installed outside the rails of train tracks (e.g., at or near an end of one or more rail ties). Alternatively or in addition, the rail-side inspection assembly can be positioned between the rails of train tracks. While the rail-side inspection assembly is described herein as being attached to (e.g., attachable to) rail ties, the disclosed technology is not so limited, and the rail-side inspection assembly can be installed in any other useful location (e.g., the ground, the ballast, another structure located proximate train tracks).

[0012] According to a first aspect, an inspection assembly, comprising: A) a first camera angled at least partially in a vertical direction and at least partially in a horizontal direction to thereby be configured to capture images of a target region in a three-dimensional space from a first viewpoint; B) a second camera positioned apart from the first camera, angled at least partially in the vertical direction and at least partially in the horizontal direction, and directed to the target region from a second viewpoint that is different from the first viewpoint; C) one or more lights; and D) a housing comprising a base and a shroud, the housing configured to attach to one or more rail ties and to at least partially envelop the first camera and the second camera.

[0013] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the shroud covers a rear of the first camera and a rear of the second camera and at least partially covers a top of the first camera and a top of the second camera.

[0014] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the shroud is configured to be attached to a first rail tie and a second rail tie and the base is configured to be attached to a third rail tie located between the first and second rail ties.

[0015] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein: A) the base comprises a first base portion and a second base portion; B) the first base portion comprises a first bottom and one or more first sidewalls; C) the second base portion comprises a second bottom and one or more second sidewalls; D) a second sidewall of the one or more second sidewalls nearest the one or more first sidewalls is spaced apart from the one or more first sidewalls such that a gap is formed between the first base portion and the second base portion.

[0016] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the gap is sized to at least partially receive a rail tie.

[0017] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the first camera is positioned in the first base portion and the second camera is positioned

in the second base portion.

[0018] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the first bottom and the second bottom are suspended above the ground when the inspection assembly is attached to rail ties.

[0019] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein: A) the first camera and two or more first lights of the one or more lights form a first imaging array; and B) the second camera and two or more second lights of the one or more lights form a second imaging array.

[0020] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein at least one of the first imaging array or the second imaging array is a linear array.

[0021] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the housing is configured to attach to one or more rail ties at a position that is outside the rails of a railway.

[0022] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the first camera and the second camera are configured to capture images from respective viewpoints that are respective heights that are 3 inches or less, with respect to a top surface of a rail tie to which the inspection assembly is mounted.

[0023] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the first camera, the second camera, and the one or more lights are in communication with one or more computing devices configured to determine a capture timing for capturing images of a target component of a moving object as the target component passes through the target region.

[0024] According to a further aspect, the inspection assembly of the first aspect or any other aspect, further comprising a first dampening device disposed between the first camera and the housing and a second dampening device disposed between the second camera and the housing.

[0025] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein: A) the first dampening device and the second dampening device each comprises: B) a first mounting plate configured to attach to the housing; C) a second mounting plate configured to attach to the first camera or the second camera, respectively; and D) one or more dampening structures located between the first mounting plate and the second mounting plate.

[0026] According to a further aspect, the inspection assembly of the first aspect or any other aspect, wherein the one or more dampening structures comprises one or more springs.

[0027] According to a further aspect, an inspection system, comprising: A) a plurality of inspection assemblies, each of the plurality of inspection assemblies comprising: 1) a first camera angled at least partially in a vertical direction and at least partially in a horizontal direction to thereby be configured to capture images of a target region in a three-dimensional space from a first viewpoint; 2) a second camera positioned apart from the first camera, angled at least partially in the vertical direction and at least partially in the horizontal direction, and directed to the target region from a second viewpoint that is different from the first viewpoint; 3) one or more lights; and 4) a housing comprising a base and a shroud, the housing configured to attach to one or more rail ties and to at least partially envelop the first camera and the second camera, wherein: i) each of the plurality of inspection assemblies is mounted to one or more rail ties at a corresponding location that is outside the rails of a railway; ii) a first inspection assembly of the plurality of inspection assemblies is located on a first side of the rails at a first longitudinal location along the railway; and iii) a second inspection assembly of the plurality of inspection assemblies is located on a second side of the rails at a second longitudinal location along the railway, the second side being opposite the first side.

[0028] According to a further aspect, the inspection system of the second aspect or any other aspect, wherein the second longitudinal location is the same as the first longitudinal location.

[0029] According to a further aspect, the inspection system of the second aspect or any other aspect, wherein the second longitudinal location is different from the first longitudinal location.

[0030] According to a further aspect, the inspection system of the second aspect or any other

aspect, further comprising: A) one or more wheel detection sensors configured to detect a presence or a non-presence of a railcar wheel at a location along the railway that is upstream from the plurality of inspection assemblies; and B) one or more computing devices in electrical communication with: 1) the one or more wheel detection sensors; and 2) inspection cameras comprising the first and second cameras of each of the plurality of inspection assemblies, wherein the one or more computing devices is configured to determine a capture timing for each of the inspection cameras based at least in part on a train speed estimation determined according to wheel detection events detected by the wheel detection sensors.

[0031] According to a further aspect, the inspection system of the second aspect or any other aspect, wherein the one or more computing devices is further configured to determine the capture timing for each of the inspection cameras based on at least (i) a physical distance between the wheel detection sensors and each corresponding one of the inspection cameras and (ii) one or more electrical signal transmission or processing latencies.

[0032] These and other aspects, features, and benefits of the claimed innovation(s) will become apparent from the following detailed written description of the preferred examples and aspects taken in conjunction with the following drawings, although variations and modifications thereto may be effected without departing from the spirit and scope of the novel concepts of the disclosure.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0033] The accompanying drawings illustrate one or more examples and/or aspects of the disclosure and, together with the written description, serve to explain the principles of the disclosure. Wherever possible, the same reference numbers are used throughout the drawings to refer to the same or like elements of the disclosed systems and processes, and wherein:

[0034] FIG. 1A illustrates a perspective view of an example installed rail-side inspection assembly, in accordance with the disclosed technology;

[0035] FIG. 1B illustrates a perspective view of an example installed rail-side inspection assembly, in accordance with the disclosed technology;

[0036] FIG. 1C illustrates a front-side view of an example installed rail-side inspection assembly, in accordance with the disclosed technology;

[0037] FIG. 1D illustrates a perspective view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0038] FIG. 1E illustrates a top view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0039] FIG. 1F illustrates a bottom view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0040] FIG. 1G illustrates a right-side view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0041] FIG. 1H illustrates a left-side view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0042] FIG. 1I illustrates a front-side view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0043] FIG. 1J illustrates a back-side view of an example rail-side inspection assembly, in accordance with the disclosed technology;

[0044] FIG. 1K illustrates a partial exploded perspective view of an example camera enclosure, in accordance with the disclosed technology;

[0045] FIG. 1L illustrates a perspective view of an example camera and light array, in accordance with the disclosed technology;

[0046] FIG. 1M illustrates a partial exploded perspective view of an example camera enclosure, in accordance with the disclosed technology; and

[0047] FIG. 2 illustrates a perspective view of an example portal focus cart, in accordance with the disclosed technology.

#### DETAILED DESCRIPTION

[0048] The disclosed technology relates generally to systems and methods for inspecting moving vehicles and, more specifically, to various components and systems for capturing images and/or gathering data of or relating to regions of moving rail-bound vehicles (e.g., railcars). Some examples of the disclosed technology will be described more fully with reference to the accompanying drawings and/or with respect to inspecting passing railcars. However, the disclosed technology can be embodied in many different forms and should not be construed as limited to the implementations set forth herein. For example, the disclosed technology can be configured to inspect moving objects (e.g., vehicles) other than railcars or other rail-bound vehicles. For example, the disclosed technology can be installed on a road to inspect and/or monitor cars or other vehicles (e.g., road vehicles). Alternatively or in addition, the disclosed technology can be installed at, near, or on a weight station to inspect and/or monitor trucks, trailers, or other shipping vehicles. Alternatively or in addition, the disclosed technology can be installed in or near a boat canal, a dock, and/or a body of water to inspect and/or monitor boats. Alternatively or in addition, the disclosed technology can be installed on or near the tarmac of an airport, an aircraft hangar, and/or an airplane gate to analyze planes, flying drones, or other aircraft.

[0049] The components described hereinafter as making up various elements of the disclosed technology are intended to be illustrative and not restrictive. Indeed, it is to be understood that other examples are contemplated. Many suitable components that would perform the same or similar functions as components described herein are intended to be embraced within the scope of the disclosed electronic devices and methods. Such other components not described herein may include, but are not limited to, for example, components developed after development of the disclosed technology.

[0050] Throughout this disclosure, various aspects of the disclosed technology can be presented in a range of formats (e.g., a range of values). It should be understood that such descriptions are merely for convenience and brevity and should not be construed as an inflexible limitation on the scope of the disclosed technology. Accordingly, the description of a range should be considered to have specifically disclosed all the possible subranges as well as individual rational numerical values within that range. For example, a range described as being “from 1 to 6” or “from approximately 1 to approximately 6” includes the values **1**, **6**, and all values therebetween. Likewise, a range described as being “between 1 and 6” or “between approximately 1 and approximately 6” includes the values **1**, **6**, and all values therebetween. The same premise applies to any other language describing a range of values. That is to say, the ranges disclosed herein are inclusive of the respective endpoints, unless otherwise indicated.

[0051] Herein, the use of terms such as “having,” “has,” “including,” or “includes” are open-ended and are intended to have the same meaning as terms such as “comprising” or “comprises” and not preclude the presence of other structure, material, or acts. Similarly, though the use of terms such as “can” or “may” are intended to be open-ended and to reflect that structure, material, or acts are not necessary, the failure to use such terms is not intended to reflect that structure, material, or acts are essential. To the extent that structure, material, or acts are presently considered to be essential, they are identified as such.

[0052] In the following description, numerous specific details are set forth. But it is to be understood that embodiments of the disclosed technology may be practiced without these specific details. In other instances, well-known methods, structures, and techniques have not been shown in detail in order not to obscure an understanding of this description. References to “one embodiment,” “an embodiment,” “example embodiment,” “some embodiments,” “certain

embodiments,” “various embodiments,” etc., indicate that the embodiment(s) of the disclosed technology so described may include a particular feature, structure, or characteristic, but not every embodiment necessarily includes the particular feature, structure, or characteristic. Further, repeated use of the phrase “in one embodiment” does not necessarily refer to the same embodiment, although it may.

[0053] Throughout the specification and the claims, the following terms take at least the meanings explicitly associated herein, unless the context clearly dictates otherwise. The term “or” is intended to mean an inclusive “or.” Further, the terms “a,” “an,” and “the” are intended to mean one or more unless specified otherwise or clear from the context to be directed to a singular form.

[0054] Unless otherwise specified, the use of the ordinal adjectives “first,” “second,” “third,” etc., to describe a common object, merely indicates that different instances of like objects are being referred to and are not intended to imply that the objects so described should be in a given sequence, either temporally, spatially, in ranking, or in any other manner.

[0055] Whether or not a term is capitalized is not considered definitive or limiting of the meaning of a term. As used in this document, a capitalized term shall have the same meaning as an uncapitalized term, unless the context of the usage specifically indicates that a more restrictive meaning for the capitalized term is intended. However, the capitalization or lack thereof within the remainder of this document is not intended to be necessarily limiting unless the context clearly indicates that such limitation is intended.

[0056] For the purpose of promoting an understanding of the principles of the present disclosure, reference will now be made to the illustrative examples provided in the drawings, and specific language will be used to describe the same. It will, nevertheless, be understood that no limitation of the scope of the disclosure is thereby intended; any alterations and further modifications of the described or illustrated embodiments, and any further applications of the principles of the disclosure as illustrated therein are contemplated as would normally occur to one skilled in the art to which the disclosure relates. All limitations of scope should be determined in accordance with and as expressed in the claims.

#### Example Embodiments

[0057] Referring now to the figures, for the purposes of example and explanation of the fundamental processes and components of the disclosed apparatuses, systems, and methods, reference is made to FIG. 1, which illustrates an example inspection system **100**. As will be understood and appreciated, the inspection system **100** shown in FIG. 1 represents merely one approach or example of the disclosed technology, and other aspects are used according to various examples of the disclosed technology.

[0058] The disclosed technology includes one or more rail-side inspection assemblies **101**, which can capture images of one or more components of a moving object, such as a passing railcar. For example, the rail-side inspection assembly **101** can be configured to capture images of a target assembly, target sub-assembly, and/or target component (referenced herein as “target component” for clarity and/or brevity). The rail-side inspection assembly **101** can be configured to capture images of the target component when the target component passes the rail-side inspection assembly **101**, and as such, the rail-side inspection assembly **101** can be configured to capture images from a target region, which can refer to a specific three-dimensional point, space, area, and/or region, such that the rail-side inspection assembly **101** can capture images of the target component as it passes the rail-side inspection assembly **101**. For example, the rail-side inspection assembly **101** can be configured to capture images of a railcar's cross-key component, which can be located on the railcar's coupler. The rail-side inspection assembly **101** can include one or more cameras, example sensors, and/or example lights aimed at the target region, which can correspond to a lower region or portion of a given passing railcar. The various cameras, sensors, and/or lights of the rail-side inspection assembly **101** can be used to capture images and/or gather data on the target component (e.g., cross-key component of the railcar coupler).



[0059] For example, the rail-side inspection assembly **101** can capture images of the cross-key component of the railcar and/or other target components of a railcar. Continuing this example, a computing system in communication with the rail-side inspection assembly **101** can be configured to process the images generated by the rail-side inspection assembly **101** to detect any defects associated with the cross-key component or the target component.

[0060] The inspection system **100** can include two or more rail-side inspection assemblies **101**, which can be positioned to capture images and/or other data on both sides of a passing railcar, as a non-limiting example. For, example, a first rail-side inspection assembly can be positioned on a first side of a train track **104**, and a second rail-side inspection assembly can be positioned on a second side of the train track **104**. Alternatively or in addition, two or more assemblies can be positioned on the same side of the tracks. One or more of the rail-side inspection assemblies **101** can be positioned adjacent to one or more rails **105**, **106** of the train track **104** (e.g., at or near the end of the rail ties). For example, the first rail-side inspection assembly can be located outside the rails on a first side of the train track **104**, and the second rail-side inspection assembly can be located outside the rails on a second side of the train track **104**. The term “outside” can refer to the region that is not between both the first rail **105** and the second rail **106**. Alternatively or in addition, one or more rail-side inspection assembly **101** can be located between the rails **105**, **106**. As discussed in more detail herein, the rail-side inspection assembly **101** can be attached to (and/or attachable to) one or more rail ties of the train track **104**. Alternatively or in addition, the rail-side inspection assembly **101** can be attached to (and/or attachable to) other locations, such as the ground, the ballast, another structure located proximate train tracks **104**, as non-limiting examples. The rail-side inspection assembly **101** can be attached to (or attachable to) a top side of one or more rail ties. Alternatively or in addition, the rail-side inspection assembly **101** can be attached to (or attachable to) the side of one or more rail ties (e.g., such that some or all of the rail-side inspection assembly **101** is located between adjacent rail ties).

[0061] The rail-side inspection assembly **101** can include one or more cameras and/or one or more lights. As a non-limiting example, the rail-side inspection assembly **101** can include one or more arrays, and the arrays can each include one or more cameras and one or more lights. For example, a given array can be a linear array and can include a single camera bookended by a pair of lights, as a non-limiting example.

[0062] The cameras of the rail-side inspection assembly **101** can be or include line-scan cameras, area-scan cameras, and/or any other cameras capable of capturing images of target components of passing railcars. For example, the cameras and lights of the rail-side inspection assembly **101** can include particular machine vision cameras with high sensitivity. Alternatively or in addition, the cameras and lights of the rail-side inspection assembly **101** can capture clear images of railcars moving at high speeds. The cameras and lights of the rail-side inspection assembly **101** can include one or more cameras and one or more lights. For example, the rail-side inspection assembly **101** can include a camera positioned in between two lights. The lights can illuminate the location of the cross-key component such that the camera can gather images of the cross-key component with less than 2 mm of blur. The rail-side inspection assembly **101** can gather images and other data from railcars moving at speeds of up to 70 mph.

[0063] Referring now to FIG. **1B**, illustrated is a perspective view of an example rail-side inspection assembly **101**, in accordance with the disclosed technology. As disclosed herein, the rail-side inspection assembly **101** can be attached to rail ties **111**. The rail-side inspection assembly **101** can be fixed to the rail ties **111** via one or more fasteners (e.g., screws, bolts, lag bolts, ties), one or more welding joints or other welds, and/or any other fixing mechanism capable of securing the rail-side inspection assembly **101** to the train tracks **104**. For example and as illustrated, the rail-side inspection assembly **101** can be fixed to three adjacent rail ties **111**. Continuing this example, the rail-side inspection assembly **101** can straddle a second rail tie **113**, where a first end **116** of the rail-side inspection assembly **101** can attach to a first rail tie **112** and a second end **117** of the rail-

side inspection assembly **101** can attach to a third rail tie **114**.

[0064] The rail-side inspection assembly **101** can be configured to mount directly onto existing rail ties **111**. For example, the rail-side inspection assembly **101** can include one or more mounting holes to account for variations in the train track **104** geometry and the spacings between the rail ties **111**.

[0065] Referring now to FIG. **1C**, illustrated is an example front-side view of the installed rail-side inspection assembly **101**, in accordance with the disclosed technology. As illustrated, the rail-side inspection assembly **101** can include a first camera and light array **121** and a second camera and light array **122**. However, the disclosed technology is not so limited and can include one, three, four, or more camera and light arrays. Alternatively or in addition, the rail-side inspection assembly **101** can include one or more cameras and/or one or more lights arranged in other (e.g., non-linear, non-array) configurations. For example, the rail-side inspection assembly **101** can include a camera positioned between a group of three, four, or more lights (e.g., arranged around or about the camera, such as in an equidistantly disposed arrangement).

[0066] Turning back to the rail-side inspection assembly illustrated in FIG. **1C**, the rail-side inspection assembly **101** can include a base. The base can include a first base portion **123** configured to support the first camera and light array **121** and a second base portion **124** configured to support the second camera and light array **122**. The first base portion **123** can extend through a first gap **126** between the first rail tie **112** and the second rail tie **113**. The second base portion **123** can extend through a second gap **127** between the second rail tie **113** and the third rail tie **114**. The first camera and light array **121** and the second camera and light array **122** can straddle the second rail tie **113**. The rail-side inspection assembly **101** can attach to the first rail tie **112**, the second rail tie **113**, and/or the third rail tie **114** via one or more screws, bolts, and/or any other fixing mechanism.

[0067] Referring now to FIG. **1D**, illustrated is another perspective view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The rail-side inspection assembly **101** can include one or more air curtains **132**. A given air curtain **132** can be installed on, near, and/or adjacent to one or more cameras. For example, a first air curtain **132** can be installed at or on the camera of the first camera and light array **121**, and a second air curtain **132** can be installed at or on the camera of the second camera and light array **122**. The air curtain **132** can be in fluid communication with a compressed air source to provide compressed air at the camera(s) that flows over the lenses of the camera **133**. The air curtains **132** can clean the lenses of the cameras **133** during use from debris.

[0068] The rail side inspection assembly **101** can include a first camera and light array **121** and a second camera and light array **122**. The first camera and light array **121** and the second camera and light array **122** can each be angled to a corresponding target region (e.g., a point or region in a three-dimensional space). Alternatively or in addition, the first camera and light array **121** and the second camera and light array **122** can be directed to a single, common target region, such that images of the target region (e.g., of a target component when it is located in the target region) can be captured. For example, the first camera and light array **121** can be angled at least partially in a vertical direction and at least partially in a horizontal direction to point at the expected location of the cross-key component or other component of a railcar. Continuing this example, the second camera and light array **122** can be partially angled in an at least partially vertical direction and an at least partially horizontal direction to point at the expected location of the cross-key component or other component of a railcar. The first camera and light array **121** and the second camera and light array **122** can be differently and/or oppositely angled such that the camera and light arrays point to the same location but from different angles and/or viewpoints. Accordingly, the rail-side inspection assembly can be configured to contemporaneously and/or simultaneously capture images of a single target region (e.g., point and/or region) and/or a single target component from different angles, which can be useful in detecting defects associated with the target component, as a non-

limiting example.

[0069] The camera and light arrays **121**, **122** can include the cameras **133** and the lights **151**. The cameras **133** can include specialized machine vision cameras with high sensitivity to generate images of the cross-key component of the passing railcar. For example, the cameras **133** can include high-speed, high resolution, and a highly sensitive sensor. The lights **151** can include any particular light that is capable of illuminating the three-dimensional space in which the cross-key component is present. For example, the lights **151** can include 150W lights capable of illuminating the area in which the cross-key component is present.

[0070] The camera and light arrays **121**, **122** can include similar configurations. For example, the camera and light arrays **121**, **122** can each include one camera **133** and two lights **151**. The camera **133** can be positioned between the two lights **151**. The two lights can equally illuminate an area such that the camera **133** can generate a low blur and high-quality image of the cross-key component.

[0071] The rail-side inspection assembly **101** can include a shroud **131**, the first base portion **123**, and the second base portion **124**. The first base portion **123** and the second base portion **123** can support the first camera and light array **121** and the second camera and light array **122**, respectively. The first base portion **123** and the second base portion **123** can protect the first camera and light array **121** and the second camera light array **122** from debris as a railcar passes the rail-side inspection assembly **101**. Alternatively or in addition, the shroud **131** can protect the first camera and light array **121** and the second camera and light array **122** from debris as a railcar passes the rail-side inspection assembly **101**.

[0072] The first base portion **123** and the second base portion **124** can rest on a ballast (e.g., the ground) between the rail ties **111**. For example, the first base portion **123** and the second base portion **124** can have a height less than the rail ties **111** such that the first base portion **123** and the second base portion **124** are suspended off the ballast. The first camera and light array **121** and the second camera and light array **122** can be configured to partially extend into the ballast and capture images from a viewpoint that is approximately at least 1 inch above the rail ties **111**, 1 to 6 inches above the rail ties **111**, or less than 6 inches above the rail ties **111**, as non-limiting examples.

[0073] Referring now to FIG. **1E**, illustrated is an example top view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The first camera and light array **121** and the second camera and light array **122** can point in a first direction **135** and a second direction **136**, respectively. The first direction **135** and the second direction **136** can indicate the angle at which the first camera and light array **121** and the second camera and light array **122** are positioned relative to a first axis **139**. The angle between the first direction **135** and the second direction **136** can be approximately 40 degrees, approximately 45 degrees, approximately 50 degrees, in a range between approximately 40 degrees and approximately 50 degrees, in a range between approximately 40 degrees and approximately 60 degrees, in a range between approximately 30 degrees and approximately 50 degrees, and/or in a range between approximately 30 degrees and approximately 60 degrees, as non-limiting examples. The angles between the first direction **135** and the first axis **139** and between the second direction **136** and the first axis **139**, respectively, can be the same. Alternatively, the angles between the first direction **135** and the first axis **139** and between the second direction **136** can be different. For example, the angle between the first direction **135** and the first axis **139** can be in a range between approximately 0 degrees and approximately 60 degrees, in a range between approximately 15 degrees and approximately 45 degrees, or in a range between approximately 30 degrees and 50 degrees, as non-limiting examples, and the angle between the second direction **136** and the first axis **139** can be (i) different the angle between the first direction **135** and the first axis **139** and (ii) in a range between approximately 0 degrees and approximately 60 degrees, in a range between approximately 15 degrees and approximately 45 degrees, or in a range between approximately 30 degrees and 50 degrees, as non-limiting examples.

[0074] 4919-608-3399.1

[0075] The shroud **131** can partially expose the first camera and light array **121** and the second camera and light array **122**. The shroud **131** can protect the first camera and light array **121** and the second camera and light array **122** while allowing the first camera and light array **121** and the second camera and light array **122** to gather data on the cross-key component of the passing railcar. The shroud **131** can be constructed out of hardened steel, stainless steel, aluminum, and/or any other material capable of protecting the components of the rail-side inspection assembly **101**.

[0076] Referring now to FIG. **1F**, illustrated is an example bottom view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The rail-side inspection assembly **101** can include the first base portion **123** and the second base portion **123**. The first base portion **123** and the second base portion **123** can protect the bottom portion of the first camera and light assembly **121** and the second camera and light assembly **122**. For example, as the railcar passes the rail-side inspection assembly **101**, the first base portion **123** and the second base portion **123** can protect the first camera and light array **121** and the second camera and light array **122**. The first base portion **123** and the second base portion **123** can be constructed out of hardened steel, stainless steel, aluminum, and/or any other material capable of protecting the components of the rail-side inspection assembly **101**.

[0077] Referring now to FIG. **1G**, illustrated is an example left-side view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The rail-side inspection assembly **101** can include one or more screws **142** at the first end **116** of the rail-side inspection assembly **101**. The one or more screws **142** can fix the rail-side inspection assembly **101** to the one or more rail ties **111**.

[0078] The rail-side inspection assembly **101** can include a third direction **137**. The third direction **137** can indicate the direction in which the first camera and light array **121** and the second camera and light array **122** are pointed. The third direction **137** can be angled relative to the second axis **141**. The angle between the third direction **137** and the second axis **141** can be in a range between approximately 15 degrees and approximately 60 degrees, between approximately 20 degrees and approximately 30 degrees, between approximately 30 degrees and approximately 40 degrees, and/or between approximately 50 degrees and approximately 60 degrees, as non-limiting examples.

[0079] Referring now to FIG. **1H**, illustrated is a right-side view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The rail-side inspection assembly **101** can include one or more screws **142** at the second end **117** of the rail-side inspection assembly **101**. The one or more screws **142** can fix the rail-side inspection assembly **101** to the one or more rail ties **111**. For example, the one or more screws **142** can fix the rail-side inspection assembly **101** to the third rail tie **114**.

[0080] Referring now to FIG. **1I**, illustrated is an example front side view of the rail-side inspection assembly **101**, in accordance with the disclosed technology. The camera and light arrays **121**, **122** of the rail-side inspection assembly **101** can include the one or more cameras **133** and one or more lights **121**. The one or more cameras **133** can each include the air curtain **132**. The air curtain **132** can connect to a compressed air source. The compressed air source can feed the air curtain **132** with air. The air curtain **132** can employ the air to generate an air curtain over a lens **152** of the camera **133**. The air curtain can blow air over the lens **152** such that any debris that accumulates on the lens **152** is blown off and removed from the lens **152**. The air curtain **132** can generate air used to cool the components of the rail-side inspection assembly **101**.

[0081] The rail-side inspection assembly **101** can include one or more screws **142**. The one or more screws **142** can fix the rail-side inspection assembly **101** to the one or more rail ties **111**. For example, the screws **142** can attach to the second rail tie **113**. Though illustrated as screws, any particular similar fixing mechanism can be used to secure the rail-side inspection assembly **101** to the rail ties **111** (e.g., bolts, welding points, ties, etc.).

[0082] Referring now to FIG. **1J**, illustrated is a backside view of the rail-side inspection assembly

**101**, in accordance with the disclosed technology. The shroud **131** of the rail-side inspection assembly **101** can extend around the camera and light arrays **121**, **122**. The shroud **131** can protect the rear of the camera and light arrays **121**, **122** such that the camera and light arrays **121**, **122** are not damaged by debris during use. The rail-side inspection assembly **101** can include one or more conduit adapters such that various wires and/or compressed air cables can run through the rail-side inspection assembly **101**. The rail-side inspection assembly **101** can include one or more conduit adapter **153**. The conduit adapter **153** can allow one or more wires and/or one or more hoses to pass into the first base portion **123** and the second base portion **124** while maintaining a watertight configuration.

[0083] Referring now to FIG. **1K**, illustrated is an example partially exploded view of the first camera and light array **121** and the first base portion **123**, in accordance with the disclosed technology. However, the various components and/or configurations discussed herein can apply to other aspects of the disclosed technology, such as the second camera and light array **122** and the first base portion **123**, as a non-limiting example. The first camera and light array **121** can be attached to the first base portion **123**. The lights **151** can be fixed to the first base portion **123**. For example, the lights **151** can include one or more screws **162** that fix or attach the lights **151** to the first base portion **123**. The camera **133** can be attached to the first base portion **123**. Alternatively or in addition, and as discussed in further detail herein, first camera and light array **121** and or the camera **133** alone can be fixed or attached to the first base portion **123** via a dampening system **161**. The dampening system **161** can reduce the mechanical vibrations exhibited by the camera **133** as a train passes the rail-side inspection assembly **101**.

[0084] Referring now to FIG. **1L**, illustrated is an example perspective view of the first camera and light assembly **121**, in accordance with the disclosed technology. The various components discussed herein can apply to both the first camera and light assembly **121** and the second camera and light assembly **122**, though only the first camera and light assembly **121** is illustrated for the sake of brevity. The first camera and light assembly **121** can include the dampening system **161**. The dampening system **161** can reduce the mechanical vibrations exerted on the camera **133** generated from a particular passing railcar. The dampening system **161** can include a lower plate **171**, one or more springs **172** (or other dampening devices), an upper plate **173**, and one or more ties **174** (e.g., mounting rings). The lower plate **171** can attach to the first base portion **123** (e.g., as shown in further details in FIG. **1M**). The one or more springs **172** can extend through a first attachment point **175** of the lower plate **171**. The one or more springs **172** can extend through a second attachment point **176** of the upper plate **173**, operatively connecting the upper plate **173** to the lower plate **171**. The upper plate **173** can attach to the camera **133** through one or more ties **174**. By connecting through the one or more ties **174**, the camera **133** can be fixed to the first base portion **123** through the upper plate **173**, the one or more springs **172**, and the lower plate **171**. The one or more springs **172** can dampen for the camera **133** any mechanical vibrations generated by the passing railcar.

[0085] Referring now to FIG. **1M**, illustrated is an example partially exploded view of the first base portion **123**, in accordance with the disclosed technology. The various components discussed herein can apply to both the first base portion **123** and the second base portion **123**, though only the first base portion **123** is illustrated for the sake of brevity. The camera **133** can be attached to the first base portion **123** through the dampening system **161**. The dampening system **161** can include the lower plate **171**. The lower plate **171** can attach to the first base portion **123** through the one or more screws **181**. The lower plate **171** can fix the camera **133** to the first base portion **123**.

[0086] Referring now to FIG. **2**, illustrated is a perspective view of a portal focus cart **200**, in accordance with the disclosed technology. The cameras **133** of the rail-side inspection assembly **101** can focus on the components or regions of interest of the passing railcar. For example, during installation of the rail-side inspection assembly **101** (and/or periodically following the initial installation), the rail-side inspection assembly **101** can use the portal focus cart **200** to calibrate one

or more sensors and/or cameras **133** of the rail-side inspection assembly **101**. Such an apparatus can have various targets **201** placed at various locations within the portal focus cart **200** such that focusing cameras on those regions can produce the desired results when the passing railcar **103** travels past the rail-side inspection assembly **101**. Such targets **201** can have fiducial markers such that their location and orientation may be automatically detected by image processing algorithms of the computing system applied to the image feeds from the cameras **133**. The portal focus cart **200** can have wheels **202** and one or more motor(s) such that it can be placed on the train tracks **104** and moved past the rail-side inspection assembly **101**. The portal focus cart can pass the rail-side inspection assembly **101** at some speed so as to mimic a passing railcar. Various components of the portal focus cart **200** can collapse or telescope such that the portal focus cart **200** can be stored and transported more conveniently. The portal focus cart **200** can also be configured so as to set the depth of field as desired, for example through the use of multiple focusing targets **201**.

[0087] The process of celebrating the one or more rail-side inspection assemblies **101** can be managed through a computing environment. For example, the inspection system **100** can include a wheel detection system that can detect the presence of a passing railcar (e.g., in this non limiting example, the passing railcar can include the portal focus cart **200**). The computing environment, based on the data gathered from the wheel detection system, can measure the speed of the passing railcar. Based on the known speed of the passing railcar and the capture speeds of each camera, the computing environment can trigger the lights **151** and the cameras **133** at specific intervals such that the images captured of the passing railcar are clear and include the particular region of interest. The computing environment can employ the wheel detection system and the portal focus cart **200** to calibrate the various cameras **133** and lights **151** of the rail side inspection assemblies **101** based on the speed of the portal focus cart **200** and the known capture speeds of the camera **133**.

[0088] The foregoing description of the present systems and processes has been presented only for the purposes of illustration and description and is not intended to be exhaustive or to limit the innovations to the precise forms disclosed. Many modifications and variations are possible in light of the above teaching.

[0089] The examples of the present systems and processes were chosen and described in order to explain the principles of the claimed innovations and their practical application so as to enable others skilled in the art to utilize the innovations and various examples with various modifications as are suited to the particular use contemplated. Alternative examples of the disclosed technology will become apparent to those skilled in the art to which the claimed innovations pertain without departing from their spirit and scope. Accordingly, the scope of the claimed innovations is defined by the appended claims rather than the foregoing description and the examples described therein.

## Claims

1. An inspection assembly, comprising: a first camera positioned to capture first images of a target region in a three-dimensional space from a first viewpoint; a second camera positioned to capture second images of the target region from a second viewpoint that is different from the first viewpoint; one or more lights; and a housing comprising a base and a shroud, the housing configured to at least partially envelop the first camera and the second camera and to attach to one or more rail ties of a railway track at a location outside a pair of rails of the railway track.
2. The inspection assembly of claim 1, wherein the shroud covers a rear of the first camera and a rear of the second camera and at least partially covers a top of the first camera and a top of the second camera.
3. The inspection assembly of claim 1, wherein: the first camera is angled at least partially in a vertical direction and at least partially in a horizontal direction; and the second camera is angled at least partially in the vertical direction and at least partially in the horizontal direction.
4. The inspection assembly of claim 1, wherein: the base comprises a first base portion and a

second base portion; the first base portion comprises a first bottom and one or more first sidewalls; the second base portion comprises a second bottom and one or more second sidewalls; and a second sidewall of the one or more second sidewalls nearest the one or more first sidewalls is spaced apart from the one or more first sidewalls such that a gap is formed between the first base portion and the second base portion.

5. The inspection assembly of claim 4, wherein the gap is sized to at least partially receive a rail tie.

6. The inspection assembly of claim 4, wherein the first camera is positioned in the first base portion and the second camera is positioned in the second base portion.

7. The inspection assembly of claim 4, wherein the first bottom and the second bottom are suspended above the ground when the inspection assembly is attached to rail ties.

8. The inspection assembly of claim 1, wherein: the first camera and two or more first lights of the one or more lights form a first imaging array; the second camera and two or more second lights of the one or more lights form a second imaging array; and at least one of the first imaging array or the second imaging array is a linear array.

9. The inspection assembly of claim 1, wherein the first camera and the second camera are configured to capture the first images and second images from respective viewpoints that are at respective heights of 3 inches or less, with respect to a top surface of a rail tie to which the inspection assembly is mounted.

10. The inspection assembly of claim 1, wherein the first camera, the second camera, and the one or more lights are in communication with one or more computing devices configured to determine a capture timing for capturing the first images and the second images of a target component of a moving object as the target component passes through the target region.

11. The inspection assembly of claim 1, further comprising one or more dampening devices disposed between one or more mount locations of the housing and at least one of the first camera or the second camera.

12. The inspection assembly of claim 11, wherein the one or more dampening devices comprises a first dampening device disposed between the first camera and the housing and a second dampening device disposed between the second camera and the housing.

13. The inspection assembly of claim 11, wherein at least one of the one or more dampening devices comprises: a first mounting plate configured to attach to the housing; a second mounting plate configured to attach to the first camera or the second camera; and one or more dampening structures located between the first mounting plate and the second mounting plate.

14. The inspection assembly of claim 13, wherein the one or more dampening structures comprises one or more springs.

15. An inspection system, comprising: an inspection assembly, comprising: a first camera positioned to capture images of a target region in a three-dimensional space from a first viewpoint; and a second camera positioned to capture images of the target region from a second viewpoint that is different from the first viewpoint; and a housing comprising a base and a shroud, the housing configured to at least partially envelop the first camera and the second camera and to attach to one or more rail ties of a railway track at a location outside a pair of rails of the railway track; and one or more computing devices in communication with the first camera and the second camera, the one or more computing devices being configured to determine a capture timing for capturing images of one or more target components of a moving object as the one or more target components passes through the target region.

16. An inspection system, comprising: a plurality of inspection assemblies, each of the plurality of inspection assemblies comprising: a first camera positioned to capture first images of a target region in a three-dimensional space from a first viewpoint; a second camera positioned to capture second images of the target region from a second viewpoint that is different from the first viewpoint; one or more lights; and a housing comprising a base and a shroud, the housing configured to at least partially envelop the first camera and the second camera, wherein: each of the

plurality of inspection assemblies is mounted to one or more rail ties of a railway track at a corresponding location that is outside a pair of rails of the railway track; a first inspection assembly of the plurality of inspection assemblies is located on a first side of the pair of rails at a first longitudinal location along a length of the railway track; and a second inspection assembly of the plurality of inspection assemblies is located on a second side of the pair of rails at a second longitudinal location along the length of the railway track, the second side being opposite the first side.

**17.** The inspection system of claim 16, wherein the second longitudinal location is the same as the first longitudinal location.

**18.** The inspection system of claim 16, wherein the second longitudinal location is different from the first longitudinal location.

**19.** The inspection system of claim 16, further comprising: one or more detection devices configured to detect a presence or a non-presence of a railcar; and one or more computing devices in communication with: the one or more detection devices; and inspection cameras comprising the first and second cameras of each of the plurality of inspection assemblies, wherein the one or more computing devices is configured to determine a capture timing for each of the inspection cameras based at least in part on a train speed estimation determined according to detection events detected by the one or more detection devices.

**20.** The inspection system of claim 19, wherein the one or more computing devices is further configured to determine the capture timing for each of the inspection cameras based on at least (i) a physical distance between the one or more detection devices and each corresponding one of the inspection cameras and (ii) one or more electrical signal transmission or processing latencies.

**21.** The inspection system of claim 16, wherein each of the plurality of inspection assemblies further comprise one or more dampening devices disposed between one or more mount locations of the housing and at least one of the first camera or the second camera.

---