

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287182

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Chapiewski; Guilherme et al.

Tracking Device Search Party Management

Abstract

A method includes receiving, by a tracking server, and from a first computing device of a plurality of computing devices, a request to locate a tracking device associated with the tracking server, establishing a search party for locating the tracking device, determining a goal for the search party and a first criteria for including members into the search party, adding one or more second computing devices of the plurality of computing devices to the search party based on the first criteria, and determining that the goal for the search party is not satisfied. The method includes modifying, by the tracking server, the first criteria to include additional computing devices of the plurality of computing devices to the search party, receiving an indication that the tracking device has been located by the search party, and providing, by the tracking server, a location of the tracking device to the first computing device.

Inventors: Chapiewski; Guilherme (Cupertino, CA), Kumar; Mayank (San Francisco, CA)

Applicant: Tile, Inc. (San Mateo, CA)

Family ID: 58690122

Appl. No.: 19/219569

Filed: May 27, 2025

Related U.S. Application Data

parent US continuation 18419176 20240122 parent-grant-document US 12342243 child US 19219569

parent US continuation 18156315 20230118 parent-grant-document US 11882499 child US 18419176

parent US continuation 17317433 20210511 parent-grant-document US 11564058 child US 18156315

parent US continuation 16899493 20200611 parent-grant-document US 11019455 child US 17317433

parent US continuation 16296228 20190308 parent-grant-document US 10820146 child US

16899493

parent US continuation 15852307 20171222 parent-grant-document US 10271168 child US 16296228

parent US continuation 14939897 20151112 parent-grant-document US 9894480 child US 15852307

Publication Classification

Int. Cl.: H04W4/02 (20180101); H04W8/00 (20090101)

U.S. Cl.:

CPC H04W4/023 (20130101); H04W8/005 (20130101)

Background/Summary

PRIORITY [0001] This application is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 18/419,176, filed 22 Jan. 2024, which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 18/156,315, filed 18 Jan. 2023, now U.S. Pat. No. 11,882,499, which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 17/317,433, filed 11 May 2021, now U.S. Pat. No. 11,564,058, which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 16/899,493, filed 11 Jun. 2020, now U.S. Pat. No. 11,019,455, which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 16/296,228, filed 8 Mar. 2019, now U.S. Pat. No. 10,820,146, which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 15/852,307, filed 22 Dec. 2017, now U.S. Pat. No. 10,271,168 which is a continuation under 35 U.S.C. § 120 of U.S. application Ser. No. 14/939,897, filed 12 Nov. 2015, now U.S. Pat. No. 9,894,480, each of which is incorporated herein by reference.

TECHNICAL FIELD

[0002] This disclosure relates generally to locating a tracking device, and more specifically, to leveraging a network of users to locate a lost tracking device.

BACKGROUND

[0003] Electronic tracking devices have created numerous ways for people to track the locations of people and/or objects. For example, a user can use GPS technology to track a device remotely or determine a location of the user. In another example, a user can attach a tracking device to an important object, such as keys or a wallet, and use the features of the tracking device to more quickly locate the object, (e.g., if it becomes lost).

[0004] However, traditional tracking devices and corresponding systems suffer from one or more disadvantages. For instance, if a tracking device is lost, the limited wireless range of the tracking device prevents an owner of the tracking device from locating the tracking device from outside the range of the tracking device. Extending the wireless range of the tracking device requires additional power often unavailable in a low-power tracking device system. Accordingly, there is a need to leverage a network of users to enable an owner of a lost tracking device to more efficiently and effectively locate the tracking device.

SUMMARY OF PARTICULAR EMBODIMENTS

[0005] A tracking system can coordinate multiple search party members in order to locate a lost tracking device. Upon losing a tracked item, the owner of the lost tracking device can request that the tracking system start a search party to locate the lost item. The tracking server can utilize information provided in this request to establish a set of search party criteria and coordinate a

search for the lost item. In some implementations, search party criteria include characteristics of desired search party members, such as a current proximity to the last known location of the lost item. Using these criteria, the tracking system can then select and invite suitable candidates out of the community of users of the tracking system to participate in searching for the lost tracking device.

[0006] Candidates who accept the invitation to the search party are added to the search party and can be provided with the last known location of the lost tracking device. Based on this information, the search party members can begin looking for the lost tracking device. When one of the candidate search party members finds the lost tracking device or detects its signal, its location can then be provided back to the tracking system, which can in turn relay this information back to the owner of the lost tracking device. This allows the tracking system to leverage a community of users in locating a lost tracking device.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1. illustrates an exemplary implementation for locating a tracking device according to principles described herein.

[0008] FIG. 2 illustrates an exemplary tracking system of the implementation of FIG. 1.

[0009] FIG. 3 illustrates an exemplary user mobile device of the implementation of FIG. 1.

[0010] FIG. 4 illustrates an exemplary community mobile device of the implementation of FIG. 1.

[0011] FIG. 5 illustrates an environment for locating a tracking device, according to one embodiment.

[0012] FIG. 6 illustrates an interface for use in locating a tracking device, according to one embodiment.

[0013] FIG. 7 is a flowchart illustrating a process for locating a tracking device, accordingly to one embodiment.

[0014] FIG. 8 is a flowchart illustrating a process for compensating a person for locating a tracking device, according to one embodiment.

[0015] The figures depict various embodiments of the present invention for purposes of illustration only. One skilled in the art will readily recognize from the following discussion that alternative embodiments of the structures and methods illustrated herein may be employed without departing from the principles of the invention described herein.

DESCRIPTION OF EXAMPLE EMBODIMENTS

[0016] Embodiments described herein provide a user with the ability to locate a lost tracking device by leveraging the capabilities of a plurality of mobile devices associated with a community of users (e.g., users of the same tracking device system) in a secure and privacy-focused environment.

[0017] A user can attach a tracking device to or enclose the tracking device within an object, such as a wallet, keys, a car, a bike, a pet, or any other object that the user wants to track. The user can then use a mobile device (e.g., by way of a software application installed on the mobile device) to track the tracking device and corresponding object. For example, the mobile device can perform a local search for a tracking device attached to a near-by object. However, in situations where the user is unable to locate the tracking device using their own mobile device (e.g., if the tracking device is beyond a distance within which the mobile device and the tracking device can communicate), the principles described herein allow the user to leverage the capabilities of a community of users of a tracking device system.

[0018] In particular, a tracking system (also referred to herein as a “cloud server” or simply “server”) can maintain user profiles associated with a plurality of users of the system. The tracking

system can associate each user within the system with one or more tracking devices associated the user (e.g., tracking devices that the user has purchased and is using to track objects owned by the user). If the user's object becomes lost or stolen, the user can send an indication that the tracking device is lost to the tracking system, which is in communication with one or more mobile devices associated with the community of users in communication with the system. The tracking system can set a flag indicating the tracking device is lost. When one of a community of mobile devices that are scanning for nearby tracking devices and providing updated locations to the tracking system identifies a flagged tracking device, the tracking system can associate the received location with the flagged tracking device, and relay the location to a user of the tracking device, thereby enabling the user to locate and track down the tracking device.

[0019] In order to aid in locating a lost tracking device, an owner of the lost tracking device can organize a search party of other users within a community of users of the tracking system. The owner of the lost tracking device can invite users within the community of users to join a search party based on one or more criteria. Upon being invited, if a user within the community of users accepts the invitation, the user is added to the search party and can be given the last known location of the lost tracking device. When a mobile device of a member of the search party receives a signal outputted by the lost tracker device (such as a beacon signal), the mobile device of the search party member reports the location of the lost tracking to the tracking system for communication to the owner of the lost tracking device. Search parties further enable an owner of a lost tracking device to provide a reward to a search party member that locates the lost tracking device.

Environment Overview

[0020] In particular, a tracking system (also referred to herein as a “cloud server” or simply “server”) can maintain user profiles associated with a plurality of users of the tracking device system. The tracking system can associate each user within the system with one or more tracking devices associated the user (e.g., tracking devices that the user has purchased and is using to track objects owned by the user). If the user's object becomes lost or stolen, the user can send an indication that the tracking device is lost to the tracking system, which is in communication with one or more mobile devices associated with the community of users in communication with the system. The tracking system can set a flag indicating the tracking device is lost. When one of a community of mobile devices that are scanning for nearby tracking devices and providing updated locations to the tracking system identifies a flagged tracking device, the tracking system can associate the received location with the flagged tracking device, and relay the location to a user of the tracking device, thereby enabling the user to locate the lost tracking device.

[0021] FIG. 1 illustrates an exemplary implementation in which a tracking system **100** is communicatively coupled to a mobile device **102** associated with the user **103** and a plurality of community mobile devices **104a** through **104n** (collectively referred to herein as “community mobile devices **104**”) associated with a plurality of users **105a** through **105n** of the tracking system **100** (collectively referred to herein as “community users **105**”). As will be explained in more detail below, the tracking system **100** can allow the user **103** to manage and/or locate a tracking device **106** associated with the user **103**. In some embodiments, the tracking system **100** leverages the capabilities of community mobile devices **104** to locate the tracking device **106** if the location of the tracking device is unknown to the user **103** and beyond the capabilities of mobile device **102** to track. In some configurations, the user **103** may own and register multiple tracking devices **106**. Although FIG. 1 illustrates a particular arrangement of the tracking system **100**, mobile device **102**, community mobile devices **104**, and tracking device **106**, various additional arrangements are possible.

[0022] In some configurations, the user **103** may be part of the community of users **105**. Further, one or more users **105** may own and register one or more tracking devices **106**. Thus, any one of the users within the community of users **105** can communicate with tracking system **100** and leverage the capabilities of the community of users **105** in addition to the user **103** to locate a

tracking device **106** that has been lost.

[0023] The tracking system **100**, mobile device **102**, and plurality of community mobile devices **104** may communicate using any communication platforms and technologies suitable for transporting data and/or communication signals, including known communication technologies, devices, media, and protocols supportive of remote data communications.

[0024] In certain embodiments, the tracking system **100**, mobile device **102**, and community mobile devices **104** may communicate via a network **108**, which may include one or more networks, including, but not limited to, wireless networks (e.g., wireless communication networks), mobile telephone networks (e.g., cellular telephone networks), closed communication networks, open communication networks, satellite networks, navigation networks, broadband networks, narrowband networks, the Internet, local area networks, and any other networks capable of carrying data and/or communications signals between the tracking system **100**, mobile device **102**, and community mobile devices **104**. The mobile device **102** and community of mobile devices **104** may also be in communication with a tracking device **106** via a second network **110**. The second network **110** may be a similar or different type of network as the first network **108**. In some embodiments, the second network **110** comprises a wireless network with a limited communication range, such as a Bluetooth or Bluetooth Low Energy (BLE) wireless network. In some configurations, the second network **110** is a point-to-point network including the tracking device **106** and one or more mobile devices that fall within a proximity of the tracking device **106**.

Accordingly, the mobile device **102** and community mobile devices **104** are only able to communicate with the tracking device **106** if they are within a close proximity to the tracking device. In some configurations, the mobile device **102** and one or more community mobile devices **104** may each be associated with multiple tracking devices associated with various users.

[0025] As mentioned above, FIG. **1** illustrates the mobile device **102** associated with the user **103**. The mobile device **102** can be configured to perform one or more functions described herein with respect to locating tracking devices (e.g., tracking device **106**). For example, the mobile device **102** can receive input from the user **103** representative of information about the user **103** and information about a tracking device **106**. The mobile device **102** may then provide the received user information, tracking device information, and/or information about the mobile device **102** to the tracking system **100**. Accordingly, the tracking system **100** is able to associate the mobile device **102**, the user **103**, and/or the tracking device **106** with one another. In some embodiments, the mobile device **102** can communicate with the tracking device **106** and provide information regarding the location of the tracking device to the user **103**. For example, the mobile device **102** can detect a communication signal from the tracking device **106** (e.g., by way of second network **110**) as well as a strength of the communication signal to determine an approximate distance between the mobile device **102** and the tracking device **106**. The mobile device **102** can then provide this information to the user **103** (e.g., by way of one or more graphical user interfaces) to assist the user **103** to locate the tracking device **106**. Accordingly, the user **103** can use the mobile device **102** to track and locate the tracking device **106** and a corresponding object associated with the tracking device **106**. If the mobile device **102** is located beyond the immediate range of communication with the tracking device **106** (e.g., beyond the second network **110**), the mobile device **102** can be configured to send an indication that a tracking device **106** is lost to the tracking system **100**, requesting assistance in finding the tracking device. The mobile device **102** can send an indication of a lost device in response to a command from the user **103**. For example, once the user **103** has determined that the tracking device **106** is lost, the user can provide user input to the mobile device **102** (e.g., by way of a graphical user interface), requesting that the mobile device **102** send an indication that the tracking device **106** is lost to the tracking system **100**. In some examples, the lost indication can include information identifying the user **103** (e.g., name, username, authentication information), information associated with the mobile device **102** (e.g., a mobile phone number), information associated with the tracking device (e.g., a unique tracking

device identifier), or a location of the user (e.g., a GPS location of the mobile device **102** at the time the request is sent).

[0026] The tracking system **100** can be configured to provide a number of features and services associated with the tracking and management of a plurality of tracking devices and/or users associated with the tracking devices. For example, the tracking system **100** can manage information and/or user profiles associated with user **103** and community users **105**. In particular, the tracking system **100** can manage information associated with the tracking device **106** and/or other tracking devices associated with the user **103** and/or the community users **105**.

[0027] As mentioned above, the tracking system **100** can receive an indication that the tracking device **106** is lost from the mobile device **102**. The tracking system **100** can then process the indication in order to help the user **103** find the tracking device **106**. For example, the tracking system **100** can leverage the capabilities of the community mobile devices **104** to help find the tracking device **106**. In particular, the tracking system **100** may set a flag for a tracking device **106** to indicate that the tracking device **106** is lost and monitor communications received from the community mobile devices **104** indicating the location of one or more tracking devices **106** within proximity of the community mobile devices **104**. The tracking system **100** can determine whether a specific location is associated with the lost tracking device **106** and provide any location updates associated with the tracking device **106** to the mobile device **102**. In one example, the tracking system may receive constant updates of tracking device **106** locations regardless of whether a tracking device **106** is lost and provide a most recent updated location of the tracking device **106** in response to receiving an indication that the tracking device **106** is lost.

[0028] In some configurations, the tracking system **100** can send a location request associated with the tracking device **106** to each of the community mobile devices **104**. The location request can include any instructions and/or information necessary for the community mobile devices **106** to find the tracking device **102**. For example, the location request can include a unique identifier associated with the tracking device **106** that can be used by the community mobile devices **104** to identify the tracking device **106**. Accordingly, if one of the community mobile devices **104** detects a communication from the tracking device **106** (e.g., if the community mobile device **104** is within range or moves within range of the communication capabilities of the tracking device **106** and receives a signal from the tracking device **106** including or associated with the unique identifier associated with the tracking device **106**), the community mobile device **104** can inform the tracking system **100**. Using the information received from the community mobile devices **104**, the tracking system **100** can inform the user (e.g., by way of the mobile device **102**) of a potential location of the tracking device **106**.

[0029] As shown in FIG. **1** and as mentioned above, the tracking system **100** can communicate with a plurality of community mobile devices **104** associated with corresponding community users **105**. For example, an implementation may include a first community mobile device **104a** associated with a first community user **105a**, a second community mobile device **104b** associated with a second community user **105b**, and additional communication mobile devices associated with additional community users up to an nth community mobile device **104n** associated with an nth community user **105n**. The community mobile devices **104** may also include functionality that enables each community mobile device **104** to identify a tracking device **106** within a proximity of the community mobile device **104**. In one example, a first community mobile device **104a** within proximity of a tracking device **106** can communicate with the tracking device **106**, identify the tracking device **106** (e.g., using a unique identifier associated with the tracking device **106**), and/or detect a location associated with the tracking device **106** (e.g., a location of the first mobile community device **104a** at the time of the communication with the tracking device **106**). This information can be used to provide updated locations and/or respond to a location request from the tracking system **100** regarding the tracking device **106**. In some embodiments, the steps performed by the first community mobile device **104a** can be hidden from the first community user **105a**.

Accordingly, the first community mobile device **104a** can assist in locating the tracking device **106** without bother and without the knowledge of the first community user **105a**.

[0030] As mentioned above, the tracking system **100** can assist a user **103** in locating a tracking device **106**. The tracking device may be a chip, tile, tag, or other device for housing circuitry and that may be attached to or enclosed within an object such as a wallet, keys, purse, car, or other object that the user **103** may track. Additionally, the tracking device **106** may include a speaker for emitting a sound and/or a transmitter for broadcasting a beacon. In one configuration, the tracking device **106** may constantly transmit a beacon signal that may be detected using a nearby mobile device **102** and/or community mobile device **104**. In some configurations, the tracking device **106** broadcasts a beacon at regular intervals (e.g., one second intervals) that may be detected from a nearby mobile device (e.g., community mobile device **104**). The strength of the signal emitted from the tracking device **106** may be used to determine a degree of proximity to the mobile device **102** or community mobile device **104** that detects the signal. For example, a higher strength signal would indicate a close proximity between the tracking device **106** and the mobile device **102** and a lower strength signal would indicate a more remote proximity between the tracking device **106** and the mobile device **102**. In some cases, the strength of signal or absence of a signal may be used to indicate that a tracking device **106** is lost.

System Overview

[0031] FIG. 2 illustrates a diagram showing example components of the tracking system **100**. As shown, the tracking system **100** may include, but is not limited to, an association manager **204**, a tracking device location manager **206**, a data manager **208**, and a search party manager **218**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **204-208** are shown to be separate in FIG. 2, any of the managers **204-208** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0032] The association manager **204** may be configured to receive, transmit, obtain, and/or update information about a user **103** and/or information about one or more specific tracking devices (e.g., tracking device **106**). In some configurations, the association manager **204** may associate information associated with a user **103** with information associated with a tracking device **106**. For example, user information and tracking information may be obtained by way of a mobile device **102**, and the association manager **204** may be used to link the user information and tracking information. The association between user **103** and tracking device **106** may be used for authentication purposes, or for storing user information, tracking device information, permissions, or other information about a user **103** and/or tracking device **106** in a database.

[0033] The tracking system **100** also includes a tracking device location manager **206**. The tracking device location manager **206** may receive and process an indication that the tracking device **106** is lost from a mobile device (e.g., mobile device **102** or community mobile devices **104**). For example, the tracking system **100** may receive a lost indication from a mobile device **102** indicating that the tracking device **106** is lost. The tracking device location manager **206** may set a flag on a database (e.g., tracker database **212**) indicating that the tracking device **106** is lost. The tracking device location manager **206** may also query a database to determine tracking information corresponding to the associated user **103** and/or tracking device **106**. The tracking system **100** may obtain tracking device information and provide the tracking device information or other information associated with the tracking device **106** to a plurality of community mobile devices **104** to be on alert for the lost or unavailable tracking device **106**. The tracking device location manager **206** may also be used to receive and process a response to a tracking request that is received from one or more community mobile devices **104** that detect the tracking device **106** and respond to the tracking request. For example, the tracking system **100** may receive a response to the tracking request indicating a location within a proximity of the tracking device **106** and provide a last known location within a proximity of the tracking device **106** as provided by the community

mobile device **104**.

[0034] In one configuration, the tracking device location manager **206** may receive an indication that a tracking device **106** is lost from the mobile device **102** and store the lost indication on a database. When the tracking device location manager **206** receives an indication that the tracking device **106** is lost, the tracking device location manager **206** may set a flag indicating that the tracking device **106** is lost. Setting a flag for a tracking device **106** may include storing and/or associating a value associated with the tracking device that indicates that the tracking device **106** is lost. This may include setting a flag, marker, digital value, or other indication that the tracking device **106** is lost and maintaining or storing the indication of the lost tracking device **106** on the tracking system **100** (e.g., on a database).

[0035] The tracking device location manager **206** may further receive updated locations from the community of mobile devices **104** that are constantly scanning for nearby tracking devices **106**. In this example, the tracking device location manager **206** may receive location updates from the community of mobile devices **104** and, based on the tracking device **106** being indicated as lost, provide a response to a lost indication to the mobile device **102**. The response to the lost indication may be a text message, push notification, ring tone, automated voice message, or other response for informing a user **103** that a tracking device **106** has been found and/or an updated location of the tracking device **106**.

[0036] The tracking device location manager **206** may further manage providing indications about whether a tracking device **106** is lost or not lost. For example, as discussed above, the tracking device location manager **206** may provide a location request to the community of mobile devices **104** indicating that a tracking device **106** is lost. Additionally, upon location of the tracking device **106** by the user **103** or by one of the community of users **105**, the tracking device location manager **206** may provide an indication to the user **103**, community user **105**, or tracking system **100** that the tracking device **106** has been found, thus removing any flags associated with a tracking device and/or canceling any location request previously provided to the community of users **105**. For example, where a user **103** sends an indication that the tracking device **106** is lost to the tracking system **100** and later finds the tracking device **106**, the mobile device **102** may provide an indication to the tracking system **100** that the tracking device **106** has been found. In response, the tracking device location manager **206** may remove a flag indicating that the tracking device **106** is lost and/or provide an updated indication to the community of users **105** that the tracking device **106** has been found, thus canceling any instructions associated with the previously provided location request. In some configurations, the notification that the tracking device **106** has been found may be provided automatically upon the mobile device **102** detecting a proximity of the tracking device **106**. Alternatively, the notification that the tracking device **106** has been found may be provided by the user **103** via user input on the mobile device **102**. In another example, a known user (e.g., a friend or family member) with whom the tracking device **106** has been shared may provide an indication that the tracking device **106** has been found.

[0037] The tracking system **100** additionally includes a data manager **208**. The data manager **208** may store and manage information associated with users, mobile devices, tracking devices, permissions, location requests, and other data that may be stored and/or maintained in a database related to performing location services of tracking devices. As shown, the data manager **208** may include, but is not limited to, a user database **210**, a tracker database **212**, permissions data **214**, and location request data **216**. It will be recognized that although databases and data within the data manager **208** are shown to be separate in FIG. 2, any of the user database **210**, tracker database **212**, permissions data **214**, and location request data **216** may be combined in a single database or manager, or divided into more databases or managers as may serve a particular embodiment.

[0038] The data manager **208** may include the user database **210**. The user database **210** may be used to store data related to various users. For example, the user database **210** may include data about the user **103** as well as data about each user **105** in a community of users **105**. The

community of users **105** may include any user that has provided user information to the tracking system **100** via a mobile device **102**, **104** or other electronic device. The user information may be associated with one or more respective tracking devices **106**, or may be stored without an association to a particular tracking device. For example, a community user **105** may provide user information and permit performance of tracking functions on the community mobile device **104** without owning or being associated with a tracking device **106**. The user database **210** may also include information about one or more mobile devices or other electronic devices associated with a particular user.

[0039] The data manager **208** may also include a tracker database **212**. The tracker database **212** may be used to store data related to tracking devices. For example, the tracker database **212** may include tracking data for any tracking device **106** that has been registered with the tracking system **100**. Tracking data may include unique tracker identifications (IDs) associated with individual tracking devices **106**. Tracker IDs may be associated with a respective user **103**. Tracker IDs may also be associated with multiple users. Additionally, the tracker database **212** may include any flags or other indications associated with whether a specific tracking device **106** has been indicated as lost and whether any incoming communications with regard to that tracking device **106** should be processed based on the presence of a flag associated with the tracking device **106**.

[0040] The data manager **208** may further include permissions data **214** and location request data **216**. Permissions data **214** may include levels of permissions associated with a particular user **103** and/or tracking device **106**. For example, permissions data **214** may include additional users that have been indicated as sharing a tracking device **106**, or who have been given permission to locate a tracking device **106** using an account and/or mobile device **102** associated with the user **103**. Location request data **216** may include information related to a location request or a lost indication received from the user **103** via a mobile device **102**.

[0041] The search party manager **218** coordinates the organization and implementation of search parties to locate lost tracking devices. For example, the search party manager **218** can, in response to a request from an owner of a lost tracking device, invite one or more other users (owners of community mobile devices such as community mobile devices **104** of FIG. **1**) to join the search party based on one or more search party criteria. The search party manager **218** can provide, for instance, a last known location of the tracking device and/or any reward information corresponding to the lost tracking device. The search party manager **218**, in response to receiving location information corresponding to the lost tracking device from a search party member, can provide the location information to an owner of the lost tracking device, can receive confirmation from the owner of the lost tracking device that the tracking device was retrieved by the owner, and can transfer a reward to the community mobile device that located the lost tracking device. Search party functionality will be described below in greater detail.

[0042] FIG. **3** illustrates a diagram showing example components of the mobile device **102**. As shown, the mobile device **102** may include, but is not limited to, a user interface manager **302**, a location request manager **304**, a database manager **306**, and a tracking manager **308**, each of which may be in communication with one another using any suitable communication technologies. It will be recognized that although managers **302-308** are shown to be separate in FIG. **3**, any of the managers **302-308** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0043] As will be explained in more detail below, the mobile device **102** includes the user interface manager **302**. The user interface manager **302** may facilitate providing the user **103** access to data on a tracking system **100** and/or providing data to the tracking system **100**. Further, the user interface manager **302** provides a user interface by which the user **103** may communicate with tracking system **100** and/or tracking device **106** via mobile device **102**.

[0044] The mobile device **102** may also include a location request manager **304**. The location request manager **304** may receive and process a request input to the mobile device **102** to send an

indication that a tracking device **106** is lost to a tracking system **100**. For example, the user **103** may provide an indication that a tracking device **106** is lost, unreachable, or otherwise unavailable from the mobile device **102** via the user interface manager **302**, and the location request manager **304** may process the lost indication and provide any necessary data to the tracking system **100** for processing and relaying a location request to other users **105** over a network **108**. In some configurations, an indication that a tracking device **106** is lost is provided via user input. Alternatively, the indication may be transmitted automatically in response to the mobile device **102** determining that a tracking device **106** is lost.

[0045] The mobile device **102** may also include a database manager **306**. The database manager **306** may maintain data related to the user **103**, tracking device **106**, permissions, or other data that may be used for locating a tracking device **106** and/or providing a request to a tracking system **100** for locating one or more tracking devices **106** associated with the user **103**. Further, the database manager **306** may maintain any information that may be accessed using any other manager on the mobile device **102**.

[0046] The mobile device **102** may further include a tracking manager **308**. The tracking manager **308** may include a tracking application (e.g., a software application) for communicating with and locating a tracking device **106** associated with the user **103**. For example, the tracking manager **308** may be one configuration of a tracking application installed on the mobile device **102** that provides the functionality for locating a tracking device **106** and/or requesting location of a tracking device **106** using a plurality of community mobile devices **104**. As shown, the tracking manager **308** may include, but is not limited to, a Bluetooth Low Energy (BLE) manager **310**, a persistence manager **312**, a local files manager **314**, a motion manager **316**, a secure storage manager **318**, a settings manager **320**, a location manager **322**, a network manager **324**, a notification manager **326**, a sound manager **328**, a friends manager **330**, a photo manager **332**, an authentication manager **334**, and a device manager **336**. Thus, the tracking manager **308** may perform any of the functions associated with managers **310-338**, described in additional detail below.

[0047] The BLE manager **310** may be used to manage communication with one or more tracking devices **106**. The persistence manager **312** may be used to store logical schema information that is relevant to the tracking manager **308**. The local files manager **314** may be responsible for managing all files that are input or output from the mobile device **102**. The motion manager **316** may be responsible for all motion management required by the tracking manager **308**. The secure storage manager may be responsible for storage of secure data, including information such as passwords and private data that would be accessed through this sub-system. The settings manager **320** may be responsible for managing settings used by the tracking manager **308**. Such settings may be user controlled (e.g., user settings) or defined by the tracking manager **308** for internal use (e.g., application settings) by a mobile device **102** and/or the tracking system **100**. The location manager **322** may be responsible for all location tracking done by the tracking manager **308**. For example, the location manager **322** may manage access to the location services of the mobile device **102** and works in conjunction with other managers to persist data. The network manager **324** may be responsible for all Internet communications from the tracking manager **308**. For example, the network manager **324** may mediate all Internet API calls for the tracking manager **308**. The notification manager **326** may be responsible for managing local and push notifications required by the tracking manager **308**. The sound manager **328** may be responsible for playback of audio cues by the tracking manager **308**. The friends manager **330** may be responsible for managing access to contacts and the user's social graph. The photo manager **332** may be responsible for capturing and managing photos used by the tracking manager **308**. The authentication manager **334** may be responsible for handling the authentication (e.g., sign in or login) of users. The authentication manager **334** may also include registration (e.g., sign up) functionality. The authentication manager **334** further coordinates with other managers to achieve registration functionality. The device manager **336** may be responsible for managing the devices discovered by the tracking manager

308. The device manager **336** may further store and/or maintain the logic for algorithms related to device discovery and update.

[0048] FIG. **4** illustrates a diagram showing example components of a community mobile device **104**. As shown, the community mobile device **104** may include, but is not limited to, a user interface manager **402**, a lost tracking device manager **404**, a database manager **406**, and a tracking manager **408**, each of which may be in communication with one another using any suitable communication technologies. The user interface manager **402**, database manager **406**, and tracking manager **408** illustrated in FIG. **4** may include similar features and functionality as the user interface manager **302**, database manager **306**, and tracking manager **308** described above in connection with FIG. **3**. It will be recognized that although managers **402-408** are shown to be separate in FIG. **4**, any of the managers **402-408** may be combined into fewer managers, such as into a single manager, or divided into more managers as may serve a particular embodiment.

[0049] The community mobile device **104** may include a lost tracking device manager **404**. The lost tracking device manager **404** may facilitate scanning for nearby tracking devices **106**. In some configurations, the lost tracking device manager **404** can continuously or periodically scan (e.g., once per second) for nearby tracking devices **106**. The lost tracking device manager **404** may determine whether to provide an updated location of the nearby tracking device **106** to the tracking system **100**. In some configurations, the lost tracking device manager **404** provides a location of a nearby tracking device **106** automatically. Alternatively, the lost tracking device manager **404** may determine whether the location of the tracking device **106** has been recently updated, and determine whether to provide an updated location based on the last time a location of the tracking device **106** has been updated (e.g., by the community mobile device **104**). For example, where the community mobile device **104** has provided a recent update of the location of a tracking device **106**, the lost tracking device manager **404** may decide to wait a predetermined period of time (e.g., 5 minutes) before providing an updated location of the same tracking device **106**.

[0050] In one configuration, the lost tracking device manager **404** may receive and process a location request or other information relayed to the community mobile device **104** by the tracking system **100**. For example, the lost tracking device manager **404** may receive an indication of a tracking device **106** that has been indicated as lost, and provide a location of the tracking device **106** if it comes within proximity of the community mobile device **104**. In some configurations, the community mobile device **104** is constantly scanning nearby areas to determine if there is a tracking device **106** within a proximity of the community mobile device **104**. Therefore, where a tracking device **106** that matches information provided by the tracking system **100** (e.g., from the location request) comes within proximity of the community mobile device **104**, the lost tracking device manager **404** may generate and transmit a response to the location request to the tracking system **100**, which may be provided to the user **103** associated with the lost tracking device **106**. Further, generating and transmitting the response to the tracking request may be conditioned on the status of the tracking device **106** being flagged as lost by the mobile device **102** and/or the tracking system **100**.

[0051] The lost tracking device manager **404** may additionally provide other information to the tracking system **100** in response to receiving the tracking request. For example, in addition to providing a location of the community mobile device **104**, the lost tracking device manager may provide a signal strength associated with the location to indicate a level of proximity to the location of the community mobile device **104** provided to the user **103**. For example, if a signal strength is high, the location provided to the user **103** is likely to be more accurate than a location accompanied by a low signal strength. This may provide additional information that the user **103** may find useful in determining the precise location of tracking device **106**.

[0052] As described above, the lost tracking device manager **404** may determine whether to send a location within the proximity of the tracking device **106** to the tracking system **100**. The determination of whether to send a location to the tracking system **100** may be based on a variety of

factors. For example, a lost tracking device manager **404** may determine to send a location of the tracking device **106** to a tracking system **100** based on whether the detected tracking device **106** has been indicated as lost or if a tracking request has been provided to the community mobile device **104** for the particular tracking device **106**. In some configurations, the community mobile device **104** may send an update of a location of a tracking device **106** even if the tracking device **106** is not associated with a current tracking request or if the tracking device **106** is not indicated as lost. For example, where the location of a tracking device **106** has not been updated for a predetermined period of time, the community mobile device **104** may provide an update of a tracking device location to the tracking system **100**, regardless of whether a tracking request has been received. [0053] In some configurations, the community mobile device **104** may include additional features. For example, the community mobile device **104** may allow a tracking system **100** to snap and download a photo using photo functionality of the community mobile device **104**. In some configurations, this may be an opt-in feature by which a community user **105** permits a tracking system **100** to take a snap-shot and possibly provide a visual image of an area within a proximity of the tracking device **106**.

Power Preservation Overview

[0054] In some embodiments, the tracking system **100** enables the use of a network of community mobile devices to locate a lost tracking device in response to a request from an owner of the lost tracking device, for instance, via the search party manager **218**. In such embodiments, the owner of the lost tracking device can request the formation of a search party to locate the lost tracking device, and the search party manager **218** invites one or more of the network of community mobile devices to join the search party. As used herein, community mobile devices that have accepted an invitation to locate a lost tracking device in response to a request from the owner of the lost tracking device are referred to as a “search party”. Community mobile devices can be invited to join a search party based on one or more criteria. In some implementations, a reward for locating the lost tracking device may be offered by the owner of the lost tracking device.

[0055] A search party, after its creation by the search party manager **218**, may be populated by inviting community mobile devices **104** to participate based on certain criteria, hereafter “search party criteria.” In some embodiments, invited community mobile devices become members of the search party after acceptance of the invitation. In some configurations, invited community mobile devices may become search party members without having to accept the invitation. Search party manager **218** may monitor membership in the search party and can expand the search party criteria based on target membership goals or other metrics associated with the management of the search party.

[0056] In response to accepting an inviting to join a search party, members of the search party are given additional information about the lost tracking device. For example, members of the search party may be given the last known location of the lost tracking device. Likewise, search party members may be given information about a reward offered in association with the search party.

[0057] In some configurations, the search party is implemented by search party manager **218** until the lost tracking device is found, until the owner of the lost tracking device cancels the search party, or until the occurrence of one or more conditions corresponding to the canceling of the search party (such as the passage of a threshold amount of time). Before the search party is canceled, the owner of the lost tracking device may be notified by search party manager **218**. For example, if the lost device was located, the owner of the lost tracking device may be notified of its location by search party manager **218**, and if a threshold amount of time has passed without the device being located, the owner can be notified that the search party was expired.

[0058] In some configurations, the owner of a lost tracking device sends a search party request via their associated mobile device or any other suitable interface to the search party manager **218**. The request may contain any relevant information associated with the search party request, for example reward information, requested search party criteria (such as a desired duration of the search party, a

desired size of the search party, the last known location of the lost tracking device, another location associated with the tracking device, a reputation of candidate search party members, a proximity to last known location of candidate search party members, a relationship type or strength between candidate search party members and the owner of the lost tracking device, and the like) or any other information associated with the lost tracking device that might be useful in locating the lost tracking device (such as a photograph of the lost tracking device, properties of the lost tracking device, and the like).

[0059] In response to receiving a search party request, the search party manager **218** implements a search party. In some embodiments, the search party manager **218** implements a search party based on requested search party criteria included within the search party request, such as a requested size of a search party and a threshold reputation of search party members. The search party manager **218** then invites candidate search party members based on the requested search party criteria. In some embodiments, if a search party is requested with invalid or infeasible search party criteria, the search party manager **218** can expand or alter the requested search party criteria before implementing the search party. For instance, if the search party request requests users above a threshold reputation for inclusion within a search party, and no users with an above threshold reputation are within a threshold distance of the lost tracking device's last known location, the search party manager **218** can implement the search party without the threshold reputation requirement. As used herein, community mobile devices that satisfy any search party criteria and that are eligible for invitation to the search party are referred to as “candidate search party members.” In some embodiments, candidate search party members are selected from owners of community mobile devices that configure their devices or tracking system accounts to participate in search parties.

[0060] In some embodiments, the search party manager **218** implements a search party based on default search party criteria. For instance, the search party manager **218** may implement a search party with a pre-determined target number of search party members, such as 10 users. In such embodiments, the search party manager **218** can invite candidate search party members to join the search party, and in response to the number of invited candidate search party members that accept the invitation, can alter the default search party criteria to expand the number of search party members. For instance, if the search party manager **218** invites 20 candidate search party members within a first threshold distance of the last known location of the lost tracking device with a goal of having 10 candidate members join the search party, and only 6 candidate members end up joining the search party, the search party manager can identify additional candidate search party members by, for example, expanding the first threshold distance to a second, larger threshold distance of the last known location.

[0061] As noted above, candidate search party members can be selected based on the proximity of the candidate search party member to a last known location of the tracking device. FIG. 5 illustrates an environment for locating a tracking device, according to one embodiment. FIG. 5 shows an owner **103** and an owner mobile device **102** associated with a lost tracking device **501**. Candidate search party members **104a-104f** are located around the last known location **502** of the lost tracking device **501**. In the embodiment of FIG. 5, search party members are identified based on a proximity to the last known location **502** of the lost tracking device. In this embodiment, users **105a**, **105b**, and **105d** are within a first threshold distance of the last known location **502** and are invited to join the search party. In response to determining to invite additional candidate search party members (for instance, in response to a less than requested threshold number of candidate search party members joining the search party), the first threshold distance can be expanded to a greater, second threshold distance from the last known location **502**, within which users **105c**, **105e**, and **105g** reside. In this embodiment, users **105f** and **105h** is outside of both the first threshold distance and the second threshold distance from the last known location **502**, and is not invited to join the search party.

[0062] Candidate search party members can be selected based on historical location data associated with the candidate search party member. For example, in the embodiment of FIG. 5, user **105f** is far from the last known location **502** of the lost tracking device **501**. However, if the candidate search party member **104f** is associated with historical location data showing past proximity within a threshold distance of the last known location **502**, candidate search party member **104f** may be invited to the search party based on this factor. For instance, if the candidate search party member **104f** passes close by the last known location **502** on the way home from work between 6 pm and 7 pm every day, the candidate search party member **104f** may be invited to join the search party. In some embodiments, candidate search party members can be selected based on historical location data and time data, and based on current time data. Continuing with the previous example, candidate search party member **104f** can be invited to join the search party if the current time is 6:30 pm (or within a threshold amount of time of the 6:00 pm to 7:00 pm interval highlighted above), and can be avoided to join the search party if the current time is 9:00 am.

[0063] In another embodiment, candidate search party members are selected based on previous participation in search parties. For example, candidate search party members may be assigned a reputation based on past participation in successful search parties. A candidate search party member's reputation may be increased in response to successfully finding the lost mobile device in a previous search party. In some embodiments, candidate search party members may be selected by comparing their reputation score against a reputation threshold included within the search party criteria. In the embodiment of FIG. 5, users **105c**, **105d**, and **105f** may have reputation exceeding a threshold reputation, and may be invited to the search party accordingly. It should be noted that a candidate search party member's reputation can also be decreased, for instance in response to bad behavior reported by other search party members or users of the tracking system **100**, in response to participating in a threshold number of search parties without successfully locating a lost tracking device, or based on any other suitable criteria.

[0064] Candidate search party members may be selected based on a connection to or relationship with the owner **103** of the lost tracking device **501**. The system **100** can store connections or relationships between users of the tracking system **100** internally. Alternatively, connections or relationships between users can be obtained from an outside source. For example, the search party manager **218** may interface with a social networking system and access connections between users from a social graph of the social networking system. Candidate search party members with an established relationship (such as "friends" within the social networking system) with the owner **103** of the lost tracking device **501** can be invited to join the search party.

[0065] In another embodiment, candidate search party members can be directly invited by the owner of the lost tracking device. For example, the search party manager **218** may provide the owner **103** a link or URL which the owner **103** can provide to candidate search party members, for instance via text messaging, email, social media, and the like. Candidate search party members who click the provided link are then added to the search party, according to one embodiment. In other embodiments, the owner **103** can invite candidate search party members directly from the mobile device **102** or from an application associated with the tracking system **100**. In the embodiment of FIG. 5, user **105c** may be directly sent an invite by the owner **103**, and, in response to a selection of a link within the invite, may be added to the search party.

[0066] In another configuration, candidate search party members **104** may request to join a search party. In some embodiments, community mobile devices **104** may present an interface that allows community users **105** to view active nearby search parties. In such embodiments, a community user **105** may then request an invite to a search party. For example, in FIG. 5, the candidate search party member **105g** may request an invite to a search party to locate the lost tracking device **501** through an interface presented by the community mobile device **104g**. Upon receiving this request, the search party manager **218** may add the candidate search party member **105g** to the search party, for instance if the candidate search party member satisfies any search party criteria corresponding to

the search party.

[0067] As noted above, in some embodiments, search party criteria are not static over the lifetime of the search party. The search party manager **218** can modify the search party criteria, for instance based on one or more search goals (such as a number of search party members, the passage of an interval of time without a lost tracking device being located, and the like). For example, if less than a threshold number of search party members have accepted invitations to join a search party, search party criteria can be expanded or eliminated, for instance by increasing a requisite threshold proximity to the last known location of a lost tracking device **501**.

[0068] Search party criteria may also be modified by search party manager **218** based on any number of additional factors. In some configurations, an owner of a lost tracking device can adjust the search party criteria after making the initial search party request, for instance using the mobile device corresponding to the lost tracking device or using any other tracking system interface. In some embodiments, the search party manager **218** adjusts the search party criteria based on outside factors such as time of day or weather conditions. It should be noted that although several search party criteria are described herein individually, in practice, candidate search party members can be identified and invited to join a search party based on any combination of search party criteria as well.

[0069] In some configurations, candidate search party members are provided with data on the progress or performance of the search party. FIG. 6 illustrates an interface for use in locating a tracking device, according to one embodiment. In the embodiment of FIG. 6, a map **600** is generated by search party manager **218** and displayed to search party members to increase the efficiency of search party members in searching for lost tracking device **501**. User paths **602** and **604** trace the paths of search party members **105i** and **105j**. Displaying this information to search party members enables the users to avoid overlapping or searching locations that have already been searched by another search party member.

[0070] In some embodiments, an approximate search range of a community mobile device **104** can be displayed in conjunction with a path taken by a search party member. For example, user path **604** has a range **606** representing an outer limit of the communicative range of the community mobile device **104j**. In such embodiments, if the lost tracking device **501** is located closer to the user path **604** than the range **606**, the community mobile device **104j** will locate the lost tracking device. For example, in the embodiment of FIG. 6, range **608** represents the communicative range of the lost tracking device **501**. Accordingly, the map area defined by locations within the range **606** on either side of the user path **604** represents locations already searched by the search party member **105j**. By displaying such areas, other search party members can expedite their search for the lost tracking device **501** by avoiding such areas. The user path **604** and the area within the range **606** can be colored, graduated, or otherwise modified within the map **600**, and can display other relevant information such as estimated signal strength of the community mobile device **104j**, the time since search was performed by the community mobile device **104j**, the identity of the search party member **105j**, or any other information. This information may additionally be used by search party manager **218** to calculate various search party metrics, for example the percentage of searched area within a target area centered on last known location **502**. This additional data may then be displayed on search party member devices, displayed to candidate search party members, accessible by the owner of the lost tracking device **501**, or used in any other suitable manner.

[0071] FIG. 7 is a flowchart illustrating a process for locating a tracking device, accordingly to one embodiment. According to the embodiment of FIG. 7, a tracking system receives **710** a search party request from an owner of a lost tracking device. The request can include search party criteria, an identity of the lost tracking device, an identity of the owner, or any other suitable information. The tracking system selects **712** search party criteria in response to and based on the received search party request. For instance, the search party criteria can include a proximity to a last known location of the lost tracking device, a target number of search party members, and a reputation of

candidate search party members. Candidate search party members are selected **714** based on the selected search party criteria, and selected candidate search party members are invited **716** to join the search party.

[0072] Responses to the invitations are received **718** from candidate search party members. The number of acceptances to join the search party is compared **722** to a target number of search party members. In response to the number of acceptances being below the target number of search party members, the search party criteria are expanded **726** and more candidate search party members are selected and invited to join the search party based on the expanded criteria.

[0073] After a threshold interval of time, the search party manager **218** checks **724** to see if the lost tracking device has been located. For example, the tracking system may receive **725** a location of the lost tracking device from a search party member. If the lost tracking device **501** has not yet been located within the threshold interval of time, the search party criteria can be expanded **726**, and additional candidate search party members can be selected and invited to join the search party based on the expanded criteria. If during the interval of time, a location of the lost tracking device is received by search party manager **218**, the tracking device is marked within the tracking system as found, and the tracking system notifies **728** the owner of the lost tracking device and cancels **730** the search party.

[0074] In some embodiments, for example when the search party is no longer deemed effective, when the number of search party members falls below a threshold, after the passage of a pre-determined interval of time, or the like, a search party may be canceled without the lost tracking device being located. In another embodiment, an owner of the lost tracking device may cancel a search party by sending a request to search party manager **218**.

[0075] As noted previously, an owner of a lost tracking device may post a reward for finding the lost tracking device. In some embodiments, the reward may be awarded to one search party member or any number of search party members that locate the lost tracking device, and may be a monetary reward, a discount or coupon, a product, a service, an achievement, a reputation increase, or any other suitable reward. The reward can be included within the search party request from the owner of the lost tracking device. For instance, when requesting a search party, the owner of the lost tracking device can transfer a monetary award from an account of the owner to the search party manager **218** for holding until the lost tracking device is located.

[0076] Upon finding the lost tracking device, a search party member can claim the reward. The search party manager **218**, in response, can ask the owner of the lost tracking device to verify that the lost tracking device has been found. Such verification can occur manually (for instance, the search party manager **218** can provide the location of the lost tracking device to the owner of the lost tracking device, who then notifies the search party manager **218** that the lost tracking device has been found), or automatically (for instance, the mobile device of the owner can communicatively detect the lost tracking device, and can notify the search party manager **218** that the lost tracking device has been found). When the owner of the lost tracking device verifies that the lost tracking device has been found, the search party manager **218** can release the reward held by the tracking system to an account of the search party member that found the lost tracking device.

[0077] FIG. **8** is a flowchart illustrating a process for compensating a person for locating a tracking device, according to one embodiment. In the embodiment of FIG. **8**, the reward is received **810** from an owner of the lost tracking device, for instance in conjunction with a search party request, where it is held **812** until claimed. A location of the lost tracking device is received **814** from a search party member, and the location of the lost tracking device is provided **816** to the owner of the lost tracking device. Verification that the lost tracking device has been found is received **818** from the owner, and the reward is transferred **820** to the search party member that found the lost tracking device.

[0078] In some embodiments, a search party may end without the lost tracking device being found, or the owner of the lost tracking device or a community user not included within the search party

may find the lost tracking device. In such embodiments, the reward is returned to the owner of the lost tracking device.

Additional Considerations

[0079] The foregoing description of the embodiments of the invention has been presented for the purpose of illustration; it is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Persons skilled in the relevant art can appreciate that many modifications and variations are possible in light of the above disclosure.

[0080] Any of the devices or systems described herein can be implemented by one or more computing devices. A computing device can include a processor, a memory, a storage device, an I/O interface, and a communication interface, which may be communicatively coupled by way of communication infrastructure. Additional or alternative components may be used in other embodiments. In particular embodiments, a processor includes hardware for executing computer program instructions by retrieving the instructions from an internal register, an internal cache, or other memory or storage device, and decoding and executing them. The memory can be used for storing data or instructions for execution by the processor. The memory can be any suitable storage mechanism, such as RAM, ROM, flash memory, solid state memory, and the like. The storage device can store data or computer instructions, and can include a hard disk drive, flash memory, an optical disc, or any other suitable storage device. The I/O interface allows a user to interact with the computing device, and can include a mouse, keypad, keyboard, touch screen interface, and the like. The communication interface can include hardware, software, or a combination of both, and can provide one or more interfaces for communication with other devices or entities.

[0081] Some portions of this description describe the embodiments of the invention in terms of algorithms and symbolic representations of operations on information. These algorithmic descriptions and representations are commonly used by those skilled in the data processing arts to convey the substance of their work effectively to others skilled in the art. These operations, while described functionally, computationally, or logically, are understood to be implemented by computer programs or equivalent electrical circuits, microcode, or the like. Furthermore, it has also proven convenient at times, to refer to these arrangements of operations as modules, without loss of generality. The described operations and their associated modules may be embodied in software, firmware, hardware, or any combinations thereof.

[0082] Any of the steps, operations, or processes described herein may be performed or implemented with one or more hardware or software modules, alone or in combination with other devices. In one embodiment, a software module is implemented with a computer program product comprising a computer-readable medium containing computer program code, which can be executed by a computer processor for performing any or all of the steps, operations, or processes described.

[0083] Embodiments of the invention may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, and/or it may comprise a general-purpose computing device selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a non-transitory, tangible computer readable storage medium, or any type of media suitable for storing electronic instructions, which may be coupled to a computer system bus. Furthermore, any computing systems referred to in the specification may include a single processor or may be architectures employing multiple processor designs for increased computing capability.

[0084] Embodiments of the invention may also relate to a product that is produced by a computing process described herein. Such a product may comprise information resulting from a computing process, where the information is stored on a non-transitory, tangible computer readable storage medium and may include any embodiment of a computer program product or other data combination described herein.

[0085] Finally, the language used in the specification has been principally selected for readability

and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. It is therefore intended that the scope of the invention be limited not by this detailed description, but rather by any claims that issue on an application based hereon. Accordingly, the disclosure of the embodiments of the invention is intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

Claims

1. A method, comprising: receiving, by a tracking server, and from a first computing device of a plurality of computing devices, a request to locate a tracking device associated with the tracking server; establishing, by the tracking server, a search party for locating the tracking device; determining, by the tracking server, a goal for the search party and a first criteria for including members into the search party; adding, by the tracking server, one or more second computing devices of the plurality of computing devices to the search party based at least in part on the first criteria; determining, by the tracking server, that the goal for the search party is not satisfied; modifying, by the tracking server, the first criteria to include additional computing devices of the plurality of computing devices to the search party; receiving, by the tracking server, an indication that the tracking device has been located by the search party; and providing, by the tracking server, a location of the tracking device to the first computing device.
2. The method of claim 1, wherein the goal for the search party comprises a minimum number of the plurality of computing devices to be added to the search party based at least in part on the first criteria.
3. The method of claim 1, wherein the first criteria for including members into the search party comprises a threshold distance between the one or more second computing devices and a last known location of the tracking device.
4. The method of claim 3, wherein modifying the first criteria to include additional computing devices of the plurality of computing devices to the search party comprises modifying, by the tracking server, the first criteria to increase the threshold distance between the one or more second computing devices and the last known location of the tracking device.
5. The method of claim 1, wherein the search party for locating the tracking device is established based at least in part on one or more of a desired duration of the search party, a desired size of the search party, a last known location of the tracking device, another location associated with the tracking device, a reputation of candidate search party members, a proximity to a last known location of candidate search party members, or a relationship type or strength between candidate search party members and an owner of the tracking device.
6. The method of claim 1, further comprising, subsequent to modifying the first criteria to include additional computing devices of the plurality of computing devices to the search party: determining, by the tracking server, that the goal for the search party is still not satisfied; removing, by the tracking server, the first criteria; and in response to removing the first criteria, adding, by the tracking server, each of the plurality of computing devices to the search party.
7. The method of claim 1, further comprising, subsequent to providing the location of the tracking device to the first computing device: canceling, by the tracking server, the search party; and notifying, by the tracking server, the one or more second computing devices and the additional computing devices of the search party that the search party has been canceled.
8. A tracking server, comprising: one or more non-transitory computer-readable storage media including instructions; and one or more processors coupled to the one or more non-transitory computer-readable storage media, the one or more processors configured to execute the instructions to: receive, from a first computing device of a plurality of computing devices, a request to locate a tracking device associated with the tracking server; establish a search party for locating the tracking device; determine a goal for the search party and a first criteria for including members into the

search party; add one or more second computing devices of the plurality of computing devices to the search party based at least in part on the first criteria; determine that the goal for the search party is not satisfied; modify the first criteria to include additional computing devices of the plurality of computing devices to the search party; receive an indication that the tracking device has been located by the search party; and provide a location of the tracking device to the first computing device.

9. The tracking server of claim 8, wherein the goal for the search party comprises a minimum number of the plurality of computing devices to be added to the search party based at least in part on the first criteria.

10. The tracking server of claim 8, wherein the first criteria for including members into the search party comprises a threshold distance between the one or more second computing devices and a last known location of the tracking device.

11. The tracking server of claim 10, wherein the instructions to modify the first criteria to include additional computing devices of the plurality of computing devices to the search party further comprise instructions to modify the first criteria to increase the threshold distance between the one or more second computing devices and the last known location of the tracking device.

12. The tracking server of claim 8, wherein the search party for locating the tracking device is established based at least in part on one or more of a desired duration of the search party, a desired size of the search party, a last known location of the tracking device, another location associated with the tracking device, a reputation of candidate search party members, a proximity to a last known location of candidate search party members, or a relationship type or strength between candidate search party members and an owner of the tracking device.

13. The tracking server of claim 8, wherein, subsequent to modifying the first criteria to include additional computing devices of the plurality of computing devices to the search party, the instructions further comprise instructions to: determine that the goal for the search party is still not satisfied; remove the first criteria; and in response to removing the first criteria, add each of the plurality of computing devices to the search party.

14. The tracking server of claim 13, wherein, subsequent to modifying the first criteria to include additional computing devices of the plurality of computing devices to the search party, the instructions further comprise instructions to: cancel the search party; and notify the one or more second computing devices and the additional computing devices of the search party that the search party has been canceled.

15. A non-transitory computer-readable medium comprising instructions that, when executed by one or more processors of a tracking server, cause the tracking server to: receive, from a first computing device of a plurality of computing devices, a request to locate a tracking device associated with the tracking server; establish a search party for locating the tracking device; determine a goal for the search party and a first criteria for including members into the search party; add one or more second computing devices of the plurality of computing devices to the search party based at least in part on the first criteria; determine that the goal for the search party is not satisfied; modify the first criteria to include additional computing devices of the plurality of computing devices to the search party; receive an indication that the tracking device has been located by the search party; and provide a location of the tracking device to the first computing device.

16. The non-transitory computer-readable medium of claim 15, wherein the goal for the search party comprises a minimum number of the plurality of computing devices to be added to the search party based at least in part on the first criteria.

17. The non-transitory computer-readable medium of claim 15, wherein the first criteria for including members into the search party comprises a threshold distance between the one or more second computing devices and a last known location of the tracking device.

18. The non-transitory computer-readable medium of claim 17, wherein the instructions to modify

the first criteria to include additional computing devices of the plurality of computing devices to the search party further comprise instructions to modify the first criteria to increase the threshold distance between the one or more second computing devices and the last known location of the tracking device.

19. The non-transitory computer-readable medium of claim 15, wherein the search party for locating the tracking device is established based at least in part on one or more of a desired duration of the search party, a desired size of the search party, a last known location of the tracking device, another location associated with the tracking device, a reputation of candidate search party members, a proximity to a last known location of candidate search party members, or a relationship type or strength between candidate search party members and an owner of the tracking device.

20. The non-transitory computer-readable medium of claim 15, wherein, subsequent to modifying the first criteria to include additional computing devices of the plurality of computing devices to the search party, the instructions further comprise instructions to: determine that the goal for the search party is still not satisfied; remove the first criteria; and in response to removing the first criteria, add each of the plurality of computing devices to the search party.
