

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384444
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Koitabashi; Hiroto et al.

Steering column device

Abstract

[Problem] To enable an adjustment lever to be operated to a normal position in a case where the adjustment lever is operated in order to hold a steering wheel at an adjusted position, even when positions in the axial direction of a protruding engagement portion and a recessed engagement portion are shifted, and to prevent a locking mechanism from being damaged. [Solution] An outer side locking member **40** includes: a first element **51** at least a portion of which is supported so as to be movable toward and away from an inner side locking member **39**; a second element **52** that has a protruding engagement portion **65** and is supported such that the protruding engagement portion **65** is able to displace in an engagement-disengagement direction with respect to a recessed engagement portion **41** provided in the inner side locking member **39**; a first biasing member **53** that elastically biases at least a portion of the first element **51** in a direction away from the inner side locking member **39**; and a second biasing member **54** that elastically biases the second element **52** in a direction with respect to the engagement-disengagement direction such that the protruding engagement portion **65** is engaged with the recessed engagement portion **41**.

Inventors:	Koitabashi; Hiroto (Maebashi, JP), Manaka; Yuta (Maebashi, JP), Kakita; Hiroshi (Maebashi, JP), Mitsui; Rei (Maebashi, JP), Koujiya; Nobuhiro (Maebashi, JP)
Applicant:	NSK Steering & Control, Inc. (Tokyo, JP)
Family ID:	85507635
Assignee:	NSK STEERING & CONTROL, INC. (Tokyo, JP)
Appl. No.:	18/689489
Filed (or PCT Filed):	September 05, 2022
PCT No.:	PCT/JP2022/033301
PCT Pub. No.:	WO2023/038013
PCT Pub. Date:	March 16, 2023

Prior Publication Data

Document Identifier

US 20250018995 A1

Publication Date

Jan. 16, 2025

Foreign Application Priority Data

JP

2021-146989

Sep. 09, 2021

Publication Classification

Int. Cl.: B62D1/184 (20060101); B62D1/185 (20060101)

U.S. Cl.:

CPC B62D1/184 (20130101); B62D1/185 (20130101);

Field of Classification Search

CPC: B62D (1/18); B62D (1/185); B62D (1/184)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8991861	12/2014	Iwakawa	74/495	B62D 1/181
9126624	12/2014	Iwakawa	N/A	B62D 1/181
9254861	12/2015	Iwakawa	N/A	B62D 1/187
9409590	12/2015	Johta	N/A	B62D 1/184
9434403	12/2015	Johta	N/A	B62D 1/184
9637161	12/2016	Orihara	N/A	B62D 1/19
9669781	12/2016	Kakita	N/A	B60R 16/027
9688222	12/2016	Kakita	N/A	B60R 16/0231
9707910	12/2016	Kakita	N/A	B62D 1/187
9834245	12/2016	Orihara	N/A	B62D 1/19
10035479	12/2017	Orihara	N/A	B62D 1/192
10160475	12/2017	Uesaka	N/A	N/A
10919559	12/2020	Shiroishi	N/A	N/A
11440579	12/2021	Kakita	N/A	B62D 1/185
11919564	12/2023	Fevre	N/A	B62D 1/185
12128947	12/2023	Patki	N/A	B62D 1/187
2015/0069745	12/2014	Iwakawa	280/775	B62D 1/185
2015/0075316	12/2014	Iwakawa	74/493	B62D 1/189
2015/0090067	12/2014	Iwakawa	74/493	B62D 1/181
2015/0239490	12/2014	Sakata	74/493	B62D 1/189
2015/0344062	12/2014	Johta	74/493	B62D 1/195
2016/0016604	12/2015	Johta	74/493	B62D 1/195
2016/0280159	12/2015	Kakita	N/A	B60R 16/03

2016/0355208	12/2015	Orihara	N/A	B62D 1/185
2017/0057433	12/2016	Kakita	N/A	B60R 16/0231
2017/0072877	12/2016	Kakita	N/A	B62D 1/192
2017/0297607	12/2016	Orihara	N/A	B62D 1/192
2018/0001845	12/2017	Orihara	N/A	B62D 1/187
2018/0037250	12/2017	Kreutz et al.	N/A	N/A
2022/0001914	12/2021	Kakita	N/A	B62D 1/185
2022/0410962	12/2021	Fevre	N/A	B62D 1/185
2024/0343292	12/2023	Park	N/A	B62D 1/185
2025/0018995	12/2024	Koitabashi	N/A	B62D 1/184

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 075 629	12/2016	EP	N/A
2007-083936	12/2006	JP	N/A
2016-190522	12/2015	JP	N/A
2017-171196	12/2016	JP	N/A
2017-197007	12/2016	JP	N/A
2018-002056	12/2017	JP	N/A
2019-031290	12/2018	JP	N/A
2019034630	12/2018	JP	N/A
2019034631	12/2018	JP	N/A
2019-093737	12/2018	JP	N/A
2019116271	12/2018	JP	N/A
2019116272	12/2018	JP	N/A
2019142500	12/2018	JP	B60R 16/027

OTHER PUBLICATIONS

International Search Report for PCT/JP2022/033301 dated Nov. 15, 2022. cited by applicant

Primary Examiner: Dickson; Paul N

Assistant Examiner: Meshaka; Maxwell L

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage of International Application No. PCT/JP2022/033301 filed Sep. 5, 2022, claiming priority based on Japanese Patent Application No. 2021-146989 filed Sep. 9, 2021.

TECHNICAL FIELD

(2) The present disclosure relates to a steering column device for rotatably supporting a steering shaft that supports a steering wheel.

BACKGROUND ART

(3) FIG. 22 illustrates an example of a steering device for an automobile. A rotation of a steering wheel **100** is transmitted to an input shaft **102** of a steering gear unit **101**, and as an input shaft **102** rotates, a pair of left and right tie rods **103** are pushed and pulled, giving a steering angle to front

wheels. The steering wheel **100** is supported and fixed to a rear end portion of a steering shaft **104**, and the steering shaft **104** is inserted in an axial direction through an inside of a steering column **105** and is rotatably supported by the steering column **105**. A front end portion of the steering shaft **104** is connected to a rear end portion of an intermediate shaft **107** through a universal joint **106**, and a front end portion of the intermediate shaft **107** is connected to the input shaft **102** through another universal joint **108**.

(4) Some steering devices for automobiles include a tilt mechanism for adjusting an up-down position of the steering wheel **100** and a telescopic mechanism for adjusting a front-rear position according to a physique and a driving posture of a driver. To configure the tilt mechanism, the steering column **105** is supported with respect to a vehicle body **110** so as to pivotally displace around a pivot shaft **109** arranged in a width direction. Furthermore, an intermediate portion in the axial direction of the steering column **105** is supported by a fixed bracket **111** supported by the vehicle body **110** so as to displace in an up-down direction.

(5) In addition, in order to configure the telescopic mechanism, the steering column **105** is configured by combining an outer column **112** and an inner column **113** in a telescopic manner so as to allow relative displacement in the axial direction. Moreover, the steering shaft **104** is configured by combining an outer tube **114** and an inner shaft **115** through a spline engagement or the like to allow torque transmission and to allow relative displacement in the axial direction. Furthermore, the intermediate portion in the axial direction of the steering column **105** (outer column **112**) is supported by the fixed bracket **111** supported by the vehicle body **110** so as to displace in a front-rear direction.

(6) In a steering device that includes a tilt mechanism and/or a telescopic mechanism, except for an electric type, the position of the steering wheel **100**, based on an operation of an adjustment lever, can be adjusted between a state in which the position can be adjusted and a state in which the steering wheel **100** is held at the adjusted position.

(7) In JP 2007-083936 A, a steering device is described that, based on the operation of an adjustment lever, switches between a state in which the front-rear position of a steering wheel can be adjusted and a state in which the steering wheel is held at the adjusted position. In this steering device, by switching an engagement state between a tooth portion of a tooth member and a tooth portion of an inner column based on the operation of the adjustment lever, it is possible to switch between a state in which the front-rear position of the steering wheel can be adjusted and a state in which the steering wheel is held at the adjusted position.

(8) In JP 2016-190522 A, a locking means is described that, by switching an engagement state between an engaging protrusion of a locking member that is pivotally supported on an outer column and a locking hole in a locking plate that is supported on an inner column based on an operation of an adjustment lever, switches between a state in which a front-rear position of a steering wheel can be adjusted and a state in which the steering wheel is held at the adjusted position.

(9) The locking means includes a biasing spring that elastically biases the locking member in a direction such that the engaging protrusion engages with the locking hole. Therefore, in a case where the adjustment lever is operated to hold the steering wheel in the adjusted position, even in a case where a semi-locked state occurs in which the engaging protrusion and a portion of the locking plate that is deviated from the locking hole come into contact with each other, when the adjustment lever is further operated from the semi-locked state, the biasing spring will be elastically deformed, allowing rotation of the adjustment lever. Therefore, the adjustment lever can be reliably returned to the normal position while the steering wheel is held in the adjusted position, and damage to the locking member and the locking plate can be prevented.

CITATION LIST

Patent Literature

(10) Patent Literature 1: JP 2007-083936 A Patent Literature 2: JP 2016-190522 A

Technical Problem

(11) The steering device described in JP 2007-083936 A may have the following problems. That is, in a case where the adjustment lever is operated in order to hold the steering wheel at the adjusted position, a semi-locked state may occur in which a tip-end surface of a protruding portion of the tooth portion of the tooth member comes into contact with a tip-end surface of a protruding portion of the tooth portion of the inner column. When trying to operate the adjustment lever further from this semi-locked state, there is a possibility that the adjustment lever will not be able to be operated any further in the operating direction required to move the steering wheel to a state where the steering wheel can be held at the adjusted position (the force required for operation becomes excessive), or damage such as deformation may occur in the tooth portion of the tooth member and/or the tooth portion of the inner column.

(12) The structure described in JP 2016-190522 A avoids the above problem in the semi-locked state; however, in a case where a large axial force is applied to the inner column in a state in which the engaging protrusion and the locking hole are engaged with each other causing the engaging protrusion and the locking hole to become strongly engaged or stuck together, and an attempt is made to operate the adjustment lever to adjust the position of the steering wheel, a large force may be required or damage such as deformation may occur to the locking plate and/or the locking member.

(13) In view of the above-mentioned circumstances, an object of the technique according to the present disclosure is to achieve a structure of a steering column device that, in a case where the adjustment lever is operated in order to hold the steering wheel in the adjusted position, even when the positions in the axial direction of a protruding engagement portion and a recessed engagement portion of the locking mechanism are misaligned, the adjustment lever can be operated to the normal position, and it is possible to prevent damage to the locking mechanism.

Solution to Problem

(14) The steering column device according to an aspect of the present disclosure includes: a steering column including an inner column, and an outer column having a column-side through hole penetrating in a width direction, arranged on one side in an axial direction of the inner column, and externally fitted so as to displace relative to the inner column in the axial direction; an adjustment rod having a cam portion on an outer circumferential surface and inserted into the column-side through hole; an adjustment lever fixed to the adjustment rod and configured to rotate the adjustment rod; and a locking mechanism including an inner side locking member having a recessed engagement portion at a plurality of locations in the axial direction and provided on the inner column, and an outer side locking member having a protruding engagement portion capable of engaging with the recessed engagement portion.

(15) The outer side locking member includes: a first element, at least a portion of which is supported movably toward and away from the inner side locking member; a second element having the protruding engagement portion and supported such that the protruding engagement portion is able to displace in an engagement-disengagement direction with respect to the recessed engagement portion; a first biasing member elastically biasing at least a portion of the first element in a direction away from the inner side locking member; and a second biasing member elastically biasing the second element in a direction such that the protruding engagement portion is able to engage with the recessed engagement portion with respect to the engagement-disengagement direction.

(16) The cam portion, due to rotation of the adjustment rod in response to operation of the adjustment lever, presses the first element in a direction such that at least a portion of the first element approaches the inner side locking member.

(17) In the steering column device according to an aspect of the present disclosure, the first element may have a stopper portion that, in a state in which the protruding engagement portion is engaged

- with the recessed engagement portion, is configured to prevent the second element from being displaced with respect to the first element in a biasing direction by the second biasing member.
- (18) In the steering column device according to an aspect of the present disclosure, the outer side locking member may have a pivot shaft that is arranged in the width direction and is supported with respect to the outer column so that relative displacement in the axial direction and radial direction of the steering column is not possible, and the first element may be supported so as to pivot about the pivot shaft.
- (19) The second element may be supported so as to pivot about the pivot shaft.
- (20) The pivot shaft may be arranged at a position closer to the inner side locking member than the adjustment rod with respect to the radial direction of the steering column.
- (21) The second biasing member may be arranged on an opposite side of the pivot shaft with the adjustment rod therebetween with respect to the axial direction of the steering column.
- (22) The second biasing member may be configured by a compression coil spring.
- (23) The steering column device according to an aspect of the present disclosure may further include a coupling member configured to support the inner side locking member with respect to the inner column so as to detach due to an impact load accompanying a secondary collision.
- (24) The steering column device according to an aspect of the present disclosure may further include a guide surface portion that is inclined in a direction toward the one side in the axial direction as going outward in the radial direction on at least one of a surface of the one side in the axial direction of the recessed engagement portion and a tip-end surface of the protruding engagement portion.
- (25) The second element may have a shoulder portion at a portion located on the one side in the axial direction of the protruding engagement portion, the shoulder portion closely facing or coming in contact with a portion of the inner side locking member that is deviated in the axial direction from the recessed engagement portion in a state in which the protruding engagement portion is engaged with the recessed engagement portion

Effect of Invention

- (26) With the steering column device according to an aspect of the present disclosure, in a case where the adjustment lever is operated in order to hold the steering wheel at the adjusted position, even when the positions in the axial direction of the protruding engagement portion and the recessed engagement portion of the locking mechanism are shifted, the adjustment lever can be operated to the normal position, and it is possible to prevent the locking mechanism from being damaged.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a perspective view, as viewed from the rear and above, of a steering column device according to a first example of an embodiment according to the present disclosure.
- (2) FIG. 2 is a perspective view of the steering column device of the first example, as viewed from the rear and below.
- (3) FIG. 3 is a plan view of the steering column device of the first example.
- (4) FIG. 4 is a bottom view of the steering column device of the first example.
- (5) FIG. 5 is a side view of the steering column device of the first example.
- (6) FIG. 6 is a cross-sectional view taken along line A-A in FIG. 4.
- (7) FIG. 7 is a cross-sectional view taken along line B-B in FIG. 4.
- (8) FIG. 8 is a cross-sectional view taken along line C-C in FIG. 6.
- (9) FIG. 9 is a cross-sectional view taken along line D-D in FIG. 6.
- (10) FIG. 10 is a cross-sectional view taken along line E-E in FIG. 6.

- (11) FIG. **11** is an enlarged view of section F in FIG. **6**, and illustrates an unlocked state.
- (12) FIG. **11** is an enlarged view of section F in FIG. **6**, and illustrates a locked state.
- (13) FIG. **13** is an enlarged view of section F in FIG. **6**, and illustrates a semi-locked state.
- (14) FIG. **14** is an enlarged view of section G in FIG. **7**, and illustrates an unlocked state.
- (15) FIG. **15** is an enlarged view of section G in FIG. **7**, and illustrates a locked or semi-locked state.
- (16) FIG. **16** is an enlarged view of section G in FIG. **7**, and illustrates the unlocked state in which the protruding engagement portion and the recessed engagement portion are fixed.
- (17) FIG. **17** is an exploded perspective view of the steering column device of the first example.
- (18) FIG. **18** is an exploded perspective view of an outer side locking member of the steering column device of the first example.
- (19) FIG. **19** is an exploded perspective view of an outer column, an adjustment rod, and an outer side locking member of the steering column device of the first example.
- (20) FIG. **20** is a cross-sectional view of the steering column device of the first example in a state where a secondary collision has occurred.
- (21) FIG. **21** is a view corresponding to FIG. **11** of a steering column device of a second example of an embodiment according to the present disclosure.
- (22) FIG. **22** is a partial cutaway side view illustrating an example of a conventional steering device.

DESCRIPTION OF EMBODIMENTS

(23) Hereinafter, a steering column device of an embodiment according to the present disclosure will be described with reference to the drawings; however, the following description merely describes one example, and the content according to the present disclosure is not limited to the following exemplary configuration. In addition, it is also possible to use known alternative members for each of the elements of the steering column device.

First Example

(24) FIG. **1** to FIG. **20** illustrate a steering column device according of a first example of an embodiment according to the present disclosure. The steering column device **1** of this example includes a steering column **2**, an adjustment rod **3**, an adjustment lever **4**, and a locking mechanism **5**. In the following description, unless otherwise specified, the front-rear direction, the up-down direction, and the width direction refer to the front-rear direction, the up-down direction, and the width direction of a vehicle body when the steering column device **1** is attached to the vehicle body. Moreover, unless otherwise specified, the axial direction and the radial direction refer to the axial direction and the radial direction of the steering column **2**. In the present example, the front side corresponds to one side in the axial direction, and the rear side corresponds to the other side in the axial direction.

(25) The steering column **2** includes an inner column **6**, and an outer column **7** having a column-side through hole **9** passing through in the width direction, and that is arranged on one side in the axial direction of the inner column **6**, and is externally fitted so as to displace in the axial direction relative to the inner column **6**. That is, the steering column **2** is configured by combining the inner column **6** and the outer column **7** such that the entire length thereof can be expanded and contracted. In the present example, the inner column **6** is arranged on the rear side, and the outer column **7** is arranged on the front side. More specifically, the steering column **2** is configured by externally fitting a rear portion of the outer column **7** onto a front portion of the inner column **6** so as to allow relative displacement in the axial direction.

(26) The inner column **6** has a cylindrical shape. In the present example, the inner column **6** has a coupling hole **8** at two positions spaced apart in the axial direction on a lower surface thereof for connecting and fixing an inner side locking member **39** to the inner column **6** so as to be detachable by an impact load caused by a secondary collision.

(27) The outer column **7** includes a column main body **10**, a pair of held portions **11**, and a front

support bracket **12**.

(28) The column main body **10** has a substantially cylindrical shape. In addition, the column main body **10** also has a slit **13** extending in the axial direction on a lower surface of the rear portion. A rear end portion of the slit **13** is open to a rear end surface of the column main body **10**.

(29) The pair of held portions **11** are fixedly provided on the lower surface of the column main body **10** at a portion that sandwiches the slit **13** from both sides in the width direction (both sides in the circumferential direction of the column main body **10**). Each held portion **11** has a column-side through hole **9** passing through in the width direction. In the present example, the column-side through hole **9** is configured by a circular hole.

(30) The front support bracket **12** is fixed to an upper surface of the front end portion of the column main body **10**. The front support bracket **12** has a pivot hole **14** passing through in the width direction.

(31) A steering shaft **15** is rotatably supported inside the steering column **2**. The steering shaft **15** is formed by combining an upper shaft **16** and a lower shaft **17** through a spline engagement or the like so that torque can be transmitted and the entire length can be expanded and contracted. The upper shaft **16** is rotatably supported inside the inner column **6** by a radial rolling bearing **18a**, and the lower shaft **17** is rotatably supported inside the outer column **7** by another radial rolling bearing **18b**. A steering wheel (not illustrated) is supported by and fixed to a rear end portion of the steering shaft **15**, that is, a rear end portion of the upper shaft **16**. In addition, a front end portion of the steering shaft **15**, that is, a front end portion of the lower shaft **17**, is connected to an input shaft of a steering gear unit through an intermediate shaft and a universal joint.

(32) A front end portion of the steering column **2**, that is, a front end portion of the outer column **7**, is supported by the vehicle body so as to pivotally displace around a tilt shaft inserted through the pivot hole **14**.

(33) An intermediate portion of the steering column **2**, that is, a rear portion of the outer column **7** is supported so as to displace in the up-down direction with respect to a vehicle body side bracket **19** that is supported by and fixed to the vehicle body. The vehicle body side bracket **19** has a mounting plate portion **20** and a pair of support plate portions **21a**, **21b**.

(34) The mounting plate portion **20** has mounting holes **22** that penetrate in the up-down direction at two positions spaced separated in the width direction, and is supported by and fixed to the vehicle body by bolts inserted through the mounting holes **22**.

(35) The pair of support plate portions **21a**, **21b** hang downward from two positions in the width direction on a lower surface of the mounting plate portion **20**, and are arranged so as to hold the pair of held portions **11** of the outer column **7** from both sides in the width direction. The pair of support plate portions **21a**, **21b** have elongated tilt holes **23a**, **23b** extending in the up-down direction at mutually aligned portions. In the present example, the elongated tilt holes **23a**, **23b** have a partially arc-shaped opening shape centered on a tilt shaft.

(36) The adjustment rod **3** has a cam portion **24** on the outer circumferential surface of an intermediate portion in the axial direction (intermediate portion in the width direction) of the adjustment rod **3**, and is inserted in the width direction through the column-side through hole **9** provided in the outer column **7** and the elongated tilt holes **23a**, **23b** provided in the pair of support plate portions **21a**, **21b**. In the present example, the adjustment rod **3** includes a rod main body **25** and a cam member **26**.

(37) The rod main body **25** has a head portion **27** and a shaft portion **28**.

(38) The shaft portion **28** has a non-circular cross-sectional shape. More specifically, in the present example, the shaft portion **28** has a width across flats shape.

(39) The cam member **26** includes a pair of arm portions **29** each having a substantially arrow shape, and a connecting portion **30** that connects the base end portions of the pair of arm portions **29** to each other. The pair of arm portions **29** have fitting holes **31** in mutually aligned portions into which the shaft portion **28** of the rod main body **25** is externally fitted without looseness. The cam

portion **24** is configured by tip end portions (upper end portions) of the pair of arm portions **29** of the cam member **26**.

(40) The shaft portion **28** of the rod main body **25** of the adjustment rod **3** is inserted into the column-side through hole **9** provided in the outer column **7** and the elongated tilt holes **23a**, **23b** provided in the pair of support plate portions **21a**, **21b** from one side in the width direction (lower side in FIG. **3**, upper side in FIG. **4**, left side in FIG. **8** to FIG. **10**), and a nut **32** is screwed onto the tip portion (the end portion on the other side in the width direction) of the shaft portion **28**. A thrust bearing **33** and a washer **34** are arranged around the shaft portion **28** between the support plate portion **21b** on the other side in the width direction (the upper side in FIG. **3**, the lower side in FIG. **4**, the right side in FIG. **8** to FIG. **10**) of the pair of support plate portions **21a**, **21b** and the nut **32**, in order from the nut **32** side.

(41) The steering column device **1** of the present example includes a pair of pressing portions **35a**, **35b** around the adjustment rod **3** and at positions sandwiching the pair of support plate portions **21a**, **21b** from both sides in the width direction, and an expansion/contraction mechanism **36** around the adjustment rod **3** that expands/contracts a distance between the pair of pressing portions **35a**, **35b**. The steering column device **1**, based on an operation of the adjustment lever **4**, expands or contracts the distance between the pair of pressing portions **35a**, **35b** by the expansion/contraction mechanism **36**, and by switching the engagement state of the locking mechanism **5**, is configured to switch between a state in which the front-rear position and the up-down position of the steering wheel supported by and fixed to the rear end of the steering shaft **15** can be adjusted, and a state in which the steering wheel is held at the adjusted position.

(42) The expansion/contraction mechanism **36** is configured by a cam device including a driven cam **37** and a driving cam **38**.

(43) The driven cam **37**, on a surface on the one side in the width direction, has a driven cam surface that is an uneven surface in the circumferential direction, and is externally fitted onto the adjustment rod **3** so as to rotate and displace (displace in the axial direction of the adjustment rod **3**) relative to the adjustment rod **3**. In addition, the driven cam **37** engages a protruding engagement portion provided at a portion on the other side in the width direction with the elongated tilt hole **23a** provided in the support plate portion **21a** of the pair of support plate portions **21a**, **21b** that is on the one side in the width direction so as to displace only along the elongated tilt hole **23a**.

(44) The driving cam **38** has a driving cam surface that is an uneven surface in the circumferential direction on a surface on the other side in the width direction facing the driven cam surface of the driven cam **37**, and is externally fitted and fixed to the adjustment rod **3** so as to be unable to rotate or displace in the width direction relative to the adjustment rod **3**.

(45) The adjustment lever **4** is fixed to the adjustment rod **3** and has the function of rotating the adjustment rod **3**. More specifically, a base end portion of the adjustment lever **4** is coupled and fixed to the driving cam **38** that is externally fitted and fixed to the adjustment rod **3**. Therefore, when the adjustment lever **4** is operated, the adjustment rod **3** and the driving cam **38** rotate around a central axis of the adjustment rod **3**.

(46) By operating the adjustment lever **4** to expand or contract the dimension in the axial direction of the expansion/contraction mechanism **36**, that is, the dimension in the width direction of the vehicle body, and expand or contract the distance between the driven cam **37** and the washer **34**, the distance between the pair of support plate portions **21a**, **21b** can be expanded or contracted. In other words, the driven cam **37** forms the pressing portion **35a** on the one side in the width direction, and the washer **34** forms the pressing portion **35b** on the other side in the width direction.

(47) The locking mechanism **5** has an inner side locking member **39** and an outer side locking member **40**.

(48) The inner side locking member **39** has a recessed engagement portion **41** at a plurality of locations in the axial direction, and is provided in the inner column **6**. More specifically, the inner side locking member **39** has a substantially rectangular plate-shaped base plate portion **42**

extending in the axial direction, and a bent plate portion **43** bent outward (downward) in the radial direction from the front end portion of the base plate portion **42**.

(49) The base plate portion **42** has the recessed engagement portion **41** at multiple locations in the axial direction, the respective engagement portion **41** being configured by a substantially long rectangular hole that penetrates in the plate thickness direction (up-down direction) and whose opening shape extends in the width direction. The recessed engagement portion **41** has an inner-side guide surface portion **44** on a lower portion of a front side surface that is inclined in a direction toward the front as going downward, and has an inner-side flat surface portion **75** orthogonal to the central axis of the inner column **6** on a rear side surface. The base plate portion **42** has coupling holes **45** penetrating in the plate thickness direction at a portion farther on the front side and at a portion farther on the rear side than the portion where the recessed engagement portions **41** are provided.

(50) The bent plate portion **43** has a through hole **46** penetrating in the plate thickness direction (front-rear direction).

(51) The inner side locking member **39** is supported by the inner column **6** by a coupling member **47** so as to detach based on an impact load applied due to a secondary collision. More specifically, the coupling member **47** is press-fitted or inserted so as to span between a coupling hole **8** provided in a lower surface of the inner column **6** and a coupling hole **45** provided in the inner side locking member **39**. The coupling member **47** is made of synthetic resin, light alloy, steel, or the like, and breaks due to an impact load applied during a secondary collision.

(52) In the present example, by pressing fitting a pin portion **49** provided on a damper **48** made of an elastic material such as an elastomer including rubber into a through hole **46** of the bent plate portion **43** from the front side, the damper **48** is supported by and fixed to a front end portion of the inner side locking member **39**. Therefore, when the steering wheel is moved to a front end position of an adjustable range of the steering wheel, a front end surface of the damper **48** comes into contact with a front end surface (deep end portion) of the slit **13** of the outer column **7**. As a result, when the steering wheel is moved to a front end position of the adjustable range, the inner column **6** or a metal member supported by the inner column **6** and the outer column **7** or a metal member supported by the outer column **7** are prevented from a direct collision (metal contact).

(53) The outer side locking member **40** has a protruding engagement portion **65** that can engage with the recessed engagement portion **41**. More specifically, the outer side locking member **40** is configured by: a first element **51** at least a portion of which is supported so as to be movable toward and away from the inner side locking member **39**; a second element **52** that has the protruding engagement portion **65** and is supported such that the protruding engagement portion **65** is able to displace in the engagement-disengagement direction with respect to the recessed engagement portion **41**; a first biasing member **53** that elastically biases at least a portion of the first element **51** in a direction away from the inner side locking member **39**; and a second biasing member **54** that elastically biases the second element **52** in a direction such that the protruding engagement portion **65** is engaged with the recessed engagement portion **41** with respect to the engagement-disengagement direction.

(54) In the present example, the outer side locking member **40** includes a pivot shaft **50** as an element for enabling the first element **51** to move toward or away from the inner side locking member **39**, and for enabling the second element **52** to be displaced in the engagement-disengagement direction. The pivot shaft **50** is arranged in the width direction, and is supported by the outer column **7** so as not to displace relative to the outer column **7** in the axial direction and the radial direction (front-rear direction and up-down direction). The pivot shaft **50** has a cylindrical shape, and end portions on both sides in the width direction of the pivot shaft **50** (end portions on both sides in the axial direction of the pivot shaft **50**) are internally fitted into support holes **55** of the pair of held portions **11** that penetrate in the width direction at a portion on the front and upper side of the column-side through hole **9**. In the present example, by press fitting, an end portion on

the one side in the width direction of the pivot shaft **50** into the support hole **55** provided in the held portion **11** on the one side in the width direction, and by inserting (internally fitting with a clearance fit) an end portion on the other side in the width direction of the pivot shaft **50** into the support hole **55** provided in the held portion **11** on the other side in the width direction, the pivot shaft **50** is supported by the outer column **7**.

(55) The first element **51** is supported by the pivot shaft **50** so as to pivot about the pivot shaft **50**. In the present example, the first element **51** is configured in a substantially rectangular box shape and includes a pair of side plate portions **56**, a connecting plate portion **57**, and an end plate portion **58**.

(56) The pair of side plate portions **56** are arranged parallel to each other and spaced apart from each other in the width direction. The side plate portions **56** have through holes **59** penetrating in the plate thickness direction (width direction) in the respective substantially central portions aligned with each other, and have support holes **60** penetrating in the plate thickness direction at portions aligned with each other on the front and upper side of the through holes **59**. The side plate portions **56** have cylindrical portions **61** that protrude outward in the width direction from portions of outer side surfaces in the width direction surrounding the support holes **60**. The inner circumferential surface of the support hole **60** and the inner circumferential surfaces of the cylindrical portions **61** are configured by the same cylindrical surface. Furthermore, the side plate portions **56** have locking pieces **62** that protrude outward in the width direction from intermediate portions in the front-rear direction of the upper end portions.

(57) The connecting plate portion **57** connects the lower end portions of the pair of side plate portions **56**. The connecting plate portion **57** has a spring locking portion **63** having a partially cylindrical shape that protrudes upward from a rear portion of the upper side surface.

(58) The end plate portion **58** connects the rear end portions of the pair of side plate portions **56**. A lower end portion of the end plate portion **58** is connected to a rear end portion of the connecting plate portion **57**. The end plate portion **58** has a rectangular hole **64** approximately in a central portion thereof that penetrates in the plate thickness direction (front-rear direction).

(59) The first element **51** is supported by the outer column **7** so as to pivot about the pivot shaft **50** by internally fitting the pivot shaft **50** into the support hole **60** and the cylindrical portion **61** without looseness. In this state, the rear portion of the first element **51** is able to move toward and away from the inner side locking member **39**. The adjustment rod **3** is inserted through the through holes **59** provided in the pair of side plate portions **56** so as to rotate relative to the first element **51**.

(60) The protruding engagement portion **65** that is able to engage with the recessed engagement portions **41** of the inner side locking member **39** is provided on the second element **52**. The second element **52** is supported by the outer column **7** so that the protruding engagement portion **65** is able to displace in the engagement-disengagement direction with respect to the recessed engagement portions **41**. More specifically, the second element **52** has a support hole **66** penetrating in the width direction at a base end portion (front end portion), and has the protruding engagement portion **65** at an upper end portion of a portion on the tip end side (rear portion). The protruding engagement portion **65** has an outer guide surface portion **67** on the tip end surface (upper side surface) that is inclined downward as going toward the front side, and has an outer side flat surface portion **76** on the rear side surface thereof, which is substantially orthogonal to the central axis of the inner column **6** in a state in which the protruding engagement portion **65** and the recessed engagement portion **41** are engaged.

(61) The second element **52**, at a portion located on the one side in the axial direction of the protruding engagement portion **65**, more specifically, at a portion of the upper side surface located on the front side of the protruding engagement portion **65**, has a shoulder portion **77** that, in a state in which the protruding engagement portion **65** and the recessed engagement portion **41** are engaged, closely faces or comes in contact with a portion of the inner side locking member **39** that is deviated in the axial direction from the recessed engagement portion **41**, more specifically, a

portion of the lower side surface of the base plate portion **42** of the inner side locking member **39** that is deviated in the axial direction from the recessed engagement portion **41**. Furthermore, the second element **52**, on a lower side surface of a portion on the tip end side, has a spring locking portion **68** having a cylindrical shape that protrudes downward, and, at the tip end portion (rear end portion), has a stopper piece **69** that protrudes toward the rear.

(62) The second element **52**, by the pivot shaft **50** being internally fitted inside the support hole **66** without looseness, is supported so as to pivot about the pivot shaft **50**. In this state, the stopper piece **69** of the second element **52** is arranged inside the rectangular hole **64** of the first element **51**.

(63) The first element **51** has a stopper portion that, in a state in which the protruding engagement portion **65** is engaged with the recessed engagement portion **41**, prevents the second element **52** from being displaced with respect to the first element **51** in the biasing direction by the second biasing member **54**. More specifically, when the second element **52** pivots upward with respect to the first element **51**, an upper side surface of the stopper piece **69** of the second element **52** comes in contact with an upper side surface (surface facing downward) of the rectangular hole **64** of the first element **51**, and the second element **52** is prevented from pivoting further upward with respect to the first element **51**. That is, the upper side surface of the rectangular hole **64** of the first element **51** forms a stopper portion.

(64) A first biasing member **53** elastically biases a rear portion of the first element **51** in a direction away from the inner side locking member **39**. The first biasing member **53** is configured by bending and forming an elastic metal wire. The first biasing member **53** has a base portion **70**, a pair of extending arm portions **71**, a pair of folded portions **72**, and a pair of locking arm portions **73**.

(65) The base portion **70** extends in the width direction.

(66) The pair of extending arm portions **71** are bent toward the front from end portions on both sides in the width direction of the base portion **70**, and are bent into a substantially S-shape (substantially crank-shape) when viewed from the side.

(67) The pair of folded portions **72** are folded upward and toward the rear from the tip end portions (front end portions) of the extending arm portions **71** in a substantially U-shape.

(68) The pair of locking arm portions **73** extend toward the rear from an upper end portion of the folded portions **72**, and have bent portions **74** bent downward at the tip end portions (rear end portions).

(69) The first biasing member **53** causes the pair of extending arm portions **71** to elastically come in contact with the lower side surface of the adjustment rod **3**, and also causes the pair of locking arm portions **73** to elastically come in contact with the upper side surfaces of the locking pieces **62** of the first element **51**. In this state, the base portion **70** is arranged on the rear side of the end plate portion **58** of the first element **51**, and the pair of folded portions **72** are arranged on the front side of the cylindrical portions **61**. The first biasing member **53**, by a force acting to elastically restore the pair of extending arm portions **71** and the pair of locking arm portions **73** in a direction toward each other, elastically presses the locking pieces **62** of the first element **51** downward. Thus, the first biasing member **53** elastically biases the portion on the rear side of the first element **51** in a direction away from the inner side locking member **39**.

(70) The second biasing member **54**, with respect to the engagement-disengagement direction of the protruding engagement portion **65** with regards to the recessed engagement portion **41** of the inner side locking member **39**, elastically biases the second element **52** in a direction causing the protruding engagement portion **65** to engage with the recessed engagement portion **41**. The second biasing member **54** is configured by a compression coil spring that has substantially linear spring characteristics and whose initial load can be easily adjusted. The second biasing member **54** is elastically held between an upper side surface of the connecting plate portion **57** of the first element **51** and a lower side surface of a tip-end portion of the second element **52**. That is, of the second biasing member **54**, a lower end portion is locked to the spring locking portion **63** provided on the

connecting plate portion **57** (the spring locking portion **63** is inserted into the lower end portion), and an upper end portion is locked to the spring locking portion **68** provided on the lower surface of the portion on the tip end side of the second element **52** (the spring locking portion **68** is inserted into the upper end portion). Thus, the tip-end portion of the second element **52** is elastically biased upward.

(71) The second biasing member **54** is arranged on the opposite side of the pivot shaft **50** across from the adjustment rod **3** in the axial direction. That is, the second biasing member **54** is arranged farther on the rear side than the adjustment rod **3**, and the pivot shaft **50** is arranged farther on the front side than the adjustment rod **3**.

(72) In the steering column device **1** of the present example, when adjusting the up-down and/or front-rear positions of the steering wheel, the locking mechanism **5**, based on operating the adjustment lever **4** in a predetermined direction (clockwise in the example of FIG. 5), is brought into the unlocked state, and the pair of pressing portions **35a**, **35b** become unclamped by widening the distance therebetween.

(73) That is, by operating the adjustment lever **4** in a predetermined direction, the cam member **26** of the adjustment rod **3** is pivoted from a state illustrated in FIG. 15 to a state illustrated in FIG. 14, and the cam portion **24** releases the force that presses the locking pieces **62** of the first element **51** upward. As a result, the locking pieces **62** are elastically pressed downward by the elastic restoring force of the first biasing member **53**, and the first element **51** pivots about the pivot shaft **50** in a direction in which the rear portion of the first element **51** moves away from the inner side locking member **39**, that is, clockwise in FIGS. 14 and 15. Therefore, the upper side surface of the rectangular hole **64** of the first element **51** presses the upper side surface of the stopper piece **69** of the second element **52** downward. As a result, by the second element **52** pivoting in a clockwise direction in FIG. 11 and FIG. 12 from a state illustrated in FIG. 12 to a state illustrated in FIG. 11, the protruding engagement portion **65** and the recessed engagement portion **41** become disengaged.

(74) By operating the adjustment lever **4** in a predetermined direction, the driving cam **38** of the expansion/contraction mechanism **36** is rotated, and protruding portions of a driving cam surface of the driving cam **38** and protruding portions of the driven cam surface of the driven cam **37** are alternately arranged. Thus, the dimension in the axial direction of the expansion/contraction mechanism **36** is reduced, the distance between the pair of pressing portions **35a**, **35b** (driven cam **37** and washer **34**) is increased, and an unclamped state is established. As a result, contact pressure between inner surfaces in the width direction of the pair of support plate portions **21a**, **21b** and the outer surfaces in the width direction of the pair of held portions **11** is reduced or lost, and the inner diameter of a rear portion of the outer column **7** expands elastically, and the contact pressure between the outer circumferential surface of the front portion of the inner column **6** and the inner circumferential surface of the rear portion of the outer column **7** decreases.

(75) In this manner, when the locking mechanism **5** is set to the unlocked state and the pair of pressing portions **35a**, **35b** are set to the unclamped state with the distance therebetween widened, it becomes possible to adjust the front-rear position and the up-down position of the steering wheel.

(76) In the present example, a front end position of the adjustable range of the steering wheel is regulated by contact between a front side surface of the damper **48** supported by the front end portion of the inner side locking member **39** and the front end portion (deep end portion) of the slit **13** provided in the outer column **7**. That is, when the steering wheel is moved to the front end position of the adjustable range, the front side surface of the damper **48** and the front end portion of the slit **13** come into contact. On the other hand, the rear end position of the adjustable range of the steering wheel is regulated by contact between the rear end surface of a pair of lateral bent portions **78** that are bent downward from portions on both sides in the width direction of the front end portion of the base plate portion **42** of the inner side locking member **39** and front side surface of the cylindrical portion **61** of first element **51**. That is, when the steering wheel is moved to the rear end position of the adjustable range, the rear end surface of the pair of lateral bent portions **78** of

the inner side locking member **39** and the front side surface of the cylindrical portion **61** of the first element **51** come into contact.

(77) The up-down position of the steering wheel can be adjusted within a range in which the adjustment rod **3** can move inside the elongated tilt holes **23a**, **23b** provided in the pair of support plate portions **21a**, **21b**. That is, when the steering wheel is moved to the upper end position of the adjustable range, the upper end portion of the elongated tilt hole **23a** provided in the support plate portion **21a** on the one side in the width direction and the upper side surface of the protruding engagement portion of the driven cam **37** externally fitted onto the shaft portion **28** come into contact, and the upper end portion of the elongated tilt hole **23b** provided in the support plate portion **21b** on the other side in the width direction and the upper side surface of the shaft portion **28** come into contact. On the other hand, when the steering wheel is moved to the lower end position of the adjustable range, the lower end position of the elongated tilt hole **23a** provided in the support plate portion **21a** on the one side in the width direction and the lower side surface of the protruding engagement portion of the driven cam **37** externally fitted onto the shaft portion **28** come into contact, and the lower end portion of the elongated tilt hole **23b** provided in the support plate portion **21b** on the other side in the width direction and the lower side surface of the shaft portion **28** come into contact.

(78) After moving the steering wheel to a desired position, the locking mechanism **5** is set to a locked state by operating the adjustment lever **4** in a direction opposite to a predetermined direction (counterclockwise in the example of FIG. 5), and a clamped state is set in which the distance between the pair of pressing portions **35a**, **35b** is reduced.

(79) That is, by operating the adjustment lever **4** in the opposite direction to the predetermined direction in order to cause the cam member **26** of the adjustment rod **3** to pivot from the state illustrated in FIG. 14 to the state illustrated in FIG. 15, the cam portion **24** presses the locking pieces **62** of the first element **51** upward. As a result, the first element **51** pivots against the clastic restoring force of the first biasing member **53** about the pivot shaft **50** in a direction in which the rear portion of the first element **51** approaches the inner side locking member **39**, that is, counterclockwise direction in FIG. 14 and FIG. 15. Furthermore, by the tip-end portion of the second element **52** being pressed upward by the first element **51** through the second biasing member **54**, the second element **52** pivots in the counterclockwise direction in FIG. 11 and FIG. 12 from the state illustrated in FIG. 11 to the state illustrated in FIG. 12, and the protruding engagement portion **65** and the recessed engagement portion **41** engage with each other. As a result, displacement in the axial direction of the inner column **6** with respect to the outer column **7** is prevented.

(80) By operating the adjustment lever **4** in the opposite direction to the predetermined direction, the driving cam **38** of the expansion/contraction mechanism **36** is rotated, and the tip-end surface of the protruding portion of the driving cam surface of the driving cam **38** and the tip-end surface of the protruding portion of the driven cam surface of the driven cam **37** come in contact with each other. As a result, the dimension in the axial direction of the expansion/contraction mechanism **36** is expanded, and the distance between the pair of pressing portions **35a**, **35b** (driven cam **37** and washer **34**) is shortened, setting a clamped state. As a result, contact pressure between inner surfaces in the width direction of the pair of support plate portions **21a**, **21b** and the outer surfaces in the width direction of the pair of held portions **11** is increased, and the inner diameter of a rear portion of the outer column **7** contracts elastically, and the contact pressure between the outer circumferential surface of the front portion of the inner column **6** and the inner circumferential surface of the rear portion of the outer column **7** increases. As a result, displacement in the up-down direction of the outer column **7** with respect to the vehicle body side bracket **19** is prevented, and displacement in the axial direction of the inner column **6** with respect to the outer column **7** is prevented, so that the steering wheel is held at the adjusted position.

(81) In the steering column device **1** of the present example, in the event of a collision accident,

when a secondary collision occurs in which the driver's body collides with the steering wheel, and an impact load in the forward direction is applied from the steering wheel to the inner column **6** through the upper shaft **16**, as illustrated in FIG. **6**, the coupling member **47** that spans the inner column **6** and the inner side locking member **39** shears as illustrated in FIG. **20**. As a result, the steering wheel supported by the inner column **6** through the inner column **6** and the upper shaft **16** is allowed to displace forward, and the impact load applied to the driver's body is alleviated.

(82) With the steering column device **1** of the present example, in a case where the adjustment lever **4** is operated in order to hold the steering wheel at the adjusted position, even when the positions in the axial direction of the protruding engagement portion **65** and the recessed engagement portion **41** are shifted, the adjustment lever **4** can be operated to the normal position, and it is possible to prevent the locking mechanism **5** from being damaged. The reason for this will be explained in the following.

(83) In the steering column device **1**, when the adjustment lever **4** is operated in the opposite direction to the predetermined direction in order to hold the steering wheel at the adjusted position, the tip-end surface of the protruding engagement portion **65** of the outer side locking member **40** and a portion of the lower side surface of the base plate portion **42** of the inner side locking member **39** that is deviated in the axial direction from the recessed engagement portion **41** may come in contact. In the steering column device **1** of the present example, when the adjustment lever **4** is further operated in the opposite direction to the predetermined direction from this state, the second element **52** having the protruding engagement portion **65** remains at the same position without pivoting, and the first element **51** pivots in the counterclockwise direction in FIG. **13** about the pivot shaft **50** while causing the second biasing member **54** to elastically deform (elastically contract).

(84) Therefore, even when attempting to further operate the adjustment lever **4** in the opposite direction to the predetermined direction from a state of contact between the tip-end surface of the protruding engagement portion **65** and a portion of the lower side surface of the base plate portion **42** that is deviated in the axial direction from the recessed engagement portion **41**, the force required to operate the adjustment lever **4** can be prevented from becoming excessive, and the contact pressure between the protruding engagement portion **65** and the lower side surface of the base plate portion **42** can be prevented from becoming excessive. Therefore, damage such as deformation of the inner side locking member **39** and/or the outer side locking member **40** can be prevented. Thus, the adjustment lever **4** can be operated to the normal position with the steering wheel held at the adjusted position, that is, the adjustment lever **4** can be operated to the end position in the opposite direction to the predetermined direction within the operable range.

(85) When, in a state in which the positions in the axial direction of the protruding engagement portion **65** and the recessed engagement portion **41** are shifted, the adjustment lever **4** is operated to the normal position with the steering wheel held in the adjusted position, the locking mechanism **5** is set to the semi-locked state as illustrated in FIG. **13**. In the semi-locked state, the tip-end surface of the protruding engagement portion **65** and the portion of the lower surface of the base plate portion **42** that is deviated in the axial direction from the recessed engagement portion **41** are in contact with each other, and the first element **51** is in the same position as the first element **51** in the locked state illustrated in FIG. **12**.

(86) In a state in which the locking mechanism **5** is in the semi-locked state, for example, when the inner column **6** is slightly displaced forward with respect to the outer column **7** due to an impact load associated with a secondary collision, and the position in the axial direction of the protruding engagement portion **65** matches the position in the axial direction of the recessed engagement portion **41**, the tip-end portion of the second element **52** is elastically pressed upward due to the elasticity of the second biasing member **54**, and the protruding engagement portion **65** engages with the recessed engagement portion **41**. As a result, the locking mechanism **5** is set to a locked state as illustrated in FIG. **12**. Therefore, even in a case where the locking mechanism **5** is in the

semi-locked state, by the coupling member **47** shearing in the event that a secondary collision occurs, the steering wheel supported by the inner column **6** is allowed to displace forward through the inner column **6** and the upper shaft **16**, and the impact load applied to the driver's body can be alleviated.

(87) In the steering column device **1** of the present example, in a state in which the recessed engagement portion **41** and the protruding engagement portion **65** are engaged, even in a case where the recessed engagement portion **41** and the protruding engagement portion **65** are strongly engaged or stuck together due to a large axial force or the like being applied to the inner column **6**, it is possible to prevent damage such as deformation to the locking mechanism **5** from occurring. In other words, in a state in which the recessed engagement portion **41** and the protruding engagement portion **65** are strongly engaged or stuck together, when the adjustment lever **4** is operated in a predetermined direction in order to adjust the position of the steering wheel, the cam member **26** of the adjustment rod **3** pivots from the state illustrated in FIG. **15** to the state illustrated in FIG. **16**. On the other hand, the first element **51** of the outer side locking member **40** remains in the same position while causing the pair of extending arm portions **71** and the pair of locking arm portions **73** of the first biasing member **53** to elastically deform in a directions away from each other. Therefore, even in a state in which the recessed engagement portion **41** and the protruding engagement portion **65** are strongly engaged or stuck together, it is possible to prevent the force for operating the adjustment lever **4** from becoming excessively large, and it is possible to prevent damage such as deformation to the locking mechanism **5** due to large force being applied when the recessed engagement portion **41** and the protruding engagement portion **65** are disengaged.

(88) Even in a case where the recessed engagement portion **41** and the protruding engagement portion **65** are strongly engaged or stuck together, when the steering wheel is moved slightly toward the front or rear after operating the adjustment lever **4** in the predetermined direction, the locking pieces **62** are elastically pressed downward by the elastic restoring force of the first biasing member **53**, and the first element **51** pivots in the clockwise direction in FIG. **16** about the pivot shaft **50**, making it possible to release the engagement or fixation of the recessed engagement portion **41** and the protruding engagement portion **65**. This allows the front-rear position of the steering wheel to be adjusted.

(89) In the present example, the recessed engagement portion **41** has an inner guide surface portion **44** on the portion on the lower side of the front side surface that inclines downward as going toward the front, and the protruding engagement portion **65** has an outer guide surface portion **67** on the tip-end surface (upper side surface) that inclines downward as going toward the front. Therefore, in a case where the inner column **6** is slightly displaced forward with respect to the outer column **7** from a state in which the tip-end surface of the protruding engagement portion **65** and the portion of the lower surface of the base plate portion **42** that is deviated in the axial direction from the recessed engagement portion **41** are in contact with each other, the protruding engagement portion **65** can be guided inside the recessed engagement portion **41** by the inner guide surface portion **44** and the outer guide surface portion **67**.

(90) In the present example, by arranging the second biasing member **54** on the opposite side of the pivot shaft **50** across from the adjustment rod **3** in the axial direction, the distance between the pivot shaft **50**, which is the center of pivoting of the second element **52** and the portion of the second element **52** that is pressed by the second biasing member **54** is increased. Therefore, the moment of force of the second element **52** about the pivot shaft **50** due to the elastic force of the second biasing member **54** can be increased, and it is possible to increase the force that elastically biases the protruding engagement portion **65** in the direction of engagement with the recessed engagement portion **41**. Accordingly, even in a case where the locking mechanism **5** is in a semi-locked state and the inner column **6** is displaced forward at a high speed relative to the outer column **7** due to an impact load caused by a secondary collision, for example, the protruding engagement portion **65** can be engaged with the recessed engagement portion **41** at the instant

when the inner column **6** is slightly displaced forward with respect to the outer column **7** and the position in the axial direction of the protruding engagement portion **65** matches the position in the axial direction of the recessed engagement portion **41**.

(91) In the present example, by arranging the pivot shaft **50**, which is the portion that supports the first element **51** and the second element **52** with respect to the outer column **7**, farther on the upper side than the column-side through hole **9**, that is, farther on the upper side than the adjustment rod **3**, the distance between the engagement portion between the protruding engagement portion **65** and the recessed engagement portion **41** and the pivot shaft **50** is shortened. Therefore, in a case where the inner column **6** is displaced forward with respect to the outer column **7**, the direction of the force applied from the recessed engagement portion **41** to the protruding engagement portion **65** can be made substantially parallel to the central axis of the steering column **2**. Accordingly, at the time of a secondary collision, the impact load applied to the inner column **6** can be efficiently transmitted from the recessed engagement portion **41** to the protruding engagement portion **65**, and the coupling member **47** can be quickly sheared.

(92) In the present example, the recessed engagement portion **41** has an inner side flat surface portion **75** perpendicular to the central axis of the inner column **6** on the rear side surface, and the protruding engagement portion **65** has an outer side flat surface portion **76** on the rear side surface that is substantially perpendicular to the central axis of the inner column **6** in a state in which the protruding engagement portion **65** and the recessed engagement portion **41** are engaged. Therefore, the impact load accompanying a secondary collision is applied from the recessed engagement portion **41** to the protruding engagement portion **65** through a contact portion between the flat surfaces of the inner side flat surface portion **75** and the outer side flat surface portion **76**. That is, by increasing the area of the contact portion between the recessed engagement portion **41** and the protruding engagement portion **65** that transmits the impact load accompanying a secondary collision, the surface pressure at the contact portion can be kept small, and stress concentration can be prevented from occurring at the engagement portion between the protruding engagement portion **65** and the recessed engagement portion **41**.

(93) In the present example, the second element **52**, at a portion of the upper side surface located on the front side of the protruding engagement portion **65**, has a shoulder portion **77** that closely faces or comes in contact with a portion of the lower side surface of the base plate portion **42** of the inner side locking member **39** that is deviated in the axial direction from the recessed engagement portion **41** in a state in which the protruding engagement portion **65** and the recessed engagement portion **41** are engaged. Therefore, when the inner column **6** is about to displace forward with respect to the outer column **7** and the second element **52** is about to rotate in the counterclockwise direction in FIG. **12** about the pivot shaft **50** in a state in which the inner side flat surface portion **75** of the recessed engagement portion **41** and the outer side flat surface portion **76** of the protruding engagement portion **65** are in contact with each other, the shoulder portion **77** comes in contact with a portion of the lower side surface of the base plate portion **42** that is deviated in the axial direction from the recessed engagement portion **41**. Thus, a part of the impact load caused by the secondary collision can be transmitted by the contact portion between the shoulder portion **77** and the portion of the lower side surface of the base plate portion **42** that is deviated in the axial direction from the recessed engagement portion **41**. In other words, the surface pressure at the contact portion between the inner side flat surface portion **75** and the outer side flat surface portion **76** can be kept small, and stress concentration can be prevented from occurring at the engagement portion between the recessed engagement portion **41** and the protruding engagement portion **65**.

(94) In the present example, in a state in which the protruding engagement portion **65** is engaged with the recessed engagement portion **41**, the upper side surface of the stopper piece **69** of the second element **52** comes in contact with the upper side surface (the surface facing downward) of the rectangular hole **64** of the first element **51**, and the second element **52** is prevented from pivoting further upward relative to the first element **51**. That is, the upper surface of the rectangular

hole **64** of the first element **51** forms a stopper portion. Therefore, in a case where the first element **51** pivots in the clockwise direction in FIG. **14** and FIG. **15** about the pivot shaft **50** due to operation of the adjustment lever **4** in the predetermined direction, the upper side surface of the stopper piece **69** of the second element **52** can be pressed downward by the upper side surface of the rectangular hole **64** which is the stopper portion. Therefore, based on the operation of the adjustment lever **4** in the predetermined direction, the engagement between the recessed engagement portion **41** and the protruding engagement portion **65** can be reliably disengaged.

(95) In the present example, an example has been described in which the content according to the present disclosure is applied to a steering column device that includes both a telescopic mechanism for adjusting the front-rear position of the steering wheel and a tilt mechanism for adjusting the up-down position; however, the content according to the present disclosure may also be applied to a steering column device that includes only a telescopic mechanism.

(96) The steering column device **1** of the present example includes a steering column **2** configured by combining an inner column **6** on the rear side and an outer column **7** on the front side so as to expand and contract; however, the content according to the present disclosure may also be applied to a steering column device including a steering column formed by combining an inner column on the front side and an outer column on the rear side. In this case, the column-side through hole is configured by a long hole extending in the front-rear direction.

(97) In the present example, the locking mechanism **5** is arranged on the lower side of the steering column **2**; however, in a case of implementing the steering column device according to the present disclosure, the circumferential position of the locking mechanism is not particularly limited, and for example, may be arranged on the upper side of the steering column.

(98) In a case of implementing the steering column device according to the present disclosure, the outer side locking member may include a plurality of protruding engagement portions. More specifically, for example, configuration may be such that the locking mechanism is switched to the locked state by engaging a rack-shaped inner tooth portion provided on the inner side locking member and a rack-shaped outer tooth portion provided on the outer side locking member. In this case, among a plurality of claws forming the inner tooth portion, recessed portions existing between adjacent claws form the recessed engagement portions, and the claws of the outer tooth portion form the protruding engagement portions.

Second Example

(99) A second example of an embodiment according to the present disclosure will be described using FIG. **21**. In the present example, in a state in which the protruding engagement portion **65** is engaged with the recessed engagement portion **41**, the first element **51a** does not have a stopper portion that prevents the second element **52a** from being further displaced with respect to the first element **51a** in the biasing direction by the second biasing member **54a**. More specifically, the first element **51a** does not have the end plate portion **58** and the rectangular hole **64** that the first element **51** has in the first example.

(100) In the present example, of the second biasing member **54a**, a lower end portion is supported by and fixed to the spring locking portion **63a** of the first element **51a** by crimping or the like, and an upper end portion is supported by and fixed to a spring locking portion **68a** of the second element **52a** by crimping or the like.

(101) In the present example, in a case where the first element **51a** pivots in a clockwise direction in FIG. **21** about the pivot shaft **50** due to operation of the adjustment lever **4** (see FIG. **1** to FIG. **5**) in a predetermined direction, in order to make it possible to adjust the position of the steering wheel, the spring locking portion **68a** of the second element **52a** is pulled downward through the second biasing member **54a**. As a result, the second element **52a** is pivoted in a clockwise direction in FIG. **21** about the pivot shaft **50**, and the protruding engagement portion **65** and the recessed engagement portion **41** are disengaged. Therefore, the spring characteristics such as the spring constant and free length of the second biasing member **54a**, which is a compression coil spring, are

regulated, and in a state in which the adjustment lever **4** is operated a certain amount in the predetermined direction, the protruding engagement portion **65** and the recessed engagement portion **41** are disengaged. The other configurations and effects of the second example are the same as those of the first example.

REFERENCE SIGNS LIST

(102) **1** Steering column device **2** Steering column **3** Adjustment rod **4** Adjustment lever **5** Locking mechanism **6** Inner column **7** Outer column **8** Coupling hole **9** Column-side through hole **10** Column main body **11** Held portion **12** Front support bracket **13** Slit **14** Pivot **15** Steering shaft **16** Upper shaft **17** Lower shaft **18a, 18b** Radial rolling bearing **19** Vehicle body side bracket **20** Mounting plate portion **21a, 21b** Support plate portion **22** Mounting hole **23a, 23b** Elongated tilt hole **24** Cam portion **25** Rod main body **26** Cam member **27** Head portion **28** Shaft portion **29** Arm portion **30** Connecting portion **31** Fitting hole **32** Nut **33** Thrust bearing **34** Washer **35a, 35b** Pressing portion **36** Expansion/contraction mechanism **37** Driven cam **38** Driving cam **39** Inner side locking member **40** Outer side locking member **41** Recessed engagement portion **42** Base plate portion **43** Bent plate portion **44** Inner guide surface portion **45** Coupling hole **46** Through hole **47** Coupling member **48** Damper **49** Pin portion **50** Pivot shaft **51, 51a** First element **52, 52a** Second element **53** First biasing member **54, 54a** Second biasing member **55** Support hole **56** Side plate portion **57** Connecting plate portion **58** End plate portion **59** Through hole **60** Support hole **61** Cylindrical portion **62** Locking piece **63, 63a** Spring locking portion **64** Rectangular hole **65** Protruding engagement portion **66** Support hole **67** Outer guide surface portion **68, 68a** Spring locking portion **69** Stopper piece **70** Base portion **71** Extending arm portion **72** Folded portion **73** Locking arm portion **74** Bent portion **75** Inner side flat surface portion **76** Outer side flat surface portion **77** Shoulder portion **78** Lateral bent portion **100** Steering wheel **101** Steering gear unit **102** Input shaft **103** Tie rod **104** Steering shaft **105** Steering column **106** Universal joint **107** Intermediate shaft **108** Universal joint **109** Pivot shaft **110** Vehicle body **111** Fixed bracket **112** Outer column **113** Inner column **114** Outer tube **115** Inner shaft

Claims

1. A steering column device comprising: a steering column including an inner column, and an outer column having a column-side through hole penetrating in a width direction, arranged on one side in an axial direction of the inner column, and externally fitted so as to displace relative to the inner column in the axial direction; an adjustment rod having a cam portion on an outer circumferential surface and inserted into the column-side through hole; an adjustment lever fixed to the adjustment rod and configured to rotate the adjustment rod; and a locking mechanism including an inner side locking member having a recessed engagement portion at a plurality of locations in the axial direction and provided on the inner column, and an outer side locking member having a protruding engagement portion capable of engaging with the recessed engagement portion; wherein the outer side locking member has a first element, at least a portion of which is supported movably toward and away from the inner side locking member; a second element having the protruding engagement portion and supported such that the protruding engagement portion is able to displace in an engagement-disengagement direction with respect to the recessed engagement portion; a first biasing member elastically biasing at least a portion of the first element in a direction away from the inner side locking member; and a second biasing member elastically biasing the second element in a direction such that the protruding engagement portion is engaged with the recessed engagement portion with respect to the engagement-disengagement direction; and the cam portion presses the first element in a direction such that at least a portion of the first element approaches the inner side locking member due to rotation of the adjustment rod in response to operation of the adjustment lever.

2. The steering column device according to claim 1, wherein the first element has a stopper portion

- that, in a state in which the protruding engagement portion is engaged with the recessed engagement portion, is configured to prevent the second element from being displaced with respect to the first element in a biasing direction by the second biasing member.
3. The steering column device according to claim 1, wherein the outer side locking member has a pivot shaft that is arranged in the width direction and is supported with respect to the outer column so that relative displacement in the axial direction and radial direction of the steering column is not possible; and the first element is supported so as to pivot about the pivot shaft.
 4. The steering column device according to claim 3, wherein the second element is supported so as to pivot about the pivot shaft.
 5. The steering column device according to claim 4, wherein the pivot shaft is arranged at a position closer to the inner side locking member than the adjustment rod with respect to the radial direction of the steering column.
 6. The steering column device according to claim 4, wherein the second biasing member is arranged on an opposite side of the pivot shaft with the adjustment rod therebetween with respect to the axial direction of the steering column.
 7. The steering column device according to claim 6, wherein the second biasing member is configured by a compression coil spring.
 8. The steering column device according to claim 1, further comprising a coupling member configured to support the inner side locking member with respect to the inner column so as to detach due to an impact load accompanying a secondary collision.
 9. The steering column device according to claim 1, further comprising a guide surface portion that is inclined toward the one side in the axial direction as going outward in the radial direction on at least one of a surface of the one side in the axial direction of the recessed engagement portion and a tip-end surface of the protruding engagement portion.
 10. The steering column device according to claim 1, wherein the second element, has a shoulder portion at a portion located on the one side in the axial direction of the protruding engagement portion, the shoulder portion closely facing or coming in contact with a portion of the inner side locking member that is deviated in the axial direction from the recessed engagement portion in a state in which the protruding engagement portion is engaged with the recessed engagement portion.
-