

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384666
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Voss; Barry et al.

Extendable needle davit assembly

Abstract

An extendable needle davit assembly has an extendable beam comprising a fixed beam portion, and a telescopic beam portion slidably receivable within a distal end of the fixed beam portion. An intermediate lateral bracing frame holds the extendable beam at an angle. The fixed beam portion is a single-piece construction, and a proximal end of the fixed beam portion is anchored. An upper end of the bracing frame is attached to a distal attachment point of the fixed beam portion, such that a distal portion of the fixed beam portion extends beyond the bracing frame. A lower portion of the bracing frame is attached to a proximal attachment point of the fixed beam portion by means of a rear brace.

Inventors:	Voss; Barry (Boronia, AU), Voss; Murray (Boronia, AU)
Applicant:	SAYFA R&D PTY LTD (Boronia, AU)
Family ID:	85382427
Assignee:	SAYFA R&DPTY LTD (Boronia, AU)
Appl. No.:	18/001927
Filed (or PCT Filed):	August 19, 2022
PCT No.:	PCT/AU2022/050925
PCT Pub. No.:	WO2023/019319
PCT Pub. Date:	February 23, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240124274 A1	Apr. 18, 2024

Foreign Application Priority Data

AU

2021902622

Aug. 20, 2021

Publication Classification

Int. Cl.: B66C23/04 (20060101); B66C23/20 (20060101); B66C23/70 (20060101)

U.S. Cl.:

CPC B66C23/04 (20130101); B66C23/205 (20130101); B66C23/701 (20130101);

Field of Classification Search

CPC: B66C (23/04); B66C (23/205); B66C (23/701); B66C (23/202); B66C (23/26)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1551132	12/1924	Butler	N/A	N/A
2446093	12/1947	Lambert	N/A	N/A
2569821	12/1950	Fredrick	N/A	N/A
2772789	12/1955	Hussong	212/299	B66C 23/72
2928564	12/1959	Figge	414/657	B66C 23/205
3910379	12/1974	Miller et al.	N/A	N/A
4135627	12/1978	McInerney	254/285	B66C 23/48
4508233	12/1984	Helms	N/A	N/A
4621741	12/1985	Boon	212/175	B66C 23/205
5622237	12/1996	Moldow	212/224	B66C 23/205
9505590	12/2015	Chen	N/A	E04G 3/34
11472241	12/2021	Baik	N/A	B60D 1/025

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2020104271	12/2020	AU	N/A
213572947	12/2020	CN	N/A
1044371	12/1957	DE	N/A
2019100180	12/2018	WO	N/A

OTHER PUBLICATIONS

Supplementary European Search Search Report dated May 23, 2024 from Application No. 22818168.1 (11 pages). cited by applicant

International Search Report & Written Opinion dated Oct. 11, 2022 from PCT Application No. PCT.AU2022/050925. cited by applicant

International type search dated Sep. 16, 2021 from Australian Application No. 2021902622. cited by applicant

Primary Examiner: Momper; Anna M

Assistant Examiner: Campos, Jr.; Juan J

Attorney, Agent or Firm: INNOVATION CAPITAL LAW GROUP, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This is a U.S. National Phase Application under 35 U.S.C. § 371 of International Application No. PCT/AU2022/050925, filed Aug. 19, 2022, which claims priority to Australian Application Nos. 2021902622, filed Aug. 20, 2021, which were published Under PCT Article 21 (2), the entire contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

(2) This invention relates generally to an extendable needle davit assembly for elevated rope access for construction and maintenance personnel working at height on buildings and structures.

BACKGROUND OF THE INVENTION

(3) Davit systems are portable lightweight anchoring device used in elevated rope access and abseil applications. Needle davit systems protrude over the parapet or façade of a building or the wall or edge of a structure, to provide a secure anchorage for abseiling, typically for maintenance purposes.

(4) U.S. Pat. No. 2,446,093 A (Lambert) 27 Jul. 1948 discloses a frame for supporting hoisting apparatus which is particularly adapted for use upon the roofs of buildings, for elevating building materials and other goods. The hoist frame is universally adjustable and thus adaptable for use on buildings in which the roofs may be either fiat or pitched, and on which the copings and fire walls may vary both in height and thickness. The hoist frame comprises an extendable boom made of telescoping tubular parts having a distal part intended to extend beyond the edge of a roof, where it is provided with an eye for the attachment of a block and tackle.

(5) U.S. Pat. No. 5,622,237 A (Moldow) 22 Apr. 1997 discloses a portable hoist system suitable for mounting to a pair of rails and includes a vertical support. The system has an inclined boom connected to the vertical support and a hoist secured to the boom. Clamping members are provided at the lower ends of the vertical support and the boom for detachably mounting to the rails. The hoist system is foldable for transport or storage purposes.

(6) WO 2019/100180 A1 (Kao) 31 May 2019 discloses a support bracket structure for a deploying/stowing type suspension apparatus. The structure has a loading box which can be movably placed on a building roof floor. A suspension arm has one end pivotally provided on the loading box, and a support bracket having a connecting seat pivotally connected to the suspension arm. The structure has support legs one on either side of the other end of the connecting seat, which stand on the building roof floor in a V-shape. The suspension arm is inclined and bridges the loading box and the support bracket, with the two support legs and building roof floor forming an isosceles triangular support structure. The support bracket structure for the apparatus can overcome problematic transport difficulties.

(7) The present invention seeks to provide an extendable needle davit assembly, which will overcome or substantially ameliorate at least some of the deficiencies of the prior art, or at least to provide an alternative.

(8) It is to be understood that, if any prior art information is referred to herein, such reference does not constitute an admission that the information forms part of the common general knowledge in the art, either in Australia or any other country.

SUMMARY OF THE DISCLOSURE

- (9) There is provided an extendable needle davit assembly which is designed as an elevated rope access anchorage device, where abseil access over non load bearing parapets, balustrades and light weight curtain walls of buildings and structures is required for personnel working at height.
- (10) Rope access is commonly required for building inspections and general maintenance of external facades, windows and equipment that cannot be accessed from a platform or enclosed safety system.
- (11) The extendable needle davit assembly is designed to withstand a 12 kN rope access load and have a serviceability load limit of 400 kg, for use by a single operator at any one time.
- (12) The extendable needle davit assembly operates well on metal deck roofs where the static and dynamic loads imposed on the roof deck, are required to be spread across the roofing area to avoid damaging or lifting the roof sheets.
- (13) The extendable needle davit assembly is also modular in design and can be configured in length, reach and travel, thereby providing a customised solution tailored to the specific requirements of a particular project.
- (14) In accordance with an embodiment, the extendable needle davit assembly comprises an extendable beam comprising a fixed beam portion, and a telescopic beam portion slidably receivable within a distal end of the fixed beam portion. The assembly further comprises an intermediate lateral bracing frame.
- (15) The fixed beam portion has a fixed (i.e. non-telescopic) construction between the anchor and the lateral bracing frame.
- (16) An upper end of the bracing frame is attached to a distal attachment point of the fixed beam portion. A distal portion of the fixed beam portion may extend just beyond the bracing frame.
- (17) A lower portion of the bracing frame is attached to a proximal attachment point of the fixed beam portion by means of a rear brace.
- (18) As such, the present assembly is telescopically adjustable beyond the bracing frame, thereby allowing for convenient length and reach adjustment, without repositioning or length adjustment of the bracing frame, in contradistinction to the arrangement taught by Lambert which has telescopic adjustment rearward of the support frame.
- (19) Furthermore, the fixed (i.e. non-telescopic) construction of the main load bearing fixed beam enhances the structural integrity and therefore load rating capacity of the extendable needle davit assembly, wherein the present rope access load rating is 12Kn, in contradistinction to the arrangement taught by Lambert which compromises loadbearing capacity by means of telescopic componentry rearward of the support frame. Both Moldow and Kao have similarly compromised loadbearing capacity configurations.
- (20) The present extendable needle davit assembly may be assembled by inserting portions thereof between bifurcated portions of interconnecting pieces, and which are secured using locating pins. This modular arrangement facilitates quick, convenient and secure slot-in assembly as illustrated in FIG. 16.
- (21) Furthermore, the proximal end of the extendable beam is preferably anchored by means of a swivel anchor, whereas the intermediate bracing frame is not anchored so that both the bracing frame and the extendable beam can be lifted together, for repositioning over the building parapet or façade, as the extendable beam swivels with respect to the swivel bracket as illustrated in FIG. 17.
- (22) Other aspects of the invention are also disclosed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Notwithstanding any other forms which may fall within the scope of the present invention, preferred embodiments of the disclosure will now be described, by way of example only, with

reference to the accompanying drawings in which:

- (2) FIG. 1 shows an exploded perspective view of an extendable needle davit assembly in accordance with an embodiment;
- (3) FIG. 2 shows an assembled perspective view of the davit assembly;
- (4) FIG. 3 shows a symmetrical left and right side view of the davit assembly;
- (5) FIG. 4 shows a top plan view of the davit assembly;
- (6) FIG. 5 shows a distal end view of the davit assembly;
- (7) FIG. 6 shows an exploded perspective view of a rear mount in accordance with an embodiment;
- (8) FIG. 7 shows an assembled perspective view of a rear mount in accordance with an embodiment;
- (9) FIG. 8 shows a magnified perspective view of a distal portion of both the structural and extension beams;
- (10) FIG. 9 shows a perspective view of the extension beam in accordance with an embodiment;
- (11) FIG. 10 shows a symmetrical side view of a rear mount in accordance with an embodiment;
- (12) FIG. 11 shows a symmetrical side view of a rear mount in accordance with a further embodiment;
- (13) FIG. 12 shows a symmetrical side view of a rear mount in accordance with a yet further embodiment;
- (14) FIG. 13 shows a locating pin in accordance with an embodiment;
- (15) FIG. 14 shows a common bolt fastener in accordance with an embodiment;
- (16) FIGS. 15-17 illustrate assembly and deployment of the present extendable needle davit assembly;
- (17) FIG. 18 shows an example embodiment of the davit assembly having a 400 mm high bracing frame;
- (18) FIG. 19 shows an example embodiment of the davit assembly having an 800 mm high bracing frame; and
- (19) FIG. 20 shows an example embodiment of the davit assembly having a 1200 mm high bracing frame.

DESCRIPTION OF EMBODIMENTS

- (20) With reference to FIGS. 1 and 2 an extendable needle davit assembly **100** comprises an extendable beam **101** comprising a fixed beam portion **101B** and a telescopic beam portion **101A**.
- (21) Given the orientation of FIG. 3 for orientational referencing, proximal is at or towards the right of the davit assembly **100**, and distal is at or towards the left.
- (22) The telescopic beam portion **101A** is slidably receivable within a distal end of the fixed beam portion **101B**.
- (23) The davit assembly **100** further comprises an intermediate lateral bracing frame **104**.
- (24) Furthermore, a proximal end of the fixed beam portion **101B** is anchored to an anchor, such as from a rear mount **103** in embodiments.
- (25) The bracing frame **104** may be of an all-welded construction, comprising RHS section aluminium extrusion members. An upper end **140** of the bracing frame **104** is attached to a distal attachment point **141** of the fixed beam portion **101B**. A distal portion **142** of the fixed beam portion **101B** may extend beyond the bracing frame **104**.
- (26) The fixed beam portion **101B** is non-telescopic, thereby conferring structural integrity between the anchor **103** and the distal attachment point **141**. Preferably, the fixed beam portion **101B** is a single piece construction and, in this regard, may be formed from an extrusion process and may further comprise aluminium.
- (27) A lower portion **143** of the bracing frame **104** is attached to a proximal attachment point **144** of the fixed beam portion **101B** via a rear brace **129**.
- (28) The positioning of the bracing frame **104** is preferably such that a ratio of the rear span (between the distal attachment point **141** and the proximal end **150** of the fixed beam portion

101B), to the cantilever span (between the distal attachment point **141** and a distal end of the telescopic beam portion **101A**), is a minimum of 1.5.

(29) Preferably, the rear brace **129** is of fixed length.

(30) Preferably, the upper end **140** of the bracing frame **104** is bifurcated and open-ended, and wherein the fixed beam portion **101B** slots between the bifurcated portions **145** thereof for attachment.

(31) An intermediate locating pin **110B** may fit through the bifurcated portions **145** and the fixed beam portion **101B** therebetween.

(32) Furthermore, a proximal end **146** of the rear brace **129** may also be bifurcated and open-ended, and wherein the fixed beam portion **101B** slots between the bifurcated portions of attachment bracket **130**. A proximal locating pin **110C** may fit through the bifurcated portions and the fixed beam portion **101B** therebetween. The rear brace **129** is of an all-welded construction comprising a pair of RHS section aluminium extrusion members **147**, with an attachment bracket **130** comprising a pair of aluminium plates welded thereto at the proximal end **146** thereof to form the bifurcated portions.

(33) The lower portion **143** of the bracing frame **104** may further be bifurcated and wherein a distal end **148** of the rear brace **129** inserts between the bifurcated portions **149** thereof. A lower locating pin **110D** may fit through the bifurcated portions **149** and the distal end **148** of the rear brace **129** therebetween. As shown in FIG. 3, the rear brace **129** may be substantially orthogonal with respect to the lateral bracing frame **104** to enhance structural integrity.

(34) According to the above configuration, the lateral bracing frame **104**, rear brace **129** and fixed beam portion **101B** may be attachable using only three locating pins **110B**, **110C** and **110D**.

(35) As shown in FIGS. 7, 12 and 17, the proximal end **150** of the inclined extendable beam **101** may be anchored using a swivel bracket **123**.

(36) Furthermore, the bracing frame **104** may comprise a base member **107** which is not attached to the surface **102**. In the embodiment shown, the base member **107** of the bracing frame **104** may be longitudinal and orientated orthogonally with respect to the extendable beam **101**, and from which a pair of upright members **108** extend perpendicularly, thereby defining the aforescribed bifurcated portions **145** and **149**, for the attachment of the fixed beam portion **101B** and the distal end **148** of the rear brace **129** respectively. Angled side brace members **109** may brace the upper end **140** of the bracing frame **104** from both ends of the base member **107**.

(37) Because the base member **107** is not anchored to the surface **102**, the bracing frame **104** can be lifted with the extendable beam **101**, as the extendable beam **101** swivels with respect to the swivel bracket **123**.

(38) With reference to FIG. 3, the telescopic beam portion **101A** is slidable with respect to the fixed beam portion **101B** between an extended position **132** and a retracted position **131**.

(39) FIGS. 2 and 16 show an embodiment wherein the telescopic beam portion **101A** is relatively shorter. In accordance with this embodiment, in the retracted position **131** a proximal end **152** of the telescopic beam portion **101A** does not cross the distal attachment point **141** of the fixed beam portion **101B**. As such, the length of the extendable beam **101** may be reconfigured by manipulating only one distal locating pin **110A** between the telescopic beam portion **101A** and the fixed beam portion **101B**, without manipulating the intermediate locating pin **110B** at the distal attachment point **141**.

(40) In accordance with this embodiment, the telescopic beam portion **101A** and the fixed beam portion **101B** may comprise a distal series of apertures **133**, which collocate at more than one position of the telescopic beam portion **101A** with respect to the fixed beam portion **101B**, for the distal locating pin **110A** to be inserted therethrough.

(41) FIGS. 1 and 15 however show an alternative embodiment wherein the telescopic beam portion **101A** is relatively longer. In accordance with this embodiment, in the retracted position **131** the proximal end **152** of the telescopic beam portion **101A** does cross the distal attachment point **141**.

In embodiments, the telescopic beam portion **101A** may be sufficiently long, so that even in the extended position **132** the proximal end **152** of the telescopic beam portion **101A** crosses the distal attachment point **141**.

(42) In accordance with this embodiment, the extendable needle davit assembly **100** has further reach, and wherein the offset of the telescopic beam portion **101A** may be adjusted with respect to the fixed beam portion **101B**, by manipulating both the distal locating pin **110A** between the telescopic beam portion **101A** and the fixed beam portion **101B**, and the intermediate locating pin **110B** at the distal attachment point **141**.

(43) In accordance with this embodiment, the telescopic beam portion **101A** and the fixed beam portion **101B** may comprise a further series of apertures **134** which collocate at more than one position of the telescopic beam portion **101A** with respect to the fixed beam portion **101B**, for the intermediate locating pin **110B** to be inserted therethrough. As such, the intermediate locating pin **110B** inserts through the bifurcated portions **145** of the upper end **140** of the bracing frame **104**, the distal attachment point **141** of the fixed beam portion **101B** and the collocating apertures **134** of the telescopic beam portion **101A**.

(44) The extendable needle davit assembly **100** may be quickly assembled, constructed and positioned over a building parapet or structure edge, in the manner shown in FIGS. **15** to **17**.

(45) Specifically, FIG. **15** shows wherein the proximal end **150** of the fixed beam portion **101B** is attached to the swivel bracket **123**. The telescopic beam portion **101A** can then be inserted into the open distal portion **142** of the fixed beam portion **101B**.

(46) FIG. **16** shows the rear brace **129** attached to the bracing frame **104**, by slotting the distal end **148** of the rear brace **129** between the lower bifurcated portions **149** of the bracing frame **104**, and inserting the lower locating pin **110D** therethrough.

(47) The fixed beam portion **101B** can then easily be slotted into the connection plates **130** of rear brace **129**, and between the bifurcated portions **145** of bracing frame **104**, and wherein the respective proximal and intermediate locating pins **110C** and **110B**, are inserted through the respective proximal and distal attachment points **144** and **141**.

(48) FIG. **17** shows wherein the constructed extendable needle davit assembly **100** can then be swivelled about the swivel bracket **123**, and positioned over the building parapet or structure edge **153**.

(49) The telescopic beam portion **101A** may then be drawn out to the extended position **132** by manipulating the distal locating pin **110A**, without having to reposition the bracing frame **104**.

(50) FIG. **13** shows an embodiment wherein the locating pin **110** takes the form of a hand-operable locating pin **110** suited for quick release, whereas FIG. **14** shows a further embodiment wherein the locating pin **110** takes the form of a locking bolt **106** for a more permanent installation.

(51) As shown in FIG. **13** the locating pin **110** comprises a shaft **111**, locking pin **112** and safety device **114**, retaining ring and short wire lanyard **113**.

(52) According to the configuration of FIG. **13**, the locating pin **110** has a minor end **154** angled from the shaft **111**, and a distal end **155** which is secured by a locking pin **112** therethrough. The locating pin **110** in accordance with this embodiment, may be used for the series of distal or proximal apertures **133** or **134** respectively, collocating between the telescopic beam portion **101A** and the fixed beam portion **101B**, for quick release and rapid adjustment of the length of the extendable beam **101**.

(53) As shown in FIGS. **8** and **9**, the shaft **111** of locating pin **110** may be inserted through the collocating apertures **133** or **134**. Once through, the distal end **155** of the shaft **111** may be secured by means of the locking pin **112** and a retaining ring and short wire lanyard **113**. The distal end **155** and angled minor end **154** of the shaft **111**, may be secured by means of the retaining ring and short wire lanyard **113** threaded over or under the extendable beam **101**. A safety device **114** secured to the extendable beam **101** may secure the short wire lanyard **113**.

(54) Alternatively, FIG. **14** shows wherein the locating pin **110** takes the form of a locking bolt **106**,

and wherein a distal end **155** of the shaft **115** is secured with a nut **117** and interfacing washer **116**. A split pin **118** may go through the distal end **155** of the shaft **115** to prevent unscrewing of the nut **117**. The locking bolt **106** in accordance with this further embodiment may be used to more permanently interface the bracing frame **104** to the fixed beam portion **101B**, and the rear brace **129** between the bracing frame **104** and the fixed beam portion **101B**.

(55) As shown in FIG. **9**, a distal end of the telescopic beam portion **101A** may support a rope guide attachment bracket **105**. The rope guide attachment bracket **105** may comprise a pair of plates secured either side of the distal end of the telescopic beam portion **101A** and have a locking pin **110** inserted through corresponding holes thereof and comprising an access rope guide thereby.

(56) As shown in FIG. **8**, the telescopic beam portion **101A** and the fixed beam portion **101B** may comprise interfacing hour-glass cross-sectional profiles which enhance structural integrity, prevent rotation between the respective proximal and distal portions, and provide flat surfaces **156** for insertion of the locating pins **110** therethrough.

(57) FIGS. **6** and **7** show respective rigid guide rail type rear mounts **103** in accordance with respective embodiments of low profile and conventional profile rigid rails. The rear mounts **103** may engage the respective rigid guide rail types **119** secured to the surface **102** by fixing brackets **120** at pre-determined intervals.

(58) A right-angled mounting plate **121** may engage through the open guide channels **122** in the respective rigid guide rail types **119** therealong, and be attached to a proximal end of the extendable beam **101B** by means of a swivel bracket **123**. A bolt fastener **135** may secure the swivel bracket **123** to the mounting plate **121** by being inserted through the collocating central holes therein. The bolt fastener **135** may further have a flat washer and a locknut.

(59) The mounting plate **121** may further engage at various positions along the respective rigid guide rail types **119**, for locating and adjusting the extendable needle davit assembly **100** via the swivel bracket **123**. A locking bolt **106** may secure the swivel bracket **123** to the proximal end of the fixed beam portion **101B** by being inserted through the collocating holes therein. The locking bolt **106** may further have an interfacing washer **116**, a nut **117** and a split pin **118**.

(60) FIG. **7** shows the extendable needle davit assembly **100** comprising a rear connection bracket **124** defining primary rear attachment apertures **125**, for tethering conventional safety hardware such as carabiners and lanyards.

(61) As further shown in FIG. **7**, the mounting plate **121** may define secondary rear attachment apertures **126**, for tethering carabiners and lanyards attached to a safety container, housing tools and equipment for rope access operations. Structural bolts **127** with flat washers and locknuts may secure the rear connection bracket **124** to a proximal end of the fixed beam portion **101B**.

(62) Different types of rear mounts **103** for various mounting options to a surface **102** are shown in FIGS. **10** to **12**.

(63) FIG. **10** shows details of a rear mount **103A** mounting option shown in FIG. **7**, and may be similar to the rear mount **103B**, but wherein the rigid guide rail type **119** defines a conventional profile as compared to the low profile as shown in FIG. **11**.

(64) FIG. **11** shows details of a rear mount **103B** mounting option shown in FIG. **6**, but further wherein the mounting plate **121** may be engaged by roller bearings **128** within the open guide channel **122** of the rigid guide rail type **119** defining a low profile.

(65) FIG. **12** shows a further rear mount **103C** wherein the swivel bracket **123** is affixed directly to a surface **102**. For example, the swivel bracket **123** may be affixed directly to a concrete surface using a concrete anchor.

(66) FIG. **18** shows an exemplary embodiment of the extendable needle davit assembly **100**, having a 400 mm high bracing frame **104**. In this embodiment, the apparatus is devoid of the rear brace **129**. The calculated vertical and horizontal forces for different cantilever lengths are tabulated as follows:

(67) TABLE-US-00001 BACK FRAME CANTILEVER SPAN UTL Point A Point B Point C

HEIGHT LENGTH (m) (m) LOAD Vx (kN) Py (kN) Vx (kN) Py (kN) Vx (kN) Py (kN) 400 mm
1000 1800 12 0.50 -6.60 -0.50 18.10 -0.10 0.40 2400 12 0.70 -4.90 -0.60 16.50 -0.10 0.40 3000
12 0.80 -3.90 -0.80 15.60 -0.10 0.40 400 mm 1200 1800 12 0.60 -8.00 -0.60 19.40 -0.10 0.40
2400 12 0.80 -5.90 -0.70 17.50 -0.10 0.40 3000 12 1.00 -4.70 -0.90 16.30 -0.10 0.40 400 mm
1500 2250 12 0.70 -8.00 -0.60 19.20 -0.10 0.40 3000 12 0.90 -6.00 -0.80 17.30 -0.10 0.40 3750
12 1.10 -4.80 -1.00 16.20 -0.10 0.40

(68) FIG. **19** shows an embodiment of the extendable needle davit assembly **100**, having an 800 mm high bracing frame **104**. The calculated vertical and horizontal forces for different cantilever lengths are tabulated as follows:

(69) TABLE-US-00002 BACK FRAME CANTILEVER SPAN UTL Point A Point B Point C
HEIGHT LENGTH (m) (m) LOAD Vx (kN) Py (kN) Vx (kN) Py (kN) Vx (kN) Py (kN) 800 mm
1200 1800 12 7.30 -7.20 -7.30 17.60 -0.10 1.00 2400 12 8.70 -5.30 -8.70 15.90 -0.10 0.90 3000
12 10.00 -4.10 -10.00 14.90 -0.10 0.90 800 mm 1500 2250 12 7.70 -7.10 -7.70 17.60 -0.10 1.00
3000 12 7.90 -5.30 -7.80 16.10 -0.10 0.90 3700 12 11.30 -4.10 -11.20 15.10 -0.30 0.90 800 mm
1800 2700 12 12.60 -7.10 -12.60 17.60 -0.10 1.00 3600 12 15.60 -5.10 -15.50 15.80 -0.10 1.00
4500 12 17.70 -3.90 -17.60 14.80 -0.10 0.90

(70) FIG. **20** shows an embodiment of the extendable needle davit assembly **100**, having a 1200 mm high bracing frame **104**. The calculated vertical and horizontal forces for different cantilever lengths are tabulated as follows:

(71) TABLE-US-00003 BACK FRAME CANTILEVER SPAN UTL Point A Point B Point C
HEIGHT LENGTH (m) (m) LOAD Vx (kN) Py (kN) Vx (kN) Py (kN) Vx (kN) Py (kN) 1200 mm
1200 1800 12 3.60 -8.40 -3.60 18.80 0.00 1.90 2400 12 4.80 -6.50 -4.80 17.20 0.00 0.90 3000 12
6.10 -5.30 -6.10 16.10 0.00 0.90 1200 mm 1500 2250 12 3.40 -7.00 -3.40 17.80 0.00 0.90 3000
12 4.50 -5.40 -4.50 16.30 0.00 0.90 3700 12 5.40 -4.30 -5.30 15.40 -0.10 0.80 1200 mm 1800
2700 12 4.60 -7.60 -4.60 18.40 0.00 1.00 3600 12 7.00 -5.60 -7.00 16.50 -0.10 0.90 4500 12
9.20 -4.30 -9.20 15.40 -0.10 0.90

(72) The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the invention. However, it will be apparent to one skilled in the art that specific details are not required in order to practise the invention. Thus, the foregoing descriptions of specific embodiments of the invention are presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, as obviously many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, thereby enabling others skilled in the art to best utilise the invention and various embodiments with various modifications as are suited to the particular use contemplated. It is intended that the following claims and their equivalents define the scope of the invention.

Claims

1. An extendable needle davit assembly comprising: an extendable beam inclined from an anchor; and an intermediate lateral bracing frame, wherein the extendable beam comprises: a fixed beam portion between the anchor and the intermediate lateral bracing frame, wherein an upper end of the bracing frame is attached to a distal attachment point of the fixed beam portion, and a telescopic beam portion, wherein the telescopic beam portion slidably receivable within a distal end of the fixed beam portion and extendable from and telescopingly fixed to the distal end of the fixed beam portion beyond the intermediate lateral bracing frame, and wherein a lower portion of the bracing frame is attached to a proximal attachment point of the fixed beam portion by means of a rear brace and wherein the anchor is a swivel anchor.
2. The davit assembly as claimed in claim 1, wherein the rear brace has a fixed length.
3. The davit assembly as claimed in claim 1, wherein the upper end of the bracing frame is

bifurcated and open-ended and wherein the fixed beam portion inserts between the bifurcated portions at the distal attachment point.

4. The davit assembly as claimed in claim 3, wherein a locating pin fits through the bifurcated portions and the fixed beam portion therebetween.

5. The assembly as claimed in claim 1, wherein a proximal end of the brace is bifurcated and open-ended and wherein the fixed beam portion slots in between bifurcated portions at the proximal attachment point.

6. The assembly as claimed in claim 5, wherein a locking pin fits through the bifurcated portions and the fixed beam portion therebetween.

7. The assembly as claimed in claim 1, wherein the lower portion of the bracing frame is bifurcated and wherein a distal end of the rear brace inserts between bifurcated portions thereof for attachment.

8. The davit assembly as claimed in claim 7, wherein a locating pin fits through the bifurcated portions and the distal end of the rear brace therebetween.

9. The davit assembly as claimed in claim 1, wherein the bracing frame, rear brace and fixed beam portion are attached using three locating pins.

10. The davit assembly as claimed in claim 9, wherein attachments between the bracing frame, rear brace and fixed beam portion comprise bifurcated portions, between which respective portions of the bracing frame, rear brace and fixed beam portion insert and are retained with respective locating pins.

11. The davit assembly as claimed in claim 1, wherein the bracing frame comprises a base member orientated orthogonally with respect to the extendable beam, and wherein the base member is not anchored so that the bracing frame can be lifted with the extendable beam, as the extendable beam swivels with respect to the anchor.

12. The davit assembly as claimed in claim 1, wherein the telescopic beam portion is slidable with respect to the fixed beam portion, between an extended position and a retracted position and wherein, in the retracted position, a proximal end of the telescopic beam does not cross the distal attachment point.

13. The davit assembly as claimed in claim 12, wherein the telescopic beam portion and the fixed beam portion comprise a series of apertures, which collocate at more than one position of the telescopic beam portion with respect to the fixed beam portion for a locating pin.

14. The davit assembly as claimed in claim 1, wherein the telescopic beam portion is slidable with respect to the fixed beam portion, between an extended position and a retracted position and wherein, in the retracted position a proximal end of the telescopic beam crosses the distal attachment point.

15. The davit assembly as claimed in claim 14, wherein the telescopic beam portion and the fixed beam portion comprise a series of apertures, which collocate at more than one position of the telescopic beam portion with respect to the fixed beam portion for a locating pin.

16. The davit assembly as claimed in claim 14, wherein, in the extended position, the proximal end of the telescopic beam crosses the distal attachment point.

17. The davit assembly as claimed in claim 16, wherein the telescopic beam portion and the fixed beam portion comprise a series of apertures which collocate at more than one position of the telescopic beam portion with respect to the fixed beam portion for a locating pin, and wherein the telescopic beam portion comprises a further series of apertures for a further locating pin which fits through the upper end of the bracing frame, the fixed beam portion and the telescopic beam portion at the distal attachment point.

18. The davit assembly as claimed in claim 1, wherein the rear brace is orthogonal with respect to the lateral bracing frame.

19. The davit assembly as claimed in claim 1, further comprising a locating pin and wherein the locating pin comprises a shaft defining a major straight section and an angled minor end.

20. The davit assembly as claimed in claim 19, wherein the straight section of the locating pin fits through transversely orientated collocating apertures through the fixed beam portion and the telescopic beam portion.
 21. The davit assembly as claimed in claim 19, wherein a distal end of the locating pin shaft is secured using a locking pin and retaining ring.
 22. The davit assembly as claimed in claim 21, wherein the retaining ring and angled end of the locating pin shaft are secured by means of a short wire lanyard, threaded over or under the fixed beam portion and the telescopic beam portion.
 23. The davit assembly as claimed in claim 1, wherein a distal end of the telescopic beam portion supports a rope guide attachment bracket.
 24. The davit assembly as claimed in claim 23, wherein the rope guide attachment bracket comprises a pair of plates secured either side of the distal end of the telescopic beam portion.
 25. The davit assembly as claimed in claim 23, wherein the rope guide attachment bracket has a locating pin inserted through corresponding apertures thereof.
 26. The davit assembly as claimed in claim 1, wherein a proximal end of the fixed beam portion is anchored from a rear mount, and wherein the rear mount engages a rigid rail secured to a surface.
 27. The davit assembly as claimed in claim 26, wherein a mounting plate engages the rigid rail, and is attached to a proximal end of the fixed beam portion by means of a swivel bracket.
 28. The davit assembly as claimed in claim 27, wherein the mounting plate is right-angled.
 29. The davit assembly as claimed in claim 27, wherein the mounting plate can engage at various positions along the rigid rail for locating and adjusting the extendable needle davit assembly by means of the swivel bracket.
 30. The davit assembly as claimed in claim 29, wherein the mounting plate is engaged by roller bearings within the rigid rail.
 31. The davit assembly as claimed in claim 1, wherein the fixed beam portion and telescopic beam portion comprise hour-glass cross-sectional profiles.
 32. The davit assembly as claimed in claim 1, further comprising a rear connection bracket defining primary rear attachment apertures.
 33. The davit assembly as claimed in claim 32, further comprising a swivel bracket defining secondary rear attachment apertures.
 34. A method of adjusting the extendable needle davit assembly as claimed in claim 1, the method comprising adjusting the longitudinal offset of the telescopic beam portion with respect to the fixed beam portion, without repositioning the bracing frame.
 35. The method as claimed in claim 34, further comprising the apparatus as claimed in claim 13, wherein the method comprises manipulating only the locating pin without manipulating any other locating pins to adjust the longitudinal offset.
 36. The method as claimed in claim 34, further comprising the apparatus as claimed in claim 17, wherein the method further comprises manipulating the locating pin and the further locating pin to adjust the longitudinal offset.
 37. A method of assembling and constructing the extendable needle davit assembly as claimed in claim 1, the method comprising: attaching a proximal end of the fixed beam portion to the anchor; inserting a proximal end of the telescopic beam portion into a distal end of the fixed beam portion; attaching the fixed beam portion and the bracing frame at the distal attachment point; attaching the rear brace between the lower portion of the bracing frame and the proximal attachment point of the fixed beam portion; swivelling the davit assembly around the anchor towards a building parapet or structure edge, such that the bracing frame lifts and moves with the extendable beam into position; and extending the telescopic beam portion with respect to the fixed beam portion without repositioning the bracing frame, such that a distal end of the telescopic beam portion extends over the building parapet or structure edge.
-

