

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387325
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Shalhon Livne; Moran et al.

System and method for machine-learning based sensor analysis and vascular tree segmentation

Abstract

Methods for automated identification of vascular features are described. In some embodiments, one or more machine learning (ML)-based vascular classifiers are used, with their results being combined to with results of at least one other vascular classifier in order to produce the final results. Potentially advantages of this approach include the ability to combine certain strengths of ML classifiers with segmentation approaches based on more classical (“formula-based”) methods. These strengths may include particularly the identification of anatomically identified targets mixed within an image also showing similar looking but anatomically distinct targets.

Inventors: Shalhon Livne; Moran (Rosh HaAyin, IL), Yaari; Avishai Baruch (Hod-HaSharon, IL), Blecher Segev; Hila (Ramat Ishai, IL), Shapira; Tomer (Ra'anana, IL), Noked Partouche; Ori Ahron (Ramat Gan, IL)

Applicant: Cathworks Ltd. (Kfar Saba, IL)

Family ID: 85328522

Assignee: Cath Works Ltd. (Kfar Saba, IL)

Appl. No.: 18/167022

Filed: February 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230252632 A1	Aug. 10, 2023

Related U.S. Application Data

us-provisional-application US 63308550 20220210

Publication Classification

Int. Cl.: **G06V10/764** (20220101); **G06T7/00** (20170101); **G06T7/11** (20170101); **G06T7/33** (20170101); **G06T7/62** (20170101)

U.S. Cl.:

CPC **G06T7/0012** (20130101); **G06T7/0016** (20130101); **G06T7/11** (20170101); **G06T7/33** (20170101); **G06T7/62** (20170101); **G06V10/764** (20220101); G06T2207/20081 (20130101); G06T2207/20084 (20130101); G06T2207/30048 (20130101); G06T2207/30101 (20130101); G06T2207/30168 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5150292	12/1991	Hoffmann et al.	N/A	N/A
5638823	12/1996	Akay et al.	N/A	N/A
6047080	12/1999	Chen et al.	N/A	N/A
6186948	12/2000	Kamiyama et al.	N/A	N/A
6236878	12/2000	Taylor et al.	N/A	N/A
6501848	12/2001	Carroll et al.	N/A	N/A
6842638	12/2004	Suri et al.	N/A	N/A
7113623	12/2005	Chen et al.	N/A	N/A
7339585	12/2007	Verstraelen et al.	N/A	N/A
7369691	12/2007	Kondo et al.	N/A	N/A
7574026	12/2008	Rasche et al.	N/A	N/A
7657299	12/2009	Huizenga et al.	N/A	N/A
7693315	12/2009	Krishnan et al.	N/A	N/A
7738626	12/2009	Weese et al.	N/A	N/A
7808503	12/2009	Duluk, Jr. et al.	N/A	N/A
7860283	12/2009	Begelman et al.	N/A	N/A
7864997	12/2010	Aben	N/A	N/A
7912260	12/2010	Breeuwer et al.	N/A	N/A
7970187	12/2010	Puts et al.	N/A	N/A
7983459	12/2010	Begelman et al.	N/A	N/A
8073224	12/2010	Strobel et al.	N/A	N/A
8086000	12/2010	Weijers et al.	N/A	N/A
8090164	12/2011	Bullitt et al.	N/A	N/A
8155411	12/2011	Hof et al.	N/A	N/A
8298147	12/2011	Huennekens et al.	N/A	N/A
8311748	12/2011	Taylor et al.	N/A	N/A
8311750	12/2011	Taylor	N/A	N/A
8315812	12/2011	Taylor	N/A	N/A
8321150	12/2011	Taylor	N/A	N/A

8331314	12/2011	Quiang et al.	N/A	N/A
8496594	12/2012	Taylor et al.	N/A	N/A
8523779	12/2012	Taylor et al.	N/A	N/A
8548778	12/2012	Hart et al.	N/A	N/A
8554490	12/2012	Tang et al.	N/A	N/A
8560968	12/2012	Nair	N/A	N/A
8715184	12/2013	Lazebnik	N/A	N/A
8768669	12/2013	Hart et al.	N/A	N/A
8771195	12/2013	Kim et al.	N/A	N/A
8787641	12/2013	Hof et al.	N/A	N/A
8812246	12/2013	Taylor	N/A	N/A
8824752	12/2013	Fonte et al.	N/A	N/A
8837860	12/2013	Grady et al.	N/A	N/A
8861820	12/2013	Fonte et al.	N/A	N/A
8917925	12/2013	Grady et al.	N/A	N/A
8934686	12/2014	Ostrovsky-Berman et al.	N/A	N/A
8970578	12/2014	Voros et al.	N/A	N/A
9008405	12/2014	Fonte et al.	N/A	N/A
9042611	12/2014	Blezek	382/128	G06V 20/64
9042613	12/2014	Spilker et al.	N/A	N/A
9070214	12/2014	Grady et al.	N/A	N/A
9078564	12/2014	Taylor	N/A	N/A
9087147	12/2014	Fonte	N/A	N/A
9129418	12/2014	Schormans et al.	N/A	N/A
9138147	12/2014	Schmitt et al.	N/A	N/A
9153047	12/2014	Grady et al.	N/A	N/A
9189600	12/2014	Spilker et al.	N/A	N/A
9256936	12/2015	Jacobs et al.	N/A	N/A
9314584	12/2015	Riley et al.	N/A	N/A
9375191	12/2015	Verstraelen et al.	N/A	N/A
9406141	12/2015	Kelm et al.	N/A	N/A
9430827	12/2015	Kelm et al.	N/A	N/A
9466117	12/2015	Habets et al.	N/A	N/A
9471999	12/2015	Ishii et al.	N/A	N/A
9572495	12/2016	Schmitt et al.	N/A	N/A
9576360	12/2016	Schormans et al.	N/A	N/A
9613186	12/2016	Fonte	N/A	N/A
9615755	12/2016	Riley et al.	N/A	N/A
9633454	12/2016	Lauritsch et al.	N/A	N/A
9646361	12/2016	Koo et al.	N/A	N/A
9706925	12/2016	Taylor	N/A	N/A
9743835	12/2016	Taylor	N/A	N/A
9754082	12/2016	Taylor et al.	N/A	N/A
9786068	12/2016	Ishii et al.	N/A	N/A
9801689	12/2016	Taylor	N/A	N/A
9805465	12/2016	Kyriakou	N/A	N/A
9814433	12/2016	Benishti et al.	N/A	N/A
9858387	12/2017	Lavi et al.	N/A	N/A

9870634	12/2017	Grady et al.	N/A	N/A
9888896	12/2017	Lauritsch et al.	N/A	N/A
9934566	12/2017	Sun et al.	N/A	N/A
9940736	12/2017	Ishii et al.	N/A	N/A
9943233	12/2017	Lavi et al.	N/A	N/A
9965873	12/2017	Grady et al.	N/A	N/A
9968256	12/2017	Taokowsky et al.	N/A	N/A
9977869	12/2017	Lavi et al.	N/A	N/A
9999361	12/2017	Sharma et al.	N/A	N/A
10141074	12/2017	Lavi et al.	N/A	N/A
10143390	12/2017	Ledoux et al.	N/A	N/A
10159529	12/2017	Taylor	N/A	N/A
10176575	12/2018	Isgum et al.	N/A	N/A
10210956	12/2018	Lavi et al.	N/A	N/A
10219704	12/2018	Lavi et al.	N/A	N/A
10229516	12/2018	Aben et al.	N/A	N/A
10235796	12/2018	Aben et al.	N/A	N/A
10245001	12/2018	Redel et al.	N/A	N/A
10342442	12/2018	Hattangadi et al.	N/A	N/A
10354744	12/2018	Sharma et al.	N/A	N/A
10360674	12/2018	Contini et al.	N/A	N/A
10363018	12/2018	Fukuda et al.	N/A	N/A
10373700	12/2018	Sharma et al.	N/A	N/A
10376165	12/2018	Lavi et al.	N/A	N/A
10395366	12/2018	Isgum et al.	N/A	N/A
10395774	12/2018	Lavi et al.	N/A	N/A
10420610	12/2018	Bai et al.	N/A	N/A
10424063	12/2018	Lavi et al.	N/A	N/A
10441235	12/2018	Lavi et al.	N/A	N/A
10441239	12/2018	Abe	N/A	N/A
10456094	12/2018	Fonte et al.	N/A	N/A
10463336	12/2018	Itu et al.	N/A	N/A
10470730	12/2018	Benishti et al.	N/A	N/A
10559388	12/2019	Lavi et al.	N/A	N/A
10580141	12/2019	Freiman et al.	N/A	N/A
10580526	12/2019	Ma et al.	N/A	N/A
10595807	12/2019	Lavi et al.	N/A	N/A
10631737	12/2019	Lavi et al.	N/A	N/A
10636146	12/2019	Zhong et al.	N/A	N/A
10650522	12/2019	Hoi et al.	N/A	N/A
10682180	12/2019	Taylor	N/A	N/A
10699407	12/2019	Isgum et al.	N/A	N/A
10702339	12/2019	Taylor	N/A	N/A
10733792	12/2019	Aben et al.	N/A	N/A
10740961	12/2019	Reiber et al.	N/A	N/A
10748285	12/2019	Igarashi et al.	N/A	N/A
10758200	12/2019	Passerini et al.	N/A	N/A
10776988	12/2019	Grady et al.	N/A	N/A
10803994	12/2019	Lavi et al.	N/A	N/A
10803995	12/2019	Sharma et al.	N/A	N/A

10828109	12/2019	Redel	N/A	N/A
10854329	12/2019	Mohr et al.	N/A	N/A
10964017	12/2020	Pack et al.	N/A	N/A
10964071	12/2020	Grady et al.	N/A	N/A
11004198	12/2020	Isgum et al.	N/A	N/A
11017531	12/2020	Harish et al.	N/A	N/A
11031136	12/2020	Grass et al.	N/A	N/A
11051779	12/2020	Turca et al.	N/A	N/A
11055845	12/2020	Nickisch et al.	N/A	N/A
11076770	12/2020	Lavi et al.	N/A	N/A
11081237	12/2020	Lavi et al.	N/A	N/A
11083377	12/2020	Bouwman et al.	N/A	N/A
11083524	12/2020	Taylor	N/A	N/A
11087884	12/2020	Sankaran et al.	N/A	N/A
11090118	12/2020	Taylor	N/A	N/A
11116575	12/2020	Taylor	N/A	N/A
11127503	12/2020	Rabbat et al.	N/A	N/A
11138733	12/2020	Lavi et al.	N/A	N/A
11141123	12/2020	Homann et al.	N/A	N/A
11160524	12/2020	Lavi et al.	N/A	N/A
11179043	12/2020	Haase et al.	N/A	N/A
11185368	12/2020	Spilker et al.	N/A	N/A
11195278	12/2020	Nickisch et al.	N/A	N/A
11202612	12/2020	Sakaguchi	N/A	N/A
11216944	12/2021	Reiber et al.	N/A	N/A
11272845	12/2021	Cheline et al.	N/A	N/A
11278208	12/2021	Lavi et al.	N/A	N/A
11282170	12/2021	Gauriau et al.	N/A	N/A
11288811	12/2021	Tu et al.	N/A	N/A
11288813	12/2021	Grady et al.	N/A	N/A
11295864	12/2021	Benishti et al.	N/A	N/A
11298187	12/2021	Taylor	N/A	N/A
11304665	12/2021	Sharma et al.	N/A	N/A
11308621	12/2021	Tu et al.	N/A	N/A
11328824	12/2021	Fonte	N/A	N/A
11341631	12/2021	Song et al.	N/A	N/A
11375904	12/2021	Igarashi	N/A	N/A
11382569	12/2021	Grady et al.	N/A	N/A
11389130	12/2021	Itu et al.	N/A	N/A
11398029	12/2021	Grady et al.	N/A	N/A
11406337	12/2021	Lavi et al.	N/A	N/A
11406339	12/2021	Mistretta et al.	N/A	N/A
11409422	12/2021	Olivan Bescos et al.	N/A	N/A
11410308	12/2021	Gulsun et al.	N/A	N/A
11423532	12/2021	Takahashi et al.	N/A	N/A
11424036	12/2021	Fonte et al.	N/A	N/A
11424038	12/2021	Grady et al.	N/A	N/A
11443428	12/2021	Petersen et al.	N/A	N/A
11445923	12/2021	Tu et al.	N/A	N/A

11462326	12/2021	Wang et al.	N/A	N/A
11462329	12/2021	Rabbat et al.	N/A	N/A
11468567	12/2021	Groth et al.	N/A	N/A
11482339	12/2021	Koo et al.	N/A	N/A
11490867	12/2021	Homann et al.	N/A	N/A
11494904	12/2021	Fonte et al.	N/A	N/A
11495357	12/2021	Ma et al.	N/A	N/A
11501485	12/2021	Grady et al.	N/A	N/A
11508460	12/2021	Wang et al.	N/A	N/A
11510587	12/2021	Kristanto et al.	N/A	N/A
11521755	12/2021	Taylor et al.	N/A	N/A
11523744	12/2021	Freiman et al.	N/A	N/A
11538161	12/2021	Wang et al.	N/A	N/A
11540931	12/2022	Grady et al.	N/A	N/A
11557036	12/2022	Liao et al.	N/A	N/A
11557069	12/2022	Senzig et al.	N/A	N/A
11559274	12/2022	Auvray et al.	N/A	N/A
11564746	12/2022	Spilker et al.	N/A	N/A
11564748	12/2022	Thienphrapa et al.	N/A	N/A
11574406	12/2022	Chen et al.	N/A	N/A
11576621	12/2022	Sharma et al.	N/A	N/A
11576626	12/2022	Fonte et al.	N/A	N/A
11576637	12/2022	Schmitt et al.	N/A	N/A
11576639	12/2022	Song et al.	N/A	N/A
11583340	12/2022	Taylor	N/A	N/A
11589924	12/2022	Passerini et al.	N/A	N/A
11599996	12/2022	Isgum et al.	N/A	N/A
11607189	12/2022	Tu et al.	N/A	N/A
11610309	12/2022	Kweon et al.	N/A	N/A
11610318	12/2022	Grady et al.	N/A	N/A
11615529	12/2022	Chitiboi	N/A	N/A
11615894	12/2022	Lavi et al.	N/A	N/A
11617620	12/2022	Tran et al.	N/A	N/A
11633118	12/2022	Freiman et al.	N/A	N/A
11638609	12/2022	Sankaran et al.	N/A	N/A
11642171	12/2022	Jaquet et al.	N/A	N/A
11653833	12/2022	Sanders et al.	N/A	N/A
11664128	12/2022	Haase et al.	N/A	N/A
11666236	12/2022	Lavi et al.	N/A	N/A
11672434	12/2022	Tochterman et al.	N/A	N/A
11678853	12/2022	Gulsun et al.	N/A	N/A
11678937	12/2022	Choi et al.	N/A	N/A
11688502	12/2022	Anderson et al.	N/A	N/A
11690518	12/2022	Haase et al.	N/A	N/A
11694339	12/2022	Schormans et al.	N/A	N/A
11707196	12/2022	Lavi et al.	N/A	N/A
11707242	12/2022	Van Walsum et al.	N/A	N/A
11710569	12/2022	Grass et al.	N/A	N/A
11728037	12/2022	Lavi et al.	N/A	N/A
11741574	12/2022	Kweon et al.	N/A	N/A

11741602	12/2022	Reiber et al.	N/A	N/A
11744472	12/2022	Zhao et al.	N/A	N/A
11744544	12/2022	Sheehan et al.	N/A	N/A
11748902	12/2022	Bai et al.	N/A	N/A
11756195	12/2022	Kweon et al.	N/A	N/A
11769254	12/2022	Song et al.	N/A	N/A
11776149	12/2022	Wang et al.	N/A	N/A
11779225	12/2022	Adiyoso	N/A	N/A
11779233	12/2022	Huo et al.	N/A	N/A
11779294	12/2022	Liu et al.	N/A	N/A
11786202	12/2022	Yin et al.	N/A	N/A
11793575	12/2022	Taylor	N/A	N/A
11803966	12/2022	Denzinger et al.	N/A	N/A
11810290	12/2022	Flohr et al.	N/A	N/A
11810661	12/2022	Barley et al.	N/A	N/A
11816836	12/2022	Isgum et al.	N/A	N/A
11816837	12/2022	Lavi et al.	N/A	N/A
11826106	12/2022	Hart et al.	N/A	N/A
11826175	12/2022	Itu et al.	N/A	N/A
11847547	12/2022	Wang et al.	N/A	N/A
11861825	12/2023	Van Pelt et al.	N/A	N/A
11861839	12/2023	Weese et al.	N/A	N/A
11861851	12/2023	Figueroa-Alvarez et al.	N/A	N/A
11869142	12/2023	Bai et al.	N/A	N/A
11883225	12/2023	Sankaran et al.	N/A	N/A
11896416	12/2023	Huo et al.	N/A	N/A
11901081	12/2023	Huo et al.	N/A	N/A
11918291	12/2023	Grass et al.	N/A	N/A
11931195	12/2023	Itu et al.	N/A	N/A
11937963	12/2023	Lavi et al.	N/A	N/A
11944387	12/2023	Sankaran et al.	N/A	N/A
11948677	12/2023	Ghose et al.	N/A	N/A
11948695	12/2023	Taylor et al.	N/A	N/A
11980492	12/2023	Venugopal et al.	N/A	N/A
11983473	12/2023	Aben et al.	N/A	N/A
11986280	12/2023	Grady et al.	N/A	N/A
11995834	12/2023	Neumann et al.	N/A	N/A
12016635	12/2023	Taylor	N/A	N/A
12023189	12/2023	Haase et al.	N/A	N/A
12027253	12/2023	Schoebinger et al.	N/A	N/A
12029494	12/2023	Taylor	N/A	N/A
12039729	12/2023	Kweon et al.	N/A	N/A
12048575	12/2023	Vaillant et al.	N/A	N/A
12051192	12/2023	Aben et al.	N/A	N/A
12051202	12/2023	Freiman et al.	N/A	N/A
12051497	12/2023	Grady et al.	N/A	N/A
12062198	12/2023	Liu et al.	N/A	N/A
12067729	12/2023	Thamm et al.	N/A	N/A
12079994	12/2023	Lavi et al.	N/A	N/A

12089977	12/2023	Isgum et al.	N/A	N/A
12094112	12/2023	Gulsun et al.	N/A	N/A
12094188	12/2023	Li et al.	N/A	N/A
12094596	12/2023	Wang et al.	N/A	N/A
12100174	12/2023	Vaillant et al.	N/A	N/A
12100502	12/2023	Cimen et al.	N/A	N/A
12109061	12/2023	Itu et al.	N/A	N/A
12109065	12/2023	Sheehan et al.	N/A	N/A
12112471	12/2023	Viti et al.	N/A	N/A
12112483	12/2023	Grady et al.	N/A	N/A
12115014	12/2023	Haase et al.	N/A	N/A
12118724	12/2023	Van Pelt et al.	N/A	N/A
12119117	12/2023	Wang et al.	N/A	N/A
12125217	12/2023	Venugopal et al.	N/A	N/A
12125261	12/2023	Petersen et al.	N/A	N/A
12131525	12/2023	Groth et al.	N/A	N/A
12136209	12/2023	Haase et al.	N/A	N/A
12138026	12/2023	Grady et al.	N/A	N/A
12138027	12/2023	Lavi et al.	N/A	N/A
12142384	12/2023	Rabbat et al.	N/A	N/A
12175631	12/2023	Kweon et al.	N/A	N/A
12175669	12/2023	Wang et al.	N/A	N/A
12176094	12/2023	Taylor et al.	N/A	N/A
12178557	12/2023	Grady et al.	N/A	N/A
2003/0105401	12/2002	Jago et al.	N/A	N/A
2004/0019264	12/2003	Suurmond et al.	N/A	N/A
2004/0066958	12/2003	Chen et al.	N/A	N/A
2005/0041842	12/2004	Frakes et al.	N/A	N/A
2005/0043614	12/2004	Huizenga et al.	N/A	N/A
2005/0249327	12/2004	Wink et al.	N/A	N/A
2005/0272992	12/2004	O'Donnell et al.	N/A	N/A
2006/0036167	12/2005	Shina	N/A	N/A
2006/0074285	12/2005	Zarkh et al.	N/A	N/A
2006/0084862	12/2005	Suurmond et al.	N/A	N/A
2007/0031019	12/2006	Lesage et al.	N/A	N/A
2007/0167833	12/2006	Redel et al.	N/A	N/A
2008/0020362	12/2007	Cotin et al.	N/A	N/A
2008/0187199	12/2007	Gulsun et al.	N/A	N/A
2008/0205722	12/2007	Schaefer et al.	N/A	N/A
2009/0016483	12/2008	Kawasaki et al.	N/A	N/A
2009/0016587	12/2008	Strobel et al.	N/A	N/A
2009/0171321	12/2008	Callaghan	N/A	N/A
2009/0299640	12/2008	Ellis et al.	N/A	N/A
2009/0312648	12/2008	Zhang et al.	N/A	N/A
2010/0010428	12/2009	Yu et al.	N/A	N/A
2010/0017171	12/2009	Spilker et al.	N/A	N/A
2010/0021025	12/2009	Hof et al.	N/A	N/A
2010/0067760	12/2009	Zhang et al.	N/A	N/A
2010/0125197	12/2009	Fishel	N/A	N/A
2010/0160764	12/2009	Steinberg et al.	N/A	N/A

2010/0160773	12/2009	Cohen et al.	N/A	N/A
2010/0220917	12/2009	Steinberg et al.	N/A	N/A
2010/0296709	12/2009	Ostrovsky-Berman et al.	N/A	N/A
2010/0298719	12/2009	Thrysoe et al.	N/A	N/A
2011/0015530	12/2010	Misawa	N/A	N/A
2011/0096907	12/2010	Mohamed	N/A	N/A
2011/0134433	12/2010	Yamada	N/A	N/A
2011/0135175	12/2010	Ostrovsky-Berman et al.	N/A	N/A
2011/0142313	12/2010	Pack et al.	N/A	N/A
2011/0182492	12/2010	Grass et al.	N/A	N/A
2012/0014574	12/2011	Ferschel et al.	N/A	N/A
2012/0041318	12/2011	Taylor	N/A	N/A
2012/0041739	12/2011	Taylor	N/A	N/A
2012/0053918	12/2011	Taylor	N/A	N/A
2012/0053919	12/2011	Taylor	N/A	N/A
2012/0053921	12/2011	Taylor	N/A	N/A
2012/0059246	12/2011	Taylor	N/A	N/A
2012/0059249	12/2011	Verard et al.	N/A	N/A
2012/0062841	12/2011	Stetson et al.	N/A	N/A
2012/0072190	12/2011	Sharma et al.	N/A	N/A
2012/0075284	12/2011	Rivers et al.	N/A	N/A
2012/0150048	12/2011	Kang et al.	N/A	N/A
2012/0177275	12/2011	Suri	N/A	N/A
2012/0230565	12/2011	Steinberg et al.	N/A	N/A
2012/0236032	12/2011	Arvidsson	N/A	N/A
2012/0243761	12/2011	Senzig et al.	N/A	N/A
2013/0054214	12/2012	Taylor	N/A	N/A
2013/0060133	12/2012	Kassab et al.	N/A	N/A
2013/0094745	12/2012	Sundar	N/A	N/A
2013/0158476	12/2012	Olson	N/A	N/A
2013/0182936	12/2012	Yoshihara et al.	N/A	N/A
2013/0226003	12/2012	Edic et al.	N/A	N/A
2013/0229621	12/2012	Stetson et al.	N/A	N/A
2013/0324842	12/2012	Mittal et al.	N/A	N/A
2014/0005535	12/2013	Edic et al.	N/A	N/A
2014/0046642	12/2013	Hart et al.	N/A	N/A
2014/0086461	12/2013	Yao et al.	N/A	N/A
2014/0094693	12/2013	Cohen et al.	N/A	N/A
2014/0094697	12/2013	Petroff et al.	N/A	N/A
2014/0100451	12/2013	Tolkowsky et al.	N/A	N/A
2014/0121513	12/2013	Tolkowsky et al.	N/A	N/A
2014/0142398	12/2013	Patil et al.	N/A	N/A
2014/0200867	12/2013	Lavi et al.	N/A	N/A
2014/0249790	12/2013	Spilker et al.	N/A	N/A
2014/0270442	12/2013	Jung	382/131	A61B 5/026
2014/0303495	12/2013	Fonte et al.	N/A	N/A
2014/0371578	12/2013	Auvray et al.	N/A	N/A

2015/0201897	12/2014	Kyriakou	N/A	N/A
2015/0213600	12/2014	Kyriakou	N/A	N/A
2015/0250395	12/2014	Igarashi	N/A	N/A
2015/0265162	12/2014	Lavi et al.	N/A	N/A
2015/0265222	12/2014	Sakaguchi	N/A	N/A
2015/0297373	12/2014	Schmitt et al.	N/A	N/A
2015/0302578	12/2014	Grady et al.	N/A	N/A
2015/0335304	12/2014	Lavi et al.	N/A	N/A
2015/0339847	12/2014	Benishti et al.	N/A	N/A
2015/0342551	12/2014	Lavi et al.	N/A	N/A
2016/0007945	12/2015	Taylor	N/A	N/A
2016/0015349	12/2015	Ohuchi et al.	N/A	N/A
2016/0022371	12/2015	Sauer et al.	N/A	N/A
2016/0035088	12/2015	Abramoff et al.	N/A	N/A
2016/0035103	12/2015	Stawiaski	382/130	G06T 7/11
2016/0073928	12/2015	Soper et al.	N/A	N/A
2016/0110866	12/2015	Taylor	N/A	N/A
2016/0110867	12/2015	Taylor	N/A	N/A
2016/0128661	12/2015	Taylor	N/A	N/A
2016/0157802	12/2015	Anderson	N/A	N/A
2016/0228000	12/2015	Spaide	N/A	N/A
2016/0247279	12/2015	Lavi et al.	N/A	N/A
2016/0371456	12/2015	Taylor et al.	N/A	N/A
2017/0018116	12/2016	Sun et al.	N/A	N/A
2017/0039736	12/2016	Aben et al.	N/A	N/A
2017/0224418	12/2016	Boettner et al.	N/A	N/A
2017/0286628	12/2016	Shim	N/A	N/A
2017/0325770	12/2016	Edic et al.	N/A	N/A
2018/0032653	12/2017	Aben et al.	N/A	N/A
2018/0075221	12/2017	Vergaro et al.	N/A	N/A
2018/0089829	12/2017	Zhong et al.	N/A	N/A
2018/0102189	12/2017	Hosoi et al.	N/A	N/A
2018/0182096	12/2017	Grady et al.	N/A	N/A
2018/0211386	12/2017	Ma et al.	N/A	N/A
2018/0235561	12/2017	Lavi et al.	N/A	N/A
2018/0243033	12/2017	Tran et al.	N/A	N/A
2018/0268941	12/2017	Lavi et al.	N/A	N/A
2018/0271614	12/2017	Kunio	N/A	N/A
2018/0280088	12/2017	Davies	N/A	N/A
2018/0315193	12/2017	Paschalakis et al.	N/A	N/A
2018/0330507	12/2017	Schormans et al.	N/A	N/A
2018/0344173	12/2017	Tu et al.	N/A	N/A
2018/0344174	12/2017	Schmitt et al.	N/A	N/A
2019/0005737	12/2018	Auvray et al.	N/A	N/A
2019/0019347	12/2018	Auvray et al.	N/A	N/A
2019/0130578	12/2018	Gulsun et al.	N/A	N/A
2019/0156159	12/2018	Kopparapu	N/A	N/A
2019/0172205	12/2018	Mao	N/A	G06T 7/0014
2019/0180880	12/2018	Lavi et al.	N/A	N/A

2019/0282199	12/2018	Merritt	N/A	N/A
2019/0380593	12/2018	Bouwman et al.	N/A	N/A
2020/0126229	12/2019	Lavi et al.	N/A	N/A
2020/0138521	12/2019	Aben et al.	N/A	N/A
2020/0160509	12/2019	Pack et al.	N/A	N/A
2020/0222018	12/2019	van Walsum et al.	N/A	N/A
2020/0226422	12/2019	Li et al.	N/A	N/A
2020/0265958	12/2019	Haase et al.	N/A	N/A
2020/0337664	12/2019	Homann et al.	N/A	N/A
2020/0349708	12/2019	Igarashi et al.	N/A	N/A
2020/0394795	12/2019	Isgum et al.	N/A	N/A
2021/0022617	12/2020	Zhao et al.	N/A	N/A
2021/0035290	12/2020	Aben et al.	N/A	N/A
2021/0085397	12/2020	Passerini et al.	N/A	N/A
2021/0209757	12/2020	Min et al.	N/A	N/A
2021/0244293	12/2020	Belleville	N/A	N/A
2021/0244475	12/2020	Taylor	N/A	N/A
2021/0259559	12/2020	Tu et al.	N/A	N/A
2021/0267690	12/2020	Taylor	N/A	N/A
2021/0272030	12/2020	Sankaran et al.	N/A	N/A
2021/0275124	12/2020	Huo et al.	N/A	N/A
2021/0280318	12/2020	Huo et al.	N/A	N/A
2021/0282731	12/2020	Vaillant et al.	N/A	N/A
2021/0282860	12/2020	Taylor	N/A	N/A
2021/0290308	12/2020	Mihalef et al.	N/A	N/A
2021/0298706	12/2020	Tu et al.	N/A	N/A
2021/0298708	12/2020	Aben et al.	N/A	N/A
2021/0334963	12/2020	Isgum et al.	N/A	N/A
2021/0338088	12/2020	Bouwman et al.	N/A	N/A
2021/0345889	12/2020	Tu et al.	N/A	N/A
2021/0358634	12/2020	Sankaran et al.	N/A	N/A
2021/0361174	12/2020	Lavi et al.	N/A	N/A
2021/0361176	12/2020	Huo et al.	N/A	N/A
2021/0374950	12/2020	Gao et al.	N/A	N/A
2021/0375474	12/2020	Lavi et al.	N/A	N/A
2021/0383539	12/2020	Haase et al.	N/A	N/A
2021/0401400	12/2020	Sheehan et al.	N/A	N/A
2022/0012876	12/2021	Sommer et al.	N/A	N/A
2022/0012878	12/2021	Aoyama	N/A	N/A
2022/0015730	12/2021	Haase et al.	N/A	N/A
2022/0028080	12/2021	Lavi et al.	N/A	N/A
2022/0036646	12/2021	Song et al.	N/A	N/A
2022/0039769	12/2021	M et al.	N/A	N/A
2022/0047236	12/2021	Lavi et al.	N/A	N/A
2022/0054022	12/2021	Van Lavieren	N/A	N/A
2022/0079455	12/2021	Haase et al.	N/A	N/A
2022/0079540	12/2021	Sankaran et al.	N/A	N/A
2022/0079563	12/2021	Kemp	N/A	N/A
2022/0087544	12/2021	Schmitt et al.	N/A	N/A
2022/0092775	12/2021	Denzinger et al.	N/A	N/A

2022/0092784	12/2021	Tu et al.	N/A	N/A
2022/0101535	12/2021	Thamm et al.	N/A	N/A
2022/0110687	12/2021	Spilker et al.	N/A	N/A
2022/0125398	12/2021	Aben	N/A	N/A
2022/0151580	12/2021	Itu et al.	N/A	N/A
2022/0156918	12/2021	Chitiboi et al.	N/A	N/A
2022/0164950	12/2021	Aben et al.	N/A	N/A
2022/0164953	12/2021	Gulsun et al.	N/A	N/A
2022/0167938	12/2021	Grass et al.	N/A	N/A
2022/0172368	12/2021	Lavi et al.	N/A	N/A
2022/0183655	12/2021	Huang et al.	N/A	N/A
2022/0211280	12/2021	Lavi et al.	N/A	N/A
2022/0211439	12/2021	Sankaran et al.	N/A	N/A
2022/0215534	12/2021	Bai et al.	N/A	N/A
2022/0230312	12/2021	Choi et al.	N/A	N/A
2022/0233081	12/2021	Cheline et al.	N/A	N/A
2022/0254028	12/2021	Liu et al.	N/A	N/A
2022/0254131	12/2021	Lavi et al.	N/A	N/A
2022/0261997	12/2021	Liu et al.	N/A	N/A
2022/0262000	12/2021	Haase et al.	N/A	N/A
2022/0273180	12/2021	Lavi et al.	N/A	N/A
2022/0277447	12/2021	Wang et al.	N/A	N/A
2022/0285034	12/2021	Lavi et al.	N/A	N/A
2022/0287668	12/2021	Gulsun et al.	N/A	N/A
2022/0301156	12/2021	Fang et al.	N/A	N/A
2022/0310265	12/2021	Benishti et al.	N/A	N/A
2022/0319004	12/2021	Bruch-El et al.	N/A	N/A
2022/0319116	12/2021	Wang et al.	N/A	N/A
2022/0335612	12/2021	Bruch-El et al.	N/A	N/A
2022/0344033	12/2021	Wang et al.	N/A	N/A
2022/0351369	12/2021	Haase et al.	N/A	N/A
2022/0359063	12/2021	Tombropoulos et al.	N/A	N/A
2022/0378383	12/2021	Chen et al.	N/A	N/A
2022/0392616	12/2021	Ghose et al.	N/A	N/A
2022/0415510	12/2021	Wang et al.	N/A	N/A
2023/0005113	12/2022	Li et al.	N/A	N/A
2023/0028300	12/2022	Lichy et al.	N/A	N/A
2023/0037338	12/2022	Wang et al.	N/A	N/A
2023/0038364	12/2022	Bhowmick et al.	N/A	N/A
2023/0052595	12/2022	Langoju et al.	N/A	N/A
2023/0071558	12/2022	Vaidya et al.	N/A	N/A
2023/0084748	12/2022	Lavi et al.	N/A	N/A
2023/0086196	12/2022	Chitiboi et al.	N/A	N/A
2023/0095242	12/2022	Liu et al.	N/A	N/A
2023/0097133	12/2022	Bai et al.	N/A	N/A
2023/0097267	12/2022	Schwemmer et al.	N/A	N/A
2023/0102646	12/2022	Birkhold et al.	N/A	N/A
2023/0108647	12/2022	Tu et al.	N/A	N/A
2023/0113721	12/2022	Kassel et al.	N/A	N/A

2023/0142152	12/2022	Venugopal et al.	N/A	N/A
2023/0142219	12/2022	Makino	N/A	N/A
2023/0144624	12/2022	Venugopal et al.	N/A	N/A
2023/0144795	12/2022	Wang et al.	N/A	N/A
2023/0148977	12/2022	Fonte et al.	N/A	N/A
2023/0177677	12/2022	Yuan et al.	N/A	N/A
2023/0186472	12/2022	Kweon et al.	N/A	N/A
2023/0196582	12/2022	Grady et al.	N/A	N/A
2023/0197286	12/2022	Grady et al.	N/A	N/A
2023/0230235	12/2022	Isgum et al.	N/A	N/A
2023/0237648	12/2022	Gulsun et al.	N/A	N/A
2023/0237652	12/2022	Flexman et al.	N/A	N/A
2023/0245301	12/2022	Wang et al.	N/A	N/A
2023/0252628	12/2022	Haase et al.	N/A	N/A
2023/0263401	12/2022	Escaned-Barbosa et al.	N/A	N/A
2023/0277247	12/2022	Taylor et al.	N/A	N/A
2023/0282365	12/2022	Lavi et al.	N/A	N/A
2023/0298176	12/2022	Choi et al.	N/A	N/A
2023/0298180	12/2022	Kweon	382/128	A61B 6/481
2023/0307144	12/2022	He et al.	N/A	N/A
2023/0309943	12/2022	van Walsum et al.	N/A	N/A
2023/0320789	12/2022	Bai et al.	N/A	N/A
2023/0326127	12/2022	Zhong et al.	N/A	N/A
2023/0334659	12/2022	Kuo et al.	N/A	N/A
2023/0346236	12/2022	Lavi et al.	N/A	N/A
2023/0352152	12/2022	Grady et al.	N/A	N/A
2023/0355107	12/2022	Haase et al.	N/A	N/A
2023/0355196	12/2022	Kang et al.	N/A	N/A
2023/0355197	12/2022	Florent et al.	N/A	N/A
2023/0360803	12/2022	Sankaran et al.	N/A	N/A
2023/0368378	12/2022	Kim et al.	N/A	N/A
2023/0386037	12/2022	Denzinger et al.	N/A	N/A
2023/0394654	12/2022	Hampe et al.	N/A	N/A
2023/0404525	12/2022	Sheehan et al.	N/A	N/A
2023/0410307	12/2022	Nickisch et al.	N/A	N/A
2024/0029529	12/2023	Scalisi	N/A	N/A
2024/0029868	12/2023	Gulsun et al.	N/A	N/A
2024/0046465	12/2023	Sharma et al.	N/A	N/A
2024/0047043	12/2023	Flexman et al.	N/A	N/A
2024/0050159	12/2023	Hart et al.	N/A	N/A
2024/0065772	12/2023	Levi et al.	N/A	N/A
2024/0078676	12/2023	Van Pelt et al.	N/A	N/A
2024/0096479	12/2023	Kraus et al.	N/A	N/A
2024/0099589	12/2023	Lavi et al.	N/A	N/A
2024/0099683	12/2023	Cimen et al.	N/A	N/A
2024/0104719	12/2023	Gulsun et al.	N/A	N/A
2024/0126958	12/2023	Aben et al.	N/A	N/A
2024/0130674	12/2023	Sonck et al.	N/A	N/A

2024/0130796	12/2023	Song et al.	N/A	N/A
2024/0153087	12/2023	Lavi et al.	N/A	N/A
2024/0164865	12/2023	Kottenstette et al.	N/A	N/A
2024/0169540	12/2023	Bouwman et al.	N/A	N/A
2024/0185485	12/2023	Salomon et al.	N/A	N/A
2024/0185509	12/2023	Kovler et al.	N/A	N/A
2024/0206838	12/2023	Lavi et al.	N/A	N/A
2024/0212159	12/2023	Katzmann et al.	N/A	N/A
2024/0215937	12/2023	Itu et al.	N/A	N/A
2024/0221355	12/2023	Kweon et al.	N/A	N/A
2024/0260919	12/2023	Venugopal et al.	N/A	N/A
2024/0273723	12/2023	Tison et al.	N/A	N/A
2024/0315777	12/2023	Choi et al.	N/A	N/A
2024/0374148	12/2023	Haase et al.	N/A	N/A
2024/0386652	12/2023	Grady et al.	N/A	N/A
2024/0394875	12/2023	Van Der Horst et al.	N/A	N/A
2024/0394996	12/2023	Hitschrich et al.	N/A	N/A
2024/0404031	12/2023	Auvray et al.	N/A	N/A
2024/0404057	12/2023	Florent et al.	N/A	N/A
2024/0407656	12/2023	This et al.	N/A	N/A
2024/0412365	12/2023	Kim	N/A	N/A
2024/0420331	12/2023	Kim et al.	N/A	N/A
2024/0423575	12/2023	Itu et al.	N/A	N/A
2024/0428477	12/2023	Salehi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010298333	12/2011	AU	N/A
104282009	12/2014	CN	N/A
113837985	12/2020	CN	N/A
113935976	12/2021	CN	N/A
1396274	12/2003	EP	N/A
2163272	12/2009	EP	N/A
2633815	12/2012	EP	N/A
2779907	12/2013	EP	N/A
2873371	12/2014	EP	N/A
3125764	12/2016	EP	N/A
2633815	12/2016	EP	N/A
3363350	12/2017	EP	N/A
2977922	12/2018	EP	N/A
3460688	12/2018	EP	N/A
3477551	12/2018	EP	N/A
3763285	12/2020	EP	N/A
3847956	12/2020	EP	N/A
2776960	12/2020	EP	N/A
3534372	12/2020	EP	N/A
3871184	12/2020	EP	N/A
3881758	12/2020	EP	N/A

3884868	12/2020	EP	N/A
3282380	12/2020	EP	N/A
3282381	12/2020	EP	N/A
3903672	12/2020	EP	N/A
3912139	12/2020	EP	N/A
3664026	12/2021	EP	N/A
3945469	12/2021	EP	N/A
3949860	12/2021	EP	N/A
3951705	12/2021	EP	N/A
3076854	12/2021	EP	N/A
3979259	12/2021	EP	N/A
3982324	12/2021	EP	N/A
3258446	12/2021	EP	N/A
4002288	12/2021	EP	N/A
4026143	12/2021	EP	N/A
4026491	12/2021	EP	N/A
4026492	12/2021	EP	N/A
4029438	12/2021	EP	N/A
3298959	12/2021	EP	N/A
3989828	12/2021	EP	N/A
3157411	12/2021	EP	N/A
3606437	12/2021	EP	N/A
4104765	12/2021	EP	N/A
4113434	12/2022	EP	N/A
4131150	12/2022	EP	N/A
4137053	12/2022	EP	N/A
4145391	12/2022	EP	N/A
4156112	12/2022	EP	N/A
3169237	12/2022	EP	N/A
4160528	12/2022	EP	N/A
4160543	12/2022	EP	N/A
4170579	12/2022	EP	N/A
4186417	12/2022	EP	N/A
3403582	12/2022	EP	N/A
3743883	12/2022	EP	N/A
3989832	12/2022	EP	N/A
4220553	12/2022	EP	N/A
4224416	12/2022	EP	N/A
3652747	12/2022	EP	N/A
4104766	12/2022	EP	N/A
4238500	12/2022	EP	N/A
3602485	12/2022	EP	N/A
4064181	12/2022	EP	N/A
3602487	12/2022	EP	N/A
4300419	12/2023	EP	N/A
4312184	12/2023	EP	N/A
3404667	12/2023	EP	N/A
3878366	12/2023	EP	N/A
3457413	12/2023	EP	N/A
4005472	12/2023	EP	N/A

4369290	12/2023	EP	N/A
4176814	12/2023	EP	N/A
4413927	12/2023	EP	N/A
4418206	12/2023	EP	N/A
3846176	12/2023	EP	N/A
3881758	12/2023	EP	N/A
3564963	12/2023	EP	N/A
4056110	12/2023	EP	N/A
H08-131429	12/1995	JP	N/A
2003-508152	12/2002	JP	N/A
2003-514600	12/2002	JP	N/A
2004-243117	12/2003	JP	N/A
2007-502644	12/2006	JP	N/A
2007-325920	12/2006	JP	N/A
4177217	12/2007	JP	N/A
2010-042247	12/2009	JP	N/A
2011-212314	12/2010	JP	N/A
2013-090799	12/2012	JP	N/A
2010-505493	12/2012	JP	N/A
2013-534154	12/2012	JP	N/A
2014-064915	12/2013	JP	N/A
2014-128631	12/2013	JP	N/A
2015-503416	12/2014	JP	N/A
2015-527901	12/2014	JP	N/A
2016-509501	12/2015	JP	N/A
2017-516535	12/2016	JP	N/A
2018-057835	12/2017	JP	N/A
2018-089364	12/2017	JP	N/A
2012324	12/2014	NL	N/A
WO 2001/21057	12/2000	WO	N/A
WO 2007/066249	12/2006	WO	N/A
WO 2010/033971	12/2009	WO	N/A
WO 2011/038044	12/2010	WO	N/A
WO 2011/039685	12/2010	WO	N/A
WO 2012/021037	12/2011	WO	N/A
WO 2012/021307	12/2011	WO	N/A
WO 2012/043498	12/2011	WO	N/A
WO 2012/173697	12/2011	WO	N/A
WO 2013/102880	12/2012	WO	N/A
WO 2014/027692	12/2013	WO	N/A
WO 2014/064702	12/2013	WO	N/A
WO 2014/111927	12/2013	WO	N/A
WO 2014/111929	12/2013	WO	N/A
WO 2014/111930	12/2013	WO	N/A
WO 2015/017420	12/2014	WO	N/A
WO 2015/059706	12/2014	WO	N/A
WO 2016/161356	12/2015	WO	N/A
WO 2017/056007	12/2016	WO	N/A
WO 2017/199245	12/2016	WO	N/A
WO 2017/199246	12/2016	WO	N/A

WO 2017/200381	12/2016	WO	N/A
WO 2018/165478	12/2017	WO	N/A
WO 2018/178272	12/2017	WO	N/A
WO 2019/101630	12/2018	WO	N/A
WO 2020/053099	12/2019	WO	N/A
WO 2020/084101	12/2019	WO	N/A
WO 2020/201942	12/2019	WO	N/A
WO 2021/016071	12/2020	WO	N/A
WO 2021/059165	12/2020	WO	N/A
WO 2021/175039	12/2020	WO	N/A
WO 2021/191909	12/2020	WO	N/A
WO 2021/258835	12/2020	WO	N/A
WO 2022/000727	12/2021	WO	N/A
WO 2022/000729	12/2021	WO	N/A
WO 2022/000733	12/2021	WO	N/A
WO 2022/000734	12/2021	WO	N/A
WO 2022/000976	12/2021	WO	N/A
WO 2022/000977	12/2021	WO	N/A
WO 2022/002765	12/2021	WO	N/A
WO 2022/019765	12/2021	WO	N/A
WO 2022/069208	12/2021	WO	N/A
WO 2022/086326	12/2021	WO	N/A
WO 2022/109902	12/2021	WO	N/A
WO 2022/109903	12/2021	WO	N/A
WO 2022/109904	12/2021	WO	N/A
WO 2022/109907	12/2021	WO	N/A
WO 2022/136043	12/2021	WO	N/A
WO 2022/161239	12/2021	WO	N/A
WO 2022/167940	12/2021	WO	N/A
WO 2022/184736	12/2021	WO	N/A
WO 2022/199238	12/2021	WO	N/A
WO 2022/235162	12/2021	WO	N/A
WO 2022/261641	12/2021	WO	N/A
WO 2023/277283	12/2022	WO	N/A
WO 2023/057296	12/2022	WO	N/A
WO 2023/099144	12/2022	WO	N/A
WO 2023/104538	12/2022	WO	N/A
WO 2023/115576	12/2022	WO	N/A
WO 2023/146401	12/2022	WO	N/A
WO 2023/152688	12/2022	WO	N/A
WO 2023/191380	12/2022	WO	N/A
WO 2023/224369	12/2022	WO	N/A
WO 2022/228464	12/2022	WO	N/A
WO 2024/022809	12/2023	WO	N/A
WO 2024/023048	12/2023	WO	N/A
WO 2024/034748	12/2023	WO	N/A
WO 2024/074309	12/2023	WO	N/A
WO 2024/083538	12/2023	WO	N/A
WO 2024/121060	12/2023	WO	N/A
WO 2024/151926	12/2023	WO	N/A

WO 2024/156859	12/2023	WO	N/A
WO 2024/160583	12/2023	WO	N/A
WO 2024/177428	12/2023	WO	N/A

OTHER PUBLICATIONS

Abraham et al., “Alternative routes in road networks”, ACM Journal of Experimental Algorithmics, Association of Computing Machinery, vol. 18(1):1.3:2-1.3:17 (2013). cited by applicant

Andriotis et al., “A new method of three-dimensional coronary artery reconstruction from X-Ray angiography: Validation against a virtual phantom and multislice computed tomography”, Catheterization and Cardiovascular Interventions, vol. 71:28-43 (2008). cited by applicant

Barnea, “Model-based estimation of coronary vessel diameter in angiographic images”, Proceedings of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, vol. 20:513-516 (1998). cited by applicant

Barratt et al., “Reconstruction and quantification of the carotid artery bifurcation from 3-D ultrasound images”, IEEE Transactions on Medical Imaging, vol. 23(5):567-583 (2004). cited by applicant

Bullitt et al., “Determining malignancy of brain tumors by analysis of vessel shape”, Medical Image Computing and Computer-Assisted Intervention, MICCAI 2004 Conference Proceedings, Lecture notes in Computer Science, LNCS, 3217:645-653. cited by applicant

Caiati et al., “New noninvasive method for coronary flow reserve assessment: Contrast-enhanced transthoracic second harmonic echo doppler”, Circulation, vol. 99:771-778 (1999). cited by applicant

Caiati et al., “Detection, location, and severity assessment of left anterior descending coronary artery stenoses by means of contrast-enhanced transthoracic harmonic echo doppler”, European Heart Journal, vol. 30:1797-1806 (2009). cited by applicant

Chung, “Image segmentation methods for detecting blood vessels in angiography”, 2006 9th International Conference on Control, Automation, Robotics and Vision, Singapore, pp. 1-6 (2006). cited by applicant

Dickie et al., “Live-vessel: interactive vascular image segmentation with simultaneous extraction of optimal medial and boundary paths”, Technical Report TR 2009-23, School of Computing Science, Simon Fraser University, Burnaby, BC, Canada, Nov. 2009. cited by applicant

Frangi et al., “Multiscale vessel and enhancement filtering”, Medical Image Computing and Computer-Assisted Intervention, MICCA '98 Lecture Notes in Computer Science, vol. 1496:130-137 (1998). cited by applicant

Fraz, “Blood vessel segmentation methodologies, in retinal images—a survey”, Computer Methods and Programs in Biomedicine, vol. 108:407-433 (2012). cited by applicant

Fusejima, “Noninvasive measurement of coronary artery blood flow using combined two-dimensional and doppler echocardiography”, JACC vol. 10(5):1024-1031 (1987). cited by applicant

Hawkes et al., “Validation of volume blood flow measurements using three-dimensional distance-concentration functions derived from digital X-Ray angiograms”, Investigative Radiology, vol. 29(4):434-442 (1994). cited by applicant

Hoffmann et al., “Determination of instantaneous and average blood flow rates from digital angiograms of vessel phantoms using distance-density curves”, Investigative Radiology, vol. 26(3):207-212 (1991). cited by applicant

Holdsworth et al., “Quantitative angiographic blood-flow measurement using pulsed intra-arterial injection”, Medical Physics, vol. 26(10):2168-2175 (1999). cited by applicant

Huo et al., “Intraspecific scaling laws of vascular trees”, J.R. Soc. Interface vol. 9:190-200 (2012). cited by applicant

Janssen et al., “New approaches for the assessment of vessel sizes in quantitative (cardio-)vascular

X-ray analysis”, *Int J Cardiovasc Imaging* vol. 26:259-271 (2010). cited by applicant

Kappetein et al, “Current percutaneous coronary intervention and coronary artery bypass grafting practices for three-vessel and left main coronary artery disease: Insights from the SYNTAX run-in phase”, *European Journal of Cardio-Thoracic Surgery*, vol. 29:486-491 (2010). cited by applicant

Kass et al., “Snakes: active contour models”, *Int. J. Comput. Vis.* vol. 1:321-331 (1987). cited by applicant

Kirkeeide, “Coronary obstructions, morphology and physiologic significance”, *Quantitative Coronary Arteriography*, Chap. 11:229-244 (1991). cited by applicant

Lethen et al., “Validation of noninvasive assessment of coronary flow velocity reserve in the right coronary artery—A comparison of transthoracic echocardiographic results with intracoronary doppler flow wire measurements”, *European Heart Journal*, vol. 24:1567-1575 (2003). cited by applicant

Li et al, “Minimization of region-scalable fitting energy for image segmentation”, in *IEEE Transactions on Image Processing*, vol. 17(10):1940-1949 (2008). cited by applicant

Meimoun et al., “Non-invasive assessment of coronary flow and coronary flow reserve by transthoracic doppler echocardiography: a magic tool for the real world”, *European Journal of Echocardiography*, vol. 9:449-457 (2008). cited by applicant

Mercer-Rosa et al., “Illustration of the additional value of real-time 3-dimensional echocardiography to conventional transthoracic and transesophageal 2-dimensional echocardiography in imaging muscular ventricular septal defects: does this have any impact on individual patient treatment”, *Journal of the American Society of Echocardiography*, vol. 19(12):1511-1519 (2006). cited by applicant

Molloi et al., “Quantification of fractional flow reserve using angiographic image data”, *World Congress on Medical Physics and Biomedical Engineering*, Munich, Germany, Sep. 7-12, 2009. cited by applicant

Molloi et al., “Estimation of coronary artery hyperemic blood flow based on arterial lumen volume using angiographic images”, *Int J Cardiovasc Imaging*, vol. 28:1-11 (2012). cited by applicant

Ng et al., “Novel QCA methodologies and angiographic scores”, *Int J Cardiovasc Imaging* vol. 27:157-165 (2011). cited by applicant

Pellot et al, “A 3D reconstruction of vascular structures from two X-Ray angiograms using an adapted simulated annealing algorithm”, *IEEE Transactions of Medical Imaging*, vol. 13(1):48-60 (1994). cited by applicant

Pinho et al., “Assessment and stenting of tracheal stenosis using deformable shape models”, *Medical Image Analysis*, vol. 15(2):250-266 (2010). cited by applicant

Polytimi et al., “Close to transplant renal artery stenosis and percutaneous transluminal treatment”, *Journal of Transplantation*, vol. 2011, 7 pages (2011). cited by applicant

Sarwal et al., “3-D reconstruction of coronary arteries”, *Proceedings of the 16th Annual Intl. Conference of the IEEE Engineering in Medicine and Biology Society, Engineering Advances: New Opportunities for Biomedical Engineers*, Nov. 3, 1994, pp. 504-505. cited by applicant

Sato et al., “A viewpoint determination system for stenosis diagnosis and quantification in coronary angiographic image acquisition”, *IEEE Transactions on Medical Imaging*, vol. 17(1):121-137 (1998). cited by applicant

Seifalian et al., “A new algorithm for deriving pulsatile blood flow waveforms tested using simulated dynamic angiographic data”, *Neuroradiology*, vol. 31:263-269 (1989). cited by applicant

Seifalian et al., “Blood flow measurements using 3D distance-concentration functions derived from digital x-ray angiograms”, *Cardiovascular Imaging*, Chap. 33:425-442 (1996). cited by applicant

Seifalian et al., “Validation of a quantitative radiographic technique to estimate pulsatile blood flow waveforms using digital subtraction angiographic data”, *Journal of Biomedical Engineering*, vol. 13(3):225-233 (1991). cited by applicant

Shang et al., “Vascular active contour for vessel tree segmentation”, in *IEEE Transactions on*

Biomedical Engineering, vol. 58(4):1023-1032 (2011). cited by applicant

Shpilfoygel et al., "Comparison of methods for instantaneous angiographic blood flow measurement", Medical Physics, vol. 26(6):862-871 (1999). cited by applicant

Sianos et al., "The SYNTAX score: an angiographic tool grading the complexity of coronary artery disease", Euro Intervention, vol. 1(2):219-227 (2005). cited by applicant

Siogkas et al., "Quantification of the effect of percutaneous coronary angioplasty on a stenosed right coronary artery", 2010 10th IEEE Intl. Conference on Information Technology and Applications in Biomedicine, Nov. 3-5, 210, pp. 1-4 (2010). cited by applicant

Slomka et al., "Fully automated wall motion and thickening scoring system for myocardial perfusion SPECT: Method development and validation in large population", Journal of Nuclear Cardiology, vol. 19(2):291-302 (2012). cited by applicant

Sprague et al., "Coronary x-ray angiographic reconstruction and image orientation", Medical Physics, vol. 33(3):707-718 (2006). cited by applicant

Sun et al., "Coronary CT angiography: current status and continuing challenges", The British Journal of Radiology, vol. 85:495-510 (2012). cited by applicant

Takarada et al., "An angiographic technique for coronary fractional flow reserve measurement: in vivo validation", International Journal of Cardiovascular Imaging, published online pp. 1-10, Aug. 31, 2012. cited by applicant

Termeer et al., "Visualization of myocardial perfusion derived from coronary anatomy", IEEE Transactions on Visualization and Computer Graphics, vol. 14(6):1595-1602 (2008). cited by applicant

Tomasello et al., "Quantitative coronary angiography in the interventional cardiology", Advances in the Diagnosis of Coronary Atherosclerosis, Chap. 14:255-272 (2011). cited by applicant

Tu et al., Assessment of obstruction length and optimal viewing angle from biplane X-ray angiograms, Int J Cardiovasc Imaging, vol. 26:5-17 (2010). cited by applicant

Tu et al., "In vivo assessment of optimal viewing angles from X-ray coronary angiography", EuroIntervention, vol. 7:112-120 (2011). cited by applicant

Tu et al., "In vivo assessment of bifurcation optimal viewing angles and bifurcation angles by three-dimensional (3D) quantitative coronary angiography", Int J Cardiovasc Imaging, published online Dec. 15, 2011, in 9 pages. cited by applicant

Tu et al., "The impact of acquisition angle differences on three-dimensional quantitative coronary angiography", Catheterization and Cardiovascular Interventions, vol. 78:214-222 (2011). cited by applicant

Tuinenburg et al., "Dedicated bifurcation analysis: basic principles", Int J Cardiovasc Imaging, vol. 27:167-174 (2001). cited by applicant

Voci et al., "Coronary flow: a new asset for the echo lab?", European Heart Journal, vol. 25:1867-1879 (2004). cited by applicant

Weickert et al., "A scheme for coherence-enhancing diffusion filtering with optimized rotation invariance", Computer Vision, Graphics, and Pattern Recognition Group, Technical Report, Computer Science Series, pp. 1-20 (2000). cited by applicant

Weickert, "Anisotropic diffusion in image processing", ECMI, published by Teubner Stuttgart, Germany, 181 pages (2008). cited by applicant

Weickert et al., "A scheme for coherence-enhancing diffusion filtering with optimized rotation invariance", Journal of Visual Communication and Image Representation, vol. 13(1-2):103-118 (2002). cited by applicant

Wong et al., "Quantification of fractional flow reserve based on angiographic image data", The International Journal of Cardiac Imaging, vol. 28(1):13-22 (2012). cited by applicant

Wong et al., "Determination of fractional flow reserve (FFR) based on scaling laws: a simulation study", Physics in Medicine and Biology, vol. 53:3995-4011 (2008). cited by applicant

Wong et al., "Automated technique for angiographic determination of coronary blood flow and

lumen volume”, *Acad. Radiol.* vol. 13:186-194 (2006). cited by applicant

Xu et al., “Snakes, shapes, and gradient vector flow”, *IEEE Transactions on Image Processing*, vol. 7:359-369 (1998). cited by applicant

Yang et al., “Novel approach for 3-D reconstruction of coronary arteries from two uncalibrated angiographic images”, *IEEE Transactions on Image Processing*, vol. 18(7):1563-1572 (2009). cited by applicant

Rabbat et al., “Interpreting results of coronary computed tomography angiography-derived fractional flow reserve in clinical practice”, *Journal of Cardiovascular Computed Tomography*, vol. 11(5):1-6 (2017). cited by applicant

Extended European Search Report in European Application No. EP 20843503, dated Jul. 7, 2023, in 10 pages. cited by applicant

International Search Report and Written Opinion in application No. PCT/IB2023/051186, mailed on Jul. 17, 2023, in 15 pages. cited by applicant

Jiang et al., “Vascular tree reconstruction by minimizing a physiological functional cost”, 2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition—workshops, San Francisco, CA, pp. 178-185, doi: 10.1109/CVPRW.2010.5543593. cited by applicant

Invitation to Pay Additional Fees in Application No. PCT/IB2023/051186, mailed on May 25, 2023, in 33 pages. cited by applicant

Hwang et al., “Diagnostic performance of resting and hyperemic invasive physiological indices to define myocardial ischemia”, *JACC: Cardiovascular Interventions*, vol. 10(8):751-760 (2017). cited by applicant

Kern, “Serial lesion FFR made simple”, *Cath Lab Digest*, vol. 20(9)(2012), in 2 pages, [retrieved on Sep. 25, 2024], retrieved from the internet: <https://www.hmpgloballearningnetwork.com/site/cathlab/articles/serial-lesion-ffr-made-simple>. cited by applicant

Neng et al., “Pre-stenting angiography-FFR based physiological map provides virtual intervention and predicts physiological and clinical outcomes”, *Catheterization and Cardiovascular Interventions*, Wiley-Liss, New York, NY, vol. 101(6):1053-1061 (2023). cited by applicant

Nijjer et al., “Pre-angioplasty instantaneous wave-free ratio pullback provides virtual intervention and predicts hemodynamic outcome for serial lesions and diffuse coronary artery disease”, *JACC: Cardiovascular Interventions*, vol. 7(12):1386-1396 (2014). cited by applicant

Pijls et al., “Experimental basis of determining maximum coronary, myocardial, and collateral blood flow by pressure measurements for assessing functional stenosis severity before and after percutaneous transluminal coronary angioplasty”, *Circulation*, vol. 87:1354-1367 (1993). cited by applicant

Rimac et al., “Clinical value of post-percutaneous coronary intervention fractional flow reserve value: A systematic review and meta-analysis”, *Am Heart J.* vol. 183:1-9 (2017). cited by applicant

Volcano Corporation, iFR instant wave-free Ratio™, “An introduction to iFR Scout™ Pullback Measurements, Moving from Justified PCI to Guided PCI”, 2015, in 11 pages, [retrieved on Aug. 29, 2024]. Retrieved from the Internet <URL: <https://www.usa.philips.com/c-dam/b2bhc/master/education-resources/technologies/igt/iFR-Scout-In-Service.pdf>>. cited by applicant

International Preliminary Report on Patentability and Written Opinion in application No. PCT/IB2023/051186, dated Aug. 6, 2024, in 8 pages. cited by applicant

Barrett et al., “Interactive live-wire 1-3 boundary extraction”, *Medical Image Analysis*, Oxford University Press, vol. 1(4):331-341 (1997). cited by applicant

Chen et al., “3-D reconstruction of coronary arterial tree to optimize angiographic visualization”, *IEEE Transactions on Medical Imaging*, vol. 19(4):318-336 (2000). cited by applicant

Marchenko, et al., “Vascular editor: from angiographic images to 3D vascular models”, *Journal of Digital Imaging*, vol. 23:386-398 (2010). cited by applicant

Wang et al., “Optimal viewing angle determination for multiple vessel segments in coronary angiographic image”, IEEE Transactions on Nuclear Science, vol. 61(3):1290-1303 (2014). cited by applicant
Wang et al., “Global optimization angiographic viewing angles for coronary arteries with multiple segments”, 35th Annual International Conference of the IEEE EMBS, pp. 2640-2643, Osaka, Japan, Jul. 3-7, 2013. cited by applicant

Primary Examiner: Tsai; Tsung Yin

Attorney, Agent or Firm: Knobbe, Martens, Olson & Bear, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57. (2) This application claims priority to U.S. Prov. Patent App. No. 63/308,550 titled “VASCULAR TREE SEGMENTATION” and filed on Feb. 10, 2022, the disclosure of which is hereby incorporated herein by reference in its entirety.

BACKGROUND

Technical Field

(1) The present invention, in some embodiments thereof, relates to the field of vascular imaging and more particularly, but not exclusively, to vascular computer modelling and segmentation.

Description of Related Art

(2) Arterial stenosis is one of the most serious forms of arterial disease. Its severity can be determined by estimations of geometric measurements or flow rate of the vessels, typically through invasive procedures. However, by creating a vascular computer model using images of the vessel, it is possible to determine the severity of an arterial stenosis without the need for invasive procedures. Vascular imaging provides characterizations of blood vessel locations needed to generate a vascular computer model. However, vascular imaging requires vascular segmentation and feature identification as a preliminary stage of image-based measurement of the vascular state.

(3) Currently, many stages of vascular segmentation and feature identification can be performed using an automated analysis. Automatic identification of vascular positions is a potential advantage, since it can reduce the time, effort, skill, and/or attention required of a human operator to identify these positions entirely manually, even if the user must manually confirm or correct a vascular tree afterwards.

(4) Despite the ability to perform automated analysis, relevant image features produced from vascular segmentation and feature identification are often of low contrast. The image features may also be embedded in a complex environment including elements of ambiguous geometry and extraneous features that causes the output to be error prone.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Throughout the drawings, reference numbers are re-used to indicate correspondence between referenced elements. The drawings are provided to illustrate embodiments of the subject matter described herein and not to limit the scope thereof.

- (2) FIG. 1 is a block diagram of an optimal image determination system outputting an optimal angiographic image based on an input image sequence.
- (3) FIG. 2 is a schematic diagram of different algorithmic components from among which vascular identifiers may be selected, according to some embodiments of the present disclosure.
- (4) FIGS. 3A, 3B, 3C, 3D, 3E, 3F, 3G and 3H depict an X-ray angiogram image (depicted in each of FIGS. 3A, 3C, 3E, and 3G) together with different mask-type ML-based vascular identifier outputs (FIGS. 3B, 3D, 3F, 3H) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure.
- (5) FIG. 4 shows two superimposed path-type ML-based vascular identifier outputs, according to some embodiments of the present disclosure.
- (6) FIGS. 5A-5B schematically represent a method of vascular identification repair using mixed path-type and mask-type ML-based vascular identifiers, according to some embodiments of the present disclosure.
- (7) FIGS. 6A, 6B, 6C, 6D, 6E, 6F, 6G and 6H depict an X-ray angiogram image (depicted in each of FIGS. 6A, 6C, 6E, and 6G) together with different mask-type ML-based vascular identifier outputs (FIGS. 6B, 6D, 6F, 6H) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure.
- (8) FIG. 6J shows two superimposed path-type ML-based vascular identifier outputs, according to some embodiments of the present disclosure.
- (9) FIG. 6K shows a segmented result, produced based on the use of the various correct and partially incorrect information available from the ML-based vascular identifier outputs shown in FIGS. 6B, 6D, 6F, 6H, and 6J, according to some embodiments of the present disclosure.
- (10) FIGS. 7A, 7B, 7C and 7D depict an X-ray angiogram image (depicted in each of FIGS. 7A and 7C) together with different mask-type ML-based vascular identifier outputs (FIGS. 7B, 7D) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure.
- (11) FIG. 7E shows a path-type ML-based vascular identifier output superimposed on the image of FIGS. 7A-7C, according to some embodiments of the present disclosure.
- (12) FIG. 7F shows a segmented result, produced based on the use of the various correct and partially incorrect information available from the ML-based vascular identifier outputs shown in FIGS. 7B, 7D, and 7E, modified by further constraints, according to some embodiments of the present disclosure.
- (13) FIGS. 8A, 8B, 8C, 8D and 8E schematically illustrate exchange of vascular orientation information from a path-type ML output to a mask-type ML-based vascular identifier output, according to some embodiments of the present disclosure.
- (14) FIGS. 9A, 9B, 9C, 9D, 9E, 9F and 9G schematically illustrate a method of performing vascular subtraction between mask-type vascular identifier outputs, according to some embodiments of the present disclosure.
- (15) FIG. 10A illustrates a block diagram of the example optimal image determination system filtering angiographic images according to cardiac phase.
- (16) FIG. 10B illustrates a block diagram of the example optimal image determination system performing additional filtering based on mask scores associated with segmentation masks.
- (17) FIG. 10C illustrates a block diagram of the example optimal image determination system generating an optimal angiographic image.
- (18) FIG. 11 is a flowchart of an example process for determining an optimal angiographic image.
- (19) FIG. 12 is a flowchart of an example process for selecting an optimal angiographic image from an image sequence based on contrast scores.
- (20) FIG. 13 is an example system which may be used to implement the techniques described herein.

DETAILED DESCRIPTION

Introduction

(21) This application describes, among other things, techniques to select a vascular image, from a sequence of vascular images, which provides enhanced contrast, enhanced visibility of vessels, enhanced image quality, and so on. As will be described, the selected vascular image may be used for further analyses, such as forming a three-dimensional model of at least a portion of a patient's heart. The selected vascular image may also be used as part of an automated process or workflow in which a user can identify vessels in the vascular image, adjust an automated determination of vessels in the vascular image, and so on. The vascular images described herein may represent angiographic images in some embodiments, with each sequence of vascular images depicting the portion of the patient's heart from a particular viewpoint. As may be appreciated, combining vascular images from different viewpoints may allow for a three-dimensional view of the portion to be generated. At present such three-dimensional views are prone to inaccuracies due to the vascular images suffering from movement errors, differences in cardiac phases when the images were obtained, and so on. This disclosure describes techniques to optimize, or otherwise enhance, the selection of a subset of these vascular images to reduce such inaccuracies.

(22) As will be described, a system described herein may implement one or more machine learning models, optionally in conjunction with classical computer vision techniques, to determine an optimal image from among a multitude of inputted vascular images. The system may be, for example, the optimal image determination system **100** described below. For example, a machine learning model may include a neural network (e.g., a deep learning model, a convolutional neural network). In this example, the system may compute a forward pass through the machine learning model to generate output utilized in the determination. In some embodiments, the neural network may output segmentation masks for at least some of the received vascular images. These segmentation masks may segment vessels depicted in the vascular images.

(23) The system may analyze the above-described segmentation masks, for example determining size or length scores associated with depicted vessels. Using these scores, the system may select a top threshold number of images. The system may analyze the threshold number of images to identify an optimal image. For example, the system may compute contrast scores indicating measures of contrast or other image quality for the vessels depicted in the images. The optimal image may represent, in some embodiments, an image with the highest scores or combination of scores. Through this automated selection of an optimal image, resulting downstream workflows such as three-dimensional model generation may allow for enhanced accuracy while lessening the need and time spent for manual adjustments by a human operator post-analysis.

(24) Introduction—Background

(25) Angiographic images are commonly used to provide detailed views of a patient's heart. These images may be obtained, for example, by injecting a radio-opaque contrast agent into the patient's blood vessels and obtaining X-ray images (e.g., via fluoroscopy). While these images provide detailed views, due to the use of X-rays medical professionals may prefer to limit an extent to which angiographic images are obtained. Thus, it is paramount that techniques are employed for downstream processes which accurately leverage existing angiographic images.

(26) One example downstream process includes generating a three-dimensional model, or vascular tree, of a portion of patient's heart. For example, angiographic images of different views of the portion may be obtained. In this example, the different views may depict different views of vessels. As known by those skilled in the art, these vessels may be correlated to identify unique vessels depicted in the views. For example, automated or semi-automated techniques may be leveraged to allow for such correlation. The views may be combined to generate a three-dimensional view of these vessels. The views may also be combined to allow for an easy-to-understand graphical representation of a vessel tree which indicates vessels which are upstream and/or downstream from each other.

(27) Typically, an image sequence of angiographic images will be obtained while an imaging

system (e.g., a c-arm) is pointing at the portion of the patient's heart. For example, 5, 10, 20, and so on, angiographic images may be obtained. As may be appreciated, these angiographic images may vary in their usefulness with respect to the above-described downstream processes. For example, a subset of the angiographic images may have errors due to movement or shaking of the imaging system. As another example, a subset may have errors associated with contrast. As another example, the angiographic images may depict the portion of the heart as the heart is in different cardiac phases. For this example, certain cardiac phases may be associated with less detail, size, and so on, of vessels in the resulting angiographic images.

(28) Additionally, errors or ambiguities may relate to: Use of angiographic images which are two-dimensional projections of complex three-dimensional vasculature, creating the spurious appearance in single images of vascular connections which don't actually exist. Potentially, blood vessels hide one another due to overlap. Contrast agent used to reveal the vasculature may fill blood vessels of interest incompletely, unevenly, weakly and/or sporadically. Indications of other body structures, and sometimes outright artifacts may appear in the image, creating image “noise” which interferes with identification of targets of interest. There are technological and/or safety limitations on image resolution and radiant energy exposure, which can limit, for example, image detail and/or contrast. Cardiac vasculature moves with the beating of the heart and/or respiration, and the patient may themselves move; so that there is even a problem of selecting which 3-D shape of the vasculature is to be reconstructed. Typically, a user of a software tool may view images in an image sequence and select one which appears to depict the vessels most clearly. For example, the user may zoom into the images and identify potential errors which are evident in these images. Certain software tools may allow for limited automated techniques to surface potential errors. For example, classical computer vision techniques may be used to detect motion artifacts.

(29) In contrast, the disclosed technology leverages machine learning models specifically trained to address such errors and ambiguities.

(30) Introduction—Optimal Image Selection

(31) The system includes one or more machine learning models, such as convolutional neural networks, which are used by the system to output a particular angiographic image from an image sequence which will be used in downstream processes. The particular angiographic image is referred to as an optimal angiographic image or image frame herein.

(32) For example, the system receives an image sequence from an angiographic imaging tool or system (e.g., a c-arm). In this example, the imaging tool or system may be rotated such that angiographic images depict, or otherwise include, a portion of a patient's heart from a particular viewpoint. The image sequence may thus include angiographic images taken at different points in time from the particular viewpoint.

(33) The patient's heart will beat and therefore transition between cardiac phases. The angiographic images in the image sequence may therefore depict the portion of the patient's heart in different cardiac phases. For example, a first image may depict the heart while it is in a systole phase. As another example, a second image may depict the heart while it is in a diastolic phase. As known by those skilled in the art, the second image may provide a clearer, more advantageous, view of vessels in the portion of the heart. For example, the second image may depict the portion as being lengthened and in more of a relaxed state as compared to the first image.

(34) As will be described, the system may leverage machine learning techniques to identify images in the image sequence which depict the heart in a particular cardiac phase. In some embodiments, the particular cardiac phase may be an end-diastolic phase. The machine learning techniques may include a convolutional neural network which is trained to label, or otherwise indicate a value indicative of, an image depicting the heart in the particular cardiac phase. While a convolutional neural network is described, as may be appreciated other machine learning models may be used. For example, fully-connected networks, recurrent neural networks, attention-based networks, and so on may be used.

(35) The system may then use machine learning techniques, or optionally classical computer vision techniques (e.g., application of a Frangi filter, and so on), to output segmentation masks for these identified images. For example, the segmentation masks may have pixel values assigned based on whether the pixel forms part of a vessel. In this example, a segmentation mask may include binary color (e.g., black, and white) with a first color indicating a pixel which does not form part of a vessel and a second color indicating a pixel which does form part of a vessel. While binary colors are described, as may be appreciated each pixel may be assigned a value or likelihood indicative of the pixel forming part of a vessel.

(36) The segmentation masks may then be analyzed to identify size or length metrics associated with vessels (herein referred to as 'mask scores'). For example, a mask score may indicate a length associated with a vessel. In this example, the length may indicate a length associated with a centerline from a first end of a vessel to a second end of the vessel. As another example, a mask score may indicate a fill score (e.g., an area) associated with a vessel. In this example, the fill score may indicate a number of pixels which form the vessel, or an estimated area encompassed by the vessel. Use of the mask scores allows for removal of images where a contrast agent fills the patient's vessels incompletely, unevenly, weakly, and/or sporadically. For example, these images may have segmentation masks which include vessels appearing in disconnected segments or with reduced length or size. A threshold number of the segmentation masks may be maintained, for example 3, 5, 7, 9, 10, 12, and so on may be maintained as having the greatest mask scores.

(37) The system may then analyze angiographic images which were used to generate the threshold number of segmentation mask. For example, the system may determine quality or clarity scores for the angiographic images. Quality or clarity scores are described herein as contrast scores and are used to indicate images with the best contrast. While contrast scores are described herein, additional quality or clarity scores may be used and fall within the scope of the disclosed technology. For example, scores associated with one or more of sharpness, focus, motion artifacts, image artifacts, and so on, may be used. An optimal image may then be selected from the analyzed angiographic images based on the quality or clarity scores.

(38) As described in FIG. 1, the optimal image may be presented to an end-user in a user interface. In some embodiments, the end-user may view the optimal image and use it for down-stream processes. For example, the end-user may mark, or otherwise identify, vessels in the optimal image. The end-user may also select a different image from the above-described image sequence.

(39) In some embodiments, and as will be described, different machine learning models may be used based on whether the image sequence depicts a left side or right side of the patient's heart. For example, the left-side images may depict the left anterior descending artery (LAD) and the circumflex artery (LCX) while the right-side images may depict the right coronary artery (RCA). In some embodiments, a machine learning model (e.g., a convolutional neural network) may be used to indicate whether the image sequence depicts the left-side or right-side. For example, the machine learning model may output a classification.

(40) The disclosed technology therefore addresses technical problems and provides technical solutions to these problems. For example, there may be no need to unnecessarily increase image resolution or radiant energy exposure during X-rays due to the intelligent selection of angiographic images. As another example, use of machine learning models allows for accurate classification and determination of information to reliably select an optimal image from an image sequence. Without such techniques, resulting three-dimensional models of a heart, or information derived from angiographic images, may include errors and inaccuracies which negatively affect patient outcome.

(41) In this disclosure, the term "ML-based vascular identifier" refers to machine learning outputs. The term "vascular identifier" more generally encompasses both ML-based vascular identifiers and computer processing-based methods of identifying vascular regions in images (e.g., formula-based methods, such as classical computer vision techniques). Example classical computer vision techniques may include a kernel filter (e.g., a skeletonization filter or Gaussian filter), an affine

transform (e.g., a combination of translation, scaling, rotation, flipping and/or shear), a bit mask, a component analysis technique (e.g., principle component analysis), and a domain transform (e.g., a Fourier transform between frequency and spatial domains). In particular, in some embodiments of the present disclosure, a version of a filter type known in the art as a Frangi filter is used to assist in detecting the generally tubular structures of which vasculature is composed.

(42) In this application, and as an example, FIGS. **1** and **10A-12** may be relevant to techniques for determining an optimal image frame from an image sequence. FIGS. **2-9G** may be relevant to techniques for determining vessels in vascular images based on segmentation masks, addressing errors in determining vessels and/or segmentation masks, and so on. In some embodiments, the optimal image may be analyzed via the techniques described in FIGS. **2-9G** to accurately identify vessels associated with vessel trees or arteries (e.g., left or right arteries), address errors, and so on. Thus, the system described herein may determine an optimal image and then analyze the image, for example via segmentation masks or other ML-based vascular identifier outputs, as described in FIGS. **2-9G**.

(43) These and other features will now be described in detail.

(44) Block Diagram

(45) FIG. **1** illustrates a block diagram of an optimal image determination system **100**. The system **102** may represent, for example, a system of one or more computers or processors which implements the techniques described herein. In some embodiments, the system may be in communication with an imaging system or tool which obtains vascular images of a patient. As described herein, the vascular images may be angiographic images. In some embodiments, the vascular images may be computed tomography images or scans.

(46) In the illustrated embodiment, the optimal image determination system **100** is receiving an image sequence **102** which includes angiographic images **104A-104N**. The image sequence **102** may depict a portion of a patient's heart from a certain angle or viewpoint. The angiographic images **104A-104N** can be obtained, in some embodiments, by user input. For example, the user may input a DICOM file which includes a series of angiographic images or a video from which the angiographic images can be extracted. The images **104A-104N** may be captured at a particular frequency (e.g., 5 Hz, 7 Hz, 10 Hz, 30 Hz. and so on) over an amount of time, resulting in potentially large numbers of images.

(47) The images **104A-104N** may be taken during a period of vascular contrast agent injection and washout. As already described, within a single image, there may arise ambiguities in vascular structure due to vascular portions which cross and/or approach each other. Since the heart is hollow, and since X-ray images image all through the heart, some of these ambiguities arise from blood vessels which are actually in completely different 3-D planes (e.g., on opposite sides of the heart). As a result, blood vessels which appear to be near each other in a static 2-D plane may nonetheless have different patterns of motion, inconsistent with them actually lying within the same tissue bed. This inconsistency may be viewed as latent information about vascular connectivity. Another form of temporal information arises from the dynamics of vascular filling. Blood vessels which connect to one another should be highly correlated in the dynamics of their filling (darkening) and emptying (lightening) upon injection of vascular contrast agent, and then again as the contrast agent washes out. Unconnected blood vessels, even if they appear to intersect in an image, may be less correlated in their filling dynamics.

(48) In view of these ambiguities, certain angiographic images in the sequence **102** may provide a clearer, and more accurate, depiction of vessels in the patient's heart. Thus, the optimal image determination system **100** may determine an optimal image **110** from the image sequence **102** which represents the best image from a particular angle or viewpoint. As will be described, for example with respect to at least FIGS. **10A-12**, the optimal image may be identified using machine learning techniques optionally in combination with classical computer vision techniques. For example, the optimal image may have an optimal, or otherwise aggregate best, combination of

features including, for example, size of depicted vessels, clarity of the image, connectedness of vessels, and so on. With respect to connectedness, the optimal image may depict a vessel as being substantially continuous without separations.

(49) The optimal image **110** may be used by an end-user as medical data for example downstream processes. For example, the system **100** may identify locations, or boundaries, of vessels in the optimal image **110**. In this example, the end-user may adjust these locations or boundaries and optionally identify locations or boundaries of other vessels in the image **110**. As another example, the end-user may obtain multiple (e.g., 2, 3, 5, and so on) optimal images from different image sequences. For this example, the end-user may cause a three-dimensional model or vascular tree to be generated. Thus, the optimal images may represent images determined to be the most advantageous for use in these down-stream processes from their respective image sequences.

(50) In FIG. **1**, a user interface **120** is illustrated as including optimal image **110**. The user interface **120** may be generated, in some embodiments, by the system **100**. For example, the system **100** may execute software which causes presentation of the user interface **120**. The user interface **120** may also be presented by a user device of the end-user. For example, the system **100** may provide information for inclusion in the user interface **120** as rendered by the user device. In this example, the system **100** may be in wired or wireless communication with the user device. As an example, the system **100** may be associated with a web application.

(51) In some embodiments, the user interface **120** may include a button or other selectable object **122** to cause selection of a different optimal image. For example, the end-user may select button **122** to view other angiographic images in the image sequence **102**. In this example, the user interface **120** may update to present at least some of these angiographic images. The end-user may thus override the optimal image **110** to select a different optimal image. In some embodiments, such an override may be used to update the machine learning models described herein.

(52) The user interface **120** may be used, for example, to identify an image sequence for analysis. For example, the end-user may provide user input which causes the user interface **120** to respond to selection of an image sequence. Once selected, the selection of the image sequence may trigger the system **100** to determine an optimal image as described herein. The optimal image may then be shown or otherwise included in the user interface **120** as illustrated in FIG. **1**. In some embodiments, an animation or movie may play in the user interface **120** with the animation or movie being formed based on the image sequence. The optimal image may be identified, for example highlighted, text presented proximate to it, or the animation or movie may pause on the optimal image for a threshold amount of time while playing. In this way, the end-user may view the optimal image in the context of the image sequence. As described above, the end-user can select a different optimal image. For example, the end-user may interact with button **122**. As another example, the end-user may select an image during the animation or movie of the image sequence.

(53) Another example downstream process may include, for example, a certain image location as being part of a blood vessel (a “vascular portion”), a certain image location as being part of a particular (anatomically identified) blood vessel, a certain image location as being more particularly part of a path definition extending along vascular portions (e.g., a general or anatomically identified vascular center line), a certain image location as being a “root” location of a vascular tree (e.g., an ostium of a coronary artery), and/or of a certain image or image portion as being a suitable target for another image processing method.

(54) From image inputs (e.g., image inputs showing discernible structural features of cardiac vasculature), a vascular identifier may produce a data structure in which there is some correspondence with positions in the image, e.g., a 1:1 correspondent between identifications and pixels (other types of scaled, binned, or otherwise transformed correspondences are not excluded). The data structure may be in any form of representation suitable to describe identification results; for example, scalar, array, matrix, linked list, or another form of representation. More particularly, the data structure may be a mask; for example, a binary image with a pixel per pixel of the input

image, values of mask pixels being set according to the identification result of corresponding input image pixels. In some embodiments, the data structure is a list of locations in the input image which have (or do not have) a certain identification (e.g., identified as representing a portion of a certain vascular centerline). Image locations may be expressed, for example, as absolute locations, or as locations relative to other locations. A path through an image, for example, may be expressed as either of a binary image mask or a list of image locations. A vascular identifier may optionally produce a data structure which performs classification of an image as a whole. For example, the data structure may classify the image according to its likelihood of being an image obtained near a certain phase of the heartbeat cycle.

(55) Types of Vascular Identifiers/Vascular Identifier Outputs

(56) FIGS. 2-9G describe example techniques which may be implemented using the optimal image determination system **100** described herein. As will be described, the system **100** may generate output (e.g., ML-based vascular identifiers, vascular identifiers) which may be included in a user interface (e.g., user interface **120**). In some embodiments, an ML-based vascular identifier may include a segmentation mask generated from an angiographic image. A ML-based vascular identifier may also represent, in some embodiments, output from a machine learning model such as score, value, likelihood, classification, and so on.

(57) Reference is now made to FIG. 2, which is a schematic diagram of different algorithmic components from among which vascular identifiers may be selected, according to some embodiments of the present disclosure. The diagram is form of Venn diagram, wherein regions of the diagram (“type-regions”) are characterized by which labeled closed-boundary regions they fall within. The type-regions represent groups of algorithmic components with properties indicated by the labels, and further described herein.

(58) Type-regions **201**, **202** represent, respectively, the generic types of ML-based vascular identifiers and formula-based vascular identifiers, respectively, which should be understood in either case as being vascular identifiers available for and suitable for use in the identification of vasculature from vascular image. More particularly, in some embodiments, the vascular identifier is suitable for use in the identification of contrast-agent filled cardiac blood vessels in X-ray angiogram images of a living heart.

(59) Within either of the type-regions **201**, **202** may be distinguished more particularly a type-region **203** of mask-type vascular identifiers and a type of region **204** path-type vascular identifiers (representations of type-regions **203**, **204** are split among type-regions **201**, **202** to reduce visual clutter). Mask-type vascular identifiers, herein, are understood to be vascular identifiers that provide output which expresses a likelihood (optionally a threshold likelihood) of a particular image pixel being in or not in a suitably defined vascular target. Characteristics of mask-like vascular identifier outputs include: Being non-directional, e.g., the vascular identifier output as such does not indicate vascular orientation. Being “blobby”—that is, having width of arbitrary size in any direction from any particular point within the mask.

(60) The output from a path-type vascular identifier in contrast, is directional; for example, locations identified are in an order which the vascular identifier output defines. The path, moreover, is skeletal (not blobby); e.g., having no representation of width as such.

(61) It should be noted that the outputs of mask-type and path-type vascular identifiers can be inter-converted by various processing methods to have the directionality/blockiness of the opposite type. For example, a blob can be skeletonized, and a path can have different widths assigned to locations along its longitudinal extent. What is counted herein for purposes of type-region assignment is the form of the initial classification. Parenthetically, it may be also noted that a vascular identifier could, in principle, combine even within its initial classification, both the directionality of a path-type output and the arbitrary width of a mask-type output (that is, these two properties are not logically incompatible). Nor is it excluded that there are vascular identifiers sharing none of the distinguishing properties of path-type and mask-type vascular identifiers. However, unless

otherwise noted, vascular identifiers used in the examples given can be reasonably understood as belonging to one of the two types just given.

(62) Corresponding to the initial classification type, there may be understood to be an underlying difference in how mask-type and path-type vascular identifiers use the information available to them which traces to differences in their underlying models. In particular, path-type vascular identifiers operate based on the model assumption that there is a path—an ordered set of locations which extend between a starting position and an ending position. From the further knowledge or assumption that two non-adjacent locations are on the path, a path-type vascular identifier relies on there being a third location between them. The model of a mask-type vascular identifier may work from model assumptions that assess pixel properties and patterns without reliance on such global properties.

(63) It is not forbidden for embodiments of the present disclosure that a vascular identifier may use (for example) both path-like information and pattern-like information to produce its output, and this may be true even if the output itself is strictly path-type or mask-type). Indeed, and particular in the case of for an ML-based vascular identifier, it may be difficult to restrict, and perhaps infeasible to determine what type of information is being used. However, even in that case, it may be understood that the use of path-type training data vs. mask-type training data will tend to influence the training process that produces the ML-based vascular identifier, so that path-like or pattern-like information is emphasized to a greater or lesser degree.

(64) Accordingly, in some embodiments of the present disclosure, there is provided for use a mask-type vascular identifier. The mask-type vascular identifier may be in turn an ML-based vascular identifier. In some embodiments, the vascular identifier is more particularly characterized by having a classification-type output layer (e.g., as a member of type-region **206**), as also described hereinabove. The mask-type ML-based vascular identifier may be one trained using mask data, with the mask data identifying which portions of a vascular image should be considered as vascular portions.

(65) In some embodiments, the mask-type vascular identifier is a formula-based vascular identifier, for example, a Frangi filter-based vascular identifier **207** (AF Frangi et al., “Multiscale Vessel Enhancement Filtering”, Medical Image Computing and Computer-Assisted Intervention—MICCAI'98 Lecture Notes in Computer Science 1496/1998: 130). Variations of this method have also been described in more recent literature. More general examples of formula-based mask-type vascular identifiers include edge detectors and threshold detectors. The Frangi filter-based vascular identifier (and its variations) may be characterized as “tube detectors”, insofar as they are designed to highlight image features which correspond to the image appearance of tubes (which are characteristic of vasculature), such as their possession of a direction of greater longitudinal extent, their possession of a more-or-less constant or slowly changing diameter, their cross-sectional brightness profile, and/or other properties.

(66) Additionally, or alternatively, in some embodiments of the present disclosure, there is provided for use a path-type vascular identifier. The path-type vascular identifier may in turn be an ML-based vascular identifier. In some embodiments, the vascular identifier is more particularly characterized by having a regression-type output layer (e.g., as a member of type-group **205**), as also described hereinabove. The path-type ML-based vascular identifier may be one trained using path data, with the path data identifying locations lying along vascular portions. In some embodiments, the locations identified are vascular centerlines. The centerlines are optionally and advantageously identified as representing the geometrical center of blood vessels; however, there is no general restriction requiring this. In some embodiments, additionally or alternatively, the path locations identified are vascular edges.

(67) In some embodiments, the path-type vascular identifier is a formula-based vascular identifier **208**. Such a path-type vascular identifier may, for example, proceed away from a seed location, travelling in one or two directions along the minimum gradient of the image's local brightness

values. When the seed location is within a blood vessel (e.g., a dark blood vessel against a brighter background), this may tend to constrain the direction of travel to be about parallel to the direction of the blood vessel itself, insofar as the vessel is relatively narrow (making a steep gradient) compared to its length (along which the gradient is shallower). The path may also trend toward the vascular center since lower overall intensity levels there may also lead to lower gradients. Refinements to this general idea may include different methods of selecting seed locations, resolving stopping conditions, and/or bridging vascular crossings and/or gaps in vascular brightness.

(68) Apart from its usefulness in description of some embodiments of the present disclosure, the distinction between path-type and mask-type vascular identifiers is of relevance to the problem of vascular identification because it allows pointing out—more generally—that even though two vascular identifiers may both be designed to solve the same problem of “identifying blood vessels” in an image, their underlying model differences drive them to somewhat different solutions.

(69) In the case of two ML-based vascular identifiers, this can be true even when the vascular identifiers were trained using the same basic underlying images. This is, in turn, practically important, because any given vascular identifier is likely to make a certain number of mistakes. It will identify a blood vessel where there is none or fail to do so when one should have been identified. Furthermore, the pairing of path-type and mask-type vascular identifiers provides an example of two different types of vascular identifier which tend to make different mistakes. An understanding of the differences there can be converted in turn to a solution which allows complementary use of a plurality of vascular identifiers to achieve results more accurate than any individual vascular identifier (or type of vascular identifier) alone.

(70) The principle of complementarity can be carried more generally to other type-distinctions, including some indicated in FIG. 2. For example, in some embodiments, one or more ML-based vascular identifiers are trained to identify a selective anatomical target, consisting, e.g., not of blood vessels generally (e.g., as may be true of generic/“branched-tube” selective ML-based vascular identifiers **210**), but more particularly of a particular, anatomically defined vascular target such as the LAD, LCX, RCA, and/or sub-tree vessels thereof (these are examples of targets which may be designated for anatomical target selective ML-based vascular identifiers **212**). It should be emphasized that there is no particular technological limitation which prevents training ML-based vascular identifiers of the generic type **210**, or on a somewhat more selective type such as cardiac vasculature generally. However, the inventors have found that training ML-based vascular identifiers on an anatomically restricted range of blood vessels has potential advantages for accuracy of identification and/or the amount of training data needed to reach an acceptable level of accuracy. There may be a further advantage when reconstructing 3-D positions of blood vessels using images taken from different angles. If it is clear which blood vessel is, e.g., the LAD or LCX in each image, then the problem of matching blood vessel coordinates is potentially simplified and/or made less error prone.

(71) Another potential advantage of such an approach is that whatever the vessel-type specialized ML-based vascular identifier identifies as vascular is by this fact also identified as belonging to a particular anatomically defined vascular type. Identification may be relevant, e.g., for analysis of vascular pathologies, wherein the severity of the pathology is judged in part based on which anatomically identified portion of the vasculature is pathological.

(72) The ability of machine learning techniques to create anatomically selective vascular identifiers by suitable selection of training data is, moreover, a potential advantage over the use of formula-based vascular identifiers. For formula-based vascular identifiers, the parameters available for adjustment are not necessarily suited to making anatomical selections of the type needed. For example, Frangi-based algorithms typically have a free parameter which can be adjusted to tune which vascular diameter(s) are detected. However, cardiac blood vessels of interest such as the LAD and LCX not only tend to share similar vascular widths, but also themselves vary in width

along their length—so a single width, or range of widths, is not particularly distinguishing. While it may be possible to develop a distinguishing vascular identifier, given sufficient investigation, formula-based vascular identifiers expose no pre-existing “knob” (parameter) which is equivalent in flexibility to the adjustment of training data which is available in the generation of ML-based vascular identifiers.

(73) Anatomically Selective ML-Based Vascular Identifiers

(74) Mask-Type ML-Based Vascular Identifiers

(75) Reference is now made to FIGS. 3A-3H, which depict an X-ray angiogram image (depicted in each of FIGS. 3A, 3C, 3E, and 3G) together with different mask-type ML-based vascular identifier outputs (FIGS. 3B, 3D, 3F, 3H) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure. FIG. 3B shows an LAD mask, FIG. 3D shows an LCX mask, FIG. 3F shows a mask comprising the LAD sub-tree (the LAD and its diagonals or branches), and FIG. 3H shows a mask comprising the LCX sub-tree (the LCX and its marginals or branches).

(76) Each of FIGS. 3B, 3D, 3F, 3H was generated from the same image input using a different respective ML-based vascular identifier trained using a training data set specific for the vascular type identified. In some embodiments, the training data set of a given ML-based vascular identifier comprises a large set of images (e.g., more than 1000 images, more than 10000 images, or another number of images), for each of which a mask is defined identifying the targeted, anatomically identified vascular type.

(77) It may be readily understood that from this set of images, each of the LCX and the LAD are distinguishable from the rest of their respective sub-tree vessels by observing which vascular regions in the whole sub-tree vascular identifier output only, and which are in the corresponding single-vessel ML-based vascular identifier's output as well. However, the images potentially require additional algorithmic processing to realize this distinction. Thus, four different vascular types may be identified in a single image, based on the application of four different ML-based vascular identifiers to the image.

(78) It should be noted that the identifications shown in this set of examples are relatively error-free, although it may be noted, e.g., that FIG. 3F shows a small number of disconnected blobs, at least some of which appear to be more appropriately identified as part of the LCX sub-tree. Following examples will describe various types of detection errors in the ML-based vascular identifier outputs, and how they may be addressed through combinations of vascular identifier outputs.

(79) Path-Type ML-Based Vascular Identifiers

(80) Reference is now made to FIG. 4, which shows two superimposed path-type ML-based vascular identifier outputs **401**, **402**, according to some embodiments of the present disclosure. Path **401** extends along the LCX, and path **402** extends along the LAD.

(81) In this case, the ML-based vascular identifiers used were of the regression type, and training data used were not blob-like masks, but rather paths. In part, regression type training proceeds by “teaching” the ML-based vascular identifier to adjust output path positions to reduce deviation in position from paths in the training set, which is a type of regression problem. The trained vascular identifiers are then expected to produce useful vascular identifications when provided with image data not used as part of their training data set. The path has an ordering of locations along the output path, including two path ends. The model may output the path as a sequence of X and Y coordinates.

(82) In some embodiments, more particularly, to apply the path-type ML-based vascular identifier, each of 50 coordinates along a seed starting path is converted to a profile image, and the profile images stacked so that a 2-D image is created. Each profile image comprises pixels perpendicular to the vessel direction and passing through the selected coordinate. In the profile image, the true vascular path extends generally along the seed starting path, but it “wiggles”. The ML-based

vascular identifier operates by moving seed path coordinates laterally to positions which are considered more likely to actually lie upon the vascular path (optionally also somewhat constrained by the lateral positioning of nearby points, to maintain at least some amount of contiguity). Optionally, this is performed on an interpolated image, e.g., so that 200 or more (for example, 210) interpolated points are generated. Since the positions of points along the lateral lines are known in the original 2-D image, the laterally moved positions can be mapped back into 2-D image coordinates to give the 2-D shape of the vascular path. Optionally, remapping uses fewer points than were available in the interpolated intermediate image; for example, remapping may return to 50 selected anchor points, and draw the vascular path between anchor points. Anchor points may be connected by straight lines, by spline fits, or by another method.

(83) It may be noted that identifications of paths **401**, **402** substantially overlap with the mask identifications made in FIGS. **3D**, **3B**, respectively. In some embodiments, pixels in the sub-tree masks of FIGS. **3H**, **3F** are divided into their main vessel vs. branch vessel types based on comparison with paths **401**, **402** additionally, or alternatively to, comparison with the mask-type outputs of FIGS. **3D**, **3B**. This is a form of cross-vascular identifier mixing of outputs which combines outputs of path-type ML-based vascular identifiers and of mask-type ML-based vascular identifiers.

(84) Cross-Type Repair Using ML-Based Vascular Identifiers

(85) Reference is now made to FIGS. **5A-5B**, which schematically represent a method of vascular identification repair using mixed path-type and mask-type ML-based vascular identifiers, according to some embodiments of the present disclosure.

(86) In FIG. **5A** are shown two overlying LCX identifications produced as outputs of ML-based vascular identifiers. Path **501** represents an output of a path-type ML-based vascular identifier, while mask **502** is the output of a mask-type vascular identifier. Each output includes at least one error. Gap **503** is an error in mask **502**, such as may be caused, for example, by a lesion which interferes with contrast agent intensity and/or vascular morphology (the gap has been artificially introduced for purposes of explanation).

(87) Path **501** crosses over gap **503**. Path-type ML-based vascular identifiers can be relatively resistant to local irregularities, since (for example) if there is “normal” vasculature on either side of the gap, the processes of regression will tend to match the path to those normal regions. The region in-between will be bridged as a matter of course, in order to maintain the overall integrity of the path.

(88) However, tail region **504** of path **501** diverges from mask **502**. In some embodiments, deviations of mask **502** and path **501** near the tail **504** are treated as more likely (and optionally necessarily) due to errors in the path **501**. The reason for this may be, for example: that path **501** may be constrained by an over-learned feature such as a limitation on how tortuous the path is allowed to be; a relatively increased sensitivity to small collateral branches; and/or in general a vulnerability to falling into local minima which tends to propagate along the path once an error occurs (previous path dependence).

(89) FIG. **5B** illustrates a corrected vascular identification combining mask **502** and path **501**. The tail region **504** can be deleted, for example, because in some portion (most distally) it leaves but never rejoins a portion of mask **502**, or because (slightly more proximally) it leaves and rejoins mask **502**, but it rejoins the same self-connected “blob”, and so is not bridging any gap.

(90) In contrast, bridge **505** is retained, for example based on the criterion that two different (not previously interconnected) blobs are bridged. Additionally, or alternatively, other criteria are applied, for example, a maximum bridging distance and/or similarity of directionality between a skeletonized version of mask **502** and regions of path **501** extending alongside.

ML-Based Vascular Identifier Repair by Combination Example

(91) Reference is now made to FIGS. **6A-6H**, which depict an X-ray angiogram image (depicted in each of FIGS. **6A**, **6C**, **6E**, and **6G**) together with different mask-type ML-based vascular identifier

outputs (FIGS. 6B, 6D, 6F, 6H) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure. FIG. 6B shows an LAD mask, FIG. 6F shows an LCX mask, FIG. 6D shows a mask comprising the LAD sub-tree (the LAD and its diagonals or branches), and FIG. 6H shows a mask comprising the LCX sub-tree (the LCX and its marginals or branches). In this example, FIGS. 6D and 6F each show significant gaps in the detected mask, compared to what can be seen in the X-ray angiogram image.

(92) Further reference is made to FIG. 6J, which shows two superimposed path-type ML-based vascular identifier outputs **601**, **602**, according to some embodiments of the present disclosure. Path **601** extends along the LCX, and path **602** extends along the LAD. However, path **602** has mostly been misidentified; it has “jumped” to a wrong vessel.

(93) Additional reference is made to FIG. 6K, which shows a segmented result **603**, produced based on the use of the various correct and partially incorrect information available from the ML-based vascular identifier outputs shown in FIGS. 6B, 6D, 6F, 6H, and 6J, according to some embodiments of the present disclosure.

(94) In some embodiments, the rules of combination which result in the segmentation of FIG. 6K are as already described for the simpler cases before. Path-type segmentation portions which leave but never return to a corresponding mask-type segmentation of the image may be disregarded in the final result. However, where gaps have been spanned by a path-type output result to join two otherwise disconnected mask-type “blobs”, the result can be unified into a single segment. Although this is not illustrated, segments can also be distinguished from each other by knowing which anatomically defined vascular type(s) are being identified by each mask-type or path-type ML-based vascular identifier.

ML-Based Vascular Identifier Repair by Combination and Heuristics Example

(95) Reference is now made to FIGS. 7A-7D, which depict an X-ray angiogram image (depicted in each of FIGS. 7A and 7C) together with different mask-type ML-based vascular identifier outputs (FIGS. 7B, 7D) corresponding to different anatomically distinct vascular types, according to some embodiments of the present disclosure. FIG. 7B shows an RCA mask, and FIG. 7D shows a mask comprising the RCA sub-tree (the RCA and its diagonals or branches). Further reference is made to FIGS. 7E, which shows a path-type ML-based vascular identifier output **701** superimposed on the image of FIGS. 7A-7C, according to some embodiments of the present disclosure. Additional reference is made to FIG. 7F, which shows a segmented result **703**, produced based on the use of the various correct and partially incorrect information available from the ML-based vascular identifier outputs shown in FIGS. 7B, 7D, and 7E, modified by further constraints, according to some embodiments of the present disclosure.

(96) In FIG. 7B, the mask-type ML-based vascular identifier of the RCA yields an erroneous loop **702**, which is due to a branch of the RCA crossing back in front of or behind the RCA itself. The error also appears in the ML-based vascular identifiers which produced the outputs of FIGS. 7D and 7E, so that they do not have the information needed to correct each other. However, the basic information that there is an error can be derived from the pattern in FIG. 7B, since the ML-based vascular identifier there is supposed to identify just a single vessel, and a single vessel should not have any such loop **702**.

(97) Nonetheless, the error can be resolved, based on mask morphology. For example, the mask of FIG. 7B can be subjected to skeletonization, allowing the locations of bifurcation (top of loop **702**) and crossing (bottom of loop **702**) to be identified. Moving away from those intersection locations, the width of the mask can be identified perpendicular to directions along which the skeletonized mask extends. Of the two branch choices, the branch that better matches the pre-branch (or post-branch) width may be considered as the more likely extension of the RCA. Additionally, or alternatively, intensities in the original image may be used to help assess similarity of vascular morphology. Optionally, locations of bifurcation vs. crossing are distinguished by the extra darkening due to cross-over of vessels that generally is not present at a branch point.

(98) Additionally, or alternatively, the directionality of the two loop branches may be determined leading toward the locations so bifurcation/crossing. Again, this directionality may be determined from a skeletonized version of the mask. The loop branch for which directionality is most nearly parallel to the pre- and/or post-loop branch of the mask may be considered as the more likely extension of the RCA.

(99) In this example, an analysis such as just described allows assigning the short side of loop **702** as part of the RCA itself. This in turn allows assignment of remaining vascular portion identifications based on the ML-based vascular identifier output, for example, to yield the vascular segmentation **703** shown in FIG. 7F.

(100) It should be understood that the analysis just described is heuristic in character. Heuristics, while often valuable, tend toward a “brittleness”, in that they focus on a particular metric which is assumed to mean something (e.g., mean something about vascular geometry), even though in realistic circumstances, it might not always guarantee what is being assumed for it.

(101) Even with a plurality of heuristics, there can arise situations wherein the heuristics are contradictory, or even agree but yield an incorrect result. Accordingly, there is a potential advantage to reducing the number of ambiguities which need to be resolved heuristically by shifting as much of the vascular segmentation and identification burden as possible to a detector such as an ML-based vascular identifier which is relatively specialized, on one hand (e.g., specialized to detect a particular target type), but also relatively robust in its ability to weight different image features in order to reach a correct vascular identification. The robustness may arise, for example, from the having been generated from realistic examples far more numerous than an algorithm designer could take into individual consideration.

(102) For example, it is noted that the mask of FIG. 7D could also be used as a basis for rationalizing bifurcations/crossovers into a simply branched (loop-free) structure. However, the situation becomes more complex because there are additional logical possibilities that must be excluded. For example, in the example shown, a single RCA branch loops twice across the RCA itself. But near the second crossing **704**, the RCA somewhat constricts, so that from width alone, it may be ambiguous whether the RCA really continues straight across, or else begins a tortuous region by curving to the right. The directionality heuristic might yield a different result, but this results in a potential deadlock unless one of the two heuristics is given priority.

(103) In this case, the directionality heuristic would be correct, but it is not generally infallible. It may be noted, for example, that the bend which a bend to the right at crossing **704** would require is similar in angle to the angle of the next downstream tortuosity **705** in the branched vessel. Should both RCA branch and RCA begin a tortuous region near the region of their closest approach, the directionality heuristic could yield an incorrect result.

(104) Thus, an algorithm designer using a formula-based heuristic approach needs to decide how to prioritize or weight heuristics. Rigorous determination of the correct method of comparison may be impractical, for example due to uncertainty about how relatively important given heuristic weaknesses are. A machine-learned vascular identifier has the advantage of being produced by a process of automatic adaptation to actual results.

(105) In short, the more loops which must be resolved using heuristics, the greater is the opportunity for error. In the case of the example of FIGS. 7A-7F, the use of an ML-based vascular identifier specialized for single vessel detection has reduced the number of crossing points requiring heuristic resolution compared to the whole sub-tree ML-based vascular identifier's result.

(106) Transfer of Vascular Orientation from Path-Type to Mask-Type Vascular Identifier Outputs

(107) Reference is now made to FIGS. **8A-8E**, which schematically illustrate exchange of vascular orientation information from a path-type ML output to a mask-type ML-based vascular identifier output, according to some embodiments of the present disclosure.

(108) Mask-type output as such detects vascular regions in or out of a certain type of blood vessel (e.g., the LAD or the RCA), but is not inherently oriented to determine which end is the ostium

(upstream of proximal side of an artery), and which is the distal end of the artery.

(109) FIG. **8A** shows a mask-type ML-based vascular identifier output detecting the extent of an LAD. FIG. **8B** is a corresponding path-type ML-based vascular identifier. The path-type vascular identifier output is ended, since it is derived from a path model also having ends. The ends themselves may have been labeled as relatively upstream (ostial) or downstream (distal) based on information implicit in how the paths were learned, and/or based on comparison to the result of yet another vascular identifier, for example, a thresholded Frangi filter heat map, wherein the Frangi filter can be tuned to find larger (and therefore more ostial) blood vessels differentially (e.g., preferentially) compared to smaller blood vessels.

(110) In FIG. **8B**, the mask has been skeletonized to skeletonized mask **801**, which can be done by an erosion filter. In FIGS. **8C** and **8D**, a path-type ML-based vascular identifier result **802** is aligned to skeletonized mask **801**. FIG. **8C** shows a magnified portion from near the ostium end of path-type ML-based vascular identifier result **802**. The arrow **803** indicates the distance between the extreme ostial end of path-type ML-based vascular identifier result **802** (for which end information is available), and the closest end of skeletonized mask **801**. This end becomes the skeletonized mask's ostial end. The opposite end is the distal end.

(111) The path of skeletonized mask **801** is optionally used as a representation of the vascular centerline. Alternatively, the skeletonized mask is used to create a geodesic distance transform of the original mask-type output, and the centerline defined as the shortest path along the geodesic transform between the positions of the ostial and distal ends of the skeletonized mask **801**. The centerline is then transformed back into Cartesian coordinates, for example as shown in FIG. **8E**.

(112) Vascular “Subtraction” in Vascular Masks

(113) Reference is now made to FIGS. **9A-9G**, which schematically illustrate a method of performing vascular subtraction between mask-type vascular identifier outputs, according to some embodiments of the present disclosure. In the example shown, the vascular identifier outputs are outputs of two different ML-based vascular identifiers, which distinguish the LAD (FIG. **9A**) and the LAD and its diagonals (FIG. **9B**), respectively.

(114) FIG. **9C** shows the result of a simple mask subtraction, with bright pixels being those found in the mask of FIG. **9B** alone, dark pixels being those found in the mask of FIG. **9A** alone, and gray pixels being either found in both masks, or in neither. The subtraction result is unsatisfactory, since it leaves a fringe of mixed black and white pixels where the two ML-based vascular identifiers reached slightly different results as to where the edges of the LAD should be placed.

(115) FIG. **9D** shows the image from which the masks of FIGS. **9A-9B** were derived. As a stage of addressing the “fringe” problem, contrast enhancement has been applied to the region of the mask of FIG. **9B**. The contours of this enhanced region are shown in FIG. **9E**, the contours having been calculated only within the vicinity of pixels which are portions of the LAD (alone) mask. This may be accomplished, for example, by dilating the mask of FIG. **9A** until it slightly over-fills contours of the whole enhanced region, and then only retaining contours in contact with the dilated mask. FIG. **9F** shows the resulting LAD mask, and FIG. **9G** shows the difference mask retaining a branch of the LAD sub-tree.

(116) Example Machine Learning Techniques—Block Diagram/Flowcharts

(117) FIGS. **10A-13** describe examples of determining an optimal image from an image sequence of angiographic images. Similar to FIGS. **2-9G**, the description of which is relevant to these figures, the optimal image determination system **100** may perform the techniques described below.

(118) FIG. **10A** illustrates a block diagram of the example optimal image determination system **100** filtering angiographic images according to cardiac phase. The optimal image determination system **100** operates by filtering an image sequence **1000** to those which include angiographic images associated with a particular cardiac phase. In some embodiments, the system **100** filters the sequence **1000** to include images which are end diastolic.

(119) As illustrated, the optimal image determination system **100** includes a cardiac phase

determination engine **1002** which analyses the image sequence **1000**. In some embodiments, the cardiac phase determination engine **1002** may be a machine learning model **1008** which receives a subset **1004** of the image sequence **1000** as input. For example, the subset **1004** may include 1 image, 3 images, 5 images, and so on. With respect to 5 images, a center image **1006** may be combined (e.g., concatenated) with two subsequent, and two previous, images in the image sequence **1000**.

(120) The system **100** may compute a forward pass through the machine learning model **1008** and obtain a likelihood, or value, associated with the center image **1006** depicting the heart during a particular cardiac phase. In some embodiments, the machine learning model **1008** may represent a neural network which is trained to assign a value indicative of a likelihood (e.g., a final layer may use a sigmoid activation function). With respect to the example of 5 input images, as may be appreciated the neural network may effectively learn to distinguish movement indicia of the heart, such as expansion, which are associated with the particular cardiac phase. The neural network may also be trained to assign a classification associated with a cardiac phase. The neural network may include, for example, a convolutional neural network, a fully-connected neural network, an attention-based network, a recurrent neural network, and so on.

(121) With respect to a recurrent neural network, the model **1008** may be a long short-term memory (LSTM) network. Use of LSTM units may allow the model **1008** to exploit temporal information associated with the image sequence **1000**. Additionally, LSTM units may help distinguish vessels and their localization using information about how they change (e.g., move and/or move relative to one another) over time, or simply information about how well another ML-based vascular identifier identifies them in a sequence of images.

(122) As described above, end diastolic images may be preferable as they capture when the blood vessels are at their largest. For example, the cardiac phase corresponds to when the ventricles of the heart are most expanded. This image is relatively identifiable since it occurs during the moments of transition between expansion and contraction of the heart. Therefore, this can assist with matching to other images obtained during later or earlier heartbeat cycles, since there is less likely to be differences in heart shape due to heart contraction.

(123) In the illustrated example, the cardiac phase determination engine **1002** has output filtered images **1004** which are associated with the particular cardiac phase (e.g., end-diastolic images). For implementations which use a likelihood or probability of the particular cardiac phase, the engine **1002** may filter (e.g., remove or discard) images which received a likelihood or probability less than a threshold (e.g., 60%, 75%, 90%).

(124) FIG. **10B** illustrates a block diagram of the example optimal image determination system **100** performing additional filtering based on mask scores associated with segmentation masks. As described in FIG. **10A**, the system **100** may analyze angiographic images included in an image sequence and identify a subset **1004** which depict the heart during a particular cardiac phase (e.g., an end-diastolic phase). As will be described, the system **100** may further refine or filter the subset **1004** using segmentation masks which indicate image portions depicting vessels.

(125) The optimal image determination system **100** includes a segmentation engine **1020** which outputs a segmentation mask based on an input of an angiographic image. For example, in FIG. **10B** the segmentation engine **1020** has received an input angiographic image **1022**. As illustrated, the input angiographic image **1022** depicts one or more vessels (e.g., 'Vessel A'). The resulting segmentation mask **1024** depicts the one or more vessels, such as Vessel A, as being segmented from the remainder of the image **1022**. In some embodiments, the segmentation mask **1024** may include pixels assigned binary values by the segmentation engine **1020**. A first binary pixel value, such as white, may indicate that the pixel forms part of a vessel. A second binary pixel value, such as black, may indicate that the pixel does not form part of a vessel.

(126) While FIG. **10B** illustrates the segmentation mask **1024**, as may be appreciated in some embodiments the segmentation engine **1020** may output information identifying the vessel's

location or position in the input image **1022**. For example, the engine **1020** may output a data structure (e.g., a vector or other information) which identifies pixels forming a vessel. As another example, the engine **1020** may output information indicating a boundary or contour of a vessel. (127) The segmentation engine **1020** may represent a machine learning model which is trained to output segmentation masks. For example, a convolutional neural network may be trained to output segmentation **1024**. In this example, the convolutional neural network may be trained based on ground truth segmentation masks and associated angiographic images. In some embodiments, the segmentation engine **1020** may represent performance of classical computer vision techniques. As described herein, the neural network may be specific to a side or artery of the heart. For example, a first neural network may output segmentation masks for images associated with a right-side of the heart. As another example, one or more additional neural networks may output segmentation masks for images associated with a particular artery of a left-side of the heart (e.g., a left anterior descending, left marginal, left circumflex artery).

(128) These segmentation masks may be of the mask-type or path-type, as described in FIG. 2. In overview, mask-type outputs comprise “blobs” of connected pixels which are categorized as belonging to a certain vascular type, but not necessarily structured except insofar as their connectivity can be used for further analysis procedures such as skeletonization. Path-type outputs arrange regions along a path in a definite order, typically with the ends themselves also being identified, e.g., as closer to the ostium, or more distal from it (e.g., relatively upstream/downstream, respectively in the case of arteries). Additionally, and as described in FIGS. 2-9G, the segmentation masks may be analyzed to address errors or update information in the masks.

(129) In some embodiments, at least one formula-based method (e.g., classical computer vision technique) is combined with at least one machine-learning based method. For example, a Frangi filter can be utilized in conjunction with the segmentation network to identify smaller unidentified vessels missed by the segmentation network. More particularly, the edgeClearFrangi (ECF) Frangi filter variant may be used. A Frangi filter is a formula-based method used to generate a “heat map” giving a likelihood of given pixels being vascular, and optionally the heat map is converted, for example by application of a threshold, into mask of image pixels judged to be vascular regions. Frames where the Frangi filter is more responsive (e.g., in terms of overall response intensity and/or area of the mask meeting a certain threshold criterion), are correspondingly considered to have greater and/or denser vascular filling with contrast agent. Additionally, the Frangi filter can be used to connect gaps missed by the segmentation network to reduce connectivity problems. Therefore, in addition to reducing connectivity problems that may otherwise remove the image from optimal frame consideration, the Frangi filter will provide an indication to the user that a vessel exists and what its contours are so a user can draw those vessels in post.

(130) Further description related to segmentation masks, and example graphical representations of segmentation masks, are included herein with respect to FIGS. 2-9G. For example, the segmentation engine **1020** may output ML-based vascular identifiers such as different mask type outputs.

(131) Based on the segmentation mask **1024**, the segmentation engine **1020** generates a mask score **1026** associated with one or more vessels in the mask **1024**. For example, the mask score may indicate a measure or metric associated with a size of Vessel A. In this example, the segmentation engine **1020** may determine a number of pixels which form Vessel A (e.g., a number of the white pixels). The segmentation engine **1020** may also determine an area (e.g., an image area) associated with Vessel A. The segmentation engine **1020** may also determine a length of Vessel A. As an example, the length may indicate a length associated with a line which is positioned through the center of Vessel A (e.g., a centerline).

(132) A segmentation mask may incompletely depict a vessel, for example the segmentation mask may have discontinuities or white portions separated by black portions. In some embodiments, the segmentation engine **1020** may correct discontinuities. For example, the engine **1020** may assign a

black portion (e.g., a portion indicated as not forming a vessel) as being a white portion if the black portion is below a threshold size or length and adjacent to white portions on one, or both, sides. To correct discontinuities, as an example, the engine **1020** may apply a Frangi filter to the segmentation mask. Correcting discontinuities is additionally described elsewhere, with respect to FIGS. 3A-9G. In some embodiments, the segmentation engine **1020** may discard certain angiographic images in the subset **1004** from further analysis based on inclusion of such discontinuities. Thus, the engine **1020** may prefer angiographic images which result in segmentation masks with reduced errors.

(133) The segmentation engine **1020** may therefore determine masks **1030** scores for the subset **1004**. As described above, a mask score may indicate a size or length associated with a vessel. In some embodiments, an image may have a mask score for each vessel depicted in an associated segmentation mask. In some embodiments, an image may have a single mask score which is based on the vessels depicted in the associated segmentation mask.

(134) Using the mask scores **1030**, the segmentation engine **1020** may filter the subset **1004**. For example, the segmentation engine **1020** may discard angiographic images which are associated with mask scores less than a threshold percent of a maximum (e.g., higher) mask score. Thus, the segmentation engine **1020** may output filtered angiographic images **1028** along with the mask scores **1030**.

(135) FIG. **10C** illustrates a block diagram of the example optimal image determination system **100** generating an optimal angiographic image **1042**. As described in FIG. **10B**, the system **100** may determine images **1028** whose associated segmentation masks include lengthy, or larger, vessels. These images **1028** may thus more provide a clearer view of the vessels.

(136) The optimal image determination system **100** includes an optimal image selection engine **1040** which determines, or otherwise outputs, the optimal angiographic image **1042**. In some embodiments, the optimal angiographic image **1042** represents one of the images **1028** which has the best image quality. For example, the optimal angiographic image **1042** may have the best contrast.

(137) As illustrated, images **1028** are provided to a contrast score engine **1044**. The contrast score engine **1044** may register the images **1028**, for example aligning the images. As known by those skilled in the art, aligning the images may allow for them to be properly compared. For example, slight movements of the imaging tool (e.g., c-arm) or of the patient may result in slight differences between the viewpoints associated with the images **1028**. Thus, the same vessel may be positioned differently in the images **1028**.

(138) Subsequent to aligning the images, the contrast score engine **1044** may determine contrast scores **1026** for the images **1028**. For example, the angiographic images may be in grayscale. In this example, the engine **1044** may determine a contrast score based on a vessel depicted in one of the images **1028**. The contrast score may indicate, for example, an average grayscale value. These contrast scores may be generated based on the same vessel as depicted or included in the images **1028**.

(139) As an example, once the images are aligned **1028** a same segmentation mask may be used (e.g., applied) to the images. The segmentation mask may thus identify the vessel in the images **1028** and the contrast scores **1026** may be generated using respective image information for the vessel. In some embodiment's, the segmentation mask may represent a segmentation mask which is a combination, or aligning of, the segmentation masks determined for the images **1028** in FIG. **10B**. In some embodiments, the segmentation masks may be aligned and then combined using a logical 'Or' such that the masks may extend beyond vessels depicted in an image. As may be appreciated, the image may thus have a shorter view of the vessels and, as described below, when computing the contrast score the image may have a lower contrast score due to use of additional non-vessel areas which are darker.

(140) A comparison engine **1044** may then identify the optimal angiographic image **1042** based on

the contrast scores **1026** and mask scores **1030**. For example, the engine **1044** may select image **1042** as being one of the images **1028** with the highest contrast score **1026**. This may indicate that the image **1042** has an acceptable size or length of vessel (e.g., as described in FIG. **10B**), and has the best image contrast. As another example, the engine **1044** may use a combination of the contrast scores **1026** and mask scores **1030**. For example, the scores **1026**, **1030**, may be weighted and the highest combination may indicate the optimal angiographic image **1042**. Optionally, the mask scores **1030** may be used only upon two or more of the images **1028** having contrast scores **1026** within a threshold.

(141) While FIGS. **10A-10C** describe use of machine learning models, as may be appreciated a single machine learning model or multiple machine learning models may be used. For example, a single machine learning model may be end-to-end trained to identify an optimal angiographic image based on a received image sequence. As another example, multiple machine learning models may be used to perform different steps. For example, a first model may be used to identify images which are end-diastolic, and a second model may be used to output segmentation masks.

(142) Left-Side/Right-Side Arteries

(143) As known by those skilled in the art, there are two primary coronary arteries—the right coronary artery and the left main coronary artery. The right-side has a main artery, known as the right coronary artery, while the left-side has more than one artery. For example, the left-side bifurcates into the left anterior descending (LAD) artery and the left circumflex artery (LCX). The left circumflex artery has a branch referred to as the left marginal artery (LMA).

(144) In some embodiments, the system **100** may analyze a received image sequence **1000** and identify whether the image sequence **1000** is depicting left-side, or right-side, vessels. For example, the system **1000** may provide each image of the image sequence **1000** to a machine learning model (e.g., a convolutional neural network, optionally with one or more fully-connected layers). The model may output, for each image, respectively probabilities of the depicted vessels being left-side or right-side. The model may also output a classification indicating whether the vessels are left-side or right-side. The image sequence **1000** as whole is determined to depict the right or left side of the heart according to what the majority of the included angiographic images are determined to be. For example, a voting technique may be used to select a side based on whether the majority of the included images are determined to be left-side or right-side.

(145) Thereafter, the system **100** may use the assigning of left-side or right-side to enhance accuracy of its determinations. For example, in some embodiments the system **1000** may use separate machine learning models to determine images which are end-diastolic. In this example, two machine learning models may be trained using training data specific to the left-side or right-side. Similarly, the system **1000** may use separate segmentation networks or models for the left-side or right-side.

(146) With respect to separate segmentation masks, as described above the left-side may have two or more arteries (e.g., the LAD, and LCX or LMA). For the left-side, the system **1000** may therefore generate two or more segmentation masks. In some embodiments, different segmentation networks may be used for the arteries. As described in FIG. **10C**, the system **1000** may determine mask scores based on the segmentation masks. For the left-side, the system **1000** may thus determine two or more mask scores for each image. These mask scores may optionally be combined, or aggregated, into a single mask score for the image. The mask scores may optionally be maintained separately and used to filter images as described above. For example, images which have a mask score less than a threshold percent of a maximum mask score may be discarded.

(147) Example Flowcharts

(148) FIG. **11** illustrates is flowchart of an example process **1100** for determining an optimal angiographic image. For convenience, the process **1100** will be described as being performed by a system of one or more computers or processors (e.g., the optimal image determination system **100**).

(149) At block **1102**, the system receives a vascular image sequence. As described, the system

receives vascular images, such as angiographic images, of a portion of a patient's heart. The images may be taken by an imaging system or tool (e.g., a c-arm) at a particular rotation and/or translation about the patient's heart. Thus, the images may be associated with a particular viewpoint of the portion.

(150) At block **1104**, the system optionally determines whether vessels in the image sequence correspond to the left-side or right-side of the patient's heart. In some embodiments, a machine learning model (e.g., a convolutional neural network) may be used to effectuate this determination. For example, and as described above, the machine learning model may output values indicative of respective likelihoods that the vessels are included in the left-side or right-side.

(151) At block **1106**, the system determines a subset of the vascular images which are end diastolic. As part of identifying an optimal image, and as described in FIG. **10A**, the system determines vascular images which are associated with a lengthening and/or relaxing of the vessels of the heart. This cardiac phase, such as end diastolic phase, may allow for enhanced downstream processing of the optimal image. For example, an end diastolic phase image may provide added detail and/or clarity of vessels such that an end-user may more rapidly identify, mark, and so on, vessels in the image. As another example, end diastolic phase images may allow for superior (e.g., less error-prone) three-dimensional modeling.

(152) At block **1108**, the system generates segmentation masks based on the subset. As described in FIG. **10B**, the system generates segmentation masks to identify vascular images which depict larger and/or lengthier vessels. For example, while taking certain vascular images the dye may not properly fill into the patient's vessels such that certain vascular images may result in less apparent vessels.

(153) The system generates mask scores based on the segmentation masks. For example, the mask scores may indicate a length or size associated with vessels included in the segmentation masks. The system may then filter, such as remove or discard, images which have less than a threshold percentage of a maximum mask score.

(154) As described above, the system may generate a single segmentation mask for a right-side vascular image and two or more segmentation masks for a left-side image. For example, and with respect to the left-side image, the system may generate a first segmentation mask depicting vessels associated with a left anterior descending artery. The system may similarly generate a second segmentation mask depicting vessels associated with a left marginal artery. These segmentation masks may be analyzed separately or combined into a single mask score as described herein.

(155) At block **1110**, the system determines the optimal vascular image based on the segmentation masks and scores associated with image quality. The image quality scores, as described in FIG. **10C**, may be referred to as contrast scores and indicate measures of contrast quality in the vascular images. An example process to determine a contrast score is described in FIG. **12**. As described above, the system may thus select the optimal image as having the best image quality. The system may also select the optimal image as having the best combination of image quality and mask score.

(156) The system may output the optimal vascular image for presentation via an interactive user interface as described in FIG. **1**. The end-user may review the determined image and optionally select a different vascular image from the sequence. In some embodiments, such overrides may be used to update the machine learning models described herein.

(157) FIG. **12** is a flowchart of an example process **1200** for selecting an optimal angiographic image from an image sequence based on contrast scores. For convenience, the process **1200** will be described as being performed by a system of one or more computers or processors (e.g., the optimal image determination system **100**).

(158) At block **1202**, the system receives obtains segmentation masks generated from vascular images. At block **1204**, the system determines mask scores associated with the vessels depicted in the segmentation masks. At block **1206**, the system selects a subset of the vascular images based on the mask scores.

(159) At block **1208**, the system registers the subset of vascular images. For example, the system aligns the images (e.g., rotates the images, removes portions of the images, and so on) to allow for the subset to have same features or elements (e.g., vessels) in same portions of the images. The system may generate a particular segmentation mask, such as a combination of the segmentation masks (e.g., a sum of the masks), to be universally applied to the subset. In some embodiments, the particular segmentation mask may be an aligning of the segmentation masks. In some embodiments, the particular segmentation mask may represent a segmentation mask generated from an aligned image.

(160) At block **1210**, the system determines contrast scores for the subset of vascular images. The system applies the particular segmentation mask to each image in the subset to identify the vessels depicted therein. The system then determines the contrast score for an image based on the average grayscale value of the pixels which form the vessels depicted in the image. A lower average grayscale value may indicate, in some embodiments, a higher contrast score.

(161) At block **1212**, the system selects an optimal vascular image as described at least in FIGS. **10C** and **11**.

(162) Example System

(163) Reference is now made to FIG. **13**, which schematically illustrates a system **1300** configured for use in vascular tree segmentation from cardiac images, according to some embodiments of the present disclosure. In some embodiments, the system **1300** may be the system **100** described herein.

(164) Computing device **1305** is a main subsystem of system **1300**. Imaging device **1310** may be provided with system **1300** or may be a separately provided imaging device with which system **1300** is interconnected to allow access to cardiac vasculature images generated by imaging device **1310**. In some embodiments, imaging device **1310** is an X-ray angiography machine.

(165) Computing device **1305**, in some embodiments, comprises processor **1301**. Processor **1301** comprises, collectively, the processing capabilities of the computing device **1305**, and does not imply limitation to either a single processing unit, a single enclosure, or a single processing device type. For example, processor **1301** may mix CPU and GPU processing units; processor **1301** is optionally distributed among processing units linked by network connections. Memory **1304A**, comprises one or both of volatile storage **1302** and data storage device **1304** (again, these blocks comprise, collectively, available memory capabilities of the computing device). Processor instructions **1303** (stored in memory **1304A**) instruct the processor to perform computational aspects of the system's function, for example, computational aspects of one or more of the methods described herein. For example, processor instructions may comprise programming instructions for any one or more of the methods of FIGS. **11** and **12**, and/or instructions for performing any one or more of the methods or techniques described in relation to FIGS. **2-9G**. Memory **1304A**, in some embodiments, encodes a machine learning product which may be a ML-based vascular identifier. In some embodiments, additionally or alternatively, memory **1304A** encodes instructions for carrying out a formula-based algorithm.

(166) Optional user interface **1307** is configured, in some embodiments, to support receiving user-specified instructions to the system, and to provide displays and indications of device function, for example, images of cardiac vasculature and/or segmentations thereof.

Other Embodiments

(167) All of the processes described herein may be embodied in, and fully automated, via software code modules executed by a computing system that includes one or more computers or processors. The code modules may be stored in any type of non-transitory computer-readable medium or other computer storage device. Some or all the methods may be embodied in specialized computer hardware.

(168) Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms

described herein can be performed in a different sequence or can be added, merged, or left out altogether (for example, not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, for example, through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

(169) The various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a processing unit or processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry configured to process computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable device that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Although described herein primarily with respect to digital technology, a processor may also include primarily analog components. For example, some or all of the signal processing algorithms described herein may be implemented in analog circuitry or mixed analog and digital circuitry. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

(170) Conditional language such as, among others, “can,” “could,” “might” or “may,” unless specifically stated otherwise, are understood within the context as used in general to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

(171) Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is understood with the context as used in general to present that an item, term, etc., may be either X, Y, or Z, or any combination thereof (for example, X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

(172) Any process descriptions, elements or blocks in the flow diagrams described herein and/or depicted in the attached figures should be understood as potentially representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or elements in the process. Alternate implementations are included within the scope of the embodiments described herein in which elements or functions may be deleted, executed out of order from that shown, or discussed, including substantially concurrently or in reverse order, depending on the functionality involved as would be understood by those skilled in the art.

(173) Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are

intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A working in conjunction with a second processor configured to carry out recitations B and C. (174) It should be emphasized that many variations and modifications may be made to the above-described embodiments, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure.

Claims

1. A method implemented by a system of one or more computers, the method comprising: accessing an image sequence comprising a plurality of vascular images, the vascular images depicting a portion of a heart from a particular viewpoint and the vascular images being associated with different times within a time range; determining a subset of the vascular images which are associated with a particular cardiac phase, wherein determining comprises computing a forward pass through a machine learning model trained to classify vascular images based on cardiac phase; generating segmentation masks associated with the subset, wherein the segmentation masks segment vessels included in the respective vascular images which form the subset, wherein mask scores are determined for the segmentation masks which are indicative of a size or length associated with a vessel included in a segmentation mask, and wherein the subset is filtered to remove one or more vascular images based on the mask scores; and determining a particular vascular image included in the filtered subset, wherein the determination is based analyzing one or more image quality measures determined for each vascular image included in the filtered subset, wherein the particular vascular image is configured for inclusion in an interactive user interface.
2. The method of claim 1, wherein the vascular images are angiographic images.
3. The method of claim 1, wherein determining a subset of cardiac phase images comprises: determining whether the image sequence is associated with a left-side or a right-side of the heart, wherein the machine learning model is selected from a plurality of machine learning models based on the determination.
4. The method of claim 1, wherein the machine learning model is a convolutional neural network, and wherein determining the subset comprises: obtaining, from the image sequence, a threshold number of the vascular images, wherein the images which form the threshold number are contiguous in the image sequence; and providing the threshold number of the vascular images as input to the machine learning model, wherein the machine learning outputs a classification associated with a particular image in the threshold number.
5. The method of claim 1, wherein the particular cardiac phase is end-diastolic.
6. The method of claim 1, wherein the segmentation masks are generated based on a different machine learning model, wherein the different machine learning model is trained to segment vessels depicted in vascular images.
7. The method of claim 1, wherein the image sequence is determined to be associated with a left-side or a right-side of the heart, and wherein for the right-side, a single segmentation mask is generated for each vascular image included in the subset.
8. The method of claim 1, wherein the image sequence is determined to be associated with a left-side or a right-side of the heart, and wherein for the left-side, two or more segmentation masks are generated for each vascular image included in the subset.
9. The method of claim 1, wherein a mask score is indicative of a length associated with a vessel or an area associated with the vessel.
10. The method of claim 1, wherein determining a particular vascular image comprises: registering the vascular images included in the filtered subset, wherein registering comprises aligning features

depicted in the vascular images; determining image quality measures comprising contrast scores for the vascular images included in the filtered subset, wherein a contrast score indicates an average grayscale value associated with vessels in the vascular images; and determining the particular vascular image based on the contrast scores.

11. The method of claim 10, wherein a unified segmentation mask is generated for the vascular images included in the filtered subset, and wherein the contrast scores compare contrast of same vessels included in the vascular images.

12. The method of claim 1, wherein the interactive user interface is configured to enable selection of a different vascular image than the particular vascular image, and wherein the system is configured to update the machine learning model based on the selection.

13. A system comprising one or more computers and non-transitory computer storage media storing instructions that when executed by the one or more computers, cause the one or more computers to: access an image sequence comprising a plurality of vascular images, the vascular images depicting a portion of a heart from a particular viewpoint and the vascular images being associated with different times within a time range; determine a subset of the vascular images which are associated with a particular cardiac phase, wherein determining comprises computing a forward pass through a machine learning model trained to classify vascular images based on cardiac phase; generate segmentation masks associated with the subset, wherein the segmentation masks segment vessels included in the respective vascular images which form the subset, wherein mask scores are determined for the segmentation masks which are indicative of a size or length associated with a vessel included in a segmentation mask, and wherein the subset is filtered to remove one or more vascular images based on the mask scores; and determine a particular vascular image included in the filtered subset, wherein the determination is based analyzing one or more image quality measures determined for each vascular image included in the filtered subset, wherein the particular vascular image is configured for inclusion in an interactive user interface.

14. The system of claim 13, wherein to determine a subset of cardiac phase images, the instructions cause the one or more computers to: determine whether the image sequence is associated with a left-side or a right-side of the heart, wherein the machine learning model is selected from a plurality of machine learning models based on the determination.

15. The system of claim 13, wherein the image sequence is determined to be associated with a left-side or a right-side of the heart, wherein for the right-side, a single segmentation mask is generated for each vascular image included in the subset, or wherein for the left-side, two or more segmentation masks are generated for each vascular image included in the subset.

16. The system of claim 13, wherein to determine a particular vascular image, the instructions cause the one or more computers to: register the vascular images included in the filtered subset, wherein registering comprises aligning features depicted in the vascular images; determine image quality measures comprising contrast scores for the vascular images included in the filtered subset, wherein a contrast score indicates an average grayscale value associated with vessels in the vascular images; and determine the particular vascular image based on the contrast scores.

17. Non-transitory computer storage media storing instructions that when executed by a system of one or more computers, cause the one or more computers to: access an image sequence comprising a plurality of vascular images, the vascular images depicting a portion of a heart from a particular viewpoint and the vascular images being associated with different times within a time range; determine a subset of the vascular images which are associated with a particular cardiac phase, wherein determining comprises computing a forward pass through a machine learning model trained to classify vascular images based on cardiac phase; generate segmentation masks associated with the subset, wherein the segmentation masks segment vessels included in the respective vascular images which form the subset, wherein mask scores are determined for the segmentation masks which are indicative of a size or length associated with a vessel included in a segmentation mask, and wherein the subset is filtered to remove one or more vascular images based on the mask

scores; and determine a particular vascular image included in the filtered subset, wherein the determination is based analyzing one or more image quality measures determined for each vascular image included in the filtered subset, wherein the particular vascular image is configured for inclusion in an interactive user interface.

18. The computer storage media of claim 17, wherein to determine a subset of cardiac phase images, the instructions cause the one or more computers to: determine whether the image sequence is associated with a left-side or a right-side of the heart, wherein the machine learning model is selected from a plurality of machine learning models based on the determination.

19. The computer storage media of claim 17, wherein the image sequence is determined to be associated with a left-side or a right-side of the heart, wherein for the right-side, a single segmentation mask is generated for each vascular image included in the subset, or wherein for the left-side, two or more segmentation masks are generated for each vascular image included in the subset.

20. The computer storage media of claim 17, wherein to determine a particular vascular image, the instructions cause the one or more computers to: register the vascular images included in the filtered subset, wherein registering comprises aligning features depicted in the vascular images; determine image quality measures comprising contrast scores for the vascular images included in the filtered subset, wherein a contrast score indicates an average grayscale value associated with vessels in the vascular images; and determine the particular vascular image based on the contrast scores.
