

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387359
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Nishi; Youhei

Package measuring apparatus and package measuring method

Abstract

A package measuring apparatus according to the present disclosure includes: a mounting table; floatation member configured to float a package above an upper surface of the mounting table; a depth sensor configured to capture an image of the package being floated by the floatation member above the upper surface of the mounting table and thereby detect a distance between the depth sensor and the package, the depth sensor being disposed at a position where the depth sensor is able to capture the image of the package from substantially directly above it; and a control unit configured to calculate a size of the package based on data acquired from the depth sensor.

Inventors:	Nishi; Youhei (Kanagawa, JP)
Applicant:	NEC Platforms, Ltd. (Kawasaki, JP)
Family ID:	85386658
Assignee:	NEC Platforms, Ltd. (Kanagawa, JP)
Appl. No.:	17/893571
Filed:	August 23, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230071500 A1	Mar. 09, 2023

Foreign Application Priority Data

JP	2021-143643	Sep. 03, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: G01B11/02 (20060101); G01B11/22 (20060101); G06T7/62 (20170101)

U.S. Cl.:

CPC **G06T7/62** (20170101); **G01B11/22** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2003/0147075	12/2002	Otsuki	356/338	C23C 16/4412
2018/0215564	12/2017	Matsumura	N/A	B65H 3/0684
2020/0139553	12/2019	Diankov	N/A	G06T 7/50
2023/0108073	12/2022	Li	700/216	B65G 1/0492

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204162105	12/2014	CN	B65G 65/34
2008-151714	12/2007	JP	N/A
2018-510347	12/2017	JP	N/A
2020-016645	12/2019	JP	N/A
2021-081431	12/2020	JP	N/A
2022-106386	12/2021	JP	N/A
20120065751	12/2011	KR	B65G 49/06

OTHER PUBLICATIONS

JP Office Action for JP Application No. 2021-143643, mailed on Jul. 4, 2023 with English Translation. cited by applicant

JP Office Communication for JP Application No. 2021-143643, mailed on Oct. 31, 2023 with English Translation. cited by applicant

Primary Examiner: Menberu; Beniyam

Background/Summary

INCORPORATION BY REFERENCE

(1) This application is based upon and claims the benefit of priority from Japanese patent application No. 2021-143643, filed on Sep. 3, 2021, the disclosure of which is incorporated herein in its entirety by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a package measuring apparatus and a package measuring method.

BACKGROUND ART

(3) A package measuring apparatus, which measure the size (the width, the depth, the height) of a

package using a depth sensor, has been known.

(4) For example, Japanese Unexamined Patent Application Publication No. 2021-081431 discloses a package measuring apparatus that captures an image of a package using a depth sensor from substantially directly above it and thereby detects a distance between the depth sensor and a rectangular parallelepiped package placed on a mounting table, and calculates the size of the package based on data acquired from the depth sensor.

(5) However, in the package measuring apparatus disclosed in Japanese Unexamined Patent Application Publication No. 2021-081431, when the size of a thin package such as a general envelope and a padded envelope is measured, since the difference between the distance from the depth sensor to the package and the distance from the depth sensor to the mounting table is small, it is difficult to identify the package. This causes a problem that the accuracy of the measurement of the size of the package may deteriorate.

SUMMARY

(6) Therefore, an object of the present disclosure is to solve the above-described problem and to provide a package measuring apparatus and a package measuring method that are capable of improving the accuracy of measurement of the size of a package even when the size of a thin package is measured.

(7) A package measuring apparatus according to an example aspect includes: a mounting table; floatation member configured to float a package above an upper surface of the mounting table; a depth sensor configured to capture an image of the package being floated by the floatation member above the upper surface of the mounting table and thereby detect a distance between the depth sensor and the package, the depth sensor being disposed at a position where the depth sensor is able to capture the image of the package from substantially directly above it; and a control unit configured to calculate a size of the package based on data acquired from the depth sensor.

(8) A package measuring method according to an example aspect includes: floating a package above an upper surface of a mounting table by floatation member; capturing an image of the package being floated by the floatation member above the upper surface of the mounting table and thereby detecting a distance between a depth sensor and the package by the depth sensor disposed at a position where the depth sensor is able to capture the image of the package from substantially directly above it; and calculating a size of the package based on data acquired from the depth sensor.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of the present disclosure will become more apparent from the following description of certain example embodiments when taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a diagram showing an example of a configuration of a package measuring apparatus according to the related art;

(3) FIG. 2 is a diagram showing an example of a rectangular parallelepiped circumscribing a package;

(4) FIG. 3 is a diagram showing an example of a contour of a package in a plan view;

(5) FIG. 4 is a perspective view showing an example of a configuration of the package measuring apparatus according to the related art;

(6) FIG. 5 is a front view showing an example of a configuration of the package measuring apparatus according to the related art;

(7) FIG. 6 is a diagram for explaining a problem of the package measuring apparatus according to the related art;

- (8) FIG. 7 is a perspective view showing an example of a configuration of a package measuring apparatus according to a first example embodiment;
- (9) FIG. 8 is a front view showing an example of the configuration of the package measuring apparatus according to the first example embodiment;
- (10) FIG. 9 is a diagram for explaining an effect of the package measuring apparatus according to the first example embodiment;
- (11) FIG. 10 is a flow diagram for explaining an example of a schematic flow of operations performed when the package measuring apparatus according to the first example embodiment measures a size of a package;
- (12) FIG. 11 is a perspective view showing an example of a configuration of a package measuring apparatus according to another example embodiment;
- (13) FIG. 12 is a front view showing an example of the configuration of the package measuring apparatus according to another example embodiment;
- (14) FIG. 13 is a perspective view showing an example of a configuration of a package measuring apparatus according to still another example embodiment;
- (15) FIG. 14 is a front view showing an example of the configuration of the package measuring apparatus according to still another example embodiment; and
- (16) FIG. 15 is a diagram showing an example of a hardware configuration of a control unit according to the first example embodiment.

EXAMPLE EMBODIMENT

(17) The related art and example embodiments will be described hereinafter with reference to the drawings. Note that, for the clarification of the description, the following descriptions and the drawings are partially omitted and simplified as appropriate. Further, the same elements are denoted by the same reference numerals or symbols throughout the drawings, and redundant descriptions are omitted as necessary.

(18) <Related Art>

(19) Prior to describing the example embodiments of the present disclosure, the related art will be described.

(20) FIG. 1 is a diagram showing an example of a configuration of a package measuring apparatus **90** according to the related art.

(21) As shown in FIG. 1, the package measuring apparatus **90** according to the related art includes a mounting table **11**, a depth sensor **12**, and a control unit **13**.

(22) The mounting table **11** is a table on which a package P is placed. Note that, although the shape of the mounting table **11** is not limited, it is assumed that the upper surface thereof on which the package P is placed is at least planar.

(23) The depth sensor **12** is disposed at a position where it can capture an image of the package P placed on the mounting table **11** from directly above it, and captures an image of the package P and thereby detects the distance between the depth sensor **12** and the package P. The depth sensor **12** may employ a Time Of Flight (TOF) method, or other measuring methods such as a pattern irradiation method. Further, although an infrared light or the like may be used in performing the measurement, it is not limited thereto. It is needless to mention that the term “directly above” may indicate substantially directly above.

(24) Further, in the example shown in FIG. 1, the depth sensor **12** is attached to the mounting table **11** via a sensor attachment part **14**. The sensor attachment part **14** includes a support pillar **14A** vertically installed on the mounting table **11**, and a sensor attachment member **14B** installed at an upper end of the support pillar **14A**. The sensor attachment member **14B** may include a mechanism for sliding the depth sensor **12** so that a position of the depth sensor **12** in the horizontal direction (the xy direction) (i.e., a distance between the depth sensor **12** and the support pillar **14A**) can be changed. Further, the support pillar **14A** may include a mechanism capable of changing its height (the z-direction). This makes it possible to change the height of the depth sensor **12**. However, the

method for installing the depth sensor **12** is not limited to the above, and the depth sensor **12** can be installed by any method in a position where it can capture an image of the package P placed on the mounting table **11** from directly above it.

(25) The control unit **13** is configured to be able to communicate with the depth sensor **12** wirelessly or by wire, and calculates the size (the width, the depth, the height) of the package P placed on the mounting table **11** based on data acquired from the depth sensor **12**.

(26) Further in the example shown in FIG. **1**, the control unit **13** is implemented by a tablet terminal which is also referred to as a mobile Personal Computer (PC). However, the method for implementing the control unit **13** is not limited thereto, and the control unit **13** may be implemented by an apparatus such as a stationary PC or a mobile phone (including one referred to as a smartphone).

(27) Further, in the example shown in FIG. **1**, the control unit **13** is attached to the support pillar **14A**. However, the place where the control unit **13** is installed is not limited thereto, and the control unit **13** may be installed in any place near the mounting table **11**. Further, when the control unit **13** is implemented by a tablet terminal or a mobile phone, it is not necessary for the control unit **13** to be fixedly installed.

(28) Next, the measurement principle in accordance with which the package measuring apparatus **90** according to the related art measures the size of the package P will be described. Note that it is assumed that the control unit **13** captures an image of the mounting table **11** on which no package P is placed by the depth sensor **12** in advance and holds it as background depth image data.

(29) Step A1:

(30) First, the control unit **13** controls the depth sensor **12** so as to capture an image of the package P placed on the mounting table **11** from directly above it and thereby acquires depth image data of the package P.

(31) Step A2:

(32) Next, the control unit **13** compares the depth image data of the package P with the background depth image data, and then it extracts a contour of the package P in a plan view (the xy plane).

(33) Step A3:

(34) If the shape of the package P is a rectangular parallelepiped shape, the contour of the package P in a plan view is a rectangle. Therefore, the control unit **13** calculates lengths of two sides of the rectangle as the width and the depth of the package P.

(35) On the other hand, if the shape of the package P is not a rectangular parallelepiped shape, the contour of the package P in a plan view is not a rectangle. Therefore, when the shape of the package P is not a rectangular parallelepiped shape, the control unit **13** assumes that a rectangular parallelepiped circumscribing the package P is the package P as shown in FIG. **2** and calculates lengths of two sides of the rectangle which is the upper surface of the rectangular parallelepiped as the width and the depth of the package P.

(36) A method for the control unit **13** to calculate the width and the depth of the package P will be described below. A description will be given below in accordance with the assumption that the shape of the package P is not a rectangular parallelepiped shape and the contour of the package P in a plan view is elliptical as shown in FIG. **3**.

(37) In the example shown in FIG. **3**, the shape of the package P is not a rectangular parallelepiped shape, and the contour of the package P in a plan view is elliptical. Therefore, the control unit **13** assumes that a rectangular parallelepiped (a dotted line in the figure) circumscribing the package P is the package P.

(38) Next, the control unit **13** specifies the following positions of first to third vertices of the aforementioned package P which the control unit **13** has assumed is a rectangular parallelepiped. The first vertex is the leftmost vertex among the vertices of the above assumed rectangular parallelepiped on the upper surface thereof. The second vertex is the rightmost vertex among the vertices of the above assumed rectangular parallelepiped on the upper surface thereof. The third

vertex is the uppermost or the lowermost vertex among the vertices of the above assumed rectangular parallelepiped on the upper surface thereof. Note that it may be determined in advance whether the third vertex is the uppermost or the lowermost vertex.

(39) The control unit **13** obtains two-dimensional (planar) coordinates of the first vertex in the space of which the origin is the center of the depth sensor **12** as follows. That is, the control unit **13** obtains the two-dimensional coordinates of the first vertex based on a viewing angle of the depth sensor **12**, data of the distance between the first vertex and the depth sensor **12**, the number of sensor elements of the depth sensor **12**, and position data of the sensor element of the depth sensor **12** corresponding to the first vertex.

(40) Similarly, the control unit **13** obtains two-dimensional coordinates of the second vertex and the third vertex in the space of which the origin is the center of the depth sensor **12** as follows. That is, the control unit **13** obtains the two-dimensional coordinates of the second vertex based on a viewing angle of the depth sensor **12**, data of the distance between the second vertex and the depth sensor **12**, the number of sensor elements of the depth sensor **12**, and position data of the sensor element of the depth sensor **12** corresponding to the second vertex. Further, the control unit **13** obtains the two-dimensional coordinates of the third vertex based on a viewing angle of the depth sensor **12**, data of the distance between the third vertex and the depth sensor **12**, the number of sensor elements of the depth sensor **12**, and position data of the sensor element of the depth sensor **12** corresponding to the third vertex.

(41) Then, the control unit **13** calculates the length of a first side between the first vertex and the third vertex based on the two-dimensional coordinates of each of the first vertex, the second vertex, and the third vertex and calculates the length of a second side between the second vertex and the third vertex. One of the length of the first side and the length of the second side calculated here is the width of the package P, and the other one is the depth of the package P.

(42) For example, in the example shown in FIG. 3, regarding the package P which the control unit **13** has assumed is a rectangular parallelepiped, the leftmost vertex is a vertex A, the rightmost vertex is a vertex B, and the uppermost vertex is a vertex C among the vertices on the upper surface of the rectangular parallelepiped. Therefore, if it is determined that the third vertex is the uppermost vertex, the first vertex, the second vertex, and the third vertex are the vertex A, the vertex B, and the vertex C, respectively. Thus, the first side is a side AC and the second side is a side BC.

(43) Therefore, in the example shown in FIG. 3, the control unit **13** first obtains the two-dimensional coordinates of each of the vertices A, B, and C, and then calculates the length of the side AC and the length of the side BC based on the two-dimensional coordinates of each of the vertices A, B, and C. Then, the control unit **13** sets one of the length of the side AC and the length of the side BC as the width of the package P, and sets the other one as the depth of the package P.

(44) Step A4:

(45) After that, the control unit **13** calculates a height of the package P based on the data of the distance from the depth sensor **12** to the upper surface of the package P in the depth image data of the package P and the data of the distance from the depth sensor **12** to the upper surface of the mounting table **11** in the background depth image data of the package P.

(46) In this way, the control unit **13** can measure the size (the width, the depth, the height) of the package P.

(47) However, as shown in FIGS. 4 and 5, the package P may be a thin package such as a general envelope or a padded envelope. In this case, since the difference between the distance from the depth sensor **12** to the package P and the distance from the depth sensor **12** to the mounting table **11** is small, it is difficult for the control unit **13** to identify the package P. As a result, in the above-described Step A2, since the control unit **13** cannot accurately extract the contour of the package P in a plan view, the accuracy of measurement of the size of the package P deteriorates. This problem will be described below with reference to FIG. 6.

(48) As shown in FIG. 6, when the package P is a thin package having a height of $\Delta\alpha$ [mm] and it is assumed the distance from the depth sensor 12 to the upper surface of the mounting table 11 is X [mm], the distance from the depth sensor 12 to the upper surface of the package P is $X - \Delta\alpha$ [mm].
(49) However, a value of the distance detected by the depth sensor 12 has a variation β . Therefore, the control unit 13 cannot distinguish whether or not the above-described $X - \Delta\alpha$ is a value ($X \pm \beta$) varied by the variation β of the depth sensor 12, and thus it is difficult to identify the package P.
(50) Therefore, when the size of a thin package P is measured, the package measuring apparatus 90 according to the related art cannot accurately extract the contour of the package P in a plan view in the above-described Step A2, and thus the accuracy of measurement of the size of the package P deteriorates.

(51) Example embodiments described below solve the above-described problem of the package measuring apparatus 90 according to the related art.

First Example Embodiment

(52) Each of FIGS. 7 and 8 is a diagram showing an example of a configuration of a package measuring apparatus 10 according to a first example embodiment, FIG. 7 being a perspective view thereof, and FIG. 8 being a front view thereof. Note that each of FIGS. 7 and 8 shows only the configuration of the mounting table 11 and the surroundings thereof, and configurations other than this one are omitted since they are similar to those of the package measuring apparatus 90 according to the related art shown in FIG. 1. Specifically, in FIGS. 7 and 8, the depth sensor 12, the control unit 13, and the sensor attachment part 14 are omitted.

(53) As shown in FIGS. 7 and 8, the package measuring apparatus 10 according to the first example embodiment differs from the package measuring apparatus 90 according to the related art shown in FIG. 1 in that a plurality of projections 15 are added as floatation members for floating the package P above the upper surface of the mounting table 11.

(54) The plurality of projections 15 are members projecting from the upper surface of the mounting table 11.

(55) The package P is placed on all or some of the plurality of projections 15. Thus, the package P is floating above the upper surface of the mounting table 11.

(56) Further, the plurality of projections 15 have the same height (α [mm]) from the top surface of the mounting table 11. Thus, it is ensured that the package P is placed in a planar fashion while it is floating above the upper surface of the mounting table 11.

(57) Note that, regarding the plurality of projections 15, the number of projections, the size of the projections in a plan view (the xy plane), the installation interval between the projections, and the like are not limited to particular ones. These may be appropriately determined in accordance with the size and the weight of the package P and the performances (e.g., the viewing angle, the number of sensor elements, and the positions of the sensor elements, which will be hereinafter the same) of the depth sensor 12. Further, in the examples shown in FIGS. 7 and 8, although the projection 15 has a quadrangular prism shape, the shape of the projection 15 is not limited to a particular shape. However, depending on the size of the package P, some projections 15 that are not covered by the package P are present as recognized by the depth sensor 12. When these projections 15 are recognized by the depth sensor 12, the control unit 13 may erroneously extract the contour of the package P. Therefore, it is preferable that the projections 15 not be recognized by the depth sensor 12. In order to achieve this, it is preferable that the size of the projection 15 in a plan view be sufficiently reduced. However, since the size of the projection 15 in a plan view which is not recognized by the depth sensor 12 varies according to the above-described performances of the depth sensor 12, the size of the projection 15 in a plan view may be appropriately determined according to the above-described performances of the depth sensor 12. Alternatively, the projection 15 may be made of glass, acrylic, or the like having a high transmittance so that it is not recognized by the depth sensor 12.

(58) The above-described configuration of the package measuring apparatus 10 according to the

first example embodiment provides an effect that the accuracy of measurement of the size of the package P can be improved even when the package P is a thin package. The reason why the above effect is obtained will be described below with reference to FIG. 9. Note that, in the example shown in FIG. 9, like in the example shown in FIG. 6, it is assumed that the height of the package P is $\Delta\alpha$ [mm] and the distance from the depth sensor 12 to the upper surface of the mounting table 11 is X [mm].

(59) As shown in FIG. 9, the package measuring apparatus 10 according to the first example embodiment includes the plurality of projections 15 projecting from the upper surface of the mounting table 11 which enable the package P to float above the upper surface of the mounting table 11.

(60) Therefore, a space corresponding to the height a [mm] of the projection 15 is formed between the mounting table 11 and the package P. As a result, the distance from the depth sensor 12 to the upper surface of the package P becomes $X - \Delta\alpha - a$ [mm], and a difference is generated between this distance and the distance X [mm] from the depth sensor 12 to the upper surface of the mounting table 11. Thus, since the control unit 13 can identify the package P even when the package P is a thin package, the contour of the package P in a plan view can be accurately extracted in the above-described Step A2, and as a result, the accuracy of measurement of the size of the package P can be improved.

(61) However, it is preferable that the height a [mm] of the projection 15 be a sufficient height so as to distinguish that the above-described $X - \Delta\alpha - a$ is not the value $(X \pm \beta)$ varied by the variation β [mm] of the depth sensor 12. Therefore, the height a of the projection 15 and the variation β of the depth sensor 12 preferably have a relationship of $a > 2 \times \beta$.

(62) Next, a schematic flow of operations performed when the package measuring apparatus 10 according to the first example embodiment measures a size of the package P will be described with reference to FIG. 10.

(63) As shown in FIG. 10, first, the plurality of projections 15 float the package P above the upper surface of the mounting table 11 (Step B1).

(64) Next, the control unit 13 controls the depth sensor 12 so as to capture an image of the package P being floated by the plurality of projections 15 above the upper surface of the mounting table 11 from directly above it and thereby detects a distance between the depth sensor 12 and the package P (Step B2). Step B2 corresponds to Step A1 described above.

(65) After that, the control unit 13 calculates the size of the package P based on data acquired from the depth sensor 12 (Step B3). Step B3 corresponds to Steps A2 to A4 described above. Therefore, Step B3 may be executed by procedures substantially similar to those of Steps A2 to A4 described above.

(66) As described above, according to the first example embodiment, the plurality of projections 15 projecting from the upper surface of the mounting table 11 which enable the package P to float above the upper surface of the mounting table 11 are provided.

(67) By this structure, a difference corresponding to the height of the projection 15 is generated between the distance from the depth sensor 12 to the upper surface of the package P and the distance X [mm] from the depth sensor 12 to the upper surface of the mounting table 11. Thus, the control unit 13 can identify the package P and accurately extract the contour of the package P in a plan view, and as a result, the accuracy of measurement of the size of the package P can be improved.

Other Example Embodiments

(68) [a]

(69) In the above-described first example embodiment, although the plurality of projections 15 are provided as floatation members for floating the package P above the upper surface of the mounting table 11, the floatation member is not limited thereto.

(70) For example, in a package measuring apparatus 10A shown in FIGS. 11 and 12, the floatation

member is a rectangular parallelepiped transmissive member **15A** which is installed on the upper surface of the mounting table **11** and which is made of a transmissive material having a high transmittance such as glass, acrylic, and polycarbonate. Since the transmissive member **15A** is made of a transmissive material, it is not recognized by the depth sensor **12**.

(71) The package **P** is placed on the upper surface of the transmissive member **15A**.

(72) By the above, like in the above-described first example embodiment, since a difference is generated between the distance from the depth sensor **12** to the upper surface of the package **P** and the distance from the depth sensor **12** to the upper surface of the mounting table **11**, the control unit **13** can identify the package **P**.

(73) Note that, like in the above-described first example embodiment, the height a of the transmissive member **15A** from the upper surface of the mounting table **11** and the variation β in the value of the distance detected by the depth sensor **12** preferably have a relationship of $\alpha > 2 \times \beta$.

(74) Further, the shape of the transmissive member **15A** is not limited to a rectangular parallelepiped shape. The transmissive member **15A** may be a columnar body (e.g., a cylindrical body and a polygonal columnar body) having a flat upper base surface.

(75) [b]

(76) Further, in a package measuring apparatus **10B** shown in FIGS. **13** and **14**, the floatation member includes a planar net-like member **15B** and a support member **15C** that supports the net-like member **15B** so that the net-like member **15B** is floating above the upper surface of the mounting table **11**. The net part of the net-like member **15B** is preferably granular so that it is not recognized by the depth sensor **12**. However, since the grain size of the net part of the net-like member **15B** which is not recognized by the depth sensor **12** varies according to the above-described performances of the depth sensor **12**, it may be appropriately determined according to the above-described performances of the depth sensor **12**. Further, the number of support members **15C** to be installed is set to four, and they are installed at the respective four corners of the upper surface of the mounting table **11**. However, the number of support members to be installed and a method for installing them are not limited to a particular number and method. Further, although the shape of the support member **15C** is a quadrangular prism shape, the shape thereof is not limited to a particular shape.

(77) The package **P** is placed on the upper surface of the net-like member **15B**.

(78) By the above, like in the above-described first example embodiment, since a difference is generated between the distance from the depth sensor **12** to the upper surface of the package **P** and the distance from the depth sensor **12** to the upper surface of the mounting table **11**, the control unit **13** can identify the package **P**.

(79) Note that, like in the above-described first example embodiment, the height a of the net-like member **15B** from the upper surface of the mounting table **11** and the variation β in the value of the distance detected by the depth sensor **12** preferably have a relationship of $\alpha > 2 \times \beta$.

(80) [c]

(81) The control unit **13** according to the above-described first example embodiment may include the following hardware configuration. FIG. **15** is a diagram showing an example of the hardware configuration of the control unit **13** according to the above-described first example embodiment.

(82) The control unit **13** shown in FIG. **15** includes a processor **131**, a memory **132**, and an input/output interface **133** for establishing connections to the depth sensor **12** and the like. The processor **131** is, for example, an arithmetic processing unit such as a Central Processing Unit (CPU) or a Graphics Processing Unit (GPU). The memory **132** is, for example, a memory such as a Random Access Memory (RAM) or a Read Only Memory (ROM). The memory **132** stores a program for implementing all or some of the functions of the control unit **13** described in the above first example embodiment. The processor **131** reads and executes this program, thereby implementing all or some of the functions of the control unit **13**. Further, the memory **132** also have a function of storing information and data held by the control unit **13**.

(83) Further, the above-described program may be stored in a non-transitory computer readable medium or a tangible storage medium. By way of example, and not a limitation, non-transitory computer readable media or tangible storage media can include a RAM, a ROM, a flash memory, a Solid State Drive (SSD) or other types of memory technologies, a Compact Disc-ROM (CD-ROM), a Digital Versatile Disc (DVD), a Blu-ray (Registered Trademark) disc or other types of optical disc storage, and magnetic cassettes, magnetic tape, magnetic disk storage or other types of magnetic storage devices. The program may be transmitted on a transitory computer readable medium or a communication medium. By way of example, and not a limitation, transitory computer readable media or communication media can include electrical, optical, acoustical, or other forms of propagated signals.

(84) The above example embodiments can be combined as desirable by one of ordinary skill in the art.

(85) Although the present disclosure has been described with reference to the example embodiments, the present disclosure is not limited to the above-described example embodiments. Various changes that may be understood by those skilled in the art may be made to the configurations and details of the present disclosure within the scope of the disclosure.

Claims

1. A package measuring apparatus comprising: a mounting table; a floatation member having a physical structure adapted to float a package above an upper surface of the mounting table; a depth sensor configured to capture an image of the package being floated by the floatation member above the upper surface of the mounting table and thereby detect a distance between the depth sensor and the package, the depth sensor being disposed at a position where the depth sensor is able to capture the image of the package from substantially directly above the package; and a memory storing instructions and a processor configured to execute the instructions to calculate a size of the package based on data acquired from the depth sensor, wherein in a case in which α is a height of the floatation member from the upper surface of the mounting table and β is a variation in a value of a distance detected by the depth sensor, α and β have a relationship of $\alpha > 2 \times \beta$.
 2. The package measuring apparatus according to claim 1, wherein the floatation member comprises a plurality of projections projecting from the upper surface of the mounting table.
 3. The package measuring apparatus according to claim 1, wherein the floatation member is a columnar body having a flat upper base surface, the floatation member being installed on the upper surface of the mounting table and being made of a transmissive material.
 4. The package measuring apparatus according to claim 1, wherein the floatation member comprises: a planar net-like member; and a support member having a physical structure adapted to support the net-like member so that the net-like member is floating above the upper surface of the mounting table.
 5. A package measuring method comprising: floating a package above an upper surface of a mounting table by a floatation member; capturing an image of the package being floated by the floatation member above the upper surface of the mounting table and thereby detecting a distance between a depth sensor and the package by the depth sensor disposed at a position where the depth sensor is able to capture the image of the package from substantially directly above the package; and calculating a size of the package based on data acquired from the depth sensor, wherein in a case in which α is a height of the floatation member from the upper surface of the mounting table and β is a variation in a value of a distance detected by the depth sensor, α and β have a relationship of $\alpha > 2 \times \beta$.
-