

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12387707
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Yanagisawa; Yoshiyuki

Projector, cooling apparatus, and control method

Abstract

A projector includes an exterior enclosure having an intake port and a discharge port, a heat source, a fan that causes a cooling gas to flow to the heat source, a loudspeaker that is disposed between one of the two openings, and the fan in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker, a characteristic data storage section that stores frequency characteristic data on the frequency characteristics of discrete frequency noise, broadband noise, and in-apparatus environmental noise, and a control section that generates the drive signal, and the control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time, a waveform generation section that generates the waveform of an interference sound, and a signal output section that outputs the drive signal.

Inventors:	Yanagisawa; Yoshiyuki (Matsumoto, JP)
Applicant:	SEIKO EPSON CORPORATION (Tokyo, JP)
Family ID:	85228466
Assignee:	SEIKO EPSON CORPORATION (Tokyo, JP)
Appl. No.:	17/889582
Filed:	August 17, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230058869 A1	Feb. 23, 2023

Foreign Application Priority Data

JP	2021-133628	Aug. 18, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: **G03B21/16** (20060101); **G06F1/20** (20060101); **G10K11/178** (20060101); **H04R1/02** (20060101)

U.S. Cl.:

CPC **G10K11/17823** (20180101); **G03B21/16** (20130101); **G06F1/206** (20130101); **G10K11/17873** (20180101); **H04R1/028** (20130101); G10K2210/109 (20130101); G10K2210/3027 (20130101); G10K2210/3044 (20130101); H04R2499/15 (20130101)

Field of Classification Search

CPC: G03B (21/14); G03B (21/16); G03B (21/18); G03B (21/20); G03B (21/145); G03B (21/202); G03B (21/2026); G03B (21/2033); G10K (11/17823); G10K (11/17825); G10K (11/17853); G10K (11/17873); G10K (11/17883); G06F (1/20); G06F (1/203); G06F (1/206); H04R (1/00); H04R (1/023); H04R (1/028); H04N (9/3141); H04N (9/3144); H04N (9/3194)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5995632	12/1998	Okada	N/A	N/A
11151978	12/2020	Tseng	N/A	G10K 11/161
2005/0094823	12/2004	Kobori et al.	N/A	N/A
2010/0097151	12/2009	Arai	331/25	H03F 3/24
2020/0310232	12/2019	Miura	N/A	F04D 27/004

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H10-020866	12/1997	JP	N/A
2005-133588	12/2004	JP	N/A

Primary Examiner: Chowdhury; Sultan

Attorney, Agent or Firm: Oliff PLC

Background/Summary

(1) The present application is based on, and claims priority from JP Application Serial Number 2021-133628, filed Aug. 18, 2021, the disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to a projector, a cooling apparatus, and a control method.

2. Related Art

(3) There is a known muffling apparatus of related art that reduces noise produced by a driven fan

(see JP-A-2005-133588 and JP-A-10-20866, for example).

(4) The muffling apparatus described in JP-A-2005-133588 includes two fans, a microphone, a loudspeaker, a rotational speed detection section, a frequency measurement section, a frequency analysis section, a rotation number counting section, a time-division control permission section, a lookup table, an f value determination section, an amplification and phase control section, and a waveform generation section.

(5) Out of the components described above, the microphone monitors the noise situation in a duct structure where airflow is generated by the rotational motion of the fans. The rotational speed detection section generates one-pulse rotation signal as information on the rotation of the two fans, and the frequency measurement section measures the frequency of the rotation of the fans from the one-pulse rotation signal and outputs information on the frequency. The rotation number counting section generates a reference for the frequency of the rotation of each of the fans with respect to the information on the frequency, a reference of the phase of the waveform of the muffled noise, and a time-division timing signal with respect to the count of the rotation number of each of the fans. The time-division control permission section issues a signal indicating control permission or non-permission for each component of the noise from each of the fans with respect to the time-division timing signal. The lookup table holds a variety of frequency characteristics of the structure, the environment, the loudspeaker, and the microphone. The f value determination section determines a fundamental frequency and a secondary component of the noise determined from the information on the frequency outputted by the frequency measurement section and the number of vanes of the fans.

(6) The amplification and phase control section controls the amplitude and the amount of shift of the phase of the waveform of the muffled noise to minimize the amount of residual noise based on the result of evaluation of the muffled noise condition during the period for which the time-division control permission signal shows a permission period for each component of the noise from each of the fans, and generates the amplitude and the amount of phase shift to which the amount of amplification correction and the amount of phase correction in the look-up table have been added. On the other hand, during the period for which the time-division control permission signal shows a non-permission period, the amplification and phase control section holds the amplitude and the amount of phase shift determined in the past permission period.

(7) The waveform generation section generates a waveform opposite in terms of phase from the waveform of each component of the noise from each of the fans based on the frequency, the rotational phase reference, the amplitude, and the amount of shift of the phase of each of four components of each of the fans to be muffled by the f-value determination section.

(8) The opposite-phase waveforms of the four components are summed up, and the summed waveform is then converted into an analog signal, from which unwanted frequency components and noise are removed. The resultant signal is amplified and then outputted to the loudspeaker.

(9) The muffling apparatus described in JP-A-2005-133588, however, uses a microphone. When the muffling apparatus includes a microphone, the cost of the microphone is added to the manufacturing cost of the muffling apparatus, resulting in a problem of not only an increase in the manufacturing cost of the muffling apparatus, but also an increase in the size of the muffling apparatus.

(10) To address the problems described above, the muffling apparatus described in JP-A-10-20866 generates the waveform of the muffled noise without using a microphone. Specifically, the muffling apparatus described in JP-A-10-20866 includes a fan, a rotation information detector, a bandpass filter, an output adjuster, and a muffling loudspeaker.

(11) The rotation information detector detects fan rotation information including the fundamental frequency of the noise produced when the fan rotates. The rotation information detector includes a photo-interrupter and a rotating disc that rotates in conjunction with the fan to transmit/block the light from the photo-interrupter, and a signal detection section outputs a signal primarily formed of

a frequency equal to the product of the “rotational speed per second” and the “number of vanes”. The bandpass filter extracts the fundamental wave of the noise based on the fan rotation information. The output adjuster adjusts the amplitude and phase of a signal representing the extracted fundamental wave of the noise. The muffling loudspeaker converts an electric signal according to the signal representing the fundamental wave outputted from the output adjuster into an audio signal and outputs the audio signal.

(12) The noise of the fan is thus reduced.

(13) The noise muffled by the muffling apparatus described in JP-A-10-20866, however, is discrete frequency noise produced as a result of the rotation of the fan, and therefore has a problem of a narrower range over which the noise can be reduced than that of the muffling apparatus described in JP-A-2005-133588.

(14) It has therefore been desired to simplify the configuration of the muffling apparatus and expand the range over which the noise can be reduced.

SUMMARY

(15) A projector according to an aspect of the present disclosure includes an exterior enclosure having an intake port and a discharge port, a heat source disposed in the exterior enclosure, a fan that causes a cooling gas to flow to the heat source, a loudspeaker that is disposed between one of two openings, the intake port and the discharge port, and the fan in a channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker, a characteristic data storage section that stores frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on a flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with a rotational speed of the fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(16) The control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates a waveform of an interference sound that interferes with the first noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(17) A cooling apparatus according to another aspect of the present disclosure includes a fan that causes a cooling gas to flow to a heat source, a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker, a characteristic data storage section that stores frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on a flow of the cooling gas generated by the driven fan, and environmental noise in accordance with a rotational speed of the fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(18) The control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates a waveform of an interference sound that reduces the first noise based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(19) A control method according to another aspect of the present disclosure is a control method executed by an electronic instrument including a fan that causes a cooling gas to flow to a heat source and a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker.

(20) The method includes acquiring frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based

on a flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with a rotational speed of the fan per unit time, generating a waveform of interference sound that interferes with the first noise leaking out of the electronic instrument based on the acquired frequency characteristic data, and outputting the drive signal based on the generated waveform of the interference sound to the loudspeaker.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagrammatic view showing the configuration of a projector according to a first embodiment.
- (2) FIG. 2 is a diagrammatic view showing the content stored in a storage section according to the first embodiment.
- (3) FIG. 3 is a graph showing the result of frequency analysis of discharge-side noise according to the first embodiment.
- (4) FIG. 4 is a block diagram showing the configuration of a control section according to the first embodiment.
- (5) FIG. 5 is a diagrammatic view showing the configuration of the projector according to a second embodiment.
- (6) FIG. 6 is a diagrammatic view showing the configuration of the projector according to a third embodiment.
- (7) FIG. 7 is a block diagram showing the configurations of the storage section and the control section according to the third embodiment.
- (8) FIG. 8 is a diagrammatic view showing the content stored in a characteristic data storage section according to the third embodiment.
- (9) FIG. 9 is a diagrammatic view showing the content stored in a phase data storage section according to the third embodiment.
- (10) FIG. 10 is a diagrammatic view showing the configuration of the projector according to a fourth embodiment.
- (11) FIG. 11 is a block diagram showing the configuration of the control section according to the fourth embodiment.

DESCRIPTION OF EXEMPLARY EMBODIMENTS

First Embodiment

- (12) A first embodiment of the present disclosure will be described below with reference to the drawings.
- (13) Schematic Configuration of Projector
- (14) FIG. 1 is a diagrammatic view showing the configuration of a projector 1A according to the present embodiment.
- (15) The projector 1A according to the present embodiment modulates light outputted from a light source to form an image according to image information and enlarges and projects the formed image on a projection receiving surface, such as a screen, and the projector 1A corresponds to an electronic apparatus. The projector 1A includes an exterior enclosure 2, an image projection apparatus 3, a power supply apparatus 4, a control apparatus 5, and a cooling apparatus 6A, as shown in FIG. 1.
- (16) Each component of the projector 1A will be described below.
- (17) Configuration of Power Supply Apparatus and Control Apparatus
- (18) The power supply apparatus 4 and the control apparatus 5 will first be described.
- (19) The power supply apparatus 4 transforms electric power supplied from a component outside the projector 1A and supplies the transformed electric power to electronic parts that form the

projector **1A**.

(20) The control apparatus **5** includes a control circuit, for example, a CPU (central processing unit) and controls the operation of the projector **1A**. The control apparatus **5**, for example, controls the operation of turning on and off a light source **30**, which will be described below, and causes light modulators **343** to form images according to image information received from an external component.

(21) Furthermore, the control apparatus **5**, for example, outputs control signals to the cooling apparatus **6A** to control the operation of cooling targets cooled by the cooling apparatus **6A** and reduce noise leaking out of the exterior enclosure **2**.

(22) The power supply apparatus **4** and the control apparatus **5** are heat sources.

(23) Configuration of Exterior Enclosure

(24) The exterior enclosure **2** forms the exterior of the projector **1A** and accommodates the image projection apparatus **3**, the power supply apparatus **4**, the control apparatus **5**, and the cooling apparatus **6A**.

(25) The exterior enclosure **2** has a front surface section **21**, a rear surface section **22**, a left side surface section **23**, and a right side surface section **24**. Although not shown, the exterior enclosure **2** includes a top surface section to which one-side ends of the surface sections **21** to **24** are coupled and a bottom surface section to which the other-side ends of the surface sections **21** to **24** are coupled. The exterior enclosure **2** is formed, for example, in a substantially box-like shape.

(26) The right side surface section **24** has an intake port **241**. The intake port **241** introduces the air outside the exterior enclosure **2** into the exterior enclosure **2**. The intake port **241** may be provided with a filter that traps dust contained in the air passing through the intake port **241**.

(27) The front surface section **21** has a passage port **211** located substantially at the center of the front surface section **21**. Light projected from a projection optical apparatus **36**, which will be described later, passes through the passage port **211**.

(28) The front surface section **21** has a discharge port **212** located in the front surface section **21** in a position shifted toward the left side surface section **23**.

(29) Air having cooled the cooling targets provided in the exterior enclosure **2** is discharged out of the exterior enclosure **2** via the discharge port **212**.

(30) The intake port may be provided in a surface of the exterior enclosure **2** other than the right side surface section **24**, and the discharge port may be provided in a surface of the exterior enclosure **2** other than the front surface section **21**.

(31) In the following description, three directions perpendicular to one another are called directions +X, +Y, and +Z. It is assumed that the direction +X is the direction from the left side surface section **23** toward the right side surface section **24**, the direction +Y is the direction from the bottom surface section toward the top surface section, and the direction +Z is the direction from the rear surface section **22** toward the front surface section **21**.

(32) Although not illustrated, the direction opposite the direction +X is called a direction -X, the direction opposite the direction +Y is called a direction -Y, and the direction opposite the direction +Z is called a direction -Z. The direction +Z is the direction in which the projection optical apparatus **36**, which will be described later, projects light when viewed along the direction +Y.

(33) Configuration of Image Projection Apparatus

(34) The image projection apparatus **3** forms an image according to image information inputted from the cooling apparatus **5** and projects the formed image. The image projection apparatus **3** includes a light source apparatus **30**, a light homogenization section **31**, a color separation section **32**, a relay section **33**, an image formation section **34**, an optical part enclosure **35**, and the projection optical apparatus **36**.

(35) The light source **30** outputs light. Although not shown, the light source **30** can employ a configuration including a solid-state light source such as an LD (laser diode) and LED (light emitting diode), or a configuration including a discharge light source lamp such as an ultrahigh-

pressure mercury lamp. The light source **30** is a heat source.

(36) The light homogenization section **31** homogenizes the light outputted from the light source **30**. The homogenized light travels via the color separation section **32** and the relay section **33** and illuminates a modulation region of each of the light modulators **343**, which will be described later, of the image formation section **34**. The light homogenization section **31** includes two lens arrays **311** and **312**, a polarization conversion element **313**, and a superimposing lens **314**.

(37) The color separation section **32** separates the light incident from the light homogenization section **31** into red light, green light, and blue light. The color separation section **32** includes two dichroic mirrors **321** and **322** and a reflection mirror **323**, which reflects the separated blue light from the dichroic mirror **321**.

(38) The relay section **33** is provided in the optical path of the red light, which is longer than the optical paths of the other color light, and suppresses loss of the red light. The relay section **33** includes a light-incident-side lens **331**, relay lenses **333**, reflection mirrors **332** and **334**. In the present embodiment, the relay section **33** is provided in the optical path of the red light, but not necessarily. For example, the blue light may be configured to have an optical path longer than those of the other color light, and the relay section **33** may be provided in the optical path of the blue light.

(39) The image formation section **34** modulates the red light, the green light, and the blue light incident thereon and combines the modulated red light, green light, and blue light with one another to form an image. The image formation section **34** includes three field lenses **341**, three light-incident-side polarizers **342**, three light modulators **343**, three viewing angle compensators **344**, and three light-exiting-side polarizers **345**, which are provided in accordance with the incident color light, and one light combining section **346**.

(40) The light modulators **343** modulate the light outputted from the light source **30** in accordance with the image information. The light modulators **343** include a light modulator **343R** for the red light, a light modulator **343G** for the green light, and a light modulator **343B** for the blue light. In the present embodiment, the light modulators **343** are each formed of a transmissive liquid crystal panel, and the light-incident-side polarizers **342**, the light modulators **343**, and the light-exiting-side polarizers **345** form liquid crystal light valves. The liquid crystal light valves are heat sources that generate heat when light is incident thereon from the light source **30**. The image formation section **34**, which includes the liquid crystal light valves, is therefore a heat source.

(41) The light combining section **346** combines the blue light modulated by the light modulator **343B**, the green light modulated by the light modulator **343G**, and the red light modulated by the light modulator **343R** with one another to form an image. In the present embodiment, the light combining section **346** is formed of a cross dichroic prism, but not necessarily, and can instead be formed, for example, of a plurality of dichroic mirrors.

(42) The optical part enclosure **35** accommodates the sections **31** to **34** described above. An illumination optical axis Ax, which is the optical axis in the design stage, is set in the image projection apparatus **3**, and the optical part enclosure **35** holds the sections **31** to **34** in predetermined positions on the illumination optical axis Ax. The light source **30** and the projection optical apparatus **36** are disposed in predetermined positions on the illumination optical axis Ax.

(43) The projection optical apparatus **36** is a projection lens that enlarges and projects the image incident from the image formation section **34** on the projection receiving surface. That is, the projection optical apparatus **36** projects the light modulated by the light modulators **343B**, **343G**, and **343R**. The projection optical apparatus **36** is configured, for example, as a lens assembly formed of a plurality of lenses accommodated in a tubular lens barrel.

(44) Configuration of Cooling Apparatus

(45) The cooling apparatus **6A** has the function of cooling the cooling targets that form the projector **1A** and the function of reducing noise leaking out of the exterior enclosure **2**. The cooling apparatus **6A** includes a duct **61A**, a fan **62A**, a detection section **63A**, a loudspeaker **64A**, a storage

section **65A**, and a control section **66A**.

(46) Configuration of Duct

(47) The duct **61A** is a tubular element extending along the direction +Z and includes an introduction port **611** and an exit port **612**. The duct **61A** is configured to allow a cooling gas to flow through the interior of the duct **61A** from the introduction port **611** toward the exit port **612**. That is, the duct **61A** has an inner channel through which the cooling gas can flow. The duct **61A** causes a space in the vicinity of the light source **30**, which is a heat source, to communicate with the discharge port **212**, and guides the cooling gas having cooled the light source **30** to the exit port discharge. The inner surface of the duct **61A** may be provided with a sound-absorbing material.

(48) The introduction port **611** is provided at the -Z-direction-side end of the duct **61A**. The introduction port **611** is an opening through which the cooling gas is introduced into the duct **61A**.

(49) The exit port **612** is provided at the +Z-direction-side end of the duct **61A**. That is, the exit port **612** is provided on the side of the duct **61A** opposite from the introduction port **611**. The exit port **612** is an opening through which the cooling gas introduced into the duct **61A** is discharged out of the duct **61A**. The cooling gas discharged via the exit port **612** is discharged out of the exterior enclosure **2** via the discharge port **212**.

(50) Configuration of Fan

(51) The fan **62A** is provided in the duct **61A**. In detail, the fan **62A** is disposed in the duct **61A** in a position shifted from the loudspeaker **64A** toward the introduction port **611**. The fan **62A** sucks the cooling gas in the exterior enclosure **2** to cause the cooling gas to flow to the light source **30** and also introduces the cooling gas having cooled the light source **30** into the duct **61A** via the introduction port **611**. The fan **62A** then sends the cooling gas introduced into the duct **61A** in the direction +Z and discharges the cooling gas out of the exterior enclosure **2** via the exit port **612** and the discharge port **212**. In the present embodiment, the fan **62A** is an axial fan and may instead be a centrifugal fan.

(52) Configuration of Detection Section

(53) The detection section **63A** detects the state of the rotation of the fan **62A**. The detection section **63A** includes a rotational speed detection section **631** and a rotational position detection section **632**.

(54) The rotational speed detection section **631** detects the rotational speed of the fan **62A** per unit time. The rotational speed per unit time is hereinafter referred in some cases to as a fan rotational speed.

(55) The rotational position detection section **632** detects the rotational position of the fan **62A**. Specifically, the rotational position detection section **632** detects the position of a target vane with respect to the reference position, the target vane being one of a plurality of vanes (not shown) of the fan **62A**. In detail, the rotational position detection section **632** detects the angle of rotation of the target vane provided that the angle of the target vane is 0° when the target vane is located in the reference position.

(56) The detection section **63A** outputs to the control section **66A** the rotational speed of the fan **62A** per unit time detected by the rotational speed detection section **631** and the rotational position of the fan **62A** detected by the rotational position detection section **632**.

(57) Configuration of Loudspeaker

(58) The loudspeaker **64A** is provided in the duct **61A** and outputs a sound wave according to a drive signal inputted from the control section **66A**, which will be described later. Specifically, the loudspeaker **64A** is disposed between the discharge port **212** and the fan **62A** in the channel of the cooling gas and outputs an interference sound that is the sound wave according to the inputted drive signal. The interference sound emitted by the loudspeaker **64A** is hereafter referred to as a discharge-side interference sound.

(59) The discharge-side interference sound is a sound wave that interferes with discharge-side noise that propagates in the duct **61A** and leaks out of the exterior enclosure **2** via the discharge port **212**

to reduce the discharge-side noise. That is, the discharge-side interference sound is a sound wave opposite in terms of phase from the discharge-side noise, and when the discharge-side interference sound interferes with the discharge-side noise in the duct **61A**, the sound pressure of the discharge-side noise leaking out of the exterior enclosure **2** decreases. The discharge-side noise corresponds to first noise.

(60) The detail of the drive signal inputted to the loudspeaker **64A** will be described later.

(61) Configuration of Storage Section

(62) FIG. **2** is a diagrammatic view showing the content stored in the storage section **65A**.

(63) The storage section **65A** stores data necessary for the function of the cooling apparatus **6A**. For example, the storage section **65A** stores fan voltages to be applied to the fan **62A** to rotate the fan **62A** at predetermined fan rotational speeds.

(64) The storage section **65A** includes a characteristic data storage section **651** and a phase data storage section **652**, as shown in FIG. **2**.

(65) Configuration of Characteristic Data Storage Section

(66) FIG. **3** is a graph showing the result of frequency analysis of the discharge-side noise produced by the fan **62A** driven at a predetermined fan rotational speed. In detail, FIG. **3** is a graph showing the sound pressures of a plurality of frequency components contained in the discharge-side noise.

(67) When the fan rotational speed of fan **62A** is a predetermined rotational speed, the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212** contains discrete frequency noise, broadband noise, and in-apparatus environmental noise, as shown in FIG. **3**.

(68) The discrete frequency noise is noise resulting from the driven fan **62A**. Specifically, the discrete frequency noise is rotational sound having a spectral peak at a frequency proportional to the number of vanes of the fan **62A** and the fan rotational speed thereof. For example, in the graph shown in FIG. **3**, the sound having a peak at about 60 Hz and the sound having a peak at about 180 Hz are the discrete frequency noise.

(69) The broadband noise is turbulent noise, such as vortices, pressure fluctuation at a boundary layer, and separation of the boundary layer caused by the driven fan **62A**.

(70) The in-apparatus environmental noise is environmental noise in the apparatus in which the fan **62A** is installed, and is noise produced when the wind generated by the driven fan **62A** collides with obstacles in the apparatus. In the present embodiment, the in-apparatus environmental noise is environmental noise in the projector **1A**.

(71) The broadband noise and the in-apparatus environmental noise are each a sound that spans a relatively wide frequency band and has a peak lower than that of the discrete frequency noise.

(72) The discharge-side noise containing the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise changes in accordance with the fan rotational speed of the fan **62A**. Specifically, the frequency characteristics of the discharge-side noise changes in accordance with the fan rotational speed of the fan **62A**.

(73) In view of the fact described above, the characteristic data storage section **651** stores frequency characteristic data representing the frequency characteristics of the discharge-side noise in accordance with the fan rotational speed of the fan **62A**, as shown in FIG. **2**. The frequency characteristic data is data representing the features of a plurality of frequency components contained in the discharge-side noise.

(74) In detail, the frequency characteristic data representing the frequency characteristics of the discharge-side noise and stored in the characteristic data storage section **651** is data based on actually measured values of the discharge-side noise measured in the exterior enclosure **2** at a position in the vicinity of the discharge port **212** when the fan **62A** is driven at a plurality of fan rotational speeds. In detail, the frequency characteristic data on the frequency characteristics of the discharge-side noise is data representing the frequencies of the plurality of frequency components and the sound pressures of the plurality of frequency components obtained by frequency analysis of

the values actually measured when the fan **62A** is driven at the plurality of fan rotational speeds.

(75) For example, the characteristic data storage section **651** stores frequency characteristic data **A1** in correspondence with a case where the fan rotational speed of the fan **62A** is 1000 rpm and frequency characteristic data **A2** in correspondence with a case where the fan rotational speed of the fan **62A** is 2000 rpm. The characteristic data storage section **651** further stores frequency characteristic data **An** in correspondence with a case where the fan rotational speed of the fan **62A** is $1000 \times n$ (n is natural number greater than 2).

(76) As described above, the characteristic data storage section **651** stores the frequency characteristic data on the frequency characteristics of the discharge-side noise containing the discrete frequency noise produced by the driven fan **62A**, the broadband noise based on the cooling gas flow generated by the driven fan **62A**, and the in-apparatus environmental noise in accordance with the fan rotational speed of the fan **62A**.

(77) Configuration of Phase Data Storage Section

(78) The phase data storage section **652** stores phase data representing the phase of at least one of the plurality of frequency components contained in the discharge-side noise. In the present embodiment, the phase data storage section **652** stores phase data representing the phase of each of the plurality of frequency components contained in the discharge-side noise.

(79) It is noted that the discharge-side noise can be efficiently reduced by causing the interference sound opposite in terms of phase from the discharge-side noise to interfere with the discharge-side noise. On the other hand, the phases of the plurality of frequency components contained in the discharge-side noise are hardly aligned with each other.

(80) In view of the fact described above, the phase data storage section **652** stores the phases of the frequency components contained in the discharge-side noise and corresponding to the rotational position of the fan **62A** in accordance with the fan rotational speed of the fan **62A** in the present embodiment.

(81) For example, the phase data storage section **652** stores phase data **B1** in accordance with a case where the fan rotational speed of the fan **62A** is 1000 rpm and the rotational position of the fan **62A** is 0° , as shown in FIG. 2. The phase data storage section **652** further stores, for example, phase data **B2** in accordance with a case where the fan rotational speed of the fan is 1000 rpm and the rotational position of the fan **62A** is 10.

(82) The phase data storage section **652** further stores, for example, phase data **B359** in accordance with a case where the fan rotational speed of the fan is 1000 rpm and the rotational position of the fan **62A** is 359° . The phase data storage section **652** further stores phase data representing the phases of the frequency components in cases where the fan rotational speed is other speeds in accordance with the rotational position of the fan **62A**.

(83) As described above, the phase data storage section **652** stores the phase data representing the phases of the plurality of frequency components contained in the discharge-side noise in accordance with the fan rotational speed and the rotational position of the fan **62A**.

(84) Configuration of Control Section

(85) FIG. 4 is a block diagram showing the configuration of the control section **66A**.

(86) The control section **66A** controls the operation of the cooling apparatus **6A** based on control signals inputted from the control apparatus **5**. Specifically, the control section **66A** controls the operation of the fan **62A** and outputs a drive signal to the loudspeaker **64A** to cause the loudspeaker **64A** to emit the discharge-side interference sound. The control section **66A** includes a fan control section **661**, a rotational speed acquisition section **662**, a rotational position acquisition section **663**, a characteristic acquisition section **664**, a phase acquisition section **665**, a waveform generation section **666**, and a signal output section **667**, as shown in FIG. 4.

(87) The fan control section **661** drives the fan **62A** based on a control signal inputted from the control apparatus **5**. For example, when a control signal representing the fan rotational speed or an operation mode is inputted from the control apparatus **5**, the fan control section **661** applies a fan

voltage, out of the fan voltages stored in the storage section **65A**, corresponding to the inputted control signal to the fan **62A**. The fan **62A** is thus driven at a fan rotational speed specified by the control apparatus **5**.

(88) The rotational speed acquisition section **662** acquires the fan rotational speed of the fan **62A** detected by the rotational speed detection section **631**.

(89) The rotational position acquisition section **663** acquires the rotational position (angle of rotation) of the fan **62A** detected by the rotational position detection section **632**.

(90) The characteristic acquisition section **664** acquires from the characteristic data storage section **651** the frequency characteristic data representing the frequency characteristics of the discharge-side noise and corresponding to the fan rotational speed of the fan **62A** acquired by the rotational speed acquisition section **662**.

(91) The phase acquisition section **665** acquires from the phase data storage section **652** the phase data representing the phase of the discharge-side noise and corresponding to the fan rotational speed of the fan **62A** acquired by the rotational speed acquisition section **662** and the rotational position of the fan **62A** acquired by the rotational position acquisition section **663**.

(92) The waveform generation section **666** generates the waveform of the interference sound, which interferes with the discharge-side noise, based on the frequency characteristic data representing the frequency characteristics of the discharge-side noise and acquired by the characteristic acquisition section **664** and the phase data representing the phase of the discharge-side noise and acquired by the phase acquisition section **665**.

(93) For example, the waveform generation section **666** first generates the waveform of each of the frequency components indicated by the acquired frequency characteristic data on the frequency characteristics of the discharge-side noise.

(94) The waveform generation section **666** then adjusts the phase of the generated waveform of each of the frequency components based on the acquired phase data on the phase of the discharge-side noise.

(95) The waveform generation section **666** then combines the waveforms of the frequency components having the adjusted phases with one another to generate the waveform of the discharge-side noise.

(96) The waveform generation section **666** inverts the generated waveform of the discharge-side noise to generate the waveform of the discharge-side interference sound. That is, the waveform generation section **666** generates the waveform of the discharge-side interference sound to be emitted from the loudspeaker **64A**.

(97) The signal output section **667** generates a drive signal according to the waveform of the discharge-side interference sound generated by the waveform generation section **666** and outputs the generated drive signal to the loudspeaker **64A** to cause the loudspeaker **64A** to emit the discharge-side interference sound. The signal output section **667** may adjust the timing at which the drive signal is outputted to the loudspeaker **64A** in such a way that the discharge-side interference sound emitted from the loudspeaker **64A** appropriately interferes with the discharge-side noise propagating through the duct **61A**.

(98) When the discharge-side interference sound emitted from the loudspeaker **64A** interferes with the discharge-side noise as described above, the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212** decreases. In this process, the discharge-side interference sound contains not only the component that interferes with the discrete frequency noise resulting from the driven fan **62A**, but also components that interfere with the broadband noise resulting from the flow generated by the driven fan **62A** and the in-apparatus environmental noise, whereby the discharge-side noise leaking out of the projector **1A** effectively decreases.

(99) Effects of First Embodiment

(100) The projector **1A** according to the present embodiment described above provides the effects below.

(101) The projector **1A** includes the exterior enclosure **2**, the light source **30**, the fan **62A**, the loudspeaker **64A**, the characteristic data storage section **651**, and the control section **66A**. The exterior enclosure **2** has the intake port **241** and the discharge port **212**. The light source **30** is a heat source disposed in the exterior enclosure **2**. The fan **62A** causes the cooling gas to flow to the light source **30**. The loudspeaker **64A** is disposed between the discharge port **212** and the fan **62A** in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker **64A**.

(102) The characteristic data storage section **651** stores the frequency characteristic data on the frequency characteristics of the discharge-side noise containing the discrete frequency noise produced by the driven fan **62A**, the broadband noise based on the cooling gas flow generated by the driven fan **62A**, and the in-apparatus environmental noise in accordance with the rotational speed of the fan **62A** per unit time. In the present embodiment, the discharge-side noise corresponds to the first noise. The control section **66A** generates a drive signal to be outputted to the loudspeaker **64A**.

(103) The control section **66A** includes the characteristic acquisition section **664**, the waveform generation section **666**, and the signal output section **667**. The characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the rotational speed of the fan **62A** per unit time from the characteristic data storage section **651**. The waveform generation section **666** generates the waveform of the discharge-side interference sound (interference sound), which interferes with the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212**, based on the frequency characteristic data representing the frequency characteristics of the discharge-side noise and acquired by the characteristic acquisition section **664**. The signal output section **667** outputs a drive signal based on the waveform generated by the waveform generation section **666** to the loudspeaker **64A**.

(104) According to the configuration described above, in which the characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the fan rotational speed of the fan **62A** from the characteristic data storage section **651**, the control section **66A** can acquire the frequency characteristics of the discharge-side noise leaking out of the exterior enclosure **2**. The waveform generation section **666** generates the waveform of the discharge-side interference sound (interference sound), which interferes with the discharge-side noise, and the signal output section **667** outputs a drive signal based on the generated waveform of the discharge-side interference sound to the loudspeaker **64A**.

(105) The discharge-side interference sound can thus be emitted from the loudspeaker **64A** with no need for a microphone that detects the discharge-side noise. The configuration of the projector **1A** can therefore be simplified. In addition, since the discharge-side noise includes the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of reducible noise can be expanded.

(106) In other words, the cooling apparatus **6A** includes the fan **62A**, the loudspeaker **64A**, the characteristic data storage section **651**, and the control section **66A**. The fan **62A** causes the cooling gas to flow to the light source **30**, which is a heat source. The loudspeaker **64A** outputs a sound wave according to a drive signal inputted thereto. The characteristic data storage section **651** stores the frequency characteristic data on the frequency characteristics of the discharge-side noise containing the discrete frequency noise produced by the driven fan **62A**, the broadband noise based on the cooling gas flow generated by the driven fan **62A**, and the environmental noise in accordance with the fan rotational speed of the fan **62A**. The control section **66A** generates a drive signal to be outputted to the loudspeaker **64A**.

(107) The control section **66A** includes the characteristic acquisition section **664**, the waveform generation section **666**, and the signal output section **667**. The characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the fan rotational speed of the fan **62A** from the characteristic data storage section **651**. The waveform generation section **666** generates

the waveform of discharge-side interference sound (interference sound), which reduces the discharge-side noise, based on the frequency characteristic data acquired by the characteristic acquisition section **664**. The signal output section **667** outputs a drive signal based on the waveform of the discharge-side interference sound generated by the waveform generation section **666** to the loudspeaker **64A**.

(108) According to the configuration described above, the discharge-side interference sound (interference sound), which interferes with the discharge-side noise, can be emitted from the loudspeaker **64A** with no need for a microphone that detects the discharge-side noise, as described above, whereby the configuration of the projector **1A** can be simplified, and the range of reducible noise can be expanded.

(109) The cooling apparatus **6A** of the projector **1A** includes the rotational speed detection section **631**, which detects the fan rotational speed of the fan **62A**. The characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the fan rotational speed of the fan **62A** detected by the rotational speed detection section **631**.

(110) According to the configuration described above, the characteristic acquisition section **664** can acquire the frequency characteristic data corresponding to the actual fan rotational speed of the fan **62A**, whereby the waveform of the discharge-side noise can be reproduced more accurately, and in turn the discharge-side interference sound, which effectively interferes with the discharge-side noise, can be emitted from the loudspeaker **64A**. The discharge-side noise emitted out of the projector **1A** can therefore be effectively reduced.

(111) The cooling apparatus **6A** of the projector **1A** includes the rotational position detection section **632** and the phase data storage section **652**. The rotational position detection section **632** detects the rotational position of the fan **62A**. The phase data storage section **652** stores phase data in accordance with the fan rotational speed of the fan **62A**, the phase data representing the phases of a plurality of frequency components contained in the discharge-side noise and according to the rotational position of the fan **62A**. The control section **66A** includes the phase acquisition section **665**, which acquires the phase data corresponding to the rotational position of the fan **62A** detected by the rotational position detection section **632** from the phase data storage section **652**. The waveform generation section **666** generates the waveform of the discharge-side interference sound (interference sound) based on the frequency characteristic data acquired by the characteristic acquisition section **664** and the phase data acquired by the phase acquisition section **665**.

(112) According to the configuration described above, the phase acquisition section **665** acquires the phase data according to the rotational position of the fan **62A** detected by the rotational position detection section **632**, and the waveform generation section **666** generates the waveform of the discharge-side interference sound (interference sound) based on the frequency characteristic data acquired by the characteristic acquisition section **664** and the phase data acquired by the phase acquisition section **665**. The interference sound that can effectively reduce the discharge-side noise can therefore be emitted from the loudspeaker **64A** to effectively reduce the discharge-side noise.

(113) In the cooling apparatus **6A** of the projector **1A**, the frequency characteristic data is data representing the features of at least one of the plurality of frequency components contained in the discharge-side noise.

(114) According to the configuration described above, based on the features of the frequency components indicated by the frequency characteristic data, the discharge-side interference sound (interference sound), which can interfere with at least one frequency component contained in the discharge-side noise to effectively reduce the at least one frequency component, can be emitted from the loudspeaker **64A**. The discharge-side noise can therefore be effectively reduced.

(115) The control method executed by the control section **66A** is executed in the projector **1A**, which is an electronic instrument including the fan **62A**, which causes the cooling gas to flow to the light source **30**, which is a heat source, and the loudspeaker **64A**, which outputs a sound wave according to a drive signal inputted thereto. In the control method, the frequency characteristic data

on the frequency characteristics of the discharge-side noise containing the discrete frequency noise produced by the driven fan **62A**, the broadband noise based on the cooling gas flow generated by the driven fan **62A**, and the in-apparatus environmental noise is acquired in accordance with the rotational speed of the fan **62A** per unit time.

(116) The waveform of the discharge-side interference sound (interference sound), which interferes with the discharge-side noise leaking out of the projector **1A**, is then generated, based on the acquired frequency characteristic data. A drive signal based on the generated waveform of the interference sound is then outputted to the loudspeaker **64A**.

(117) According to the configuration described above, the same effects as those provided by the projector **1A** or the cooling apparatus **6A** described above can be provided.

Second Embodiment

(118) A second embodiment of the present disclosure will next be described.

(119) The projector according to the present embodiment has the same configuration as that of the projector **1A** according to the first embodiment. In the projector **1A**, the loudspeaker **64A** is provided between the fan **62A** and the discharge port **212**, via which the cooling gas having cooled the light source **30**, which is a heat source disposed in the exterior enclosure **2**, is discharged.

(120) In contrast, in the projector according to the present embodiment, the loudspeaker is provided between the fan and the intake port **241**, via which the cooling gas is taken into the exterior enclosure **2**. The projector according to the present embodiment differs in this regard from the projector **1A** according to the first embodiment. In the following description, portions that are the same or substantially the same as the portions having been already described have the same reference characters and will not be describe.

(121) Configuration of Projector

(122) FIG. 5 is a diagrammatic view showing the configuration of a projector **1B** according to the present embodiment. That is, FIG. 5 shows the arrangement of a cooling apparatus **6B** in the exterior enclosure **2**.

(123) The projector **1B** according to the present embodiment has the same configuration and function as those of the projector **1A** according to the first embodiment except that the cooling apparatus **6A** according to the first embodiment is replaced with the cooling apparatus **6B** shown in FIG. 5.

(124) Configuration of Cooling Apparatus

(125) The cooling apparatus **6B** is provided in association with the intake port **241** and has the function of causing the cooling gas introduced into the exterior enclosure **2** via the intake port **241** to flow to the heat sources to cool the heat sources and the function of reducing intake-side noise leaking out of the exterior enclosure **2** via the intake port **241**. In the present embodiment, the intake-side noise corresponds to the first noise.

(126) The cooling apparatus **6B** includes a duct **61B**, a fan **62B**, a detection section **63B**, a loudspeaker **64B**, a storage section **65B**, and a control section **66B**.

(127) Configuration of Duct

(128) The duct **61B** is a tubular element extending along the direction +Z and includes an introduction port **613** and an exit port **614**. The duct **61B** is configured to allow the cooling gas to flow through the interior of the duct **61B** from the introduction port **613** toward the exit port **614**.

(129) That is, the duct **61B** has an inner channel through which the cooling gas can flow. The duct **61B** is provided in association with the intake port **241** and guides the cooling gas introduced into the exterior enclosure **2** via the intake port **241** to the image formation section **34**. The inner surface of the duct **61B** may be provided with a sound-absorbing material.

(130) The introduction port **613** is provided on a side of the duct **61B**, the side facing the right side surface section **24**. That is, the introduction port **613** is provided in a portion of the duct **61B**, the portion corresponding to the intake port **241**. The introduction port **613** is an opening via which the air outside the exterior enclosure **2** is introduced as the cooling gas via the intake port **241** into the

duct **61B**.

(131) The exit port **614** is provided on at an end of the duct **61B**, the end opposite from the introduction port **613**. That is, the exit port **614** is provided at an end of the duct **61B**, the end facing the direction $-Z$. The exit port **614** is an opening via which the cooling gas having flowed through the duct **61B** is caused to exit out of the duct **61B**.

(132) That is, the exit port **614** opens toward the image formation section **34** and guides the cooling gas having flowed through the duct **61B** to the image formation section **34**.

(133) Configuration of Fan

(134) The fan **62B** is provided in the duct **61B**. In detail, the fan **62B** is disposed in the duct **61B** in a position shifted from the loudspeaker **64B** toward the exit port **614**. The fan **62B** sucks the air outside the exterior enclosure **2** as the cooling gas into the duct **61B** and causes the sucked cooling gas to flow to the image formation section **34**, which is a heat source. In the present embodiment, the fan **62B** is an axial fan and may instead be a centrifugal fan.

(135) Configuration of Detection Section

(136) The detection section **63B** includes the rotational speed detection section **631**, which detects the rotational speed of the fan **62B** per unit time, and the rotational position detection section **632**, which detects the rotational position of the fan **62B**, as the detection section **63A** in the first embodiment does.

(137) That is, the rotational speed detection section **631** of the detection section **63B** detects the fan rotational speed of the fan **62B**. The detection section **63B** outputs to the control section **66B** the rotational speed of the fan **62B** detected by the rotational speed detection section **631** and the rotational position of the fan **62B** detected by the rotational position detection section **632**.

(138) Configuration of Loudspeaker

(139) The loudspeaker **64B** is provided in the duct **61B** and emits a sound wave according to a drive signal inputted from the control section **66B**. Specifically, the loudspeaker **64B** is disposed between the intake port **241** and the fan **62B** in the channel of the cooling gas and emits an interference sound according to the inputted drive signal. The interference sound emitted by the loudspeaker **64B** is hereafter referred to as an intake-side interference sound.

(140) The intake-side interference sound is a sound wave that interferes with the intake-side noise that propagates in the duct **61B** and leaks out of the exterior enclosure **2** via the intake port **241** to reduce the intake-side noise. In detail, the intake-side interference sound is a sound wave opposite in terms of phase from the intake-side noise. The intake-side interference sound emitted from the loudspeaker **64B** interferes with the intake-side noise in the duct **61B** to reduce the sound pressure of the intake-side noise emitted out of the projector **1B**. The detail of the drive signal inputted to the loudspeaker **64B** will be described later.

(141) Configuration of Storage Section

(142) The storage section **65B** stores data necessary for the function of the cooling apparatus **6B**. For example, the storage section **65B** stores a fan voltage to be applied to the fan **62B** to rotate the fan **62B** at a predetermined fan rotational speed, as the storage section **65A** does. The storage section **65B** includes the characteristic data storage section **651** and the phase data storage section **652**, as the storage section **65A** does.

(143) The characteristic data storage section **651** and the phase data storage section **652** of the storage section **65B** will be described below.

(144) The characteristic data storage section **651** stores frequency characteristic data on the frequency characteristics of the intake-side noise, which contains the discrete frequency noise produced by the driven fan **62B**, the broadband noise based on the cooling gas flow generated by the driven fan **62B**, and the in-apparatus environmental noise, in accordance with the fan rotational speed of the fan **62B**. In the present embodiment, the frequency characteristic data stored in the characteristic data storage section **651** represents the features of a plurality of frequency components based on the result of frequency analysis of actually measured values of the intake-side

noise measured in the exterior enclosure **2** in the vicinity of the intake port **241**. Specifically, the frequency characteristic data contains the frequencies of the plurality of frequency components contained in the intake-side noise and the sound pressures of the plurality of frequency components.

(145) The phase data storage section **652** stores phase data which represents the phases of the plurality of frequency components contained in the intake-side noise and corresponds to the rotational position of the fan **62B**, in accordance with the fan rotational speed of the fan **62B**. Specifically, the phase data storage section **652** stores the phases of the plurality of frequency components contained in the intake-side noise for each rotational position of the fan **62B**, which is incremented by 1° , in accordance with the fan rotational speed of the fan **62B**, as the phase data storage section **652** of the storage section **65A** does.

(146) Configuration of Control Section

(147) The control section **66B** controls the operation of the cooling apparatus **6B** based on the control signals inputted from the control apparatus **5**. Specifically, the control section **66B** controls the operation of the fan **62B** and causes the loudspeaker **64B** to emit the intake-side interference sound. The control section **66B** includes, although not shown, the fan control section **661**, the rotational speed acquisition section **662**, the rotational position acquisition section **663**, the characteristic acquisition section **664**, the phase acquisition section **665**, the waveform generation section **666**, and the signal output section **667**, as the control section **66A** does.

(148) The fan control section **661**, the rotational speed acquisition section **662**, the rotational position acquisition section **663**, the characteristic acquisition section **664**, the phase acquisition section **665**, the waveform generation section **666**, and the signal output section **667** of the control section **66B** will be described below.

(149) The fan control section **661** drives the fan **62B** based on a control signal inputted from the control apparatus **5**.

(150) The rotational speed acquisition section **662** acquires the detected fan rotational speed of the fan **62B**.

(151) The rotational position acquisition section **663** acquires the rotational position (angle of rotation) of the fan **62B** detected by the rotational position detection section **632**.

(152) The characteristic acquisition section **664** acquires the frequency characteristic data representing the frequency characteristics of the intake-side noise and corresponding to the acquired fan rotational speed of the fan **62B** from the characteristic data storage section **651**.

(153) The phase acquisition section **665** acquires the phase data representing the phase of the intake-side noise and corresponding to the acquired fan rotational speed and rotational position of the fan **62B** from the phase data storage section **652**.

(154) The waveform generation section **666** generates the waveform of the intake-side interference sound, which interferes with the intake-side noise, based on the acquired frequency characteristic data on the frequency characteristics of the intake-side noise and the acquired phase data on the phase of the intake-side noise.

(155) The signal output section **667** generates a drive signal according to the generated waveform of the intake-side interference sound and outputs the drive signal to the loudspeaker **64B** to cause the loudspeaker **64B** to emit the intake-side interference sound. The signal output section **667** may adjust the timing at which the drive signal is outputted to the loudspeaker **64B** in such a way that the intake-side interference sound emitted by the loudspeaker **64B** appropriately interferes with the intake-side noise propagating through the duct **61B**, as described above.

(156) When the intake-side interference sound emitted from the loudspeaker **64B** interferes with the intake-side noise as described above, the intake-side noise leaking out of the exterior enclosure **2** via the intake port **241** decreases. In this process, the intake-side interference sound contains not only the component that interferes with the discrete frequency noise resulting from the driven fan **62B**, but also component that interferes with the broadband noise resulting from the flow generated

by the driven fan **62B**, whereby the intake-side noise leaking out of the projector **1B** effectively decreases.

(157) Effects of Second Embodiment

(158) The projector **1B** according to the present embodiment described above provides the same effects as those provided by the projector **1A** according to the first embodiment.

(159) For example, the projector **1B** includes the exterior enclosure **2**, the image formation section **34**, the fan **62B**, the loudspeaker **64B**, the characteristic data storage section **651**, and the control section **66B**. The exterior enclosure **2** has the intake port **241** and the discharge port **212**. The image formation section **34** is a heat source disposed in the exterior enclosure **2**. The fan **62B** causes the cooling gas to flow to the image formation section **34**. The loudspeaker **64B** is disposed between the intake port **241** and the fan **62B** in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker **64B**. The characteristic data storage section **651** of the storage section **65B** stores the frequency characteristic data on the frequency characteristics of the intake-side noise, which contains the discrete frequency noise produced by the driven fan **62B**, the broadband noise based on the cooling gas flow generated by the driven fan **62B**, and the in-apparatus environmental noise, in accordance with the rotational speed of the fan **62B** per unit time. In the present embodiment, the intake-side noise corresponds to the first noise. The control section **66B** generates a drive signal to be outputted to the loudspeaker **64B**.

(160) The control section **66B** includes the characteristic acquisition section **664**, the waveform generation section **666**, and the signal output section **667**. The characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the rotational speed of the fan **62B** per unit time from the characteristic data storage section **651**. The waveform generation section **666** generates the waveform of intake-side interference sound (interference sound), which interferes with the intake-side noise leaking out of the exterior enclosure **2** via the intake port **241**, based on the frequency characteristic data representing the frequency characteristics of the intake-side noise and acquired by the characteristic acquisition section **664**. The signal output section **667** outputs a drive signal based on the waveform generated by the waveform generation section **666** to the loudspeaker **64B**.

(161) In other words, the cooling apparatus **6B** includes the fan **62B**, the loudspeaker **64B**, the characteristic data storage section **651**, and the control section **66B**. The fan **62B** causes the cooling gas to flow to the image formation section **34**, which is a heat source. The loudspeaker **64B** outputs a sound wave according to the inputted drive signal. The characteristic data storage section **651** stores the frequency characteristic data representing the frequency characteristics of the intake-side noise containing the discrete frequency noise produced by the driven fan **62B**, the broadband noise based on the cooling gas flow generated by the driven fan **62B**, and the environmental noise in accordance with the fan rotational speed of the fan **62B**. The control section **66B** generates a drive signal to be outputted to the loudspeaker **64B**.

(162) The control section **66B** includes the characteristic acquisition section **664**, the waveform generation section **666**, and the signal output section **667**. The characteristic acquisition section **664** acquires the frequency characteristic data corresponding to the fan rotational speed of the fan **62B** from the characteristic data storage section **651**. The waveform generation section **666** generates the waveform of the intake-side interference sound (interference sound), which reduces the intake-side noise, based on the frequency characteristic data acquired by the characteristic acquisition section **664**. The signal output section **667** outputs a drive signal based on the waveform of the intake-side interference sound generated by the waveform generation section **666** to the loudspeaker **64B**.

(163) According to the configuration described above, the same effects as those provided by the projector **1B** and the cooling apparatus **6B** according to the first embodiment can be provided.

Third Embodiment

(164) A third embodiment of the present disclosure will next be described.

(165) The projector according to the present embodiment has the same configuration as those of the projectors **1A** and **1B** according to the first and second embodiments but differs therefrom in that the cooling apparatus includes a plurality of fans and a plurality of loudspeakers. In the following description, portions that are the same or substantially the same as the portions having been already described have the same reference characters and will not be described.

(166) Configuration of Projector

(167) FIG. **6** is a diagrammatic view showing the configuration of a projector **1C** according to the present embodiment. In other words, FIG. **6** is a diagrammatic view showing the arrangement of a cooling apparatus **7C** in the exterior enclosure **2**.

(168) The projector **1C** according to the present embodiment has the same configuration and function as those of the projector **1A** according to the first embodiment except that the cooling apparatus **6A** according to the first embodiment is replaced with the cooling apparatus **7C** shown in FIG. **6**.

(169) Configuration of Cooling Apparatus

(170) The cooling apparatus **7C** has the function of cooling the heat sources that form the projector **1C** and the function of reducing noise leaking out of the projector **1C**. In the present embodiment, the light source **30**, the image formation section **34**, the power supply apparatus **4**, and the control apparatus **5** are heat sources to be cooled by the cooling apparatus **7C**. As shown in FIG. **6**, the cooling apparatus **7C** includes a first cooling section **71**, a second cooling section **72**, a third cooling section **73**, and a fourth cooling section **74**, as well as a storage section **75** and a control section **76C**, which are not shown in FIG. **6**.

(171) Configuration of First Cooling Section

(172) The first cooling section **71** cools the light source **30** by sucking the cooling gas in the exterior enclosure **2** and causing the cooling gas to flow to the light source **30**, which is a cooling target, as the cooling apparatus **6A** does. The first cooling section **71** emits the discharge-side interference sound, which interferes with the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212**, to reduce the discharge-side noise under control by the control section **76C**.

(173) The first cooling section **71** includes the duct **61A** provided in association with the discharge port **212**, a first fan **711**, a first detection section **712**, and a first loudspeaker **713**.

(174) The first fan **711** is disposed in the duct **61A** in a position shifted from the first loudspeaker **713** toward the introduction port **611**, as the fan **62A** is. The first fan **711** sucks the cooling gas in the exterior enclosure **2**, causes the cooling gas to flow to the light source **30**, and introduces the cooling gas having cooled the light source **30** into the duct **61A** via the introduction port **611**. The first fan **711** then sends the cooling gas introduced into the duct **61A** in the direction +Z to discharge the cooling gas out of the exterior enclosure **2** via the exit port **612** and the discharge port **212**. In the present embodiment, the first fan **711** is an axial fan and may instead be a centrifugal fan.

(175) The first detection section **712** includes the rotational speed detection section **631**, which detects the rotational speed (fan rotational speed) of the first fan **711** per unit time, and the rotational position detection section **632**, which detects the rotational position of the first fan **711**, as the detection section **63A** according to the first embodiment does. The first detection section **712** outputs the detected fan rotational speed and rotational position of the first fan **711** to the control section **76C**.

(176) The first loudspeaker **713** is provided in the duct **61A** and outputs the discharge-side interference sound according to a drive signal inputted from the control section **76C**, as the loudspeaker **64A** is. That is, the first loudspeaker **713** is disposed between the discharge port **212** and the first fan **711** in the channel of the cooling gas and outputs the discharge-side interference sound, which is the sound wave according to the drive signal inputted from the control section **76C**. The discharge-side interference sound is a sound wave that interferes with the discharge-side noise

propagating in the duct **61A** and leaking out of the exterior enclosure **2** via the discharge port **212** to reduce the discharge-side noise, as the discharge-side interference sound in the first embodiment is.

(177) Configuration of Second Cooling Section

(178) The second cooling apparatus **72** causes the cooling gas introduced into the exterior enclosure **2** via the intake port **241** to flow to the image formation section **34** to cool the image formation section **34**, as the cooling apparatus **6B** does. The second cooling section **72** emits the intake-side interference sound, which interferes with the intake-side noise leaking out of the exterior enclosure **2** via the intake port **241**, to reduce the intake-side noise under control by the control section **76C**.

(179) The second cooling section **72** includes the duct **61B** provided in association with the intake port **241**, a second fan **721**, a second detection section **722**, and a second loudspeaker **723**.

(180) The second fan **721** is provided in the duct **61B**, as the fan **62B** is. In detail, the second fan **721** is disposed in the duct **61B** in a position shifted from the second loudspeaker **723** toward the exit port **614**. The second fan **721** sucks the air outside the exterior enclosure **2** as the cooling gas into the duct **61B** and causes the sucked cooling gas to flow to the image formation section **34**. In the present embodiment, the second fan **721** is an axial fan and may instead be a centrifugal fan.

(181) The second detection section **722** includes the rotational speed detection section **631**, which detects the fan rotational speed of the second fan **721**, and the rotational position detection section **632**, which detects the rotational position of the second fan **721**, as the detection section **63B** in the second embodiment does. The second detection section **722** outputs the detected fan rotational speed and rotational position of the second fan **721** to the control section **76C**.

(182) The second loudspeaker **723** is provided in the duct **61B** and emits the intake-side interference sound, which is a sound wave according to a drive signal inputted from the control section **76C**, as the loudspeaker **64B** is. That is, the second loudspeaker **723** is disposed between the intake port **241** and the second fan **721** in the channel of the cooling gas and emits the intake-side interference sound. The intake-side interference sound is a sound wave that interferes with the intake-side noise propagating in the duct **61B** and emitted out of the exterior enclosure **2** via the intake port **241** to reduce the intake-side noise.

(183) Configuration of Third Cooling Section

(184) The third cooling section **73** causes the cooling gas in the exterior enclosure **2** to flow to the power supply apparatus **4** to cool the power supply apparatus **4**. The third cooling section **73** includes a third fan **731** and a third detection section **732**.

(185) The third fan **731** is disposed in the vicinity of the power supply apparatus **4** in the exterior enclosure **2**. The third fan **731** causes the cooling gas in the exterior enclosure **2** to flow to the power supply apparatus **4** to cool the power supply apparatus **4** by sucking the cooling gas. In the present embodiment, the third fan **731** is a centrifugal fan and may instead be an axial fan.

(186) The third detection section **732** includes the rotational speed detection section **631**, which detects the fan rotational speed of the third fan **731**, and the rotational position detection section **632**, which detects the rotational position of the third fan **731**. The third detection section **732** outputs the detected fan rotational speed and rotational position of the third fan **731** to the control section **76C**.

(187) Configuration of Fourth Cooling Section

(188) The fourth cooling section **74** causes the cooling gas in the exterior enclosure **2** to flow to the control apparatus **5** to cool the control apparatus **5**. The fourth cooling section **74** includes a fourth fan **741** and a fourth detection section **742**.

(189) The fourth fan **741** is disposed in the vicinity of the control apparatus **5** in the exterior enclosure **2**. The fourth fan **741** sucks the cooling gas in the exterior enclosure **2** and causes the cooling gas to flow to the control apparatus **5** by sending the cooling gas to the control apparatus **5** to cool the control apparatus **5**. In the present embodiment, the fourth fan **741** is a centrifugal fan

and may instead be an axial fan.

(190) The fourth detection section **742** includes the rotational speed detection section **631**, which detects the fan rotational speed of the fourth fan **741**, and the rotational position detection section **632**, which detects the rotational position of the fourth fan **741**. The fourth detection section **742** outputs the detected fan rotational speed and rotational position of the fourth fan **741** to the control section **76C**.

(191) Configuration of Storage Section

(192) FIG. 7 is a block diagram showing the configurations of the storage section **75** and the control section **76C**.

(193) The storage section **75** stores data necessary for the function of the cooling apparatus **7C**. The storage section **75** stores fan voltages to be applied to the first fan **711**, the second fan **721**, the third fan **731**, and the fourth fan **741**. The storage section **75** further includes a characteristic data storage section **751** and a phase data storage section **754**, as shown in FIG. 7.

(194) Configuration of Characteristic Data Storage Section

(195) FIG. 8 is a diagrammatic view showing the content stored in the characteristic data storage section **751**.

(196) The characteristic data storage section **751** includes a discharge-side characteristic data storage section **752** and an intake-side characteristic data storage section **753**, as shown in FIG. 7.

(197) The discharge-side characteristic data storage section **752** stores the frequency characteristic data on the frequency characteristics of discharge-side noise. Specifically, the discharge-side characteristic data storage section **752** stores the frequency characteristic data on the noise for each of the fans disposed in the exterior enclosure **2**. In the present embodiment, the discharge-side characteristic data storage section **752** includes a first characteristic data storage section **7521**, a second characteristic data storage section **7522**, a third characteristic data storage section **7523**, and a fourth characteristic data storage section **7524**, as shown in FIG. 8.

(198) The first characteristic data storage section **7521** stores the frequency characteristic data on the frequency characteristics of first discharge-side noise resulting from the first fan **711**.

Specifically, the first characteristic data storage section **7521** stores the frequency characteristic data on the frequency characteristics of the first discharge-side noise, which contains the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise, in accordance with the rotational speed of the first fan **711** per unit time. That is, the frequency characteristic data on the frequency characteristics of the first discharge-side noise is data based on the result of frequency analysis of actually measured values of the first discharge-side noise measured in the vicinity of the discharge port **212** in the external enclosure **2** when only the first fan **711** is operated at each fan rotational speed.

(199) For example, the first characteristic data storage section **7521** stores frequency characteristic data **C1** corresponding to a case where the fan rotational speed of the first fan **711** is 1000 (rpm), frequency characteristic data **C2** corresponding to a case where the fan rotational speed of the first fan **711** is 2000 (rpm), and frequency characteristic data **Cn** corresponding to a case where the fan rotational speed of the first fan **711** is $1000 \times n$ (rpm) (n is natural number greater than 2), as the characteristic data storage section **651** according to the first embodiment does.

(200) The first discharge-side noise corresponds to the first noise in the discharge-side noise.

(201) The second characteristic data storage section **7522** stores the frequency characteristic data on the frequency characteristics of second discharge-side noise resulting from the second fan **721**. The second discharge-side noise corresponds to second noise in the discharge-side noise. The third characteristic data storage section **7523** stores the frequency characteristic data on the frequency characteristics of third discharge-side noise resulting from the third fan **731**, and the fourth characteristic data storage section **7524** stores the frequency characteristic data on the frequency characteristics of fourth discharge-side noise resulting from the fourth fan **741**. The frequency

characteristic data on the frequency characteristics of the second discharge-side noise, the frequency characteristic data on the frequency characteristics of third discharge-side noise, and the frequency characteristic data on the frequency characteristics of fourth discharge-side noise are similar to the frequency characteristic data on frequency characteristics of the first discharge-side noise.

(202) That is, the frequency characteristic data on the frequency characteristics of each of the second to fourth discharge-side noise include values actually measured when only the corresponding fan is driven at the fan rotational speed thereof, that is, the features of a plurality of frequency components based on the result of frequency analysis of the actually measured values of the noise measured in the vicinity of the discharge port **212** in the exterior enclosure **2**. In the present embodiment, the frequency characteristic data include the frequency and the sound pressure of each of the frequency components.

(203) The intake-side characteristic data storage section **753** stores the frequency characteristic data on the frequency characteristics of the intake-side noise. Specifically, the intake-side characteristic data storage section **753** stores the frequency characteristic data on the frequency characteristics of the noise for each of the fans disposed in the exterior enclosure **2**. In the present embodiment, the intake-side characteristic data storage section **753** includes a first characteristic data storage section **7531**, a second characteristic data storage section **7532**, a third characteristic data storage section **7533**, and a fourth characteristic data storage section **7534**.

(204) The first characteristic data storage section **7531** stores the frequency characteristic data on the frequency characteristics of first intake-side noise resulting from the first fan **711**. Specifically, the first characteristic data storage section **7531** stores the frequency characteristic data on the frequency characteristics of the first intake-side noise, which contains the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise, in accordance with the rotational speed of the first fan **711** per unit time. That is, the frequency characteristic data on the frequency characteristics of the first intake-side noise is data based on the result of frequency analysis of actually measured values of the first intake-side noise measured in the vicinity of the intake port **241** in the external enclosure **2** when only the first fan **711** is operated at each fan rotational speed.

(205) For example, the first characteristic data storage section **7531** stores frequency characteristic data **D1** corresponding to a case where the fan rotational speed of the first fan **711** is 1000 (rpm), frequency characteristic data **D2** corresponding to a case where the fan rotational speed of the first fan **711** is 2000 (rpm), and frequency characteristic data **Dn** corresponding to a case where the fan rotational speed of the first fan **711** is $1000 \times n$ (rpm) (n is natural number greater than 2), as the characteristic data storage section **651** according to the second embodiment does.

(206) The second characteristic data storage section **7532** stores the frequency characteristic data on the frequency characteristics of second intake-side noise resulting from the second fan **721**. The second intake-side noise corresponds to second noise in the intake-side noise. The third characteristic data storage section **7533** stores the frequency characteristic data on the frequency characteristics of third intake-side noise resulting from the third fan **731**, and the fourth characteristic data storage section **7534** stores the frequency characteristic data on the frequency characteristics of fourth intake-side noise resulting from the fourth fan **741**. The frequency characteristic data on the frequency characteristics of the second intake-side noise, the frequency characteristic data on the frequency characteristics of third intake-side noise, and the frequency characteristic data on the frequency characteristics of fourth intake-side noise are similar to the frequency characteristic data on the frequency characteristics of the first discharge-side noise.

(207) That is, the frequency characteristic data on the frequency characteristics of each of the second to fourth intake-side noise include values actually measured when only the corresponding fan is driven at the fan rotational speed thereof, that is, the features of the plurality of frequency

components based on the result of frequency analysis of the actually measured values of the noise measured in the vicinity of the discharge port **212** in the exterior enclosure **2**. In the present embodiment, the frequency characteristic data include the frequency and the sound pressure of each of the frequency components.

(208) Configuration of Phase Data Storage Section

(209) FIG. **9** is a diagrammatic view showing the content stored in the phase data storage section **754**.

(210) The phase data storage section **754** includes a discharge-side phase data storage section **755** and an intake-side phase data storage section **756**, as shown in FIG. **9**.

(211) The discharge-side phase data storage section **755** stores phase data representing the phases of the plurality of frequency components contained in each of the first to fourth discharge-side noise and according to the rotational position of the corresponding fan on a corresponding fan basis. The discharge-side characteristic data storage section **755** includes a first phase data storage section **7551**, a second phase data storage section **7552**, a third phase data storage section **7553**, and a fourth phase data storage section **7554**.

(212) The first phase data storage section **7551** stores phase data representing the phases of the frequency components contained in the first discharge-side noise resulting from the first fan **711**. Specifically, the first phase data storage section **7551** stores in accordance with the fan rotational speed of the first fan **711** the phase data representing the phases of the frequency components contained in the first discharge-side noise resulting from the first fan **711** and according to the rotational position of the first fan **711**.

(213) For example, the first phase data storage section **7551** stores phase data **E1** in accordance with a case where the fan rotational speed of the first fan **711** is 1000 (rpm) and the rotational position of the first fan **711** is 0°, as shown in FIG. **9**. Furthermore, for example, the first phase data storage section **7551** stores phase data **E2** in accordance with a case where the fan rotational speed of the first fan **711** is 1000 (rpm) and the rotational position of the first fan **711** is 1°. Moreover, for example, the first phase data storage section **7551** stores phase data **E359** in accordance with a case where the fan rotational speed of the first fan **711** is 1000 (rpm) and the rotational position of the first fan **711** is 359°. The first phase data storage section **7551** further stores phase data representing the phases of the frequency components in cases where the fan rotational speed is other speeds for each angle of rotation of the first fan **711**, which is incremented by 10.

(214) The first phase data storage section **7551** thus stores the phase data representing the phases of the frequency components for each fan rotational speed of the first fan **711** and for each angle of rotation of the first fan **711**, which is incremented by 1°.

(215) The second phase data storage section **7552** stores the phase data representing the phases of the frequency components contained in the second discharge-side noise resulting from the second fan **721**. The third phase data storage section **7553** stores the phase data representing the phases of the frequency components contained in the third discharge-side noise resulting from the third fan **731**, and the fourth phase data storage section **7554** stores the phase data representing the phases of the frequency components contained in the fourth discharge-side noise resulting from the fourth fan **741**.

(216) The phase data stored in the second phase data storage section **7552**, the phase data stored in the third phase data storage section **7553**, and the phase data stored in the fourth phase data storage section **7554** are similar to the phase data stored in the first phase data storage section **7551**. That is, the second phase data storage section **7552**, the third phase data storage section **7553**, and the fourth phase data storage section **7554** each store the phase data representing the phases of the frequency components contained in the corresponding noise of the second discharge-side noise, the third discharge-side noise, and the fourth discharge-side noise for each fan rotational speed of the corresponding one of the second fan **721**, the third fan **731**, and the fourth fan **741** and for each angle of rotation of the corresponding fan, which is incremented by 1°.

(217) The intake-side phase data storage section **756** stores the phase data representing the phases of the plurality of frequency components contained in each of the first to fourth intake-side noise and according to the rotational position of the corresponding fan on a corresponding fan basis. The intake-side phase data storage section **756** includes a first phase data storage section **7561**, a second phase data storage section **7562**, a third phase data storage section **7563**, and a fourth phase data storage section **7564**.

(218) The first phase data storage section **7561** stores the phase data representing the phases of the frequency components contained in the first intake-side noise resulting from the first fan **711**. Specifically, the first phase data storage section **7561** stores in accordance with the fan rotational speed of the first fan **711** the phase data representing the phases of the frequency components contained in the first intake-side noise resulting from the first fan **711** and according to the fan rotational position of the first fan **711**.

(219) The second phase data storage section **7562** stores the phase data representing the phases of the frequency components contained in the second intake-side noise resulting from the second fan **721**. The third phase data storage section **7563** stores the phase data representing the phases of the frequency components contained in the third intake-side noise resulting from the third fan **731**. The fourth phase data storage section **7564** stores the phase data representing the phases of the frequency components contained in the fourth intake-side noise resulting from the fourth fan **741**.

(220) The phase data stored in the second phase data storage section **7562**, the phase data stored in the third phase data storage section **7563**, and the phase data stored in the fourth phase data storage section **7564** are similar to the phase data stored in the first phase data storage section **7561**. That is, the second phase data storage section **7562**, the third phase data storage section **7563**, and the fourth phase data storage section **7564** each store the phase data representing the phases of the frequency components contained in the corresponding noise of the second intake-side noise, the third intake-side noise, and the fourth intake-side noise for each fan rotational speed of the corresponding one of the second fan **721**, the third fan **731**, and the fourth fan **741** and for each angle of rotation of the corresponding fan, which is incremented by 1° .

(221) Configuration of Control Section

(222) The control section **76C** controls the operation of the cooling apparatus **7C** based on the control signals inputted from the control apparatus **5**, as the control sections **66A** and **66B** do. Specifically, the control section **76C** drives the fans **711**, **721**, **731**, and **741** based on the inputted control signals. In addition, the control section **76C** outputs drive signals to the first loudspeaker **713** and the second loudspeaker **723** to cause the first loudspeaker **713** to emit the discharge-side interference sound and the second loudspeaker **723** to emit the intake-side interference sound.

(223) The control section **76C** includes a fan control section **761**, a rotational speed acquisition section **762**, a rotational position acquisition section **763**, a first characteristic acquisition section **764**, a first phase acquisition section **765**, a first waveform generation section **766**, a first signal output section **767**, a second characteristic acquisition section **768**, a second phase acquisition section **769**, a second waveform generation section **770**, and a second signal output section **771**, as shown in FIG. 7.

(224) The fan control section **761** drives the fans **711**, **721**, **731**, and **741** based on control signals inputted from the control apparatus **5**, as the fan control section **661** does.

(225) The rotational speed acquisition section **762** acquires the fan rotational speeds of the fans **711**, **721**, **731**, and **741** detected by the rotational speed detection sections **631** of the detection sections **712**, **722**, **732**, and **742**.

(226) The rotational position acquisition section **763** acquires the rotational positions (angles of rotation) of the fans **711**, **721**, **731**, and **741** detected by the rotational position detection sections **632** of the detection sections **712**, **722**, **732**, and **742**.

(227) The first characteristic acquisition section **764**, the first phase acquisition section **765**, the first waveform generation section **766**, and the first signal output section **767** form a functional

portion that emits the discharge-side interference sound, which interferes with the discharge-side noise, from the first loudspeaker **713**.

(228) The first characteristic acquisition section **764** acquires from the first characteristic data storage section **7521** of the discharge-side characteristic data storage section **752** the frequency characteristic data representing the frequency characteristics of the first discharge-side noise and corresponding to the fan rotational speed of the first fan **711** acquired by the rotational speed acquisition section **762**. The first characteristic acquisition section **764** further acquires from the second characteristic data storage section **7522** of the discharge-side characteristic data storage section **752** the frequency characteristic data representing the frequency characteristics of the second discharge-side noise and corresponding to the fan rotational speed of the second fan **721** acquired by the rotational speed acquisition section **762**. The first characteristic acquisition section **764** further acquires from the third characteristic data storage section **7523** of the discharge-side characteristic data storage section **752** the frequency characteristic data representing the frequency characteristics of the third discharge-side noise and corresponding to the fan rotational speed of the third fan **731** acquired by the rotational speed acquisition section **762**. Similarly, the first characteristic acquisition section **764** acquires from the fourth characteristic data storage section **7524** of the discharge-side characteristic data storage section **752** the frequency characteristic data representing the frequency characteristics of the fourth discharge-side noise and corresponding to the fan rotational speed of the fourth fan **741** acquired by the rotational speed acquisition section **762**.

(229) The first phase acquisition section **765** acquires from the first phase data storage section **7551** of the phase data storage section **754** the phase data corresponding to the fan rotational speed and the rotational position of the first fan **711** acquired by the rotational speed acquisition section **762** and the rotational position acquisition section **763**. The first phase acquisition section **765** further acquires from the second phase data storage section **7552** of the phase data storage section **754** the phase data corresponding to the fan rotational speed and the rotational position of the second fan **721** acquired by the rotational speed acquisition section **762** and the rotational position acquisition section **763**. The first phase acquisition section **765** further acquires from the third phase data storage section **7553** of the phase data storage section **754** the phase data corresponding to the fan rotational speed and the rotational position of the third fan **731** acquired by the rotational speed acquisition section **762** and the rotational position acquisition section **763**. Similarly, the first phase acquisition section **765** acquires from the fourth phase data storage section **7554** of the phase data storage section **754** the phase data corresponding to the fan rotational speed and the rotational position of the fourth fan **741** acquired by the rotational speed acquisition section **762** and the rotational position acquisition section **763**.

(230) The first waveform generation section **766** generates the waveform of the discharge-side interference sound, which interferes with the discharge-side noise, based on the frequency characteristic data corresponding to the fan rotational speeds of the fans **711**, **721**, **731**, and **741** and acquired by the first characteristic acquisition section **764** and the phase data corresponding to the fan rotational speeds and the rotational positions of the fans **711**, **721**, **731**, and **741** and acquired by the first phase acquisition section **765**, as the waveform generation section **666** does.

(231) For example, the first waveform generation section **766** generates the waveform of the discharge-side interference sound as follows.

(232) First, the first waveform generation section **766** generates the waveform of the interference sound for the first discharge-side noise based on the frequency characteristic data corresponding to the fan rotational speed of the first fan **711** and the phase data corresponding to the fan rotational speed and the rotational position of the first fan **711**. Similarly, the first waveform generation section **766** generates the waveform of the interference sound for the second discharge-side noise based on the frequency characteristic data corresponding to the fan rotational speed of the second fan **721** and the phase data corresponding to the fan rotational speed and the rotational position of

the second fan **721**. The first waveform generation section **766** uses the same method to generate the waveform of the interference sound for the third discharge-side noise and the waveform of the interference sound for the fourth discharge-side noise.

(233) The first waveform generation section **766** then combines the waveforms of the interference sounds generated as described above with one another to generate the waveform of the discharge-side interference sound. The discharge-side interference sound therefore contains interference sounds that interfere with the first discharge-side noise, the second discharge-side noise, the third discharge-side noise, and the fourth discharge-side noise.

(234) The first waveform generation section **766** may instead generate the waveform of the first discharge-side noise, the waveform of the second discharge-side noise, the waveform of the third discharge-side noise, and the waveform of the fourth discharge-side noise based on the respective frequency characteristic data and phase data, combine the generated waveforms with one another to generate the waveform of the discharge-side noise, and then generate the waveform opposite in terms of phase from the discharge-side noise as the waveform of the discharge-side interference sound.

(235) The first signal output section **767** outputs a drive signal according to the waveform of the discharge-side interference sound generated by the first waveform generation section **766** to the first loudspeaker **713** to cause the first loudspeaker **713** to emit the discharge-side interference sound.

(236) That is, the control section **76C** generates the drive signal to be outputted to the first loudspeaker **713**. The first signal output section **767** may adjust the timing at which the drive signal is outputted to the first loudspeaker **713** in such a way that the discharge-side interference sound emitted by the first loudspeaker **713** appropriately interferes with the discharge-side noise propagating in the duct **61A**.

(237) When the discharge-side interference sound emitted from the first loudspeaker **713** interferes with the discharge-side noise as described above, the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212** decreases. In this process, the discharge-side interference sound contains not only the components that interfere with the discrete frequency noise resulting from the driven fans **711**, **721**, **731**, and **741**, but also the components that interfere with the broadband noise resulting from the flow generated by the driven fans **711**, **721**, **731**, and **741** and the component that interferes with the in-apparatus environmental noise, whereby the discharge-side noise leaking out of the projector **1C** effectively decreases, as in the first embodiment described above.

(238) The second characteristic acquisition section **768**, the second phase acquisition section **769**, the second waveform generation section **770**, and the second signal output section **771** form a functional portion that emits the intake-side interference sound, which interferes with the intake-side noise, from the second loudspeaker **723**.

(239) The second characteristic acquisition section **768** acquires from the intake-side characteristic data storage section **753** of the characteristic data storage section **751** the frequency characteristic data corresponding to the fan rotational speeds of the fans **711**, **721**, **731**, and **741** acquired by the rotational speed acquisition section **762**, as the first characteristic acquisition section **764** does.

(240) The second phase acquisition section **769** acquires from the intake-side phase data storage section **756** of the phase data storage section **754** the phase data corresponding to the fan rotational speeds and the rotational positions of the fans **711**, **721**, **731**, and **741** acquired by the rotational speed acquisition section **762** and the rotational position acquisition section **763**.

(241) The second waveform generation section **770** generates the waveform of the intake-side interference sound, which interferes with the intake-side noise, based on the frequency characteristic data corresponding to the fan rotational speeds of the fans **711**, **721**, **731**, and **741** and acquired by the second characteristic acquisition section **768** and the phase data corresponding to the fan rotational speeds and the rotational positions of the fans **711**, **721**, **731**, and **741** and

acquired by the second phase acquisition section **769**. The second waveform generation section **770** can generate the waveform of the intake-side interference sound, for example, in the same manner as the first waveform generation section **766** generates the waveform of the discharge-side interference sound.

(242) The second signal output section **771** generates a drive signal according to the waveform of the intake-side interference sound generated by the second waveform generation section **770** and outputs the drive signal to the second loudspeaker **723** to cause the second loudspeaker **723** to emit the intake-side interference sound.

(243) That is, the control section **76C** generates the drive signal to be outputted to the second loudspeaker **723**. The second signal output section **771** may adjust the timing at which the drive signal is outputted to the second loudspeaker **723** in such a way that the intake-side interference sound emitted by the second loudspeaker **723** appropriately interferes with the intake-side noise propagating in the duct **61B**.

(244) When the intake-side interference sound emitted from the second loudspeaker **723** interferes with the intake-side noise as described above, the intake-side noise leaking out of the exterior enclosure **2** via the intake port **241** decreases. In this process, the intake-side interference sound contains not only the components that interfere with the discrete frequency noise resulting from the driven fans **711**, **721**, **731**, and **741**, but also the components that interfere with the broadband noise resulting from the flow generated by the driven fans **711**, **721**, **731**, and **741** and the component that interferes with the in-apparatus environmental noise, whereby the intake-side noise leaking out of the projector **1C** effectively decreases, as in the second embodiment described above.

(245) Effects of Third Embodiment

(246) The projector **1C** according to the present embodiment described above can provide the effects below as well as the same effects as those provided by the projectors **1A** and **1B** according to the first and second embodiments.

(247) The projector **1C** includes the exterior enclosure **2**, the light source **30**, the image formation section **34**, the first fan **711**, the second fan **721**, the first loudspeaker **713**, the second loudspeaker **723**, the characteristic data storage section **751**, and the control section **76C**.

(248) The exterior enclosure **2** has the intake port **241** and the discharge port **212**. The light source **30** and the image formation section **34** are heat sources disposed in the exterior enclosure **2**. The first fan **711** causes the cooling gas to flow to the light source **30**, and the second fan **721** causes the cooling gas to flow to the image formation section **34**.

(249) The third fan **731** and the fourth fan **741** cause the cooling gas to flow to the power supply apparatus **4** and the control apparatus **5**, which are heat sources disposed in the exterior enclosure **2**. The first loudspeaker **713** is disposed between the discharge port **212** and the first fan **711**, which is disposed in a position closer to the discharge port **212**, out of the first fan **711** and the second fan **721**, in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the first loudspeaker **713**. The second loudspeaker **723** is disposed between the intake port **241** and the second fan **721**, which is disposed in a position closer to the intake port **241**, out of the first fan **711** and the second fan **721**, in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the second loudspeaker **723**.

(250) The first characteristic data storage section **7521** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first discharge-side noise (first noise) containing the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711** per unit time. The second characteristic data storage section **7522** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second discharge-side noise (second noise) containing the discrete frequency noise produced by the driven second fan **721**, the broadband noise based on the cooling gas flow generated by the driven second

fan **721**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721** per unit time.

(251) The first characteristic data storage section **7531** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first intake-side noise (first noise) containing the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711** per unit time. The second characteristic data storage section **7532** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second intake-side noise (second noise) containing the discrete frequency noise produced by the driven second fan **721**, the broadband noise based on the cooling gas flow generated by the driven second fan **721**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721** per unit time.

(252) The control section **76C** generates drive signals to be outputted to the first loudspeaker **713** and the second loudspeaker **723**. The control section **76C** includes the first characteristic acquisition section **764** and the second characteristic acquisition section **768** as a characteristic acquisition section, the first waveform generation section **766** and the second waveform generation section **770** as a waveform generation section, and the first signal output section **767** and the second signal output section **771** as a signal output section.

(253) The first characteristic acquisition section **764** acquires the frequency characteristic data on the frequency characteristics of the first discharge-side noise corresponding to the rotational speed of the first fan **711** per unit time from the first characteristic data storage section **7521**. The first characteristic acquisition section **764** further acquires the frequency characteristic data on the frequency characteristics of the second discharge-side noise corresponding to the rotational speed of the second fan **721** per unit time from the second characteristic data storage section **7522**. The first characteristic acquisition section **764** still further acquires the frequency characteristic data on the frequency characteristics of the third discharge-side noise corresponding to the rotational speed of the third fan **731** per unit time and the frequency characteristic data on frequency characteristics of the fourth discharge-side noise corresponding to the rotational speed of the fourth fan **741** per unit time.

(254) The first waveform generation section **766** generates the waveform of the discharge-side interference sound, which interferes with the discharge-side noise leaking out of the exterior enclosure **2** via the discharge port **212** and containing the first to fourth discharge-side noise, based on the frequency characteristic data acquired by the first characteristic acquisition section **764**.

(255) The first signal output section **767** outputs a drive signal based on the waveform of the discharge-side interference sound generated by the first waveform generation section **766** to the first loudspeaker **713**.

(256) The second characteristic acquisition section **768** acquires the frequency characteristic data on the frequency characteristics of the first intake-side noise corresponding to the rotational speed of the first fan **711** per unit time from the first characteristic data storage section **7531**. The second characteristic acquisition section **768** further acquires the frequency characteristic data on the frequency characteristics of the second intake-side noise corresponding to the rotational speed of the second fan **721** per unit time from the second characteristic data storage section **7532**. The second characteristic acquisition section **768** still further acquires the frequency characteristic data on the frequency characteristics of the third intake-side noise corresponding to the rotational speed of the third fan **731** per unit time and the frequency characteristic data on the frequency characteristics of the fourth intake-side noise corresponding to the rotational speed of the fourth fan **741** per unit time.

(257) The second waveform generation section **770** generates the waveform of the intake-side interference sound, which interferes with the intake-side noise leaking out of the exterior enclosure

2 via the intake port **241** and containing the first to fourth intake-side noise, based on the frequency characteristic data acquired by the second characteristic acquisition section **768**.

(258) The second signal output section **771** outputs a drive signal based on the waveform of the intake-side interference sound generated by the second waveform generation section **770** to the second loudspeaker **723**.

(259) According to the configuration described above, the control section **76C** allows the first loudspeaker **713** to emit the discharge-side interference sound, which interferes with the discharge-side noise containing the first discharge-side noise and the second discharge-side noise to reduce the discharge-side noise, with no need for a microphone that detects the noise leaking out of the exterior enclosure **2** via the discharge port **212**, as in the projectors **1A** and **1B** according to the first and second embodiments.

(260) Similarly, the control section **76C** allows the second loudspeaker **723** to emit the intake-side interference sound, which interferes with the intake-side noise containing the first intake-side noise and the second intake-side noise to reduce the intake-side noise, with no need for a microphone that detects the noise leaking out of the exterior enclosure **2** via the intake port **241**.

(261) Since the discharge-side noise and the intake-side noise each contain the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise produced by the fans **711**, **721**, **731**, and **741**, the range of noise reduced by emitting the discharge-side interference sound and the intake-side interference sound can be expanded. Therefore, the configuration of the projector **1C** can be simplified, and the discharge-side noise and the intake-side noise can be effectively reduced.

(262) That is, the cooling apparatus **7C** includes the first fan **711**, the second fan **721**, the first loudspeaker **713** and the second loudspeaker **723** as a loudspeaker, the characteristic data storage section **751**, and the control section **76C**.

(263) The first fan **711** causes the cooling gas to flow to the light source **30**, which is a heat source, and the second fan **721** causes the cooling gas to flow to the image formation section **34**, which is a heat source. The third fan **731** causes the cooling gas to flow to the power supply apparatus **4**, which is a heat source, and the fourth fan **741** causes the cooling gas to flow to the control apparatus **5**, which is a heat source. The first loudspeaker **713** and the second loudspeaker **723** output sound waves according to the inputted drive signals.

(264) The first characteristic data storage section **7521** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first discharge-side noise (first noise) containing the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711** per unit time. The second characteristic data storage section **7522** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second discharge-side noise (second noise) containing the discrete frequency noise produced by the driven second fan **721**, the broadband noise based on the cooling gas flow generated by the driven second fan **721**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721** per unit time.

(265) The first characteristic data storage section **7531** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first intake-side noise (first noise) containing the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711** per unit time. The second characteristic data storage section **7532** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second intake-side noise (second noise) containing the discrete frequency noise produced by the driven second fan **721**, the broadband noise based on the cooling gas flow generated by the driven second fan

721, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721** per unit time.

(266) The control section **76C** generates drive signals to be outputted to the first loudspeaker **713** and the second loudspeaker **723**. The control section **76C** includes the first characteristic acquisition section **764** and the second characteristic acquisition section **768** as the characteristic acquisition section, the first waveform generation section **766** and the second waveform generation section **770** as the waveform generation section, and the first signal output section **767** and the second signal output section **771** as the signal output section.

(267) The first characteristic acquisition section **764** acquires the frequency characteristic data on the frequency characteristics of the first discharge-side noise (first noise) corresponding to the rotational speed of the first fan **711** per unit time from the first characteristic data storage section **7521**. The first characteristic acquisition section **764** further acquires the frequency characteristic data on the frequency characteristics of the second discharge-side noise (second noise) corresponding to the rotational speed of the second fan **721** per unit time from the second characteristic data storage section **7522**. The first characteristic acquisition section **764** still further acquires the frequency characteristic data on frequency characteristics of the third discharge-side noise (third noise) corresponding to the rotational speed of the third fan **731** per unit time and the frequency characteristic data on the frequency characteristics of the fourth discharge-side noise (fourth noise) corresponding to the rotational speed of the fourth fan **741** per unit time.

(268) The first waveform generation section **766** generates the waveform of discharge-side interference sound, which interferes with the discharge-side noise containing the first to fourth discharge-side noise, based on the frequency characteristic data acquired by the first characteristic acquisition section **764**.

(269) The first signal output section **767** outputs a drive signal based on the waveform of the discharge-side interference sound generated by the first waveform generation section **766** to the first loudspeaker **713**.

(270) The second characteristic acquisition section **768** acquires the frequency characteristic data on the frequency characteristics of the first intake-side noise (first noise) corresponding to the rotational speed of the first fan **711** per unit time from the first characteristic data storage section **7531**. The second characteristic acquisition section **768** further acquires the frequency characteristic data on the frequency characteristics of the second intake-side noise (second noise) corresponding to the rotational speed of the second fan **721** per unit time from the second characteristic data storage section **7532**. The second characteristic acquisition section **768** still further acquires the frequency characteristic data on the frequency characteristics of the third intake-side noise (third noise) corresponding to the rotational speed of the third fan **731** per unit time and the frequency characteristic data on the frequency characteristics of the fourth intake-side noise (fourth noise) corresponding to the rotational speed of the fourth fan **741** per unit time.

(271) The second waveform generation section **770** generates the waveform of the intake-side interference sound, which interferes with the intake-side noise containing the first to fourth discharge-side noise, based on the frequency characteristic data acquired by the second characteristic acquisition section **768**.

(272) The second signal output section **771** outputs a drive signal based on the waveform of the intake-side interference sound generated by the second waveform generation section **770** to the second loudspeaker **723**.

(273) The thus configured cooling apparatus **7C** can provide the same effects as those provided by the projector **1C** described above.

(274) The cooling apparatus **7C** of the projector **1C** includes the rotational speed detection section **631** of the first detection section **712**, which detects the rotational speed of the first fan **711** per unit time, and the rotational speed detection section **631** of the second detection section **722**, which detects the rotational speed of the second fan **721** per unit time. The rotational speed detection

section **631** of the first detection section **712** corresponds to a first rotational speed detection section, and the rotational speed detection section **631** of the second detection section **722** corresponds to a second rotational speed detection section.

(275) The first characteristic acquisition section **764** acquires from the first characteristic data storage section **7521** the frequency characteristic data on the frequency characteristics of the first discharge-side noise corresponding to the rotational speed of the first fan **711** per unit time detected by the rotational speed detection section **631** of the first detection section **712** and acquires from the second characteristic data storage section **7522** the frequency characteristic data on the frequency characteristics of the second discharge-side noise corresponding to the rotational speed of the second fan **721** per unit time detected by the rotational speed detection section **631** of the second detection section **722**.

(276) The second characteristic acquisition section **768** acquires from the first characteristic data storage section **7531** the frequency characteristic data on the frequency characteristics of the first intake-side noise corresponding to the rotational speed of the first fan **711** per unit time detected by the rotational speed detection section **631** of the first detection section **712** and acquires from the second characteristic data storage section **7532** the frequency characteristic data on the frequency characteristics of the second intake-side noise corresponding to the rotational speed of the second fan **721** per unit time detected by the rotational speed detection section **631** of the second detection section **722**.

(277) According to the configuration described above, the first characteristic acquisition section **764** can acquire the frequency characteristic data on the frequency characteristics of the first discharge-side noise according to the actual rotational speed of the first fan **711** per unit time and the frequency characteristic data on the frequency characteristics of the second discharge-side noise according to the actual rotational speed of the second fan **721** per unit time. Therefore, the waveform of the first discharge-side noise and the waveform of the second discharge-side noise can be reproduced more accurately, and in turn, the discharge-side interference sound, which effectively interferes with the discharge-side noise containing the first discharge-side noise and the second discharge-side noise, can be emitted from the first loudspeaker **713**. The discharge-side noise emitted out of the projector **1C** can therefore be effectively reduced.

(278) The second characteristic acquisition section **768** can acquire the frequency characteristic data on the frequency characteristics of the first intake-side noise according to the actual rotational speed of the first fan **711** per unit time and the frequency characteristic data on the frequency characteristics of the second intake-side noise according to the actual rotational speed of the second fan **721** per unit time. The intake-side noise emitted out of the projector **1C** can therefore be effectively reduced in the same manner described above.

(279) The cooling apparatus **7C** of the projector **1C** includes the rotational position detection section **632** of the first detection section **712**, which detects the rotational position of the first fan **711**, the rotational position detection section **632** of the second detection section **722**, which detects the rotational position of the second fan **721**, and the phase data storage section **754**. The rotational position detection section **632** of the first detection section **712** corresponds to a first rotational position detection section, and the rotational position detection section **632** of the second detection section **722** corresponds to a second rotational position detection section.

(280) The first phase data storage section **7551** of the phase data storage section **754** stores the phase data (first phase data) representing the phases of the plurality of frequency components contained in the first discharge-side noise in accordance with the rotational position of the first fan **711**. The second phase data storage section **7552** of the phase data storage section **754** stores the phase data (second phase data) representing the phases of the plurality of frequency components contained in the second discharge-side noise in accordance with the rotational position of the second fan **721**.

(281) The first phase data storage section **7561** of the phase data storage section **754** stores the

phase data (first phase data) representing the phases of the plurality of frequency components contained in the first intake-side noise in accordance with the rotational position of the first fan **711**. The second phase data storage section **7562** of the phase data storage section **754** stores the phase data (second phase data) representing the phases of the plurality of frequency components contained in the second intake-side noise in accordance with the rotational position of the second fan **721**.

(282) In the control section **76C**, the first phase acquisition section **765** as a phase acquisition section acquires the phase data (first phase data) corresponding to the detected rotational position of the first fan **711** from the first phase data storage section **7551** and acquires the phase data (second phase data) corresponding to the detected rotational position of the second fan **721** from the second phase data storage section **7552**. The first waveform generation section **766** generates the waveform of the discharge-side interference sound based on the frequency characteristic data on the frequency characteristics of the first discharge-side noise and the frequency characteristic data on the frequency characteristics of the second discharge-side noise acquired by the first characteristic acquisition section **764** and the phase data acquired by the first phase acquisition section **765**.

(283) Similarly, the second phase acquisition section **769** as the phase acquisition section acquires the phase data (first phase data) corresponding to the detected rotational position of the first fan **711** from the first phase data storage section **7561** and acquires the phase data (second phase data) corresponding to the detected rotational position of the second fan **721** from the second phase data storage section **7562**. The second waveform generation section **770** generates the waveform of the intake-side interference sound based on the frequency characteristic data on the frequency characteristics of the first intake-side noise and the frequency characteristic data on the frequency characteristics of the second intake-side noise acquired by the second characteristic acquisition section **768** and the phase data acquired by the second phase acquisition section **769**.

(284) According to the configuration described above, the phase acquisition sections **765** and **769** acquire the phase data according to the rotational position of the first fan **711** and the phase data according to the rotational position of the second fan **721**, respectively. The phase acquisition sections **765** and **769** further acquire the phase data according to the rotational position of the third fan **731** and the phase data according to the rotational position of the fourth fan **741**, respectively. Thereafter, the first waveform generation section **766** generates the waveform of the discharge-side interference sound based on the frequency characteristic data on the frequency characteristics of the first discharge-side noise, the frequency characteristic data on the frequency characteristics of the second discharge-side noise, and the phase data, and the second waveform generation section **770** generates the waveform of the intake-side interference sound based on the frequency characteristic data on the frequency characteristics of the first intake-side noise, the frequency characteristic data on the frequency characteristics of the second intake-side noise, and the phase data.

(285) The discharge-side interference sound, which can effectively reduce the discharge-side noise containing the first discharge-side noise and the second discharge-side noise, can thus be emitted from the first loudspeaker **713**, as in the projectors **1A** and **1B** according to the first and second embodiments described above. Furthermore, the intake-side interference sound, which can effectively reduce the intake-side noise containing the first intake-side noise and the second intake-side noise, can be emitted from the second loudspeaker **723**. The two types of noise can therefore be effectively reduced.

(286) In the cooling apparatus **7C** of the projector **1C**, the frequency characteristic data on the frequency characteristics of the first discharge-side noise is data representing the features of each of the plurality of frequency components contained in the first discharge-side noise and formed of the frequency and sound pressure of each of the frequency components. The frequency characteristic data on the frequency characteristics of the second discharge-side noise is data representing the features of each of the plurality of frequency components contained in the second discharge-side

noise and formed of the frequency and sound pressure of each of the frequency components. The same holds true for the frequency characteristic data on the frequency characteristics of the first intake-side noise and the frequency characteristic data on the frequency characteristics of the second intake-side noise.

(287) According to the configuration described above, the discharge-side interference sound and the intake-side interference sound, which can effectively reduce at least one frequency component contained in the discharge-side noise and the intake-side noise, can be emitted from the loudspeakers **713** and **723**, as in the projectors **1A** and **1B** according to the first and second embodiments described above.

(288) The discharge-side noise and the intake-side noise can therefore be effectively reduced.

(289) In the cooling apparatus **7C** of the projector **1C**, the first fan **711** causes the cooling gas to flow to the light source **30** as a first heat source out of the heat sources, and the second fan **721** causes the cooling gas to flow to the image formation section **34** as a second heat source out of the heat sources. The third fan **731** causes the cooling gas to flow to the power supply apparatus **4** out of the heat sources, and the fourth fan **741** causes the cooling gas to flow to the control apparatus **5** out of the heat sources.

(290) According to the configuration described above, in which the cooling gas flows to each of the heat sources, the heat sources can each be cooled efficiently.

(291) The control method executed by the control section **76C** is executed in the projector **1C**, which is an electronic instrument including the first fan **711** and the second fan **721**, which cause the cooling gas to flow to the light source **30** and the image formation section **34**, which are heat sources, and the first loudspeaker **713** and the second loudspeaker **723**, which each output a sound wave according to a drive signal inputted to the loudspeaker. The control method acquires the frequency characteristic data on the frequency characteristics of the first discharge-side noise (first noise) containing the discrete frequency noise produced by the driven first fan **711**, the broadband noise based on the cooling gas flow generated by the driven first fan **711**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711** per unit time.

(292) The control method acquires the frequency characteristic data on the frequency characteristics of the second discharge-side noise (second noise) containing the discrete frequency noise produced by the driven second fan **721**, the broadband noise based on the cooling gas flow generated by the driven second fan **721**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721** per unit time. The control method then, based on the acquired frequency characteristic data on the frequency characteristics of the first discharge-side noise and the acquired frequency characteristic data on the frequency characteristics of the second discharge-side noise, generates the waveform of the discharge-side interference sound, which interferes with the discharge-side noise containing the first discharge-side noise and the second discharge-side noise, and outputs a drive signal based on the generated waveform of the discharge-side interference sound to the first loudspeaker **713**.

(293) The control method executed by the control section **76C** uses the same procedure of the control method described above to generate the waveform of the intake-side interference sound, which interferes with the intake-side noise containing the first intake-side noise and the second intake-side noise, and output a drive signal based on the generated waveform of the intake-side interference sound to the second loudspeaker **723**.

(294) According to the configuration described above, the same effects as those provided by the projector **1C** or the cooling apparatus **7C** described above can be provided.

Fourth Embodiment

(295) A fourth embodiment of the present disclosure will next be described.

(296) The projector according to the present embodiment has the same configuration as that of the projector **1C** according to the third embodiment, but differs therefrom in that the fans **711**, **721**, **731**, and **741** are formed of fans having the same specifications, and that the control section causes

the fans **711**, **721**, **731**, and **741** to operate at the same fan rotational speed and to have the same rotational position. In the following description, portions that are the same or substantially the same as the portions having been already described have the same reference characters and will not be described.

(297) Configuration of Projector

(298) FIG. **10** is a diagrammatic view showing the configuration of a projector **1D** according to the present embodiment.

(299) The projector **1D** according to the present embodiment has the same configuration and function as those of the projector **1C** according to the third embodiment except that the cooling apparatus **7C** according to the third embodiment is replaced with a cooling apparatus **7D** shown in FIG. **10**.

(300) Configuration of Cooling Apparatus

(301) The cooling apparatus **7D** has the same configuration and function as those in the projector **1C** according to the third embodiment except that the fans **711**, **721**, **731**, and **741**, the detection sections **722**, **732**, and **742**, and the control section **76C** are replaced with fans **711D**, **721D**, **731D**, and **741D**, detection sections **722D**, **732D**, and **742D**, and a control section **76D**.

(302) The first fan **711D** sucks the cooling gas in the exterior enclosure **2** and causes the cooling gas to flow to the light source **30**, which is a heat source, as the first fan **711** does.

(303) The second fan **721D** sucks the air outside the exterior enclosure **2** as the cooling gas and sends the cooling gas to the image formation section **34**, which is a heat source, to cause the cooling gas to flow to the image formation section **34**, as the second fan **721** does.

(304) The third fan **731D** sucks the cooling gas in the exterior enclosure **2** and sends the cooling gas to the power supply apparatus **4**, which is a heat source, to cause the cooling gas to flow to the power supply apparatus **4**, as the third fan **731** does.

(305) The fourth fan **741D** sucks the cooling gas in the exterior enclosure **2** and sends the cooling gas to the control apparatus **5**, which is a heat source, to cause the cooling gas to flow to the control apparatus **5**, as the fourth fan **741** does.

(306) The fans **711D**, **721D**, **731D**, and **741D** have the same specifications and are driven by the control section **76D** at the same fan rotational speed. Fans having the same specifications are fans having the same dimensions and the same number of vanes.

(307) The cooling apparatus **7D** includes the first detection section **712**, the second detection section **722D**, the third detection section **732D**, and the fourth detection section **742D**, as described above.

(308) The second detection section **722D** includes the rotational position detection section **632**, which detects the rotational position of the second fan **721D**, but does not include the rotational speed detection section **631**, which detects the fan rotational speed of the second fan **721D**. The third detection section **732D** includes the rotational position detection section **632**, which detects the rotational position of the third fan **731D**, but does not include the rotational speed detection section **631**, which detects the fan rotational speed of the third fan **731D**. The fourth detection section **742D** includes the rotational position detection section **632**, which detects the rotational position of the fourth fan **741D**, but does not include the rotational speed detection section **631**, which detects the fan rotational speed of the fourth fan **741D**.

(309) On the other hand, the first detection section **712** includes not only the rotational position detection section **632**, which detects the rotational position of the first fan **711D**, but also the rotational speed detection section **631**, which detects the fan rotational speed of the first fan **711D**.

(310) Configuration of Control Section

(311) FIG. **11** is a block diagram showing the configuration of the control section **76D**.

(312) The control section **76D** controls the operation of the cooling apparatus **7D** based on control signals inputted from the control apparatus **5**, as the control section **76C** does. The control section **76D** has the same configuration and function as those of the control section **76C** according to the

third embodiment except that the fan control section **761** according to the third embodiment is replaced with a fan control section **761D**, as shown in FIG. **11**.

(313) That is, the control section **76D** includes the fan control section **761D**, the rotational speed acquisition section **762**, the rotational position acquisition section **763**, the first characteristic acquisition section **764**, the first phase acquisition section **765**, the first waveform generation section **766**, the first signal output section **767**, the second characteristic acquisition section **768**, the second phase acquisition section **769**, the second waveform generation section **770**, and the second signal output section **771**.

(314) The fan control section **761D** of the control section **76D** operates the fans **711D**, **721D**, **731D**, and **741D** based on a control signal inputted from the control apparatus **5**. In this process, the control apparatus **5** outputs a control signal that drives the fans **711D**, **721D**, **731D**, and **741D** at the same fan rotational speed to the control section **76D**.

(315) To this end, the fan control section **761D** applies the same fan voltage to the fans **711D**, **721D**, **731D**, and **741D**. The fans **711D**, **721D**, **731D**, and **741D** are thus driven at the same fan rotational speed.

(316) The fan control section **761D** rotates the fans **711D**, **721D**, **731D**, and **741D** with the rotational positions thereof aligned with one another. Specifically, the fan control section **761D** aligns the rotational positions of the second fan **721D**, the third fan **731D**, and the fourth fan **741D** with the rotational position of the first fan **711D** based on the result of detection performed by the rotational position detection section **632** of each of the detection sections **712**, **722D**, **732D**, and **742D**.

(317) In this process, the fan control section **761D** may sequentially align the rotational positions of the second fan **721D**, third fan **731D**, and fourth fan **741D** with the rotational position of the first fan **711D** or all at once.

(318) The fan control section **761D** aligns the fan rotational speeds of the fans **721D**, **731D**, and **741D** with the fan rotational speed of the fan **711D** as described above, eliminating the need to provide the rotational speed detection sections **631** that detect the fan rotational speeds of the fans **721D**, **731D**, and **741D**.

(319) When the rotational positions of the fans **711D**, **721D**, **731D**, and **741D** are aligned with one another, the discharge-side noise and the intake-side noise leaking out of the projector **1D** can be reduced, for example, even when the discharge-side phase data storage section **755** and the intake-side phase data storage section **756** store in accordance with the fan rotational speed only the phase data on the phases of the fans **711D**, **721D**, **731D**, and **741D** provided when the rotational positions thereof are a predetermined position (reference position, for example), by outputting drive signals based on the discharge-side interference sound and the intake-side interference sound at the timing when the rotational positions of the fans **711D**, **721D**, **731D**, and **741D** become the predetermined position to the first loudspeaker **713** and the second loudspeaker **723**.

(320) In other words, the fan control section **761D** aligns the fan rotational speeds and rotational positions of the fans **721D**, **731D**, and **741D** with the fan rotational speed and the rotational position of the fan **711** to reduce the storage capacities of the discharge-side phase data storage section **755** and the intake-side phase data storage section **756**.

(321) Effects of Fourth Embodiment

(322) The projector **1D** according to the present embodiment described above provides the effects below as well as the same effects as those provided by the projector **1C** according to the third embodiment described above.

(323) The projector **1D** includes the exterior enclosure **2**, the light source **30**, the image formation section **34**, the first fan **711D**, the second fan **721D**, the first loudspeaker **713**, the second loudspeaker **723**, the characteristic data storage section **751**, and the control section **76D**.

(324) The exterior enclosure **2** has the intake port **241** and the discharge port **212**. The light source **30** and the image formation section **34** are heat sources disposed in the exterior enclosure **2**. The

first fan **711D** causes the cooling gas to flow to the light source **30**. The second fan **721D** has the same specifications as those of the first fan **711D** and causes the cooling gas to flow to the image formation section **34**. The first loudspeaker **713** is disposed between the discharge port **212** and the first fan **711D**, which is disposed in a position closer to the discharge port **212**, out of the first fan **711D** and the second fan **721D**, in the channel of the cooling gas, and outputs a sound wave according to a drive signal inputted to the first loudspeaker **713**. The second loudspeaker **723** is disposed between the intake port **241** and the second fan **721D**, which is disposed in a position closer to the intake port **241**, out of the first fan **711D** and the second fan **721D**, in the channel of the cooling gas, and outputs a sound wave according to a drive signal inputted to the second loudspeaker **723**.

(325) The first characteristic data storage section **7521** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first discharge-side noise containing the discrete frequency noise produced by the driven first fan **711D**, the broadband noise based on the cooling gas flow generated by the driven first fan **711D**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711D** per unit time. The second characteristic data storage section **7522** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second discharge-side noise containing the discrete frequency noise produced by the driven second fan **721D**, the broadband noise based on the cooling gas flow generated by the driven second fan **721D**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721D** per unit time.

(326) The first characteristic data storage section **7531** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the first intake-side noise containing the discrete frequency noise produced by the driven first fan **711D**, the broadband noise based on the cooling gas flow generated by the driven first fan **711D**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711D** per unit time. The second characteristic data storage section **7532** of the characteristic data storage section **751** stores the frequency characteristic data on the frequency characteristics of the second intake-side noise containing the discrete frequency noise produced by the driven second fan **721D**, the broadband noise based on the cooling gas flow generated by the driven second fan **721D**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721D** per unit time.

(327) The control section **76D** generates drive signals to be outputted to the first loudspeaker **713** and the second loudspeaker **723**. The control section **76D** includes the fan control section **761D**, the first characteristic acquisition section **764** and the second characteristic acquisition section **768** as the characteristic acquisition section, the first waveform generation section **766** and the second waveform generation section **770** as the waveform generation section, and the first signal output section **767** and the second signal output section **771** as the signal output section.

(328) The fan control section **761D** drives the first fan **711D** and the second fan **721D** at the same rotational speed per unit time. The effects of the first characteristic acquisition section **764**, the first waveform generation section **766**, the first signal output section **767**, the second characteristic acquisition section **768**, the second waveform generation section **770**, and the second signal output section **771** are the same as those in the third embodiment described above.

(329) That is, the cooling apparatus **7D** includes the first fan **711D**, the second fan **721D**, the first loudspeaker **713**, the second loudspeaker **723**, the characteristic data storage section **751**, and the control section **76D**.

(330) The first fan **711D** causes the cooling gas to flow to the light source **30**. The second fan **721D** has the same specifications as those of the first fan **711D** and causes the cooling gas to flow to the image formation section **34**.

(331) The first loudspeaker **713** and the second loudspeaker **723** output sound waves according to the inputted drive signals. The first characteristic data storage section **7521** and the second characteristic data storage section **7522** of the characteristic data storage section **751**, the first

characteristic data storage section **7531** and the second characteristic data storage section **7532** of the characteristic data storage section **751**, and the control section **76D** are the same as those in the description of the projector **1C**.

(332) According to the configuration described above, the control section **76D** allows the discharge-side interference sound to be emitted from the first loudspeaker **713** with no need for a microphone that detects the discharge-side noise containing the first discharge-side noise and the second discharge-side noise, as in the projector **1C** and the cooling apparatus **7C** according to the third embodiment described above.

(333) The control section **76D** further allows the intake-side interference sound to be emitted from the second loudspeaker **723** with no need for a microphone that detects the intake-side noise containing the first intake-side noise and the second intake-side noise.

(334) Since the first discharge-side noise and the second discharge-side noise each contain the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of the noise reduced by emitting the discharge-side interference sound can be expanded.

(335) Similarly, since the first intake-side noise and the second intake-side noise each contain the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of the noise reduced by emitting the intake-side interference sound can be expanded. Therefore, the configuration of the projector **1D** can be simplified, and the discharge-side noise and the intake-side noise can be effectively reduced.

(336) Furthermore, since the fan control section **761D** drives the first fan **711D**, the second fan **721D**, the third fan **731D**, and the fourth fan **741D** at the same rotational speed per unit time, there is no need to detect the rotational speeds of the fans other than the first fan **711D** per unit time. Therefore, the configuration of the projector **1D** can be simplified, and the process of outputting the discharge-side interference sound and the intake-side interference sound can be simplified.

(337) The cooling apparatus **7D** of the projector **1D** includes the rotational speed detection section **631**, which detects the rotational speed of the first fan **711D** per unit time out of the first fan **711D** and the second fan **721D**. The first characteristic acquisition section **764** acquires the frequency characteristic data representing the frequency characteristics of the first discharge-side noise and corresponding to the rotational speed detected by the rotational speed detection section **631** and the frequency characteristic data representing the frequency characteristics of the second discharge-side noise and corresponding to the rotational speed detected by the rotational speed detection section **631**. Similarly, the second characteristic acquisition section **768** acquires the frequency characteristic data representing the frequency characteristics of the first intake-side noise and corresponding to the rotational speed detected by the rotational speed detection section **631** and the frequency characteristic data representing the frequency characteristics of the second intake-side noise and corresponding to the rotational speed detected by the rotational speed detection section **631**. The same applies to the acquisition of the frequency characteristic data on the frequency characteristics of each of the third discharge-side noise, the fourth discharge-side noise, the third intake-side noise, and the fourth intake-side noise.

(338) As described above, since the fans **711D**, **721D**, **731D**, and **741D** are driven at the same rotational speed per unit time, the actual rotational speeds of the fans **711D**, **721D**, **731D**, and **741D** per unit time can be detected by detecting the rotational speed of the first fan **711D** per unit time. There is therefore no need to provide each of the fans **711D**, **721D**, **731D**, and **741D** with the rotational speed detection section **631**.

(339) Since the first characteristic acquisition section **764** and the second characteristic acquisition section **768** can acquire the frequency characteristic data according to the actual fan rotational speeds of the fans **711D**, **721D**, **731D**, and **741D**, the waveforms of the discharge-side noise and the intake-side noise can be reproduced more accurately. The discharge-side interference sound and the intake-side interference sound, which effectively interfere with the discharge-side noise and the intake-side noise, can therefore be emitted from the first loudspeaker **713** and the second

loudspeaker **723**, whereby the noise emitted out of the projector **1D** can be effectively reduced.

(340) The cooling apparatus **7D** of the projector **1D** includes the rotational position detection section **632** of the first detection section **712**, which detects the rotational position of the first fan **711D**, the rotational position detection section **632** of the second detection section **722**, which detects the rotational position of the second fan **721D**, and the phase data storage section **754**.

(341) The first phase data storage section **7551** of the phase data storage section **754** stores the first phase data representing the phases of the plurality of frequency components contained in the first discharge-side noise in accordance with the rotational speed and the rotational position of the first fan **711D**. The second phase data storage section **7552** of the phase data storage section **754** stores the second phase data representing the phases of the plurality of frequency components contained in the second discharge-side noise in accordance with the rotational speed and the rotational position of the second fan **721D**. The same applies to the third phase data storage section **7553** and the fourth phase data storage section **7554**.

(342) The first phase data storage section **7561** of the phase data storage section **754** stores the first phase data representing the phases of the plurality of frequency components contained in the first intake-side noise in accordance with the rotational speed and the rotational position of the first fan **711D**. The second phase data storage section **7562** of the phase data storage section **754** stores the second phase representing the phases of the plurality of frequency components contained in the second intake-side noise in accordance with the rotational speed and the rotational position of the second fan **721D**. The same applies to the third phase data storage section **7563** and the fourth phase data storage section **7564**.

(343) The fan control section **761D** drives the first fan **711D** and the second fan **721D** in synchronization with each other in such a way that the rotational position of the first fan **711D** coincides with the rotational position of the second fan **721D**. The control section **76D** includes the first phase acquisition section **765** and the second phase acquisition section **769** as the phase acquisition section.

(344) The first phase acquisition section **765** acquires the phase data corresponding to the rotational position of the first fan **711D** from the first phase data storage section **7551** and the phase data corresponding to the rotational position of the first fan **711D** from the second phase data storage section **7552**.

(345) The second phase acquisition section **769** acquires the phase data corresponding to the rotational position of the first fan **711D** from the first phase data storage section **7561** and the phase data corresponding to the rotational position of the first fan **711D** from the second phase data storage section **7562**.

(346) The first waveform generation section **766** generates the waveform of the discharge-side interference sound based on the frequency characteristic data on the frequency characteristics of the first discharge-side noise and the frequency characteristic data on the frequency characteristics of the second discharge-side noise acquired by the first characteristic acquisition section **764** and the phase data acquired by the first phase acquisition section **765**.

(347) The second waveform generation section **770** generates the waveform of the intake-side interference sound based on the frequency characteristic data on the frequency characteristics of the first intake-side noise and the frequency characteristic data on the frequency characteristics of the second intake-side noise acquired by the second characteristic acquisition section **768** and the phase data acquired by the second phase acquisition section **769**.

(348) According to the configuration described above, the fan control section **761D** drives the fans **711D**, **721D**, **731D**, and **741D** in synchronization with one another in such a way that the fans have the same rotational position.

(349) The rotational positions of the fans **711D**, **721D**, **731D**, and **741D** can therefore be acquired by the rotational position detection section **632** through detection of the rotational position of one of the fans. Therefore, the configuration of the projector **1D** can be simplified, and the interference

sound outputting process can be simplified.

(350) Thereafter, the first phase acquisition section **765** acquires the phase data according to the rotational positions of the fans **711D**, **721D**, **731D**, and **741D**, and the first waveform generation section **766** generates the waveform of the discharge-side interference sound based on the frequency characteristic data on the frequency characteristics of each discharge-side noise and the phase data on the phase thereof.

(351) Similarly, the second phase acquisition section **769** acquires the phase data according to the rotational positions of the fans **711D**, **721D**, **731D**, and **741D**, and the second waveform generation section **770** generates the waveform of the intake-side interference sound based on the frequency characteristic data on the frequency characteristics of each intake-side noise and the phase data on the phase thereof.

(352) The discharge-side interference sound and the intake-side interference sound that can effectively reduce the discharge-side noise and the intake-side noise can thus be emitted from the first loudspeaker **713** and the second loudspeaker **723**. The two types of noise can therefore be effectively reduced.

(353) The control method executed by the control section **76D** is executed in the projector **1D**, which is an electronic instrument including the first fan **711D**, which causes the cooling gas to flow to the light source **30**, which is a heat source, the second fan **721D**, which has the same specifications as those of the first fan **711D** and causes the cooling gas to flow to the image formation section **34**, which is a heat source, and the first loudspeaker **713** and the second loudspeaker **723**, which each output a sound wave according to a drive signal inputted to the loudspeaker.

(354) In the control method, the fans **711D** and **721D** are driven at the same rotational speed per unit time. The control method then acquires the frequency characteristic data on the frequency characteristics of the first discharge-side noise containing the discrete frequency noise produced by the driven first fan **711D**, the broadband noise based on the cooling gas flow generated by the driven first fan **711D**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711D** per unit time.

(355) The control method further acquires the frequency characteristic data on the frequency characteristics of the second discharge-side noise containing the discrete frequency noise produced by the driven second fan **721D**, the broadband noise based on the cooling gas flow generated by the driven second fan **721D**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721D** per unit time.

(356) The control method then, based on the acquired frequency characteristic data on the frequency characteristics of the first discharge-side noise and the frequency characteristic data on the frequency characteristics of the second discharge-side noise, generates the waveform of the discharge-side interference sound, which interferes with the discharge-side noise containing the first discharge-side noise and the second discharge-side noise, and outputs a drive signal based on the generated waveform of the discharge-side interference sound to the first loudspeaker **713**.

(357) The control method described above further acquires the frequency characteristic data on the frequency characteristics of the first intake-side noise containing the discrete frequency noise produced by the driven first fan **711D**, the broadband noise based on the cooling gas flow generated by the driven first fan **711D**, and the in-apparatus environmental noise in accordance with the rotational speed of the first fan **711D** per unit time.

(358) The control method further acquires the frequency characteristic data on the frequency characteristics of the second intake-side noise containing the discrete frequency noise produced by the driven second fan **721D**, the broadband noise based on the cooling gas flow generated by the driven second fan **721D**, and the in-apparatus environmental noise in accordance with the rotational speed of the second fan **721D** per unit time.

(359) The control method then, based on the acquired frequency characteristic data on the

frequency characteristics of the first intake-side noise and the frequency characteristic data on the frequency characteristics of the second intake-side noise, generates the waveform of the intake-side interference sound, which interferes with the intake-side noise containing the first intake-side noise and the second intake-side noise, and outputs a drive signal based on the generated waveform of the intake-side interference sound to the second loudspeaker **723**.

(360) According to the configuration described above, the same effects as those provided by the projector **1D** and the cooling apparatus **7D** can be provided by executing the control method described above.

(361) Variations of Embodiments

(362) The present disclosure is not limited to the embodiments described above, and variations, improvements, and other modifications to the extent that the advantage of the present disclosure is achieved fall within the scope of the present disclosure.

(363) In the first and second embodiments described above, the cooling apparatuses **6A** and **6B** of the projectors **1A** and **1B** each include a single fan. In the third and fourth embodiments described above, the cooling apparatuses **7C** and **7D** of the projectors **1C** and **1D** each include four fans. The number of fans provided in each of the cooling apparatuses is not limited to one or four and may be changed as appropriate.

(364) In the first embodiment described above, the light source **30** is presented as a heat source to which the cooling gas is caused to flow, and in the second embodiment described above, the image forming section **34** is presented as a heat source to which the cooling gas is caused to flow. In the third and fourth embodiments described above, the light source **30**, the image formation section **34**, the power supply apparatus **4**, and the control apparatus **5** are presented as heat sources to which the cooling gas is caused to flow.

(365) The heat sources are not limited to those described above and may be other components. For example, in the projector **1A** shown in the first embodiment described above, the heat source to which the cooling gas is caused to flow by the fan may be a component other than the light source **30**.

(366) In each of the embodiments described above, the cooling apparatus includes the rotational speed detection section **631**, which detects the rotational speed of the fan (fan rotational speed) per unit time, but not necessarily.

(367) For example, when the fan control sections **661**, **761**, and **761D** can accurately grasp and set the fan rotational speed of the driven fan from the fan voltage or any other factor, the cooling apparatus may not include the rotational speed detection section **631**.

(368) In each of the embodiments described above, the cooling apparatus includes the rotational position detection section **632**, which detects the rotational position of the fan, but not necessarily.

(369) The cooling apparatus may not necessarily include the rotational position detection section **632**.

(370) In each of the embodiments described above, for example, the frequency characteristic data is data representing the frequency and the sound pressure of each of a plurality of frequency components contained in the noise.

(371) The content of the frequency characteristic data is, however, not limited to the frequency and the sound pressure. For example, the frequency characteristic data may be expressed by a numerical formula or any other form.

(372) In each of the embodiments described above, the noise having a reduced sound pressure as a result of interference with an interference sound is noise containing discrete frequency noise produced by the driven fan, broadband noise based on the cooling gas flow generated by the driven fan, and in-apparatus environmental noise.

(373) The interference sound may be interference sound that interferes with part of the frequency components contained in the noise.

(374) For example, the interference sound may be sound that reduces part of the discrete frequency

noise, the broadband noise, and the in-apparatus environmental noise, that is, noise that belongs to any of a low frequency band, an intermediate frequency band, and a high frequency band.

(375) In each of the embodiments described above, the projectors **1A**, **1B**, **1C**, and **1D** each include the three light modulators **343R**, **343G**, and **343B**, but not necessarily. The present disclosure is also applicable to a projector including two or less or four or more light modulators.

(376) In each of the embodiments described above, the image projection apparatus **3** includes the optical parts arranged as shown in the layout diagram of FIG. **1**.

(377) The optical parts provided in the image projection apparatus **3** and the layout thereof are not limited to those described above.

(378) The overall layout of the projector can also be changed as appropriate. For example, at least one of the duct **61A** provided in association with the discharge port **212** and the duct **61B** provided in association with the intake port **241** may be omitted.

(379) In each of the embodiments described above, the light modulators **343** are each a transmissive liquid crystal panel having a light incident surface and a light exiting surface different from each other, but not necessarily.

(380) The light modulators may each be a reflective liquid crystal panel having a surface that serves both as the light incident surface and the light exiting surface.

(381) Furthermore, a light modulator using any component other than a liquid-crystal-based component and capable of modulating an incident luminous flux to form an image according to image information, such as a device using micromirrors, for example, a digital micromirror device (DMD), may be employed.

(382) The embodiments described above have been presented with reference to the case where the cooling apparatuses **6A**, **6B**, **7C**, and **7D** according to the present disclosure are used for the projectors **1A**, **1B**, **1C**, and **1D**, but not necessarily.

(383) The electronic instrument for which any of the cooling apparatuses according to the present disclosure is used may be electronic instruments other than projectors. The cooling apparatuses according to the present disclosure may also be each used as a stand-alone electronic instrument.

(384) Overview of Present Disclosure

(385) The present disclosure will be summarized below as additional remarks.

(386) A projector according to a first aspect of the present disclosure includes an exterior enclosure having an intake port and a discharge port, a heat source disposed in the exterior enclosure, a fan that causes a cooling gas to flow to the heat source, a loudspeaker that is disposed between one of the two openings, the intake port and the discharge port, and the fan in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker, a characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on the flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with the rotational speed of the fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(387) The control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates the waveform of an interference sound that interferes with the first noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(388) According to the configuration described above, in which the characteristic acquisition section acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, the control section can acquire the frequency characteristics of the first noise leaking out of the exterior enclosure.

(389) The waveform generation section then generates the waveform of the interference sound, which interferes with the first noise, and the signal output section outputs a drive signal based on the generated waveform of the interference sound to the loudspeaker, whereby the interference sound, which interferes with the first noise, can be emitted from the loudspeaker without no need for a microphone that detects the first noise.

(390) The configuration of the projector can therefore be simplified. In addition, since the first noise contains the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of reducible noise can be expanded.

(391) In the first aspect described above, the projector may include a rotational speed detection section that detects the rotational speed of the fan per unit time, and the characteristic acquisition section may acquire the frequency characteristic data corresponding to the rotational speed of the fan per unit time detected by the rotational speed detection section.

(392) According to the configuration described above, the characteristic acquisition section can acquire the frequency characteristic data corresponding to the actual rotational speed of the fan per unit time and can therefore more accurately reproduce the waveform of the first noise, and the loudspeaker can in turn emit the interference sound, which effectively interferes with the first noise.

(393) The first noise emitted out of the projector can therefore be effectively reduced.

(394) In the first aspect described above, the projector includes a rotational position detection section that detects the rotational position of the fan, and a phase data storage section that stores phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the fan per unit time and the rotational position of the fan.

(395) The control section may include a phase acquisition section that acquires from the phase data storage section the phase data corresponding to the rotational position of the fan detected by the rotational position detection section, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section.

(396) It is noted that the first noise can be efficiently reduced by causing interference sound opposite in terms of phase from the first noise to be interfered with the first noise. On the other hand, the phases of the plurality of frequency components contained in the first noise are hardly aligned with each other.

(397) In contrast, the phase data storage section stores the phases of plurality of frequency components contained in the first noise in accordance with the rotational position of the fan.

(398) As described above, the phase acquisition section acquires the phase data according to the rotational position of the fan detected by the rotational position detection section, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section, whereby the interference sound, which can effectively reduce the first noise, can be emitted from the loudspeaker. The first noise can therefore be effectively reduced.

(399) In the first aspect described above, the frequency characteristic data may be data representing the features of at least one of the plurality of frequency components contained in the first noise.

(400) According to the configuration described above, based on the features of the frequency components indicated by the frequency characteristic data, the interference sound that can interfere with at least one frequency component contained in the first noise to effectively reduce the at least one frequency component can be emitted from the loudspeaker. The first noise can therefore be effectively reduced.

(401) A projector according to a second aspect of the present disclosure includes an exterior enclosure having an intake port and a discharge port, a heat source disposed in the exterior

enclosure, a first fan and a second fan that cause a cooling gas to flow to the heat source, a loudspeaker that is disposed between one of the two openings, the intake port and the discharge port, and one of the first and second fans, the one fan disposed in a position close to the one opening, in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker, a first characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with the rotational speed of the first fan per unit time, a second characteristic data storage section that stores frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas generated by the driven second fan, and in-apparatus environmental noise in accordance with the rotational speed of the second fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(402) The control section includes a characteristic acquisition section that acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time from the first characteristic data storage section and acquires the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time from the second characteristic data storage section, a waveform generation section that generates the waveform of an interference sound that interferes with the first noise and the second noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(403) According to the configuration described above, the control section allows the loudspeaker to emit the interference sound, which interferes with the first noise and the second noise to reduce the first noise and the second noise, with no need for a microphone that detects the first noise and the second noise leaking out of the exterior enclosure via the one opening, as in the projector according to the first aspect described above.

(404) Since the first noise and the second noise each include the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of the noise reduced by emitting the interference sound can be expanded.

(405) Therefore, the configuration of the projector can be simplified, and the first noise and the second noise can be effectively reduced.

(406) In the second aspect described above, the projector includes a first rotational speed detection section that detects the rotational speed of the first fan per unit time, and a second rotational speed detection section that detects the rotational speed of the second fan per unit time.

(407) The characteristic acquisition section may acquire from the first characteristic data storage section the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time detected by the first rotational speed detection section and acquire from the second characteristic data storage section the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time detected by the second rotational speed detection section.

(408) According to the configuration described above, the characteristic acquisition section can acquire the frequency characteristic data representing the frequency characteristics of the first noise and according to the actual rotational speed of the first fan per unit time and the frequency characteristic data representing the frequency characteristics of the second noise and according to

the actual rotational speed of the second fan per unit time.

(409) Therefore, the waveform of the first noise and the waveform of the second noise can be reproduced more accurately, and in turn, the interference sound, which effectively interferes with the first noise and the second noise, can be emitted from the loudspeaker.

(410) The first noise and the second noise emitted out of the projector can therefore be effectively reduced.

(411) In the second aspect described above, the projector includes a first rotational position detection section that detects the rotational position of the first fan, a second rotational position detection section that detects the rotational position of the second fan, a first phase data storage section that stores first phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan, and a second phase data storage section that stores second phase data representing the phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan.

(412) The control section may include a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the first fan detected by the first rotational position detection section, and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the second fan detected by the second rotational position detection section, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

(413) According to the configuration described above, the phase acquisition section acquires the first phase data according to the rotational position of the first fan detected by the first rotational position detection section and the second phase data according to the rotational position of the second fan detected by the second rotational position detection section.

(414) The configuration described above, in which the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section, allows the interference sound, which can effectively reduce the first noise and the second noise, to be emitted from the loudspeaker, as in the projector according to the first aspect described above.

(415) The first noise and the second noise can therefore be effectively reduced.

(416) A projector according to a third aspect of the present disclosure includes an exterior enclosure having an intake port and a discharge port, a heat source disposed in the exterior enclosure, a first fan that causes a cooling gas to flow to one of the heat source, a second fan that has the same specifications as those of the first fan and causes the cooling gas to flow to the heat source, a loudspeaker that is disposed between one of the two openings, the intake port and the discharge port, and one of the first and second fans, the one fan disposed in a position close to the one opening, in the channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker, a first characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with the rotational speed of the first fan per unit time, a second characteristic data storage section that stores frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas

generated by the driven second fan, and in-apparatus environmental noise in accordance with the rotational speed of the second fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(417) The control section includes a fan control section that drives the first and second fans at the same rotational speed per unit time, a characteristic acquisition section that acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time from the first characteristic data storage section and acquires the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time from the second characteristic data storage section, a waveform generation section that generates the waveform of an interference sound that interferes with the first noise and the second noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(418) According to the configuration described above, the control section allows the loudspeaker to emit the interference sound, which interferes with the first noise and the second noise to reduce the first noise and the second noise, with no need for a microphone that detects the first noise and the second noise leaking out of the exterior enclosure via the one opening, as in the projectors according to the first and second aspects described above.

(419) Since the first noise and the second noise each include the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of the noise reduced by emitting the interference sound can be expanded.

(420) Therefore, the configuration of the projector can be simplified, and the first noise and the second noise can be effectively reduced.

(421) Furthermore, since the fan control section drives the first and second fans at the same rotational speed per unit time, there is no need to detect the rotational speeds of the first and second fans per unit time.

(422) Therefore, the configuration of the projector can be simplified, and the interference sound outputting process can be simplified.

(423) In the third aspect described above, the projector may include a rotational speed detection section that detects the rotational speed of one of the first and second fans per unit time, and the characteristic acquisition section may acquire the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed detected by the rotational speed detection section and the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed detected by the rotational speed detection section.

(424) According to the configuration described above, since the first and second fans are driven at the same rotational speed per unit time, the actual rotational speeds of the first and second fans per unit time can be detected by the rotational speed detection section through detection of the rotational speed of one of the first and second fans per unit time. There is therefore no need to provide each of the first and second fans with the rotational speed detection section.

(425) The characteristic acquisition section can acquire the frequency characteristic data representing the frequency characteristics of the first noise and according to the actual rotational speed of the first fan per unit time and the frequency characteristic data representing the frequency characteristics of the second noise and according to the actual rotational speed of the second fan per unit time.

(426) Therefore, the waveform of the first noise and the waveform of the second noise can be reproduced more accurately, and the loudspeaker can in turn emit the interference sound, which

effectively interferes with the first and second noise, whereby the first noise and the second noise emitted out of the projector can be effectively reduced, as in the projector according to the second aspect described above.

(427) In the third aspect described above, the projector includes a rotational position detection section that detects the rotational position of one of the first and second fans, a first phase data storage section that stores first phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan, and a second phase data storage section that stores second phase data representing the phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan.

(428) The fan control section may drive the first and second fans in synchronization with each other in such a way that the rotational position of the first fan coincides with the rotational position of the second fan, the control section may include a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the one fan and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the one fan, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

(429) According to the configuration described above, the fan control section drives the first and second fans in synchronization with each other in such a way that the rotational position of the first fan coincides with the rotational position of the second fan. The rotational positions of the first and second fans can each be acquired by the rotational position detection section through detection of the rotational position of one of the first and second fans.

(430) Therefore, the configuration of the projector can be simplified, and the interference sound outputting process can be simplified.

(431) Thereafter, the phase acquisition section acquires the first phase data according to the rotational position of the first fan and the second phase data according to the rotational position of the second fan, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise, the frequency characteristic data on the frequency characteristics of the second noise, the first phase data, and the second phase data.

(432) The interference sound that can effectively reduce the first noise and the second noise can thus be emitted from the loudspeaker, as in the projector according to the second embodiment described above. The first noise and the second noise can therefore be effectively reduced.

(433) In the second and third aspects described above, the frequency characteristic data on the frequency characteristics of the first noise may be data representing the features of at least one of the plurality of frequency components contained in the first noise, and the frequency characteristic data on the frequency characteristics of the second noise may be data representing the features of at least one of the plurality of frequency components contained in the second noise.

(434) According to the configuration described above, the interference sound, which can effectively reduce at least one frequency component contained in the first noise and the second noise, can be emitted from the loudspeaker, as in the projector according to the first aspect described above.

(435) The first noise and the second noise can therefore be effectively reduced.

(436) In the second and third aspects described above, the heat source may include a first heat source and a second heat source, the first fan may cause the cooling gas to flow to the first heat source, and the second fan may cause the cooling gas to flow to the second heat source.

(437) According to the configuration described above, in which the cooling gas flows to each of the

first and second heat sources, the first and second heat sources can be cooled efficiently.

(438) A cooling apparatus according to a fourth aspect of the present disclosure includes a fan that causes a cooling gas to flow to a heat source, a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker, a characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on the flow of the cooling gas generated by the driven fan, and environmental noise in accordance with the rotational speed of the fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(439) The control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates the waveform of an interference sound that reduces the first noise based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(440) According to the configuration described above, the interference sound, which interferes with the first noise, can be emitted from the loudspeaker with no need for a microphone that detects the first noise, whereby the configuration of the projector can be simplified, and the range of reducible noise can be expanded, as in the projector according to the first aspect described above.

(441) In the fourth aspect described above, the cooling apparatus may include a rotational speed detection section that detects the rotational speed of the fan per unit time, and the characteristic acquisition section may acquire the frequency characteristic data corresponding to the rotational speed of the fan per unit time detected by the rotational speed detection section.

(442) According to the configuration described above, the characteristic acquisition section can acquire the frequency characteristic data corresponding to the actual rotational speed of the fan per unit time, can therefore more accurately reproduce the waveform of the first noise, and in turn allows the interference sound, which effectively interferes with the first noise, to emit from the loudspeaker, as in the projector according to the first aspect described above.

(443) In the fourth aspect described above, the cooling apparatus includes a rotational position detection section that detects the rotational position of the fan, and a phase data storage section that stores phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the fan per unit time and the rotational position of the fan.

(444) The control section may include a phase acquisition section that acquires from the phase data storage section the phase data corresponding to the rotational position of the fan detected by the rotational position detection section, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section.

(445) The configuration described above, in which the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section, allows the interference sound, which can effectively reduce the first noise, to be emitted from the loudspeaker, as in the projector according to the first aspect described above.

(446) In the fourth aspect described above, the frequency characteristic data described above may be data representing the features of at least one of the plurality of frequency components contained in the first noise described above.

(447) According to the configuration described above, the interference sound, which can effectively reduce at least one frequency component contained in the first noise, can be emitted from the loudspeaker, whereby the first noise can be effectively reduced, as in the projectors according to the first aspect described above.

(448) A cooling apparatus according to a fifth aspect of the present disclosure includes a first fan

and a second fan that cause a cooling gas to flow to a heat source, a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker, a first characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and environmental noise in accordance with the rotational speed of the first fan per unit time, a second characteristic data storage section that stores frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas generated by the driven second fan, and environmental noise in accordance with the rotational speed of the second fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(449) The control section includes a characteristic acquisition section that acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time from the first characteristic data storage section and acquires the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time from the second characteristic data storage section, a waveform generation section that generates the waveform of interference sound that interferes with the first noise and the second noise based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(450) According to the configuration described above, the control section allows the interference sound, which interferes with the first noise and the second noise, to be emitted from the loudspeaker with no need for a microphone that detects the first noise and the second noise, whereby the configuration of the projector can be simplified, as in the projector according to the second aspect described above.

(451) In addition, since the first noise and the second noise each contain the discrete frequency noise, the broadband noise, and the in-apparatus environmental noise, the range of noise reduced by emitting the interference noise can be expanded.

(452) In the fifth aspect described above, the cooling apparatus includes a first rotational speed detection section that detects the rotational speed of the first fan per unit time, and a second rotational speed detection section that detects the rotational speed of the second fan per unit time.

(453) The characteristic acquisition section may acquire from the first characteristic data storage section the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time detected by the first rotational speed detection section and acquire from the second characteristic data storage section the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time detected by the second rotational speed detection section.

(454) According to the configuration described above, the characteristic acquisition section can acquire the frequency characteristic data representing the frequency characteristics of the first noise and according to the actual rotational speed of the first fan per unit time and the frequency characteristic data representing the frequency characteristics of the second noise and according to the actual rotational speed of the second fan per unit time, whereby the first noise and the second noise can be effectively reduced, as in the projector according to the second aspect described above.

(455) In the fifth aspect described above, the cooling apparatus includes a first rotational position detection section that detects the rotational position of the first fan, a second rotational position detection section that detects the rotational position of the second fan, a first phase data storage

section that stores first phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan, and a second phase data storage section that stores second phase data representing the phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan.

(456) The control section may include a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the first fan detected by the first rotational position detection section, and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the second fan detected by the second rotational position detection section, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

(457) The configuration described above, in which the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section, allows effective reduction in the first noise and the second noise, as in the projector according to the second aspect described above.

(458) A cooling apparatus according to a sixth aspect of the present disclosure includes a first fan that causes a cooling gas to flow to a heat source, a second fan that has the same specifications as those of the first fan and causes the cooling gas to flow to the heat source, a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker, a first characteristic data storage section that stores frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and environmental noise in accordance with the rotational speed of the first fan per unit time, a second characteristic data storage section that stores frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas generated by the driven second fan, and environmental noise in accordance with the rotational speed of the second fan per unit time, and a control section that generates the drive signal to be outputted to the loudspeaker.

(459) The control section includes a fan control section that drives the first and second fans at the same rotational speed per unit time, a characteristic acquisition section that acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time from the first characteristic data storage section and acquires the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time from the second characteristic data storage section, a waveform generation section that generates the waveform of interference sound that interferes with the first noise and the second noise based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

(460) According to the configuration described above, the control section allows the interference sound, which interferes with the first noise and the second noise, to be emitted from the loudspeaker with no need for a microphone that detects the first noise and the second noise, and

can expand the range of the noise reduced by emitting the interference sound, as in the projector according to the third aspect described above.

(461) Furthermore, since the fan control section drives the first and second fans at the same rotational speed per unit time, there is no need to detect the rotational speeds of the first and second fans per unit time.

(462) Therefore, the configuration of the projector can be simplified, and the interference sound outputting process can be simplified.

(463) In the sixth aspect described above, the cooling apparatus may include a rotational speed detection section that detects the rotational speed of one of the first and second fans per unit time, and the characteristic acquisition section may acquire the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed detected by the rotational speed detection section and the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed detected by the rotational speed detection section.

(464) According to the configuration described above, the first and second fans do not each need to be provided with the rotational speed detection section, as in the projector according to the third aspect described above. In addition, the waveform of the first noise and the waveform of the second noise can be reproduced more accurately, and in turn, the interference sound, which effectively interferes with the first noise and the second noise, can be emitted from the loudspeaker.

(465) In the sixth aspect described above, the cooling apparatus includes a rotational position detection section that detects the rotational position of one of the first and second fans, a first phase data storage section that stores first phase data representing the phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan, and a second phase data storage section that stores second phase data representing the phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan.

(466) The fan control section may drive the first and second fans in synchronization with each other in such a way that the rotational position of the first fan coincides with the rotational position of the second fan, the control section may include a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the one fan and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the one fan, and the waveform generation section may generate the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

(467) According to the configuration described above, the rotational position detection section can acquire the rotational positions of the first and second fans by detecting the rotational position of one of the first and second fans, whereby the configuration of the projector can be simplified, and the interference sound outputting process can be simplified, as in the projector according to third aspect described above.

(468) The waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise, the frequency characteristic data on the frequency characteristics of the second noise, the first phase data, and the second phase data, whereby the interference sound, which can effectively reduce the first noise and the second noise, can be emitted from the loudspeaker.

(469) In the fifth and sixth aspects described above, the frequency characteristic data on the frequency characteristics of the first noise may be data representing the features of at least one of the plurality of frequency components contained in the first noise, and the frequency characteristic

data on the frequency characteristics of the second noise may be data representing the features of at least one of the plurality of frequency components contained in the second noise.

(470) According to the configuration described above, the interference sound, which can effectively reduce at least one frequency component contained in the first noise and the second noise, can be emitted from the loudspeaker, as in the projectors according to the second and third aspects described above. The first noise and the second noise can therefore be effectively reduced.

(471) In the fifth and sixth aspects described above, the heat source may include a first heat source and a second heat source, the first fan may cause the cooling gas to flow to the first heat source, and the second fan may cause the cooling gas to flow to the second heat source.

(472) According to the configuration described above, the first and second heat sources can be cooled efficiently, as in the projectors according to the second and third aspects described above.

(473) A control method according to a seventh aspect of the present disclosure is a control method executed by an electronic instrument including a fan that causes a cooling gas to flow to a heat source, and a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker.

(474) The method includes acquiring frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on the flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with the rotational speed of the fan per unit time, generating the waveform of interference sound that interferes with the first noise leaking out of the electronic instrument based on the acquired frequency characteristic data, and outputting the drive signal based on the generated waveform of the interference sound to the loudspeaker.

(475) According to the configuration described above, the same effects as those provided by the projector according to the first aspect described above can be provided by executing the control method according to the seventh aspect described above.

(476) A control method according to an eighth aspect of the present disclosure is a control method executed by an electronic instrument including a first fan and a second fan that cause a cooling gas to flow to a heat source, and a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker.

(477) The method includes acquiring frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with the rotational speed of the first fan per unit time, acquiring frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas generated by the driven second fan, and in-apparatus environmental noise in accordance with the rotational speed of the second fan per unit time, generating the waveform of interference sound that interferes with the first noise and the second noise based on the acquired frequency characteristic data on the frequency characteristics of the first noise and the acquired frequency characteristic data on the frequency characteristics of the second noise, and outputting the drive signal based on the generated waveform of the interference sound to the loudspeaker.

(478) According to the configuration described above, the same effects as those provided by the projector according to the second aspect described above can be provided by executing the control method according to the eighth aspect described above.

(479) A control method according to a ninth aspect of the present disclosure is a control method executed by an electronic instrument including a first fan that causes a cooling gas to flow to a heat source, a second fan that has the same specifications as those of the first fan and causes the cooling gas to flow to the heat source, and a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker.

(480) The method includes driving the first and second fans at the same rotational speed per unit

time, acquiring frequency characteristic data on the frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on the flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with the rotational speed of the first fan per unit time, acquiring frequency characteristic data on the frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on the flow of the cooling gas generated by the driven second fan, and in-apparatus environmental noise in accordance with the rotational speed of the second fan per unit time, generating the waveform of interference sound that interferes with the first noise and the second noise based on the acquired frequency characteristic data on the frequency characteristics of the first noise and the acquired frequency characteristic data on the frequency characteristics of the second noise, and outputting the drive signal based on the generated waveform of the interference sound to the loudspeaker.

(481) According to the configuration described above, the same effects as those provided by the projector according to the third aspect described above can be provided by executing the control method according to the ninth aspect described above.

Claims

1. A projector comprising: an exterior enclosure having an intake port and a discharge port; a heat source disposed in the exterior enclosure; a fan that causes a cooling gas to flow to the heat source; a loudspeaker that is disposed between one of two openings, the intake port and the discharge port, and the fan in a channel of the cooling gas and outputs a sound wave according to a drive signal inputted to the loudspeaker; a characteristic data storage section that stores frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on a flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with a rotational speed of the fan per unit time; and a control section that generates the drive signal to be outputted to the loudspeaker, wherein the control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates a waveform of an interference sound that interferes with the first noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

2. The projector according to claim 1, further comprising a rotational speed detection section that detects the rotational speed of the fan per unit time, wherein the characteristic acquisition section acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time detected by the rotational speed detection section.

3. The projector according to claim 2, further comprising: a rotational position detection section that detects a rotational position of the fan; and a phase data storage section that stores phase data representing phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the fan per unit time and the rotational position of the fan, wherein the control section includes a phase acquisition section that acquires from the phase data storage section the phase data corresponding to the rotational position of the fan detected by the rotational position detection section, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section.

4. The projector according to claim 1, wherein the frequency characteristic data is data representing features of at least one of the plurality of frequency components contained in the first noise.

5. The projector according to claim 1, wherein the fan includes a first fan and a second fan, and the

loudspeaker is disposed between one of the two openings, the intake port and the discharge port, and one of the first and second fans, the one fan disposed in a position close to the one opening, in the channel of the cooling gas, the characteristic data storage section includes a first characteristic data storage section that stores frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on a flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with a rotational speed of the first fan per unit time, and a second characteristic data storage section that stores frequency characteristic data on frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on a flow of the cooling gas generated by the driven second fan, and in-apparatus environmental noise in accordance with a rotational speed of the second fan per unit time, the characteristic acquisition section acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time from the first characteristic data storage section and acquires the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time from the second characteristic data storage section, and the waveform generation section generates a waveform of an interference sound that interferes with the first noise and the second noise leaking out of the exterior enclosure via the one opening based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section.

6. The projector according to claim 5, further comprising: a first rotational speed detection section that detects a rotational speed of the first fan per unit time; and a second rotational speed detection section that detects the rotational speed of the second fan per unit time; and wherein the characteristic acquisition section acquires from the first characteristic data storage section the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed of the first fan per unit time detected by the first rotational speed detection section and acquires from the second characteristic data storage section the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed of the second fan per unit time detected by the second rotational speed detection section.

7. The projector according to claim 6, further comprising: a first rotational position detection section that detects a rotational position of the first fan; a second rotational position detection section that detects a rotational position of the second fan; a first phase data storage section that stores first phase data representing phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan; and a second phase data storage section that stores second phase data representing phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan, wherein the control section includes a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the first fan detected by the first rotational position detection section, and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the second fan detected by the second rotational position detection section, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

8. The projector according to claim 5, wherein the second fan and the first fan have the same

specifications, and the control section includes a fan control section that drives the first and second fans at a same rotational speed per unit time.

9. The projector according to claim 8, further comprising a rotational speed detection section that detects the rotational speed of one of the first and second fans per unit time, wherein the characteristic acquisition section acquires the frequency characteristic data representing the frequency characteristics of the first noise and corresponding to the rotational speed detected by the rotational speed detection section and the frequency characteristic data representing the frequency characteristics of the second noise and corresponding to the rotational speed detected by the rotational speed detection section.

10. The projector according to claim 9, further comprising: a rotational position detection section that detects a rotational position of one of the first and second fans; a first phase data storage section that stores first phase data representing phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the first fan per unit time and the rotational position of the first fan; and a second phase data storage section that stores second phase data representing phases of a plurality of frequency components contained in the second noise in accordance with the rotational speed of the second fan per unit time and the rotational position of the second fan, wherein the fan control section drives the first and second fans in synchronization with each other in such a way that the rotational position of the first fan coincides with the rotational position of the second fan, the control section includes a phase acquisition section that acquires from the first phase data storage section the first phase data corresponding to the rotational position of the one fan and acquires from the second phase data storage section the second phase data corresponding to the rotational position of the one fan, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data on the frequency characteristics of the first noise and the frequency characteristic data on the frequency characteristics of the second noise acquired by the characteristic acquisition section and the first phase data and the second phase data acquired by the phase acquisition section.

11. The projector according to claim 5, wherein the frequency characteristic data on the frequency characteristics of the first noise is data representing features of at least one of the plurality of frequency components contained in the first noise, and the frequency characteristic data on the frequency characteristics of the second noise is data representing features of at least one of the plurality of frequency components contained in the second noise.

12. The projector according to claim 5, wherein the heat source includes a first heat source and a second heat source, the first fan causes the cooling gas to flow to the first heat source, and the second fan causes the cooling gas to flow to the second heat source.

13. A cooling apparatus comprising: a fan that causes a cooling gas to flow to a heat source; a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker; a characteristic data storage section that stores frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on a flow of the cooling gas generated by the driven fan, and environmental noise in accordance with a rotational speed of the fan per unit time; and a control section that generates the drive signal to be outputted to the loudspeaker, wherein the control section includes a characteristic acquisition section that acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time from the characteristic data storage section, a waveform generation section that generates a waveform of an interference sound that reduces the first noise based on the frequency characteristic data acquired by the characteristic acquisition section, and a signal output section that outputs the drive signal based on the waveform generated by the waveform generation section to the loudspeaker.

14. The cooling apparatus according to claim 13, further comprising a rotational speed detection section that detects the rotational speed of the fan per unit time, wherein the characteristic

acquisition section acquires the frequency characteristic data corresponding to the rotational speed of the fan per unit time detected by the rotational speed detection section.

15. The cooling apparatus according to claim 14, further comprising: a rotational position detection section that detects a rotational position of the fan; and a phase data storage section that stores phase data representing phases of a plurality of frequency components contained in the first noise in accordance with the rotational speed of the fan per unit time and the rotational position of the fan, wherein the control section includes a phase acquisition section that acquires from the phase data storage section the phase data corresponding to the rotational position of the fan detected by the rotational position detection section, and the waveform generation section generates the waveform of the interference sound based on the frequency characteristic data acquired by the characteristic acquisition section and the phase data acquired by the phase acquisition section.

16. The cooling apparatus according to claim 13, wherein the frequency characteristic data is data representing features of at least one of the plurality of frequency components contained in the first noise.

17. A control method executed by an electronic instrument including a fan that causes a cooling gas to flow to a heat source and a loudspeaker that outputs a sound wave according to a drive signal inputted to the loudspeaker, the method comprising: acquiring frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven fan, broadband noise based on a flow of the cooling gas generated by the driven fan, and in-apparatus environmental noise in accordance with a rotational speed of the fan per unit time; generating a waveform of interference sound that interferes with the first noise leaking out of the electronic instrument based on the acquired frequency characteristic data; and outputting the drive signal based on the generated waveform of the interference sound to the loudspeaker.

18. The control method according to claim 17, wherein the fan includes a first fan and a second fan, and the method comprising: acquiring frequency characteristic data on frequency characteristics of first noise containing discrete frequency noise produced by the driven first fan, broadband noise based on a flow of the cooling gas generated by the driven first fan, and in-apparatus environmental noise in accordance with a rotational speed of the first fan per unit time; acquiring frequency characteristic data on frequency characteristics of second noise containing discrete frequency noise produced by the driven second fan, broadband noise based on a flow of the cooling gas generated by the driven second fan, and in-apparatus environmental noise in accordance with a rotational speed of the second fan per unit time; and generating a waveform of interference sound that interferes with the first noise and the second noise based on the acquired frequency characteristic data on the frequency characteristics of the first noise and the acquired frequency characteristic data on the frequency characteristics of the second noise.

19. The control method according to claim 18, wherein the second fan and the first fan have the same specifications, and the method comprising driving the first and second fans at a same rotational speed per unit time.
