

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414744
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yamamoto; Junya et al.

Imaging position correction application introduction support system, and imaging position correction application introduction support method

Abstract

An imaging position correction application introduction support system is provided with a storage unit and a display unit. The imaging position correction application introduction support system is configured to cause the storage unit to store at least one of the number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application, as the tentative use information on when the imaging position correction application is tentatively used. The display unit displays the information based on the tentative use information.

Inventors:	Yamamoto; Junya (Kyoto, JP), Okumura; Hiroshi (Kyoto, JP)
Applicant:	Shimadzu Corporation (Kyoto, JP)
Family ID:	1000008821908
Assignee:	SHIMADZU CORPORATION (Kyoto-shi, JP)
Appl. No.:	18/090829
Filed:	December 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230277142 A1	Sep. 07, 2023

Foreign Application Priority Data

JP	2022-031745	Mar. 02, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: **A61B6/04** (20060101); **A61B6/00** (20060101); **G06T7/00** (20170101)

U.S. Cl.:

CPC **A61B6/0492** (20130101); **A61B6/5205** (20130101); **G06T7/0012** (20130101);
G06T2207/10116 (20130101); G06T2207/30008 (20130101)

Field of Classification Search

CPC: A61B (6/032); A61B (6/587); A61B (6/03); A61B (6/02); A61B (6/027); A61B (6/04);
A61B (6/5235); A61B (6/5211); A61B (6/584); A61B (6/547); A61B (5/70); A61N
(5/1049); A61N (5/1048); A61N (2005/1052); A61N (2005/1063)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0256134	12/2017	Nakamura	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004313576	12/2003	JP	N/A
2018-143699	12/2017	JP	N/A

Primary Examiner: Wong; Don K

Attorney, Agent or Firm: Muir Patent Law, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The related application number JP2022-031745, entitled “Imaging Position Correction Application Introduction Support System and Imaging Position Correction Application Introduction Support Method,” filed on Mar. 2, 2022, Junya Yamamoto, Hiroshi Okumura, upon which this patent application is based is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

(2) The present invention relates to an imaging position correction application introduction support system and an imaging position correction application introduction support method.

Description of the Related Art

(3) Conventionally, there is known an imaging position correction application for easily positioning a radiation irradiation device of an X-ray imaging when capturing an X-ray image. Such an application is disclosed in, for example, Japanese Unexamined Patent Application Publication No. 2018-143699.

(4) Japanese Unexamined Patent Application Publication No. 2018-143699 described above discloses an imaging position correction application configured to calculate a correction amount for

a user to correct a position of a radiation irradiation device of an X-ray imaging device to a position where an imaging target appropriately appears and notify the calculated correction amount, when capturing an X-ray image.

(5) Further, although not described in the above-described Japanese Unexamined Patent Application Publication No. 2018-143699, various imaging position correction applications corresponding to imaging sites are provided for an X-ray imaging system (X-ray imaging apparatus).

(6) Here, although a user of an X-ray imaging system (X-ray imaging apparatus) considers introducing an imaging position correction application with a high need from among various imaging position correction applications, it is difficult for a provider or a user of the imaging position correction application to recognize in advance which imaging position correction application should be introduced prior to the actual introduction of the imaging position correction application. In such a case, even if it is an imaging position correction application with a high need for introduction for a user, the actual introduction may be deferred because of the reason that the provider or the user of the imaging position correction application couldn't recognize the need for the imaging position correction application prior to the actual introduction. Under the circumstance, there is a demand for an imaging position correction application introduction support system and an imaging position correction application introduction support method capable for a provider or a user of the imaging position correction application to recognize an imaging position correction application with a high need for introduction for a user prior to the actual introduction.

SUMMARY OF THE INVENTION

(7) The present invention has been made to solve the above-described problems. One object of the present invention is to provide an imaging position correction application introduction support system and an imaging position correction application introduction support method capable for a provider or user of an imaging position correction application to recognize an imaging position correction application with a high need for introduction for the user prior to actual introduction.

(8) An imaging position correction application introduction support system according to a first aspect of the present invention, includes: a storage unit configured to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively used as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display unit configured to display information based on the tentative use information stored in the storage unit, wherein the storage unit is configured to store, as the tentative use information, at least one of a number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

(9) An imaging position correction application introduction support method according to a second aspect of the present invention, includes: a storage step configured to cause the storage unit to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively introduced as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display step configured to display information based on the tentative use information stored in the storage unit; wherein the storage step includes a step configured to cause the storage to store, as the tentative use information, at least one of the number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

(10) In the imaging position correction application introduction support system according to the first aspect of the present invention and the imaging position correction application introduction support method according to the second aspect of the present invention, as the information used to recommend actual introduction of an imaging position correction application tentatively introduced, tentative use information on when the imaging position correction application was tentatively used is stored, and information based on the tentative use information is displayed. Then, as the tentative use information, at least one of the number of times the imaging position correction application was used and the degree of correction when the relative position of the X-ray irradiation unit with respect to a specific site of the subject was corrected by the imaging position correction application is stored in a storage unit. With this, in a case where the number of times the imaging position correction application was used is stored as the tentative use information, it is possible for the provider or the user of the imaging position correction application to recognize the imaging position correction application with a high use frequency when tentatively introduced and high possibility when actually introduced, by visually recognizing the information based on the tentative use information. As a result, it is possible to provide an imaging position correction application introduction support system and an imaging position correction application introduction support method capable for the provider or the user of the imaging position correction application to recognize the imaging position correction application with a high need for introduction for the user prior to the actual introduction. Further, in a case where the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application is stored, as the tentative use information, the provider or the user of the imaging position correction application can recognize an imaging position correction application with a high degree of correction when tentatively introduced and with a significant effect when introduced actually, by visually recognizing the information based on the tentative use information. This enables to provide an imaging position correction application introduction support system and an imaging position correction application introduction support method capable for the provider or the user of the imaging position correction application to recognize the imaging position correction application with a high need for introduction for the user. As a result, it is possible to provide an imaging position correction application introduction support system and an imaging position correction application introduction support method capable for the provider or the user of the imaging position correction application to recognize an imaging position correction application with a high need for introduction for the user prior to the actual introduction.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The preferred embodiments of the present invention are shown by way of example, and not limitation, in the accompanying figures.
- (2) FIG. 1 is a schematic diagram showing an entire configuration of an imaging position correction application introduction support system according to a first embodiment of the present invention.
- (3) FIG. 2 is a schematic diagram showing a configuration of an X-ray imaging apparatus according to a first embodiment.
- (4) FIG. 3 is a diagram showing one example of the processing performed by an imaging position correction application.
- (5) FIG. 4 is a diagram showing one example of recommendation information displayed on a display unit of a tablet terminal in the first embodiment.
- (6) FIG. 5 is a flowchart showing one example of the processing performed by an imaging position correction application introduction support system.

(7) FIG. 6 is a schematic diagram showing an entire configuration of an imaging position correction application introduction support system according to a second embodiment of the present invention.

(8) FIG. 7 is a diagram showing one example of tentative use information displayed on a display unit.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(9) In the following paragraphs, some preferred embodiments of the invention will be described by way of example and not limitation. It should be understood based on this disclosure that various other modifications can be made by those skilled in the art based on these illustrated embodiments.

(10) Hereinafter, some embodiments in which the present invention is embodied will be described with reference to the attached drawings.

First Embodiment

(11) A configuration of an imaging position correction application introduction support system **100** according to a first embodiment will be described with reference to FIG. 1 to FIG. 4.

(12) (General Configuration of System)

(13) As shown in FIG. 1, the imaging position correction application introduction support system **100** is provided with a server **2** connected to the X-ray imaging apparatus **1** via a network **101**, and a tablet terminal **3**. The imaging position correction application introduction support system **100** is a system used to consider actual introduction of an imaging position correction application **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**), which will be described later.

(14) The X-ray imaging apparatus **1** is a device in which imaging position correction applications **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**) are tentatively introduced, and an X-ray image **4** (see FIG. 3) of a subject **800** (see FIG. 2) is captured.

(15) As shown in FIG. 1, the X-ray imaging apparatus **1** is provided with an imaging apparatus main body **11** and a PC12. Note that the PC12 is a console PC (Personal Computer) used for manipulation at the time of imaging by the imaging apparatus main body **11** and an analysis of the captured X-ray image **4**, and the like.

(16) The imaging apparatus main body **11** is provided with an X-ray irradiation unit **111**, an X-ray detection unit **112**, an irradiation unit moving mechanism **113**, and an apparatus control unit **114**.

(17) The X-ray irradiation unit **111** is configured to irradiate the subject **800** with X-rays. The X-ray irradiation unit **111** is provided with an X-ray source (not shown) for irradiating the subject **800** with X-rays and a collimator (not shown) for adjusting the irradiation range of the X-rays.

(18) The X-ray detection unit **112** is configured to detect the X-rays emitted from the X-ray irradiation unit **111** and transmitted through the subject **800**. The X-ray detection unit **112** is, for example, an FPD (Flat Panel Detector) and detects the X-rays transmitted through the subject **800**.

(19) The irradiation unit moving mechanism **113** is configured to change the relative position of the X-ray irradiation unit **111** with respect to the subject **800** by moving the X-ray irradiation unit **111**. In the X-ray imaging apparatus **1**, the X-ray irradiation unit **111** is supported by being suspended from the ceiling by the irradiation unit moving mechanism **113**. The X-ray irradiation unit **111** is movably supported in an imaging room by the irradiation unit moving mechanism **113**. The irradiation unit moving mechanism **113** is provided with a motor and an electromagnetic brake (not shown) corresponding to each of the X-direction, the Y-direction, and the Z-direction. The X-ray irradiation unit **111** is configured to be movable by the irradiation unit moving mechanism **113** in each of the X-direction, the Y-direction, and the Z-direction. Further, the irradiation unit moving mechanism **113** is provided with an encoder (not shown) used to control the movements of the X-ray irradiation unit **111** corresponding to each of the X-direction, the Y-direction, and the Z-direction. Further, the irradiation unit moving mechanism **113** is provided with a potentiometer (not shown) corresponding to each of the X-direction, the Y-direction, and the Z-direction and is configured to be able to detect the position of the X-ray irradiation unit **111** in each of the X-

direction, the Y-direction, and the Z-direction.

(20) The apparatus control unit **114** includes a processor, such as, e.g., a CPU (Central Processing Unit) or an FPGA (Field-Programmable Gate Array). The apparatus control unit **114** is configured to control the entire imaging apparatus main body **11**. Specifically, the apparatus control unit **114** is configured to perform control of X-ray irradiation by the X-ray irradiation unit **111**, such as, e.g., starting and stopping the X-ray irradiation, control of the change of the X-ray irradiation range by the X-ray irradiation unit **111**, control of the detection by the X-ray detection unit **112**, control of the movements of the X-ray irradiation unit **111** by the irradiation unit moving mechanism **113**, control of the movements of the top board, and the like.

(21) Further, the apparatus control unit **114** is configured to receive the detection signal of encoders and potentiometers (not shown) included in the irradiation unit moving mechanism **113**. Further, the apparatus control unit **114** is configured to control a motor (not shown) and an electromagnetic brake (not shown) equipped in the irradiation unit moving mechanism **113**.

(22) The PC12 is provided with a processing unit **121**, a storage unit **122**, a display unit **123**, an operation unit **124**, and a communication unit **125**. The PC12 is communicatively coupled to the imaging apparatus main body **11** (apparatus control unit **114**). Note that the PC12 may be integrally formed with the apparatus control unit **114**.

(23) The processing unit **121** includes a CPU, a GPU (Graphics Processing Unit), an ROM (Read Only Memory), and a RAM (Random Access Memory).

(24) The storage unit **122** includes a storage device (internal storage), such as, e.g., an HDD (Hard Disk Drive) and an SSD (Solid State Drive).

(25) The display unit **123** includes, for example, a liquid crystal display or an organic EL display. The operation unit **124** is a user interface for operating the PC12. The operation unit **124** includes, for example, a keyboard, a mouse, and the like. The display unit **123** may be provided with a touch panel as the operation unit **124**.

(26) The communication unit **125** is a communication interface. The PC **12** is configured to transmit tentative use information **23a** to the server **2** by the communication unit **125** via the network **101**.

(27) To the X-ray imaging apparatus **1**, imaging position correction applications **120a**, **120b**, **120c**, and **120d** are tentatively introduced as imaging position correction applications **120** which are application software for correcting the relative position of the X-ray irradiation unit **111** for emitting X-ray with respect to a specific site of a subject **800** when capturing an X-ray image **4** of the specific site of the subject **800**. Note that the imaging position correction applications **120a**, **120b**, **120c**, and **120d** are examples of “a plurality of imaging position correction applications” as recited in claims.

(28) Further, the imaging position correction application **120a** is an imaging position correction application **120** for correcting the relative position of the X-ray irradiation unit **111** with respect to a knee of the subject **800** when capturing an X-ray image **4** of a knee (knee joint) of the subject **800**. The imaging position correction application **120a** is one example of the “knee imaging position correction application” recited in claims.

(29) The imaging position correction applications **120b**, **120c**, and **120d** each are, for example, an imaging position correction application **120** for correcting the relative position of the X-ray irradiation unit **111** with respect to each imaging target when capturing an X-ray image **4** of a chest, an elbow, and a waist, respectively.

(30) The server **2** is configured to be connected to the X-ray imaging apparatus **1** via the network **101**. The server **2** includes a communication unit **21**, an acquisition unit **22**, and a storage unit **23**. Note that the acquisition unit **22** and the storage unit **23** of the server **2** are examples of the “acquisition unit” and the “storage unit” recited in claims, respectively.

(31) The server **2** is configured to cause the storage unit **23** to store the tentative use information **23a** acquired from the X-ray imaging apparatus **1** via the network **101** and acquire recommendation

information **23b** for recommending the introduction of the imaging position correction application **120** to the user, based on the tentative use information **23a** stored in the storage unit **23**. Further, the recommendation information **23b** is stored in the storage unit **23**.

(32) The communication unit **21** of the server **2** is a communication interface. The acquisition unit **22** of the server **2** includes a processor, such as, e.g., a CPU, and a memory. The server **2** (acquisition unit **22**) acquires the tentative use information **23a** from the X-ray imaging apparatus **1** via the network **101** by the communication unit **21** and stores it in the storage unit **23**.

(33) The storage unit **23** of the server **2** includes a storage device (internal storage), such as, e.g., an HDD and an SSD. The storage unit **23** of the server **2** stores tentative use information **23a** on when each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was tentatively used, as information used to recommend the actual introduction of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** tentatively introduced.

(34) Note that the tentative use information **23a** is stored in the storage unit **122** of the PC **12** temporarily or for a long period of time when each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** is tentatively used, in the X-ray imaging apparatus **1**, and is stored in the storage unit **23** of the server **2** by being transmitted to the server **2** via the network **101**.

(35) The tentative use information **23a** is stored, for example, as log information on each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**. In this case, the tentative use information **23a** is stored in the storage unit **122** of the PC temporarily or for a long period of time by the imaging position correction applications **120a**, **120b**, **120c**, and **120d**, respectively. Alternatively, each tentative use information **23a** of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** may be collectively managed and stored by a dedicated application for storing the tentative use information **23a**.

(36) Further, the tentative use information **23a** is stored in the storage unit **23** of the server **2** in real time, for example, during the use of each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**. Further, tentative use information **23a** stored in the X-ray imaging apparatus **1** (storage unit **122**) may be transmitted to the server **2** via the network **101** and stored in the storage unit **23** of the server **2** when each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** is started or terminated.

(37) Further, in a case where the usage fee or the purchase fee of the imaging position correction application **120** is determined depending on the number of available functions included in the imaging position correction application **120**, the extra cost can be reduced by limiting (disabling) less needed functions. Therefore, in a case where each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** has a plurality of correction functions, the imaging position correction application introduction support system **100** is configured to store tentative use information **23a** (the number of uses and the degree of correction) for each correction function. In this way, the provider or the user of the imaging position correction application **120** can consider the actual introduction of the imaging position correction application **120** not only in the unit of the imaging position correction application **120** but also in the correcting function unit of the imaging position correction application **120**.

(38) Further, in a case where there is a mistake in imaging, such as, e.g., a mistake in setting the imaging site and a mistake in setting the imaging direction, when using each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**, the imaging position correction application introduction support system **100** may store presence or absence of the mistake in imaging, such as, e.g., the mistake in setting the imaging site and the mistake in setting the imaging direction, as the tentative use information **23a**.

(39) The imaging position correction application introduction support system **100** is configured to store, as tentative use information **23a**, the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, in the storage unit **23** of the server **2**. Further, the imaging position correction application introduction support system **100** is configured to store,

as the tentative use information **23a**, the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the subject **800** was corrected, by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**, respectively, in the storage unit **23** of the server **2**. The degree of correction to be stored as the tentative use information **23a** may be each value of the correction amount in all corrections performed within a time period during which it was tentatively introduced or within a predetermined time period, or may be a maximal value or an average value of the correction amounts of all corrections performed within a time period during which it was tentatively introduced or within a predetermined time period.

(40) That is, the storage unit **23** of the server **2** is storing, as the tentative use information **23a**, the number of times the imaging position correction application as a knee imaging position correction application **120a** was used and the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the knee of the subject **800** was corrected by the imaging position correction application **120a**.

(41) The acquisition unit **22** of the server **2** is configured to acquire the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced, as the information for recommending the actual introduction of the imaging position correction application **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**) to the user, based on the tentative use information **23a**.

(42) In the first embodiment, the acquisition unit **22** determines the imaging position correction application **120** recommended to be actually introduced, based on the magnitude of the number of times each of imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**.

(43) In other words, the acquisition unit **22** determines the imaging position correction application **120a** as the imaging position correction application **120** recommended to be actually introduced, based on the magnitude of the number of times the imaging position correction application **120a** as a knee imaging position correction application was used and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the knee of the subject **800** was corrected.

(44) And, the acquisition unit **22** is configured to acquire the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced, the recommendation information **26b** being determined based on the magnitude of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**.

(45) Further, the server **2** may be connected to a plurality of X-ray imaging apparatuses **1** via the network **101** to acquire the tentative use information **23a** from each of the plurality of X-ray imaging apparatuses **1** and acquire the recommendation information **23b** individually or collectively from each of the acquired tentative use information **23a**. Further, the server **2** may be configured to be connected to a plurality of user's X-ray imaging apparatuses **1** via the network **101** to acquire the tentative use information **23a** from each of the X-ray imaging apparatuses **1** of a plurality of users and acquire the recommendation information **23b** from each acquired tentative use information **23a** for each user.

(46) The tablet terminal **3** is provided with a communication unit **31**, a control unit **32**, and a display unit **33**. The tablet terminal **3** is, for example, a terminal owned by the provider of the imaging position correction application **120**. The tablet terminal **3** is used when the provider of the imaging position correction application **120** recommends the introduction of the imaging position correction application **120** to a user.

(47) The communication unit **31** is a communication interface. The tablet terminal **3** acquires the recommendation information **23b** from the server **2** via the network **101** by the communication unit **31**.

(48) The control unit **32** is configured to control the entire tablet terminal **3**. The control unit **32** controls the entire tablet terminal **3** based on the software installed on the terminal. Specifically, the control unit **32** is configured to perform control of communication using the communication unit **31**, control of displaying the display unit **33**, and the like.

(49) The display unit **33** is configured to display the information based on the tentative use information **23a** stored in the storage unit **23**. The display unit **33** is, for example, a touch panel display including a liquid crystal display or an organic EL display. In the first embodiment, the display unit **33** is configured to display the recommendation information **23b** as the information based on the tentative use information **23a**.

(50) (Imaging Position Correction)

(51) When capturing an X-ray image **4**, it is necessary to adjust the posture of the subject **800** and the position of the X-ray irradiation unit **111** so that the posture of the subject **800** and the position of the X-ray irradiation unit **111** are appropriate depending on the observation target site. Since the appropriate posture of the subject **800** and the appropriate position of the X-ray irradiation unit **111** differ depending on the observation target site, it is required to perform correction of the relative position of the X-ray irradiation unit **111** with respect to the observation target unit of the subject **800** by the corresponding imaging position correction application **120**.

(52) For example, in the case of imaging a knee (knee joint), the imaging position correction application **120a** is used. In the imaging position correction application **120a**, as shown in FIG. 3, the outer edge of the medial condyle and the outer edge of the lateral condyle of the femoral bone are identified (estimated) from the X-ray image **4** by the segmentation processing by a trained model. Then, based on the outer edge of the medial condyle and the outer edge of the lateral condyle identified (estimated) from the X-ray image **4**, the deviation between the outer edge of the medial condyle and the outer edge of the lateral condyle of the femoral bone (the deviation amount and the deviation direction) is calculated. Note that the X-ray image **4** used for calculating the deviation may be an image captured with substantially the same radiation amount as an image used for the actual diagnosis, or may be an image captured with a less radiation amount than an image used for the actual diagnosis.

(53) In the imaging position correction application **120a**, based on the calculated deviation (the deviation amount and the deviation direction) between the outer edge of the medial condyle and the outer edge of the lateral condyle, position correction information for correcting the relative position of the X-ray irradiation unit **111** with respect to the knee of the subject **800** is calculated to a position where the X-ray image **4** in which the outer edge of the medial condyle and the outer edge of the lateral condyle overlap each other can be imaged. The imaging position correction application **120a** has a function of automatically correcting the position of the X-ray irradiation unit **111** based on the calculated position correction information. With this, it is possible to capture the X-ray image **4** capable of accurately identifying diseases occurring around the knee joint, such as, e.g., disruptive bone cartilage inflammation and osteoarthritis.

(54) As described above, the correction by the imaging position correction applications **120** (the imaging position correction application **120a**, **120b**, **120c**, and **120d**) may be performed based on the X-ray image **4** or may be performed based on a camera image acquired by imaging visible light or the like. Further, the correction by the imaging position correction application **120** may be performed based on both the X-ray image **4** and the camera image acquired by imaging visible light or the like. That is, in the imaging position correction application introduction support system **100**, the imaging position correction application **120** tentatively introduced and considered for actual introduction may be an imaging position correction application **120** that performs corrections in any manner.

(55) In the imaging position correction application **120** (imaging position correction application **120a**, **120b**, **120c**, and **120d**), in a case where the relative position of the X-ray irradiation unit **111** with respect to the observation target site of the subject **800** is not appropriate or the like, it is determined that a correction by the imaging position correction application **120** is required. That is, the case where the degree of correction when performing the correction by the imaging position correction application **120** is large is considered to be a case in which the positional matching of the relative position of the X-ray irradiation unit **111** with respect to the observation target site of the subject **800** is insufficient.

(56) (Acquisition of Recommendation Information)

(57) In the first embodiment, the acquisition unit **22** is configured to, based on the magnitude of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, select an imaging position correction application **120** recommended to be actually introduced from among the imaging position correction applications **120a**, **120b**, **120c**, and **120d** and acquire the recommendation information **23b** including the information on the selected imaging position correction application **120** recommended to be actually introduced.

(58) Specifically, the acquisition unit **22** selects the imaging position correction application **120** recommended to be actually introduced, from among the imaging position correction applications **120a**, **120b**, and **120c**, based on the comparison of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used with the predetermined threshold of the number of uses, and the ranking of the imaging position correction applications **120** based on the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used. The acquisition unit **22** is configured to acquire the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced selected from among the imaging position correction applications **120a**, **120b**, **120c**, and **120d**.

(59) Note that the predetermined threshold of the number of uses may be set by the provider of the imaging position correction application introduction support system **100** or may be changed (set) according to the user's request. By setting the threshold of the number of uses, the acquisition unit **22** can exclude an imaging position correction application **120** with the number of uses less than the predetermined threshold of the number of uses from among the tentatively used imaging position correction applications **120**. The ranking based on the number of times the imaging position correction application **120** was used allows the acquisition unit **22** to acquire the priority order of the imaging position correction application **120** recommended to be actually introduced.

(60) Further, the acquisition unit **22** is configured to select an imaging position correction application **120** recommended to be actually introduced, from among the imaging position correction application **120a**, **120b**, **120c**, and **120d**, based on the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** and the predetermined threshold of the degree of correction, and acquire the recommendation information **23b** including the information on the selected imaging position correction application **120** recommended to be actually introduced.

(61) The predetermined threshold of the degree of correction may be set by the provider of the imaging position correction application introduction support system **100** or may be changed (set) according to the user's request. For example, the predetermined threshold of the degree of correction may be set according to the image (failed image) that needs to be re-taken and the reference determined by the user.

(62) In the first embodiment, as shown in FIG. 4, on the display unit **33** of the tablet terminal **3**, as the recommendation information **23b**, the application name, the number of uses, and the degree of correction of each of the imaging position correction applications **120** recommended to be actually introduced are displayed. In FIG. 4, an example is shown in which the recommendation

information **23b** in which the imaging position correction applications **120** with the higher number of uses and the higher degree of correction among the imaging position correction applications **120a**, **120b**, **120c**, and **120d** are shown as the imaging position correction applications **120** recommended to be actually introduced.

(63) Note that imaging position correction application introduction support system **100** (X-ray imaging apparatus **1**) can also display the recommendation information **23b** on the display unit **123** of the X-ray imaging apparatus **1** by transmitting the recommendation information **23b** from the server **2** to the X-ray imaging apparatus **1** via the network **101**.

(64) (Processing Flow of Imaging Position Correction Application Introduction Support System)

(65) Next, the processing flow in acquiring the tentative use information **23a** and the recommendation information **23b** by the imaging position correction application introduction support system **100** according to the first embodiment will be described with reference to FIG. 5.

(66) In Step **901**, the tentative use information **23a** is stored. In Step **901**, as the information used to recommend the actual introduction of the tentatively used imaging correction application **120**, the tentative use information **23a** acquired when the imaging position correction application **120** was tentatively used is stored in the storage unit **23**. Note that Step **901** is one example of the “storage step” recited in claims.

(67) In Step **901**, as described above, as the tentative use information **23a**, the number of times the imaging position correction application **120** was tentatively used and the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the tentatively used imaging position correction application **120** are stored in the storage unit **23**.

(68) In Step **902**, the recommendation information **23b** is acquired. In Step **902**, based on the tentative use information **23a**, as the information for recommending the actual introduction of the imaging position correction application **120** to the user, the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced is acquired by the acquisition unit **22** of the server **2**. Note that the transition from Step **901** to Step **902** may be performed after the completion of Step **901**, or when the server **2** accepts the operation for acquiring the recommendation information **23b** after completion of Step **901**, the processing step may proceed to Step **902**. Then, after completion of Step **902**, the processing step proceeds to Step **903**.

(69) In Step **903**, the recommendation information **23b** is transmitted. In Step **903**, the recommendation information **23b** acquired by the acquisition unit **22** of the server **2** in Step **902** is transmitted from the server **2** to the tablet terminal **3** via the network **101**. After completing Step **903**, the processing step proceeds to Step **904**.

(70) In Step **904**, the recommendation information **23b** is displayed. In Step **904**, as the information based on the tentative use information **23a** stored in Step **901**, the recommendation information **23b** transmitted from the server **2** in Step **903** is displayed on the display unit **33** (see FIG. 4). Note that Step **904** is one example of the “display step” recited in claims.

(71) Note that in Step **903**, it may be configured such that the recommendation information **23b** is transmitted to the X-ray imaging apparatus **1**, and in Step **904**, the recommendation information **23b** is displayed on the display unit **123** of the X-ray imaging apparatus **1**.

Effects of First Embodiment

(72) In the first embodiment, the following effects can be obtained.

(73) In the first embodiment, the information (recommendation information **23b**) based on the tentative use information **23a** is stored as the information used to recommend the actual introduction of the tentatively used imaging position correction applications **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**), and the information (recommendation information **23b**) based on the tentative use information **23a** is displayed.

(74) Then, as the tentative use information **23a**, the number of times the imaging position

correction application **120** was used, and the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the imaging position correction application **120** are stored in the storage unit **23**. With this, the number of times the imaging position correction application **120** was used is stored as the tentative use information **23a**. Therefore, the provider or the user of the imaging position correction application **120** can recognize the imaging position correction application **120** with the higher frequency of uses when tentatively introduced and the higher possibility of uses when actually introduced by visually recognizing the information (recommendation information **23b**) based on the tentative use information **23a**. As a consequence, the provider or the user of the imaging position correction application **120** can recognize the imaging position correction application **120** with a high need for introduction for the user prior to the actual introduction.

(75) Further, as the tentative use information **23a**, the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the imaging position correction application **120** is stored. Therefore, the provider or the user of the imaging position correction application **120** can recognize the imaging position correction application **120** with a higher degree of correction when tentatively introduced and a more significant effect when tentatively introduced by visually recognizing the information (recommendation information **23b**) based on tentative use information **23a**. With this, the provider or the user of the imaging position correction application **120** can recognize the imaging position correction application **120** with a high need for introduction for the user prior to the actual introduction.

(76) Consequently, the provider or the user of the imaging position correction application **120** can recognize the imaging position correction application **120** with the higher possibility of usage when actually introduced and a more significant effect when actually introduced, by visually recognizing the information (recommendation information **23b**) based on the tentative use information **23a**. This allows the provider or the user of the imaging position correction application **120** to recognize the imaging position correction application **120** with a higher need for introduction for the user prior to the actual introduction.

(77) Further, in the imaging position correction application introduction support system **100** according to the first embodiment, the following further effects can be obtained by configuring as follows.

(78) In the first embodiment, the acquisition unit **22** of the server **2** acquires, based on the tentative use information **23a**, the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced, as the information for recommending the actual introduction of the imaging position correction application **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**) for the user. This allows the provider or the user of the imaging position correction application **120** to acquire the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced, by the acquisition unit **22** of the server **2**, without carefully reviewing the tentative use information **23a**.

(79) Consequently, the provider of the imaging position correction application **120** can use the recommendation information **23b** acquired by the acquisition unit **22** of the server **2**, including the information on the imaging position correction application **120** recommended to be actually introduced, when proposing the introduction of the imaging position correction application **120** to the user. With this, as compared with a case in which the introduction of the imaging position correction application **120** is proposed to a user by using only the tentative use information **23a**, the provider can easily propose the introduction of the imaging position correction application **120** to a user.

(80) Further, the display unit **33** displays, as the information based on the tentative use information **23a**, the recommendation information **23b** including the information on the imaging position

correction applications **120** recommended to be actually introduced. With this, the user and the provider of the imaging position correction application **120** can recognize the imaging position correction application **120** with a higher need for introduction by visually recognizing the recommendation information **23b** displayed on the display unit **33**.

(81) Further, in the first embodiment, the acquisition unit **22** is configured to acquire the recommendation information **23b** including the information on the imaging position correction application **120** recommended to be actually introduced, determining the imaging position correction application **120** recommended to be actually introduced, based on the magnitude of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d**.

(82) As a result, the user and the provider of the imaging position correction application **120** can recognize the imaging position correction application **120** with a higher possibility of use when actually introduced and a higher need for introduction by the recommendation information **23b** acquired by the acquisition unit **22**, based on the magnitude of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used.

(83) Further, the user or the provider of the imaging position correction application **120** can recognize the imaging position correction application with a more significant effect when actually introduced and a higher need for introduction by the recommendation information **23b** acquired by the acquisition unit **22**, based on the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected.

(84) As a consequence, the user and the provider of the imaging position correction application **120** can recognize the imaging position correction application **120** with a higher possibility of use when actually introduced, a more significant effect when actually introduced, and a higher need for introduction, from the recommendation information **23b**.

(85) Further, in the first embodiment, the acquisition unit **22** is configured to select the imaging position correction application **120** recommended to be actually introduced from among the imaging position correction applications **120a**, **120b**, **120c**, and **120d**, based on the magnitude of the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, and acquire the recommendation information **23b** including the information on the selected imaging position correction application **120** recommended to be actually introduced.

(86) With this, the user and the provider of the imaging position correction application **120** can recognize the imaging position correction application **120** with a higher possibility of use when actually introduced and a higher need for introduction by the recommendation information **23b** acquired based on the magnitude of the number of uses by the acquisition unit **22** from among the tentatively used imaging position correction applications **120a**, **120b**, **120c** and **120d**.

(87) Further, in the first embodiment, the acquisition unit **22** is configured to acquire the recommendation information **23b** including information on the imaging position correction application **120** recommended to be actually introduced selected from among the imaging position correction applications **120a**, **120b**, **120c** and **120d**, based on the comparison between the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used and the predetermined threshold of the number of uses and the ranking of the imaging position correction applications **120** based on the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used.

(88) With this, the acquisition unit **22** can acquire the recommendation information **23b** including the information on the imaging position correction application **120** with a higher usage possibility when actually introduced and higher introduction necessity from among the tentatively used imaging position correction applications **120a**, **120b**, **120c**, and **120d**, by selecting the imaging

position correction application **120** used over a predetermined threshold of the number of uses as an imaging position correction application **120** recommended to be actually introduced.

(89) Further, by selecting the imaging position correction application **120** recommended to be actually introduced with a higher ranking based on the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, the recommendation information **23b** including the information on the imaging position correction application **120** with higher usage possibility when actually introduced and higher introduction necessity can be acquired from among the tentatively used imaging position correction applications **120a**, **120b**, **120c**, and **120d**.

(90) As a consequence, the acquisition unit **22** can acquire the recommendation information **23b** including the information on the imaging position correction application **120** used over a predetermined threshold of the number of uses with a higher ranking based on the number of uses and higher usage possibility when actually introduced, from among the tentatively used imaging position correction application **120a**, **120b**, **120c**, and **120d**.

(91) Further, in the first embodiment, the acquisition unit **22** is configured to acquire the recommendation information **23b** including the information on the selected imaging position correction application **120** recommended to be actually introduced, from among the imaging position correction applications **120a**, **120b**, **120c**, and **120d**, based on the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** and the predetermined threshold of the degree of correction.

(92) With this, the acquisition unit **22** can acquire the recommendation information **23b** including the imaging position correction application **120** with a more significant effect when actually introduced and higher introduction necessity, from among the tentatively used imaging position correction applications **120a**, **120b**, **120c**, and **120d**, by selecting the imaging position correction application **120** that performs correction over a predetermined threshold of the degree of correction as an imaging position correction application **120** recommended to be actually introduced.

(93) Further, in the first embodiment, the acquisition unit **22** determines the imaging position correction application **120a** as an imaging position correction application **120** recommended to be actually introduced, based on the magnitude of the number of times the imaging position correction application **120a** as a knee imaging position correction application was used and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the knee of the subject **800** was corrected by the imaging position correction application **120**. With this, in a case where the imaging position correction application **120a** that is the tentatively used imaging position correction application is higher in the frequency of use when actually introduced and higher in possibility of uses when actually introduced, the information on the imaging position correction application **120a** is included in the recommendation information **23b**.

(94) Further, in a case where the imaging position correction application **120a** that is the tentatively introduced knee imaging position correction application was significant in the degree of correction when tentatively introduced and large in the effect when actually introduced, the information on the imaging position correction application **120a** is included in the recommendation information **23b**.

(95) As a consequence, in a case where the imaging position correction application **120a** that is the tentatively introduced knee imaging position correction application is the imaging position correction application **120** with high usage possibility when actually introduced and with a significant effect when actually introduced, the user and the provider of the imaging position correction application **120** can recognize that the imaging position correction application **120a** is an imaging position correction application **12** with a high need for introduction, from the recommendation information **23b**.

(96) Further, in the first embodiment, the server **2** is configured to be connected to the X-ray imaging apparatus **1** via the network **101**. The server **2** is configured to record the tentative use

information **23a** acquired from the X-ray irradiation unit **1** in the storage unit **23** via the network **101** and acquire the recommendation information **23b** for recommending the introduction of the imaging position correction application **120** to the user, based on the tentative use information **23a** stored in the storage unit **23**.

(97) With this, the provider of the imaging position correction application **120** can acquire the recommendation information **23b** based on the tentative use information **23a** acquired from the X-ray imaging apparatus **1**, by accessing the server **2** via the network **101**. Consequently, the provider of the imaging position correction application **120** can acquire the recommendation information **23b** based on the tentative use information **23a** without going to the location of the X-ray imaging apparatus **1** and propose the imaging position correction application **120** recommended to be actually introduced based on the recommendation information **23b** to the user.

Second Embodiment

(98) With reference to FIG. **6**, the configuration of the imaging position correction application introduction support system **200** according to a second embodiment will be described. In the drawings, the same component as that of the first embodiment will be assigned by the same reference numeral.

(99) In the imaging position correction application introduction support system **200** according to the second embodiment, the processing unit **121** in the PC **12** of the X-ray imaging apparatus **1** is configured to process the imaging position correction applications **120** (imaging position correction applications **120a**, **120b**, **120c**, and **120d**) and acquire the recommendation information **23b**. Note that the processing unit **121** is one example of the “acquisition unit” and the “processing unit” recited in claims.

(100) In the second embodiment, the processing unit **121** of the X-ray imaging apparatus **1** is configured to record the tentative use information **23a** in the storage unit **122** and acquire the recommendation information **23b** for recommending the actual introduction of the imaging position correction application **120** to the user based on the tentative use information **23a** stored in the storage unit **122**. The recommendation information **23b** is stored in the storage unit **122**. The processing unit **121** is configured to display the acquired recommendation information **23b** on the display unit **123**. Note that the X-ray imaging apparatus **1** may transmit the tentative use information **23a** and the recommendation information **23b** to an external device, such as, e.g., a tablet terminal **3** (see FIG. **1**), via the network **101**.

(101) The rest of the configuration of the second embodiment is the same as that of the first embodiment.

Effects of Second Embodiment

(102) In the second embodiment, the following effects can be obtained.

(103) In the second embodiment, in the same manner as in the first embodiment described above, it is possible to provide an imaging position correction application introduction support system **200** capable for the provider or the user of the imaging position correction application **120** to recognize the imaging position correction application **120** with a high need for introduction for the user prior to the actual introduction.

(104) Further, in the imaging position correction application introduction support system **200** according to the second embodiment, the following advantages can be further obtained by the following configuring.

(105) In the second embodiment, the processing unit **121** of the X-ray imaging apparatus **1** is configured to cause the storage unit **122** to store the tentative use information **23a** in the storage unit **122** and acquire the recommendation information **23b** for recommending the actual introduction of the imaging position correction application **120** to the user, based on the tentative use information **23a** stored in the storage unit **122**. The processing unit **121** is configured to display the acquired recommendation information **23b** on the display unit **123**.

(106) With this, in the X-ray imaging apparatus **1**, since the tentative use information **23a** is stored,

and the recommendation information **23b** is acquired, the imaging position correction application **120** with a high need for introduction for the user can be recognized prior to the actual introduction without connecting to the external network **101**.

(107) Other effects of the second embodiment are the same as those of the first embodiment.

Modified Embodiments

(108) It should be understood that the embodiments disclosed here are examples in all respects and are not restrictive. The scope of the present invention is shown by claims rather than the descriptions of the embodiments described above, and includes all changes (modifications) within the meaning and the scope equivalent to the claims.

(109) For example, in the first and second embodiments described above, an example is shown in which the recommendation information **23b** is displayed as the information based on the tentative use information **23a**, but the present invention is not limited thereto. In the present invention, as shown in FIG. 7, the tentative use information **23a** may be displayed on the display unit **33** of the tablet terminal **3**. Further, the tablet terminal **3** may be configured such that the tentative use information **23a** and the recommendation information **23b** can be displayed simultaneously or displayed in a switched manner. Further, the tentative use information **23a** may be displayed on the display unit **123** (see FIG. 1) of the X-ray imaging apparatus **1**.

(110) Further, in the first and second embodiments, an example is shown in which the recommendation information **23b** is acquired by the acquisition unit **22** and the processing unit **121**, respectively, but the present invention is not limited thereto. In the present invention, the provider or the user may consider the imaging position correction application recommended to be actually introduced by visually recognizing the tentative use information displayed on the display unit.

(111) Further, in the first and second embodiments described above, an example is shown in which the imaging position correction application introduction support system **100** stores, as the tentative use information **23a**, the number of times the imaging position correction application **120** was used and the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the imaging position correction application **120** in the storage unit **23**, but the present invention is not limited thereto. In the present invention, it may be configured such that the imaging position correction application introduction support system causes the storage unit to store, as the tentative use information, only one of the number of times the imaging position correction application was used and the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

(112) Further, in the first and second embodiments 1 described above, an example is shown in which the acquisition unit **22** determined the imaging position correction application **120** for recommending the actual introduction based on the magnitude of the number of times the imaging position correction application was used **120** and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the imaging position correction application **120** and acquire the recommendation information **23b** including the information on the determined imaging position correction application **120** recommended to be actually introduced, but the present invention is not limited.

(113) In the present invention, it may be configured such that the acquisition unit determines the imaging position correction application recommended to be actually introduced based on only one of the magnitude of the number of times the imaging position correction application was used and the magnitude of the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected.

(114) Further, in the first and second embodiments described above, an example is shown in which the acquisition unit **22** selects the imaging position correction application **120** recommended to be

actually introduced from among the imaging position correction applications **120a**, **120b**, **120c**, **120d**, based on the magnitude of the number of times the imaging position correction application **120** was used and acquires the recommendation information **23b** including the selected imaging position correction application **120** recommended to be actually introduced, but the present invention is not limited thereto.

(115) The present invention may be used when tentatively introducing one imaging position correction application. In this situation, it is determined whether to recommend the introduction of the tentatively used imaging position correction application based on the magnitude of the number of times the imaging position correction application was used.

(116) Further, in the first and second embodiments described above, an example is shown in which the acquisition unit **22** selects the imaging position correction application recommended to be actually introduced **120a**, **120b**, **120c**, and **120d** based on the comparison between the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used and a predetermined threshold of the number of uses, and the ranking of the imaging position correction application **120** based on the number of times each of the imaging position correction applications **120a**, **120b**, **120c**, and **120d** was used, and acquires the recommendation information **23b** including the information on the selected imaging position correction application **120** recommended to be actually introduced, but the present invention is not limited thereto.

(117) In the present invention, it may be configured such that the acquisition unit selects the imaging position correction application recommended to be actually introduced from among a plurality of imaging position correction applications, based on only one of the comparison between the number of times each of a plurality of imaging position correction applications was used and a predetermined threshold of the number of uses, and the ranking of the imaging position correction application based on the number of times each of the plurality of imaging position correction applications was used.

(118) Further, in the first and second embodiments described above, an example is shown in which the acquisition unit **22** selects the imaging position correction application recommended to be actually introduced from among the imaging position correction applications **120a**, **120b**, **120c**, and **120d** based on the degree of correction when the relative position of the X-ray irradiation unit **111** with respect to the specific site of the subject **800** was corrected by the imaging position correction application **120** and the predetermined threshold of the degree of correction, and acquires the recommendation information **23b** including the information on the selected actual introduced recommended imaging position correction application **120**, but the present invention is not limited thereto.

(119) The present invention may be used when tentatively introducing one imaging position correction application. In this case, whether to recommend the introduction of the tentatively used imaging position correction application is determined by the imaging position correction application, based on the degree of correction when the relative position of the X-ray imaging unit with respect to the specific site of the subject was corrected and the predetermined threshold of the degree of correction.

(120) Further, in the second embodiment, an example is shown in which the tentative use information **23a** is recorded in the storage unit **122** of the PC **12** of the X-ray imaging apparatus **1**, but the present invention is not limited thereto. In the present invention, in the imaging position correction application introduction support system, the tentative use information may be stored in a storage unit, such as, e.g., a memory provided on the imaging apparatus main body **11** (see FIG. 1) of the X-ray imaging apparatus **1**.

(121) Further, in the first and second embodiments described above, an example is shown in which the tentative use information **23a** of the imaging position correction application tentatively introduced into the ceiling-suspended X-ray imaging apparatus **1** and the recommendation information **23b** are acquired, but the present invention is not limited thereto. In the present

intention, the tentative use information on the imaging position correction application tentatively introduced to the X-ray fluoroscopic imaging table (fluoroscopic table) and the recommendation information may be acquired.

(122) Further, in the first and second embodiments described above, for convenience of explanation, the processing (processing of the acquiring tentative use information **23a** and the recommendation information **23b**) in the imaging position correction application support system according to the present invention is described using a flow-driven flowchart that sequentially performs processing along the processing flow, but the present invention is not limited thereto.

(123) In the present invention, the processing in the imaging position correction application introduction support system may be performed by event-driven processing (event-driven type) that executes processing on an event-by-event basis. In this case, the processing may be performed in a complete event-driven fashion or in combination of event-driven type processing and flow-driven type processing.

(124) [Aspects]

(125) It will be understood by those skilled in the art that the above-described exemplary embodiments are concrete examples of the following aspects.

(126) (Item 1)

(127) An imaging position correction application introduction support system, comprising: a storage unit configured to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively used as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display unit configured to display information based on the tentative use information stored in the storage unit, wherein the storage unit is configured to store, as the tentative use information, at least one of a number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

(Item 2)

(128) The imaging position correction application introduction support system as recited the above-described Item 1, further comprising: an acquisition unit configured to acquire, as the information to be used to recommend the actual introduction of the imaging position correction application to a user, recommendation information including information on the imaging position correction application recommended to be actually introduced, based on the tentative use information, wherein the display unit is configured to display the recommendation information as information based on the tentative use information.

(Item 3)

(129) The imaging position correction application introduction support system as recited in the above-described Item 2, wherein the acquisition unit is configured to determine the imaging position correction application recommended to be actually introduced, based on at least one of magnitude of the number of times the imaging position correction application was used, the magnitude of the number of times being stored in the storage unit as the tentative use information, and magnitude of a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application, the degree of correction being stored in the storage unit as the tentative use information, and acquire the recommendation information including information on the determined imaging position correction application recommended to be actually introduced.

(Item 4)

(130) The imaging position correction application introduction support system as recited in the above-described Item 3, wherein the storage unit stores at least the number of times the imaging

position correction application was used as the tentative use information, and wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced from a plurality of imaging position correction applications, based on the magnitude of the number of times the imaging position correction application was used, the number of times being stored in the storage unit as the tentative use information, and acquire the recommendation information including information on the selected imaging position correction application recommended to be actually introduced.

(Item 5)

(131) The imaging position correction application introduction support system as recited in the above-described Item 4, wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced from the plurality of imaging position correction applications, based on at least one of comparison between the number of times each of the plurality of imaging position correction applications was used and a predetermined threshold of the number of times and a ranking of the plurality of imaging position correction applications based on the number of times each of the plurality of imaging position correction application was used; and acquire the recommendation information including information on the selected imaging position correction application recommended to be actually introduced.

(Item 6)

(132) The imaging position correction application introduction support system as recited in any one of the above-described Items 2 to 5, wherein the storage unit stores, as the tentative use information, at least the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application, and wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced, from the plurality of imaging position correction applications, based on the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject by the imaging position correction application was corrected and a predetermined threshold of the degree of correction, the degree of correction and the predetermined threshold being stored in the storage unit as the tentative use information, and acquire the recommendation information including the information on the selected imaging position correction application recommended to be actually introduced.

(Item 7)

(133) The imaging position correction application introduction support system as recited in any one of the above-described Items 2 to 6, wherein the imaging position correction application to be introduced includes a knee imaging position correction application for correcting a relative position of the X-ray irradiation unit with respect to a knee of the subject when capturing an X-ray image of the knee of the subject, wherein the storage unit stores, as the tentative use information, at least one of the number of times the knee imaging position correction application was used and a degree of correction when a relative position of the X-ray irradiation unit with respect to the knee of the subject was corrected, and wherein the acquisition unit is configured to determine the knee imaging position correction application as the imaging position correction application recommended to be actually introduced, based on at least one of magnitude of the number of times the knee imaging position correction application was used, the magnitude of the number of times being stored in the storage unit as the tentative use information, and magnitude of a degree of correction when the relative position of the X-ray irradiation unit with respect to the knee of the subject was corrected by the knee imaging position correction application, the degree of correction being stored in the storage unit as the tentative use information.

(Item 8)

(134) The imaging position correction application introduction support system as recited in any one of the above-described Items 2 to 7, further comprising: a server connected to an X-ray imaging apparatus in which the imaging position correction application is tentatively introduced, the X-ray

imaging apparatus being configured to capture an X-ray image of the subject via a network, wherein the server includes a storage unit and an acquisition unit, and wherein the server is configured to cause the storage unit to store, via a network, the tentative use information acquired from the X-ray imaging apparatus, and acquire the recommendation information for recommending an introduction of the imaging position correction application to a user, based on the tentative use information stored in the storage unit.

(Item 9)

(135) The imaging position correction application introduction support system as recited in any one of the above-described Items 2 to 7, further comprising: an X-ray imaging apparatus in which the imaging position correction application is tentatively introduced, the X-ray imaging apparatus being configured to capture an X-ray image of the subject, wherein the X-ray imaging apparatus includes: the X-ray irradiation unit; the storage unit; the display unit; an X-ray detection unit configured to detect X-rays emitted from the X-ray irradiation unit and transmitted through the subject; and a processing unit as the acquisition unit, the processing unit being configured to process the imaging position correction application and acquire the recommendation information, and wherein the processing unit of the X-ray imaging apparatus is configured to cause the storage unit to store the tentative use information, acquire the recommendation information for recommending an actual introduction of the imaging position correction application to a user, based on the tentative use information stored in the storage unit, and cause the display unit to display the acquired recommendation information.

(Item 10)

(136) An imaging position correction application introduction support method, comprising: a storage step configured to cause the storage unit to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively introduced as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display step configured to display information based on the tentative use information stored in the storage unit; wherein the storage step includes a step configured to cause the storage to store, as the tentative use information, at least one of the number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

Claims

1. An imaging position correction application introduction support system, comprising: a storage unit configured to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively used as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display unit configured to display information based on the tentative use information stored in the storage unit, wherein the storage unit is configured to store, as the tentative use information, at least one of a number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.

2. The imaging position correction application introduction support system as recited claim 1, further comprising: an acquisition unit configured to acquire, as the information to be used to recommend the actual introduction of the imaging position correction application to a user,

recommendation information including information on the imaging position correction application recommended to be actually introduced, based on the tentative use information, wherein the display unit is configured to display the recommendation information as information based on the tentative use information.

3. The imaging position correction application introduction support system as recited in claim 2, wherein the acquisition unit is configured to determine the imaging position correction application recommended to be actually introduced, based on at least one of magnitude of the number of times the imaging position correction application was used, the magnitude of the number of times being stored in the storage unit as the tentative use information, and magnitude of a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application, the degree of correction being stored in the storage unit as the tentative use information, and acquire the recommendation information including information on the determined imaging position correction application recommended to be actually introduced.

4. The imaging position correction application introduction support system as recited in claim 3, wherein the storage unit stores at least the number of times the imaging position correction application was used as the tentative use information, and wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced from a plurality of imaging position correction applications, based on the magnitude of the number of times the imaging position correction application was used, the number of times being stored in the storage unit as the tentative use information, and acquire the recommendation information including information on the selected imaging position correction application recommended to be actually introduced.

5. The imaging position correction application introduction support system as recited in claim 4, wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced from the plurality of imaging position correction applications, based on at least one of comparison between the number of times each of the plurality of imaging position correction applications was used and a predetermined threshold of the number of times and a ranking of the plurality of imaging position correction applications based on the number of times each of the plurality of imaging position correction application was used; and acquire the recommendation information including information on the selected imaging position correction application recommended to be actually introduced.

6. The imaging position correction application introduction support system as recited in claim 2, wherein the storage unit stores, as the tentative use information, at least the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application, and wherein the acquisition unit is configured to select the imaging position correction application recommended to be actually introduced, from the plurality of imaging position correction applications, based on the degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject by the imaging position correction application was corrected and a predetermined threshold of the degree of correction, the correction degree and the predetermined threshold being stored in the storage unit as the tentative use information, and acquire the recommendation information including the information on the selected imaging position correction application recommended to be actually introduced.

7. The imaging position correction application introduction support system as recited in claim 2, wherein the imaging position correction application to be introduced includes a knee imaging position correction application for correcting a relative position of the X-ray irradiation unit with respect to a knee of the subject when capturing an X-ray image of the knee of the subject, wherein the storage unit stores, as the tentative use information, at least one of the number of times the knee imaging position correction application was used and a degree of correction when a relative

position of the X-ray irradiation unit with respect to the knee of the subject was corrected, and wherein the acquisition unit is configured to determine the knee imaging position correction application as the imaging position correction application recommended to be actually introduced, based on at least one of magnitude of the number of times the knee imaging position correction application was used, the magnitude of the number of times being stored in the storage unit as the tentative use information, and magnitude of a degree of correction when the relative position of the X-ray irradiation unit with respect to the knee of the subject was corrected by the knee imaging position correction application, the degree of correction being stored in the storage unit as the tentative use information.

8. The imaging position correction application introduction support system as recited in claim 2, further comprising: a server connected to an X-ray imaging apparatus in which the imaging position correction application is tentatively introduced, the X-ray imaging apparatus being configured to capture an X-ray image of the subject via a network, wherein the server includes a storage unit and an acquisition unit, and wherein the server is configured to cause the storage unit to store, via a network, the tentative use information acquired from the X-ray imaging apparatus, and acquire the recommendation information for recommending an introduction of the imaging position correction application to a user, based on the tentative use information stored in the storage unit.

9. The imaging position correction application introduction support system as recited in claim 2, further comprising: an X-ray imaging apparatus in which the imaging position correction application is tentatively introduced, the X-ray imaging apparatus being configured to capture the X-ray image of the subject, wherein the X-ray imaging apparatus includes: the X-ray irradiation unit; the storage unit; the display unit; an X-ray detection unit configured to detect X-rays emitted from the X-ray irradiation unit and transmitted through the subject; and a processing unit as the acquisition unit, the processing unit being configured to process the imaging position correction application and acquire the recommendation information, and wherein the processing unit of the X-ray imaging apparatus is configured to cause the storage unit to store the tentative use information, acquire the recommendation information for recommending an actual introduction of the imaging position correction application to a user, based on the tentative use information stored in the storage unit, and cause the display unit to display the acquired recommendation information.

10. An imaging position correction application introduction support method, comprising: a storage step configured to cause the storage unit to store tentative use information on when an imaging position correction application was tentatively used, as information to be used to recommend an actual introduction of the imaging position correction application tentatively introduced as an application for correcting a relative position of an X-ray irradiation unit for emitting X-rays with respect to a specific site of a subject when capturing an X-ray image of the specific site of the subject; and a display step configured to display information based on the tentative use information stored in the storage unit; wherein the storage step includes a step configured to cause the storage to store, as the tentative use information, at least one of the number of times the imaging position correction application was used and a degree of correction when the relative position of the X-ray irradiation unit with respect to the specific site of the subject was corrected by the imaging position correction application.
