

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415590
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Curtin; Thomas M. et al.

Foldable fin for watersport equipment

Abstract

The present technology is generally directed to a fin assembly for watersport equipment, a watersport system including thereof, and a method of using thereof. In various embodiments, the fin assembly includes a support base and a foldable fin. The support base may be configured to attach the fin assembly to a surface of the watersport equipment. The foldable fin may include a fin portion configured to move between a folded position and a use position. The support base may have a locking member configured to lock the fin portion in and release the fin portion from the use position.

Inventors: Curtin; Thomas M. (Snoqualmie, WA), Vukelic; Gregg A. (Issaquah, WA), Stephan; Scott M. (Seattle, WA)

Applicant: HO SPORTS COMPANY, LLC (Snoqualmie, WA)

Family ID: 1000008821847

Assignee: HO SPORTS COMPANY, LLC (Snoqualmie, WA)

Appl. No.: 18/074441

Filed: December 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230174200 A1	Jun. 08, 2023

Related U.S. Application Data

us-provisional-application US 63285941 20211203

Publication Classification

Int. Cl.: B63B32/64 (20200101); B63B32/66 (20200101)

U.S. Cl.:

CPC B63B32/64 (20200201); B63B32/66 (20200201);

Field of Classification Search

CPC: B63B (32/64); B63B (32/66)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5664979	12/1996	Benham	114/140	B63B 32/64
5813890	12/1997	Benham	114/140	B63B 32/66
D428459	12/1999	Broz	D21/769	N/A
6244921	12/2000	Pope	114/130	B63B 32/66
8408958	12/2012	Benham	441/74	B63B 32/66
9139265	12/2014	Peberdy	N/A	B63B 32/64
9487276	12/2015	Kusch	N/A	B63B 32/66
9896168	12/2017	Lindbergh	N/A	B63B 32/66
9944363	12/2017	Venables	N/A	G05D 1/0875
11661155	12/2022	Khaladj	441/79	B63B 32/66
2004/0043681	12/2003	Jolly	441/79	B63B 32/66
2010/0323568	12/2009	Chambers	441/79	B63B 32/66
2013/0183152	12/2012	Peberdy	416/9	B63B 39/06
2017/0096199	12/2016	Hall	N/A	B63B 32/66

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104260844	12/2014	CN	N/A
WO-2015135034	12/2014	WO	B63B 32/66

OTHER PUBLICATIONS

Kaetano (CN 104260844) Machine Translation (Year: 2015). cited by examiner

Primary Examiner: Delrue; Brian Christopher

Attorney, Agent or Firm: BakerHostetler

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) The present application claims the benefit of U.S. Provisional Patent Application No. 63/285,941, filed Dec. 3, 2021, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present technology is directed generally to fins or skegs for watersport boards, such as

paddle boards, kayaks, wakeboards, surfboards, and water skis, and other types of boards used in water sports, and more particularly to a fin that is not rigidly attached to the watersport board.

BACKGROUND

(2) Watersport boards typically include a downwardly projecting fin situated on the rear bottom of the board that is used to aid steering and stability. However, when the user wishes to transport or store the board, the projecting fin makes doing so more difficult and requires more space. Stacking of boards is difficult or impossible, and the protruding fin can present a hazard. In the case of inflatable watersport boards, rolling and packing of the deflated board is difficult and often requires use of a fin that is shorter than desirable. In addition, the projecting fin can present a hazard when the board is not in the water.

(3) The fin is typically fixedly attached to the watersport board, though some designs provide for complete removal of a fin from the board. Once disconnected and separated from the board, the removable fin may be easily lost, damaged, and/or the user may forget to take the removed fin along on the next trip when the board is intended to be used. Further, the removable fin has a risk of falling off in the water during use of the board. Also, reattaching the fin to the board may take more time and effort than desirable.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Many aspects of the present disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale. Instead, emphasis is placed on clearly illustrating the principles of the present disclosure.

(2) FIG. 1 is a perspective view of a fin assembly with a support base attached to a bottom side of a watersport board configured in accordance with embodiments of the present technology.

(3) FIG. 2 is an exploded view of the fin assembly of FIG. 1.

(4) FIG. 3 is a side perspective view of the fin assembly of FIG. 1 with a foldable fin locked in a use position by a locking member in accordance with embodiments of the present technology.

(5) FIG. 4 is a side elevational view of the fin assembly of FIG. 3.

(6) FIG. 5 is a perspective, partial cross-sectional side view of the fin assembly of FIG. 3.

(7) FIG. 6 is a side elevational, partial cross-sectional view of the fin assembly of FIG. 3.

(8) FIG. 7 is a front elevational view of the fin assembly of FIG. 3.

(9) FIG. 8 is a rear elevational view of the fin assembly of FIG. 3.

(10) FIG. 9A is a cross-sectional view taken substantially along the line 9A-9A of FIG. 4.

(11) FIG. 9B is a cross-sectional view taken substantially along the line 9B-9B of FIG. 4.

(12) FIG. 10 is a side elevational view of a support base of the fin assembly of FIG. 1.

(13) FIG. 10A is a cross-sectional view taken substantially along the line 10A-10A of FIG. 10.

(14) FIG. 10B is a cross-sectional view taken substantially along the line 10B-10B of FIG. 10.

(15) FIG. 10C is a cross-sectional view taken substantially along the line 10C-10C of FIG. 10.

(16) FIG. 11 is a plan view of a locking member of the fin assembly of FIG. 1.

(17) FIG. 12 is a side perspective view of the fin assembly of FIG. 1 with the locking member rotated in a direction “A” to an unlocked position in accordance with embodiments of the present technology.

(18) FIG. 13 is a side elevational view of the fin assembly of FIG. 12.

(19) FIG. 14 is a perspective, partial cross-sectional view of the fin assembly of FIG. 12.

(20) FIG. 15 is a side elevational, partial cross-sectional view of the fin assembly of FIG. 12.

(21) FIG. 16 is a side perspective view of the fin assembly of FIG. 12 with the foldable fin moved in a direction “B” relative to the support base in accordance with embodiments of the present technology.

- (22) FIG. 17 is a side elevational view of the fin assembly of FIG. 16.
- (23) FIG. 18 is a perspective, partial cross-sectional view of the fin assembly of FIG. 16.
- (24) FIG. 19 is a side elevational, partial cross-sectional view of the fin assembly of FIG. 16.
- (25) FIG. 20 is a side perspective view of the fin assembly of FIG. 16 with the foldable fin moved in a direction “C” relative to the support base in accordance with embodiments of the present technology.
- (26) FIG. 21 is a side elevational view of the fin assembly of FIG. 20.
- (27) FIG. 22 is a perspective, partial cross-sectional view of the fin assembly of FIG. 20.
- (28) FIG. 23 is a side elevational, partial cross-sectional view of the fin assembly of FIG. 20.
- (29) FIG. 24 is a front elevational view of the fin assembly of FIG. 20.
- (30) FIG. 25 is a rear elevational view of the fin assembly of FIG. 20.
- (31) FIG. 26A is a cross-sectional view taken substantially along the line 26A-26A of FIG. 20.
- (32) FIG. 26B is a cross-sectional view taken substantially along the line 26B-26B of FIG. 20.
- (33) FIG. 27 is a side perspective view of the fin assembly of FIG. 20 with the foldable fin folded in a direction “D” relative to the support base in accordance with embodiments of the present technology.
- (34) FIG. 28 is a side elevational view of the fin assembly of FIG. 27.
- (35) FIG. 29A is a side perspective, partial cross-sectional view of the fin assembly of FIG. 27.
- (36) FIG. 29B is an enlarged view of the circled portion of the fin assembly of FIG. 29A.
- (37) FIG. 30 is a side elevational, cross-sectional view of the fin assembly of FIG. 27.
- (38) FIG. 31 is a front elevational view of the fin assembly of FIG. 27.
- (39) FIG. 32 is a rear elevational view of the fin assembly of FIG. 27.
- (40) FIG. 33A is a cross-sectional view taken substantially along the line 33A-33A of FIG. 28.
- (41) FIG. 33B is a cross-sectional view taken substantially along the line 33B-33B of FIG. 28.
- (42) Like reference numerals have been used in the figures to identify like components.

DETAILED DESCRIPTION

(43) Folding fins for water sports and associated systems and methods are disclosed herein. The folding fins disclosed herein can be fixedly attached to various types of watersport equipment, such as paddle boards, kayaks, wakeboards, surfboards, and water skis, and/or other types of sporting equipment that typically includes a fin. Specific details of several embodiments of the present technology are described herein with reference to FIGS. 1-33B. The present technology, however, can be practiced without some of these specific details. In some instances, well-known structures and techniques often associated watersport boards, and the like, have not been shown in detail so as not to obscure the present technology. The terminology used in the description presented below is intended to be interpreted in its broadest reasonable manner, even though it is being used in conjunction with a detailed description of certain specific embodiments of the disclosure. Certain terms can even be emphasized below; however, any terminology intended to be interpreted in any restricted manner will be overtly and specifically defined as such in this Detailed Description section.

(44) The accompanying Figures depict embodiments of the present technology and are not intended to be limiting of its scope. The sizes of various depicted elements are not necessarily drawn to scale, and these various elements can be arbitrarily enlarged to improve legibility. Component details can be abstracted in the Figures to exclude details such as position of components and certain precise connections between such components when such details are unnecessary for a complete understanding of how to make and use the present technology. Many of the details, dimensions, angles, and other features shown in the Figures are merely illustrative of particular embodiments of the disclosure. Accordingly, other embodiments can have other details, dimensions, angles, and features without departing from the spirit or scope of the present technology.

(45) FIG. 1 is a perspective view of a fin assembly 10 in a use position in accordance with

embodiments of the present technology, and FIG. 2 is an exploded view of the fin assembly **10** of FIG. **1**. The fin assembly **10** includes a foldable fin **12** and a support base **14** (also referred to as a “fin box”) that can be permanently or removably attached to a watersport board **16** having a forward end **16A** and a rearward end **16B**. The support base **14** is shown attached to a bottom side **18** of the watersport board **16** at a rearward end portion **20** of the watersport board **16**. While the support base **14** is illustrated as attached to the surface of the watersport board **16**, the support base **14** may be positioned within a recess (not shown) and/or opening in the bottom side **18** of the watersport board **16**.

(46) Referring to FIG. **2**, the fin assembly **10** can include a positioning retainer member **22** (also referred to as a “wedge”), a locking lever or member **24**, and a fastener **26**, which together form part of the support base **14**. The fastener **26** may be a screw or other type fastener **26**. The foldable fin **12** has a fin portion **28** rigidly attached to a fin base portion **30** and projecting away from the fin base portion **30**. When the fully assembled fin assembly **10** is attached to the watersport board **16** and the foldable fin **12** is in a use position, as shown in FIG. **1**, the fin portion **28** projects away from (e.g., being substantially perpendicular to) the bottom side **18** of the watersport board **16**. The fin assembly **10** is also shown in the use position in FIGS. **3-9B**.

(47) As shown in FIG. **2**, the fin base portion **30** has a forward end base portion **32** and a rearward end base portion **34**, with a middle portion **36** located between the forward and rearward end base portions **32** and **34**. The fin base portion **30** further includes a cylindrical forward bolt or pivot member **38** projecting forward from the forward end base portion **32** of the fin base portion **30**, and a rearward bolt or pivot member **40** projecting rearward from the rearward end base portion **34** of the fin base portion **30**. The forward and rearward pivot members **38** and **40** are in axial alignment with a central axis of rotation **42** for the fin assembly **10**.

(48) As further shown in FIG. **2**, the support base **14** has a mounting side portion **44** in contact with the bottom side **18** of the watersport board **16** when attached thereto, and an outward projecting portion **46** projecting away from the bottom side **18** of the watersport board **16** and having an outward perimeter wall portion **48** extending fully about the outward projecting portion **46**. As viewed in the drawings, the outward projecting portion **46** projects upward, although when the watersport board **16** is in use in water, the outward projecting portion **46** projects downward into the water.

(49) The outward projecting portion **46** of the support base **14** has a forward end portion **50** and a rearward end portion **52**, with a middle portion **54** extending therebetween. The outward projecting portion **46** further includes a channel **56** (also referred to as an “elongated slot”) extending along a longitudinal axis of the support base **14** between and within the forward end portion **50** and the rearward end portion **52**, and along the middle portion **54**, of the outward projecting portion **46**. The channel **56** faces away from the mounting side portion **44** of the support base **14**, and also away from the bottom side **18** of the watersport board **16**. The channel **56** includes a forward channel portion **58** sized to receive the forward pivot member **38** of the fin base portion **30**, and a rearward channel portion **60** sized to receive the rearward pivot member **40** of the fin base portion **30**, with a middle channel portion **62** located and extending between the forward and rearward channel portions **58** and **60**. The channel **56** has a bottom wall **56A** running its full length. The fin assembly **10** is shown fully assembled with the forward pivot member **38** in the forward channel portion **58** and the rearward pivot member **40** in the rearward channel portion **60**, with the fin portion **28** in the use position in FIGS. **3-9B**. With the orientation shown in the drawings, the channel **56** is upwardly opening except at its forward and rearward end portions **50** and **52**, as will be described below.

(50) Referring to FIG. **6** and FIG. **10A**, the forward end portion of the forward channel portion **58** includes a forward recess **64** with a rearward opening in a rearward facing wall **66** of the forward end portion **50** of the outward projecting portion **46**. The forward recess **64** includes an inward recess portion **64A** and an outward recess portion **64B** positioned forward of the inward recess

portion **64A**. When the fin portion **28** is in the use position, the forward pivot member **38** is positioned in the forward channel portion **58** and projects through the inward recess portion **64A** and into the outward recess portion **64B**, with the forward end of the forward pivot member **38** in engagement with a forward wall **64C** of the outward recess portion **64B** to limit forward movement of the forward pivot member **38** within the forward channel portion **58** during use of the watersport board **16**. The outward recess portion **64B** can have a partial cylindrical shape sized to snugly hold the forward pivot member **38** to limit its left and right movement and a wall portion **65** limiting movement of the forward pivot member **38** away from the support base **14** during use of the watersport board **16**. When so positioned in the outward recess portion **64B**, the forward pivot member **38** is held adjacent to the bottom wall **56A** of the channel **56**.

(51) As shown in FIGS. **6** and **10B**, the rearward end portion of the rearward channel portion **60** includes a rearward recess **68** with a forward opening in a forward facing wall **70** of the rearward end portion **52** of the outward projecting portion **46**. When the fin portion **28** is in the use position, the rearward pivot member **40** is positioned in the rearward channel portion **60** and projects through the rearward recess **68**. When so positioned in the rearward recess **68**, the rearward pivot member **38** is held adjacent to the bottom wall **56A** of the channel **56** by the locking member **24**, as will be described below.

(52) Referring to FIGS. **2-10C**, left and right lateral wall portions **72** and **74** of the rearward recess **68** extending rearward of the forward facing wall **70**, each have a notch **76** and **78**, respectively, therein with a rearward open end, the notches **76** and **78** being sized to rotatably retain a corresponding one of left and right pivot pins **80** and **82**, respectively, of the locking member **24** (see FIGS. **2** and **11**). The retainer member **22** is positioned in the rearward channel portion **60** within the rearward recess **68** and is removably held in position therein by the fastener **26** (see the left side elevational, cross-sectional view of FIG. **6**). Left and right forward edge walls **84** and **86** of the retainer member **22** are positioned to block the rearward open ends of the notches **76** and **78**, respectively, to retain the left and right pivot pins **80** and **82** in the notches **76** and **78**.

(53) Referring to FIGS. **2**, **11** and **15**, the locking member **24** includes a rearward end portion **88** for gripping/pressing by a user to selectively rotate the locking member **24** about an axis of rotation of the left and right pivot pins **80** and **82** in clockwise and counterclockwise directions relative to the rearward channel portion **60**, as viewed in the drawings, and a forward end portion **90** that moves in the same rotational direction as the rearward end portion **88** is moved. A rearward opening, laterally extending notch or groove **92** is provided in a rearward end face **94** of the rearward pivot member **40**. In FIG. **6**, the rearward end portion **88** of the locking member **24** has been rotated clockwise to position a forward end **90A** of the forward end portion **90** of the locking member **24** in a locked position within the groove **92** of the rearward end face **94** of the rearward pivot member **40**. In this position, the forward end portion **90** of the locking member **24** inhibits rearward movement of the rearward pivot member **40** and movement of the rearward pivot member **40** away from the support base **14** during use of the watersport board **16**. The left and right lateral wall portions **72** and **74** of the rearward recess **68** limit left and right movement of the rearward pivot member **40** during use of the watersport board **16**.

(54) As shown in FIGS. **2** and **9B**, outward projecting portion **46** of the support base **14** includes left and right side wall portions **96** and **98**, respectfully, laterally spaced apart by a distance to receive (e.g., snugly receive) the middle portion **36** of the fin base portion **30** therebetween and provide lateral support to the fin base portion **30** to assist in preventing lateral movement/rotation of the fin base, and hence the fin portion **28**, during use of the watersport board **16**. The middle portion **36** of the fin base portion **30** has an inward edge wall **100** that is spaced outward away from the bottom wall **56A** of the channel **56**. The left and right side wall portions **96** and **98** project away from the bottom wall **56A** of the channel **56**, and each has an outward edge wall **102** located farther outward than the inward edge wall **100** of the middle portion **36** so that the left and right side wall portions **96** and **98** overlap with the middle portion **36** of the fin base portion **30** during use of the

watersport board **16**. The left and right side wall portions **96** and **98** longitudinally extend along the channel **56** with forward ends **96A** and **98A**, respectively, located rearward of a rearward end **32A** of the forward end base portion **32** of the fin base portion **30**, and with rearward ends **96B** and **98B**, respectively, located forward of a forward end **34A** of the rearward end base portion **34** of the fin base portion **30**.

(55) To facilitate transportation or storage the watersport board **16**, the foldable fin **12** can move to a folded position (also referred to as a “folded state”) with the fin portion **28** adjacent to the bottom side **18** of the watersport board **16**, while remaining securely attached to the support base **14** during folding and when in the folded position. FIGS. **27-33B** illustrate the fin assembly **10** in a folded state, with the foldable fin **12** positioned fully to the side (e.g., being substantially parallel to the bottom side **18** of the watersport board **16**. The design of the foldable fin **12** and the support base **14** eliminates the possibility of losing the fin portion **28** since the support base **14** remains securely attached to the watersport board **16**, unlike with designs where the fin is fully disconnected from the watersport board **16** for transport or storage and must be reattached before the next use of the watersport board **16**.

(56) The fin assembly **10** provides a mechanism that allows a user to easily folding of the foldable fin **12**. The first step includes moving the locking member **24** to a release position as shown in FIGS. **12-15**. As shown in FIG. **15**, the first step is to rotate the rearward end portion **88** of the locking member **24** counterclockwise, as viewed in FIG. **15** and indicated by arrow “A”, to move the forward end portion **90** of the locking member **24** toward the support base **14** sufficiently to disengage the forward end portion **90** from the rearward end face **94** of the rearward pivot member **40** and thereby withdraw the forward end **90A** of the forward end portion **90** from within the groove **92** of the rearward end face **94** of the rearward pivot member **40**.

(57) The second step includes moving the foldable fin **12** in a first longitudinally relative to the support base **14** as shown in FIGS. **16-19**. The first direction is illustrated by arrow “B” in FIG. **19**. This includes moving (e.g., sliding) the fin base portion **30** rearward within the channel **56** as indicated by arrow “B” until the forward pivot member **38** is fully withdrawn from within the outward recess portion **64B** of the forward recess **64**. As is shown in FIG. **19**, upon rearward movement of the fin base portion **30** sufficient to fully withdraw the forward pivot member **38** from within the outward recess portion **64B**, the rearward end face **94** of the rearward pivot member **40** will engage the forward end portion **90** of the locking member **24** which acts as a stop and prevents further rearward movement of the fin base portion **30**. When so rearwardly moved the forward pivot member **38** is fully withdrawn from within the outward recess portion **64B** but remains within the inward recess portion **64A** of the forward recess **64** which has a wall portion **69** (see FIG. **10A**) limiting the extent of its movement away from the bottom wall **56A** of the channel **56**. The rearward movement of the fin base portion **30** leaves the rearward pivot member **40** within the rearward recess **68**, with a wall portion **71** of the forward facing wall **70** (see FIGS. **10B** and **10C**) limiting the extent of its movement of the rearward pivot member **40** away from the bottom wall **56A** of the channel **56**. The rearward movement does not result in disconnection of the fin base portion **30** from the support base **14**.

(58) The third step includes moving the foldable fin **12** away from the support base **14** along a second direction of the support base **14** as shown in FIGS. **20-26B**. The second direction as illustrated by arrow “C” in FIG. **23** is different from the first direction as illustrated by arrow “B” in FIG. **19**. Referring to FIG. **23**, the third step is to move the fin base portion **30** in a direction away from the bottom wall **56A** of the channel **56** (i.e., upward as viewed in FIG. **23** and as indicated by arrow “C”), until the inward edge wall **100** of the middle portion **36** of the fin base portion **30** is positioned farther away from the bottom wall **56A** of the channel **56** than the outward edge walls **102** of the left and right side wall portions **96** and **98**, or at least farther away than the one of the left and right side wall portions **96** and **98** on the side of the outward projecting portion **46** of the support base **14** to which the user wishes to fold the foldable fin **12**. The inward edge wall

100 of the middle portion **36** should be positioned away from the outward edge wall **102** sufficient to prevent the side wall portions **96** and **98** from interfering with folding over the foldable fin **12**. (59) In this position, the forward pivot member **38** is fully withdrawn from within the outward recess portion **64B** but still remains within the inward recess portion **64A** of the forward recess **64** with its wall portion **69** limiting the extent of its movement away from the bottom wall **56A** of the channel **56**, and the rearward pivot member **40** is still within the rearward recess **68** with the wall portion **71** of the forward facing wall **70** limiting the extent of its movement of the rearward pivot member **40** away from the bottom wall **56A** of the channel **56**. However, in this position the fin base portion **30** is rotatably retained by the support base **14**, but the movement does not result in disconnection of the fin base portion **30** from the support base **14**. As shown in FIGS. **26A** and **26B**, the movement in the direction of arrow “C” results in forming a gap **104** between the bottom wall **56A** of the channel **56** and the forward end base portion **32** of the fin base portion **30**. A similar gap is formed between the bottom wall **56A** of the channel **56** and the rearward end base portion **34** of the fin base portion **30**.

(60) The fourth step includes rotating the foldable fin **12** along a rotation axis to place the fin portion **28** in a folded position as shown in FIGS. **27-33B**. The rotation axis is illustrated as a central axis of rotation **42** in FIG. **2**. Referring to FIGS. **29A** and **30**, the fourth step is to rotate the foldable fin **12** clockwise or counterclockwise about the central axis of rotation **42** of the forward and rearward pivot members **38** and **40**, to place the foldable fin **12** into the folded position with the fin portion **28** adjacent to the bottom side **18** of the watersport board **16** when the fin assembly **10** is attached to the watersport board **16**. Snap features (not shown) are included to releasably retain the foldable fin **12** in the folded position. In the illustrated embodiment, the foldable fin **12** may be folded to the left past the outward edge wall **102** of the left side wall portion **96** or folded to the right past the outward edge wall **102** of the right side wall portion **98**. Folding to the right side is illustrated in the drawings, as indicated by arrow “D”. To facilitate the folding, the inward edge wall **100** of the middle portion **36** can be positioned sufficiently away from the outward edge wall **102** by the third step so that, during the rotation of the foldable fin **12** in the fourth step, there is sufficient clearance to prevent the side wall portion **96** or **98** from interfering with the folding of the foldable fin **12**.

(61) The outward recess portion **64B** is sized and the wall portion **69** thereof is positioned to permit at least the limited amount of movement of the forward pivot member **38** in the direction away from the bottom wall **56A** sufficient to provide the needed clearance between the inward edge wall **100** and the outward edge wall **102** to permit the folding action. Further, the device is sized and shaped to still prevent the forward pivot member **38** from being fully removed from the outward recess portion **64B** and disconnected from the support base **14** during the folding step or when the foldable fin **12** is fully folded. Similarly, the rearward recess **68** is sized and the wall portion **71** of the forward facing wall **70** is positioned to permit at least the limited amount of movement of the rearward pivot member **40** in the direction away from the bottom wall **56A** sufficient to provide the needed clearance between the inward edge wall **100** and the outward edge wall **102** to permit the folding action, but still prevent the rearward pivot member **40** from being fully removed from the rearward recess **68** and disconnected from the support base **14** during the folding step or when the foldable fin **12** is fully folded.

(62) To move the fin portion **28** from its folded position to its use position, the four steps described above are essentially taken in reverse. The first step includes rotating the foldable fin **12** along the rotation axis. The foldable fin **12** is rotated about the central axis of rotation **42** of the forward and rearward pivot members **38** and **40** sufficiently to place the foldable fin **12** into an upright position. The second step includes moving the foldable fin **12** toward the support base **14**. The fin base portion **30** is moved in a direction toward the bottom wall **56A** of the channel **56** (i.e., downward as viewed in the drawings and opposite to the direction as illustrated by arrow “C” in FIG. **23**), to position the fin base portion **30** within the channel **56**. Next, the third step includes moving the

foldable fin **12** longitudinally relative to the support base **14** to place the fin portion **28** in the use position. The fin base portion **30** is moved forward within the channel **56** (e.g., along a direction opposite to the direction as illustrated by arrow “B” in FIG. **19**) until the forward pivot member **38** is in engagement with the forward wall **64C** of the outward recess portion **64B** to limit forward movement of the forward pivot member **38** within the forward channel portion **58** during use of the watersport board **16**. Finally, the fourth step includes locking the fin portion **28** in the use position by rotating the locking member **24** to a locked position. The rearward end portion **88** of the locking member **24** is rotated clockwise as viewed in the drawings (e.g., opposite to a direction indicated by arrow “A” in FIG. **15**) to move the forward end portion **90** of the locking member **24** away the support base **14** and position its forward end **90A** within the groove **92** of the rearward end face **94** of the rearward pivot member **40** such that the locking member **24** is in a locked position. The fin portion **28** is thereby locked by the locking member **24** in the use position and ready for use to aid steering and stability of the watersport board **16** when ridden by a user.

(63) Should it become desirable to remove the foldable fin **12** from the support base **14** for cleaning, repair or replacement, the user need only remove the fastener **26** that holds the retainer member **22** in position within the rearward recess **68** of the rearward channel portion **60** and remove the retainer member **22** and the locking member **24** pivotally attached thereto. With the retainer member **22** and locking member **24** removed, the forward end portion **90** of the locking member **24** no longer inhibits rearward movement of the rearward pivot member **40**, and the rearward pivot member **40** may be moved sufficiently rearward to move the forward pivot member **38** sufficiently rearward to fully withdraw the forward pivot member **38** from within both the outward recess portion **64B** and the inward recess portion **64A** of the forward recess **64**. Once so withdrawn, the inward recess portion **64A** no longer limits the extent of movement of the forward pivot member **38** away from the bottom wall **56A** of the channel **56** and the foldable fin **12** can be disconnected from the support base **14**. To reinstall the foldable fin **12**, or a replacement foldable fin, the above-described process is repeated in reverse. While the foldable fin **12** may be remove from the support base **14** as described, during normal use, transportation and storage, the foldable fin **12** stays attached to the support base **14**, and hence to the watersport board **16**, whether in the use position or the folded position.

(64) The foldable fin **12** may be made of a glass filled nylon, or any polymer, composite material, metal, foam, and/or wood, and can be rigid, have a high tensile strength, and/or be impact resistant. The support base **14** may be made of acrylonitrile butadiene styrene (ABS), any polymer or composite material, and/or from a material that is weldable and/or impact resistant. The locking member **24** may be made of an injected polymer, composite material, and/or metal.

EXAMPLES

(65) The following examples are illustrative of several embodiments of the present technology. 1. A fin assembly for a watersport board, comprising: a support base having a locking member, the support base being configured to attach the fin assembly to a surface of the watersport board, and a foldable fin comprising a fin base portion coupled to the support base and a fin portion extending from the fin base portion, wherein: the fin portion is configured to move between a folded position and a use position, and the locking member is configured to lock the fin portion in and release the fin portion from the use position. 2. The fin assembly of any one of the embodiments herein wherein: the support base comprises a channel extending along a longitudinal axis of the support base; and the channel receives at least a portion of the fin base portion so as to movably couple the fin base portion to the support base. 3. The fin assembly of any one of the embodiments wherein: the channel comprises a first channel portion and a second channel portion; and the fin base portion comprises a first pivot member positioned in the first channel portion and a second pivot member positioned in the second channel portion. 4. The fin assembly of any one of the embodiments wherein the first pivot member and the second pivot member are spaced apart from each other on opposing end portions of the fin base portion. 5. The fin assembly of any one of the embodiments

wherein the first channel portion comprises a recess portion configured to receive and limit movement of the first pivot member when the fin portion is in the use position. 6. The fin assembly of any one of the embodiments wherein the locking member is configured to engage with the second pivot member so as to lock the fin portion in the use position. 7. The fin assembly of any one of the embodiments wherein: the second pivot member comprises a groove; and the locking member is configured to be positioned within the groove to limit movement of the second pivot member. 8. The fin assembly of any one of the embodiments wherein: the first channel portion comprises a first wall portion configured to limit movement of the first pivot member away from the support base, the second channel portion comprises a second wall portion configured to limit movement of the second pivot member away from the support base, and the fin base portion remains attached to the support base by the first wall portion and the second wall portion when the foldable fin is in the folded position. 9. The fin assembly of any one of the embodiments wherein the support base comprises: a mounting side portion configured to be mounted on the surface of the watersport board; and an outward projecting portion extending along the longitudinal axis of the support base and projecting away from the mounting side portion of the support base. 10. The fin assembly of any one of the embodiments wherein: the outward projecting portion comprises the channel, and the channel has an opening facing outward away from the mounting side portion of the support base. 11. The fin assembly of any one of the embodiments wherein the outward projecting portion comprises a first wall and a second wall laterally spaced apart from each other by a distance to receive a middle portion of the fin base portion therebetween and provide lateral support to the fin base portion when the fin portion is in the use position. 12. The fin assembly of any one of the embodiments, wherein the support base has a recess, and the fin assembly further comprises: a retainer member received in the recess and configured to attach the locking member to the support base; and a fastener configured to removably hold the retainer member to the support base. 13. A watersport system comprising: watersport equipment having a surface; and a fin assembly mounted to the surface of the watersport equipment, the fin assembly comprising— a support base having a locking member, the support base being configured to attach the fin assembly to the surface of the watersport equipment, and a foldable fin movably coupled to the support base, the foldable fin comprising a fin base portion coupled to the support base and a fin portion extending from the fin base portion, wherein: the fin portion is movable between a folded position substantially parallel to the surface of the watersport equipment and a use position substantially perpendicular to the surface, and the locking member is configured to lock the fin portion in and release the fin portion from the use position. 14. The watersport system of any one of the embodiments wherein the watersport equipment is a board. 15. The watersport system of any one of the embodiments wherein: the support base comprises a channel extending along a longitudinal axis of the support base; and the channel receives at least a portion of the fin base portion so as to movably couple the fin base portion to the support base. 16. The watersport system of any one of the embodiments wherein: the channel comprises a first channel portion and a second channel portion; and the fin base portion comprises a first pivot member positioned in the first channel portion and a second pivot member positioned in the second channel portion. 17. The watersport system of any one of the embodiments wherein the first channel portion comprises a recess portion configured to receive and limit movement of the first pivot member when the fin portion is in the use position. 18. The watersport system of any one of the embodiments wherein the locking member is configured to engage with the second pivot member so as to lock the fin portion in the use position. 19. The watersport system of any one of the embodiments wherein: the second pivot member comprises a groove; and the locking member is configured to be positioned within the groove to limit movement of the second pivot member. 20. The watersport system of any one of the embodiments wherein: the first channel portion comprises a first wall portion configured to limit movement of the first pivot member away from the support base, the second channel portion comprises a second wall portion configured to limit movement of the second pivot member

away from the support base, and the fin base portion remains attached to the support base by the first wall portion and the second wall portion when the foldable fin is in the folded position. 21. The watersport system of any one of the embodiments wherein the support base comprises a first wall and a second wall that extend along the longitudinal axis of the support base and are laterally spaced apart from each other by a distance to receive a middle portion of the fin base portion therebetween and provide lateral support to the fin base portion when the fin portion is in the use position. 22. A method of using a fin assembly on watersport equipment, the method comprising: moving a locking member to a release position; moving a foldable fin in a first direction longitudinally relative to a support base; moving the foldable fin away from the support base along a second direction of the support base that is different from the first direction; and rotating the foldable fin along a rotation axis to place a fin portion of the foldable fin in a folded position. 23. The method of any one of the embodiments, further comprising: maintaining attachment of a fin base portion of the foldable fin to the support base when the foldable fin is in the folded position. 24. The method of any one of the embodiments wherein the second direction is substantially perpendicular to the first direction. 25. The method of any one of the embodiments wherein the second direction of the support base is substantially perpendicular to a surface of the watersport equipment to which the fin assembly is attached. 26. The method of any one of the embodiments, further comprising: removing a fastener that is configured to hold a retainer member in position so as to attach the locking member to the support base; removing the retainer member; removing the locking member; and removing the foldable fin from the support base. 27. The method of any one of the embodiments, further comprising: rotating the foldable fin along the rotation axis; moving the foldable fin toward the support base, moving the foldable fin longitudinally relative to the support base to place the fin portion to a use position; and locking the fin portion in the use position by rotating the locking member to a locked position. 28. A fin assembly, comprising: a support base having a locking member, the support base being configured to fixedly attach the fin assembly to a surface of watersport equipment; and a foldable fin comprising a fin base portion coupled to the support base and a fin portion extending from the fin base portion, wherein: the fin portion is configured to move between a folded position and a use position, and the locking member is configured to lock the fin portion in and release the fin portion from the use position.

(66) The foregoing described embodiments depict different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected,” or “operably coupled,” to each other to achieve the desired functionality.

(67) While particular embodiments of the present technology have been shown and described, it will be obvious to those skilled in the art that, based upon the teachings herein, changes and modifications may be made without departing from this technology and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of this technology. Furthermore, it is to be understood that the technology is solely defined by the appended claims. It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of

such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to technologies containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations).

(68) Conjunctive language, such as phrases of the form “at least one of A, B, and C,” or “at least one of A, B and C,” (i.e., the same phrase with or without the Oxford comma) unless specifically stated otherwise or otherwise clearly contradicted by context, is otherwise understood with the context as used in general to present that an item, term, etc., may be either A or B or C, any nonempty subset of the set of A and B and C, or any set not contradicted by context or otherwise excluded that contains at least one A, at least one B, or at least one C. For instance, in the illustrative example of a set having three members, the conjunctive phrases “at least one of A, B, and C” and “at least one of A, B and C” refer to any of the following sets: {A}, {B}, {C}, {A, B}, {A, C}, {B, C}, {A, B, C}, and, if not contradicted explicitly or by context, any set having {A}, {B}, and/or {C} as a subset (e.g., sets with multiple “A”). Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of A, at least one of B, and at least one of C each to be present. Similarly, phrases such as “at least one of A, B, or C” and “at least one of A, B or C” refer to the same as “at least one of A, B, and C” and “at least one of A, B and C” refer to any of the following sets: {A}, {B}, {C}, {A, B}, {A, C}, {B, C}, {A, B, C}, unless differing meaning is explicitly stated or clear from context.

Claims

1. A fin assembly for a watersport board, comprising: a support base having a locking member, the support base being configured to attach the fin assembly to a surface of the watersport board, and a foldable fin comprising a fin base portion coupled to the support base and a fin portion extending from the fin base portion, wherein: the fin portion is configured to move between a folded position and a use position, and the locking member is configured to lock the fin portion in and release the fin portion from the use position.
2. The fin assembly of claim 1 wherein: the support base comprises a channel extending along a longitudinal axis of the support base; and the channel receives at least a portion of the fin base portion so as to movably couple the fin base portion to the support base.
3. The fin assembly of claim 2 wherein: the channel comprises a first channel portion and a second channel portion; and the fin base portion comprises a first pivot member positioned in the first channel portion and a second pivot member positioned in the second channel portion.
4. The fin assembly of claim 3 wherein the first pivot member and the second pivot member are spaced apart from each other on opposing end portions of the fin base portion.
5. The fin assembly of claim 3 wherein the first channel portion comprises a recess portion configured to receive and limit movement of the first pivot member when the fin portion is in the use position.
6. The fin assembly of claim 3 wherein the locking member is configured to engage with the second pivot member so as to lock the fin portion in the use position.
7. The fin assembly of claim 6 wherein: the second pivot member comprises a groove; and the

locking member is configured to be positioned within the groove to limit movement of the second pivot member.

8. The fin assembly of claim 3 wherein: the first channel portion comprises a first wall portion configured to limit movement of the first pivot member away from the support base, the second channel portion comprises a second wall portion configured to limit movement of the second pivot member away from the support base, and the fin base portion remains attached to the support base by the first wall portion and the second wall portion when the foldable fin is in the folded position.

9. The fin assembly of claim 2 wherein the support base comprises: a mounting side portion configured to be mounted on the surface of the watersport board; and an outward projecting portion extending along the longitudinal axis of the support base and projecting away from the mounting side portion of the support base.

10. The fin assembly of claim 9 wherein: the outward projecting portion comprises the channel, and the channel has an opening facing outward away from the mounting side portion of the support base.

11. The fin assembly of claim 9 wherein the outward projecting portion comprises a first wall and a second wall laterally spaced apart from each other by a distance to receive a middle portion of the fin base portion therebetween and provide lateral support to the fin base portion when the fin portion is in the use position.

12. The fin assembly of claim 1, wherein the support base has a recess, and the fin assembly further comprises: a retainer member received in the recess and configured to attach the locking member to the support base; and a fastener configured to removably hold the retainer member to the support base.

13. A watersport system comprising: watersport equipment having a surface; and a fin assembly mounted to the surface of the watersport equipment, the fin assembly comprising— a support base having a locking member, the support base being configured to attach the fin assembly to the surface of the watersport equipment, and a foldable fin movably coupled to the support base, the foldable fin comprising a fin base portion coupled to the support base and a fin portion extending from the fin base portion, wherein: the fin portion is movable between a folded position substantially parallel to the surface of the watersport equipment and a use position substantially perpendicular to the surface, and the locking member is configured to lock the fin portion in and release the fin portion from the use position.

14. The watersport system of claim 13 wherein the watersport equipment is a board.

15. A method of using a fin assembly on watersport equipment, the method comprising: moving a locking member to a release position; moving a foldable fin in a first direction longitudinally relative to a support base; moving the foldable fin away from the support base along a second direction of the support base that is different from the first direction; and rotating the foldable fin along a rotation axis to place a fin portion of the foldable fin in a folded position.

16. The method of claim 15, further comprising: maintaining attachment of a fin base portion of the foldable fin to the support base when the foldable fin is in the folded position.

17. The method of claim 15 wherein the second direction is substantially perpendicular to the first direction.

18. The method of claim 15 wherein the second direction of the support base is substantially perpendicular to a surface of the watersport equipment to which the fin assembly is attached.

19. The method of claim 15, further comprising: removing a fastener that is configured to hold a retainer member in position so as to attach the locking member to the support base; removing the retainer member; removing the locking member; and removing the foldable fin from the support base.

20. The method of claim 15, further comprising: rotating the foldable fin along the rotation axis; moving the foldable fin toward the support base, moving the foldable fin longitudinally relative to

the support base to place the fin portion to a use position; and locking the fin portion in the use position by rotating the locking member to a locked position.
