

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                    |
|----------------------|--------------------|
| United States Patent | 12416142           |
| Kind Code            | B2                 |
| Date of Patent       | September 16, 2025 |
| Inventor(s)          | Kondo; Yuta et al. |

---

### Discharge valve device, flush water tank device, and flush toilet

---

#### Abstract

A discharge valve device includes a valve body, an actuation shaft, a water storage cylinder, and a float, and from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode in which the flush water in a water storage tank is supplied from a discharge opening to the flush toilet in a first flush water amount or a small flushing mode in which the flush water is supplied in a second flush water amount smaller than the first flush water amount is selectively executable, and the water storage cylinder or the float is configured to change a lowering speed of the float with decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode.

---

**Inventors:** Kondo; Yuta (Kitakyushu, JP), Matsuda; Haruki (Kitakyushu, JP), Hiwa; Koichiro (Kitakyushu, JP), Shimokawa; Yuki (Kitakyushu, JP)

**Applicant:** TOTO LTD. (Kitakyushu, JP)

**Family ID:** 1000008821938

**Assignee:** TOTO LTD. (Kitakyushu, JP)

**Appl. No.:** 18/100793

**Filed:** January 24, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20230243138 A1   | Aug. 03, 2023    |

#### Foreign Application Priority Data

|    |             |               |
|----|-------------|---------------|
| JP | 2022-012162 | Jan. 28, 2022 |
| JP | 2022-012163 | Jan. 28, 2022 |
| JP | 2022-012164 | Jan. 28, 2022 |

---

## Publication Classification

**Int. Cl.:** E03D3/12 (20060101); E03D1/35 (20060101)

**U.S. Cl.:**

**CPC** E03D3/12 (20130101); E03D1/35 (20130101);

## Field of Classification Search

**CPC:** E03D (3/12); E03D (1/14); E03D (1/33); E03D (1/35)

**USPC:** 4/324; 4/325; 4/395-404; 4/416

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name  | U.S. Cl. | CPC        |
|--------------|-------------|----------------|----------|------------|
| 2004/0111793 | 12/2003     | Sutherland     | 4/325    | E03D 1/142 |
| 2013/0055496 | 12/2012     | YYoshioka      | 4/324    | E03D 1/33  |
| 2021/0270025 | 12/2020     | Hayashi et al. | N/A      | N/A        |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| H07-011680  | 12/1994          | JP      | N/A |
| H08-134979  | 12/1995          | JP      | N/A |
| 2014-185491 | 12/2013          | JP      | N/A |
| 2019-157601 | 12/2018          | JP      | N/A |
| 2021-055449 | 12/2020          | JP      | N/A |
| 2021-134630 | 12/2020          | JP      | N/A |

### OTHER PUBLICATIONS

Office Action for JP Application No. 2022-012163, dated Jul. 18, 2023. cited by applicant

Office Action for JP Application No. 2022-012164, dated Jul. 18, 2023. cited by applicant

Office Action (with translation) issued in JP 2022-012162, dated Jun. 19, 2025 [6 pages]. cited by applicant

---

*Primary Examiner:* Nguyen; Tuan N

*Attorney, Agent or Firm:* IceMiller LLP

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims benefit of priority to Japanese Patent Applications No. 2022-012162 (filed on Jan. 28, 2022), No. 2022-012163 (filed on Jan. 28, 2022), and No. 2022-012164 (filed on Jan. 28, 2022), the entire contents of which are incorporated herein by reference.

### BACKGROUND OF THE INVENTION

(2) The present invention relates to a discharge valve device, a flush water tank device, and a flush toilet, and more particularly to a discharge valve device provided in a flush water tank device that supplies flush water to a flush toilet, a flush water tank device including this discharge valve device, and a flush toilet including this flush water tank device.

#### Description of the Related Art

(3) Conventionally, as a discharge valve device provided in a flush water tank that supplies flush water to a flush toilet, for example, a device has been known that includes a discharge valve to open and close a discharge opening of a flush water tank and that uses buoyancy by a float in an operation of opening and closing this discharge valve as disclosed in Japanese Patent Laid-Open No. 2014-185491 and Japanese Patent Laid-Open No. 2019-157601. First, the conventional discharge valve device disclosed in Japanese Patent Laid-Open No. 2014-185491 includes a valve body that opens and closes the discharge opening provided in a bottom of the flush water tank, an actuation shaft that moves up and down to open and close the valve body, a water storage cylinder in which this actuation shaft is inserted in a vertical direction and that stores part of flush water in the flush water tank, and the float that is disposed in this water storage cylinder and that causes buoyancy to act on the actuation shaft. Further, in the conventional discharge valve device disclosed in Japanese Patent Laid-Open No. 2014-185491, since the float is disposed in the water storage cylinder, the float is not affected by flow of flush water outside the water storage cylinder, and a valve opening time of the discharge valve can be kept constant. An amount of flush water drained from the discharge opening of the flush water tank during large flushing is different from an amount of flush water during small flushing.

(4) Next, a conventional discharge valve device described in Japanese Patent Laid-Open No. 2019-157601 described above is a so-called ball tap type of discharge valve device including two floats, a float for large flushing and a float for small flushing. In this discharge valve device, a valve opening time of the discharge valve during large flushing is set longer than a valve opening time of the discharge valve during small flushing, and hence the flush water amount during large flushing can be set larger than the flush water amount during small flushing.

(5) In the conventional discharge valve device described in Japanese Patent Laid-Open No. 2014-185491 described above, during large flushing and small flushing, the valve opening time of the discharge valve is kept constant, while a difference is made in amount of flush water drained from the discharge opening of the flush water tank. Accordingly, especially during small flushing, immediately after the discharge valve is opened, a flow rate per unit time of flush water drained from the discharge opening (hereinafter referred to as “instantaneous flow rate”) [L/min] indicates about the same maximum value (so-called “water draining peak”) as in large flushing. However, subsequently, while the discharge valve is opened, the instantaneous flow rate [L/min] noticeably decreases as compared with large flushing. Therefore, maintaining the instantaneous flow rate [L/min] as high as possible has been a conventionally required issue to ensure satisfactory flushing performance. Further, in the conventional discharge valve device described in Patent Laid-Open No. 2019-157601 described above, two floats, the float for large flushing and the float for small flushing, are used to change the valve opening time of the discharge valve during each of large flushing and small flushing, and hence the instantaneous flow rate [L/min] of flush water drained from the discharge opening during small flushing can be maintained comparatively high. However, there is a problem in that as the instantaneous flow rate [L/min] of the flush water drained from the discharge opening is maintained comparatively high, closing sound generated when the discharge valve closes the discharge opening increases. This leads to a problem in that design of a size of each of two floats, the float for large flushing and the float for small flushing, has to be contrived. To solve the problems, the present inventors have focused on changing a lowering speed of the float with decrease in water level in the water storage cylinder depending on a selected large or small flushing mode, to maintain a comparatively high instantaneous flow rate [L/min] of flush

water drained from the discharge opening during small flushing and to reduce the closing sound generated when the discharge valve closes the discharge opening. Accordingly, the present inventors have found various means that can change a lowering time of the float and the valve opening time of the valve body depending on the flushing mode.

(6) That is, an object of the present invention, which has been made to solve the above-described conventionally requested issues and conventional technical problems, is to provide a discharge valve device, a flush water tank device and a flush toilet in which changing a lowering speed of a float with decrease in water level in a water storage cylinder depending on the selected large flushing mode or small flushing mode can maintain a comparatively high instantaneous flow rate [L/min] of flush water drained from a discharge opening during small flushing and can reduce closing sound generated when a discharge valve closes the discharge opening.

#### SUMMARY OF THE INVENTION

(7) In order to solve the above-described problems, the present invention provides a discharge valve device provided in a flush water tank that supplies flush water to a flush toilet, the discharge valve device comprising: a valve body configured to open and close a discharge opening provided in a bottom of the flush water tank; an actuation shaft including a lower end provided with the valve body, the actuation shaft being configured to open and close the discharge opening by moving up and down the valve body; a water storage cylinder configured to store a part of flush water in the flush water tank, the water storage cylinder including an outlet port configured to cause flush water in the water storage cylinder to flow outside of the water storage cylinder, the actuation shaft being inserted into the water storage cylinder in a vertical direction; and a float disposed in the water storage cylinder, the float being configured to cause buoyancy obtained by the flush water in the water storage cylinder to act on the actuation shaft, wherein when the float lowers with decrease in water level in the water storage cylinder, the actuation shaft and the valve body are configured to be lowered in conjunction with the float and the valve body is configured to close the discharge opening, during a period from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode or a small flushing mode is selectively performed, in the large flushing mode the flush water in the flush water tank is supplied from the discharge opening to the flush toilet in a first flush water amount, and in the small flushing mode the flush water is supplied in a second flush water amount smaller than the first flush water amount, and the water storage cylinder or the float is configured to change a lowering speed of the float with the decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode. According to the present invention described above, to start flushing of the flush toilet, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft of the discharge valve device is raised, to raise (open) the valve body, and the flush water in the flush water tank is supplied from the discharge opening to the flush toilet. Then, the water level in the water storage cylinder decreases depending on the selected large flushing mode or small flushing mode, and the float in the water storage cylinder lowers with the decrease in water level. Accordingly, as the actuation shaft of the discharge valve device lowers, the valve body lowers (closes), and the supply of flush water from the flush water tank to the flush toilet is stopped, to finish the flushing of the flush toilet. At this time, since the water storage cylinder or the float is configured to change the lowering speed of the float with the decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode, a lowering time of the float and a valve opening time of the valve body can be changed depending on the selected flushing mode. Therefore, a flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, by changing the lowering speed of the float with the decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode, closing sound generated when the valve body

closes the discharge opening can be reduced.

(8) In the present invention, preferably, the water storage cylinder is configured to increase a total opening area of the outlet port during the small flushing mode as compared to a total opening area of the outlet port during the large flushing mode, when the valve body is opened, and a flush water amount per unit time of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode is larger than in the large flushing mode. According to the present invention described above, the water storage cylinder is configured to increase the total opening area of the outlet port during the small flushing mode as compared to the total opening area of the outlet port during the large flushing mode when the valve body is opened, and the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) in the small flushing mode is larger than in the large flushing mode. Therefore, the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(9) In the present invention, preferably, the water storage cylinder includes a first outlet port that causes the flush water in the water storage cylinder to flow out to the flush water tank in the large flushing mode, and a second outlet port that causes the flush water in the water storage cylinder to flow out to the flush water tank in the small flushing mode. When the valve body is opened, total opening areas of the first outlet port and the second outlet port are the same as each other, the second outlet port is disposed above the first outlet port, and the water storage cylinder is configured to increase a second flush water amount per unit time of the flush water in the water storage cylinder flowing out from the second outlet port to the flush water tank in the small flushing mode as compared to a first flush water amount per unit time of the flush water in the water storage cylinder flowing out from the first outlet port to the flush water tank in the large flushing mode. According to the present invention described above, when the valve body is opened during the large flushing mode, the flush water in the water storage cylinder flows out from the first outlet port to the flush water tank, whereas when the valve body is opened during the small flushing mode, the flush water in the water storage cylinder flows out from the second outlet port to the flush water tank. At this time, even if the total opening areas of the first outlet port and the second outlet port are the same as each other, the second outlet port is disposed above the first outlet port. Therefore, the second flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the second outlet port to the flush water tank in the small flushing mode (so-called “second water drainage speed”) can be increased as compared to the first flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the first outlet port to the flush water tank in the large flushing mode (so-called “first water drainage speed”). Therefore, since the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode, the lowering time of the float and the opening time of the valve body during the small flushing mode can be shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in

water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of the flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(10) In the present invention, preferably, the outlet port includes a first outlet port and a second outlet port. The water storage cylinder causes the flush water in the water storage cylinder to flow out from the first outlet port to the flush water tank in the large flushing mode, whereas the water storage cylinder causes the flush water in the water storage cylinder to flow out from both the first outlet port and the second outlet port to the flush water tank in the small flushing mode. According to the present invention described above, when the valve body is opened during the large flushing mode, the flush water in the water storage cylinder flows out from the first outlet port to the flush water tank, whereas when the valve body is opened during the small flushing mode, the flush water in the water storage cylinder flows out from both the first outlet port and the second outlet port to the flush water tank. At this time, a second flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from both the first outlet port and the second outlet port to the flush water tank in the small flushing mode (so-called “second water drainage speed”) can be increased as compared to a first flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the first outlet port to the flush water tank in the large flushing mode (so-called “first water drainage speed”). Therefore, since the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode, the lowering time of the float and the valve opening time of the valve body during the small flushing mode can be shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float lowering with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of the flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(11) In the present invention, preferably, the second outlet port is disposed above the first outlet port. According to the present invention described above, when the valve body is opened during the large flushing mode, the flush water in the water storage cylinder flows out only from the first outlet port to the flush water tank, whereas when the valve body is opened during the small flushing mode, the flush water in the water storage cylinder flows out from both the first outlet port and the second outlet port to the flush water tank. At this time, since the second outlet port is disposed above the first outlet port, the second flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from both the first outlet port and the second outlet port to the flush water tank in the small flushing mode (so-called “second water drainage speed”) can be increased as compared to the first flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out only from the first outlet port to the flush water tank in the large flushing mode (so-called “first drainage speed”). Therefore, since the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode, the lowering time of the float and the valve opening time of the valve body during the small flushing mode can be shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the

lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(12) In the present invention, preferably, the water storage cylinder includes a partition that closes a part of the outlet port, and the partition closes a part of the outlet port so that the total opening area of the outlet port during the large flushing mode is smaller than the total opening area of the outlet port during the small flushing mode. According to the present invention described above, the partition that closes a part of the outlet port of the water storage cylinder can close a part of the outlet port so that the total opening area of the outlet port during the large flushing mode is smaller than the total opening area of the outlet port during the small flushing mode. Consequently, since the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) is larger in the small flushing mode than in the large flushing mode, the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(13) In the present invention, preferably, the partition includes a communication hole that can communicate between inside of the water storage cylinder and inside of the flush water tank in a state where the outlet port is closed, the communication hole including an opening cross-sectional area smaller than an opening cross-sectional area of the outlet port. The partition causes the flush water in the water storage cylinder to flow out from the communication hole into the flush water tank in the state where the outlet port is closed in the large flushing mode, whereas the partition opens the outlet port and causes the flush water in the water storage cylinder to flow out from the whole outlet port into the flush water tank in the small flushing mode. According to the present invention described above, in the large flushing mode, the partition closes the outlet port, so that the flush water in the water storage cylinder can flow out into the flush water tank from the communication hole of the partition including a smaller opening cross-sectional area than that of the outlet port. On the other hand, in the small flushing mode, as the partition opens the outlet port, the flush water in the water storage cylinder can flow out from the whole outlet port into the flush water tank. Accordingly, the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the whole outlet port to the flush water tank (so-called “water drainage speed”) in the small flushing mode is larger than the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the communication hole of the partition to the flush water tank (so-called “water drainage speed”) in the large flushing mode. Therefore, the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode. This can make the valve opening

time of the valve body during the small flushing mode shorter than the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount per unit time [L/min] of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage speed”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(14) Next, the present invention provides a flush water tank device including the discharge valve device. The present invention including this configuration can provide the flush water tank device including the discharge valve device in which changing a lowering speed of a float with decrease in water level in a water storage cylinder depending on the selected large flushing mode or small flushing mode can maintain a comparatively high instantaneous flow rate [L/min] of flush water drained from a discharge opening during small flushing, and can reduce closing sound generated when a valve body closes the discharge opening.

(15) Next, the present invention provides a flush toilet including the flush water tank device. The present invention including this configuration can provide the flush toilet including the flush water tank device in which changing a lowering speed of a float with decrease in water level in a water storage cylinder depending on a selected large flushing mode or small flushing mode can maintain a comparatively high instantaneous flow rate [L/min] of flush water drained from a discharge opening during small flushing and can reduce closing sound generated when a valve body closes the discharge opening.

(16) Next, the present invention provides a discharge valve device provided in a flush water tank that supplies flush water to a flush toilet, the discharge valve device including a valve body that opens and closes a discharge opening provided in a bottom of the flush water tank, an actuation shaft including a lower end provided with the valve body, and moving up and down to open and close the valve body, a water storage cylinder in which the actuation shaft is inserted in a vertical direction and that stores part of flush water in the flush water tank, in the water storage cylinder, an outlet port being formed to cause flush water in the water storage cylinder to flow outside, and a float that is disposed in the water storage cylinder and that causes buoyancy obtained by the flush water in the water storage cylinder to act on the actuation shaft, wherein when the float lowers with decrease in water level in the water storage cylinder, the actuation shaft and the valve body are configured to be lowered in conjunction with the float, and the valve body is configured to close the discharge opening. During a period from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode or a small flushing mode is selectively performed, in the large flushing mode the flush water in the flush water tank is supplied from the discharge opening to the flush toilet in a first flush water amount, and in the small flushing mode the flush water is supplied in a second flush water amount smaller than the first flush water amount. A first total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the large flushing mode is larger than a second total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode. According to the present invention described above, when starting flushing of the flush toilet, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft of the discharge valve device is raised to raise (open) the valve body, and the flush water in the flush water tank is supplied from the discharge opening to the flush toilet. Then, the water level in the water storage cylinder decreases depending on the selected large flushing mode or small flushing mode, and the float in the water storage cylinder lowers with the decrease in water level. Therefore, the actuation shaft of



the discharge valve device lowers, the valve body lowers (closes), and the supply of flush water from the flush water tank to the flush toilet is stopped, to finish the flushing of the flush toilet. At this time, since the first total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the large flushing mode is larger than the second total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode, the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage amount”) depending on the selected large flushing mode or small flushing mode. Therefore, the flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(17) In the present invention, preferably, the water storage cylinder includes a water storage cylinder body including the outlet port, and a small tank communicatively connected to the water storage cylinder body, the small tank includes a communication opening that communicates with the water storage cylinder body, and a partition that opens and closes the communication opening, and the partition opens the communication opening to communicate between the water storage cylinder body and the small tank in the large flushing mode, whereas the partition closes the communication opening to separate the water storage cylinder body and the small tank in the small flushing mode. In the present invention including the configuration, the small tank communicatively connected to the water storage cylinder body includes a communication opening that communicates with the water storage cylinder body, and a partition that opens and closes the communication opening, so that the partition can communicate between the water storage cylinder body and the small tank by opening the communication opening in the large flushing mode. On the other hand, the partition of the small tank can separate the water storage cylinder body and the small tank by closing the communication opening in the small flushing mode. As a result, the first total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the large flushing mode can be larger than the second total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode, so that the lowering speed of the float during the small flushing mode can be larger than the lowering speed of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be changed by changing the flush water amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called “water drainage amount”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(18) In the present invention, preferably, the partition is provided rotatably with respect to the communication opening, rotates in a direction to open the communication opening in the large flushing mode, and rotates in a direction to close the communication opening in the small flushing

mode. According to the present invention described above, if the partition does not rotate with respect to the communication opening but is provided slidably with respect to the communication opening and when the communication opening is closed by the partition, a seal portion in contact with the partition and the communication opening has a risk of being damaged due to wear or the like caused by repeating sliding to open and close the partition with respect to the communication opening. However, according to the present invention, the partition is provided rotatably with respect to the communication opening, can rotate in the direction to open the communication opening in the large flushing mode, and can rotate in the direction to close the communication opening in the small flushing mode. Consequently, as compared with a form in which the partition slides to open and close the communication opening, a risk of the partition normally contacting the communication opening regardless of the flushing mode can be avoided while suppressing the number of parts. This can reduce a risk of damage due to wear or the like on a portion (seal portion) in contact with the partition that closes the communication opening in the small tank.

(19) In the present invention, preferably, the communication opening includes a locking portion that is provided at a rim of the communication opening and that rotatably supports the partition, and the locking portion restricts rotation of the partition, when the partition rotates in the direction to close the communication opening and contacts the locking portion in the small flushing mode. According to the present invention described above, the communication opening of the small tank includes the locking portion that is provided at the rim of the communication opening and that rotatably supports the partition, so that the locking portion can reliably restrict the rotation of the partition, when the partition rotates in the direction to close the communication opening and contacts the locking portion in the small flushing mode. Further, in a state where the partition is in contact with the locking portion in the small flushing mode, the partition and the rim of the communication opening can be reliably brought in contact and sealed by the locking portion, so that water tightness between the water storage cylinder body and the small tank can be improved. Therefore, in the small flushing mode, the flush water in the small tank can be reliably inhibited from flowing into the water storage cylinder body from the communication opening.

(20) In the present invention, preferably, the partition further includes a water weight portion configured to store flush water, the small tank further includes an auxiliary outlet port that is formed in a bottom surface of the small tank and that causes the flush water in the small tank to flow outside. In a state where the partition abuts on the locking portion, the water weight portion is to store flush water and the auxiliary outlet port of the small tank is opened. When the flush water in the small tank flows out from the auxiliary outlet port, the partition rotates in a direction apart from the locking portion and causes the flush water in the water weight portion to flow outside. According to the present invention described above, the partition includes the water weight portion that stores flush water, and the small tank includes the auxiliary outlet port that is formed in the bottom surface of the small tank and that causes the flush water in the small tank to flow outside. Therefore, in the state where the partition abuts on the locking portion, the water weight portion can store flush water, and the flush water in the small tank flows out from the auxiliary outlet port. Further, when the flush water in the small tank flows out from the auxiliary outlet port, the partition rotates in the direction apart from the locking portion, and the flush water in the water weight portion can flow out. Therefore, a series of rotating operations until the partition opens the closed communication opening of the small tank can be executed reliably and smoothly by using change in water level in the small tank and change in amount of flush water stored in the water weight portion.

(21) In the present invention, preferably, the partition at an initial position has a state where the partition is not in contact with the locking portion and the communication opening is opened and any flush water is not stored in the water weight portion, in a standby period in which any flushing mode is not executed and a period in which the large flushing mode is executed, the partition is maintained at the initial position, to close the auxiliary outlet port of the small tank, and flush water

is storable in the small tank, whereas in a period in which the small flushing mode is executed, the partition rotates from the initial position and contacts the locking portion, to maintain a state where the communication opening is closed, and then, when the flush water in the small tank flows out from the auxiliary outlet port, the partition causes the flush water in the water weight portion to flow outside while rotating toward the initial position and then returns to the initial position. According to the present invention described above, the partition at the initial position has the state where the partition is not in contact with the locking portion and the communication opening is opened and any flush water is not stored in the water weight portion, in the standby period in which any flushing mode is not executed and the period in which the large flushing mode is executed, the partition is maintained at the initial position, to close the auxiliary outlet port of the small tank, and flush water can be stored in the small tank. On the other hand, in the period in which the small flushing mode is executed, the partition rotates from the initial position and contacts the locking portion, to maintain the state where the communication opening is closed, and then, when the flush water in the small tank flows out from the auxiliary outlet port, the partition causes the flush water in the water weight portion to flow outside while rotating toward the initial position and can then return to the initial position. As a result, the lowering speed of the float with the decrease in water level in the water storage cylinder can be efficiently changed by efficiently changing the flush water amount (so-called "water drainage amount") of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank depending on the selected large flushing mode or small flushing mode.

(22) In the present invention, preferably, a top edge of the water storage cylinder body and a top edge of the small tank are flush with each other, and in a state where the communication opening is closed by the partition, an upper end of the partition protrudes upward from the top edge of the communication opening and the top edge of the small tank. According to the present invention described above, the top edge of the water storage cylinder body and the top edge of the small tank are flush with each other, and in the state where the communication opening of the small tank is closed by the partition, the upper end of the partition protrudes upward from the top edge of the communication opening or the top edge of the small tank, which can reliably suppress inflow from the small tank into the water storage cylinder body.

(23) Further, the present invention provides a flush water tank device including the discharge valve device. The present invention including this configuration can provide the flush water tank device including the discharge valve device in which changing the flush water amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called "water drainage amount") depending on the selected large flushing mode or small flushing mode can change the lowering speed of the float with the decrease in water level in the water storage cylinder, can maintain comparatively high the instantaneous flow rate [L/min] of the flush water drained from the discharge opening during the small flushing, and can reduce the closing sound generated when the valve body closes the discharge opening.

(24) Further, the present invention provides a flush toilet including the flush water tank device. The present invention including this configuration can provide the flush toilet including the flush water tank device including the discharge valve device in which changing the flush water amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank (so-called "water drainage amount") depending on the selected large flushing mode or small flushing mode can change the lowering speed of the float with the decrease in water level in the water storage cylinder, can maintain comparatively high the instantaneous flow rate [L/min] of the flush water drained from the discharge opening during small flushing, and can reduce the closing sound generated when the valve body closes the discharge opening.

(25) Next, the present invention provides a discharge valve device provided in a flush water tank that supplies flush water to a flush toilet, the discharge valve device including a valve body that opens and closes a discharge opening provided in a bottom of the flush water tank, an actuation

shaft including a lower end provided with the valve body, and moving up and down to open and close the valve body, a water storage cylinder in which the actuation shaft is inserted in a vertical direction and that stores part of flush water in the flush water tank, in the water storage cylinder, an outlet port being formed to cause flush water in the water storage cylinder to flow outside, and a float that is disposed in the water storage cylinder and that causes buoyancy obtained by the flush water in the water storage cylinder to act on the actuation shaft, wherein when the float lowers with decrease in water level in the water storage cylinder, the actuation shaft and the valve body are configured to be lowered in conjunction with the float, and the valve body is configured to close the discharge opening, during a period from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode or a small flushing mode is selectively performed, in the large flushing mode the flush water in the flush water tank is supplied from the discharge opening to the flush toilet in a first flush water amount, and in the small flushing mode the flush water is supplied in a second flush water amount smaller than the first flush water amount, and the float is configured to decrease buoyancy obtained during the small flushing mode as compared to buoyancy obtained during the large flushing mode. According to the present invention described above, to start flushing of the flush toilet, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft of the discharge valve device is raised, to raise (open) the valve body, and the flush water in the flush water tank is supplied from the discharge opening to the flush toilet. Then, the water level in the water storage cylinder decreases depending on the selected large flushing mode or small flushing mode, and the float in the water storage cylinder lowers with the decrease in water level. Thus, as the actuation shaft of the discharge valve device lowers, the valve body lowers (closes), and the supply of flush water from the flush water tank to the flush toilet is stopped, to finish the flushing of the flush toilet. At this time, since the buoyancy obtained in the float during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode, the lowering time of the float during the small flushing mode can be shorter than the lowering time of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, when the flush water in the water storage cylinder flows out from the outlet port to the flush water tank, a balance position between the water level in the water storage cylinder and the float can be changed and the lowering time of the float with the decrease in water level in the water storage cylinder can be changed, by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode. Therefore, the flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(26) In the present invention, preferably, the float includes a storing portion for storing flush water in a part of the float, and the storing portion is configured so that the amount of flush water stored during the small flushing mode is larger than the amount of flush water stored during the large flushing mode. According to the present invention described above, since the float includes the storing portion for storing flush water in a part of the float, this storing portion makes the amount of flush water stored during the small flushing mode larger than the amount of flush water stored during the large flushing mode. Consequently, a weight of the storing portion during the small flushing mode is also larger than a weight of the storing portion during the large flushing mode, and hence the buoyancy obtained in the float during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode. This can make the lowering time of the float during the small flushing mode shorter than the lowering time of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of

the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, when the flush water in the water storage cylinder flows out from the outlet port to the flush water tank, the balance position between the water level in the water storage cylinder and the float can be changed and the lowering time of the float with the decrease in water level in the water storage cylinder can be changed, by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can be reduced.

(27) In the present invention, preferably, the storing portion is provided in an upper part of the float and includes a peripheral wall surrounding a part of the upper part of the float to store flush water, and a partition provided to open and close an outlet formed in a part of the peripheral wall. The partition opens the outlet of the peripheral wall and allows flush water in the storing portion to flow out of the outlet during the large flushing mode, whereas the partition closes the outlet of the peripheral wall and maintains a state where flush water is stored in the storing portion to make the storing portion a water weight during the small flushing mode. According to the present invention described above, when the large flushing mode is executed, the partition opens the outlet of the peripheral wall of the storing portion provided in the upper part of the float, so that the flush water in the storing portion flows out from the outlet, and any flush water is not stored in the storing portion in the upper part of the float. Therefore, the buoyancy of the float can be set comparatively large. On the other hand, when the small flushing mode is executed, the partition closes the outlet of the peripheral wall, so that the flush water in the storing portion cannot flow out from the outlet, and flush water is stored in the storing portion in the upper part of the float. In this state, the storing portion itself functions as the water weight. This can set the buoyancy of the float during the small flushing mode to be smaller than during the large flushing mode. As a result, the lowering time of the float and the valve opening time of the valve body can be reliably switched, by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode. Further, the valve opening time of the valve body is not affected by manufacturing error of the flush water tank or the flush toilet to which the discharge valve device is applied, and hence proper flushing can be executed.

(28) In the present invention, preferably, the float includes a peripheral wall provided in a lower part of the float and surrounding a part of the lower part of the float to store flush water, a communication port formed in a part of the peripheral wall to communicate inside and outside the float, and a partition provided to open and close the communication port. The partition closes the communication port of the peripheral wall to regulate communication of flush water or air inside and outside the float during the large flushing mode, whereas the partition opens the communication port of the peripheral wall to enable the communication of flush water or air inside and outside the float during the small flushing mode. According to the present invention described above, when the large flushing mode is executed, the partition closes the communication port of the peripheral wall provided in the lower part of the float, so that the communication of flush water or air inside and outside the float is regulated. Therefore, air trapped in the float can set the buoyancy of the float to be comparatively large. On the other hand, when the small flushing mode is executed, the partition opens the communication port of the peripheral wall, to enable the communication of flush water or air inside and outside the float. Accordingly, part of air in the float is discharged from the communication port of the peripheral wall to outside of the float, and in the float, the flush water outside the float can partially flow into a lower region in the float by a volume of the discharged air. Therefore, a volume of air occupying inside of the float during the small flushing mode is smaller than a volume of air occupying the inside of the float during the large

flushing mode, and hence the buoyancy of the float during the small flushing mode can be set smaller than during the large flushing mode. As a result, the lowering time of the float and the valve opening time of the valve body can be reliably switched by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode. Further, the valve opening time of the valve body is not affected by the manufacturing error of the flush water tank or the flush toilet to which the drain valve device is applied, and hence proper flushing can be executed even for the flush toilet to which the device is applied.

(29) In the present invention, preferably, the float includes a top surface that closes an upper region of the peripheral wall and a lower opening formed along a bottom edge of the peripheral wall, and forms a generally cylindrical shape opened downward, and the communication port is provided at a height position between the top surface and the lower opening. According to the present invention described above, in a state where the communication port of the peripheral wall of the float is closed by the partition during the large flushing mode, the float is filled with air, and the flush water outside the float is inhibited from flowing into the float from the lower opening. On the other hand, in a state where the communication port of the peripheral wall of the float is opened by the partition during the small flushing mode, part of air in the float is discharged from the communication port, so that the flush water outside the float can flow into the float close to a height of the communication port from the lower opening and/or the communication port. The buoyancy that acts on the float during the small flushing mode decreases as compared to the buoyancy that acts on the float during the large flushing mode. As a result, the lowering time of the float and the valve opening time of the valve body can be reliably switched by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode. Further, since the valve opening time of the valve body is not affected by the manufacturing error of the flush water tank or the flush toilet to which the drain valve device is applied, proper flushing can be executed even for the flush toilet to which the device is applied.

(30) Next, the present invention provides a discharge valve device provided in a flush water tank that supplies flush water to a flush toilet, the discharge valve device including a valve body that opens and closes a discharge opening provided in a bottom of the flush water tank, an actuation shaft including a lower end provided with the valve body and moving up and down to open and close the valve body, and a float that is connected to the actuation shaft and that causes buoyancy obtained by the flush water in the flush water tank to act on the actuation shaft. When the float lowers with decrease in water level in the flush water tank, the actuation shaft and the valve body are configured to be lowered in conjunction with the float, and the valve body is configured to close the discharge opening. During a period from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode or a small flushing mode is selectively performed, in the large flushing mode the flush water in the flush water tank is supplied from the discharge opening to the flush toilet in a first flush water amount, and in the small flushing mode the flush water is supplied in a second flush water amount smaller than the first flush water amount. The float is configured to decrease the buoyancy obtained during the small flushing mode as compared to the buoyancy obtained during the large flushing mode. According to the present invention described above, to start flushing of the flush toilet, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft of the discharge valve device is raised, to raise (open) the valve body, and the flush water in the flush water tank is supplied from the discharge opening to the flush toilet. Then, when the water level in the flush water tank decreases depending on the selected large flushing mode or small flushing mode, the float lowers with the decrease in water level. Accordingly, as the actuation shaft of the discharge valve device lowers, the valve body lowers (closes), and the supply of flush water from the flush water tank to the flush toilet is stopped, to finish the flushing of the flush toilet. At this time, the buoyancy obtained in the float during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode, and hence the lowering time of the float during

the small flushing mode can be shorter than the lowering time of the float during the large flushing mode. This can make the lowering time of the float and the valve opening time of the valve body during the small flushing mode shorter than the lowering time of the float and the valve opening time of the valve body during the large flushing mode. As a result, a balance position between the water level in the flush water tank and the float can be changed and the lowering time of the float with the decrease in water level in the flush water tank can be changed, by changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode.

Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body closes the discharge opening can also be reduced.

(31) Further, the present invention provides a flush water tank device including the discharge valve device. The present invention including this configuration can provide the flush water tank device including the discharge valve device in which changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode can change the lowering time of the float with the decrease in water level, can maintain comparatively high the instantaneous flow rate [L/min] of flush water drained from the discharge opening during small flushing, and can reduce the closing sound generated when the valve body closes the discharge opening.

(32) Furthermore, the present invention provides a flush toilet including the flush water tank device. The present invention including this configuration can provide the flush toilet including the flush water tank device including the discharge valve device in which changing the buoyancy that acts on the float depending on the selected large flushing mode or small flushing mode can change the lowering time of the float with the decrease in water level, can maintain comparatively high the instantaneous flow rate [L/min] of the flush water drained from the discharge opening during small flushing, and can reduce the closing sound generated when the valve body closes the discharge opening.

(33) According to the discharge valve device, the flush water tank device, and the flush toilet of the present invention, changing the lowering speed of the float with decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode can maintain comparatively high the instantaneous flow rate [L/min] of flush water drained from the discharge opening during the small flushing and can reduce the closing sound generated when the drain valve closes the discharge opening.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings:

(2) FIG. 1 is a perspective view of a flush water tank device and a flush toilet to which a discharge valve device according to first to ninth embodiments of the present invention is applied as seen from diagonally above;

(3) FIG. 2 is a front sectional view of a flush water tank device including a discharge valve device according to the first embodiment of the present invention;

(4) FIG. 3A is a schematic diagram showing a configuration of the discharge valve device according to the first embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by a large flushing mode;

(5) FIG. 3B is a schematic diagram showing a configuration of the discharge valve device according to the first embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by a small flushing mode;

(6) FIG. 4A is a schematic diagram showing a configuration of a discharge valve device according to the second embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(7) FIG. 4B is a schematic diagram showing a configuration of the discharge valve device according to the second embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode;

(8) FIG. 5A is a schematic diagram showing a configuration of a discharge valve device according to the third embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(9) FIG. 5B is a schematic diagram showing a configuration of the discharge valve device according to the third embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode;

(10) FIG. 6A is a conceptual diagram of a configuration of a discharge valve device according to the fourth embodiment of the present invention and a state where a float is lowered after a valve is started to open by the large flushing mode;

(11) FIG. 6B is a conceptual diagram of the configuration of the discharge valve device according to the fourth embodiment of the present invention and a state where the float is lowered after the valve is started to open by the small flushing mode;

(12) FIG. 7 is a front sectional view of a flush water tank device including a discharge valve device according to the fifth embodiment of the present invention;

(13) FIG. 8 is a perspective view of the discharge valve device according to the fifth embodiment of the present invention as seen from diagonally above;

(14) FIG. 9 is a top view of the discharge valve device according to the fifth embodiment of the present invention;

(15) FIG. 10 is a cross-sectional view along the X-X-line of FIG. 9;

(16) FIG. 11A is a schematic diagram showing a configuration of the discharge valve device according to the fifth embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(17) FIG. 11B is a schematic diagram showing a configuration of the discharge valve device according to the fifth embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode;

(18) FIG. 12 is a front sectional view of a flush water tank device including a discharge valve device according to the sixth embodiment of the present invention;

(19) FIG. 13A is a schematic diagram showing a configuration of the discharge valve device according to the sixth embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(20) FIG. 13B is a schematic diagram showing a configuration of the discharge valve device according to the sixth embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode;

(21) FIG. 14A is a schematic diagram showing a configuration of a discharge valve device according to the seventh embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(22) FIG. 14B is a schematic diagram showing a configuration of the discharge valve device according to the seventh embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode;

(23) FIG. 15A is a schematic diagram showing a configuration of a discharge valve device according to the eighth embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode;

(24) FIG. 15B is a schematic diagram showing a configuration of the discharge valve device according to the eighth embodiment of the present invention and a series of operations from the



standby state until the valve is started to open and closed by the small flushing mode;

(25) FIG. 16A is a schematic diagram showing a configuration of a discharge valve device according to the ninth embodiment of the present invention and a series of operations from a standby state until a valve is started to open and closed by the large flushing mode; and

(26) FIG. 16B is a schematic diagram showing a configuration of the discharge valve device according to the ninth embodiment of the present invention and a series of operations from the standby state until the valve is started to open and closed by the small flushing mode.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(27) Hereinafter with reference to the accompanying drawings, some embodiments relating to a discharge valve device of the present invention, a flush water tank device including the discharge valve device and a flush toilet including the flush water tank device will be described. First, with FIGS. 1 to 3B, a discharge valve device 1 according to a first embodiment of the present invention, a flush water tank device 2 including the discharge valve device 1 and a flush toilet 4 including the flush water tank device 2 will be described. As shown in FIGS. 1 and 2, the flush toilet 4 including the flush water tank device 2 to which the discharge valve device 1 according to the first embodiment of the present invention is applied includes a ceramic toilet main body 8 that forms a bowl 6. On a rear side of an upper surface of the toilet main body 8, the flush water tank device 2 described later in detail is provided. When flush water stored in the flush water tank device 2 is supplied to the toilet main body 8 of the flush toilet 4 by actuation of the discharge valve device 1 of the present embodiment, inside of the bowl 6 is flushed. Here, as a form of the flush toilet 4 including the flush water tank device 2 to which the discharge valve device 1 of the present embodiment is applied, for example, a form of so-called “siphon-type flush toilet” may be applied that suctions waste in the bowl 6 by use of a siphon action and that discharges the waste at once to outside from a drain trap (not shown) on a downstream side, or a form of so-called “flush-away-type flush toilet” that pushes away waste by water flow due to water drop in the bowl 6 may be applied.

(28) Next, with reference to FIG. 2, a schematic configuration of the flush water tank device 2 to which the discharge valve device 1 of the present embodiment is applied will be described. As shown in FIG. 2, the flush water tank device 2 includes a ceramic exterior tank 10, a storage tank 12 that is a flush water tank disposed inside the exterior tank to store flush water for flushing the toilet, and a lid body 14 placed above the exterior tank 10. First, the storage tank 12 is attached to the exterior tank 10 via an insulating body 16 surrounding an outer periphery of the storage tank. Further, a discharge opening 18 communicating with a water conduit 8a of the toilet main body 8 is provided in a bottom of each of the storage tank 12 and the exterior tank 10. The discharge opening 18 can be opened and closed by the discharge valve device 1 of the present embodiment, which will be described later in detail. For the lid body 14 of the flush water tank device 2 of the present embodiment, a form in which hand washing means, such as a hand washing bowl (washbasin) or a hand washing faucet, is not provided on an upper surface of the lid body will be described, and a form in which the hand washing means is provided is also applicable.

(29) Next, as shown in FIG. 2, the flush water tank device 2 includes a water supply device 20 that supplies flush water into the storage tank 12. The water supply device 20 includes a water supply pipe 22, a valve unit 24 including a water supply valve (not shown), a water supplying float 26, a discharge pipe 28, and the like. First, the water supply pipe 22 connects a water supply source (not shown) such as an external water pipe and the valve unit 24, and can supply, to the valve unit 24, flush water supplied from the water supply source (not shown) such as the external water pipe. Next, the water supplying float 26 is coupled to the valve unit 24 via a lever 30 and moves up and down depending on a water level in the storage tank 12, to open and close the water supply valve (not shown) of the valve unit 24. Further, the discharge pipe 28 is connected to a downstream side of the valve unit 24. As the water supply valve (not shown) opens and closes, flush water from the valve unit 24 into the storage tank 12 can be discharged and stopped (supplied and stopped).

(30) Next, as shown in FIG. 2, the flush water tank device 2 includes an operation device 32 that operates the discharge valve device 1 to open and close the valve. The operation device 32 includes an operation lever 34 that is manually rotationally operated by a user, an actuating portion (pulling-up actuating portion 38) that pulls up a valve body 36 of the discharge valve device 1, and a plurality of rotary shafts (outer rotary shaft 40, inner rotary shaft 42) that couple the operation lever 34 and the pulling-up actuating portion 38, respectively.

(31) First, the operation lever 34 is provided on one of left and right outer sides of the exterior tank 10 (the right side of the exterior tank 10 of the flush water tank device 2 shown in FIG. 2 as seen from a front side) and can be rotationally operated about a rotation center axis A1 extending in a left-right direction, manually by the user. Next, the outer rotary shaft 40 is provided in the exterior tank 10, extends in the left-right direction and has one end side (operation lever 34 side) coupled to the operation lever 34. Further, the other end side (inner end side) of the outer rotary shaft 40 is coupled to one end side (outer end side) of the inner rotary shaft 42 disposed inside the outer rotary shaft.

(32) Next, the pulling-up actuating portion 38 has an upper end portion fixed to an upper end and a center side of the storage tank 12. The pulling-up actuating portion 38 includes a rotary spindle portion 44 coupled to the other end side (inner end side) of the inner rotary shaft 42, and a cylindrical rotating portion 46 provided on an outer peripheral side of the rotary spindle portion 44. When the rotary spindle portion 44 rotates about a rotation center axis A2, the cylindrical rotating portion 46 can rotate integrally with the rotary spindle portion 44 about the rotation center axis A2. Also, the cylindrical rotating portion 46 includes a first swing lever 48 involved in pulling up the valve body 36 when the valve body 36 of the discharge valve device 1 is opened to start flushing of the toilet, and a second swing lever 50 involved in switching a toilet flushing mode to either one of a large flushing mode or a small flushing mode. Further, the first swing lever 48 is connected to an upper side of a first bead chain 52, and a lower side of the first bead chain 52 is connected to an upper end portion of an actuation shaft 54 that actuates (linearly moves) the valve body 36 of the discharge valve device 1, which will be described later in detail. On the other hand, the second swing lever 50 is connected to an upper side of a second bead chain 56, and a lower side of the second bead chain 56 is connected to a part of a partition for switching large or small flushing (switching valve 58 for switching large or small flushing) of the discharge valve device 1 described later in detail.

(33) For example, to start toilet flushing by the large flushing mode, when the operation lever 34 shown in FIG. 2 is rotated at a predetermined angle (for example, 90 degrees) to one side (front side of FIG. 2) about the rotation center axis A1, the outer rotary shaft 40 and the inner rotary shaft 42 coupled to the operation lever 34 rotate to one side, and the rotary spindle portion 44 of the pulling-up actuating portion 38 rotates to one side about the rotation center axis A2. Accordingly, the cylindrical rotating portion 46 of the pulling-up actuating portion 38 rotates integrally with the rotary spindle portion 44 about the rotation center axis A2 to one side (front side of FIG. 2). The first swing lever 48 swings (rotates) to one side (front side of FIG. 2) to pull up the first bead chain 52, and the second swing lever 50 swings (rotates) to one side (front side of FIG. 2) to pull up the second bead chain 56. On the other hand, to start toilet flushing by the small flushing mode, when the operation lever 34 shown in FIG. 2 is rotated at a predetermined angle (for example, 90 degrees) on the other side (back side of FIG. 2) about the rotation center axis A1, the outer rotary shaft 40 and the inner rotary shaft 42 coupled to the operation lever 34 rotate to the other side, and the rotary spindle portion 44 of the pulling-up actuating portion 38 rotates to the other side about the rotation center axis A2. Consequently, the cylindrical rotating portion 46 of the pulling-up actuating portion 38 also rotates integrally with the rotary spindle portion 44 about the rotation center axis A2 to the other side (back side of FIG. 2). The first swing lever 48 swings (rotates) to the other side (back side of FIG. 2) to pull up the first bead chain 52, while the second swing lever 50 does not swing, and the second bead chain 56 is not pulled up.

(34) In the present embodiment, a form in which the user manually operates the operation lever **34** will be described as the operation device **32** that operates the discharge valve device **1**, but the embodiment is not limited to such a form, and another form is also applicable. For example, as another form of the operation device, a controller may electrically control actuation of a drive unit (motor or the like) of the pulling-up actuating portion based on a signal input from the user with an operation button or the like, and accordingly a pulling-up operation of the valve body **36** of the discharge valve device **1** with the first swing lever **48** and a switch operation of the large and small flushing modes with the second swing lever **50** may be automatically performed. Further, each of the bead chains **52** and **56** of the discharge valve device **1** of the present embodiment may be a linear wire member.

(35) Next, details of the discharge valve device **1** of the present embodiment will be described with reference to FIGS. **2** to **3B**. Here, in states (I) to (VI) of the discharge valve device **1** in each of the large flushing mode and the small flushing mode shown in FIGS. **3A** and **3B**, a state (standby state) before starting valve opening of the valve body **36** is obtained as the state (I), and thereafter, in time series, a valve opened state of the valve body **36** is obtained as states (II) to (V), and a valve closed state of the valve body **36** is obtained as state (VI).

(36) First, as shown in FIG. **2**, the discharge valve device **1** of the present embodiment includes a discharge opening forming portion **60** attached to a bottom surface of the storage tank **12** to form the discharge opening **18**, a water storage cylinder **62** provided above the discharge opening forming portion **60**, and an overflow pipe **64** attached to the discharge opening forming portion **60** to communicate with the discharge opening **18**. Next, as shown in FIG. **2**, the discharge valve device **1** includes a valve seat **66** formed at a top edge of the discharge opening **18**, the valve body **36** provided to be closable and movable linearly upward with respect to the valve seat **66**, and the actuation shaft **54** including a lower end provided with the valve body **36** and linearly moving (moving up and down) in a vertical direction to open and close the valve body **36**. The actuation shaft **54** is provided to be inserted in the water storage cylinder **62** in the vertical direction. Further, the water storage cylinder **62** stores part of the flush water in the storage tank **12**, and left and right side walls **62a** are provided with a first outlet port **68** and a second outlet port **70**, respectively, that cause the flush water in the water storage cylinder **62** to flow outside (into the storage tank **12**). Further, a float **72** is disposed in the water storage cylinder **62**. The float **72** is concentrically provided on an outer peripheral side of the actuation shaft **54**, moves (moves up and down) in conjunction with a water level in the water storage cylinder **62**, and allows buoyancy obtained by the flush water in the water storage cylinder **62** to act on the actuation shaft **54**.

(37) Next, as shown in FIG. **2**, the partition for switching large or small flushing (switching valve **58**) is openably and closably provided in the second outlet port **70** on one side of the left and right side walls **62a** of the water storage cylinder **62** (on the right side as the water storage cylinder **62** in FIG. **2** is seen from the front side). As shown in FIG. **3A**, to execute the toilet flushing by the large flushing mode, the partition (switching valve **58**) can close the second outlet port **70**, when the second bead chain **56** is pulled up by the second swing lever **50**. On the other hand, as shown in FIG. **3B**, to execute the toilet flushing by the small flushing mode, the partition (switching valve **58**) can open the second outlet port **70**, when the second bead chain **56** loosens without being pulled up by the second swing lever **50**.

(38) That is, as shown in the states (II) to (V) of FIG. **3A**, when the valve body **36** is opened for the large flushing mode, the first outlet port **68** is normally open, and the second outlet port **70** is closed by the switching valve **58**. On the other hand, as shown in the states (II) to (V) of FIG. **3B**, when the valve body **36** is opened for the small flushing mode, the first outlet port **68** is normally open, and the second outlet port **70** is opened by the switching valve **58**. These settings are such that a total opening area **S2** of the outlet ports **68** and **70** when the valve body **36** is opened in the small flushing mode shown in the states (II) to (V) of FIG. **3B** increases as compared to a total opening area **S1** of the outlet ports **68** and **70** of the water storage cylinder **62** when the valve body

**36** is opened in the large flushing mode shown in the states (II) to (V) of FIG. 3A ( $S2 < S1$ ).

Therefore, a flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from each outlet port **68**, **70** to the storage tank **12** when the valve body **36** is opened during the small flushing mode (so-called “water drainage speed  $Q2$ ”) is larger than a flush water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out only from the first outlet port **68** to the storage tank **12** when the valve body **36** is opened during the large flushing mode (so-called “water drainage speed  $Q1$ ”) ( $Q2 > Q1$ ).

(39) Here, in the states (I) to (VI) of each of FIGS. 3A and 3B, the water level in the storage tank **12** is denoted with sign  $W1$ , and the water level in the water storage cylinder **62** is denoted with sign  $W2$ . Since the flush water amount  $Q2$  per unit time of the flush water flowing out from the outlet ports **68** and **70** of the water storage cylinder **62** to the storage tank **12** during the small flushing mode is larger than the flush water amount  $Q1$  per unit time of the flush water flowing only from the first outlet port **68** of the water storage cylinder **62** during the large flushing mode ( $Q2 > Q1$ ), a lowering speed  $v2$  of the water level  $W2$  in the water storage cylinder **62** that lowers during the small flushing mode is also larger than a lowering speed  $v1$  of the water level  $W1$  in the water storage cylinder **62** that lowers during the large flushing mode ( $v2 > v1$ ). This also makes the lowering speed  $v2$  of the float **72** when the float **72** lowers in conjunction with decrease in water level in the water storage cylinder **62** during the small flushing mode to be larger than the lowering speed  $v1$  of the float **72** during the large flushing mode ( $v2 > v1$ ).

(40) Next, an operation of the discharge valve device **1** according to the first embodiment of the present invention will be described with reference to FIGS. 2 to 3B. First, with reference to FIGS. 2 and 3A, the large flushing mode executed by the discharge valve device **1** according to the first embodiment of the present invention will be described. To start the large flushing mode from the standby state (I) of FIGS. 2 and 3A, for example, when the user rotates the operation lever **34** shown in FIG. 2 at 90 degrees to the front side, each of the first swing lever **48** and the second swing lever **50** in an initial position state (standby state) shown in FIG. 2 is swung, and each of the first bead chain **52** and the second bead chain **56** is pulled up. Accordingly, as the actuation shaft **54** and the valve body **36** of the discharge valve device **1** are pulled up to linearly move upward via the first bead chain **52**, the float **72** is also integrally pulled up via the actuation shaft **54** (see the state (II) of FIG. 3A). Further, as a part of the partition (switching valve **58**) for switching large or small flushing of the discharge valve device **1** is pulled up via the second bead chain **56**, the switching valve **58** rotates to close the second outlet port **70** of the water storage cylinder **62** (see the state (II) of FIG. 3A).

(41) At this time, as shown in the state (II) of FIG. 3A, the float **72** and the valve body **36** are raised to the highest position, and the discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start draining of flush water from inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the state (III) of FIG. 3A, when the water level  $W1$  in the storage tank **12** decreases close to the upper end of the water storage cylinder **62** and further to a water level lower than the upper end of the water storage cylinder **62**, a water pressure due to the water level  $W2$  in the water storage cylinder **62** is higher than a water pressure due to the water level  $W1$  in the storage tank **12** outside the cylinder. Therefore, the flush water in the water storage cylinder **62** flows out from the first outlet port **68** into the storage tank **12** outside the cylinder. Then, as shown in the state (IV) of FIG. 3A, the water level  $W2$  in the water storage cylinder **62** is higher than the water level  $W1$  in the storage tank **12** outside the cylinder, but the flush water in the water storage cylinder **62** continues to flow out of the first outlet port **68**. Therefore, as the water level  $W2$  in the water storage cylinder **62** gradually decreases, the float **72** also lowers in conjunction with lowering of the water level  $W2$ .

(42) Next, as shown in the state (V) of FIG. 3A, when the water level  $W1$  in the storage tank **12** outside the water storage cylinder **62** decreases to below an upper end of the first outlet port **68** of the water storage cylinder **62**, outside of the first outlet port **68** of the water storage cylinder **62** is

open to the atmosphere. This increases a speed at which the flush water in the water storage cylinder **62** flows out of the first outlet port **68**, and the water level W2 in the water storage cylinder **62** further decreases. Therefore, the float **72** also lowers, and the actuation shaft **54** and the valve body **36** also lower integrally. Then, as shown in the state (VI) of FIG. 3A, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed. Accordingly, draining of flush water from the inside of the storage tank **12** to the discharge opening **18** is stopped, and supply of flush water from the flush water tank device **2** to the toilet main body **8** by the large flushing mode is finished. At this time, the float **72**, the actuation shaft **54** and the valve body **36** are in a stopped state, but a minimum water level DWL1 (draining stop water level so-called “dead water line”) in the storage tank **12** is located below a lower end of the first outlet port **68** of the water storage cylinder **62**. For this reason, the flush water in the water storage cylinder **62** continues to flow out from the first outlet port **68** to the storage tank **12** side. As only the water level W2 in the water storage cylinder **62** gradually decreases, a water pressure in the water storage cylinder **62** also decreases. At this time, as the water pressure in the water storage cylinder **62** decreases, the switching valve **58** that closes the second outlet port **70** of the water storage cylinder **62** is actuated (rotated) from a state where the valve closed state is maintained with the water pressure of the flush water in the water storage cylinder **62** in a direction to open the second outlet port **70**, thereby obtaining the valve opened state. That is, after the large flushing mode is finished, the switching valve **58** is in a state of opening the second outlet port **70** in the standby state until the next flushing mode is started.

(43) Next, with reference to FIGS. 2 and 3B, a small flushing mode executed by the discharge valve device **1** according to the first embodiment of the present invention will be described. To start the small flushing mode from FIG. 2 and the standby state (I) of FIG. 3B, for example, when the user rotates the operation lever **34** shown in FIG. 2 at 90 degrees to the back side, only the first swing lever **48** in the state at the initial position (standby state) shown in FIG. 2 is swung, and only the first bead chain **52** is pulled up. Accordingly, as the actuation shaft **54** and the valve body **36** of the discharge valve device **1** are pulled up and move linearly upward via the first bead chain **52**, the float **72** is also integrally pulled up via the actuation shaft **54** (see state (II) of FIG. 3B). On the other hand, the second swing lever **50** is not swung, and hence the second bead chain **56** cannot be pulled up, thereby maintaining a state where the second outlet port **70** of the water storage cylinder **62** is normally opened by the switching valve **58** for switching large or small flushing. The state where the switching valve **58** is normally open is maintained thereafter until the small flushing mode ends (see states (II) to (VI) of FIG. 3B).

(44) Further, as shown in the state (II) of FIG. 3B, the float **72** and the valve body **36** are raised to the highest position, and the discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start the draining of flush water from the inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the state (III) of FIG. 3B, when the water level W1 in the storage tank **12** decreases close to the upper end of the water storage cylinder **62** and further to a water level below the upper end of the water storage cylinder **62**, the water pressure due to the water level W2 in the water storage cylinder **62** is higher than the water pressure due to the water level W1 in the storage tank **12** outside the cylinder. Therefore, the flush water in the water storage cylinder **62** flows out of the first outlet port **68** and the second outlet port **70**, into the storage tank **12** outside the cylinder. Then, as shown in the states (IV) and (V) of FIG. 3B, the water level W2 in the water storage cylinder **62** is higher than the water level W1 in the storage tank **12** outside the cylinder, but the flush water in the water storage cylinder **62** continues to flow out of the outlet ports **68** and **70**. Therefore, as the water level W2 in the water storage cylinder **62** gradually decreases, the float **72** also lowers in conjunction with lowering of the water level W2.

(45) At this time, the flush water amount Q2 per unit time flowing out from the outlet ports **68** and **70** of the water storage cylinder **62** to the storage tank **12** during the small flushing mode shown in the state (IV) and (V) of FIG. 3B becomes larger than the flush water amount Q1 per unit time

flowing out only from the first outlet port **68** of the water storage cylinder **62** to the storage tank **12** during the large flushing mode shown in the state (IV) and (V) of FIG. 3A ( $Q2 > Q1$ ). Accordingly, the lowering speed  $v2$  when the water level  $W2$  in the water storage cylinder **62** and the float **72** lower during the small flushing mode also becomes larger than the lowering speed  $v1$  when the water level  $W1$  in the water storage cylinder **62** and the float **72** lower during the large flushing mode ( $v2 > v1$ ).

(46) Then, as shown in the state (VI) of FIG. 3B, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed, and the draining of flush water from the inside of the storage tank **12** to the discharge opening **18** is stopped. Accordingly, the supply of flush water from the flush water tank device **2** to the toilet main body **8** by the small flushing mode is finished. At this time, a minimum water level  $DWL2$  (draining stop water level so-called “dead water line”) in the storage tank **12** during the small flushing mode in the state (IV) of FIG. 3B is located above the minimum water level  $DWL1$  in the storage tank **12** during the large flushing mode in the state (VI) of FIG. 3A. That is, the minimum water level  $DWL2$  during the small flushing mode is higher than the minimum water level  $DWL1$  during the large flushing mode, by which the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the small flushing mode is lower than the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the large flushing mode.

(47) According to the discharge valve device **1** of the first embodiment of the present invention described above, to start the flushing of the flush toilet **4**, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft **54** of the discharge valve device **1** is raised to raise (open) the valve body **36**, and the flush water in the storage tank **12** of the flush water tank device **2** is supplied from the discharge opening **18** to the toilet main body **8** of the flush toilet **4**. Then, the water level  $W2$  in the water storage cylinder **62** decreases depending on the selected large flushing mode or small flushing mode, and the float **72** in the water storage cylinder **62** lowers with the decrease in water level  $W2$ . Accordingly, as the actuation shaft **54** of the discharge valve device **1** lowers, the valve body **36** lowers (closes), and the supply of flush water from the storage tank **12** to the flush toilet **4** is stopped, to finish the flushing of the flush toilet **4**. At this time, the lowering speeds  $v1$  and  $v2$  of the float **72** with the decrease in water level in the water storage cylinder **62** can be changed depending on the selected large flushing mode or small flushing mode, and hence a lowering time of the float **72** and a valve opening time of the valve body **36** can be changed depending on the selected flushing mode. Therefore, a flow rate per unit time of flush water (instantaneous flow rate) [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced by changing the lowering speeds  $v1$  and  $v2$  of the float **72** with the decrease in water level in the water storage cylinder **62** depending on the selected large flushing mode or small flushing mode.

(48) Further, according to the discharge valve device **1** of the present embodiment, the total opening area  $S2$  of the outlet ports **68** and **70** of the water storage cylinder **62** when the valve body **36** is opened during the small flushing mode is set larger than the total opening area  $S1$  of the outlet port **68** of the water storage cylinder **62** when the valve body **36** is opened during the large flushing mode ( $S2 > S1$ ). Consequently, the flush water amount  $Q2$  per unit time [L/min] (so-called “water drainage speed  $Q2$ ”) of the flush water in the water storage cylinder **62** flowing out from the outlet ports **68** and **70** to the storage tank **12** when the valve body **36** is opened during the small flushing mode is larger than the flush water amount  $Q1$  per unit time [L/min] (so-called “water drainage speed  $Q1$ ”) of flush water flowing out only from the first outlet port **68** to the storage tank **12** when the valve is opened during the large flushing mode, and hence the lowering speed  $v2$  of the float **72** during the small flushing mode can be larger than the lowering speed  $v1$  of the float **72** during the large flushing mode ( $v2 > v1$ ). Consequently, the lowering time of the float **72** and the valve opening

time of the valve body **36** during the small flushing mode can be shorter than the lowering time of the float **72** and the valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speeds  $v_1$ ,  $v_2$  of the float **72** with the decrease in water level in the water storage cylinder **62** can be changed by changing the flush water amounts  $Q_1$ ,  $Q_2$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from the outlet ports **68**, **70** to the storage tank **12** (so-called “water drainage speeds  $Q_1$ ,  $Q_2$ ”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced.

(49) Further, according to the discharge valve device **1** of the present embodiment, when the valve body **36** is opened during the large flushing mode, the flush water in the water storage cylinder **62** flows out from the first outlet port **68** to the flush water tank, whereas when the valve body **36** is opened during the small flushing mode, the flush water in the water storage cylinder **62** flows out from both the first outlet port **68** and the second outlet port **70** to the storage tank **12**. At this time, the second flush water amount  $Q_2$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from both the first outlet port **68** and the second outlet port **70** to the storage tank **12** in the small flushing mode (so-called “second water drainage speed  $Q_2$ ”) can be increased, as compared to the first flush water amount  $Q_1$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from the first outlet port **68** to the storage tank **12** in the large flushing mode (so-called “first water drainage speed  $Q_1$ ”). Therefore, since the lowering speed  $v_2$  of the float **72** during the small flushing mode can be larger than the lowering speed  $v_1$  of the float **72** during the large flushing mode, the lowering time of the float **72** and the valve opening time of the valve body **36** during the small flushing mode can be shorter than the lowering time of the float **72** and the valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed  $v_1$ ,  $v_2$  of the float **72** with the decrease in water level in the water storage cylinder **62** can be changed by changing the flush water amount  $Q_1$ ,  $Q_2$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from the outlet port **68**, **70** to the storage tank **12** (so-called “water drainage speed  $Q_1$ ,  $Q_2$ ”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced.

(50) Further, according to the discharge valve device **1** of the present embodiment, the switching valve **58** for switching large or small flushing that closes a part (second outlet port **70**) of the outlet ports **68** and **70** of the water storage cylinder **62** can close a part (second outlet port **70**) of the outlet ports **68** and **70** so that the total opening area  $S_1$  of the outlet port **68** during the large flushing mode is smaller than the total opening area  $S_2$  of the outlet ports **68** and **70** during the small flushing mode. Accordingly, since the flush water amount  $Q_2$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from the outlet ports **68** and **70** to the storage tank **12** when the valve body **36** is opened during the small flushing mode (so-called “water drainage speed  $Q_2$ ”) is larger than the flush water amount  $Q_1$  per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out only from the first outlet port **68** when the valve body **36** is opened during the large flushing mode (so-called “water drainage speed  $Q_1$ ”) ( $Q_2 > Q_1$ ), the lowering speed  $v_2$  of the float **72** during the small flushing mode can be larger than the lowering speed  $v_1$  of the float **72** during the large flushing mode ( $v_2 > v_1$ ). Therefore, the lowering time of the float **72** and the valve opening time of the valve body **36** during the small flushing mode can be shorter than the lowering time of the float **72** and the valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed  $v_1$ ,  $v_2$  of the float **72** with

the decrease in water level in the water storage cylinder **62** can be changed by changing the flush water amount **Q1**, **Q2** per unit time [L/min] of the flush water in the water storage cylinder **62** flowing out from the outlet port **68**, **70** to the storage tank **12** (so-called “water drainage speed **Q1**, **Q2**”) depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced.

(51) Next, with reference to FIGS. **1**, **4A**, and **4B**, a discharge valve device **100** according to a second embodiment of the present invention will be described. Here, in the discharge valve device **100** according to the second embodiment of the present invention shown in FIGS. **4A** and **4B**, the same part as in the discharge valve device **1** according to the first embodiment of the present invention described above is denoted with the same sign and is not described.

(52) First, as shown in FIGS. **4A** and **4B**, in the discharge valve device **100** according to the second embodiment of the present invention, a water storage cylinder **162** includes a single outlet port **168** in one of left and right side walls **162a**. Also, in the outlet port **168** of the water storage cylinder **162**, a partition (switching valve **158**) for switching large or small flushing is openably and closably provided. The switching valve **158** can slide in a vertical direction depending on a second bead chain **56** moving up and down, to open and close the outlet port **168**. Further, in the discharge valve device **100** of the present embodiment, the switching valve **158** includes a communication hole **170** that can communicate between inside of the water storage cylinder **162** and inside of a storage tank **12** in a state where the outlet port **168** is closed. The communication hole **170** has an opening sectional area set smaller than the outlet port **168**. Furthermore, in the discharge valve device **100** of the present embodiment, even if the outlet port **168** of the water storage cylinder **162** is closed by the switching valve **158**, the communication hole **170** can normally communicate between the inside of the water storage cylinder **162** and the inside of the storage tank **12**, and these structures are different from the structure of the discharge valve device **1** according to the first embodiment of the present invention described above.

(53) Next, with reference to FIGS. **4A** and **4B**, an operation of the discharge valve device **100** according to the second embodiment of the present invention will be described. First, in a standby state shown in state (I) of FIGS. **4A** and **4B**, the switching valve **158** opens the outlet port **168** of the water storage cylinder **162**. Then, when a large flushing mode is started from the standby state shown in the state (I) of FIG. **4A**, in state (II) of FIG. **4A**, an actuation shaft **54** and a valve body **36** are pulled upward by a first bead chain **52**. At this time, the switching valve **158** is also pulled upward by the second bead chain **56** to slide upward, and the outlet port **168** of the water storage cylinder **162** is closed by the switching valve **158** (see state (II) of FIG. **4A**).

(54) The state where the outlet port **168** of the water storage cylinder **162** is closed by the switching valve **158** is maintained from subsequent state (III) of FIG. **4A** to state (VI) of FIG. **4A** in which the valve body **36** is closed and the large flushing mode ends. However, as shown in the states (II) to (VI) of FIG. **4A**, even if the outlet port **168** of the water storage cylinder **162** is closed by the switching valve **158**, the communication hole **170** normally communicates between the inside of the water storage cylinder **162** and the inside of the storage tank **12**. Then, as shown in the states (IV) to (VI) of FIG. **4A**, when a water level **W1** in the storage tank **12** outside the water storage cylinder **162** becomes lower than a water level **W2** in the water storage cylinder **162**, a water pressure in the water storage cylinder **162** is higher than a water pressure in the storage tank **12**. Therefore, even in a state where the outlet port **168** of the water storage cylinder **162** is closed by the switching valve **158**, the flush water in the water storage cylinder **162** can flow out from the communication hole **170** into the storage tank **12** due to a difference in pressure between the inside of the water storage cylinder **162** and the inside of the storage tank **12** outside the cylinder.

(55) On one hand, when a small flushing mode is started from the standby state shown in the state



(I) of FIG. 4B, in the state (II) of FIG. 4B, the actuation shaft 54 and the valve body 36 are pulled upward by the first bead chain 52. On the other hand, the switching valve 158 is not pulled upward by the second bead chain 56 and does not slide upward, and hence the outlet port 168 of the water storage cylinder 162 is opened by the switching valve 158 (see state (II) of FIG. 4B). Then, a state where the outlet port 168 of the water storage cylinder 162 is normally opened by the switching valve 158 is maintained from the standby state (I) of FIG. 4B to state (VI) of FIG. 4B where the small flushing mode is finished. Additionally, in the state (VI) of FIG. 4B where the small flushing mode is finished, a minimum water level DWL2 in the storage tank 12 during the small flushing mode is located above the minimum water level DWL1 in the storage tank 12 during the large flushing mode in the state (VI) of FIG. 4A.

(56) According to the discharge valve device 100 of the second embodiment of the present invention described above, in the large flushing mode shown in FIG. 4A, as the switching valve 158 for switching large or small flushing closes the single outlet port 168 of the water storage cylinder 162, the flush water in the water storage cylinder 162 can flow out into the storage tank 12 from the communication hole 170 of the switching valve 158 that has an opening sectional area smaller than the outlet port 168. On the other hand, in the small flushing mode shown in FIG. 4B, the switching valve 158 normally opens the outlet port 168, and hence the flush water in the water storage cylinder 162 can flow out from the whole outlet port 168 into the storage tank 12.

Accordingly, a flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder 162 flowing out from the whole outlet port 168 to the storage tank 12 in the small flushing mode (so-called “water drainage speed  $Q2$ ”) becomes larger than a flush water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder 162 flowing out from the communication hole 170 of the switching valve 158 to the storage tank 12 in the large flushing mode (so-called “water drainage speed  $Q1$ ”) ( $Q2 > Q1$ ). Therefore, a lowering speed  $v2$  of a float 72 during the small flushing mode can be larger than a lowering speed  $v1$  of the float 72 during the large flushing mode. Consequently, a valve opening time of the valve body 36 during the small flushing mode can be shorter than a valve opening time of the valve body 36 during the large flushing mode. As a result, the lowering speed of the float 72 with the decrease in water level in the water storage cylinder 162 can be changed by changing the flush water amount  $Q1$ ,  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder 162 flowing out from the outlet port 168 to the storage tank 12 (so-called “water drainage speed  $Q1$ ,  $Q2$ ”) depending on the selected large flushing mode or small flushing mode. Therefore, an instantaneous flow rate of flush water [L/min] that affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body 36 closes the discharge opening 18 can be reduced.

(57) Next, with reference to FIGS. 1, 5A and 5B, a discharge valve device 200 according to a third embodiment of the present invention will be described. Here, in the discharge valve device 200 according to the third embodiment of the present invention shown in FIGS. 5A and 5B, the same part as in the discharge valve devices 1 and 100 according to the first and second embodiments of the present invention described above is denoted with the same sign and is not described.

(58) First, as shown in FIGS. 5A and 5B, in the discharge valve device 200 according to the third embodiment of the present invention, a water storage cylinder 262 includes a first outlet port 268 disposed below and a second outlet port 270 disposed above the first outlet port 268 in one of left and right side walls 262a. Further, in the second outlet port 270 of the water storage cylinder 262, a partition (switching valve 258) for switching large or small flushing is openably and closably provided. As the switching valve 258 rotates from a horizontal posture to a vertical posture depending on a second bead chain 56 moving up and down, the second outlet port 270 can be opened and closed. Accordingly, in a large flushing mode shown in FIG. 5A, the second outlet port 270 of the water storage cylinder 262 is closed by the switching valve 258, and hence the flush

water in the water storage cylinder **262** flows out only from the lower first outlet port **268** to a storage tank **12**. On the other hand, in the small flushing mode shown in FIG. 5B, since the second outlet port **270** of the water storage cylinder **262** is opened by the switching valve **258**, the flush water in the water storage cylinder **262** flows out from both the first outlet port **268** and the second outlet port **270** to the storage tank **12**. Further, when a valve body **36** is opened, the water storage cylinder **262** is configured to increase a total opening area  $S_2$  of the first outlet port **268** and the second outlet port **270** during a small flushing mode as compared to a total opening area  $S_1$  only of the first outlet port **268** during the large flushing mode. Accordingly, a flush water amount  $Q_2$  per unit time [L/min] of the flush water in the water storage cylinder **262** flowing out from the first outlet port **268** and the second outlet port **270** to the storage tank **12** during the small flushing mode (so-called “water drainage speed  $Q_2$ ”) is set larger than a flush water amount  $Q_1$  per unit time [L/min] of the flush water in the water storage cylinder **262** flowing out only from the first outlet port **268** to the storage tank **12** during the large flushing mode (so-called “water drainage speed  $Q_1$ ”) ( $Q_2 > Q_1$ ).

(59) Next, with reference to FIGS. 5A and 5B, an operation of the discharge valve device **200** according to the third embodiment of the present invention will be described. First, in a standby state shown in state (I) of FIGS. 5A and 5B, the switching valve **258** is in the horizontal posture and the second outlet port **270** of the water storage cylinder **262** is open. Then, when the large flushing mode is started from the standby state shown in the state (I) of FIG. 5A, in state (II) of FIG. 5A, an actuation shaft **54** and the valve body **36** are pulled upward by a first bead chain **52**. At this time, the switching valve **258** is pulled upward by the second bead chain **56** and rotated from the horizontal posture to the vertical posture, and the outlet port **268** of the water storage cylinder **262** is closed by the switching valve **258** (see state (II) of FIG. 5A). The state where the outlet port **268** of the water storage cylinder **262** is closed by the switching valve **258** is maintained from the subsequent state (III) of FIG. 5A to state (VI) of FIG. 5A where the valve body **36** is closed and the large flushing mode ends. However, as shown in states (II) to (VI) of FIG. 5A, even if the second outlet port **270** of the water storage cylinder **262** is closed by the switching valve **258**, the first outlet port **268** is normally open to normally communicate between the inside of the water storage cylinder **262** and the inside of the storage tank **12**. Then, as shown in the states (III) to (VI) of FIG. 5A, when a water level  $W_1$  in the storage tank **12** outside the water storage cylinder **262** is lower than a water level  $W_2$  in the water storage cylinder **262**, a water pressure in the water storage cylinder **262** is higher than a water pressure in the storage tank **12**. Therefore, even in the state where the second outlet port **270** of the water storage cylinder **262** is closed by the switching valve **258**, the flush water in the water storage cylinder **262** can flow out from the first outlet port **268** into the storage tank **12** due to a difference in pressure between the inside of the water storage cylinder **262** and the inside of the storage tank **12** outside the cylinder.

(60) On one hand, when the small flushing mode is started from the standby state shown in the state (I) of FIG. 5B, in the state (II) of FIG. 5B, the actuation shaft **54** and the valve body **36** are pulled upward by the first bead chain **52**. On the other hand, since the switching valve **258** is not pulled upward by the second bead chain **56** and does not rotate from the horizontal posture to the vertical posture, the second outlet port **270** of the water storage cylinder **262** is opened by the switching valve **258** (see state (II) of FIG. 5B). Then, a state where the second outlet port **270** of the water storage cylinder **262** is normally opened by the switching valve **258** is maintained from the standby state (I) of FIG. 5B to the state (VI) of FIG. 5B where the small flushing mode ends.

(61) Next, in the state during the small flushing mode shown in the state (III) to (V) of FIG. 5B, the water level  $W_1$  in the storage tank **12** is lower than the water level  $W_2$  in the water storage cylinder **262**, and the water level  $W_2$  in the water storage cylinder **262** is located above a lower end of the second outlet port **270**. Therefore, the flush water in the water storage cylinder **262** flows out from the first outlet port **268** in a flush water amount  $Q_{2a}$  per unit time [L/min] (so-called “water drainage speed  $Q_{2a}$ ”) and flows out from the second outlet port **270** in a flush water amount  $Q_{2b}$

per unit time [L/min] (so-called “water drainage speed  $Q2b$ ”). At this time, in a state where the water level  $W1$  in the storage tank **12** is lower than the second outlet port **270**, the second outlet port **270** is open to the atmosphere, and hence the water drainage speed  $Q2b$  in the second outlet port **270** is equal to or larger than the water drainage speed  $Q2a$  in the first outlet port **268** ( $Q2b \geq Q2a$ ). As shown in the state (VI) of FIG. 5B, in a state where the small flushing mode is finished, a minimum water level  $DWL2$  in the storage tank **12** during the small flushing mode is located above a minimum water level  $DWL1$  in the storage tank **12** during the large flushing mode in the state (VI) of FIG. 5A.

(62) According to the discharge valve device **200** of the third embodiment of the present invention described above, a total opening area  $S2$  of the first outlet port **268** and the second outlet port **270** of the water storage cylinder **262** during the small flushing mode is configured to increase as compared to a total opening area  $S1$  only of the first outlet port **268** of the water storage cylinder **262** during the large flushing mode, and the second outlet port **270** is disposed above the first outlet port **268**. Accordingly, when the valve body **36** is opened during the large flushing mode shown in FIG. 5A, the flush water in the water storage cylinder **262** flows out only from the first outlet port **268** to the storage tank **12**, whereas when the valve body **36** is opened during the small flushing mode shown in FIG. 5B, the flush water in the water storage cylinder **262** flows out from both the first outlet port **268** and the second outlet port **270** to the storage tank **12**. Further, a second flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **262** flowing out from both the first outlet port **268** and the second outlet port **270** to the storage tank **12** in the small flushing mode (so-called “second water drainage speed  $Q2$ ”) can be increased as compared to a first flush water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder **262** flowing out only from the first outlet port **268** to the storage tank **12** in the large flushing mode (so-called “first water drainage speed  $Q1$ ”). Therefore, a lowering speed  $v2$  of a float **72** during the small flushing mode can be larger than a lowering speed  $v1$  of the float **72** during the large flushing mode, and hence a lowering time of the float **72** and a valve opening time of the valve body **36** during the small flushing mode can be shorter than a lowering time of the float **72** and a valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed  $v1$ ,  $v2$  of the float **72** with the decrease in water level in the water storage cylinder **262** can be changed by changing the flush water amount  $Q1$ ,  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **262** flowing out from the outlet port **268**, **270** to the storage tank **12** (so-called “water drainage speed  $Q1$ ,  $Q2$ ”) depending on the selected large flushing mode or small flushing mode. Therefore, an instantaneous flow rate of flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body **36** closes a discharge opening **18** can be reduced.

(63) Next, with reference to FIGS. 1, 6A and 6B, a discharge valve device **300** according to a fourth embodiment of the present invention will be described. Here, in the discharge valve device **300** according to the fourth embodiment of the present invention shown in FIGS. 6A and 6B, the same part as in the discharge valve devices **1**, **100** and **200** according to the first to third embodiments of the present invention described above is denoted with the same sign and is not described.

(64) First, as shown in FIGS. 6A and 6B, in the discharge valve device **300** according to the fourth embodiment of the present invention, a water storage cylinder **362** includes a first outlet port **368** disposed below, and a second outlet port **370** disposed above the first outlet port **368** in one of left and right side walls **362a**. Further, a partition (switching valve **358**) for switching large or small flushing is provided to be openable and closable with respect to each of the first outlet port **368** and the second outlet port **370** of the water storage cylinder **362**. The switching valve **358** can slide in a vertical direction with a second bead chain **56** moving up and down depending on large and small flushing modes. That is, during the large flushing mode shown in FIG. 6A, as the switching valve

**358** is pulled up by the second bead chain **56** and slides upward, the first outlet port **368** is opened by the switching valve **358**, and the second outlet port **370** is closed by the switching valve **358**. On the other hand, during the small flushing mode shown in FIG. **6B**, the switching valve **358** is not pulled up by the second bead chain **56**, so that the first outlet port **368** is closed by the switching valve **358**, and the second outlet port **370** is opened by the switching valve **358**.

(65) Furthermore, a total opening area  $S1$  of the first outlet port **368** opened by the switching valve **358** during the large flushing mode is the same as a total opening area  $S2$  of the second outlet port **370** opened by the switching valve **358** during the small flushing mode ( $S1=S2$ ). Then, in the discharge valve device **300** of the present embodiment, in the same manner as in the discharge valve devices **1**, **100** and **200** according to the first to third embodiments of the present invention described above, when the large flushing mode is started, a water level  $W1$  in a storage tank **12** outside the water storage cylinder **362** decreases to below a water level  $W2$  in the water storage cylinder **362**. Thereafter, when the water level  $W1$  in the storage tank **12** lowers to below an upper end position of the first outlet port **368**, a first flush water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the first outlet port **368** into the storage tank **12** (so-called “water drainage speed  $Q1$ ”) is accelerated. On the other hand, when the small flushing mode is started, the water level  $W1$  in the storage tank **12** outside the water storage cylinder **362** decreases to below a water level  $W2$  in the water storage cylinder **362**. Thereafter, when the water level  $W1$  in the storage tank **12** decreases to below an upper end position of the second outlet port **370**, a second flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the second outlet port **370** into the storage tank **12** (so-called “water drainage speed  $Q2$ ”) is accelerated. These settings are such that the second flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the second outlet port **370** to the storage tank **12** in the small flushing mode (so-called “water drainage speed  $Q2$ ”) increases as compared to the first flush water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the first outlet port **368** to the storage tank **12** in the large flushing mode (so-called “water drainage speed  $Q1$ ”) ( $Q1<Q2$ ).

(66) According to the discharge valve device **300** of the fourth embodiment of the present invention described above, when the valve body **36** is opened during the large flushing mode, the flush water in the water storage cylinder **362** flows out from the first outlet port **368** to the storage tank **12**. On the other hand, when the valve body **36** is opened during the small flushing mode, the flush water in the water storage cylinder **362** flows out from the second outlet port **370** to the storage tank **12**. At this time, even if the total opening areas  $S1$  and  $S2$  of the first outlet port **368** and the second outlet port **370** are the same as each other, the second outlet port **370** is disposed above the first outlet port **368**, and hence as compared to the first water amount  $Q1$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the first outlet port **368** to the storage tank **12** in the large flushing mode (so-called “first water drainage speed  $Q1$ ”), the second flush water amount  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the second outlet port **370** to the flush water tank in the small flushing mode (so-called “second water drainage rate speed”) can be increased. Therefore, a lowering speed  $v2$  of a float **72** during the small flushing mode can be larger than a lowering speed  $v1$  of the float **72** during the large flushing mode, and hence a lowering time of the float **72** and a valve opening time of the valve body **36** during the small flushing mode can be shorter than a lowering time of the float **72** and a valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed  $v1$ ,  $v2$  of the float **72** with the decrease in water level in the water storage cylinder **362** can be changed by changing the flush water amount  $Q1$ ,  $Q2$  per unit time [L/min] of the flush water in the water storage cylinder **362** flowing out from the outlet port **368** or **370** to the storage tank **12** (so-called “water drainage speed  $Q1$ ,  $Q2$ ”) depending on the selected large flushing mode or small flushing mode. Therefore, an instantaneous flow rate of flush water [L/min] that

affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body **36** closes a discharge opening **18** can be reduced.

(67) In the discharge valve devices **1**, **100**, **200** and **300** according to the first to fourth embodiments of the present invention described above, as means for changing the lowering speed  $v_1$ ,  $v_2$  of the float **72** with the decrease in water level in the water storage cylinder **62**, **162**, **262** or **362** depending on the selected large flushing mode or small flushing mode, some forms of changing the flush water amount  $Q_1$ ,  $Q_2$  per unit time [L/min] of the flush water in each water storage cylinder **62**, **162**, **262** or **362** flowing out from each outlet port **68**, **70**, **168**, **170**, **268**, **270**, **368** or **370** to the storage tank **12** (so-called “water drainage speed  $Q_1$ ,  $Q_2$ ”) have been described, but are not limited to these examples, and a form other than the forms of changing the so-called “water drainage speed” is also applicable. For example, as the other form, a total outflow amount [L] (so-called “water drainage amount”) of the flush water in the water storage cylinder flowing out from the outlet port to the storage tank may be changed depending on the selected large flushing mode or small flushing mode. Alternatively, as yet another form, buoyancy that acts on the float may be changed with the flush water in the storage tank or in the water storage cylinder depending on the selected large flushing mode or small flushing mode.

(68) Next, with reference to FIGS. **1** and **7** to **11B**, a discharge valve device **400** according to a fifth embodiment of the present invention will be described. Here, in the discharge valve device **400** according to the fifth embodiment of the present invention shown in FIGS. **7** to **11B**, the same part as in the discharge valve devices **1**, **100**, **200** and **300** according to the first to fourth embodiments of the present invention described above is denoted with the same sign and is not described. Further, in states (I) to (VI) of the discharge valve device **400** in each of a large flushing mode and a small flushing mode shown in FIGS. **11A** and **11B**, a state (standby state) before valve opening of a valve body **36** is started is shown in state (I), and thereafter, in time series, a valve opened state of the valve body **36** is shown in states (II) to (V), and a valve closed state of the valve body **36** is shown in state (VI).

(69) First, as shown in FIGS. **7** to **10**, a water storage cylinder **462** of the discharge valve device **400** of the present embodiment includes a water storage cylinder body **468**, and a small tank **470** that is communicatively connected to the water storage cylinder body **468**. Each of the water storage cylinder body **468** and the small tank **470** stores part of the flush water in a storage tank **12**. Further, in a side wall **468a** of the water storage cylinder body **468**, an outlet port **472** that causes the flush water in the water storage cylinder body **468** to flow outside (into the storage tank **12**) is provided. The outlet port **472** is normally open, and normally communicates between inside of the water storage cylinder body **468** and inside of the storage tank **12** outside the cylinder body. Further, a float **474** is disposed in the water storage cylinder body **468**. The float **474** is concentrically provided on an outer peripheral side of an actuation shaft **54** and moves (moves up and down) in conjunction with a water level in the water storage cylinder body **468**, so that buoyancy obtained by the flush water in the water storage cylinder body **468** can act on the actuation shaft **54**.

(70) Next, as shown in FIGS. **7** to **11B**, a connecting portion of the small tank **470** connected to the side wall **468a** of the water storage cylinder body **468** is provided with a communication opening **476** that can communicate with the water storage cylinder body **468**. Further, in the communication opening **476**, a partition (switching valve **458**) for switching large or small flushing is openably and closably provided. For the partition (switching valve **458**) for switching large or small flushing, as shown in FIGS. **7** to **11A**, when toilet flushing by the large flushing mode is executed, a second bead chain **56** loosens without being pulled up by a second swing lever **50**, and the partition is rotated in a direction **C1** to open the communication opening **476** and can open the communication opening **476**. Accordingly, during the large flushing mode, the water storage cylinder body **468** and the small tank **470** communicate with each other via the opened communication opening **476**. On

the other hand, for the partition (switching valve **458**) for switching large or small flushing, as shown in FIGS. **7** to **10** and **11B**, when toilet flushing by the small flushing mode is executed, the second bead chain **56** is pulled up by the second swing lever **50**, the partition is rotated in a direction **C2** to close the communication opening **476**, and the communication opening **476** can be closed. Accordingly, during the small flushing mode, the water storage cylinder body **468** and the small tank **470** are separated from each other by the switching valve **458** that closes the communication opening **476**.

(71) Next, as shown in FIGS. **8** to **10**, a locking portion **478** that rotatably supports the switching valve **458** is provided on both left and right sides of a rim and a lower end side in the communication opening **476**. The locking portion **478** rotates in the direction **C2** in which the switching valve **458** closes the communication opening **476** in the small flushing mode and contacts the locking portion **478**, and rotation of the switching valve **458** is restricted by the locking portion **478**.

(72) Next, as shown in FIGS. **8** to **10**, the switching valve **458** includes a valve body portion **480** and a water weight portion **482**. First, for the valve body portion **480** of the switching valve **458**, in a state where the communication opening **476** is closed by the switching valve **458**, a pulling-up force by the second swing lever **50** and the second bead chain **56** and a water pressure of the flush water in the small tank **470** bring the whole valve body portion **480** into a standing posture extending in a vertical direction, and left, right and lower peripheral edge portions of the valve body portion **480** contact the locking portion **478**. Further, a plurality of (two) water weight portions **482** of the switching valve **458** are provided on an upper side of the valve body portion **480** with the standing posture and on the small tank **470** side. Each of these water weight portions **482** can store flush water in the water weight portion **482** in a state where the valve body portion **480** is in the standing posture.

(73) Further, as shown in FIG. **9**, a pair of left and right auxiliary outlet ports **484** that allow the flush water in the small tank **470** to flow out are provided in a bottom surface of the small tank **470**. Further, in the state of the standing posture where the valve body portion **480** abuts on the locking portion **478**, the water weight portion **482** can store flush water, and at this time, each of the auxiliary outlet ports **484** of the small tank **470** is opened by the valve body portion **480**.

Furthermore, when the flush water in the small tank **470** flows out from each auxiliary outlet port **484**, the water pressure in the small tank **470** that presses the valve body portion **480** in a valve closing direction decreases, and hence the valve body portion **480** rotates in a direction apart from the locking portion **478** (valve opening direction). Accordingly, the valve body portion **480** and the water weight portion **482** are easily rotated from the standing posture to a falling posture due to an own weight of the water weight portion **482**. Then, when the water weight portion **482** tilts, the valve body portion **480** and the water weight portion **482** (signs **480** and **482** shown with a virtual line in FIG. **10**) shift to the falling posture (horizontal posture) while the flush water in the water weight portion **482** flows out. Further, when the valve body portion **480** and the water weight portion **482** are in a state of the falling posture (horizontal posture), each auxiliary outlet port **484** is closed by a lower surface of the water weight portion **482** with the falling posture.

(74) Additionally, at an initial position **P0** in a standby period before the large and small flushing modes are started (see state (I) in FIGS. **11A** and **11B**), the valve body portion **480** and the water weight portion **482** of the switching valve **458** are in the falling posture (horizontal posture). Further, after the standby period shown in the state (I) of FIG. **11A**, even in a period in which the large flushing mode shown in the states (II) to (VI) of FIG. **11A** is executed, the valve body portion **480** and the water weight portion **482** of the switching valve **458** are in the initial position **P0**, and the state of the falling posture (horizontal posture) is maintained. Furthermore, in the state of the falling posture (horizontal posture) where the valve body portion **480** and the water weight portion **482** of the switching valve **458** are in the initial position **P0**, the valve body portion **480** of the switching valve **458**, without abutting on the locking portion **478**, opens the communication

opening **476** and closes each auxiliary outlet port **484**. Further, in the state where the valve body portion **480** and the water weight portion **482** are in the falling posture (horizontal posture), an opening end portion **482a** (see FIG. **8**) at a tip of the water weight portion **482** is directed in a horizontal direction, so that the flush water in the small tank **470** can flow into the water weight portion **482** from the opening end portion **482a**, and the flush water can be stored in the water weight portion **482**. On the other hand, in a period in which the small flushing mode shown in the states (II) to (VI) of FIG. **11B** is executed, the valve body portion **480** and the water weight portion **482** of the switching valve **458** rotate from the initial position **P0** to contact the locking portion **478**. Accordingly, when a state where the communication opening **476** is closed is maintained and then the flush water in the small tank **470** flows out from each auxiliary outlet port **484**, the valve body portion **480** and the water weight portion **482** rotate toward the initial position **P0** to cause the flush water in the water weight portion **482** to flow out and then return to the initial position **P0** of the standby state (I).

(75) Next, as shown in FIGS. **8** to **10**, a top edge **468b** of the water storage cylinder body **468**, a top edge **470a** of the small tank **470**, and an upper end **478a** of the locking portion **478** are flush with one another. Further, as shown in FIGS. **8** and **10**, in a state where the communication opening **476** is closed by the switching valve **458**, an upper end **458a** of the switching valve **458** (valve body portion **480** and water weight portion **482**) protrudes upward from a top edge of the communication opening **476** and the top edge **470a** of the small tank **470**. According to the configuration of the discharge valve device **400** of the present embodiment, in the large flushing mode of the states (III) to (VI) of FIG. **11A**, a first total outflow amount (first water drainage amount) **Q401** [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** into the storage tank **12** is larger than a second total outflow amount (second water drainage amount) **Q402** [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** into the storage tank **12** (**Q401**>**Q402**) in the small flushing mode of the states (III) to (VI) of FIG. **11B**.

(76) Next, an operation of the discharge valve device **400** according to the present embodiment will be described with reference to FIGS. **7** to **11B**. First, the large flushing mode executed by the discharge valve device **400** according to the present embodiment will be described with reference to with FIGS. **7** to **11A**. As shown in FIGS. **7** and **11A**, to start the large flushing mode from the standby state (I), for example, when the user rotates an operation lever **34** shown in FIG. **7** at 90 degrees to a front side, only a first swing lever **48** in the initial position state (standby state) shown in FIG. **7** is swung, and only the first bead chain **52** is pulled up. Accordingly, as the actuation shaft **54** and the valve body **36** of the discharge valve device **400** are pulled up and move linearly upward via a first bead chain **52**, the float **474** is also integrally pulled up via the actuation shaft **54** (see state (II) of FIG. **11A**). On the other hand, since the second bead chain **56** cannot be pulled up by the second swing lever **50**, the switching valve **58** is at the initial position **P0** and rotated to open the communication opening **476** of the water storage cylinder **462**, to obtain a state where the water storage cylinder body **468** communicates with the small tank **470** (see state (II) of FIG. **11A**). Thereafter, a state where the water storage cylinder body **468** and the small tank **470** normally communicate is maintained until the large flushing mode is finished (see states (II) to (VI) in FIG. **11B**).

(77) At this time, as shown in the state (II) of FIG. **11A**, the float **474** and the valve body **36** are raised to the highest position, and in this state, a discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start draining of flush water from the inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the states (III) to (V) of FIG. **11A**, when a water level **W1** in the storage tank **12** decreases further to a water level lower than an upper end of the water storage cylinder **462**, a water pressure due to a water level **W2** in the water storage cylinder **462** is higher than a water pressure due to the water level **W1** in the storage tank **12** outside the cylinder, and hence the flush water in the water storage cylinder **462** flows out from the outlet port **472** into the storage tank **12** outside the cylinder. Then, as shown in the states (III) and

(IV) of FIGS. 11A, the water level W2 in the water storage cylinder 462 is higher than the water level W1 in the storage tank 12 outside the cylinder, but the flush water in the water storage cylinder 462 continues to flow out of the outlet port 472. Therefore, as the water level W2 in the water storage cylinder 462 gradually decreases, the float 474 also lowers in conjunction with lowering of the water level W2.

(78) Next, as shown in the state (V) of FIG. 11A, when the water level W1 in the storage tank 12 outside the water storage cylinder 462 lowers from an upper end of the outlet port 472 of the water storage cylinder 462, outside of the outlet port 472 of the water storage cylinder 462 is open to the atmosphere. Accordingly, a speed at which the flush water in the water storage cylinder 462 flows out of the outlet port 472 is increased, and the water level W2 in the water storage cylinder 462 further decreases. Therefore, the float 474 also lowers, and the actuation shaft 54 and the valve body 36 also lower integrally. Then, as shown in the state (VI) of FIG. 11A, when the valve body 36 contacts a valve seat 66, the discharge opening 18 is closed. Consequently, draining of flush water from the inside of the storage tank 12 to the discharge opening 18 is stopped, and the supply of flush water from a flush water tank device 402 to a toilet main body 8 by the large flushing mode is finished. At this time, the float 474, the actuation shaft 54 and the valve body 36 are in a stopped state, but a minimum water level DWL1 in the storage tank 12 (draining stop water level so-called "dead water line") is located below a lower end of the outlet port 472 of the water storage cylinder 462. For this reason, the flush water in the water storage cylinder 462 continues to flow out from the outlet port 472 to the storage tank 12 side. As only the water level W2 in the water storage cylinder 462 gradually decreases, the water pressure in the water storage cylinder 462 also decreases. Further, in the standby state after the end of the large flushing mode, the switching valve 458 is in a state where the communication opening 476 is opened, and a state where the water storage cylinder body 468 and the small tank 470 communicate with each other is maintained until the next flushing mode is started.

(79) Next, with reference to FIGS. 7 to 10 and 11B, the small flushing mode executed by the discharge valve device 400 according to the present embodiment will be described. To start the small flushing mode from the standby state (I) of FIGS. 7 and 11B, for example, when the user rotates the operation lever 34 shown in FIG. 7 at 90 degrees to a back side, each of the first swing lever 48 and the second swing lever 50 in the state at the initial position (standby state) shown in FIG. 7 is swung, and each of the first bead chain 52 and the second bead chain 56 is pulled up. Accordingly, as the actuation shaft 54 and the valve body 36 of the discharge valve device 1 are pulled up and move linearly upward via the first bead chain 52, the float 474 is also integrally pulled up via the actuation shaft 54 (see state (II) of FIG. 11B). Further, the switching valve 58 for switching large or small flushing is pulled up via the second bead chain 56, and the switching valve 458 rotates from the state where the communication opening 476 of the water storage cylinder 462 is open (initial position P0) in the direction C2 to close the communication opening 476. Accordingly, the communication opening 476 of the small tank 470 is closed by the switching valve 458, and thereafter, a state where the water storage cylinder body 468 and the small tank 470 are separated by the switching valve 458 is maintained until the small flushing mode ends (see states (II) to (VI) of FIG. 11B).

(80) Further, in the state (II) of FIG. 11B, the float 474 and the valve body 36 are raised to the highest position, and the discharge opening 18 of the storage tank 12 is opened by the raised valve body 36, to start the draining of flush water from the inside of the storage tank 12 to the discharge opening 18. Thereafter, as shown in the states (III) to (V) of FIG. 11B, when the water level W1 in the storage tank 12 decreases to a water level lower than the upper end of the water storage cylinder 462, a water pressure due to a water level W2a in the water storage cylinder body 468 is higher than a water pressure due to the water level W1 in the storage tank 12 outside the cylinder body, and hence the flush water in the water storage cylinder body 468 flows out from the outlet port 472 into the storage tank 12 outside the cylinder body. Then, in the states (III) to (V) of FIG. 11B, the



water level  $W2a$  in the water storage cylinder body **468** is higher than the water level  $W1$  in the storage tank **12** outside the cylinder body, and hence the flush water in the water storage cylinder **462** continues to flow out of the outlet port **472**. As the water level  $W2$  in the water storage cylinder **462** gradually decreases, the float **474** also lowers in conjunction with lowering of water level  $W2$ . Here, in the states (III) to (V) of FIG. **11B**, the water level  $W2a$  in the water storage cylinder body **468** is lower than a water level  $W2b$  in the small tank **470**, and the water pressure in the small tank **470** is higher than a water pressure in the water storage cylinder body **468**. Accordingly, the switching valve **458** is pressed in the direction  $C2$  to close the communication opening **476** by the water pressure in the small tank **470**, and hence the communication opening **476** of the small tank **470** is closed by the switching valve **458**, to maintain a state where the water storage cylinder body **468** and the small tank **470** are separated by the switching valve **458**.

(81) Then, as shown in the state (VI) of FIG. **11B**, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed, and the draining of flush water from the inside of the storage tank **12** to the discharge opening **18** is stopped. Accordingly, the supply of flush water from the flush water tank device **402** to the toilet main body **8** by the small flushing mode is finished. At this time, a minimum water level  $DWL2$  (draining stop water level so-called “dead water line”) in the storage tank **12** during the small flushing mode in the state (VI) of FIG. **11B** is located above the minimum water level  $DWL1$  in the storage tank **12** during the large flushing mode in the state (VI) of FIG. **11A**. That is, the minimum water level  $DWL2$  during the small flushing mode is higher than the minimum water level  $DWL1$  during the large flushing mode, by which the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the small flushing mode is lower than the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the large flushing mode. Additionally, the first total outflow amount (first water drainage amount)  $Q401$  [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** into the storage tank **12** in the large flushing mode of the states (III) to (VI) of FIG. **11A** is larger than the second total outflow amount (second water drainage amount)  $Q402$  [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** into the storage tank **12** in the small flushing mode of the states (III) to (VI) of FIG. **11B** ( $Q401 > Q402$ ).

(82) According to the discharge valve device **400** of the fifth embodiment of the present invention described above, to start flushing of the flush toilet **4**, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft **54** of the discharge valve device **400** is raised to raise (open) the valve body **36**, and the flush water in the storage tank **12** is supplied from the discharge opening **18** to a water conduit **8a** of the toilet main body **8** of the flush toilet **4**. Then, the water level  $W2$  in the water storage cylinder **462** decreases depending on the selected large flushing mode or small flushing mode, and the float **474** in the water storage cylinder **462** lowers as the water level  $W2$  decreases. Accordingly, as the actuation shaft **54** of the discharge valve device **400** lowers, the valve body **36** lowers (closes), and the supply of flush water from the storage tank **12** to the flush toilet **4** is stopped, to finish the flushing of the flush toilet **4**. At this time, the first total outflow amount  $Q401$  [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** in the large flushing mode is larger than the second total outflow amount  $Q402$  [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** in the small flushing mode ( $Q401 > Q402$ ). Accordingly, a lowering speed  $v2$  of the float **474** during the small flushing mode can be larger than a lowering speed  $v1$  of the float **474** in the large flushing mode ( $v2 > v1$ ). Therefore, a lowering time of the float **474** and a valve opening time of the valve body **36** during the small flushing mode can be shorter than a lowering time of the float **474** and a valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed  $v1$ ,  $v2$  of the float **474** with the decrease in water level  $W2$  in the water storage cylinder **462** can be changed by changing the flush water amount of the flush water in the water storage cylinder **462** flowing out

from the outlet port **472** to the storage tank **12** (so-called “water drainage amount **Q401**, **Q402**”) depending on the selected large flushing mode or small flushing mode. Therefore, a flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced.

(83) Further, according to the discharge valve device **400** of the present embodiment, the small tank **470** communicatively connected to the water storage cylinder body **468** includes the communication opening **476** communicating with the water storage cylinder body **468**, and the switching valve **458** for switching large or small flushing that opens and closes the communication opening **476**. Accordingly, the switching valve **458** can communicate between the water storage cylinder body **468** and the small tank **470** by opening the communication opening **476** in the large flushing mode. On the other hand, the switching valve **458** of the small tank **470** can separate the water storage cylinder body **468** and the small tank **470** by closing the communication opening **476** in the small flushing mode. As a result, since the first total outflow amount **Q401** [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** in the large flushing mode can be larger than the second total outflow amount **Q402** [L] of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** in the small flushing mode, the lowering speed **v2** of the float **474** during the small flushing mode can be larger than the lowering speed **v1** of the float **474** during the large flushing mode.

Accordingly, the lowering time of the float **474** and the valve opening time of the valve body **36** during the small flushing mode can be shorter than the lowering time of the float **474** and the valve opening time of the valve body **36** during the large flushing mode. As a result, the lowering speed **v1** and **v2** of the float **474** with the decrease in water level in the water storage cylinder **462** can be changed by changing the flush water amounts **Q401** and **Q402** [L] (so-called “water drainage amounts **Q401** and **Q402**”) of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** depending on the selected large flushing mode or small flushing mode. Therefore, the instantaneous flow rate of the flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body **36** closes the discharge opening **18** can be reduced.

(84) Further, according to the discharge valve device **400** of the present embodiment, if the switching valve **458** for switching large or small flushing does not rotate with respect to the communication opening **476**, and the switching valve **458** is provided slidably with respect to the communication opening **476** and when the communication opening **476** is closed by the switching valve **458**, a seal portion in which the switching valve **458** and the communication opening **476** are in contact might have a risk of being damaged by wear or the like due to repeated sliding of the switching valve **458** to open and close the communication opening **476**. However, according to the discharge valve device **400** of the present embodiment, the switching valve **458** is provided rotatably with respect to the communication opening **476**. The communication opening **476** can be rotated in the direction **C1** to open the communication opening **476** in the large flushing mode and can be rotated in the direction **C2** to close the communication opening **476** in the small flushing mode. Accordingly, as compared to a form in which the switching valve **458** slides to open and close the communication opening **476**, a risk of normal contact of the switching valve **458** with the communication opening **476** regardless of the flushing mode can be avoided while suppressing the number of parts. Therefore, the risk of damage due to wear or the like on a portion (seal portion) of the communication opening **476** of the small tank **470** that contacts the switching valve **458** during closing can be reduced.

(85) Further, according to the discharge valve device **400** of the present embodiment, the communication opening **476** of the small tank **470** includes the locking portion **478** that is provided

at the rim of the opening and that rotatably supports the switching valve **458**. Accordingly, when the switching valve **458** rotates in the direction C2 to close the communication opening **476** and contacts the locking portion **478** in the small flushing mode, the locking portion **478** can reliably restrict the rotation of the switching valve **458**. Further, in the state where the switching valve **458** is in contact with the locking portion **478** in the small flushing mode, the locking portion **478** can reliably contact and seal the switching valve **458** and the rim of the communication opening **476**, and hence water tightness between the water storage cylinder body **468** and the small tank **470** can be improved. Therefore, in the small flushing mode, flowing of flush water in the small tank **470** into the water storage cylinder body **468** from the communication opening **476** can be reliably suppressed.

(86) Further, according to the discharge valve device **400** of the present embodiment, the switching valve **458** includes a pair of water weight portions **482** that store flush water, and in the bottom surface of the small tank **470**, a pair of auxiliary outlet ports **484** for the flush water in the small tank **470** to flow outside are provided. Accordingly, when the switching valve **458** abuts on the locking portion **478**, the water weight portions **482** can store flush water, and the flush water in the small tank **470** flows out of the auxiliary outlet ports **484**. Further, when the flush water in the small tank **470** flows out from the auxiliary outlet ports **484**, the switching valve **458** rotates in the direction apart from the locking portion **478** (direction C1 to open the communication opening **476**), and the flush water in the water weight portions **482** can flow outside. Therefore, a series of rotating operations from the state where the communication opening **476** of the small tank **470** is closed by the switching valve **458** until the switching valve opens the communication opening can be reliably and smoothly executed using the change in water level in the small tank **470** and the change in amount of flush water stored in the water weight portions **482**.

(87) Further, according to the discharge valve device **400** of the present embodiment, at the initial position P0, the switching valve **458** takes the falling posture (horizontal posture), does not abut on the locking portion **478** and opens the communication opening **476**, and any flush water is not stored in the water weight portion **482**. In the standby period in which any flushing mode is not executed (see state (I) of FIGS. **11A** and **11B**) and in the period in which the large flushing mode is executed (see states (II) to (VI) of FIG. **11A**), the switching valve **458** is maintained at the initial position P0. Accordingly, the auxiliary outlet port **484** of the small tank **470** is closed by the switching valve **458**, and flush water can be stored in the small tank. On the other hand, in the period in which the small flushing mode is executed (see states (II) to (VI) of FIG. **11B**), the switching valve **458** rotates from the initial position P0 in the direction C2 to close the communication opening **476** and contacts the locking portion **478** to maintain the state where the communication opening **476** is closed. Thereafter, when the flush water in the small tank **470** flows out from the auxiliary outlet port **484**, the switching valve **458** can return to the initial position P0 after causing the flush water in the water weight portion **482** to flow outside, while rotating from the state where the communication opening **476** is closed toward the initial position P0. As a result, the lowering speed  $v1$ ,  $v2$  of the float **474** with the decrease in water level W2 in the water storage cylinder **462** can be efficiently changed by efficiently changing the flush water amount Q401, Q402 (so-called "water drainage amount Q401, Q402") of the flush water in the water storage cylinder **462** flowing out from the outlet port **472** to the storage tank **12** depending on the selected large flushing mode or small flushing mode.

(88) Further, according to the discharge valve device **400** of the present embodiment, as shown in FIGS. **8** and **10**, the top edge **468b** of the water storage cylinder body **468** and the top edge **470a** of the small tank **470** are flush with each other. Also, as shown in FIG. **10**, in the state where the communication opening **476** of the small tank **470** is closed by the switching valve **458**, the upper end **458a** of the switching valve **458** protrudes upward from the top edge of the communication opening **476** and the top edge **470a** of the small tank **470**. Accordingly, in the state where the communication opening **476** is closed by the switching valve **458**, the flush water in the small tank

**470** can be reliably inhibited from flowing over the upper end **458a** of the switching valve **458** into the water storage cylinder body **468**.

(89) Next, with reference to FIGS. **1** and **12** to **13B**, a discharge valve device **500** according to a sixth embodiment of the present invention will be described. Here, in the discharge valve device **500** of the sixth embodiment of the present invention shown in FIGS. **12** to **13B**, the same part as in the discharge valve devices **1**, **100**, **200**, **300** and **400** according to the first to fifth embodiments of the present invention described above is denoted with the same sign and is not described.

(90) As shown in FIG. **12**, in the discharge valve device **500** of the present embodiment, to start toilet flushing by a large flushing mode, when an operation lever **34** is rotated at a predetermined angle (for example, 90 degrees) to one side (front side of FIG. **12**) about a rotation center axis **A1**, an outer rotary shaft **40** and an inner rotary shaft **42** that are coupled to the operation lever **34** rotate to one side, and a rotary spindle portion **44** of a pulling-up actuating portion **38** rotates to one side about a rotation center axis **A2**. Accordingly, a cylindrical rotating portion **46** of the pulling-up actuating portion **38** also rotates integrally with the rotary spindle portion **44** to one side (front side of FIG. **12**) about the rotation center axis **A2**, and a first swing lever **48** swings (rotates) to one side (front side of FIG. **12**) to pull up a first bead chain **52**, whereas a second swing lever **50** does not swing, and a second bead chain **56** is not pulled up. On the other hand, to start toilet flushing by a small flushing mode, when the operation lever **34** shown in FIG. **12** is rotated at a predetermined angle (for example, 90 degrees) to the other side (back side of FIG. **12**) about the rotation center axis **A1**, the outer rotary shaft **40** and the inner rotary shaft **42** that are coupled to the operation lever **34** rotate to the other side, and the rotary spindle portion **44** of the pulling-up actuating portion **38** rotates to the other side about the rotation center axis **A2**. Accordingly, the cylindrical rotating portion **46** of the pulling-up actuating portion **38** also rotates integrally with the rotary spindle portion **44** to the other side (back side of FIG. **12**) about the rotation center axis **A2**, and the first swing lever **48** swings (rotates) to the other side (back side of FIG. **12**) to pull up the first bead chain **52**. The second swing lever **50** also swings (rotates) to the other side (back side of FIG. **12**) to pull up the second bead chain **56**.

(91) Next, as shown in FIG. **12**, the discharge valve device **500** of the present embodiment includes a water storage cylinder **562** provided above a discharge opening forming portion **60**, and an overflow pipe **560a** communicating with a discharge opening **18**. Further, in a side wall **62a** on one of left and right sides of the water storage cylinder **62** (side wall **62a** on the left side when the water storage cylinder **62** is seen from the front side), an outlet port **68** is provided for the flush water in the water storage cylinder **62** to flow outside.

(92) Further, as shown in FIG. **12**, the outlet port **68** of the water storage cylinder **62** is normally open regardless of the large or small flushing mode, and a storing portion **574** for storing flush water is provided in an upper part of a float **572**. The storing portion **574** includes a peripheral wall **576** surrounding the storing portion, an outlet **578** formed in a part of the peripheral wall **576**, and a partition (switching valve **558** for switching large or small flushing) provided to be openable and closable for the outlet **578**. Furthermore, the switching valve **558** opens the outlet **578** of the peripheral wall **576** in the storing portion **574** of the float **572** during the large flushing mode, so that the flush water in the storing portion **574** can flow out from the outlet **578**.

(93) On the other hand, the switching valve **558** closes the outlet **578** of the peripheral wall **576** in the storing portion **574** of the float **572** during the small flushing mode and maintains a state where flush water is stored in the storing portion **574**, and the storing portion **574** functions as a water weight. Consequently, the amount of flush water stored in the storing portion **574** during the small flushing mode is larger than the amount of flush water stored in the storing portion **574** during the large flushing mode, and hence a weight of the storing portion **574** during the small flushing mode is larger than a weight of the storing portion **574** during the large flushing mode. A buoyancy obtained in the float **572** during the small flushing mode decreases as compared to a buoyancy obtained during the large flushing mode.

(94) Additionally, as shown in FIG. 13A, when toilet flushing by the large flushing mode is executed, for the switching valve 558, the second bead chain 56 loosens without being pulled up by the second swing lever 50. Further, as shown in FIG. 13A, the switching valve 558 opens the outlet 578 of the storing portion 574 of the float 572 without being pulled up by the second bead chain 56. Consequently, any flush water is not stored in the storing portion 574 of the float 572.

(95) On the other hand, as shown in FIG. 13B, when the toilet flushing by the small flushing mode is executed, the switching valve 558 allows the second bead chain 56 to be pulled up by the second swing lever 50. The switching valve 558 is pulled up by the second bead chain 56 to close the outlet 578 of the storing portion 574 of the float 572. Accordingly, flush water is stored in the storing portion 574 of the float 572. Consequently, in the float 572, the storing portion 574 functions as the water weight during the small flushing mode, whereas the storing portion 574 is difficult to function as the water weight during the large flushing mode. Therefore, the buoyancy obtained during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode. Therefore, in each flushing mode of the large and small flushing modes, a balance position between a water level W2 in the water storage cylinder 62 and the float 572 is changed depending on the selected flushing mode, and hence a lowering time T2 of the float 572 during the small flushing mode is shorter than a lowering time T1 of the float 572 during the large flushing mode ( $T2 < T1$ ).

(96) Next, with reference to FIGS. 12 to 13B, an operation of the discharge valve device 500 according to the sixth embodiment of the present invention will be described. First, with reference to FIGS. 12 and 13A, the large flushing mode executed by the discharge valve device 500 according to the present embodiment will be described. To start the large flushing mode from FIG. 12 and standby state (I) of FIG. 13A, for example, when the user rotates the operation lever 34 shown in FIG. 12 at 90 degrees to the front side, only the first swing lever 48 in a state at an initial position (standby state) shown in FIG. 12 is swung, and only the first bead chain 52 is pulled up. Consequently, as an actuation shaft 54 and a valve body 36 of the discharge valve device 500 are pulled up and move linearly upward via the first bead chain 52, the float 572 is also integrally pulled up via the actuation shaft 54 (see state (II) of FIG. 13A). At this time, since the second bead chain 56 is not pulled up by the second swing lever 50, the switching valve 58 is rotated to open the outlet 578 of the storing portion 574 of the float 572 without being pulled up by the second bead chain 56 (see state (II) of FIG. 13A). This state where the outlet 578 of the storing portion 574 of the float 572 is opened is maintained thereafter until the large flushing mode ends (see states (II) to (VI) of FIG. 13A).

(97) Consequently, in the state (II) of FIG. 13A, the float 572 and the valve body 36 are raised to the highest position, and the discharge opening 18 of a storage tank 12 is opened by the raised valve body 36. Then, the flush water in the storage tank 12 is drained to the discharge opening 18. Thereafter, as shown in the state (III) of FIG. 13A, when the water level W1 in the storage tank 12 decreases close to an upper end of the water storage cylinder 62 and further to a water level lower than the upper end of the water storage cylinder 62, a water pressure due to the water level W2 in the water storage cylinder 62 is higher than a water pressure due to the water level W1 in the storage tank 12, and hence the flush water in the water storage cylinder 62 flows out of the outlet port 68. Then, as shown in the states (IV) and (V) of FIG. 13A, the water level W2 in the water storage cylinder 62 is higher than the water level W1 in the storage tank 12, and the flush water in the water storage cylinder 62 continues to flow out of the outlet port 68. For this reason, as the water level W2 in the water storage cylinder 62 gradually decreases, the float 572 also lowers in conjunction with lowering of the water level W2.

(98) Next, as shown in the state (VI) of FIG. 13A, when the water level W1 in the water storage cylinder 62 and the storage tank 12 lowers from below an upper end of the outlet port 68 of the water storage cylinder 62, outside of the outlet port 68 of the water storage cylinder 62 is open to the atmosphere. Accordingly, a speed at which the flush water in the water storage cylinder 62

flows out of the outlet port **68** is increased, and the water level **W2** in the water storage cylinder **62** further lowers. Therefore, the float **572** also lowers, and the actuation shaft **54** and the valve body **36** also integrally lower. Then, when the valve body **36** contacts a valve seat **66**, the discharge opening **18** is closed, and draining of flush water from inside of the storage tank **12** to the discharge opening **18** is stopped. Consequently, supply of flush water from a flush water tank device **502** to a toilet main body **8** by the large flushing mode is finished.

(99) Next, with reference to FIGS. **12** and **13B**, the small flushing mode executed by the discharge valve device **500** according to the sixth embodiment of the present invention will be described. To start the small flushing mode from FIG. **12** and the standby state (I) of FIG. **13B**, for example, when the user rotates the operation lever **34** shown in FIG. **12** at 90 degrees to the back side, each of the first swing lever **48** and the second swing lever **50** in a state (standby state) at the initial position shown in FIG. **12** is swung, and each of the first bead chain **52** and the second bead chain **56** is pulled up. Consequently, as the actuation shaft **54** and the valve body **36** of the discharge valve device **500** are pulled up and move linearly upward via the first bead chain **52**, the float **572** is also integrally pulled up via the actuation shaft **54** (see the state (II) of FIG. **13B**). Further, the switching valve **58** is pulled up via the second bead chain **56**, and the outlet **578** of the storing portion **574** of the float **572** is opened by the switching valve **558**. Also, a state where the outlet **578** of the storing portion **574** of the float **572** is closed by the switching valve **558** is maintained thereafter until the small flushing mode ends (see states (II) to (IV) of FIG. **13B**).

(100) Further, as shown in the state (II) of FIG. **13B**, the float **572** and the valve body **36** are raised to the highest position, and the discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start draining of flush water from the inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the state (III) of FIG. **13B**, when the water level **W1** in the storage tank **12** decreases close to the upper end of the water storage cylinder **62**, and further to a water level lower than the upper end of the water storage cylinder **62**, the water pressure due to the water level **W2** in the water storage cylinder **62** is higher than the water pressure due to the water level **W1** in the storage tank **12**, thereby causing the flush water in the water storage cylinder **62** to flow out of the first outlet port **68**.

(101) At this time, in the storing portion **574** of the float **572** in which flush water is stored, a state where the outlet **578** is closed by the switching valve **558** is maintained. Accordingly, the weight of the storing portion **574** (and the amount of flush water stored in the storing portion **574**) during the small flushing mode is larger than the weight of the storing portion **574** (and the amount of flush water stored in the storing portion **74**) during the large flushing mode. Consequently, during the small flushing mode, since the storing portion **574** of the float **572** acts as the water weight, the buoyancy that acts on the float **572** during the small flushing mode decreases as compared to the buoyancy during the large flushing mode. Therefore, the lowering time **T2** of the float **572** during the small flushing mode is shorter than the lowering time **T1** of the float **572** during the large flushing mode ( $T2 < T1$ ). Further, the balance position, based on the water storage cylinder **62**, between the water level **W2** in the water storage cylinder **62** and the float **572** during the small flushing mode is also lower than the balance position during the large flushing mode.

(102) Then, as shown in the state (IV) of FIG. **13B**, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed, and the draining of flush water from the inside of the storage tank **12** to the discharge opening **18** is stopped. Accordingly, the supply of flush water from the flush water tank device **502** to the toilet main body **8** by the small flushing mode is finished. At this time, a minimum water level **DWL2** (water draining stop water level so-called "dead water line") in the storage tank **12** during the small flushing mode in the state (VI) of FIG. **13B** is located above a minimum water level **DWL1** in the storage tank **12** during the large flushing mode in the state (VI) of FIG. **3A**. That is, the minimum water level **DWL2** during the small flushing mode is higher than the minimum water level **DWL1** during the large flushing mode, by which the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the small

flushing mode is lower than the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the large flushing mode.

(103) According to the discharge valve device **500** of the sixth embodiment of the present invention described above, to start flushing of a flush toilet **4**, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft **54** of the discharge valve device **500** is raised, to raise (open) the valve body **36**, and the flush water in the storage tank **12** is supplied from the discharge opening **18** to the toilet main body **8** of the flush toilet **4**. Then, the water level **W2** of the water storage cylinder **62** decreases depending on the selected large flushing mode or small flushing mode, and the float **72** in the water storage cylinder **62** lowers as the water level **W2** decreases. Accordingly, as the actuation shaft **54** of the discharge valve device **500** lowers, the valve body **36** lowers (closes), and the flush water in the storage tank **12** is supplied from the discharge opening **18** to the toilet main body **8** of the flush toilet **4**. Then, the water level **W2** of the water storage cylinder **62** decreases depending on the selected large flushing mode or small flushing mode, and the supply of flush water from the water level **W2** to the toilet main body **8** of the flush toilet **4** is stopped, thereby finishing flushing of the flush toilet **4**. At this time, since the buoyancy obtained during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode in the float **72**, the lowering time **T2** of the float **572** during the small flushing mode can be shorter than the lowering time **T1** of the float **572** during the large flushing mode ( $T2 < T1$ ). This can make the lowering time of the float **572** and the valve opening time of the valve body **36** during the small flushing mode shorter than the lowering time of the float **572** and the valve opening time of the valve body **36** during the large flushing mode. As a result, when allowing the flush water in the water storage cylinder **62** to flow out of the outlet port **68**, by changing the buoyancy that acts on the float **572** depending on the selected large flushing mode or small flushing mode, the balance position between the water level **W2** in the water storage cylinder **62** and the float **572** can be changed, and the lowering time **T1**, **T2** of the float **572** with the decrease in water level **W2** in the water storage cylinder **62** can be changed. Therefore, a flow rate of flush water per unit time that affects flushing performance (hereinafter referred to as “instantaneous flow rate”) [L/min] can be maintained comparatively high even in a small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body **36** closes the discharge opening can be reduced.

(104) Further, according to the discharge valve device **500** of the present embodiment, since the float **572** includes the storing portion **574** for storing flush water in a part thereof, the storing portion **574** allows the amount of flush water stored during the small flushing mode to be larger than the amount of flush water stored during the large flushing mode. Therefore, since the weight of the storing portion **574** during the small flushing mode is also larger than the weight of the storing portion **574** during the large flushing mode, the buoyancy obtained during the small flushing mode in the float **572** decreases as compared to the buoyancy obtained during the large flushing mode. This can make the lowering time **T2** of the float **572** during the small flushing mode shorter than the lowering time **T1** of the float **572** during the large flushing mode ( $T2 < T1$ ). This can make the lowering time of the float **572** and the valve opening time of the valve body **36** during the small flushing mode shorter than the lowering time of the float **572** and the valve opening time of the valve body **36** during the large flushing mode. As a result, when allowing the flush water in the water storage cylinder **62** to flow out from the outlet port **68** to the storage tank **12**, changing the buoyancy that acts on the float **572** depending on the selected large flushing mode or small flushing mode can change the balance position between the water level **W2** in the water storage cylinder **62** and the float **572** depending on the flushing mode, and can change the lowering time **T1**, **T2** of the float **572** with the decrease in water level in the water storage cylinder **62**. Therefore, the instantaneous flow rate of the flush water [L/min] that affects the flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, the closing sound generated when the valve body

**36** closes the discharge opening **18** can be reduced.

(105) Furthermore, according to the discharge valve device **500** of the present embodiment, when the large flushing mode is executed, the switching valve **558** can open the outlet **578** of the peripheral wall **576** of the storing portion **574** provided in the upper part of the float **572**. Accordingly, since the flush water in the storing portion **574** flows out of the outlet **578** and the flush water is not stored in the storing portion **574** in the upper part of the float **572**, the buoyancy of the float **572** can be set comparatively large. On the other hand, the small flushing mode is executed, the switching valve **558** closes the outlet **578** of the peripheral wall **576** of the storing portion **574**, so that the flush water in the storing portion **574** cannot flow out of the outlet **578**, and flush water is stored in the storing portion **574** in the upper part of the float **572**. In this state, the storing portion **574** itself functions as the water weight. This can set the buoyancy of the float **572** during the small flushing mode to be smaller than during the large flushing mode. As a result, changing the buoyancy that acts on the float **572** depending on the selected large flushing mode or small flushing mode can reliably switch the lowering time of the float **572** and the valve opening time of the valve body **36**. Further, the valve opening time of the valve body **36** is not affected by manufacturing error of the flush water tank device **502** and the flush toilet **4** to which the discharge valve device **500** is applied, and hence proper flushing can be executed on the flush toilet **4** to which the device is applied.

(106) Next, with reference to FIGS. **14A** and **14B**, a discharge valve device **600** according to a seventh embodiment of the present invention will be described. Here, in the discharge valve device **600** according to the seventh embodiment of the present invention shown in FIGS. **14A** and **14B**, the same part as in the discharge valve devices **1**, **100**, **200**, **300**, **400** and **500** according to the first to sixth embodiments of the present invention described above is denoted with the same sign and is not described.

(107) First, as shown in FIGS. **14A** and **14B**, in the discharge valve device **600** according to the seventh embodiment of the present invention, a float **672** includes a peripheral wall **676** provided in a lower part of the float and surrounding a part of the lower part of the float **672** to store flush water. Further, the float **672** includes a communication port **678** formed in a part of the peripheral wall **676** and communicating between inside and outside of the float **672**. Further, the float **672** includes a partition (switching valve **658** for switching large or small flushing) that slides in a vertical direction to the communication port **678**, to be openable and closable. Further, the switching valve **658** closes the communication port **678** of the peripheral wall **676** of the float **672** during a large flushing mode, so that the communication of flush water or air inside and outside the float **672** can be regulated. On the other hand, the switching valve **658** opens the communication port **678** of the peripheral wall **676** of the float **672** during a small flushing mode, to enable the communication of flush water or air inside and outside the float **672**.

(108) Next, as shown in FIGS. **14A** and **14B**, the float **672** includes a top surface **680** that closes an upper region of the peripheral wall **676**, and a lower opening **682** formed along a bottom edge of the peripheral wall **676**. Accordingly, the float **672** forms a generally cylindrical shape opened downward, and the communication port **678** is provided at a height position between the top surface **680** and the lower opening **682**. These structures of the discharge valve device **600** of the present embodiment described above are different from that of the discharge valve device **500** according to the sixth embodiment of the present invention described above.

(109) Next, with reference to FIGS. **14A** and **14B**, an operation of the discharge valve device **600** according to the seventh embodiment of the present invention will be described. First, a standby state shown in state (I) of FIGS. **14A** and **14B** is a state where the communication port **678** is closed by the switching valve **658**. Then, when the large flushing mode is started from the standby state shown in the state (I) of FIG. **14A**, an actuation shaft **54** and a valve body **36** are pulled upward by a first bead chain **52** in state (II) of FIG. **14A**. On the other hand, the switching valve **658** closes the communication port **678** of the float **672** without being pulled upward by a second



bead chain **56** (see state (II) of FIG. **14A**). The state where the communication port **678** of the float **672** is closed by the switching valve **658** is maintained from subsequent state (III) of FIG. **14A** to state (VI) of FIG. **14A** where the valve body **36** is closed and the large flushing mode ends.

(110) Consequently, in the state (II) of FIG. **14A**, the float **672** and the valve body **36** are raised to the highest position, and a discharge opening **18** of a storage tank **12** is opened by the raised valve body **36**. Then, the flush water in the storage tank **12** is drained to the discharge opening **18**.

Thereafter, as shown in the state (III) of FIG. **14A**, when a water level **W1** in the storage tank **12** decreases close to an upper end of the water storage cylinder **62** and further to a water level lower than the upper end of the water storage cylinder **62**, a water pressure due to a water level **W2** in the water storage cylinder **62** is higher than a water pressure due to the water level **W1** in the storage tank **12**, and hence the flush water in the water storage cylinder **62** flows out of the outlet port **68**. Then, as shown in the states (IV) and (V) of FIG. **14A**, the water level **W2** in the water storage cylinder **62** is higher than the water level **W1** in the storage tank **12**, and the flush water in the water storage cylinder **62** continues to flow out of the outlet port **68**. For this reason, as the water level **W2** in the water storage cylinder **62** gradually decreases, the float **672** also lowers in conjunction with lowering of the water level **W2**.

(111) Next, as shown in the state (VI) of FIG. **14A**, when the water level **W1** in the storage tank **12** outside the water storage cylinder **62** lowers to below an upper end of the outlet port **68** of the water storage cylinder **62**, outside of the outlet port **68** of the water storage cylinder **62** is open to the atmosphere. Consequently, a speed at which the flush water in the water storage cylinder **62** flows out of the outlet port **68** is increased, and the water level **W2** in the water storage cylinder **62** further lowers. Therefore, the float **672** also lowers, and the actuation shaft **54** and the valve body **36** also lower integrally. Then, when the valve body **36** contacts a valve seat **66**, the discharge opening **18** is closed, and draining of flush water from inside of the storage tank **12** to the discharge opening **18** is stopped. Consequently, the supply of flush water from a flush water tank device **502** to a toilet main body **8** by the large flushing mode is finished.

(112) On the other hand, when the small flushing mode is started from the standby state shown in the state (I) of FIG. **14B**, the actuation shaft **54** and the valve body **36** are pulled upward by the first bead chain **52** in state (II) of FIG. **14B**. Further, when the switching valve **658** is pulled up via the second bead chain **56**, the switching valve **658** slides upward to open the communication port **678** of the float **672**. A state where the communication port **678** of the float **672** is opened by the switching valve **658** is maintained thereafter until the small flushing mode ends (see state (II) to (IV) of FIG. **14B**).

(113) Further, as shown in the state (II) of FIG. **14B**, the float **672** and the valve body **36** are raised to the highest position, and the discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start draining of flush water from the inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the state (III) of FIG. **14B**, when the water level **W1** in the storage tank **12** decreases close to the upper end of the water storage cylinder **62** and further to a water level lower than the upper end of the water storage cylinder **62**, a water pressure due to a water level **W2** in the water storage cylinder **62** is higher than a water pressure due to the water level **W1** in the storage tank **12** outside the cylinder, and hence the flush water in the water storage cylinder **62** flows out of the outlet port **68**.

(114) Here, for the float **672**, a state where the communication port **678** is opened by the switching valve **658** is maintained. Accordingly, part of air **A** in the float **672** is discharged from the communication port **678** of the peripheral wall **676** to the outside of the float **672**, and in the float **672**, the flush water outside the float **672** partially flows into a lower region of the float **672** by a volume of the discharged air. Therefore, a volume **Q602** of air occupying inside of the float **672** during the small flushing mode is smaller than a volume **Q601** of air occupying inside of the float **672** during the large flushing mode ( $Q602 < Q601$ ). Consequently, buoyancy of the float **672** during the small flushing mode becomes smaller than in the large flushing mode. Therefore, a lowering

time T2 of the float **672** during the small flushing mode is shorter than a lowering time T1 of the float **672** during the large flushing mode ( $T2 < T1$ ). Further, a balance position between the water level W2 and the float **672** in the water storage cylinder **62** during the small flushing mode is also lower than a balance position during the large flushing mode.

(115) Then, as shown in the state (IV) of FIG. **14B**, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed, to stop draining of flush water from the storage tank **12** to the discharge opening **18**. Accordingly, the supply of flush water from the flush water tank device **502** to the toilet main body **8** by the small flushing mode is finished. At this time, a minimum water level DWL2 in the storage tank **12** during the small flushing mode in the state (IV) of FIG. **14B** (draining stop water level so-called “dead water line”) is located above a minimum water level DWL1 in the storage tank **12** during the large flushing mode in the state (VI) of FIG. **14A**. That is, the minimum water level DWL2 during the small flushing mode is higher than the minimum water level DWL1 during the large flushing mode, by which the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the small flushing mode is lower than the amount of flush water drained from the storage tank **12** to the discharge opening **18** during the large flushing mode.

(116) According to the discharge valve device **600** of the seventh embodiment of the present invention described above, as shown in FIG. **14A**, when the large flushing mode is executed, the switching valve **658** for switching large and small flushing closes the communication port **678** of the peripheral wall **676** provided in a lower part of the float **672**. Accordingly, communication of flush water or air inside and outside the float **672** is regulated, and hence the buoyancy of the float **672** can be set comparatively large by the air A trapped in the float **672**. On the other hand, as shown in FIG. **14B**, when the small flushing mode is executed, the switching valve **658** opens the communication port **678** of the peripheral wall **676**, to enable the communication of the flush water or air inside and outside the float **672**. Consequently, during the small flushing mode, part of the air A in the float **672** is discharged from the communication port **678** of the peripheral wall **676** to the outside of the float **672**, and in the float **672**, the flush water outside the float **672** can partially flow into the lower region in the float **672** by the volume of the discharged air. Therefore, the volume Q602 of air occupying the inside of the float **672** during the small flushing mode is smaller than the volume Q601 of air occupying the inside of the float **672** during the large flushing mode ( $Q602 < Q601$ ). Accordingly, the buoyancy of the float **672** during the small flushing mode can be set smaller than during the large flushing mode. As a result, by changing the buoyancy that acts on the float **672** depending on the selected large flushing mode or small flushing mode, the lowering time of the float **672** and the valve opening time of the valve body **36** can be reliably switched. Further, since the valve opening time of the valve body **36** is not affected by the manufacturing error of the flush water tank device **502** and the flush toilet **4** to which the discharge valve device **600** of the present embodiment is applied, proper flushing can be executed on the flush toilet **4** to which the device is applied.

(117) Further, according to the discharge valve device **600** of the present embodiment, as shown in FIG. **14A**, in a state where the communication port **678** of the peripheral wall **676** of the float **672** is closed by the switching valve **658** for switching large and small flushing during the large flushing mode, as the inside of the float **672** is filled with the air A, the flush water outside the float **672** is inhibited from flowing into the float **672** from the lower opening **682**. On the other hand, as shown in FIG. **14B**, in the state where the communication port **678** of the peripheral wall **676** of the float **672** is opened by the switching valve **658** during the small flushing mode, part of the air in the float **672** is discharged from the communication port **678**, so that the flush water outside the float **672** can flow from the lower opening **682** and/or the communication port **678** close into the height of the communication port **678** in the float **672**. Accordingly, the buoyancy that acts on the float **672** during the small flushing mode decreases as compared to the buoyancy that acts on the float **672** during the large flushing mode. As a result, by changing the buoyancy that acts on the float **672**

depending on the selected large flushing mode or small flushing mode, the lowering time of the float **672** and the valve opening time of the valve body **36** can be reliably switched. Further, since the valve opening time of the valve body **36** is not affected by the manufacturing error of the flush water tank device **502** and the flush toilet **4** to which the discharge valve device **600** of the present embodiment is applied, proper flushing can be also executed on the flush toilet **4** to which the device is applied.

(118) Next, with reference to FIGS. **15A** and **15B**, a discharge valve device **700** according to an eighth embodiment of the present invention will be described. Here, in the discharge valve device **700** according to the eighth embodiment of the present invention shown in FIGS. **15A** and **15B**, the same part as in the discharge valve devices **1**, **100**, **200**, **300**, **400**, **500** and **600** according to the first to seventh embodiments of the present invention described above is denoted with the same sign and is not described.

(119) As shown in FIGS. **15A** and **15B**, the discharge valve device **700** according to the eighth embodiment of the present invention is common with the structure of the discharge valve device **500** according to the sixth embodiment of the present invention described above in that the device includes the same float as the float **572** including the storing portion **574** and the outlet **578** in the peripheral wall **576** of the discharge valve device **500** according to the sixth embodiment of the present invention described above. However, the discharge valve device **700** of the present embodiment has a structure different from that of the discharge valve device **500** according to the sixth embodiment in that the device does not include a water storage cylinder corresponding to the water storage cylinder **62** of the discharge valve device **500** according to the sixth embodiment of the present invention described above.

(120) Next, a large flushing mode executed by the discharge valve device **700** according to the eighth embodiment of the present invention will be described with reference to FIG. **15A**. When the large flushing mode is started from a standby state (I) of FIG. **15A**, only a first bead chain **52** is pulled up. Accordingly, an actuation shaft **54** and a valve body **36** of the discharge valve device **700** are pulled up via the first bead chain **52** to linearly move upward, and accordingly the float **572** is also integrally pulled up via the actuation shaft **54** (see state (II) of FIG. **15A**). At this time, the second bead chain **56** is not pulled up, and hence a switching valve **558** is rotated to open the outlet **578** of the storing portion **574** of the float **572** without being pulled up by the second bead chain **56** (see state (II) of FIG. **15A**). A state where the outlet **578** of the storing portion **574** of the float **572** is opened by the switching valve **558** is maintained thereafter until the large flushing mode ends (see state (II) to (V) of FIG. **15A**).

(121) Consequently, in the state (II) of FIG. **15A**, the float **572** and the valve body **36** are raised to the highest position, and a discharge opening **18** of a storage tank **12** is opened by the raised valve body **36**, thereby draining the flush water in the storage tank **12** from the discharge opening **18** to a water conduit **8a** of a toilet main body **8**. Thereafter, as shown in the states (III) and (IV) of FIGS. **15A**, when a water level **W1** in the storage tank **12** lowers, the float **572** lowers in conjunction with lowering of the water level **W1**. At this time, in the storing portion **574** of the float **572**, the outlet **578** is opened by the switching valve **558**, and any flush water is not stored. In this state, the storing portion does not act as a water weight. Then, when the actuation shaft **54** and the valve body **36** lower integrally with the float **572** and the valve body **36** contacts the valve seat **66** as shown in the state (V) of FIG. **15A**, the discharge opening **18** is closed, and the draining of flush water from inside of the storage tank **12** to the discharge opening **18** is stopped. Consequently, supply of flush water from a flush water tank device **502** to the toilet main body **8** by the large flushing mode is finished.

(122) Next, a small flushing mode executed by the discharge valve device **700** according to the eighth embodiment of the present invention will be described with reference to FIG. **15B**. When the small flushing mode is started from the standby state (I) of FIG. **15B**, for example, each of the first bead chain **52** and the second bead chain **56** is pulled up. Accordingly, the actuation shaft **54**

and the valve body 36 of the discharge valve device 700 are raised and linearly move upward via the first bead chain 52, and accordingly the float 572 is also integrally pulled up via the actuation shaft 54 (see state (II) of FIG. 15B). Further, the switching valve 558 is pulled up via the second bead chain 56, and the outlet 578 of the storing portion 574 of the float 572 is closed by the switching valve 558. A state where the outlet 578 of the storing portion 574 of the float 572 is closed by the switching valve 558 is maintained until the small flushing mode ends (see state (II) to (V) of FIG. 15B).

(123) Further, as shown in the state (II) of FIG. 15B, the float 572 and the valve body 36 are raised to the highest position, and the discharge opening 18 of the storage tank 12 is opened by the raised valve body 36, to start draining of flush water from the inside of the storage tank 12 to the discharge opening 18. Thereafter, as shown in the state (III) of FIG. 15B, when the water level W1 in the storage tank 12 lowers to a water level lower than an upper end of the float 572, the float 572 lowers in conjunction with lowering of the water level W1 in the storage tank 12.

(124) At this time, for the storing portion 574 of the float 572 in which flush water is stored, a state where the outlet 578 is closed by the switching valve 558 is maintained. Consequently, a weight of the storing portion 574 (and the amount of flush water stored in the storing portion 574) during the small flushing mode is larger than a weight of the storing portion 574 (and the amount of flush water stored in the storing portion 574) during the large flushing mode. Therefore, during the small flushing mode, the storing portion 574 of the float 572 acts as the water weight, and hence buoyancy that acts on the float 572 during the small flushing mode decreases as compared to buoyancy during the large flushing mode. Accordingly, a lowering time T2 of the float 572 during the small flushing mode is shorter than a lowering time T1 of the float 572 during the large flushing mode ( $T2 < T1$ ). Further, a balance position between the water level W1 in the storage tank 12 and the float 572 during the small flushing mode is also lower than the balance position during the large flushing mode.

(125) Then, when the actuation shaft 54 and the valve body 36 lower integrally with the float 572 and the valve body 36 contacts the valve seat 66 as shown in the state (V) of FIG. 15B, the discharge opening 18 is closed, to stop draining of flush water from the inside of the storage tank 12 to the discharge opening 18. Accordingly, the supply of flush water from the flush water tank device 502 to the toilet main body 8 by the small flushing mode is finished. At this time, a minimum water level DWL2 in the storage tank 12 during the small flushing mode in the state (V) of FIG. 15B (draining stop water level so-called “dead water line”) is located above a minimum water level DWL1 in the storage tank 12 during the large flushing mode in the state (V) of FIG. 15A. That is, the minimum water level DWL2 during the small flushing mode is higher than the minimum water level DWL1 during the large flushing mode, by which the amount of flush water drained from the storage tank 12 to the discharge opening 18 during the small flushing mode is lower than the amount of flush water drained from the storage tank 12 to the discharge opening 18 during the large flushing mode.

(126) According to the discharge valve device 700 of the eighth embodiment of the present invention described above, to start flushing of a flush toilet 4, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft 54 of the discharge valve device 700 is raised to raise (open) the valve body 36, and the flush water in the storage tank 12 is supplied from the discharge opening 18 to the toilet main body 8 of the flush toilet 4. Then, when the water level W1 in the storage tank 12 decreases depending on the selected large flushing mode or small flushing mode, the float 572 lowers as the water level W1 decreases. Consequently, as the actuation shaft 54 of the discharge valve device 700 lowers, the valve body 36 lowers (closes), and the flush water in the storage tank 12 is supplied from the discharge opening 18 to the toilet main body 8 of the flush toilet 4. At this time, since the buoyancy obtained in the float 572 during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode, the lowering time T2 of the float 572 during the small flushing mode can be shorter

than the lowering time T1 of the float 572 during the large flushing mode ( $T2 < T1$ ). This can make the lowering time of the float 572 and the valve opening time of the valve body 36 during the small flushing mode shorter than the lowering time of the float 572 and the valve opening time of the valve body 36 during the large flushing mode. As a result, changing the buoyancy that acts on the float 572 depending on the selected large flushing mode or small flushing mode can change the balance position between the water level W1 in the storage tank 12 and the float 572, and can change the lowering time T1, T2 of the float 572 with the decrease in water level W1 in the storage tank 12. Therefore, a flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body 36 closes the discharge opening can be reduced.

(127) Next, with reference to FIGS. 16A and 16B, a discharge valve device 800 according to a ninth embodiment of the present invention will be described. Here, in the discharge valve device 800 according to the ninth embodiment of the present invention shown in FIGS. 16A and 16B, the same part as in the discharge valve devices 1, 100, 200, 300, 400, 500, 600 and 700 according to the first to eighth embodiments of the present invention described above is denoted with the same sign and is not described.

(128) As shown in FIGS. 16A and 16B, the discharge valve device 800 according to the ninth embodiment of the present invention is common in structure with the discharge valve device 600 according to the seventh embodiment of the present invention described above in that the device includes the same float as the float 672 including the communication port 678 of the discharge valve device 600 according to the seventh embodiment of the present invention described above. However, the discharge valve device 800 of the present embodiment is different in structure from the discharge valve device 600 of the seventh embodiment in that the device does not include a water storage cylinder corresponding to the water storage cylinder 62 of the discharge valve device 600 according to the seventh embodiment of the present invention described above.

(129) Next, a large flushing mode executed by the discharge valve device 800 according to the ninth embodiment of the present invention will be described with reference to FIG. 16A. When the large flushing mode is started from a standby state (I) of FIG. 16A, only a first bead chain 52 is pulled up. Accordingly, an actuation shaft 54 and a valve body 36 of the discharge valve device 800 are pulled up and linearly move upward via the first bead chain 52, and accordingly the float 672 is also integrally pulled up via the actuation shaft 54 (see state (II) of FIG. 16A). At this time, a second bead chain 56 is not pulled up, and hence a switching valve 658 closes the communication port 678 of the float 672 without being pulled up by the second bead chain 56 (see state (II) of FIG. 16A). A state where the communication port 678 of the float 672 is closed by the switching valve 658 is maintained thereafter until the large flushing mode ends (see state (II) to (V) of FIG. 16A).

(130) Consequently, in the state (II) of FIG. 16A, the float 672 and the valve body 36 are raised to the highest position, and a discharge opening 18 of a storage tank 12 is opened by the raised valve body 36. In this state, the flush water in the storage tank 12 is drained from the discharge opening 18 to a water conduit 8a of a toilet main body 8. Thereafter, as shown in the states (III) and (IV) of FIG. 16A, as a water level W1 in the storage tank 12 lowers, the float 672 lowers in conjunction with lowering of the water level W1. At this time, the communication port 678 of the float 672 is closed by the switching valve 658, and a pressure in the float 672 is higher than a water pressure in the storage tank 12 outside the float 672. Therefore, flush water outside the float 672 cannot flow into the float 672 from the communication port 678 of the float 672 and a lower opening 682. Then, when the actuation shaft 54 and the valve body 36 lower integrally with the float 672 and the valve body 36 contacts a valve seat 66 as shown in the state (V) of FIG. 16A, the discharge opening 18 is closed, and draining of flush water from inside of the storage tank 12 to the discharge opening 18 is stopped. Consequently, the supply of flush water from a flush water tank device 502 to the toilet

main body **8** by the large flushing mode is finished.

(131) On the other hand, when a small flushing mode is started from a standby state shown in state (I) of FIG. **16B**, the actuation shaft **54** and the valve body **36** are pulled upward by the first bead chain **52** in state (II) of FIG. **16B**. Further, when the switching valve **658** is pulled up via the second bead chain **56**, the switching valve **658** slides upward, to open the communication port **678** of the float **672**. A state where the communication port **678** of the float **672** is opened by the switching valve **658** is maintained thereafter until the small flushing mode ends (see state (II) to (V) of FIG. **16B**).

(132) Further, as shown in the state (II) of FIG. **16B**, the float **672** and the valve body **36** are raised to the highest position, and the discharge opening **18** of the storage tank **12** is opened by the raised valve body **36**, to start draining of flush water from the inside of the storage tank **12** to the discharge opening **18**. Thereafter, as shown in the state (III) of FIG. **16B**, when the water level **W1** in the storage tank **12** lowers to a water level lower than an upper end of the float **672**, the float **672** lowers in conjunction with lowering of the water level **W1** in the storage tank **12**.

(133) Here, for the float **672**, a state where the communication port **678** is opened by the switching valve **658** is maintained. Accordingly, part of air **A** in the float **672** is discharged from the communication port **678** of a peripheral wall **676** to outside of the float **672**, and in the float **672**, the flush water outside the float **672** partially flows into a lower region of the float **672** by a volume of the discharged air and flush water. Therefore, a volume **Q602** of air occupying inside of the float **672** during the small flushing mode is smaller than a volume **Q601** of air occupying inside of the float **672** during the large flushing mode ( $Q602 < Q601$ ). Consequently, buoyancy of the float **672** during the small flushing mode becomes smaller than during the large flushing mode. Therefore, a lowering time **T2** of the float **672** during the small flushing mode is shorter than a lowering time **T1** of the float **672** during the large flushing mode ( $T2 < T1$ ). Further, a balance position between the water level **W1** in the storage tank **12** and the float **672** during the small flushing mode is also lower than the balance position during the large flushing mode.

(134) Then, as shown in the state (V) of FIG. **16B**, when the valve body **36** contacts the valve seat **66**, the discharge opening **18** is closed, and the draining of flush water from the inside of the storage tank **12** to the discharge opening **18** is stopped. Consequently, the supply of flush water from the flush water tank device **502** to the toilet main body **8** by the small flushing mode is finished. At this time, a minimum water level **DWL2** (draining stop water level so-called “dead water line”) in the storage tank **12** during the small flushing mode in the state (V) of FIG. **16B** is located above a minimum water level **DWL1** in the storage tank **12** during the large flushing mode in the state (V) of FIG. **16A**. That is, the minimum water level **DWL2** during the small flushing mode is higher than the minimum water level **DWL1** during the large flushing mode, by which an amount of flush water drained from the storage tank **12** to the discharge opening **18** during the small flushing mode is lower than an amount of flush water drained from the storage tank **12** to the discharge opening **18** during the large flushing mode.

(135) According to the discharge valve device **800** of the ninth embodiment of the present invention described above, to start flushing of the flush toilet **4**, first, on selecting either flushing mode of the large flushing mode or the small flushing mode, the actuation shaft **54** of the discharge valve device **800** is raised, to raise (open) the valve body **36**. The flush water in the storage tank **12** is supplied from the discharge opening **18** to the toilet main body **8** of the flush toilet **4**. Then, when the water level **W1** in the storage tank **12** decreases depending on the selected large flushing mode or small flushing mode, the float **672** lowers as the water level **W1** decreases. Accordingly, as the actuation shaft **54** of the discharge valve device **800** lowers, the valve body **36** lowers (closes), and the flush water in the storage tank **12** is supplied from the discharge opening **18** to the toilet main body **8** of the flush toilet **4**. At this time, the buoyancy obtained in the float **672** during the small flushing mode decreases as compared to the buoyancy obtained during the large flushing mode, and hence the lowering time **T2** of the float **672** during the small flushing mode can be shorter than

the lowering time T1 of the float 672 during the large flushing mode ( $T2 < T1$ ). This can make the lowering time of the float 672 and the valve opening time of the valve body 36 during the small flushing mode shorter than the lowering time of the float 672 and the valve opening time of the valve body 36 during the large flushing mode. As a result, changing the buoyancy that acts on the float 672 depending on the selected large flushing mode or small flushing mode can change the balance position between the water level W1 in the storage tank 12 and the float 672 and can change the lowering time T1, T2 of the float 672 with the decrease in water level W1 in the storage tank 12. Therefore, a flow rate per unit time of flush water (hereinafter referred to as “instantaneous flow rate”) [L/min] that affects flushing performance can be maintained comparatively high even in the small flushing mode in which the flush water amount is smaller than in the large flushing mode. Further, closing sound generated when the valve body 36 closes the discharge opening can be reduced.

(136) Although the present disclosure has been explained with reference to specific, preferred embodiments, one of ordinary skill in the art will recognize that modifications and improvements can be made while remaining within the scope and spirit of the present disclosure. The scope of the present disclosure is determined solely by appended claims.

## Claims

1. A discharge valve device provided in a flush water tank configured to supply flush water to a flush toilet, the discharge valve device comprising: a valve body configured to open and close a discharge opening provided in a bottom of the flush water tank; an actuation shaft including a lower end provided with the valve body, the actuation shaft being configured to open and close the discharge opening by moving up and down the valve body; a water storage cylinder configured to store a part of flush water in the flush water tank, the water storage cylinder including an outlet port configured to cause flush water in the water storage cylinder to flow outside of the water storage cylinder, the actuation shaft being inserted into the water storage cylinder in a vertical direction; and a float disposed in the water storage cylinder, the float being configured to cause buoyancy obtained by the flush water in the water storage cylinder to act on the actuation shaft, wherein when the float lowers with a decrease in water level in the water storage cylinder, the actuation shaft and the valve body are configured to be lowered in conjunction with the float and then the valve body is configured to close the discharge opening, during a period from when the valve body opens to when the valve body closes, either flushing mode of a large flushing mode or a small flushing mode is selectively performed, in the large flushing mode the flush water in the flush water tank is supplied from the discharge opening to the flush toilet in a first flush water amount, and in the small flushing mode the flush water is supplied in a second flush water amount smaller than the first flush water amount, and the water storage cylinder or the float is configured to change a lowering speed of the float with the decrease in water level in the water storage cylinder depending on the selected large flushing mode or small flushing mode, wherein a first total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the large flushing mode is larger than a second total outflow amount of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode.

2. The discharge valve device according to claim 1, wherein the water storage cylinder is configured to increase a total opening area of the outlet port during the small flushing mode as compared to a total opening area of the outlet port during the large flushing mode, when the valve body is opened, and a flush water amount per unit time of the flush water in the water storage cylinder flowing out from the outlet port to the flush water tank in the small flushing mode is larger than in the large flushing mode.

3. The discharge valve device according to claim 2, wherein the outlet port includes a first outlet

port and a second outlet port, and the water storage cylinder causes the flush water in the flush water tank to flow out from the first outlet port to the flush water tank in the large flushing mode, whereas the water storage cylinder causes the flush water in the water storage cylinder to flow out from both the first outlet port and the second outlet port to the flush water tank in the small flushing mode.

4. The discharge valve device according to claim 3, wherein the second outlet port is disposed above the first outlet port.

5. The discharge valve device according to claim 2, wherein the water storage cylinder includes a partition that closes a part of the outlet port, and the partition closes a part of the outlet port so that the total opening area of the outlet port during the large flushing mode is smaller than the total opening area of the outlet port during the small flushing mode.

6. The discharge valve device according to claim 5, wherein the partition includes a communication hole that communicates between inside of the water storage cylinder and inside of the flush water tank in a state where the outlet port is closed, the communication hole including an opening cross-sectional area smaller than an opening cross-sectional area of the outlet port, and the partition causes the flush water in the water storage cylinder to flow out from the communication hole into the flush water tank in the state where the outlet port is closed in the large flushing mode, whereas the partition opens the outlet port and causes the flush water in the water storage cylinder to flow out from the whole outlet port into the flush water tank in the small flushing mode.

7. The discharge valve device according to claim 1, wherein the water storage cylinder includes a first outlet port configured to cause the flush water in the water storage cylinder to flow out to the flush water tank in the large flushing mode, and a second outlet port configured to cause the flush water in the water storage cylinder to flow out to the flush water tank in the small flushing mode, when the valve body is opened, a total opening area of the first outlet port is the same as a total opening area of the second outlet port, and the second outlet port is disposed above the first outlet port, and the water storage cylinder is configured to increase a second flush water amount per unit time of the flush water in the water storage cylinder flowing out from the second outlet port to the flush water tank in the small flushing mode as compared to a first flush water amount per unit time of the flush water in the water storage cylinder flowing out from the first outlet port to the flush water tank in the large flushing mode.

8. The discharge valve device according to claim 1, wherein the water storage cylinder includes a water storage cylinder body including the outlet port, and a small tank communicatively connected to the water storage cylinder body, the small tank includes a communication opening that communicates with the water storage cylinder body, and a partition that opens and closes the communication opening, and the partition opens the communication opening to communicate between the water storage cylinder body and the small tank in the large flushing mode, whereas the partition closes the communication opening to separate the water storage cylinder body and the small tank in the small flushing mode.

9. The discharge valve device according to claim 8, wherein the partition is provided rotatably with respect to the communication opening, rotates in a direction to open the communication opening in the large flushing mode, and rotates in a direction to close the communication opening in the small flushing mode.

10. The discharge valve device according to claim 9, wherein the communication opening includes a locking portion that is provided at a rim of the communication opening and that rotatably supports the partition, and the locking portion restricts rotation of the partition, when the partition rotates in the direction to close the communication opening and contacts the locking portion in the small flushing mode.

11. The discharge valve device according to claim 10, wherein the partition further includes a water weight portion configured to store flush water, the small tank further includes an auxiliary outlet port that formed in a bottom surface of the small tank, the auxiliary outlet port being configured to



cause the flush water in the small tank to flow outside, and in a state where the partition abuts on the locking portion, the water weight portion is to store flush water and the auxiliary outlet port of the small tank is opened, and when the flush water in the small tank flows out from the auxiliary outlet port, the partition rotates in a direction apart from the locking portion and causes the flush water in the water weight portion to flow outside.

12. The discharge valve device according to claim 11, wherein the partition at an initial position has a state where the partition is not in contact with the locking portion and the communication opening is opened and any flush water is not stored in the water weight portion, in a standby period in which any flushing mode is not executed and a period in which the large flushing mode is executed, the partition is maintained at the initial position, to close the auxiliary outlet port of the small tank, and flush water is storable in the small tank, whereas in a period in which the small flushing mode is executed, the partition rotates from the initial position and contacts the locking portion, to maintain a state where the communication opening is closed, and then when the flush water in the small tank flows out from the auxiliary outlet port, the partition causes the flush water in the water weight portion to flow outside while rotating toward the initial position and then returns to the initial position.

13. The discharge valve device according to claim 8, wherein a top edge of the water storage cylinder body and a top edge of the small tank are flush with each other, and in a state where the communication opening is closed by the partition, an upper end of the partition protrudes upward from the top edge of the communication opening or the top edge of the small tank.

14. The discharge valve device according to claim 1, wherein the float is configured to decrease buoyancy obtained during the small flushing mode as compared to buoyancy obtained during the large flushing mode.

15. The discharge valve device according to claim 14, wherein the float includes a storing portion for storing flush water in a part of the float, and the storing portion is configured so that the amount of flush water stored during the small flushing mode is larger than the amount of flush water stored during the large flushing mode.

16. The discharge valve device according to claim 15, wherein the storing portion is provided in an upper part of the float and includes a peripheral wall surrounding a part of the upper part of the float to store flush water, and a partition provided to open and close an outlet formed in a part of the peripheral wall, the partition opens the outlet of the peripheral wall and allows flush water in the storing portion to flow out of the outlet during the large flushing mode, whereas the partition closes the outlet of the peripheral wall and maintains a state where flush water is stored in the storing portion to make the storing portion a water weight during the small flushing mode.

17. The discharge valve device according to claim 14, wherein the float includes a peripheral wall provided in a lower part of the float and surrounding a part of the lower part of the float to store flush water, a communication port formed in a part of the peripheral wall to communicate inside and outside the float, and a partition provided to open and close the communication port, the partition closes the communication port of the peripheral wall to regulate communication of flush water or air inside and outside the float during the large flushing mode, whereas the partition opens the communication port of the peripheral wall to enable the communication of flush water or air inside and outside the float during the small flushing mode.

18. The discharge valve device according to claim 17, wherein the float includes a top surface that closes an upper region of the peripheral wall, and a lower opening formed along a bottom edge of the peripheral wall, the float forms a generally cylindrical shape opened downward, and the communication port is provided at a height position between the top surface and the lower opening.

19. A flush water tank device comprising the discharge valve device according to claim 1.

20. A flush toilet comprising the flush water tank device according to claim 19.

---