

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416357
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yu; Ji Hun et al.

Control apparatus for transmission of agricultural work vehicle and control method for transmission of agricultural work vehicle

Abstract

A control apparatus and a control method for a transmission of an agricultural work vehicle are provided, the control apparatus including: a forward/backward clutch of a forward/backward shifting unit that performs forward/backward shifting with respect to drive generated by an engine; and a drive clutch of a drive shifting unit that performs drive shifting with respect to the drive generated by the engine.

Inventors:	Yu; Ji Hun (Anyang-si, KR), Lee; Jin Woong (Anyang-si, KR), Shin; Ok Shik (Anyang-si, KR), Cho; Bong Jin (Anyang-si, KR)
Applicant:	LS MTRON LTD. (Anyang-si, KR)
Family ID:	1000008821852
Assignee:	LS MTRON LTD. (Anyang-si, KR)
Appl. No.:	17/284646
Filed (or PCT Filed):	September 20, 2019
PCT No.:	PCT/KR2019/012187
PCT Pub. No.:	WO2020/080686
PCT Pub. Date:	April 23, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210396308 A1	Dec. 23, 2021

Foreign Application Priority Data

Publication Classification

Int. Cl.: **F16H59/56** (20060101); **F16H59/48** (20060101); **F16H59/54** (20060101); **F16H59/74** (20060101); **F16H61/00** (20060101); **F16H61/02** (20060101)

U.S. Cl.:

CPC **F16H59/56** (20130101); **F16H59/48** (20130101); **F16H59/54** (20130101); **F16H59/74** (20130101); **F16H61/02** (20130101); F16H2059/746 (20130101); F16H2061/0075 (20130101)

Field of Classification Search

CPC: F16H (59/56); F16H (59/48); F16H (59/54); F16H (59/74); F16H (61/02); F16H (2059/746); F16H (2061/0075)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5024305	12/1990	Kurihara et al.	N/A	N/A
5662548	12/1996	Mori	N/A	N/A
2004/0229728	12/2003	Oshima	477/176	F16H 61/143
2004/0231951	12/2003	Hasegawa	192/220	B60W 10/184
2006/0150624	12/2005	Shah	60/445	F16H 61/431
2007/0087897	12/2006	Kitamura	N/A	N/A
2008/0300105	12/2007	Eriksson	477/107	B60W 30/18118
2011/0218716	12/2010	Olsson	74/665A	F16H 3/006
2013/0116895	12/2012	Smith	701/50	F16H 61/70
2016/0311433	12/2015	Shelton	N/A	B60W 10/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101228343	12/2007	CN	N/A
102338216	12/2011	CN	N/A
107336706	12/2016	CN	N/A
H03200431	12/1990	JP	N/A
2014156919	12/2013	JP	N/A
2018017295	12/2017	JP	N/A
10-1994-0009464	12/1993	KR	N/A
20-2000-0006297	12/1999	KR	N/A
20120001370	12/2011	KR	N/A

OTHER PUBLICATIONS

Extended European Search Report for related European Application No. 19874051.6; action dated Apr. 20, 2022; (8 pages). cited by applicant
International Search Report for related International Application No. PCT/KR2019/012187; report dated Apr. 23, 2020; (5 pages). cited by applicant
Written Opinion for related International Application No. PCT/KR2019/012187; report dated Apr. 23, 2020; (4 pages). cited by applicant
Chinese Office action for related Chinese Application No. 201980065462.2; action dated Nov. 11, 2021; (5 pages). cited by applicant
Japanese Office Action for related Japanese Application No. 2021-521180; action dated May 23, 2022; (3 pages). cited by applicant

Primary Examiner: Hilgendorf; Dale W

Assistant Examiner: Glenn, III; Frank T

Attorney, Agent or Firm: K&L Gates LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is a National Stage of International Application No. PCT/KR2019/012187 filed on Sep. 20, 2019, which claims priority to Korean Application No. 10-2018-0124485, filed on Oct. 18, 2018 and Korean Application No. 10-2019-0108182, filed on Sep. 2, 2019, the disclosures of which are incorporated herein by reference.

FIELD

(2) The present disclosure relates to a control apparatus and control method for controlling a transmission of an agricultural work vehicle.

BACKGROUND

(3) Agricultural work vehicles are used for cultivating crops necessary for human life using the land. For example, combines, tractors, and the like correspond to the agricultural work vehicles. The combines harvest and thresh crops such as rice, barley, wheat, and soybeans. The tractors perform work necessary for growing crops using a tractive force. Such an agricultural work vehicle includes a transmission for adjusting a torque, a speed, and the like as needed in a work process.

(4) The transmission of a general vehicle implements an idling travel mode in which the vehicle slowly travels at a preset traveling stage using a torque converter even in a state in which a driver does not perform an operation on an accelerator pedal. Even when the transmission is controlled in the idling travel mode, the vehicle may not travel and remain in a stopped state due to the torque converter when the driver is applying the brake.

(5) However, the transmission of an agricultural work vehicle according to the related art does not use a torque converter. Accordingly, when the agricultural work vehicle that has been started is switched from the stopped state to the idling travel mode just by operating a shuttle lever forward or rearward, even when the driver applies the brake, the agricultural work vehicle may not maintain the stopped state and travels due to a large traveling power (torque) of the agricultural work vehicle. Thus, since the transmission of the agricultural work vehicle according to the related art is switched to the idling travel mode even in a situation in which the driver does not intend to drive the agricultural work vehicle, the driving difficulty of the agricultural work vehicle increases, and a risk of increasing accidents is high.

SUMMARY

(6) The present disclosure is designed to solve the problems and is for providing a transmission control device for an agricultural work vehicle and a transmission control method of an agricultural work vehicle that can prevent a transmission from being switched to an idling travel mode just by operating a shuttle lever forward or rearward.

(7) In order to solve the above problems, the present disclosure may include the following configurations.

(8) A transmission control device for an agricultural work vehicle including a front-rear clutch of a front-rear shifting part that performs front-rear shifting with respect to driving generated from an engine and a traveling clutch of a travel shifting part that performs travel shifting with respect to the driving generated by the engine according to the present disclosure includes: a reception module that receives operation information of a shuttle lever, operation information of a traveling operation mechanism, and operation information of a clutch operation mechanism from an operation unit including the shuttle lever for front-rear shifting control, the traveling operation mechanism for traveling control, and the clutch operation mechanism for release control of a main clutch among the front-rear clutch and the traveling clutch; an identification module that identifies, on the basis of the operation information of the shuttle lever, whether the shuttle lever is in a front-rear operation state in which the agricultural work vehicle moves forward or rearward or a neutral operation state in which the agricultural work vehicle does not move forward or rearward, identifies, on the basis of the operation information of the traveling operation mechanism, whether the traveling operation mechanism is in a traveling operation state in which the agricultural work vehicle travels or a traveling release state in which the agricultural work vehicle does not travel, and identifies, on the basis of the operation information of the clutch operation mechanism, whether the clutch operation mechanism is in a release operation state in which the main clutch is to be unfastened or a fastening operation state in which the main clutch is to be fastened; and a control module that controls, according to a result of the identification by the identification module, the transmission in any one of a traveling standby mode in which a traveling standby mode in which the agricultural work vehicle, the engine of which is started, is maintained in a stopped state, a normal traveling mode in which the agricultural work vehicle travels to correspond to operation of an acceleration operation mechanism of the traveling operation mechanism, and an idling travel mode in which the agricultural work vehicle travels in a state in which the engine is in an idle state.

(9) The control module may control the transmission in the traveling standby mode when it is identified that the shuttle lever is in the front-rear operation state, the traveling operation mechanism is in the traveling release state, and the clutch operation mechanism is in a state in which the agricultural work vehicle, the engine of which is started, is stopped in the fastening operation state.

(10) A transmission control method of an agricultural work vehicle including a front-rear clutch of a front-rear shifting part that performs front-rear shifting with respect to driving generated from an engine and a traveling clutch of a travel shifting part that performs travel shifting with respect to the driving generated by the engine according to the present disclosure includes: identifying an operation state of an operation unit including a shuttle lever for front-rear shifting control, a traveling operation mechanism for traveling control, and a clutch operation mechanism for release control of a main clutch among the front-rear clutch and the traveling clutch in a state in which the agricultural work vehicle, the engine of which is started, is stopped; in a stopped state of the agricultural work vehicle the engine of which is started, controlling the transmission in a traveling standby mode in which the agricultural work vehicle is maintained in the stopped state depending on a result obtained by identifying the operation state of the operation unit; and identifying an operation state of the traveling operation mechanism in the traveling standby mode; and controlling the transmission in a traveling mode in which the agricultural work vehicle travels when it is identified in the traveling standby mode that the traveling operation mechanism is in a traveling operation state in which the agricultural work vehicle travels.

(11) The identifying of the operation state of the operation unit may include identifying whether the shuttle lever is in a front-rear operation state in which the agricultural work vehicle moves forward or rearward or in a neutral operation state in which the agricultural work vehicle does not move forward or rearward, identifying whether the traveling operation mechanism is in the traveling operation state or in a traveling release state in which the agricultural work vehicle does not travel, and identifying whether the clutch operation mechanism is in a release operation state in which the main clutch is to be released or in a fastening operation state in which the main clutch is to be fastened,

(12) The controlling of the transmission in the traveling standby mode may include switching the transmission to the traveling standby mode as releasing of the main clutch is maintained when it is identified that the shuttle lever is in the front-rear operation state, the traveling operation mechanism is in the traveling release state, and the clutch operation mechanism is in the fastening operation state,

(13) The identifying of the operation state of the traveling operation mechanism in the traveling standby mode may include identifying whether the traveling operation mechanism is in the traveling operation state or the traveling release state in the traveling standby mode.

(14) The controlling of the transmission in the traveling mode may include: controlling the transmission in a normal traveling mode in which the agricultural work vehicle travels according to a degree of operation of an acceleration operation mechanism when it is identified that the acceleration operation mechanism of the traveling operation mechanism is in an acceleration operation state in which the agricultural work vehicle is accelerated; and controlling the transmission in an idling travel mode in which the agricultural work vehicle travels in a state in which the engine is in an idle state when it is identified that the acceleration operation mechanism is in an acceleration release state in which the agricultural work vehicle is not accelerated.

(15) According to the present disclosure, a transmission control device can have the following effects.

(16) According to the present disclosure, since a transmission can be controlled so that an agricultural work vehicle does not travel just by operating a shuttle lever forward or rearward in a state in which an agricultural work vehicle of which an engine is started is stopped, the agricultural work vehicle is prevented from traveling in a situation in which travel is not intended by a driver. Thus, the driving difficulty of the agricultural work vehicle can be reduced, and the occurrence of accidents can be prevented.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic side view illustrating an example of an agricultural work vehicle.

(2) FIGS. 2 to 4 are schematic block diagrams of transmission control devices of an agricultural work vehicle according to the present disclosure.

(3) FIGS. 5 to 9 are schematic flowcharts of a transmission control method of the agricultural work vehicle according to the present disclosure.

DETAILED DESCRIPTION

(4) Hereinafter, embodiments of a transmission control device of an agricultural work vehicle according to the present disclosure will be described in detail with reference to the accompanying drawings.

(5) Referring to FIGS. 1 to 3, a transmission control device 1 of an agricultural work vehicle according to the present disclosure is applied to an agricultural work vehicle 100. The agricultural work vehicle 100 is used for cultivating crops necessary for human life by using the land. For example, the agricultural work vehicle 100 may be a tractor, a combine, or the like. Prior to

describing the transmission control device **1** of the agricultural work vehicle according to the present disclosure, the agricultural work vehicle **100** will be described below.

(6) The agricultural work vehicle **100** may include a vehicle body **110** to which an engine (not illustrated) is coupled, a driver seat **120** provided in the vehicle body **110**, wheels **130** coupled to the vehicle body **110**, an operation unit **140** provided at the driver seat **120**, and a transmission **150** coupled to the vehicle body **110**.

(7) The operation unit **140** may include a shuttle lever **141**, a traveling operation mechanism **142**, and a clutch operation mechanism **143**.

(8) The shuttle lever **141** is for front-rear shift control. The shuttle lever **141** may be in a front-rear operation state for moving the agricultural work vehicle **100** forward or rearward. The shuttle lever **141** may be in a neutral operation state to prevent the agricultural work vehicle **100** from being moved forward or rearward. The shuttle lever **141** may be in the front-rear operation state or the neutral operation state according to operation by a driver.

(9) The traveling operation mechanism **142** is for traveling control. The traveling operation mechanism **142** may be in a traveling operation state in which the agricultural work vehicle **100** travels. The traveling operation mechanism **142** may be in a traveling release state in which the agricultural work vehicle **100** does not travel. The traveling operation mechanism **142** may be in the traveling operation state or the traveling release state according to the operation by the driver.

(10) The traveling operation mechanism **142** may include an acceleration operation mechanism **1421** and a brake pedal **1422**.

(11) The acceleration operation mechanism **1421** is for acceleration control. The acceleration operation mechanism **1421** may be in an acceleration operation state in which the agricultural work vehicle **100** is accelerated. When the acceleration operation mechanism **1421** is in the acceleration operation state, thus accelerating the agricultural work vehicle **100**, the driving of the engine is changed according to the degree of operation of the acceleration operation mechanism **1421**, and thus the agricultural work vehicle **100** may be accelerated. The acceleration operation mechanism **1421** may be in an acceleration release state in which the agricultural work vehicle **100** is not accelerated. The acceleration operation mechanism **1421** may be in the acceleration operation state or the acceleration release state according to the operation by the driver. The acceleration operation mechanism **1421** may include a hand throttle **14211** that the driver may operate with his/her hand, and an accelerator pedal **14212** that the driver may operate with his/her foot.

(12) The brake pedal **1422** is for deceleration control. The brake pedal **1422** may be in a braking state in which a traveling speed of the agricultural work vehicle **100** is reduced. The brake pedal **1422** may be in a non-braking state in which the traveling speed of the agricultural work vehicle **100** is not reduced. The brake pedal **1422** may be in the braking state or in the non-braking state according to the operation by the driver. The brake pedal **1422** may be operated by the driver's foot.

(13) The clutch operation mechanism **143** is for release control of a main clutch **150a** (see FIG. 2) of the transmission **150**. The main clutch **150a** selectively transmits driving according to whether or not the main clutch **150a** is fastened. When the main clutch **150a** is fastened, the main clutch **150a** may transmit the driving. When the main clutch **150a** is released, the main clutch **150a** may not transmit the driving. The clutch operation mechanism **143** may be in a release operation state for releasing the main clutch **150a**. The clutch operation mechanism **143** may be in a fastening operation state for fastening the main clutch **150a**. The clutch operation mechanism **143** may be in the release operation state or the fastening operation state according to the operation by the driver. The clutch operation mechanism **143** may include a clutch pedal **1431** which the driver may operate with his/her foot and a hand clutch **1432** which the driver may operate with his/her hand. The hand clutch **1432** may be a clutch switch (not illustrated).

(14) The transmission **150** is for performing gear shifting with respect to the driving generated by the engine. The transmission control device **1** of the agricultural work vehicle according to the present disclosure may control the transmission **150** to identify an operation state of the operation

unit **140** and to correspond to the operation state of the operation unit **140**. The transmission **150** may include a front-rear shifting part **151** and a travel shifting part **152**.

(15) The front-rear shifting part **151** performs front-rear shifting with respect to the driving generated from the engine. The transmission control device **1** of the agricultural work vehicle according to the present disclosure may control the front-rear shifting part **151** to identify an operation state of the shuttle lever **141** and to correspond to the operation state of the shuttle lever **141**. The front-rear shifting part **151** may include a front-rear clutch **1511**. The front-rear shifting part **151** may transmit the driving, in which the front-rear shifting is performed, to the travel shifting part **152**. When the front-rear clutch **1511** is fastened, the driving generated from the engine may be transmitted to the travel shifting part **152** after the front-rear shifting is performed. When the front-rear clutch **1511** is unfastened, the driving generated from the engine is not transmitted to the travel shifting part **152**. The front-rear clutch **1511** may be implemented as a multiple disc clutch that selectively transmits the driving using friction. In this case, as the plurality of friction members come into contact with each other, the front-rear clutch **1511** may be fastened to transmit the driving. As the plurality of friction members are spaced apart from each other, the front-rear clutch **1511** may be unfastened so as not to transmit the driving. Meanwhile, the front-rear shifting part **151** may include at least one gear and at least one sleeve for the front-rear shifting.

(16) The front-rear shifting part **151** may perform the front-rear shifting with respect to the driving in which the travel shifting is performed by the travel shifting part **152**. In this case, the travel shifting part **152** may perform the travel shifting with respect to the driving generated from the engine, and the front-rear shifting part **151** may perform the front-rear shifting with respect to the driving in which the travel shifting is performed by the travel shifting part **152**, and then the driving may be transmitted to an axle (not illustrated).

(17) The travel shifting part **152** may perform the travel shifting with respect to the driving transmitted from the engine. The transmission control device **1** of the agricultural work vehicle according to the present disclosure may control the travel shifting part **152** to identify an operation state of the traveling operation mechanism **142** and to correspond to the operation state of the traveling operation mechanism **142**. The travel shifting part **152** may include a traveling clutch **1521**. The travel shifting part **152** may perform the travel shifting with respect to the driving transmitted from the front-rear shifting part **151**. When the traveling clutch **1521** is fastened, the driving transmitted from the front-rear shifting part **151** may be transmitted to the axle after the travel shifting is performed. When the traveling clutch **1521** is unfastened, the driving transmitted from the front-rear shifting part **151** is not transmitted to the axle. The traveling clutch **1521** may be implemented as a multiple disc clutch that selectively transmits the driving using friction. In this case, as the plurality of friction members come into contact with each other, the traveling clutch **1521** may be fastened to transmit the driving. As the plurality of friction members are spaced apart from each other, the traveling clutch **1521** may be unfastened so as not to transmit the driving. The travel shifting part **152** may include a plurality of traveling clutches **1521**. Meanwhile, the travel shifting part **152** may include at least one gear and at least one sleeve for the travel shifting.

(18) The travel shifting part **152** may transmit the driving, in which the travel shifting is performed, to the front-rear shifting part **151**. In this case, the travel shifting part **152** may perform the travel shifting with respect to the driving generated from the engine, and the front-rear shifting part **151** may perform the front-rear shifting with respect to the driving in which the travel shifting is performed by the travel shifting part **152**, and then the driving may be transmitted to an axle.

(19) Hereinafter, the description will be made based on an embodiment in which the front-rear shifting part **151** performs the front-rear shifting with respect to the driving generated from the engine, the travel shifting part **152** performs the travel shifting with respect to the driving transmitted from the front-rear shifting part **151**, and then the driving is transmitted to the axle. From this, those skilled in the art to which the present disclosure belongs can easily understand the

embodiment in which the travel shifting part **152** performs the travel shifting with respect to the driving generated from the engine, the front-rear shifting part **151** performs the front-rear shifting with respect to the driving transmitted from the travel shifting part **152**, and then the driving is transmitted to the axle.

(20) Here, one of the front-rear clutch **1511** and the traveling clutch **1521** may correspond to the main clutch **150a**. When the front-rear clutch **1511** corresponds to the main clutch **150a**, the clutch operation mechanism **143** may be in the release operation state in which the front-rear clutch **1511** is to be unfastened or in the fastening operation state in which the front-rear clutch **1511** is to be fastened. When the traveling clutch **1521** corresponds to the main clutch **150a**, the clutch operation mechanism **143** may be in the release operation state in which the traveling clutch **1521** is to be unfastened or in the fastening operation state in which the traveling clutch **1521** is to be fastened. Which of the front-rear clutch **1511** and the traveling clutch **1521** corresponds to the main clutch **150a** is determined according to an arrangement relationship, a connection relationship, and the like between the shifting parts and peripheral devices of the transmission **150**.

(21) In order to control the transmission **150** of the agricultural work vehicle **100**, the transmission control device **1** of the agricultural work vehicle according to the present disclosure may include a reception module **2**, an identification module **3**, and a control module **4**. The transmission control device **1** of an agricultural work vehicle according to the present disclosure may be coupled to the vehicle body **110** (see FIG. 1).

(22) Referring to FIGS. 2 and 3, the reception module **2** is for receiving operation information from the agricultural work vehicle **100**. The reception module **2** may receive the operation information from the operation unit **140**. The reception module **2** may receive the operation information from the operation unit **140** using wired communication, wireless communication, or the like.

(23) The reception module **2** may receive the operation information of the shuttle lever **141**. The operation information of the shuttle lever **141** is information on which of the front-rear operation state and the neutral operation state the shuttle lever **141** belongs to. The reception module **2** may provide the operation information of the shuttle lever **141** to the identification module **3**.

(24) The reception module **2** may receive the operation information of traveling operation mechanism **142**. The operation information of the traveling operation mechanism **142** is information on which of the traveling operation state and the traveling release state the traveling operation mechanism **142** belongs to. The reception module **2** may provide the operation information of the traveling operation mechanism **142** to the identification module **3**.

(25) When the traveling operation mechanism **142** includes the acceleration operation mechanism **1421**, the reception module **2** may receive the operation information of the acceleration operation mechanism **1421**. The operation information of the acceleration operation mechanism **1421** is information on which of the acceleration operation state and the acceleration release state the acceleration operation mechanism **1421** belongs to. When the acceleration operation mechanism **1421** includes the hand throttle **14211** and the accelerator pedal **14212**, the reception module **2** may receive operation information of the hand throttle **14211** and operation information of the accelerator pedal **14212**.

(26) When the traveling operation mechanism **142** includes the brake pedal **1422**, the reception module **2** may receive operation information of the brake pedal **1422**. The operation information of the brake pedal **1422** is information on which of the braking state and the non-braking state the brake pedal **1422** belongs to.

(27) The reception module **2** may receive operation information of the clutch operation mechanism **143**. The operation information of the clutch operation mechanism **143** is information on which of the release operation state and the fastening operation state the clutch operation mechanism **143** belongs to. The reception module **2** may provide the operation information of the clutch operation mechanism **143** to the identification module **3**. When the clutch operation mechanism **143** includes the clutch pedal **1431** and the hand clutch **1432**, the reception module **2** may receive operation

information of the clutch pedal **1431** and operation information of the hand clutch **1432**.

(28) Referring to FIGS. **2** and **3**, the identification module **3** is for identifying the operation information received by the reception module **2**.

(29) The identification module **3** may identify, on the basis of the operation information of the shuttle lever **141**, whether the shuttle lever belongs to the front-rear operation state or the neutral operation state. When it is identified that the shuttle lever **141** is in the front-rear operation state, the identification module **3** may provide a front-rear operation signal to the control module **4**. When it is determined that the shuttle lever **141** is in the neutral operation state, the identification module **3** may provide a neutral operation signal to the control module **4**.

(30) The identification module **3** may identify whether the traveling operation mechanism **142** is in the traveling operation state or the traveling release state on the basis of the operation information of the traveling operation mechanism **142**. When it is identified that the traveling operation mechanism **142** is in the traveling operation state, the identification module **3** may provide a traveling operation signal to the control module **4**. When it is identified that the traveling operation mechanism **142** is in the traveling release state, the identification module **3** may provide a traveling release signal to the control module **4**.

(31) When the traveling operation mechanism **142** includes the acceleration operation mechanism **1421**, the identification module **3** may identify whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state on the basis of the operation information of the acceleration operation mechanism **1421**. When it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state, the identification module **3** may provide an acceleration operation signal to the control module **4**. When it is identified that the acceleration operation mechanism **1421** is in the acceleration release state, the identification module **3** may provide an acceleration release signal to the control module **4**.

(32) When the traveling operation mechanism **142** includes the brake pedal **1422**, the identification module **3** may identify whether the brake pedal **1422** is in the braking state or the non-braking state on the basis of the operation information of the brake pedal **1422**. When it is identified that the brake pedal **1422** is in the braking state, the identification module **3** may provide a braking signal to the control module **4**. When it is identified that the brake pedal **1422** is in the non-braking state, the identification module **3** may provide a non-braking signal to the control module **4**.

(33) When the identification module **3** identifies only the operation state of the acceleration operation mechanism **1421** without identifying the operation state of the brake pedal **1422**, the traveling operation mechanism **142** may correspond to the traveling release state when the acceleration operation mechanism **1421** is in the acceleration release state. In this case, when the acceleration operation mechanism **1421** is in the acceleration operation state, the traveling operation mechanism **142** may correspond to the traveling operation state.

(34) When the identification module **3** identifies both the operation state of the acceleration operation mechanism **1421** and the operation state of the brake pedal **1422**, the traveling operation mechanism **142** may correspond to the traveling release state when the acceleration operation mechanism **1421** is in the acceleration release state and when the brake pedal **1422** is in the braking state. In this case, the traveling operation mechanism **142** may correspond to the traveling operation state when the brake pedal **1422** is in the non-braking state regardless of the operation state of the acceleration operation mechanism **1421**.

(35) The identification module **3** may identify whether the clutch operation mechanism **143** is in the release operation state or the fastening operation state on the basis of the operation information of the clutch operation mechanism **143**. When it is identified that the clutch operation mechanism **143** is in the release operation state, the identification module **3** may provide a release operation signal to the control module **4**. When it is identified that the clutch operation mechanism **143** is in the fastening operation state, the identification module **3** may provide a fastening operation signal to the control module **4**.

(36) Referring to FIGS 2 and 3, the control module 4 controls the transmission 150 according to the result identified by the identification module 3. The control module 4 may control the transmission 150 in one of a traveling standby mode, an idling travel mode, and a normal traveling mode. In the traveling standby mode, the agricultural work vehicle 100, the engine of which is started, is maintained in a stopped state. In the idling travel mode, the agricultural work vehicle 100 travels in a state in which the engine is in an idle state. In this case, the agricultural work vehicle 100 may travel at a preset low traveling speed in a state in which the acceleration operation mechanism 1421 is not operated. Accordingly, the driver may allow the agricultural work vehicle 100 to travel at the present low traveling speed even without operating the hand throttle 14211 and the accelerator pedal 14212. In the normal traveling mode, the agricultural work vehicle 100 travels to correspond to the operation of the acceleration operation mechanism 1421. In this case, the agricultural work vehicle 100 may travel by driving of the engine and a travel shifting stage corresponding to a degree to which the acceleration operation mechanism 1421 is operated. Accordingly, the driver may allow the agricultural work vehicle 100 to travel at a desired traveling speed by operating at least one of the hand throttle 14211 and the accelerator pedal 14212.

(37) The control module 4 may control the transmission 150 in the traveling standby mode when it is identified that the shuttle lever 141 is in the front-rear operation state, the traveling operation mechanism 142 is in the traveling release state, and the clutch operation mechanism 143 is in a state in which the agricultural work vehicle 100, the engine of which is started, is stopped in the fastening operation state. Accordingly, the transmission control device 1 of the agricultural work vehicle according to the present disclosure may control the transmission 150 so that the agricultural work vehicle 100 does not travel only by operating the shuttle lever 141 forward or rearward in a state in which the agricultural work vehicle 100, the engine of which is started, is stopped. Further, the transmission control device 1 of the agricultural work vehicle according to the present disclosure may control the transmission 150 so that the agricultural work vehicle 100 does not travel only by operating the clutch operation mechanism 143 in a state in which the agricultural work vehicle 100, the engine of which is started, is stopped in the fastening operation state. Thus, in the transmission control device 1 of the agricultural work vehicle according to the present disclosure, since the agricultural work vehicle 100 may be prevented from traveling in a situation in which travel is not intended by the driver, the driving difficulty in the agricultural work vehicle 100 can be lowered, and the occurrence of accidents can be prevented. The control module 4 may control the transmission 150 in the traveling standby mode when the front-rear operation signal, the traveling release signal, and the fastening operation signal are received from the identification module 3 in a state in which the agricultural work vehicle 100, the engine of which is started, is stopped.

(38) When controlling the transmission 150 in the traveling standby mode, the control module 4 may control the transmission 150 so that releasing of the main clutch 150a is maintained. That is, the control module 4 may maintain the releasing of the main clutch 150a even when the clutch operation mechanism 143 is in the fastening operation state in the traveling standby mode. Thus, in the traveling standby mode, the control module 4 may maintain a state in which the agricultural work vehicle 100, the engine of which is started, is stopped.

(39) For example, when the traveling clutch 1521 corresponds to the main clutch 150a, in the traveling standby mode, the control module 4 may control the transmission 150 so that the releasing of the traveling clutch 1521 is maintained. In this case, in the traveling standby mode, since the shuttle lever 141 is in the front-rear operation state, the control module 4 may control the front-rear clutch 1511 in a fastened state. Accordingly, immediately after the traveling clutch 1521 is fastened, the control module 4 may control the front-rear shifting part 151 to wait in a state in which the driving is receivable from the front-rear shifting part 151. Thus, the control module 4 may shorten a time for which the traveling standby mode is switched to the idling travel mode or the normal traveling mode.

(40) For example, when the front-rear clutch **1511** corresponds to the main clutch **150a**, in the traveling standby mode, the control module **4** may control the transmission **150** so that the releasing of the front-rear clutch **1511** is maintained. In this case, the control module **4** may control the transmission **150** so that the traveling clutch **1521** is fastened or the fastening with the traveling clutch **1521** is maintained. That is, in the traveling standby mode, the control module **4** may control the traveling clutch **1521** in a fastened state. Accordingly, immediately after the front-rear clutch **1511** is fastened, the control module **4** may control the travel shifting part **152** to wait in a state in which the travel shifting part **152** may transmit the driving. Thus, the control module **4** may shorten a time for which the traveling standby mode is switched to the idling travel mode or the normal traveling mode.

(41) When the front-rear clutch **1511** corresponds to the main clutch **150a**, the releasing of the traveling clutch **1521** when the agricultural work vehicle **100** is started may be maintained, and the traveling clutch **1521** may be fastened in the traveling standby mode. When controlling the transmission **150** in the traveling standby mode, the control module **4** may control the transmission **150** so that the releasing of the front-rear clutch **1511** is maintained and the traveling clutch **1521** is fastened.

(42) When the front-rear clutch **1511** corresponds to the main clutch **150a**, the traveling clutch **1521** may be fastened when the agricultural work vehicle **100** is started and may be maintained in a fastened state in the traveling standby mode. When controlling the transmission **150** in the traveling standby mode, the control module **4** may control the transmission **150** so that the releasing of the front-rear clutch **1511** is maintained, and the fastening of the traveling clutch **1521** is maintained.

(43) Referring to FIGS. 2 to 4, when the transmission **150** is implemented as a dual clutch transmission (DCT) and the front-rear clutch **1511** is implemented as the main clutch **150a**, the control module **4** may control the transmission **150** in the traveling standby mode by controlling the travel shifting part **152** so that one of a first traveling clutch **1521a** and a second traveling clutch **1521b** is fastened or fastening of one of the first traveling clutch **1521a** and the second traveling clutch **1521b** is maintained.

(44) The first traveling clutch **1521a** and the second traveling clutch **1521b** will be described in detail below.

(45) First, the first traveling clutch **1521a** is connected to at least one of a first leading shifting mechanism **1522a** and a trailing shifting mechanism **1523a**. When the first traveling clutch **1521a** is fastened, the driving may be transmitted from the first leading shifting mechanism **1522a** via the first traveling clutch **1521a** to the first trailing shifting mechanism **1523a**. When the first traveling clutch **1521a** is unfastened, the driving may not be transmitted from the first leading shifting mechanism **1522a** via the first traveling clutch **1521a** to the first trailing shifting mechanism **1523a**. The first leading shifting mechanism **1522a** may correspond to a main shifting part, and the first trailing shifting mechanism **1523a** may correspond to a sub-shifting part. The first leading shifting mechanism **1522a** may correspond to a sub-shifting part, and the first trailing shifting mechanism **1523a** may correspond to a main shifting part. Meanwhile, the first traveling clutch **1521a** may be connected to only at least one of the first leading shifting mechanism **1522a** and the first trailing shifting mechanism **1523a**. The first traveling clutch **1521a** may be connected to only one of the first leading shifting mechanism **1522a** and the first trailing shifting mechanism **1523a** and thus may be implemented so that the driving generated by the engine is transmitted to or is not transmitted to the axle through the first leading shifting mechanism **1522a** and the first trailing shifting mechanism **1523a**.

(46) Next, the second traveling clutch **1521b** is connected to at least one of a second leading shifting mechanism **1522b** and a second trailing shifting mechanism **1523b**. When the second traveling clutch **1521b** is fastened, the driving may be transmitted from the second leading shifting mechanism **1522b** via the second traveling clutch **1521b** to the second trailing shifting mechanism **1523b**. When the second traveling clutch **1521b** is unfastened, the driving may not be transmitted

from the second leading shifting mechanism **1522b** via the second traveling clutch **1521b** to the second trailing shifting mechanism **1523b**. The second leading shifting mechanism **1522b** may correspond to a main shifting part, and the second trailing shifting mechanism **1523b** may correspond to a sub-shifting part. The second leading shifting mechanism **1522b** may correspond to a sub-shifting part, and the second trailing shifting mechanism **1523b** may correspond to a main shifting part. Meanwhile, the second traveling clutch **1521b** may be connected to only at least one of the second leading shifting mechanism **1522b** and the second trailing shifting mechanism **1523b**. The second traveling clutch **1521b** may be connected to only one of the second leading shifting mechanism **1522b** and the second trailing shifting mechanism **1523b** and thus may be implemented so that the driving generated by the engine is transmitted to or is not transmitted to the axle through the second leading shifting mechanism **1522b** and the second trailing shifting mechanism **1523b**.

(47) When the front-rear clutch **1511** is implemented as the main clutch **150a**, in the traveling standby mode, the control module **4** may control the travel shifting part **152** so that the releasing of the front-rear clutch **1511** is maintained, any one of the first traveling clutch **1521a** and the second traveling clutch **1521b** is fastened, or the fastening of any one of the first traveling clutch **1521a** and the second traveling clutch **1521b** is maintained. Accordingly, immediately after the front-rear clutch **1511** is fastened, the control module **4** may control the travel shifting part **152** to wait in a state in which the driving may be transmitted through any one of the first traveling clutch **1521a** and the second traveling clutch **1521b**. Thus, even when the transmission **150** is implemented as the DCT, the control module **4** may shorten a time for which the traveling standby mode is switched to the idling travel mode or the normal traveling mode.

(48) When it is identified that in the traveling standby mode, the acceleration operation mechanism **1421** is in the acceleration operation state, the control module **4** may control the transmission **150** so that the main clutch **150a** is fastened. Accordingly, the transmission **150** may transmit the driving generated from the engine to the axle. Thus, the agricultural work vehicle **100** may start and travel. In the traveling standby mode, an operation of identifying whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state may be performed by the identification module **3**. In the traveling standby mode, when it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state, the identification module **3** may provide the acceleration operation signal to the control module **4**. In the traveling standby mode, when receiving the acceleration operation signal from the identification module **3**, the control module **4** may fasten the main clutch **150a**. Meanwhile, in the traveling standby mode, when it is identified that the acceleration operation mechanism **1421** is in the acceleration release state, the control module **4** may maintain the releasing of the main clutch **150a**.

(49) When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state, the control module **4** may control the transmission **150** in the normal traveling mode. In the normal traveling mode, the control module **4** may control the transmission **150** so that the agricultural work vehicle **100** travels according to the degree of operation of the acceleration operation mechanism **1421**. An operation of identifying whether the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened may be performed by the identification module **3** in the acceleration operation state or the acceleration release state. When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state, the identification module **3** may provide the acceleration operation signal to the control module **4**. When receiving the acceleration operation signal from the identification module **3** in a state in which the main clutch **150a** is fastened, the control module **4** may control the transmission **150** in the normal traveling mode. Meanwhile, in the traveling standby mode, as it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state, the main clutch **150a** is fastened. Thus, when it is identified that the acceleration operation mechanism

1421 is maintained in a state in which the main clutch **150a** is fastened in the acceleration operation state, the control module **4** may control the transmission **150** in the normal traveling mode.

(50) When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration release state, the control module **4** may control the transmission **150** in the idling travel mode. In the idling travel mode, the control module **4** may control the transmission **150** so that the agricultural work vehicle **100** travels at the preset low traveling speed in a state in which the engine is in an idle state. In this case, the control module **4** may control the transmission **150** so that both the front-rear clutch **1511** and the traveling clutch **1521** are maintained in a fastened state. When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration release state, the identification module **3** may provide the acceleration release signal to the control module **4**. When receiving the acceleration release signal from the identification module **3** in a state in which the main clutch **150a** is fastened, the control module **4** may control the transmission **150** in the idling travel mode.

(51) In this way, in the traveling standby mode, the transmission control device **1** of an agricultural work vehicle according to the present disclosure may be implemented to control the transmission **150** so that the main clutch **150a** is fastened according to the operation state of the traveling operation mechanism **142**, and to control the transmission **150** in the normal traveling mode or the idling travel mode according to the operation state of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

(52) Here, the transmission control device **1** of an agricultural work vehicle according to a modified embodiment of the present disclosure may control the transmission **150** in the traveling standby mode, the normal traveling mode, and the idling travel mode additionally in consideration of whether the brake pedal **1422** is in the braking state or the non-braking state. Detailed description thereof will be described below.

(53) First, the reception module **2** may additionally receive the operation information of the brake pedal **1422** from the operation unit **140**. Accordingly, the reception module **2** may receive, from the operation unit **140**, the operation information of the shuttle lever **141**, the operation information of the acceleration operation mechanism **1421**, the operation information of the brake pedal **1422**, and the operation information of the clutch operation mechanism **143**.

(54) Next, the identification module **3** may additionally identify whether the brake pedal **1422** is in the braking state or the non-braking state. Accordingly, the identification module **3** may identify whether the shuttle lever **141** is in the front-rear operation state or the neutral operation state, identify whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state, identify whether the brake pedal **1422** is in the braking state or the non-braking state, and identify whether the clutch operation mechanism **143** is in the release operation state or the fastening operation state.

(55) Next, in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped, when it is identified that the shuttle lever **141** is in the front-rear operation state, the traveling operation mechanism **142** is in the acceleration release state, the brake pedal **1422** is in the braking state, and the clutch operation mechanism **143** is in the fastening operation state, the control module **4** may control the transmission in the traveling standby mode as the releasing of the main clutch **150a** is maintained.

(56) Next, in the traveling standby mode, when it is identified that the brake pedal **1422** is in the non-braking state, the control module **4** may control the transmission **150** so that the main clutch **150a** is fastened. In the traveling standby mode, the fact that the brake pedal **1422** is in the non-braking state may be identified by the identification module **3**.

(57) Next, in a state in which the main clutch **150a** is fastened, the control module **4** may control the transmission **150** in the normal traveling mode or the idling travel mode according to whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration

release state. Whether the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state or the acceleration release state may be identified by the identification module **3**.

(58) When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state, the control module **4** may control the transmission **150** in the normal traveling mode.

(59) When it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration release state, the control module **4** may control the transmission **150** in the idling travel mode. Meanwhile, since the acceleration operation mechanism **1421** has been maintained in the acceleration release state from the traveling standby mode, the control module **4** may control the transmission **150** in the idling travel mode when it is identified that the acceleration operation mechanism **1421** is maintained in a state in which the main clutch **150a** is fastened in the acceleration release state.

(60) In this way, in the traveling standby mode, the transmission control device **1** of an agricultural work vehicle according to the modified embodiment of the present disclosure may be implemented to control the transmission **150** so that the main clutch **150a** is fastened according to the operation state of the brake pedal **1422**, and to control the transmission **150** in the normal traveling mode or the idling travel mode according to the operation state of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

(61) Hereinafter, embodiments of a transmission control method of an agricultural work vehicle according to the present disclosure will be described in detail with reference to the accompanying drawings.

(62) Referring to FIGS. **1** to **6** and **8**, the transmission control method of the agricultural work vehicle according to the present disclosure relates to controlling the transmission **150** of the agricultural work vehicle **100**. The transmission control method of the agricultural work vehicle according to the present disclosure may be performed by the above-described transmission control device **1** of the agricultural work vehicle according to the present disclosure. The transmission control method of the agricultural work vehicle according to the present disclosure may include the following operation.

(63) First, the operation state of the operation unit **140** is identified (**S10**). Operation **S10** may be performed by identifying the operation state of the shuttle lever **141**, the operation state of the traveling operation mechanism **142**, and the operation state of the clutch operation mechanism **143** in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped. Operation **S10** of identifying the operation state of the operation unit may be performed by the identification module **3**. The identification module **3** may identify the operation state of the operation unit **140** by using the operation information provided from the reception module **2**. Operation **S10** of identifying the operation state of the operation unit may include operation **S11** of identifying whether the shuttle lever **141** is in the front-rear operation state or the neutral operation state, operation **S12** of identifying whether the traveling operation mechanism **142** is in the traveling operation state or the traveling release state, and operation **S13** of identifying whether the clutch operation mechanism **143** is in the release operation state or the fastening operation state.

(64) Next, the transmission **150** is controlled in the traveling standby mode (**S20**). Operation **S20** may be performed by controlling the transmission **150** in the traveling standby mode according to the result obtained by identifying the operation state of the operation unit **140** in a state in which the agricultural work vehicle, the engine of which is started, is stopped. Operation **S20** of controlling the transmission **150** in the traveling standby mode may be performed by controlling the transmission **150** in the traveling standby mode when it is identified that the shuttle lever **141** is in the front-rear operation state, the traveling operation mechanism **142** is in the traveling release state, and the clutch operation mechanism **143** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the fastening operation state. When operation **S20**

of controlling the transmission in the traveling standby mode is performed, the agricultural work vehicle **100** may be maintained in a stopped state even when the shuttle lever **141** is in the front-rear operation state and the clutch operation mechanism **143** is in the fastening operation state.

(65) Accordingly, in the transmission control method of the agricultural work vehicle according to the present disclosure, the transmission **150** may be controlled so that the agricultural work vehicle **100** does not travel only due to operating the shuttle lever **141** forward or rearward in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped. Further, in the transmission control method of the agricultural work vehicle according to the present disclosure, the transmission **150** may be controlled so that the agricultural work vehicle **100** does not travel only due to operating the clutch operation mechanism **143** in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the fastening operation state. Thus, in the transmission control method of the agricultural work vehicle according to the present disclosure, since the agricultural work vehicle **100** may be prevented from traveling in a situation in which travel is not intended by the driver, the driving difficulty in the agricultural work vehicle **100** can be lowered, and the occurrence of accidents can be prevented.

(66) Operation **S20** of controlling the transmission in the traveling standby mode may be performed by the control module **4**. When receiving the front-rear operation signal, the traveling release signal, and the fastening operation signal from the identification module **3**, the control module **4** may control the transmission **150** in the traveling standby mode.

(67) Next, in the traveling standby mode, the operation state of the traveling operation mechanism **142** is identified (**S30**). In the traveling standby mode, operation **S30** may be performed by identifying whether the traveling operation mechanism **142** is in the traveling operation state or the traveling release state. In the traveling standby mode, operation **S30** of identifying the operation state of the traveling operation mechanism may be performed by the identification module **3**.

(68) Next, the transmission **150** is controlled in a traveling mode (**S40**). In the traveling standby mode, operation **S40** may be performed by controlling the transmission **150** in the traveling mode in which the agricultural work vehicle travels when it is determined that the traveling operation mechanism **142** is in the traveling operation state. Operation **S40** of controlling the transmission in the traveling mode may be performed by the control module **4**.

(69) Operation **S40** of controlling the transmission in the traveling mode may include operation **S41** of controlling the transmission in the normal traveling mode and operation **S42** of controlling the transmission in the idling travel mode.

(70) Operation **S41** of controlling the transmission in the normal traveling mode may be performed by controlling the transmission **150** in the normal traveling mode when it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state. Operation **S41** of controlling the transmission **150** in the normal traveling mode may be performed by the control module **4**. When receiving the acceleration operation signal, the control module **4** may control the transmission **150** in the normal traveling mode. When operation **S41** of controlling the transmission in the normal traveling mode is performed, the agricultural work vehicle **100** may travel according to the degree of operation of the acceleration operation mechanism **1421** after starting.

Accordingly, the driver may allow the agricultural work vehicle **100** to travel at a desired traveling speed by operating the acceleration operation mechanism **1421**.

(71) Operation **S42** of controlling the transmission in the idling travel mode may be performed by controlling the transmission **150** in the idling travel mode when it is identified that the acceleration operation mechanism **1421** is in the acceleration release state. Operation **S42** of controlling the transmission **150** in the idling travel mode may be performed by the control module **4**. When receiving the acceleration release signal, the control module **4** may control the transmission **150** in the idling travel mode. When operation **S42** of controlling the transmission in the idling travel mode is performed, the agricultural work vehicle **100** may travel at the preset low traveling speed in a state in which the acceleration operation mechanism **1421** is not operated. Accordingly, the

driver may allow the agricultural work vehicle **100** to travel at the present low traveling speed even without operating the hand throttle **14211** and the accelerator pedal **14212**.

(72) Referring to FIGS. **1** to **6** and **8**, operation **S20** of controlling the transmission in the traveling standby mode may include operation **S21** of switching the transmission in the traveling standby mode.

(73) Operation **S21** of switching the transmission **150** in the traveling standby mode may be performed by switching the transmission **150** in the traveling standby mode as the releasing of the main clutch **150a** is maintained. In this case, in operation **S21** of switching the transmission **150** in the traveling standby mode, even when it is identified that the clutch operation mechanism **143** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the fastening operation state, the releasing of the main clutch **150a** may be maintained. Operation **S21** of switching the transmission **150** in the traveling standby mode may be performed by the control module **4**. When the front-rear clutch **1511** corresponds to the main clutch **150a**, in operation **S21** of switching the transmission **150** in the traveling standby mode, the releasing of the front-rear clutch **1511** may be maintained even when the shuttle lever **141** is in the front-rear operation state and the clutch operation mechanism **143** is in the fastening operation state. When the traveling clutch **1521** corresponds to the main clutch **150a**, in operation **S21** of switching the transmission **150** in the traveling standby mode, the releasing of the traveling clutch **1521** may be maintained even when the clutch operation mechanism **143** is in the fastening operation state. In this case, in operation **S21** of switching the transmission in the traveling standby mode, as the shuttle lever **141** is in the front-rear operation state, the front-rear clutch **1511** may be fastened.

(74) When the transmission **150** is implemented as the DCM, operation **S21** of switching the transmission **150** in the traveling standby mode is performed by the transmission **150** in the traveling standby mode by fastening any one of the first traveling clutch **1521a** and the second traveling clutch **1521b** or by maintaining the fastening of any one of the first traveling clutch **1521a** and the second traveling clutch **1521b**. In this case, the front-rear clutch **1511** may correspond to the main clutch **150a**. When the front-rear clutch **1511** corresponds to the main clutch **150a**, the control module **4** may control the transmission **150** so that the releasing of the front-rear clutch **1511** is maintained, any one of the first traveling clutch **1521a** and the second traveling clutch **1521b** is fastened, or the fastening of any one of the first traveling clutch **1521a** and the second traveling clutch **1521b** is maintained.

(75) Referring to FIGS. **1** to **9**, the transmission control method of the agricultural work vehicle according to the present disclosure may roughly include a first embodiment and a second embodiment according to a method of changing a control manner of controlling the transmission **150** in the normal traveling mode and the idling travel mode. Such a first embodiment and a second embodiment will be sequentially described below in detail with reference to the accompanying drawings.

First Embodiment

(76) Referring to FIGS. **1** to **7**, a transmission control method of an agricultural work vehicle according to a first embodiment of the present disclosure will be implemented as follows.

(77) First, operation **S10** of identifying an operation state of the operation unit may be performed by identifying the operation state of the shuttle lever **141**, the operation state of the acceleration operation mechanism **1421**, and the operation state of the clutch operation mechanism **143** in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped.

(78) In operation **S10** of identifying the operation state of the operation unit, operation **S12** of identifying the operation state of the traveling operation mechanism may include operation **S121** of identifying the operation state of the acceleration operation mechanism. Operation **S121** of identifying the operation state of the acceleration operation mechanism may be performed by identifying whether the acceleration operation mechanism **1421** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the acceleration

operation state or the acceleration release state. Operation **S121** of identifying the operation state of the acceleration operation mechanism may be performed by the identification module **3**.

(79) Next, operation **S20** of controlling the transmission **150** in the traveling standby mode may be performed by controlling the transmission **150** in the traveling standby mode when it is identified that the shuttle lever **141** is in the front-rear operation state, the acceleration operation mechanism **1421** is in the acceleration release state, and the clutch operation mechanism **143** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the fastening operation state. In this case, in operation **S21** of switching the transmission **150** in the traveling standby mode, when it is identified that the shuttle lever **141** is in the front-rear operation state, the acceleration operation mechanism **1421** is in the acceleration release state, and the clutch operation mechanism **143** is in the fastening operation state, the releasing of the main clutch **150a** is maintained, and thus the transmission **150** may be switched to the traveling standby mode.

(80) Next, operation **S30** of identifying the operation state of the traveling operation mechanism in the traveling standby mode may include operation **S31** of identifying the operation state of the acceleration operation mechanism in the traveling standby mode. In the traveling standby mode, operation **S31** of identifying the operation state of the acceleration operation mechanism may be performed by identifying whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state. In the traveling standby mode, operation **S31** of identifying the operation state of the acceleration operation mechanism may be performed by the identification module **3**.

(81) Next, operation **S40** of controlling the transmission **150** in the traveling mode may include operation **S43** of fastening the main clutch, operation **S41** of controlling the transmission **150** in the normal traveling mode, and operation **s42** of controlling the transmission **150** in the idling travel mode.

(82) In the traveling standby mode, when it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state (**S31**), operation **S43** of fastening the main clutch may be performed by fastening the main clutch **150a**. Operation **S43** of fastening the main clutch may be performed by the control module **4**. In the traveling standby mode, when receiving the acceleration operation signal from the identification module **3**, the control module **4** may control the transmission **150** so that the main clutch **150a** is fastened. When the main clutch is fastened, the agricultural work vehicle **100** may travel at a traveling speed corresponding to the degree of operation of the acceleration operation mechanism **1421**.

(83) Operation **S43** of fastening the main clutch may be performed before operation **S41** of controlling the transmission in the normal traveling mode and operation **S42** of controlling the transmission in the idling travel mode are performed. Operation **S43** of fastening the main clutch may be performed after operation **S31** of identifying the operation state of the acceleration operation mechanism is performed in the traveling standby mode.

(84) Next, operation **S40** of controlling the transmission in the traveling mode may include operation **S44** of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened.

(85) Operation **S44** of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed by identifying whether the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state or the acceleration release state. Operation **S44** of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed by the identification module **3**. The identification module **3** may identify whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state on the basis of the operation information of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

(86) Operation **S44** of identifying the operation state of the acceleration operation mechanism in a

state in which the main clutch is fastened may be performed before operation **S41** of controlling the transmission in the normal traveling mode and operation **S42** of controlling the transmission in the idling travel mode are performed. Operation **S44** of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed after operation **S43** of fastening the main clutch is performed.

(87) In the transmission control method of an agricultural work vehicle according to the first embodiment of the present disclosure, operation **S41** of controlling the transmission in the normal traveling mode and operation **S42** of controlling the transmission in the idling travel mode may be implemented as follows.

(88) Operation **S41** of controlling the transmission in the normal traveling mode may be performed by controlling the transmission **150** in the normal traveling mode when it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state. In the traveling standby mode, as it is identified that the acceleration operation mechanism **1421** is in the acceleration operation state, the main clutch **150a** may be in a fastened state. In this case, operation **S41** of controlling the transmission in the normal traveling mode may be performed by controlling the transmission in the normal traveling mode when it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state.

(89) Operation **S42** of controlling the transmission in the idling travel mode may be performed by controlling the transmission **150** in the idling travel mode when it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration release state.

(90) In this way, in the traveling standby mode, the transmission control method of an agricultural work vehicle according to the first embodiment of the present disclosure may be implemented to control the transmission **150** so that the main clutch **150a** is fastened according to the operation state of the acceleration operation mechanism **1421** and to control the transmission **150** in the normal traveling mode or the idling travel mode according to the operation state of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

Second Embodiment

(91) Referring to FIGS. **1** to **5**, **8**, and **9**, a transmission control method of an agricultural work vehicle according to a second embodiment of the present disclosure will be implemented as follows.

(92) First, operation **S10** of identifying an operation state of the operation unit **140** may be performed by identifying the operation state of the shuttle lever **141**, the operation state of the acceleration operation mechanism **1421**, the operation state of the brake pedal **1422**, and the operation state of the clutch operation mechanism **143** in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped.

(93) In operation **S10** of identifying the operation state of the operation unit, operation **S12** of identifying the operation state of the traveling operation mechanism may include operation **S121** of identifying the operation state of the acceleration operation mechanism, and operation **S122** of identifying the operation state of the brake pedal. Operation **S121** of identifying the operation state of the acceleration operation mechanism **1421** may be performed by identifying whether the acceleration operation mechanism **1421** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the acceleration operation state or the acceleration release state. Operation **S122** of identifying the operation state of the brake pedal **1422** may be performed by identifying whether the brake pedal **1422** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the braking state or the non-braking state. Operation **S121** of identifying the operation state of the acceleration operation mechanism and operation **S122** of identifying the operation state of the brake pedal may be performed by the identification module **3**.

(94) Next, operation S20 of controlling the transmission **150** in the traveling standby mode may be performed by controlling the transmission **150** in the traveling standby mode when it is identified that the shuttle lever **141** is in the front-rear operation state, the acceleration operation mechanism **1421** is in the acceleration release state, the brake pedal **1422** is in the braking state, and the clutch operation mechanism **143** is in a state in which the agricultural work vehicle **100**, the engine of which is started, is stopped in the fastening operation state. In this case, in operation S21 of switching the transmission **150** in the traveling standby mode, when it is identified that the shuttle lever **141** is in the front-rear operation state, the acceleration operation mechanism **1421** is in the acceleration release state, the brake pedal **1422** is in the braking state, and the clutch operation mechanism **143** is in the fastening operation state, the releasing of the main clutch **150a** is maintained, and thus the transmission **150** may be switched to the traveling standby mode.

(95) Next, operation S30 of identifying the operation state of the traveling operation mechanism in the traveling standby mode may include operation S32 of identifying the operation state of the brake pedal in the traveling standby mode. Operation S32 of identifying the operation state of the brake pedal in the traveling standby mode may be performed by identifying whether the brake pedal **1422** is in the braking state or the non-braking state in the traveling standby mode. In the traveling standby mode, operation S32 of identifying the operation state of the brake pedal may be performed by the identification module **3**.

(96) Next, operation S40 of controlling the transmission in the traveling mode may include operation S43 of fastening the main clutch, operation S41 of controlling the transmission in the normal traveling mode, and operation s42 of controlling the transmission in the idling travel mode.

(97) In the traveling standby mode, when it is identified that the brake pedal **1422** is in the non-braking state (S32), operation S43 of fastening the main clutch may be performed by fastening the main clutch **150a**. Operation S43 of fastening the main clutch may be performed by the control module **4**. In the traveling standby mode, when receiving the non-braking signal from the identification module **3**, the control module **4** may control the transmission **150** so that the main clutch **150a** is fastened. When the main clutch is fastened, the agricultural work vehicle **100** may start traveling at the preset low traveling speed.

(98) Operation S43 of fastening the main clutch may be performed before operation S41 of controlling the transmission in the normal traveling mode and operation S42 of controlling the transmission in the idling travel mode are performed. Operation S43 of fastening the main clutch may be performed after operation S31 of identifying the operation state of the acceleration operation mechanism is performed in the traveling standby mode.

(99) Next, operation S40 of controlling the transmission in the traveling mode may include operation S44 of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened.

(100) Operation S44 of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed by identifying whether the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state or the acceleration release state. Operation S44 of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed by the identification module **3**. The identification module **3** may identify whether the acceleration operation mechanism **1421** is in the acceleration operation state or the acceleration release state on the basis of the operation information of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

(101) Operation S44 of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed before operation S41 of controlling the transmission in the normal traveling mode and operation S42 of controlling the transmission in the idling travel mode are performed. Operation S44 of identifying the operation state of the acceleration operation mechanism in a state in which the main clutch is fastened may be performed

after operation **S43** of fastening the main clutch is performed.

(102) In the transmission control method of an agricultural work vehicle according to a second embodiment of the present disclosure, operation **S41** of controlling the transmission in the normal traveling mode and operation **S42** of controlling the transmission in the idling travel mode may be implemented as follows.

(103) Operation **S41** of controlling the transmission in the normal traveling mode may be performed by controlling the transmission **150** in the normal traveling mode when it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration operation state.

(104) Operation **S42** of controlling the transmission in the idling travel mode may be performed by controlling the transmission **150** in the idling travel mode when it is identified that the acceleration operation mechanism **1421** is in a state in which the main clutch **150a** is fastened in the acceleration release state. Meanwhile, since the acceleration operation mechanism **1421** has been maintained in the acceleration release state from the traveling standby mode, operation **S42** of controlling the transmission in the idling travel mode may be performed by controlling the transmission **150** in the idling travel mode when it is identified that the acceleration operation mechanism **1421** is maintained in a state in which the main clutch **150a** is fastened in the acceleration release state.

(105) In this way, in the traveling standby mode, the transmission control method of an agricultural work vehicle according to the first embodiment of the present disclosure may be implemented to control the transmission **150** so that the main clutch **150a** is fastened according to the operation state of the brake pedal **1422**, and to control the transmission **150** in the normal traveling mode or the idling travel mode according to the operation state of the acceleration operation mechanism **1421** in a state in which the main clutch **150a** is fastened.

(106) The present disclosure described above is not limited to the above-described embodiments and the accompanying drawings, and it is apparent to those skilled in the art to which the present disclosure belongs that various substitutes, modifications, and changes can be made without departing from the technical spirit of the present disclosure.

Claims

1. A method of controlling a transmission in an agricultural work vehicle including a front-rear clutch of a front-rear shifting part that performs front-rear shifting with respect to driving generated by an engine and a traveling clutch of a travel shifting part that performs travel shifting with respect to the driving generated by the engine, the agricultural work vehicle having an operation unit including: a shuttle lever that is positionable by a human operator to be in one of a front-rear operation state or a neutral operation state, a traveling operation mechanism that is positionable by the human operator to be in one of a traveling operation state or a traveling release state, and a clutch operation mechanism that is positionable by the human operator to be in one of a release operation state or a fastening operation state, the method comprising: while the engine is running and the vehicle is not moving: identifying whether the shuttle lever is in the front-rear operation state in which the transmission is configured to apply the driving generated by the engine to move the agricultural work vehicle forward or rearward or in the neutral operation state in which the transmission is configured to not apply the driving generated by the engine to move the agricultural work vehicle, identifying whether the traveling operation mechanism is in the traveling operation state or in the traveling release state in which the agricultural work vehicle does not travel, and identifying whether the clutch operation mechanism is in: the release operation state in which a main clutch is to be placed in a released state for not transmitting the driving; or in the fastening operation state in which the main clutch is to be placed in a fastened, state for transmitting the driving, wherein the main clutch is a given one of the front-rear clutch and the traveling clutch; in

response to identifying that the shuttle lever is in the front-rear operation state, the traveling operation mechanism is in the traveling release state, and the clutch operation mechanism is in the fastening operation state: switching the transmission to a traveling standby mode in which the main clutch is maintained in the released state despite the shuttle lever being in the front-rear operation state and the clutch operation mechanism being in the fastening operation state, wherein a different one of the front-rear clutch and the traveling clutch than the given one is in the fastened state in the traveling standby mode.

2. The method of claim 1, further comprising: identifying an operation state of the traveling operation mechanism in the traveling standby mode; and controlling the transmission in a traveling mode in which the agricultural work vehicle travels when identified in the traveling standby mode that the traveling operation mechanism is in the traveling operation state in which the agricultural work vehicle travels.

3. The method of claim 2, wherein the traveling operation mechanism comprises an acceleration operation mechanism, and identifying the operation state of the traveling operation mechanism in the traveling standby mode includes identifying whether the acceleration operation mechanism is in an acceleration operation state or an acceleration release state; and wherein controlling the transmission in the traveling mode includes fastening the main clutch in response to identifying that the acceleration operation mechanism is in the acceleration operation state.

4. The method of claim 3, wherein controlling the transmission in the traveling mode comprises: controlling the transmission in a normal traveling mode in which the agricultural work vehicle travels according to a degree of operation of an acceleration operation mechanism when it is identified in the traveling standby mode that the acceleration operation mechanism of the traveling operation mechanism is in the acceleration operation state in which the agricultural work vehicle is accelerated and controlling the transmission in an idling travel mode in which the agricultural work vehicle travels in a state in which the engine is in an idle state when it is identified in the traveling standby mode that the acceleration operation mechanism is in the acceleration release state in which the agricultural work vehicle is not accelerated.

5. The method of claim 2, wherein the traveling operation mechanism comprises a brake pedal, and identifying the operation state of the traveling operation mechanism in the traveling standby mode includes identifying whether the brake pedal is in a braking state or a non-braking state; and wherein controlling the transmission in the traveling mode includes fastening the main clutch in response to identifying that the brake pedal is in the non-braking state.

6. The method of claim 1, wherein the traveling operation mechanism comprises an acceleration operation mechanism, and identifying whether the traveling operation mechanism is in the traveling operation state or the traveling release state includes identifying whether the acceleration operation mechanism is in an acceleration operation state or an acceleration release state, and wherein switching the transmission to the traveling standby mode is in response to identifying that the shuttle lever is in the front-rear operation state, the acceleration operation mechanism is in the acceleration release state, and the clutch operation mechanism is in the fastening operation state.

7. The method of claim 1, wherein the traveling operation mechanism comprises an acceleration operation mechanism and a brake pedal, and identifying whether the traveling operation mechanism is in the traveling operation state or the traveling release state includes identifying whether the acceleration operation mechanism is in an acceleration operation state or an acceleration release state and identifying whether the brake pedal is in a braking state or a non-braking state; and wherein switching the transmission to the traveling standby mode is in response to determining that the shuttle lever is in the front-rear operation state, the acceleration operation mechanism is in the acceleration release state, the brake pedal is in the braking state, and the clutch operation mechanism is in the fastening operation state.

8. The method of claim 1, wherein switching the transmission to the traveling standby mode includes: fastening or maintaining in the fastened state in any one of a first traveling clutch and a

second traveling clutch, wherein the first traveling clutch is connected to at least one of a first leading shifting mechanism and a first trailing shifting mechanism of the travel shifting part, wherein the second traveling clutch is connected to at least one of a second leading shifting mechanism and a second trailing shifting mechanism of the travel shifting part, and wherein switching the transmission to the traveling standby mode maintains the front-rear clutch in the released state when the front-rear clutch is the main clutch.

9. A device for controlling a transmission in an agricultural work vehicle including a front-rear clutch of a front-rear shifting part that performs front-rear shifting with respect to driving generated by an engine and a traveling clutch of a travel shifting part that performs travel shifting with respect to the driving generated by the engine, the device comprising: an operation unit including: a shuttle lever for front-rear shifting control, positionable by a human operator to be in a front-rear operation state or a neutral operation state, a traveling operation mechanism for traveling control, positionable by the human operator to be in a traveling operation state or a traveling release state, and a clutch operation mechanism for release control of a main clutch, wherein the clutch operation mechanism is positionable by the human operator to be in a release operation state or a fastening operation state, wherein the main clutch is any one of the front-rear clutch and the traveling clutch; wherein the vehicle is configured, when the engine is running and based on respective states of the shuttle lever, the traveling operation mechanism, and the clutch operation mechanism to operate in one of: a traveling standby mode in which the agricultural work vehicle is maintained in a stopped state, a normal traveling mode in which the agricultural work vehicle travels to correspond to operation of the traveling operation mechanism, and an idling travel mode in which the agricultural work vehicle travels in a state in which the engine is in an idle state, wherein, the transmission is switched to the traveling standby mode when the shuttle lever is in the front-rear operation state, the traveling operation mechanism is in the traveling release state, and the clutch operation mechanism is in the fastening operation state while the engine is running and the vehicle is not moving, and in the traveling standby mode, a remaining clutch other than the main clutch among the front-rear clutch and the traveling clutch is switched to or maintained in a fastened state for transmitting the driving and the main clutch is in a released state for not transmitting the driving despite the shuttle lever being in the front-rear operation state and the clutch operation mechanism being in the fastening operation state.

10. The device of claim 9, wherein the traveling operation mechanism includes an acceleration operation mechanism of one of an accelerator pedal or a hand throttle that is configured to be positionable by the human operator via a foot or a hand, respectively, to be in an acceleration operation state or an acceleration release state, wherein the transmission is configured to switch to the traveling standby mode while the engine is running and the vehicle is not moving in response to: (1) the shuttle lever being in the front-rear operation state; (2) the acceleration operation mechanism being in the acceleration release state; and (3) the clutch operation mechanism being in the fastening operation state.

11. The device of claim 10, wherein in response to identifying in the traveling standby mode that the acceleration operation mechanism is positioned in the acceleration operation state: the transmission fastens the main clutch.

12. The device of claim 9, wherein the traveling operation mechanism comprises an acceleration operation mechanism of one of an accelerator pedal or a hand throttle that is configured to be positionable by the human operator via a foot or a hand, respectively, to be in an acceleration operation state or an acceleration release state, and brake pedal, positionable by the human operator to be in one of a braking state or a non-braking state for the agricultural work vehicle; and the brake pedal being in the braking state or the non-braking state affects whether the traveling operation mechanism is in the traveling release state or the traveling operation state, respectively, wherein, while the engine is running and the vehicle is not moving, the transmission is switched to the traveling standby mode in response to: (1) the shuttle lever is in the front-rear operation state,

(2) the acceleration operation mechanism is in the acceleration release state, (3) the brake pedal is in the braking state, and (4) the clutch operation mechanism is in the fastening operation state.

13. The device of claim 12, wherein the brake pedal being in the braking state or the non-braking state affects whether the traveling operation mechanism is in the traveling release state or the traveling operation state, respectively, and wherein the transmission fastens the main clutch in response to identifying in the traveling standby mode that the brake pedal is positioned to the non-braking state.

14. The device of claim 9, wherein when switching the transmission to the traveling standby mode, the transmission is configured to fasten or maintain in the fastened state any one of a first traveling clutch and a second traveling clutch, wherein the first traveling clutch is connected to at least one of a first leading shifting mechanism and a first trailing shifting mechanism of the travel shifting part, wherein the second traveling clutch is connected to at least one of a second leading shifting mechanism and a second trailing shifting mechanism of the travel shifting part, and wherein switching the transmission to the traveling standby mode maintains the front-rear clutch in the released state when the front-rear clutch is the main clutch.
