

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416884
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Imaizumi; Toru

Fixing device and image forming apparatus

Abstract

A fixing device includes a fixing film, a heater for heating the fixing film, a heater holder including a heater holding portion holding the heater, and a pressing roller forming a nip between itself and the fixing film to be heated by the heater. In the nip, a toner image carried on a recording material is fixed. The heater holder includes an opposing surface which is provided on a side upstream of the heater holding portion with respect to a recording material feeding direction and which opposes the pressing roller, a lubricant holding portion provided on the opposing surface, for supplying a lubricant to between the fixing film and the heater, and a projected portion provided on the side upstream of the heater holding portion with respect to the recording material feeding direction and projecting toward the pressing roller from the opposing surface.

Inventors:	Imaizumi; Toru (Kanagawa, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008821950
Assignee:	Canon Kabushiki Kaisha (Tokyo, JP)
Appl. No.:	18/186675
Filed:	March 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230229099 A1	Jul. 20, 2023

Foreign Application Priority Data

JP	2019-211823	Nov. 22, 2019
----	-------------	---------------

Related U.S. Application Data

division parent-doc US 17850897 20220627 US 11635713 child-doc US 18186675
division parent-doc US 17458140 20210826 US 11402774 20220802 child-doc US 17850897
division parent-doc US 16953958 20201120 US 11131949 20210928 child-doc US 17458140

Publication Classification

Int. Cl.: G03G15/20 (20060101)

U.S. Cl.:

CPC G03G15/2025 (20130101);

Field of Classification Search

CPC: G03G (15/2017); G03G (15/2025); G03G (15/2028); G03G (15/2053); G03G (15/206)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6456819	12/2001	Abe et al.	N/A	G03G 15/20
8331819	12/2011	Fukuzawa et al.	399/69	N/A
8744296	12/2013	Fukuzawa et al.	399/69	N/A
9229388	12/2015	Imaizumi et al.	N/A	G03G 15/2017
9235172	12/2015	Imaizumi et al.	N/A	G03G 15/2025
9417576	12/2015	Minamishima et al.	N/A	G03G 15/206
9507303	12/2015	Imaizumi et al.	N/A	G03G 15/2057
9513586	12/2015	Narahara et al.	N/A	G03G 15/2053
9829839	12/2016	Ando et al.	N/A	G03G 15/55
9915897	12/2017	Narahara et al.	N/A	G03G 15/2053
9983522	12/2017	Imaizumi et al.	N/A	G03G 15/2053
10078297	12/2017	Imaizumi et al.	N/A	G03G 15/2017
10216130	12/2018	Imaizumi et al.	N/A	G03G 15/2057
10268145	12/2018	Ando et al.	N/A	G03G 15/55
10310424	12/2018	An et al.	N/A	G03G 15/2057
10503105	12/2018	Imaizumi et al.	N/A	G03G 15/2057
10558153	12/2019	Wakatsu et al.	N/A	G03G 15/2053
10635032	12/2019	Imaizumi et al.	N/A	G03G 15/2039
11131949	12/2020	Imaizumi	N/A	G03G 15/20
11402774	12/2021	Imaizumi	N/A	G03G 15/20
11635713	12/2022	Imaizumi	399/325	G03G 15/2025
2003/0007813	12/2002	Yasui et al.	399/324	N/A
2004/0151522	12/2003	Kato et al.	399/328	N/A
2008/0187372	12/2007	Kato	399/328	N/A
2015/0198919	12/2014	Lee et al.	399/329	N/A
2017/0010572	12/2016	Amano	N/A	G03G 15/2064
2017/0131664	12/2016	Utsunomiya et al.	N/A	G03G 15/2053

2017/0219969	12/2016	Umeda et al.	N/A	G03G 15/20
2018/0011434	12/2017	Adachi	N/A	G03G 2215/2035
2018/0032009	12/2017	Ogura	N/A	G03G 15/2028
2018/0356757	12/2017	Kobayashi et al.	N/A	G03G 15/20
2019/0155202	12/2018	Imaizumi et al.	N/A	G03G 15/6573
2019/0179243	12/2018	Hara et al.	N/A	G03G 15/00
2019/0204765	12/2018	Morimoto	N/A	G03G 15/2064
2019/0346795	12/2018	Morimoto	N/A	G03G 15/20
2019/0346796	12/2018	Imaizumi	N/A	G03G 15/5004
2020/0278628	12/2019	Kawaguchi et al.	N/A	G03G 15/2064
2020/0379386	12/2019	Watatani et al.	N/A	G03G 15/2025
2020/0387094	12/2019	Yamaguchi et al.	N/A	G03G 15/2025

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H09-101695	12/1996	JP	N/A
2001-042670	12/2000	JP	N/A
2004-184814	12/2003	JP	N/A
2007-057851	12/2006	JP	N/A
2008-076589	12/2007	JP	N/A
2008-146964	12/2007	JP	N/A
2017-138369	12/2016	JP	N/A
2018-205669	12/2017	JP	N/A
2019-101373	12/2018	JP	N/A

OTHER PUBLICATIONS

Office Action dated Sep. 26, 2023 in counterpart Japanese Application No. 2020-026484, together with English translation thereof. cited by applicant

Office Action dated Feb. 4, 2025 in counterpart Japanese Application No. 2024-009306, together with English translation thereof. cited by applicant

Primary Examiner: Therrien; Carla J

Attorney, Agent or Firm: Venable LLP

Background/Summary

(1) This application is a divisional of application Ser. No. 17/850,897 filed Jun. 27, 2022, which was a division of application Ser. No. 17/458,140 filed Aug. 26, 2021, now issued as U.S. Pat. No. 11,402,774 on Aug. 2, 2022, which was a divisional of application Ser. No. 16/953,958 filed Nov. 20, 2020, now issued as U.S. Pat. No. 11,131,949 on Sep. 28, 2021; and claims priority under 35 U.S.C. § 119 to Japan Application JP 2019-211823 filed in Japan on Nov. 22, 2019; and the contents of all of which are incorporated herein by reference as if set forth in full.

FIELD OF THE INVENTION AND RELATED ART

(1) The present invention relates to a fixing device and an image forming apparatus, and particularly relates to the fixing device for use with an electrophotographic image forming apparatus such as a copying machine or a laser printer.

(2) As the fixing device used in the electrophotographic image forming apparatus, conventionally, a fixing device of a film heating type has been known. The fixing device of the film heating type includes a heater including a ceramic substrate and a heat generating resistor formed on the ceramic substrate, a fixing film rotating while being heated in contact with the heater, a pressing roller forming a nip in cooperation with the heater through the fixing film, and the like. A recording material on which an unfixed toner image is carried is heated in the nip while being nipped and fed, whereby the unfixed toner image on the recording material is fixed on the recording material.

(3) In the fixing device of the film heating type, a lubricant is interposed between the heater and an inner surface of the fixing film, so that a sliding friction resistance is decreased. This lubricant is applied onto, for example, the heater in an initial stage of assembling, and is interposed between the heater and the inner surface of the fixing film. Then, the pressing roller is pressed against the fixing film toward the heater, and the fixing film is rotationally driven, so that the lubricant moves around entirety of an inner surface of the fixing film. However, when the fixing film is further continuously driven rotationally, an excessive lubricant leaks out of an end portion of the fixing film and moves around another surface of the fixing film, so that the lubricant enters the nip in some cases. When such a state is formed, there is a liability that the lubricant adheres to the recording material and thus a problem such as an image defect is caused to arise.

(4) For example, a constitution in which grooves for storing the lubricant are provided on a side downstream, with respect to a recording material feeding direction, of a heater of a heater supporting member for supporting the heater and in positions corresponding to opposite end portions of the heater supporting member with respect to a longitudinal direction perpendicular to the recording material feeding direction or in an entire region including the opposite end portions of the heater supporting member with respect to the longitudinal direction has been proposed (Japanese Laid-Open Patent Application (JP-A) 2008-076589).

(5) However, in the constitution disclosed in JP-A 2008-076589, when the fixing film rotates, the fixing film steadily contacts and slides on the groove portions at portions of the grooves close to the fixing film. As the lubricant applied to the heater, grease comprising base oil and a thickener which constitute a main component is used in many instances, but particularly at a high temperature, the base oil is liable to separate from the thickener. In such a case, the base oil detected from the grease stored in the grooves at the portions close to the fixing film successively leaks out of a minute gap between the inner surface of the fixing film and the heater supporting portion by a capillary phenomenon. In the case where the base oil is supplied to between the fixing film and the heater, the base oil is pressed in the nip, and thus is extended in the longitudinal direction. Further, by the capacity phenomenon, the base oil is moved from the minute gap between the inner surface of the fixing film and the heater in an end portion direction of the fixing film with respect to the longitudinal direction, so that a risk such that the base oil, i.e., the lubricant leaks out of the fixing film increases.

SUMMARY OF THE INVENTION

(6) The present invention has been accomplished in view of the above-described circumstances. A principal object of the present invention is to provide a fixing device and an image forming apparatus which are capable of reducing a degree of leakage of a lubricant from an end portion of a fixing film with an inexpensive and simple structure while ensuring a sliding property of the fixing film.

(7) According to an aspect of the present invention, there is provided a fixing device comprising: a fixing film; a heater configured to heat the fixing film; a heater holder including a heater holding portion holding the heater; and a pressing roller forming a nip, between itself and the fixing film to be heated by the heater, in which a toner image carried on a recording material is fixed, wherein the heater holder comprises: an opposing surface which is provided on a side upstream of the heater holding portion with respect to a recording material feeding direction and which opposes the pressing roller; a lubricant holding portion provided on the opposing surface and configured to

supply a lubricant to between the fixing film and the heater; and a projected portion provided on the side upstream of the heater holding portion with respect to the recording material feeding direction and projecting toward the pressing roller from the opposing surface.

(8) According to another aspect of the present invention, there is provided an image forming apparatus comprising: a photosensitive member on which an electrostatic latent image is formed; developing means configured to develop the electrostatic latent image with toner to form a toner image; transfer means configured to transfer the toner image onto a recording material; the above-described fixing device.

(9) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic sectional view of an image forming apparatus of an embodiment 1.

(2) FIG. 2 is a schematic sectional view of a fixing device of the embodiment 1.

(3) Parts (a) and (b) of FIG. 3 are schematic views showing a lubricant holding portion of the fixing device and a peripheral portion thereof in the embodiment 1.

(4) Parts (a) and (b) of FIG. 4 are schematic views for illustrating action on grease in the embodiment 1.

(5) FIG. 5 is a schematic view for illustrating action on grease in a comparison example for being compared with the embodiment 1.

(6) Parts (a) and (b) of FIG. 6 are schematic views each showing a modified example of a recessed portion in the embodiment 1.

(7) Part (a) of FIG. 7 is a schematic view for illustrating a lubricant holding portion in an embodiment 2, and parts (b) and (c) of FIG. 7 are schematic views each for illustrating action on grease in the embodiment 2.

(8) Parts (a) and (b) of FIG. 8 are schematic views for illustrating a lubricant holding portion and action on grease, respectively, in an embodiment 3.

(9) FIG. 9 is a schematic view for illustrating a lubricant holding portion in an embodiment 4.

DESCRIPTION OF THE EMBODIMENTS

(10) In the following, embodiments for carrying out the present invention will be specifically described with reference to the drawings.

Embodiment 1

(11) An embodiment 1 will be described below. First, a structure of a main assembly of an image forming apparatus **50** of the embodiment 1, and then, a fixing device according to the present invention will be described in detail.

Image Forming Apparatus

(12) When a recording material P is fed by a sheet feeding roller **4**, the recording material P is fed to a transfer nip Ntr by a feeding roller **6**. To a transfer roller **10**, a transfer voltage of a positive polarity opposite to a charge polarity of toner is applied from a voltage source (not shown), so that a toner image on a photosensitive drum **1** is transferred onto the recording material P in the transfer nip Nst. From the surface of the photosensitive drum **1** after transfer, the toner remaining on the surface of the photosensitive drum **1** is removed by a photosensitive drum cleaner **16** provided with an elastic blade. The recording material P carrying thereon the toner image is fed to a fixing device **100**, in which the toner image is heated and fixed on the surface of the recording material P.

Incidentally, the image forming apparatus to which the fixing device **100** is applied is not limited to the image forming apparatus **50** shown in FIG. 1. For example, a color image forming apparatus may also be used.

Fixing Device

(13) The fixing device **100** of the embodiment 1 will be described below. The fixing device **100** of the embodiment 1 is a fixing device of a film heating type for the purposes of reducing a rise time and electric power consumption. FIG. 2 is a sectional view of the fixing device **100** of the embodiment 1. Incidentally, in the following description, a feeding direction of the recording material P, a longitudinal direction of a heater holder **130** described later, and a perpendicular direction perpendicular to a sliding surface described later, which are perpendicular to each other are referred to as A, B and C, respectively.

(14) A heater **113** is held by a heater holder **130** and is provided with a fixing film **112**, which is a cylindrical belt, at a periphery thereof. The heater holder **130** includes a heater holding portion **135** holding a heater **113**. The heater **113** slides on an inner surface of the fixing film **112** and heats the fixing film **112** from an inside of the fixing film **112**. A pressing roller **110** presses the fixing film **112** toward the heater **113** from an outside of the fixing film **112**. A region in which the pressing roller **110** and the fixing film **112** contact each other by the pressing of the pressing roller **110** is a fixing nip N. When the pressing roller **110** is driven in an arrow R1 direction in FIG. 2, the fixing film **112** receives power from the pressing roller **110** in the fixing nip N, and is rotated in an arrow R2 direction in FIG. 2 by the pressing roller **110**. When the recording material P on which the toner image is transferred is fed in the feeding direction A of the recording material P indicated by an arrow in the figure and then reaches the fixing nip N, the toner image T is fixed on the recording material P.

(15) The fixing film **112** in the embodiment 1 has an outer diameter of 18 mm in a cylindrical state in which the fixing film **112** is not deformed and has a multi-layer structure with respect to a thickness direction. The multi-layer structure of the fixing film **112** includes a base layer for holding strength of the film and a parting layer for reducing a degree of deposition of a contaminant on the surface of the film. The base layer needs a heat-resistant property for receiving heat of the heater **113** and also needs strength for sliding on the heater **113**. For this reason, as a material of the base layer, metal such as stainless steel or nickel or a heat-resistant resin such as polyimide may preferably be used. In the embodiment 1, as the material of the base layer of the fixing film **112**, a polyimide resin material is used, and for improving thermal conductivity and strength, a carbon-based filler was added. As regards a thickness of the base layer, the heat of the heater **113** is move easily conducted to the surface of the pressing roller **110** with a thinner (smaller) thickness, but when the thickness of the base layer is excessively thin, the strength lowers, and therefore, the thickness may preferably be about 15 μm to 100 μm , and in the embodiment 1, the thickness was 60 μm .

(16) As a material of the parting layer of the fixing film **112**, fluorine-containing resin material such as perfluoro-alkoxy (PFA) resin, polytetrafluoroethylene (PTFE) resin or tetrafluoroethylene-hexafluoropropylene (FEP) resin may preferably be used. In the embodiment 1, the PFA which is excellent in parting property and heat-resistant property in the fluorine-containing resin was used. The parting layer may be pressed by coating the base layer with a tube but may also be prepared by coating a surface of the base layer with point. In the embodiment 1, the parting layer was molded by the paint coating excellent in thin layer molding property. As regards a thickness of the parting layer, the heat of the heater **113** is move easily conducted to the surface of the fixing film **112** with a thinner (smaller) thickness, but when the thickness of the base layer is excessively thin, durability lowers, and therefore, the thickness may preferably be about 5 μm to 30 μm , and in the embodiment 1, the thickness was 10 μm . Further, an elastic layer is not used in the embodiment 1, but may also be provided between the base layer and the parting layer. In that case, as a material of the elastic layer, a silicone rubber or a fluorine-containing rubber is used.

(17) On an inner peripheral surface side of the fixing film **112**, the heater holder **130** is provided. The heater holder **130** is formed of a liquid crystal polymer resin material high in heat-resistant property in order to satisfy the heat-resistant property and rigidity. Incidentally, in the embodiment

1, as the liquid crystal polymer resin material, "SUMIKASUPER" (registered trademark) manufactured by Sumitomo Chemical Company is used. Further, the heater holder **130** includes a recess-shaped portion (heater holding portion **135**) in cross-section where the heater **113** is held. The fixing film **112** is loosely fitted around the heater holder **130**, whereby the heater holder **130** also performs a function of guiding a rotation of the fixing film **112**. The heater holder **130** relates to a feature of the embodiment 1, and therefore will be described later in detail.

(18) A pressing stay **119** is provided along the longitudinal direction B of the heater holder **130**. The pressing stay **119** is constituted by subjecting a metal plate high in rigidity, such as stainless steel to bending in order to uniformly press the heater holder **130** with respect to the longitudinal direction B. The pressing roller **110** in this embodiment is 20 mm in outer diameter and includes an iron core (metal) **117** of 13 mm in outer diameter and a 3.5 mm-thick elastic layer **116**. As a material of the elastic layer, a solid rubber or a foam rubber is used. The foam rubber is low in thermal capacity and thermal conductivity and thus heat of the surface of the pressing roller **110** is not readily absorbed therein, and therefore a surface temperature easily increases, so that there is an advantage such that a rise time of the fixing device can be shortened. In the embodiment 1, a foam rubber obtained by foaming a silicone rubber was used.

(19) A small outer diameter of the pressing roller **110** is effective in suppressing the thermal capacity, but when the outer diameter is excessively small, a width of the fixing nip N becomes narrow, so that a proper diameter is needed. Therefore, in the embodiment 1, the outer diameter of the pressing roller **110** was 20 mm. Also as regards the thickness of the elastic layer **116**, a proper thickness is needed since heat is dissipated into the core metal. Therefore, in the embodiment 1, the thickness of the elastic layer **116** was 3.5 mm. On the elastic layer, as a toner parting layer, a parting layer **118** made of the PFA resin material is formed. The parting layer **118** may be prepared by coating the elastic layer **116** with a tube or by coating the surface of the elastic layer **116** with paint similarly as in the case of the parting layer of the fixing film **112**, but in the embodiment 1, the tube excellent in durability was used. As the material of the parting layer **118** other than the PFA, the fluorine-containing resin material such as the PTFE or the FEP or a rubber material such as the fluorine-containing rubber or the silicone rubber may also be used. As regards surface hardness of the pressing roller **110**, with lower surface hardness, the width of the fixing nip N can be obtained at lower pressure. In the embodiment 1, the pressing roller **110** of 50° in Asker-C hardness (load: 4.9 N) was used. The pressing roller **110** is pressed against the fixing film **112** toward the heater **113** by pressing means (not shown). A pressing force (pressure) was 14 kgf in total. The width of the fixing nip N with respect to the feeding direction A in the embodiment 1 is about 6.0 mm over the longitudinal direction B. The pressing roller **110** is rotated in the arrow R1 direction at a surface movement speed of 200 mm/sec by a rotating means (not shown).

(20) The heater **113** in the embodiment 1 is general-purpose heater used in the fixing device of the film heating type, and a heater prepared by providing a heat generating resistor on a ceramic substrate is used. As the heater **113**, an about 10 μm-thick heat generating resistor of Ag/Pd (silver/palladium) is applied onto a surface of a 1 mm-thick alumina substrate by screen printing, and thereon, a 50 μm-thick glass layer is coated for protecting the heat generating resistor and for ensuring sliding property. The thus-prepared heater **113** was used. Further, depending on a signal of a temperature detecting element (not shown) for detecting a temperature of the ceramic substrate or the fixing film **112**, a current passed through the heat generating resistor is appropriately controlled, so that a temperature of the heater **113** is adjusted. The heater **113** is fixedly supported by being engaged in the heater holding portion **135** which is a groove provided on the heater holder **130**. In the embodiment 1, in order to efficiently conduct the heat to the recording material, with respect to the feeding direction A, a center of the heater **113** and a center of the pressing roller **110** are aligned with each other.

(21) Onto the heater **113**, a lubricant for being interposed between the heater **113** and the fixing film **112** is applied. As the lubricant applied onto the heater **113**, fluorine-containing grease was

used in the embodiment 1. Specifically, grease in which perfluoropolyether (PFPE) oil is used as base oil and polytetrafluoroethylene (PTFE) powder is used as a thickener in mixture with the base oil was used.

(22) An effect of the embodiment 1 is particularly effective in the case where a ratio of the base oil to a total amount of the grease used is relatively large, and is particularly effective in the case where grease of 80 wt. % or more in ratio of the base oil was used. The grease high in ratio of the base oil is relatively small in amount of the thickener and viscosity becomes low, and therefore, a sliding property is good, but a function of holding the base oil by the thickener is weak. For that reason, there is a need to make up for a function of holding the grease and the base oil by the constitution of the embodiment 1. In the embodiment 1, grease of 85 wt. % in ratio of the base oil was used. The grease was applied in an amount of 200 mg by spray application (coating) onto a sliding surface S, which is a contact surface between the fixing film **112** and the heater **113**, over a region width of 210 mm which is somewhat shorter than a pressing region width of 220 mm with respect to the longitudinal direction B of the pressing roller **110**. A projected portion **131** and a lubricant holding portion **132** will be described later.

Feature of Embodiment 1

(23) A shape of the heater holder **130**, particularly the lubricant holding portion **132** provided on the heater holder **130**, which is a feature of the embodiment 1 will be described while making reference to FIG. 3. Part (a) of FIG. 3 is a schematic view of a principal portion, showing a positional relationship between the heater **113**, the fixing film **112**, the projected portion **131** and the lubricant holding portion **132** in an enlarged manner. Part (b) of FIG. 3 is a schematic view of the principal portion in the neighborhood of the lubricant holding portion **132** as seen from the pressing roller **110** side. The heater holder **130** in the embodiment 1 includes the lubricant holding portion **132** and the projected portion **131**. The lubricant holding portion **132** is provided upstream of the heater holding portion **135** with respect to the feeding direction A. The projected portion **131** is provided upstream of the lubricant holding portion **132** with respect to the feeding direction A and projects toward the pressing roller **110** compared with an opposing surface described later. The opposing surface projects toward the pressing roller **110** than the sliding surface S, in other words, the fixing nip N is, so that the projected portion **131** projects toward the pressing roller **110** than the lubricant holding portion **132** is.

(24) The heater holder **130** includes the projected portion **131** projecting toward the pressing roller **110** side than the heater **113** is, on a side upstream of the fixing nip N with respect to the feeding direction A. A degree of projection of the projected portion **131** from the sliding surface S (hereinafter, this degree is referred to as a projection height H1) is required to be a certain height in order to regulate a locus of the fixing film **112**. However, when the projection height H1 is excessively high, it causes prevention of entrance of the recording material P into the fixing nip N, and therefore the projection height H1 may desirably be about 0.1 mm to 1.0 mm. In the embodiment 1, the projection height H1 of a top point V of the projected portion **131** from the sliding surface S is 0.4 mm.

(25) Between the fixing nip N and the projected portion **131**, the lubricant holding portion **132** for holding the grease is provided. A height H2 of the lubricant holding portion **132** from the sliding surface S is needed to be set at a value lower than the projection height H1 of the projected portion **131** ($H2 < H1$). Further, the lubricant holding portion **131** is made higher than the sliding surface S. This is because when the fixing film **112** rotates in the arrow R2 direction, an edge portion **113e** of the heater **113** on an upstream side of the heater **113** with respect to the feeding direction A and on the pressing roller **110** side of the heater **113** (hereinafter, this edge portion is referred to as an upstream edge portion) is protected from rubbing against the inner surface of the fixing film **112**. In the embodiment 1, the height H2 of the lubricant holding portion **132** from the sliding surface S was 0.2 mm. Therefore, a height of the projected portion **131** from the lubricant holding portion **132** is $H1 - H2 = 0.2$ mm. Further, a width W1 of the projected portion **131** with respect to the

feeding direction A is 0.5 mm. Further, a width W2 of the lubricant holding portion **132** with respect to the feeding direction A is larger (wider) than the width W1 of the projected portion **131** with respect to the feeding direction A ($W > W1$). In the embodiment 1, the projected portion **131** was provided by changing the shape of the heater holder **130**, but the projected portion **131** may also be provided as a member separate from the heater holder **130** and may also be formed of a material of the heater holder **130**.

Lubricant Holding Portion

(26) The lubricant holding portion **132** includes a flat surface portion **132b** as the opposing surface opposing the pressing roller **110**, and the flat surface portion **132b** includes a plurality of recessed portions **132a** each recessed in a direction in which the recessed portion **132a** is distant from the pressing roller **110**. Incidentally, the opposing surface is the flat surface portion **132b**, but is not limited to the flat surface. The lubricant holding portion **132** is provided with the plurality of recessed portions **132a** for holding the grease over the longitudinal direction B. The recessed portions **132a** may desirably be disposed independently with respect to the longitudinal direction B from the viewpoint such that the held grease is not intended to spread in the longitudinal direction B to the extent possible. Further, from the viewpoint such that the grease is held and is prevented from excessively flowing onto the sliding surface S, with respect to the feeding direction A, it is desirable that each recessed portion **132a** does not penetrate through the heater holding portion (groove portion) **135** holding the heater **113**. It is further desirable that as regards a shape of each recessed portion **132a**, a length with respect to the feeding direction A is made longer than a length with respect to the longitudinal direction B from the viewpoint such that the grease is moved in a diameter toward the fixing nip N, i.e., in the feeding direction A. That is, when the length of each recessed portion **132a** of the lubricant holding portion **132** with respect to the feeding direction A is L_a and the length of each recessed portion **132a** is L_b , $L_a > L_b$ may desirably be satisfied.

(27) In the embodiment 1, each recessed portion **132a** has an elliptical shape in cross-section on the flat surface portion **132b**, as shown in part (b) of FIG. 3. Each recessed portion **132a** has a smoothly recessed shape such that the length L_a with respect to the feeding direction A is 2.0 mm, the length L_b with respect to the longitudinal direction B is 1.0 mm, and a depth is 0.5 mm. That is, as regards the lubricant holding portion **132**, each recessed portion **132a** may only be required to have a recessed shape such that a cross-sectional area of each recessed portion **132a** parallel to the flat surface portion **132b** becomes smaller with an increasing distance from the pressing roller **110**. In other words, as regards the lubricant holding portion **132**, a cross-sectional shape of each recessed portion **132a** perpendicular to the longitudinal direction B may also be a rectangular groove, other than an arcuate groove which has a shape (bow shape) as indicated by a broken line of part (a) of FIG. 3. Incidentally, in the case where each recessed portion **132a** of the lubricant holding portion **132** is the rectangular groove, a constitution in which a cross-sectional area parallel to the flat surface portion **132b** is the same irrespective of a distance from the pressing roller **110** and a constitution in which the cross-sectional area made small with an increasing distance from the pressing roller **110** may also be employed.

(28) A pitch P_t of adjacent recessed portions **132a** (i.e., a distance between centers of adjacent parts of the lubricant holding portion **132** with respect to the longitudinal direction B) and an interval S_p (predetermined interval) between the adjacent recessed portions **132a** determined as follows. When an expansion amount of the base oil in the case where the grease (lubricant) is added dropwise to the flat surface portion **132b** of the heater holder **130** in amount per (one) pitch of the base oil contained in the grease applied is a diameter D (mm), the interval S_p between the adjacent recessed portions **132a** may desirably be set a value which is D or less ($S_p < D$). By setting so, even in the case where the base oil is separated from the grease adhering to between the recessed portions **132a**, the base oil can be caught and held by the recessed portions **132a**. Thus, the interval between the recessed portions **132a** is smaller than the diameter in which the base oil expands in the case where the base oil is added dropwise to the flat surface portion **132b** in an amount per (one)

recessed portion **132a**. In the embodiment 1, the pitch Pt and the interval Sp are set so that the base oil is added dropwise to the flat surface portion **132b** in the amount per recessed portion **132a** is smaller than the diameter in which the base oil expands.

(29) In the embodiment 1, the recessed portions **132a** are disposed with the certain pitch of 2 mm (Pt=2 mm), and therefore, the amount per pitch of the base oil of $200 \times 0.85 / 210 \times 2 = 1.6$ mg. The base oil expansion amount when the base oil is added dropwise to the flat surface portion **132b** of the heater holder **130** in this amount was about 2.2 mm in the embodiment 1 from a result of study by the present inventor. For that reason, in the embodiment 1, the interval between the recessed portions **132a** was set at 1.0 mm. Further, from the viewpoint of ease of holding of the base oil by the recessed portion **132a**, a contact angle of the base oil to the heater holder **130** by a liquid droplet method may desirably be 90° or less, and is about 20° to 40° in the embodiment 1. In the embodiment 1, many recessed portions **132a** are disposed independently over the pressing region width of the pressing roller **110** with respect to the longitudinal direction B as described above.

(30) The fixing film **112** is backed up by the fixing nip N, the heater holder **130** and the projected portion **131**. The fixing film **112** originally has a cylindrical shape, and therefore, in the neighborhood of the projected portion **131** positioned upstream of the fixing nip N, the fixing film **112** rotates while contacting the projected portion **131** by a restoring force by which the shape of the fixing film **112** is returned to the cylindrical shape. The projected portion **131** projects toward the pressing roller **110** direction than the sliding surface S of the heater **113** is, and therefore, a locus of the fixing film **112** is regulated by the projected portion **131**. For this reason, as shown in part (a) of FIG. 2, the lubricant holding portion **132** is disposed in the neighborhood of the inner surface of the fixing film **112** on a side upstream of the fixing nip N without being contacted steadily to the fixing film **112** at strong pressure.

(31) Immediately after the fixing device **100** is assembled, the grease is applied onto the sliding surface S, but the fixing film **112** is rotated by performing a fixing operation, so that the grease adheres to the inner surface of the fixing film **112** and the fixing film **112** rotates. A part of the grease reaches the lubricant holding portion **132** with rotation of the fixing film **112** and is held in the recessed portions **132a** of the lubricant holding portion **132**. The grease once held in the recessed portions **132a** is not readily contacted directly and steadily to the inner surface of the fixing film **112** because the fixing film **112** is regulated by the projected portion **131**.

Comparison with Comparison Example

(32) Next, action on the grease G by the constitution of the embodiment 1 will be described while making comparison with a comparison example with reference to FIGS. 4 and 5. Parts (a) and (b) of FIG. 4 are schematic views for illustrating action of supply of the grease G in the embodiment 1. FIG. 5 is a schematic view for illustrating action of supply of the grease G in a comparison example in which the projected portion **131** is not provided. Incidentally, constituent elements similar to those described above are represented by the same reference numerals or symbols and will be omitted from illustration.

(33) In the comparison example shown in FIG. 5, the projected portion **131** is not provided and therefore, the inner surface of the fixing film **112** steadily contacts the recessed portions **132a** of the lubricant holding portion **132** and the grease G stored therein. When the fixing film **112** steadily contacts the recessed portions **132a**, the grease G always moves in the sliding surface (portion) S direction, so that the grease G is excessively supplied. Particularly, when the grease G steadily contacts the fixing film **112**, the grease G is liable to become a high temperature and thus the base oil is liable to be separated from the thickener. The separated base oil of the grease G moves from a minute gap Gp (indicated by a broken line) between the inner surface of the fixing film **112** and the heater holder **130** in a direction of the sliding surface S as indicated by an arrow in FIG. 5 by a capillary phenomenon. When the amount of the grease G supplied to the sliding surface S becomes excessive, the grease G pressed in the fixing nip N also expands in the longitudinal direction B by being pressed and deformed, and therefore is gradually pushed out in a direction of an end portion

of the fixing film **112** with respect to the longitudinal direction B, so that there is a liability that the grease G leaks out of the end portion of the fixing film **112** with respect to the longitudinal direction B sooner or later.

(34) In comparison with this comparison example, in the embodiment 1, the locus of the fixing film **112** is regulated by the projected portion **131** as shown in part (a) of FIG. 4, and therefore, the fixing film **112** does not steadily contact the recessed portions **132a**, and therefore, excessive supply of the grease G to the sliding surface S is suppressed. On the other hand, the fixing film **112** has a characteristic such that when the fixing film **112** is cooled depending on an ambient temperature after being heated and then is left standing for a long time, the fixing film **112** follows a shape of the fixing nip N and is plastically deformed to some extent. In the case where the following fixing operation is performed after the fixing film **112** is left standing for the long time, the locus of the fixing film **112** when the fixing film **112** starts rotation is different from a normal locus, so that the fixing film **112** exhibits behavior such that the fixing film **112** fluctuates to some extent between the fixing nip N and the projected portion **131**.

(35) At that time, as shown in part (b) of FIG. 4, the fixing film **112** temporarily contacts the recessed portions **132a**, and by the capillary phenomenon, the grease G is supplied in a slight amount to the sliding surface S through the gap Gp as shown by the arrow in the figure. However, when the fixing film **112** is heated and becomes the high temperature, the shape of the fixing film **112** deforms is returned to the original (cylindrical) shape. For this reason, as shown in part (a) of FIG. 3, the locus of the fixing film **112** is stabilized again, and the fixing film **112** does not steadily contact the recessed portions **132a**, so that the amount of excessive supply of the grease G to the sliding surface S is suppressed. By that, the amount of the grease G positioned at the sliding surface S becomes an appropriate amount, and therefore, it is possible to reduce a degree of an occurrence of a phenomenon such that the grease G pressed in the fixing nip N is pushed out in the longitudinal direction B and leaks out of the end portion of the fixing film **112** with respect to the longitudinal direction B.

(36) As described above, in the constitution of the embodiment 1, the grease G is supplied periodically in a proper amount to the sliding surface S while being held by the lubricant holding portion **132**. By this, it is possible to reduce a degree of leakage of the grease G out of the end portion of the fixing film **112** with respect to the longitudinal direction B while maintaining a sliding property.

(37) Incidentally, in the embodiment 1, the elliptical recessed portions **132a** were used, but even when recessed portions **132a** formed in other shapes are used, an effect of the embodiment 1 is achieved. Parts (a) and (b) of FIG. 6 are schematic views showing the recessed portions **132a** formed in other shapes, in which constituent elements similar to those described above are represented by the same reference numerals or symbols and will be omitted from description. For example, the present invention is also applicable to even other shapes such as a rectangular shape as shown in part (a) of FIG. 6 and a diamond shape as shown in part (b) of FIG. 6. Thus, with respect to a direction perpendicular to the feeding direction and the longitudinal direction of the heater holder **130** perpendicular to the feeding direction, when the flat surface portion **132b** is seen from the pressing roller **110** side, the lubricant holding portion **132** may also include recessed portions **132a** formed in the elliptical shape, the rectangular shape or the diamond shape. Incidentally, in parts (a) and (b) of FIG. 6, a shape of a cross-section of each recessed portion **132a** perpendicular to the longitudinal direction B may also be various shapes such as a curved line shape, a tapered shape and another rectangular shape. Further, in the embodiment 1, the recessed portions **132a** were provided by changing the shape of the heater holder **130**, but a separate member may also be disposed in the recessed portions **132a** by providing nonwoven fabric impregnated with the grease or a pad in the recessed portions **132a**, for example.

(38) As described above, according to the embodiment 1, with expansive and simple structure, it is possible to reduce a degree of leakage of the lubricant out of the end portion of the fixing film

while ensuring the sliding property of the fixing film.

Embodiment 2

(39) An embodiment 2 will be described below. In the embodiment 2, only a portion relating to the shape of the recessed portions **132a** is different from that in the embodiment 1. Other constitutions are similar to those in the embodiment 1, and therefore, detailed structures of the image forming apparatus **50** and the fixing device **100** will be omitted from description. Each of the recessed portions **132a** in the second embodiment is such that for the cross-sectional shape thereof on the flat surface portion **132b**, with respect to the longitudinal direction B, a length of a portion near to the sliding surface S, in other words, the fixing nip N is shorter than a portion far from the sliding surface S.

Feature of Embodiment 2

(40) A shape of the recessed portions **132a** which is a feature of the embodiment 2 will be described using part (a) of FIG. 7. In the embodiment 2, as shown in part (a) of FIG. 7, a width of each recessed portion **132a** is changed between the portion near to the sliding surface S and the portion far from the sliding surface S, so that each recessed portion **132a** has a wedge-like shape. In the embodiment 2, setting is made so that a width W_n of the portion near to the sliding surface S is smaller than a width W_d of the portion far from the sliding surface S. That is, each recessed portion **132a** has a shape such that as regards the width thereof with respect to the longitudinal direction B, the width W_n of the portion near to the sliding surface S and the width W_d of the portion far from the sliding surface S satisfies the relationship of: $W_n < W_d$. Specifically, the width W_n of the portion near to the sliding surface S is 0.3 mm, and the width W_d of the portion far from the sliding surface S is 1.2 mm. Incidentally, the length L_a of each recessed portion **132a** with respect to the feeding direction A was 2.0 mm similarly as in the embodiment 1. Incidentally, in part (a) of FIG. 7, a shape of a cross-section of each recessed portion **132a** perpendicular to the longitudinal direction B may also be various shapes such as a curved line shape, a tapered shape and another rectangular shape.

Effect of Embodiment 2

(41) A further effect in the embodiment 2 will be described using parts (b) and (c) of FIG. 7. For example, the case where the grease G adhered to the portion of the recessed portion **132a** far from the sliding surface S as shown in part (b) of FIG. 7 and the case where the grease G adhered to the portion of the recessed portion **132a** near to the sliding surface S as shown in part (c) of FIG. 7 will be considered. In the case where the base oil is separated from the grease G in a state of part (b) of FIG. 7, the width of the recessed portion **132a** with respect to the longitudinal direction B gradually narrows as an associated portion approaches the sliding surface S, and therefore, the base oil easily moves on the recessed portion **132a** in the sliding surface S direction by the capillary phenomenon. On the other hand, in the case where the base oil is separated from the grease G in a state of part (c) of FIG. 7, the base oil of the grease G does not readily move toward the portion far from the sliding surface S. That is, by changing the shape of each recessed portion **132a** to the shape in the embodiment 2, the base oil of the grease G can be localized at the portion of each recessed portion **132a** nearer to the sliding surface S. Of the base oil held by the recessed portion **132a**, the base oil to be supplied to the sliding surface S is successively used by being supplied principally from the portion near to the portion. At that time, of the base oil held by the recessed portion **132a**, from the base oil held at the portion far from the sliding surface S, the base oil is supplied to a position of the portion of the recessed portion **132a** near to the sliding surface S. By this action, the base oil held by the recessed portions **132a** is successively supplied and used, and therefore, of the grease G held in the recessed portions **132a**, the grease G which does not contribute to lubrication and which is held as it is can be decreased in amount.

(42) As described above, according to the embodiment 2, with expansive and simple structure, it is possible to reduce a degree of leakage of the lubricant out of the end portion of the fixing film while ensuring the sliding property of the fixing film.

Embodiment 3

(43) An embodiment 3 will be described below. In the embodiment 3, only a portion relating to the arrangement of the recessed portions **132a** is different from that in the embodiment 2. Other constitutions are similar to those in the embodiment 2, and therefore, detailed structures of the image forming apparatus **50** and the fixing device **100** will be omitted from description.

Feature of Embodiment 3

(44) An arrangement of the recessed portions **132a** which is a feature of the embodiment 3 will be described using part (a) of FIG. **8**. A shape of the recessed portions **132a** is similar to the shape of the recessed portions **132a** in the embodiment 2, and therefore, will be omitted from description. In the embodiment 3, as shown in parts (a) and (b) of FIG. **8**, a phantom line on which a center of the recording material P which will pass through a deeding passage is referred to as a phantom line M, and with respect to the phantom line M extending in the feeding direction, each of the recessed portions **132a** is disposed so that a longitudinal direction thereof is inclined. In other words, a constitution in which each recessed portion **132a** has a shape such that the portion near to the sliding surface S is oriented toward the phantom line M is employed. Specifically, with respect to the feeding direction A of the recording material P, an angle at which a phantom line Cl connecting a center of the width Wn on one end (downstream side) of the recessed portion **132a** and a center of the width Wd on the other end (upstream side) of the recessed portion **132a** is inclined relative to the phantom line M is referred to as θ . In the embodiment 3, the recessed portions **132a** are disposed by being inclined with $\theta=10^\circ$ with respect to the phantom line (center line) M. Incidentally, as arrangement of the plurality of recessed portions **132a**, the angle θ may also be changed depending on a position of an associated recessed portion **132a** with respect to the longitudinal direction. For example, as to the arrangement of the plurality of recessed portions **132a**, the angle θ may also be changed so as to become larger with a position closer to the end portion with respect to the longitudinal direction.

Effect of Embodiment 3

(45) A further effect in the embodiment 3 will be described using part (b) of FIG. **8**. As described above in the embodiment 2, the base oil separated from the grease G moves toward the portion near to the sliding surface S by the capillary phenomenon. At this time, as described above, the recessed portions **132a** are inclined toward the phantom line M on which the center of the recording material P which will pass through the deeding passage passes, and therefore, a movement direction of the base oil is also oriented by being inclined toward the phantom line M.

(46) By this action, an effect of collecting the base oil, which is expanded in the longitudinal direction B being pressed in the fixing nip N, toward the phantom line M on which the center of the recording material P which will pass through the deeding passage passes is created. For that reason, in the embodiment 3, the degree of the leakage of the grease G out of the end portion of the fixing film **112** with respect to the longitudinal direction B can be further reduced. Incidentally, the constitution of the embodiment 3 in which the recessed portions **132a** are inclined with respect to the phantom line M may also be applied to the recessed portions **132a** having the shapes shown in part (b) of FIG. **3** and parts (a) and (b) of FIG. **6** in the embodiment 1.

(47) As described above, according to the embodiment 3, with expansive and simple structure, it is possible to reduce a degree of leakage of the lubricant out of the end portion of the fixing film while ensuring the sliding property of the fixing film.

Embodiment 4

(48) An embodiment 4 will be described below. In the embodiment 4, only a portion where the shape and the arrangement of the recessed portions **132a** are changed depending on positions of the recessed portions **132** with respect to the longitudinal direction B is different from that in the embodiment 3. Other constitutions are similar to those in the embodiment 2, and therefore, detailed structures of the image forming apparatus **50** and the fixing device **100** will be omitted from description. In the embodiment 4, with respect to a perpendicular direction perpendicular to the

feeding direction A and the longitudinal direction B of the heater holder **130** perpendicular to the feeding direction A, when the flat surface portion **132** is seen from the pressing roller **110** side, the areas of the plurality of recessed portions **132a** change depending on the positions of the recessed portions **132a** with respect to the longitudinal direction. Specifically, as regards the areas of the recessed portions **132a**, compared with the recessed portions **132a** positioned at a central portion with respect to the longitudinal direction, the recessed portions **132a** positioned at end portions with respect to the longitudinal direction have larger areas. Further, compared with an interval between adjacent recessed portions **132a** positioned at the central portion with respect to the longitudinal direction, an interval between adjacent recessed portions **132a** positioned at each of the end portions with respect to the longitudinal direction is narrower. In the following, this will be described using the drawing.

Feature of Embodiment 4

(49) The arrangement of the recessed portions **132a** which is a feature of the embodiment 4 will be described using FIG. **9**. In the embodiment 4, the area (cross-sectional area on the flat surface portion **132b**) and the pitch are made different from each other between the central portion (in the neighborhood of the phantom line M) with respect to the longitudinal direction B and each of the end portions. At the central portion with respect to the longitudinal direction B, both the area and the pitch of each of the recessed portions **132a** are similar to those in the embodiment 3. On the other hand, at each of the end portions with respect to the longitudinal direction B, the widths (W_n and W_d) are made 1.17 times the widths at the central portion, and the pitch P_1 is reduced to 18 mm compared with the case of the central portion. That is, the recessed portions **132a** in the embodiment 4 are larger in width with respect to the longitudinal direction B with the position closer to each of the end portions with respect to the longitudinal direction B. In other words, the recessed portions **132a** are larger in area with the position closer to each end portion with respect to the longitudinal direction B. Further, the recessed portions **132a** are narrower in pitch P_t (or the interval S_p) with the position closer to each end portion with respect to the longitudinal direction B. Incidentally, in the embodiment 4, both the width and the pitch (interval) were changed depending on the position with respect to the longitudinal direction B, but either one of the width and the pitch may also be changed depending on the position with respect to the longitudinal direction B. Further, as to the arrangement of the plurality of recessed portions **132a**, the angle θ formed by the longitudinal direction of the recessed portion **132a** and the phantom line M may also be changed so as to become larger with the position closer to the end portion with respect to the longitudinal direction.

Effect of Embodiment 4

(50) In the embodiment 4, between the central portion and the end portion with respect to the longitudinal direction B, the area and the pitch of the recessed portions **132a** are made different, and therefore, retention power of the grease G by the lubricant holding portion **132** can be made different with respect to the longitudinal direction B. As regards the fixing device **100** of the film heating type as in the embodiment 4, when the recording material P narrow in length (paper width) with respect to the longitudinal direction B is fed, thermal capacity is small, and therefore, the member constituting the fixing device **100** is liable to increase in temperature at end portions with respect to the longitudinal direction B. That is, a phenomenon which is called end portion temperature rise occurs.

(51) In such a situation, compared with the central portion, separation of the base oil from the grease G at each end portion with respect to the longitudinal direction B is accelerated, so that there is a possibility that the base oil separated from the grease G at each end portion with respect to the longitudinal direction B leaks out of the end portion of the fixing film **112** and that the base oil component of the grease G at the end portion with respect to the longitudinal direction B is used up. In such a case, by employing the constitution as in the embodiment 4, the grease G retention power at each end portion with respect to the longitudinal direction B is enhanced, so that even

when the recording material P with a narrow paper width is fed, the grease G in a proper amount can be supplied to the sliding surface S while holding the grease G. Incidentally, the constitution of the embodiment 4 in which the recessed portions **132a** are changed in area and/or pitch depending on the positions thereof with respect to the longitudinal direction B may also be applied to the recessed portions **132a** having the shapes shown in part (b) of FIG. 3 and parts (a) and (b) of FIG. 6 in the embodiment 1.

(52) As described above, according to the embodiment 4, with expansive and simple structure, it is possible to reduce a degree of leakage of the lubricant out of the end portion of the fixing film while ensuring the sliding property of the fixing film.

(53) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(54) This application claims the benefit of Japanese Patent Application No. 2019-211823 filed on Nov. 22, 2019, which is hereby incorporated by reference herein in its entirety.

Claims

1. A fixing device comprising: a cylindrical fixing film; a heater configured to heat said fixing film, said heater being arranged in an internal space of said fixing film such that a longitudinal direction thereof is along a longitudinal direction of said fixing film; a heater holder including a heater holding portion holding said heater; and a pressing roller forming a nip, between itself and said fixing film to be heated by said heater, in which a toner image carried on a recording material is fixed, the pressing roller forming the nip with the heater via the fixing film, wherein said heater holder comprises: an opposing surface which is provided on a side upstream of said heater holding portion with respect to a recording material feeding direction and which opposes said pressing roller; and plural lubricant holding portions arranged on said opposing surface in the longitudinal direction and arranged in an area where said heater exists with respect to the longitudinal direction, the plural lubricant holding portions being configured to supply a lubricant to between said fixing film and said heater, each lubricant holding portion of the plural lubricant holding portions having four corners, a side on an upstream side in the recording material feeding direction and a side on a downstream side in the recording material feeding direction, and extending in the recording material feeding direction, and said side on the upstream side and said side on the downstream side overlapping when viewed in the recording material feeding direction, wherein those of said plural lubricant holding portions that are positioned on an end side of said heater holder in the longitudinal direction are inclined so that a first phantom line, which passes through a center of said side of said lubricant holding portion on the upstream side and a center of said side of said lubricant holding portion on the downstream side, is inclined toward a second phantom line through which a center of the recording material in the longitudinal direction passes as the first phantom line goes to the downstream side of the first phantom line when viewed in a direction which is vertical to both the longitudinal direction and the recording material feeding direction, and wherein, with respect to the recording material feeding direction, an inclination angle of a lubricant holding portion of said plural lubricant holding portions located close to said end side of said heater holder in the longitudinal direction is larger than an inclination angle of a lubricant holding portion of said plural lubricant holding portions located close to the second phantom line through which the center of the recording material passes in the longitudinal direction.

2. A fixing device according to claim 1, wherein said opposing surface is projected more toward said pressing roller than the nip is projected.

3. A fixing device according to claim 1, wherein when said opposing surface is seen from said pressing roller side in a direction perpendicular to the feeding direction and perpendicular to a

longitudinal direction of said heater holder perpendicular to the feeding direction, said plural lubricant holding portions have a trapezoid shape.

4. A fixing device according to claim 1, wherein when said opposing surface is seen from said pressing roller side in a direction perpendicular to the feeding direction and perpendicular to a longitudinal direction of said heater holder perpendicular to the feeding direction, with respect to the longitudinal direction of said heater holder, a length of a lubricant holding portion of said plural lubricant holding portions is longer at a portion far from the nip than at a portion near to the nip.

5. A fixing device according to claim 1, wherein a longitudinal direction of said plural lubricant holding portions forms a predetermined angle with respect to the feeding direction.

6. A fixing device according to claim 1, wherein said plural lubricant holding portions are provided at regular intervals.

7. A fixing device according to claim 1, wherein when viewed in a direction that is vertical to both the longitudinal direction and the recording material feeding direction, respective areas of said plural lubricant holding portions change depending on positions thereof with respect to the longitudinal direction and/or intervals of said plural lubricant holding portions change depending on the positions thereof with respect to the longitudinal direction.

8. A fixing device according to claim 1, wherein when viewed in a direction which is vertical to both the longitudinal direction and the recording material feeding direction, each of areas of said plural lubricant holding portions is larger at an end portion than at a central portion with respect to the longitudinal direction and/or each of intervals of said plural lubricant holding portions is narrower at the end portion than at the central portion with respect to the longitudinal direction.

9. A fixing device according to claim 1, wherein said lubricant at least contains base oil having a contact angle of 90° or less with respect to said heater holder, and wherein each of the intervals of said plural lubricant holding portions is smaller than a diameter in which said base oil extends when said base oil in an amount held by one lubricant holding portion is added dropwise to said opposing surface.

10. An image forming apparatus comprising: a photosensitive member on which an electrostatic latent image is formed; a developing unit configured to develop the electrostatic latent image with toner to form a toner image; a transfer unit configured to transfer the toner image onto a recording material; and the fixing device according to claim 1, configured to fix the toner image carried by the recording material.

11. A fixing device according to claim 1, wherein the side downstream of said heater holding portion of the heater holder is a flat portion.

12. A fixing device according to claim 1, wherein plural lubricant holding portions are not formed on a side downstream of said heater holding portion of said heater holder with respect to the recording material feeding direction.

13. A fixing device comprising: a cylindrical fixing film; a heater arranged in an internal space of said fixing film such that a longitudinal direction thereof is along a longitudinal direction of the fixing film; a heater holder arranged in the internal space of said fixing film such that the longitudinal direction thereof is along the longitudinal direction of the fixing film and including a function to guide said fixing film which is rotating; and a pressing roller forming a nip between itself and said fixing film in contact with an outer peripheral surface of said fixing film and by nipping said fixing film with said heater, wherein a recording material is fed by the nip and heated with heat of said heater, and an unfixed toner image carried by the on the recording material is fixed on the recording material, wherein on a fixing film guiding surface in an upstream side of said heater of said heater holder with respect to a rotational direction of said fixing film, a plurality of recessed portions, which have a side on the upstream side and a side on a downstream side which overlap with each other when viewed in a recording material feeding direction, and four corners and which extend in the rotational direction and in which a lubricant is entered, are arranged in an area where said heater exists with respect to the longitudinal direction and side by

side with respect to the longitudinal direction, wherein when viewed in a direction which is vertical to both the longitudinal direction and the rotational direction, a first phantom line connecting a center of said side of a recessed portion of the plurality of said recessed portions on the upstream side and a center of said side of said recessed portion of the plurality of said recessed portions on the downstream side is inclined so as to be close to a second phantom line through which a center of the recording material with respect to the longitudinal direction passes as the plurality of said recessed portions go to a downstream side of the recording material feeding direction, and wherein inclination angles of the first phantom line of the plurality of said recessed portions are larger toward the end portion of said heater holder in the longitudinal direction.

14. A fixing device according to claim 13, wherein said opposing surface is projected more toward said pressing roller than said nip is projected.

15. A fixing device according to claim 13, wherein when said opposing surface is seen from said pressing roller side in a direction perpendicular to the feeding direction and perpendicular to a longitudinal direction of said heater holder perpendicular to the feeding direction, said plurality of recessed portions have a trapezoid shape.

16. A fixing device according to claim 13, wherein a longitudinal direction of said plurality of recessed portions forms a predetermined angle with respect to the feeding direction.

17. A fixing device according to claim 13, wherein said plurality of recessed portions are provided at regular intervals.

18. A fixing device according to claim 13, wherein said lubricant at least contains base oil having a contact angle of 90° or less with respect to said heater holder, and wherein each of the intervals of the plurality of said recessed portions is smaller than a diameter in which said base oil extends when said base oil in an amount held by one recessed portion is added dropwise to said opposing surface.

19. An image forming apparatus comprising: a photosensitive member on which an electrostatic latent image is formed; a developing unit configured to develop the electrostatic latent image with toner to form a toner image; a transfer unit configured to transfer the toner image onto a recording material; and the fixing device according to claim 13, configured to fix the toner image carried by the recording material.

20. A fixing device according to claim 13, wherein recessed portions are not formed in the fixing film guiding portion on a side downstream of said heater of said heater holder with respect to the rotational direction of said fixing film.

21. A fixing device comprising: a cylindrical fixing film; a heater configured to heat said fixing film, said heater being arranged in an internal space of said fixing film such that a longitudinal direction thereof is along a longitudinal direction of said fixing film; a heater holder including a heater holding portion holding said heater; and a pressing roller forming a nip, between itself and said fixing film to be heated by said heater, in which a toner image carried on a recording material is fixed, the pressing roller forming the nip with the heater via the fixing film, wherein said heater holder comprises: a first opposing surface which is provided on a side upstream of said heater holding portion with respect to a recording material feeding direction and which opposes said pressing roller; and plural lubricant holding portions arranged on said first opposing surface in the longitudinal direction and arranged in an area where said heater exists with respect to the longitudinal direction, wherein those of said plural lubricant holding portions that are positioned on an end side of said heater holder in the longitudinal direction are inclined so that the lubricant flows in a direction toward a phantom line through which a center of the recording material in the longitudinal direction passes when viewed in a direction which is vertical to both the longitudinal direction and the recording material feeding direction, wherein a second opposing surface which is provided on a downstream side of said heater holding portion with respect to the recording material feeding direction and which opposes said pressing roller is flat, and wherein an inclination angle, with respect to the recording material feeding direction, of one of said plural lubricant holding

portions located close to said end side of said heater holder in the longitudinal direction is larger than an inclination angle, with respect to the recording material feeding direction, of another one of said plural lubricant holding portions located close to the phantom line through which the center of the recording material in the longitudinal direction passes.

22. A fixing device according to claim 21, wherein said plural lubricant holding portions are not formed on the downstream side of said heater holding portion of said heater holder with respect to the recording material feeding direction.
