

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12418612
B2
September 16, 2025
Choi; Junsu et al.

Electronic device for changing operation of wireless communication based on change of angle of housing and method therefor

Abstract

An electronic device includes: a hinge structure; a foldable housing including a first housing structure and a second housing structure that are configured to be foldable relative to each other around the hinge structure; a first antenna provided in the first housing structure; a second antenna provided in the second housing structure; a communication circuit electrically connected to the first antenna and the second antenna, and configured to transmit and receive data through a first link and a second link established between an external electronic device and the electronic device; and a processor operatively connected to the communication circuit, wherein the processor is configured to: identify whether an angle between the first housing structure and the second housing structure satisfies a specified condition; and control the communication circuit to transmit, through at least one of the first link and the second link, a signal related to a change in an operation of short-range wireless communication, based on whether the angle satisfies the specified condition.

Inventors: Choi; Junsu (Suwon-si, KR), Choi; Hyeonu (Suwon-si, KR), Kim; Sunghwan (Suwon-si, KR), Min; Hyunkee (Suwon-si, KR), Lim; Junhak (Suwon-si, KR), Jeong; Kiyeong (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008821834

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/071927

Filed: November 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230126559 A1	Apr. 27, 2023

Foreign Application Priority Data

KR	10-2021-0141553	Oct. 22, 2021
KR	10-2022-0134245	Oct. 18, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/015891 20221018 PENDING child-doc US 18071927

Publication Classification

Int. Cl.: H04M1/02 (20060101); H04M1/72454 (20210101)

U.S. Cl.:

CPC H04M1/72454 (20210101); H04M1/0216 (20130101);

Field of Classification Search

CPC: H04M (1/0243); H04M (1/0268); H04M (1/0241); H04M (1/72454); H04M (1/0216)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10148304	12/2017	Chang	N/A	H04W 52/367
10833392	12/2019	Zekios et al.	N/A	N/A
11158929	12/2020	Shi et al.	N/A	N/A
2006/0118625	12/2005	Sekita	235/451	G06F 1/1677
2021/0014811	12/2020	Seok et al.	N/A	N/A
2021/0075459	12/2020	Noh et al.	N/A	N/A
2021/0076398	12/2020	Naribole et al.	N/A	N/A
2021/0168227	12/2020	Jung et al.	N/A	N/A
2021/0218137	12/2020	Zhu	N/A	H01Q 1/44
2021/0344783	12/2020	Jeong et al.	N/A	N/A
2022/0109472	12/2021	Na et al.	N/A	N/A
2022/0166132	12/2021	Chu	N/A	H04B 1/0064
2022/0167444	12/2021	Jang et al.	N/A	N/A
2022/0286542	12/2021	Seo	N/A	H01Q 1/2283
2022/0303997	12/2021	Aio et al.	N/A	N/A
2023/0004195	12/2022	Hase	N/A	N/A
2023/0231297	12/2022	Kim	455/73	H04B 7/0413

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112436265	12/2020	CN	H01Q 1/22
2019-57756	12/2018	JP	N/A
10-2020-0024500	12/2019	KR	N/A
10-2020-0121199	12/2019	KR	N/A
10-2020-0144772	12/2019	KR	N/A
10-2021-0031309	12/2020	KR	N/A
2019/062891	12/2018	WO	N/A
2021/002618	12/2020	WO	N/A
2021/090718	12/2020	WO	N/A
2021/192729	12/2020	WO	N/A

OTHER PUBLICATIONS

Communication dated Oct. 25, 2024, issued by the European Patent Office in European Application No. 22883996.5. cited by applicant

International Search Report & Written Opinion (PCT/ISA/210 & PCT/ISA/237) issued Jan. 25, 2023 by the International Searching Authority in International Application No. PCT/KR2022/015891. cited by applicant

Primary Examiner: Perez; Angelica

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of International Application No. PCT/KR2022/015891, filed on Oct. 18, 2022, which is based on and claims priority to Korean Patent Application No. 10-2022-0134245, filed on Oct. 18, 2022, and Korean Patent Application No. 10-2021-0141553, filed on Oct. 22, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device and a method of operating an electronic device, and more particularly, to changing an operation of a wireless communication, based on a change in an angle of a housing.

2. Description of Related Art

(2) In line with proliferation of various electronic devices, improvement of speed for wireless communication that may be used by various electronic devices has been implemented. Among wireless communications supported by related electronic devices, Institute of Electrical and Electronics Engineers (IEEE) 802.11 wireless local-area network (WLAN) (e.g., Wireless-Fidelity (Wi-Fi)) is a communications standard for implementing high-speed wireless connection of various electronic devices. The first implemented Wi-Fi could support a transmission rate of up to 1 to 9 Mbps, and Wi-Fi 6 technology (or IEEE 802.11 ax) can support a transmission rate of up to about 10 Gbps.

- (3) A related electronic device may support various services (e.g., ultra high definition (UHD) video streaming services, augmented reality (AR) services, virtual reality (VR) services, or mixed reality (MR) services) using a large amount of data through wireless communication supporting a high transmission rate, and support various other services.
- (4) In the IEEE 802.11 WLAN standard, a technology supporting a multi-link operation (MLO) is scheduled to be introduced in order to improve data transmission/reception speed and reduce delay time. Electronic devices supporting MLO may transmit or receive data through a plurality of links, and thus are expected to be able to implement a higher transmission rate and a lower latency.
- (5) The IEEE 802.11 WLAN standard is considering a method of supporting a non-station (non-STA) mode or an enhanced multi-link single-radio (EMLSR) mode in which when data is transmitted to an external electronic device through one link, data is not received through another link in consideration of interference occurring between links due to a limited mounting space of the electronic device.
- (6) Furthermore, in recent years, an electronic device (e.g., a foldable device) having a flexible display to be bent and capable of being folded or an electronic device (e.g., a rollable device or a slidable device) capable of enlarging a display in a slide manner have been popular.
- (7) In an electronic device, a plurality of antennas may be disposed in different housings in order to improve the performance of short-range wireless communication (e.g., Wi-Fi). As a distance between the plurality of antennas increases, interference due to signals output or received by the antennas may be reduced, thereby improving the performance of short-range wireless communication.
- (8) However, in the case where an electronic device is implemented using a foldable housing (or a rollable housing), the distance between the antennas may change as an angle of the housing changes (or the degree to which the housing slides in changes). For example, when the electronic device is fully folded (or when the electronic device is in a fully slide-in state), the distance between the antennas may be reduced.
- (9) When the distance between the antennas is reduced, maintaining the operation of short-range wireless communication capable of implementing a low delay time and/or a high transmission or reception rate (e.g., simultaneous transmission and reception (STR) or high-level modulation coding scheme (MCS)) may not attain a required transmission (or reception) rate and delay time.

SUMMARY

- (10) According to an aspect of the disclosure, an electronic device includes: a hinge structure; a foldable housing including a first housing structure and a second housing structure that are configured to be foldable relative to each other around the hinge structure; a first antenna provided in the first housing structure; a second antenna provided in the second housing structure; a communication circuit electrically connected to the first antenna and the second antenna, and configured to transmit and receive data through a first link and a second link established between an external electronic device and the electronic device; and a processor operatively connected to the communication circuit, wherein the processor is configured to: identify whether an angle between the first housing structure and the second housing structure satisfies a specified condition; and control the communication circuit to transmit, through at least one of the first link and the second link, a signal related to a change in an operation of short-range wireless communication, based on whether the angle satisfies the specified condition.
- (11) The processor may be further configured to: select a mode from among a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is prevented from being received through the second link while transmitting data through the first link, based on identifying that the angle satisfies the specified condition; and control the communication circuit to transmit, through the at least one of the first link and the second link, the signal including information indicating the selected mode.
- (12) The processor may be further configured to control the communication circuit to transmit,

through the at least one of the first link and the second link, a changed signal including information indicating a changed selected mode, based on changing the selected mode to the changed selected mode.

(13) The processor may be further configured to change a modulation and coding scheme (MCS) of the at least one of the first link and the second link, based on identifying that the angle satisfies the specified condition.

(14) The processor may be further configured to change a bandwidth of the at least one of the first link and the second link, based on identifying that the angle satisfies the specified condition.

(15) The specified condition may include a condition related to a distance between the first antenna and the second antenna.

(16) The processor may be further configured to determine whether to transmit the signal, based on whether a difference between a first frequency band corresponding to the first link and a second frequency band corresponding to the second link is greater than or equal to a specified value.

(17) The processor may be further configured to prevent transmission of the signal, based on identifying that the difference between the first frequency band and the second frequency band is greater than or equal to the specified value.

(18) The processor may be further configured to prevent transmission of the signal, based on identifying that the difference between the first frequency band corresponding to the first link and the second frequency band is less than the specified value and identifying that the angle satisfies the specified condition.

(19) A distance between the first antenna and the second antenna may change according a change in the angle between the first housing structure and the second housing structure due to the first housing structure and the second housing structure being folded or unfolded about the hinge structure.

(20) According to an aspect of the disclosure, a method of operating an electronic device, including a first housing structure and a second housing structure that are configured to be foldable relative to each other, a first antenna provided in the first housing structure, and a second antenna provided in the second housing structure, includes: identifying whether an angle between the first housing structure and the second housing structure satisfies a specified condition; and transmitting a signal related to a change in an operation of short-range wireless communication established between an external electronic device and the electronic device through at least one of a first link and a second link, based on whether the angle satisfies the specified condition.

(21) The method may further include: selecting a mode from among a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is prevented from being received through the second link while transmitting data through the first link, based on identifying that the angle satisfies the specified condition; and transmitting, through the at least one of the first link and the second link, the signal including information indicating the selected mode.

(22) The method may further include transmitting, through the at least one of the first link and the second link, a changed signal including information indicating a changed selected mode, based on changing the selected mode to the changed selected mode.

(23) The method may further include changing a modulation and coding scheme (MCS) of the at least one of the first link and the second link, based on identifying that the angle satisfies the specified condition.

(24) The method may further include changing a bandwidth of the at least one of the first link and the second link, based on identifying that the angle satisfies the specified condition.

(25) The specified condition may include a condition related to a distance between the first antenna and the second antenna.

(26) The method may further include determining whether to transmit the signal, based on whether a difference between a first frequency band corresponding to the first link and a second frequency

band corresponding to the second link is greater than or equal to a specified value.

(27) The determining of whether to transmit the signal may include preventing transmission of the signal, based on identifying that the difference between the first frequency band and the second frequency band is greater than or equal to the specified value.

(28) The determining of whether to transmit the signal may include preventing transmission of the signal, based on identifying that the difference between the first frequency band and the second frequency band is less than the specified value and identifying that the angle satisfies the specified condition.

(29) A distance between the first antenna and the second antenna may change according a change in the angle between the first housing structure and the second housing structure due to the first housing structure and the second housing structure being folded or unfolded about a hinge structure of the electronic device.

(30) In an electronic device and a method of operating an electronic device according to various embodiments of the disclosure, the electronic device may transmit, to an external electronic device, a signal for changing the operation of short-range wireless communication if an angle between a first housing structure and a second housing structure satisfies a specified condition. An electronic device and an operation method of an electronic device may perform an operation (e.g., non-STR, low-level MCS, or low-performance operation mode) corresponding to the state in which a required distance between antennas is relatively small in the state in which a foldable housing is folded (or when a rollable housing is in a slide-in state), thereby preventing (or reducing) degradation of short-range wireless communication that may be caused when the foldable housing is folded.

(31) Alternatively or additionally, an electronic device and an operation method of an electronic device may perform an operation (e.g., STR, high-level MCS, or high-performance operation mode) corresponding to the state in which a required distance between antennas is relatively large in the state in which a foldable housing is unfolded (or when a rollable housing is in a slide-out state), thereby improving the performance of short-range wireless communication.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device according to various embodiments of the disclosure;

(3) FIG. 2A is a diagram illustrating an unfolded state of an electronic device including a foldable housing according to various embodiments of the disclosure;

(4) FIG. 2B is a diagram illustrating a folded state of an electronic device including a foldable housing according to various embodiments of the disclosure;

(5) FIG. 3A is a diagram illustrating a front surface of an electronic device in a slide-in state of an electronic device including a rollable housing according to various embodiments of the disclosure;

(6) FIG. 3B is a diagram illustrating a rear surface of an electronic device in a slide-in state of an electronic device including a rollable housing according to various embodiments of the disclosure;

(7) FIG. 3C is a diagram illustrating a front surface of an electronic device in a slide-out state of an electronic device including a rollable housing according to various embodiments of the disclosure;

(8) FIG. 3D is a diagram illustrating a rear surface of an electronic device in a slide-out state of an electronic device including a rollable housing according to various embodiments of the disclosure;

(9) FIG. 4A is a diagram illustrating an embodiment in which an electronic device and an access

point (AP) operate in a multi-link operation (MLO) according to various embodiments of the disclosure;

(10) FIG. 4B is a diagram illustrating an embodiment in which an electronic device operates in a non-simultaneous transmission and reception (non-STR) mode according to various embodiments of the disclosure;

(11) FIG. 4C is a diagram illustrating an embodiment in which an electronic device operates in an enhanced multi-link single-radio (EMLSR) mode according to various embodiments of the disclosure;

(12) FIG. 5 is a block diagram of an electronic device according to various embodiments of the disclosure;

(13) FIGS. 6A, 6B, 6C and 6D are diagrams illustrating an embodiment in which an electronic device according to various embodiments of the disclosure changes the operation of short-range wireless communication, based on a change in the angle of a first housing structure and a second housing structure;

(14) FIG. 7 is a diagram illustrating an embodiment in which an electronic device according to various embodiments of the disclosure changes the operation of short-range wireless communication, based on the degree to which a second housing structure slides in;

(15) FIG. 8 is an operational flowchart illustrating a method of operating an electronic device according to various embodiments of the disclosure; and

(16) FIG. 9 is an operational flowchart illustrating a method of operating an electronic device according to various embodiments of the disclosure.

DETAILED DESCRIPTION

(17) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network).

According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).

(18) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes

the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(19) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(20) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(21) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(22) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(23) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(24) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(25) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(26) The sensor module **176** may detect an operational state (e.g., power or temperature) of the

electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(27) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(28) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(29) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(30) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(31) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(32) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(33) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international

mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(34) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1ms or less) for implementing URLLC.

(35) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(36) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(37) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(38) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at

least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(39) FIG. 2A is a diagram illustrating an unfolded state of an electronic device **200** according to various embodiments of the disclosure. FIG. 2B is a diagram illustrating a folded state of the electronic device **200** in FIG. 2A according to various embodiments of the disclosure.

(40) The electronic device **200** in FIGS. 2A and 2B may be at least partially similar to the electronic device **101** in FIG. 1, or may include other embodiments of the electronic device.

(41) Referring to FIG. 2A, the electronic device **200** may include a pair of housing structures **210** and **220** rotatably coupled through a hinge structure (e.g., the hinge structure **264** in FIG. 3) to be folded relative to each other, a hinge cover **265** for covering foldable portions of the pair of housing structures **210** and **220**, and a display **230** (e.g., a flexible display or a foldable display) disposed in a space formed by the pair of housing structures **210** and **220**. In the present disclosure, the surface on which the display **230** is disposed may be referred to as a front surface of the electronic device **200**, and the opposite surface of the front surface may be referred to as a rear surface of the electronic device **200**. Alternatively or additionally, the surface surrounding a space between the front surface and the rear surface may be referred to as a side surface of the electronic device **200**.

(42) In an embodiment, the pair of housing structures **210** and **220** may include a first housing structure **210** including a sensor area **231d**, a second housing structure **220**, a first rear cover **240**, and a second rear cover **250**. The pair of housing structures **210** and **220** of the electronic device **200** is not limited to the shapes and coupling shown in FIGS. 2A and 2B, and may be implemented by a combination and/or coupling of other shapes or components. For example, in another embodiment, the first housing structure **210** and the first rear cover **240** may be integrally formed, and the second housing structure **220** and the second rear cover **250** may be integrally formed.

(43) According to an embodiment, the first housing structure **210** and the second housing structure **220** may be disposed on both sides of a folding axis (e.g., axis A) and/or have an overall symmetrical shape with respect to the folding axis (e.g., axis A). According to an embodiment, the angle or distance between the first housing structure **210** and the second housing structure **220** may vary depending on an unfolded state (flat state or closed state), a folded state, or an intermediate state of the electronic device **200**. According to an embodiment, the first housing structure **210**, unlike the second housing structure **220**, may further include a sensor area **231d** in which various sensors are disposed but have a symmetrical shape in other areas. In another embodiment, the sensor placement area **231d** may be further disposed in at least a partial area of the second housing structure **220** or may be replaced therewith.

(44) In an embodiment, the first housing structure **210** may be connected to a hinge structure (not shown) in the unfolded state of the electronic device **200** and include a first surface **211** disposed to face the front surface of the electronic device **200**, a second surface **212** facing in the opposite direction of the first surface **211**, and a first side member **213** surrounding at least a portion of a space between the first surface **211** and the second surface **212**. In an embodiment, the first side member **213** may include a first side surface **213a** disposed parallel to the folding axis (e.g., axis A), a second side surface **213b** extending from one end of the first side surface **213a** in a direction

perpendicular to the folding axis, and a third side surface **213c** extending from the opposite end of the first side surface **213a** in a direction perpendicular to the folding axis (e.g., axis A).

(45) In an embodiment, the second housing structure **220** may be connected to the hinge structure (e.g., the hinge structure **264** in FIG. 3) in the unfolded state of the electronic device **200** and include a third surface **221** disposed to face the front surface of the electronic device **200**, a fourth surface **222** facing in the opposite direction of the third surface **221**, and a second side member **223** surrounding at least a portion of a space between the third surface **221** and the fourth surface **222**. In an embodiment, the second side member **223** may include a fourth side surface **223a** disposed parallel to the folding axis (e.g., axis A), a fifth side surface **223b** extending from one end of the fourth side surface **223a** in a direction perpendicular to the folding axis (e.g., axis A), and a sixth side surface **223c** extending from the opposite end of the fourth side surface **223a** in a direction perpendicular to the folding axis (e.g., axis A). In an embodiment, the third surface **221** may face the first surface **211** in the folded state.

(46) In an embodiment, the electronic device **200** may include a recess **201** formed to receive the display **230** through structural shape coupling of the first housing structure **210** and the second housing structure **220**. The recess **201** may have substantially the same size as the display **230**. In an embodiment, the recess **201** may have two or more different widths in a direction perpendicular to the folding axis (e.g., axis A) due to the sensor area **231d**. For example, the recess **201** may have a first width **W1** between a first portion **220a** of the second housing structure **220**, which is parallel to the folding axis (e.g., axis A), and a first portion **210a** of the first housing structure **210**, which is formed on the periphery of the sensor area **231d**, and a second width **W2** formed between a second portion **220b** of the second housing structure **220** and a second portion **210b** of the first housing structure **210**, which does not belong to the sensor area **231d** and is parallel to the folding axis (e.g., axis A). In this case, the second width **W2** may be formed to be greater than the first width **W1**. For example, the recess **201** may have a first width **W1** formed between a first portion **210a** of the first housing structure **210**, which has an asymmetric shape, and a first portion **220a** of the second housing structure **220**, and a second width **W2** formed between a second portion **210b** of the first housing structure **210**, which has a symmetrical shape, and a second portion **220b** of the second housing structure **220**. In an embodiment, the first portion **210a** and the second portion **210b** of the first housing structure **210** may be formed to have different distances from the folding axis (e.g., axis A). The widths of the recess **201** are not limited to the illustrated example. In various embodiments, the recess **201** may have at least two different widths due to the shape of the sensor area **231d** or the asymmetric portions of the first housing structure **210** and the second housing structure **220**.

(47) In an embodiment, at least a portion of the first housing structure **210** and the second housing structure **220** may be formed of a metal material or a non-metal material having a rigidity selected to support the display **230**.

(48) In an embodiment, the sensor area **231d** may be formed adjacent to one corner of the first housing structure **210** to have a predetermined area. However, the arrangement, shape, or size of the sensor area **231d** is not limited to the illustrated example. For example, in another embodiment, the sensor area **231d** may be provided at another corner or any area between the top and bottom corners of the first housing structure **210**. In another embodiment, the sensor area **231d** may be disposed in at least a partial area of the second housing structure. In another embodiment, the sensor area **231d** may be disposed to extend to the first housing structure **210** and the second housing structure **220**. In an embodiment, the electronic device **200** may include components performing various functions, which are disposed to be exposed to the front surface of the electronic device **200** through the sensor area **231d** or one or more openings provided in the sensor area **231d**. In various embodiments, the components may include, for example, at least one of a front camera device, a receiver, a proximity sensor, an illuminance sensor, an iris recognition sensor, an ultrasonic sensor, or an indicator.

(49) In an embodiment, the first rear cover **240** may be disposed in the second surface **212** of the first housing structure **210** and may have a substantially rectangular periphery. In an embodiment, at least a portion of the periphery may be surrounded by the first housing structure **210**. Similarly, the second rear cover **250** may be disposed in the fourth surface **222** of the second housing structure **220**, and at least a portion of its periphery may be surrounded by the second housing structure **220**.

(50) Continuing to refer to FIG. 2A, the first rear cover **240** and the second rear cover **250** may have a substantially symmetrical shape with respect to the folding axis (e.g., axis A). In another embodiment, the first rear cover **240** and the second rear cover **250** may include various shapes different from each other. In another embodiment, the first rear cover **240** may be integrally formed with the first housing structure **210**, and the second rear cover **250** may be integrally formed with the second housing structure **220**.

(51) In an embodiment, the first rear cover **240**, the second rear cover **250**, the first housing structure **210**, and the second housing structure **220** may be coupled to each other in a structure providing a space in which various components (e.g., a printed circuit board, an antenna module, a sensor module, or a battery) of the electronic device **200** may be disposed. In an embodiment, one or more components may be disposed on the rear surface of the electronic device **200** or may be visually exposed therethrough. For example, one or more components or sensors may be visually exposed through a first rear surface area **241** of the first rear cover **240**. In various embodiments, the sensors may include a proximity sensor, a rear camera device, and/or a flash. In another embodiment, at least a portion of a sub-display **252** may be visually exposed through a second rear surface area **251** of the second rear cover **250**.

(52) The display **230** may be disposed in a space formed by the foldable housings **210** and **220**. For example, the display **230** may be seated in a recess (e.g., the recess **201** in FIG. 2A) formed by a pair of housing structures **210** and **220**, and may be disposed to occupy substantially most of the front surface of the electronic device **200**. Accordingly, the front surface of the electronic device **200** may include the display **230**, and a partial area (e.g., a periphery area) of the first housing structure **210** and a partial area (e.g., a periphery area) of the second housing structure **220**, which are adjacent to the display **230**. In an embodiment, the rear surface of the electronic device **200** may include a first rear cover **240**, a partial area (e.g., a periphery area) of the first housing structure **210** adjacent to the first rear cover **240**, the second rear cover **250**, and a partial area (e.g., a periphery area) of the second housing structure **220** adjacent to the second rear cover **250**.

(53) In an embodiment, the display **230** may indicate a display in which at least a partial area may be transformed into a flat surface or a curved surface. In an embodiment, the display **230** may include a folding area **231c**, a first area **231a** disposed at one side of the folding area **231c** (e.g., in the right area of the folding area **231c**), and a second area **231b** disposed at the other side thereof (e.g., in the left area of the folding area **231c**). For example, the first area **231a** may be disposed on the first surface **211** of the first housing structure **210**, and the second area **231b** may be disposed on the third surface **221** of the second housing structure **220**. In an embodiment, division of the display **230** is provided by way of example, and the display **230** may be divided into a plurality of (e.g., four or more or two) areas depending on a structure or function thereof. For example, the area of the display **230** may be divided based on the folding area **231c** or the folding axis (e.g., axis A) extending parallel to the y-axis in the embodiment shown in FIG. 2A. Alternatively or additionally, the area of the display **230** may be divided based on another folding area (e.g., a folding area parallel to the x-axis) or another folding axis (e.g., a folding axis parallel to the x-axis). The above-described division of the area of the display is only a physical division by the pair of housing structures **210** and **220** and the hinge structure (e.g., the hinge structure **264** in FIG. 3), and the display **230** may display substantially one full screen through the pair of housing structures **210** and **220** and the hinge structure (e.g., the hinge structure **264** in FIG. 3). In an embodiment, the first area **231a** and the second area **231b** may have an overall symmetrical shape with respect to the

folding area **231c**. However, unlike the second area **231b**, the first area **231a** may include a notch area (e.g., the notch area **233** in FIG. 3) that is cut due to the presence of the sensor area **231d**, but may have a symmetrical shape to the second area **231b** in other areas. For example, the first area **231a** and the second area **231b** may include portions having shapes symmetric to each other and portions having shapes asymmetric to each other.

(54) Referring to FIG. 2B, the hinge cover **265** may be configured to be disposed between the first housing structure **210** and the second housing structure **220** to cover internal components (e.g., the hinge structure **264** in FIG. 3). In an embodiment, the hinge cover **265** may be covered by a portion of the first housing structure **210** and the second housing structure **220** or exposed to the outside depending on the operation state (flat state or folded state) of the electronic device **200**.

(55) For example, as shown in FIG. 2A, when the electronic device **200** is in the unfolded state, the hinge cover **265** may be covered by the first housing structure **210** and the second housing structure **220** so as not to be exposed. For example, as shown in FIG. 2B, when the electronic device **200** is in the folded state (e.g., in a completely folded state), the hinge cover **265** may be exposed to the outside between the first housing structure **210** and the second housing structure **220**. For example, in the case of the intermediate state in which the first housing structure **210** and the second housing structure **220** are folded at a certain angle, the hinge cover **265** may be partially exposed to the outside of the electronic device **200** between the first housing structure **210** and the second housing structure **220**. In this case, the exposed area may be smaller than in the completely folded state. In an embodiment, the hinge cover **265** may include a curved surface.

(56) Hereinafter, the operation of the first housing structure **210** and the second housing structure **220** depending on the operation state (e.g., the unfolded state (flat state) and the folded state) of the electronic device **200**, and respective areas of the display **230** will be described.

(57) In an embodiment, when the electronic device **200** is in the unfolded state (flat state) (e.g., the state in FIG. 2A), the first housing structure **210** and the second housing structure **220** may form an angle of 180 degrees, and the first area **231a** and the second area **231b** of the display may be disposed to face in the same direction. Alternatively or additionally, the folding area **231c** may form the same plane as the first area **231a** and the second area **231b**.

(58) In an embodiment, when the electronic device **200** is in the folded state (e.g., the state in FIG. 2B), the first housing structure **210** and the second housing structure **220** may be disposed to face each other. The first area **231a** and the second area **231b** of the display **230** may form a narrow angle (e.g., between 0 degrees and 10 degrees) therebetween and, in some cases, face each other. At least a portion of the folding area **231c** may be formed of a curved surface having a predetermined curvature.

(59) In an embodiment, when the electronic device **200** is in the intermediate state, the first housing structure **210** and the second housing structure **220** may be disposed at a certain angle therebetween. The first area **231a** and the second area **231b** of the display **230** may form an angle greater than in the folded state and smaller than in the unfolded state. At least a portion of the folding area **231c** may be formed of a curved surface having a predetermined curvature, and the curvature may be smaller than that in the folded state.

(60) The embodiment described above relates to an in-folding type in which the first surface **211** of the first housing structure **210** and the third surface **221** of the second housing structure **220** are disposed to face each other when the electronic device **200** is in the folded state. However, various embodiments of the disclosure to be described below may be applied to an out-folding type in which the second surface **212** of the first housing structure **210** and the fourth surface **222** of the second housing structure **220** are disposed to face each other when the electronic device **300** is in the folded state.

(61) FIGS. 3A and 3B are diagrams illustrating a front surface and a rear surface, respectively, of an electronic device in a slide-in state according to various embodiments of the disclosure. FIGS. 3C and 3D are diagrams illustrating a front surface and a rear surface, respectively, of an electronic

device in a slide-out state according to various embodiments of the disclosure.

(62) An electronic device **300** in FIGS. **3A** to **3D** may be at least partially similar to the electronic device **101** in FIG. **1** and the electronic device **200** of FIGS. **2A** and **2B** or may further include other embodiments of the electronic device.

(63) Referring to FIGS. **3A** to **3D**, the electronic device **300** may include a first housing **310** (e.g., a first housing structure or a base housing), a second housing **320** (e.g., a second housing structure or a slide housing) coupled to move in a specified direction (e.g., the x-axis direction) and within a specified distance from the first housing **310**, and a flexible display **330** (e.g., an expandable display or a stretchable display) disposed to be supported through at least a portion of the first housing **210** and the second housing **320**. According to an embodiment, at least a portion of the second housing **320** may be received inside a first space **3101** of the first housing **310**, switching to a slide-in state. According to an embodiment, the electronic device **300** may include a bendable member (or a bendable support member) (e.g., an articulated hinge module or a multi-bar assembly) that at least partially forms the same plane as at least a portion of the first housing **310** in the slide-out state and is at least partially received inside a second space **3201** of the second housing **320** in the slide-in state. According to an embodiment, at least a portion of the flexible display **330** may be received inside an inner space **3201** of the second housing **320** while being supported by the bendable member in the slide-in state, thereby being disposed to be invisible to the outside. According to an embodiment, at least a portion of the flexible display **330** may be disposed to be visible to the outside in the slide-out state while being supported by the bendable member forming at least partially the same plane as the first housing **310**.

(64) According to various embodiments, the electronic device **300** may include a front surface **300a** (e.g., a first surface), a rear surface **300b** (e.g., a second surface) facing in the opposite direction of the front surface **300a**, and a side surface (not shown) surrounding a space between the front surface **300a** and the rear surface **300b**. According to an embodiment, the electronic device **300** may include a first housing **310** including a first side member **311**, and a second housing **320** including a second side member **321**. According to an embodiment, the first side member **311** may include a first side surface **3111** having a first length along a first direction (e.g., the x-axis direction), a second side surface **3112** extending from the first side surface **3111** in a substantially perpendicular direction (e.g., the y-axis direction) to have a second length greater than the first length, and a third side surface **3113** extending substantially parallel to the first side surface **3111** from the second side surface **3112** and having the first length. According to an embodiment, the first side member **311** may be at least partially formed of a conductive material (e.g., metal). According to an embodiment, at least a portion of the first side member **311** may include a first support member **312** extending to at least a portion of the first space **3101** of the first housing **310**.

(65) According to various embodiments, the second side member **321** may include a fourth side surface **3211** at least partially corresponding to the first side surface **3111** and having a third length, a fifth side surface **3212** extending in a direction substantially parallel to the second side surface **3112** from the fourth side surface **3211** and having a fourth length greater than the third length, and a sixth side surface **3213** extending from the fifth side surface **3212** to correspond to the third side surface **3113** and having the third length. According to an embodiment, the second side member **321** may be at least partially formed of a conductive material (e.g., metal). According to an embodiment, at least a portion of the second side member **321** may include a second support member **322** extending to at least a portion of the second space **3201** of the second housing **320**. According to an embodiment, the first side surface **3111** and the fourth side surface **3211**, and the third side surface **3113** and the sixth side surface **3213** may be slidably coupled to each other. According to an embodiment, in the slide-in state, the fourth side surface **3211** may be disposed to overlap the first side surface **3111** so as to be substantially invisible to the outside. According to an embodiment, in the slide-in state, the sixth side surface **3213** may be disposed to overlap the third side surface **3113** so as to be substantially invisible to the outside. In some embodiments, at least a

portion of the fourth side surface **3211** and the sixth side surface **3213** may be disposed to be at least partially visible to the outside in the slide-in state. According to an embodiment, in the slide-in state, the second support member **322** may be disposed to overlap the first support member **312** so as to be substantially invisible to the outside. In some embodiments, a portion of the second support member **322**, in the slide-in state, may be disposed to overlap the first support member **312** so as to be invisible to the outside, and the remaining portions of the second support member **322** may be disposed to be visible to the outside. According to an embodiment, the electronic device may include a rear cover **313** disposed in at least a portion of the first housing **310** on the rear surface **300b**. According to an embodiment, the rear cover **313** may be disposed through at least a portion of the first support member **312**. In some embodiments, the rear cover **313** may be integrally formed with the first side member **311**. According to an embodiment, the rear cover **313** may be formed of polymer, coated or tinted glass, ceramic, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the above materials. In some embodiments, the rear cover **313** may extend to at least a portion of the first side member **311**. In some embodiments, at least a portion of the first support member **312** may be replaced with the rear cover **313**. In some embodiments, the electronic device **300**, in the second housing **320**, may be disposed in at least a portion of the second support member **322** or may include another rear cover (e.g., a second rear cover) that is replaced with at least a portion of the second support member **322**.

(66) According to various embodiments, the electronic device **300** may include a flexible display **330** disposed to be supported by at least a portion of the first housing **310** and the second housing **320**. According to an embodiment, the flexible display **330** may include a first portion **330a** (e.g., a flat portion) that is visible to the outside and a second portion **330b** (e.g., a bendable portion) extending from the first portion **330a** and at least partially received inside the second space **3201** of the second housing **320** so as to be invisible to the outside in the slide-in state. According to an embodiment, the first portion **330a** may be disposed to be supported by the first housing **310**, and the second portion **330b** may be disposed to be supported at least partially by the bendable member. According to an embodiment, the flexible display **330** may extend from the first portion **330a** while being supported by the bendable member in the state in which the second housing **320** has slid out along a specified direction (the direction {circle around (1)}) to be disposed to form substantially the same plane as the first portion **330a** and to be visible to the outside. According to an embodiment, the second portion **330b** of the flexible display **330** may be received inside the second space **3201** of the second housing **320** in the state in which the second housing **320** has slid in along a specified direction (the direction {circle around (2)}) so as to be disposed to be invisible to the outside. Accordingly, the electronic device **300** may induce the flexible display **230** to change the display area thereof as the second housing **320** slides from the first housing **310** in a specified direction (e.g., the x-axis direction).

(67) According to various embodiments, the first housing **310** and the second housing **320** may be operated in a sliding manner such that the overall width thereof is variable with respect to each other. According to an embodiment, the electronic device **300** may be configured to have a first width **W1** between the second side surface **3112** and the fifth side surface **3212** in the slide-in state. According to an embodiment, the electronic device **300** may be configured to have a third width **W3** greater than the first width **W1** in the slide-out state through an operation in which at least a portion of the bendable member received inside the second space **3201** of the second housing **320** moves to have an additional second width **W2**. For example, the flexible display **330** may have a display area substantially corresponding to the first width **W1** in the slide-in state and may have an expand display area substantially corresponding to the third width **W3** in the slide-out state.

(68) According to various embodiments, a slide-in/slide-out operation of the electronic device **300** may be performed automatically. For example, if the electronic device **300** detects a triggering operation for switching from the slide-in state to the slide-out state or from the slide-out state to the slide-in state in the state in which a driving module does not operate, the electronic device **300** may

operate the driving module disposed inside the electronic device **300**. According to an embodiment, the triggering operation may include an operation of detecting the movement distance to which the second housing moves by a push-pull section in a slide-in direction (e.g., the direction {circle around (2)}). For example, the electronic device **300** may operate or stop the driving module through a driving motor control module that is operatively connected to a processor (e.g., the processor **120** in FIG. **1**) and controls a driving motor of the driving module (e.g., servo control). (69) According to various embodiments, the electronic device **300** may include a sensor (e.g., the sensor module **192** in FIG. **1**) for sensing a slide-in/slide-out operation. The sensor **192** may detect a slide-in/slide-out operation of the electronic device **300** and detect a length between the first housing **310** and the second housing **320**. The length between the first housing **310** and/or the second housing **320** may indicate the degree to which the second housing structure **320** (or the first housing **310**) slides in (or slides out). According to an embodiment, the sensor **192** may include at least one of a magnetic-force sensor (e.g., the Hall integrated circuit (IC)) and a capacitor sensor for measuring a change in a capacitor value of a touch screen panel included in the flexible display **330** in order to measure the length between the first housing **310** and/or the second housing **320**. Alternatively or additionally, the sensor **192** may include operation information (e.g., torque) of a motor to perform slide-in and/or slide-out operation between the first housing **310** and/or the second housing **320**, an optical sensor, and/or a strain gauge sensor that measures a resistance value that changes depending on the slide-in and/or slide-out operation of the first housing **310** and/or the second housing **320**.

(70) According to various embodiments, the electronic device **300** may include at least one of an input device (e.g., a microphone **303**), a sound output device (e.g., a receiver for a call **306** or a speaker **307**), sensor modules **304** and **317**, a camera module (first camera module **305** or second camera module **316**), a connector port **308**, a key input device (not shown), or an indicator (not shown), which are disposed in the first space **3101** of the first housing **310**. In another embodiment, the electronic device **300** may be configured to exclude at least one of the above-described elements or further include other elements. In another embodiment, at least one of the above-described elements may be disposed in the second space **3201** of the second housing **320**.

(71) According to various embodiments, the input device may include a microphone **303**. In some embodiments, the input device (e.g., the microphone **303**) may include a plurality of microphones disposed to detect the direction of sound. The sound output device may include, for example, a receiver **306** for a call and a speaker **307**. According to an embodiment, the speaker **307** may face the outside through at least one speaker hole formed in the first housing **310** in the slide-out state. According to an embodiment, the connector port **308** may face the outside through a connector port hole formed in the first housing **310** in the slide-out state. In some embodiments, the receiver **306** for a call may include a speaker (e.g., a piezo speaker) that operates without a separate speaker hole.

(72) According to various embodiments, the sensor modules **304** and **317** may produce an electrical signal and/or data value corresponding to an internal operation state of the electronic device **300** or an external environmental state. The sensor modules **304** and **317** may include, for example, a first sensor module **304** (e.g., a proximity sensor, an illuminance sensor) disposed on the front surface **300a** of the electronic device **300** and/or a second sensor module **317** (e.g., a heart rate monitoring (HRM) sensor) disposed on the rear surface **300b**. According to an embodiment, the first sensor module **304** may be disposed under the flexible display **330** on the front surface **300a** of the electronic device **300**. According to an embodiment, the first sensor module **304** and/or the second sensor module **317** may include at least one of a proximity sensor, an illuminance sensor, a time-of-flight (TOF) sensor, an ultrasonic sensor, a fingerprint recognition sensor, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, or a humidity sensor.

(73) According to various embodiments, the camera module may include a first camera module **305**

disposed on the front surface **300a** of the electronic device **300** and a second camera module **316** disposed on the rear surface **300b** of the electronic device **300**. According to an embodiment, the electronic device **300** may include a flash **318** positioned near the second camera module **316**. According to an embodiment, the camera modules **305** and **316** may include one or more lenses, an image sensor, and/or an image signal processor. According to an embodiment, the first camera module **305** may be configured to be disposed under the flexible display **330** and photograph a subject through a portion of the active area of the flexible display **330**. According to an embodiment, the flash **318** may include, for example, a light-emitting diode or a xenon lamp.

(74) According to various embodiments, the first camera module **305** among the camera modules and some sensor modules **304** among the sensor modules **304** and **317** may be disposed to detect an external environment through the flexible display **330**. For example, the first camera module **305** or some sensor modules **304** may be disposed to communicate with the external environment through a transparent area or perforated opening formed in the flexible display **330** in the first space **3101** of the first housing **310**. According to an embodiment, the area of the flexible display **330** facing the first camera module **305**, as a portion of the area displaying content, may be formed as a transmission area having a specified transmittance. According to an embodiment, the transmission area may be formed to have a transmittance in the range of about 5% to about 20%, for example. The transmission area may include an area overlapping an effective area (e.g., an angle of view) of the first camera module **305** through which light incident on an image sensor to produce an image passes. For example, the transmission area of the flexible display **330** may include an area having a lower pixel density and/or wire density than that in the surrounding area. For example, the transmission area may replace the aforementioned opening. For example, some camera modules **305** may include an under-display camera (UDC). In some embodiments, some sensor modules **304** may be disposed in the internal space of the electronic device **300** to perform their functions without being visually exposed through the flexible display **330**.

(75) According to various embodiments, the electronic device **300** may include one or more antennas (e.g., first antenna **A1** and second antenna **A2**) electrically connected to a wireless communication circuit (e.g., the wireless communication module **192** in FIG. **1**) disposed in the first space **3101** of the first housing **310**. According to an embodiment, the one or more antennas **A1** and **A2** may include the first antenna **A1** disposed in the upper area of the electronic device **300** and the second antenna **A2** disposed in the lower area of the electronic device **300**. In some embodiments, the electronic device **300** may further include at least one antenna disposed on the second side surface **3112** of the first housing **310** and/or the fifth side surface **3212** of the second housing **320**. According to an embodiment, the first antenna **A1** may include a first conductive part **411** segmented by one or more non-conductive parts **4111** and **4112** on the third side surface **3113** of the first side member **311**. According to an embodiment, the first conductive part **411** may be disposed to be segmented by a first non-conductive part **4111** and a second non-conductive part **4112** spaced apart by a predetermined interval and may be electrically connected to a wireless communication circuit (e.g., the wireless communication module **192** in FIG. **1**). According to an embodiment, the second antenna **A2** may include a second conductive part **412** segmented by one or more non-conductive parts **4211** and **4212** on the first side surface **3111** of the first side member **311**. According to an embodiment, the second conductive part **412** may be disposed to be segmented by a third non-conductive part **4211** and a fourth non-conductive part **4212** spaced apart by a predetermined interval and may be electrically connected to a wireless communication circuit (e.g., the wireless communication module **192** in FIG. **1**). According to an embodiment, the wireless communication circuit (e.g., the wireless communication module **192** in FIG. **1**) may be configured to transmit and/or receive wireless signals in a specified frequency band (e.g., about 800 MHz to 6000 MHz) (e.g., a legacy band) through the first conductive part **411** and/or the second conductive part **412**. In some embodiments, the electronic device **200** may further include at least one antenna module (e.g., an antenna module for short-range wireless communication, or a 5G

antenna module or antenna structure) disposed in the internal space (e.g., a first space **2101** or a second space **2201**) to transmit and receive wireless signals in a frequency band of about 3 GHz to 100 GHz through another wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1).

(76) The electronic device **300** according to exemplary embodiments of the disclosure may include a driving module disposed in the internal space (e.g., a second space **3201**) for a slide-in/slide-out operation. According to an embodiment, the electronic device **300** may use a push-pull operation as a triggering operation for driving the driving module. For example, if the electronic device **300** detects a triggering operation in which the second housing **320** is pushed by a push-pull section in a direction (e.g., the direction {circle around (2)}) in which the second housing **320** slides in the slide-in state while the driving module does not operate, the electronic device **300** may automatically slide out the second housing **320** through the drive module (push and pull-out operation) (e.g., slide-out operation). According to an embodiment, if the electronic device **300** detects a triggering operation in which the second housing **320** is pushed by a push-pull section in a direction (e.g., the direction {circle around (2)}) in which the second housing **320** slides in the slide-out state while the driving module does not operate, the electronic device **300** may cause the second housing **320** to automatically slide in through the drive module (push and pull-in operation) (e.g., slide-in operation). Accordingly, the electronic device **300** may provide an intuitive triggering means (switching means) for slide-in/slide-out operation to the user, thereby providing an intuitive and new experience and improving convenience for use.

(77) FIG. 4A is a diagram illustrating an embodiment in which an electronic device and an external electronic device (e.g., an access point (AP)) operate in a multi-link operation (MLO) according to various embodiments of the disclosure.

(78) Referring to FIG. 4, a wireless local-area network (WLAN) system **400** may include an electronic device **410** and/or an external electronic device **420**. According to an embodiment, the electronic device **410** may perform wireless communication with the external electronic device **420** through short-range wireless communication. Wireless communication may indicate various communication schemes that both the electronic device **410** and/or the external electronic device **420** can support. For example, the wireless communication may be Wi-Fi. The external electronic device **420** may serve as a base station that provides wireless communication to at least one electronic device **410** located within a communication radius of the WLAN system **400**. For example, the external electronic device **420** may include an AP of IEEE 802.11. The electronic device **410** may include a station (STA) of IEEE 802.11.

(79) According to various embodiments of the disclosure, the electronic device **410** and/or the external electronic device **420** may support a multi-link operation (MLO). The multi-link operation may be an operation mode for transmitting or receiving data through a plurality of links (e.g., a first link **431** and a second link **432**). The multi-link operation may be an operation mode to be introduced in IEEE 802.11be, and may be an operation mode for transmitting or receiving data through a plurality of links based on a plurality of bands or channels.

(80) According to various embodiments of the disclosure, the electronic device **410** may include a plurality of communication circuits (e.g., a first communication circuit **411** and/or a second communication circuit **412**) to support the multi-link operation. The first communication circuit **411** may transmit data to the external electronic device **420** through the first link **431** or receive data transmitted by the external electronic device **420** through the first link **431**. The first communication circuit **411** may output or receive a signal in a frequency band corresponding to the first link **431** through the first antenna **413**. The second communication circuit **412** may transmit data to the external electronic device **420** through the second link **432** or receive data transmitted by the external electronic device **420** through the second link **432**. The second communication circuit **412** may output or receive a signal in a frequency band corresponding to the second link **432** through the second antenna **414**.

(81) According to various embodiments of the disclosure, the external electronic device **420** may include a plurality of communication circuits (e.g., a third communication circuit **421** and/or a fourth communication circuit **422**) to support the multi-link operation. The third communication circuit **421** may transmit data to the electronic device **410** through the first link **431** or receive data transmitted by the electronic device **410** through the first link **431**. The third communication circuit **421** may output or receive a signal in a frequency band corresponding to the first link **431** through the third antenna **423**. The fourth communication circuit **422** may transmit data to the electronic device **410** through the second link **432** or receive data transmitted by the electronic device **410** through the second link **432**. The fourth communication circuit **422** may output or receive a signal in a frequency band corresponding to the second link **432** through the fourth antenna **424**.

(82) According to various embodiments of the disclosure, the frequency band of the first link **431** and the frequency band of the second link **433** may be different from each other. For example, the frequency band of the first link **431** may be 2.5 GHz, and the frequency band of the second link **432** may be 5 GHz or 6 GHz.

(83) According to various embodiments of the disclosure, the first link **431** and the second link **432** may use an electronic device other than the electronic device **410**. In order to prevent the electronic device **410** and another electronic device from simultaneously transmitting or receiving data through the same link, the electronic device **410** may support a carrier sense multiple-access-with-collision avoidance (CSMA/CA) method. The CSMA/CA method may be a method of transmitting data when a specific link is in an idle state. The electronic device **410** supporting CSMA/CA may identify whether or not another electronic device transmits data through a specific link and, if data transmission is detected, wait, instead of transmitting data through the specific link. The electronic device **410** supporting CSMA/CA, in response to identifying that another electronic device does not transmit data through the specific link, may transmit data in a specified manner (e.g., activate a timer and transmit data when the timer expires) through the specific link. Through the above method, the electronic device **410** may perform transmission and/or reception of data using a specific link without colliding with other electronic devices.

(84) According to various embodiments of the disclosure, the first link **431** and/or the second link **432** supported by the multi-link operation may independently support CSMA/CA.

(85) FIG. 4B is a diagram illustrating an embodiment in which an electronic device operates in a non-simultaneous transmission and reception (non-STR) mode according to various embodiments of the disclosure.

(86) Referring to FIG. 4B, a WLAN system **400** may include an electronic device **410** and/or an external electronic device **420**. According to an embodiment, the electronic device **410** may perform wireless communication with the external electronic device **420** through short-range wireless communication. Wireless communication may indicate various communication schemes that both the electronic device **410** and/or the external electronic device **420** are able to support. For example, the wireless communication may be Wi-Fi. The external electronic device **420** may serve as a base station that provides wireless communication to at least one electronic device **410** located within a communication radius of the WLAN system **400**. For example, the external electronic device **420** may include an AP of IEEE 802.11. The electronic device **410** may include a STA of IEEE 802.11.

(87) According to various embodiments of the disclosure, the electronic device **410** and/or the external electronic device **420** may support a multi-link operation (MLO). The multi-link operation may be an operation mode for transmitting or receiving data through a plurality of links (e.g., a first link **431** and a second link **432**). The multi-link operation may be an operation mode to be introduced in IEEE 802.11be, and may be an operation mode for transmitting or receiving data through a plurality of links based on a plurality of bands or channels.

(88) According to various embodiments of the disclosure, the electronic device **410** may include a plurality of communication circuits (e.g., a first communication circuit **411** and/or a second

communication circuit **412**) to support the multi-link operation. The first communication circuit **411** may transmit data to the external electronic device **420** through the first link **431** or receive data transmitted by the external electronic device **420** through the first link **431**. The first communication circuit **411** may output or receive a signal in a frequency band corresponding to the first link **431** through the first antenna **413**. The second communication circuit **412** may transmit data to the external electronic device **420** through the second link **432** or receive data transmitted by the external electronic device **420** through the second link **432**. The second communication circuit **412** may output or receive a signal in a frequency band corresponding to the second link **432** through the second antenna **414**.

(89) According to various embodiments of the disclosure, the external electronic device **420** may include a plurality of communication circuits (e.g., a third communication circuit **421** and/or a fourth communication circuit **422**) to support the multi-link operation. The third communication circuit **421** may transmit data to the electronic device **410** through the first link **431** or receive data transmitted by the electronic device **410** through the first link **431**. The third communication circuit **421** may output or receive a signal in a frequency band corresponding to the first link **431** through the third antenna **423**. The fourth communication circuit **422** may transmit data to the electronic device **410** through the second link **432** or receive data transmitted by the electronic device **410** through the second link **432**. The fourth communication circuit **422** may output or receive a signal in a frequency band corresponding to the second link **432** through the fourth antenna **424**.

(90) According to various embodiments of the disclosure, the frequency band of the first link **431** and the frequency band of the second link **433** may be different from each other. For example, the frequency band of the first link **431** may be 2.5 GHz, and the frequency band of the second link **432** may be 5 GHz.

(91) According to various embodiments of the disclosure, the electronic device **410** may fail to secure a sufficient space **441** between the first antenna **413** and the second antenna **414** due to implementation reasons. According to an embodiment, in the case where the space **441** between the first antenna **413** and the second antenna **414** is not sufficiently secured, the signal output from the first antenna **413** and the signal received through second antenna **414** may interfere with each other. For example, the second antenna **414** may receive a signal in which the signal received through the second link **432** and a portion of the signal output from the first antenna **413** are combined, so the quality of a signal received through the second link **432** may be degraded.

(92) According to various embodiments of the disclosure, in order to prevent a situation in which the signal output from the first antenna **413** and the signal output from the second antenna **414** interfere with each other, the electronic device **410** may support a non-simultaneous transmission and reception (STR) mode. The non-STR mode may indicate a mode in which the electronic device **410** does not receive data through the second link **432** when transmitting data to the external electronic device **420** through the first link **431**. The non-STR mode may support an operation of receiving data through the second link **432** while receiving data through the first link **431** and/or an operation of transmitting data through the second link **432** while transmitting data through the first link **431**.

(93) According to various embodiments of the disclosure, the electronic device **410** operating in the non-STR mode may not receive data through the second link **432** in the case of transmitting data to the external electronic device **420** through the first link **431**. Accordingly, the electronic device **410** operating in the non-STR mode may have a lower data transmission and/or reception rate than operating in the STR mode.

(94) FIG. 4C is a diagram illustrating an embodiment in which an electronic device operates in an enhanced multi-link single-radio (EMLSR) mode according to various embodiments of the disclosure.

(95) Referring to FIG. 4C, a WLAN system **400** may include an electronic device **410** and/or an external electronic device **420**. According to an embodiment, the electronic device **410** may

perform wireless communication with the external electronic device **420** through short-range wireless communication. Wireless communication may indicate various communication schemes that both the electronic device **410** and/or the external electronic device **420** are able to support. For example, the wireless communication may be Wi-Fi. The external electronic device **420** may serve as a base station that provides wireless communication to at least one electronic device **410** located within a communication radius of the WLAN system **400**. For example, the external electronic device **420** may include an AP of IEEE 802.11. The electronic device **410** may include a STA of IEEE 802.11.

(96) According to various embodiments of the disclosure, the electronic device **410** and/or the external electronic device **420** may support a multi-link operation (MLO). The multi-link operation may be an operation mode for transmitting or receiving data through a plurality of links (e.g., a first link **431** and a second link **432**). The multi-link operation may be an operation mode to be introduced in IEEE 802.11be, and may be an operation mode for transmitting or receiving data through a plurality of links based on a plurality of bands or channels.

(97) According to various embodiments of the disclosure, the electronic device **410** may include a first communication circuit **411** to support the multi-link operation. The first communication circuit **411** may transmit data to the external electronic device **420** through the first link **431** or receive data transmitted by the external electronic device **420** through the first link **431**. The first communication circuit **411** may transmit data to the external electronic device **420** through the second link **432** or receive data transmitted by the external electronic device **420** through the second link **432**. The first communication circuit **411** may output or receive a signal in a frequency band corresponding to the first link **431** through the first antenna **413**, and output or receive a signal in a frequency band corresponding to the second link **432** through the second antenna **414**.

(98) According to various embodiments of the disclosure, the external electronic device **420** may include a plurality of communication circuits (e.g., a third communication circuit **421** and/or a fourth communication circuit **422**) to support the multi-link operation. The third communication circuit **421** may transmit data to the electronic device **410** through the first link **431** or receive data transmitted by the electronic device **410** through the first link **431**. The third communication circuit **421** may output or receive a signal in a frequency band corresponding to the first link **431** through the third antenna **423**. The fourth communication circuit **422** may transmit data to the electronic device **410** through the second link **432** or receive data transmitted by the electronic device **410** through the second link **432**. The fourth communication circuit **422** may output or receive a signal in a frequency band corresponding to the second link **432** through the fourth antenna **424**.

(99) According to various embodiments of the disclosure, the frequency band of the first link **431** and the frequency band of the second link **433** may be different from each other. For example, the frequency band of the first link **431** may be 2.5 GHz, and the frequency band of the second link **432** may be 5 GHz.

(100) According to various embodiments of the disclosure, the electronic device **410** may support a multi-link operation using a plurality of links using one communication circuit (e.g., the first communication circuit **411**) for implementation reasons. In this case, the electronic device **410** may perform an enhanced multi-link single-radio (EMLSR) mode in which relatively small data (e.g., control data, request-to-send (RTS) frames, clear-to-send (CTS) frames, or acknowledgement (ACK) messages) is transmitted using a plurality of links (e.g., the first link **431** and the second link **432**) but relatively large data is transmitted through one link (e.g., the first link **431**). The EMLSR mode may indicate a mode in which relatively small data is transmitted/received using a plurality of links and in which relatively large data is transmitted/received using a single link. The electronic device **410** operating in the EMLSR mode may not receive data through the second link **432** in the case of transmitting relatively large data to the external electronic device **420** through the first link **431**. Accordingly, the electronic device **410** operating in the EMLSR mode may have a lower data transmission and/or reception rate than operating in the STR mode.

(101) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a foldable housing in which a first housing structure (e.g., the first housing structure **210** in FIG. 2A) and a second housing structure (e.g., the second housing structure **220** in FIG. 2A) are foldable (or rotatable) through a hinge structure. The first antenna **413** may be implemented inside the first housing structure **210**, and the second antenna **414** may be implemented inside the second housing structure **220**. When the first housing structure **210** and the second housing structure **220** are folded or unfolded, the distance (or isolation) between the first antenna **413** and the second antenna **414** may vary. For example, the distance between the first antenna **413** and the second antenna **414** may decrease when the first housing structure **210** and the second housing structure **220** are folded. If the first housing structure **210** and the second housing structure **220** are folded in the state in which the electronic device **410** operates in the STR mode, the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **413** and the second antenna **414** is reduced.

(102) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a rollable housing (or a slidable housing) in which a first housing structure (e.g., the first housing **310** in FIG. 3A) and a second housing structure (e.g., the second housing **320** in FIG. 3A) are movable in a specified direction and within a specified distance. The first antenna **413** may be implemented inside the first housing structure **310**, and the second antenna **414** may be implemented inside the second housing structure **320**. When the first housing structure **310** and the second housing structure **320** are in a slide-in or slide-out state, the distance (or isolation) between the first antenna **413** and the second antenna **414** may vary. For example, the distance between the first antenna **413** and the second antenna **414** may decrease when the first housing structure **310** and the second housing structure **320** are in the slide-in state. If the distance between the first housing structure **310** and the second housing structure **320** is reduced in the state in which the electronic device **410** operates in the STR mode, the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **413** and the second antenna **414** is reduced.

(103) Hereinafter, a specific embodiment in which the electronic device **410** is able to effectively perform short-range wireless communication according to change of the first housing structure **210** or **310** and the second housing structure **220** or **320** will be described.

(104) FIG. 5 may be a block diagram of an electronic device according to various embodiments of the disclosure.

(105) An electronic device (e.g., the electronic device **410** in FIG. 4A) may include a first antenna **511** (e.g., the first antenna **411** in FIG. 4A), a second antenna **512** (e.g., the second antenna **412** in FIG. 4A), a communication circuit (e.g., the first communication circuit **411** or the second communication circuit **412** in FIG. 4B) **520** and/or a processor (e.g., the processor **120** in FIG. 1) **530**.

(106) The first antenna **511** may receive a signal transmitted by an external electronic device (e.g., the external electronic device **420** in FIG. 4A) or transmit a signal to the external electronic device **420**. In the case where the electronic device **410** supports MLO, a signal in a frequency band corresponding to a first link (e.g., the first link **431** in FIG. 4A) may be transmitted or received, and a signal in a frequency band corresponding to a second link (e.g., the second link **432** in FIG. 4A) may be transmitted or received. The first antenna **511** may be implemented in the form of an array of a plurality of antennas.

(107) The second antenna **512** may receive a signal transmitted by the external electronic device **420** or transmit a signal to the external electronic device **420**. In the case where the electronic device **410** supports MLO, a signal in a frequency band corresponding to the first link **431** may be transmitted or received, and a signal in a frequency band corresponding to the second link **432** may be transmitted or received. The second antenna **512** may be implemented in the form of an array of a plurality of antennas.

(108) The communication circuit **520** may transmit data to the external electronic device **420** through the first link **431** or receive data transmitted by the external electronic device **420** through the first link **431**. The communication circuit **520** may transmit data to the external electronic device **420** through the second link **432** or receive data transmitted by the external electronic device **420** through the second link **432**. The communication circuit **520** may output or receive a signal in a frequency band corresponding to the first link **431** through the first antenna **511** and/or the second antenna **512**, and output or receive a signal in a frequency band corresponding to the second link **432** through the first antenna **511** and/or the second antenna **512**.

(109) Although one communication circuit **520** is illustrated in FIG. 5, the electronic device **410** may be implemented to include a plurality of communication circuits such as the first communication circuits **411** and/or the second communication circuits **412** as shown in FIG. 4A and/or FIG. 4B.

(110) The processor **530** may be operatively connected to the communication circuit **520** to control the operation of the communication circuit **520**.

(111) The processor **530** may receive data transmitted by an application processor (e.g., the processor **120** in FIG. 1) and produce a packet for transmitting the received data to the external electronic device **420**. The processor **530** may refer to a communication processor included in a communication module (e.g., the wireless communication module **192** in FIG. 1). According to an embodiment, the processor **530** may perform channel coding based on data transmitted by the application processor (e.g., the application processor **120** in FIG. 1) to produce a packet, identify whether or not there is an error in at least a portion of the data transmitted by the external electronic device **420**, or perform an error recovery operation (e.g., hybrid auto repeat request (HARQ)) if there is an error.

(112) The processor **530** may perform channel coding on the data as part of an operation of producing a packet, based on the data transmitted by the application processor **120**. Channel coding may be performed by the processor **530** to increase a success rate of data transmission. The processor **530** may produce encoded data through a variety of channel coding (e.g., turbo coding, polar coding, or low-density parity check code (LDPC)) on data. When performing channel coding, the processor **530** may determine (or change) a data rate and/or modulation level (hereinafter, referred to as a modulation-and-coding scheme (MCS) level) of a packet. The processor **530** may produce mapping data in which a data rate and FER (or expected data throughput) are mapped through a frame error rate (FER) sampling method and store the same in a memory (e.g., the memory **130** in FIG. 1). The processor **530** may select a data rate corresponding to a value having the highest expected data throughput with reference to the mapping data stored in the memory (e.g., the memory **130** in FIG. 1) and perform channel coding on the data, based on the selected data rate, thereby producing a packet to be transmitted to the external electronic device **420**.

(113) The electronic device **410** may realize a high data transmission and/or reception rate when transmitting data having a high MCS level and realize a lower data transmission rate and/or reception rate when transmitting or receiving data having a lower MCS level. However, in order to transmit or receive data having a high MCS level, a distance between the first antenna **511** and the second antenna **512** must be a specified value or more, thereby obtaining high performance, and if the distance between the first antenna **511** and the second antenna **512** is not a specified value or more, high performance may not be obtained.

(114) The processor **530** may negotiate with the external electronic device **420** for data transmission and/or reception through short-range wireless communication. The processor **530** may control the communication circuit **520** to transmit or receive data through an operation mode (STR mode or NSTR mode) determined by the negotiation with the external electronic device **420**.

(115) The simultaneous transmission-and-reception (STR) mode may indicate a mode in which the electronic device **410** may simultaneously transmit or receive data to or from the external electronic device **420** through the first link **431** and/or the second link **432**. The electronic device **410**

supporting the STR mode may transmit and/or receive data through the second link **432** while transmitting data through the first link **431**. The STR mode may exhibit high performance when the distance between the first antenna **511** and the second antenna **512** is a specified value or more and may not exhibit high performance if the distance between the first antenna **511** and the second antenna **512** is not a specified value or more.

(116) The non-STR mode may indicate a mode in which the electronic device **410** does not receive data the second link **432** when transmitting data to the external electronic device **420** through the first link **431**. The electronic device **410** supporting the non-STR mode may support an operation of receiving data through the second link **432** while receiving data through the first link **431** and/or an operation of transmitting data through the second link **432** while transmitting data through the first link **431**.

(117) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a foldable housing in which a first housing structure (e.g., the first housing structure **210** in FIG. 2A) and a second housing structure (e.g., the second housing structure **220** in FIG. 2A) are foldable (or rotatable) through a hinge structure. The first antenna **511** may be implemented inside the first housing structure **210**, and the second antenna **512** may be implemented inside the second housing structure **220**. When the first housing structure **210** and the second housing structure **220** are folded or unfolded, the distance (or isolation) between the first antenna **511** and the second antenna **512** may vary. For example, the distance between the first antenna **511** and the second antenna **512** may decrease when the first housing structure **210** and the second housing structure **220** are folded. If the first housing structure **210** and the second housing structure **220** are folded in the state in which the electronic device **410** operates in the STR mode (or in the state in which data having a high MCS level is transmitted or received), the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **511** and the second antenna **512** is reduced.

(118) The processor **530** may detect a change in the angle between the first housing structure **210** and the second housing structure **220**. The processor **530** may detect a change in the angle between the first housing structure **210** and the second housing structure **220** in a manner of receiving, from the application processor **120**, information related to a change in the angle between the first housing structure **210** and the second housing structure **220**. The information related to a change in the angle may include the amount of change in the angle between the first housing structure **210** and the second housing structure **220** and/or information indicating whether or not the amount of change in the angle between the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value.

(119) The processor **530** may be operatively connected to a sensor (not shown) that measures the angle between the first housing structure **210** and the second housing structure **220**. The processor **530** may detect occurrence of an event in which the angle between the first housing structure **210** and the second housing structure **220** changes, based on data received from the sensor measuring the angle.

(120) According to various embodiments of the disclosure, the processor **530** may detect occurrence of an event in which the angle between the first housing structure **210** and the second housing structure **220** changes using at least one sensor (e.g., a Hall sensor) capable of identifying a folding state of the electronic device **410** (e.g., the folded state of the electronic device **410**, the unfolded state of the electronic device **410**).

(121) The processor **530** may measure the angle between the first housing structure **210** and the second housing structure **220**, based on the sensor, and identify whether or not the angle satisfies a specified condition. The specified condition may indicate a condition related to the distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may increase as the angle between the first housing structure **210** and the second housing structure **220** increases. The distance between the first antenna **511** and the

second antenna **512** may decrease as the angle between the first housing structure **210** and the second housing structure **220** decreases.

(122) Alternatively or additionally, in the case where the processor **530** receives, from the application processor **120**, information indicating that the amount of change in the angle between the first housing structure **210** and the second housing structure **220** satisfies a specified condition (e.g., information indicating that a condition in which the angle between the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value is satisfied), the operation of determining whether or not a specified condition is satisfied may be omitted.

(123) The processor **530**, based on whether or not the angle satisfies the specified condition, may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**.

(124) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(125) According to an embodiment, the processor **530** may control the communication circuit **520** to operate in the STR mode in the unfolded state of the foldable housing. The processor **530** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the processor **530** may control the communication circuit **520** to switch from the STR mode to the non-STR mode. The processor **530** may control the communication circuit **520** to transmit information indicating switching to the non-STR mode to the external electronic device **420**. The processor **530** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the non-STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by switching to the non-STR mode.

(126) According to an embodiment, the processor **530** may control the communication circuit **520** to operate in the non-STR mode in the state in which the foldable housing is folded. The processor **530** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the processor **530** may control the communication circuit **520** to switch from the non-STR mode to the STR mode. The processor **530** may control the communication circuit **520** to transmit information indicating switching to the STR mode to the external electronic device **420**. The processor **530** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by switching to the STR mode that provides higher performance.

(127) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g.,

high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(128) According to an embodiment, the processor **530** may produce data corresponding to a first level of the MCS level in the unfolded state of the foldable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the processor **530** may receive data corresponding to the first level of the MCS level in the unfolded state of the foldable housing and decode the received data. The processor **530** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the processor **530** may perform a series of operations for setting the MCS level to a second level lower than the first level. The processor **530** may control the communication circuit **520** to transmit information for reducing the MCS level to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations for reducing the MCS level. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by transmitting or receiving data having a low MCS level.

(129) According to an embodiment, the processor **530** may produce data corresponding to a second level of the MCS level, which is lower than the first level, in the folded state of the foldable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the processor **530** may receive data corresponding to the first level of the MCS level in the unfolded state of the foldable housing and decode the received data. The processor **530** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the processor **530** may perform a series of operations to increase the MCS level. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by transmitting and receiving data a higher MCS level that provides higher performance.

(130) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(131) According to an embodiment, the processor **530**, in the unfolded state of the foldable housing, may control the communication circuit **520** to operate in a first operation mode (e.g., the number of spatial streams having a first value, the number of space time streams having a second value, and/or a channel width having a first size). The processor **530** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified

condition, the processor **530** may perform a series of operations to operate in a second operation mode (e.g., the number of spatial streams having a third value less than the first value, the number of space time streams having a fourth value less than the second value, and/or a channel width having a second size smaller than the first size). The processor **530** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the second operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the first operation mode to the second operation mode. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by operating in the second operation mode that requires a smaller distance between the first antenna **511** and the second antenna **512**.

(132) According to an embodiment, the processor **530**, in the folded state of the foldable housing, may control the communication circuit **520** to operate in the second operation mode. The processor **530** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the processor **530** may perform a series of operations to switch to the first operation mode. The processor **530** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the first operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the second operation mode to the first operation mode. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by operating in the first operation mode that provides higher performance.

(133) The disclosure is not limited to the embodiments described above (e.g., switching to the STR mode or the non-STR mode, changing the MCS level, or changing the operation mode) and may be applied to various cases of changing the operation of short-range wireless communication, which may occur according to the folding of the foldable housing.

(134) The disclosure may be applied to an electronic device implemented in the form of a rollable housing (or a slidable housing), as well as to the foldable housing described above.

(135) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a rollable housing (or a slidable housing) in which a first housing structure (e.g., the first housing **310** in FIG. 3A) and a second housing structure (e.g., the second housing **320** in FIG. 3A) are coupled to be movable in a specified direction and within a specified distance. The first antenna **511** may be implemented inside the first housing structure **310**, and the second antenna **512** may be implemented inside the second housing structure **320**. When the first housing structure **310** and the second housing structure **320** are in a slide-in or slide-out state, the distance (or isolation) between the first antenna **511** and the second antenna **512** may vary. For example, the distance between the first antenna **511** and the second antenna **512** may decrease when the first housing structure **310** and the second housing structure **320** are in the slide-in state. If the distance between the first housing structure **310** and the second housing structure **320** is reduced in the state in which the electronic device **410** operates in the STR mode (or in the state in which data having a high MCS level is transmitted or received), the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **511** and the second antenna **512** is reduced.

(136) The processor **530** may detect the degree to which the second housing structure **320** slides into (or the degree to which the second housing structure slides out of) the first housing structure

310. The processor **530** may detect the degree to which the second housing structure **320** slides in by a method of receiving, from the application processor **120**, information related to the degree to which the second housing structure **320** slides in. The information related to the degree to which the second housing structure **320** slides in may include the degree to which the second housing structure **320** slides in and/or information indicating whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition (e.g., a condition in which the degree to which the second housing structure **320** slides in is less than or equal to a specified value).

(137) The processor **530** may measure the degree to which the second housing structure **320** slides in, based on a sensor, and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may indicate a condition related to the distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may be reduced as the degree to which the second housing structure **320** slides in increases. The distance between the first antenna **511** and the second antenna **512** may increase as the degree to which the second housing structure **320** slides out increases.

(138) Alternatively or additionally, in the case where the processor **530** receives, from the application processor **120**, information indicating that the degree to which the second housing structure **320** slides in satisfies a specified condition, the operation of determining whether or not the specified condition is satisfied may be omitted.

(139) Based on whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition, the processor **530** may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**.

(140) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(141) According to an embodiment, the processor **530** may control the communication circuit **520** to operate in the STR mode in the unrolled state of the rollable housing. The processor **530** may detect that the second housing structure **320** slides into the first housing structure **310** and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include a condition in which the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may control the communication circuit **520** to switch from the STR mode to the non-STR mode. The processor **530** may control the communication circuit **520** to transmit information indicating switching to the non-STR mode to the external electronic device **420**. The processor **530** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the non-STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by switching to the non-STR mode.

(142) According to an embodiment, the processor **530** may control the communication circuit **520** to operate in the non-STR mode when the rollable housing is in the slide-in state. The processor **530** may detect sliding-out of the rollable housing and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include a condition in which the degree to which the second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may control the communication circuit **520** to switch from

the non-STR mode to the STR mode. The processor **530** may control the communication circuit **520** to transmit information indicating switching to the STR mode to the external electronic device **420**. The processor **530** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by switching to the STR mode that provides higher performance.

(143) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(144) According to an embodiment, the processor **530** may produce data corresponding to a first level of the MCS level in the slide-out state of the rollable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the processor **530** may receive data corresponding to the first level of the MCS level in the slide-out state of the rollable housing and decode the received data. The processor **530** may detect that the second housing structure **320** slides in and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may perform a series of operations to set the MCS level to a second level lower than the first level. The processor **530** may control the communication circuit **520** to transmit information for reducing the MCS level to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to reduce the MCS level. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by transmitting or receiving data having a low MCS level.

(145) According to an embodiment, the processor **530** may produce data corresponding to a second level of the MCS level, which is lower than the first level, when the rollable housing is in the slide-in state, and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the processor **530** may receive data corresponding to the second level of the MCS level when the rollable housing is in the slide-in state and decode the received data. The processor **530** may detect that the second housing structure **320** slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may perform a series of operations to increase the MCS level. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by transmitting and receiving data a higher MCS level that provides higher performance.

(146) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless

communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(147) According to an embodiment, the processor **530**, when the rollable housing is in the slide-out state, may control the communication circuit **520** to operate in a first operation mode (e.g., the number of spatial streams having a first value, the number of space time streams having a second value, and/or a channel width having a first size). The processor **530** may detect that the second housing structure **320** slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may perform a series of operations to operate in a second operation mode (e.g., the number of spatial streams having a third value less than the first value, the number of space time streams having a fourth value less than the second value, and/or a channel width having a second size smaller than the first size). The processor **530** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the second operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the first operation mode to the second operation mode. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by operating in the second operation mode that requires a smaller distance between the first antenna **511** and the second antenna **512**.

(148) According to an embodiment, the processor **530** may control the communication circuit **520** to operate in the second operation mode when the rollable housing is in the slide-in state. The processor **530** may detect that the second housing structure slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the processor **530** may perform a series of operations to switch to the first operation mode. The processor **530** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the first operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the second operation mode to the first operation mode. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by operating in the first operation mode that provides higher performance.

(149) The embodiments described above may be embodiments derived as the distance between the first antenna **511** and the second antenna **512** changes. However, although the distance between the first antenna **511** and the second antenna **512** is reduced, if a difference between the frequency band of the first link **341** and the frequency band of the second link **342** corresponds to the extent capable of producing appropriate performance, the electronic device **410** may not transmit a signal for changing the operation of short-range wireless communication.

(150) The processor **530** may identify whether or not a difference between the frequency band corresponding to the first link **431** and the frequency band corresponding to the second link **432** is greater than or equal to a specified value and, based on the identified result, determine whether or not to transmit a signal related to a change in the operation of short-range wireless communication.

(151) The processor **530**, in response to a difference between the frequency band corresponding to the first link **431** and the frequency band corresponding to the second link **432**, which is less than or equal to a specified value, may identify whether or not the angle of the first housing structure **210** and the second housing structure **220** (or the degree to which the second housing structure **320**

slides in) satisfies a specified condition. Based on the case where the angle of the first housing structure **210** and the second housing structure **220** (or the degree to which the second housing structure **320** slides in) satisfies the specified condition, the processor **530** may transmit a signal related to a change in the operation of short-range wireless communication to the external electronic device **420**.

(152) The processor **530**, in response to a difference between the frequency band corresponding to the first link **431** and the frequency band corresponding to the second link **432**, which is greater than or equal to a specified value, may determine to not transmit a signal related to a change in the operation of short-range wireless communication. Alternatively or additionally, the processor **530**, in response to a difference between the frequency band corresponding to the first link **431** and the frequency band corresponding to the second link **432**, which is greater than or equal to a specified value, may determine to not transmit a signal related to a change in the operation of short-range wireless communication, regardless of a change in the angle of the first housing structure **210** and the second housing structure **220**.

(153) The processor **530** may change the characteristics of a service using short-range wireless communication as the operation of short-range wireless communication changes.

(154) In the state in which the first housing structure **210** and the second housing structure **220** satisfy a specified condition, the processor **530** may perform short-range wireless communication through a communication mode (e.g., a non-STR mode) capable of providing relatively low quality. When it is identified that the first housing structure **210** and the second housing structure **220** do not satisfy a specified condition, the processor **530** may provide short-range wireless communication through a communication mode (e.g., an STR mode) capable of providing relatively high quality.

(155) In the case where the processor **530** is able to use a communication mode capable of providing relatively high quality, the processor **530** may change characteristics of a service using short-range wireless communication. According to an example, in the case where the processor **530** is able to use a communication mode capable of providing relatively high quality while providing a content providing service (e.g., a streaming service) or a call service (e.g., a video call or a voice call), the processor **530** may change the characteristics of a service using short-range wireless communication in order to receive higher quality content or receive higher quality videos or voices.

(156) Alternatively, in the case where the processor **530** is able to use a communication mode capable of providing relatively high quality while providing a content providing service (e.g., a streaming service) or a call service (e.g., a video call or a voice call), the processor **530** may provide a user interface (e.g., screen, sound, or vibration) for inducing a change in the characteristics of a service using short-range wireless communication in order to receive higher quality videos or voices. The processor **530** may change the characteristics of a service using short-range wireless communication according to a user input onto the user interface.

(157) The processor **530** may perform short-range wireless communication through a communication mode (e.g., an STR mode) capable of providing relatively high quality in the state in which the first housing structure **210** and the second housing structure **220** do not satisfy a specified condition. If the processor **530** identifies that the first housing structure **210** and the second housing structure **220** satisfy a specified condition, the processor **530** may provide short-range wireless communication through a communication mode (e.g., a non-STR mode) having relatively low quality but capable of providing a high data transmission or reception success rate.

(158) The processor **530** may change the characteristics of a service using short-range wireless communication in the situation in which a communication mode (e.g., a non-STR mode) capable of providing a high data transmission or reception success rate is provided. According to an example, in the case where the processor **530** is able to use a communication mode capable of providing relatively low quality while providing a content providing service (e.g., a streaming service) or a call service (e.g., a video call or a voice call), the processor **530** may change the characteristics of a

service using short-range wireless communication in order to receive lower quality content or receive lower quality videos or voices.

(159) Alternatively, in the case where the processor **530** is able to use a communication mode capable of providing relatively low quality while providing a content providing service (e.g., a streaming service) or a call service (e.g., a video call or a voice call), the processor **530** may provide a user interface (e.g., screen, sound, or vibration) for inducing a change in the characteristics of a service using short-range wireless communication in order to receive lower quality videos or voices. The processor **530** may change the characteristics of a service using short-range wireless communication according to a user input onto the user interface.

(160) FIGS. **6A**, **6B**, **6C** and **6D** are diagrams illustrating an embodiment in which an electronic device according to various embodiments of the disclosure changes the operation of short-range wireless communication, based on a change in the angle of a first housing structure and a second housing structure.

(161) Referring to FIG. **6A**, an electronic device (e.g., the electronic device **410** in FIG. **5**) may include a foldable housing **610** including a first housing **210** and a second housing **220**.

(162) According to various embodiments of the disclosure, the second housing **220** may be coupled to the first housing **210** to be foldable. The first housing **210** and the second housing **220** may be foldable to each other about a folding axis **620** (e.g., the folding axis (e.g., axis A) in FIG. **2A**) extending in a first direction. The first housing **210** and the second housing **220** may be disposed to face, at least in part, each other in a folded state.

(163) Referring to FIG. **6A**, the angle formed between the first housing **210** and the second housing **220** may be 180 degrees. If the angle formed between the first housing **210** and the second housing **220** is greater than or equal to a predetermined angle, the electronic device **300** may be referred to as being in an unfolded state. The predetermined angle may be 180 degrees, but it may vary according to the intention of a designer. When the electronic device **200** is in the unfolded state, the first housing **210** and the second housing **220** may form a planar structure.

(164) FIG. **6B** illustrates the electronic device **410** that is folded in a counterclockwise (C.C.W.) direction around a folding axis **620** according to various embodiments of the disclosure, and FIG. **6C** illustrates the electronic device **410** that is fully folded about the center line of the folding axis **620** according to various embodiments of the disclosure.

(165) FIGS. **6B** and **6C**, the user of the electronic device **410** may apply a force to the electronic device **200** in the unfolded state to fold the foldable housing **610** of the electronic device **410** about the folding axis **620**.

(166) The angle **621** between the first housing structure **210** and the second housing structure **220** may be greatest when the foldable housing **610** is fully unfolded (FIG. **6A**) and may be reduced while the foldable housing **610** is folded. The angle **621** may be smallest when the foldable housing **610** is fully folded (FIG. **6C**).

(167) A first antenna (e.g., the first antenna **511** in FIG. **5**) may be disposed inside the first housing **210**, and a second antenna (e.g., the second antenna **512** in FIG. **5**) may be disposed inside the second housing **220**. The distance **631** between the first antenna **511** and the second antenna **512** may vary as the first housing **210** and the second housing **220** are folded (or unfolded) about the folding axis **620**. The distance **631** may be greatest when the foldable housing **610** is fully unfolded (e.g., FIG. **6A**) and may be reduced while the foldable housing **610** is folded. When the foldable housing **610** is partially folded (e.g., FIG. **6B**), the distance **632** between the first antenna **511** and the second antenna **512** may be smaller than the distance **631** when the foldable housing **610** is fully unfolded. When the foldable housing **610** is fully folded (e.g., FIG. **6C**), the distance **633** between the first antenna **511** and the second antenna **512** may be less than the distance **632**. That is, the distances **631**, **632**, and **633** may be correlated with the angle **621**.

(168) The electronic device **410** may measure an angle between the first housing structure **210** and the second housing structure **220**, based on a sensor, and identify whether or not the angle satisfies

a specified condition. The specified condition may indicate a condition related to the distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may increase as the angle between the first housing structure **210** and the second housing structure **220** increases. The distance between the first antenna **511** and the second antenna **512** may decrease as the angle between the first housing structure **210** and the second housing structure **220** decreases.

(169) Based on whether or not the angle satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**.

(170) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(171) Based on the case where the angle satisfies a specified condition, the electronic device **410** may transmit, to the external electronic device **420**, a signal including information instructing to switch to any one of the STR mode and/or the non-STR mode.

(172) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(173) Based on the case where the angle satisfies a specified condition, the electronic device **410** may transmit a signal for changing the MCS level to the external electronic device **420**.

(174) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(175) Based on the case where the angle satisfies a specified condition, the electronic device **410** may transmit a signal for changing the operation mode of short-range wireless communication to the external electronic device **420**.

(176) FIG. 6D is a diagram illustrating an embodiment of changing the operation of short-range wireless communication while an electronic device **410** is folded or unfolded about a folding axis **650** according to various embodiments of the disclosure.

(177) The user of the electronic device **410** may fold the foldable housing of the electronic device **410** in the unfolded state about the folding axis **620** by applying a force to the electronic device **410**.

(178) The angle between the first housing structure **630** and the second housing structure **640** may be greatest when the foldable housing is fully unfolded (e.g., (a) in FIG. 6D) and may be reduced as the foldable housing is folded. The angle **621** may be smallest when the foldable housing **610** is fully folded (e.g., (b) in FIG. 6D).

(179) A first antenna (e.g., the first antenna **511** in FIG. 5) may be disposed inside the first housing structure **630** or on the first housing structure **630**, and a second antenna (e.g., the second antenna **512** in FIG. 5) may be disposed inside the second housing structure **640** or on the second housing structure **640**. The first antenna **511** may be disposed in various spaces of the first housing structure **630**, and disposition of the first antenna **511** is not limited to a specific position. The second

antenna **512** may be disposed in various spaces of the second housing structure **640**, and disposition of the first antenna **511** is not limited to a specific position. Although one first antenna **511** and one second antenna **512** are shown in the drawing, the number of antennas is not limited. The distance between the first antenna **511** and the second antenna **512** may vary depending on folding (or unfolding) of the first housing structure **630** and the second housing structure **640** about the folding axis **650**. The distance may be greatest when the foldable housing is fully unfolded (e.g., (a) in FIG. **6D**) and may be reduced as the foldable housing is folded. When the foldable housing is fully folded (e.g., (b) in FIG. **6D**), the distance between the first antenna **511** and the second antenna **512** may be less than the distance **632**. That is, the distance may have a correlation with the angle.

(180) The electronic device **410** may measure the angle between the first housing structure **630** and the first housing structure **640**, based on a sensor, and identify whether or not the angle satisfies a specified condition. The specified condition may indicate a condition related to a distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may increase as the angle between the first housing structure **630** and the first housing structure **640** increases. The distance between the first antenna **511** and the second antenna **512** may decrease as the angle between the first housing structure **630** and the first housing structure **640** decreases.

(181) The electronic device **410** may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**, based on whether or not the angle satisfies a specified condition.

(182) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among the management frames defined in IEEE 802.11.

(183) The electronic device **410**, based on the case the angle satisfying a specified condition, may transmit a signal including information instructing to switch to any one of the STR mode and/or the non-STR mode to the external electronic device **420**.

(184) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(185) The electronic device **410** may transmit a signal for changing an MCS level to the external electronic device **420**, based on the angle satisfying a specified condition.

(186) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing an operation mode of short-range wireless communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(187) The electronic device **410** may transmit the signal for changing an operation mode of short-range wireless communication to the external electronic device **420**, based on the angle satisfying a specified condition.

(188) FIG. **7** is a diagram illustrating an embodiment in which an electronic device according to various embodiments of the disclosure changes the operation of short-range wireless communication, based on the degree to which a second housing structure slides in.

(189) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a rollable housing (or a slidable housing) in which a first housing structure (e.g., the first housing **310** in FIG. 3A) and a second housing structure (e.g., the second housing **320** in FIG. 3A) are coupled to be movable in a specified direction and within a specified distance. The first antenna **511** may be implemented inside the first housing structure **310**, and the second antenna **512** may be implemented inside the second housing structure **320**. When the first housing structure **310** and the second housing structure **320** are in a slide-in or slide-out state, the distance (or isolation) between the first antenna **511** and the second antenna **512** may vary. For example, the distance between the first antenna **511** and the second antenna **512** may decrease when the first housing structure **310** and the second housing structure **320** are in the slide-in state. If the distance between the first housing structure **310** and the second housing structure **320** is reduced in the state in which the electronic device **410** operates in the STR mode (or in the state in which data having a high MCS level is transmitted or received), the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **511** and the second antenna **512** is reduced.

(190) The distance **711** between the first antenna **511** and the second antenna **512** may vary as the second housing **320** slides into (or slides out of) the first housing **310**. For example, the distance **711** between the first antenna **511** and the second antenna **512** when the second housing **320** maximally slides out of the first housing **310** may be greater than the distance **712** between the first antenna **511** and the second antenna **512** when the second housing **320** maximally slides into the first housing **310**. That is, the distances **711** and **712** may be correlated with the degree to which the second housing **320** slides in (or slides out).

(191) Based on whether or not the degree to which the second housing **320** slides in satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**. The specified condition may include a condition in which the degree to which the second housing **320** slides in is greater than or equal to a specified value.

(192) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(193) Based on the case where the degree to which the second housing **320** slides in satisfies a specified condition, the electronic device **410** may transmit, to the external electronic device **420**, a signal including information instructing to switch to any one of the STR mode and/or the non-STR mode.

(194) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(195) Based on the case where the degree to which the second housing **320** slides in satisfies a specified condition, the electronic device **410** may transmit a signal for changing the MCS level to the external electronic device **420**.

(196) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless

communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(197) Based on the case where the degree to which the second housing **320** slides in satisfies a specified condition, the electronic device **410** may transmit a signal for changing the operation mode of short-range wireless communication to the external electronic device **420**.

(198) An electronic device according to various embodiments of the disclosure may include: a foldable housing including a first housing structure and a second housing structure, the first housing structure and the second housing structure being foldable around a hinge structure; a first antenna disposed in the first housing structure; a second antenna disposed in the second housing structure; a communication circuit electrically connected to the first antenna and/or the second antenna, and configured to transmit and receive data through a first link and/or a second link established between an external electronic device and the electronic device; and a processor operatively connected to the communication circuit, wherein the processor may be configured to identify whether or not an angle between the first housing structure and the second housing structure satisfies a specified condition and control the communication circuit to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link and the second link, based on whether or not the angle satisfies the specified condition.

(199) In an electronic device according to various embodiments of the disclosure, the processor may be configured to select one of a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is not able to be received through the second link while transmitting data through the first link, based on the case where the angle satisfies the specified condition, and control the communication circuit to transmit the signal including information indicating the selected mode through the at least one link.

(200) In an electronic device according to various embodiments of the disclosure, the processor may be configured to control the communication circuit to transmit a changed signal after changing information indicating the mode, which is included in the signal, to indicate the selected mode.

(201) In an electronic device according to various embodiments of the disclosure, the processor may be configured to change a modulation and coding scheme (MCS), based on the case where the angle satisfies the specified condition.

(202) In an electronic device according to various embodiments of the disclosure, the processor may be configured to change a bandwidth of the first link and/or the second link, based on the case where the angle satisfies the specified condition.

(203) In an electronic device according to various embodiments of the disclosure, the specified condition may include a condition related to a distance between the first antenna and the second antenna.

(204) In an electronic device according to various embodiments of the disclosure, the processor may be configured to determine whether or not to transmit the signal, based on whether or not a difference between a frequency band corresponding to the first link and a frequency band corresponding to the second link is greater than or equal to a specified value.

(205) In an electronic device according to various embodiments of the disclosure, the processor may be configured to determine to not transmit the signal, based on identifying that the difference between the frequency band corresponding to the first link and the frequency band corresponding to the second link is greater than or equal to the specified value.

(206) In an electronic device according to various embodiments of the disclosure, the processor may be configured to determine to not transmit the signal, based on the difference between the frequency band corresponding to the first link and the frequency band corresponding to the second link being less than or equal to the specified value and based on the case the angle satisfies the specified condition.

(207) In an electronic device according to various embodiments of the disclosure, the foldable

housing may be a housing in which the distance between the first antenna and the second antenna changes while the first housing structure and the second housing structure is folded or unfolded about the hinge structure.

(208) FIG. 8 is an operational flowchart illustrating a method **800** of operating an electronic device according to various embodiments of the disclosure.

(209) According to various embodiments of the disclosure, an electronic device (e.g., the electronic device **410** in FIG. 5), in operation **810**, may identify whether or not an angle (e.g., the angle **621** in FIG. 6B) between a first housing structure (e.g., the first housing structure **210** in FIG. 2A) and a second housing structure (e.g., the second housing structure **220** in FIG. 2A) satisfies a specified condition.

(210) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a foldable housing in which a first housing structure (e.g., the first housing structure **210** in FIG. 2A) and a second housing structure (e.g., the second housing structure **220** in FIG. 2A) are foldable (or rotatable) through a hinge structure. A first antenna **511** may be implemented inside the first housing structure **210**, and a second antenna **512** may be implemented inside the second housing structure **220**. When the first housing structure **210** and the second housing structure **220** are folded or unfolded, the distance (or isolation) between the first antenna **511** and the second antenna **512** may vary. For example, the distance between the first antenna **511** and the second antenna **512** may decrease when the first housing structure **210** and the second housing structure **220** are folded. If the first housing structure **210** and the second housing structure **220** are folded in the state in which the electronic device **410** operates in the STR mode (or in the state in which data having a high MCS level is transmitted or received), the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **511** and the second antenna **512** is reduced.

(211) The electronic device **410** may measure an angle between the first housing structure **210** and the second housing structure **220**, based on a sensor, and identify whether or not the angle satisfies a specified condition. The specified condition may indicate a condition related to the distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may increase as the angle between the first housing structure **210** and the second housing structure **220** increases. The distance between the first antenna **511** and the second antenna **512** may decrease as the angle between the first housing structure **210** and the second housing structure **220** decreases.

(212) According to various embodiments of the disclosure, in operation **820**, the electronic device **410** may transmit a signal related to a change in the operation of short-range wireless communication, based on whether or not the angle **621** satisfies a specified condition.

(213) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(214) According to an embodiment, the electronic device **410** may control the communication circuit **520** to operate in the STR mode when the foldable housing is in the unfolded state. The electronic device **410** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to switch from the STR mode to the non-STR mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating switching to the non-STR mode to the external electronic device **420**. The electronic device **410** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the

management frame (or action frame), to a value indicating the non-STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by switching to the non-STR mode.

(215) According to an embodiment, the electronic device **410** may control the communication circuit **520** to operate in the non-STR mode when the foldable housing is in the folded state. The electronic device **410** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to switch from the non-STR mode to the STR mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating switching to the STR mode to the external electronic device **420**. The electronic device **410** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by switching to the STR mode that provides higher performance.

(216) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(217) According to an embodiment, the electronic device **410** may produce data corresponding to a first level of the MCS level in the unfolded state of the foldable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the electronic device **410** may receive data corresponding to the first level of the MCS level in the unfolded state of the foldable housing and decode the received data. The electronic device **410** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may perform a series of operations for setting the MCS level to a second level lower than the first level. The electronic device **410** may control the communication circuit **520** to transmit information for reducing the MCS level to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations for reducing the MCS level. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by transmitting or receiving data having a low MCS level.

(218) According to an embodiment, the electronic device **410** may produce data corresponding to a second level of the MCS level, which is lower than the first level, in the folded state of the foldable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the electronic device **410** may receive data corresponding to the first level of the MCS level in the unfolded state of the foldable housing and decode the received data. The electronic

device **410** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may perform a series of operations to increase the MCS level. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by transmitting and receiving data a higher MCS level that provides higher performance. (219) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(220) According to an embodiment, the electronic device **410**, in the unfolded state of the foldable housing, may control the communication circuit **520** to operate in a first operation mode (e.g., the number of spatial streams having a first value, the number of space time streams having a second value, and/or a channel width having a first size). The electronic device **410** may detect that the foldable housing is folded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is less than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may perform a series of operations to operate in a second operation mode (e.g., the number of spatial streams having a third value less than the first value, the number of space time streams having a fourth value less than the second value, and/or a channel width having a second size smaller than the first size). The electronic device **410** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the second operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the first operation mode to the second operation mode. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the foldable housing is folded by operating in the second operation mode that requires a smaller distance between the first antenna **511** and the second antenna **512**.

(221) According to an embodiment, the electronic device **410**, in the folded state of the foldable housing, may control the communication circuit **520** to operate in the second operation mode. The electronic device **410** may detect that the foldable housing is unfolded and identify whether or not the angle of the first housing structure **210** and the second housing structure **220** satisfies a specified condition. The specified condition may include whether or not the angle of the first housing structure **210** and the second housing structure **220** is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may perform a series of operations to switch to the first operation mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the first operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the second operation mode to the first operation mode. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the

distance between the first antenna **511** and the second antenna **512** increases as the foldable housing is unfolded by operating in the first operation mode that provides higher performance.

(222) FIG. **9** is an operational flowchart illustrating a method **900** of operating an electronic device according to various embodiments of the disclosure.

(223) According to various embodiments of the disclosure, in operation **910**, an electronic device (e.g., the electronic device **410** in FIG. **5**) may identify whether or not the degree to which a second housing structure (e.g., the second housing structure **320** in FIG. **2A**) slides in satisfies a specified condition.

(224) According to various embodiments of the disclosure, the electronic device **410** may be implemented in the form of a rollable housing (or a slidable housing) in which a first housing structure (e.g., the first housing **310** in FIG. **3A**) and a second housing structure (e.g., the second housing **320** in FIG. **3A**) are coupled to be movable in a specified direction and within a specified distance. A first antenna **511** may be implemented inside the first housing structure **310**, and a second antenna **512** may be implemented inside the second housing structure **320**. When the first housing structure **310** and the second housing structure **320** are in a slide-in or slide-out state, the distance (or isolation) between the first antenna **511** and the second antenna **512** may vary. For example, the distance between the first antenna **511** and the second antenna **512** may decrease when the first housing structure **310** and the second housing structure **320** are in the slide-in state. If the distance between the first housing structure **310** and the second housing structure **320** is reduced in the state in which the electronic device **410** operates in the STR mode (or in the state in which data having a high MCS level is transmitted or received), the STR mode of the electronic device **410** may not be effectively operated as the distance between the first antenna **511** and the second antenna **512** is reduced.

(225) The electronic device **410** may detect the degree to which the second housing structure **320** slides into (or the degree to which the second housing structure slides out of) the first housing structure **310**. The electronic device **410** may detect the degree to which the second housing structure **320** slides in by a method of receiving, from the application processor **120**, information related to the degree to which the second housing structure **320** slides in.

(226) The electronic device **410** may measure the degree to which the second housing structure **320** slides in, based on a sensor, and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may indicate a condition related to the distance between the first antenna **511** and the second antenna **512**. The distance between the first antenna **511** and the second antenna **512** may be reduced as the degree to which the second housing structure **320** slides in increases. The distance between the first antenna **511** and the second antenna **512** may increase as the degree to which the second housing structure **320** slides out increases.

(227) According to various embodiments of the disclosure, in operation **920**, the electronic device **410**, based on whether or not the degree of sliding-in satisfies a specified condition, may transmit a signal related to a change in the operation of short-range wireless communication.

(228) Based on whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to transmit a signal related to a change in the operation of short-range wireless communication through at least one of the first link **431** and/or the second link **432**.

(229) The signal related to a change in the operation of short-range wireless communication may include information instructing to switch to any one of the STR mode and/or the non-STR mode. The information instructing to switch to any one of the STR mode and/or the non-STR mode may be included in an action frame among management frames defined in IEEE 802.11.

(230) According to an embodiment, the electronic device **410** may control the communication circuit **520** to operate in the STR mode in the unrolled state of the rollable housing. The electronic device **410** may detect that the second housing structure **320** slides into the first housing structure

310 and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include a condition in which the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to switch from the STR mode to the non-STR mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating switching to the non-STR mode to the external electronic device **420**. The electronic device **410** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the non-STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by switching to the non-STR mode.

(231) According to an embodiment, the electronic device **410** may control the communication circuit **520** to operate in the non-STR mode when the rollable housing is in the slide-in state. The electronic device **410** may detect sliding-out of the rollable housing and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include a condition in which the degree to which the second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the electronic device **410** may control the communication circuit **520** to switch from the non-STR mode to the STR mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating switching to the STR mode to the external electronic device **420**. The electronic device **410** may change a value of a field (e.g., NSTR bitmap) indicating the STR mode, which is included in the management frame (or action frame), to a value indicating the STR mode and control the communication circuit **520** to transmit a signal including the changed field to the external electronic device **420**. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by switching to the STR mode that provides higher performance.

(232) The signal related to a change in the operation of short-range wireless communication may include information for changing an MCS level. The information for changing an MCS level (e.g., high efficiency adaptation (HEA) control) may be included in a control frame defined in IEEE 802.11. According to an embodiment, the information for changing an MCS level may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(233) According to an embodiment, the electronic device **410** may produce data corresponding to a first level of the MCS level in the slide-out state of the rollable housing and control the communication circuit **520** to transmit the produced data. Alternatively or additionally, the electronic device **410** may receive data corresponding to the first level of the MCS level in the slide-out state of the rollable housing and decode the received data. The electronic device **410** may detect that the second housing structure **320** slides in and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the electronic device **410** may perform a series of operations to set the MCS level to a second level lower than the first level. The electronic device **410** may control the communication circuit **520** to transmit information for reducing the MCS level to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to reduce the MCS level. The electronic device **410** may reduce

degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by transmitting or receiving data having a low MCS level.

(234) According to an embodiment, the electronic device **410** may produce data corresponding to a second level of the MCS level, which is lower than the first level, when the rollable housing is in the slide-in state, and control the communication circuit **520** to transmit the produced data.

Alternatively or additionally, the electronic device **410** may receive data corresponding to the second level of the MCS level when the rollable housing is in the slide-in state and decode the received data. The electronic device **410** may detect that the second housing structure **320** slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the electronic device **410** may perform a series of operations to increase the MCS level. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by transmitting and receiving data a higher MCS level that provides higher performance.

(235) The signal related to a change in the operation of short-range wireless communication may include information for changing an operation mode of short-range wireless communication. The operation mode of short-range wireless communication may include a channel width, the number of space time streams (N.sub.STS), and/or the number of spatial streams (N.sub.SS) of short-range wireless communication (or the first link **341** and/or the second link **342**). According to an embodiment, the information for changing the operation mode of short-range wireless communication may be included in a header of a signal transmitted through a medium access control (MAC) layer.

(236) According to an embodiment, the electronic device **410**, when the rollable housing is in the slide-out state, may control the communication circuit **520** to operate in a first operation mode (e.g., the number of spatial streams having a first value, the number of space time streams having a second value, and/or a channel width having a first size). The electronic device **410** may detect that the second housing structure **320** slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the second housing structure **320** slides in is greater than or equal to a specified value. Based on the case where the angle satisfies a specified condition, the electronic device **410** may perform a series of operations to operate in a second operation mode (e.g., the number of spatial streams having a third value less than the first value, the number of space time streams having a fourth value less than the second value, and/or a channel width having a second size smaller than the first size). The electronic device **410** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the second operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the first operation mode to the second operation mode. The electronic device **410** may reduce degradation of the quality of short-range wireless communication caused by a decrease in the distance between the first antenna **511** and the second antenna **512** as the rollable housing slides in by operating in the second operation mode that requires a smaller distance between the first antenna **511** and the second antenna **512**.

(237) According to an embodiment, the electronic device **410** may control the communication circuit **520** to operate in the second operation mode when the rollable housing is in the slide-in state. The electronic device **410** may detect that the second housing structure **320** slides out and identify whether or not the degree to which the second housing structure **320** slides in satisfies a specified condition. The specified condition may include whether or not the degree to which the

second housing structure **320** slides in is less than or equal to a specified value. Based on the case where the degree of sliding-in satisfies a specified condition, the electronic device **410** may perform a series of operations to switch to the first operation mode. The electronic device **410** may control the communication circuit **520** to transmit information indicating that the electronic device **410** operates in the first operation mode to the external electronic device **420**. The external electronic device **420** and the electronic device **410** may perform a series of operations to switch from the second operation mode to the first operation mode. Through the above method, the electronic device **410** may improve the quality of short-range wireless communication when the distance between the first antenna **511** and the second antenna **512** increases as the rollable housing slides out by operating in the first operation mode that provides higher performance.

(238) A method of operating an electronic device according to various embodiments of the disclosure may include identifying whether or not an angle between a first housing structure including a first antenna and a second housing structure including a second antenna satisfies a specified condition and transmitting a signal related to a change in the operation of short-range wireless communication established between an external electronic device and the electronic device through at least one of a first link and a second link, based on whether or not the angle satisfies the specified condition.

(239) The method of operating an electronic device according to various embodiments of the disclosure may further include selecting one of a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is not able to be received through the second link while transmitting data through the first link, based on the case where the angle satisfies the specified condition, and transmitting the signal including information indicating the selected mode through the at least one link.

(240) The method of operating an electronic device according to various embodiments of the disclosure may further include transmitting a changed signal after changing information indicating the mode, which is included in the signal, to indicate the selected mode.

(241) The method of operating an electronic device according to various embodiments of the disclosure may further include changing a modulation and coding scheme (MCS), based on the case where the angle satisfies the specified condition.

(242) The method of operating an electronic device according to various embodiments of the disclosure may further include changing a bandwidth of the first link and/or the second link, based on the case where the angle satisfies the specified condition.

(243) In the method of operating an electronic device according to various embodiments of the disclosure, the specified condition may include a condition related to a distance between the first antenna and the second antenna.

(244) The method of operating an electronic device according to various embodiments of the disclosure may further include determining whether or not to transmit the signal, based on whether or not a difference between a frequency band corresponding to the first link and a frequency band corresponding to the second link is greater than or equal to a specified value.

(245) In the method of operating an electronic device according to various embodiments of the disclosure, the determining whether or not to transmit the signal may include determining to not transmit the signal, based on identifying that the difference between the frequency band corresponding to the first link and the frequency band corresponding to the second link is greater than or equal to the specified value.

(246) In the method of operating an electronic device according to various embodiments of the disclosure, the determining whether or not to transmit the signal may include determining to not transmit the signal, based on the difference between the frequency band corresponding to the first link and the frequency band corresponding to the second link being less than or equal to the specified value and based on the case the angle satisfies the specified condition.

(247) In the method of operating an electronic device according to various embodiments of the

disclosure, the electronic device may include a foldable housing in which the distance between the first antenna and the second antenna changes while the first housing structure and the second housing structure is folded or unfolded about a hinge structure.

(248) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(249) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(250) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(251) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(252) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least

temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(253) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

Claims

1. An electronic device comprising: a hinge structure; a foldable housing comprising a first housing structure and a second housing structure that are configured to be foldable relative to each other around the hinge structure; a first antenna disposed in the first housing structure; a second antenna disposed in the second housing structure; a communication circuit electrically connected to the first antenna and the second antenna, and configured to transmit and receive data through a first link and a second link established between an external electronic device and the electronic device; and a processor operatively connected to the communication circuit, wherein the processor is configured to: identify whether an angle between the first housing structure and the second housing structure satisfies a specified condition, the specified condition being related to a distance between the first antenna and the second antenna, control the communication circuit to transmit, to the external electronic device through at least one of the first link and the second link, a signal related to a change in an operation of short-range wireless communication, based at least on the angle satisfying the specified condition, the signal instructing the external electronic device to switch to the changed operation mode, and perform, through the first antenna and the second antenna, the operation of the short-range wireless communication in the changed operation mode.
2. The electronic device of claim 1, wherein the processor is further configured to: select a mode from among a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is prevented from being received through the second link while transmitting data through the first link, based on identifying that the angle satisfies the specified condition; and control the communication circuit to transmit, through the at least one of the first link and the second link, the signal comprising information indicating the selected mode.
3. The electronic device of claim 2, wherein the processor is further configured to control the communication circuit to transmit, through the at least one of the first link and the second link, a changed signal after changing information indicating the mode, which is included in the signal, to indicate the selected mode.
4. The electronic device of claim 1, wherein the processor is further configured to change a modulation and coding scheme (MCS) of the at least one of the first link and the second link, based on that the angle satisfies the specified condition.
5. The electronic device of claim 1, wherein the processor is further configured to change a bandwidth of the at least one of the first link and the second link, based on that the angle satisfies the specified condition.
6. The electronic device of claim 1, wherein the specified condition comprises a condition related

to the distance between the first antenna and the second antenna.

7. The electronic device of claim 1, wherein the processor is further configured to determine whether to transmit the signal, based on whether a difference between a first frequency band corresponding to the first link and a second frequency band corresponding to the second link is greater than or equal to a specified value.

8. The electronic device of claim 7, wherein the processor is further configured to prevent transmission of the signal, based on identifying that the difference between the first frequency band and the second frequency band is greater than or equal to the specified value.

9. The electronic device of claim 7, wherein the processor is further configured to prevent transmission of the signal, based on that the difference between the first frequency band corresponding to the first link and the second frequency band is less than the specified value and the angle satisfies the specified condition.

10. The electronic device of claim 1, wherein the distance between the first antenna and the second antenna changes according to a change in the angle between the first housing structure and the second housing structure due to the first housing structure and the second housing structure being folded or unfolded about the hinge structure.

11. A method of operating an electronic device, the method comprising: identifying whether an angle between a first housing structure comprising a first antenna and a second housing structure comprising a second antenna satisfies a specified condition, the specified condition being related to a distance between the first antenna and the second antenna; transmitting, to an external electronic device, a signal related to a change in an operation of short-range wireless communication established between the external electronic device and the electronic device through at least one of a first link and a second link, based at least on the angle satisfying the specified condition, the signal instructing the external electronic device to switch to the changed operation mode; and performing, through the first antenna and the second antenna, the operation of the short-range wireless communication in the changed operation mode.

12. The method of claim 11, further comprising: selecting a mode from among a first mode in which data is transmitted through the first link and in which data is received through the second link, and a second mode in which data is prevented from being received through the second link while transmitting data through the first link, based on that the angle satisfies the specified condition; and transmitting, through the at least one of the first link and the second link, the signal comprising information indicating the selected mode.

13. The method of claim 12, further comprising transmitting, through the at least one of the first link and the second link, a changed signal after changing information indicating the mode, which is included in the signal, to indicate the selected mode.

14. The method of claim 11, further comprising changing a modulation and coding scheme (MCS) of the at least one of the first link and the second link, based on that the angle satisfies the specified condition.

15. The method of claim 11, further comprising changing a bandwidth of the at least one of the first link and the second link, based on that the angle satisfies the specified condition.

16. The method of claim 11, wherein the specified condition comprises a condition related to the distance between the first antenna and the second antenna.

17. The method of claim 11, further comprising determining whether to transmit the signal, based on whether a difference between a first frequency band corresponding to the first link and a second frequency band corresponding to the second link is greater than or equal to a specified value.

18. The method of claim 17, wherein the determining of whether to transmit the signal comprises preventing transmission of the signal, based on identifying that the difference between the first frequency band and the second frequency band is greater than or equal to the specified value.

19. The method of claim 17, wherein the determining of whether to transmit the signal comprises preventing transmission of the signal, based on that the difference between the first frequency band

and the second frequency band is less than the specified value and identifying that the angle satisfies the specified condition.

20. The method of claim 11, wherein the distance between the first antenna and the second antenna changes according to a change in the angle between the first housing structure and the second housing structure due to the first housing structure and the second housing structure being folded or unfolded about a hinge structure of the electronic device.
