

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418757
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Milne; James R. et al.

Hearing aid proximity detection and action to optimize a call

Abstract

A first hearing aid includes a first sensor that receives first sensor data associated with a mobile device. The first hearing aid determines, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold. The first hearing aid changes a first preset associated with the first hearing aid to a second preset. A second hearing aid changes a first preset associated with the second hearing aid to a third preset.

Inventors:	Milne; James R. (Romona, CA), Clay; William (San Diego, CA)
Applicant:	Sony Group Corporation (Tokyo, JP)
Family ID:	1000008821985
Assignee:	SONY GROUP CORPORATION (Tokyo, JP)
Appl. No.:	18/119481
Filed:	March 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240305936 A1	Sep. 12, 2024

Publication Classification

Int. Cl.: H04R25/00 (20060101)

U.S. Cl.:

CPC H04R25/552 (20130101); H04R2225/55 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9942670	12/2017	Dickel et al.	N/A	N/A
11146898	12/2020	Neumeyer	N/A	H04R 25/554
2009/0154742	12/2008	Rasmussen	381/312	H04R 25/453
2021/0058105	12/2020	Landry	N/A	H04W 12/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
708609	12/2014	CH	N/A

Primary Examiner: Huber; Paul W

Attorney, Agent or Firm: Trellis IP Law Group, PC

Background/Summary

BACKGROUND

(1) Due to cost constraints, some hearing aids cannot connect to a mobile phone via Bluetooth or WiFi. As a result, the hearing aids are unable to determine when a mobile phone is near the hearing aid. Hearing aids have different presets based on particular situations. For example, the presets for when a hearing aid is detecting noise in a room is different than the presets for when a hearing aid is used to detect noise emitted from a mobile phone that is next to the user's ear.

SUMMARY

(2) A computer-implemented method includes receiving, at a first sensor associated with a first hearing aid, first sensor data associated with a mobile device. The method further includes determining, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold. The method further includes changing a first preset associated with the first hearing aid to a second preset. The method further includes changing a first preset associated with a second hearing aid to a third preset.

(3) In some embodiments, the first preset associated with the first hearing aid is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise. In some embodiments, the first preset associated with the first hearing aid includes a far-field microphone setting and the second preset includes a near-field microphone setting. In some embodiments, the method further includes receiving, at a second sensor associated with the second hearing aid, second sensor data associated with the mobile device and determining, based on the second sensor data, that a second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold, wherein changing the first preset associated with the second hearing aid occurs responsive to the determining. In some embodiments, the first preset associated with the second hearing aid is an ambient noise setting and the third preset is noise cancellation. In some embodiments, the method further includes determining that the first distance between the first hearing aid and the mobile device meets the first distance threshold and changing the second preset

associated with the first hearing aid to the first preset. In some embodiments, the method further includes determining that the second distance between the second hearing aid and the mobile device is below the first distance threshold and changing the third preset associated with the second hearing aid to the second preset. In some embodiments, first sensor is selected from the group of an ultrasonic sensor, radar, an inductive proximity sensor, a photoelectric sensor, and combinations thereof.

(4) A system includes a first hearing aid that includes one or more first processors and first logic encoded in one or more first non-transitory media for execution by the one or more first processors and when executed operable to: receive first sensor data associated with a mobile device, determine, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold, and change a first preset associated with the first hearing aid to a second preset. The system further includes a second hearing aid that includes one or more second processors and second logic encoded in one or more second non-transitory media for execution by the one or more first processors and when executed operable to change a first preset associated with a second hearing aid to a third preset.

(5) In some embodiments, wherein the first preset associated with the first hearing aid is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise. In some embodiments, the first preset associated with the first hearing aid includes a far-field microphone setting and the second preset includes a near-field microphone setting. In some embodiments, the second logic is further operable to: receive second sensor data associated with the mobile device and determine based on the second sensor data, that a second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold, wherein changing the first preset associated with the second hearing aid occurs responsive to the determining. In some embodiments, the first preset associated with the second hearing aid is an ambient noise setting and the third preset is noise cancellation. In some embodiments, the second logic is further operable to: determine that the second distance between the second hearing aid and the mobile device is below the first distance threshold and change the third preset associated with the second hearing aid to the second preset.

(6) Software encoded in one or more non-transitory computer-readable media for execution by the one or more processors and when executed is operable to: receive, at a first sensor associated with a first hearing aid, first sensor data associated with a mobile device; determine, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold; change a first preset associated with the first hearing aid to a second preset; and change a first preset associated with a second hearing aid to a third preset. In some embodiments, the first preset associated with the first hearing aid is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise. In some embodiments, the first preset associated with the first hearing aid includes a far-field microphone setting and the second preset includes a near-field microphone setting. In some embodiments, the software is further operable to: receive, at a second sensor associated with the second hearing aid, second sensor data associated with the mobile device and determine, based on the second sensor data, that a second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold, wherein changing the first preset associated with the second hearing aid occurs responsive to the determining. In some embodiments, the first preset associated with the second hearing aid is an ambient noise setting and the third preset is noise cancellation.

(7) As a result of the techniques described below, the hearing aids advantageously change the presets for the hearing aids when the mobile device is within proximity without requiring a Bluetooth connection. The hearing aids are able to avoid feedback and control for loudness during phone calls.

(8) A further understanding of the nature and the advantages of particular embodiments disclosed herein may be realized by reference of the remaining portions of the specification and the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example environment according to some embodiments described herein.
- (2) FIG. 2 is a block diagram of an example computing device according to some embodiments described herein.
- (3) FIG. 3 includes illustrations of how different sensors are used to determine a distance between a hearing aid and a mobile device according to some embodiments described herein.
- (4) FIG. 4 is an illustration of a user with hearing aids and a mobile device according to some embodiments described herein.
- (5) FIG. 5 illustrates a flowchart of a method to determine a distance between a hearing aid and a mobile device according to some embodiments described herein.
- (6) FIG. 6 illustrates a flowchart of another method to determine a distance between a hearing aid and a mobile device according to some embodiments described herein.

DETAILED DESCRIPTION OF EMBODIMENTS

(7) Example Environment **100**

(8) FIG. 1 illustrates a block diagram of an example environment **100**. In some embodiments, the environment **100** includes hearing aids **120**, a mobile device **115**, and a server **101**. A user **125** is associated with the mobile device **115** and the hearing aids **120**. In some embodiments, the environment **100** may include other servers or devices not shown in FIG. 1. In FIG. 1 and the remaining figures, a letter after a reference number, e.g., “**103a**,” represents a reference to the element having that particular reference number (e.g., a hearing application **103a** stored on the mobile device **115**). A reference number in the text without a following letter, e.g., “**103**,” represents a general reference to embodiments of the element bearing that reference number (e.g., any hearing application).

(9) The hearing aids **120** may include a processor, a memory, a microphone, and a speaker. The hearing aids **120** may include two hearing aids, such as a hearing aid for the left ear and a hearing aid for the right ear. The hearing aids **120** may be in-ear hearing aids or external hearing aids. More specifically, the hearing aids **120** may include devices that are invisible in the canal, completely in the canal, in the canal, half shell, full shell, behind the ear, or other variations.

(10) In some embodiments, the hearing aids **120** includes a hearing application **103a** that performs hearing tests. For example, the user **125** may be asked to identify sounds emitted by speakers of the hearing aids **120** and the user may provide user input, for example, by pressing a button on the hearing aids **120** or by interacting with the mobile device **115**.

(11) In some embodiments, the hearing aids **120** communicate with a hearing application **103b** stored on the mobile device **115**. During testing, the hearing aids **120** receive instructions from the mobile device **115** to emit test sounds at particular decibel levels. In some embodiments, the instructions are provided in the form of high-frequency chirps emitted by the mobile device **115**. The user may be asked to identify on a user interface generated by the mobile device **115** when they hear sounds generated by each of the hearing aids **120**. Once testing is complete, the hearing aids **120** store a hearing profile that includes instructions for how to modify sound based on different factors, such as frequencies, types of sounds, etc. In some embodiments, the hearing aids **120** also store one or more presets, such as a first preset that includes an ambient noise setting and a far-field microphone setting, a second preset that includes a mix of ambient noise and noise

cancellation and a near-field microphone setting, and a third preset that includes noise cancellation.

(12) The hearing application **103a** on the hearing aids **120** determines when to switch between presets. A sensor associated with the first hearing aid **120a** receives sensor data associated with a mobile device **115**. The sensor may include an ultrasonic sensor, radar, an inductive proximity sensor, a photoelectric sensor, or a combination of any of those sensors. The hearing application **103a** determines that a first distance between the mobile device **115** and the first hearing aid **120a** is below a first distance threshold. The hearing application **103a** changes a first preset associated with the first hearing aid **120a** to a second preset. For example, the first preset is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation.

(13) In some embodiments, a sensor associated with the second hearing aid **120b** determines, based on the sensor data, that a second distance between the mobile device **115** and the second hearing aid **120b** exceeds the first distance threshold and is below a second distance threshold. The hearing application **103a** changes a first preset associated with the second hearing aid **120b** to a third preset. For example, the first preset is an ambient noise setting and the third preset is noise cancellation. As a result, the user **125** is able to hear sounds from the mobile device **115** more clearly with the first hearing aid **120a** based on the second preset and noise is blocked from the second hearing aid **120b** based on the third preset.

(14) The mobile device **115** may be a computing device that includes a memory, a hardware processor, and a hearing application **103b**. The mobile device **115** may include a smart phone, a mobile telephone, a tablet computer, a wearable device (e.g., a smart watch), a mobile email device, or another electronic device capable of accessing a network **105** to communicate with the server **101** and capable of communicating with the hearing aids **120**.

(15) In the illustrated implementation, mobile device **115** is coupled to the network **105** via signal line **108**. Signal line **108** may be a wired connection, such as Ethernet, coaxial cable, fiber-optic cable, etc., or a wireless connection, such as Wi-Fi®, Bluetooth®, or other wireless technology. The mobile device **115** is used by way of example. While FIG. 1 illustrates one mobile device **115**, the disclosure applies to a system architecture having one or more mobile devices **115**.

(16) The hearing application **103b** on the mobile device **115** may implement hearing tests and generate a hearing profile based on the hearing test. In some embodiments, the hearing application **103b** implements the hearing tests through a series of high-frequency chirps that are received by the hearing aids **120**.

(17) The server **101** may include a processor, a memory, and network communication hardware. In some embodiments, the server **101** is a hardware server. The server **101** is communicatively coupled to the network **105** via signal line **102**. Signal line **102** may be a wired connection, such as Ethernet, coaxial cable, fiber-optic cable, etc., or a wireless connection, such as Wi-Fi®, Bluetooth®, or other wireless technology.

(18) In some embodiments, the server **101** includes a hearing application **103c**. In some embodiments and with user consent, the hearing application **103c** on the server **101** maintains a copy of the hearing profile and the presets.

(19) Example Computing Device **200**

(20) FIG. 2 is a block diagram of an example computing device **200** that may be used to implement one or more features described herein. The computing device **200** can be any suitable computer system, server, or other electronic or hardware device. In one example, the computing device **200** includes the hearing aids **120** illustrated in FIG. 1.

(21) In some embodiments, computing device **200** includes a processor **235**, a memory **237**, an Input/Output (I/O) interface **239**, a battery **241**, a microphone **243**, an amplifier **245**, a speaker **247**, a sensor set **249**, and a storage device **251**. Although particular components of the computing device **200** are illustrated, other components may be added or removed.

(22) The processor **235** may be coupled to a bus **218** via signal line **222**, the memory **237** may be coupled to the bus **218** via signal line **224**, the I/O interface **239** may be coupled to the bus **218** via

signal line **226**, the battery **241** may be coupled to the bus **218** via signal line **228**, the microphone **243** may be coupled to the bus **218** via signal line **230**, the amplifier **245** may be coupled to the bus **218** via signal line **232**, the speaker **247** may be coupled to the bus **218** via signal line **334**, the sensor set **249** may be coupled to the bus **218** via signal line **336**, and the storage device **251** may be coupled to the bus **218** via signal line **338**.

(23) The processor **235** can be one or more processors and/or processing circuits to execute program code and control basic operations of the computing device **200**. A processor includes any suitable hardware system, mechanism or component that processes data, signals or other information. A processor may include a system with a general-purpose central processing unit (CPU) with one or more cores (e.g., in a single-core, dual-core, or multi-core configuration), multiple processing units (e.g., in a multiprocessor configuration), a graphics processing unit (GPU), a field-programmable gate array (FPGA), an application-specific integrated circuit (ASIC), a complex programmable logic device (CPLD), dedicated circuitry for achieving functionality, or other systems. A computer may be any processor in communication with a memory.

(24) The memory **237** is typically provided in computing device **200** for access by the processor **235** and may be any suitable processor-readable storage medium, such as random access memory (RAM), read-only memory (ROM), Electrical Erasable Read-only Memory (EEPROM), Flash memory, etc., suitable for storing instructions for execution by the processor or sets of processors, and located separate from processor **235** and/or integrated therewith. Memory **237** can store software operating on the computing device **200** by the processor **235**, including the hearing application **103**.

(25) The I/O interface **239** can provide functions to enable interfacing the computing device **200** with other systems and devices. Interfaced devices can be included as part of the computing device **200** or can be separate and communicate with the computing device **200**. For example, network communication devices, storage devices (e.g., the memory **237** or the storage device **251**), and input/output devices can communicate via I/O interface **239**. In some embodiments, the I/O interface **239** can connect to interface devices such as input devices (keyboard, pointing device, touchscreen, microphone, sensors, etc.) and/or output devices (display **341**, speakers, etc.).

(26) The battery **241** includes hardware for providing energy to the computing device. In some embodiments, the battery **241** may include one or more disposable batteries where the batteries are different depending on the type of hearing aid. For example, behind-the-ear hearing aids may take size 675 batteries and mini-behind-the-ear hearing aids may use 312 batteries. The size of the batteries may also be a compromise between power, length of charge, and weight. In some embodiments, the battery **241** may be a rechargeable battery.

(27) The microphone **243** includes hardware for detecting sounds. For example, the microphone **243** may detect ambient noises, people speaking, music, etc. The microphone **243** converts the detected sounds to an electrical signal that is transmitted to the amplifier **245** via the I/O interface **239**. In some embodiments, the microphone **243** includes different settings, such as far-field detection and near-field detection.

(28) The amplifier **245** includes hardware for modifying portions of the electrical signal based on instructions received from the hearing application **103** via the I/O interface **239** to amplify, reduce, or block certain sounds based on the applicable preset. For example, the hearing application **103** may instruct the amplifier **245** to amplify voices by increasing the gain and reduce sounds from ambient noise by reducing the gain of the amplifier according to a preset that is used when the user is using their mobile device for a phone call.

(29) The speaker **247** includes hardware for receiving the electrical signal from the amplifier **245** and converting the electrical signal into sound waves that are output for the user to hear. For example, the speaker **247** may include a digital to analog converter that converts the electrical signal to sound waves.

(30) The sensor set **249** includes one or more of an ultrasonic sensor, radar, an inductive proximity

sensor, a photoelectric sensor, or other sensors that generate sensor data that is transmitted to the hearing application **103** via the I/O interface **239** to determine the proximity of a mobile device. The sensors in the sensor set **249** may be selected based on balancing the demands of cost, size, performance, amount of digital signal processor (DSP) processing available (i.e., the amount of resources for processing audio that are available), and the amount of central processing unit (CPU) performance available.

(31) An ultrasonic sensor can be used to measure a distance to an object using ultrasonic sound waves. In some embodiments, the ultrasonic sensor emits high-frequency sound waves. When the high-frequency sound waves hit an object, the sound waves are reflected back to the ultrasonic sensor. The hearing application **103** uses the return time of the sound wave to measure the distance between the hearing aid and the mobile device.

(32) Radar can be used to measure a distance to an object using a transmitter that generates high-frequency electromagnetic waves, one or more antennas that transmit the electromagnetic wave and receive the wave, and a receiver that can be used to measure a distance to an object. The antenna transmits the electromagnetic wave until it hits an object. The wave is reflected back and detected by the antenna and used to determine the distance and the angle of the object.

(33) An inductive proximity sensor can be used to measure a distance to an object. The inductive proximity sensor includes a coil and oscillator that create an electromagnetic field. When a metallic object (i.e., a mobile device) enters the operating area it causes a dampening of the oscillation amplitude. The rise or fall of the oscillation amplitude is identified by a threshold circuit that changes the output of the sensor. The distance between the inductive proximity sensor and the mobile device is based on the sensitivity of the inductive proximity sensor to different metals. The inductive proximity sensor may be as small as 3-5 millimeters.

(34) A photoelectric sensor can be used to measure a distance to an object by emitting a beam of light that is used to detect the presence or absence of items and equipment or changes in surface conditions. When the emitted light is interrupted or reflected by the object, the change in light patterns is measured by a receiver and the target object or surface is recognized.

(35) The storage device **251** stores data related to the hearing application **103**. For example, the storage device **251** may store hearing profiles generated by the hearing application **103**, sets of test sounds for testing speech, sets of test sounds for testing music, etc.

(36) The hearing application **103** is stored in the memory **237**. In some embodiments, the hearing aids **120** generate a hearing test that includes instructions for how to modify sound based on different factors, such as frequencies, types of sounds, etc.

(37) In some embodiments, the hearing application **103** receives sensor data that is associated with a mobile device from the sensor set **249**. For example, the sensor data may include sensor data from an ultrasonic sensor about the return time it took a sound wave to be reflected off the mobile device, sensor data from radar about the time taken for the electromagnetic wave to be reflected off the mobile device, sensor data from the inductive proximity sensor indicating that the mobile device is within the operating area, or sensor data from the photoelectric sensor about the time it took light to be reflected off the mobile device.

(38) The hearing application **103** determines, based on the sensor data, a first distance between the first hearing aid and the mobile device. Turning to FIG. **3**, different sensors are illustrated to show how the sensor data is used to determine a distance between a hearing aid and a mobile device.

(39) In a first example **300**, the ultrasonic sensor **305** emits high-frequency sound waves **310** that reach the mobile device **315**. When the sound waves **310** reach the mobile device **315**, the sound waves **310** are reflected back to the ultrasonic sensor **305**. The hearing application **103** uses a time of flight equation to calculate the distance (D) as $\frac{1}{2} \times T \times C$, where T is the time between the emission and reception and C is the sonic speed.

(40) In a second example **325**, the radar includes an antenna **330** that transmits the electromagnetic waves **335** that reach the mobile device **340**. The antenna transmits the electromagnetic wave until

it hits an object. The electromagnetic waves **335** are reflected back (as illustrated by dashed lines) and detected by the antenna **330**. The hearing application **103** calculates the distance (D) as $v \times t$ where v is the speed of light (300,000 km/s) and t is time. In some embodiments, the hearing application **103** uses radar to determine the angle of the mobile device **340**.

(41) In a third example **350**, the inductive proximity sensor **355** can be used to measure a distance to an object. The inductive proximity sensor **355** includes a coil and oscillator that create an electromagnetic field **365**. When the mobile device **360** enters the operating area it causes a dampening of the oscillation amplitude. The distance between the inductive proximity sensor **355** and the mobile device **360** is based on the sensitivity of the inductive proximity sensor **355** to different metals.

(42) In a fourth example **375**, a photoelectric sensor **380** can be used to measure a distance to the mobile device **385** by emitting a beam of light **390** that is used to detect the presence of the mobile device **385**. The beam of light **390** is reflected by the mobile device **385** and the change in light patterns is measured by a receiver that is also part of the photoelectric sensor **380** and the target object or surface is recognized. The hearing application **103** may use a time of flight equation to determine the distance (D).

(43) The hearing application **103** determines, that the first distance between the first hearing aid and the mobile device is below a first distance threshold. The first distance threshold indicates that the mobile device is close enough to the first hearing aid that a preset should be changed. In some embodiments, the first distance threshold is a default setting, such as six inches, two inches, etc. In some embodiments, the user may specify the first distance threshold.

(44) In some embodiments, the hearing application **103** generates a confidence score that determines a likelihood that the mobile device is within proximity to the first hearing aid. The hearing application **103** may not change from a first preset to a second preset unless the confidence score meets a threshold score.

(45) The hearing application **103** changes a first preset associated with the first hearing aid to a second preset. For example, the first preset associated with the first hearing aid is an ambient noise setting that allows the user to hear any noises and adjusts the sounds based on the hearing profile and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise. The first preset may also be referred to as transparency mode, which allows a user to hear all background noises in an environment including ambient noises. The second preset may also include adjustments based on the hearing profile, such as increasing the gain for frequencies where the user experiences hearing loss.

(46) In some embodiments, the mix of ambient noise and noise cancellation includes different types of noise cancellation settings. For example, the noise cancellation could include active cancellation where the microphones and speakers are used to reduce background and surrounding noises; adaptive noise cancellation where the microphones and speakers are used to automatically adjust to the surroundings; transparency mode; or noise cancellation is mixed with ambient sound so that voices are amplified, but not all noises are blocked.

(47) In some embodiments, the first preset includes a far-field microphone setting and the second preset includes a near-field microphone setting. A far-field microphone setting is designed for a microphone to capture noise from larger distances, such as 15 feet or more. A near-field microphone setting is designed for a microphone to capture noise that is closer to the microphone and therefore works best when a user is conducting a phone conversation because it reduces instances where the microphone detects sounds that are farther away.

(48) The hearing application **103** may determine, based on the sensor data, a second distance between the second hearing aid and the mobile device. The hearing application **103** may determine that the second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold. For example, the second distance may be between two inches and 10 inches. This occurs, for example, where the user puts the mobile

device against the ear that has the first hearing aid.

(49) The hearing application **103** changes a first preset associated with the second hearing aid to a third preset. For example, the first preset is an ambient noise setting and the third preset is for noise cancellation. This change advantageously allows the user to hear the phone call using the mobile device in one ear while blocking noise in the other ear to improve the user's ability to focus on the phone call.

(50) In some embodiments, the hearing application **103** subsequently determines that the first distance between the first hearing aid and the mobile device meets the distance threshold. For example, the user moves the phone away from the user's ear because they have completed a phone call or to briefly speak to someone. The hearing application **103** changes the second preset associated with the first hearing aid to the first preset. For example, the hearing application **103** changes the preset from the mix of ambient noise and noise cancellation back to the ambient noise setting.

(51) In some embodiments, the hearing application **103** determines that the second distance between the second hearing aid and the mobile device is below the distance threshold. For example, instead of ending the phone call, the user may switch the phone from being next to the first hearing aid to being next to the second hearing aid. The hearing application **103** changes the third preset associated with the second hearing aid to the second preset. For example, the hearing application **103** changes from noise cancellation to the mix of ambient noise and noise cancellation.

(52) Turning to FIG. 4, a user **405** with hearing aids **410** and a mobile device **415** is illustrated. As the user **405** moves the mobile device **415** to be closer to the first hearing aid **410a**, the hearing application determines whether the first distance **420** between the first hearing aid **410a** and the mobile device **415** is less than a first distance threshold. Once the first distance **420** is less than the first distance threshold, the first hearing aid **410a** changes from a first preset to a second preset.

(53) The second hearing aid **410b** determines whether the second distance **425** between the second hearing aid **410b** and the mobile device **415** meets the first distance threshold and is less than a second distance threshold. If the second distance **425** is between the first distance threshold and the second distance threshold, the second hearing aid **410b** changes from the first preset to a third preset.

(54) Example Methods

(55) FIG. 5 illustrates a flowchart of a method **500** to determine a distance between a hearing aid and a mobile device. The method **500** may be performed by the computing device **200** in FIG. 2. For example, the computing device **200** may be the hearing aids **120** illustrated in FIG. 1. The computing device **200** includes a hearing application **103** that implements the steps described below.

(56) The method **500** may begin at block **502**. At block **502**, a first sensor associated with a first hearing device receives sensor data associated with a mobile device. For example, the sensor data may include sound waves generated by an ultrasonic sensor that are reflected by the mobile device, a high-frequency electromagnetic wave pulse generated by radar that is reflected by the mobile device, detection that the mobile device is within proximity to an electromagnetic field generated by an inductive proximity sensor, or light generated by a photoelectric sensor that is reflected by the mobile device. Block **502** may be followed by block **504**.

(57) At block **504**, it is determined, based on the sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold. Block **504** may be followed by block **506**.

(58) At block **506**, a first preset associated with the first hearing aid is changed to a second preset. For example, the first preset may be changed from an ambient noise setting and a far-field microphone setting to a mix of ambient noise and noise cancellation and a near-field microphone setting. Block **506** may be followed by block **508**.

(59) At block **508**, a first preset associated with a second hearing aid is changed to a third preset.

For example, the first preset may be changed from an ambient noise setting to noise cancellation. (60) FIG. 6 illustrates a flowchart of another method to determine a distance between a hearing aid and a mobile device. The method 600 may be performed by the computing device 200 in FIG. 2. For example, the computing device 200 may be the hearing aids 120 illustrated in FIG. 1. The computing device 200 includes a hearing application 103 that implements the steps described below.

(61) At block 602, a hearing test is implemented for a user. For example, the hearing aids play test sounds at different decibel levels until the user identifies that they can detect the test sounds. Block 602 may be followed by block 604.

(62) At block 604, a first sensor associated with a first hearing aid receives first sensor data associated with a mobile device. Block 604 may be followed by block 606.

(63) At block 606, it is determined, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold. For example, the user may be moving the mobile phone to their first ear to take a phone call. Block 606 may be followed by block 608.

(64) At block 608, a first preset associated with the first hearing aid is changed to a second preset. For example, the first preset is designed for hearing ambient noises in a room as modified for the user based on the hearing test. The second preset may be designed for adding gain to voices so the user can hear the phone call better. Block 608 may be followed by block 610.

(65) At block 610, a second sensor associated with the second hearing aid may receive second sensor data associated with the mobile device. Block 610 may be followed by block 612.

(66) At block 612, it is determined, based on the second sensor data, that a second distance between a second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold. For example, the second hearing aid may determine that the mobile device is within sensing proximity, but is closer to the first ear. Block 612 may be followed by block 614.

(67) At block 614, a first preset associated with the second hearing aid is changed to a third preset. For example, the first preset is designed for hearing ambient noises in a room as modified for the user based on the hearing test. The third preset may be designed for cancelling all noises so that the user can better hear the voices during the phone call.

(68) Although the description has been described with respect to particular embodiments thereof, these particular embodiments are merely illustrative, and not restrictive.

(69) Any suitable programming language can be used to implement the routines of particular embodiments including C, C++, Java, assembly language, etc. Different programming techniques can be employed such as procedural or object oriented. The routines can execute on a single processing device or multiple processors. Although the steps, operations, or computations may be presented in a specific order, this order may be changed in different particular embodiments. In some particular embodiments, multiple steps shown as sequential in this specification can be performed at the same time.

(70) Particular embodiments may be implemented in a computer-readable storage medium for use by or in connection with the instruction execution system, apparatus, system, or device. Particular embodiments can be implemented in the form of control logic in software or hardware or a combination of both. The control logic, when executed by one or more processors, may be operable to perform that which is described in particular embodiments.

(71) Particular embodiments may be implemented by using a programmed general purpose digital computer, by using application specific integrated circuits, programmable logic devices, field programmable gate arrays, optical, chemical, biological, quantum or nanoengineered systems, components and mechanisms may be used. In general, the functions of particular embodiments can be achieved by any means as is known in the art. Distributed, networked systems, components, and/or circuits can be used. Communication, or transfer, of data may be wired, wireless, or by any

other means.

(72) It will also be appreciated that one or more of the elements depicted in the drawings/figures can also be implemented in a more separated or integrated manner, or even removed or rendered as inoperable in certain cases, as is useful in accordance with a particular application. It is also within the spirit and scope to implement a program or code that can be stored in a machine-readable medium to permit a computer to perform any of the methods described above.

(73) A “processor” includes any suitable hardware and/or software system, mechanism or component that processes data, signals or other information. A processor can include a system with a general-purpose central processing unit, multiple processing units, dedicated circuitry for achieving functionality, or other systems. Processing need not be limited to a geographic location, or have temporal limitations. For example, a processor can perform its functions in “real time,” “offline,” in a “batch mode,” etc. Portions of processing can be performed at different times and at different locations, by different (or the same) processing systems. Examples of processing systems can include servers, clients, end mobile devices, routers, switches, networked storage, etc. A computer may be any processor in communication with a memory. The memory may be any suitable processor-readable storage medium, such as random-access memory (RAM), read-only memory (ROM), magnetic or optical disk, or other non-transitory media suitable for storing instructions for execution by the processor.

(74) As used in the description herein and throughout the claims that follow, “a”, “an”, and “the” includes plural references unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

(75) Thus, while particular embodiments have been described herein, latitudes of modification, various changes, and substitutions are intended in the foregoing disclosures, and it will be appreciated that in some instances some features of particular embodiments will be employed without a corresponding use of other features without departing from the scope and spirit as set forth. Therefore, many modifications may be made to adapt a particular situation or material to the essential scope and spirit.

Claims

1. A computer-implemented method comprising: receiving, at a first sensor associated with a first hearing aid, first sensor data associated with a mobile device; determining, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold; changing a first preset associated with the first hearing aid to a second preset, wherein the first preset associated with the first hearing aid is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise; and changing a first preset associated with a second hearing aid to a third preset.
2. The method of claim 1, wherein the first preset associated with the first hearing aid includes a far-field microphone setting and the second preset includes a near-field microphone setting.
3. The method of claim 1, further comprising: receiving, at a second sensor associated with the second hearing aid, second sensor data associated with the mobile device; and determining, based on the second sensor data, that a second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold, wherein changing the first preset associated with the second hearing aid occurs responsive to the determining.
4. The method of claim 3, wherein the first preset associated with the second hearing aid is an ambient noise setting and the third preset is noise cancellation.
5. The method of claim 3, further comprising: determining that the first distance between the first hearing aid and the mobile device meets the first distance threshold; and changing the second

preset associated with the first hearing aid to the first preset.

6. The method of claim 5, further comprising: determining that the second distance between the second hearing aid and the mobile device is below the first distance threshold; and changing the third preset associated with the second hearing aid to the second preset.

7. The method of claim 1, wherein the first sensor is selected from a group of an ultrasonic sensor, radar, an inductive proximity sensor, a photoelectric sensor, and combinations thereof.

8. A system comprising: a first hearing aid that includes one or more first processors and first logic encoded in one or more first non-transitory media for execution by the one or more first processors and when executed operable to: receive first sensor data associated with a mobile device; determine, based on the first sensor data, that a first distance between the first hearing aid and the mobile device is below a first distance threshold; and change a first preset associated with the first hearing aid to a second preset, wherein the first preset associated with the first hearing aid is an ambient noise setting and the second preset is a mix of ambient noise and noise cancellation that amplifies voices and reduces background noise; a second hearing aid that includes one or more second processors and second logic encoded in one or more second non-transitory media for execution by the one or more first processors and when executed operable to: change a first preset associated with a second hearing aid to a third preset.

9. The system of claim 8, wherein the first preset associated with the first hearing aid includes a far-field microphone setting and the second preset includes a near-field microphone setting.

10. The system of claim 8, wherein the second logic is further operable to: receive second sensor data associated with the mobile device; and determine based on the second sensor data, that a second distance between the second hearing aid and the mobile device exceeds the first distance threshold and is below a second distance threshold, wherein changing the first preset associated with the second hearing aid occurs.

11. The system of claim 10, wherein the first preset associated with the second hearing aid is an ambient noise setting and the third preset is noise cancellation.

12. The system of claim 10, wherein the first logic is further operable to: determine that the first distance between the first hearing aid and the mobile device meets the first distance threshold; and change the second preset associated with the first hearing aid to the first preset.

13. The system of claim 12, wherein the second logic is further operable to: determine that the second distance between the second hearing aid and the mobile device is below the first distance threshold; and change the third preset associated with the second hearing aid to the second preset.
