

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418859
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lin; Yuan-Chieh et al.

UE auto update cag configuration when accessing pni-npn as hosting network for localized services

Abstract

A method of UE autonomously updating a CAG related configuration upon receiving a downlink NAS message is provided. If a CAG-ID is included in an allowed CAG-IDs list of the CAG related configuration and is supported by a CAG cell in a PLMN, then UE may attempt to access the CAG cell in the PLMN. If the access is denied, e.g., UE receives a DL NAS message with a cause value, then UE needs to update the CAG related configuration. If the CAG-ID is not associated with any validity or restriction information, then the CAG-ID should be deleted from the CAG related configuration. If the CAG-ID is associated with validity or restriction information and corresponding validity or restriction criteria are not met, then the CAG-ID should not be deleted from the CAG related configuration.

Inventors:	Lin; Yuan-Chieh (Hsin-Chu, TW), Lai; Chia-Lin (Hsin-Chu, TW)
Applicant:	MEDIATEK INC. (Hsin-Chu, TW)
Family ID:	1000008821988
Assignee:	MediaTek Inc. (Hsinchu, TW)
Appl. No.:	18/119511
Filed:	March 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230354174 A1	Nov. 02, 2023

Related U.S. Application Data

us-provisional-application US 63336357 20220429

Publication Classification

Int. Cl.: H04W48/18 (20090101); H04W12/61 (20210101); H04W12/63 (20210101); H04W84/04 (20090101)

U.S. Cl.:

CPC H04W48/18 (20130101); H04W12/61 (20210101); H04W12/63 (20210101); H04W84/042 (20130101)

Field of Classification Search

CPC: H04W (48/18); H04W (12/61); H04W (12/63); H04W (84/042)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0250890	12/2020	Won	N/A	H04W 48/16
2022/0264415	12/2021	Khirallah	N/A	H04W 12/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113453311	12/2019	CN	N/A
WO 2021/064092	12/2018	WO	N/A
WO 2022/033675	12/2023	WO	N/A

OTHER PUBLICATIONS

Taiwan Intellectual Property Office Action 112115530, dated Dec. 29, 2023 (6 pages). cited by applicant

Primary Examiner: Cai; Wayne H

Attorney, Agent or Firm: Imperium Patent Works

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims priority under 35 U.S.C. § 119 from U.S. Provisional Application No. 63/336,357, entitled “Local Service Provided by NPN (PNI-NPN or SNPN-NPN) (NPN for localized services)”, filed on Apr. 29, 2022, the subject matter of which is incorporated herein by reference.

TECHNICAL FIELD

(1) The disclosed embodiments relate generally to wireless mobile communication network, and, more particularly, to methods for UE autonomously update CAG related configuration when accessing PNI-NPN as hosting network for Localized services.

BACKGROUND

(2) A Public Land Mobile Network (PLMN) is a network established and operated by an

administration or recognized operating agency (ROA) for the specific purpose of providing land mobile communication services to the public. PLMN provides communication possibilities for mobile users. A PLMN may provide service in one or a combination of frequency bands. Access to PLMN services is achieved by means of an air interface involving radio communications between mobile phones and base stations with integrated IP network services. One PLMN may include multiple radio access networks (RAN) utilizing different radio access technologies (RAT) for accessing mobile services. A radio access network is part of a mobile communication system, which implements a radio access technology. Conceptually, RAN resides between a mobile device and provides connection with its core network (CN). Depending on the standard, mobile phones and other wireless connected devices are varyingly known as user equipment (UE, i.e., MS), terminal equipment (TE), mobile stations (MS, i.e., UE), mobile termination (MT), etc. Examples of different RATs include 2G GERAN (GSM) radio access network, 3G UTRAN (UMTS) radio access network, 4G E-UTRAN (LTE), 5G new radio (NR) radio access network, NG-RAN (Next-Generation RAN), and other non-3GPP access RAT including WiFi.

(3) As compared to PLMN, a non-public network (NPN) is a network for non-public use. An NPN is either a Stand-alone Non-Public Network (SNPN), i.e., operated by an NPN operator and not relying on network functions provided by a PLMN; or a Public Network Integrated NPN (PNI-NPN), i.e., a non-public network deployed with the support of a PLMN. A Credentials Holder (CH) may authenticate and authorize access to an SNPN separate from the Credentials Holder. The combination of a PLMN ID and Network identifier (NID) identifies an SNPN. A UE may be enabled for SNPN.

(4) PNI-NPNs are NPNs made available via PLMNs e.g., by means of dedicated DNNs, or by one (or more) Network Slice instances allocated for the NPN. When a PNI-NPN is made available via a PLMN, then the UE shall have a subscription of the PLMN in order to access PNI-NPN. As network slicing does not enable the possibility to prevent UEs from trying to access the network in areas where the UE is not allowed to use the Network Slice allocated for the NPN, Closed Access Groups can be used to apply access control for PNI-NPN. A Closed Access Group (CAG) identifies a group of subscribers who are permitted to access one or more CAG cells associated to the CAG. CAG is used for the PNI-NPNs to prevent UE(s), which are not allowed to access the NPN via the associated cell(s), from automatically selecting and accessing the associated CAG cell(s). CAG is used for access control e.g., authorization at cell selection and configured in the subscription as part of the Mobility Restrictions. A CAG is identified by a CAG Identifier which is unique within the scope of a PLMN ID.

(5) Local or Localized services are services that are localized (e.g., provided at specific/limited area and/or are bounded in time). A localized service provider is an application provider or a network operator who make their services localized and to be offered to end user via a hosting network. A hosting network is a network that provides (access for) Localized services, and a hosting network can be an SNPN or a PNI-NPN, while a home network is network owning the current in use subscription or credential of the UE. Home network can be either Home-PLMN or Subscribed-SNPN. End user can enable or disable to access Localized services. If the end user disables to access Localized services, the UE (i.e., MS) may not access an NPN providing access for Localized services.

(6) For providing (access for) Localized services to UE, UE needs to be able to discover, select and access an NPN (as hosting network) providing access for Localized services.

SUMMARY

(7) A method of UE autonomously updating a CAG related configuration upon receiving a downlink NAS message is provided. If a CAG-ID is included in an allowed CAG-IDs list of the CAG related configuration and is supported by a CAG cell in a PLMN, then UE may attempt to access the CAG cell in the PLMN. If the access is denied, e.g., UE receives a DL NAS message with a cause value, then UE needs to update the CAG related configuration. If the CAG-ID is not

associated with any validity or restriction information, then the CAG-ID should be deleted from the CAG related configuration. If the CAG-ID is associated with validity or restriction information and corresponding validity or restriction criteria are not met, then the CAG-ID should not be deleted from the CAG related configuration.

(8) Other embodiments and advantages are described in the detailed description below. This summary does not purport to define the invention. The invention is defined by the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 schematically shows a communication system having a Public Land Mobile Network (PLMN), a Stand-alone Non-public Network (SNPN), and a Public Network Integrated NPN (PNI-NPN) supporting (hosting) network and cell selection with Localized services in accordance with one novel aspect.
- (2) FIG. 2 illustrates simplified block diagrams of a user equipment and a network entity in accordance with embodiments of the current invention.
- (3) FIG. 3A illustrates a first embodiment of a 5G system architecture with access to SNPN using credentials from credentials holder.
- (4) FIG. 3B illustrates a second embodiment of a 5G system architecture with access to SNPNs using credentials from credentials holder.
- (5) FIG. 4 illustrates an example of NG-RAN modes which broadcast certain information in order to provide access to SNPNs.
- (6) FIG. 5A illustrates an example of an SNPN-enabled UE that is configured with 2 SNPN subscriptions (i.e., 2 subscribed SNPNs in the “list of subscriber data”).
- (7) FIG. 5B illustrates an example of an SNPN-enabled UE that is configured with 2 PLMN subscriptions (i.e., 2 USIMs).
- (8) FIG. 6 illustrates Network selection in SNPN access mode with automatic SNPN network selection and manual SNPN network selection.
- (9) FIG. 7A illustrates a first embodiment of network and cell selection and access control of CAG cells for PNI-NPN (CAG), where access to a CAG cell is accepted.
- (10) FIG. 7B illustrates a second embodiment of network and cell selection and access control of non-CAG cells (public cells), where access to a PLMN is accepted.
- (11) FIG. 8A illustrates a first embodiment of network and cell selection and access control of CAG cells for PNI-NPN (CAG), where access to a CAG cell is rejected.
- (12) FIG. 8B illustrates a second embodiment of network and cell selection and access control of non-CAG cells (public cells), where access to a PLMN is rejected.
- (13) FIG. 9A illustrates one example of UE to discover, select and access NPN (as hosting network) providing access for Localized services using validity information.
- (14) FIG. 9B illustrates another example of UE to discover, select and access NPN (as hosting network) and receive localized services using validity information associated with an SNPN.
- (15) FIG. 9C illustrates different examples of UE to discover, select and access NPN (as hosting network) and receive localized services using validity information associated with a CAG (of a PLMN).
- (16) FIG. 10A illustrates a first example of accessing SNPN (as a hosting network) providing access for Localized services, where access is accepted.
- (17) FIG. 10B illustrates a second example of accessing SNPN (as a hosting network) providing access for Localized services, where access is rejected.
- (18) FIG. 11A illustrates a first example of accessing PNI-NPN/CAG (as a hosting network) providing access for Localized services, where access is accepted.

(19) FIG. 11B illustrates a sequence flow between a UE and a 5GS for updating a CAG related configuration upon receiving a DL NAS message with a cause value.

(20) FIG. 12 illustrates a sequence flow between a UE and a 5GS for updating a CAG related configuration upon receiving a DL NAS message with a cause value.

(21) FIG. 13 illustrates examples of UE autonomously updating a UE maintained/stored CAG related configuration upon receiving a DL NAS message with a cause value.

(22) FIG. 14 is a flow chart of UE autonomously updating a UE maintained/stored CAG related configuration upon receiving a DL NAS message with a cause value in accordance with one novel aspect.

DETAILED DESCRIPTION

(23) Reference will now be made in detail to some embodiments of the invention, examples of which are illustrated in the accompanying drawings.

(24) FIG. 1 schematically shows a communication system **100** having a Public Land Mobile Network (PLMN) **110**, a Stand-alone Non-public Network (SNPN) **120**, and a Public Network Integrated NPN (PNI-NPN)/CAG **130** providing access for Localized services in accordance with one novel aspect. PLMN network **110** comprises control plane functionalities, user plane functionality (e.g., UPF), and applications that provides various services by communicating with a plurality of user equipments (UEs) including UE **101**. Serving base station gNB **112** belong to part of a radio access network RAN **140**. RAN **140** provides radio access for UE **101** via a radio access technology (RAT). An access and mobility management function (AMF) in PLMN **110** communicates with gNB **112**. UE **101** may be equipped with a radio frequency (RF) transceiver or multiple RF transceivers.

(25) SNPN network **120** comprises control plane functionalities, user plane functionality (e.g., UPF), and applications that provides various services by communicating with a plurality of user equipments (UEs) including UE **101**. The combination of a PLMN ID and Network identifier (NID) identifies an SNPN. Serving base station gNB **122** belongs to part of RAN **150**. RAN **150** provides radio access for UE **101** via a RAT. An AMF in SNPN **120** communicates with gNB **122**. SNPN **120** is operated by an NPN operator and does not rely on network functions provided by a public network. A Credentials Holder (CH) may authenticate and authorize access to an SNPN separate from the Credentials Holder. NG-RAN nodes which provide access to SNPNs broadcast the following information: One or multiple PLMN IDs, and a List of NIDs per PLMN ID identifying the non-public networks NG-RAN provides access to (**123**). An SNPN-enabled UE is configured with PLMN ID and NID (SNPN ID) of the subscribed SNPN, and an SNPN-enabled UE that supports access to an SNPN using credentials from a Credentials Holder may additionally be configured with information for SNPN selection (SNPN selection information or configuration) and registration using the SNPN subscription or using PLMN subscription (USIM) (in SNPN access mode) (**102**).

(26) PNI-NPN (CAG) network **130** comprises control plane functionalities (optional, it may rely on PLMN's control plane functionality), user plane functionality (optional, it may rely on PLMN's user plane functionality), and applications that provides various services by communicating with a plurality of user equipments (UEs) including UE **101**. PNI-NPN (CAG) **130** is a non-public network deployed with the support of a PLMN, e.g., PLMN **110**, by sharing e.g., RAN/gNB **112** and e.g., control plane functionalities. A Closed Access Group (CAG) identifies a group of subscribers who are permitted to access one or more CAG cells associated to the CAG. CAG is used for the PNI-NPNs to prevent UE(s), which are not allowed to access the NPN via the associated cell(s), from automatically selecting and accessing the associated CAG cell(s). A CAG is identified by a CAG Identifier which is unique within the scope of a PLMN ID. A CAG cell broadcasts one or multiple CAG Identifiers per PLMN (**113**), and a UE is configured with CAG related configuration/information (e.g., an (enhanced) CAG information list containing list of allowed CAGs per PLMN) (**102**).

(27) Local or Localized services are services that are localized (i.e., provided at specific/limited area and/or are bounded in time (a specific period of time)). A localized service provider is an application provider or a network operator who makes their services localized and to be offered to end user via a hosting network. A hosting network is a network that provides access for localized services and can be an SNPN or a PNI-NPN, while a home network is network owning the current in use subscription or credential of the UE. In the example of FIG. 1, both SNPN **120** and PNI-NPN (CAG) **130** can be a hosting network providing access for Localized services to UE **101**.

(28) A URSP rule may include an association of the UE application and the DNN or network slice which is meant for a specific localized service. A URSP rule can also include “Route Selection Validity Criteria” (Time Window and/or a Location Criteria Validity Conditions) with the time/location defined for the specific localized service. The LADN (Local Access Data Network) can also be used for enabling the UE access to localized service.

(29) To enable a PNI-NPN or SNPN to provide access to localized services, the PNI-NPN or SNPN operator configures the network with information enabling the UEs to access the localized services according to validity of the localized services, and the information is determined in agreement with the localized service provider, e.g.: (a) Identification of each localized service, e.g. to be used in URSP rules; (b) validity criteria/restriction for each localized service, e.g., the validity of time duration and/or (area of) location.

(30) When localized services in a network are completed, all UEs registered with the network are expected to be moved to other network or to other cells within the same network. The other network can be HPLMN, VPLMN or another SNPN. UE can stop using the network resources for localized services for numerous reasons, e.g.: (a) Localized services in a network are completed; (b) Validity conditions of network selection information are no longer met; (c) The user decides to stop using the localized services before they are completed (e.g., end user disables to access Localized services); (d) A policy decision is taken by the network, with the effect that the UE is deregistered before the localized services are completed. Validity information or restrictions or criteria or conditions (**103**) are provided or configured to UE as part of the localized service information, which are used to restrict the UE's access of the SNPN/PNI-NPN (as hosting network) providing access for Localized services. For providing localized services to UE, UE needs to be able to discover, select and access a SNPN/PNI-NPN (as hosting network) providing access for the Localized services. The discovery mechanism is based on provisioning or configuring the UE with appropriate information.

(31) FIG. 2 illustrates simplified block diagrams of wireless devices, e.g., a UE **201** and network entity **211** in accordance with embodiments of the current invention. Network entity **211** may be a base station combined with an AMF. Network entity **211** has an antenna **215**, which transmits and receives radio signals. A radio frequency RF transceiver module **214**, coupled with the antenna, receives RF signals from antenna **215**, converts them to baseband signals and sends them to processor **213**. RF transceiver **214** also converts received baseband signals from processor **213**, converts them to RF signals, and sends out to antenna **215**. Processor **213** processes the received baseband signals and invokes different functional modules to perform features in base station **211**. Memory **212** stores program instructions and data **220** to control the operations of base station **211**. In the example of FIG. 2, network entity **211** also includes a set of control functional modules and circuit **290**. Registration circuit **231** handles registration and mobility procedure. Session management circuit **232** handles session management functionalities. Configuration and control circuit **233** provides different parameters to configure and control UE.

(32) Similarly, UE **201** has memory **202**, a processor **203**, and radio frequency (RF) transceiver module **204**. RF transceiver **204** is coupled with antenna **205**, receives RF signals from antenna **205**, converts them to baseband signals, and sends them to processor **203**. RF transceiver **204** also converts received baseband signals from processor **203**, converts them to RF signals, and sends out to antenna **205**. Processor **203** processes the received baseband signals and invokes different

functional modules and circuits to perform features in UE **201**. Memory **202** stores data and program instructions **210** to be executed by the processor to control the operations of UE **201**. Suitable processors include, by way of example, a special purpose processor, a digital signal processor (DSP), a plurality of micro-processors, one or more micro-processor associated with a DSP core, a controller, a microcontroller, application specific integrated circuits (ASICs), file programmable gate array (FPGA) circuits, and other type of integrated circuits (ICs), and/or state machines. A processor in associated with software may be used to implement and configure features of UE **201**.

(33) UE **201** also comprises a set of functional modules and control circuits to carry out functional tasks of UE **201**. Protocol stacks **260** comprise Non-Access-Stratum (NAS) layer to communicate with an AMF entity connecting to the core network, Radio Resource Control (RRC) layer for high layer configuration and control, Packet Data Convergence Protocol/Radio Link Control (PDCP/RLC) layer, Media Access Control (MAC) layer, and Physical (PHY) layer. System modules and circuits **270** may be implemented and configured by software, firmware, hardware, and/or combination thereof. The function modules and circuits, when executed by the processors via program instructions contained in the memory, interwork with each other to allow UE **201** to perform embodiments and functional tasks and features in the network. In one example, system modules and circuits **270** comprise registration circuit **221** that performs registration and mobility procedure with the network, a network and cell selection circuit **222** for performing network and cell selection, a PLMN/PNI-NPN(CAG)/SNPN information maintenance circuit **223** that handles the adding, removing, and resetting of one or more PLMN/PNI-NPN(CAG)/SNPN information in SIM/USIM and/or in UE (non-volatile) memory (source of the information may come from signaling as well), a config and control circuit **224** that handles configuration and control parameters. Note that the network selection and registration related information, such as HPLMN, Operator Controlled PLMN/SNPN Selector list, User Controlled PLMN/SNPN Selector list, may be stored in SIM/USIM **225** and/or in UE (non-volatile) memory.

(34) SNPN

(35) FIG. **3A** illustrates a first embodiment of a 5G system architecture with access to SNPN using credentials from credentials holder. FIG. **3A** depicts the 5G System architecture for SNPN with Credentials Holder using AAA Server for primary authentication and authorization. The AUSF and the UDM in SNPN may support primary authentication and authorization of UEs using credentials from a AAA Server in a Credentials Holder (CH). The SNPN in FIG. **3A** can be the subscribed SNPN for the UE (i.e. NG-RAN broadcasts SNPN ID of the subscribed SNPN). As a deployment option, the SNPN in FIG. **3A** can also be another SNPN than the subscribed SNPN for the UE (i.e. none of the SNPN IDs broadcast by NG-RAN matches the SNPN ID corresponding to the subscribed SNPN). The NSSAAF deployed in the SNPN can support primary authentication in the SNPN using credentials from Credentials Holder using a AAA Server (as depicted) and/or the NSSAAF can support Network Slice-Specific Authentication and Authorization with a Network Slice-Specific AAA Server (not depicted).

(36) FIG. **3B** illustrates a second embodiment of a 5G system architecture with access to SNPNs using credentials from credentials holder. FIG. **3B** depicts the 5G System architecture for SNPN with Credentials Holder using AUSF and UDM for primary authentication and authorization and network slicing. An SNPN may support primary authentication and authorization of UEs that use credentials from a Credentials Holder using AUSF and UDM. The Credentials Holder may be an SNPN or a PLMN. The Credentials Holder UDM provides to SNPN the subscription data.

(37) FIG. **4** illustrates an example of NG-RAN mode(s) which broadcasts certain information in order to provide access to SNPNs. A Credentials Holder (CH) may authenticate and authorize access to an SNPN separate from the Credentials Holder. For SNPN identification, the combination of a PLMN ID and Network identifier (NID) identifies an SNPN. The NID supports two assignment models. Under self-assignment model, NIDs are chosen individually by SNPNs at

deployment time (and may therefore not be unique) but use a different numbering space than the coordinated assignment NIDs. Under coordinated assignment model, NIDs are assigned using one of the following two options: 1) The NID is assigned such that it is globally unique independent of the PLMN ID used; or 2) The NID is assigned such that the combination of the NID and the PLMN ID is globally unique.

(38) The Group IDs for Network Selection (GIN) supports two assignment models. Under self-assignment model, GINs are chosen individually and may therefore not be unique. Under coordinated assignment model, GIN uses a combination of PLMN ID and NID and is assigned using one of the following two options: 1) The GIN is assigned such that the NID is globally unique (e.g., using IANA Private Enterprise Numbers) independent of the PLMN ID used; or 2) The GIN is assigned such that the combination of the NID and the PLMN ID is globally unique.

(39) In the example of FIG. 4, NG-RAN **401** provides access to SNPNs and broadcasts the following information (**410**): One or multiple PLMN IDs and List of NIDs per PLMN ID identifying the non-public networks the NG-RAN provides access to (e.g., SNPN **1** and SNPN **2**). Optionally, the broadcasted information further includes the following: a human-readable network name (HRNN) per SNPN; an indication per SNPN of whether access using credentials from a Credentials Holder is supported; a list of supported Group IDs for Network Selection (GINs) per SNPN (e.g., GIN **1** and GIN **2**); and an indication per SNPN of whether the SNPN allows registration attempts from UEs that are not explicitly configured to select the SNPN, i.e., UEs that do not have any SNPN ID (PLMN ID+NID) nor GIN broadcast by the SNPN in the Credentials Holder controlled prioritized lists of preferred SNPNs/GINs.

(40) FIG. 5A illustrates an example of an SNPN-enabled UE that is configured with SNPN subscription information for each subscribed SNPN. In the example of FIG. 5A, an SNPN-enabled UE **501** is configured with the 2 SNPN subscriptions as depicted by **510/520** for each subscribed SNPN: SNPN ID (PLMN ID+NID) of the subscribed SNPN (e.g., SNPN **1** in Entry 1 of the “list of subscriber data”, SNPN **2** in Entry 2 of the “list of subscriber data”); and Subscription identifier (SUPI) and credentials for each of the subscribed SNPN. If the UE supports access to an SNPN using credentials from a Credentials Holder for each subscribed SNPN: 1) User controlled prioritized list of preferred SNPNs (e.g., SNPN **111**, SNPN **112** for Entry 1; SNPN **211**, SNPN **212** for Entry 2); 2) Credentials Holder controlled prioritized list of preferred SNPNs (e.g., SNPN **121**, SNPN **122** for Entry 1; SNPN **221**, SNPN **222** for Entry 2); and 3) Credentials Holder controlled prioritized list of GINs (e.g., GIN**131**, GIN**132** for Entry 1; GIN **231**, GIN **232** for Entry 2).

(41) FIG. 5B illustrates an example of an SNPN-enabled UE that is configured with 2 PLMN subscriptions (i.e., 2 USIMs). An SNPN-enabled UE that supports access to an SNPN using credentials from a Credentials Holder and that is equipped with a PLMN subscription (USIM) may additionally be configured with information for SNPN selection and registration using the PLMN subscription (in SNPN access mode). For example, PLMN subscription 1 is associated with information for SNPN selection **530**: 1) User controlled prioritized list of preferred SNPNs (e.g., SNPN **311**, SNPN **312**); 2) Credentials Holder controlled prioritized list of preferred SNPNs (e.g., SNPN **321**, SNPN **322**); and 3) Credentials Holder controlled prioritized list of GINs (e.g., GIN **331**, GIN **332**). Similarly, PLMN subscription 2 is associated with information for SNPN selection **540**: 1) User controlled prioritized list of preferred SNPNs (e.g., SNPN **411**, SNPN **412**); 2) Credentials Holder controlled prioritized list of preferred SNPNs (e.g., SNPN **421**, SNPN **422**); and 3) Credentials Holder controlled prioritized list of GINs (e.g., GIN **431**, GIN **432**).

(42) A subscription of an SNPN is either identified by a SUPI containing a network-specific identifier that takes the form of a Network Access Identifier (NAI). The realm part of the NAI may include the NID of the SNPN; or identified by a SUPI containing an IMSI. For an SNPN-enabled UE with SNPN subscription, the Credentials Holder controlled prioritized lists of preferred SNPNs/GINs may be updated by the CH using the Steering of Roaming (SoR) procedure. For an SNPN-enabled UE with PLMN subscription, the Credentials Holder controlled prioritized lists of

preferred SNPNs/GINs may be updated by the CH using the Steering of Roaming (SoR) procedure. When the Credentials Holder updates a UE with the Credentials Holder controlled prioritized lists of preferred SNPNs and GINs, the UE may perform SNPN selection again, e.g., to potentially select a higher prioritized SNPN.

(43) FIG. 6 illustrates Network selection in SNPN access mode with automatic SNPN network selection and manual SNPN network selection. An SNPN-enabled UE **601** supports to access SNPN (in SNPN access mode). When the UE is set to operate in SNPN access mode the UE only selects and registers with SNPNs. When a UE is set to operate in SNPN access mode the UE does not perform normal PLMN selection procedures. There are two SNPN network selection procedures: an automatic SNPN network selection procedure and a manual SNPN network selection procedure.

(44) Under automatic SNPN network selection, UE selects and attempts registration on available and allowable SNPNs in the following order: 1) the SNPN the UE was last registered with (if available) or the equivalent SNPN (if available); 2) the subscribed SNPN, which is identified by the SNPN ID (PLMN ID+NID) for which the UE has SUPI and credentials; 3) if the UEs supports access to an SNPN using credentials from a Credentials Holder then the UE continues by selecting and attempting registration on available and allowable SNPNs which broadcast the indication that access using credentials from a Credentials Holder is supported in the following order: a) SNPNs in the user controlled prioritized list of preferred SNPNs (in priority order); b) SNPNs in the Credentials Holder controlled prioritized list of preferred SNPNs (in priority order); c) SNPNs, which additionally broadcast a GIN contained in the Credentials Holder controlled prioritized list of preferred GINs (in priority order); and 4) SNPNs, which additionally broadcast an indication that the SNPN allows registration attempts from UEs that are not explicitly configured to select the SNPN, i.e. the broadcasted SNPN ID or GIN is not present in the Credentials Holder controlled prioritized lists of preferred SNPNs/GINs in the UE.

(45) In the example of FIG. 6, UE **601** was registered to SNPN **100**, the subscribed SNPN is SNPN **1** and has three lists for credentials. The User controller prioritized list of preferred SNPNs includes SNPN **111**, SNPN **112**; the Credential Holder controlled prioritized list of preferred SNPNs includes SNPN **121**, SNPN **122**; the Credential Holder controlled prioritized list of GINs includes GIN **131**, GIN **132**. There are a list of SNPNs/GINs (broadcasted by one or more NG-RANs) available in current UE location e.g., SNPN **100**, SNPN **1**, SNPN **111**, SNPN **112**, SNPN **121**, SNPN **300**/GIN **131**. UE **601** selects and attempts to register to an SNPN in the following preference/priority order: SNPN **100**, SNPN **1**, SNPN **111**, SNPN **112**, SNPN **121**, and SNPN **300** which also broadcasts GIN **131**.

(46) Under manual network selection, UEs operating in SNPN access mode provide to the user the list of SNPNs (each is identified by a PLMN ID and NID) and related human-readable network names (if available) of the available SNPNs the UE has respective SUPI and credentials for. If the UEs supports access to an SNPN using credentials from a Credentials Holder, the UE also presents available SNPNs which broadcast the “access using credentials from a Credentials Holder is supported” indication and the human-readable names related to the SNPNs (if available). When a UE performs Initial Registration to an SNPN, the UE shall indicate the selected PLMN ID and NID as broadcast by the selected SNPN to NG-RAN. NG-RAN shall inform the AMF of the selected PLMN ID and NID.

(47) If a UE performs the registration or service request procedure in an SNPN identified by a PLMN ID and a self-assigned NID and there is no subscription for the UE, then the AMF shall reject the UE with an appropriate cause code to temporarily prevent the UE from automatically selecting and registering with the same SNPN. If a UE performs the registration or service request procedure in an SNPN identified by a PLMN ID and a coordinated assigned NID and there is no subscription for the UE, then the AMF shall reject the UE with an appropriate cause code to permanently prevent the UE from automatically selecting and registering with the same SNPN. If a

UE performs the registration in an SNPN using credentials from a Credentials Holder and UE is not authorized to access that specific SNPN, then the UDM can reject the UE which results in AMF rejecting the registration request from the UE with an appropriate cause code to prevent the UE from selecting and registering with the same SNPN using credentials from the Credentials Holder. In order to prevent access to SNPNs for authorized UE(s) in the case of network congestion/overload, Unified Access Control information is configured per SNPN (i.e., as part of the subscription information that the UE has for a given SNPN) and provided to the UE.

(48) PNI-NPN (CAG)

(49) PNI-NPNs (CAGs) are NPNs made available via PLMNs e.g., by means of dedicated DNNs, or by one (or more) Network Slice instances allocated for the NPN. The existing network slicing functionalities apply. When a PNI-NPN is made available via a PLMN, then the UE shall have a subscription for the PLMN in order to access PNI-NPN. A Closed Access Group (CAG) identifies a group of subscribers who are permitted to access one or more CAG cells associated to the CAG. CAG is used for the PNI-NPNs to prevent UE(s), which are not allowed to access the NPN via the associated cell(s), from automatically selecting and accessing the associated CAG cell(s). A CAG is identified by a CAG Identifier which is unique within the scope of a PLMN ID. A CAG cell broadcasts one or multiple CAG Identifiers per PLMN. A CAG cell may in addition broadcast a human-readable network name (HRNN) per CAG Identifier.

(50) To use CAG, the UE, that supports CAG as indicated as part of the UE 5GMM Core Network Capability, may be pre-configured or (re)configured with the following CAG related information. If the UE supports CAG, the UE can be provisioned by the network with a CAG related configuration (e.g., (enhanced) CAG information (list) containing list of allowed CAGs per PLMN)), consisting of zero or more entries, each entry containing a) a PLMN ID, b) an “Allowed CAG list” having zero or more CAG-IDs, and c) an optional “indication that the UE is only allowed to access 5GS via CAG cells”. The HPLMN may (pre-)configure or re-configure a UE with the above CAG related configuration using the UE Configuration Update procedure or other 5GMM procedures (e.g., registration procedure or service procedure). The above CAG related configuration is provided by the HPLMN on a per PLMN basis. In a PLMN the UE shall only consider the CAG information provided for this PLMN.

(51) When the subscribed CAG related configuration changes, UDM sets a CAG information Subscription Change Indication and sends it to the AMF. The AMF shall provide the UE with the CAG related configuration when the UDM indicates that the CAG related configuration within the Access and Mobility Subscription data has been changed. When AMF receives the indication from the UDM that the CAG related configuration within the Access and Mobility Subscription has changed, the AMF uses the CAG related configuration received from the UDM to update the UE. Once the AMF updates the UE and obtains an acknowledgment from the UE, the AMF informs the UDM that the update was successful and the UDM clears the CAG information Subscription Change Indication flag. The AMF may update the UE using either the UE Configuration Update procedure after registration procedure is completed, or by including the new CAG related configuration in the Registration Accept or in the Registration Reject or in the Deregistration Request or in the Service Reject.

(52) When the UE is roaming and the Serving PLMN provides CAG related configuration, the UE shall update only the CAG related configuration provided for the Serving PLMN, while the stored CAG related configuration for other PLMNs is not updated. When the UE is not roaming and the HPLMN provides CAG related configuration, the UE shall update the CAG related configuration stored in the UE with the received CAG related configuration for all the PLMNs. The UE shall store the latest available CAG related configuration for every PLMN for which it is provided and keep it stored when the UE is de-registered or switched off. The CAG related configuration is only applicable with 5GS.

(53) For network and cell selection, the CAG cell shall broadcast information such that only UEs

supporting CAG are accessing the cell; cells are either CAG cells or normal PLMN cells (non CAG cells). For access control, in order to prevent access to NPNs for authorized UE(s) in the case of network congestion or overload, existing mechanisms defined for Control Plane load control, congestion and overload control can be used, as well as the access control and barring functionality, or Unified Access Control using the access categories can be used. The Mobility Restrictions shall be able to restrict the UE's mobility according to the Allowed CAG list (if configured in the subscription) and include an indication whether the UE is only allowed to access 5GS via CAG cells (if configured in the subscription).

(54) During transition from CM-IDLE to CM-CONNECTED and during Registration after connected mode mobility from E-UTRAN to NG-RAN, the AMF shall verify whether UE access is allowed by Mobility Restrictions. If the UE is accessing the 5GS via a CAG cell and if at least one of the CAG Identifier(s) received from the NG-RAN is part of the UE's Allowed CAG list, then the AMF accepts the NAS request. If the UE is accessing the 5GS via a CAG cell and if none of the CAG Identifier(s) received from the NG-RAN are part of the UE's Allowed CAG list, then the AMF rejects the NAS request and the AMF can include CAG related configuration in the NAS reject message. The AMF then release the NAS signaling connection for the UE by triggering the AN release procedure. If the UE is accessing the 5GS via a non-CAG cell and the UE's subscription contains an indication that the UE is only allowed to access 5GS via CAG cells, then the AMF rejects the NAS request and the AMF should include CAG related configuration in the NAS reject message. The AMF then release the NAS signaling connection for the UE by triggering the AN release procedure.

(55) During transition from RRC Inactive to RRC Connected state, when the UE initiates the RRC Resume procedure for RRC Inactive to RRC Connected state transition in a CAG cell, NG-RAN shall reject the RRC Resume request from the UE if none of the CAG Identifiers supported by the CAG cell are part of the UE's Allowed CAG list according to the Mobility Restrictions received from the AMF or if no Allowed CAG list has been received from the AMF. When the UE initiates the RRC Resume procedure for RRC Inactive to RRC Connected state transition in a non-CAG cell, NG-RAN shall reject the UE's Resume request if the UE is only allowed to access CAG cells according to the Mobility Restrictions received from the AMF.

(56) During connected mode mobility procedures within NG-RAN, i.e., handover procedures, source NG-RAN shall not handover the UE to a target NG-RAN node if the target is a CAG cell and none of the CAG Identifiers supported by the target CAG cell are part of the UE's Allowed CAG list in the Mobility Restriction List or if no Allowed CAG list has been received from the AMF. Source NG-RAN shall not handover the UE to a non-CAG cell if the UE is only allowed to access CAG cells based on the Mobility Restriction List. If the target cell is a CAG cell, target NG-RAN shall reject the N2 based handover procedure if none of the CAG Identifiers supported by the CAG cell are part of the UE's Allowed CAG list in the Mobility Restriction List or if no Allowed CAG list has been received from the AMF. If the target cell is a non-CAG cell, target NG-RAN shall reject the N2 based handover procedure if the UE is only allowed to access CAG cells based on the Mobility Restriction List. When the AMF receives the Nudm_SDM_Notification from the UDM and the AMF determines that the Allowed CAG list or the indication whether the UE is only allowed to access CAG cells have changed, AMF shall update the Mobility Restrictions in the UE and NG-RAN accordingly under the conditions.

(57) FIG. 7A illustrates a first embodiment of network and cell selection and access control of CAG cells for PNI-NPN (CAG), where access to a CAG cell is accepted. In the example of FIG. 7A, UE 711 is configured with a CAG related configuration (e.g., CAG information list 710), comprising a list of entries. For each entry, it comprises a) a PLMN ID, b) an "Allowed CAG list" having zero or more CAG-IDs, and c) an optional "indication that the UE is only allowed to access 5GS via CAG cells". For example, entry 1 comprises PLMN 111, and an allowed CAG list with CAG-ID AAA and BBB. Through 5GC/AMF and NG-RAN, a CAG cell broadcasts one or more

CAG-IDs per PLMN, e.g., CAG-ID AAA and CCC can be accessed via the CAG cell **712**. As a result, UE **711** can access the CAG cell **712** in PLMN **111**.

(58) FIG. 7B illustrates a second embodiment of network and cell selection and access control of non-CAG cells, where access to a PLMN is accepted. In the example of FIG. 7B, UE **721** is configured with a CAG related configuration (e.g., CAG information list **720**), comprising a list of entries. For each entry, it comprises a) a PLMN ID, b) an “Allowed CAG list” having zero or more CAG-IDs, and c) an optional “indication that the UE is only allowed to access 5GS via CAG cells”. For example, entry 1 comprises PLMN **111**, and an allowed CAG list with CAG-ID AAA and BBB. In addition, there is no indication in entry 1 that indicates the UE is only allowed to access 5GS via CAG cells. Through 5GC/AMF and NG-RAN **722**, UE **721** finds non-CAG cell in PLMN **111** (i.e., no CAG IDs are broadcasted by the cell **722**). Since UE **721** is allowed to access 5GS via non-CAG cell, as a result, UE **721** can access the non-CAG cell **722** in PLMN **111**.

(59) FIG. 8A illustrates a first embodiment of network and cell selection and access control of CAG cells for PNI-NPN (CAG), where access to a CAG cell is rejected. In the example of FIG. 8A, UE **811** is configured with a CAG related configuration (e.g., CAG information list **810**), comprising a list of entries. For each entry, it comprises a) a PLMN ID, b) an “Allowed CAG list” having zero or more CAG-IDs, and c) an optional “indication that the UE is only allowed to access 5GS via CAG cells”. For example, entry 1 comprises PLMN **111**, and an allowed CAG list with CAG-ID AAA and BBB. Through 5GC/AMF and NG-RAN **812**, a CAG cell broadcasts one or more CAG-IDs per PLMN, e.g., CAG-ID CCC and DDD. However, neither CAG-ID CCC nor CAG-ID DDD are in the “Allowed CAG list”. As a result, UE **811** cannot access this CAG cell CCC/DDD of PLMN **111**.

(60) FIG. 8B illustrates a second embodiment of network and cell selection and access control of CAG cells for PNI-NPN (CAG), where access to a PLMN is rejected. In the example of FIG. 8B, UE **821** is configured with a CAG related configuration (CAG information list **820**), comprising a list of entries. For each entry, it comprises a) a PLMN ID, b) an “Allowed CAG list” having zero or more CAG-IDs, and c) an optional “indication that the UE is only allowed to access 5GS via CAG cells”. For example, entry 1 comprises PLMN **111**, and an allowed CAG list with CAG-ID AAA and BBB. In addition, there is an indication in entry 1 that indicates the UE is only allowed to access 5GS via CAG cells. Through 5GC/AMF and NG-RAN **822**, UE **821** finds non-CAG cell in PLMN **111** (i.e., no CAG cell IDs are broadcasted by the cell **822**). Since UE **821** is not allowed to access 5GS via non-CAG cell, as a result, UE **821** cannot access the non-CAG cell **822** in PLMN **111**.

(61) NPN (as Hosting Network) Providing Access for Localized Services.

(62) Local or localized service is localized (i.e., provided at specific/limited area and/or can be bounded in time). The service can be realized via applications (e.g., live or on-demand audio/video stream, electric game, IMS, etc.), or connectivity (e.g., UE to UE, UE to Data Network, etc.). A localized service provider is an application provider or network operator who make their services localized and to be offered to end users via a hosting network, which is a network that provides access for local or Localized services. A home network is network owning the current in use subscription or credential of the UE. Home network can be either Home-PLMN or Subscribed-SNPN. An SNPN may support primary authentication and authorization of UEs that use credentials from a Credentials Holder using AUSF and UDM. The Credentials Holder may be Home-PLMN or Subscribed-SNPN. For SNPN as hosting network, home network can be regarded as CH. For PNI-NPN (CAG) as hosting network, home network can be regarded as (Home-)PLMN. For providing Localized services to UE, UE needs to be able to discover, select and access a NPN (as hosting network) providing access for the Localized services. The discovery mechanism is based on provisioning/(pre-)configuring/signaling the UE with appropriate information.

(63) FIG. 9A illustrates one example of UE to discover, select and access NPN (as hosting network) and receive localized services using validity information. When UE accesses the NPN (as Hosting network) using the subscription/credentials of its home network, only two cases are

considered. If Home network (/CH) is PLMN, the Hosting network can be PNI-NPN or SNPN. If Home network (/CH) is SNPN, the Hosting network can be only SNPN. If the UE accesses the Hosting network using subscriptions or credentials from the UE Home network, and the UE has multiple credentials or subscriptions, the UE needs to determine which credential or subscription to be used to access the Hosting network. Validity information or conditions information provided to the UE as part of the localized service information can be used to restrict the UE's access of the hosting network, including: (time and/or location) validity information or conditions information ((Time and/or Location:) duration, criteria, or restriction) associated with SNPN(ID) or GIN; and (time and/or location) validity information/conditions ((Time and/or Location:) duration, criteria, or restriction) associated with PNI-NPN/CAG-ID.

(64) As depicted by **910**, an SNPN-enabled UE is configured with the following information for each subscribed SNPN: PLMN ID and NID (SNPN ID) of the subscribed SNPN (e.g., SNPN **1**); and Subscription identifier (SUPI) and credentials for the subscribed SNPN. If the UE supports access to an SNPN using credentials from a Credentials Holder, then the UE is also configured with 1) User controlled prioritized list of preferred SNPNS (e.g., SNPN **111**, SNPN **112**); 2) Credentials Holder controlled prioritized list of preferred SNPNS (e.g., SNPN **121**, SNPN **122**, SNPN **123**); and 3) Credentials Holder controlled prioritized list of GINs (e.g., GIN **131**, GIN **132**).

(65) FIG. **9B** illustrates another example of UE to discover, select and access NPN (as hosting network) and receive localized services using validity information. For automatic network selection, in the case of SNPN (as hosting network) for Localized services, there can be associated (time (duration) and/or location (restriction)) validity information for SNPN(s) or GIN(s). For one example, as depicted by **910**, (1) the existing Credentials Holder controlled prioritized list of preferred SNPNS (and GINs) can be extended with the (time and/or location) validity information or conditions information for each entry in the list; or as another example depicted by **911**, (2) there can be a (or more) new list type defined to provide entries with validity information for SNPNS (and GINs) (ex: define new CH controlled prioritized lists of preferred SNPNS/GINs (for access localized service, where each entry contains an SNPN/GIN identity and/) including (optional) validity information/conditions).

(66) As depicted by **910** or **911**, SNPN **121** has associated time (duration) validity condition (the time duration (e.g., start and end time) in which the UE is allowed to access the SNPN **121**) of January-1~January-2, SNPN **123** has associated time validity condition of January-1~January-3, and GIN **131** has associated time (duration) validity condition of January-1~January-3. Such time (duration) validity/conditions information are provided to the UE as part of the localized service information to restrict the UE's access of the (hosting network) Localized services. The validity/conditions information can also optionally include location validity/conditions information, which can be in the form of geolocation and/or TAI(s)/Cell(s) (of serving network (serving PLMN/PNI-NPN or serving SNPN)), the location validity/conditions information can be used to assist the UE to know where to start searching for SNPNS hosting networks.

(67) FIG. **9C** illustrates another example of UE to discover, select and access NPN (as hosting network) and receive localized services using validity/conditions information. For automatic network selection, in the case of PNI-NPN with CAG, a CAG-ID (in the (enhanced/extended (allowed)) CAG list) can be optionally associated with time validity/conditions or restriction information (the time duration (e.g., start and end time) in which the UE is allowed to access the PNI-NPN/CAG) and/or location validity/conditions or restriction information. Time duration and/or location validity/conditions or restriction may be provided together with the CAG Identifier. For example, the ((enhance/extended) Allowed) CAG list can be provided to UE and AMF for enforcement, to make sure that UE not accessing the CAG cell outside of the time duration or/(and) outside of the allowed-location. The location validity/conditions information can be in the form of geolocation and/or TAI(s)/Cell(s) (of serving network (serving PLMN/PNI-NPN or serving SNPN)), the location validity/conditions or restriction information can be used to assist the UE to

know where to start searched for the PNI-NPN hosting networks.

(68) Note that, as depicted by **920**, the (time and/or location) validity information can be stored next to the CAG-ID (e.g., enhance/extend the original allowed CAG list), or stored independently in the UE and is associated to a (or more) CAG-ID; or as depicted by **921** there can be a (or more) new list type defined to provide entries with validity information for CAG(s). As depicted by **920**, for example, the ((enhanced/extended) Allowed) CAG list for PLMN **111** includes CAG AAA, BBB, and CCC. CAG-ID AAA is associated with time validity information of January-1~January-3, and CAG-ID CCC is associated with time validity information of January-1~January-2. Similar logic applies for location validity, if any. Such (time and location) validity conditions are provided to the UE as part of the localized service information to restrict the UE's access of the localized services (hosting network).

(69) FIG. **10A** illustrates a first example of accessing localized services via SNPN (as a hosting network), where access is accepted. In the example of FIG. **10A**, UE **1001** is configured with the following SNPN subscription: the subscribed SNPN=SNPN **1**, Credentials Holder controlled prioritized list of preferred SNPNs, which includes SNPN **121**, SNPN **122**, and SNPN **123**. SNPN **121** is associated with time validity condition of January-1~January-2, and SNPN **123** is associated with time validity condition of January-1~January-3. Through 5GC/AMF and NG-RAN **1002**, SNPN **123** broadcasts its SNPN ID==123, with an indication of access using credentials from a Credentials Holder is supported. Since UE **1001** is subscribed to SNPN **1**, and SNPN **123** is included as a preferred SNPN in the entry of "list of subscriber data" for SNPN1, UE **1001** may attempt to access SNPN **123** using credentials from SNPN **1**. Since a time validity condition is associated with SNPN **123**, UE **1001** needs to determine whether such time validity condition is satisfied before the access. UE **1001** checks the current time of January 2, which is inside the time period of January-1~January-3. As a result, UE **1001** can access SNPN **123** using credentials from the (subscribed) SNPN **1**. SNPN **123** is the localized service provider. SNPN **123** is the hosting network. SNPN **1** is the credential holder. (If location validity information is available, in this example we assume location validity is met per the location validity information.)

(70) FIG. **10B** illustrates a second example of accessing localized services via SNPN (as a hosting network), where access is not allowed (if UE tries to access, the network will reject). In the example of FIG. **10B**, UE **1001** is configured with the following SNPN subscription: the subscribed SNPN=SNPN **1**, a Credentials Holder controlled prioritized list of preferred SNPNs, which includes SNPN **121**, SNPN **122**, and SNPN **123**. SNPN **121** is associated with time validity condition of January-1~January-2, and SNPN **123** is associated with time validity condition of January-1~January-3. Through 5GC/AMF and NG-RAN **1002**, the hosting network SNPN **123** broadcasts its SNPN ID==123, with an indication of access using credentials from a Credentials Holder is supported. Since UE **1001** is subscribed to SNPN **1**, and SNPN **123** is included as a preferred SNPN in the entry of "list of subscriber data" for SNPN1, UE **1001** may attempt to access SNPN **123**. However, since a time validity condition is associated with SNPN **123**, UE **1001** also needs to additionally determine whether such time validity condition is satisfied before the access. UE **1001** checks the current time of January 4, which is outside the time period of January-1~January-3. As a result, UE **1001** cannot access SNPN **123** using credentials from SNPN **1**.

(71) FIG. **11A** illustrates a first example of accessing localized services via PNI-NPN with CAG (as a hosting network), where access is accepted. In the example of FIG. **11A**, UE **1101** is configured with a CAG related configuration **1110**, comprising a list of entries. For example, entry 1 comprises PLMN **111**, and an enhanced or extended allowed CAG list with CAG-ID AAA, BBB and CCC. CAG AAA is associated with time validity condition of January-1~January-3, and CAG CCC is associated with time validity condition of January-1~January-2. Through 5GC/AMF and NG-RAN **1102**, a CAG cell broadcasts one or more CAG-IDs per PLMN, e.g., CAG-ID AAA of PLMN **111**. Since a time validity condition is associated with CAG AAA, UE **1101** needs to determine whether such time validity condition is satisfied before the access. UE **1101** checks the

current time of January 2, which is inside the time period of January-1~January-3 associated with CAG AAA. As a result, UE **1101** can access CAG AAA of PLMN **111** via the cell. (PNI-NPN/CAG-AAA is the service provider, PNI-NPN/CAG-AAA is the hosting network, Home PLMN of the currently used USIM is the home network, and Home PLMN is the credential holder.) (If location validity information is available, in this example, we assume location validity is met per the location validity information.)

(72) FIG. **11B** illustrates a second example of accessing localized services via PNI-NPN with CAG (as a hosting network), where access is rejected. In the example of FIG. **11B**, UE **1101** is configured with a CAG related configuration **1110**, comprising a list of entries. For example, entry 1 comprises PLMN **111**, and an enhanced or extended allowed CAG list with CAG-ID AAA, BBB and CCC. CAG AAA is associated with time validity condition of January-1~January-3, and CAG CCC is associated with time validity condition of January-1~January-2. Through 5GC/AMF and NG-RAN **1102**, a CAG cell broadcasts one or more CAG-IDs per PLMN, e.g., CAG-ID AAA and CAG-ID CCC of PLMN **111**. Since time validity conditions are associated with CAG AAA and CCC, UE **1101** needs to determine whether such time validity conditions are satisfied before the access. UE **1101** checks the current time of January 4, which is outside the time period of January-1~January-3 associated with CAG AAA, and outside the time period of January-1~January-2 associated with CAG CCC. As a result, UE **1101** cannot access CAG cell AAA or CCC.

(73) UE Auto Update CAG Related Configuration

(74) When a PNI-NPN is made available via a PLMN, a UE shall have a subscription for the PLMN in order to access the PNI-NPN. A Closed Access Group (CAG) identifies a group of subscribers who are permitted to access one or more CAG cells associated to the CAG. CAGs may be used to apply access control for the PNI-NPN. For a PNI-NPN (as hosting network) that provides localized services, a CAG cell of the PNI-NPN hosting network may be associated with validity or restriction information, e.g., time and/or location validity or restriction criteria. As a result, the condition in determining whether a UE can access a CAG cell may change. For example, if a CAG-ID of a PLMN is associated with a validity or restriction information and the validity or restriction criteria are not met, then a CAG cell broadcasting the CAG-ID cannot be accessed by the UE even if the CAG-ID is listed in a CAG related configuration (e.g., enhanced/extended Allowed CAG list) and broadcasted by the PLMN.

(75) If the UE supports accessing localized services via PNI-NPN with CAG (as a hosting network), the UE maintains the CAG related configuration. When UE sends an uplink 5GMM message requesting to access a CAG cell, sometimes UE receives a downlink 5GMM message with a cause value, indicating that the UE is not authorized for accessing the CAG cell. As a result, the UE may need to update the current CAG related configuration stored in the UE, so that the stored UE configuration is in sync with the Core network configuration for the UE. Typically, if a CAG-ID is listed in the CAG related configuration and broadcasted via a CAG cell by the PLMN, and if the UE is not authorized to access the CAG cell, then the UE should delete such CAG-ID from the CAG related configuration. However, if such CAG-ID is associated with validity or restriction information, then the UE need to consider whether the validity or restriction information before updating the CAG related configuration.

(76) In accordance with one novel aspect, a method of UE autonomously updating a CAG related configuration upon receiving a downlink NAS message is provided. If a CAG-ID is included in an allowed CAG-IDs list of the CAG related configuration and is supported by a CAG cell in a PLMN, then UE may attempt to access the CAG cell in the PLMN. If the access is denied, e.g., UE receives a DL NAS message with a cause value, then UE needs to update the CAG related configuration. If the CAG-ID is not associated with any validity or restriction information, then the CAG-ID needs to be deleted from the CAG related configuration. If the CAG-ID is associated with validity or restriction information and corresponding validity or restriction criteria are not met, then the CAG-ID should not be deleted from the CAG related configuration.

(77) FIG. 12 illustrates a sequence flow between a UE and a 5GS for updating a CAG related configuration upon receiving a DL NAS message with a cause value. In step **1211**, UE **1201** maintains a CAG related configuration, including a list of ((enhanced/extended) (allowed)) CAG-IDs of a PLMN. In step **1221**, the 5GS **1202** broadcasts one or more supported CAG-IDs via a CAG cell. In step **1231**, UE **1201** attempts to access the CAG cell, e.g., based on the ((enhanced/extended) (allowed)) CAG-ID list stored or maintained in the UE and the supported CAG-ID list broadcasted by the CAG cell. For example, if there are overlapping CAG-IDs, then the UE may be able to access the CAG cell. In step **1241**, UE **1201** sends an uplink 5GMM message to 5GS **1202**, e.g., a registration request message or a service request message. However, such request is rejected by the network. In step **1242**, UE **1201** receives a downlink 5GMM message from 5GS **1202**, e.g., a registration reject message, a service reject message, or a deregistration request message. The DL 5GMM message may further carry a cause value, e.g., a cause value #76 indicating that the UE is not authorized to access the CAG cell; or a new cause value indicating that the validity or restriction criteria associated with the CAG-ID broadcasted by the CAG cell are not met.

(78) In response to the DL 5GMM message, UE **1201** knows that the currently stored/maintained CAG related configuration is not synchronized with the network stored latest UE configuration, and thus the CAG related configuration needs to be updated (step **1251**) by the UE itself using “educational guess” approach. (For a PLMN) If a CAG-ID is included in the UE maintained/stored ((enhanced/extended) (allowed)) CAG-IDs list and in the CAG cell broadcasted CAG-IDs list, and the CAG-ID is not associated with any validity or restriction information, then the CAG-ID needs to be deleted by the UE from the CAG related configuration. On the other hand, if a CAG-ID is included in the UE maintained/stored ((enhanced/extended) (allowed)) CAG-IDs list and in the CAG cell broadcasted CAG-IDs list, and the CAG-ID is associated with validity or restriction information and corresponding validity or restriction criteria are not met, then the CAG-ID should not be deleted by the UE from the CAG related configuration.

(79) FIG. 13 illustrates examples of UE autonomously updating a CAG related configuration upon receiving a DL NAS message with a cause value. In general, a CAG related configuration includes zero or more entries, each entry containing a) a PLMN ID, b) an ((enhanced/extended) Allowed) CAG list having zero or more CAG-IDs, and c) an optional indication that the UE is only allowed to access 5GS via CAG cells. In the example of FIG. 13, UE **1301** maintains a CAG related configuration **1300** for accessing localized services via PNI-NPN with CAG (as a hosting network). The ((enhanced/extended) Allowed) CAG list in entry 1 of CAG related configuration **1300** comprises a list of CAG-IDs for PLMN **111** including CAG AAA, BBB, and CCC. Among the list of CAG-IDs, CAG CCC is associated with validity or restriction information, e.g., time validity or restriction criteria of January-3~January-5 (**1311**).

(80) Through 5GC/AMF and NG-RAN **1302**, a CAG cell broadcasts one or more CAG-IDs per PLMN, e.g., CAG-ID BBB, CCC, and DDD of PLMN **111**. Since CAG BBB is broadcasted by the CAG cell and are included in ((enhanced/extended) Allowed) CAG list of the CAG related configuration **1300**, UE **1301** assumes that it can access CAG BBB of PLMN **111** via the CAG cell **1302**. However, due to dynamic network environments, the 5G core network (5GC) may have different CAG related configuration for UE **1301**, e.g. CAG related configuration **1310** as depicted, which comprises an allowed CAG list for PLMN **111** including CAG AAA, and CCC (without including CAG BBB). CAG CCC is associated with validity or restriction information **1311**, e.g., time validity or restriction criteria of January-3~January-5. If the current time is January 2, which is outside the time period of January-3~January-5 associated with CAG CCC, then the time validity or restriction criteria are not met.

(81) As a result, based on the CAG related configuration **1310** at 5GC, UE **1301** cannot access CAG BBB nor CAG CCC of PLMN **111** via the CAG cell. When UE **1301** attempts to access the CAG cell **1302**, UE **1301** will receive a downlink 5GMM message with a cause value indicating

that the UE is not authorized to access the CAG cell. In response, UE **1301** knows that the UE stored/maintained CAG related configuration (**1300**) is not in sync with the network stored/maintained CAG related configuration (**1310**) for the UE. Since the DL 5GMM message does not carry any updated CAG related configuration, UE **1301** thus needs to update such information autonomously (i.e., educational guess). In a first example, because CAG related configuration (**1300**) comprises an allowed CAG list for PLMN **111** including CAG BBB, and CAG BBB is broadcasted by the CAG cell, UE **1301** can determine that the UE is no longer allowed to access CAG BBB of the CAG cell (since the access is rejected by the NW). UE **1301** thus deletes CAG BBB from the CAG-ID list.

(82) In a second example, CAG related configuration (**1300**) comprises an allowed CAG list for PLMN **111** including CAG CCC and CAG CCC is also broadcasted by the CAG cell, UE **1301** can NOT determine that the UE is not allowed to access CAG CCC of the CAG cell (since the access is rejected by the NW) at January 2. This is because CAG CCC is associated with validity or restriction information **1311** and the validity or restriction criteria are not met. Therefore, UE **1301** is still allowed to access CAG CCC of the CAG cell, as long as the associated validity or restriction criteria are met (e.g., in the future during January 3~January 5). As a result, UE **1301** keeps CAG CCC in the stored/maintained CAG-ID list. As depicted in FIG. **13**, the updated CAG related configuration **1320** comprises a list of CAG-IDs for PLMN **111** including CAG AAA and CCC. CAG CCC is associated with validity or restriction information **1311**, e.g., time validity or restriction criteria of January-3~January-5.

(83) FIG. **14** is a flow chart of UE autonomously updating a UE maintained/stored CAG related configuration upon receiving a DL NAS message with a cause value in accordance with one novel aspect. In step **1401**, a UE maintains a closed access group (CAG) related configuration of a PLMN, wherein the CAG related configuration comprises an allowed CAG list, and wherein a first CAG-ID from the allowed CAG list is associated with validity or restriction information comprising validity or restriction criteria. In step **1402**, the UE sends an uplink request message to access a CAG cell, wherein the CAG cell broadcasts the first CAG-ID that is also included in the CAG-ID list maintained/stored by the UE. In step **1403**, the UE receives a downlink non-access stratum (NAS) message via the CAG cell in response to the request message, wherein the NAS message does not include any updated CAG related configuration. In step **1404**, the UE autonomously updates the CAG related configuration based on the validity or restriction information of the first CAG-ID, wherein the UE deletes the first CAG-ID from the UE maintained allowed CAG list when the validity or restriction criteria are met, otherwise the UE keeps the first CAG-ID in the UE maintained allowed CAG list when the validity or restriction criteria are not met.

(84) Although the present invention has been described in connection with certain specific embodiments for instructional purposes, the present invention is not limited thereto. Accordingly, various modifications, adaptations, and combinations of various features of the described embodiments can be practiced without departing from the scope of the invention as set forth in the claims.

Claims

1. A method, comprising: maintaining a closed access group (CAG) related configuration of a PLMN by a user equipment (UE), wherein the CAG related configuration comprises an allowed CAG list, and wherein a first CAG-ID from the allowed CAG list is associated with validity information comprising corresponding validity criteria; receiving a downlink non-access stratum (NAS) message via a CAG cell, wherein the first CAG-ID is broadcasted by the CAG cell and the NAS message does not include any CAG related configuration; and autonomously updating the CAG related configuration by the UE based on the validity information of the first CAG-ID,

- wherein the UE deletes the first CAG-ID from the maintained allowed CAG list when the associated validity criteria are met, otherwise the UE keeps the first CAG-ID in the maintained allowed CAG list when the associated validity criteria are not met.
2. The method of claim 1, wherein the UE sends an uplink request message to the CAG cell and the downlink NAS message is a response to the uplink request message, wherein the uplink request message is a registration request or a service request message.
 3. The method of claim 1, wherein the downlink NAS message is a registration reject, a service reject, or a deregistration request message.
 4. The method of claim 1, wherein the downlink NAS message carries a cause value indicating that the UE is not authorized for accessing the CAG cell.
 5. The method of claim 1, wherein the downlink NAS message carries a cause value indicating that the validity criteria associated with the first CAG-ID are not met.
 6. The method of claim 1, wherein the CAG cell broadcasts a second CAG-ID that is included in the allowed CAG list maintained by the UE, and wherein the UE deletes the second CAG-ID from the allowed CAG list when the second CAG-ID is not associated with any validity information.
 7. The method of claim 1, wherein the validity information includes only time validity information, wherein the validity criteria are met if the time validity information matches a current time of the UE, and wherein the validity criteria are not met if the time validity information does not match the current time of the UE.
 8. The method of claim 1, wherein the validity information includes only location validity information, wherein the validity criteria are met if the location validity information matches a current location of the UE, and wherein the validity criteria are not met if the location validity information does not match the current location of the UE.
 9. The method of claim 1, wherein the validity information includes both time validity information and location validity information, wherein the validity criteria are met if the time validity information matches a current time of the UE and the location validity information matches a current location of the UE, and wherein the validity criteria are not met if the time validity information does not match the current time of the UE or the location validity information does not match the current location of the UE.
 10. A User Equipment (UE), comprising: a closed access group (CAG) information handling circuit that maintains a CAG related configuration of a PLMN, wherein the CAG related configuration comprises an allowed CAG list, and wherein a first CAG-ID from the allowed CAG list is associated with validity information comprising corresponding validity criteria; a receiver that receives a downlink non-access stratum (NAS) message via a CAG cell, wherein the first CAG-ID is broadcasted by the CAG cell and the NAS message does not include any CAG related configuration; and a control circuit that autonomously updates the CAG related configuration maintained by the UE based on the validity information of the first CAG-ID, wherein the UE deletes the first CAG-ID from the allowed CAG list when the associated validity criteria are met, otherwise the UE keeps the first CAG-ID in the allowed CAG list when the associated validity criteria are not met.
 11. The UE of claim 10, wherein a transmitter sends an uplink request message to the CAG cell and the downlink NAS message is a response to the uplink request message, wherein the uplink request message is a registration request or a service request message.
 12. The UE of claim 10, wherein the downlink NAS message is a registration reject, a service reject, or a deregistration request message.
 13. The UE of claim 10, wherein the downlink NAS message carries a cause value indicating that the UE is not authorized for accessing the CAG cell.
 14. The UE of claim 10, wherein the downlink NAS message carries a cause value indicating that the validity criteria associated with the first CAG-ID are not met.
 15. The UE of claim 10, wherein the CAG cell broadcasts a second CAG-ID that is included in the

allowed CAG list maintained by the UE, and wherein the UE deletes the second CAG-ID from the allowed CAG list when the second CAG-ID is not associated with any validity information.

16. The UE of claim 10, wherein the validity information includes only time validity information, wherein the validity criteria are met if the time validity information matches a current time of the UE, and wherein the validity criteria are not met if the time validity information does not match the current time of the UE.

17. The UE of claim 10, wherein the validity information includes only location validity information, wherein the validity criteria are met if the location validity information matches a current location of the UE, and wherein the validity criteria are not met if the location validity information does not match the current location of the UE.

18. The UE of claim 10, wherein the validity information includes both time validity information and location validity information, wherein the validity criteria are met if the time validity information matches a current time of the UE and the location validity information matches a current location of the UE, and wherein the validity criteria are not met if the time validity information does not match the current time of the UE or the location validity information does not match the current location of the UE.
