

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404095
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Nadarian; Marine

Trash receptacle with storage compartment

Abstract

A trash receptacle for storing garbage and other objects includes a container with a base wall and a perimeter wall. The perimeter wall is coupled to and extends upwardly from the base wall, and an upper edge of the perimeter wall defines an opening to the container. A storage compartment is coupled to the base wall of the container and comprises a tubular wall and a drawer. The tubular wall defines a channel which extends laterally with respect to the container and defines a pair of apertures to the channel which are laterally spaced with respect to the container. The drawer is slidably coupled to the tubular wall.

Inventors:	Nadarian; Marine (Van Nuys, CA)
Applicant:	Nadarian; Marine (Van Nuys, CA)
Family ID:	95485750
Appl. No.:	18/383968
Filed:	October 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250136360 A1	May. 01, 2025

Publication Classification

Int. Cl.: **B65F1/06** (20060101); **B65F1/00** (20060101); **B65F1/14** (20060101); **B65F1/16** (20060101)

U.S. Cl.:

CPC **B65F1/004** (20130101); **B65F1/06** (20130101); **B65F1/141** (20130101); **B65F1/16** (20130101);

Field of Classification Search

CPC: B65D (83/0888); B65D (83/0805); B65D (2209/00); B65D (5/38); B65D (5/16); A47K (10/421); A47K (2010/3233); A45C (13/02); A45C (3/00); A45C (3/06); A45C (5/00); A45C (5/065); A45C (1/024); B65F (1/062); B65F (1/06); B65F (1/068); B65F (1/141); B65F (2001/061); B65F (2220/12)

USPC: 221/102; 206/233; 206/581; 150/104; 150/116; 150/113; 150/117; 220/495.07; 220/495.11; 220/908; 220/908.1; 220/495.08

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2036986	12/1935	Treat	131/239	A24F 15/18
2463993	12/1948	Meyers	D3/319	A45C 3/06
5127720	12/1991	Shultz	206/39	A63F 3/068
6568555	12/2002	LoCascio	N/A	N/A
D493267	12/2003	Strobel	N/A	N/A
6994132	12/2005	Antrobus	190/110	A45C 5/065
2007/0138184	12/2006	Smith	N/A	N/A
2007/0216269	12/2006	Kischitz	N/A	N/A
2022/0212863	12/2021	Gann	N/A	N/A
2022/0356011	12/2021	Beegle	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO2007075700	12/2006	WO	N/A

Primary Examiner: Chu; King M

Background/Summary

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(1) The disclosure relates to trash receptacles and more particularly pertains to a new trash receptacle for storing garbage and other objects.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(2) Myriad trash receptacles are disclosed by the prior art, but the prior art fails to describe such a trash receptacle which includes a storage compartment below a garbage-holding container with a drawer that can slide either of two lateral directions with respect to the container to access the drawer's contents.

BRIEF SUMMARY OF THE INVENTION

(3) An embodiment of the disclosure meets the needs presented above by generally comprising a container with a base wall and a perimeter wall. The perimeter wall is coupled to and extends upwardly from the base wall, and an upper edge of the perimeter wall defines an opening to the container. A storage compartment is coupled to the base wall of the container and comprises a

tubular wall and a drawer. The tubular wall defines a channel which extends laterally with respect to the container and defines a pair of apertures to the channel which are laterally spaced with respect to the container. The drawer is slidably coupled to the tubular wall.

(4) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(5) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

(1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

(2) FIG. 1 is a perspective view of a trash receptacle according to an embodiment of the disclosure.

(3) FIG. 2 is an exploded view of an embodiment of the disclosure.

(4) FIG. 3 is a front view of an embodiment of the disclosure.

(5) FIG. 4 is a back view of an embodiment of the disclosure.

(6) FIG. 5 is a top view of an embodiment of the disclosure.

(7) FIG. 6 is a cross-section view of an embodiment of the disclosure taken from Arrows 6-6 in FIG. 5.

(8) FIG. 7 is a side view of an embodiment of the disclosure.

(9) FIG. 8 is a bottom view of an embodiment of the disclosure.

(10) FIG. 9 is an in-use view of an embodiment of the disclosure.

(11) FIG. 10 is a detail view of a liner of an embodiment of the disclosure supporting a pair of bags.

DETAILED DESCRIPTION OF THE INVENTION

(12) With reference now to the drawings, and in particular to FIGS. 1 through 10 thereof, a new trash receptacle embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.

(13) As best illustrated in FIGS. 1 through 10, the trash receptacle 10 generally comprises a container 12 with a base wall 14 and a perimeter wall 16. The perimeter wall 16 is coupled to and extends upwardly from the base wall 14, and an upper edge 18 of the perimeter wall 16 defines an opening 20 to the container 12. The base wall 14 has a rectangular shape. A storage compartment 22 is coupled to the base wall 14 of the container 12. The storage compartment 22 comprises a tubular wall 24 and a drawer 30. The tubular wall 24 defines a channel 26 which extends laterally with respect to the container 12 and defines a pair of apertures 28 to the channel 26. The apertures 28 are laterally spaced with respect to the container 12, and the channel 26 has a rectangular cross section. The drawer 30 is slidably coupled to the tubular wall 24 and is complementary in shape to the channel 26. The drawer 30 defines a cavity 32 which extends downwardly into the drawer 30. The drawer 30 has a pair of handles 34, each of which is positioned on an associated lateral side 36 of a pair of lateral sides 36 of the drawer 30.

(14) A liner 38 is removably positionable in the container 12. The liner 38 has a bottom wall 40 and a peripheral wall 42, the peripheral wall 42 being coupled to and extending upwardly from the bottom wall 40. A top edge 50 of the peripheral wall 42 defines a front notch 52 and a rear notch

54. The front notch **52** is positioned on a front portion **44** of the peripheral wall **42**, and the rear notch **54** is positioned on a rear portion **46** of the peripheral wall **42**. The front notch **52** and the rear notch **54** define a pair of lateral segments **56** of the top edge **50**, each of which is configured for supporting a rim **66** of an associated bag **64** of a pair of bags **64**. The front notch **52** and the rear notch **54** are centered between a pair of lateral portions **48** of the peripheral wall **42**. The top edge **50** of the peripheral wall **42** is positioned below the upper edge **18** of the container **12** when the liner **38** is positioned in the container **12**.

(15) A lid **58** is pivotably coupled to the container **12** and is movable to alternately open and close the opening **20**. A pair of hooks **60** is removably mountable to the container **12**. The pair of hooks **60** extends upwardly past the upper edge **18** of the container **12** when mounted to the container **12** and is configured to hang the container **12** on a cabinet door **68**. A pair of connectors **62** is engageable with the pair of hooks **60** to mount the pair of hooks **60** to the container **12**. The pair of connectors **62** comprises a pair of threaded fasteners but may comprise a latch, a hook **60**-and-loop fastener, or the like.

(16) In use, the bags **64** are positioned in the liner **38** and laterally positioned with respect to each other, and the liner **38** is positioned in the container **12**. The bags **64** are accessible through the opening **20** by opening **20** the lid **58** and may be used to store garbage. Items may be stored in the drawer **30** of the storage compartment **22**, which are accessible by moving the drawer **30** through either aperture **28** of the pair of apertures **28** of the channel **26**. Such items may include toilet paper, facial tissues, linens, or the like, and the storage compartment **22** may be sized according to the items intended to be stored. The container **12** may be hung onto the cabinet door **68** via the pair of hooks **60**, in which position the drawer **30** may still be accessed through either aperture **28**.

(17) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(18) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A trash receptacle comprising: a container having a base wall and a perimeter wall, the perimeter wall being coupled to and extending upwardly from the base wall, an upper edge of the perimeter wall defining an opening to the container; a storage compartment being coupled to the base wall of the container, the storage compartment comprising a tubular wall and a drawer, the tubular wall defining a channel which extends laterally with respect to the container, the tubular wall defining a pair of apertures to the channel, the pair of apertures being laterally spaced with respect to the container, the drawer being slidably coupled to the tubular wall; and a liner being removably positionable in the container, the liner having a bottom wall and a peripheral wall, the peripheral wall being coupled to and extending upwardly from the bottom wall, a top edge of the peripheral wall defining a front notch and a rear notch, the front notch being positioned on a front portion of

the peripheral wall, the rear notch being positioned on a rear portion of the peripheral wall, the front notch and the rear notch defining a pair of lateral segments of the top edge, each lateral segment of the pair of lateral segments being configured for supporting a rim of an associated bag of a pair of bags.

2. The trash receptacle of claim 1, wherein the drawer defines a cavity which extends downwardly into the drawer.

3. The trash receptacle of claim 1, wherein the drawer has a pair of handles, each handle of the pair of handles being positioned on an associated lateral side of a pair of lateral sides of the drawer.

4. The trash receptacle of claim 1, wherein the front notch and the rear notch are centered between a pair of lateral portions of the peripheral wall.

5. The trash receptacle of claim 1, wherein the top edge of the peripheral wall is positioned below the upper edge of the container when the liner is positioned in the container.

6. The trash receptacle of claim 1, further comprising a lid being pivotably coupled to the container, the lid being movable to alternately open and close the opening.

7. A trash receptacle comprising: a container having a base wall and a perimeter wall, the perimeter wall being coupled to and extending upwardly from the base wall, an upper edge of the perimeter wall defining an opening to the container; a storage compartment being coupled to the base wall of the container, the storage compartment comprising a tubular wall and a drawer, the tubular wall defining a channel which extends laterally with respect to the container, the tubular wall defining a pair of apertures to the channel, the pair of apertures being laterally spaced with respect to the container, the drawer being slidably coupled to the tubular wall; a pair of hooks being removably mountable to the container, the pair of hooks extending upwardly past the upper edge of the container when mounted to the container, the pair of hooks being configured to hang the container on a cabinet door; and a pair of connectors being engageable with the pair of hooks to mount the pair of hooks to the container, the pair of connectors comprising a pair of threaded fasteners.

8. A trash receptacle comprising: a container having a base wall and a perimeter wall, the perimeter wall being coupled to and extending upwardly from the base wall, an upper edge of the perimeter wall defining an opening to the container, the base wall having a rectangular shape; a storage compartment being coupled to the base wall of the container, the storage compartment comprising a tubular wall and a drawer, the tubular wall defining a channel which extends laterally with respect to the container, the tubular wall defining a pair of apertures to the channel, the pair of apertures being laterally spaced with respect to the container, the channel having a rectangular cross section, the drawer being slidably coupled to the tubular wall, the drawer being complementary in shape to the channel, the drawer defining a cavity which extends downwardly into the drawer, the drawer having a pair of handles, each handle of the pair of handles being positioned on an associated lateral side of a pair of lateral sides of the drawer; a liner being removably positionable in the container, the liner having a bottom wall and a peripheral wall, the peripheral wall being coupled to and extending upwardly from the bottom wall, a top edge of the peripheral wall defining a front notch and a rear notch, the front notch being positioned on a front portion of the peripheral wall, the rear notch being positioned on a rear portion of the peripheral wall, the front notch and the rear notch defining a pair of lateral segments of the top edge, each lateral segment of the pair of lateral segments being configured for supporting a rim of an associated bag of a pair of bags, the front notch and the rear notch being centered between a pair of lateral portions of the peripheral wall, the top edge of the peripheral wall being positioned below the upper edge of the container when the liner is positioned in the container; a lid being pivotably coupled to the container, the lid being movable to alternately open and close the opening; a pair of hooks being removably mountable to the container, the pair of hooks extending upwardly past the upper edge of the container when mounted to the container, the pair of hooks being configured to hang the container on a cabinet door; and a pair of connectors being engageable with the pair of hooks to mount the pair of hooks to the container, the pair of connectors comprising a pair of threaded fasteners.

