

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404929
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Battles; Darin et al.

Coolant tube seal

Abstract

A tube seal assembly includes a nipple connected to a first fluid passage and a seal assembly connected to a second fluid passage. The seal assembly includes a cylindrical member attached to the second fluid passage and having a radially extending flange. A seal member includes a metal reinforcement with a cylindrical outer wall and a radially inwardly extending flange at a first end of the cylindrical outer wall. An over-molded seal body includes a locking feature on an interior surface of the cylindrical outer wall that engages the radially extending flange to retain the seal member to the cylindrical member. The over-molded seal body further includes a first sealing lip extending from the radially inwardly extending flange and received against an inner wall of the cylindrical member. An interior surface of the first sealing lip includes a sealing bead engaging the nipple.

Inventors:	Battles; Darin (Dahlonge, GA), Blake; Michael (Northville, MI)
Applicant:	Freudenberg-NOK General Partnership (Plymouth, MI)
Family ID:	94388165
Assignee:	Freudenberg-NOK General Partnership (Plymouth, MI)
Appl. No.:	18/363866
Filed:	August 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250043864 A1	Feb. 06, 2025

Publication Classification

Int. Cl.: F16J15/02 (20060101)

U.S. Cl.:

CPC F16J15/022 (20130101);

Field of Classification Search

CPC: F16J (15/022); F16J (15/024); F16J (15/025); F16J (15/3252); F16L (17/02); F16L (17/03); F16L (17/035); F16L (25/12); F16L (25/14); F16L (21/02); F16L (21/022)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1843927	12/1931	Manchester	285/379	F16L 27/0845
3997195	12/1975	Bartholomew	285/915	F16L 37/05
12188561	12/2024	Hernandez- Vazquez	N/A	F16J 15/3224
2009/0023056	12/2008	Adams	29/890.035	B60L 58/25
2024/0125390	12/2023	Hernandez- Vazquez	N/A	F16J 15/322

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2009037051	12/2008	WO	F16L 21/005

Primary Examiner: Foster; Nicholas L

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

FIELD

(1) The present disclosure relates to a coolant tube seal.

BACKGROUND

(2) This section provides background information related to the present disclosure which is not necessarily prior art.

(3) Battery packs typically consist of multiple battery modules. Each module can include an enclosure with a group of battery cells. In order to prevent the temperature of the battery cells from becoming too high, the module often includes a radiator type cooling plate. Coolant is distributed thru the battery pack via a manifold. Two lines from the manifold (supply/return) would typically connect via nipples attached to the cooling plate. The purpose of the present disclosure is to provide an improved seal assembly between a battery pack cooling manifold and a battery module cooling plate. The current sealing solution consists of one or more O-rings and a pair of other components that position the O-ring(s) at the end of the tube assembly.

SUMMARY

(4) This section provides a general summary of the disclosure, and is not a comprehensive

disclosure of its full scope or all of its features.

(5) According to an aspect of the present disclosure, a tube seal assembly is provided for connecting two fluid passages. The tube seal assembly includes a nipple connected to a first fluid passage and a seal assembly connected to a second fluid passage. The seal assembly includes a cylindrical member attached to the second fluid passage and having a radially extending flange. A seal member includes a metal reinforcement with a cylindrical outer wall and a radially inwardly extending flange at a first end of the cylindrical outer wall. An over-molded seal body includes a locking feature on an interior surface of the cylindrical outer wall that engages the radially extending flange to retain the seal member to the cylindrical member. The over-molded seal body further includes a first sealing lip extending from the radially inwardly extending flange and received against an inner wall of the cylindrical member. An interior surface of the first sealing lip includes a sealing bead engaging the nipple.

(6) According to another aspect, the over-molded seal body includes a second sealing lip extending from a second end of the cylindrical outer wall of the metal reinforcement and engaging the cylindrical member.

(7) According to another aspect, the second sealing lip extends radially inwardly at an angle from the second end of the cylindrical outer wall of the metal reinforcement.

(8) According to another aspect, the over-molded seal body includes a third sealing lip extending from the radially inwardly extending flange of the metal reinforcement in a direction opposite to the first sealing lip.

(9) According to another aspect, the third sealing lip extends radially outwardly at an angle from the radially inwardly extending flange of the metal reinforcement.

(10) According to another aspect, the sealing bead of the first sealing lip includes a pair of sealing beads engaging the nipple.

(11) According to another aspect, the pair of sealing beads are compressed against the nipple.

(12) Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

(2) FIG. 1 is a cross-sectional view of a tube seal assembly according to the principles of the present disclosure; and

(3) FIG. 2 is a cross-sectional view of the seal member according to the principles of the present disclosure.

(4) Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

(5) Example embodiments will now be described more fully with reference to the accompanying drawings.

(6) With reference to FIGS. 1 and 2, a tube seal assembly **10** will now be described. With reference to FIG. 1, the tube seal assembly **10** provides a connection between a first fluid passage **12** through a tube **14** and a second fluid passage **16** through a nipple **18**. An attachment member **20** includes a first cylindrical portion **20a** that can be crimped to the tube **14** and includes a second cylindrical portion **20b** radially outwardly extending flange **20b1** at a second end. Alternatively, the cylindrical member can be formed as a one-piece design with an end of the tube **14**. A seal member **22**

includes a cup-shaped metal reinforcement **24** with a cylindrical outer wall **26** and a radially inwardly extending flange **28** at a first end of the cylindrical outer wall **26**. The nipple **18** can be mounted to a radiator cooling plate **29** or other structure.

(7) A seal body **30** is over-molded on the cup-shaped metal reinforcement **24** and includes a locking feature **32** in the form of a raised rib extending radially inward from an interior surface of the cylindrical outer wall **26**. The locking feature **32** engages the radially extending flange **20b** of the attachment member **20** to retain the seal member **22** to the attachment member **20**. The seal body **30** further includes a first sealing lip **34** extending from the radially inwardly extending flange **28** and received against an inner wall of the second cylindrical portion **20b** of the attachment member **20**. An interior surface of the first sealing lip **34** includes a pair of annular sealing beads **36, 38** for sealingly engaging the nipple **18**. It should be understood that a single sealing bead **36** can be used or that a larger number of sealing beads can be used. The pair of sealing beads **36, 38** are compressed against the nipple **18** by the second cylindrical portion **20b** of the attachment member **20**.

(8) The seal body **30** includes a second sealing lip **40** extending from a second end of the cylindrical outer wall **26** of the metal reinforcement **24** and engaging the attachment member **20**. The second sealing lip **40** extends radially inwardly at an angle of less than 45 degrees from the second end of the cylindrical outer wall **26** of the metal reinforcement **24**. The second sealing lip **40** seals radially onto the attachment member **20** of the tube to prevent hot gases and particles from reaching the primary coolant sealing lips **36, 38** that engage the nipple **18**. The second sealing lip **40** defines a dead air space **41** interior of the seal member to provide further thermal isolation for the inner sealing lips **36, 38**.

(9) The seal body **30** further includes a third sealing lip **42** extending from the radially inwardly extending flange **28** of the metal reinforcement **24** in a direction opposite to a direction of the first sealing lip **34**. The third sealing lip **42** extends radially outwardly at an angle of approximately 45 degrees from the radially inwardly extending flange **28** of the metal reinforcement **24**. The third sealing lip **42** can press against the radiator cooling plate **29** and flare outward when installed, creating a seal to prevent hot particles and gasses from reaching the inner sealing beads. The third sealing lip **42** defines a dead air space **43** interior of the third sealing lip **42** to provide further thermal isolation for the inner sealing lips **36, 38**. The flared third sealing lip **42** also aids in aligning the seal assembly **10** with the nipple **18** during assembly.

(10) The improved seal assembly **10** includes a single piece elastomer **30** with a bonded metallic reinforcement **24**. The proposed seal assembly **10** provides better protection of the sealing element during the occurrence of a thermal event within the battery pack. In addition, the proposed seal assembly **10** consolidates the function of multiple current components into a single component. The proposed seal assembly **10** includes a primary coolant seal **36** and a secondary backup coolant seal **38**. The second sealing lip **40** and the third sealing lip **42** provide a continuous external barrier to prevent hot gases from reaching the primary and secondary coolant seals **36, 38**.

(11) Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

(12) The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify

the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

(13) When an element or layer is referred to as being “on,” “engaged to,” “connected to,” or “coupled to” another element or layer, it may be directly on, engaged, connected or coupled to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly connected to,” or “directly coupled to” another element or layer, there may be no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(14) Although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as “first,” “second,” and other numerical terms when used herein do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example embodiments.

(15) Spatially relative terms, such as “inner,” “outer,” “beneath,” “below,” “lower,” “above,” “upper,” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. Spatially relative terms may be intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the example term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

(16) The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

Claims

1. A tube seal assembly for connecting two fluid passages, comprising: a nipple connected to a first fluid passage; and a seal assembly connected to a second fluid passage, the seal assembly including: an attachment member attached to the second fluid passage and having a radially extending flange, a seal member includes a metal reinforcement with a cylindrical outer wall and a radially inwardly extending flange at a first end of the cylindrical outer wall, an over-molded seal body including a locking feature, the over-molded seal body positioned on an interior surface of the cylindrical outer wall and engaging the radially extending flange of the attachment member to retain the seal member to the attachment member, the over-molded seal body further includes a first

sealing lip extending from the radially inwardly extending flange and received against an inner wall of the attachment member, an interior surface of the first sealing lip including a sealing bead engaging the nipple.

2. The tube seal assembly according to claim 1, wherein the over-molded seal body includes a second sealing lip extending from a second end of the cylindrical outer wall of the metal reinforcement and engaging the attachment member.

3. The tube seal assembly according to claim 2, wherein the second sealing lip extends radially inwardly at an angle from the second end of the cylindrical outer wall of the metal reinforcement.

4. The tube seal assembly according to claim 2, wherein the over-molded seal body includes a third sealing lip extending from the radially inwardly extending flange of the metal reinforcement in a direction opposite to the first sealing lip.

5. The tube seal assembly according to claim 4, wherein the third sealing lip extends radially outwardly at an angle from the radially inwardly extending flange of the metal reinforcement.

6. The tube seal assembly according to claim 1, comprising a second sealing bead on the interior surface of the first sealing lip, the second sealing bead engaging the nipple.

7. The tube seal assembly according to claim 6, wherein the sealing beads are compressed against the nipple.
