

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407515
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tan; Danilo Ong et al.

Codec management at an information handling system

Abstract

Enabling codecs at an IHS including: accessing a local token store that stores tokens, each token associated with a codec; identifying codecs enabled at the IHS based on the tokens; receiving a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining that the particular codec is not enabled at the IHS based on the previously identified enabled codecs, and in response, transmitting a request to a cloud codec management service; receiving the particular token, the particular token signed and unique to the IHS, and in response, storing the particular token at the local token store; restarting the driver, and in response, accessing the local token store; obtaining from the local token store, the particular token, and in response, enabling the particular codec for the media file.

Inventors:	Tan; Danilo Ong (Austin, TX), Gillespie; Douglas Wayne (Anna, TX)
Applicant:	Dell Products L.P. (Round Rock, TX)
Family ID:	94481392
Assignee:	Dell Products L.P. (Round Rock, TX)
Appl. No.:	18/448280
Filed:	August 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250055689 A1	Feb. 13, 2025

Publication Classification

Int. Cl.: H04L29/06 (20060101); H04L9/32 (20060101)

U.S. Cl.:

Field of Classification Search

CPC: H04L (9/3213); H04L (2209/34)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11461771	12/2021	Coburn	N/A	G06F 16/2255
11665382	12/2022	Ericson	713/171	H04L 9/0825
2008/0080694	12/2007	Usuba	379/219	H04M 1/2535
2017/0244688	12/2016	Kim	N/A	H04L 63/107
2021/0178996	12/2020	Verma	N/A	G07C 5/0808
2024/0187619	12/2023	Zhang	N/A	H04N 19/42
2025/0056023	12/2024	Tan	N/A	H04N 19/42

Primary Examiner: Rahman; Shawnchoy

Attorney, Agent or Firm: McDermott Will & Schulte LLP

Background/Summary

BACKGROUND

Field of the Disclosure

(1) The disclosure relates generally to an information handling system, and in particular, codec management at the information handling system.

Description of the Related Art

(2) As the value and use of information continues to increase, individuals and businesses seek additional ways to process and store information. One option available to users is information handling systems. An information handling system generally processes, compiles, stores, and/or communicates information or data for business, personal, or other purposes thereby allowing users to take advantage of the value of the information. Because technology and information handling needs and requirements vary between different users or applications, information handling systems may also vary regarding what information is handled, how the information is handled, how much information is processed, stored, or communicated, and how quickly and efficiently the information may be processed, stored, or communicated. The variations in information handling systems allow for information handling systems to be general or configured for a specific user or specific use such as financial transaction processing, airline reservations, enterprise data storage, or global communications. In addition, information handling systems may include a variety of hardware and software components that may be configured to process, store, and communicate information and may include one or more computer systems, data storage systems, and networking systems.

SUMMARY

(3) Innovative aspects of the subject matter described in this specification may be embodied in a method of enabling codecs at an information handling system, including: accessing, by a driver, a local token store at a first time that stores one or more tokens, each token associated with a codec;

identifying, by the driver, one or more codecs enabled at the information handling system based on the tokens stored by the local token store; receiving, at a media framework, a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining, by the driver, that the particular codec is not enabled at the information handling system based on the previously identified enabled codecs; in response to determining that the particular codec is not enabled at the information handling system, transmitting a request to a cloud codec management service; receiving, from the cloud codec management service, the particular token, the particular token signed and unique to the information handling system; in response to receiving the particular token: storing the particular token at the local token store; restarting the driver, and in response, accessing, by the driver, the local token store at a second time after the first time; obtaining, by the driver and from the local token store, the particular token; and in response to obtaining the particular token, enabling, by the driver, the particular codec for the media file.

(4) Other embodiments of these aspects include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices.

(5) These and other embodiments may each optionally include one or more of the following features. For instance, in response to enabling the particular codec, encoding the media file utilizing the particular codec. In response to enabling the particular codec, decoding the media file utilizing the particular codec. Generating, at the cloud codec management service, the particular token; signing, at the cloud codec management service, the particular token as unique to the information handling system; and providing, by the cloud codec management service, the particular token to the information handling system. Storing, by the cloud codec management service and at a cloud data store, data indicating the generation of the particular token. In response to receiving the particular token: verifying the particular token, and in response, storing the particular token at the local token store. In response to obtaining the particular token: verifying the particular token, and in response, enabling, by the driver, the particular codec for the media file. In response to determining that the particular codec is not enabled at the information handling system: displaying, upon a display of the information handling system, a notification indicating that the particular codec is not enabled at the information handling system; and receiving, in response to the notification, user input indicating enablement of the codec. In response to receiving the user input, transmitting the request to the cloud codec management service.

(6) The details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other potential features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a block diagram of selected elements of an embodiment of an information handling system.

(2) FIG. 2 illustrates a block diagram of an information handling system for codec management at the information handling system.

(3) FIG. 3 illustrates a method for codec management at the information handling system.

DESCRIPTION OF PARTICULAR EMBODIMENT(S)

(4) This disclosure discusses methods and systems for codec management of an information handling system. In short, codecs at the information handling system can be initially disabled until the codec is needed to decode or encode a media file. The information handling system can communicate with a cloud codec management service to receive an appropriate token for

enablement of such a codec. When the token is received for a codec, the media file then can be encoded or decoded utilizing the codec.

(5) Specifically, this disclosure discusses a system and a method for enabling codecs at an information handling system, including accessing, by a driver, a local token store at a first time that stores one or more tokens, each token associated with a codec; identifying, by the driver, one or more codecs enabled at the information handling system based on the tokens stored by the local token store; receiving, at a media framework, a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining, by the driver, that the particular codec is not enabled at the information handling system based on the previously identified enabled codecs; in response to determining that the particular codec is not enabled at the information handling system, transmitting a request to a cloud codec management service; receiving, from the cloud codec management service, the particular token, the particular token signed and unique to the information handling system; in response to receiving the particular token: storing the particular token at the local token store; restarting the driver, and in response, accessing, by the driver, the local token store at a second time after the first time; obtaining, by the driver and from the local token store, the particular token; and in response to obtaining the particular token, enabling, by the driver, the particular codec for the media file.

(6) In the following description, details are set forth by way of example to facilitate discussion of the disclosed subject matter. It should be apparent to a person of ordinary skill in the field, however, that the disclosed embodiments are exemplary and not exhaustive of all possible embodiments.

(7) For the purposes of this disclosure, an information handling system may include an instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize various forms of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For example, an information handling system may be a personal computer, a PDA, a consumer electronic device, a network storage device, or another suitable device and may vary in size, shape, performance, functionality, and price. The information handling system may include memory, one or more processing resources such as a central processing unit (CPU) or hardware or software control logic. Additional components of the information handling system may include one or more storage devices, one or more communications ports for communicating with external devices as well as various input and output (I/O) devices, such as a keyboard, a mouse, and a video display. The information handling system may also include one or more buses operable to transmit communication between the various hardware components.

(8) For the purposes of this disclosure, computer-readable media may include an instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. Computer-readable media may include, without limitation, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), and/or flash memory (SSD); as well as communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing.

(9) Particular embodiments are best understood by reference to FIGS. **1-3** wherein like numbers are used to indicate like and corresponding parts.

(10) Turning now to the drawings, FIG. **1** illustrates a block diagram depicting selected elements of an information handling system **100** in accordance with some embodiments of the present disclosure. In various embodiments, information handling system **100** may represent different types of portable information handling systems, such as, display devices, head mounted displays, head mount display systems, smart phones, tablet computers, notebook computers, media players, digital

cameras, 2-in-1 tablet-laptop combination computers, and wireless organizers, or other types of portable information handling systems. In one or more embodiments, information handling system **100** may also represent other types of information handling systems, including desktop computers, server systems, controllers, and microcontroller units, among other types of information handling systems. Components of information handling system **100** may include, but are not limited to, a processor subsystem **120**, which may comprise one or more processors, and system bus **121** that communicatively couples various system components to processor subsystem **120** including, for example, a memory subsystem **130**, an I/O subsystem **140**, a local storage resource **150**, and a network interface **160**. System bus **121** may represent a variety of suitable types of bus structures, e.g., a memory bus, a peripheral bus, or a local bus using various bus architectures in selected embodiments. For example, such architectures may include, but are not limited to, Micro Channel Architecture (MCA) bus, Industry Standard Architecture (ISA) bus, Enhanced ISA (EISA) bus, Peripheral Component Interconnect (PCI) bus, PCI-Express bus, HyperTransport (HT) bus, and Video Electronics Standards Association (VESA) local bus.

(11) As depicted in FIG. **1**, processor subsystem **120** may comprise a system, device, or apparatus operable to interpret and/or execute program instructions and/or process data, and may include a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or another digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor subsystem **120** may interpret and/or execute program instructions and/or process data stored locally (e.g., in memory subsystem **130** and/or another component of information handling system). In the same or alternative embodiments, processor subsystem **120** may interpret and/or execute program instructions and/or process data stored remotely (e.g., in network storage resource **170**).

(12) Also in FIG. **1**, memory subsystem **130** may comprise a system, device, or apparatus operable to retain and/or retrieve program instructions and/or data for a period of time (e.g., computer-readable media). Memory subsystem **130** may comprise random access memory (RAM), electrically erasable programmable read-only memory (EEPROM), a PCMCIA card, flash memory, magnetic storage, opto-magnetic storage, and/or a suitable selection and/or array of volatile or non-volatile memory that retains data after power to its associated information handling system, such as system **100**, is powered down.

(13) In information handling system **100**, I/O subsystem **140** may comprise a system, device, or apparatus generally operable to receive and/or transmit data to/from/within information handling system **100**. I/O subsystem **140** may represent, for example, a variety of communication interfaces, graphics interfaces, video interfaces, user input interfaces, and/or peripheral interfaces. In various embodiments, I/O subsystem **140** may be used to support various peripheral devices, such as a touch panel, a display adapter, a keyboard, an accelerometer, a touch pad, a gyroscope, an IR sensor, a microphone, a sensor, or a camera, or another type of peripheral device.

(14) Local storage resource **150** may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or another type of solid state storage media) and may be generally operable to store instructions and/or data. Likewise, the network storage resource may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or other type of solid state storage media) and may be generally operable to store instructions and/or data.

(15) In FIG. **1**, network interface **160** may be a suitable system, apparatus, or device operable to serve as an interface between information handling system **100** and a network **110**. Network interface **160** may enable information handling system **100** to communicate over network **110** using a suitable transmission protocol and/or standard, including, but not limited to, transmission protocols and/or standards enumerated below with respect to the discussion of network **110**. In some embodiments, network interface **160** may be communicatively coupled via network **110** to a

network storage resource **170**. Network **110** may be a public network or a private (e.g. corporate) network. The network may be implemented as, or may be a part of, a storage area network (SAN), personal area network (PAN), local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), a wireless local area network (WLAN), a virtual private network (VPN), an intranet, the Internet or another appropriate architecture or system that facilitates the communication of signals, data and/or messages (generally referred to as data). Network interface **160** may enable wired and/or wireless communications (e.g., NFC or Bluetooth) to and/or from information handling system **100**.

(16) In particular embodiments, network **110** may include one or more routers for routing data between client information handling systems **100** and server information handling systems **100**. A device (e.g., a client information handling system **100** or a server information handling system **100**) on network **110** may be addressed by a corresponding network address including, for example, an Internet protocol (IP) address, an Internet name, a Windows Internet name service (WINS) name, a domain name or other system name. In particular embodiments, network **110** may include one or more logical groupings of network devices such as, for example, one or more sites (e.g. customer sites) or subnets. As an example, a corporate network may include potentially thousands of offices or branches, each with its own subnet (or multiple subnets) having many devices. One or more client information handling systems **100** may communicate with one or more server information handling systems **100** via any suitable connection including, for example, a modem connection, a LAN connection including the Ethernet or a broadband WAN connection including DSL, Cable, T1, T3, Fiber Optics, Wi-Fi, or a mobile network connection including GSM, GPRS, 3G, or WiMax.

(17) Network **110** may transmit data using a desired storage and/or communication protocol, including, but not limited to, Fibre Channel, Frame Relay, Asynchronous Transfer Mode (ATM), Internet protocol (IP), other packet-based protocol, small computer system interface (SCSI), Internet SCSI (iSCSI), Serial Attached SCSI (SAS) or another transport that operates with the SCSI protocol, advanced technology attachment (ATA), serial ATA (SATA), advanced technology attachment packet interface (ATAPI), serial storage architecture (SSA), integrated drive electronics (IDE), and/or any combination thereof. Network **110** and its various components may be implemented using hardware, software, or any combination thereof.

(18) Turning to FIG. 2, FIG. 2 illustrates an environment **200** including an information handling system **202**, a cloud codec management service **204**, a network **206**, a cloud data store **208**, a display **210**, and an user input device **212**. The information handling system **202** can include a codec enablement computing module **220**, a media framework **222**, a driver **224**, a token store **226**, firmware **228**, and a media engine **230**. In some examples, the information handling system **202** is similar to, or includes, the information handling system **100** of FIG. 1.

(19) The information handling system **202** can be in communication with the cloud codec management service **204** over the network **206**. The information handling system **202** can be in communication with the display **210** and the user input device **212**. The codec enablement computing module **220** can be in communication with the driver **224**, the token store **226**, and the cloud codec management service **204**. The media framework **222** can be in communication with the driver **224**. The driver **224** can be in communication with the media framework **222**, the codec enablement computing module **220**, the token store **226**, and the firmware **228**. The token store **226** can be in communication with the codec enablement computing module **220** and the driver **224**. The firmware **228** can be in communication with the driver **224** and the media engine **230**. The media engine **230** can be in communication with the firmware **228**. The cloud codec management server **204** can be in communication with the cloud data store **208**.

(20) In some examples, the media framework **222** is a video framework. In some examples, the driver **224** is a graphics driver (Gfx).

(21) In some examples, the user input device **212** is any user input device or combination of multiple user input devices such as a keyboard, mouse, or similar.

(22) In short, codecs at the information handling system **202** can be initially disabled until the codec is needed to decode or encode a media file. The information handling system **202** can communicate with the cloud codec management service to receive an appropriate token for enablement of such a codec. When the token is received for a codec, the media file than can be encoded or decoded utilizing the codec.

(23) Specifically, the driver **224** accesses the token store **226** at a first time, at A. The local token store **226** stores one or more tokens. Each of the tokens is associated with a respective codec. The driver **224** can receive data identifying the tokens stored at the token store **226**, at B. The driver **224** identifies one or more codecs enabled at the information handling system **202**, at C. That is, the driver **224** identifies codecs enabled at the information handling system **202** based on the tokens stored by the token store **226**. The user **250** can provide user input at the user input device **212**, at D. The user input can indicate a request to encode or decode a media file. The media file can be associated with a particular codec for encoding or decoding of the media file. The information handling system **202** receives the user input. Specifically, the media framework **222** receives the user input.

(24) The media framework **222** can communicate the request with the driver **224**, at E. Specifically, the media framework **222** can communicate data indicating the particular codec, the media file, and/or details of the media file to the driver **224**. The driver **224** can determine that the particular codec is not enabled at the information handling system, at F. That is, the driver **224** can determine that the particular codec is not enabled at the information handling system **202** based on the previously identified enabled codecs. Specifically, based on the previous access of the token store **226** to identify codecs enabled by the tokens at the token store **226** (at steps A and B), the driver **224** can determine that the particular codec is not enabled at the information handling system **202**. The driver **224** can provide data indicating that the particular codec is not enabled at the information handling system **202** to the codec enablement computing module **220**, at G. In some examples, the driver **224** can perform steps A and B in response to receiving the request, at E.

(25) The codec enablement computing module **220** provides for display, upon the display **210**, a notification indicating that the particular codec is not enabled at the information handling system **202**, at H. In some examples, the notification can further indicate that encoding or decoding of the media file has failed. The user **250** provides user input, in response to the notification, indicating enablement of the codec, at I. The information handling system **202**, and in particular, the codec enablement computing module **220**, receives the user input indicating the enablement of the codec.

(26) The codec enablement computing module **220**, in response to receiving the user input, transmits a request to the cloud codec management service **204**, e.g., over the network **206**, at J. In other words, in response to the driver **224** determining that the particular codec is not enabled at the information handling system **202**, the codec enablement computing module **220** transmits the request to the cloud codec management service **204**. The request can include a request for a token for enablement of the codec at the information handling system **202**.

(27) The cloud codec management service **204** generates the particular token, at K. Further, the cloud codec management service **204** signs the particular token as unique to the information handling system **202**, at K. That is, the particular token is tied to the information handling system **202** (platform) via serviceTag. The cloud codec management service **204** stores, at the cloud data store **208**, data indicating the generation of the particular token, at L. That is, the cloud codec management service **204** tracks enablement of codecs at the information handling system **202** via generation of tokens associated with the codecs. The cloud codec management service **204** provides, over the network **206**, the particular token to the information handling system **202**, at M. Specifically, the codec enablement computing module **220** receives the particular token from the cloud codec management service **202**. The particular token is signed and unique to the information handling system **202**.

(28) In response to receiving the particular token, the codec enablement computing module **220**

verifies the particular token, at N. In some examples, verifying the particular token can include determining if an identification (ID) (e.g., svctag) of the particular token matches an ID of the information handling system **202**. The codec enablement computing module **220**, in response to verifying the particular token (at N), stores the particular token at the token store **226**, at O. That is, in response to receiving the particular token (at M) and verifying the particular token (at N), the codec enablement computing module **220** store the particular token at the token store **226**. In some examples, storing the particular token at the token store **226** can include storing the particular token as a UEFI variable, at a registry, or as a file.

(29) The codec enablement computing module **220** transmit a signal to restart the driver **224**, at P. In some examples, the information handling system **202** can be rebooted to restart the driver **224**. The driver **224** can be restarted, at Q. In response to the driver **224** restarting, the driver **224** can access the token store **226** at a second time after the first time, at R. The driver **224** can obtain from the token store **226** the particular token, at S. The driver **224**, in response to obtaining the particular token from the token store **226** (at S), verifies the particular token, at T. In some examples, verifying the particular token can include determining if an identification (ID) (e.g., svctag) of the particular token matches an ID of the information handling system **202**. The driver **224**, in response to verifying the particular token, enables the particular codec for the media file, at U. That is, the driver **224**, in response to obtaining the particular token from the token store **226** and verifying the particular token, enables the particular codec for the media file, at U. The driver **224** provides the enabled codec to the media engine **230** through the firmware **228**, at V and W. In some examples, in response to enabling the particular codec, the media engine **230** and/or the driver **224** can encode the media file utilizing the particular codec. In some examples, in response to enabling the particular codec, the media engine **230** and/or the driver **224** can decode the media file utilizing the particular codec.

(30) FIG. **3** illustrates a flowchart depicting selected elements of an embodiment of a method **300** for codec management of an information handling system **202**. The method **300** may be performed by the information handling system **100**, the information handling system **202**, and/or the cloud codec management service **204**, and with reference to FIGS. **1-2**. It is noted that certain operations described in method **300** may be optional or may be rearranged in different embodiments.

(31) The driver **224** accesses the token store **226** at a first time, at **302**. The driver **224** identifies codecs enabled at the information handling system **202** based on the tokens stored by the token store **226**, at **304**. The media framework **222** receives a request to encode or decode a media file, at **306**. The driver **224** determines whether a particular codec is enabled at the information handling system **202** based on the previously identified enabled codecs, at **308**. The particular codec is for encoding or decoding the media file.

(32) In some examples, the driver **224** determines that the particular codec is not enabled at the information handling system **202**, and in response, the codec enablement computing module **220** transmits a request to the cloud codec management service **204**, at **310**. The request can be for a particular token associated with the particular codec. The codec enablement computing module **220** receives, from the cloud codec management service **204**, the particular token, at **312**. The codec enablement computing module **220**, in response to receiving the particular token, stores the particular token at the token store **226**, at **314**. The codec enablement computing module **220** restarts the driver **224**, at **316**. The driver **224** accesses the token store **226** at a second time after the first time, at **318**. The driver **224** obtains from the token store **226** the particular token, at **320**. The driver **224**, in response to obtaining the particular token, enables the particular codec for the media file, at **322**.

(33) In some examples, the driver **224** determines that the particular codec is enabled at the information handling system **202**, and in response, proceeds to step **320**.

(34) The above disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other

embodiments which fall within the true spirit and scope of the present disclosure. Thus, to the maximum extent allowed by law, the scope of the present disclosure is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

(35) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(36) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, features, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

Claims

1. A computer-implemented method of enabling codecs at an information handling system, the method comprising: accessing, by a driver, a local token store at a first time that stores one or more tokens, each token associated with a codec; identifying, by the driver, one or more codecs enabled at the information handling system based on the tokens stored by the local token store; receiving, at a media framework, a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining, by the driver, that the particular codec is not enabled at the information handling system based on the previously identified enabled codecs; in response to determining that the particular codec is not enabled at the information handling system, transmitting a request to a cloud codec management service; receiving, from the cloud codec management service, the particular token, the particular token signed and unique to the information handling system; in response to receiving the particular token: storing the particular token at the local token store; restarting the driver, and in response, accessing, by the driver, the local token store at a second time after the first time; obtaining, by the driver and from the local token store, the particular token; and in response to obtaining the particular token, enabling, by the driver, the particular codec for the media file.
2. The computer-implemented method of claim 1, further including: in response to enabling the particular codec, encoding the media file utilizing the particular codec.
3. The computer-implemented method of claim 1, further including: in response to enabling the particular codec, decoding the media file utilizing the particular codec.
4. The computer-implemented method of claim 1, further including: generating, at the cloud codec management service, the particular token; signing, at the cloud codec management service, the particular token as unique to the information handling system; and providing, by the cloud codec management service, the particular token to the information handling system.

5. The computer-implemented method of claim 4, further including: storing, by the cloud codec management service and at a cloud data store, data indicating the generation of the particular token.
6. The computer-implemented method of claim 1, further in response to receiving the particular token: verifying the particular token, and in response, storing the particular token at the local token store.
7. The computer-implemented method of claim 6, further in response to obtaining the particular token: verifying the particular token, and in response, enabling, by the driver, the particular codec for the media file.
8. The computer-implemented method of claim 1, further in response to determining that the particular codec is not enabled at the information handling system: displaying, upon a display of the information handling system, a notification indicating that the particular codec is not enabled at the information handling system; and receiving, in response to the notification, user input indicating enablement of the codec.
9. The computer-implemented method of claim 8, in response to receiving the user input, transmitting the request to the cloud codec management service.
10. An information handling system comprising a processor having access to memory media storing instructions executable by the processor to perform operations, comprising: accessing, by a driver, a local token store at a first time that stores one or more tokens, each token associated with a codec; identifying, by the driver, one or more codecs enabled at the information handling system based on the tokens stored by the local token store; receiving, at a media framework, a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining, by the driver, that the particular codec is not enabled at the information handling system based on the previously identified enabled codecs; in response to determining that the particular codec is not enabled at the information handling system, transmitting a request to a cloud codec management service; receiving, from the cloud codec management service, the particular token, the particular token signed and unique to the information handling system; in response to receiving the particular token: storing the particular token at the local token store; restarting the driver, and in response, accessing, by the driver, the local token store at a second time after the first time; obtaining, by the driver and from the local token store, the particular token; and in response to obtaining the particular token, enabling, by the driver, the particular codec for the media file.
11. The information handling system of claim 10, the operations further including: in response to enabling the particular codec, encoding the media file utilizing the particular codec.
12. The information handling system of claim 10, the operations further including: in response to enabling the particular codec, decoding the media file utilizing the particular codec.
13. The information handling system of claim 10, the operations further including: generating, at the cloud codec management service, the particular token; signing, at the cloud codec management service, the particular token as unique to the information handling system; and providing, by the cloud codec management service, the particular token to the information handling system.
14. The information handling system of claim 13, the operations further including: storing, by the cloud codec management service and at a cloud data store, data indicating the generation of the particular token.
15. The information handling system of claim 10, the operations further in response to receiving the particular token: verifying the particular token, and in response, storing the particular token at the local token store.
16. The information handling system of claim 15, the operations further in response to obtaining the particular token: verifying the particular token, and in response, enabling, by the driver, the particular codec for the media file.
17. The information handling system of claim 10, the operations further in response to determining that the particular codec is not enabled at the information handling system: displaying, upon a

display of the information handling system, a notification indicating that the particular codec is not enabled at the information handling system; and receiving, in response to the notification, user input indicating enablement of the codec.

18. The information handling system of claim 17, the operations in response to receiving the user input, transmitting the request to the cloud codec management service.

19. A non-transitory computer-readable medium storing software comprising instructions executable by one or more computers which, upon such execution, cause the one or more computers to perform operations comprising: accessing, by a driver, a local token store at a first time that stores one or more tokens, each token associated with a codec; identifying, by the driver, one or more codecs enabled at the information handling system based on the tokens stored by the local token store; receiving, at a media framework, a request to encode or decode a media file, the media file associated with a particular codec for encoding or decoding of the media file; determining, by the driver, that the particular codec is not enabled at the information handling system based on the previously identified enabled codecs; in response to determining that the particular codec is not enabled at the information handling system, transmitting a request to a cloud codec management service; receiving, from the cloud codec management service, the particular token, the particular token signed and unique to the information handling system; in response to receiving the particular token: storing the particular token at the local token store; restarting the driver, and in response, accessing, by the driver, the local token store at a second time after the first time; obtaining, by the driver and from the local token store, the particular token; and in response to obtaining the particular token, enabling, by the driver, the particular codec for the media file.

20. The non-transitory computer-readable medium of claim 19, the operations further including: in response to enabling the particular codec, encoding the media file utilizing the particular codec.
