

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281032

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

HUANG; Wei et al.

STEERABLE ORTHOPEDIC ENDOSCOPIC SYSTEM WITH NAVIGATION FUNCTION

Abstract

The present disclosure belongs to the technical field of orthopedic surgery, and in particular, to a steerable orthopedic endoscope system with navigation function. The system includes a handle, an endoscope body, a rotating adjustment component, an angle detection component, a processor, an optical navigation component, and an electromagnetic navigation component. The endoscope body includes a rod portion, a bendable portion, and a lens. The bendable portion is internally provided with bending sections. The rotating adjustment component includes a rotating wheel and two pull wires. The angle detection component includes a marker arranged on the rotating wheel and a detection device configured to identify the marker. The processor is electrically connected to the angle detection component and the rotating adjustment component.

Inventors: HUANG; Wei (Chongqing, CN), ZHAO; Chen (Chongqing, CN), XIA; Guifeng (Chongqing, CN), HU; Ning (Chongqing, CN), SHUI; Wei (Chongqing, CN)

Applicant: THE FIRST AFFILIATED HOSPITAL OF CHONGQING MEDICAL UNIVERSITY (Chongqing, CN)

Family ID: 1000008474218

Appl. No.: 19/068057

Filed: March 03, 2025

Foreign Application Priority Data

CN 202410247234.X

Mar. 05, 2024

CN 202411256528.5

Sep. 09, 2024

Publication Classification

Int. Cl.: A61B1/005 (20060101); A61B1/00 (20060101); A61B1/317 (20060101)

U.S. Cl.:

CPC **A61B1/009** (20220201); **A61B1/00057** (20130101); **A61B1/00195** (20130101);
A61B1/0057 (20130101); **A61B1/317** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Chinese Patent Application 202410247234.X, filed on Mar. 5, 2024, and entitled “ENDOSCOPE WITH VARIABLE ANGLE”, and Chinese Patent Application 202411256528.5, filed Sep. 9, 2024, and entitled “STEERABLE ORTHOPEDIC ENDOSCOPE SYSTEM WITH NAVIGATION FUNCTION”. Chinese Patent Application 202410247234.X and Chinese Patent Application 202411256528.5 are incorporated herein by reference in their entireties.

FIELD

[0002] The present disclosure relates to the technical field of orthopedic surgery, and in particular, to a steerable orthopedic endoscope system with navigation function.

BACKGROUND

[0003] With the deepening of minimally invasive concepts, the use of endoscopy in orthopedic surgery has become an important trend in development of surgical technologies. Orthopedic endoscopes allow orthopedic surgeon to perform intraoperative diagnosis and procedures through minimally invasive incisions, which greatly improves patient satisfaction and reduces medical costs. However, a current orthopedic endoscope (arthroscopes and foraminoscopes) typically features a rigid cylindrical design with a fixed field of view angle, which makes it difficult to adapt to irregular surgical environment. This limitation results in blind spots and restricted operational areas during surgery. In addition, current endoscopic systems are lack of navigation designs, forcing surgeons to rely solely on their interpretation of endoscopic anatomical structures viewed through the endoscope to estimate the spatial positioning of the lens and instruments. This technology has a steep learning curve and carries a high risk of iatrogenic injury. Therefore, there is an urgent clinical need for an orthopedic endoscope with variable observation angles and navigation functionality to support various surgeries, including joint surgery, spine surgery, and trauma surgery.

SUMMARY

[0004] To eliminate surgical blind spots and restricted areas in orthopedic endoscope surgery, shorten a learning period of the orthopedic endoscope surgery, and improve surgical safety and quality, the present disclosure provides a steerable orthopedic endoscope system with navigation function. The endoscopic system can obtain pose information of a lens based on a rotation angle of a rotating wheel, and co-locate the lens through optical magnetic composite, which facilitates observing and operating by using the orthopedic endoscope system more accurately, reduces medical safety risks, shortens a learning curve of a doctor, and improves surgical quality.

[0005] Embodiments of the present disclosure provide a steerable orthopedic endoscope system with navigation function, including: [0006] a handle; [0007] an endoscope body, comprising a rod portion connected to the handle, a bendable portion located at a front end of the rod portion, and a lens located at a front end of the bendable portion, wherein the bendable portion is internally provided with bending sections, whereby the bendable portion is capable of bending at different angles; [0008] a rotating adjustment component, comprising a rotating wheel and two pull wires arranged on two sides in a radial direction of the rotating wheel respectively, wherein the two pull wires are connected to the bending sections to adjust bending degree of the bendable portion;

[0009] an angle detection component, comprising a marker arranged on the rotating wheel and a detection device configured to identify the marker, wherein the detection device obtains a rotation angle of the rotating wheel by detecting changes of the marker; and [0010] a processor, electrically connected to the angle detection component and the rotating adjustment component, wherein the processor receives rotation angle information obtained by the angle detection component, and calculates a pose of the lens relative to the rod portion according to the rotation angle information, and the pose comprises coordinates and a direction angle of the lens.

[0011] In some embodiments, an operation in which the processor calculates the pose of the lens relative to the rod portion according to the rotation angle information comprises:

[0012] Determining an x-axis coordinate (x) and a y-axis coordinate (y) of the lens according to the following mathematical expression:

$$[00001] y = \sum_{j=0}^n a_j \cdot \text{Math. } x^j = f(x) \quad x = \sum_{j=0}^n b_j \cdot \text{Math. } \theta^j = g(\theta)$$

[0013] wherein n is a number of terms in a polynomial, $a_{\text{sub } j}$ and $b_{\text{sub } j}$ are respectively coefficients of a j^{th} item in a vertical coordinate and a horizontal coordinate, and 0 is the rotation angle of the rotating wheel.

[0014] In some embodiments, the operation in which the processor calculates the pose of the lens relative to the rod portion according to the rotation angle information further comprises: [0015]

determining a normal at the lens according to the following mathematical expression, and taking an angle of the normal as the direction angle of the lens:

$$[00002] y = \frac{x_i - x}{k_i} + y_i \quad [0016] \text{ wherein } x_{\text{sub } i} = g(\theta_{\text{sub } i}), k_{\text{sub } i} = f'(g(\theta_{\text{sub } i})), \text{ and } y_{\text{sub } i} = f(g(\theta_{\text{sub } i})).$$

[0017] In some embodiments, an optical navigation component, wherein the processor adjusts an origin of the optical navigation component based on pose information of the lens, whereby a field of view of the optical navigation component is with the same as a field of view of the lens.

[0018] In some embodiments, the optical navigation component comprises a reference frame and a reflection sphere arranged on the handle, and the electromagnetic navigation component comprises an electromagnetic positioning sensor arranged at the front end of the bendable portion.

[0019] In some embodiments, the optical navigation component includes a plurality of the reflection spheres, and a number of the reflection spheres is three or more.

[0020] In some embodiments, the marker is a grating, and the detection device is a sensor that matches the grating.

[0021] In some embodiments, the rotating wheel is driven by a motor, and the motor is embedded into the handle.

[0022] In some embodiments, a button configured to start or stop the motor is arranged on the handle.

[0023] In some embodiments, the steerable orthopedic endoscope system with navigation function includes an electromagnetic navigation component, providing reference coordinates for the lens.

[0024] In some embodiments, n, $a_{\text{sub } j}$ and $b_{\text{sub } j}$ are determined by fitting a plurality of calibration results.

[0025] By using the steerable orthopedic endoscope system with navigation function according to the present disclosure, the orthopedic endoscope system controls the pull wires to adjust a bending angle of the bendable portion through the rotating wheel, the angle detection component detects and sends the rotation angle of the rotating wheel to the processor, the processor calculates the pose information of the lens relative to the rod portion through information of the rotation angle, and the orthopedic endoscope system can co-locate the lens based on the pose information in cooperation with optical magnetic composite, which facilitates observing and operating by using the orthopedic endoscope system more accurately, reduces medical safety risks, shortens a learning curve of a doctor, and improves surgical quality.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] FIG. 1 is a schematic structural diagram of a steerable orthopedic endoscope system with navigation function.

[0027] FIG. 2 is a schematic structural diagram of the bendable portion in some embodiments.

[0028] FIG. 3 is a partial explosion diagram of the bendable portion in some embodiments.

[0029] FIG. 4 is a schematic structural diagram of the bendable section in some embodiments.

[0030] FIG. 5 is a block diagram showing various functional elements of an exemplary steerable orthopedic endoscope system.

[0031] In the drawing: **10**, lens; **20**, rod portion; **21**, bendable portion; **211**, bending section; **212**, through-hole; **213**, interior space; **214**, pin; **30**, handle; **40**, rotating wheel; **41**, pull wire; **50**, grating; **51**, angle detection component; **52**, sensor; **60**, motor; **61**, button; **70**, reference frame; **71**, reflection sphere; **72**, optical navigation component; **73**, IR Camera; **81**, electromagnetic navigation component; **80**, electromagnetic positioning sensor and **90**, processor.

DETAILED DESCRIPTION

[0032] To make purposes, technical solutions, and advantages of the present disclosure clearer, the present disclosure is described below in detail in some embodiments with reference to an accompanying drawing and embodiments. It is to be understood that specific embodiments described here are merely used to explain the present disclosure and are not intended to limit the present disclosure.

[0033] Structures, proportions, sizes, and the like drawn in the drawing of the present specification are merely used to cooperate with the contents disclosed in the specification for those familiar with the technology to understand and read, and are not intended to limit the limitation conditions under which the present disclosure can be implemented. Any modifications of the structures, changes in proportion relationships or adjustment of the sizes still fall within the scope that can be covered by the technical content disclosed by the present disclosure without affecting the efficacy and the purpose that can be achieved by the present disclosure.

[0034] Orientations or positional relationships indicated by terms “upper”, “lower”, “left”, “right”, “middle”, “longitudinal”, “transverse”, “horizontal”, “inner”, “outer”, “radial”, “circumferential” and the like are the orientations or positional relationships shown based on the accompanying drawing, and are merely for the convenience of describing, rather than indicating or implying that devices or elements referred to need to have particular orientations, and constructed and operated in particular orientations. Thus, it cannot be construed as a limitation to the present disclosure. In addition, terms “first” and “second” are merely used for description, and cannot be understood as indicating or implying relative importance.

[0035] As shown in FIG. 1, the present disclosure discloses a steerable orthopedic endoscope system with navigation function, including a handle **30**, an endoscope body, a rotating adjustment component, an angle detection component, and a processor **90**. The endoscope body includes a rod portion **20** connected to the handle **30**, a bendable portion **21** located at a front end of the rod portion **20**, and a lens **10** located at a front end of the bendable portion **21**. The bendable portion **21** is internally provided with bending sections **211**, whereby the bendable portion **21** is capable of bending at different angles, which ensures that the lens **10** can meet visual field requirements at different positions within a human body. In some embodiments, bending sections **211** are linked together to form one line in the axial direction of the bendable portion **21**. Each of the bending sections **211** includes through-holes **212** and an interior space **213**. The through-holes **212** are provided in a manner to extend in the axial direction of the bendable portion **21**, and allow pull wires **41** to be inserted therethrough. The interior space **213** is provided in a manner to extend in the axial direction of the bendable portion **21**. Each pair of adjacent bending section **211** is coupled

together by a pair of pins **214**, thereby each bending sections **211** is connected to its adjacent bending sections **211**, such that each bending section **211** is swingable about the axis of the pair of pins **214** (i.e., swingable about a swing axis). The swing axes of the bending sections **211** are configured to be parallel to each other. That is, the bendable portion **21** is configured to be bendable in respective directions of the swing axes of the bending sections **211**.

[0036] The rotating adjustment component in this embodiment includes a rotating wheel **40** and two pull wires **41** arranged on two sides in a radial direction of the rotating wheel **40** respectively. The two pull wires **41** are connected to the bending sections **211**. The rotating wheel **40** drives the bending sections **211** to move through the pull wires **41**, so as to adjust bending degree of the bendable portion **21**. During rotating of the rotating wheel **40**, the pull wire **41** on one side of the rotating wheel **40** is tightened, and the pull wire **41** on the other side of the rotating wheel **40** is loosened, whereby the bendable portion **21** bends towards the side where the pull wire **41** is tightened. In some embodiments, the rotating adjustment component further includes a motor **60**. The rotating wheel **40** is driven by the motor **60**. In some embodiments, the motor **60** is a servo motor. The motor **60** is controlled to start or stop by a button **61** on the handle **30**. The motor **60** is embedded into the handle **30**. It is to be noted that, a method for controlling the bendable portion **21** to bend by using the rotating wheel **40**, the pull wires **41**, and the bending sections **211** is a conventional technology. Therefore, specific structures and principles are not described in detail in this embodiment.

[0037] The angle detection component **51** in this embodiment includes an marker arranged on the rotating wheel **40** and a detection device configured to identify the marker. The detection device obtains a rotation angle of rotating wheel **40** by detecting changes of the marker. In some embodiments, the marker is a grating **50**. The detection device is a sensor **52** that cooperates with the grating **50**. The grating **50** in cooperation with the sensor **52** has high measurement accuracy and high stability. In some embodiments, the marker is an optical structure typically includes periodic patterns, i.e., a grating with Moire fringes.

[0038] In some embodiments, the marker may be a conductor arranged on the rotating wheel **40**, and a corresponding detection device is an ejector pin. The ejector pin is in contact with the conductor to form an electrical circuit to obtain the rotation angle of the rotating wheel **40**. It is to be noted that a method for detecting the rotation angle of an object by using the grating **50** and the sensor is a conventional technology, which is not described in detail in this disclosure.

[0039] In some embodiments, the processor **90** is electrically connected to the angle detection component **51** and rotating adjustment component. Furthermore, the processor **90** is electrically connected to the motor **60**.

[0040] The processor **90** receives rotation angle information obtained by the angle detection component, and calculates a pose (coordinates and a direction angle) of the lens **10** relative to the rod portion **20** according to the rotation angle information. It is to be noted that the lens **10** is controlled through the rotating wheel **40**, the pull wires **41**, and the bending sections **211**. The lens **10** is constrained to move within a plane, that is, the lens **10** can only move in a plane where a certain radial direction of the rod portion **20** is located, so a numerical value of a z-axis coordinate of the lens **10** relative to the rod portion **20** is 0, and coordinates of the lens **10** relative to the rod portion **20** are (x, y, 0). This embodiment is mainly to calculate an x-axis coordinate and a y-axis coordinate of the lens **10** relative to the rod portion **20**. The processor **90** in this embodiment may be a conventional STM32F4 or STM32F7 series single chip microcomputer, and the like.

[0041] A method that the processor calculates a pose of the lens **10** relative to the rod portion **20** according to the rotation angle information is as follows:

[0042] Firstly, a polynomial function curve of a trajectory of the lens **10** is set. A mathematical expression of the x-axis coordinate and the y-axis coordinate of the lens **10** relative to the rod portion **20** is represented by formula (1) as follows:

$$[00003] \ y = \sum_{j=0}^n a_j \cdot x^j = f(x) \quad (1)$$

[0043] where n is a number of terms in a polynomial, and a.sub.j is a coefficient of a j.sup.th item in a vertical coordinate and is determined by fitting a plurality of calibration results. In some embodiments, the vertical coordinate is the y-axis coordinate and the horizontal coordinate is the x-axis coordinate. Therefore, in some embodiments, x is abscissa and y is ordinate.

[0044] Secondly, a polynomial function of the x-axis coordinate of the lens **10** and a rotation angle θ of the rotating wheel **40** is set. When $\theta > 0$, as the rotation angle θ increases, coordinates of the lens **10** are monotonically invariant in an x-axis direction when the rotation angle $\theta > 0$, $x = g(\theta)$ is set, the x-axis coordinate of the lens **10** may form a polynomial function with respect to the rotation angle θ , which is represented by formula (2) as follows:

$$[00004] \ x = \sum_{j=0}^n b_j \cdot \theta^j = g(\theta) \quad (2)$$

[0045] where b.sub.j is a coefficient of a j.sup.th item in the horizontal coordinate. θ .sup.j is a coefficient of the j.sup.th item in the rotation angle, which is determined by fitting a plurality of calibration results.

[0046] In some embodiments, specific calculation methods for a.sub.j and θ .sup.j are as follows:

[0047] First, a mapping relationship between coordinates (x.sub.i, y.sub.i, 0) of the lens **10** relative to the rod portion **20** and the rotation angle θ of the rotating wheel **40**, a single rotation angle of the rotating wheel **40** is set as $\Delta\alpha$, when the rotating wheel is rotated for an i.sup.th time, the rotation angle of the rotating wheel **40** is θ .sub.i=i.Math. $\Delta\alpha$, and the coordinates (x.sub.i, y.sub.i, 0) of the lens **10** relative to the rod portion **20** at this moment are recorded, where i=0, 1, 2, . . . , m.

[0048] After data is counted for m+1 times, list data of the rotation angle θ of the rotating wheel **40** and the coordinates (x.sub.i, y.sub.i, 0) of the lens **10** is obtained, which is represented by formula (3) as follows:

$$[00005] \ \begin{cases} y_0 - a_0 + a_1 \cdot x_0 + a_2 \cdot x_0^2 + \dots + a_n \cdot x_0^n \\ y_1 - a_0 + a_1 \cdot x_1 + a_2 \cdot x_1^2 + \dots + a_n \cdot x_1^n \\ y_2 - a_0 + a_1 \cdot x_2 + a_2 \cdot x_2^2 + \dots + a_n \cdot x_2^n \\ \vdots \\ y_m - a_0 + a_1 \cdot x_m + a_2 \cdot x_m^2 + \dots + a_n \cdot x_m^n \end{cases} \quad (3)$$

[0049] Then, formula (3) is converted into a matrix form, which is represented by formula as follows:

$$[00006] \ \begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix} = \begin{bmatrix} 1 & x_0 & x_0^2 & \dots & x_0^n \\ 1 & x_1 & x_1^2 & \dots & x_1^n \\ 1 & x_2 & x_2^2 & \dots & x_2^n \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_m & x_m^2 & \dots & x_m^n \end{bmatrix} \cdot \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ \vdots \\ a_m \end{bmatrix} \quad (4)$$

$X = \begin{bmatrix} 1 & x_0 & x_0^2 & \dots & x_0^n \\ 1 & x_1 & x_1^2 & \dots & x_1^n \\ 1 & x_2 & x_2^2 & \dots & x_2^n \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 1 & x_m & x_m^2 & \dots & x_m^n \end{bmatrix}, Y = \begin{bmatrix} y_0 \\ y_1 \\ y_2 \\ \vdots \\ y_m \end{bmatrix}, \text{ and } A = \begin{bmatrix} a_0 \\ a_1 \\ a_2 \\ \vdots \\ a_m \end{bmatrix}$

are set to obtain formula $Y=XA$.

[0050] Next, by using a least square method, a formula for a sum of squared errors is set as follows:

[00007] $E = (Y - XA)^T \cdot \text{Math.} (Y - XA)$; [0051] the formula for a sum of squared errors is simplified as follows:

[00008] $E = Y^T Y - Y^T XA - A^T X^T Y + A^T X^T XA$; and [0052] then,

[00009] $\frac{\partial E}{\partial A} = 0$ is set, whereby an error between obtained data and actual data is the least, which is represented by formula (5) as follows:

[00010] $0 - X^T Y - X^T Y + X^T XA + X^T XA = 0$ (5) $X^T XA = X^T YA = (X^T X)^{-1} X^T Y$

[0053] So far, a curve equation $Y=XA$ of the lens **10** relative to the rod portion **20** can be obtained by using the least square method, that is, a coefficient a.sub.j may be defined.

[0054] It may be learned from formula (1) that the y-axis coordinate of the lens **10** may be calculated through the x-axis coordinate of the lens **10**, and it may be learned from formula (2) that the x-axis coordinate of the lens **10** may be calculated through the rotation angle θ of the rotating wheel **40**. A simplified formula of a value of the x-axis coordinate of the lens **10** and θ is set as $X=\Theta B$, where

$$[00011] X, \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ \vdots \\ x_m \end{bmatrix}, = \begin{bmatrix} 1 & 0 & \frac{2}{0} \\ 1 & 1 & \frac{2}{1} \\ 1 & 2 & \frac{2}{2} \\ \vdots & \vdots & \vdots \\ 1 & m & \frac{2}{m} \end{bmatrix} \cdot \text{Math.} \begin{bmatrix} n \\ n \\ n \\ \vdots \\ n \end{bmatrix}, \text{ and } B = \begin{bmatrix} b_0 \\ b_1 \\ b_2 \\ \vdots \\ b_m \end{bmatrix}.$$

[0055] Formula (6) is obtained by using the least square method, which is as follows:

[00012] $B = (X^T X)^{-1} X^T Y$ (6)

[0056] A coefficient b.sub.j may be defined, a parameter of a function $x=g(\theta)$ with respect to the rotation angle θ may be obtained, and a formula may be obtained by combining formula (1) and formula (2):

$y=f(g(\theta))$.

[0057] This polynomial function is continuous and differentiable, so:

[00013] $k = \frac{\partial f(x)}{\partial x} = f'(x)$.

[0058] When the rotation angle of the rotating wheel **40** is θ .sub.i, the coordinates of the lens **10** relative to the rod portion **20** are $(g(\theta$.sub.i), $f(g(\theta$.sub.i)), 0), a normal direction of this point is a direction angle of the lens **10**, and a normal equation of a direction of the lens **10** is represented by formula (7) as follows:

[00014] $y = \frac{x_i - x}{k_i} + y_i$ (7)

[0059] where x .sub.i= $g(\theta$.sub.i), k .sub.i= $f'(g(\theta$.sub.i)), and y .sub.i= $f(g(\theta$.sub.i)).

[0060] In conclusion, when the rotation angle of the rotating wheel **40** is $\theta > 0$, the pose of the lens **10** relative to the rod portion **20** may be obtained according to the value of the rotation angle θ . The lens **10** can only move in a plane where a certain radial direction of the rod portion **20** is located, and a movable path of the lens **10** is symmetrical with respect to a central axis of the rod portion **20**, so the pose of the lens **10** is symmetrical with respect to the central axis of the rod portion **20** when the rotation angle of the rotating wheel **40** $\theta < 0$ and the rotation angle $\theta > 0$.

[0061] In some embodiments, the orthopedic endoscope system controls the pull wires **41** to adjust a bending angle of the bendable portion **21** through the rotating wheel **40**, the angle detection component **51** detects and sends the rotation angle of the rotating wheel **40** to the processor **90**, and the processor **90** calculates the pose of the lens **10** relative to the rod portion **20** through information of the rotation angle, whereby the orthopedic endoscope system is configured to search

for lesions more accurately, and medical safety risks are reduced.

[0062] The orthopedic endoscope system according to this embodiment further includes an optical navigation component **72** and an electromagnetic navigation component **81**. Both the optical navigation component **72** and the electromagnetic navigation component **81** are electrically connected to the processor **90**. The optical navigation component includes a reference frame **70** and a reflection sphere **71** arranged on the handle **30**, and the electromagnetic navigation component **81** includes an electromagnetic positioning sensor **80** arranged at the front end of the bendable portion. The processor **90** adjusts an origin of the optical navigation component based on pose information of the lens **10**, whereby a field of view of the optical navigation component is consistent with a field of view of the lens **10**, and navigation accuracy is ensured. The electromagnetic navigation component **81** provides reference coordinates for the lens **10**. When a difference value between the reference coordinates and the coordinates of the lens **10** is too large, a doctor is reminded of detecting a damage to the orthopedic endoscope system to ensure surgical safety.

[0063] In some embodiments, the optical navigation component **72** includes an IR Camera (Infrared Ray Camera) **73**, which is electrically connected to the processor **90**. The IR camera **73** is provided with an infrared emitter. The infrared ray emitted by the infrared emitter could be reflected off the reflection sphere **71** and bones. The reflected infrared ray will be received by an infrared receiver of the IR Camera **73**, generating some electrical signal. The processor **90** determines the position of the reflection sphere **71** and bones, and makes an optical coordinate. In some embodiments, the infrared receiver includes infrared sensor. In some embodiments, the optical navigation component **72** includes three or more reflection spheres.

[0064] In some embodiments, the processor **90** may build a first coordinate system based on the images captured by the lens **10**, and it builds a second coordinate system (i.e., an optical coordinate system) based on the optical navigation component **72**. Since the optical navigation component **72** is fixed to the handle, the positions of the reflection spheres **71** are fixed relative to it. Therefore, the processor **90** determines the positions of the reflection spheres **71** using the IR Camera **73** and establishes the second coordinate system based on these positions. Furthermore, the original position and orientation of the lens **10** are recorded in the processor **90**. Consequently, the processor acquires the coordinates of the lens **10** within the second coordinate system.

[0065] As the lens **10** moves, the processor receives rotation angle information obtained by the angle detection component, calculates the pose of the lens **10** relative to the rod portion **20** based on the rotation angle information, and determines the pose of the lens in the second coordinate system. In some embodiments, the position of the lens **10** differs from the position of the IR Camera, hence, the origin of the first coordinate system, which is based on the position of the lens **10**, differs from the origin of the second coordinate system, which is based on the position of the IR Camera. Therefore, the processor **90** adjusts the origin of the second coordinate system based on the pose information of the lens and the optical navigation component **72** to align it with the origin of the first coordinate system. For example, the processor can set the position of the lens **10** as the origin of the second coordinate system so that the field of view of the optical navigation component is consistent with the field of view of the lens **10**.

[0066] In some embodiments, the processor **90** calculates the position of the bones that appear in images captured by the lens **10** within the first coordinate system. Furthermore, the processor **90** can also calculate the positions of the bones and the reflection spheres **71** within the second coordinate system, based on the optical navigation component **72**. Therefore, the processor **90** can perform a coordinate fitting of the first and second coordinate systems to calculate more accurate bone positions.

[0067] In some embodiments, the position of the electromagnetic positioning sensor **80** is determined by an external magnetic field to the human body. When this magnetic field passes through the electromagnetic positioning sensor **80**, a weak electrical signal is generated by the coil within the sensor, which is then transmitted to the processor **90** via a wire. The processor **90**

acquires the position of the electromagnetic positioning sensor **80** by calculating this electrical signal. The position of the electromagnetic positioning sensor **80** relative to the lens is fixed. Therefore, the processor **90** can calculate the position of the lens, and thus the electromagnetic navigation component provides reference coordinates for the lens.

[0068] It is to be noted that a method for fitting positioning information of an optical navigation technology and/or an electromagnetic navigation technology and/or an endoscope system navigation technology is a conventional technology. Therefore, a specific principle of navigation is not described in detail in this embodiment. It is to be noted that the lens **10** of this embodiment is represented by using a right-handed coordinate system.

[0069] Various technical features of the above embodiments may be arbitrarily combined. To make the description concise, all possible combinations of the various technical features in the foregoing embodiments are not described. However, contradiction in the combinations of these technical features are considered to be in a range described in this specification as long as there is no conflict.

[0070] The above embodiments merely express several implementations manners of the present disclosure, with specific and detailed description, and are not to be construed as a limitation on the patent scope of the present disclosure. It is to be noted that a number of variations and modifications may be made by those of ordinary skill in the art without departing from the conception of the present disclosure. All of these belong to the scope of protection of the present disclosure. Therefore, the scope of protection of the present disclosure should be determined by the appended claims.

Claims

1. A steerable orthopedic endoscope system with navigation function, comprising: a handle; an endoscope body, comprising a rod portion connected to the handle, a bendable portion located at a front end of the rod portion, and a lens located at a front end of the bendable portion, wherein the bendable portion is internally provided with bending sections, whereby the bendable portion is capable of bending at different angles; a rotating adjustment component, comprising a rotating wheel and two pull wires arranged on two sides in a radial direction of the rotating wheel respectively, wherein the two pull wires are connected to the bending sections to adjust a bending degree of the bendable portion; an angle detection component, comprising a marker arranged on the rotating wheel and a detection device configured to identify the marker, wherein the detection device obtains a rotation angle of the rotating wheel by detecting changes of the marker; and a processor, electrically connected to the angle detection component and the rotating adjustment component, wherein the processor receives rotation angle information obtained by the angle detection component, and calculates a pose of the lens relative to the rod portion according to the rotation angle information, and the pose comprises coordinates and a direction angle of the lens.
2. The steerable orthopedic endoscope system with navigation function according to claim 1, wherein an operation in which the processor calculates the pose of the lens relative to the rod portion according to the rotation angle information comprises: determining an x-axis coordinate (x) and a y-axis coordinate (y) of the lens according to the following mathematical expression:
$$y = \sum_{j=0}^n a_j \cdot x^j = f(x) \quad x = \sum_{j=0}^n b_j \cdot \theta^j = g(\theta)$$
wherein n is a number of terms in a polynomial, a_j and b_j are respectively coefficients of a j -th item in a vertical coordinate and a horizontal coordinate, and θ is the rotation angle of the rotating wheel.
3. The steerable orthopedic endoscope system with navigation function according to claim 2, wherein the operation in which the processor calculates the pose of the lens relative to the rod portion according to the rotation angle information further comprises: determining a normal at the lens according to the following mathematical expression, and taking an angle of the normal as the

direction angle of the lens: $y = \frac{x_i - x}{k_i} + y_i$ wherein $x_{\text{sub}.i} = g(\theta_{\text{sub}.i})$, $k_{\text{sub}.i} = f'(g(\theta_{\text{sub}.i}))$, and $y_{\text{sub}.i} = f(g(\theta_{\text{sub}.i}))$.

4. The steerable orthopedic endoscope system with navigation function according to claim 1, comprising an optical navigation component, wherein the processor adjusts an origin of the optical navigation component based on pose information of the lens, whereby a field of view of the optical navigation component is the same as a field of view of the lens.
 5. The steerable orthopedic endoscope system with navigation function according to claim 4, wherein the optical navigation component comprises a reference frame and a reflection sphere arranged on the handle.
 6. The steerable orthopedic endoscope system with navigation function according to claim 5, wherein the optical navigation component comprises a plurality of the reflection spheres, and a number of the reflection spheres is three or more.
 7. The steerable orthopedic endoscope system with navigation function according to claim 1, wherein the marker is a grating, and the detection device is a sensor that matches the grating.
 8. The steerable orthopedic endoscope system with navigation function according to claim 1, wherein the rotating wheel is driven by a motor, and the motor is embedded into the handle.
 9. The steerable orthopedic endoscope system with navigation function according to claim 8, wherein a button configured to start or stop the motor is arranged on the handle.
 10. The steerable orthopedic endoscope system with navigation function according to claim 1, comprising an electromagnetic navigation component, providing reference coordinates for the lens, and the electromagnetic navigation component comprises an electromagnetic positioning sensor arranged at the front end of the bendable portion.
 11. The steerable orthopedic endoscope system with navigation function according to claim 2, wherein n , $a_{\text{sub}.j}$ and $b_{\text{sub}.j}$ are determined by fitting a plurality of calibration results.
-