

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284241

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KUSUDA; Masakatsu

DOCUMENT CONVEYANCE APPARATUS AND IMAGE FORMING APPARATUS

Abstract

According to an embodiment, a document conveyance apparatus includes: an opening-and-closing cover; a driving roller and a driven roller; a driven roller holding member which rotatably holds the driven roller, and causes the driven roller to contact or be separated from the driving roller in conjunction with opening and closing of the opening-and-closing cover; and a pressure-contact spring which applies, to the driven roller holding member, a biasing force in a direction of pressing the driven roller against the driving roller. The opening-and-closing cover is provided with a side wall and a holding rib, and the driven roller holding member is provided with a first surface and a second surface. When the opening-and-closing cover is opened, the side wall contacts the first surface to bias the opening-and-closing cover in a closing direction, and the holding rib contacts the second surface to bias the same in an opening direction.

Inventors: KUSUDA; Masakatsu (Sakai City, JP)

Applicant: SHARP KABUSHIKI KAISHA (Sakai City, JP)

Family ID: 1000008476199

Appl. No.: 19/055760

Filed: February 18, 2025

Foreign Application Priority Data

JP 2024-033190

Mar. 05, 2024

Publication Classification

Int. Cl.: G03G21/16 (20060101); G03G15/00 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority from Japanese Application JP2024-033190, the content of which is hereby incorporated by reference into this application.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present disclosure relates to a document conveyance apparatus and an image forming apparatus.

2. Description of the Related Art

[0003] In general, a document conveyance apparatus has a structure in which, when a document being conveyed by document conveyance rollers is jammed, an opening-and-closing cover is opened to have a document conveyance path opened, whereby the jammed document can be removed (i.e., jam processing can be performed). In a conventional document conveyance apparatus, a pressure-contact state of the document conveyance rollers is released in conjunction with an operation of opening the opening-and-closing cover such that the jammed document can be easily pulled out.

SUMMARY OF THE INVENTION

[0004] In a document conveyance apparatus in which jam processing is performed by opening an opening-and-closing cover, it is troublesome for the user to perform the operation of removing (pulling out) a jammed document with one hand while holding the opening-and-closing cover with the other hand. If a structure by which the opening-and-closing cover that is opened can be held without requiring the user to support the opening-and-closing cover is achieved, it becomes easy for the user to perform jam processing.

[0005] However, if a complicated structure using a spring, an arm, or the like for holding the opening-and-closing cover that is opened is employed, the number of components increases, and a space for arranging the components is also required.

[0006] The present disclosure has been conceived in view of the above-described problems, and an object of the present disclosure is to provide a document conveyance apparatus and an image forming apparatus in which jam processing by opening the opening-and-closing cover can be performed, and the opening-and-closing cover that is opened can be held with a simple configuration.

[0007] In order to solve the above problems, a document conveyance apparatus according to a first aspect of the present disclosure pertains to a document conveyance apparatus including an opening-and-closing cover which is openable and closable with respect to an apparatus housing, and the document conveyance apparatus is provided with: document conveyance rollers including a driving roller, and a driven roller provided to be contactable with and separable from the driving roller; a driven roller holding member which rotatably holds the driven roller, and causes the driven roller to be in contact with or separated from the driving roller in conjunction with opening and closing of the opening-and-closing cover; and a biasing member which applies, to the driven roller holding member, a biasing force in a direction of bringing the driven roller into pressure contact with the driving roller, in which the document conveyance apparatus is characterized in that: the opening-and-closing cover is provided with a first contact portion and a second contact portion; the driven roller holding member is provided with a first surface and a second surface; and in a state in which the opening-and-closing cover is opened, the first contact portion comes into contact with the first surface and the second contact portion comes into contact with the second surface, the first surface

biases, by the biasing force of the biasing member, the first contact portion in a direction in which the opening-and-closing cover closes, and the second surface biases, by the biasing force of the biasing member, the second contact portion in a direction in which the opening-and-closing cover opens.

[0008] According to the above configuration, in a state in which the opening-and-closing cover is opened, by virtue of a balance between the biasing force acting between the first surface and the first contact portion and the biasing force acting between the second surface and the second contact portion, the opening-and-closing cover can be held in a state of being opened at a predetermined position even if the user does not support the opening-and-closing cover with his/her hand. Here, since it is possible to hold the opening-and-closing cover by using the biasing force of the biasing member for bringing the driven roller into pressure contact with the driving roller, no complicated structure using another spring, an arm, or the like, for holding the opening-and-closing cover that is opened is required.

[0009] Further, in the above document conveyance apparatus, the first contact portion and the second contact portion may be configured as a rib provided on the opening-and-closing cover.

[0010] Furthermore, in the above document conveyance apparatus, the first contact portion may be configured as a side wall of the opening-and-closing cover.

[0011] Furthermore, the above document conveyance apparatus may be configured such that the document conveyance apparatus is provided with a connection rib which connects between the ribs of the first contact portion and the second contact portion, and the connection rib is of a shape that does not contact the driven roller holding member during a process of opening and closing the opening-and-closing cover.

[0012] Also, in order to solve the above problems, a document conveyance apparatus according to a second aspect of the present disclosure pertains to a document conveyance apparatus including an opening-and-closing cover which is openable and closable with respect to an apparatus housing, and the document conveyance apparatus is provided with: document conveyance rollers including a driving roller, and a driven roller provided to be contactable with and separable from the driving roller; a driven roller holding member which rotatably holds the driven roller, and causes the driven roller to be in contact with or separated from the driving roller in conjunction with opening and closing of the opening-and-closing cover; and a biasing member which applies, to the driven roller holding member, a biasing force in a direction of bringing the driven roller into pressure contact with the driving roller, in which the document conveyance apparatus is characterized in that: the opening-and-closing cover is provided with a cover side abutment portion which contacts the driven roller holding member when the opening-and-closing cover is opened; the driven roller holding member is provided with a driven-roller-holding-member-side abutment portion which contacts the cover side abutment portion when the opening-and-closing cover is opened; the apparatus housing is provided with a restrictor which restricts opening of the opening-and-closing cover beyond a predetermined position; and in a state in which the opening-and-closing cover is opened, the driven-roller-holding-member-side abutment portion biases, by the biasing force of the biasing member, the cover side abutment portion in a direction in which the opening-and-closing cover opens.

[0013] According to the above configuration, in a state in which the opening-and-closing cover is opened, by virtue of the biasing force acting between the driven-roller-holding-member-side abutment portion and the cover side abutment portion, it is possible to prevent the opening-and-closing cover from being closed by its own weight, and the opening-and-closing cover that is opened can also be held at a predetermined position by the restrictor.

[0014] Further, the above document conveyance apparatus may be configured such that the restrictor is in a shape of a hook, and when the opening-and-closing cover is opened to the predetermined position, the hook engages with a side wall of the opening-and-closing cover.

[0015] Furthermore, an image forming apparatus according to a third aspect of the present

disclosure is characterized by including the document conveyance apparatus described above.

[0016] The document conveyance apparatus and the image forming apparatus of the present disclosure bring about an advantage of being able to keep the state in which the opening-and-closing cover is opened by using the biasing force of the biasing member for bringing the driven roller into pressure contact with the driving roller, enabling jam processing to be performed by opening the opening-and-closing cover, and also being able to hold the opening-and-closing cover that is opened with a simple configuration.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIG. 1 is a schematic cross-sectional view illustrating a configuration example of an image forming apparatus on which a document conveyance apparatus of the present disclosure is mounted.

[0018] FIG. 2 is a perspective view showing the outside appearance of a document conveyance apparatus in a state in which an opening-and-closing cover is closed.

[0019] FIG. 3 is a perspective view showing the outside appearance of the document conveyance apparatus in a state in which the opening-and-closing cover is opened.

[0020] FIG. 4 is a plan view of the document conveyance apparatus in a state in which the opening-and-closing cover is removed.

[0021] FIG. 5 is a partial cross-sectional view of the vicinity of document conveyance rollers in a document conveyance apparatus in a state in which an opening-and-closing cover is closed in a first embodiment.

[0022] FIG. 6 is a perspective view of a driven roller holding member.

[0023] FIG. 7 is a partial cross-sectional view of the vicinity of the document conveyance rollers in the document conveyance apparatus in a state of being in the process of opening the opening-and-closing cover in the first embodiment.

[0024] FIG. 8 is a partial cross-sectional view of the vicinity of the document conveyance rollers in the document conveyance apparatus in a state in which the opening-and-closing cover is opened in the first embodiment.

[0025] FIG. 9 is an enlarged perspective view of an end portion of the opening-and-closing cover on a rotation shaft side in the first embodiment.

[0026] FIG. 10 is a diagram illustrating an action by which the opening-and-closing cover is held in an opened state in the first embodiment.

[0027] FIG. 11 is a partial cross-sectional view of the vicinity of the document conveyance rollers, which illustrates a modified example of the document conveyance apparatus of the first embodiment.

[0028] FIG. 12 is a partial cross-sectional view of the vicinity of document conveyance rollers in a document conveyance apparatus in a state in which an opening-and-closing cover is closed in a second embodiment.

[0029] FIG. 13 is a partial cross-sectional view of the vicinity of the document conveyance rollers in the document conveyance apparatus in a state in which the opening-and-closing cover is opened in the second embodiment.

[0030] FIG. 14 is an enlarged perspective view of an end portion of the opening-and-closing cover on a rotation shaft side in the second embodiment.

[0031] FIG. 15 is a diagram illustrating an action by which the opening-and-closing cover is held in an opened state in the second embodiment.

[0032] FIG. 16 is a cross-sectional view illustrating a restrictor in the second embodiment.

DETAILED DESCRIPTION OF THE INVENTION

First Embodiment

[0033] In the following, embodiments of the present disclosure will be described in detail with reference to the drawings. First, an overall configuration of an image forming apparatus **10** according to the present embodiment will be described. FIG. **1** is a schematic configuration diagram of the image forming apparatus **10** on which a document conveyance apparatus **20** of the present disclosure is mounted. While the image forming apparatus **10** illustrated in FIG. **1** is a color image forming apparatus including a plurality of process units, the present disclosure is not limited to the above and may also be applied to a monochrome image forming apparatus including a single process unit. Further, in the present embodiment, an X direction indicated in the drawings is assumed as a width direction, a Y direction is assumed as a depth direction, and a Z direction is assumed as a height direction.

[0034] As illustrated in FIG. **1**, the image forming apparatus **10** is constituted by including a main body part **11**, a document reader **12**, a document conveyance apparatus **20**, and a paper feeding apparatus **13**. The main body part **11** includes therein an image former for forming (printing) an image on a sheet of recording paper. The document reader **12** is arranged above the main body part **11**, and reads a document when the document is to be copied. In an automatic reading mode, the document conveyance apparatus **20** sequentially conveys documents that are placed on a document set tray toward a document placement table of the document reader **12**. The paper feeding apparatus **13** is provided with at least one paper feed cassette in which sheets of recording paper are stocked, and the paper feeding apparatus **13** separates the sheets of recording paper one by one from the selected paper feed cassette and conveys the recording paper toward the main body part **11**. In the main body part **11**, an image is formed on the recording paper sent from the paper feeding apparatus **13**.

[0035] Image data handled in the image forming apparatus **10** is that corresponding to a color image using colors which are black (K), cyan (C), magenta (M), and yellow (Y), or that corresponding to a monochrome image using a single color (e.g., black). Therefore, the image forming apparatus **10** includes, as the image former, four process units which are Pa to Pd associated with black, cyan, magenta, and yellow. Each of the process units Pa to Pd forms a toner image corresponding to the image data by using publicly known electrophotographic technology.

[0036] The toner images formed by the respective process units Pa to Pd are sequentially transferred to and superimposed on an intermediate transfer belt **14**. A colored toner image is thus formed on the intermediate transfer belt **14**. The colored toner image on the intermediate transfer belt **14** is transferred onto the recording paper by a transfer apparatus **15**, and then a fixing unit **16** heats and pressurizes the recording paper to fix the colored toner image on the recording paper.

[0037] FIGS. **2** and **3** are perspective views each showing the outside appearance of the document conveyance apparatus **20**. FIG. **2** is a perspective view of the document conveyance apparatus **20** in a state in which an opening-and-closing cover **24** is closed, and FIG. **3** is a perspective view of the same in a state in which the opening-and-closing cover **24** is opened. The document conveyance apparatus **20** includes a document tray **21** on which a bundle of documents before reading is conducted is placed and a paper discharge tray **22** on which the read document is to be discharged, and a document conveyance path is formed between the document tray **21** and the paper discharge tray **22**. The documents are fed to the document conveyance path one by one from the bundle of documents that are placed on the document tray **21**, and are read while being conveyed. Document conveyance rollers **23** (FIG. **3**) are rollers that convey a document in the document conveyance path.

[0038] Further, on the upper part of the document conveyance apparatus **20**, the opening-and-closing cover **24**, which can be opened and closed with respect to an apparatus housing **27** by being rotated about a rotation shaft **271** (FIGS. **5** and **7**), is provided, and the document conveyance path can be made open by opening the opening-and-closing cover **24**. The opening-and-closing cover **24** is opened by lifting an end portion thereof on a side opposite to the rotation shaft **271** upward.

Further, in the present embodiment, the rotation shaft **271** is provided on the apparatus housing **27**, and a shaft hole through which the rotation shaft **271** passes is provided in the opening-and-closing cover **24**.

[0039] FIG. **4** is a plan view of the document conveyance apparatus **20** in a state in which the opening-and-closing cover **24** is removed. FIG. **5** is a partial cross-sectional view of the vicinity of the document conveyance rollers **23** in the document conveyance apparatus **20** in a state in which the opening-and-closing cover **24** is closed. Note that a cross section illustrated in FIG. **5** exists in at least one place along a front-rear direction of the document conveyance apparatus **20** (i.e., a rotation axis direction of the opening-and-closing cover **24**), and should preferably exist in two or more places. In the present embodiment, it is assumed that the cross section illustrated in FIG. **5** corresponds to, for example, an A-A cross section in FIG. **4**. Also, in the present embodiment, it is assumed that the cross sections illustrated in FIGS. **7**, **8**, **10**, and **11** correspond to, for example, the A-A cross section in FIG. **4**.

[0040] As illustrated in FIG. **5**, the document conveyance rollers **23** are formed as a pair of rollers including a driving roller **231** and a driven roller **232**. In the document conveyance rollers **23**, the driven roller **232** is provided to be contactable with and separable from the driving roller **231**. That is, the driven roller **232** is movable in accordance with the opening and closing operation of the opening-and-closing cover **24**. The driven roller **232** is in contact with the driving roller **231** in a state in which the opening-and-closing cover **24** is closed, and is separated from the driving roller **231** in a state in which the opening-and-closing cover **24** is opened. By this configuration, when a conveyance jam occurs due to a paper jam at the document conveyance rollers **23**, the opening-and-closing cover **24** is opened to have the document conveyance path opened, and the holding of a document by the document conveyance rollers **23** is also released. Thus, it becomes easy to remove the jammed document.

[0041] Specifically, a rotation shaft **232a** of the driven roller **232** is axially supported by a driven roller holding member **25**, and the driven roller holding member **25** is made turnable about a rotation shaft **272** provided on the apparatus housing **27**. FIG. **6** is a perspective view of the driven roller **232**, the driven roller holding member **25**, and a pressure-contact spring (biasing member) **26** to be described later. As illustrated in FIG. **6**, the driven roller holding member **25** includes a bearing portion **251** which is fitted with the rotation shaft **272**, and a shaft hole **252** which axially supports the rotation shaft **232a** of the driven roller **232**.

[0042] In the driven roller holding member **25**, the bearing portion **251** axially supports the rotation shaft **232a** of the driven roller **232** on the lower side relative to the rotation shaft **272**. Further, the driven roller holding member **25** includes an abutment portion (driven-roller-holding-member-side abutment portion) **253** on the upper side relative to the rotation shaft **272**. Furthermore, the driven roller holding member **25** is subjected to a biasing force exerted by the pressure-contact spring **26**, and in a state in which the opening-and-closing cover **24** is closed, the driven roller **232** is brought into pressure contact with the driving roller **231** by the biasing force of the pressure-contact spring **26**. Note that one end of the pressure-contact spring **26** is fitted with a projection portion **254** (FIG. **6**) of the driven roller holding member **25**, and the other end of the pressure-contact spring **26** abuts against an inner surface of a side wall of the apparatus housing **27**.

[0043] FIG. **7** is a partial cross-sectional view of the vicinity of the document conveyance rollers **23** in the document conveyance apparatus **20** in a state of being in the process of opening the opening-and-closing cover **24**. FIG. **8** is a partial cross-sectional view of the vicinity of the document conveyance rollers **23** in the document conveyance apparatus **20** in a state in which the opening-and-closing cover **24** is opened. FIG. **9** is an enlarged perspective view of an end portion of the opening-and-closing cover **24** on the rotation shaft side.

[0044] As illustrated in FIG. **9**, at the end portion of the opening-and-closing cover **24** on the rotation shaft side, a holding rib (second contact portion) **243** is provided on the inner side of a side wall (first contact portion) **242**. It is sufficient if the holding rib **243** is provided at a position which

abuts against at least the abutment portion **253** in the rotation axis direction of the opening-and-closing cover **24**.

[0045] In the document conveyance apparatus **20**, as illustrated in FIG. 5, neither the side wall **242** nor the holding rib **243** is in contact with the abutment portion **253** in a state in which the opening-and-closing cover **24** is closed. That is, the opening-and-closing cover **24** does not exert any force on the driven roller holding member **25**. In the document conveyance apparatus **20**, as illustrated in FIG. 7, the holding rib **243** of the opening-and-closing cover **24** comes into contact with the abutment portion **253** of the driven roller holding member **25** during the process of opening the opening-and-closing cover **24**, and the opening-and-closing cover **24** is opened while the holding rib **243** is kept in contact with the abutment portion **253**. Consequently, a rotational force in a direction opposite to the biasing force of the pressure-contact spring **26** is applied to the driven roller holding member **25**. By this rotational force, the driven roller holding member **25** rotates about the rotation shaft **272** in a clockwise direction and separates the driven roller **232** from the driving roller **231**. Up to a point in the middle of the process of opening the opening-and-closing cover **24**, the state in which the holding rib **243** is in contact with the abutment portion **253** but the side wall **242** does not contact the driven roller holding member **25** is exhibited (this state is referred to as a first state).

[0046] When the opening-and-closing cover **24** is further moved in an open direction from the first state, as illustrated in FIG. 8, the state in which both the side wall **242** and the holding rib **243** of the opening-and-closing cover **24** abut against the abutment portion **253** is exhibited (this state is referred to as a second state). In the second state of the document conveyance apparatus **20**, by the abutment of the side wall **242** and the holding rib **243** against the abutment portion **253**, the opening-and-closing cover **24** can be held in a state in which the opening-and-closing cover **24** is opened without requiring the user to support the opening-and-closing cover **24** with his/her hand. FIG. 10 is a diagram illustrating an action by which the opening-and-closing cover **24** is held in an opened state. As regards the opening-and-closing cover **24** of this case, the weight of the opening-and-closing cover **24** itself in the opened state acts in a direction of closing the opening and closing cover **24**.

[0047] As illustrated in FIG. 10, the abutment portion **253** includes a first surface **253a** and a second surface **253b** having different angles when viewed from the rotation axis direction of the opening-and-closing cover **24**. The second surface **253b** is provided below the first surface **253a**. In the second state in which the opening-and-closing cover **24** is opened, the side wall **242** abuts against the first surface **253a**, and the holding rib **243** abuts against the second surface **253b**.

[0048] Further, in the second state, since the biasing force exerted by the pressure-contact spring **26** acts on the driven roller holding member **25**, the driven roller holding member **25** exerts a pressing force on the opening-and-closing cover **24**. Specifically, the opening-and-closing cover **24** receives a pressing force **F1** from the driven roller holding member **25** at a place of abutment between the side wall **242** and the first surface **253a**, and receives a pressing force **F2** from the driven roller holding member **25** at a place of abutment between the holding rib **243** and the second surface **253b**. Here, while the pressing force **F1** acts downward so as to bias the opening-and-closing cover **24** in a closing direction, the pressing force **F2** acts upward so as to bias the opening-and-closing cover **24** in an opening direction. Note that causing the pressing forces **F1** and **F2** to act as described above can be achieved by appropriately adjusting the inclination angles of the first surface **253a** and the second surface **253b** of the abutment portion **253**. Preferably, an angle between the first surface **253a** and the second surface **253b** should be an obtuse angle greater than 90 degrees and smaller than 180 degrees.

[0049] In the document conveyance apparatus **20** of the present embodiment, by virtue of a balance between the pressing force **F1** and the pressing force **F2** in the second state in which the opening-and-closing cover **24** is opened, the opening-and-closing cover **24** can be held in a state of being opened at a predetermined position even if the user does not support the opening-and-closing cover

24 with his/her hand. Further, with the configuration of the present embodiment, it is possible to hold the opening-and-closing cover **24** in the opened state by using a spring force of the pressure-contact spring **26** for bringing the driven roller **232** into pressure contact with the driving roller **231**. Thus, no complicated structure using another spring, an arm, or the like, for holding the opening-and-closing cover that is opened is required. In other words, jam processing by opening the opening-and-closing cover **24** can be performed, and it becomes possible to hold the opening-and-closing cover **24** that is opened with a simple configuration.

[0050] Note that in the present embodiment, in the first state, as the holding rib **243** comes into contact with the second surface **253b**, the driven roller **232** is separated from the driving roller **231**. Then, when the opening-and-closing cover **24** is opened from the first state, the state in which the holding rib **243** is in contact with the second surface **253b** is maintained, and further in the second state in which the opening-and-closing cover **24** is opened, the side wall **242** comes into contact with the first surface **253a**.

[0051] In the opening-and-closing cover **24**, since both the side wall **242** and the holding rib **243** which abut against the driven roller holding member **25** are formed as ribs (the side wall is also regarded as a rib), the opening-and-closing cover **24** can be easily molded without complicating the shape of the opening-and-closing cover **24**.

[0052] FIG. **11** is a partial cross-sectional view of the vicinity of the document conveyance rollers **23**, which illustrates a modified example of the document conveyance apparatus **20** of the present embodiment. In the document conveyance apparatus **20** illustrated in FIG. **11**, the side wall **242** and the vicinity of a front edge of the holding rib **243** in the opening-and-closing cover **24** are connected to each other by a connection rib **244**. By virtue of the connection rib **244**, deformation of the side wall **242** and the holding rib **243** is suppressed when the opening-and-closing cover **24** is held in an opened state, and the opening-and-closing cover **24** can be stably held. Note that the connection rib **244** is formed in a shape that does not contact the driven roller holding member **25** during the process of opening and closing the opening-and-closing cover **24**. In the example of FIG. **11**, the connection rib **244** has a substantially U-shaped cross section which is curved toward the side opposite to the driven roller holding member **25**. Consequently, the connection rib **244** is formed in a shape that does not contact the driven roller holding member **25**.

Second Embodiment

[0053] A document conveyance apparatus **20** according to a second embodiment will be described below with reference to FIGS. **12** to **16**. FIG. **12** is a partial cross-sectional view of the vicinity of document conveyance rollers **23** in the document conveyance apparatus **20** in a state in which an opening-and-closing cover **24** is closed. FIG. **13** is a partial cross-sectional view of the vicinity of the document conveyance rollers **23** in the document conveyance apparatus **20** in a state in which the opening-and-closing cover **24** is opened. FIG. **14** is an enlarged perspective view of an end portion of the opening-and-closing cover **24** on a rotation shaft side. FIG. **15** is a diagram illustrating an action by which the opening-and-closing cover **24** is held in an opened state. In the present embodiment, it is assumed that the cross sections illustrated in FIGS. **12**, **13**, and **15** correspond to, for example, the A-A cross section in FIG. **4**. In the second embodiment, configurations which are the same as those of the first embodiment are denoted by the same reference numerals as in the first embodiment, and detailed description thereof will be omitted.

[0054] As illustrated in FIGS. **12** to **15**, at the end portion of the opening-and-closing cover **24** on the rotation shaft side, the holding rib **243** of the first embodiment is not provided, but instead a cover side abutment portion **242a** is provided at a front edge of a side wall **242**.

[0055] As illustrated in FIG. **15**, in the present embodiment, in a state in which the opening-and-closing cover **24** is opened, the cover side abutment portion **242a** abuts against an abutment portion (driven-roller-holding-member-side abutment portion) **253** of a driven roller holding member **25**. At this time, since a biasing force exerted by a pressure-contact spring **26** acts on the driven roller holding member **25**, the driven roller holding member **25** exerts a pressing force on the opening-

and-closing cover **24**. Specifically, the opening-and-closing cover **24** receives a pressing force $F2'$ from the driven roller holding member **25** at a place of abutment between the cover side abutment portion **242a** and the abutment portion **253**. The pressing force $F2'$ corresponds to the pressing force $F2$ (FIG. **10**) of the first embodiment, and acts upward so as to bias the opening-and-closing cover **24** in an opening direction.

[0056] In addition, the document conveyance apparatus **20** according to the present embodiment is provided with a restrictor which prevents the opening-and-closing cover **24** from opening beyond a predetermined position. In the present embodiment, as illustrated in FIG. **16**, a restrictor **273** in a shape of a hook (claw) is provided on an apparatus housing **27**. The hook of the restrictor **273** is formed to be oriented on the outer side of the apparatus housing **27**, more specifically, the side toward the opening-and-closing cover **24**. In this configuration, when the opening-and-closing cover **24** is opened to the predetermined position, the hook of the restrictor **273** engages with the side wall **242** of the opening-and-closing cover **24**, whereby the opening-and-closing cover **24** is prevented from opening beyond the predetermined position. The restrictor **273** can be provided at an arbitrary place in an axial direction of the opening-and-closing cover **24** (for example, in FIG. **16**, the position at a B-B cross section in FIG. **4**). Note that the restrictor **273** of the present embodiment is merely an example of a restrictor, and the specific shape and the place of formation of the restrictor are not particularly limited. Also, the restrictor of the present embodiment may be provided in the document conveyance apparatus **20** of the first embodiment.

[0057] In the document conveyance apparatus **20** of the present embodiment, in a state in which the opening-and-closing cover **24** is opened, by virtue of the pressing force $F2'$, it is possible to prevent the opening-and-closing cover **24** from being closed by its own weight, and the opening-and-closing cover **24** that is opened can also be held at a predetermined position by the restrictor **273**. As described above, also in the configuration of the present embodiment, no complicated structure using another spring, an arm, or the like for holding the opening-and-closing cover that is opened is required. In other words, jam processing by opening the opening-and-closing cover **24** can be performed, and it becomes possible to hold the opening-and-closing cover **24** that is opened with a simple configuration.

[0058] The embodiments disclosed herein are merely exemplary in all respects, and do not constitute grounds for restrictive interpretation. Accordingly, the technical scope of the present disclosure should not be interpreted solely from the above-described embodiments, but is defined on the basis of the recitations of the claims.

Claims

1. A document conveyance apparatus including an opening-and-closing cover which is openable and closable with respect to an apparatus housing, the document conveyance apparatus comprising: document conveyance rollers including a driving roller, and a driven roller provided to be contactable with and separable from the driving roller; a driven roller holding member which rotatably holds the driven roller, and causes the driven roller to be in contact with or separated from the driving roller in conjunction with opening and closing of the opening-and-closing cover; and a biasing member which applies, to the driven roller holding member, a biasing force in a direction of bringing the driven roller into pressure contact with the driving roller, wherein: the opening-and-closing cover is provided with a first contact portion and a second contact portion which contact the driven roller holding member; the driven roller holding member is provided with a first surface and a second surface; and in a state in which the opening-and-closing cover is opened, the first contact portion comes into contact with the first surface and the second contact portion comes into contact with the second surface, the first surface biases, by the biasing force of the biasing member, the first contact portion in a direction in which the opening-and-closing cover closes, and the second surface biases, by the biasing force of the biasing member, the second contact portion in a direction

in which the opening-and-closing cover opens.

2. The document conveyance apparatus according to claim 1, wherein: in a first state in which the opening-and-closing cover is in a process of being opened, the driven roller is separated from the driving roller as the second contact portion comes into contact with the second surface; and in the first state, the first contact portion is not in contact with the driven roller holding member.

3. The document conveyance apparatus according to claim 1, wherein when the opening-and-closing cover is opened from the first state, a state in which the second contact portion is in contact with the second surface is maintained, and further in a second state in which the opening-and-closing cover is opened, the first contact portion comes into contact with the first surface.

4. The document conveyance apparatus according to claim 1, wherein the first contact portion and the second contact portion are ribs provided on the opening-and-closing cover, respectively.

5. The document conveyance apparatus according to claim 4, wherein the first contact portion is a side wall of the opening-and-closing cover.

6. The document conveyance apparatus according to claim 4, wherein: the document conveyance apparatus is provided with a connection rib which connects between the ribs of the first contact portion and the second contact portion; and the connection rib is of a shape that does not contact the driven roller holding member during a process of opening and closing the opening-and-closing cover.

7. A document conveyance apparatus including an opening-and-closing cover which is openable and closable with respect to an apparatus housing, the document conveyance apparatus comprising: document conveyance rollers including a driving roller, and a driven roller provided to be contactable with and separable from the driving roller; a driven roller holding member which rotatably holds the driven roller, and causes the driven roller to be in contact with or separated from the driving roller in conjunction with opening and closing of the opening-and-closing cover; and a biasing member which applies, to the driven roller holding member, a biasing force in a direction of bringing the driven roller into pressure contact with the driving roller, wherein: the opening-and-closing cover is provided with a cover side abutment portion which contacts the driven roller holding member when the opening-and-closing cover is opened; the driven roller holding member is provided with a driven-roller-holding-member-side abutment portion which contacts the cover side abutment portion when the opening-and-closing cover is opened; the apparatus housing is provided with a restrictor which restricts opening of the opening-and-closing cover beyond a predetermined position; and in a state in which the opening-and-closing cover is opened, the driven-roller-holding-member-side abutment portion biases, by the biasing force of the biasing member, the cover side abutment portion in a direction in which the opening-and-closing cover opens.

8. The document conveyance apparatus according to claim 7, wherein: the restrictor is in a shape of a hook, and when the opening-and-closing cover is opened to the predetermined position, the hook engages with a side wall of the opening-and-closing cover.

9. An image forming apparatus comprising the document conveyance apparatus according to claim 1.
