



US012403083B2

(12) **United States Patent**
Hamersky et al.

(10) **Patent No.: US 12,403,083 B2**

(45) **Date of Patent: Sep. 2, 2025**

(54) **DISSOLVABLE SOLID STRUCTURE
COMPRISING FIRST AND SECOND
POLYMERIC STRUCTURANTS**

(71) Applicant: **The Procter & Gamble Company**,
Cincinnati, OH (US)

(72) Inventors: **Mark William Hamersky**, Hamilton,
OH (US); **Jennifer Elaine Hilvert**,
Cincinnati, OH (US)

(73) Assignee: **The Procter & Gamble Company**,
Cincinnati, OH (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/898,685**

(22) Filed: **Aug. 30, 2022**

(65) **Prior Publication Data**

US 2023/0060806 A1 Mar. 2, 2023

Related U.S. Application Data

(60) Provisional application No. 63/238,220, filed on Aug.
30, 2021.

(51) **Int. Cl.**
A61K 8/81 (2006.01)
A61K 8/02 (2006.01)
A61Q 5/12 (2006.01)

(52) **U.S. Cl.**
CPC **A61K 8/8176** (2013.01); **A61K 8/0216**
(2013.01); **A61Q 5/12** (2013.01); **A61K**
2800/594 (2013.01)

(58) **Field of Classification Search**
CPC A61K 8/8176; A61K 8/0216; A61K
2800/594; A61K 8/342; A61K 8/416;
A61K 8/42; A61Q 5/12
USPC 424/70, 701
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,421,350	A	6/1922	Powell
2,356,168	A	8/1944	Mabley
2,396,278	A	3/1946	Otto
2,438,091	A	3/1948	Lynch
2,486,921	A	11/1949	Byerly
2,486,922	A	11/1949	Bruce
2,528,378	A	10/1950	Mannheimer
2,613,185	A	10/1952	Marshall
2,648,635	A	8/1953	Jacques et al.
2,658,072	A	11/1953	Milton
2,694,668	A	11/1954	Fricke
2,809,971	A	10/1957	Jack et al.
3,152,046	A	10/1964	Maria
3,157,611	A	11/1964	Lindemann
3,236,733	A	2/1966	Karsten et al.
3,293,718	A	12/1966	Melvin
3,321,425	A	5/1967	Karl-ludwig et al.
3,332,880	A	7/1967	Adriaan et al.

3,426,440	A	2/1969	Shen et al.
3,428,478	A	2/1969	Donaldson et al.
3,452,382	A	7/1969	Kazdan
3,463,308	A	8/1969	Deneke
3,489,688	A	1/1970	Pospischil
3,570,122	A	3/1971	Willimas
3,589,007	A	6/1971	Walton
3,653,383	A	4/1972	Wise
3,695,989	A	10/1972	Albert
3,753,196	A	8/1973	Kurtz et al.
3,761,418	A	9/1973	Parran
3,859,125	A	1/1975	Miller
3,875,300	A	4/1975	Homm et al.
3,904,543	A	9/1975	Knighten
3,929,678	A	12/1975	Laughlin
3,943,949	A	3/1976	Ashton et al.
3,954,113	A	5/1976	Bohrer et al.
3,957,921	A	5/1976	Iwahashi et al.
3,967,921	A	7/1976	Haberli et al.
4,020,156	A	4/1977	Murray et al.
4,024,078	A	5/1977	Gilbert et al.
4,033,365	A	7/1977	Klepak et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU	2004202461	B2	11/2007
CA	2300638	A1	8/2000

(Continued)

OTHER PUBLICATIONS

“Green Chemistry”, Huazhong University of Science and Technol-
ogy Press, published on Jun. 30, 2008, pp. 6.
Afifi-Effat et al., Polymer Letters, 9: 651-655 (1971).
Anonymous “P8136 Poly(vinyl alcohol)” Internet article, [Online]
XP002538935, Retrieved from the Internet: URL: [http://20.NWWW.
sigmaaldrich.com/catalog/ProductDetail.do?D7=0%N25-
SEARCH_CONCAT_PNOIBRAND_KEY%N4=P8136%7SCIAL%
N25=0%QS=ON%F=SPEC](http://20.NWWW.sigmaaldrich.com/catalog/ProductDetail.do?D7=0%N25-SEARCH_CONCAT_PNOIBRAND_KEY%N4=P8136%7SCIAL%N25=0%QS=ON%F=SPEC) retrieved on Jul. 28, 2009, year 2009,
1 pg.
Ashland, KLUCEL hydroxypropylcellulose, accessed at [http://www.
ashland.com/Ashland/Static/Documents/ASI/PC_11229_Klucel_
HPC.pdf](http://www.ashland.com/Ashland/Static/Documents/ASI/PC_11229_Klucel_HPC.pdf) on Apr. 20, 2016.

(Continued)

Primary Examiner — Frederick F Krass

Assistant Examiner — Lucy M Tien

(74) Attorney, Agent, or Firm — Alexandra S. Anoff

(57)

ABSTRACT

A dissolvable solid structure that is formed by a homoge-
neous mixture. The mixture includes from about 1% to about
10% of a first polymeric structurant having a molecular
weight of from about 1,000,000 g/mol to about 4,000,000
g/mol, from about 10% to about 20% of a second polymeric
structurant having a molecular weight of from about 50,000
g/mol to about 500,000 g/mol, from about 10 wt % to about
85 wt % of one or more high melting point fatty material
having a carbon chain length C12-C22 or mixtures thereof
and a melting point above 25° C., and from about 1 wt % to
about 60 wt % of a cationic surfactant. The dissolvable solid
structures can provide an adequate strength during manu-
facturing, while not deteriorating usage feel when used
and/or applied by consumers.

14 Claims, No Drawings

(56)

References Cited

U.S. PATENT DOCUMENTS

4,051,081	A	9/1977	Jabs et al.	5,364,627	A	11/1994	Song
4,089,945	A	5/1978	Brinkman et al.	5,387,147	A	2/1995	Ohshima
4,149,551	A	4/1979	Benjamin et al.	5,391,368	A	2/1995	Gerstein
4,180,558	A	12/1979	Franklin	D357,115	S	4/1995	Ashley et al.
4,185,125	A	1/1980	Kimura et al.	5,409,703	A	4/1995	Mcanalley et al.
4,196,190	A	4/1980	Gehman et al.	D358,025	S	5/1995	Martin et al.
4,197,865	A	4/1980	Jacquet et al.	5,415,810	A	5/1995	Lee et al.
4,206,196	A	6/1980	Davis	5,429,628	A	7/1995	Trinh et al.
4,217,914	A	8/1980	Jacquet et al.	5,429,874	A	7/1995	Vanputte
4,272,511	A	6/1981	Papantoniou et al.	5,446,079	A	8/1995	Buchanan et al.
4,286,016	A	8/1981	Dimond	5,455,114	A	10/1995	Ohmory
4,287,219	A	9/1981	Fabre	5,457,895	A	10/1995	Thompson et al.
4,315,965	A	2/1982	Mason	5,458,433	A	10/1995	Stastny
4,323,525	A	4/1982	Bornat	5,470,424	A	11/1995	Isaac
4,323,683	A	4/1982	Bolich, Jr. et al.	5,470,492	A	11/1995	Childs et al.
4,340,583	A	7/1982	Wason	5,470,653	A	11/1995	Honeycutt
4,342,813	A	8/1982	Erickson	5,476,597	A	12/1995	Sakata et al.
4,345,080	A	8/1982	Bolich, Jr.	5,486,418	A	1/1996	Ohmory
4,349,531	A	9/1982	Mlodozieniec	5,501,238	A	3/1996	Borstel et al.
D266,829	S	11/1982	Yoshizawa et al.	5,518,730	A	5/1996	Fuisz
4,377,615	A	3/1983	Suzuki	5,520,924	A	5/1996	Chapman
4,379,753	A	4/1983	Bolich, Jr.	5,533,636	A	7/1996	Reiker
4,381,919	A	5/1983	Jacquet et al.	5,538,735	A	7/1996	Ahn
4,415,617	A	11/1983	D Elia	5,580,481	A	12/1996	Sakata et al.
4,422,853	A	12/1983	Jacquet et al.	5,582,786	A	12/1996	Brunskill et al.
4,448,699	A	5/1984	Barrat et al.	5,585,059	A	12/1996	Kobayashi
4,470,982	A	9/1984	Winkler	D378,180	S	2/1997	Hayes et al.
4,507,280	A	3/1985	Pohl et al.	5,651,987	A	7/1997	Fuisz
4,529,586	A	7/1985	De et al.	5,660,845	A	8/1997	Trinh et al.
4,536,361	A	8/1985	Torobin	5,672,576	A	9/1997	Behrens et al.
D286,450	S	10/1986	Tovey	5,673,576	A	10/1997	Chen et al.
4,635,351	A	1/1987	Koch et al.	5,674,478	A	10/1997	Dodd
4,637,859	A	1/1987	Trokhan	5,691,015	A	11/1997	Tsukamoto
4,639,390	A	1/1987	Shoji	5,705,183	A	1/1998	Phillips
4,663,158	A	5/1987	Wolfram et al.	5,716,692	A	2/1998	Warner
4,683,001	A	7/1987	Floyd	5,717,026	A	2/1998	Ikimine
4,710,374	A	12/1987	Grollier et al.	5,735,812	A	4/1998	Hardy
4,723,362	A	2/1988	Boerger	5,750,122	A	5/1998	Evans
4,727,410	A	2/1988	Higgins, III	5,756,438	A	5/1998	Rau et al.
4,822,613	A	4/1989	Rodero	5,780,047	A	7/1998	Kamiya et al.
4,885,107	A	12/1989	Wetzel	5,780,418	A	7/1998	Niinaka
4,892,758	A	1/1990	Serbiak	D398,847	S	9/1998	Wyslowsky et al.
4,923,660	A	5/1990	Willenberg	D399,260	S	10/1998	Thimote
4,976,953	A	12/1990	Orr et al.	5,827,586	A	10/1998	Yamashita
4,990,280	A	2/1991	Thorengaard	5,840,423	A	11/1998	Sano
5,034,421	A	7/1991	Fuisz	5,840,675	A	11/1998	Yeazell
5,041,252	A	8/1991	Fujii	5,849,378	A	12/1998	Gask
5,052,296	A	10/1991	Shiba	5,863,887	A	1/1999	Gillette
5,055,384	A	10/1991	Kuehnert	5,879,493	A	3/1999	Johnson
5,061,481	A	10/1991	Suzuki et al.	D407,640	S	4/1999	Crapser et al.
5,062,889	A	11/1991	Hoehl et al.	D408,223	S	4/1999	Henry
5,062,994	A	11/1991	Imperatori	5,911,224	A	6/1999	Berger
5,094,853	A	3/1992	Hagarty	5,914,124	A	6/1999	Mahoney
5,098,636	A	3/1992	Balk	5,925,603	A	7/1999	D Angelo
5,100,657	A	3/1992	Ansher-jackson et al.	5,942,179	A	8/1999	Tallentire
5,100,658	A	3/1992	Bolich, Jr. et al.	5,952,286	A	9/1999	Puvvada et al.
5,102,129	A	4/1992	Roberts	5,955,419	A	9/1999	Barket, Jr. et al.
5,104,646	A	4/1992	Bolich, Jr.	D416,103	S	11/1999	Hashmi
5,106,609	A	4/1992	Bolich, Jr.	5,976,454	A	11/1999	Sterzel et al.
5,110,678	A	5/1992	Narukawa	D418,415	S	1/2000	Hayes et al.
5,112,515	A	5/1992	Buxton et al.	D418,750	S	1/2000	Blin
5,120,888	A	6/1992	Nohr	6,010,719	A	1/2000	Remon et al.
5,135,804	A	8/1992	Harpell	6,028,016	A	2/2000	Yahiaoui et al.
5,158,810	A	10/1992	Oishi	6,029,808	A	2/2000	Peck et al.
5,166,276	A	11/1992	Hayama et al.	6,034,043	A	3/2000	Fujiwara et al.
D334,420	S	3/1993	Copeland et al.	6,037,319	A	3/2000	Dickler
5,208,104	A	5/1993	Ueda	6,066,396	A	5/2000	Inada
5,220,033	A	6/1993	Kamei et al.	6,074,997	A	6/2000	Rau et al.
5,230,853	A	7/1993	Colegrove	6,080,346	A	6/2000	Jack
5,261,426	A	11/1993	Kellett et al.	D427,902	S	7/2000	Hayes et al.
5,280,079	A	1/1994	Allen et al.	6,106,849	A	8/2000	Malkan et al.
RE34,584	E	4/1994	Grote et al.	6,130,193	A	10/2000	Gillette
5,342,335	A	8/1994	Rhim	6,175,054	B1	1/2001	Jacques
D351,345	S	10/1994	Geho	6,177,391	B1	1/2001	Zafar
5,362,532	A	11/1994	Famili	6,197,238	B1	3/2001	Wang
				6,200,949	B1	3/2001	Reijmer et al.
				6,207,274	B1	3/2001	Ferenc
				D441,869	S	5/2001	Bloor et al.
				D442,353	S	5/2001	Macias

(56)

References Cited

U.S. PATENT DOCUMENTS

D442,739 S	5/2001	Friesenhahn	D577,332 S	9/2008	Moore
D443,389 S	6/2001	Friesenhahn	7,429,273 B2	9/2008	De Dominicis
6,274,162 B1	8/2001	Steffenino	D578,881 S	10/2008	Friedland et al.
D448,802 S	10/2001	Lariviere, Jr. et al.	7,446,084 B2	11/2008	Barthel
D449,881 S	10/2001	Mock, Sr.	7,491,407 B2	2/2009	Pourdeyhim
D450,378 S	11/2001	Minakuchi et al.	D588,332 S	3/2009	Phelan
6,319,510 B1	11/2001	Yates	7,507,698 B2	3/2009	Franzolin
6,335,312 B1	1/2002	Coffindaffer et al.	7,547,737 B2	6/2009	Kochvar
6,365,142 B1	4/2002	Tamura	7,563,757 B2	7/2009	Kouvroukoglou
6,382,526 B1	5/2002	Reneker et al.	7,704,328 B2	4/2010	Bailey et al.
6,406,797 B1	6/2002	Vanputte	7,708,840 B2	5/2010	Wiedemann
6,417,156 B1	7/2002	Smith et al.	7,727,946 B2	6/2010	Catalfamo
6,420,625 B1	7/2002	Jones	7,824,588 B2	11/2010	Yang
6,426,091 B1	7/2002	Okumura et al.	7,832,552 B2	11/2010	Newman
6,440,926 B1	8/2002	Spadoni et al.	7,846,462 B2	12/2010	Spadini et al.
D462,900 S	9/2002	Yamada et al.	7,856,989 B2	12/2010	Karles
6,448,462 B2	9/2002	Groitzsch	7,892,992 B2	2/2011	Kamada et al.
6,458,754 B1	10/2002	Velazquez et al.	7,901,696 B2	3/2011	Eknoian et al.
6,465,407 B2	10/2002	Hayashi	7,967,801 B2	6/2011	Hammons
D465,303 S	11/2002	Friesenhahn	D640,921 S	7/2011	Caldwell
6,503,521 B1	1/2003	Atis et al.	D644,541 S	9/2011	Schrader et al.
6,525,034 B2	2/2003	Dalrymple et al.	8,049,061 B2	11/2011	Ehrenreich et al.
6,552,123 B1	4/2003	Katayama	D651,096 S	12/2011	Nakagiri
6,576,575 B2	6/2003	Griesbach, III	8,197,830 B2	6/2012	Helfman et al.
6,608,121 B2	8/2003	Isozaki	8,268,764 B2	9/2012	Glenn, Jr. et al.
D479,561 S	9/2003	Meyer	8,273,333 B2	9/2012	Glenn, Jr. et al.
6,623,694 B1	9/2003	Ferguson et al.	8,288,332 B2	10/2012	Fossum et al.
6,657,004 B2	12/2003	Mizutani	8,309,505 B2	11/2012	Fossum et al.
D484,749 S	1/2004	Garraway	8,349,232 B2	1/2013	Pourdeyhim
6,699,826 B1	3/2004	Saijo	8,349,341 B2	1/2013	Glenn, Jr. et al.
6,723,160 B2	4/2004	Mackey et al.	8,349,786 B2	1/2013	Glenn, Jr. et al.
D489,162 S	5/2004	Dings-plooi	8,349,787 B2	1/2013	Glenn, Jr. et al.
6,730,648 B2	5/2004	Gorlin	8,357,728 B2	1/2013	Butler et al.
6,783,852 B2	8/2004	Inada	8,367,596 B2	2/2013	Fossum et al.
6,787,512 B1	9/2004	Verrall	D680,882 S	4/2013	Logue
6,790,814 B1	9/2004	Marin	8,415,287 B2	4/2013	Glenn, Jr. et al.
6,800,295 B2	10/2004	Fox	D682,622 S	5/2013	Keys
6,802,295 B2	10/2004	Bedwell et al.	8,453,653 B2	6/2013	Mishra et al.
6,808,375 B2	10/2004	Kloetzer	8,461,090 B2	6/2013	Glenn, Jr. et al.
6,808,598 B1	10/2004	Takeuchi	8,461,091 B2	6/2013	Glenn, Jr. et al.
6,818,606 B1	11/2004	Hanada	8,466,099 B2	6/2013	Glenn, Jr. et al.
6,825,161 B2	11/2004	Shefer et al.	D685,436 S	7/2013	Menting
6,831,046 B2	12/2004	Carew et al.	8,476,211 B2	7/2013	Glenn, Jr. et al.
6,846,784 B2	1/2005	Engel et al.	8,541,081 B1	9/2013	Ranganathan et al.
6,878,368 B2	4/2005	Ohta et al.	8,546,640 B2	10/2013	Popovsky et al.
6,898,819 B2	5/2005	Tanaka et al.	D694,621 S	12/2013	Mccarthy
6,898,921 B2	5/2005	Duffield	8,723,333 B2	5/2014	Park et al.
D509,935 S	9/2005	Burt	8,765,170 B2	7/2014	Glenn, Jr. et al.
6,943,200 B1	9/2005	Corrand et al.	8,785,361 B2	7/2014	Sivik et al.
6,946,506 B2	9/2005	Bond	D712,159 S	9/2014	Clerici et al.
6,949,498 B2	9/2005	Murphy	D712,822 S	9/2014	Brusaw et al.
6,956,070 B2	10/2005	Fujiwara	8,962,501 B2	2/2015	Johnson et al.
6,977,116 B2	12/2005	Cabell	8,980,816 B2	3/2015	Dreher
D515,915 S	2/2006	Karim	9,005,635 B2	4/2015	Darcy et al.
7,015,181 B2	3/2006	Lambino	9,062,186 B2	6/2015	Longdon et al.
7,026,049 B2	4/2006	Endo	9,074,305 B2	7/2015	Glenn, Jr. et al.
7,041,369 B1	5/2006	Mackey et al.	D739,227 S	9/2015	Mitchell et al.
7,067,575 B2	6/2006	Kitamura	9,125,811 B2	9/2015	Tojo et al.
7,083,047 B2	8/2006	Bone	9,139,802 B2	9/2015	Weisman et al.
7,094,744 B1	8/2006	Kobayashi	D740,928 S	10/2015	Bruining et al.
7,115,551 B2	10/2006	Hasenoechl	9,163,205 B2	10/2015	Sivik et al.
7,125,828 B2	10/2006	Catlin	9,173,826 B2	11/2015	Schwartz et al.
7,169,740 B2	1/2007	Sommerville-roberts	9,175,250 B2	11/2015	Sivik et al.
7,172,765 B2	2/2007	Chu et al.	9,198,838 B2	12/2015	Glenn, Jr. et al.
7,196,026 B2	3/2007	Di Luccio	D748,240 S	1/2016	Goode
RE39,557 E	4/2007	Moe	9,421,153 B2	8/2016	Sivik et al.
7,208,460 B2	4/2007	Shefer et al.	D769,522 S	10/2016	Venet
7,221,900 B2	5/2007	Reade et al.	D771,788 S	11/2016	Duckwitz
7,226,899 B2	6/2007	Cole	9,480,628 B2	11/2016	Sivik et al.
D549,051 S	8/2007	Nordwall	D774,086 S	12/2016	Montes et al.
7,285,520 B2	10/2007	Krzsik	D775,198 S	12/2016	Montes et al.
7,291,300 B2	11/2007	Chhabra et al.	9,539,444 B2	1/2017	Kinoshita et al.
7,387,787 B2	6/2008	Fox	9,545,364 B2	1/2017	Glenn, Jr. et al.
7,407,669 B2	8/2008	Leung	D778,026 S	2/2017	Roetheli
D576,753 S	9/2008	Mukai	D793,025 S	8/2017	Slusarczyk et al.
			D797,551 S	9/2017	Chatterton et al.
			D798,143 S	9/2017	Chatterton
			D808,583 S	1/2018	Zietek
			9,902,077 B2	2/2018	Park et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

D811,922	S	3/2018	Lefave	2003/0207776	A1	11/2003	Shefer et al.
D811,935	S	3/2018	Hughes	2003/0209166	A1	11/2003	Vanmaele et al.
D819,836	S	6/2018	Noël	2003/0215522	A1	11/2003	Johnson et al.
10,045,915	B2	8/2018	Glenn, Jr. et al.	2003/0216098	A1	11/2003	Carlyle
D848,102	S	5/2019	Carlson et al.	2003/0224959	A1	12/2003	Smith
D850,041	S	5/2019	Endle	2003/0232183	A1	12/2003	Dufton
10,294,586	B2	5/2019	Sivik et al.	2004/0029762	A1	2/2004	Hensley
D851,344	S	6/2019	Carlson et al.	2004/0032859	A1	2/2004	Miao
D857,156	S	8/2019	Hani	2004/0048759	A1	3/2004	Ribble et al.
D857,242	S	8/2019	Darrow et al.	2004/0048771	A1	3/2004	Mcdermott et al.
D857,929	S	8/2019	Darrow et al.	2004/0053808	A1	3/2004	Raehse et al.
D862,020	S	10/2019	Gorrell et al.	2004/0059055	A1	3/2004	Inada et al.
D863,600	S	10/2019	Chao	2004/0071742	A1	4/2004	Popplewell
D864,507	S	10/2019	Stoughton et al.	2004/0071755	A1	4/2004	Fox
D866,105	S	11/2019	Carlson et al.	2004/0082239	A1	4/2004	Di Luccio et al.
D866,891	S	11/2019	Carlson et al.	2004/0092635	A1	5/2004	Kitamura
D866,892	S	11/2019	Hunt et al.	2004/0108615	A1	6/2004	Foley
D866,893	S	11/2019	Hunt et al.	2004/0110656	A1	6/2004	Casey et al.
D867,717	S	11/2019	Chavez	2004/0116018	A1	6/2004	Fenwick et al.
D868,159	S	11/2019	Swisher et al.	2004/0116539	A1	6/2004	Biercevicz et al.
D868,953	S	12/2019	Mckendree	2004/0118852	A1	6/2004	Barmore et al.
10,569,286	B2	2/2020	Anderson et al.	2004/0126585	A1	7/2004	Kerins et al.
D878,694	S	3/2020	Carlson et al.	2004/0167256	A1	8/2004	Verrall
10,646,413	B2	5/2020	Sivik et al.	2004/0170836	A1	9/2004	Bond
10,694,917	B2	6/2020	Dreher et al.	2004/0175404	A1	9/2004	Shefer
D901,115	S	11/2020	Carlson et al.	2004/0180597	A1	9/2004	Kamada
D903,152	S	11/2020	Chao	2004/0202632	A1	10/2004	Gott et al.
10,821,056	B2	11/2020	Swartz et al.	2004/0204543	A1	10/2004	Yang
D906,802	S	1/2021	Chi	2004/0206270	A1	10/2004	Vanmaele et al.
10,894,005	B2	1/2021	Sivik et al.	2004/0242097	A1	12/2004	Hasenoechl
D910,434	S	2/2021	Tan et al.	2004/0242772	A1	12/2004	Huth et al.
D910,457	S	2/2021	Lee	2004/0253434	A1	12/2004	Patel
D921,166	S	6/2021	Meyers	2004/0254086	A1	12/2004	Hedges et al.
D933,095	S	10/2021	Heiner et al.	2004/0266300	A1	12/2004	Isele et al.
11,351,094	B2	6/2022	Hamersky et al.	2005/0003048	A1	1/2005	Pearce
11,395,789	B2	7/2022	Pratt et al.	2005/0003991	A1	1/2005	Macquarrie
11,419,808	B2	8/2022	Hilvert et al.	2005/0008776	A1	1/2005	Chhabra
11,679,066	B2	6/2023	Song et al.	2005/0010010	A1	1/2005	Kitamura
12,018,232	B2	6/2024	Macnamara	2005/0069575	A1	3/2005	Fox
2001/0037851	A1	11/2001	Mortellite	2005/0118237	A1	6/2005	Krzszyk et al.
2002/0018906	A1	2/2002	Clark	2005/0136112	A1	6/2005	Gonzales
2002/0044968	A1	4/2002	Van Lengerich	2005/0136772	A1	6/2005	Chen et al.
2002/0064510	A1	5/2002	Dalrymple et al.	2005/0136780	A1	6/2005	Clark et al.
2002/0077264	A1	6/2002	Roberts et al.	2005/0137115	A1	6/2005	Cole et al.
2002/0081732	A1	6/2002	Bowlin et al.	2005/0137272	A1	6/2005	Gaserod
2002/0081930	A1	6/2002	Jackson et al.	2005/0159730	A1	7/2005	Kathrani et al.
2002/0098994	A1	7/2002	Zafar	2005/0180962	A1	8/2005	Raz et al.
2002/0099109	A1	7/2002	Dufton et al.	2005/0186256	A1	8/2005	Dihel
2002/0161088	A1	10/2002	Kochvar	2005/0202992	A1	9/2005	Grandio et al.
2002/0169092	A1	11/2002	Alexandre et al.	2005/0209574	A1	9/2005	Boehringer
2002/0173213	A1	11/2002	Chu	2005/0220745	A1	10/2005	Lu
2002/0175449	A1	11/2002	Chu et al.	2005/0232954	A1	10/2005	Yoshinari et al.
2002/0176827	A1	11/2002	Rajaiah	2005/0253297	A1	11/2005	Pedmo et al.
2002/0177621	A1	11/2002	Hanada et al.	2005/0267005	A1	12/2005	Dasque et al.
2002/0187181	A1	12/2002	Godbey et al.	2005/0272836	A1	12/2005	Yaginuma et al.
2003/0013369	A1	1/2003	Soane et al.	2005/0281757	A1	12/2005	Ibrahim
2003/0017208	A1	1/2003	Ignatious	2005/0287106	A1	12/2005	Legendre
2003/0018242	A1	1/2003	Hursh et al.	2006/0002880	A1	1/2006	Peffly et al.
2003/0032573	A1	2/2003	Tanner et al.	2006/0013869	A1	1/2006	Ignatious
2003/0045441	A1	3/2003	Hsu et al.	2006/0035042	A1	2/2006	Morken
2003/0045446	A1	3/2003	Dihora	2006/0052263	A1	3/2006	Roreger et al.
2003/0054966	A1	3/2003	Bone et al.	2006/0064510	A1	3/2006	Low et al.
2003/0069154	A1	4/2003	Hsu et al.	2006/0078528	A1	4/2006	Yang et al.
2003/0080150	A1	5/2003	Cowan et al.	2006/0078529	A1	4/2006	Uchida et al.
2003/0099691	A1	5/2003	Lydzinski et al.	2006/0083784	A1	4/2006	Ignatious
2003/0099692	A1	5/2003	Lydzinski et al.	2006/0089276	A1	4/2006	Klotz
2003/0114332	A1	6/2003	Ramcharan et al.	2006/0127458	A1	6/2006	Kiser
2003/0141662	A1	7/2003	Kost et al.	2006/0128592	A1	6/2006	Ross et al.
2003/0166489	A1	9/2003	Van Asten et al.	2006/0134412	A1	6/2006	Mackey
2003/0166495	A1	9/2003	Wang	2006/0135026	A1	6/2006	Arendt et al.
2003/0180242	A1	9/2003	Eccard et al.	2006/0159730	A1	7/2006	Simon
2003/0185872	A1	10/2003	Kochinke	2006/0160453	A1	7/2006	Suh
2003/0186826	A1	10/2003	Eccard et al.	2006/0189772	A1	8/2006	Scheibel
2003/0194416	A1	10/2003	Shefer	2006/0228319	A1	10/2006	Vona et al.
2003/0199412	A1	10/2003	Gupta	2006/0254013	A1	11/2006	Konishi
				2006/0254014	A1	11/2006	Konishi
				2006/0258251	A1	11/2006	Konishi
				2006/0264130	A1	11/2006	Karles
				2006/0274263	A1	12/2006	Yacktmann et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0028939	A1	2/2007	Mareri et al.	2010/0286011	A1	11/2010	Glenn, Jr. et al.
2007/0054579	A1	3/2007	Baker, Jr.	2010/0291165	A1	11/2010	Glenn, Jr. et al.
2007/0098749	A1	5/2007	Eknoian et al.	2010/0298188	A1	11/2010	Glenn, Jr. et al.
2007/0099813	A1	5/2007	Luizzi et al.	2011/0014252	A1	1/2011	Sagel et al.
2007/0110792	A9	5/2007	Simon	2011/0023240	A1	2/2011	Fossum
2007/0128256	A1	6/2007	Aubrun-sonneville	2011/0027328	A1	2/2011	Baig et al.
2007/0134304	A1	6/2007	Aubrun-sonneville	2011/0028373	A1	2/2011	Fossum et al.
2007/0134481	A1	6/2007	Aubrun-sonneville	2011/0028374	A1	2/2011	Fossum et al.
2007/0135528	A1	6/2007	Butler et al.	2011/0033509	A1	2/2011	Simon
2007/0149435	A1	6/2007	Koenig et al.	2011/0045041	A1	2/2011	Golubovic-liakopoulos et al.
2007/0225388	A1	9/2007	Cooper et al.	2011/0123596	A1	5/2011	Baecker et al.
2007/0253926	A1	11/2007	Tadrowski	2011/0129510	A1	6/2011	Liebmann
2007/0259170	A1	11/2007	Brown	2011/0136719	A1	6/2011	Jalbert
2007/0259996	A1	11/2007	Vicari	2011/0159267	A1	6/2011	Lee
2007/0269651	A1	11/2007	Denome et al.	2011/0165110	A1	7/2011	Kinoshita et al.
2007/0298064	A1	12/2007	Koslow	2011/0182956	A1	7/2011	Glenn, Jr. et al.
2008/0008906	A1	1/2008	Catalfamo	2011/0189246	A1	8/2011	Glenn, Jr. et al.
2008/0019935	A1	1/2008	Khan	2011/0189247	A1	8/2011	Glenn, Jr. et al.
2008/0035174	A1	2/2008	Aubrun-sonneville	2011/0195098	A1	8/2011	Glenn, Jr. et al.
2008/0083420	A1	4/2008	Glenn et al.	2011/0223381	A1	9/2011	Sauter
2008/0087293	A1	4/2008	Glenn et al.	2011/0230112	A1	9/2011	Rose
2008/0090939	A1	4/2008	Netravali et al.	2011/0250256	A1	10/2011	Hyun-oh et al.
2008/0095828	A1	4/2008	Privitera et al.	2011/0287687	A1	11/2011	Kramer et al.
2008/0108748	A1	5/2008	Buckley	2011/0301070	A1	12/2011	Ochomogo
2008/0118727	A1	5/2008	Andersen	2012/0021026	A1	1/2012	Glenn, Jr.
2008/0131695	A1	6/2008	Aouad et al.	2012/0027838	A1	2/2012	Gordon et al.
2008/0138492	A1	6/2008	Cingotti	2012/0048769	A1	3/2012	Sivik
2008/0146481	A1	6/2008	Brown	2012/0052036	A1	3/2012	Glenn, Jr.
2008/0149119	A1	6/2008	Shen	2012/0052037	A1	3/2012	Sivik et al.
2008/0152894	A1	6/2008	Beihoffer et al.	2012/0053103	A1	3/2012	Sivik
2008/0153730	A1	6/2008	Tsaur et al.	2012/0053108	A1	3/2012	Glenn, Jr.
2008/0215023	A1	9/2008	Scavone et al.	2012/0058100	A1	3/2012	Shastri et al.
2008/0220054	A1	9/2008	Shastri	2012/0058166	A1	3/2012	Glenn, Jr.
2008/0226919	A1	9/2008	Hosoda	2012/0082037	A1	4/2012	Wang
2008/0242572	A1	10/2008	Icht	2012/0107534	A1	5/2012	Wnuk et al.
2008/0269095	A1	10/2008	Aubrun-sonneville	2012/0172831	A1	7/2012	Darcy
2008/0276178	A1	11/2008	Fadell et al.	2012/0215148	A1	8/2012	Ewert
2008/0279905	A1	11/2008	Kawamoto et al.	2012/0237576	A1	9/2012	Gordon
2008/0292669	A1	11/2008	Deng et al.	2012/0258902	A1	10/2012	Parrish et al.
2008/0293839	A1	11/2008	Stobby	2012/0270029	A1	10/2012	Glenn, Jr. et al.
2009/0004254	A1	1/2009	Maibach	2012/0288693	A1	11/2012	Stanley et al.
2009/0041820	A1	2/2009	Wu et al.	2012/0294823	A1	11/2012	Aramwit
2009/0054860	A1	2/2009	Young et al.	2012/0321580	A1	12/2012	Glenn, Jr.
2009/0061225	A1	3/2009	Bailey et al.	2013/0052277	A1	2/2013	Weiss et al.
2009/0061496	A1	3/2009	Kuhn	2013/0142852	A1	6/2013	Tojo et al.
2009/0061719	A1	3/2009	Shibutani	2013/0171421	A1	7/2013	Weisman
2009/0144913	A1	6/2009	Yu et al.	2013/0230482	A1	9/2013	Saguchi et al.
2009/0155326	A1	6/2009	Mack	2013/0236520	A1	9/2013	Popovsky et al.
2009/0155383	A1	6/2009	Kitko et al.	2013/0280979	A1	10/2013	Mckee
2009/0181587	A1	7/2009	Kang	2013/0303419	A1	11/2013	Glenn, Jr. et al.
2009/0197787	A1	8/2009	Venet et al.	2014/0017402	A1	1/2014	Kleinwaechter et al.
2009/0232873	A1	9/2009	Glenn, Jr. et al.	2014/0039114	A1	2/2014	Hagihara et al.
2009/0247036	A1	10/2009	Shi et al.	2014/0105946	A1	4/2014	Glenn, Jr. et al.
2009/0249558	A1	10/2009	Fileccia	2014/0127145	A1	5/2014	Deckner
2009/0258099	A1	10/2009	Brown et al.	2014/0128345	A1	5/2014	Woodrow et al.
2009/0263342	A1	10/2009	Glenn, Jr. et al.	2014/0265007	A1	9/2014	Bruning et al.
2009/0285718	A1	11/2009	Privitera	2014/0271744	A1	9/2014	Glenn, Jr. et al.
2009/0286437	A1	11/2009	Cunningham et al.	2014/0271745	A1	9/2014	Glenn, Jr. et al.
2009/0291282	A1	11/2009	Kitamura et al.	2014/0287973	A1	9/2014	Sivik
2009/0293281	A1	12/2009	Bruno	2014/0329428	A1	11/2014	Glenn, Jr. et al.
2009/0312220	A1	12/2009	Boutoille	2015/0044157	A1	2/2015	Kulkarni et al.
2010/0018641	A1	1/2010	Branham	2015/0071572	A1	3/2015	Dreher
2010/0021517	A1	1/2010	Ahlers	2015/0102307	A1	4/2015	Tajima et al.
2010/0098745	A1	4/2010	Staab	2015/0157548	A1	6/2015	De Feij et al.
2010/0105821	A1	4/2010	Verrall	2015/0297494	A1	10/2015	Mao et al.
2010/0135921	A1	6/2010	Hughes et al.	2015/0313803	A1	11/2015	Lynch et al.
2010/0150976	A1	6/2010	Schnitzler et al.	2015/0313804	A1	11/2015	Lynch et al.
2010/0166854	A1	7/2010	Michniak-kohn	2015/0313805	A1	11/2015	Lynch et al.
2010/0167971	A1	7/2010	Glenn, Jr. et al.	2015/0313806	A1	11/2015	Lynch et al.
2010/0173817	A1	7/2010	Glenn, Jr. et al.	2015/0313807	A1	11/2015	Lynch et al.
2010/0179083	A1	7/2010	Glenn, Jr. et al.	2015/0313808	A1	11/2015	Lynch et al.
2010/0196440	A1	8/2010	Stark	2015/0313809	A1	11/2015	Lynch et al.
2010/0266668	A1	10/2010	Coffee	2015/0315350	A1	11/2015	Mao et al.
2010/0279905	A1	11/2010	Glenn, Jr.	2016/0008235	A1	1/2016	Sivik et al.
2010/0285101	A1	11/2010	Moore	2016/0010041	A1	1/2016	Sivik et al.
				2016/0101026	A1	4/2016	Pratt et al.
				2016/0101204	A1	4/2016	Lynch et al.
				2016/0143827	A1	5/2016	Castan Barberan et al.
				2016/0250109	A1	9/2016	Dreher et al.

(56)	References Cited			EP	0948960	A2	10/1999
	U.S. PATENT DOCUMENTS			EP	1048722	A1	11/2000
				EP	1160311	A2	12/2001
				EP	1214879	A2	6/2002
2016/0324741	A1	11/2016	Baig	EP	1227152	A1	7/2002
2016/0367104	A1	12/2016	Dreher et al.	EP	1275368	A1	1/2003
2017/0121641	A1	5/2017	Smith	EP	1306425	A2	5/2003
2017/0319876	A1	11/2017	Hentrich et al.	EP	1217987	B1	12/2004
2017/0335080	A1	11/2017	Mao et al.	EP	1574561	A1	9/2005
2018/0015643	A1	1/2018	Patel et al.	EP	1375377	B1	10/2005
2018/0104177	A1	4/2018	Constantine et al.	EP	1614790	A1	1/2006
2018/0110710	A1	4/2018	Zhao et al.	EP	1409628	B1	2/2006
2018/0140469	A1	5/2018	Kane et al.	EP	1512701	B1	6/2006
2018/0163325	A1*	6/2018	Glenn, Jr. D01D 5/423	EP	1887036	A2	2/2008
2018/0258555	A1	9/2018	Glenn, Jr.	EP	1888036		2/2008
2018/0311135	A1	11/2018	Chang et al.	EP	1958532	A2	8/2008
2018/0333339	A1*	11/2018	Hamersky A61K 8/41	EP	2085434	A1	8/2009
2018/0334644	A1	11/2018	Hamersky et al.	EP	1436376	B1	4/2010
2018/0338890	A1	11/2018	Glenn, Jr.	EP	2226379	A1	9/2010
2019/0015875	A1	1/2019	Gardner, Jr. et al.	EP	1317916	B1	10/2010
2019/0105243	A1	4/2019	Song et al.	EP	2246031	A1	11/2010
2019/0282457	A1	9/2019	Pratt et al.	EP	1948771	B1	12/2010
2019/0282461	A1	9/2019	Glassmeyer et al.	EP	2319965	A1	5/2011
2019/0350819	A1*	11/2019	Hamersky A61K 8/463	EP	2363432	A1	9/2011
2020/0071851	A1	3/2020	Glenn, Jr. et al.	EP	2363517	A1	9/2011
2020/0093710	A1	3/2020	Hamersky et al.	EP	2395142	A1	12/2011
2020/0214946	A1	7/2020	Chan et al.	FR	2871685	A1	12/2005
2020/0261326	A1	8/2020	Sivik et al.	FR	2886845	A1	12/2006
2020/0275818	A1	9/2020	Dreher et al.	GB	2107579	A	5/1983
2020/0308360	A1	10/2020	Mao et al.	GB	2235204	A	2/1991
2020/0405587	A1	12/2020	Song	GB	2355008	A	4/2001
2021/0000733	A1	1/2021	Hilvert	GB	2375542	A	11/2002
2021/0094744	A1	4/2021	Benson et al.	GB	2378407	A	2/2003
2021/0107263	A1	4/2021	Bartolucci et al.	GB	2449418	A	11/2008
2021/0121373	A1	4/2021	Tan et al.	HU	221299	B1	9/2002
2021/0128417	A1	5/2021	Sivik et al.	IN	20150354411		5/2017
2021/0137798	A1	5/2021	Sivik et al.	JP	S4912158	A	2/1974
2021/0147763	A1	5/2021	Tan et al.	JP	S8021608		2/1983
2021/0189602	A1	6/2021	Glenn, Jr. et al.	JP	S58216109	A	12/1983
2021/0261885	A1	8/2021	Tibbs et al.	JP	S59163458	A	9/1984
2021/0322290	A1	10/2021	Lynch et al.	JP	S6272609	A	4/1987
2021/0401677	A1	12/2021	Song	JP	S6272610	A	4/1987
2022/0054365	A1	2/2022	Xu et al.	JP	S6281432	A	4/1987
2022/0257476	A1	8/2022	Hamersky et al.	JP	S6281462	A	4/1987
2022/0323309	A1	10/2022	Pratt et al.	JP	62156348		7/1987
2023/0190588	A1	6/2023	Song	JP	S6346251	A	2/1988
				JP	S63156715	A	6/1988
				JP	H01172319	A	7/1989
				JP	H01229805	A	9/1989
				JP	H01313418	A	12/1989
CA	2524099	A1	4/2006	JP	H0243268	A	2/1990
CA	2695068	A1	9/2010	JP	H0275650	A	3/1990
CA	166297		5/2018	JP	H02280771	A	11/1990
CA	169627	S	5/2018	JP	3040879	A	2/1991
CN	1138091		12/1996	JP	3101618	A	4/1991
CN	1219388		6/1999	JP	H05344873	A	12/1993
CN	1268558		10/2000	JP	H0617083	A	1/1994
CN	1357613	A	7/2002	JP	H06116568	A	4/1994
CN	1454231	A	11/2003	JP	0753349		2/1995
CN	1530431	A	9/2004	JP	H0789852	A	4/1995
CN	1583991	A	2/2005	JP	H07173724	A	7/1995
CN	1726074	A	1/2006	JP	H08325133	A	12/1996
CN	3648760		5/2007	JP	H09216809	A	8/1997
CN	101161877	A	4/2008	JP	H09216909	A	8/1997
CN	101280467	A	10/2008	JP	09279457		10/1997
CN	101424009	A	5/2009	JP	10008364	A	1/1998
CN	101538745	A	9/2009	JP	H101824	A	1/1998
CN	301666535		9/2011	JP	10158700	A	6/1998
CN	103735428	A	4/2014	JP	H10251371	A	9/1998
CN	304115833		4/2017	JP	H10251952	A	9/1998
CN	106726634	A	5/2017	JP	H10512929	A	12/1998
CN	106728634	A	5/2017	JP	H11505569	A	5/1999
CN	106916659	A	7/2017	JP	H11513053	A	11/1999
CN	304537587		3/2018	JP	2000053998	A	2/2000
DE	19607851	A1	9/1997	JP	2000169896	A	6/2000
DE	10331767	A1	2/2005	JP	2000212828	A	8/2000
DE	102007011606	A1	9/2008	JP	2000229841	A	8/2000
EP	0392608	A2	10/1990	JP	2001302868	A	10/2001
EP	609808	A1	8/1994	JP	2001519376	A	10/2001
EP	0858828	A1	8/1998				

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2002201531	A	7/2002
JP	2002226895	A	8/2002
JP	2003073700	A	3/2003
JP	2003082397	A	3/2003
JP	2003532554	A	11/2003
JP	2004256799	A	9/2004
JP	2004533551	A	11/2004
JP	2004345983	A	12/2004
JP	2005509734	A	4/2005
JP	2005171063	A	6/2005
JP	2005534716	A	11/2005
JP	2006002337	A	1/2006
JP	2006056835	A	3/2006
JP	2006511732	A	4/2006
JP	3828217	B2	7/2006
JP	2006249029	A	9/2006
JP	2007001889	A	1/2007
JP	2007091954	A	4/2007
JP	2007197365	A	8/2007
JP	2007197540	A	8/2007
JP	2007528748	A	10/2007
JP	2007533763	A	11/2007
JP	4128580	B2	5/2008
JP	2008156807	A	7/2008
JP	2008525436	A	7/2008
JP	2009079329	A	4/2009
JP	2009533569	A	9/2009
JP	4510221	B2	5/2010
JP	2010100966	A	5/2010
JP	2010126856	A	6/2010
JP	2013099467	A	5/2013
JP	5344873	B2	8/2013
JP	5821609	B2	10/2015
JP	6272610	B2	1/2018
KR	20020003442	A	1/2002
KR	20040094520	A	11/2004
RU	19735	U1	10/2001
RU	2192451	C2	11/2002
RU	2300196	C2	6/2007
RU	2347557	C2	2/2009
TW	232027	B	10/1994
WO	8301943	A1	6/1983
WO	1992006603	A1	4/1992
WO	1994002377	A1	2/1994
WO	9404656	A2	3/1994
WO	9514495	A1	6/1995
WO	9523888	A1	9/1995
WO	9918182	A1	4/1999
WO	9951715	A1	10/1999
WO	9957155	A1	11/1999
WO	2000013680	A2	3/2000
WO	0042992	A2	7/2000
WO	0107194	A1	2/2001
WO	0110421	A1	2/2001
WO	0119948	A1	3/2001
WO	0125322	A1	4/2001
WO	0125393	A1	4/2001
WO	200125322	A1	4/2001
WO	2001024770	A1	4/2001
WO	200154667	A1	8/2001
WO	2001054667	A1	8/2001
WO	0183657	A2	11/2001
WO	0238722	A2	5/2002
WO	03044153	A1	5/2003
WO	03060007	A1	7/2003
WO	2004009335	A1	1/2004
WO	2004032859	A2	4/2004
WO	2004041991	A1	5/2004
WO	2004081162	A1	9/2004
WO	2005003423	A1	1/2005
WO	2005068604	A1	7/2005
WO	2005070374	A1	8/2005
WO	2005075547	A1	8/2005
WO	2006106514	A2	10/2006
WO	2006130647	A1	12/2006

WO	2007022229	A1	2/2007
WO	2007033598	A1	3/2007
WO	2007089259	A1	8/2007
WO	2007093558	A1	8/2007
WO	2007093619	A1	8/2007
WO	2007102119	A1	9/2007
WO	2008015641	A2	2/2008
WO	2008049242	A1	5/2008
WO	2008104954	A2	9/2008
WO	2008149248	A2	12/2008
WO	2009019571	A2	2/2009
WO	2009022761	A1	2/2009
WO	2007014221	A3	4/2009
WO	2009095891	A1	8/2009
WO	2009103576	A1	8/2009
WO	2009121900	A1	10/2009
WO	2010006708	A1	1/2010
WO	2010015709	A2	2/2010
WO	2010077627	A2	7/2010
WO	2010085569	A1	7/2010
WO	2011153023	A1	12/2011
WO	2012003349	A2	1/2012
WO	2012120199	A1	9/2012
WO	2014158472	A1	10/2014
WO	2015034975	A1	3/2015
WO	2015153185	A1	10/2015
WO	100932		4/2018
WO	100938		4/2018
WO	101063		5/2018
WO	101100		5/2018
WO	101101		5/2018
WO	2018109200	A1	6/2018
WO	2018140675	A1	8/2018
WO	2019001940	A1	1/2019
WO	2020192519	A1	10/2020

OTHER PUBLICATIONS

Briscoe et al. "The effects of hydrogen bonding upon the viscosity of aqueous poly(vinyl alcohol) solutions," from Polymer, 41 (2000), pp. 3851-3860.

Color Keeper [online], [site visited Oct. 18, 2021]. Available from internet, URL: https://shopgemz.com/products/color-keeper?variant=13094595002434&utm_source=google&utm_medium=cpc&utm_campaign=Shopping&gclid=Cj0KCQjw5JSLBhCxARIsAHgO2SdAT7LTehpyxM1qTGtnFETDa1Nuo9_cQSOpPwCmsmmdGA1YOUSekQEaAh0iEALw_wcB (Year: 2021). Dahiya, A., Karnath, M.G., Hegde, R.R. Melt Blown Technology, Updated Apr. 2004, downloaded from the site <http://www.engr.utk.edu/mse/Textiles/Melt%20Blown%20Technology.htm> on Dec. 12, 2015.

Definition of Derivative by Merriam Webster Online Dictionary, Year, 2021, 1 Page.

Design of "Detergent tablets" (Design Registration No. 000634142-0003), (No. of Publicly known information: HH18274488), Registered Community Designs Bulletin, published by EUIPO on Jan. 9, 2007, 4 pgs.

Design of "Detergent tablets" (Design Registration No. 000634142-0004), (No. of Publicly known information: HH18274489), Registered Community Designs Bulletin, published by EUIPO on Jan. 9, 2007, 4 pgs.

Dow, UCARE™ Polymer LR-400, Technical Data Sheet, Downloaded in Mar. 2022, 4 pages.

Encyclopedia of Polymer Science and Engineering, vol. 15, 2nd ed., pp. 204 308 Silicones, year 1989.

Francis Ignatious, Linghong Sun, Chao-Pin Lee, and John Baldoni. Electrospun Nanofibers in Oral Drug Delivery—Expert Review. Pharmaceutical Research, vol. 27, No. 4, Apr. 2010, pp. 576-588. Published online Feb. 9, 2010.

Gemz Hair Care. Perfect Pairs. Publication date unavailable. Visited Jan. 26, 2022. <https://shopgemz.com/collections/perfect-pairs> (Year: 0).

Guerrini et al. "Thermal and Structural Characterization of Nanofibers of Poly(vinyl alcohol) Produced by Electrospinning", Journal of Applied Polymer Science, vol. 112, Feb. 9, 2009, pp. 1680-1687.

(56)

References Cited**OTHER PUBLICATIONS**

Hildebrand, T., et al. "Quantification of bone microarchitecture with the structure mode index", *Computer Methods in Biomechanics and Biomedical Engineering*, vol. 1, Jan. 14, 1997, pp. 15-23.

Hiroshi Yagi & 4 Others, Research Study of a Friction Protector for Preventing a Tow Line From Breaking, Working Papers for Fiscal 2006 | Japan | Japan Coast Guard IDec. 2007, pp. 1-8.

How Gemz work?, Gemz Hair Care, published on Oct. 1, 2018, retrieved on Apr. 27, 2021, retrieved from the Internet URL: <https://www.youtube.com/watch?v=ts1waYk43g4>, 3 pgs.

Karen Duis et al., "Environmental fate and effects of water-soluble synthetic organic polymers used in cosmetic products", *Environmental Sciences Europe*, vol. 33, Article No. 21, Feb. 16, 2021, 78 pages.

Latorre Carmen, Nanotribological Effects of Hair Careproducts and Environment On Human Hair Using Atomic Force microscopy, *Journal of Vacuum Science and Technology: Part A*, U.S.A, AVS/AIP, Jun. 28, 2005, V2 3 N 4, p. 1034-1045.

Makadia, et al., "Poly Lactic-co-Glycolic Acid (PLGA) as Biodegradable Controlled Drug Delivery Carrier", *Polymers*, 3, pp. 1377-1397 (2011).

Menard et al., "Gnotobiotic Mouse Immune Response Induced by *Bifidobacterium* sp. Strains Isolated from Infants", *Applied and Environmental Microbiology*, vol. 74, Issue 3, Feb. 1, 2008, pp. 660-666.

Michelle Villett, Why You Need a Sulfate-Free Shampoo, The Skincare Edit, updated date: Jan. 25, 2019, Original publication date: Feb. 22, 2016 (Year: 2016), 7 pages. Mar. 23, 2021.

Minifibers, Inc., accessed on line at <http://www.minifibers.com/documents/Choosing-the-Proper-Short-Cut-Fiber.pdf> Oct. 3, 2016.

Ni Genshan et al. "Drug Classification and Pharmacology Summary", PLA Press, published on Apr. 30, 1988, pp. 3.

Okasaka et al., "Evaluation Of Anionic Surfactants Effects On The Skin Barrier Function Based On Skin Permeability", *Pharmaceutical Development and Technology*, vol. 24, No. 1, Jan. 23, 2018, pp. 99-104.

Overview of pharmaceutical excipients used in tablets and capsules in Drug Topics, dated Oct. 24, 2008. Downloaded Sep. 20, 2016 from <http://drugtopics.modernmedicine.com/drugtopics/news/modernmedicine/modernmedicineweb/overviewpharmaceuticalexcipientsusedtablets>.

Paper Pieces Hexagons, announced 2018 [online], [site visited Oct. 14, 2021]. Available from internet, URL: <https://www.amazon.com/Paper-Pieces-HEX100B-Hexagons-1200pc/dp/B07DVYV2HN/> (Year: 2018).

Product Review: Gemz Solid Shampoo, Travel As Much, published on Mar. 19, 2019, retrieved on Apr. 27, 2021, retrieved from the Internet URL: <https://travelasmuch.com/gemz-solid-shampoo-review/>, 14 pgs.

Retrieved from: <https://www.craftcuts.com/hexagon-craft-shape.html> Hexagon wood cutouts, www.craftcuts.com, 1 page, reviewed as early as May 2018 (Year: 2018), 16 pgs.

Rounded hexagon shape, announced 2016 [online], [site visited Oct. 20, 2021]. Available from internet, URL: <https://www.vexels.com/png-svg/preview/139199/rounded-hexagon-shape> (Year: 2016).

Sahin et al. "A Study on Physical and Chemical Properties of Cellulose Paper Immersed in Various Solvent Mixtures" *International Journal Of Molecular Sciences*, Jan. 2008; 9(1): 78-88.

Smith, et al., "Nanofibrous Scaffolds and Their Biological Effects", *Nanotechnologies for the Life Sciences*, vol. 9, pp. 188-215 (2006).

Vaughan, C.D. "Solubility, Effects in Product, Package, Penetration and Preservation", *Cosmetics and Toiletries*, vol. 103, Oct. 1988, 24 pgs.

Vesterby, A.: "Star Volume in Bone Research: A Histomorphometric Analysis Of Trabecular Bone Structure Using Vertical Sections", *Anal Rec*: Feb. 1993, 232(2), pp. 325-334.

W S Ratnayake and D S Jackson. Gelatinization and solubility of corn starch during heating in excess water. Faculty Publications in

Food Science and Technology, Jan. 1, 2006. Also published in *Journal of Agricultural and Food Chemistry* 54:1 O(2006), pp. 3712-3716.

Wang, et al., "A Novel Controlled Release Drug Delivery System for Multiple Drugs Based on Electrospun Nanofibers Containing Nanoparticles", *Journal of Pharmaceutical Sciences*, vol. 99, No. 12 (Dec. 2010).

PCT Search Report and Written Opinion for PCT/US2022/075613 dated Feb. 3, 2023, 12 pages.

Design Gazette (Application No. 3019850005996), "Design of Soaps", Korean Intellectual Property Office (KIPO), published on Jun. 9, 1986, 3 pgs.

Final Office Action; U.S. Appl. No. 13/173,639 dated Oct. 10, 2014.

Final Office Action; U.S. Appl. No. 13/173,639 dated Nov. 14, 2012.

Final Office Action; U.S. Appl. No. 13/173,639 dated Nov. 19, 2015.

Final Office Action; U.S. Appl. No. 13/229,825 dated Feb. 14, 2022.

Final Office Action; U.S. Appl. No. 13/229,825 dated Feb. 19, 2020.

Final Office Action; U.S. Appl. No. 13/229,825 dated Feb. 21, 2023.

Final Office Action; U.S. Appl. No. 13/229,825 dated Mar. 6, 2015.

Final Office Action; U.S. Appl. No. 13/229,825 dated Mar. 7, 2013.

Final Office Action; U.S. Appl. No. 13/229,825 dated Jun. 5, 2019.

Final Office Action; U.S. Appl. No. 13/229,825 dated Oct. 13, 2016.

Final Office Action; U.S. Appl. No. 13/229,825 dated Dec. 11, 2018.

Final Office Action; U.S. Appl. No. 13/229,825 dated Dec. 18, 2020.

Final Office Action; U.S. Appl. No. 14/334,862 dated Sep. 22, 2016.

Final Office Action; U.S. Appl. No. 15/374,486 dated Apr. 19, 2019.

Final Office Action; U.S. Appl. No. 15/979,961 dated Jan. 29, 2020.

L'Alimentation article, Dizolve Group Corporation, Nov. 2010, p. 28.

Non-Final Office Action; U.S. Appl. No. 13/173,639 dated Mar. 12, 2015.

Non-Final Office Action; U.S. Appl. No. 13/173,639 dated May 23, 2012.

Non-Final Office Action; U.S. Appl. No. 13/173,639 dated Oct. 7, 2013.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Apr. 28, 2016.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Jul. 10, 2018.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Aug. 6, 2014.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Aug. 28, 2012.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Sep. 3, 2020.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Sep. 7, 2022.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Sep. 17, 2021.

Non-Final Office Action; U.S. Appl. No. 13/229,825 dated Sep. 30, 2019.

Non-Final Office Action; U.S. Appl. No. 14/334,862 dated Sep. 3, 2015.

Non-Final Office Action; U.S. Appl. No. 15/374,486 dated Aug. 8, 2019.

Non-Final Office Action; U.S. Appl. No. 15/374,486 dated Oct. 5, 2018.

Non-Final Office Action; U.S. Appl. No. 15/978,503 dated Apr. 22, 2021.

Non-Final Office Action; U.S. Appl. No. 15/978,503 dated Jun. 15, 2020.

Non-Final Office Action; U.S. Appl. No. 15/978,503 dated Dec. 23, 2020.

Non-Final Office Action; U.S. Appl. No. 15/979,961 dated Jul. 17, 2020.

Non-Final Office Action; U.S. Appl. No. 15/979,961 dated Aug. 2, 2019.

Non-Final Office Action; U.S. Appl. No. 16/674,837 dated Mar. 14, 2023.

Non-Final Office Action; U.S. Appl. No. 16/674,837 dated Mar. 24, 2023.

Non-Final Office Action; U.S. Appl. No. 17/184,712 dated Jun. 15, 2023.

(56)

References Cited

OTHER PUBLICATIONS

Non-Final Office Action; U.S. Appl. No. 17/730,390 dated Apr. 27, 2022.
 Notice of Allowance; U.S. Appl. No. 15/170,125 dated Oct. 3, 2016.
 Notice of Allowance; U.S. Appl. No. 15/978,503 dated Aug. 9, 2021.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated Feb. 4, 2022.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated Apr. 18, 2022.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated May 3, 2021.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated Aug. 19, 2021.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated Sep. 15, 2021.
 Notice of Allowance; U.S. Appl. No. 15/979,961 dated Oct. 14, 2021.
 Rowe et al., "Polyvinyl Alcohol", Handbook of Pharmaceutical Excipients Sixth Edition, Pharmaceutical Press, published in 2009, 5 pages.
 Wermuth, "Similarity in Drugs: Reflections on Analogue Design", Drug Discovery, Drug Discovery Today, vol. 11 No. 7/8, Apr. 2006; pp. 348-354.

Yasuhiro Hiramatsu et al. "Bifidobacterium Components Have Immunomodulatory Characteristics Dependent on the Method of Preparation" Cytotechnology, Kluwer Academic Publishers, Do, vol. 55, Issue No. 2-3, Nov. 1, 2007, p. 79-87.
 Pattama Taepaiboon, et al., "Effect of Cross-linking on Properties and Release Characteristics of Sodium Salicylate-loaded Electrospun Poly (Vinyl Alcohol) Fibre Mats", Nanotechnology, vol. 18, No. 17, Apr. 2, 2007.
 Wikipedia "Polyvinyl alcohol," URL Link—https://en.wikipedia.org/wiki/Polyvinyl_alcohol, dated May 25, 2017, 5 pgs.
 "Prill", wikipedia, <https://en.wikipedia.org/wiki/Prill>, No Known date, 1 Page.
 da Rosa Zavareze, E. et al., Impact of heat-moisture treatment and annealing in starches: A review, Carbohydrate polymers, 83(2), 2011, pp. 317-328.
 Database GNPD Mintel, "Dishes & Hands Camp Soap Sheets", XP093208089, Database accession No. 1636025, dated Oct. 6, 2011, 02 Pages.
 Database GNPD Mintel, "Soap Leaves", XP093208087, Database accession No. 5336785, dated Dec. 21, 2017, 02 Pages.
 Non-Final Office Action; U.S. Appl. No. 16/674,837 dated Dec. 4, 2024.
 Zhang et al. "Study on Morphology of Electrospun Poly(vinyl alcohol) Mats," European Polymer Journal 41 (2005), pp. 423-432.

* cited by examiner

1

DISSOLVABLE SOLID STRUCTURE COMPRISING FIRST AND SECOND POLYMERIC STRUCTURANTS

FIELD OF THE INVENTION

The present invention relates to a dissolvable solid structure, wherein the dissolvable solid structure is formed by a homogeneous mixture comprising, by weight of the structure: from about 1% to about 10% of a first polymeric structurant having a molecular weight of from about 1,000,000 g/mol to about 4,000,000 g/mol; from about 10% to about 20% of a second polymeric structurant having a molecular weight of from about 50,000 g/mol to about 500,000 g/mol; from about 10 wt % to about 85 wt % of one or more high melting point fatty material having a carbon chain length C12-C22 or mixtures thereof, wherein the melting point is above 25° C.; and from about 1 wt % to about 60 wt % of a cationic surfactant. The dissolvable solid structures of present invention provide an adequate strength during manufacturing, while not deteriorating usage feel when used and/or applied by consumers.

BACKGROUND OF THE INVENTION

Many personal care and other consumer products in the market today are sold in liquid form. While widely used, liquid products often have tradeoffs in terms of packaging, storage, transportation, and convenience of use. Liquid consumer products typically are sold in bottles which add cost as well as packaging waste, much of which ends up in land-fills.

Hair Care products in the form of a dissolvable solid structures present an attractive form to consumers. Market executions of dissolvable solid structures may include, dissolvable films, compressed powders in a solid, fibrous structures, porous foams, soluble deformable solids, powders, etc.

For example, US Patent Application Publication No. 2018/0333339 A discloses a dissolvable solid structure which can be in the form of a fibrous structure comprising: (a) a polymeric structurant having a weight average molecular weight of from about 10,000 g/mol to about 6,000,000 g/mol; (b) a high melting point fatty compound such as a fatty amphiphile, and (c) a cationic surfactant.

However, a need still exists for such dissolvable solid structures, especially for those containing a high melting point fatty compound and a cationic surfactant, which have an adequate strength during manufacturing, while not deteriorating usage feel when used and/or applied by consumers.

SUMMARY OF THE INVENTION

The present invention is directed to a dissolvable solid structure, wherein the dissolvable solid structure is formed by a homogeneous mixture comprising, by weight of the structure:

- from about 1% to about 10% of a first polymeric structurant having a molecular weight of from about 1,000,000 g/mol to about 4,000,000 g/mol;
- from about 10% to about 20% of a second polymeric structurant having a molecular weight of from about 50,000 g/mol to about 500,000 g/mol;
- from about 10 wt % to about 85 wt % of one or more high melting point fatty material having a carbon chain length C12-C22 or mixtures thereof, wherein the melt-

2

ing point is above 25° C.; and from about 1 wt % to about 60 wt % of a cationic surfactant.

It has now been surprisingly found by the present inventors that, by the use of the first and second polymeric structurants having specific molecular weights, the dissolvable solid structures of present invention provide an adequate strength during manufacturing, while not deteriorating usage feel when used and/or applied by consumers.

DETAILED DESCRIPTION OF THE INVENTION

Definitions

As used herein, The Dissolvable Solid Structure may be referred to herein as “the Dissolvable Solid Structure”, “the Structure”, or “the Dissolvable Structure”.

As used herein, “dissolvable” means that the Dissolvable Solid Structure is completely soluble in water or it provides a uniform dispersion upon mixing in water according to the hand dissolution test. The Dissolvable Solid Structure has a hand dissolution value of from about 1 to about 30 strokes, alternatively from about 2 to about 25 strokes, alternatively from about 3 to about 20 strokes, and alternatively from about 4 to about 15 strokes, as measured by the Hand Dissolution Method.

As used herein, “flexible” means a Dissolvable Solid Structure meets the distance to maximum force values discussed herein.

“Fibrous structure” as used herein means a structure that comprises one or more fibrous elements and optionally, one or more particles. The fibrous structure as described herein can mean an association of fibrous elements and optionally, particles that together form a structure, such as a unitary structure, capable of performing a function.

The fibrous structure may have a multi-ply fibrous structure which comprises two or more different fibrous structure plies. Each ply may be the same as or different from other ply.

A layer comprising fibrous elements may sometimes be referred to as a ply. A ply may be a fibrous structure which may be homogeneous or layered as described herein.

The single-ply fibrous structure or a multi-ply fibrous structure comprising one or more fibrous structure plies as described herein may exhibit a basis weight of less than 5000 g/m² as measured according to the Basis Weight Test Method described herein. For example, the single- or multi-ply fibrous structure may exhibit a basis weight of greater than 10 g/m² to about 5000 g/m² and/or greater than 10 g/m² to about 3000 g/m² and/or greater than 10 g/m² to about 2000 g/m² and/or greater than 10 g/m² to about 1000 g/m² and/or greater than 20 g/m² to about 800 g/m² and/or greater than 30 g/m² to about 600 g/m² and/or greater than 50 g/m² to about 500 g/m² and/or greater than 300 g/m² to about 3000 g/m² and/or greater than 500 g/m² to about 2000 g/m² as measured according to the Basis Weight Test Method.

In one example, the fibrous structure can be a “unitary fibrous structure.”

“Unitary fibrous structure” as used herein is an arrangement comprising a plurality of two or more and/or three or more fibrous elements that are inter-entangled or otherwise associated with one another to form a fibrous structure and/or fibrous structure plies. A unitary fibrous structure may be one or more plies within a multi-ply fibrous structure. In one example, a unitary fibrous structure may comprise three or more different fibrous elements. In another

example, a unitary fibrous structure may comprise two or more different fibrous elements.

“Article” as used herein refers to a consumer use unit, a consumer unit dose unit, a consumer use saleable unit, a single dose unit, or other use form comprising a unitary fibrous dissolvable solid structure and/or comprising one or more fibrous structures.

“Fibrous element” as used herein means an elongated particulate having a length greatly exceeding its average diameter, i.e., a length to average diameter ratio of at least about 10. A fibrous element may be a filament or a fiber. In one example, the fibrous element is a single fibrous element rather than a yarn comprising a plurality of fibrous elements.

The fibrous elements may be spun from a filament-forming composition also referred to as fibrous element-forming compositions via suitable spinning process operations, such as meltblowing, spunbonding, electro-spinning, and/or rotary spinning.

The fibrous elements may be monocomponent (single, unitary solid piece rather than two different parts, like a core/sheath bicomponent) and/or multicomponent. For example, the fibrous elements may comprise bicomponent fibers and/or filaments. The bicomponent fibers and/or filaments may be in any form, such as side-by-side, core and sheath, islands-in-the-sea and the like.

“Filament” as used herein means an elongated particulate as described above that exhibits a length of greater than or equal to 5.08 cm (2 in.) and/or greater than or equal to 7.62 cm (3 in.) and/or greater than or equal to 10.16 cm (4 in.) and/or greater than or equal to 15.24 cm (6 in.). Filaments are typically considered continuous or substantially continuous in nature. Filaments are relatively longer than fibers. Non-limiting examples of filaments include meltblown and/or spunbond filaments.

“Fiber” as used herein means an elongated particulate as described above that exhibits a length of less than 5.08 cm (2 in.) and/or less than 3.81 cm (1.5 in.) and/or less than 2.54 cm (1 in.). Fibers are typically considered discontinuous in nature. Non-limiting examples of fibers include staple fibers produced by spinning a filament or filament tow and then cutting the filament or filament tow into segments of less than 5.08 cm (2 in.) thus producing fibers. Therefore, references to filaments herein also include fibers made from such filaments unless otherwise noted. Fibers are typically considered discontinuous in nature relative to filaments, which are considered continuous in nature.

“Filament-forming composition” and/or “fibrous element-forming composition” as used herein means a composition that is suitable for making a fibrous element of the present invention such as by meltblowing and/or spunbonding. The filament-forming composition comprises one or more filament-forming materials that exhibit properties that make them suitable for spinning into a fibrous element. In one example, the filament-forming material comprises a polymer. In addition to one or more filament-forming materials, the filament-forming composition may comprise one or more additives, for example one or more active agents. In addition, the filament-forming composition may comprise one or more polar solvents, such as water, into which one or more, for example all, of the filament-forming materials and/or one or more, for example all, of the active agents are dissolved and/or dispersed prior to spinning a fibrous element, such as a filament from the filament-forming composition.

As used herein, “porous” means that the Dissolvable Solid Structure has spaces, voids or interstices, (generally referred to herein as “pores”) provided by the microscopic

complex three-dimensional configuration, that provide channels, paths or passages through which a liquid can flow.

As used herein, “porosity” and “percent porosity” are used interchangeably and each refers to a measure of void volume of the Dissolvable Solid Structure and is calculated as

$$\frac{[1 - ((\text{basis weight of Dissolvable Solid Structure}) / (\text{thickness of Dissolvable Solid Structure} \times \text{density of the bulk, dried material}))] \times 100\%}{100}$$

with the units adjusted so they cancel and multiplied by 100% to provide percent porosity.

The Dissolvable Solid Structure may be referred to herein as “the Dissolvable Solid Structure” or “the Dissolvable Structure”.

The term “molecular weight” or “Molecular weight” refers to the weight average molecular weight unless otherwise stated. Molecular weight is measured using industry standard method, gel permeation chromatography (“GPC”).

As used herein, the articles including “a” and “an” when used in a claim, are understood to mean one or more of what is claimed or described.

As used herein, the terms “include,” “includes,” and “including,” are meant to be non-limiting.

The methods disclosed in the Test Methods Section of the present application should be used to determine the respective values of the parameters of Applicants’ inventions, including those discussed in the Dissolvable Structures—Physical Characteristics section below.

All percentages and ratios are calculated by weight unless otherwise indicated. All percentages and ratios are calculated based on the total composition unless otherwise indicated.

It should be understood that every maximum numerical limitation given throughout this specification includes every lower numerical limitation, as if such lower numerical limitations were expressly written herein. Every minimum numerical limitation given throughout this specification will include every higher numerical limitation, as if such higher numerical limitations were expressly written herein. Every numerical range given throughout this specification will include every narrower numerical range that falls within such broader numerical range, as if such narrower numerical ranges were all expressly written herein.

Dissolvable Solid Structure (Dissolvable Solid Articles)

The dissolvable solid structure of the present invention is formed by a homogeneous mixture, comprises, by weight of the structure:

- from about 1% to about 10% of a first polymeric structurant having a molecular weight of from about 1,000,000 g/mol to about 4,000,000 g/mol;
- from about 10% to about 20% of a second polymeric structurant having a molecular weight of from about 50,000 g/mol to about 500,000 g/mol;
- from about 10 wt % to about 85 wt % of one or more high melting point fatty material having a carbon chain length C12-C22 or mixtures thereof, wherein the melting point is above 25° C.; and
- from about 1 wt % to about 60 wt % of a cationic surfactant.

The dissolvable solid structure can be a fibrous structure formed by a plurality of fibrous elements wherein the fibrous elements are formed by the above homogeneous mixture.

The dissolvable solid structure of the present invention can be a personal care product, for example a hair care

5

product, alternatively rinse-off hair care product, even alternatively rinse-off hair care product containing non-sulfate surfactant.

The dissolvable solid structure may contain particulates. The dissolvable solid structure may have an aesthetic feature selected from the group consisting of printing, embossing, texture, colored and mixtures thereof.

First and Second Polymeric Structurants

The structure comprises:

from about 1% to about 10% of a first polymeric structurant having a molecular weight of from about 1,000,000 g/mol to about 4,000,000 g/mol, alternatively from about 1,500,000 g/mol to about 3,500,000 g/mol; and from about 10% to about 20% of a second polymeric structurant having a molecular weight of from about 50,000 g/mol to about 500,000 g/mol, alternatively from about 65,000 g/mol to about 395,000 g/mol.

In the present invention, it is preferred the weight ratio between the first and second polyvinylpyrrolidones is from about 1:1 to about 1:100, alternatively from about 1:1 to about 1:50, alternatively from about 1:1 to about 1:10.

In the present invention, it is preferred that the weight ratio between the first and second polymeric structurant is in a range such that the combined average molecular weight of the first and second polymeric structurants is from about 300,000 g/mol to about 3,000,000 g/mol, alternatively from about 350,000 g/mol to about 2,000,000 g/mol, alternatively from about 400,000 g/mol to about 1,000,000 g/mol, and alternatively from about 500,000 g/mol to about 1,000,000 g/mol.

In the present invention, it is preferred that the amounts of the first and second polymeric structurants, the molecular weights of the first and second polymeric structurants, and the weight ratio between the first and second polymeric structurants are selected such that the mixture in melt at 85° C. has a viscosity of from about 0.3 Pa-s to about 10 Pa-s, alternatively from about 3 Pa-s to about 8 Pa-s.

The first and second polymeric structurants are water-soluble polymers. As used in the present invention, the term “water-soluble polymer” is broad enough to include both water-soluble and water-dispersible polymers, and is defined as a polymer with a solubility in water, measured at 25° C., of at least about 0.1 gram/liter (g/L). In some embodiments, the polymers have a solubility in water, measured at 25° C., of from about 0.1 gram/liter (g/L), to about 500 grams/liter (g/L). (This indicates production of a macroscopically isotropic or transparent, colored or colorless solution). The polymers for making these solids may be of synthetic or natural origin and may be modified by means of chemical reactions. They may or may not be film-forming. These polymers should be physiologically acceptable, i.e., they should be compatible with the skin, mucous membranes, the hair and the scalp. The terms “water-soluble polymer” and “polymer structurant” are used interchangeably herein. Furthermore, whenever the singular term “polymer” is stated, it should be understood that the term is broad enough to include one polymer or a mixture of more than one polymer. For instance, if a mixture of polymers is used, the polymer solubility as referred to herein would refer to the solubility of the mixture of polymers, rather than to the solubility of each polymer individually.

Non-limiting examples of such water-soluble polymers can include polyacrylic acid and its copolymers, polyvinylpyrrolidone and its copolymers, polyacrylamide and its copolymers, polyvinylmethyl ether, polyethyleneimine, polymethacrylic acid, other water soluble acrylic polymers


6

such as polyN-isopropyl acrylamide, polyN-N-dimethylacrylamide, poly (2-ethyl-2-oxazoline), polyoxazoline, polyvinylloxazolidone, polyvinyl caprolactam, polystyrene sulfonate, polyvinyl formamide, polyvinyl amine, alkylated polyvinyl pyrrolidone, poly vinyl caprolactam, polyvinyl valerolactam, polyvinyl imidazole, polyacrylic acid, polyacrylamide, polymethacrylamide, polydimethacrylamide, polyalkylaminomethacrylate, and polyalkylaminomethacrylamide, and combinations thereof. For purposes of clarity, the use of the term “copolymer” is intended to convey that the vinyl pyrrolidone monomer can be copolymerized with other non-limiting monomers such as vinyl acetate, alkylated vinyl pyrrolidone, vinyl caprolactam, vinyl valerolactam, vinyl imidazole, acrylic acid, methacrylate, acrylamide, vinyl oxazoline, 2-ethyl-2oxazoline, methacrylamide, dimethacrylamide, alkylaminomethacrylate, and alkylaminomethacrylamide monomers.

Among a variety of the water soluble polymers, the first and second polymeric structurants can be selected from the group consisting of: polyvinylpyrrolidone and its copolymers, and mixtures thereof. alternatively, the first and second polymeric structurants are polyvinylpyrrolidone.

As used herein, “vinyl pyrrolidone copolymer” (and “copolymer” when used in reference thereto) refers to a polymer of the following structure (I):

(I)



In structure (I), n is an integer such that the polymeric structurant has the degree of polymerization such that it possesses characteristics described herein. For purposes of clarity, the use of the term “copolymer” is intended to convey that the vinyl pyrrolidone monomer can be copolymerized with other non-limiting monomers such as vinyl acetate, alkylated vinyl pyrrolidone, vinyl caprolactam, vinyl valerolactam, vinyl oxazoline, 2-ethyl-2oxazoline, vinyl imidazole, acrylic acid, methacrylate, acrylamide, methacrylamide, dimethacrylamide, alkylaminomethacrylate, and alkylaminomethacrylamide monomers.

For example, suitable polymers for use are PVP K120 from Ashland having a weight average molecular weight of about 3,470,000 g/mol, PVP K90 from Ashland having a weight average molecular weight of 1,570,000 g/mol, PVP K60 from Jarchem having a weight average molecular weight of 396,000 g/mol, PVP K30 from Ashland having a weight average molecular weight of 66,800 g/mol. Additional suitable polymers include copolymers of polyvinylpyrrolidone, such as Ganex® or PVP/VA (weight average molecular weight of about 50,000 g/mol) copolymers from Ashland Inc., also performed as suitable structurants but a higher level was utilized to be effective due to their lower weight average molecular weight.

Additional Polymeric Structurant

The structure may further contain an additional structurant. Such additional structurant can be the polymers listed above, but those having different MW from FIRST and SECOND

7

Polymer Structurants.

Cationic Surfactant

The structure further comprises a cationic surfactant at a level of from about 1 wt % to about 60 wt %, alternatively from about 10 wt % to about 50 wt %, alternatively from about 20 wt % to about 40 wt % by weight of the structure.

Cationic surfactant useful herein can be one cationic surfactant or a mixture of two or more cationic surfactants. The cationic surfactant can be selected from the group consisting of, but not limited to: a mono-long alkyl quaternized ammonium salt; a combination of a mono-long alkyl quaternized ammonium salt and a di-long alkyl quaternized ammonium salt; a mono-long alkyl amine; a combination of a mono-long alkyl amine and a di-long alkyl quaternized ammonium salt; and a combination of a mono-long alkyl amine and a mono-long alkyl quaternized ammonium salt, a tertiary amine and combinations thereof.

Mono-Long Alkyl Amine

Mono-long alkyl amine useful herein are those having one long alkyl chain of from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively from 18 to 22 alkyl group. Mono-long alkyl amines useful herein also include mono-long alkyl amidoamines. Primary, secondary, and tertiary fatty amines are useful.


Suitable for use in the dissolvable solid structure are tertiary amido amines having an alkyl group of from about 12 to about 22 carbons. Exemplary tertiary amido amines include: stearamidopropyldimethylamine, stearamidopropyldiethylamine, stearamidoethyldiethylamine, stearamidoethyldimethylamine, palmitamidopropyldimethylamine, palmitamidopropyldiethylamine, palmitamidoethyldiethylamine, palmitamidoethyldimethylamine, behenamidopropyldimethylamine, behenamidopropyldiethylamine, behenamidoethyldiethylamine, behenamidoethyldimethylamine, arachidamidopropyldimethylamine, arachidamidopropyldiethylamine, arachidamidoethyldiethylamine, arachidamidoethyldimethylamine, diethylaminoethylstearamide. Useful amines in the present invention are disclosed in U.S. Pat. No. 4,275,055, Nachtigal, et al.

These amines can be used in combination with acids such as 1-glutamic acid, lactic acid, hydrochloric acid, malic acid, succinic acid, acetic acid, fumaric acid, tartaric acid, citric acid, 1-glutamic hydrochloride, maleic acid, and mixtures thereof; alternatively 1-glutamic acid, lactic acid, citric acid, at a molar ratio of the amine to the acid of from about 1:0.3 to about 1:2, alternatively from about 1:0.4 to about 1:1.

Mono-Long Alkyl Quaternized Ammonium Salt

The mono-long alkyl quaternized ammonium salts useful herein are those having one long alkyl chain which has from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively a C18-22 alkyl group. The remaining groups attached to nitrogen are independently selected from an alkyl group of from 1 to about 4 carbon atoms or an alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 4 carbon atoms.

Mono-long alkyl quaternized ammonium salts useful herein are those having the formula (I):



8


wherein one of R^{75} , R^{76} , R^{77} and R^{78} is selected from an alkyl group of from 12 to 30 carbon atoms or an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 30 carbon atoms; the remainder of R^{75} , R^{76} , R^{77} and R^{78} are independently selected from an alkyl group of from 1 to about 4 carbon atoms or an alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 4 carbon atoms; and X^- is a salt-forming anion such as those selected from halogen, (e.g. chloride, bromide), acetate, citrate, lactate, glycolate, phosphate, nitrate, sulfonate, sulfate, alkylsulfate, and alkyl sulfonate radicals. The alkyl groups can contain, in addition to carbon and hydrogen atoms, ether and/or ester linkages, and other groups such as amino groups. The longer chain alkyl groups, e.g., those of about 12 carbons, or higher, can be saturated or unsaturated. One of R^{75} , R^{76} , R^{77} and R^{78} can be selected from an alkyl group of from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively from 18 to 22 carbon atoms, alternatively 22 carbon atoms; the remainder of R^{75} , R^{76} , R^{77} and R^{78} can be independently selected from CH_3 , C_2H_5 , C_2H_4OH , and mixtures thereof; and X can be selected from the group consisting of Cl , Br , CH_3OSO_3 , $C_2H_5OSO_3$, and mixtures thereof.

Nonlimiting examples of such mono-long alkyl quaternized ammonium salt cationic surfactants include: behenyl trimethyl ammonium salt; stearyl trimethyl ammonium salt; cetyl trimethyl ammonium salt; and hydrogenated tallow alkyl trimethyl ammonium salt.

Di-Long Alkyl Quaternized Ammonium Salts

When used, di-long alkyl quaternized ammonium salts can be combined with a mono-long alkyl quaternized ammonium salt and/or mono-long alkyl amine salt, at the weight ratio of from 1:1 to 1:5, alternatively from 1:1.2 to 1:5, alternatively from 1:1.5 to 1:4, in view of stability in rheology and conditioning benefits.

Di-long alkyl quaternized ammonium salts useful herein are those having two long alkyl chains of from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively from 18 to 22 carbon atoms. Such di-long alkyl quaternized ammonium salts useful herein are those having the formula (I):



wherein two of R^{71} , R^{72} , R^{73} and R^{74} are selected from an aliphatic group of from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively from 18 to 22 carbon atoms or an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 30 carbon atoms; the remainder of R^{71} , R^{72} , R^{73} and R^{74} are independently selected from an aliphatic group of from 1 to about 8 carbon atoms, alternatively from 1 to 3 carbon atoms or an aromatic, alkoxy, polyoxyalkylene, alkylamido, hydroxyalkyl, aryl or alkylaryl group having up to about 8 carbon atoms; and X^- is a salt-forming anion selected from the group consisting of halides such as chloride and bromide, C_1 - C_4 alkyl sulfate such as methosulfate and ethosulfate, and mixtures thereof. The aliphatic groups can contain, in addition to carbon and hydrogen atoms, ether linkages, and other groups such as amino groups. The longer

chain aliphatic groups, e.g., those of about 16 carbons, or higher, can be saturated or unsaturated. Two of R⁷¹, R⁷², R⁷³ and R⁷⁴ can be selected from an alkyl group of from 12 to 30 carbon atoms, alternatively from 16 to 24 carbon atoms, alternatively from 18 to 22 carbon atoms; and the remainder of R⁷¹, R⁷², R⁷³ and R⁷⁴ are independently selected from CH₃, C₂H₅, C₂H₄OH, CH₂C₆H₅, and mixtures thereof.

Suitable di-long alkyl cationic surfactants include, for example, dialkyl (14-18) dimethyl ammonium chloride, ditallow alkyl dimethyl ammonium chloride, dihydrogenated tallow alkyl dimethyl ammonium chloride, distearyl dimethyl ammonium chloride, and dicetyl dimethyl ammonium chloride.

High Melting Point Fatty Compound

The structure further comprises a high melting point fatty compound at a level of from about 10 wt % to about 85 wt %, alternatively from 20 wt % to 70 wt %, alternatively from about 50 wt % to about 70 wt %, alternatively from about 10 wt % to about 20 wt % by weight of the structure. The fatty compound can be selected from the group consisting of, but not limited to, fatty amphiphiles, fatty alcohol, fatty acid, fatty amide, fatty ester and combinations thereof.

The high melting point fatty compound useful herein have a melting point of 25° C. or higher, alternatively 40° C. or higher, alternatively 45° C. or higher, alternatively 50° C. or higher, in view of stability of the emulsion especially the gel matrix. Such melting point is up to about 90° C., alternatively up to about 80° C., alternatively up to about 70° C., alternatively up to about 65° C., in view of easier manufacturing and easier emulsification. The high melting point fatty compound can be used as a single compound or as a blend or mixture of at least two high melting point fatty compounds. When used as such blend or mixture, the above melting point means the melting point of the blend or mixture.

The high melting point fatty compound useful herein is selected from the group consisting of fatty alcohols, fatty acids, fatty alcohol derivatives, fatty acid derivatives, fatty amides, and mixtures thereof. It is understood by the artisan that the compounds disclosed in this section of the specification can in some instances fall into more than one classification, e.g., some fatty alcohol derivatives can also be classified as fatty acid derivatives. However, a given classification is not intended to be a limitation on that particular compound, but is done so for convenience of classification and nomenclature. Further, it is understood by the artisan that, depending on the number and position of double bonds, and length and position of the branches, certain compounds having certain required carbon atoms may have a melting point of less than the above. Such compounds of low melting point are not intended to be included in this section. Non-limiting examples of the high melting point compounds are found in International Cosmetic Ingredient Dictionary, Fifth Edition, 1993, and CTFA Cosmetic Ingredient Handbook, Second Edition, 1992.

Among a variety of high melting point fatty compounds, fatty alcohols can be used in the composition described herein. The fatty alcohols useful herein are those having from about 14 to about 30 carbon atoms, alternatively from about 16 to about 22 carbon atoms. These fatty alcohols are saturated and can be straight or branched chain alcohols.

Suitable fatty alcohols include, but are not limited to, cetyl alcohol (having a melting point of about 56° C.), stearyl alcohol (having a melting point of about 58-59° C.), behenyl alcohol (having a melting point of about 71° C.), and mixtures thereof. These compounds are known to have the above melting point. However, they often have lower

melting points when supplied, since such supplied products are often mixtures of fatty alcohols having alkyl chain length distribution in which the main alkyl chain is cetyl, stearyl or behenyl group.

Generally, in the mixture, the weight ratio of cetyl alcohol to stearyl alcohol is from about 1:9 to 9:1, alternatively from about 1:4 to about 4:1, alternatively from about 1:2.3 to about 1.5:1.

When using high level of total cationic surfactant and high melting point fatty compounds, the mixture has the weight ratio of cetyl alcohol to stearyl alcohol of from about 1:1 to about 4:1, alternatively from about 1:1 to about 2:1, alternatively from about 1.2:1 to about 2:1, in view of maintaining acceptable consumer usage. It may also provide more conditioning on damaged part of the hair.

Dispersing Agent

The structure may further comprise a dispersing agent for increasing the wetting, hydration, and/or dispersion of the conditioner materials. The dispersing agent can be included at a level of from about 1 wt % to about 30 wt %, alternatively from about 5 wt % to about 15 wt %, and alternatively from about 5 wt % to about 10 wt % by weight of the second layer. A surfactant from the nonionic class of alkyl glucamides can improve the wetting and hydration when added to the solid conditioner formula. The alkyl glucamide surfactant contains a hydrophobic tail of about 8-18 carbons and a nonionic head group of glucamide. For glucamide, the presence of the amide and hydroxyl groups may provide sufficient polarity that balances the hydrophobic carbon tail in such a way to permit the surfactant's solubility in the conditioner oils and also imparts a rapid dispersion of the conditioner ingredients upon exposure to water. Other similar dispersing agents include, but are not limited to, reverse alkyl glucamides, gluconamides, cocamidopropyl betaines, alkyl glucoside, triethanol amine, cocamide MEAs and mixtures thereof.

Plasticizer

The structure may optionally comprise from about 1 wt % to about 25 wt % plasticizer, in one embodiment from about 3 wt % to about 20 wt % plasticizer, in one embodiment from about 5 wt % to about 15 wt % plasticizer, by weight of the layer.

When present in the Structures, non-limiting examples of suitable plasticizing agents include polyols, copolyols, polycarboxylic acids, polyesters and dimethicone copolyols.

Examples of useful polyols include, but are not limited to, glycerin, diglycerin, propylene glycol, ethylene glycol, butylene glycol, pentylene glycol, cyclohexane dimethanol, hexane diol, polyethylene glycol (200-600), sugar alcohols such as sorbitol, manitol, lactitol, isosorbide, glucamine, N-methylglucamine and other mono- and polyhydric low molecular weight alcohols (e.g., C₂-C₈ alcohols); mono di- and oligo-saccharides such as fructose, glucose, sucrose, maltose, lactose, and high fructose corn syrup solids and ascorbic acid.

Examples of polycarboxylic acids include, but are not limited to citric acid, maleic acid, succinic acid, polyacrylic acid, and polymaleic acid.

Examples of suitable polyesters include, but are not limited to, glycerol triacetate, acetylated-monoglyceride, diethyl phthalate, triethyl citrate, tributyl citrate, acetyl triethyl citrate, acetyl tributyl citrate.

Examples of suitable dimethicone copolyols include, but are not limited to, PEG-12 dimethicone, PEG/PPG-18/18 dimethicone, and PPG-12 dimethicone.

Other suitable plasticizers include, but are not limited to, alkyl and allyl phthalates; naphthalates; lactates (e.g., sodium,

ammonium and potassium salts); sorbeth-30; urea; lactic acid; sodium pyrrolidone carboxylic acid (PCA); sodium hyaluronate or hyaluronic acid; soluble collagen; modified protein; monosodium L-glutamate; alpha & beta hydroxyl acids such as glycolic acid, lactic acid, citric acid, maleic acid and salicylic acid; glyceryl polymethacrylate; polymeric plasticizers such as polyquaterniums; proteins and amino acids such as glutamic acid, aspartic acid, and lysine; hydrogen starch hydrolysates; other low molecular weight esters (e.g., esters of C₂-C₁₀ alcohols and acids); and any other water soluble plasticizer known to one skilled in the art of the foods and plastics industries; and mixtures thereof.

EP 0283165 B1 discloses suitable plasticizers, including glycerol derivatives such as propoxylated glycerol.

Optional Ingredients

The first and/or the second layer may comprise other optional ingredients that are known for use or otherwise useful in compositions, provided that such optional materials are compatible with the selected essential materials described herein, or do not otherwise unduly impair product performance.

Such optional ingredients are most typically those materials approved for use in cosmetics and that are described in reference books such as the CTFA Cosmetic Ingredient Handbook, Second Edition, The Cosmetic, Toiletries, and Fragrance Association, Inc. 1992.

Further non-limiting examples of such optional ingredients include preservatives, perfumes or fragrances, coloring agents or dyes, conditioning agents, hair bleaching agents, thickeners, moisturizers, emollients, pharmaceutical actives, vitamins or nutrients, sunscreens, deodorants, sensates, plant extracts, nutrients, astringents, cosmetic particles, absorbent particles, adhesive particles, hair fixatives, fibers, reactive agents, skin lightening agents, skin tanning agents, anti-dandruff agents, perfumes, exfoliating agents, acids, bases, humectants, enzymes, suspending agents, pH modifiers, hair colorants, hair perming agents, pigment particles, anti-acne agents, anti-microbial agents, sunscreens, tanning agents, exfoliation particles, hair growth or restorer agents, insect repellents, shaving lotion agents, co-solvents or other additional solvents, and similar other materials. Further non-limiting examples of optional ingredients include encapsulated perfumes, such as by β -cyclodextrins, polymer microcapsules, starch encapsulated accords and combinations thereof.

Suitable conditioning agents include high melting point fatty compounds, silicone conditioning agents and cationic conditioning polymers. Suitable materials are discussed in US 2008/0019935, US 2008/0242584 and US 2006/0217288.

Physical Properties of the Dissolvable Solid Structure

For fibrous Structures, the Structure comprises a significant number of dissolvable fibers with an average diameter less than about 150 micron, alternatively less than about 100 micron, alternatively less than about 10 micron, and alternatively less than about 1 micron with a relative standard deviation of less than 100%, alternatively less than 80%, alternatively less than 60%, alternatively less than 50%, such as in the range of 10% to 50%, for example. As set forth herein, the significant number means at least 10% of all the dissolvable fibers, alternatively at least 25% of all the dissolvable fibers, alternatively at least 50% of all the dissolvable fibers, alternatively at least 75% of all the dissolvable fibers. The significant number may be at least 99% of all the dissolvable fibers. Alternatively, from about 50% to about 100% of all the dissolvable fibers may have an average diameter less than about 10 micron. The dissolvable

fibers produced by the method of the present disclosure have a significant number of dissolvable fibers with an average diameter less than about 1 micron, or sub-micron fibers. In an embodiment, Dissolvable Solid Structure may have from about 25% to about 100% of all the dissolvable fibers with an average diameter less than about 1 micron, alternatively from about 35% to about 100% of all the dissolvable fibers with an average diameter less than about 1 micron, alternatively from about 50% to about 100% of all the dissolvable fibers with an average diameter less than about 1 micron, and alternatively from about 75% to about 100% of all the dissolvable fibers with an average diameter less than about 1 micron.

The percent porosity of the dissolvable solid Structure is at least about 25%, alternatively at embodiment at least about 50%, alternatively at least about 60%, alternatively at least about 70% and alternatively at least about 80%. The porosity of the dissolvable solid Structure is not more than about 99%, alternatively not more than about 98%, alternatively not more than about 95%, and alternatively not more than about 90%. Porosity of a Structure is determined according to the procedure set forth in the definition of "porosity" above.

A range of effective sizes of pores can be accommodated. The pore size distribution through the Structure cross-section may be symmetric or asymmetric.

The Structure can be flexible and have a distance to maximum force value of from about 6 mm to about 30 mm. The distance to maximum force value from about 7 mm to about 25 mm, alternatively from about 8 mm to about 20 mm, and alternatively from about 9 mm to about 15 mm.

The Structure can be characterized in one aspect by its Specific Surface Area. The Structure can have a Specific Surface Area of from about 0.03 m²/g to about 0.25 m²/g, alternatively from about 0.035 m²/g to about 0.22 m²/g, alternatively from about 0.04 m²/g to about 0.19 m²/g, and alternatively from about 0.045 m²/g to about 0.16 m²/g.

The Structure can be a flat, flexible Structure in the form of a pad, a strip, or tape and having a thickness of from about 0.5 mm to about 10 mm, alternatively from about 1 mm to about 9 mm, alternatively from about 2 mm to about 8 mm, and alternatively from about 3 mm to about 7 mm as measured by the below methodology. The Structure can be a sheet having a thickness from about 5 mm to about 6.5 mm. Alternatively, two or more sheets are combined to form a Structure with a thickness of about 5 mm to about 10 mm.

The Structure can have a basis weight of from about 200 grams/m² to about 2,000 grams/m², alternatively from about 400 g/m² to about 1,200 g/m², alternatively from about 600 g/m² to about 2,000 g/m², and alternatively from about 700 g/m² to about 1,500 g/m².

The Structure can have a dry density of from about 0.08 g/cm³ to about 0.40 g/cm³, alternatively from about 0.08 g/cm³ to about 0.38 g/cm³, alternatively from about 0.10 g/cm³ to about 0.25 g/cm³, and alternatively from about 0.12 g/cm³ to about 0.20 g/cm³.

Method of Use

The dissolvable solid substrates described herein may be used for cleaning and/or treating hair, hair follicles, skin, teeth, and the oral cavity. The method for treating these consumer substrates may comprise the steps of: a) applying an effective amount of the Structure to the hand, b) wetting the Structure with water to dissolve the solid, c) applying the dissolved material to the target consumer substrate such as to clean or treat it, and d) rinsing the diluted treatment composition from the consumer substrate. These steps can

13

be repeated as many times as desired to achieve the desired cleansing and or treatment benefit.

A method useful for providing a benefit to hair, hair follicles, skin, teeth, and/or the oral cavity, includes the step of applying a composition according to the first embodiment to these target consumer substrates in need of regulating.

Alternatively, a useful method for regulating the condition of hair, hair follicles, skin, teeth, the oral cavity, includes the step of applying one or more compositions described herein to these target consumer substrates in need of regulation.

The amount of the composition applied, the frequency of application and the period of use will vary widely depending upon the purpose of application, the level of components of a given composition and the level of regulation desired. For example, when the composition is applied for whole body or hair treatment, effective amounts generally range from about 0.5 grams to about 10 grams, alternatively from about 1.0 grams to about 5 grams, and alternatively from about 1.5 grams to about 3 grams.

Product Types and Articles of Commerce

Non-limiting examples of products that utilize the dissolvable solid structures include hand cleansing substrates, teeth cleaning or treating substrates, oral cavity substrates, hair shampoo or other hair treatment substrates, body cleansing substrates, shaving preparation substrates, personal care substrates containing pharmaceutical or other skin care active, moisturizing substrates, sunscreen substrates, chronic skin benefit agent substrates (e.g., vitamin-containing substrates, alpha-hydroxy acid-containing substrates, etc.), deodorizing substrates, fragrance-containing substrates, and so forth.

The dissolvable solid structure can be a personal care product, alternatively hair care product, alternatively rinse-off hair care product, alternatively rinse-off hair care product containing non-sulfate surfactant.

Described herein is an article of commerce comprising one or more dissolvable solid structures described herein, and a communication directing a consumer to dissolve the Structure and apply the dissolved mixture to hair, hair follicles, skin, teeth, the oral cavity, to achieve a benefit to the target consumer substrate, a rapidly lathering foam, a rapidly rinsing foam, a clean rinsing foam, and combinations thereof. The communication may be printed material attached directly or indirectly to packaging that contains the dissolvable solid structure or on the dissolvable solid structure itself. Alternatively, the communication may be an electronic or a broadcast message that is associated with the article of manufacture. Alternatively, the communication may describe at least one possible use, capability, distinguishing feature and/or property of the article of manufacture.

Test Methods

Basis Weight Measurement

In general, basis weight of a material or article (including the dissolvable solid structure) is measured by first cutting the sample to a known area, using a die cutter or equivalent, then measuring & recording the weight of the sample on a top-loading balance with a minimum resolution of 0.01 g, then finally by calculating the basis weight as follows:

Basis Weight (g/m²)=weight of basis weight pad (g)

$$\text{Basis Weight} \left(\frac{\text{g}}{\text{m}^2} \right) = \frac{\text{Weight of pad (g)} \times 10,000 \frac{\text{cm}^2}{\text{m}^2}}{\text{area of pad (cm}^2\text{)}}$$

14

Suitable pad sample sizes for basis weight determination are >10 cm² and should be cut with a precision die cutter having the desired geometry. If the dissolvable solid structure to be measured is smaller than 10 cm², a smaller sampling area can be used for basis weight determination with the appropriate changes to calculation.

In the present examples, basis weight was calculated based on the full dissolvable solid structure having a known area of 17.28 cm². Thus, the basis weight calculation becomes:

$$\text{Basis Weight} \left(\frac{\text{g}}{\text{m}^2} \right) = \frac{\text{Weight of pad (g)} \times 10,000 \frac{\text{cm}^2}{\text{m}^2}}{17.28 \text{ cm}^2}$$

Hand Dissolution Test Method

Materials Needed:

Dissolvable solid structures to be tested: 3-5 dissolvable solid structures (finished product samples) are tested so that an average of the number of strokes for each if the individual dissolvable solid structure samples is calculated and recorded as the Average Hand Dissolution value for the dissolvable solid structure. For this method, the entire consumer saleable or consumer use dissolvable solid structure is tested. If the entire consumer saleable or consumer use dissolvable solid structure has a footprint greater than 50 cm², then first cut the dissolvable solid structure to have a footprint of 50 cm².

Nitrile Gloves

10 cc syringe

Plastic Weigh boat (~3 in×3 in)

100 mL Glass beaker

Water (City of Cincinnati Water or equivalent having the following properties: Total Hardness=155 mg/L as CaCO₃; Calcium content=33.2 mg/L; Magnesium content=17.5 mg/L; Phosphate content=0.0462 mg/L)

Water used is 7 gpg hardness and 40° C.±5° C.

Protocol:

1. Add 80 mL of water to glass beaker. Add 300-500 ml of water to glass beaker.
2. Heat water in beaker until water is at a temperature of 40° C.±5° C.
3. Transfer 10 mL of the water from the beaker into the weigh boat via the syringe.
4. Within 10 seconds of transferring the water to the weigh boat, place dissolvable solid structure sample in palm of gloved hand (hand in cupped position in non-dominant hand to hold dissolvable solid structure sample).
5. Using dominant hand, add water quickly from the weigh boat to the dissolvable solid structure sample and allow to immediately wet for a period of 5-10 seconds.
6. Rub with opposite dominant hand (also gloved) in 2 rapid circular strokes.
7. Visually examine the dissolvable solid structure sample in hand after the 2 strokes. If dissolvable solid structure sample is completely dissolved, record number of strokes=2 Dissolution Strokes. If not completely dissolved, rub remaining dissolvable solid structure sample for 2 more circular strokes (4 total) and observe degree of dissolution. If the dissolvable solid structure sample contains no solid pieces after the 2 additional strokes, record number of strokes=4 Dissolution Strokes. If after the 4 strokes total, the dissolvable solid structure sample still contains solid pieces of un-dis-

15

solved dissolvable solid structure sample, continue rubbing remaining dissolvable solid structure sample in additional 2 circular strokes and check if there are any remaining solid pieces of dissolvable solid structure sample after each additional 2 strokes until dissolvable solid structure sample is completely dissolved or until reaching a total of 30 strokes, whichever comes first. Record the total number of strokes. Record 30 Dissolution Strokes even if solid dissolvable solid structure sample pieces remain after the maximum of 30 strokes.

8. Repeat this process for each of the additional 4 dissolvable solid structure samples.
9. Calculate the arithmetic mean of the recorded values of Dissolution Strokes for the 5 individual dissolvable solid structure samples and record as the Average Hand Dissolution Value for the dissolvable solid structure. The Average Hand Dissolution Value is reported to the nearest single Dissolution Stroke unit.

Fibrous Structures—Fiber Diameter

For fibrous Structures, the diameter of dissolvable fibers in a sample of a web is determined by using a Scanning Electron Microscope (SEM) or an Optical Microscope and image analysis software. A magnification of 200 to 10,000 times is chosen such that the fibers are suitably enlarged for measurement. When using the SEM, the samples are sputtered with gold or a palladium compound to avoid electric charging and vibrations of the fibers in the electron beam. A manual procedure for determining the fiber diameters is used from the image (on monitor screen) taken with the SEM or the optical microscope. Using a mouse and a cursor tool, the edge of a randomly selected fiber is sought and then measured across its width (i.e., perpendicular to fiber direction at that point) to the other edge of the fiber. A scaled and calibrated image analysis tool provides the scaling to get actual reading in microns (μm). Several fibers are thus randomly selected across the sample of the web using the SEM or the optical microscope. At least two specimens from the web (or web inside a product) are cut and tested in this manner. Altogether at least 100 such measurements are made and then all data are recorded for statistical analysis. The recorded data are used to calculate average (mean) of the fiber diameters, standard deviation of the fiber diameters, and median of the fiber diameters. Another useful statistic is the calculation of the amount of the population of fibers that is below a certain upper limit. To determine this statistic, the software is programmed to count how many results of the fiber diameters are below an upper limit and that count (divided by total number of data and multiplied by 100%) is reported in percent as percent below the upper limit, such as percent below 1 micron diameter or %-submicron, for example. We denote the measured diameter (in microns) of an individual circular fiber as d_i .

In case the fibers have non-circular cross-sections, the measurement of the fiber diameter is determined as and set equal to the hydraulic diameter which is four times the cross-sectional area of the fiber divided by the perimeter of the cross of the fiber (outer perimeter in case of hollow fibers). The number-average diameter, alternatively average diameter is calculated as, d_{num}

$$\frac{\sum_{i=1}^n d_i}{n}$$

16

Combinations

1. A dissolvable solid structure, wherein the dissolvable solid structure is formed by a homogeneous mixture comprising, by weight of the structure:
 - from about 1% to about 10% of a first polymeric structurant having a molecular weight of from about 1,000,000 g/mol to about 4,000,000 g/mol;
 - from about 10% to about 20% of a second polymeric structurant having a molecular weight of from about 50,000 g/mol to about 500,000 g/mol;
 - from about 10 wt % to about 85 wt % of one or more high melting point fatty material having a carbon chain length C12-C22 or mixtures thereof, wherein the melting point is above 25° C.; and from about 1 wt % to about 60 wt % of a cationic surfactant.
2. The dissolvable solid structure of the preceding feature, wherein the first and second polymeric structurants are selected from the group consisting of: polyacrylic acid and its copolymers, polyvinylpyrrolidone and its copolymers, polyacrylamide and its copolymers, polyvinylmethyl ether, polyethyleneimine, polymethacrylic acid, poly N-isopropyl acrylamide, poly N—N-dimethylacrylamide, polyvinylloxazolidone, a poly(vinyl oxazoline), poly 2-ethyl-2-oxazoline, polyvinylcaprolactam, polystyrene sulfonate, polyvinyl formamide, polyvinyl amine, poly alkylated vinyl pyrrolidone, poly vinyl valerolactam, polyvinyl imidazole, polyacrylic acid, polymethacrylate, polyacrylamide, polymethacrylamide, polydimethacrylamide, polyalkylaminomethacrylate, and polyalkylaminomethacrylamide, and copolymer combinations thereof.
3. The dissolvable solid structure of any of the preceding features, wherein the first and second polymeric structurants are selected from the group consisting of: polyvinylpyrrolidone and its copolymer, and mixtures thereof, preferably wherein the first and second polymeric structurants are polyvinylpyrrolidone.
4. The dissolvable solid structure of any of the preceding features, wherein the first polymeric structurant has a molecular weight of from about 1,500,000 g/mol to about 3,500,000 g/mol.
5. The dissolvable solid structure of any of the preceding features, wherein the second polymeric structurant has a molecular weight of from about 65,000 g/mol to about 395,000 g/mol.
6. The dissolvable solid structure of any of the preceding features, wherein the weight ratio between the first and second polymeric structurants is from about 1:1 to about 1:100, preferably from about 1:1 to about 1:50, more preferably from about 1:1 to about 1:10.
7. The dissolvable solid structure of any of the preceding features, wherein the weight ratio between the first and second polymeric structurants is in a range such that the average molecular weight of the first and second polymeric structurants is from about 300,000 g/mol to about 3,000,000 g/mol, preferably from about 350,000 g/mol to about 2,000,000 g/mol, more preferably from about 400,000 g/mol to about 1,000,000 g/mol, and even more preferably from about 500,000 g/mol to about 1,000,000 g/mol.
8. The dissolvable solid structure of any of the preceding features, wherein a total amount of the first and second polymeric structurants is from about 11% to about 25% by weight of the structure, preferably from about 13% to about 20% by weight of the structure.
9. The dissolvable solid structure of any of the preceding features, wherein the dissolvable solid structure is a personal care product, preferably hair care product,

more preferably rinse-off hair care product, still more preferably rinse-off hair care product containing non-sulfate surfactant.

10. The dissolvable solid structure of any of the preceding features, comprising from about 10 wt % to about 50 wt % of cationic surfactant by weight of the structure, preferably from about 20 wt % to about 40 wt % of cationic surfactant.
11. The dissolvable solid structure of any of the preceding features, wherein the Dissolvable Solid Structure dissolves in less than 30 strokes of the Hand Dissolution Method, preferably wherein the Dissolvable Solid Structure dissolves in less than 20 strokes of the Hand Dissolution Method, and even more preferably wherein the Dissolvable Solid Structure dissolves in less than 15 strokes of the Hand Dissolution Method.

NON-LIMITING EXAMPLES

The compositions illustrated in the following Examples illustrate specific embodiments of the composition, but are not intended to be limiting thereof. Other modifications can be undertaken by the skilled artisan without departing from the spirit and scope of this invention. These exemplified embodiments of the composition as described herein provide enhanced conditioning benefits to the hair.

All exemplified amounts are listed as weight percents and exclude minor materials such as diluents, preservatives, color solutions, imagery ingredients, botanicals, and so forth, unless otherwise specified. All percentages are based on weight unless otherwise specified.

The dissolvable solid structures of Ex.1 to Ex. 5 are examples of the present invention. These examples of the present invention provide an adequate strength during manufacturing, while not deteriorating usage feel when used and/or applied by consumers.

The dissolvable solid structures of CEx.i and CEx.ii are comparative examples of the present invention. In CEx.i, the mechanical strength of the fibrous element-forming composition during manufacturing is sufficient, however, its overall hair feel is inferior than the control conditioner. In CEx.ii, the mechanical strength of the fibrous element-forming composition during manufacturing too low while it exhibits acceptable hair feel.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Every document cited herein, including any cross referenced or related patent or application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the

Dissolvable solid structure-Hair conditioner Examples							
Raw Material	Ex 1	Ex 2	Ex 3	Ex 4	Ex 5	CEx. i	CEx. ii
Behentrimonium Methosulfate	21	21.5	21.7	21.8	—	—	25
Behentrimonium Chloride	—	—	—	—	14	20	—
Stearyl Alcohol	37	38	38.2	38.4	41.3	35	40
1-Hexadecanol	15	15.5	15.6	15.7	20.7	15	20
Lauroyl Methyl Glucamide	10	9.5	7.8	7.8	7	10	10
Polyvinyl pyrrolidone (PVP K30 from Ashland) having MW of 66,800	10	9.3	13.3	10.7	10	18	—
Polyvinyl pyrrolidone (PVP K60 from Jarchem) having MW of 396,000	—	—	—	1.6	—	—	—
Polyvinyl pyrrolidone (PVP K90 from Ashland) having MW of 1,570,000	5.5	5	3.3	—	5.5	5	—
Polyvinyl pyrrolidone (PVP K120 from Ashland) having MW of 3,470,000	1.5	1.2	—	4	1.5	—	4
Combined average MW of PVPs	853,412	815,177	365,629	934,255	853,412	66,800	3,470,000
Strength during manufacturing *1	Pass	Pass	Pass	Pass	Pass	Pass	Fail
Usage feel *2	Pass	Pass	Pass	Pass	Pass	Fail	Pass

*1 Mechanical strength during any suitable method to manufacturing the dissolvable solid structure which is a fibrous structure formed by a plurality of fibrous elements. For example, the fibrous elements are formed by meltblowing and/or spunbonding, by using a fibrous element-forming composition comprising the above ingredients in the table. The levels of the ingredients in such fibrous element-forming composition are adjusted such that the ingredients have the levels defined above in the dissolvable solid structure.

*2 Usage feel is assessed as follows: Samples provided to 10 panelists who rate the product based on overall hair feel compared to a control conditioner (CEx.ii). "Pass" means that 6 or more panelists answer that the overall hair feel is parity to or superior than the control conditioner.

19

same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

What is claimed is:

1. A dissolvable solid structure, wherein the dissolvable solid structure is formed by a homogeneous mixture comprising, by weight of the structure:

polymeric structurants consisting of:

from about 1% to about 10% of one or more first polymeric structurants wherein the structurants comprise a molecular weight of from about 1,500,000 g/mol to about 3,500,000 g/mol;

from about 10% to about 20% of or more second polymeric structurants wherein the structurants comprise a molecular weight of from about 65,000 g/mol to about 396,000 g/mol;

wherein the ratio of the first polymeric structurants to the second polymeric structurants is less than 1:1;

wherein the first and second polymeric structurants are polyvinylpyrrolidone, its copolymer, or a mixture thereof;

from about 10 wt % to about 85 wt % of one or more high melting point fatty material comprising a carbon chain length C12-C22 or mixtures thereof and a melting point above 25° C.; and

from about 1 wt % to about 60 wt % of a cationic surfactant;

wherein the combined average molecular weight of the first and second polymeric structurants is from about 350,000 g/mol to about 1,000,000 g/mol;

wherein the dissolvable structure is a hair conditioner.

2. The dissolvable solid structure of claim 1 wherein the first and second polymeric structurants are polyvinylpyrrolidone.

20

3. The dissolvable solid structure of claim 1, wherein a total amount of the first and second polymeric structurants is from about 11% to about 25% by weight of the structure.

4. The dissolvable solid structure of claim 3, wherein a total amount of the first and second polymeric structurants is from about 13% to about 20% by weight of the structure.

5. The dissolvable solid structure of claim 1, comprising from about 10 wt % to about 50 wt % of cationic surfactant by weight of the structure.

6. The dissolvable solid structure of claim 5, comprising from about 20 wt % to about 40 wt % of cationic surfactant by weight of the structure.

7. The dissolvable solid structure of claim 1, wherein the dissolvable solid structure dissolves in less than 20 strokes, according to a Hand Dissolution Method described herein.

8. The dissolvable solid structure of claim 7, wherein the dissolvable solid structure dissolves in less than 15 strokes, according to the Hand Dissolution Method described herein.

9. The dissolvable solid structure of claim 1, wherein the cationic surfactant is chosen from behentrimonium methosulfate, behentrimonium chloride, or mixtures thereof.

10. The dissolvable solid structure of claim 1, wherein the fatty material is stearyl alcohol.

11. The dissolvable solid structure of claim 1, wherein the structurants consist of two first polymeric structurants and one second polymeric structurant.

12. The dissolvable solid structure of claim 11, wherein the two first polymeric structurants have a molecular weight of about 1,570,000 and about 3,470,000 and the second polymeric structurant has a molecular weight of about 66,800.

13. The dissolvable solid structure of claim 1, wherein the structurants consist of one first polymeric structurant and two second polymeric structurants.

14. The dissolvable solid structure of claim 13, wherein the first polymeric structurant comprises a molecular weight of about 3,470,000 and the two second polymeric structurant comprises a molecular weight of about 66,800 and about 396,000.

* * * * *