

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                        |
|----------------------|------------------------|
| United States Patent | 12403749               |
| Kind Code            | B2                     |
| Date of Patent       | September 02, 2025     |
| Inventor(s)          | Yamada; Atsushi et al. |

---

### Air conditioner

---

#### Abstract

An air conditioner includes: a heat pump cycle including a compressor, a heating part and a low-temperature side water-refrigerant heat exchanger; a heat medium circuit; and a blower. In the air conditioner, when a heating capability of the heating part is increased by using the heat generated by the heat generating part, a heating preparation control is executed, in which a refrigerant discharge capability of the compressor is set to be equal to or less than a predetermined reference discharge capability and a blowing capability of the blower is set to be equal to or less than a predetermined reference blowing capability, until an inlet-side heat medium temperature of the heat medium flowing into the heat medium passage of the low-temperature side water-refrigerant heat exchanger becomes equal to or higher than a target heat medium temperature.

---

**Inventors:** Yamada; Atsushi (Kariya, JP), Tada; Kazuhiro (Kariya, JP), Harada; Masaki (Kariya, JP)

**Applicant:** DENSO CORPORATION (Kariya, JP)

**Family ID:** 83048893

**Assignee:** DENSO CORPORATION (Kariya, JP)

**Appl. No.:** 18/366866

**Filed:** August 08, 2023

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20230382195 A1          | Nov. 30, 2023           |

#### Foreign Application Priority Data

|    |             |               |
|----|-------------|---------------|
| JP | 2021-026880 | Feb. 23, 2021 |
|----|-------------|---------------|

Related U.S. Application Data

continuation parent-doc WO PCT/JP2022/001290 20220117 PENDING child-doc US 18366866

Publication Classification

Int. Cl.: B60H1/32 (20060101); B60H1/00 (20060101)

U.S. Cl.:

CPC B60H1/3205 (20130101); B60H1/00571 (20130101);

Field of Classification Search

CPC: B60H (1/3205); B60H (1/00571); B60H (1/00314); B60H (1/143); B60H (1/3213); B60H (1/23384); B60H (1/00914); B60H (1/00921); B60H (2001/00307); B60H (2001/00949)

References Cited

U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name    | U.S. Cl. | CPC          |
|--------------|-------------|------------------|----------|--------------|
| 11498391     | 12/2021     | Shiratori        | N/A      | B60H 1/03    |
| 2013/0152611 | 12/2012     | Furll et al.     | N/A      | N/A          |
| 2014/0158322 | 12/2013     | Homann et al.    | N/A      | N/A          |
| 2020/0207182 | 12/2019     | Ishizeki et al.  | N/A      | N/A          |
| 2022/0314742 | 12/2021     | Miyakoshi et al. | N/A      | N/A          |
| 2024/0190210 | 12/2023     | Michikawauchi    | N/A      | B60H 1/00278 |

FOREIGN PATENT DOCUMENTS

| Patent No.    | Application Date | Country | CPC |
|---------------|------------------|---------|-----|
| 102011109055  | 12/2011          | DE      | N/A |
| 112018004722  | 12/2019          | DE      | N/A |
| 2019130980    | 12/2018          | JP      | N/A |
| WO-2012028307 | 12/2011          | WO      | N/A |
| WO-2013013790 | 12/2012          | WO      | N/A |
| 2020203348    | 12/2019          | WO      | N/A |
| 2020235263    | 12/2019          | WO      | N/A |

Primary Examiner: Norman; Marc E

Attorney, Agent or Firm: Harness, Dickey & Pierce, P.L.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) The present application is a continuation application of International Patent Application No. PCT/JP2022/001290 filed on Jan. 17, 2022, which designated the U.S. and claims the benefit of priority from Japanese Patent Application No.

2021-026880 filed on Feb. 23, 2021. The entire disclosures of all of the above applications are incorporated herein by reference.

## TECHNICAL FIELD

(1) The present disclosure relates to an air conditioner having a heat generating part that generates heat.

## BACKGROUND ART

(2) A vehicle air conditioner includes a heat pump cycle and a low-temperature side heat medium circuit. The heat pump cycle may include a heating part and a low-temperature side water-refrigerant heat exchanger. The heating part heats ventilation air to be blown into a vehicle interior using, as a heat source, a high-pressure refrigerant discharged from a compressor. The low-temperature side water-refrigerant heat exchanger exchanges heat between a low-pressure refrigerant and a low-temperature side heat medium circulating in a low-temperature side heat medium circuit, and causes the low-pressure refrigerant to absorb heat of the low-temperature side heat medium.

## SUMMARY

(3) According to an aspect of the present disclosure, it is possible to set a heating preparation control. In the heating preparation control, a refrigerant discharge capability of a compressor of a heat pump cycle is made to be equal to or lower than a reference discharge capability until a temperature of a heat medium flowing into a heat medium passage of a low-temperature side water-refrigerant heat exchanger of the heat pump cycle becomes equal to or higher than a target heat medium temperature. Therefore, it is possible to suppress an unnecessary increase in the amount of heat to be absorbed from a heat medium to a low-pressure refrigerant in a low-temperature side water-refrigerant heat exchanger.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure will become more apparent from the following detailed description made with reference to the accompanying drawings. In the drawings:
- (2) FIG. 1 is a schematic overall configuration view of an air conditioner of a first embodiment;
  - (3) FIG. 2 is a block diagram illustrating an electric control unit of the air conditioner of the first embodiment;
  - (4) FIG. 3 is a flowchart showing a control flow during heating preparation control in the air conditioner of the first embodiment;
  - (5) FIG. 4 is a schematic overall configuration view illustrating a flow of a refrigerant or the like under the heating preparation control in the air conditioner of the first embodiment;
  - (6) FIG. 5 is a graph showing changes in an inlet side heat medium temperature and a target heat medium temperature under a comparative condition in the air conditioner of the first embodiment;
  - (7) FIG. 6 is a graph showing changes in the inlet side heat medium temperature and the target heat medium temperature under a first condition in the air conditioner of the first embodiment;
  - (8) FIG. 7 is a graph showing changes in the inlet side heat medium temperature and the target heat medium temperature under a second condition in the air conditioner of the first embodiment;
  - (9) FIG. 8 is a schematic overall configuration view illustrating a flow of the refrigerant or the like in a modification of the heating preparation control in the air conditioner of the first embodiment;
  - (10) FIG. 9 is a schematic overall configuration view illustrating a flow of the refrigerant or the like in another modification of the heating preparation control in the air conditioner of the first embodiment;
  - (11) FIG. 10 is a schematic overall configuration view of an air conditioner of a second

embodiment;

(12) FIG. 11 is a schematic overall configuration view illustrating a flow of a refrigerant or the like during heating preparation control in an air conditioner of a third embodiment;

(13) FIG. 12 is a schematic overall configuration view illustrating a flow of a refrigerant or the like during heating preparation control in an air conditioner of a fourth embodiment; and

(14) FIG. 13 is a schematic overall configuration view illustrating a flow of a refrigerant or the like during heating preparation control in an air conditioner of a fifth embodiment.

#### DESCRIPTION OF EMBODIMENTS

(15) In a low-temperature side heat medium circuit of an air conditioner, a heat medium passage of a low-temperature side water-refrigerant heat exchanger and an electric heater may be disposed. The electric heater is a heat generating part that generates heat for heating a low-temperature side heat medium.

(16) In the air conditioner, the heat generated by the electric heater is moved from a low-pressure side to a high-pressure side by a heat pump cycle, which can be used to improve the heating capability of a heating part.

(17) In the air conditioner, however, the temperature of the low-temperature side heat medium having a relatively large heat capacity may need to be raised higher than that of the low-pressure refrigerant in order to improve the heating capability of the heating part using the heat generated by the electric heater.

(18) For example, when the temperature of the low-temperature side heat medium is as low as in the case of low outside air temperature, the time for raising the temperature of the low-temperature side heat medium becomes long, and thus it is impossible to promptly improve the heating capability of the heating part. As a result, warm-up time, necessary for raising the temperature of the ventilation air to a temperature at which the vehicle interior can be sufficiently heated, becomes long, and thus it is impossible to realize air conditioning with immediate effectiveness and high responsiveness.

(19) In view of the above points, an object of the present disclosure is to provide an air conditioner capable of promptly increasing heating capability of a heating part by using heat generated by a heat generating part.

(20) An air conditioner according to an exemplar of the present disclosure includes a heat pump cycle, a heat medium circuit and a blower. The heat pump cycle includes a compressor, a heating part and a low-temperature side water-refrigerant heat exchanger. The compressor is configured to compress and discharge a refrigerant. The heating part is configured to heat air to be blown into a space to be air-conditioned using a high-pressure refrigerant discharged from the compressor as a heat source. The low-temperature side water-refrigerant heat exchanger is configured to cause a low-pressure refrigerant to absorb heat of a heat medium.

(21) The heat medium circuit is configured to circulate therein the heat medium, and the blower is configured to blow the air toward the space to be air-conditioned.

(22) The heat medium circuit is provided with a heat medium passage of the low-temperature side water-refrigerant heat exchanger, and a heat generating part configured to heat the heat medium to flow into the heat medium passage of the low-temperature side water-refrigerant heat exchanger.

(23) Further, when a heating capability of the heating part is increased by using the heat generated by the heat generating part, a heating preparation control is executed, in which a refrigerant discharge capability of the compressor is set to be equal to or less than a predetermined reference discharge capability and a blowing capability of the blower is set to be equal to or less than a predetermined reference blowing capability, until an inlet-side heat medium temperature of the heat medium flowing into the heat medium passage of the low-temperature side water-refrigerant heat exchanger becomes equal to or higher than a target heat medium temperature.

(24) According to this, in the heating preparation control, the refrigerant discharge capability of the compressor is made to be equal to or lower than the reference discharge capability until the

temperature of the heat medium flowing into the heat medium passage of the low-temperature side water-refrigerant heat exchanger becomes equal to or higher than the target heat medium temperature. Therefore, it is possible in the low-temperature side water-refrigerant heat exchanger to suppress an unnecessary increase in the amount of heat to be absorbed from the heat medium to the low-pressure refrigerant.

(25) In the heating preparation control, the blowing capability of the blower is made to be equal to or lower than the reference blowing capability until the temperature of the heat medium flowing into the heat medium passage of the low-temperature side water-refrigerant heat exchanger becomes equal to or higher than the target heat medium temperature. Therefore, it is possible in the heating part to suppress an unnecessary increase in the amount of heat to be dissipated to the ventilation air.

(26) As a result, when the heating preparation control is executed, the temperature of the heat medium can be promptly raised using the heat generated by the heat generating part. Furthermore, when the heat of the heat medium whose temperature has been promptly raised is absorbed by the low-pressure refrigerant in the heat pump cycle and is moved to the high-pressure refrigerant, the heating capability of the heating part can be promptly increased.

(27) According to the air conditioner of the present disclosure, it is possible to provide an air conditioner capable of promptly increasing the heating capability of the heating part using the heat generated by a heat generating part.

(28) Hereinafter, a plurality of embodiments for carrying out the present disclosure will be described with reference to the drawings. In each embodiment, parts corresponding to matters described in the preceding embodiment are denoted by the same reference numerals, and redundant description may be omitted. In a case where only a part of the configuration is described in each embodiment, other embodiments previously described can be applied to other parts of the configuration. In addition to the combination of parts that are specifically and explicitly described as being capable of being combined in each embodiment, it is also possible to partially combine the embodiments even if they are not explicitly described, as long as there is no problem in the combination.

#### First Embodiment

(29) A first embodiment of an air conditioner **1** according to the present disclosure will be described with reference to FIGS. **1** to **9**. The air conditioner **1** of the present embodiment is applied to an electric car. The electric car is a vehicle that obtains driving force for traveling from an electric motor. In the electric car, the air conditioner **1** air conditions a vehicle interior that is a space to be air conditioned, and adjusts the temperatures of in-vehicle devices whose temperatures are to be adjusted. Therefore, the air conditioner **1** of the present embodiment is a vehicle air conditioner with an in-vehicle device temperature adjustment function.

(30) In the air conditioner **1** of the present embodiment, the in-vehicle devices whose temperatures are to be adjusted are a battery **80** and a strong current device **81**.

(31) The battery **80** is a secondary battery that stores electric power to be supplied to electric in-vehicle devices. In the present embodiment, a lithium ion battery is adopted as the battery **80**. The battery **80** is an assembled battery formed by electrically connecting a plurality of stacked battery cells in series or in parallel.

(32) The battery **80** generates heat during operation (i.e., during charging and discharging). The battery **80** has characteristics that the output is likely to decrease at a low temperature and the deterioration is likely to progress at a high temperature. Therefore, the temperature of the battery **80** needs to be maintained within an appropriate temperature range (in the present embodiment, 15° C. or higher and 55° C. or lower).

(33) The strong current device **81** is an in-vehicle device that operates by being supplied with electric power and generates heat during operation. The strong current device **81** of the present embodiment is specifically an inverter and a motor generator.

(34) The inverter is a power conversion device that converts the frequency of electric power to be supplied from the battery **80** to the motor generator, converts AC power generated by the motor generator into DC power, and outputs the DC power to the battery **80** side. The motor generator serves as an electric motor that outputs driving force for traveling by being supplied with electric power, and serves as a power generator that generates regenerative power when the vehicle is decelerating or traveling downhill.

(35) When the temperature of the strong current device **81** is high, degradation of electric circuits may progress. Therefore, it is necessary to maintain the temperature of each electric circuit at a temperature lower than a reference heat resistant temperature (in the present embodiment, 130° C.) at which the electric circuit can be protected.

(36) Therefore, in the present embodiment, an appropriate temperature zone, in which the battery **80** can be appropriately operated, and an appropriate temperature zone, in which the strong current device **81** can be appropriately operated, do not completely match. In other words, the appropriate temperature zone of the battery **80** is different from the appropriate temperature zone of the strong current device **81**. As illustrated in the overall configuration view of FIG. **1**, the air conditioner **1** includes a heat pump cycle **10**, an indoor air conditioning unit **30**, a high-temperature side heat medium circuit **40**, a low-temperature side heat medium circuit **50**, and the like.

(37) First, the heat pump cycle **10** will be described. The heat pump cycle **10** is a vapor compression type refrigeration cycle device that, in order to perform air conditioning of the vehicle interior and adjust the temperatures of the in-vehicle devices, adjusts the temperatures of: ventilation air to be blown into the vehicle interior, a high-temperature side heat medium circulating in the high-temperature side heat medium circuit **40**, and a low-temperature side heat medium circulating in the low-temperature side heat medium circuit **50**.

(38) In order to perform air conditioning of the vehicle interior and adjust the temperatures of the in-vehicle devices, the heat pump cycle **10** is formed so as to be able to switch a refrigerant circuit according to various operation modes to be described later.

(39) In the heat pump cycle **10**, an HFO refrigerant (specifically, R1234yf) is adopted as the refrigerant. The heat pump cycle **10** constitutes a subcritical refrigeration cycle in which the pressure of the high-pressure refrigerant discharged from a compressor **11** does not exceed the critical pressure of the refrigerant. Refrigerator oil for lubricating the compressor **11** is mixed in the refrigerant. The refrigerator oil is PAG oil having compatibility with a liquid-phase refrigerant. A part of the refrigerator oil circulates in the cycle together with the refrigerant.

(40) The compressor **11** sucks, compresses, and discharges the refrigerant in the heat pump cycle **10**. The compressor **11** is disposed in a driving device room on the front side of a vehicle cabin. The driving device room forms a space where at least a part of a device (e.g., a motor generator) or the like to be used for generating a driving force for traveling the vehicle is disposed.

(41) The compressor **11** is an electric compressor that drives a fixed capacity type compression mechanism having a fixed discharge capacity by an electric motor. The number of rotation (i.e., refrigerant discharge capability) of the compressor **11** is controlled by a control signal output from a control device **60** for system control to be described later.

(42) The inlet side of a refrigerant passage **12a** of a water-refrigerant heat exchanger **12** is connected to the discharge port of the compressor **11**. The water-refrigerant heat exchanger **12** includes the refrigerant passage **12a** that causes the high-pressure refrigerant discharged from the compressor **11** to flow through, and a heat medium passage **12b** that causes the high-temperature side heat medium circulating in the high-temperature side heat medium circuit **40** to flow through.

(43) The water-refrigerant heat exchanger **12** is a high-temperature side water-refrigerant heat exchange part that exchanges heat between the high-pressure refrigerant flowing through the refrigerant passage **12a** and the high-temperature side heat medium flowing through the heat medium passage **12b**. In the water-refrigerant heat exchanger **12**, the heat of the high-pressure refrigerant is dissipated to the heat medium to heat the high-temperature side heat medium.

(44) The inflow port side of a first refrigerant joint part **13a** is connected to the outlet of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12**. The first refrigerant joint part **13a** is a three-way joint having three inflow outlets communicating with each other. As the first refrigerant joint part **13a**, a joint member formed by joining a plurality of pipes, or a joint member formed by providing a plurality of refrigerant passages in a metal block or a resin block, can be adopted.

(45) As described later, the heat pump cycle **10** further includes a second refrigerant joint part **13b** to a sixth refrigerant joint part **13f**. The basic configurations of the second refrigerant joint part **13b** to the sixth refrigerant joint part **13f** are similar to that of the first refrigerant joint part **13a**.

(46) When one of the three inflow outlets is used as an inflow port and the remaining two are used as outflow ports, these joint parts serve as branch parts that branch the flow of the refrigerant. When two of the three inflow outlets are used as inflow ports and the remaining one is used as an outflow port, these joint parts serve as merging parts that merge the flows of the refrigerant.

(47) The inlet side of a heating expansion valve **14a** is connected to one outflow port of the first refrigerant joint part **13a**. One inflow port side of the second refrigerant joint part **13b** is connected to the other outflow port of the first refrigerant joint part **13a** via a dehumidifying passage **22a**.

(48) The dehumidifying passage **22a** forms a refrigerant flow path that causes the refrigerant to flow through during a parallel dehumidifying-heating mode or the like to be described later. A dehumidifying on-off valve **15a** is disposed in the dehumidifying passage **22a**. The dehumidifying on-off valve **15a** is an electromagnetic valve that opens and closes the dehumidifying passage **22a**. The operation of the dehumidifying on-off valve **15a** is controlled by a control voltage output from the control device **60**.

(49) As described later, the heat pump cycle **10** further includes a heating on-off valve **15b**. The basic configuration of the heating on-off valve **15b** is similar to that of the dehumidifying on-off valve **15a**. The dehumidifying on-off valve **15a** and the heating on-off valve **15b** can switch the refrigerant circuit of the heat pump cycle **10** by opening and closing the refrigerant passage. Therefore, the dehumidifying on-off valve **15a** and the heating on-off valve **15b** are refrigerant circuit switching parts that switch the refrigerant circuit.

(50) The heating expansion valve **14a** is a heating pressure-reducing part that, during a heating mode or the like to be described later, reduces the pressure of the high-pressure refrigerant flowing out of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12** and adjusts the flow rate (mass flow rate) of the refrigerant that is caused to flow out to the downstream side.

(51) The heating expansion valve **14a** is an electric variable throttle mechanism including a valve body part **141a** that changes an opening degree (i.e., a valve opening degree) of a throttle passage and an electric actuator (specifically, a stepping motor) that displaces the valve body part **141a**. The operation of the heating expansion valve **14a** is controlled by a control signal (specifically, a control pulse) output from the control device **60**.

(52) The heating expansion valve **14a** has a fully opening function of functioning as a simple refrigerant passage with rarely exerting a flow rate adjusting action and a refrigerant pressure reducing action when the valve body part **141a** fully opens the valve opening degree. The heating expansion valve **14a** also has a fully closing function of closing the refrigerant passage when the valve body part **141a** fully closes the throttle passage.

(53) As described later, the heat pump cycle **10** further includes an air-cooling expansion valve **14b** and a cooling expansion valve **14c**. The basic configurations of the air-cooling expansion valve **14b** and the cooling expansion valve **14c** are similar to that of the heating expansion valve **14a**. Therefore, the air-cooling expansion valve **14b** includes a valve body part **141b** and has the fully opening function and the fully closing function. The cooling expansion valve **14c** includes a valve body part **141c** and has the fully opening function and the fully closing function.

(54) The heating expansion valve **14a**, the air-cooling expansion valve **14b**, and the cooling expansion valve **14c** can switch the refrigerant circuit of the heat pump cycle **10** by the above-

described fully closing function. More specifically, the valve body part **141a** of the heating expansion valve **14a**, the valve body part **141b** of the air-cooling expansion valve **14b**, and the valve body part **141c** of the cooling expansion valve **14c** also have a function as the refrigerant circuit switching part.

(55) Of course, the heating expansion valve **14a**, the air-cooling expansion valve **14b**, and the cooling expansion valve **14c** may be formed by combining a variable throttle mechanism not having the fully closing function with an on-off valve. In this case, the on-off valve serves as the refrigerant circuit switching part.

(56) The refrigerant inlet side of an outdoor heat exchanger **16** is connected to the outlet of the heating expansion valve **14a**. Therefore, the valve body part **14a** of the heating expansion valve **141a** serves as an outdoor unit inlet side opening/closing part that opens and closes the refrigerant inlet side of the outdoor heat exchanger **16**. The outdoor heat exchanger **16** is an outdoor heat exchange part that exchanges heat between the refrigerant flowing out of the heating expansion valve **14a** and the outside air blown by a non-illustrated cooling fan. The outdoor heat exchanger **16** is disposed on the front side of the drive device room. Therefore, traveling air can be applied to the outdoor heat exchanger **16** during traveling the vehicle.

(57) The inflow port side of the third refrigerant joint part **13c** is connected to the refrigerant outlet of the outdoor heat exchanger **16**. One inflow port side of the fourth refrigerant joint part **13d** is connected to one outflow port of the third refrigerant joint part **13c** via a heating passage **22b**. The heating passage **22b** forms a refrigerant flow path that causes the refrigerant to flow through during a heating mode or the like to be described later.

(58) The heating on-off valve **15b** and a first check valve **17a** are disposed in the heating passage **22b**. The heating on-off valve **15b** is an electromagnetic valve that opens and closes the heating passage **22b**. The first check valve **17a** allows the refrigerant to flow from the third refrigerant joint part **13c** side to the fourth refrigerant joint part **13d** side, and prohibits the refrigerant from flowing from the fourth refrigerant joint part **13d** side to the third refrigerant joint part **13c** side. Therefore, the heating on-off valve **15b** and the first check valve **17a** serve as an outdoor unit outlet side opening/closing part that opens and closes the refrigerant outlet side of the outdoor heat exchanger **16**.

(59) The other inflow port side of the second refrigerant joint part **13b** is connected to the other outflow port of the third refrigerant joint part **13c**. A second check valve **17b** is disposed in a refrigerant passage connecting the other outflow port of the third refrigerant joint part **13c** and the other inflow port of the second refrigerant joint part **13b**. The second check valve **17b** allows the refrigerant to flow from the third refrigerant joint part **13c** side to the second refrigerant joint part **13b** side, and prohibits the refrigerant from flowing from the second refrigerant joint part **13b** side to the third refrigerant joint part **13c** side. Therefore, the second check valve **17b** serves as an outdoor unit outlet side opening/closing part.

(60) The inflow port side of the fifth refrigerant joint part **13e** is connected to the outflow port of the second refrigerant joint part **13b**. The inlet side of the air-cooling expansion valve **14b** is connected to one outflow port of the fifth refrigerant joint part **13e**. The inlet side of the cooling expansion valve **14c** is connected to the other outflow port of the fifth refrigerant joint part **13e**.

(61) The air-cooling expansion valve **14b** is an air-cooling pressure-reducing part that, during an air-cooling mode or the like to be described later, reduces the pressure of the refrigerant and adjusts the flow rate of the refrigerant that is caused to flow out to the downstream side. The refrigerant inlet side of an indoor evaporator **18** is connected to the outlet of the air-cooling expansion valve **14b**. Therefore, the valve body part **141b** of the air-cooling expansion valve **14b** serves as an indoor unit inlet side opening/closing part that opens and closes the refrigerant inlet side of the indoor evaporator **18**.

(62) The indoor evaporator **18** is disposed in an air conditioning case **31** of the indoor air conditioning unit **30** to be described later. The indoor evaporator **18** is a cooling heat exchanger

that exchanges heat between the low-pressure refrigerant whose pressure has been reduced by the air-cooling expansion valve **14b** and the ventilation air to be blown into the vehicle interior. The indoor evaporator **18** cools the ventilation air by evaporating the low-pressure refrigerant to exert an endothermic action.

(63) One inflow port side of the sixth refrigerant joint part **13f** is connected to the refrigerant outlet of the indoor evaporator **18**. A third check valve **17c** is disposed in a refrigerant flow path connecting the refrigerant outlet of the indoor evaporator **18** and the one inflow port of the sixth refrigerant joint part **13f**. The third check valve **17c** allows the refrigerant to flow from the indoor evaporator **18** side to the sixth refrigerant joint part **13f** side, and prohibits the refrigerant from flowing from the sixth refrigerant joint part **13f** side to the indoor evaporator **18** side. Therefore, the third check valve **17c** serves as an indoor unit outlet side opening/closing part that opens and closes the refrigerant outlet side of the indoor evaporator **18**.

(64) The cooling expansion valve **14c** is a cooling pressure-reducing part that, during a battery cooling mode or the like to be described later, reduces the pressure of the refrigerant and adjusts the flow rate of the refrigerant that is caused to flow out to the downstream side. The inlet side of a refrigerant passage **20a** of a chiller **20** is connected to the outlet of the cooling expansion valve **14c**.

(65) The chiller **20** includes a refrigerant passage **20a** that causes the low-pressure refrigerant whose pressure has been reduced by the cooling expansion valve **14c** to flow through, and a heat medium passage **20b** that causes the low-temperature side heat medium circulating in the low-temperature side heat medium circuit **50** to flow through. The chiller **20** is a low-temperature side water-refrigerant heat exchanger that exchanges heat between the low-pressure refrigerant flowing through the refrigerant passage **20a** and the low-temperature side heat medium flowing through the heat medium passage **20b**. The chiller **20** cools the low-temperature side heat medium by evaporating the low-pressure refrigerant to exert an endothermic action.

(66) The other inflow port side of the sixth refrigerant joint part **13f** is connected to the outlet of the refrigerant passage **20a** of the chiller **20**. Therefore, the indoor evaporator **18** and the chiller **20** are connected in parallel for the flow of the refrigerant moving from the fifth refrigerant joint part **13e** to the sixth refrigerant joint part **13f**. The other inflow port side of the fourth refrigerant joint part **13d** is connected to the outflow port of the sixth refrigerant joint part **13f**.

(67) The inlet side of an accumulator **21** is connected to the outflow port of the fourth refrigerant joint part **13d**. The accumulator **21** is a low-pressure side gas-liquid separator that separates the gas and liquid of the refrigerant having flowed into its inside and stores a surplus liquid-phase refrigerant in the cycle. The suction port side of the compressor **11** is connected to the gas-phase refrigerant outlet of the accumulator **21**.

(68) Next, the high-temperature side heat medium circuit **40** will be described. The high-temperature side heat medium circuit **40** is a circuit that circulates the high-temperature side heat medium. In the high-temperature side heat medium circuit **40**, an ethylene glycol aqueous solution is adopted as the high-temperature side heat medium. In the high-temperature side heat medium circuit **40**, the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, a high-temperature side pump **41**, a heater core **42**, and the like are disposed.

(69) The high-temperature side pump **41** is a high-temperature side heat medium pressure-feeding part that sucks and pressure-feeds the high-temperature side heat medium. The high-temperature side pump **41** pressure-feeds the high-temperature side heat medium to the inlet side of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**. The high-temperature side pump **41** is an electric water pump whose number of rotation (i.e., pressure-feeding capability) is controlled by a control voltage output from control device **60**.

(70) The heat medium inlet side of the heater core **42** is connected to the outlet of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**. The heater core **42** is disposed in the air conditioning case **31** of the indoor air conditioning unit **30**. The heater core **42** is a heating heat exchange part that exchanges heat between the high-temperature side heat medium heated by the

water-refrigerant heat exchanger **12** and the ventilation air. In the heater core **42**, the heat of the high-temperature side heat medium is dissipated to the ventilation air to heat the ventilation air. The suction port side of the high-temperature side pump **41** is connected to the heat medium outlet of the heater core **42**.

(71) Therefore, in the present embodiment, the respective components of the water-refrigerant heat exchanger **12** and the high-temperature side heat medium circuit form a heating part that heats the ventilation air using the high-pressure refrigerant discharged from the compressor **11** as a heat source.

(72) Next, the low-temperature side heat medium circuit **50** will be described. The low-temperature side heat medium circuit **50** is a circuit that circulates the low-temperature side heat medium. The low-temperature side heat medium is a heat medium to be heated by a heat generating part to be described later. In the low-temperature side heat medium circuit **50**, the same kind of fluid as the high-temperature side heat medium is adopted as the low-temperature side heat medium. The low-temperature side heat medium circuit **50** is formed so as to be able to switch the heat medium circuit according to various operation modes to be described later.

(73) In the low-temperature side heat medium circuit **50**, a first low-temperature side pump **51a**, a second low-temperature side pump **51b**, a first low-temperature side three-way valve **52a**, a second low-temperature side three-way valve **52b**, the heat medium passage **20b** of the chiller **20**, a cooling water passage **80a** of the battery **80**, a cooling water passage **81a** of the strong current device **81**, an electric heater **54**, a battery bypass passage **55a**, a low-temperature side radiator **56**, and the like are disposed.

(74) The first low-temperature side pump **51a** and the second low-temperature side pump **51b** are low-temperature side heat medium pressure-feeding parts that suck and pressure-feed the low-temperature side heat medium. The basic configurations of the first low-temperature side pump **51a** and the second low-temperature side pump **51b** are similar to that of the high-temperature side pump **41**. The first low-temperature side pump **51a** pressure-feeds the low-temperature side heat medium to the inlet side of the cooling water passage **80a** of the battery **80**.

(75) The cooling water passage **80a** of the battery **80** is a battery side heat exchange part that exchanges heat between the plurality of battery cells and the low-temperature side heat medium. The cooling water passage **80a** of the battery **80** houses the plurality of battery cells and is formed in a battery case forming the outer shell of the battery **80**.

(76) The inflow port side of the first low-temperature side three-way valve **52a** is connected to the outlet of the cooling water passage **80a** of the battery **80**. The first low-temperature side three-way valve **52a** is a three-way type flow regulating valve. The first low-temperature side three-way valve **52a** causes the low-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** to flow into its inside, and causes the low-temperature side heat medium to flow out to at least one of one inflow port side of the first heat medium joint part **53a** and the battery bypass passage **55a** side.

(77) The first low-temperature side three-way valve **52a** can continuously adjust the flow ratio between the flow rate of the low-temperature side heat medium that is caused to flow out to the first heat medium joint part **53a** side and the flow rate of the low-temperature side heat medium that is caused to flow out to the battery bypass passage **55a** side. Furthermore, by adjusting the flow ratio, the first low-temperature side three-way valve **52a** can cause the total flow rate of the low-temperature side heat medium that has been caused to flow into its inside to flow out to one of the first heat medium joint part **53a** side and the battery bypass passage **55a** side.

(78) That is, the first low-temperature side three-way valve **52a** serves as a heat medium circuit switching part that switches the circuit configuration of the heat medium circuit. The operation of the first low-temperature side three-way valve **52a** is controlled by a control signal output from the control device **60**.

(79) The second low-temperature side three-way valve **52b** is further disposed in the low-

temperature side heat medium circuit **50**. The basic configurations of the second low-temperature side three-way valve **52b** and a heat medium circuit three-way valve adopted in an embodiment to be described later are similar to that of the first low-temperature side three-way valve **52a**. Therefore, the second low-temperature side three-way valve **52b** and the like also serve as the heat medium circuit switching part.

(80) The first heat medium joint part **53a** is a heat medium three-way joint. The low-temperature side heat medium circuit **50** of the present embodiment further includes a second heat medium joint part **53b** to a fourth heat medium joint part **53d**, as described later. The basic configurations of the first heat medium joint part **53a** to the fourth heat medium joint part **53d** and a heat medium joint part adopted in an embodiment to be described later are similar to those of the first refrigerant joint part **13a** and the like of the heat pump cycle **10**.

(81) The inlet side of the electric heater **54** is connected to the outflow port of the first heat medium joint part **53a**. Therefore, the first low-temperature side three-way valve **52a** substantially causes the low-temperature side heat medium having flowed into its inside to flow out to at least one of the electric heater **54** side and the battery bypass passage **55a** side.

(82) The battery bypass passage **55a** forms a heat medium flow path that guides the low-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** to the suction port side of the first low-temperature side pump **51a** while causing the heat medium to bypass the electric heater **54**, the heat medium passage of the chiller **20**, and the like. One inflow port of the second heat medium joint part **53b** is connected to the outlet portion of the battery bypass passage **55a**. The suction port side of the first low-temperature side pump **51a** is connected to the outflow port of the second heat medium joint part **53b**.

(83) The second low-temperature side pump **51b** pressure-feeds the low-temperature side heat medium to the inlet side of the cooling water passage **81a** of the strong current device **81**. The cooling water passage **81a** of the strong current device **81** is a strong current device side heat exchange part that exchanges heat between the strong current device **81** and the low-temperature side heat medium. The cooling water passage **81a** of the strong current device **81** is formed in a housing part or a case part, which forms the outer shell of the strong current device **81**.

(84) The inflow port side of the second low-temperature side three-way valve **52b** is connected to the outlet of the cooling water passage **81a** of the strong current device **81**. The second low-temperature side three-way valve **52b** causes the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** to flow into its inside, and causes the low-temperature side heat medium to flow out to at least one of the other inflow port side of the first heat medium joint part **53a** and the low-temperature side radiator **56** side.

(85) Therefore, the second low-temperature side three-way valve **52b** substantially causes the low-temperature side heat medium having flowed into its inside to flow out to at least one of the electric heater **54** side and the low-temperature side radiator **56** side.

(86) The second low-temperature side three-way valve **52b** can continuously adjust the flow ratio between the flow rate of the low-temperature side heat medium that is caused to flow out to the electric heater **54** side and the flow rate of the low-temperature side heat medium that is caused to flow out to the low-temperature side radiator **56** side. Furthermore, by adjusting the flow ratio, the second low-temperature side three-way valve **52b** can cause the total flow rate of the low-temperature side heat medium that has been caused to flow into its inside to flow out to one of the electric heater **54** side and the battery bypass passage **55a** side.

(87) The low-temperature side radiator **56** is a low-temperature side outside air heat exchange part that exchanges heat between the outside air and the low-temperature side heat medium flowing out of the second low-temperature side three-way valve **52b**. The low-temperature side radiator **56** is disposed on the front side of the drive device room, together with the outdoor heat exchanger **16** of the heat pump cycle **10**.

(88) One inflow port side of the third heat medium joint part **53c** is connected to the heat medium

outlet of the low-temperature side radiator **56**. The suction port side of the second low-temperature side pump **51b** is connected to the outflow port of the third heat medium joint part **53c**.

(89) The electric heater **54** is a heat generating part that generates heat for heating the low-temperature side heat medium. In the present embodiment, a PTC heater having a PTC element (i.e., a positive characteristic thermistor) that generates heat by being supplied with electric power and heats the low-temperature side heat medium flowing through a heating flow path is adopted as the electric heater **54**. The inlet side of the heat medium passage **20b** of the chiller **20** is connected to the outlet of the heating heat medium flow path of the electric heater **54**.

(90) The inflow port side of the fourth heat medium joint part **53d** is connected to the outlet of the heat medium passage **20b** of the chiller **20**. The other inflow port side of the second heat medium joint part **53b** is connected to one outflow port of the fourth heat medium joint part **53d**. The other inflow port side of the third heat medium joint part **53c** is connected to the other outflow port of the fourth heat medium joint part **53d**.

(91) As is apparent from the above description, the high-temperature side heat medium circuit **40** and low-temperature side heat medium circuit **50** of the present embodiment are formed as completely independent heat medium circuits. Therefore, the high-temperature side heat medium and the low-temperature side heat medium are not mixed. In addition, the electric heater **54**, the heat generating part, is disposed only in the low-temperature side heat medium circuit **50**. In the high-temperature side heat medium circuit **40**, only the water-refrigerant heat exchanger **12** is disposed as a configuration for heating the high-temperature side heat medium.

(92) Next, the indoor air conditioning unit **30** will be described. The indoor air conditioning unit **30** is a unit in which a plurality of components are integrated in order to blow out the ventilation air, the temperature of which has been adjusted to an appropriate temperature for air conditioning the vehicle interior, to an appropriate place in the vehicle interior. The indoor air conditioning unit **30** is disposed inside an instrument panel at the forefront of the vehicle interior.

(93) As illustrated in FIG. **1**, the indoor air conditioning unit **30** houses an indoor blower **32**, the indoor evaporator **18**, the heater core **42**, and the like in the air conditioning case **31** forming an air passage for the ventilation air. The air conditioning case **31** is made of resin (e.g., polypropylene) having a certain degree of elasticity and excellent strength.

(94) An inside/outside air switching device **33** is disposed on the most upstream side, in the ventilation air flow, of the air conditioning case **31**. The inside/outside air switching device **33** introduces, in a switching manner, the inside air (i.e., vehicle interior air) and the outside air (i.e., vehicle exterior air) into the air conditioning case **31**. The operation of the inside/outside air switching device **33** is controlled by a control signal output from the control device **60**.

(95) The indoor blower **32** is disposed on the downstream side, in the ventilation air flow, of the inside/outside air switching device **33**. The indoor blower **32** blows the air sucked via the inside/outside air switching device **33** toward the vehicle interior. The indoor blower **32** is an electric blower that drives a centrifugal multi-blade fan with an electric motor. The number of rotation (i.e., blowing capability) of the indoor blower **32** is controlled by a control voltage output from the control device **60**.

(96) The indoor evaporator **18** and the heater core **42** are disposed on the downstream side, in the ventilation air flow, of the indoor blower **32**. The indoor evaporator **18** is disposed on the upstream side, in the ventilation air flow, of the heater core **42**. In the air conditioning case **31**, a cold air bypass passage **35**, that causes the ventilation air having passed through the indoor evaporator **18** to flow while bypassing the heater core **42**, is formed.

(97) In the air conditioning case **31**, an air mix door **34** is disposed on the downstream side, in the ventilation air flow, of the indoor evaporator **18** and on the upstream side, in the ventilation air flow, of the heater core **42** and the cold air bypass passage **35**.

(98) The air mix door **34** is an air volume ratio adjuster that adjusts the air volume ratio between, of the ventilation air having passed through the indoor evaporator **18**, the air volume of the ventilation

air that is caused to pass through the heater core **42** side and the air volume of the ventilation air that is caused to pass through the cold air bypass passage **35**. The air mix door **34** is driven by an air mix door electric actuator. The operation of the air mix door electric actuator is controlled by a control signal output from the control device **60**.

(99) A mixing space **36** is disposed on the downstream side, in the ventilation air flow, of the heater core **42** and the cold air bypass passage **35**. The mixing space **36** is a space for mixing the ventilation air heated by the heater core **42** and the ventilation air having passed through the cold air bypass passage **35** and not heated. Therefore, in the indoor air conditioning unit **30**, the temperature of the ventilation air (i.e., conditioned air) mixed in the mixing space **36** can be adjusted by adjusting the opening degree of the air mix door **34**.

(100) A plurality of opening holes (not illustrated) for blowing out the ventilation air mixed in the mixing space **36** into the vehicle interior are formed in the most downstream portion, in the ventilation air flow, of the air conditioning case **31**. The plurality of opening holes communicate with a plurality of blowing-out ports formed in the vehicle interior. As the plurality of blowing-out ports, a face blowing-out port, a foot blowing-out port, and a defroster blowing-out port are provided.

(101) The face blowing-out port is a blowing-out port for blowing out the ventilation air toward the upper body of an occupant. The foot blowing-out port is a blowing-out port for blowing out the ventilation air toward the feet of an occupant. The defroster blowing-out port is a blowing-out port for blowing out the ventilation air toward the vehicle front window glass.

(102) A blowing-out mode door (not illustrated) is disposed in each of the plurality of opening holes. The blowing-out mode door opens and closes each of the opening holes. The blowing-out mode door is driven by a blowing-out mode door electric actuator. The operation of the blowing-out mode door electric actuator is controlled by a control signal output from the control device **60**.

(103) Therefore, in the indoor air conditioning unit **30**, it is possible to change the place in the vehicle interior to which the conditioned air is to be blown out by switching the opening hole to be opened by the blowing-out mode door.

(104) Next, the outline of an electric control unit of the present embodiment will be described. The control device **60** includes a known microcomputer including a CPU, a ROM, a RAM, and the like, and peripheral circuits thereof. The control device **60** performs various calculations and processing on the basis of control programs stored in the ROM, and controls the operations of the various control target devices **11**, **14a** to **14c**, **15a**, **15b**, **32** to **34**, **41**, **51a**, **51b**, **52a**, **52b**, **54**, and the like connected to the output side thereof.

(105) As illustrated in the block diagram of FIG. 2, an inside air temperature sensor **61**, an outside air temperature sensor **62**, a solar radiation sensor **63**, a first refrigerant temperature sensor **64a** to a third refrigerant temperature sensor **64c**, an evaporator temperature sensor **64f**, a first refrigerant pressure sensor **65a** to a third refrigerant pressure sensor **65c**, a high-temperature side heat medium temperature sensor **66a**, a first low-temperature side heat medium temperature sensor **67a** to a third low-temperature side heat medium temperature sensor **67c**, a battery temperature sensor **68**, a conditioned air temperature sensor **69a**, an intake air temperature sensor **69b**, and the like are connected to the input side of the control device **60**. Then, detection signals of these sensor groups are input to the control device **60**.

(106) The inside air temperature sensor **61** is an inside air temperature detector that detects a vehicle interior temperature (inside air temperature)  $T_i$ . The outside air temperature sensor **62** is an outside air temperature detector that detects a vehicle exterior temperature (outside air temperature)  $T_{am}$ . The solar radiation sensor **63** is a solar radiation amount detector that detects a solar radiation amount  $A_s$  with which the vehicle interior is irradiated.

(107) The first refrigerant temperature sensor **64a** is a first refrigerant temperature detector that detects a first refrigerant temperature  $TR_1$  that is the temperature of the refrigerant discharged from the compressor **11**. The second refrigerant temperature sensor **64b** is a second refrigerant

temperature detector that detects a second refrigerant temperature TR2 that is the temperature of the refrigerant flowing out of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12**. The third refrigerant temperature sensor **64c** is a third refrigerant temperature detector that detects a third refrigerant temperature TR3 that is the temperature of the refrigerant flowing out of the outdoor heat exchanger **16**.

(108) The evaporator temperature sensor **64f** is an evaporator temperature detector that detects a refrigerant evaporating temperature (evaporator temperature) T<sub>efin</sub> in the indoor evaporator **18**. Specifically, the evaporator temperature sensor **64f** of the present embodiment detects a heat exchange fin temperature of the indoor evaporator **18**.

(109) The first refrigerant pressure sensor **65a** is a first refrigerant pressure detector that detects a first refrigerant pressure PR1 that is the pressure of the refrigerant discharged from the compressor **11**. The second refrigerant pressure sensor **65b** is a second refrigerant pressure detector that detects a second refrigerant pressure PR2 that is the pressure of the refrigerant flowing out of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12**. The third refrigerant pressure sensor **65c** is a third refrigerant pressure detector that detects a third refrigerant pressure PR3 that is the pressure of the refrigerant flowing out of the outdoor heat exchanger **16**.

(110) The high-temperature side heat medium temperature sensor **66a** is a high-temperature side heat medium temperature detector that detects a high-temperature side heat medium temperature TWH that is the temperature of the high-temperature side heat medium to flow into the heater core **42**.

(111) The first low-temperature side heat medium temperature sensor **67a** is a first low-temperature side heat medium temperature detector that detects a first low-temperature side heat medium temperature TWL1 that is the temperature of the low-temperature side heat medium that has been pressure-fed from the first low-temperature side pump **51a** and flows into the cooling water passage **80a** of the battery **80**.

(112) The second low-temperature side heat medium temperature sensor **67b** is a second low-temperature side heat medium temperature detector that detects a second low-temperature side heat medium temperature TWL2 that is the temperature of the low-temperature side heat medium that has been pressure-fed from the second low-temperature side pump **51b** and flows into the cooling water passage **81a** of the strong current device **81**.

(113) The third low-temperature side heat medium temperature sensor **67c** is a chiller inlet side heat medium temperature detector that detects an inlet side heat medium temperature TWin that is the temperature of the low-temperature side heat medium to flow into the heat medium passage **20b** of the chiller **20**.

(114) The battery temperature sensor **68** is a battery temperature detector that detects a battery temperature TB (i.e., the temperature of the battery **80**). The battery temperature sensor **68** of the present embodiment includes a plurality of temperature sensors, and detects temperatures at a plurality of places in the battery **80**. Therefore, the control device **60** can detect a temperature difference between the respective battery cells forming the battery **80**. As the battery temperature TB, an average of the detected values of the plurality of temperature sensors is adopted.

(115) The conditioned air temperature sensor **69a** is a conditioned air temperature detector that detects a ventilation air temperature TAV that is the temperature of the ventilation air to be blown into the vehicle interior from the mixing space **36**. The intake air temperature sensor **69b** is an intake air temperature detector that detects an intake air temperature TAin that is the temperature of the ventilation air to flow into the heater core **42**.

(116) As illustrated in FIG. 2, an air conditioning operation panel **70** is connected to the input side of the control device **60**. The air conditioning operation panel **70** is disposed near the instrument panel in the front part of the vehicle interior. Operation signals from various operation switches provided on the air conditioning operation panel **70** are input to the control device **60**.

(117) Specific examples of the various operation switches provided on the air conditioning

operation panel **70** include an auto switch, an air conditioner switch, an air volume setting switch, and a temperature setting switch.

(118) The auto switch is an operation part for a user to set or cancel the automatic control operation of vehicle interior air conditioning. The air conditioner switch is an operation part for a user to request the indoor evaporator **18** to cool the ventilation air. The air volume setting switch is an operation part for a user to manually set the air volume of the indoor blower **32**. The temperature setting switch is an operation part for a user to set a set temperature  $T_{set}$  of the vehicle interior.

(119) In the control device **60** of the present embodiment, control units for controlling the various control target devices connected to the output sides of the control units are integrally formed. In the control device **60**, a configuration (hardware and software) for controlling the operation of each of the control target devices constitutes the control unit that controls the operation of each of the control target devices.

(120) For example, in the control device **60**, a configuration for controlling the refrigerant discharge capability of the compressor **11** (specifically, the number of rotation of the compressor **11**) constitutes a discharge capability control unit **60a**. A configuration for controlling the blowing capability of the indoor blower **32** (specifically, the number of rotation of the indoor blower **32**) constitutes a blowing capability control unit **60b**. A configuration for controlling the heating capability of the electric heater **54** constitutes a heat generation capability control unit **60c**.

(121) Next, the operation of the air conditioner **1** having the above configuration will be described. As described above, the air conditioner **1** can perform air conditioning of the vehicle interior and adjust the temperatures of the in-vehicle devices. Therefore, in the air conditioner **1**, various operation modes are executed by switching the circuit configuration of the heat pump cycle **10** and the circuit configuration of the low-temperature side heat medium circuit **50**.

(122) The operation modes of the air conditioner **1** include an operation mode for air conditioning the vehicle interior and an operation mode for adjusting the temperatures of the in-vehicle devices. In the air conditioner **1**, the air conditioning operation mode and the temperature adjusting operation mode can be appropriately combined and executed.

(123) Therefore, in the air conditioner **1**, the vehicle interior can only be air conditioned without the temperatures of the in-vehicle devices adjusted. In addition, the temperatures of the in-vehicle devices can be adjusted without the vehicle interior air conditioned. In addition, the vehicle interior can be air conditioned, and simultaneously the temperatures of the in-vehicle devices can be adjusted.

(124) First, the air conditioning operation mode will be described. The air conditioning operation mode in the present embodiment includes (A1) an air-cooling mode, (A2) a series dehumidifying-heating mode, (A3) a parallel dehumidifying-heating mode, and (A4) a heating mode. (A1) The air-cooling mode is an operation mode for cooling the vehicle interior by cooling the ventilation air and blowing out it into the vehicle interior. (A2) The series dehumidifying-heating mode is an operation mode for dehumidifying and heating the vehicle interior by reheating the cooled and dehumidified ventilation air and blowing out it into the vehicle interior. (A3) The parallel dehumidifying-heating mode is an operation mode for dehumidifying and heating the vehicle interior by reheating the cooled and dehumidified ventilation air with higher heating capability than that in the series dehumidifying-heating mode and blowing out it into the vehicle interior. (A4) The heating mode is an operation mode for heating the vehicle interior by heating the ventilation air and blowing out it into the vehicle interior.

(125) Switching between the air conditioning operation modes is performed with an air conditioning control program stored in the control device **60** executed. The air conditioning control program is executed when the auto switch on the operation panel **70** is turned on and the automatic control operation of the in-vehicle air conditioning is set.

(126) In the main routine of the air conditioning control program, the detection signals of the sensor groups and the operation signals of the operation switches on the operation panel **70**, which

have been described above, are read at predetermined periods. Then, based on the values of the read detection signals and operation signals, a target blowing-out temperature TAO, which is a target temperature of the air to be blown out into the vehicle interior, is calculated.

(127) More specifically, the target blowing-out temperature TAO is calculated using the following mathematical expression F1.

$$TAO = K_{set} \times T_{set} - K_r \times T_r - K_{am} \times T_{am} - K_s \times A_s + C \quad (F1)$$

(128) Where,  $T_{set}$  is a vehicle interior set temperature set by the temperature setting switch on the operation panel **70**.  $T_r$  is the inside air temperature detected by the inside air temperature sensor **61**.  $T_{am}$  is the outside air temperature detected by the outside air temperature sensor **62**.  $A_s$  is the solar radiation amount detected by the solar radiation sensor **63**.  $K_{set}$ ,  $K_r$ ,  $K_{am}$ , and  $K_s$  are control gains, and  $C$  is a constant for correction.

(129) When the target blowing-out temperature TAO is lower than a predetermined air-cooling target heat medium temperature KTAO1 in a state in which the air conditioner switch on the operation panel **70** is turned on, the air conditioning operation mode is switched to the air-cooling mode.

(130) When the target blowing-out temperature TAO is equal to or higher than the air-cooling target heat medium temperature KTAO1 and the outside air temperature  $T_{am}$  is higher than a predetermined dehumidifying-heating target heat medium temperature KTAO2 in a state in which the air conditioner switch is turned on, the air conditioning operation mode is switched to the series dehumidifying-heating mode.

(131) When the target blowing-out temperature TAO is equal to or higher than the air-cooling target heat medium temperature KTAO1 and the outside air temperature  $T_{am}$  is equal to or lower than the dehumidifying-heating target heat medium temperature KTAO2 in a state in which the air conditioner switch is turned on, the air conditioning operation mode is switched to the parallel dehumidifying-heating mode.

(132) When the air-cooling switch of the air conditioner switch is not turned on, the air conditioning operation mode is switched to the heating mode.

(133) Therefore, the air-cooling mode is executed mainly in a case where the outside air temperature is relatively high like in summer. The series dehumidifying-heating mode is executed mainly in spring or autumn. The parallel dehumidifying-heating mode is executed mainly in a case where the ventilation air needs to be heated with higher heating capability than in the series dehumidifying-heating mode, like in early spring or late autumn. The heating mode is executed mainly when the outside air temperature is low in winter. Hereinafter, detailed operation of each air conditioning operation mode will be described.

(134) (A1) Air-Cooling Mode

(135) In the air-cooling mode, the control device **60** brings the heating expansion valve **14a** into a fully opened state and brings the air-cooling expansion valve **14b** into a throttled state in which a refrigerant pressure-reducing action is exerted. The cooling expansion valve **14c** is controlled according to the temperature adjusting operation mode. The same applies to the other air conditioning operation modes. In addition, the control device **60** closes the dehumidifying on-off valve **15a** and closes the heating on-off valve **15b**.

(136) Therefore, in the heat pump cycle **10** in the air-cooling mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the heating expansion valve **14a** in a fully opened state, the outdoor heat exchanger **16**, the air-cooling expansion valve **14b**, the indoor evaporator **18**, the accumulator **21**, and the suction port of the compressor **11**.

(137) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the number of rotation of the compressor **11** such that the evaporator temperature  $T_{efin}$  detected by the evaporator temperature sensor **64f** approaches a target evaporator temperature TEO. The target evaporator temperature

TEO is determined based on the target blowing-out temperature TAO and with reference to a control map stored in advance in the control device **60**.

(138) The control device **60** controls the throttle opening degree of the air-cooling expansion valve **14b** such that the super-cooling degree SC3 of the refrigerant to flow into the air-cooling expansion valve **14b** approaches a target super-cooling degree SCO3.

(139) The super-cooling degree SC3 of the refrigerant to flow into the air-cooling expansion valve **14b** is calculated using the third refrigerant temperature TR3 detected by the third refrigerant temperature sensor **64c** and the third refrigerant pressure PR3 detected by the third refrigerant pressure sensor **65c**. The target super-cooling degree SCO3 is determined based on the outside air temperature Tam and with reference to the control map stored in advance in the control device **60** such that a coefficient of performance (COP) of the cycle approaches the maximum value.

(140) In addition, the control device **60** controls the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability.

(141) Therefore, in the high-temperature side heat medium circuit **40** in the air-cooling mode, the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the heater core **42**, and the suction port of the high-temperature side pump **41**.

(142) The control device **60** determines the number of rotation of the indoor blower **32** so as to approach a target blowing capability determined by the blowing capability control unit **60b**. Therefore, the blowing capability control unit **60b** is a target blowing capability determination unit. More specifically, the blowing capability control unit **60b** determines the number of rotation thereof on the basis of the target blowing-out temperature TAO and with reference to the control map stored in advance in the control device **60**.

(143) In the control map for the indoor blower **32**, it is determined such that, when the target blowing-out temperature TAO is in an extremely low temperature range (i.e., at the time of the maximum air-cooling) or an extremely high temperature range (i.e., at the time of the maximum heating), the blowing capability is maximum. Furthermore, it is determined such that, as the target blowing-out temperature TAO moves from the extremely low temperature range or the extremely high temperature range to an intermediate temperature range, the blowing capability is reduced. Then, it is determined such that, when the target blowing-out temperature TAO is in the intermediate temperature range, the blowing capability is minimum.

(144) The control device **60** controls the opening degree of the air mix door **34** such that the ventilation air temperature TAV detected by the conditioned air temperature sensor **69a** approaches the target blown-out temperature TAO. In addition, the control device **60** determines the opening/closing operation of the blowing-out mode door on the basis of the target blowing-out temperature TAO and with reference to the control map stored in advance in the control device **60**.

(145) Therefore, in the heat pump cycle **10** in the air-cooling mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** and the outdoor heat exchanger **16** are caused to function as condensers (in other words, radiators) that dissipate the heat of the refrigerant and condense the refrigerant, and the indoor evaporator **18** is caused to function as an evaporator that evaporates the refrigerant.

(146) As a result, in the heat pump cycle **10** in the air-cooling mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the ventilation air is cooled by the indoor evaporator **18**.

(147) In the high-temperature side heat medium circuit **40** of the air-cooling mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42**.

(148) In the indoor air conditioning unit **30** in the air-cooling mode, the ventilation air blown from the indoor blower **32** is cooled by the indoor evaporator **18**. The temperature of the ventilation air cooled by the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose

temperature has been adjusted is blown into the vehicle interior, the air-cooling of the vehicle interior is realized.

(149) (A2) Series Dehumidifying-Heating Mode

(150) In the series dehumidifying-heating mode, the control device **60** brings the heating expansion valve **14a** into a throttled state, and brings the air-cooling expansion valve **14b** into a throttled state. In addition, the control device **60** closes the dehumidifying on-off valve **15a** and closes the heating on-off valve **15b**.

(151) Therefore, in the heat pump cycle **10** in the series dehumidifying-heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the air-cooling expansion valve **14b**, the indoor evaporator **18**, the accumulator **21**, and the suction port of the compressor **11**.

(152) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the compressor **11** similarly to the air-cooling mode.

(153) Based on the target blowing-out temperature TAO and with reference to the control map stored in advance in the control device **60**, the control device **60** determines the throttle opening degree of the heating expansion valve **14a** and the throttle opening degree of the air-cooling expansion valve **14b** such that the COP approaches the maximum value. In the control map for the series dehumidifying-heating mode, it is determined such that, as the target blowing-out temperature TAO rises, the throttle opening degree of the heating expansion valve **14a** is reduced and the throttle opening degree of the air-cooling expansion valve **14b** is increased.

(154) Similarly to the air-cooling mode, the control device **60** controls the operations of the high-temperature side pump **41** and the like of the high-temperature side heat medium circuit **40**. Similarly to the air-cooling mode, the control device **60** controls the operations of the indoor blower **32** and the like of the indoor air conditioning unit **30**.

(155) Therefore, in the heat pump cycle **10** in the series dehumidifying-heating mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the indoor evaporator **18** is caused to function as an evaporator. Furthermore, when the saturation temperature of the refrigerant in the outdoor heat exchanger **16** is higher than the outside air temperature Tam, the outdoor heat exchanger **16** is caused to function as a condenser. When the saturation temperature of the refrigerant in the outdoor heat exchanger **16** is lower than the outside air temperature Tam, the outdoor heat exchanger **16** is caused to function as an evaporator.

(156) As a result, in heat pump cycle **10** in the series dehumidifying-heating mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the ventilation air is cooled by the indoor evaporator **18**.

(157) In the high-temperature side heat medium circuit **40** in the series dehumidifying-heating mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42**.

(158) In the indoor air conditioning unit **30** in the series dehumidifying-heating mode, the ventilation air blown from the indoor blower **32** is cooled and dehumidified by the indoor evaporator **18**. The temperature of the ventilation air cooled and dehumidified by the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose temperature has been adjusted is blown out into the vehicle interior, the dehumidification and heating of the vehicle interior is realized.

(159) Furthermore, in the heat pump cycle **10** in the series dehumidifying-heating mode, as the target blowing-out temperature TAO rises, the throttle opening degree of the heating expansion valve **14a** is reduced and the throttle opening degree of the air-cooling expansion valve **14b** is

increased. According to this, the heating capability for the ventilation air in the heater core **42** can be improved as the target blowing-out temperature TAO rises.

(160) More specifically, when the saturation temperature of the refrigerant in the outdoor heat exchanger **16** is higher than the outside air temperature Tam, the temperature difference between the saturation temperature of the refrigerant in the outdoor heat exchanger **16** and the outside air temperature Tam can be reduced as the target blowing-out temperature TAO rises. Therefore, as the target blowing-out temperature TAO rises, the amount of heat to be dissipated from the refrigerant to the outside air in the outdoor heat exchanger **16** can be reduced, and the amount of heat to be dissipated from the refrigerant to the heat medium in the water-refrigerant heat exchanger **12** can be increased.

(161) When the saturation temperature of the refrigerant in the outdoor heat exchanger **16** is lower than the outside air temperature Tam, the temperature difference between the outside air temperature Tam and the refrigerant in the outdoor heat exchanger **16** can be increased as the target blowing-out temperature TAO rises. Therefore, as the target blowing-out temperature TAO rises, the amount of heat to be absorbed by the refrigerant from the outside air in the outdoor heat exchanger **16** can be increased, and the amount of heat to be dissipated from the refrigerant to the heat medium in the water-refrigerant heat exchanger **12** can be increased.

(162) As a result, in the series dehumidifying-heating mode, the heating capability for the ventilation air in the heater core **42** can be improved as the target blowing-out temperature TAO rises.

(163) (A3) Parallel Dehumidifying-Heating Mode

(164) In the parallel dehumidifying-heating mode, the control device **60** brings the heating expansion valve **14a** into a throttled state, and brings the air-cooling expansion valve **14b** into a throttled state. In addition, the control device **60** opens the dehumidifying on-off valve **15a** and opens the heating on-off valve **15b**.

(165) Therefore, in the heat pump cycle **10** in the parallel dehumidifying-heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the heating passage **22b**, the accumulator **21**, and the suction port of the compressor **11**. At the same time, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the dehumidifying passage **22a**, the air-cooling expansion valve **14b**, the indoor evaporator **18**, the accumulator **21**, and the suction port of the compressor **11**. That is, refrigerant circuits are switched to, in which the outdoor heat exchanger **16** and the indoor evaporator **18** are connected in parallel for the flow of the refrigerant.

(166) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the number of rotation of the compressor **11** such that the first refrigerant pressure PR1 detected by the first refrigerant pressure sensor **65a** approaches a target condensation pressure PDO.

(167) The target condensation pressure PDO is determined such that the high-temperature side heat medium temperature TWH detected by the high-temperature side heat medium temperature sensor **66a** approaches a predetermined target high-temperature side heat medium temperature TWHO (in the present embodiment, about 50° C.). The target high-temperature side heat medium temperature TWHO is set such that, by the heater core **42** constituting the heating part, the temperature of the ventilation air can be raised to a temperature at which sufficient heating of the vehicle interior can be realized.

(168) Based on the target blowing-out temperature TAO and with reference to the control map stored in advance in the control device **60**, the control device **60** determines the throttle opening degree of the heating expansion valve **14a** and the throttle opening degree of the air-cooling

expansion valve **14b** such that the COP approaches the maximum value. In the control map in the parallel dehumidifying-heating mode, it is determined such that, as the target blowing-out temperature TAO rises, the throttle opening degree of the heating expansion valve **14a** is reduced and the throttle opening degree of the air-cooling expansion valve **14b** is increased.

(169) Similarly to the air-cooling mode, the control device **60** controls the operations of the high-temperature side pump **41** and the like of the high-temperature side heat medium circuit **40**.

Similarly to the air-cooling mode, the control device **60** controls the operations of the indoor blower **32** and the like of the indoor air conditioning unit **30**.

(170) Therefore, in the heat pump cycle **10** in the parallel dehumidifying-heating mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the outdoor heat exchanger **16** and the indoor evaporator **18** are caused to function as evaporators. As a result, in heat pump cycle **10** in the parallel dehumidifying-heating mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the ventilation air is cooled by the indoor evaporator **18**.

(171) In the high-temperature side heat medium circuit **40** in the parallel dehumidifying-heating mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42**.

(172) In the indoor air conditioning unit **30** in the parallel dehumidifying-heating mode, the ventilation air blown from the indoor blower **32** is cooled and dehumidified by the indoor evaporator **18**. The temperature of the ventilation air cooled and dehumidified by the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose temperature has been adjusted is blown out into the vehicle interior, the dehumidification and heating of the vehicle interior is realized.

(173) Furthermore, in the heat pump cycle **10** in the parallel dehumidifying-heating mode, the throttle opening degree of the heating expansion valve **14a** can be made smaller than the throttle opening degree of the air-cooling expansion valve **14b**. According to this, the refrigerant evaporating temperature in the outdoor heat exchanger **16** can be lowered to a temperature lower than the refrigerant evaporating temperature in the indoor evaporator **18**.

(174) Therefore, in the parallel dehumidifying-heating mode, the amount of heat to be absorbed by the refrigerant from the outside air in the outdoor heat exchanger **16** can be increased more than in the series dehumidifying-heating mode, and the amount of heat to be dissipated from the refrigerant to the heat medium in the water-refrigerant heat exchanger **12** can be increased. As a result, in the parallel dehumidifying-heating mode, the heating capability for the ventilation air in the heater core **42** can be improved more than in the series dehumidifying-heating mode.

(175) (A4) Heating Mode

(176) In the heating mode, the control device **60** brings the heating expansion valve **14a** into a throttled state, and brings the air-cooling expansion valve **14b** into a fully closed state. In addition, the control device **60** closes the dehumidifying on-off valve **15a** and opens the heating on-off valve **15b**.

(177) Therefore, in the heat pump cycle **10** in the heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the heating passage **22b**, the accumulator **21**, and the suction port of the compressor **11**.

(178) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the compressor **11** similarly to the parallel dehumidifying-heating mode.

(179) The control device **60** controls the throttle opening degree of the heating expansion valve **14a** such that the super-cooling degree SC2 of the refrigerant to flow into the heating expansion valve

**14a** approaches a target super-cooling degree **SCO2**.

(180) The super-cooling degree **SC2** of the refrigerant to flow into the heating expansion valve **14a** is calculated using the second refrigerant temperature **TR2** detected by the second refrigerant temperature sensor **64b** and the second refrigerant pressure **PR2** detected by the second refrigerant pressure sensor **65b**. Based on the second refrigerant temperature **TR2** and with reference to the control map stored in advance in the control device **60**, the target super-cooling degree **SCO2** is determined such that the COP approaches the maximum value.

(181) Similarly to the air-cooling mode, the control device **60** controls the operations of the high-temperature side pump **41** and the like of the high-temperature side heat medium circuit **40**.

Similarly to the air-cooling mode, the control device **60** controls the operations of the indoor blower **32** and the like of the indoor air conditioning unit **30**.

(182) Therefore, in the heat pump cycle **10** in the heating mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the outdoor heat exchanger **16** is caused to function as an evaporator. As a result, in the heat pump cycle **10** in the heating mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**.

(183) In the high-temperature side heat medium circuit **40** in the heating mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42**.

(184) In the indoor air conditioning unit **30** in the heating mode, the ventilation air blown from the indoor blower **32** passes through the indoor evaporator **18**. The temperature of the ventilation air having passed through the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature **TAO** by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose temperature has been adjusted is blown into the vehicle interior, the heating of the vehicle interior is realized.

(185) Next, the temperature adjusting operation mode will be described. In the temperature adjusting operation mode, the temperatures of the battery **80** and the strong current device **81**, the temperatures of which are to be adjusted, are adjusted.

(186) In the present embodiment, the appropriate temperature zone of the battery is different from the appropriate temperature zone of the strong current device **81**, as described above. Therefore, in the temperature adjusting operation mode, a battery operation mode for adjusting the temperature of the battery **80** and a strong current device operation mode for adjusting the temperature of the strong current device **81** are executed in combination.

(187) The battery operation mode includes (B1) a battery warm-up mode, (B2) a battery temperature equalization mode, and (B3) a battery cooling mode. (B1) The battery warm-up mode is an operation mode in which the battery is warmed up by the low-temperature side heat medium heated by the electric heater **54**. (B2) The battery temperature equalization mode is an operation mode in which the temperatures of the respective battery cells forming the battery **80** are equalized. (B3) The battery cooling mode is an operation mode in which the battery **80** is cooled by the heat medium cooled by the chiller **20**.

(188) The strong current device operation mode includes (C1) a strong current device warm-up mode, (C2) a strong current device waste heat recovery mode, and (C3) a strong current device cooling mode. (C1) The strong current device warm-up mode is an operation mode in which the strong current device **81** is warmed up by the low-temperature side heat medium heated by the electric heater **54**. (C2) The strong current device waste heat recovery mode is an operation mode in which, in the chiller **20**, the heat generated by the strong current device **81** is absorbed by the low-pressure refrigerant. (C3) The strong current device cooling mode is an operation mode in which the strong current device **81** is cooled by the heat medium cooled by the low-temperature side radiator **56**.

(189) Switching between the temperature adjusting operation modes is performed by executing a temperature adjusting control program stored in the control device **60**. The temperature adjusting

control program is also executed when the vehicle system is activated, when the battery **80** is charged from an external power supply, or the like, regardless of whether a user requests air conditioning of the vehicle interior.

(190) In the temperature adjusting control program, the detection signals of the above-described sensor groups are read at predetermined periods. Then, the temperature adjusting operation mode is switched based on the read detection signal.

(191) More specifically, in the temperature adjusting control program, the battery operation mode is switched based on the battery temperature TB detected by the battery temperature sensor **68** and with reference to the control map stored in advance in the control device **60**. In the control map, as the battery temperature TB rises, switching is performed in the order of (B1) the battery warm-up mode, (B2) the battery temperature equalization mode, and (B3) the battery cooling mode.

(192) In addition, in the temperature adjusting control program, the strong current device operation mode is switched based on the second low-temperature side heat medium temperature TWL2 detected by the second low-temperature side heat medium temperature sensor **67b** and with reference to the control map stored in advance in the control device **60**. In the control map, as the second low-temperature side heat medium temperature TWL2 rises, switching is performed in the order of (C1) the strong current device warm-up mode, (C2) the strong current device waste heat recovery mode, and (C3) the strong current device cooling mode.

(193) However, when the battery operation mode and the strong current device operation mode cannot be simultaneously executed due to convenience of the circuit configuration of the low-temperature side heat medium circuit **50** or the like, priority is given to the battery operation mode. For example, when (B3) the battery cooling mode and (C1) the strong current device warm-up mode are simultaneously selected, (C1) the strong current device warm-up mode is not executed, but (B3) the battery cooling mode is executed. Hereinafter, detailed operation of each temperature adjusting operation mode will be described.

(194) (B1) Battery Warm-Up Mode

(195) In the battery warm-up mode, the control device **60** brings the cooling expansion valve **14c** into a fully closed state. Therefore, in the battery warm-up mode, the refrigerant never flows into the chiller **20**.

(196) In addition, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** is caused to flow out to the electric heater **54** side. In addition, the control device **60** controls the operation of the electric heater **54** so as to exert predetermined heating capability. In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability.

(197) Therefore, in the low-temperature side heat medium circuit **50** in the battery warm-up mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the cooling water passage **80a** of the battery **80**, the electric heater **54**, the heat medium passage **20b** of the chiller **20**, and the suction port of the first low-temperature side pump **51a**.

(198) Therefore, in the low-temperature side heat medium circuit **50** in the battery warm-up mode, the low-temperature side heat medium heated by the electric heater **54** is sucked into the first low-temperature side pump **51a**. The low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** flows into the cooling water passage **80a** of the battery **80** and dissipates heat to each battery cell of the battery **80**. As a result, the battery **80** is warmed up.

(199) (B2) Battery Temperature Equalization Mode

(200) In the battery temperature equalization mode, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** is caused to flow out to the battery bypass passage **55a** side. In addition, the control device **60** controls the operation of the first low-

temperature side pump **51a** so as to exert predetermined pressure-feeding capability.

(201) Therefore, in the low-temperature side heat medium circuit **50** in the battery temperature equalization mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the cooling water passage **80a** of the battery **80**, the battery bypass passage **55a**, and the suction port of the high-temperature side pump **41**.

(202) Therefore, in the low-temperature side heat medium circuit **50** in the battery temperature equalization mode, the temperatures of the respective battery cells forming the battery **80** are equalized when the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** flows through the cooling water passage **80a** of the battery **80**.

(203) Here, the battery temperature equalization mode is an operation mode aimed to equalize the temperatures of the respective battery cells of the battery **80**. Therefore, even if the battery temperature equalization mode is selected based on the battery temperature **TB**, the battery temperature equalization mode may be stopped when the temperature equalization of the battery **80** is not required. The case where the temperature equalization of the battery **80** is not required corresponds to a case where a temperature difference  $\Delta TB$  between the temperatures of the respective battery cells is smaller than a predetermined target cell temperature difference  $\Delta KTB$ , or the like.

(204) (B3) Battery Cooling Mode

(205) The battery cooling mode is an operation mode in which the battery **80** is cooled by the heat medium cooled by the chiller **20**. Therefore, when the compressor **11** of the heat pump cycle **10** is operating as during air conditioning, the control device **60** brings the cooling expansion valve **14c** of the heat pump cycle **10** into a throttled state. Furthermore, when the air conditioning operation mode is (A4) the heating mode, the control device **60** opens the dehumidifying on-off valve **15a** and opens the heating on-off valve **15b**.

(206) Therefore, in the heat pump cycle **10** in the battery cooling mode, the low-pressure refrigerant whose pressure has been reduced by the cooling expansion valve **14c** flows into the refrigerant passage **20a** of the chiller **20**. The refrigerant flowing out of the refrigerant passage **20a** of the chiller **20** flows into the accumulator **21** via the sixth refrigerant joint part **13f** and the fourth refrigerant joint part **13d**.

(207) Furthermore, when the battery cooling mode is executed during the execution of (A4) the heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the heating passage **22b**, the accumulator **21**, and the suction port of the compressor **11**. At the same time, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the dehumidifying passage **22a**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**. That is, refrigerant circuits are switched to, in which the outdoor heat exchanger **16** and the chiller **20** are connected in parallel for the flow of the refrigerant.

(208) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the first low-temperature side heat medium temperature **TWL1** detected by the first low-temperature side heat medium temperature sensor **67a** approaches a battery target temperature **TWLO1**. The battery target temperature **TWLO1** is set such that the battery **80** can be appropriately operated.

(209) In addition, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** is caused to flow out to the electric heater **54** side. In addition,

the control device **60** stops the supply of electric power to the electric heater **54**. In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability.

(210) Therefore, in the low-temperature side heat medium circuit **50** in the battery cooling mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the cooling water passage **80a** of the battery **80**, the electric heater **54**, the heat medium passage **20b** of the chiller **20**, and the suction port of the first low-temperature side pump **51a**.

(211) Therefore, in the heat pump cycle **10** in the battery cooling mode during air conditioning, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** or the outdoor heat exchanger **16** is caused to function as a condenser and at least the chiller **20** is caused to function as an evaporator. As a result, in the heat pump cycle **10** in the battery cooling mode during air conditioning, the low-temperature side heat medium is cooled by the chiller **20**.

(212) In the low-temperature side heat medium circuit **50**, the low-temperature side heat medium cooled by the chiller **20** is sucked into the first low-temperature side pump **51a**. The low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** flows into the cooling water passage **80a** of the battery **80**, and absorbs heat from the respective battery cells of the battery **80**. As a result, the battery **80** is cooled.

(213) Next, the battery cooling mode during non-air conditioning will be described. In the battery cooling mode during non-air conditioning, the control device **60** brings the heating expansion valve **14a** into a fully opened state, brings the air-cooling expansion valve **14b** into a fully closed state, and brings the cooling expansion valve **14c** into a throttled state. In addition, the control device **60** closes the dehumidifying on-off valve **15a** and closes the heating on-off valve **15b**.

(214) Therefore, in the heat pump cycle **10** in the battery cooling mode during non-air conditioning, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the heating expansion valve **14a** in a fully opened state, the outdoor heat exchanger **16**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**.

(215) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the number of rotation of the compressor **11** so as to exert predetermined battery cooling mode discharge capability. In addition, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the first low-temperature side heat medium temperature **TWL1** approaches the battery target temperature **TWLO1**.

(216) Similarly to the battery cooling mode during air conditioning, the control device **60** controls the operations of the first low-temperature side three-way valve **52a** and the like. Therefore, in the low-temperature side heat medium circuit **50** in the battery cooling mode during non-air conditioning, a circuit is switched to, in which the low-temperature side heat medium circulates in the same order as in the battery cooling mode during air conditioning.

(217) Therefore, in the heat pump cycle **10** in the battery cooling mode during non-air conditioning, a vapor compression type refrigeration cycle is formed in which the outdoor heat exchanger **16** is caused to function as a condenser and the chiller **20** is caused to function as an evaporator. As a result, in the heat pump cycle **10** in the battery cooling mode during non-air conditioning, the low-temperature side heat medium is cooled by the chiller **20**.

(218) In the low-temperature side heat medium circuit **50**, the battery **80** is cooled similarly to the battery cooling mode during air conditioning.

(219) (C1) Strong Current Device Warm-Up Mode

(220) In the strong current device warm-up mode, the control device **60** brings the cooling expansion valve **14c** into a fully closed state. Therefore, in the strong current device warm-up mode, the refrigerant never flows into the chiller **20**.

(221) In addition, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** is caused to flow out to the electric heater **54** side. In addition, the control device **60** controls the operation of the electric heater **54** so as to exert predetermined heating capability. In addition, the control device **60** controls the operation of the second low-temperature side pump **51b** so as to exert predetermined pressure-feeding capability.

(222) Therefore, in the low-temperature side heat medium circuit **50** in the strong current device warm-up mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the electric heater **54**, the heat medium passage **20b** of the chiller **20**, and the suction port of the second low-temperature side pump **51b**.

(223) Therefore, in the low-temperature side heat medium circuit **50** in the strong current device warm-up mode, the low-temperature side heat medium heated by the electric heater **54** is sucked into the second low-temperature side pump **51b**. The low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** flows into the cooling water passage **81a** of the strong current device **81** and dissipates heat to the strong current device **81**. As a result, the strong current device **81** is warmed up.

(224) (C1) Strong Current Device Waste Heat Recovery Mode

(225) The strong current device waste heat recovery mode is an operation mode in which waste heat from the strong current device **81** is used as a heating source for the ventilation air. Therefore, the strong current device waste heat recovery mode is executed during air conditioning.

(226) In the strong current device waste heat recovery mode, the cooling expansion valve **14c** of the heat pump cycle **10** is brought into a throttled state. Furthermore, when the air conditioning operation mode is (A4) the heating mode, the control device **60** opens the dehumidifying on-off valve **15a** and opens the heating on-off valve **15b**.

(227) Therefore, in the heat pump cycle **10** in the strong current device waste heat recovery mode, the low-pressure refrigerant whose pressure has been reduced by the cooling expansion valve **14c** flows into the refrigerant passage **20a** of the chiller **20**. The refrigerant flowing out of the refrigerant passage **20a** of the chiller **20** flows into the accumulator **21** via the sixth refrigerant joint part **13f** and the fourth refrigerant joint part **13d**.

(228) Furthermore, when the strong current device waste heat recovery mode is executed during the execution of (A4) the heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the heating passage **22b**, the accumulator **21**, and the suction port of the compressor **11**. At the same time, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the dehumidifying passage **22a**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**. That is, refrigerant circuits are switched to, in which the outdoor heat exchanger **16** and the chiller **20** are connected in parallel for the flow of the refrigerant.

(229) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the second low-temperature side heat medium temperature TWL2 approaches a strong current device target temperature TWLO2. The strong current device target temperature TWLO2 is set such that the strong current device **81** can be appropriately operated.

(230) In addition, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** is caused to flow out to the electric heater **54**

side. In addition, the control device **60** stops the supply of electric power to the electric heater **54**. In addition, the control device **60** controls the operation of the second low-temperature side pump **51b** so as to exert predetermined pressure-feeding capability.

(231) Therefore, in the low-temperature side heat medium circuit **50** in the strong current device waste heat recovery mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the electric heater **54**, the heat medium passage **20b** of the chiller **20**, and the suction port of the second low-temperature side pump **51b**.

(232) Therefore, in the heat pump cycle **10** in the strong current device waste heat recovery mode during air conditioning, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** or the outdoor heat exchanger **16** is caused to function as a condenser and at least the chiller **20** is caused to function as an evaporator. As a result, in the heat pump cycle **10** in the strong current device waste heat recovery mode during air conditioning, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, in the chiller **20**, the heat of the low-temperature side heat medium (i.e., waste heat from the strong current device **81**) is absorbed by the low-pressure refrigerant.

(233) In the low-temperature side heat medium circuit **50**, the low-temperature side heat medium cooled by the chiller **20** is sucked into the second low-temperature side pump **51b**. The low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** flows into the cooling water passage **81a** of the strong current device **81** and absorbs waste heat from the strong current device **81**.

(234) Here, the strong current device waste heat recovery mode is an operation mode aimed to effectively use the waste heat from the strong current device **81** as a heat source for heating or the like. Therefore, even if the strong current device waste heat recovery mode is selected based on the second low-temperature side heat medium temperature **TWL2**, the strong current device waste heat recovery mode may be stopped when waste heat recovery is not required.

(235) The case where waste heat recovery is not required corresponds to a case where a high-temperature side temperature difference  $\Delta T_{WH}$  obtained by subtracting the high-temperature side heat medium temperature **TWH** from the target high-temperature side heat medium temperature **TWHO** is equal to or lower than a reference high-temperature side temperature difference  $K\Delta T_{WH2}$  for recovery.

(236) (C3) Strong Current Device Cooling Mode

(237) In the strong current device cooling mode, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** is caused to flow out to the low-temperature side radiator **56** side. In addition, the control device **60** controls the operation of the second low-temperature side pump **51b** so as to exert predetermined pressure-feeding capability.

(238) Therefore, in the low-temperature side heat medium circuit **50** in the strong current device cooling mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the low-temperature side radiator **56**, and the suction port of the second low-temperature side pump **51b**.

(239) Therefore, in the low-temperature side heat medium circuit **50** in the strong current device cooling mode, the low-temperature side heat medium cooled by heat exchange with the outside air in the low-temperature side radiator **56** is sucked into the second low-temperature side pump **51b**. The low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** flows into the cooling water passage **81a** of the strong current device **81**. As a result, the strong current device **81** is cooled.

(240) In the air conditioner **1** of the present embodiment, comfortable air conditioning of the

vehicle interior and appropriate temperature adjustment of a plurality of in-vehicle devices can be performed by appropriately combining and executing the air conditioning operation mode and the temperature adjusting operation mode, as described above.

(241) In the air conditioner **1** of the present embodiment, the temperature of the ventilation air is adjusted by heating the ventilation air in the heating part when the vehicle interior is air conditioned. Therefore, in order to realize air conditioning with immediate effectiveness and high responsiveness in the air conditioner **1**, it is desirable that, when air conditioning of the vehicle interior is started, the heating part is in a state of being able to exert sufficient heating capability.

(242) The heating part of the present embodiment is formed by the respective components of the water-refrigerant heat exchanger **12** and the high-temperature side heat medium circuit **40** of the heat pump cycle **10**. Therefore, the heating capability of the heating part can be defined by the high-temperature side heat medium temperature TWH that is the temperature of the high-temperature side heat medium to flow into the heater core **42**.

(243) Therefore, in the heating part of the present embodiment, it is desirable that, when air conditioning of the vehicle interior is started, the high-temperature side heat medium temperature TWH, corresponding to the actual heating capability of the heating part, is equal to or higher than the target high-temperature side heat medium temperature TWHO corresponding to the reference heating capability of the heating part.

(244) Therefore, in the present embodiment, heating preparation control for improving the heating capability of the heating part is executed when air conditioning of the vehicle interior is started, by executing a control flow illustrated in FIG. **3** to use the heat generated by the electric heater **54** that is the heat generating part. The control flow illustrated in FIG. **3** is executed at predetermined periods as a subroutine of the main routine of the air conditioning control program. Each control step illustrated in the flowchart of FIG. **3** is a function implementation part included in the control device **60**.

(245) First, in a step **S1**, it is determined whether the high-temperature side temperature difference  $\Delta TWH$  obtained by subtracting the high-temperature side heat medium temperature TWH from the target high-temperature side heat medium temperature TWHO is equal to or larger than the predetermined reference high-temperature side temperature difference  $K\Delta TWH$  (in the present embodiment,  $15^{\circ} \text{C.}$ ).

(246) As described above, the heating capability of the heating part of the present embodiment can be defined by the high-temperature side heat medium temperature TWH. Therefore, when it is determined in the step **S1** that the high-temperature side temperature difference  $\Delta TWH$  is equal to or larger than the reference high-temperature side temperature difference  $K\Delta TWH$ , it is determined that the heating part is not in a state of being able to exert sufficient heating capability for air conditioning the vehicle interior, and the process proceeds to a step **S2**. In the step **S2** to a step **S7**, the heating preparation control is executed.

(247) On the other hand, when it is determined in the step **S1** that the high-temperature side temperature difference  $\Delta TWH$  is smaller than the reference high-temperature side temperature difference  $K\Delta TWH$ , it is determined that the heating part is in a state of being able to exert sufficient heating capability, and the process returns to the main routine.

(248) In the step **S2**, in order to execute the heating preparation control, switching of the circuit configuration of the heat pump cycle **10**, switching of the circuit configuration of the low-temperature side heat medium circuit, and control of the operations of the various components, are performed.

(249) Specifically, under the heating preparation control, the control device **60** brings the heating expansion valve **14a** into a fully closed state, brings the air-cooling expansion valve **14b** into a fully closed state, and brings the cooling expansion valve **14c** into a throttled state. In addition, the control device **60** opens the dehumidifying on-off valve **15a** and closes the heating on-off valve **15b**.

(250) Therefore, in the heat pump cycle **10** under the heating preparation control, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the dehumidifying passage **22a**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**, as indicated by dashed arrows in FIG. 4.

(251) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the number of rotation of the compressor **11** such that the discharge capability of the compressor **11** is equal to or lower than predetermined reference discharge capability for the heating preparation control. The reference discharge capability for the heating preparation control is set to a value lower than the discharge capability to be exerted in the normal air conditioning operation mode. In the present embodiment, the number of rotation of the compressor **11** is specifically set to 0 rpm. That is, in the step S2 of the present embodiment, the compressor **11** is stopped.

(252) In addition, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** so as to be a predetermined reference opening degree for the heating preparation control.

(253) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability.

(254) Therefore, in the high-temperature side heat medium circuit **40** during the heating preparation control, the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the heater core **42**, and the suction port of the high-temperature side pump **41**, as indicated by solid arrows in FIG. 4.

(255) In addition, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** is caused to flow out to the electric heater **54** side. In addition, the control device **60** controls the operation of the electric heater **54** so as to exert predetermined heating capability. In addition, the control device **60** controls the operation of the second low-temperature side pump **51b** so as to exert predetermined pressure-feeding capability.

(256) Therefore, in the low-temperature side heat medium circuit **50** under the heating preparation control, the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the electric heater **54**, the heat medium passage **20b** of the chiller **20**, and the suction port of the second low-temperature side pump **51b**, as indicated by the solid arrows in FIG. 4. That is, in the low-temperature side heat medium circuit **50** under the heating preparation control, a circuit is switched to, in which the low-temperature side heat medium heated by the electric heater **54** flows while bypassing the cooling water passage **80a** of the battery **80**.

(257) Therefore, in the low-temperature side heat medium circuit **50** under the heating preparation control, the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** is heated when passing through the electric heater **54**.

(258) In addition, the control device **60** controls the number of rotation of the indoor blower **32** such that the blowing capability of the indoor blower **32** is equal to or lower than predetermined reference blowing capability for the heating preparation control. The reference blowing capability for the heating preparation control is set to a value lower than the blowing capability to be exerted in the normal air conditioning operation mode. In the present embodiment, the number of rotation of the indoor blower **32** is specifically set to 0 rpm. That is, in the step S2, the indoor blower **32** is stopped.

(259) Next, in a step S3, a target heat medium temperature  $T_{WinO}$  is determined. Therefore, the step S3 is a target heat medium temperature determination unit. The target heat medium temperature  $T_{WinO}$  is determined to be a value at which, even when the low-pressure refrigerant

absorbs heat from the low-temperature side heat medium in the chiller **20**, the inlet side heat medium temperature  $T_{Win}$  is not lowered below a lower limit heat medium temperature  $T_{Wmin}$  (in the present embodiment,  $15^{\circ}\text{C}$ .). The lower limit heat medium temperature  $T_{Wmin}$  is set to the lowest temperature of the low-pressure side heat medium that can be used as an air conditioning heat source.

(260) More specifically, in the step **S3**, the target heat medium temperature  $T_{WinO}$  is determined based on the intake air temperature  $T_{Ain}$  detected by the intake air temperature sensor **69b** and the target blowing capability determined by the blowing capability control unit **60b** and with reference to the control map stored in advance in the control device **60**. In the control map for the heating preparation control, it is determined to raise the target heat medium temperature  $T_{WinO}$  as the intake air temperature  $T_{Ain}$  lowers. It is also determined to raise the target heat medium temperature  $T_{WinO}$  as the target blowing capability increases.

(261) Next, in a step **S4**, it is determined whether the inlet side heat medium temperature  $T_{Win}$  detected by the third low-temperature side heat medium temperature sensor **67c** is equal to or higher than the target heat medium temperature  $T_{WinO}$ .

(262) When it is determined in the step **S4** that the inlet side heat medium temperature  $T_{Win}$  is equal to or higher than the target heat medium temperature  $T_{WinO}$ , it is determined that, even if the number of rotation of the compressor **11** is increased, the inlet side heat medium temperature  $T_{Win}$  is not below the lower limit heat medium temperature  $T_{Wmin}$ , and the process proceeds to a step **S5**.

(263) On the other hand, when it is determined in the step **S4** that the inlet side heat medium temperature  $T_{Win}$  is not equal to or higher than the target heat medium temperature  $T_{WinO}$ , it is determined that there is a possibility that, if the number of rotation of the compressor **11** is increased, the inlet side heat medium temperature  $T_{Win}$  may be below the lower limit heat medium temperature  $T_{Wmin}$ , and the process returns to the step **S2**.

(264) In the step **S5**, the number of rotation of the compressor **11** is increased. More specifically, the compressor **11**, in the present embodiment, is operated and controlled in the same manner as in (A4) the heating mode or the like. Therefore, under the heating preparation control in the present embodiment, the refrigerant discharge capability of the compressor **11** is increased when the inlet side heat medium temperature  $T_{Win}$  is equal to or higher than the target heat medium temperature  $T_{WinO}$ .

(265) As a result, in the heat pump cycle **10**, the refrigerant circulates as indicated by the dashed arrows in FIG. **4**. Then, in the heat pump cycle **10**, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the chiller **20** is caused to function as an evaporator.

(266) Therefore, in the heat pump cycle **10** during the heating preparation control, the heat of the low-temperature side heat medium is absorbed by the low-pressure refrigerant in the chiller **20**. The high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**.

(267) Next, in a step **S6**, it is determined whether the high-temperature side heat medium temperature  $T_{WH}$  is equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ .

(268) When it is determined in the step **S6** that the high-temperature side heat medium temperature  $T_{WH}$  is equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ , it is determined that the heating capability of the heating part is equal to or higher than the reference heating capability, and the process proceeds to a step **S7**. On the other hand, when it is determined in the step **S6** that the high-temperature side heat medium temperature  $T_{WH}$  is below the target high-temperature side heat medium temperature  $T_{WHO}$ , it is determined that the heating capability of the heating part is not equal to or higher than the reference heating capability, and the process returns to the step **S5**.

(269) In the step **S7**, the number of rotation of the indoor blower **32** is increased. More specifically,

the indoor blower **32**, in the present embodiment, is operated and controlled in the same manner as in the air-cooling mode or the like. Therefore, under the heating preparation control in the present embodiment, when the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$  and the heating capability of the heating part becomes equal to or higher than the reference heating capability, the indoor blower **32** is operated and the blowing capability of the indoor blower **32** is increased.

(270) As a result, in the indoor air conditioning unit **30**, a part or all of the ventilation air blown from the indoor blower **32** is heated when passing through the heater core **42**. As a result, the ventilation air whose temperature has been adjusted is blown into the vehicle interior, and the vehicle interior can be air conditioned.

(271) As described above, the heating preparation control is executed in the air conditioner **1** of the present embodiment, so that the heating capability of the heating part (in the present embodiment, the high-temperature side heat medium temperature  $T_{WH}$ ) can be promptly increased using the heat generated by the electric heater **54**. As a result, the air conditioner **1** can realize air conditioning with immediate effectiveness and high responsiveness.

(272) More specifically, under the heating preparation control in the present embodiment, the compressor **11** is stopped until the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$ , as described in the step S5. When the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$ , the compressor **11** is operated and the refrigerant discharge capability of the compressor **11** is increased.

(273) According to this, it is possible, until the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$ , to suppress an unnecessary increase in the amount of heat absorbed by the low-pressure refrigerant from the low-temperature side heat medium in the chiller **20**. Therefore, the inlet side heat medium temperature  $T_{Win}$ , the temperature of the low-temperature side heat medium, can be promptly raised by the heat generated by the electric heater **54**.

(274) As a result, a warm-up time  $T_W$ , required for raising the high-temperature side heat medium temperature  $T_{WH}$  to the target high-temperature side heat medium temperature  $T_{WHO}$ , can be shortened as illustrated in FIGS. 5 and 6.

(275) Here, FIG. 5 is a graph showing changes in the high-temperature side heat medium temperature  $T_{WH}$  and the inlet side heat medium temperature  $T_{Win}$  under a comparative condition in which, immediately after the electric heater **54** is powered, both the compressor **11** and the indoor blower **32** are operated. In FIGS. 5 to 7, the electric heater **54** is powered at an elapsed time of 0 second.

(276) FIG. 6 is a graph showing changes in the high-temperature side heat medium temperature  $T_{WH}$  and the inlet side heat medium temperature  $T_{Win}$  under a first condition in which, when the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$  after the electric heater **54** is powered, the compressor **11** and the indoor blower **32** are operated. In FIG. 6, the target heat medium temperature  $T_{WinO}$  is determined to be about the lower limit heat medium temperature  $T_{Wmin}+20^{\circ}\text{C}$ .

(277) Furthermore, under the heating preparation control in the present embodiment, the indoor blower **32** is stopped until the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$  and the high-temperature side heat medium temperature  $T_{WH}$  becomes equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ , as described in the step S7. When the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$  and the high-temperature side heat medium temperature  $T_{WH}$  becomes equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ , the indoor blower **32** is operated.

(278) According to this, it is possible, until the inlet side heat medium temperature  $T_{Win}$  becomes

equal to or higher than the target heat medium temperature  $T_{WinO}$  and the high-temperature side heat medium temperature  $T_{WH}$  becomes equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ , to suppress an unnecessary increase in the amount of heat dissipated from the high-temperature side heat medium to the ventilation air in the heater core **42** constituting the heating part. Therefore, the inlet side heat medium temperature  $T_{Win}$  can be promptly raised by the heat generated by the electric heater **54**.

(279) As a result, the warm-up time  $TW$  can be further shortened as illustrated in FIG. 7.

(280) Here, FIG. 7 is a graph showing changes in the high-temperature side heat medium temperature  $T_{WH}$  and the inlet side heat medium temperature  $T_{Win}$  under the second condition in which the compressor **11** is operated when the inlet side heat medium temperature  $T_{Win}$  becomes equal to or higher than the target heat medium temperature  $T_{WinO}$  after the electric heater **54** is powered, and then the indoor blower **32** is operated when the high-temperature side heat medium temperature  $T_{WH}$  becomes equal to or higher than the target high-temperature side heat medium temperature  $T_{WHO}$ . In FIG. 7, the target heat medium temperature  $T_{WinO}$  is determined to be about the lower limit heat medium temperature  $T_{Wmin}+10^{\circ}\text{C}$ .

(281) The heating preparation control in the present embodiment is executed when the high-temperature side temperature difference  $\Delta T_{WH}$  is equal to or larger than the reference high-temperature side temperature difference  $K\Delta T_{WH}$ , as described in the step **S1**. Therefore, the heating preparation control in the present embodiment is executed when the heating capability of the heating part is insufficient. According to this, it is possible to suppress frequent stoppage of the indoor blower **32** due to execution of unnecessary heating preparation control, that is, stoppage of air conditioning of the vehicle interior.

(282) Under the heating preparation control in the present embodiment, the second low-temperature side three-way valve **52b**, the heat medium circuit switching part, switches the circuit configuration of the low-temperature side heat medium circuit as described in the step **S2**. Specifically, the low-temperature side heat medium circuit **50** is switched to a circuit in which the low-temperature side heat medium heated by the electric heater **54** flows while bypassing the cooling water passage **80a** of the battery **80**.

(283) According to this, the heat of the low-temperature side heat medium heated by the electric heater **54** is suppressed from being absorbed by the battery **80** having a relatively large heat capacity, and the inlet side heat medium temperature  $T_{Win}$  can be promptly raised. Accordingly, the warm-up time  $TW$  can be further shortened.

(284) Under the heating preparation control in the present embodiment, the air-cooling expansion valve **14b** is brought into a fully closed state, as described in the step **S2**. Furthermore, the third check valve **17c**, configured such that the refrigerant outlet side can be closed, is disposed on the refrigerant outlet side of the indoor evaporator **18**.

(285) According to this, even if the low-temperature side heat medium heated by the electric heater **54** flows into the heat medium passage **20b** of the chiller **20** and the refrigerant pressure in the refrigerant passage **20a** increases, it is possible to suppress the refrigerant from flowing back into the indoor evaporator **18** from the chiller **20** side. As a result, it is possible to suppress occurrence of a so-called asleep phenomenon of the refrigerant in which the refrigerant stagnates in the indoor evaporator **18**.

(286) Similarly, under the heating preparation control in the present embodiment, the heating expansion valve **14a** is brought into a fully closed state and the heating on-off valve **15b** is closed, as described in the step **S2**. Furthermore, the first check valve **17a** and the second check valve **17b**, which are configured such that the refrigerant outlet sides can be closed, are disposed on the refrigerant outlet side of the outdoor heat exchanger **16**.

(287) According to this, even if the low-temperature side heat medium heated by the electric heater **54** flows into the heat medium passage **20b** of the chiller **20** and the refrigerant pressure in the refrigerant passage **20a** increases, it is possible to suppress the refrigerant from flowing back into

the outdoor heat exchanger **16** from the chiller side. As a result, it is possible to suppress occurrence of an asleep phenomenon of the refrigerant in the outdoor heat exchanger **16**.

(288) In the step **S3** that is a target heat medium temperature determination unit of the present embodiment, it is determined to raise the target heat medium temperature  $T_{WinO}$  as the intake air temperature  $T_{Ain}$  lowers. It is also determined to raise the target heat medium temperature  $T_{WinO}$  as the target blowing capability increases.

(289) According to this, when the indoor blower **32** is operated, the target heat medium temperature  $T_{WinO}$  can be raised as the amount of dissipated heat, assumed to be dissipated from the high-temperature side heat medium to the ventilation air in the heater core **42**, increases. Therefore, it is possible to suppress an increase in a temperature lowering amount  $\Delta TL$  of the high-temperature side heat medium temperature  $T_{WH}$  immediately after the indoor blower **32** is operated, as illustrated in FIG. 7.

(290) In the heating preparation control in the present embodiment, an example has been described in which the refrigerant circuit of the heat pump cycle **10** is switched to a refrigerant circuit that circulates the refrigerant as indicated by the dashed arrows in FIG. 4, as described in the step **S2**, but the present disclosure is not limited thereto.

(291) For example, as a modification of the heating preparation control, the control device **60** brings, in the step **S2**, the heating expansion valve **14a** into a throttled state, the air-cooling expansion valve **14b** into a fully closed state, and the cooling expansion valve **14c** into a throttled state. Furthermore, the control device **60** opens the dehumidifying on-off valve **15a** and opens the heating on-off valve **15b**.

(292) Therefore, in the heat pump cycle **10** of the modification, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the heating passage **22b**, the accumulator **21**, and the suction port of the compressor **11**, as indicated by dashed arrows in FIG. 8. At the same time, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the first refrigerant joint part **13a**, the dehumidifying passage **22a**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**. That is, refrigerant circuits are switched to, in which the outdoor heat exchanger **16** and the chiller **20** are connected in parallel for the flow of the refrigerant.

(293) Furthermore, the control device **60** appropriately controls the operations of the other control target devices of the heat pump cycles **10**. For example, the control device **60** controls the throttle opening degree of the heating expansion valve **14a** such that the refrigerant evaporating temperature in the outdoor heat exchanger **16** becomes lower than the outside air temperature  $T_{am}$ . The other operations are the same as those under the heating preparation control in the above-described first embodiment.

(294) Therefore, in the modification of the heating preparation control, the high-temperature side heat medium can be heated not only by absorbing the heat generated by the electric heater **54** in the chiller **20** but also by using the heat absorbed from the outside air in the outdoor heat exchanger **16**. As a result, the heating capability of the heating part can be increased more promptly. The modification of the heating preparation control can be effectively executed when the outside air temperature  $T_{am}$  is higher than the refrigerant evaporating temperature in the chiller **20**, or the like.

(295) When the outdoor heat exchanger **16** includes a shutter device **16a**, as illustrated in the overall configuration view of FIG. 9, the control device **60** brings, as another modification of the heating preparation control and in the step **S2**, the heating expansion valve **14a** into a fully opened state, the air-cooling expansion valve **14b** into a fully closed state, and the cooling expansion valve **14c** into a throttled state. Furthermore, the control device **60** closes the dehumidifying on-off valve **15a** and closes the heating on-off valve **15b**. In addition, the control device **60** brings the shutter device **16a** into a fully closed state.

(296) The shutter device **16a** adjusts the flow rate of the outside air to flow into the outside air passage of the outdoor heat exchanger **16** to continuously adjust the heat exchange amount between the refrigerant and the outside air in the outdoor heat exchanger **16**. The shutter device **16a** can also stop the heat exchange between the refrigerant and the outside air in the outdoor heat exchanger **16** by creating a fully closed state in which the outside air passage of the outdoor heat exchanger **16** is closed. The operation of the shutter device **16a** is controlled by a control signal output from the control device **60**.

(297) Therefore, in the heat pump cycle **10** of the another modification, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the heating expansion valve **14a** in a fully opened state, the outdoor heat exchanger **16**, the cooling expansion valve **14c**, the chiller **20**, the accumulator **21**, and the suction port of the compressor **11**, as indicated by dashed arrows in FIG. **9**. The other operations are the same as those in the above-described embodiment.

(298) In the another modification, the shutter device **16a** is brought into a fully closed state, and thus the heat exchange between the refrigerant and the outside air is not performed in the outdoor heat exchanger **16**. Therefore, the heat pump cycle **10** under the heating preparation control in the another modification operates similarly to the first embodiment. Therefore, according to the heating preparation control in the another modification, the same effect as that under the heating preparation control in the first embodiment can be obtained.

#### Second Embodiment

(299) In the present embodiment, an example will be described in which the configuration of the heating part of the heat pump cycle **10** in the air conditioner **1** of the first embodiment is changed. Specifically, in the heat pump cycle **10** of the present embodiment, the water-refrigerant heat exchanger **12** and the high-temperature side heat medium circuit **40** are eliminated, and an indoor condenser **121** is adopted as the heating part, as illustrated in the overall configuration view of FIG. **10**.

(300) The indoor condenser **121** is a heating heat exchanger that exchanges heat between the high-pressure refrigerant discharged from the compressor **11** and the ventilation air to heat the ventilation air. Similarly to the heater core **42**, the indoor condenser **121** is disposed in the air conditioning case **31** of the indoor air conditioning unit **30**.

(301) The second refrigerant temperature sensor **64b** of the present embodiment detects the temperature of the refrigerant flowing out of the indoor condenser **121** as the second refrigerant temperature TR2. The second refrigerant pressure sensor **65b** of the present embodiment detects the pressure of the refrigerant flowing out of the indoor condenser **121** as the second refrigerant pressure PR2. The other configurations of the air conditioner **1** are similar to those of the first embodiment.

(302) In the present embodiment, as the target condensation pressure PDO to be used during the parallel heating mode or the like, a value determined such that the refrigerant condensation temperature in the indoor condenser **121** approaches a target condensation temperature TDO (in the present embodiment, about 50° C.) is used.

(303) Here, the heating part of the present embodiment is formed by the indoor condenser **121**. Therefore, the heating capability of the heating part can be defined by the second refrigerant pressure PR2 corresponding to the refrigerant condensation pressure in the indoor condenser **121** or the second refrigerant temperature TR2 corresponding to the refrigerant condensation temperature in the indoor condenser **121**.

(304) Therefore, in the heating part of the present embodiment, it is desirable that, when air conditioning of the vehicle interior is started, the second refrigerant temperature TR2 corresponding to the actual heating capability of the heating part is equal to or higher than the target condensation temperature TDO corresponding to the reference heating capability of the heating part. Alternatively, it is desirable that the second refrigerant pressure PR2 corresponding to

the actual heating capability of the heating part is equal to or higher than the target condensation pressure PDO corresponding to the reference heating capability of the heating part.

(305) Therefore, in the step S1 of the heating preparation control in the present embodiment, it is determined whether a pressure difference  $\Delta PH$  obtained by subtracting the second refrigerant pressure PR2 from the target condensation pressure PDO is equal to or larger than a predetermined reference pressure difference  $K\Delta PH$ . Here, for the refrigerant in the present embodiment, the temperature at the pressure obtained by subtracting the reference pressure difference  $K\Delta PH$  from the target condensation pressure PDO is set to a temperature lower than the target condensation temperature TDO by about 15° C.

(306) When it is determined in the step S1 that the pressure difference  $\Delta PH$  is equal to or larger than the reference pressure difference  $K\Delta PH$ , it is determined that the heating part is not in a state of being able to exert sufficient heating capability, and the process proceeds to the step S2. On the other hand, when it is determined in the step S1 that the pressure difference  $\Delta PH$  is smaller than the reference pressure difference  $K\Delta PH$ , it is determined that the heating part is in a state of being able to exert sufficient heating capability, and the process returns to the main routine.

(307) Similarly, in the step S6 of the heating preparation control in the present embodiment, it is determined whether the second refrigerant pressure PR2 is equal to or higher than the target condensation pressure PDO.

(308) When it is determined in the step S6 that the second refrigerant pressure PR2 is equal to or higher than the target condensation pressure PDO, it is determined that the heating capability of the heating part is equal to or higher than the reference heating capability, and the process proceeds to the step S7. On the other hand, when it is determined in the step S6 that the second refrigerant pressure PR2 is lower than the target condensation pressure PDO, it is determined that the heating capability of the heating part is not equal to or higher than the reference heating capability, and the process returns to the step S5. The other operations of the air conditioner 1 are the same as those in the first embodiment.

(309) Therefore, according to the air conditioner 1 of the present embodiment, the same effects as those of the first embodiment can be obtained. That is, also in the air conditioner 1 of the present embodiment, comfortable air conditioning of the vehicle interior and appropriate temperature adjustment of a plurality of in-vehicle devices can be performed. Furthermore, the heating capability (in the present embodiment, the target condensation pressure PDO) of the heating part can be promptly increased using the heat generated by the electric heater 54. As a result, it is possible to realize air conditioning with immediate effectiveness and high responsiveness.

### Third Embodiment

(310) In the present embodiment, an example will be described in which an inlet side connection passage 91, an outlet side connection passage 92, and the like are added to the air conditioner 1 of the first embodiment, as illustrated in the overall configuration view of FIG. 11. The inlet side connection passage 91 and the outlet side connection passage 92 form a heat medium flow path that connects the high-temperature side heat medium circuit 40 and the low-temperature side heat medium circuit 50.

(311) Furthermore, a high-temperature side three-way valve 43 is disposed in a heat medium flow path extending, in the high-temperature side heat medium circuit 40 of the present embodiment, from the outlet of the heat medium passage 12b of the water-refrigerant heat exchanger 12 to the heater core 42. The high-temperature side three-way valve 43 causes the high-temperature side heat medium flowing out of the heat medium passage 12b of the water-refrigerant heat exchanger 12 to flow into its inside and flow out to at least one of the heater core 42 side and the inlet side connection passage 91 side.

(312) The high-temperature side three-way valve 43 can continuously adjust the flow ratio between the flow rate of the high-temperature side heat medium that is caused to flow out to the heater core 42 side and the flow rate of the high-temperature side heat medium that is caused to flow out to the

inlet side connection passage **91** side. Furthermore, by adjusting the flow ratio, the high-temperature side three-way valve **43** can cause the total flow rate of the high-temperature side heat medium that has been caused to flow into its inside to flow out to one of the heater core **42** side and the inlet side connection passage **91** side.

(313) The inlet portion of the inlet side connection passage **91** is connected to one outflow port of the high-temperature side three-way valve **43**. The outlet portion of the inlet side connection passage **91** is connected to one inflow port of a fifth heat medium joint part **53e** disposed in the heat medium flow path extending from the discharge port of the first low-temperature side pump **51a** of the low-temperature side heat medium circuit **50** to the inlet of the cooling water passage **80a** of the battery **80**.

(314) The inlet portion of the outlet side connection passage **92** is connected to one outflow port of a sixth heat medium joint part **53f** disposed in the heat medium flow path extending, in the low-temperature side heat medium circuit **50**, from the outlet of the cooling water passage **80a** of the battery **80** to the inflow port of the first low-temperature side three-way valve **52a**. The outlet portion of the outlet side connection passage **92** is connected to one inflow port of a seventh heat medium joint part **53g** disposed in the heat medium flow path extending, in the high-temperature side heat medium circuit **40**, from the other outflow port of the high-temperature side three-way valve **43** to the heat medium inlet of the heater core **42**. The other configurations of the air conditioner **1** are similar to those of the first embodiment.

(315) Next, the operation of the vehicle air conditioner **1**, having the above configuration, of the present embodiment will be described. In the air conditioner **1** of the present embodiment, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that, during the normal operation, the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the heater core **42** side.

(316) Therefore, when the air conditioning operation mode and the temperature adjusting operation mode are executed, the circuit configurations of the heat pump cycle **10**, the high-temperature side heat medium circuit **40**, and the low-temperature side heat medium circuit **50** are the same as those of the first embodiment. Therefore, also in the air conditioner **1** of the present embodiment, comfortable air conditioning of the vehicle interior and appropriate temperature adjustment of a plurality of in-vehicle devices can be performed by appropriately combining and executing the air conditioning operation mode and the temperature adjusting operation mode.

(317) Furthermore, also in the air conditioner **1** of the present embodiment, the heating preparation control can be performed similarly to the first embodiment. Therefore, the heating capability of the heating part can be promptly increased using the heat generated by the electric heater **54**. As a result, it is possible to realize air conditioning with immediate effectiveness and high responsiveness.

(318) The heating preparation control is executed for the purpose of promptly improving the heating capability of the heating part when air conditioning of the vehicle interior is started. Therefore, the heating preparation control is often executed before the start of air conditioning at a relatively low outside air temperature. At such a low outside air temperature, warm-up of the battery **80** may be required.

(319) On the other hand, in the low-temperature side heat medium circuit **50** during the heating preparation control, a circuit is switched to, in which the low-temperature side heat medium heated by the electric heater **54** flows while bypassing the cooling water passage **80a** of the battery **80**. Therefore, it is impossible to perform the warm-up of the battery **80** due to the low-temperature side heat medium that is heated by the electric heater **54** and flows into the cooling water passage **80a** of the battery **80**.

(320) Therefore, in the present embodiment, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that, when the heating preparation control is being

executed and the battery temperature TB is equal to or lower than a predetermined reference warm-up temperature KTBL, the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the inlet side connection passage **91** side. The reference warm-up temperature KTBL is set to a temperature at which the warm-up of the battery **80** is determined to be necessary.

(321) Therefore, when warm-up of the battery **80** is required during the execution of the heating preparation control in the air conditioner **1** of the present embodiment, the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the high-temperature side three-way valve **43**, the inlet side connection passage **91**, the cooling water passage **80a** of the battery **80**, the outlet side connection passage **92**, the heater core **42**, and the suction port of the high-temperature side pump **41**, as indicated by solid arrows in FIG. **11**.

(322) According to this, when the compressor **11** is operated in the step S5 of the heating preparation control described in the first embodiment, the high-temperature side heat medium can be heated by the water-refrigerant heat exchanger **12**. The high-temperature side heat medium heated by the water-refrigerant heat exchanger **12** can be caused to flow into the cooling water passage **80a** of the battery **80** via the high-temperature side three-way valve **43** and inlet side connection passage **91**. As a result, the battery **80** can be warmed up.

(323) The high-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** flows into the heater core **42** via the outlet side connection passage **92**. Under the heating preparation control, the indoor blower **32** is stopped until the high-temperature side heat medium temperature TWH becomes equal to or higher than the target high-temperature side heat medium temperature TWHO. Therefore, the high-temperature side heat medium having flowed into the heater core **42** flows out of the heater core **42** without exchanging heat with the ventilation air, and is sucked into the high-temperature side pump **41**.

(324) The other operations are the same as those in the first embodiment. Therefore, according to the air conditioner **1** of the present embodiment, the battery **80** can be warmed up during the execution of the heating preparation control.

#### Fourth Embodiment

(325) In the present embodiment, an air conditioner **1a** illustrated in the overall configuration view of FIG. **12** will be described. The air conditioner **1a** of the present embodiment is used as a vehicle air conditioner with an in-vehicle device temperature adjustment function, similarly to the first embodiment. The air conditioner **1a** includes a heat pump cycle **10a**, the indoor air conditioning unit **30**, a high-temperature side heat medium circuit **40a**, a low-temperature side heat medium circuit **50a**, and the like.

(326) Here, the configuration of the indoor air conditioning unit **30** of the air conditioner **1a** is similar to that of the first embodiment. Therefore, the indoor air conditioning unit **30** is not illustrated in FIG. **12** for clarity of illustration. Therefore, the indoor evaporator **18** of the heat pump cycle **10a** and the heater core **42** of the high-temperature side heat medium circuit **40a** are disposed in the air conditioning case **1** of the indoor air conditioning unit **30**, similarly to the first embodiment.

(327) In the heat pump cycle **10a** of the present embodiment, the first refrigerant joint part **13a**, the heating expansion valve **14a**, the outdoor heat exchanger **16**, the accumulator **21**, and the like are eliminated from the heat pump cycle **10** described in the first embodiment.

(328) In the heat pump cycle **10a**, the inlet side of a receiver **23** is connected to the outlet of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12**. The receiver **23** is a high-pressure side gas-liquid separator that separates the gas and liquid of the high-pressure refrigerant flowing out of the refrigerant passage **12a** of the water-refrigerant heat exchanger **12** and stores a surplus liquid-phase refrigerant in the cycle. The inflow port side of the fifth refrigerant joint part **13e** is connected to the refrigerant outlet of the receiver **23**.

(329) The other configurations of the heat pump cycle **10a** are similar to those of the heat pump cycle **10** described in the first embodiment.

(330) In the high-temperature side heat medium circuit **40a** of the present embodiment, the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the high-temperature side pump **41**, the heater core **42**, the high-temperature side three-way valve **43**, a high-temperature side radiator **44**, and the like are disposed. The high-temperature side three-way valve **43** of the present embodiment causes the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** to flow into its inside and flow out to at least one of the heater core **42** side and the high-temperature side radiator **44** side.

(331) The high-temperature side three-way valve **43** can continuously adjust the flow ratio between the flow rate of the high-temperature side heat medium that is caused to flow out to the heater core **42** side and the flow rate of the high-temperature side heat medium that is caused to flow out to the high-temperature side radiator **44** side. Furthermore, by adjusting the flow ratio, the high-temperature side three-way valve **43** can cause the total flow rate of the high-temperature side heat medium that has been caused to flow into its inside to flow out to one of the heater core **42** side and the high-temperature side radiator **44** side.

(332) The high-temperature side radiator **44** is a high-temperature side outside air heat exchange part that exchanges heat between the outside air and the high-temperature side heat medium flowing out of the high-temperature side three-way valve **43**.

(333) One inflow port side of an eighth heat medium joint part **53h** is connected to the heat medium outlet of the high-temperature side radiator **44**. The other inflow port side of the eighth heat medium joint part **53h** is connected to the heat medium outlet of the heater core **42** of the present embodiment. The suction port side of the high-temperature side pump **41** is connected to the outflow port of the eighth heat medium joint part **53h**.

(334) The other configurations of the high-temperature side heat medium circuit **40a** are similar to those of the high-temperature side heat medium circuit **40** described in the first embodiment.

(335) In the low-temperature side heat medium circuit **50a** of the present embodiment, the first low-temperature side pump **51a**, the second low-temperature side pump **51b**, the first low-temperature side three-way valve **52a** to a third low-temperature side three-way valve **52c**, the heat medium passage **20b** of the chiller **20**, the cooling water passage **80a** of the battery **80**, the cooling water passage **81a** of the strong current device **81**, the electric heater **54**, a strong current device bypass passage **55b**, the low-temperature side radiator **56**, and the like are disposed.

(336) In the low-temperature side heat medium circuit **50a**, the inlet side of the heat medium passage **20b** of the chiller **20** is connected to the discharge port of the first low-temperature side pump **51a**. The inflow port side of the first low-temperature side three-way valve **52a** is connected to the outlet of the heat medium passage **20b** of the chiller **20**.

(337) The first low-temperature side three-way valve **52a** of the present embodiment causes the low-temperature side heat medium flowing out of the heat medium passage **20b** of the chiller **20** to flow into its inside and flow out to at least one of the electric heater **54** side and the inflow port side of the third low-temperature side three-way valve **52c**.

(338) The first low-temperature side three-way valve **52a** can continuously adjust the flow ratio between the flow rate of the low-temperature side heat medium that is caused to flow out to the electric heater **54** side and the flow rate of the low-temperature side heat medium that is caused to flow out to the third low-temperature side three-way valve **52c** side. Furthermore, by adjusting the flow ratio, the first low-temperature side three-way valve **52a** can cause the total flow rate of the low-temperature side heat medium that has been caused to flow into its inside to flow out to one of the electric heater **54** side and the third low-temperature side three-way valve **52c** side.

(339) One inflow port side of a ninth heat medium joint part **53i** is connected to the outlet of the heating flow path of the electric heater **54**. The suction port side of the first low-temperature side pump **51a** is connected to the outflow port of the ninth heat medium joint part **53i**.

(340) The third low-temperature side three-way valve **52c** causes the low-temperature side heat medium flowing out of the first low-temperature side three-way valve **52a** to flow into its inside and flow out to at least one of the cooling water passage side of the battery **80** and one inflow port side of a tenth heat medium joint part **53j**.

(341) The third low-temperature side three-way valve **52c** can continuously adjust the flow ratio between the flow rate of the low-temperature side heat medium that is caused to flow out to the cooling water passage **80a** side of the battery **80** and the flow rate of the low-temperature side heat medium that is caused to flow out to the tenth heat medium joint part **53j** side. Furthermore, by adjusting the flow ratio, the third low-temperature side three-way valve **52c** can cause the total flow rate of the low-temperature side heat medium that has been caused to flow into its inside to flow out to one of the cooling water passage **80a** side of the battery **80** and the tenth heat medium joint part **53j** side.

(342) One inflow port side of an eleventh heat medium joint part **53k** is connected to the outlet of the cooling water passage **80a** of the battery **80**. The other inflow port side of the ninth heat medium joint part **53i** is connected to the outflow port of the eleventh heat medium joint part **53k**.

(343) In the low-temperature side heat medium circuit **50a**, the inlet side of the cooling water passage **81a** of the strong current device **81** is connected to the discharge port of the second low-temperature side pump **51b**. The inflow port side of the second low-temperature side three-way valve **52b** is connected to the outlet of the cooling water passage **81a** of the strong current device **81**.

(344) The second low-temperature side three-way valve **52b** of the present embodiment causes the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** to flow into its inside and flow out to at least one of the other inflow port side of the tenth heat medium joint part **53j** and the strong current device bypass passage **55b** side.

(345) The second low-temperature side three-way valve **52b** can continuously adjust the flow ratio between the flow rate that is caused to flow out to the tenth heat medium joint part **53j** side and the flow rate of the low-temperature side heat medium that is caused to flow out to the strong current device bypass passage **55b** side. Furthermore, by adjusting the flow ratio, the second low-temperature side three-way valve **52b** can cause the total flow rate of the low-temperature side heat medium that has been caused to flow into its inside to flow out to one of the tenth heat medium joint part **53j** side and the strong current device bypass passage **55b** side.

(346) The strong current device bypass passage **55b** is a heat medium passage that guides the low-temperature side heat medium flowing out of the cooling water passage **81a** of the strong current device **81** to the suction port side of the second low-temperature side pump **51b** while causing the heat medium to bypass the low-temperature side radiator **56** and the like. One inflow port of a twelfth heat medium joint part **53m** is connected to the outlet portion of the strong current device bypass passage **55b**. The suction port side of the second low-temperature side pump **51b** is connected to the outflow port of the twelfth heat medium joint part **53m**.

(347) The heat medium inlet side of the low-temperature side radiator **56** is connected to the outflow port of the tenth heat medium joint part **53j**. The inflow port side of a thirteenth heat medium joint part **53n** is connected to the heat medium outlet of the low-temperature side radiator **56**. The other inflow port side of the twelfth heat medium joint part **53m** is connected to one outflow port of the thirteenth heat medium joint part **53n**. The other inflow port side of the eleventh heat medium joint part **53k** is connected to the other outflow port of the thirteenth heat medium joint part **53n**.

(348) The other configurations of the low-temperature side heat medium circuit are similar to those of the low-temperature side heat medium circuit **50** described in the first embodiment.

(349) Next, the operation of the air conditioner **1a**, having the above configuration, of the present embodiment will be described. The air conditioner **1a** according to the present embodiment has air conditioning operation modes including (A1) an air-cooling mode, (A2) a dehumidifying-heating

mode, and (A3) a heating mode. Similarly to the first embodiment, the air conditioning operation modes are switched by executing an air conditioning control program stored in the control device **60**. Hereinafter, detailed operation of each air conditioning operation mode will be described.

(350) (A1) Air-Cooling Mode

(351) In the air-cooling mode, the control device **60** brings the air-cooling expansion valve **14b** into a throttled state. Similarly to the first embodiment, the cooling expansion valve **14c** is controlled according to the temperature adjusting operation mode.

(352) Therefore, in the heat pump cycle **10a** in the air-cooling mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the air-cooling expansion valve **14b**, the indoor evaporator **18**, and the suction port of the compressor **11**.

(353) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the compressor **11** similarly to the air-cooling mode in the first embodiment. The throttle opening degree of the cooling expansion valve **14c** is controlled such that a super-heat degree SH of the outlet side refrigerant in the indoor evaporator **18** approaches a predetermined reference super-heat degree KSH.

(354) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that the high-temperature side heat medium temperature TWH approaches the target high-temperature side heat medium temperature TWHO.

(355) Therefore, in the high-temperature side heat medium circuit **40** in the air-cooling mode, a refrigerant circuit is switched to, in which the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the water-refrigerant heat exchanger **12**, the heater core **42**, and the suction port of the high-temperature side pump **41**. At the same time, a refrigerant circuit is switched to, in which the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the water-refrigerant heat exchanger **12**, the high-temperature side radiator **44**, and the suction port of the high-temperature side pump **41**. That is, circuits are switched to, in which the heater core **42** and the high-temperature side radiator **44** are connected in parallel for the flow of the high-temperature side heat medium.

(356) Here, in the air-cooling mode, the amount of heat exchange between the high-temperature side heat medium and the ventilation air in the heater core **42** is small. Therefore, in the high-temperature side three-way valve **43** in the air-cooling mode, almost the total flow rate of the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the high-temperature side radiator **44** side. The other operations are the same as those in the air-cooling mode described in the first embodiment.

(357) Therefore, in the heat pump cycle **10a** in the air-cooling mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the indoor evaporator **18** is caused to function as an evaporator. As a result, in the heat pump cycle **10a** in the air-cooling mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the ventilation air is cooled by the indoor evaporator **18**.

(358) In the high-temperature side heat medium circuit **40a** in the air-cooling mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42** in accordance with the flow ratio control of the high-temperature side three-way valve **43**.

(359) In the indoor air conditioning unit **30** in the air-cooling mode, the ventilation air blown from the indoor blower **32** is cooled by the indoor evaporator **18**. The temperature of the ventilation air cooled by the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose

temperature has been adjusted is blown into the vehicle interior, the air-cooling of the vehicle interior is realized.

(360) (A2) Dehumidifying-Heating Mode

(361) In the dehumidifying-heating mode, the control device **60** brings the air-cooling expansion valve **14b** in a throttled state and brings the cooling expansion valve **14c** into a throttled state.

(362) Therefore, in the heat pump cycle **10a** in the dehumidifying-heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the air-cooling expansion valve **14b**, the indoor evaporator **18**, and the suction port of the compressor **11**. At the same time, a refrigerant circuit is switched to, in which the refrigerant discharged from compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the cooling expansion valve **14c**, the chiller **20**, and the suction port of compressor **11**. That is, refrigerant circuits are switched to, in which the indoor evaporator **18** and the chiller **20** are connected in parallel for the flow of the refrigerant.

(363) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the compressor **11** similarly to the parallel dehumidifying-heating mode in the first embodiment. In addition, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the refrigerant evaporating temperature in the chiller **20** becomes lower than the outside air temperature  $T_{am}$ .

(364) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that the high-temperature side heat medium temperature  $T_{WH}$  approaches the target high-temperature side heat medium temperature  $T_{WHO}$ .

(365) Therefore, in the high-temperature side heat medium circuit **40a** in the dehumidifying-heating mode, a circuit is switched to, in which the high-temperature side heat medium circulates in the same order as in the air-cooling mode.

(366) In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability.

(367) In addition, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the heat medium passage **20b** of the chiller **20** is caused to flow out to the third low-temperature side three-way valve **52c** side. In addition, the control device **60** controls the operation of the third low-temperature side three-way valve **52c** such that the low-temperature side heat medium flowing out of the first low-temperature side three-way valve **52a** is caused to flow out to the tenth heat medium joint part **53j** side. In addition, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the low-temperature side heat medium flowing out of the third low-temperature side three-way valve **52c** is caused to flow out to the low-temperature side radiator **56** side.

(368) Therefore, in the low-temperature side heat medium circuit **50a** in the dehumidifying-heating mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the heat medium passage **20b** of the chiller **20**, the first low-temperature side three-way valve **52a**, the third low-temperature side three-way valve **52c**, the low-temperature side radiator **56**, and the suction port of the first low-temperature side pump **51a**. The other operations are the same as those in the air-cooling mode.

(369) Therefore, in the heat pump cycle **10a** in the dehumidifying-heating mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the indoor evaporator **18** and the chiller **20** are caused to function as evaporators.

(370) As a result, in the heat pump cycle **10a** in the dehumidifying-heating mode, the high-

temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. The ventilation air is cooled by the indoor evaporator **18**. Furthermore, the low-pressure refrigerant absorbs heat from the low-temperature side heat medium in the chiller **20**, so that the temperature of the low-temperature side heat medium becomes lower than the outside air temperature.

(371) In the high-temperature side heat medium circuit **40a** in the dehumidifying-heating mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42** in accordance with the flow ratio control of the high-temperature side three-way valve **43**.

(372) In the low-temperature side heat medium circuit **50a** in the dehumidifying-heating mode, the low-temperature side heat medium cooled by the chiller **20** flows into the low-temperature side radiator **56** via the first low-temperature side three-way valve **52a** and the third low-temperature side three-way valve **52c**. The low-temperature side heat medium having flowed into the low-temperature side radiator **56** absorbs heat from the outside air. The low-temperature side heat medium whose temperature has risen by absorbing heat from the outside air in the low-temperature side radiator **56** is sucked into the first low-temperature side pump **51a** and pressure-fed to the heat medium passage **20b** of the chiller **20**.

(373) In the indoor air conditioning unit **30** in the dehumidifying-heating mode, the ventilation air blown from the indoor blower **32** is cooled and dehumidified by the indoor evaporator **18**. The temperature of the ventilation air cooled and dehumidified by the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose temperature has been adjusted is blown out into the vehicle interior, the dehumidification and heating of the vehicle interior is realized.

(374) (A3) Heating Mode

(375) In the heating mode, the control device **60** brings the air-cooling expansion valve **14b** into a fully closed state and brings the cooling expansion valve **14c** into a throttled state.

(376) Therefore, in the heat pump cycle **10a** in the heating mode, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the cooling expansion valve **14c**, chiller **20**, and the suction port of the compressor **11**.

(377) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the compressor **11**, similarly to the heating mode in the first embodiment. In addition, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the super-heat degree SH of the outlet side refrigerant in the chiller **20** approaches the predetermined reference super-heat degree KSH.

(378) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that the high-temperature side heat medium temperature TWH approaches the target high-temperature side heat medium temperature TWHO.

(379) Therefore, in the high-temperature side heat medium circuit **40a** in the dehumidifying-heating mode, a circuit is switched to, in which the high-temperature side heat medium circulates in the same order as in the air-cooling mode.

(380) Here, in the heating mode, the amount of heat exchange between the high-temperature side heat medium and the ventilation air in the heater core **42** increases. Therefore, in the high-temperature side three-way valve **43** in the heating mode, almost the total flow rate of the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the heater core **42** side.

(381) In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability. Similarly to the dehumidifying-heating mode, the control device **60** controls the operations of the first low-temperature side three-way valve **52a** to the third low-temperature side three-way valve **52c**.

(382) Therefore, in the low-temperature side heat medium circuit **50a** in the heating mode, a circuit is switched to, in which the low-temperature side heat medium circulates in the same order as in the dehumidifying-heating mode. The other operations are the same as those in the heating mode described in the first embodiment.

(383) Therefore, in the heat pump cycle **10a** in the heating mode, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the chiller **20** is caused to function as an evaporator. As a result, in the heat pump cycle **10a** in the heating mode, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the low-pressure refrigerant absorbs heat from the low-temperature side heat medium in the chiller **20**, so that the temperature of the low-temperature side heat medium becomes lower than the outside air temperature.

(384) In the high-temperature side heat medium circuit **40a** in the heating mode, the heat medium heated by the water-refrigerant heat exchanger **12** is supplied to the heater core **42** in accordance with the flow ratio control of the high-temperature side three-way valve **43**.

(385) In the low-temperature side heat medium circuit **50a** in the heating mode, the low-temperature side heat medium cooled by the chiller **20** flows into the low-temperature side radiator **56** via the first low-temperature side three-way valve **52a** and the third low-temperature side three-way valve **52c**. The low-temperature side heat medium having flowed into the low-temperature side radiator **56** absorbs heat from the outside air. The low-temperature side heat medium flowing out of the low-temperature side radiator **56** is sucked into the first low-temperature side pump **51a** and pressure-fed to the heat medium passage **20b** of the chiller **20**.

(386) In the indoor air conditioning unit **30** in the heating mode, the ventilation air blown from the indoor blower **32** passes through the indoor evaporator **18**. The temperature of the ventilation air having passed through the indoor evaporator **18** is adjusted so as to approach the target blowing-out temperature TAO by adjusting the opening degree of the air mix door **34**. Then, when the ventilation air whose temperature has been adjusted is blown into the vehicle interior, the heating of the vehicle interior is realized.

(387) Next, the temperature adjusting operation mode will be described. In the present embodiment, the battery operation mode includes (B1) a battery temperature equalization mode and (B2) a battery cooling mode. The strong current device operation mode includes (C1) a strong current device cooling mode. Hereinafter, detailed operation of each temperature adjusting operation mode will be described.

(388) (B1) Battery Temperature Equalization Mode

(389) The battery cooling mode is executed when the temperature difference  $\Delta TB$  between the respective battery cells is equal to or larger than the target cell temperature difference  $\Delta KTB$ .

(390) In the battery temperature equalization mode, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability. The operation of the first low-temperature side three-way valve **52a** is controlled such that the low-temperature side heat medium flowing out of the heat medium passage **20b** of the chiller **20** is caused to flow out to the third low-temperature side three-way valve **52c** side. In addition, the control device **60** controls the operation of the third low-temperature side three-way valve **52c** such that the low-temperature side heat medium flowing out of the first low-temperature side three-way valve **52a** is caused to flow out to the cooling water passage **80a** side of the battery **80**.

(391) Therefore, in the low-temperature side heat medium circuit **50a** in the battery temperature equalization mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the heat medium passage **20b** of the chiller **20**, the first low-temperature side three-way valve **52a**, the third low-temperature side three-way valve **52c**, the cooling water passage **80a** of the battery **80**, and the suction port of the first low-temperature side pump **51a**.

(392) Therefore, in the low-temperature side heat medium circuit **50a** in the battery temperature

equalization mode, the temperatures of the respective battery cells forming the battery **80** are equalized when the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** flows through the cooling water passage **80a** of the battery **80**.

(393) (B2) Battery Cooling Mode

(394) The battery cooling mode is executed when the battery temperature TB becomes equal to or higher than a predetermined reference cooling temperature KTBH. The battery cooling mode is an operation mode in which the battery **80** is cooled by the low-temperature side heat medium cooled by the chiller **20**. Therefore, when the compressor **11** of the heat pump cycle **10** is operating as during air conditioning, the control device **60** brings the cooling expansion valve **14c** of the heat pump cycle **10** into a throttled state even in the air-cooling mode.

(395) Therefore, in the heat pump cycle **10a** in the battery cooling mode, the low-pressure refrigerant whose pressure has been reduced by the cooling expansion valve **14c** flows into the refrigerant passage **20a** of the chiller **20**. The refrigerant flowing out of the refrigerant passage **20a** of the chiller **20** is sucked into the compressor **11** via the sixth refrigerant joint part **13f**.

(396) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the cooling expansion valve **14c** similarly to the dehumidifying-heating mode.

(397) In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the heat medium passage **20b** of the chiller **20** is caused to flow out to the third low-temperature side three-way valve **52c** side. In addition, the control device **60** controls the operation of the third low-temperature side three-way valve **52c** such that the first low-temperature side heat medium temperature TWL1 approaches the battery target temperature TWLO1.

(398) Therefore, in the low-temperature side heat medium circuit **50a** in the dehumidifying-heating mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the heat medium passage **20b** of the chiller **20**, the first low-temperature side three-way valve **52a**, the third low-temperature side three-way valve **52c**, the cooling water passage **80a** of the battery **80**, and the suction port of the first low-temperature side pump **51a**. At the same time, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the heat medium passage **20b** of the chiller **20**, the first low-temperature side three-way valve **52a**, the third low-temperature side three-way valve **52c**, the low-temperature side radiator **56**, and the suction port of the first low-temperature side pump **51a**. That is, circuits are switched to, in which the cooling water passage **80a** of the battery **80** and the low-temperature side radiator **56** are connected in parallel for the flow of the low-temperature side heat medium.

(399) Therefore, in the heat pump cycle **10a** in the battery cooling mode during air conditioning, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and at least the chiller **20** is caused to function as an evaporator.

(400) In the low-temperature side heat medium circuit **50a**, the low-temperature side heat medium cooled by the chiller **20** flows into both the cooling water passage of the battery **80** and the low-temperature side radiator **56** in accordance with the flow ratio control of the first low-temperature side three-way valve **52a**. The low-temperature side heat medium having flowed into the cooling water passage **80a** of the battery **80** absorbs heat from the battery **80**. As a result, the battery **80** is cooled.

(401) Next, the battery cooling mode during non-air conditioning will be described. In the battery cooling mode during non-air conditioning, the control device **60** brings the air-cooling expansion valve **14b** into a fully closed state and brings the cooling expansion valve **14c** into a throttled state.

(402) Therefore, in the heat pump cycle **10a** in the battery cooling mode during non-air conditioning, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the cooling expansion valve **14c**, the chiller **20**, and the suction port of the compressor **11**.

(403) Furthermore, the control device **60** appropriately controls the operations of the other control target devices. For example, the control device **60** controls the number of rotation of the compressor **11** so as to exert predetermined discharge capability. In addition, the control device **60** controls the throttle opening degree of the cooling expansion valve **14c** such that the first low-temperature side heat medium temperature **TWL1** approaches the battery target temperature **TWLO1**.

(404) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that the high-temperature side heat medium having flowed in from the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the high-temperature side radiator **44** side.

(405) Therefore, in the high-temperature side heat medium circuit **40a** in the battery cooling mode during non-air conditioning, a circuit is switched to, in which the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the high-temperature side three-way valve **43**, the high-temperature side radiator **44**, and the suction port of the high-temperature side pump **41**.

(406) In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability. Similarly to the battery cooling mode during air conditioning, the control device **60** controls the operations of the first low-temperature side three-way valve **52a** and the third low-temperature side three-way valve **52c**.

(407) Therefore, in the low-temperature side heat medium circuit **50a** in the battery cooling mode during non-air conditioning, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates similarly to the battery cooling mode during air conditioning.

(408) Therefore, in the heat pump cycle **10a** in the battery cooling mode during non-air conditioning, a vapor compression type refrigeration cycle is formed in which the water-refrigerant heat exchanger **12** is caused to function as a condenser and the chiller **20** is caused to function as an evaporator. As a result, in the heat pump cycle **10a** in the battery cooling mode during non-air conditioning, the high-temperature side heat medium is heated by the water-refrigerant heat exchanger **12**. Furthermore, the low-pressure side heat medium is cooled by the chiller **20**.

(409) In the high-temperature side heat medium circuit **40a**, the high-temperature side heat medium heated by the water-refrigerant heat exchanger **12** is pressure-fed to the high-temperature side radiator **44** via the high-temperature side three-way valve **43**. The high-temperature side heat medium having flowed into the high-temperature side radiator **44** dissipates heat to the outside air and is cooled.

(410) In the low-temperature side heat medium circuit **50a**, the low-temperature side heat medium cooled by the chiller **20** flows into the cooling water passage **80a** of the battery **80** similarly to the battery cooling mode during air conditioning. The low-temperature side heat medium having flowed into the cooling water passage **80a** of the battery **80** absorbs heat from the battery **80**. As a result, the battery **80** is cooled.

(411) (C1) Strong Current Device Cooling Mode

(412) The strong current device cooling mode is executed when the second low-temperature side heat medium temperature **TWL2** becomes equal to or higher than a predetermined reference strong current device cooling temperature **KTWL2**. The strong current device cooling mode is an operation mode in which the strong current device **81** is cooled by the low-temperature side heat

medium cooled by the low-temperature side radiator **56**.

(413) In the strong current device cooling mode, the control device **60** controls the operation of the second low-temperature side pump **51b** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the second low-temperature side three-way valve **52b** such that the second low-temperature side heat medium temperature TWL2 approaches the strong current device target temperature TWLO2.

(414) Therefore, in the low-temperature side heat medium circuit **50a** in the strong current device cooling mode, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the second low-temperature side three-way valve **52b**, the strong current device bypass passage **55b**, and the suction port of the second low-temperature side pump **51b**. At the same time, a circuit is switched to, in which the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** circulates in the order of the cooling water passage **81a** of the strong current device **81**, the second low-temperature side three-way valve **52b**, the low-temperature side radiator **56**, and the suction port of the second low-temperature side pump **51b**. That is, circuits are switched to, in which the strong current device bypass passage **55b** and the low-temperature side radiator **56** are connected in parallel for the flow of the low-temperature side heat medium.

(415) Therefore, in the low-temperature side heat medium circuit **50a** in the strong current device cooling mode, at least a part of the low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** flows into the low-temperature side radiator **56**. The low-temperature side heat medium having flowed into the low-temperature side radiator **56** is cooled by heat exchange with the outside air. The low-temperature side heat medium flowing out of the low-temperature side radiator **56** merges, in the twelfth heat medium joint part **53m**, with the low-temperature side heat medium having flowed through the strong current device bypass passage **55b** and is mixed.

(416) At this time, by the flow ratio control of the second low-temperature side three-way valve **52b**, the temperature of the low-temperature side heat medium mixed in the twelfth heat medium joint part **53m** approaches the strong current device target temperature TWLO2. The low-temperature side heat medium mixed in the twelfth heat medium joint part **53m** is sucked into the second low-temperature side pump **51b**. The low-temperature side heat medium pressure-fed from the second low-temperature side pump **51b** flows into the cooling water passage **81a** of the strong current device **81**. As a result, the strong current device **81** is cooled.

(417) According to the air conditioner **1a** of the present embodiment, comfortable air conditioning of the vehicle interior and appropriate temperature adjustment of a plurality of in-vehicle devices can be performed by appropriately combining and executing the air conditioning operation mode and the temperature adjusting operation mode, as described above.

(418) Furthermore, also in the air conditioner **1a** of the present embodiment, the heating preparation control can be executed similarly to the first embodiment.

(419) Specifically, in the step S2 of the heating preparation control in the present embodiment, the control device **60** brings the air-cooling expansion valve **14b** into a fully closed state and brings the cooling expansion valve **14c** into a throttled state in order to execute the heating preparation control.

(420) Therefore, in the heat pump cycle **10a** under the heating preparation control, a refrigerant circuit is switched to, in which the refrigerant discharged from the compressor **11** circulates in the order of the water-refrigerant heat exchanger **12**, the receiver **23**, the cooling expansion valve **14c**, the chiller **20**, and the suction port of the compressor **11**, as indicated by dashed arrows in FIG. **12**.

(421) In addition, the control device **60** controls the operation of the high-temperature side pump **41** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the high-temperature side three-way valve **43** such that the high-

temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to the heater core **42** side.

(422) Therefore, in the high-temperature side heat medium circuit **40a** during the heating preparation control, the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the heater core **42**, and the suction port of the high-temperature side pump **41**, as indicated by solid arrows in FIG. **12**.

(423) In addition, the control device **60** controls the operation of the first low-temperature side pump **51a** so as to exert predetermined pressure-feeding capability. In addition, the control device **60** controls the operation of the first low-temperature side three-way valve **52a** such that the low-temperature side heat medium flowing out of the heat medium passage **20b** of the chiller **20** is caused to flow into the cooling water passage **80a** of the battery **80**.

(424) Therefore, in the low-temperature side heat medium circuit **50a** under the heating preparation control, the low-temperature side heat medium pressure-fed from the first low-temperature side pump **51a** circulates in the order of the heat medium passage **20b** of the chiller **20**, the electric heater **54**, and the suction port of the first low-temperature side pump **51a**, as indicated by the solid arrows in FIG. **12**. That is, in the low-temperature side heat medium circuit **50a** under the heating preparation control, a circuit is switched to, in which the low-temperature side heat medium heated by the electric heater **54** flows while bypassing the cooling water passage **80a** of the battery **80**.

(425) The other operations under the heating preparation control are the same as those in the first embodiment. Therefore, the same effects as those in the first embodiment can be obtained also in the heating preparation control in the air conditioner **1a** of the present embodiment. That is, the heating capability of the heating part can be promptly increased using the heat generated by the electric heater **54**. As a result, it is possible to realize air conditioning with immediate effectiveness and high responsiveness.

#### Fifth Embodiment

(426) In the present embodiment, an example will be described in which an inlet side connection passage **91a**, an outlet side connection passage **92a**, and the like are added to the air conditioner **1a** of the fourth embodiment, as illustrated in the overall configuration view of FIG. **13**. The inlet side connection passage **91a** and the outlet side connection passage **92a** form a heat medium flow path that connects the high-temperature side heat medium circuit **40a** and the low-temperature side heat medium circuit **50a**.

(427) In the high-temperature side heat medium circuit **40a** of the present embodiment, a high-temperature side four-way valve **43a** is disposed instead of the high-temperature side three-way valve **43**. The high-temperature side four-way valve **43a** causes the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** to flow into its inside, and causes the high-temperature side heat medium to flow out to at least one of the heater core **42** side, the high-temperature side radiator **44** side, and the inlet side connection passage **91a** side.

(428) The high-temperature side four-way valve **43a** can adjust the flow ratio among the flow rate of the high-temperature side heat medium that is caused to flow out to the heater core **42** side, the flow rate of the high-temperature side heat medium that is caused to flow out to the high-temperature side radiator **44** side, and the flow rate of the high-temperature side heat medium that is caused to flow out to the inlet side connection passage **91a** side. Furthermore, by adjusting the flow ratio, the high-temperature side four-way valve **43a** can cause the total flow rate of the high-temperature side heat medium that has been caused to flow into its inside to flow out to any one of the heater core **42** side, the high-temperature side radiator **44** side, and the inlet side connection passage **91a** side.

(429) That is, the high-temperature side four-way valve **43a** serves as a heat medium circuit switching part. The operation of the high-temperature side four-way valve **43a** is controlled by a

control signal output from control device **60**.

(430) Furthermore, in the high-temperature side heat medium circuit **40a**, a first four-way joint part **53q** is disposed instead of the eighth heat medium joint part **53h**. The first four-way joint part **53q** is a four-way joint part having four inflow outlets communicating with each other. As the first four-way joint part **53q**, a joint member formed in the same manner as the first refrigerant joint part **13a** or the like can be adopted.

(431) In the low-temperature side heat medium circuit **50a** of the present embodiment, a fourteenth heat medium joint part **53p** is disposed. The fourteenth heat medium joint part **53p** is disposed in the heat medium flow path extending from the outflow port of the third low-temperature side three-way valve **52c** to the inlet of the cooling water passage **80a** of the battery **80**.

(432) Furthermore, in the low-temperature side heat medium circuit **50a**, a second four-way joint part **53r** is disposed instead of the eleventh heat medium joint part **53k**. The basic configuration of the second four-way joint part **53r** is similar to that of the first four-way joint part **53q**.

(433) The inlet portion of the inlet side connection passage **91a** is connected to one outflow port of the high-temperature side four-way valve **43a**. The outlet portion of the inlet side connection passage **91a** is connected to one inflow port of the fourteenth heat medium joint part **53p**. The inlet portion of the outlet side connection passage **92a** is connected to one outflow port of the second four-way joint part **53r**. The outlet portion of the outlet side connection passage **92a** is connected to one inflow port of the first four-way joint part **53q**. The other configurations of the air conditioner **1a** are similar to those of the fourth embodiment.

(434) Next, the operation of the air conditioner **1a**, having the above configuration, of the present embodiment will be described. During the normal operation in the air conditioner **1a** of the present embodiment, the control device **60** controls the operation of the high-temperature side four-way valve **43a** such that the high-temperature side heat medium circuit **40a** becomes the same circuit as that of the fourth embodiment. Therefore, during the normal operation, the high-temperature side heat medium never flows out from the high-temperature side four-way valve **43a** to the inlet side connection passage **91a** side.

(435) Therefore, also in the air conditioner **1a** of the present embodiment, comfortable air conditioning of the vehicle interior and appropriate temperature adjustment of a plurality of in-vehicle devices can be performed by appropriately combining and executing the air conditioning operation mode and the temperature adjusting operation mode. Furthermore, the heating capability of the heating part can be promptly increased by performing the heating preparation control, similarly to the fourth embodiment. As a result, it is possible to realize air conditioning with immediate effectiveness and high responsiveness.

(436) In the present embodiment, when the heating preparation control is being executed and the battery temperature **TB** is equal to or lower than the predetermined reference warm-up temperature **KTBL**, the control device **60** controls the operation of the high-temperature side four-way valve **43a** such that the high-temperature side heat medium flowing out of the heat medium passage **12b** of the water-refrigerant heat exchanger **12** is caused to flow out to both the heater core **42** side and the inlet side connection passage **91a** side.

(437) Therefore, when warm-up of the battery **80** is required during the execution of the heating preparation control in the air conditioner **1a** of the present embodiment, a circuit is switched to, in which the high-temperature side heat medium pressure-fed from the high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the high-temperature side four-way valve **43a**, the heater core **42**, and the suction port of the high-temperature side pump **41**, as indicated by solid arrows in FIG. **13**. At the same time, a circuit is switched to, in which the high-temperature side heat medium pressure-fed from high-temperature side pump **41** circulates in the order of the heat medium passage **12b** of the water-refrigerant heat exchanger **12**, the high-temperature side four-way valve **43a**, the inlet-side connection passage **91a**, the cooling water passage **80a** of the battery the outlet side connection passage **92a**, and the suction

port of the high-temperature side pump **41**. That is, circuits are switched to, in which the heater core **42** and the cooling water passage **80a** of the battery **80** are connected in parallel for the flow of the high-temperature side heat medium.

(438) According to this, when the compressor **11** is operated in the step S5 of the heating preparation control described in the first embodiment, the high-temperature side heat medium can be heated by the water-refrigerant heat exchanger **12**. Then, at least a part of the high-temperature side heat medium heated by the water-refrigerant heat exchanger **12** can be caused to flow into the cooling water passage **80a** of the battery **80** via the high-temperature side four-way valve **43a** and the inlet side connection passage **91a**. As a result, the battery **80** can be warmed up.

(439) The high-temperature side heat medium flowing out of the cooling water passage **80a** of the battery **80** is sucked into the high-temperature side pump **41** via the outlet side connection passage **92a**.

(440) The other operations are the same as those in the first embodiment. Therefore, according to the air conditioner **1a** of the present embodiment, the battery can be warmed up during the execution of the heating preparation control.

(441) The present disclosure is not limited to the above-described embodiments, and can be variously modified as follows within the scope that does not deviate from the gist of the present disclosure.

(442) In the above-described embodiments, examples have been described in which the air conditioners **1** and **1a** according to the present disclosure are applied to an electric car, but the application of the air conditioner **1** is not limited thereto. For example, the air conditioner **1** may be applied to a hybrid vehicle that obtains driving force for traveling from an electric motor and an internal combustion engine (i.e., an engine), and further to a plug-in hybrid vehicle that can charge a battery with electric power supplied from an external power supply while the vehicle is stopped.

(443) The air conditioner **1** may also be applied to a stationary air conditioner or the like with a temperature adjustment function that adjusts the temperature of an object whose temperature is to be adjusted (e.g., a computer, a computer server device, and other electric devices) while air conditioning the room.

(444) In the above-described embodiments, an example has been described in which an inverter and a motor generator are adopted as the strong current device **81**, but the strong current device **81** is not limited thereto. For example, a charging device, a power control unit (so-called PCU), a transaxle, an ADAS control device, or the like may be adopted as the strong current device **81**.

(445) The charging device is an in-vehicle charger that charges the battery **80** with regenerative power or the like. The PCU is a power control device that performs transformation of electric power and power distribution. The transaxle is a power transmission mechanism in which a transmission, a differential gear, and the like are integrated. The ADAS control device is a control device for an advanced driver assistance system. When the air conditioner **1** is applied to the stationary air conditioner, it may be configured such that other heat generating devices are cooled.

(446) The respective configurations of the heat pump cycles **10** and **10a** are not limited to the configurations disclosed in the above-described embodiments.

(447) For example, an example has been described in the above-described embodiments, in which the third check valve **17c** whose refrigerant passage has a relatively small cross-sectional area is adopted as the indoor unit outlet side opening/closing part. However, the indoor unit outlet side opening/closing part may be formed by combining an evaporating pressure regulating valve and a normal check valve.

(448) The evaporating pressure regulating valve is a variable throttle mechanism that, in order to suppress frosting in the indoor evaporator **18**, changes a valve opening degree such that the refrigerant evaporating pressure in the indoor evaporator **18** is maintained to be equal to or higher than a predetermined set pressure. As the evaporating pressure regulating valve, a mechanical mechanism, that increases a valve opening degree as the flow rate of a refrigerant flowing through

its inside increases, can be adopted.

(449) In the second embodiment, an example has been described in which the water-refrigerant heat exchanger **12** and the receiver **23** are adopted, but the present disclosure is not limited thereto. For example, a so-called sub-cooling heat exchanger, including a condensing part that condenses a refrigerant, a liquid receiving part that separates the gas and liquid of the refrigerant condensed by the condensing part and stores a liquid-phase refrigerant, and a super-cooling part that super-cools the liquid-phase refrigerant flowing out of the liquid receiving part, may be adopted.

(450) In addition, a plurality of components may be integrated or separated within a range in which the above-described effects can be obtained. For example, the fourth refrigerant joint part **13d** and the sixth refrigerant joint part **13f** may be integrated similarly to the first four-way joint part **53q**.

(451) In the above embodiments, an example has been described in which R1234yf is adopted as the refrigerant, but the refrigerant is not limited thereto. For example, R134a, R600a, R410A, R404A, R32, R407C, or the like may be adopted. Alternatively, a mixed refrigerant obtained by mixing a plurality of kinds of these refrigerants, or the like, may be adopted. Furthermore, carbon dioxide may be adopted as the refrigerant to form a supercritical refrigeration cycle in which the high-pressure side refrigerant pressure is equal to or higher than the critical pressure of the refrigerant.

(452) The respective configurations of the high-temperature side heat medium circuits **40** and **40a** and the low-temperature side heat medium circuits **50** and **50a** are not limited to the configurations disclosed in the above-described embodiments.

(453) For example, an example has been described in the above-described embodiments, in which the PTC heater is adopted as the electric heater **54** that is the heat generating part, but the heater is not limited thereto. For example, a nichrome wire, a carbon fiber heater, or the like may be adopted. Furthermore, a strong current device can also be adopted as the heat generating part. For example, the ADAS control device may be adopted as the heat generating part, and a calorific value may be adjusted by performing an inefficient operation.

(454) In addition, a plurality of components may be integrated or separated within a range in which the above-described effects can be obtained. For example, the first low-temperature side three-way valve **52a**, second low-temperature side three-way valve **52b**, and first heat medium joint part **53a** of the first to third embodiments may be integrated as a five-way valve having five heat medium inflow outlets. In addition, the first four-way joint part **53q** and the second four-way joint part **53r** may be formed by combining two three-way joints.

(455) In the above-described embodiments, an example has been described in which an ethylene glycol aqueous solution is adopted as the high-temperature side heat medium and the low-temperature side heat medium, but the heat media are not limited thereto. For the high-temperature side heat medium circuits **40** and **40a**, a solution containing dimethylpolysiloxane, nano-fluid, or the like, an antifreeze, an aqueous liquid refrigerant containing alcohol or the like, a liquid medium containing oil or the like, or the like may be adopted.

(456) The operations of the air conditioners **1** and **1a** are not limited to the above-described operation modes. The air conditioners **1** and **1a** may be configured to be able to execute other operation modes. As long as the air conditioner **1** or **1a** has an operation mode in which the ventilation air is heated by at least a heating part, it is possible to obtain an effect that the heating capability of the heating part can be promptly increased by the above-described heating preparation control.

(457) In addition, in the step S2 of the above-described heating preparation control, an example, in which the compressor **11** is stopped, has been described, but the present disclosure is not limited thereto. For example, as the reference discharge capability for the heating preparation control, a lower limit value in a possible range of the number of rotation (refrigerant discharge capability) of the compressor **11** that is assumed during normal operation, or a value lower than the lower limit value, may be adopted.

(458) In addition, in the step S2 of the above-described heating preparation control, an example, in which the indoor blower 32 is stopped, has been described, but the present disclosure is not limited thereto. For example, as the reference blowing capability for the heating preparation control, a lower limit value in a possible range of the number of rotation (blowing capability) of the indoor blower 32 that is assumed during normal operation, or a value lower than the lower limit value, may be adopted.

(459) Although the present disclosure has been described in accordance with embodiments, it is understood that the present disclosure is not limited to the embodiments and the structures. The present disclosure also encompasses various modifications and variations within the scope of equivalents. In addition, various combinations and modes, and other combinations and modes including only one element, more elements, or less elements are also within the scope and idea of the present disclosure.

## Claims

1. An air conditioner comprising: a heat pump cycle including a compressor configured to compress and discharge a refrigerant, a heating part configured to heat air to be blown into a space to be air-conditioned using a high-pressure refrigerant discharged from the compressor as a heat source, and a low-temperature side water-refrigerant heat exchanger configured to cause a low-pressure refrigerant to absorb heat of a heat medium; a heat medium circuit in which the heat medium is circulated, the heat medium circuit being provided with a heat medium passage of the low-temperature side water-refrigerant heat exchanger, and a heat generating part configured to heat the heat medium to flow into the heat medium passage of the low-temperature side water-refrigerant heat exchanger; a blower configured to blow the air toward the space to be air-conditioned; and a controller configured to set a heating preparation control in a case where a heating capability of the heating part is increased by using the heat generated by the heat generating part, wherein in the heating preparation control, the controller is configured to set a refrigerant discharge capability of the compressor to be equal to or less than a predetermined reference discharge capability, and to set a blowing capability of the blower to be equal to or less than a predetermined reference blowing capability, until an inlet-side heat medium temperature of the heat medium flowing into the heat medium passage of the low-temperature side water-refrigerant heat exchanger becomes equal to or higher than a target heat medium temperature.
2. The air conditioner according to claim 1, wherein, in the heating preparation control, the controller is configured to increase the refrigerant discharge capability of the compressor when the inlet side heat medium temperature becomes equal to or higher than the target heat medium temperature.
3. The air conditioner according to claim 2, wherein, in the heating preparation control, the controller is configured to increase the blowing capability of the blower when the inlet-side heat medium temperature becomes equal to or higher than the target heat medium temperature and the heating capability of air in the heating part becomes equal to or higher than a predetermined reference heating capability.
4. The air conditioner according to claim 1, wherein the controller is configured to perform the heating preparation control, when a value obtained by subtracting an actual heating capability of the heating part from the reference heating capability of the heating part is equal to or larger than a predetermined reference value.
5. The air conditioner according to claim 1, wherein the heat pump cycle includes an indoor evaporator configured to exchange heat between the low-pressure refrigerant and the air, an inlet side opening/closing part configured to open or close a refrigerant inlet side of the indoor evaporator, and an outlet side opening/closing part configured to open or close a refrigerant outlet side of the indoor evaporator, the indoor evaporator and the low-temperature side water-refrigerant

heat exchanger are connected in parallel with respect to a flow of the refrigerant, and the inlet side opening/closing part and the outlet side opening/closing part are configured to close the refrigerant inlet side and the refrigerant outlet side of the indoor evaporator in the heating preparation control.

6. The air conditioner according to claim 1, wherein the heat medium circuit is provided with a cooling water passage of a battery and a heat medium circuit switching part that switches a circuit configuration, and when the heating preparation control is executed by the controller, the heat medium circuit switching part switches to a circuit in which the heat medium flows while bypassing the cooling water passage.

7. The air conditioner according to claim 1, further comprising: a target heat-medium temperature determination unit configured to determine the target heat medium temperature, wherein the target heat medium temperature determination unit is configured to raise the target heat medium temperature as the temperature of the air flowing into the heating part lowers.

8. The air conditioner according to claim 1, further comprising: a target heat-medium temperature determination unit configured to determine the target heat medium temperature; and a target blowing capability determination unit configured to determine a target blowing capability of the blower, wherein the target heat-medium temperature determination unit is configured to raise the target heat medium temperature as the target blowing capability increases.

---