

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404163
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kang; Wanku

Water discharge unit and water purifier including same

Abstract

A water purifier including a water discharge unit configured so that purified, cold, and hot water are selectably dischargeable therethrough, the water discharge unit including a rotatable body, a water discharge tube having a changeable position according to rotation of the body, and a display device including a first and a second light source, a light guide cover, and a guide case to guide light emitted from the first and second light source so as to be incident on the light guide cover, and to prevent mixing of the light from the first and the second light sources. The light guide cover projects the light from the first light source in a direction of water discharge from the water discharge tube, and projects the light from the second light source toward an outer peripheral surface of the display device to indicate which of purified, cold, and hot water is selected.

Inventors:	Kang; Wanku (Suwon-si, KR)
Applicant:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Family ID:	83048308
Assignee:	SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)
Appl. No.:	18/208972
Filed:	June 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230322542 A1	Oct. 12, 2023

Foreign Application Priority Data

KR	10-2021-0024385	Feb. 23, 2021
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **F21V33/00** (20060101); **B67D1/08** (20060101); **E03C1/04** (20060101); **F21V19/00** (20060101); **F21V23/04** (20060101)

U.S. Cl.:

CPC **B67D1/0872** (20130101); **B67D1/0888** (20130101); **E03C1/0404** (20130101); **F21V19/006** (20130101); **F21V23/0471** (20130101); **F21V33/006** (20130101); **B67D2210/0001** (20130101); **E03C2201/40** (20130101)

Field of Classification Search

CPC: F21V (33/004); F21V (33/006); E03C (1/0404); B67D (2210/0001)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6439472	12/2001	Lin et al.	N/A	N/A
11549243	12/2022	Jeong et al.	N/A	N/A
2006/0289343	12/2005	Schmitt	137/553	E03C 1/04
2007/0199886	12/2006	Korb et al.	N/A	N/A
2010/0213398	12/2009	Brunner et al.	N/A	N/A
2013/0100650	12/2012	Beregszaszi	N/A	N/A
2016/0146358	12/2015	Lin	137/636.4	E03C 1/04
2021/0000289	12/2020	Krüger et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105508659	12/2015	CN	F16K 11/072
109882629	12/2018	CN	N/A
111386060	12/2019	CN	N/A
20 2006 012 383	12/2007	DE	N/A
3 760 795	12/2020	EP	N/A
07-42211	12/1994	JP	N/A
2001-123485	12/2000	JP	N/A
2002-294775	12/2001	JP	N/A
2003-064743	12/2002	JP	N/A
4342894	12/2008	JP	N/A
4360092	12/2008	JP	N/A
20-0237689	12/2000	KR	N/A
10-1146626	12/2011	KR	N/A
10-2012-0076945	12/2011	KR	N/A
10-1459498	12/2013	KR	N/A
10-1633929	12/2015	KR	N/A

10-2016-0077017	12/2015	KR	N/A
10-1808831	12/2016	KR	N/A
10-2018-0063657	12/2017	KR	N/A
10-1901614	12/2017	KR	N/A
10-1902386	12/2017	KR	N/A
10-2019-0065848	12/2018	KR	N/A
10-2020-0133315	12/2019	KR	N/A
WO-9105114	12/1990	WO	E03C 1/0404
WO-2006072399	12/2005	WO	E03C 1/0404
WO 2013/062511	12/2012	WO	N/A

OTHER PUBLICATIONS

International Search Report issued in PCT/KR2022/00240 on May 12, 2022. cited by applicant
Extended European Search Report dated Apr. 19, 2024 for European Application No. 22759894.3.
cited by applicant

Primary Examiner: Song; Zheng

Attorney, Agent or Firm: STAAS & HALSEY LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application under 35 U.S.C. § 111(a) of international Application No. PCT/KR2022/000240, filed on Jan. 6, 2022, which claims priority to Korean Patent Application No. 10-2021-0024385, filed on Feb. 23, 2021, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) The present disclosure relates to a water discharge unit and a water purifier including the same, and more particularly, to a water purifier equipped with a display device.

2. Description of the Related Art

(2) A water purifier is a device that provides drinking water to a user by removing harmful substances contained in raw water such as tap water or groundwater through various water purification methods such as precipitation, filtration, and sterilization. The water purifier is provided to supply clean water to the user by one or more water purification filters filtering the water introduced thereinto.

(3) When classified based on form, water purifiers may be classified into a direct connection type in which the water purifier is directly connected to a faucet and a storage type in which water is held in a container and caused to pass through a filter, and when classified according to the water purification principle or method, water purifiers may be classified into a natural filtration type, a direct filtration type, an ion exchange resin type, a distillation type, and a reverse osmosis type.

(4) In the direct filtration type water purifier, the water purifier is directly connected to a water pipe, and as water passes through a filter due to water pressure, impurities are filtered from the water. The water purified in this way may be discharged through a faucet and used as drinking water. The faucet may also be referred to as a water discharge unit.

(5) In the direct filtration type water purifier, a main body in which the filter is embedded may be disposed in a space under a sink, and the faucet may be provided in the sink. This type of water purifier is referred to as an under-sink water purifier.

(6) In many cases, the faucet of the under-sink water purifier is provided to rotate to promote user convenience by enabling the position of a water discharge hole to be changed. In this case, due to a change in the position of the water discharge hole, it may be difficult for the user to intuitively recognize the position of water discharge.

(7) Also, there is a need for a user, who is washing dishes or cooking, to be able to immediately obtain information on water currently being discharged from a faucet without keeping an eye on a display of the faucet.

SUMMARY

(8) Aspects of embodiments of the disclosure will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(9) According to an embodiment of the disclosure, a water purifier includes a main body arrangeable in a lower space of a cabinet; and a water discharge unit connected to the main body so that, when the main body is arranged in the lower space of the cabinet, at least a portion of the water discharge unit is exposed to an upper side of the cabinet, and purified water, cold water, and hot water are selectably dischargeable through the water discharge unit, wherein the water discharge unit includes a body configured to be rotatable, a water discharge tube having a position that is changeable according to rotation of the body, and a display device including a first light source, a second light source, a light guide cover, and a guide case configured to guide light emitted from the first light source and light emitted from the second light source so as to be incident on the light guide cover, and to prevent the light emitted from the first light source from being mixed with the light emitted from the second light source, wherein the light guide cover is configured to project the light emitted from the first light source and incident on the light guide cover in a direction of water discharge from the water discharge tube to indicate the direction of water discharge, and project the light emitted from the second light source and incident on the light guide cover toward an outer peripheral surface of the display device to indicate which of purified water, cold water, and hot water is selected.

(10) According to an embodiment of the disclosure, the guide case and the light guide cover surround the water discharge tube.

(11) According to an embodiment of the disclosure, the guide case includes a first guide hole configured to guide the light emitted from the first light source so as to be incident on the light guide cover, and a second guide hole spaced apart from the first guide hole and configured to guide the light emitted from the second light source so as to be incident on the light guide cover.

(12) According to an embodiment of the disclosure, the display device includes a diffusion space formed between the guide case and the light guide cover, and partitioned from the first guide hole, the diffusion space being configured to communicate with the second guide hole, and the light guide cover includes a sidewall portion having an inner peripheral surface configured to form the diffusion space, and a light-emitting rib configured to protrude from an outer peripheral surface of the sidewall portion so as to be exposed to the outer peripheral surface of the display device.

(13) According to an embodiment of the disclosure, the light guide cover projects the light emitted from the second light source, which is guided to the diffusion space and is incident on an inner peripheral surface of the light guide cover, through the light-emitting rib.

(14) According to an embodiment of the disclosure, the light guide cover includes a bottom wall portion configured to form a lower surface of the display device and cover a lower end of the first guide hole, and the light emitted from the first light source guided by the first guide hole and incident on the light guide cover passes through the bottom wall portion and is projected in the direction of water discharge.

(15) According to an embodiment of the disclosure, the light guide cover includes a lens provided on the bottom wall portion at a position corresponding to the first guide hole and configured to condense the light emitted from the first light source and incident on the light guide cover that is

guided by the first guide hole.

(16) According to an embodiment of the disclosure, the display device further includes a light shielding member disposed on the bottom wall portion to prevent the light emitted from the second light source and incident on the light guide cover from passing through the bottom wall portion.

(17) According to an embodiment of the disclosure, the guide case includes a leakage reducing curved surface formed on an upper end of the first guide hole to allow the first light source to be seated in the leakage reducing curved surface, and configured to reduce leakage of the light emitted from the first light source.

(18) According to an embodiment of the disclosure, the water discharge unit further includes a detecting sensor configured to detect an approach of a user, and a controller configured to control the detecting sensor, the first light source, and the second light source, and, in response to the detecting sensor detecting the approach of the user, the controller turns on the first light source.

(19) According to an embodiment of the disclosure, the second light source emits rays of light of a plurality of different colors, and, in response to any one of the purified water, cold water, and hot water being selected, the controller controls the second light source to emit light of a color, among the plurality of different colors, corresponding to the selection of any one of the purified water, cold water, and hot water.

(20) According to an embodiment of the disclosure, the water discharge unit includes a display configured to output an image, and, in response to the detecting sensor detecting the approach of the user, the controller turns on the display as well as the first light source.

(21) According to an embodiment of the disclosure, the light guide cover includes a coupling hook extending upward so as to be fastenable to the guide case to couple the light guide cover to the guide case.

(22) According to an embodiment of the disclosure, the guide case forms a hollow portion through which the water discharge tube passes.

(23) According to an embodiment of the disclosure, the cabinet includes a sink, and when the main body is arranged in the lower space of the cabinet, the body of the water discharge unit is couplable to the sink so as to be rotatable.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and/or other embodiments of the disclosure will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings of which:

(2) FIG. 1 is a view schematically illustrating a water purifier according to an embodiment of the disclosure.

(3) FIG. 2 is a perspective view of a water discharge unit illustrated in FIG. 1 according to an embodiment of the disclosure.

(4) FIG. 3 is a lateral cross-sectional view of the water discharge unit illustrated in FIG. 2 according to an embodiment of the disclosure.

(5) FIG. 4 is an enlarged view of portion A of FIG. 3 according to an embodiment of the disclosure.

(6) FIG. 5 is a perspective view of a display device illustrated in FIG. 2 according to an embodiment of the disclosure.

(7) FIG. 6 is a bottom perspective view of the display device illustrated in FIG. 2 according to an embodiment of the disclosure.

(8) FIG. 7 is an exploded view of a light source module and a guide assembly in the display device illustrated in FIG. 5 according to an embodiment of the disclosure.

(9) FIG. 8 is an exploded view of the light source module illustrated in FIG. 7 according to an

embodiment of the disclosure.

(10) FIG. 9 is an exploded view of the guide assembly illustrated in FIG. 7 according to an embodiment of the disclosure.

(11) FIG. 10 is a cross-sectional view taken along line X-X' of FIG. 5 according to an embodiment of the disclosure.

(12) FIG. 11 is a cross-sectional view taken along line Y-Y' of FIG. 5 according to an embodiment of the disclosure.

(13) FIG. 12 is a control block diagram of the water purifier illustrated in FIG. 1 according to an embodiment of the disclosure.

(14) FIG. 13 is a flowchart of a control method of the water purifier illustrated in FIG. 1 according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(15) Embodiments described herein and configurations illustrated in the drawings are merely exemplary embodiments of the present disclosure, and various modifications which may replace the embodiments and the drawings herein may be present at the time of filing this application.

(16) Also, like reference numerals or symbols presented in the drawings of the application indicate parts or elements that perform substantially the same functions.

(17) Also, terms used herein are for describing the embodiments and are not intended to limit and/or restrict the disclosure. A singular expression includes a plural expression unless context clearly indicates otherwise. In the application, terms such as “include” or “have” are for designating that features, numbers, steps, operations, elements, parts, or combinations thereof are present, and do not preclude the possibility of presence or addition of one or more other features, numbers, steps, operations, elements, parts, or combinations thereof in advance.

(18) Also, terms including ordinals such as “first” and “second” used herein may be used to describe various elements, but the elements are not limited by the terms, and the terms are only used for the purpose of distinguishing one element from another element. For example, a first element may be referred to as a second element while not departing from the scope of rights of the present disclosure, and likewise, a second element may also be referred to as a first element. The term “and/or” includes a combination of a plurality of associated listed items or any one item among the plurality of associated listed items.

(19) Meanwhile, terms such as “upward,” “downward,” “front end,” and “rear end” used in the following description are defined based on the drawings, and the shape and position of each element are not limited by the terms.

(20) Embodiments of the present disclosure may provide a water discharge unit which can provide pieces of information on water being discharged, and a water purifier including the same.

(21) According to example embodiments of the present disclosure, a water discharge unit may use light to make a user recognize a position to which water will be discharged.

(22) According to example embodiments of the present disclosure, a water discharge unit can use light to notify a user of information on a user's selection.

(23) According to an example embodiment of the present disclosure, a plurality of indicators configured to provide pieces of different information using light can be provided in a single device, and thus, while size reduction is promoted, rays of light of the plurality of indicators can be clearly recognized by the user without being mixed with each other.

(24) FIG. 1 is a view schematically illustrating a water purifier according to one embodiment of the present disclosure.

(25) Referring to FIG. 1, a water purifier 1 may include a water purifier main body (or “main body”) 10 and a water discharge unit 100 connected to the water purifier main body 10 and configured to discharge water to an outside of the water purifier main body 10. The water purifier main body 10 may be disposed in a lower space of a cabinet, such as a kitchen cabinet 2, and the water discharge unit 100 may be disposed so that at least a portion is exposed to an upper portion

of the kitchen cabinet **2**. The kitchen cabinet **2** may include a sink. The sink may include a sink and a kitchen countertop. The water discharge unit **100** may be referred to as a faucet.

(26) The water discharge unit **100** may be installed on an upper portion of the kitchen cabinet **2**. The water discharge unit **100** may be installed on an upper portion of the sink. The water discharge unit **100** may be rotatably provided on the upper portion of the kitchen cabinet **2**. The water discharge unit **100** may be connected to the water purifier main body **10** through connecting members **40**.

(27) The water purifier main body **10** may be disposed inside the kitchen cabinet **2**. The water purifier main body **10** may include a filter unit **20** including at least one or more filters **21** and a heat exchange unit **30** provided to cool or heat water purified by the filter unit **20**. Although not illustrated, the heat exchange unit **30** may include a heater and a refrigeration cycle device which includes a compressor, a condenser, an expansion valve, and an evaporator.

(28) The water purifier main body **10** may receive raw water such as tap water through an external pipe **43**.

(29) The connecting members **40** connected to the water purifier main body **10** may include a first pipe **41** connected to the water discharge unit **100** and a second pipe **42** connected to a faucet **400** installed in the kitchen cabinet **2**. The first pipe **41** may include a plurality of first pipes **41**.

(30) An installation site **3** for installation of the water discharge unit **100** may be provided in the kitchen cabinet **2**. The installation site **3** may be formed by at least a portion of the kitchen cabinet **2** being open. The first pipe **41** and the water discharge unit **100** may be connected through the installation site **3** of the kitchen cabinet **2**.

(31) The water discharge unit **100** may be rotatably installed at the installation site **3**. The water purifier **1** may include a rotating device **200** configured to rotatably install the water discharge unit **100** at the installation site **3**. The rotating device **200** may be coupled to the kitchen cabinet **2**.

(32) The water purifier **1** may include a pipe fixing device **300** provided to fix the pipes **40**. The pipe fixing device **300** may be disposed inside the kitchen cabinet **2**. The pipe fixing device **300** may be disposed between the water purifier main body **10** and the water discharge unit **100**. The pipe fixing device **300** may be fixed to at least any one of the water purifier main body **10** and the water discharge unit **100**. A portion of the pipes **40** may be wound around the pipe fixing device **300**, and a length of the pipes **40** may be extended or shortened according to the portion of the pipes **40** being unwound from or wound around the pipe fixing device **300**.

(33) FIG. **2** is a perspective view of the water discharge unit illustrated in FIG. **1**. FIG. **3** is a lateral cross-sectional view of the water discharge unit illustrated in FIG. **2**. FIG. **4** is an enlarged view of portion A of FIG. **3**.

(34) Referring to FIGS. **2** to **4**, the water discharge unit **100** may include a body **110** forming an exterior and in which various parts may be disposed. The body **110** may be formed in a substantially L-shape. One side of the body **110** may be rotatably coupled to the kitchen cabinet **2**. Specifically, the body **110** may include a neck housing **120** extending substantially upward and a head housing **130** extending substantially horizontal from an upper end of the neck housing **120**, and a lower end of the neck housing **120** may be rotatably coupled to the kitchen cabinet **2** by the rotating device **200**.

(35) The neck housing **120** and the head housing **130** may be separately formed and coupled to each other, or the neck housing **120** and the head housing **130** may be integrally formed.

(36) The neck housing **120** may be perpendicular to or tilted from one surface of the kitchen cabinet **2** on which the installation site **3** is formed.

(37) The water discharge unit **100** may include a water discharge tube **140** disposed at the other end of the body **110** which is the opposite side of one end of the body **110** that is coupled to the kitchen cabinet **2**. The water discharge tube **140** may be disposed at the other end of the head housing **130** which is the opposite side of one end of the head housing **130** that is connected to the neck housing **120**. The water discharge tube **140** may form a water discharge hole **141** through which water is

discharged to an outside of the water discharge unit **100**. The water discharge tube **140** may extend in an up-down direction, and the water discharge hole **141** may be disposed at a lower portion of the other end of the body **110**. Since the water discharge tube **140** may be fixed to the head housing **130**, the position of the water discharge tube **140** may be changeable according to rotation of the body **110**.

(38) The water discharge unit **100** may include one or more pipes **171**, **172**, **173**, **174**, and **175** disposed inside the body **110**. Water supplied by the water purifier main body **10** may flow inside the pipes **171**, **172**, **173**, **174**, and **175**. The one or more pipes **171**, **172**, **173**, **174**, and **175** may form a water discharge flow path **180** to allow the water supplied by the water purifier main body **10** to flow. The pipes **171**, **172**, **173**, **174**, and **175** may be connected to the water discharge tube **140**. The water discharge flow path **180** may communicate with the water discharge hole **141**.

(39) The one or more pipes **171**, **172**, **173**, **174**, and **175** may include first to third pipes **171**, **172**, and **173** and first and second elbow pipes **174** and **175**. One end of the first pipe **173** may be connected to the first pipe **41** by a connector, and the other end of the first pipe **173** may be connected to a water discharge valve **150**. One end of the second pipe **172** may be connected to the water discharge valve **150**, and the other end of the second pipe **172** may be connected to the third pipe **171** by the first elbow pipe **174**. The third pipe **171** may be connected to the water discharge tube **140** by the second elbow pipe **175**. Two or more of the first pipe **173**, the second pipe **172**, the third pipe **171**, the first elbow pipe **174**, and the second elbow pipe **175** may be integrally formed. Meanwhile, the present disclosure is not limited thereto, and the first pipe **173** may be omitted, and the first pipe **41** may be directly connected to the water discharge valve **150**.

(40) The water discharge unit **100** may include the water discharge valve **150** configured to turn the water on or off. That is, the water discharge valve **150** may control whether water is discharged through the water discharge hole **141**. The water discharge valve **150** may be disposed in the water discharge flow path **180**. The water discharge valve **150** may regulate water flowing from the first pipe **173** to the second pipe **172**. That is, the water discharge valve **150** may open and close the water discharge flow path **180**. In other words, the water discharge valve **150** may selectively supply water to the inside of the pipes **171**, **172**, **174**, and **175** disposed at the opposite side of the first pipe **41** relative to the water discharge valve **150**.

(41) The water discharge valve **150** may be disposed inside the body **110**. The water discharge valve **150** may be disposed inside the neck housing **120**.

(42) The water discharge unit **100** may include a water discharge mechanism **101** configured to control the water discharge valve **150**. The water discharge mechanism **101** may control the water discharge valve **150** to control whether water is discharged through the water discharge hole **141**. The water discharge mechanism **101** may be made of a lever or a button.

(43) The water discharge unit **100** may include a display **160** configured to receive a touch input and output an image. The display **160** may form an upper surface of the water discharge unit **100**. Specifically, the head housing **130** may be open upward, and the display **160** may be coupled to the open upper end of the head housing **130** and cover an inner space of the head housing **130** in which various electronic parts are disposed.

(44) The display **160** may be disposed above the water discharge tube **140**. The display **160** may be disposed at the other end side of the head housing **130** which is the opposite side of the one end of the head housing **130** that is connected to the neck housing **120**. The display **160** may extend a predetermined length from the other end of the head housing **130** toward the one end of the head housing **130**.

(45) The display **160** may be electrically connected to the water purifier main body **10** by an electric wire or may be wirelessly connected to the water purifier main body **10**. The display **160** may receive a user's touch input for selecting a desired type of water and/or a user's touch input for selecting the amount of water discharged through the water discharge hole **141** and may transmit an input signal corresponding to the received touch input to the water purifier main body **10**. The

water purifier main body **10** which has received the input signal from the display **160** may supply the selected type of water to the water discharge unit **100** according to the input signal or control the amount of water supplied to the water discharge unit **100** according to the input signal.

(46) For example, selecting the amount of discharged water may be selecting one of 120 ml, 500 ml, 1,000 ml, and continuous water discharge. The continuous water discharge may refer to a state in which water is continuously discharged until the user operates the water discharge mechanism **101** to turn off the water.

(47) Meanwhile, water discharged through the water discharge hole **141** may be classified into purified water, cold water, and hot water according to whether the water is cooled or heated. The purified water may refer to water supplied to the water discharge unit **100** without separately cooling or heating raw water filtered by the filter **21**. The cold water may refer to water supplied to the water discharge unit **100** after raw water filtered by the filter **21** is cooled by the heat exchange unit **30**. The hot water may refer to water supplied to the water discharge unit **100** after raw water filtered by the filter **21** is heated by the heat exchange unit **30**. That is, the purified water, cold water, and hot water may correspond to water of different temperatures. Among the cold water, purified water, and hot water, the temperature of the cold water is the lowest, the temperature of the hot water is the highest, and the temperature of the purified water is higher than the temperature of the cold water and lower than the temperature of the hot water. Accordingly, selecting the type of water may correspond to selecting any one of the purified water, cold water, and hot water classified based on temperature.

(48) However, the present disclosure is not limited thereto. For example, water discharged from the water discharge unit **100** may be classified based on chemical configuration such as the concentration of a specific ion or based on state of matter, and selecting the type of water may correspond to selecting any one of various types of water classified based on such factors.

(49) The display **160** may output an image button to allow the user to input a selection of the purified water, cold water, or hot water or input a selection of the amount of discharged water. The user may touch an area of the display **160** where the image button appears and operate the water purifier main body **10**.

(50) The water discharge unit **100** may include the rotating device **200** configured to rotatably fix the body **110** to the installation site **3**. The rotating device **200** may include a cylindrical rotary bracket **202** having one end rotatably coupled to the lower end of the neck housing **120** and having a through-hole **201** through which the first pipe **41** passes formed therein and a fixing member **203** into which the rotary bracket **202** is inserted to be fixed. Specifically, screw threads may be formed on an outer side surface of the rotary bracket **202**, and in a state in which the rotary bracket **202** passes through the installation site **3**, the fixing member **203** may be, like a nut, screw-coupled to a portion of the rotary bracket **202** passing through the installation site **3**.

(51) The water discharge unit **100** may include a display device **500** configured to, by using light, provide information on water discharged from the water discharge tube **140**.

(52) The display device **500** may include a first indicator **510** configured to indicate a position of water discharge and a second indicator **520** configured to indicate a selection made by the user. The first indicator **510** and the second indicator **520** may be disposed adjacent to the water discharge tube **140**.

(53) The first indicator **510** may indicate a position at which water is discharged from the water discharge tube **140** in a state in which the water discharge tube **140** is moved to a specific position according to rotation of the body **110** (or “position of water discharge”). The selection made by the user that is indicated by the second indicator **520** may be the type of water. The second indicator **520** may indicate which of the purified water, cold water, and hot water the user has selected.

(54) The display device **500** may surround and cover an outer peripheral surface of the water discharge tube **140**. In other words, the water discharge tube **140** may be inserted into substantially the center of the display device **500**. Here, one end of the second elbow pipe **175** that is coupled to

the water discharge tube **140** may also be inserted into the display device **500**.

(55) The position of the display device **500** may be changed along with the position of the water discharge tube **140** according to rotation of the body **110**. The first indicator **510** may be formed on a lower surface of the display device **500**, and the second indicator **520** may be formed in an annular shape on an outer peripheral surface of the display device **500**.

(56) The first indicator **510** may radiate light to a portion under the water discharge tube **140** to form an image under the water discharge tube **140**. Specifically, the first indicator **510** may form an image on a surface of one area of the kitchen cabinet **2** that is positioned under the water discharge hole **141**. The user may intuitively identify the position of water discharge by looking at the image formed by the first indicator **510** and may place a container at the position where the image is formed and fill the container with water.

(57) The second indicator **520** may emit light to the outer peripheral surface of the display device **500**. The second indicator **520** may emit light of a color corresponding to the selection made by the user, and the user may, by looking at the color of light emitted by the second indicator **520**, check information on water discharged based on his or her selection. For example, in a case in which cold water is being discharged, the second indicator **520** may emit light of a first color, in a case in which hot water is being discharged, the second indicator **520** may emit light of a second color, and in a case in which purified water is being discharged, the second indicator **520** may emit light of a third color. The first to third colors may be different colors.

(58) FIG. 5 is a perspective view of a display device illustrated in FIG. 2. FIG. 6 is a bottom perspective view of the display device illustrated in FIG. 2. FIG. 7 is an exploded view of a light source module and a guide assembly in the display device illustrated in FIG. 5. FIG. 8 is an exploded view of the light source module illustrated in FIG. 7. FIG. 9 is an exploded view of the guide assembly illustrated in FIG. 7. FIG. 10 is a cross-sectional view taken along line X-X.sup.| of FIG. 5. FIG. 11 is a cross-sectional view taken along line Y-Y.sup.| of FIG. 5.

(59) Referring to FIGS. 5 to 11, the display device **500** may include a light source module **600** including a plurality of light sources **610** and **620** and a guide assembly **700** configured to guide light emitted from the light source module **600**.

(60) The light source module **600** may be disposed above the guide assembly **700**. The light source module **600** may be coupled to the guide assembly **700**. Specifically, the guide assembly **700** may include a supporter **730** configured to protrude upward from an upper surface of a guide case **740** and support a housing **601** of the light source module **600**, and the light source module **600** may be fixed to the supporter **730** by a fastening member such as a pin, a screw, or a bolt. The light source module **600** may be disposed inside the head housing **130**. The light source module **600** may be disposed so that the plurality of light sources **610** and **620** are adjacent to the water discharge tube **140**. The light source module **600** may form a seating groove **630** on which the second elbow pipe **175** is seated.

(61) The plurality of light sources of the light source module **600** may include a first light source **610** and a pair of second light sources **620**. The first light source **610** and the second light sources **620** may be spaced apart from each other. The first light source **610** and the second light sources **620** may be disposed to face the guide assembly **700**.

(62) The first light source **610** and the second light sources **620** may emit light downward. The second light sources **620** may emit light in a plurality of colors. For example, the second light sources **620** may selectively emit light in any one of a first color, a second color, and a third color and may emit light in any one color and change the color of the light. However, the present disclosure is not limited thereto, and the second light sources **620** may emit light in two different colors or emit light in four or more different colors.

(63) The first light source **610** may include a first light emitting diode (LED) **611**. Each of the second light sources **620** may include a second LED **621** configured to emit light in a plurality of colors. The second LED **621** may correspond to a RGB LED.

(64) The light source module **600** may include the housing **601** configured to accommodate therein a printed circuit board **623** on which the first and second LEDs **611** and **621** are mounted. The housing **601** may include an upper housing **602** configured to form an upper surface of the light source module **600** and a lower housing **603** configured to form a lower surface of the light source module **600**. The upper housing **602** may be coupled to an upper end of the lower housing **603**. However, the present disclosure is not limited thereto, and the upper housing **602** and the lower housing **603** may be integrally formed.

(65) The lower housing **603** may include a through-hole **612** provided to correspond to the first LED **611** and allow the first LED **611** to pass therethrough, and covers **622** each configured to correspond to one of the second LEDs **621** and cover one of the second LEDs **621**. The lower housing **603** may be formed of a substantially transparent material or formed of a semitransparent material. As the first LED **611** is inserted into the through-hole **612**, the first light source **610** may be formed accordingly, and as the second LEDs **621** are covered by the covers **622**, the second light sources **620** may be formed accordingly.

(66) The guide assembly **700** may be disposed under the light source module **600** and form an exterior of the water discharge unit **100**.

(67) The guide assembly **700** may include the guide case **740** configured to form a hollow portion **760** through which the water discharge tube **140** passes and guide light of the first light source **610** and light of the second light source **620** in one direction to prevent the rays of light from being mixed with each other. Specifically, the guide case **740** may guide the light of the first light source **610** and the light of the second light source **620** downward in a direction parallel to the direction in which the water discharge tube **140** extends while preventing the rays of light from being mixed with each other.

(68) The guide case **740** may surround and cover the outer peripheral surface of the water discharge tube **140**. The guide case **740** may be formed of a material such as a metal (e.g., aluminum), a synthetic resin, or the like.

(69) The guide case **740** may include a first guide hole **741** configured to guide the light of the first light source **610** downward and a second guide hole **742** configured to guide the light of the second light source **620** downward. The first guide hole **741** and the second guide hole **742** may pass through upper and lower surfaces of the guide case **740**. The light of the first light source **610** may be introduced through an upper end of the first guide hole **741**. The light of the second light source **620** may be introduced through an upper end of the second guide hole **742**. The light of the first light source **610** may be emitted through a lower end of the first guide hole **741**. The light of the second light source **620** may be emitted through a lower end of the second guide hole **742**. The first guide hole **741** and the second guide hole **742** may be spaced apart and separated from each other. The first guide hole **741** may be disposed at a position corresponding to the first light source **610**. The second guide hole **742** may be disposed at a position corresponding to the second light source **620**. The second guide hole **742** may include a pair of second guide holes **742** each disposed at a position corresponding to one of the pair of second light sources **620**.

(70) The guide case **740** may include a leakage reducing curved surface **741a** formed on the upper end of the first guide hole **741** to allow the first light source **610** to be seated thereon and configured to reduce leakage of the light of the first light source **610**. The leakage reducing curved surface **741a** may be formed in a shape corresponding to one surface of the first LED **611** that has a curved shape. The leakage reducing curved surface **741a** may come in contact with the surface of the first LED **611** having the curved shape, and the leakage reducing curved surface **741a** in contact with the surface of the first LED **611** may reflect light emitted to a space other than the first guide hole **741** back to the first LED **611** to cause most of the light emitted from the first LED **611** to be incident on the first guide hole **741**. However, the present disclosure is not limited thereto, and the leakage reducing curved surface **741a** may be omitted, and one area of an upper surface of the guide case **740** that is connected to the first guide hole **741** may be flat like other portions of the

upper surface of the guide case **740**.

(71) The guide assembly **700** may include a light guide cover **750** on which light guided by the guide case **740** is incident. The light guide cover **750** may cover the first guide hole **741** and the second guide hole **742**. The light guide cover **750** may be formed of a substantially transparent material. The light guide cover **750** may be formed of plastic, acrylic, glass, or the like in order to be substantially transparent.

(72) The light guide cover **750** may be coupled to the guide case **740**. Specifically, the light guide cover **750** may include a coupling hook **754** configured to extend upward from a bottom wall portion **753**, and as the coupling hook **754** is fastened to the guide case **740**, the light guide cover **750** may be coupled to the guide case **740**.

(73) The light guide cover **750** may include the bottom wall portion **753** configured to form a lower surface of the guide assembly **700** that corresponds to the lower surface of the display device **500**, a sidewall portion **752** configured to protrude upward from an outer periphery of the bottom wall portion **753**, and a light-emitting rib **751** configured to extend in a radial direction of the sidewall portion **752** and/or a radial direction of the water discharge tube **140** from an outer peripheral surface of the sidewall portion **752**. The light guide cover **750** may project the light of the second light source **620** guided by the guide case **740** in the radial direction of the sidewall portion **752** and/or the radial direction of the water discharge tube **140** through the light-emitting rib **751**.

(74) The bottom wall portion **753** may be formed in a substantially annular shape with an open central portion to form an opening **753a** at a position corresponding to the hollow portion **760**. The sidewall portion **752** extending upward from the outer periphery of the bottom wall portion **753** may be formed in a cylindrical shape. The light-emitting rib **751** extending in the radial direction from the outer peripheral surface of the sidewall portion **752** may be formed in a substantially annular shape. Accordingly, the water discharge tube **140** may pass through the light guide cover **750**, and the light guide cover **750** may surround and cover the outer peripheral surface of the water discharge tube **140**. A lower end of the guide case **740** may be inserted into and coupled to the opening **753a** of the central portion of the bottom wall portion **753**.

(75) The bottom wall portion **753** may cover or block the lower end of the first guide hole **741**. The light of the first light source **610** guided by the first guide hole **741** may be incident on the bottom wall portion **753**, and the light guide cover **750** may project the light of the first light source **610** that has passed through the bottom wall portion **753** to a portion under the water discharge tube **140**. Here, one area of the bottom wall portion **753** from which the light of the first light source **610** is projected may correspond to the first indicator **510**.

(76) Meanwhile, the light guide cover **750** may include a lens **755** formed on the bottom wall portion **753** to be disposed at a position corresponding to the first guide hole **741** and configured to condense the light of the first light source **610** that is guided by the first guide hole **741**. The lens **755** may include a convex lens. The light guide cover **750** may project the light of the first light source **610**, which is condensed while passing through the lens **755**, to the portion under the water discharge tube **140**. However, the present disclosure is not limited thereto, and the lens **755** may be omitted.

(77) The light guide cover **750** may project the light of the second light source **620** to the outer peripheral surface of the display device **500**. Hereinafter, the process in which the light of the second light source **620** is guided to the outer peripheral surface of the display device **500** will be described.

(78) The guide assembly **700** may include a diffusion space **780** formed between the light guide cover **750** and the guide case **740**. The diffusion space **780** may correspond to a separation space between the light guide cover **750** and the guide case **740**. The diffusion space **780** may form a closed loop that surrounds the water discharge tube **140**. A bottom surface of the diffusion space **780** may be formed by the bottom wall portion **753**, and at least a portion of an outer peripheral surface of the diffusion space **780** may be formed by the sidewall portion **752**. An inner peripheral

surface of the diffusion space **780** may be formed by the guide case **740**.

(79) In order to prevent the light of the first light source **610** guided by the first guide hole **741** from leaking to the diffusion space **780**, the diffusion space **780** may be partitioned from the first guide hole **741**. The diffusion space **780** may communicate with the second guide hole **742**. The lower end of the second guide hole **742** may be connected to the diffusion space **780**. In other words, since the first guide hole **741** may be partitioned from the diffusion space **780** and extend downward from the upper surface of the guide case **740** until the lower end of the first guide hole **741** touches the bottom wall portion **753**, and the second guide hole **742** may extend downward from the upper surface of the guide case **740** until the lower end of the second guide hole **742** is connected to the diffusion space **780** disposed above the bottom wall portion **753**, a length at which the first guide hole **741** extends in the up-down direction may be longer than a length at which the second guide hole **742** extends in the up-down direction. The length at which the first guide hole **741** extends in the up-down direction may be substantially longer than or equal to a sum of the length at which the second guide hole **742** extends in the up-down direction and a height of the diffusion space **780** in the up-down direction.

(80) The light of the second light source **620** guided by the second guide hole **742** may be incident on the diffusion space **780**. The light of the second light source **620** guided by the second guide hole **742** may be diffused and/or irregularly reflected from the diffusion space **780** and incident on an inner peripheral surface of the sidewall portion **752**.

(81) The light-emitting rib **751** connected to the sidewall portion **752** may be exposed to the outer peripheral surface of the display device **500**. That is, the light-emitting rib **751** may be exposed to the outer peripheral surface of the guide assembly **700**. Specifically, the guide assembly **700** may include first and second deco plates **710** and **720** configured to form an exterior of the display device **500**, and the light-emitting rib **751** may be disposed between the first deco plate **710** and the second deco plate **720** in the up-down direction in order to be exposed to the outer peripheral surface of the display device **500** while forming the exterior of the display device **500**.

(82) The light of the second light source **620** incident on the inner peripheral surface of the sidewall portion **752** may be guided to the light-emitting rib **751** and projected from the light-emitting rib **751** to the outside of the display device **500**. Here, one area of the light-emitting rib **751** that is exposed to the outside of the display device **500** may correspond to the second indicator **520**.

(83) The first and second deco plates **710** and **720** may extend in a direction toward an outer periphery of the guide assembly **700**. The first and second deco plates **710** and **720** may each be formed in an annular shape to form the outer peripheral surface of the display device **500**. The guide case **740** may be inserted into the first deco plate **710**, and the first deco plate **710** may be coupled to an outer peripheral surface of the guide case **740**. The light guide cover **750** may be inserted into the second deco plate **720**, and the second deco plate **720** may be coupled to the outer peripheral surface of the sidewall portion **752** of the light guide cover **750**.

(84) The guide assembly **700** may include a light shielding member **770** disposed on an upper surface of the bottom wall portion **753** and provided to prevent the light of the second light source **620** from being projected through the bottom wall portion **753**. The light shielding member **770** may be provided in a shape that corresponds to the bottom wall portion **753**. The light shielding member **770** may be formed in a substantially annular shape. The light shielding member **770** may include a cut-out portion **771** formed at a position corresponding to the lower end of the first guide hole **741** in order to prevent the lower end of the first guide hole **741** from being covered by the light shielding member **770**.

(85) The light shielding member **770** may reflect light heading toward the bottom wall portion **753**, among the rays of light of the second light source **620** entering the diffusion space **780**, back to the diffusion space **780** or absorb the light to prevent the light of the second light source **620** from passing through the bottom wall portion **753**. However, the present disclosure is not limited thereto, and the light shielding member **770** may be omitted.

(86) In this way, the display device **500** may implement the plurality of indicators **510** and **520**, which may be independently operated, into a single device to reduce the size of the product and reduce manufacturing costs and may prevent the rays of light of the plurality of light sources **610** and **620**, which are used in the indicators **510** and **520**, from being mixed with each other or leaking to unnecessary areas so that pieces of information that the indicators **510** and **520** indicate can be more clearly delivered to the user.

(87) FIG. **12** is a control block diagram of the water purifier illustrated in FIG. **1**. FIG. **13** is a flowchart of a control method of the water purifier illustrated in FIG. **1**.

(88) The order of operation of the display device will be described with reference to FIGS. **12** and **13**.

(89) The water discharge unit **100** may include a detecting sensor **800** configured to detect a user approaching the water discharge unit **100**. The detecting sensor **800** may transmit a detection signal to a controller **900** in a case in which the user approaches the water discharge unit **100** within a predetermined distance.

(90) The water discharge unit **100** may include the controller **900**. The controller **900** may be disposed inside the water discharge unit **100** or disposed in the water purifier main body **10**. The controller **900** may be electrically connected to the first light source **610** and the second light sources **620**. The controller **900** may control the first light source **610** and the second light sources **620**. Specifically, the controller **900** may turn the first LED **611** and the second LEDs **621** on and off and may set a color of the light emitted by the second LEDs **621**. Also, the controller **900** may control the on and off of the display **160**.

(91) In a case in which a user approaches the water discharge unit **100** in order to use the water purifier **1**, the detecting sensor **800** may detect the approach and transmit a detection signal to the controller **900** (**1000**).

(92) The controller **900** which has received the detection signal may operate the display **160** and the first indicator **510**. Specifically, the controller **900** which has received the detection signal may operate the display **160** and the first LED **611** (**2000**).

(93) In response to the first indicator **510** being operated, the user may place a container at a position indicated by the first indicator **510** and operate the display **160** to select the type of water (**3000**). Specifically, one of cold water, hot water, and purified water may be selected. Also, the user may operate the display **160** to select the amount of discharged water.

(94) When the user operates the water discharge mechanism **101** after selecting one of the cold water, hot water, and purified water and the amount of discharged water, the water discharge unit **100** may discharge water reflecting the selections made by the user. While water is being discharged through the water discharge hole **141**, the controller **900** may operate the second indicator **520** so that the second indicator **520** emits light of a color corresponding to the selections made by the user (**4000**). Specifically, the controller **900** may operate the second LEDs **621** to emit light of a color corresponding to the selections made by the user. For example, the controller **900** may cause the second LEDs **621** to emit light of a first color while cold water is being discharged, cause the second LEDs **621** to emit light of a second color while hot water is being discharged, and cause the second LEDs **621** to emit light of a third color while purified water is being discharged.

(95) In a case in which the water discharge unit **100** has completed supplying water by as much as the amount of discharged water selected by the user or the user has operated the water discharge mechanism **101** to turn off the water, the controller **900** may turn off the first indicator **510** and the second indicator **520**. Specifically, the controller **900** may turn off the first LED **611** and the second LEDs **621**.

(96) Embodiments of the present disclosure may provide a water discharge unit for a water purifier, the water discharge unit including a body; a water discharge tube disposed at one side of the body and through which water is discharged; first and second light sources disposed inside the body and adjacent to the water discharge tube; a guide case configured to guide light emitted from the first

and second light sources in a direction in which the water discharge tube extends; and a light guide cover coupled to the guide case and configured to guide the light of the first and second light sources guided by the guide case, wherein the light guide cover is provided to project the light of the first light source in the direction in which the water discharge tube extends and project the light of the second light source in a radial direction of the water discharge tube.

(97) The light of the first light source may indicate a position of water discharge, and the light of the second light source may indicate which of purified water, cold water, and hot water is selected.

(98) The guide case may include a first guide hole provided to allow the light of the first light source to pass therethrough and a second guide hole spaced apart from the first guide hole and provided to allow the light of the second light source to pass therethrough, and the light guide cover may include a bottom wall portion configured to transmit the light of the first light source that has passed through the first guide hole, a sidewall portion configured to protrude from an outer peripheral side of the bottom wall portion and allow the light of the second light source that has passed through the second guide hole to be incident thereon, and a light-emitting rib connected to the sidewall portion and configured to extend in the radial direction of the water discharge tube.

(99) The light guide cover may include a lens provided on the bottom wall portion to be disposed at a position corresponding to the first guide hole and configured to condense the light of the first light source that is guided by the first guide hole.

(100) The guide case may include a leakage reducing curved surface formed on one end of the first guide hole to allow the first light source to be seated thereon and configured to reduce leakage of the light of the first light source.

(101) Specific embodiments illustrated in the drawings have been described above. However, the present disclosure is not limited to the embodiments described above, and those of ordinary skill in the art to which the disclosure pertains may make various changes thereto without departing from the gist of the technical spirit of the disclosure defined in the claims below.

Claims

1. A water purifier comprising: a main body arrangeable in a lower space of a cabinet; and a water discharge unit connected to the main body so that, when the main body is arranged in the lower space of the cabinet, at least a portion of the water discharge unit is exposed to an upper side of the cabinet, and purified water, cold water, and hot water are selectably dischargeable through the water discharge unit, wherein the water discharge unit includes: a body configured to be rotatable, a water discharge tube having a position that is changeable according to rotation of the body, and a display device including: a first light source, a second light source, a light guide cover, and a guide case configured to guide light emitted from the first light source and light emitted from the second light source so as to be incident on the light guide cover, and to prevent the light emitted from the first light source from being mixed with the light emitted from the second light source, wherein the light guide cover is configured to: project the light emitted from the first light source and incident on the light guide cover in a direction of water discharge from the water discharge tube to indicate the direction of water discharge, and project the light emitted from the second light source and incident on the light guide cover toward an outer peripheral surface of the display device to indicate which of purified water, cold water, and hot water is selected.

2. The water purifier of claim 1, wherein the guide case and the light guide cover surround the water discharge tube.

3. The water purifier of claim 2, wherein the guide case includes: a first guide hole configured to guide the light emitted from the first light source so as to be incident on the light guide cover, and a second guide hole spaced apart from the first guide hole and configured to guide the light emitted from the second light source so as to be incident on the light guide cover.

4. The water purifier of claim 3, wherein the light guide cover includes a bottom wall portion

- configured to form a lower surface of the display device and cover a lower end of the first guide hole, and the light emitted from the first light source guided by the first guide hole and incident on the light guide cover passes through the bottom wall portion and is projected in the direction of water discharge.
5. The water purifier of claim 4, wherein the light guide cover includes a lens provided on the bottom wall portion at a position corresponding to the first guide hole and configured to condense the light emitted from the first light source and incident on the light guide cover that is guided by the first guide hole.
6. The water purifier of claim 4, wherein the display device further includes a light shielding member disposed on the bottom wall portion to prevent the light emitted from the second light source and incident on the light guide cover from passing through the bottom wall portion.
7. The water purifier of claim 3, wherein the display device includes: a diffusion space formed between the guide case and the light guide cover, and partitioned from the first guide hole, the diffusion space being configured to communicate with the second guide hole, and the light guide cover includes: a sidewall portion having an inner peripheral surface configured to form the diffusion space, and a light-emitting rib configured to protrude from an outer peripheral surface of the sidewall portion so as to be exposed to the outer peripheral surface of the display device.
8. The water purifier of claim 7, wherein the light guide cover projects the light emitted from the second light source, which is guided to the diffusion space and is incident on an inner peripheral surface of the light guide cover, through the light-emitting rib.
9. The water purifier of claim 3, wherein the guide case includes a leakage reducing curved surface formed on an upper end of the first guide hole to allow the first light source to be seated in the leakage reducing curved surface, and configured to reduce leakage of the light emitted from the first light source.
10. The water purifier of claim 2, wherein the water discharge unit further includes: a detecting sensor configured to detect an approach of a user, and a controller configured to control the detecting sensor, the first light source, and the second light source, and in response to the detecting sensor detecting the approach of the user, the controller turns on the first light source.
11. The water purifier of claim 10, wherein the second light source emits rays of light of a plurality of different colors, and in response to any one of the purified water, cold water, and hot water being selected, the controller controls the second light source to emit light of a color, among the plurality of different colors, corresponding to the selection of any one of the purified water, cold water, and hot water.
12. The water purifier of claim 11, wherein the water discharge unit includes a display configured to output an image, and in response to the detecting sensor detecting the approach of the user, the controller turns on the display as well as the first light source.
13. The water purifier of claim 1, wherein the light guide cover includes a coupling hook extending upward so as to be fastenable to the guide case to couple the light guide cover to the guide case.
14. The water purifier of claim 1, wherein the guide case forms a hollow portion through which the water discharge tube passes.
15. The water purifier of claim 1, wherein the cabinet includes a sink, and when the main body is arranged in the lower space of the cabinet, the body of the water discharge unit is couplable to the sink so as to be rotatable.
-