

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405634
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	An; Seongyong et al.

Antenna and electronic device including same

Abstract

An electronic device is provided. The electronic device includes at least one hinge device, a plurality of housings that are foldably connected to each other via the at least one hinge device and configured to at least partially define a rolling space in a rolled state, a flexible display supported by the plurality of housings and disposed to be visible from the outside in the rolled state, a cavity defined to have a predetermined spatial volume through a conductive material in a first housing among the plurality of housings, wherein the cavity includes a slit that is at least partially connected to the outside, and a wireless communication circuit disposed in an inner space of at least one housing among the plurality of housings and electrically connected to a first point within the cavity, wherein the wireless communication circuit may be configured to form a radiation pattern through the cavity structure.

Inventors: An; Seongyong (Suwon-si, KR), Kim; Hyunsuk (Suwon-si, KR), Seol; Kyungmoon (Suwon-si, KR), Jung; Hojin (Suwon-si, KR), Chun; Jaebong (Suwon-si, KR), Hwang; Hochul (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 83509239

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/717711

Filed: April 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220326738 A1	Oct. 13, 2022

Foreign Application Priority Data

KR	10-2021-0046533	Apr. 09, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/005121 20220408 PENDING child-doc US 17717711

Publication Classification

Int. Cl.: **G06F1/16** (20060101); **H01Q1/22** (20060101); **H01Q1/38** (20060101); **H01Q1/42** (20060101)

U.S. Cl.:

CPC **G06F1/1658** (20130101); **G06F1/1641** (20130101); **G06F1/1652** (20130101); **G06F1/1681** (20130101); **H01Q1/2266** (20130101); **H01Q1/38** (20130101); **H01Q1/42** (20130101);

Field of Classification Search

CPC: G06F (1/1658); G06F (1/1641); G06F (1/1652); G06F (1/1681); G06F (1/1615); G06F (1/1679); G06F (1/1686); G06F (1/1698); H01Q (1/2266); H01Q (1/38); H01Q (1/42); H01Q (1/08); H01Q (1/24); H01Q (1/243)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9071673	12/2014	Choi et al.	N/A	N/A
9196952	12/2014	Tran et al.	N/A	N/A
10243624	12/2018	Kim et al.	N/A	N/A
10498041	12/2018	Lin et al.	N/A	N/A
10629982	12/2019	Kim et al.	N/A	N/A
2003/0030595	12/2002	Radley-Smith	345/1.3	G06F 1/163
2013/0058063	12/2012	O'Brien	N/A	N/A
2016/0044801	12/2015	Lee	361/679.55	H05K 7/1427
2017/0139442	12/2016	Yoshizumi	N/A	N/A
2017/0141820	12/2016	Kim	N/A	H04M 1/0266
2019/0013584	12/2018	Ryu	N/A	H01Q 21/0006
2019/0237847	12/2018	Wu	N/A	H01Q 9/42
2019/0311692	12/2018	Shai	N/A	N/A
2020/0076062	12/2019	Lee	N/A	H04M 1/0268
2020/0245481	12/2019	Yoon	N/A	G06F 1/1652
2021/0075459	12/2020	Noh et al.	N/A	N/A
2021/0219437	12/2020	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017-097345	12/2016	JP	N/A
2018-186488	12/2017	JP	N/A
6505582	12/2018	JP	N/A
20170056246	12/2016	KR	H01Q 1/2266
10-2019-0077107	12/2018	KR	N/A
10-2019-0143029	12/2018	KR	N/A
10-2020-0024500	12/2019	KR	N/A
10-2021-0031309	12/2020	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Jul. 21, 2022, issued in International Application No. PCT/KR2022/005121. cited by applicant
Extended European Search Report dated May 21, 2024, issued in European Application No. 22785017.9-1201. cited by applicant
Korean Office Action dated Jun. 18, 2025, issued in Korean Application No. 10-2021-0046533. cited by applicant

Primary Examiner: Parker; Allen L
Assistant Examiner: Kim; Keon
Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2022/005121, filed on Apr. 8, 2022, which is based on and claims the benefit of a Korean patent application number 10-2021-0046533, filed on Apr. 9, 2021, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The disclosure relates to an electronic device including an antenna. More particularly, the disclosure relates to an electronic device including a plurality of housings foldably coupled to each other via hinge devices and a foldable flexible display disposed to be supported by the plurality of housings.

BACKGROUND ART

(2) Electronic devices are being gradually slimmed, and are being developed to increase rigidity, to enhance a design aspect, and to differentiate functional elements thereof. Electronic devices are gradually changing from a uniform rectangular shape to various shapes. An electronic device may have a deformable structure that makes it easy to carry the electronic device and enables a large screen display to be used. For example, as a type of a deformable structure, an electronic device may have an operating structure (e.g., a rollable structure or a rolling structure) capable of implementing various display forms of a flexible display through support of a plurality of housings that are foldably coupled to each other. Such an electronic device may include an antenna.

(3) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

DISCLOSURE OF INVENTION

Technical Problem

(4) An electronic device may include a plurality of housings foldably coupled to each other via hinge devices and a foldable flexible display disposed to be supported by the plurality of housings. When the electronic device is in a flat state, the plurality of housings are capable of supporting the flexible display to cause the flexible display to be deformed into a usable flat state. When the electronic device is in a rolled state, the plurality of housings are capable of being folded relative to each other to have a rolling space in the inside thereof and to cause the flexible display to be rolled. In this case, the housings define the rolling space so as to face each other, and the flexible display may be deformed to be visible from the outside while being supported by the housings.

(5) Meanwhile, the plurality of housings may be at least partially made of a conductive material to reinforce rigidity of the electronic device. The electronic device may include at least one antenna disposed in at least one housing among the plurality of housings. In the flat state, the at least one antenna may form a radiation pattern in a rearward direction in which the housings are oriented.

(6) However, in the rolled state of the electronic device in which the plurality of housings are deformed to face each other, the radiation pattern formed from at least one antenna may be degraded in radiation performance compared to that in the flat state due to peripheral housings made of a conductive material.

(7) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an antenna capable of exhibiting a predetermined radiation performance regardless of a deformation operation of the electronic device and an electronic device including the same.

(8) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

Solution to Problem

(9) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes at least one hinge device, a plurality of housings that are foldably connected to each other via the at least one hinge device and configured to at least partially define a rolling space in a rolled state, a flexible display supported by the plurality of housings and disposed to be visible from the outside in the rolled state, a cavity defined to have a predetermined spatial volume through a conductive material in a first housing among the plurality of housings, wherein the cavity includes a slit that is at least partially connected to the outside, and a wireless communication circuit disposed in an inner space of at least one housing among the plurality of housings and electrically connected to a first point within the cavity, wherein the wireless communication circuit may be configured to form a radiation pattern through the cavity structure.

Advantageous Effects of Invention

(10) The electronic device according to various embodiments of the disclosure includes an antenna having a radiation pattern formed through a feeding structure inside the cavity so that the predetermined radiation performance of an antenna can be ensured in the flat state and the rolled state.

(11) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;

(3) FIGS. 2A and 2B are front and rear perspective views illustrating an electronic device in a flat state according to various embodiments of the disclosure;

(4) FIG. 3A is a perspective view illustrating an electronic device in a rolled state according to an embodiment of the disclosure;

(5) FIG. 3B is a perspective view illustrating an electronic device in a rolled state according to an embodiment of the disclosure;

(6) FIG. 4 is an exploded perspective view of an electronic device according to an embodiment of the disclosure;

(7) FIG. 5 is a cut-away perspective view of an electronic device taken along line 5-5 in FIG. 2B according to an embodiment of the disclosure;

(8) FIG. 6 is a partially cut-away perspective view illustrating a region 6 in FIG. 2B according to an embodiment of the disclosure;

(9) FIGS. 7A and 7B are rear perspective views of an electronic device illustrating a current distribution via a first antenna and a second antenna according to various embodiments of the disclosure;

(10) FIGS. 8A and 8B are diagrams illustrating directions of radiation patterns when an electronic device is in a flat state and a rolled state, respectively, according to various embodiments of the disclosure;

(11) FIG. 9A is a graph comparing a radiation performances of a first antenna in a flat state and a rolled state of an electronic device according to an embodiment of the disclosure;

(12) FIG. 9B is a graph comparing a radiation performances of a second antenna in a flat state and a rolled state of an electronic device according to an embodiment of the disclosure;

(13) FIG. 10A is a perspective view of an electronic device illustrating an arrangement structure of slits with respect to cavities according to an embodiment of the disclosure;

(14) FIG. 10B is a graph comparing operating frequency bands of a first antenna according to a change in a length of a slit according to an embodiment of the disclosure; and

(15) FIGS. 11 and 12 are rear perspective views of an electronic device including at least one antenna according to various embodiments of the disclosure.

(16) Throughout the drawings, like reference numerals will be understood to refer to like parts, components, and structures.

BEST MODE FOR CARRYING OUT THE INVENTION

(17) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(18) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims

and their equivalents.

(19) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(20) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure.

(21) Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). The electronic device **101** may communicate with the electronic device **104** via the server **108**. The electronic device **101** includes a processor **120**, a memory **130**, an input device **150**, an audio output device **155**, a display device **160**, an audio module **170**, a sensor module **176**, an interface **177**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In various embodiments of the disclosure, at least one (e.g., the display device **160** or the camera module **180**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In various embodiments of the disclosure, some of the components may be implemented as single integrated circuitry. For example, the sensor module **176** (e.g., a fingerprint sensor, an iris sensor, or an illuminance sensor) may be implemented as embedded in the display device **160** (e.g., a display).

(22) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. As at least part of the data processing or computation, the processor **120** may load a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**, which includes an internal memory **136** and an external memory **138**. The processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), and an auxiliary processor **123** (e.g., a graphics processing unit (GPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. Additionally or alternatively, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(23) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). The auxiliary processor **123** (e.g., an ISP or a CP) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**.

(24) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(25) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(26) The input device **150** may receive a command or data to be used by other component (e.g., the

processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input device **150** may include, for example, a microphone, a mouse, a keyboard, or a digital pen (e.g., a stylus pen).

(27) The audio output device **155** may output sound signals to the outside of the electronic device **101**. The audio output device **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record, and the receiver may be used for an incoming calls. The receiver may be implemented as separate from, or as part of the speaker.

(28) The display device **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display device **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. The display device **160** may include touch circuitry adapted to detect a touch, or sensor circuitry (e.g., a pressure sensor) adapted to measure the intensity of force incurred by the touch.

(29) The audio module **170** may convert a sound into an electrical signal and vice versa. The audio module **170** may obtain the sound via the input device **150**, or output the sound via the audio output device **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(30) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. The sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(31) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. The interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(32) A connection terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). The connection terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(33) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. The haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(34) The camera module **180** may capture a image or moving images. The camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(35) The power management module **188** may manage power supplied to the electronic device **101**. The power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(36) The battery **189** may supply power to at least one component of the electronic device **101**. The battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(37) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The

communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the AP) and supports a direct (e.g., wired) communication or a wireless communication. The communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a cellular network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the SIM **196**.

(38) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment of the disclosure, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(39) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment of the disclosure, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment of the disclosure, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment of the disclosure, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(40) According to various embodiments of the disclosure, the antenna module **197** may form a mmWave antenna module. According to an embodiment of the disclosure, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a

designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(41) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(42) According to an embodiment of the disclosure, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment of the disclosure, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In an embodiment of the disclosure, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment of the disclosure, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(43) FIGS. 2A and 2B are front and rear perspective views illustrating an electronic device in a flat state according to various embodiments of the disclosure. FIG. 3A is a perspective view illustrating an electronic device in a rolled state according to an embodiment of the disclosure.

(44) An electronic device **200** of FIGS. 2A to 3A may be at least partially similar to the electronic device **101** of FIG. 1 or may further include other embodiments of the electronic device.

(45) Referring to FIGS. 2A, 2B, and 3A, the electronic device **200** may include a plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** foldably coupled to each other via at least one hinge device **h** and a flexible display **201** supported via the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**. According to an embodiment of the disclosure, the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** may include a first housing **210**, a second housing **220**, and a third housing **230**, a fourth housing **240**, a fifth housing **250**, and/or a sixth housing **260**, which are connected to each other via hinge devices **h**. The electronic device **200** according to various embodiments of the disclosure is not limited to the number of housings **210**, **220**, **230**, **240**, **250**, and **260**, and various numbers of housings may be coupled to each other as necessary. According to an embodiment of the disclosure, the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** may be at least partially made of a metal material. According to an embodiment of the disclosure, in the flat state, the electronic device **200** may be deformed to define a substantially flat plane and may support the flexible display **201** via the flat plane, thereby providing a larger display region. According to an embodiment of the disclosure, when the electronic device **200** is in the rolled state (e.g., a rolling

state), the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** may be folded at a predetermined angle, thereby being deformed to form a hollow rolling space **2001** as a whole. According to an embodiment of the disclosure, in the rolled state, the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** may be folded such that the first housing **210** and the sixth housing **260** come into contact with each other. In this case, the flexible display **201** may be deformed according to the folding operation of the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** and may be curved in the manner of being rolled along the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**. According to an embodiment of the disclosure, in the rolled state, the flexible display **201** may be disposed to be partially visible from the outside in various directions in the outside.

(46) According to various embodiments of the disclosure, the electronic device **200** may include at least one of at least one input device **203**, at least one sound output device **206** or **207**, at least one sensor module **204** or **217** or **218**, at least one camera module **205** or **216**, a connector port **208**, or a key input device (not illustrated). In another embodiment of the disclosure, the electronic device **200** may be configured such that at least one of the above-mentioned components is omitted or other components (e.g., an indicator) are additionally included. According to an embodiment of the disclosure, the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** are at least partially have of inner spaces (e.g., inner spaces **2101**, **2201**, **2301**, **2401**, **2501**, and **2601** in FIG. 5), respectively. According to an embodiment of the disclosure, the above-described components may be disposed in the inner spaces of at least some of the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**.

(47) According to various embodiments of the disclosure, the input device **203**, the at least one sound output device **206** or **207**, the at least one sensor module **204** or **217**, the connector port **208**, or the at least one camera module **205** or **216** may be disposed through a third space of a third housing **230** (e.g., the third space **2301** in FIG. 5) and/or a second space of a second housing **220** (e.g., the second space **2201** in FIG. 5). According to an embodiment of the disclosure, the above-described components may be disposed in other housings among the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**. In some embodiments of the disclosure, the electronic device **200** may be configured such that at least one of the above-mentioned components is omitted or other components are additionally included.

(48) According to various embodiments of the disclosure, the input device **203** may include a microphone. In some embodiments of the disclosure, the input device **203** may include a plurality of microphones arranged to detect the direction of sound. According to an embodiment of the disclosure, the at least one sound output device **206** or **207** may include a speaker. According to an embodiment of the disclosure, the at least one sound output device **206** or **207** may include a receiver **206** disposed in the third housing **230** and an external speaker **207** disposed in the second housing **220**. According to an embodiment of the disclosure, the connector port **208** may face the outside through a connector port hole provided in the third housing **230**. In some embodiments of the disclosure, the sound output device **206** may include a speaker that is operated without a separate speaker hole (e.g., a piezo speaker). According to an embodiment of the disclosure, the at least one sensor module **204** or **217** may include a first sensor module **204** disposed to detect an external environment through the third housing **230** and a second sensor module **217** disposed to detect the external environment via the second housing **220**. According to an embodiment of the disclosure, the at least one sensor module **204** or **217** may generate an electrical signal or a data value corresponding to the internal operating state of the electronic device **200** or the external environmental state. According to an embodiment of the disclosure, the first sensor module **204** may include a proximity sensor or an illuminance sensor. According to an embodiment of the disclosure, the second sensor module **217** may include a heart rate monitoring (HRM) sensor. According to an embodiment of the disclosure, the first sensor module **204** may be disposed under the flexible display **201** in the third space of the third housing **230** (e.g., the third space **2301** in FIG. 5) and may detect the external environment through the flexible display **201**. According to an embodiment of the disclosure, the second sensor module **217** may be disposed in the second space

of the second housing **220** (e.g., the second space **2201** in FIG. 5) and may detect the external environment through at least a portion of the second housing **220**. According to an embodiment of the disclosure, the at least one sensor module **204** or **217** may further include at least one of a proximity sensor, an illuminance sensor, a time of flight (TOF) sensor, an ultrasonic sensor, a fingerprint recognition sensor, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, or a humidity sensor.

(49) According to various embodiments of the disclosure, the electronic device **200** may include at least one antenna **A1** or **A2**. According to an embodiment of the disclosure, the at least one antenna **A1** or **A2** may include a first antenna **A1** disposed through a first cavity **CV1** (e.g., at least a portion of the fourth space **2401** in FIG. 5) sealed and defined to have a predetermined first spatial volume in the fourth housing **240** made of a conductive material, and/or a second antenna **A2** disposed through a second cavity **CV2** (e.g., at least a portion of the first space **2101** in FIG. 5) sealed and defined to have a predetermined second spatial volume smaller than the first spatial volume in the first housing **210** made of a conductive material. According to an embodiment of the disclosure, the first cavity **CV1** may be provided through a conductive material and a first slit **241** having a predetermined shape and coupled to the conductive material. For example, the first slit **241** may have a first length **L1** corresponding to the first cavity **CV1**. In some embodiments of the disclosure, the first length **L1** of the first slit **241** may be different from that of the first cavity **CV1**. In this case, the first length **L1** of the first slit **241** may be determined depending on the operating frequency band of the first antenna **A1**. According to an embodiment of the disclosure, the second cavity **CV2** may be provided through a conductive material and a second non-conductive portion coupled to the conductive material and having a predetermined shape. For example, a second slit **211** may have a second length **L2** corresponding to the second cavity **CV2**. In some embodiments of the disclosure, the second length **L2** of the second slit **211** may be different from that of the second cavity **CV2**. In this case, the second length **L2** of the second slit **211** may be determined depending on the operating frequency band of the second antenna **A2**. According to an embodiment of the disclosure, the first slit **241** and/or the second slit **211** may be filled with a non-conductive materials **241a** and **211a** coupled to the conductive material through injection molding.

(50) According to various embodiments of the disclosure, the electronic device **200** may include wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) disposed in at least one housing among the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**.

According to an embodiment of the disclosure, the wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) may be electrically connected to a predetermined position within the first cavity **CV1** in the fourth housing **240** via an electrical connection member (e.g., the electrical connection member **223** in FIG. 5). According to an embodiment of the disclosure, the wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) may be electrically connected to a predetermined position within the second cavity **CV2** in the first housing **210** via an electrical connection member (e.g., the electrical connection member **223** in FIG. 5). According to an embodiment of the disclosure, the first antenna **A1** may be configured to transmit and/or receive a radio signal in a first frequency band via the wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) electrically connected to the first cavity **CV1**. According to an embodiment of the disclosure, the second antenna **A2** may be configured to transmit and/or receive a radio signal in a second frequency band higher than the first frequency band via the wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) electrically connected to the second cavity **CV2**. According to an embodiment of the disclosure, the first frequency band and/or the second frequency band may include a frequency band in the range of 800 MHz to 6,000 MHz. According to an embodiment of the disclosure, the first frequency band may include a high frequency band (e.g., 2.3 GHz to 2.7 GHz). According to an embodiment of the disclosure, the second frequency band may include an

n77 (e.g., 3.3 GHz to 4.2 GHz) band. In some embodiments of the disclosure, the first antenna A1 and/or the second antenna A2 may be disposed in at least one housing among the other housings 220, 230, 250, and 260.

(51) The at least one antenna A1 or A2 according to various embodiments of the disclosure forms a field in the inside of a cavity via a feed structure within the cavity CV1 or CV2), and may thus be relatively less influenced by peripheral conductors. Accordingly, when the electronic device is in the rolled state, even if the peripheral housings 220, 230, 250, and 260 are close to the fourth housing 240 and/or the first housing 210, the radiation pattern of the first antenna A1 and/or the second antenna A2 is formed in a direction in which the hollow rolling space 2001 faces the outside (e.g., in direction {circle around (1)} direction) (e.g., the y-axis direction) so that degradation in radiation performance can be reduced.

(52) FIG. 3B is a perspective view illustrating an electronic device in the rolled state according to an embodiment of the disclosure.

(53) In describing the electronic device 200-1 of FIG. 3B, the same components as those of the electronic device 200 of FIG. 3A are denoted by the same reference numerals, and a detailed description thereof may be omitted.

(54) Referring to FIG. 3B, compared to the electronic device 200 of FIG. 3A, the electronic device 200-1 may further include a seventh housing 270, an eighth housing 280, and/or a ninth housing 290, which may be sequentially coupled to each other via hinge devices h to be foldable relative to each other. In this case, when the electronic device 200-1 is in the rolled state, at least some of the plurality of housings 210, 220, 230, 240, 250, 260, 270, 280, and 290 may be deformed to overlap each other. For example, in the rolled state, the electronic device 200-1 may be deformed such that the first housing 210 overlaps the seventh housing 270, the second housing 220 overlaps the eighth housing 280, and the third housing 230 overlaps the ninth housing 290. In this case, in the electronic device 200-1, a radiation pattern may be formed in a direction in which the hollow rolling space 2001 faces the outside (e.g., direction {circle around (1)}) (e.g., the y-axis direction) via a first antenna A1 and a second antenna A2 disposed in at least one housing 240 or 210 among the plurality of housings 210, 220, 230, 240, 250, 260, 270, 280, and 290.

(55) FIG. 4 is an exploded perspective view of an electronic device according to an embodiment of the disclosure. FIG. 5 is a cut-away perspective view of an electronic device taken along line 5-5 in FIG. 2B according to an embodiment of the disclosure.

(56) Referring to FIGS. 4 and 5, the electronic device 200 may include a plurality of housings 210, 220, 230, 240, 250, and 260 foldably coupled to each other via at least one hinge device h and a flexible display 201 supported via the plurality of housings 210, 220, 230, 240, 250, and 260. According to an embodiment of the disclosure, the plurality of housings 210, 220, 230, 240, 250, and 260 may include a first housing 210, a second housing 220, and a third housing 230, a fourth housing 240, a fifth housing 250, and a sixth housing 260, which are connected to each other via hinge devices h. According to an embodiment of the disclosure, each of the plurality of housings 210, 220, 230, 240, 250, and 260 may define a space sealed by being coupled with corresponding one of a plurality of conductive support members 210a, 220a, 230a, 240a, 250a, and 260a. According to an embodiment of the disclosure, each of the plurality of housings 210, 220, 230, 240, 250, and 260 may be coupled with a corresponding one of the plurality of support members 210a, 220a, 230a, 240a, 250a, and 260a via fastening members, such as screws S. For example, the first housing 210 may define a first space 2101 (e.g., the second cavity CV2) by being coupled with a first support member 210a. The second housing 220 may define a second space 2201 by being coupled with a second support member 220a. The third housing 230 may define a third space 2301 by being coupled with a third support member 230a. The fourth housing 240 may define a fourth space 2401 (e.g., the first cavity CV1) by being coupled with a fourth support member 240a. The fifth housing 250 may define a fifth space 2501 by being coupled with a fifth support member 250a. The sixth housing 260 may define a sixth space 2601 by being coupled with a sixth support

member **260a**. According to an embodiment of the disclosure, the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** may define a substantially flat plane for supporting the flexible display **201** via the support members **210a**, **220a**, **230a**, **240a**, **250a**, and **260a**.

(57) According to various embodiments of the disclosure, the electronic device may include at least one substrate **221** and at least one battery **222** disposed in the inner spaces of at least some of the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**, and a bendable electrical connection member **223** disposed to cross the inner spaces of the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**. According to an embodiment of the disclosure, the electrical connection member **223** may include a flexible printed circuit board (FPCB) or a coaxial cable. According to an embodiment of the disclosure, the at least one substrate **221** may include a first substrate **2211** disposed in the second space **2201** of the second housing **220** and/or a second substrate **2212** disposed in the third space **2301** of the third housing **230**. According to an embodiment of the disclosure, the at least one battery **222** may be disposed in each of the fifth space **2501** of the fifth housing **250** and/or the sixth space **2601** of the sixth housing **260**. In some embodiments of the disclosure, batteries may be disposed in one housing or in three or more different housings. According to an embodiment of the disclosure, the first substrate **2211** and the second substrate **2212** may be electrically connected to the electrical connection member **223**, which crosses the second space **2201** of the second housing **220** and the third space **2301** of the third housing **230**, via a substrate connector **C2**. According to an embodiment of the disclosure, the at least one battery **222** may be electrically connected to the electrical connection member **223**, which crosses the fifth space **2501** of the fifth housing **250** and the sixth space **2601** of the sixth housing **260**, via a battery connector **C3**. Accordingly, even when one or more batteries **222** are disposed in different housings, respectively, the batteries **222** may be electrically connected to the at least one substrate **221** via the electrical connection member **223**.

(58) According to various embodiments of the disclosure, the electronic device **200** may include a first antenna **A1** configured through the first cavity **V1** defined in at least a portion of the fourth space **2401** of the fourth housing **240** and a second antenna **A2** configured through the second cavity **CV2** defined by at least a portion of the first space **2101** of the first housing **210**. According to an embodiment of the disclosure, the fourth space **2401** and the first cavity **CV1** may be substantially the same. According to an embodiment of the disclosure, the first space **2101** and the second cavity **CV2** may be substantially the same. According to an embodiment of the disclosure, the fourth housing **240** may include a first slit **241** disposed to have substantially the same length as the first cavity **CV1** in the longitudinal direction (the y-axis direction) of the first cavity **CV1** at a position corresponding to the first cavity **CV1**. According to an embodiment of the disclosure, the first housing **210** may include a second slit **211** disposed to have substantially the same length as the second cavity **CV2** in the longitudinal direction (the y-axis direction) of the second cavity **CV2** at a position corresponding to the second cavity **CV2**. According to an embodiment of the disclosure, the first cavity **CV1** may be electrically connected to the electrical connection member **223**, which crosses the first cavity **CV1**, via an antenna connector **C1**. According to an embodiment of the disclosure, the second cavity **CV2** may be electrically connected to the electrical connection member **223**, which crosses the second cavity **CV2**, via the antenna connector **C1**. Accordingly, the first point in the first cavity **CV1** and the second point in the second cavity **CV2** may be electrically connected to at least one substrate **221** including the wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) via the electrical connection member **223**. In some embodiments of the disclosure, the at least one substrate **221** and/or the at least one battery **222** may be disposed in the same housing. According to an embodiment of the disclosure, the connectors **C1**, **C2**, and **C3** may include at least one of a C-clip, a conductive tape, a pogo pin, or a conductive sponge.

(59) FIG. 6 is a partially cut-away perspective view illustrating a region **6** in FIG. 2B according to an embodiment of the disclosure.

(60) Referring to FIG. 6, the fourth housing **240** may include a first surface **2401a** oriented in a

first direction (e.g., the z-axis direction), and a second surface **2401b** oriented in a direction opposite to the first surface **2401a** (e.g., the -z-axis direction), and a side surface **2401c** surrounding a fourth space **2401** (e.g., the first cavity CV1) between the first surface **2401a** and the second surface **2401b**. According to an embodiment of the disclosure, the first surface **2401a** may support a portion of the flexible display **201**. According to an embodiment of the disclosure, the second surface **2401b** may be disposed through the fourth support member **240a**. In some embodiments of the disclosure, the second surface **2401b** may be provided in a manner of extending from the side surface **2401c** without the fourth support member **240a**. In some embodiments of the disclosure, the second surface **2401b** may be provided through a separate rear cover coupled to the side surface **2401c**. According to an embodiment of the disclosure, the fourth housing **240** may include a conductive material **242**. According to an embodiment of the disclosure, the fourth housing **240** may include a first cavity CV1 provided to have a predetermined spatial volume through at least a portion of the fourth space **2401**. According to an embodiment of the disclosure, the first cavity CV1 may be substantially the same as the fourth space **2401**. According to an embodiment of the disclosure, the shape and the spatial volume of the first cavity CV1 may be determined through a wall **2421** extending from the conductive material **242**. According to an embodiment of the disclosure, the fourth housing **240** may include a first slit **241** provided to have a first length L1 substantially equal to that of the first cavity CV1 in the longitudinal direction (e.g., the y-axis direction) of the first cavity CV1. According to an embodiment of the disclosure, the first slit **241** may be filled with a non-conductive material **241a**. In some embodiments of the disclosure, the first slit **241** may be provided through the non-conductive material **241a** injection-molded into the conductive material **242**. According to an embodiment of the disclosure, the first slit **241** may be provided in the second surface **2401b**. In some embodiments of the disclosure, the first slit **241** may be disposed in a manner of extending to at least a portion of the side surface **2401c** from the second surface **2401b**.

(61) According to an embodiment of the disclosure, the first cavity CV1 has a feed structure electrically connected to a wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) in at least a portion of the internal space, and thus, an electric field may be formed near at least a portion of the first slit **241**. Thus, the first cavity CV1 may operate as an antenna (e.g., the first antenna A1 in FIG. 5). Although not illustrated, the second cavity (e.g., the second cavity CV2 in FIG. 5) disposed in the first housing (e.g., the first housing **210** in FIG. 5) may also be provided in substantially the same manner.

(62) According to an embodiment of the disclosure, the fourth housing **240**, the partition wall, or the fourth support member **240a** defining the first cavity CV1 may include a conductive member.

(63) FIGS. 7A and 7B are rear perspective views of an electronic device illustrating a current distribution via a first antenna and a second antenna according to various embodiments of the disclosure.

(64) Referring to FIGS. 7A and 7B, in an embodiment of the disclosure, the electronic device **200** may include a first antenna A1 disposed in the fourth housing **240** and operated by a first cavity structure including the first slit **241** and a second antenna A2 disposed in the first housing **210** and operated by a second cavity structure including the second slit **211**. As illustrated in FIG. 7A, it can be seen that the first antenna A1 is able to operate as an antenna since an electric field is formed near the first slit **241** included in the first cavity (e.g., the first cavity CV1 in FIG. 5). As another example, as illustrated in FIG. 7B, it can be seen that the second antenna A2 is able to operate as an antenna since an electric field is formed near the second slit **211** included in the second cavity (e.g., the second cavity CV2 in FIG. 5).

(65) FIGS. 8A and 8B are diagrams illustrating directions of radiation patterns when an electronic device is in a flat state and a rolled state, respectively, according to various embodiments of the disclosure.

(66) Referring to FIG. 8A, it can be seen that, when the electronic device **200** is in the flat state, the

radiation pattern is formed in a direction in which the rear surface of the electronic device **200** is oriented (e.g., the $-z$ -axis direction).

(67) Referring to FIG. **8B**, it can be seen that, when the electronic device **200** is in the rolled state, the radiation pattern is smoothly formed outward (e.g., in the y -axis direction) from the hollow rolling space **2001** defined through the folding operation of the plurality of housings (e.g., the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** in FIG. **5**).

(68) FIG. **9A** is a graph comparing a radiation performances of a first antenna in a flat state and a rolled state of an electronic device according to an embodiment of the disclosure.

(69) Referring to FIG. **9A**, a graph (including 901 and 902) obtained by measuring radiation efficiencies in the flat state and the rolled state of the electronic device **200** when the first length **L1** of the first slit **241** is about 70 mm in the first antenna **A1** of FIG. **2A** is illustrated. It can be seen that predetermined radiation performances are exhibited in the flat state and the rolled state by showing a slight gain deviation of about 2 dB in a high frequency band (e.g., about 2300 MHz to 2700 MHz).

(70) FIG. **9B** is a graph comparing a radiation performances of a second antenna in a flat state and a rolled state of an electronic device according to an embodiment of the disclosure.

(71) Referring to FIG. **9B**, is a graph (including 903 and 904) obtained by measuring radiation efficiencies in a flat state and rolled state of the electronic device when the second length **L2** of the second slit **211** is about 35 mm in the second antenna **A2** of FIG. **2A** is illustrated. It can be seen that predetermined radiation performances are exhibited in the flat state and the rolled state by showing a slight gain deviation of about 2 dB in the n77 band (e.g., about 3300 MHz to 4200 MHz).

(72) FIG. **10A** is a perspective view of an electronic device illustrating an arrangement structure of slits with respect to cavities according to an embodiment of the disclosure.

(73) In describing the electronic device **200** of FIG. **10A**, the same reference numerals are assigned to components substantially the same as those of the electronic device **200** of FIG. **2B**, and a detailed description thereof may be omitted.

(74) Referring to FIG. **10A**, the electronic device **200** may include a plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** foldably coupled to each other via hinge devices **h** and a flexible display (e.g., the flexible display **201** in FIG. **2A**) disposed to be supported by the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260**. According to an embodiment of the disclosure, the electronic device **200** may include a first cavity **CV1** provided through a structural shape of the fourth housing **240** made of a conductive material (e.g., the conductive material **242** in FIG. **6**), and having the first length **L1**. According to an embodiment of the disclosure, the fourth housing **240** may include a first slit **241** disposed at a position at which the first slit **241** partially corresponds to the first cavity **CV1** and having a third length **L3** shorter than the first length **L1**. According to an embodiment of the disclosure, the electronic device **200** may include a first antenna **A1** configured to operate in a predetermined frequency band through the first cavity **CV1** and the first slit **241**.

(75) FIG. **10B** is a graph comparing operating frequency bands of a first antenna according to a change in a length of a slit according to an embodiment of the disclosure.

(76) Referring to FIG. **10B**, in the electronic device **200** of FIG. **10A**, it can be seen that an operating frequency band (graph **1001**) formed through the first slit **241** having the third length **L2** (e.g., about 55 mm) shorter than the first length **L1** (e.g., about 70 mm) of the first cavity **CV1** is relatively higher than the operating frequency band (graph **1002**) of the first antenna formed through the first slit **241** having a length substantially the same as the first length **L1** of the first cavity **CV1**. For example, when the first slit **241** has a length closer to the first length **L1** of the first cavity **CV1**, it may mean that the operating frequency band of the first antenna **A1** is shifted to a lower frequency band. For example, this may be advantageous in determining the operating frequency band of the first antenna **A1** by changing the length **L3** of the first slit **241** after the first cavity **CV1** is provided.

(77) FIGS. 11 and 12 are rear perspective views of an electronic device including at least one antenna according to various embodiments of the disclosure.

(78) In describing the electronic device 200 of FIGS. 11 and 12, the same reference numerals are assigned to components substantially the same as those of the electronic device 200 of FIG. 2B, and a detailed description thereof may be omitted.

(79) Referring to FIG. 11, the electronic device 200 may include a plurality of housings 210, 220, 230, 240, 250, and 260 foldably coupled to each other via hinge devices h and a flexible display (e.g., the flexible display 201 in FIG. 2A) disposed to be supported by the plurality of housings 210, 220, 230, 240, 250, and 260. According to an embodiment of the disclosure, the electronic device 200 may include a first cavity CV1 provided through a structural change of the fourth housing 240 including a conductive material and a first antenna A1 configured to operate in a predetermined first frequency band through the first slit 243 disposed at a position at which the first slit 243 partially corresponds to the first cavity CV1. According to an embodiment of the disclosure, the electronic device 200 may include a second cavity CV2 provided through a structural change of the first housing 210 including a conductive material and a second antenna A2 configured to operate in a predetermined second frequency band through the second slit 213 disposed at a position at which the second slit 213 partially corresponds to the second cavity CV2. According to an embodiment of the disclosure, the first slit 243 and the second slit 213 may be filled through non-conductive materials 243a and 213a, respectively. According to an embodiment of the disclosure, the first slit 243 may be provided in a “ custom character” shape in the fourth housing 240. According to an embodiment of the disclosure, the second slit 213 may be provided in a “I” shape in the first housing 210. Although not illustrated, the shapes of the first slit 243 and the second slit 213 may be provided in various ways depending on the shapes of the first cavity CV1 and the second cavity CV2 and the operating frequency band.

(80) Referring to FIG. 12, the electronic device 200 may include a first cavity CV1 provided through a structural change in the upper region of the fourth housing 240 and a first antenna A1 configured to operate in a predetermined first frequency band through the first slit 241 disposed at a position at which the first slit 241 partially corresponds to the first cavity CV1. According to an embodiment of the disclosure, the electronic device 200 may include a second cavity CV2 provided through a structural change in the upper region of the first housing 210 and a second antenna A2 configured to operate in a predetermined second frequency band through the second slit 211 disposed at a position at which the second slit 211 partially corresponds to the second cavity CV2. According to an embodiment of the disclosure, the electronic device 200 may include a third cavity CV3 provided through a structural change in the lower region of the fourth housing 240 (e.g., the -y-axis direction region) and a third antenna A3 configured to operate in a predetermined third frequency band through the third slit 244 disposed at a position at which the third slit 244 partially corresponds to the third cavity CV3. According to an embodiment of the disclosure, the electronic device 200 may include a fourth cavity CV4 provided through a structural change in the lower region of the first housing 210 (e.g., the -y-axis direction region) and a fourth antenna A4 configured to operate in a predetermined fourth frequency band through the fourth slit 214 disposed at a position at which the fourth slit 214 partially corresponds to the fourth cavity CV4. According to an embodiment of the disclosure, the first slit 241, the second slit 211, the third slit 244 and/or the fourth slit 214 may be filled with non-conductive materials 241a, 211a, 244a, and 214a, respectively. According to an embodiment of the disclosure, the first to fourth frequency bands may be the same as or different from each other.

(81) The antennas A1, A2, A3, and A4 having a cavity structure according to various embodiments of the disclosure may have operating frequency bands, which are determined depending on the shapes of the cavities CV1, CV2, CV3, and CV4 and/or the shapes of the slits 241, 211, 244, and 214, respectively. According to an embodiment of the disclosure, even when peripheral conductive structures (e.g., other conductive housings) are disposed close thereto, the antennas A1, A2, A3,

and A4 having a cavity structure may be helpful in reducing degradation in radiation performance since a radiation pattern is formed through a resonance characteristic of the cavity structure when the electronic device **200** is in the rolled state.

(82) According to various embodiments of the disclosure, an electronic device (e.g., the electronic device **200** in FIG. 5) may include at least one hinge device (e.g., the hinge device **h** in FIG. 2B), a plurality of housings (e.g., the plurality of housings **210**, **220**, **230**, **240**, **250**, and **260** in FIG. 5) foldably connected to each other through the at least one hinge device and configured to at least partially define a rolling space (e.g., the hollow rolling space **2001** in FIG. 3A) in a rolled state, a flexible display (e.g., the flexible display **201** in FIG. 5) supported by the plurality of housings and disposed to be visible from the outside in the rolled state, a cavity (e.g., the first cavity **CV1** in FIG. 5) formed in a first housing (e.g., the fourth housing **240** in FIG. 5) among the plurality of housings through a conductive material (e.g., the conductive material **242** in FIG. 6) to have a predetermined spatial volume, wherein the cavity includes a slit (e.g., the first slit **241** in FIG. 5) at least partially connected to the outside, and a wireless communication circuit (e.g., the wireless communication module **192** in FIG. 1) disposed in an inner space of at least one housing (e.g., the second housing **220** or the third housing **230** in FIG. 5) among the plurality of housings and electrically connected to a first point in the cavity, wherein the wireless communication circuit may be configured to form a radiation pattern through the cavity structure.

(83) According to various embodiments of the disclosure, the at least one frequency band may be determined depending on the size of the spatial volume.

(84) According to various embodiments of the disclosure, the at least one frequency band may be determined depending on the shape of the slit.

(85) According to various embodiments of the disclosure, the first housing may include a first surface configured to support a portion of the flexible display, a second surface facing away from the first surface, and a side surface surrounding an inner space between the first surface and the second surface, and the cavity may be formed through the first surface, the second surface, and the side surface.

(86) According to various embodiments of the disclosure, the spatial volume of the cavity may be determined via the conductive material at least partially filled in the inner space.

(87) According to various embodiments of the disclosure, the second surface and the side surface may be integrated with each other.

(88) According to various embodiments of the disclosure, the cavity may be formed through a conductive support member coupled to the side surface and configured to support a portion of the flexible display.

(89) According to various embodiments of the disclosure, the slit may be disposed in at least a portion of the second surface or the side surface.

(90) According to various embodiments of the disclosure, the slit may extend from at least a portion of the second surface to at least a portion of the side surface.

(91) According to various embodiments of the disclosure, the slit may include a non-conductive material injection-molded into the conductive material.

(92) According to various embodiments of the disclosure, the wireless communication circuit may be disposed within the cavity.

(93) According to various embodiments of the disclosure, the electronic device may include a substrate disposed to include the wireless communication circuit in an inner space of a second housing different from the first housing among the plurality of housings, and the substrate and the first point in the cavity may be electrically connected to each other via an electrical connection member.

(94) According to various embodiments of the disclosure, the electrical connection member may include a flexible FPCB or coaxial cable.

(95) According to various embodiments of the disclosure, the electronic device may further include

at least one electronic component disposed in an inner space of at least one housing different from the first housing and/or the second housing among the plurality of housings, wherein the at least one electronic component may be electrically connected to the substrate via the electrical connection member.

(96) According to various embodiments of the disclosure, the at least one electronic component may include at least one of at least one camera module, at least one battery, a speaker module, a microphone module, and at least one sensor module.

(97) According to various embodiments of the disclosure, the wireless communication circuit may be configured to form a radiation pattern in a direction opposite to a direction in which the flexible display is oriented when the electronic device is in a flat state.

(98) According to various embodiments of the disclosure, the at least one frequency band may include a range of 800 MHz to 6,000 MHz.

(99) According to various embodiments of the disclosure, the rolling space may be defined to open in a direction perpendicular to the direction in which the flexible display is oriented.

(100) According to various embodiments of the disclosure, the rolling space may be sealed by the plurality of housings, except for a portion opened in the perpendicular direction.

(101) According to various embodiments of the disclosure, at least one housing adjacent to the first housing among the plurality of housings may be made of the conductive material.

(102) According to various embodiments of the disclosure, the cavity may be provided through a structural change of a third housing including the conductive material and an antenna configured to operate in a predetermined first frequency band through the slit disposed at a position at which the slit partially corresponds to the cavity.

(103) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: at least one hinge device; a plurality of housings that are foldably connected to each other via the at least one hinge device and configured to at least partially define a rolling space in a rolled state; a flexible display supported by the plurality of housings and disposed to be visible from outside in the rolled state; a cavity defined to have a predetermined spatial volume in a first housing among the plurality of housings, the cavity being sealed by the first housing and including a slit that is at least partially connected to the outside; and a wireless communication circuit disposed in an inner space of at least one housing among the plurality of housings and electrically connected to a first point within the cavity, wherein the wireless communication circuit is configured to form a radiation pattern through a cavity structure, wherein the first housing is made of a conductive material, the first housing including a first surface supporting a portion of the flexible display, a second surface facing away from the first surface, and a side surface surrounding a space between the first surface and the second surface, wherein the cavity is formed through the first surface, the second surface, and the side surface, wherein the slit is disposed on the second surface and the side surface at a position corresponding to at least a portion of the cavity, wherein the slit is formed in an L-shape in which a first portion of the slit extends in a first direction on the second surface and a second portion of the slit extends in a second direction perpendicular to the first direction on the side surface, wherein the first portion of slit extending in the first direction on the second surface extends into the side surface in the first direction to connect with the second portion of the slit extending in the second direction on the side surface, and wherein the slit changes direction from extending in the first direction to extending in the second direction on the side surface.

2. The electronic device of claim 1, wherein at least one frequency band is determined based on a size of the predetermined spatial volume.
 3. The electronic device of claim 1, wherein at least one frequency band is determined based on a shape of the slit.
 4. The electronic device of claim 1, wherein the predetermined spatial volume of the cavity is determined via the conductive material at least partially filled in the inner space.
 5. The electronic device of claim 4, wherein the second surface and the side surface are integrated with each other.
 6. The electronic device of claim 5, wherein the cavity is formed through a conductive support member coupled to the side surface and configured to support a portion of the flexible display.
 7. The electronic device of claim 1, wherein the slit is disposed in at least a portion of the second surface or the side surface.
 8. The electronic device of claim 1, wherein the slit extends from at least a portion of the second surface to at least a portion of the side surface.
 9. The electronic device of claim 1, wherein the slit includes a non-conductive material injection-molded into the conductive material.
 10. The electronic device of claim 1, wherein the wireless communication circuit is disposed within the cavity.
 11. The electronic device of claim 1, further comprising: a substrate disposed to include the wireless communication circuit in an inner space of a second housing different from the first housing among the plurality of housings, wherein the substrate and the first point within the cavity are electrically connected via an electrical connection member.
 12. The electronic device of claim 11, wherein the electrical connection member includes a flexible printed circuit board (FPCB) or coaxial cable.
 13. The electronic device of claim 11, further comprising: at least one electronic component disposed in an inner space of at least one housing different from at least one of the first housing or the second housing among the plurality of housings, wherein the at least one electronic component is electrically connected to the substrate via the electrical connection member.
 14. The electronic device of claim 13, wherein the at least one electronic component includes at least one of at least one camera, at least one battery, a speaker, a microphone, or at least one sensor.
 15. The electronic device of claim 11, further comprising: a second cavity defined to have a second predetermined spatial volume through a conductive material in one housing among the plurality of housings and different from the first housing, wherein the first point within the cavity and a second point within the second cavity are electrically connected to the substrate including the wireless communication circuit via the electrical connection member.
 16. The electronic device of claim 1, wherein the wireless communication circuit is configured to, while the electronic device is in a flat state, form the radiation pattern in a direction opposite to a direction in which the flexible display is oriented.
 17. The electronic device of claim 1, further comprising: at least one antenna, wherein the at least one antenna is configured to at least one of transmit or receive a radio signal in at least one frequency band via the wireless communication circuit, and wherein the at least one frequency band includes a range of 800 megahertz (MHz) to 6,000 MHz.
 18. The electronic device of claim 1, wherein the rolling space is defined to open in a direction perpendicular to a direction in which the flexible display is oriented.
 19. The electronic device of claim 18, wherein the rolling space is sealed by the plurality of housings, except for a portion opened in the direction perpendicular to the direction in which the flexible display is oriented.
 20. The electronic device of claim 1, wherein at least one housing adjacent to the first housing among the plurality of housings is made of the conductive material.
-

