

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405699
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Cho; Seungki et al.

Electronic device and controlling method of electronic device

Abstract

Provided is an electronic device including a first sensor configured to sense a user; a second sensor configured to sense light incident from an external light source; a mirror display; a memory; and a processor configured to: based on the first sensor sensing the user in front of the mirror display, obtain information about a first area in which a first image corresponding to a reflection of the user is located on the mirror display; determine a second area for displaying content to be provided to the user based on the information about the first area; based on information about light being obtained through the second sensor, determine luminance of the second area based on the information about the light; and control the mirror display to display the content with the determined luminance on the second area.

Inventors: Cho; Seungki (Suwon-si, KR), Kang; Han (Suwon-si, KR), Sim; Jaemun (Suwon-si, KR), Lee; Changwoo (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 83321171

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/511285

Filed: November 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240086028 A1	Mar. 14, 2024

Foreign Application Priority Data

KR	10-2021-0034481	Mar. 17, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 17877400 20220729 US 11842027 child-doc US 18511285
continuation parent-doc WO PCT/KR2022/003665 20220316 PENDING child-doc US 17877400

Publication Classification

Int. Cl.: **G06F3/0481** (20220101); **A47G1/02** (20060101); **G06T7/70** (20170101)

U.S. Cl.:

CPC **G06F3/0481** (20130101); **A47G1/02** (20130101); **G06T7/70** (20170101);
G06T2207/20081 (20130101); G06T2207/20084 (20130101)

Field of Classification Search

CPC: G06F (3/0481); G06T (7/70); G06T (2207/20081); G06T (2207/20084); A47G (1/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8436803	12/2012	Inoue	N/A	N/A
10147393	12/2017	Yoon et al.	N/A	N/A
10431186	12/2018	Park et al.	N/A	N/A
10467949	12/2018	Han et al.	N/A	N/A
10758780	12/2019	Putnam	N/A	N/A
2007/0124694	12/2006	Van De Sluis et al.	N/A	N/A
2010/0188325	12/2009	Inoue	N/A	N/A
2013/0171601	12/2012	Yuasa et al.	N/A	N/A
2014/0270535	12/2013	Hung	N/A	N/A
2016/0093081	12/2015	Kim et al.	N/A	N/A
2016/0231918	12/2015	Shin	N/A	G06F 3/048
2017/0140732	12/2016	Kim	N/A	N/A
2018/0144718	12/2017	Park	N/A	N/A
2020/0066036	12/2019	Choi	N/A	N/A
2021/0026142	12/2020	Gotoh	N/A	N/A
2021/0033760	12/2020	Coa	N/A	N/A
2021/0193085	12/2020	Haas	N/A	G09G 5/10
2021/0201661	12/2020	Al Jazaery	N/A	G08C 23/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
207397618	12/2017	CN	N/A
10-2008-0007499	12/2007	KR	N/A
10-2015-0108571	12/2014	KR	N/A
10-2018-0005862	12/2017	KR	N/A
10-2018-0058363	12/2017	KR	N/A

10-2018-0089646	12/2017	KR	N/A
10-2106708	12/2019	KR	N/A
10-2020-0099246	12/2019	KR	N/A
10-2020-0107520	12/2019	KR	N/A
10-2188766	12/2019	KR	N/A
10-2193036	12/2019	KR	N/A
10-2209745	12/2020	KR	N/A
2012/039467	12/2011	WO	N/A
2019/078867	12/2018	WO	N/A

OTHER PUBLICATIONS

Guan Ming Lim et al., Camera-based Hand Tracking using a Mirror-based Multi-view Setup, Jul. 1, 2020, Annual International Conference of the IEEE Engineering in Medicine & Biology Society, pp. 5789-5793 (Year: 2020). cited by examiner

Pedro Henriquez et al., Mirror Mirror on the Wall . . . An Unobtrusive Intelligent Multisensory Mirror for Well-Being Status Self-Assessment and Visualization, Jul. 1, 2017, IEEE Transactions on Multimedia, vol. 19, No. 7, pp. 1467-1481 (Year: 2017). cited by examiner

Communication dated Jun. 24, 2022, issued by the International Searching Authority in counterpart International Application No. PCT/KR2022/003665 (PCT/ISA/210 and PCT/ISA/237). cited by applicant

Yasmina Andreu-Cabedo et al., Mirror Mirror on the Wall . . . An Intelligent Multisensory Mirror for Well-Being Self-Assessment, Jun. 1, 2015, IEEEExplore, pp. 1-6 (Year: 2015). cited by applicant

Jong-Jae Lee et al., 3D Mirrored Object Selection for Occluded Objects in Virtual Environments, Jan. 1, 2020, IEEE Access, vol. 8 pp. 200259-200270 (Year: 2020). cited by applicant

Communication issued Mar. 21, 2024 by the European Patent Office in European Patent Application No. 22771755.0. cited by applicant

Communication issued on Oct. 8, 2024 by the Korean Intellectual Property Office in Korean Patent Application No. 10-2021-0034481. cited by applicant

Communication dated Apr. 23, 2025, issued by the Korean Intellectual Property Office in Korean Application No. 10-2021-0034481. cited by applicant

Primary Examiner: Tran; Tam T

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a Continuation of U.S. application Ser. No. 17/877,400, filed Jul. 29, 2022, which is a bypass continuation of International Application No. PCT/KR2022/003665, filed on Mar. 16, 2022, which is based on and claims priority to Korean Patent Application No. 10-2021-0034481, filed on Mar. 17, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

(1) This disclosure relates to an electronic device and a controlling method thereof, and more particularly, to an electronic device that may improve visibility of reflected content viewed on a

mirror display and a controlling method thereof.

2. Description of Related Art

(2) An electronic device equipped with a minor display capable of displaying content while performing a mirror function has been developed. Specifically, the mirror display reflects light incident on the mirror display from an external light source to perform a mirror function, while displaying content/information stored in the electronic device.

(3) However, when an image corresponding to a reflection of a user in front of the mirror display is reflected off of the mirror display according to the mirror function for viewing by the user, there may be a problem in that the visibility of the content/information displayed by the electronic device may be degraded by light incident from the external light source and/or the user image.

(4) Accordingly, there is need to improve the visibility of the content/information displayed on the minor display in consideration of the effect of light incident from the external light source and/or the user image.

SUMMARY

(5) Provided are an electronic device that may improve visibility of content displayed on a minor display and a controlling method thereof.

(6) According to an aspect of the disclosure, a first electronic device may include a first sensor configured to sense a user; a second sensor configured to sense light incident from an external light source; a mirror display; a memory; and a processor configured to: based on the first sensor sensing the user in front of the minor display, obtain information about a first area in which a first image corresponding to a reflection of the user is located on the mirror display, determine a second area for displaying content to be provided to the user based on the information about the first area, based on information about light being obtained through the second sensor, determine luminance of the second area based on the information about light, and control the minor display to display the content with the determined luminance on the second area.

(7) The information about the first area may include information about a size of the first area and information about a position of the first area. The processor may be further configured to determine a position and a size of the second area based on the information about the size of the first area and the information about the position of the first area.

(8) The information about light may include information about a direction of light and information about an intensity of light. The processor may be further configured to: determine the position and the size of the second area based on the information about the first area and the information about the direction of the light, and determine luminance of the second area based on the information about the intensity of light.

(9) The first sensor may include an image sensor, and the processor may be further configured to: obtain a second image corresponding to the user through the image sensor, obtain information about a pose of the user by inputting the second image into a trained neural network model, and determine the position and the size of the first area based on the information about the pose of the user.

(10) The processor may be further configured to identify types of a plurality of objects within the content, respectively, by inputting data about the content to a trained neural network model, and determine luminance of areas corresponding to each of the plurality of objects in the second area based on the information about light and the types of each of the plurality of objects.

(11) The processor may be further configured to determine luminance of the second area based on the information about light, the information about types of the content, and information about brightness of the content.

(12) The processor may be further configured to: determine a position of a user interface to control the content based on the information about the first area and the information about the second area, and control the mirror display to display the user interface at the determined position.

(13) The processor may be further configured to: identify whether the user is a pre-registered user

based on user data stored in the memory, based on the user being the pre-registered user, identify the content based on the user data corresponding to the pre-registered user, and control the mirror display to display the identified content on the second area.

(14) The electronic device may further include a communication interface. The user data may be health-related data received from an external device through the communication interface, and the content may include recommended content corresponding to the health-related data.

(15) The processor may be further configured to: process the content so that a boundary area between the first area and the second area is blended, and control the mirror display to display the processed content on the second area.

(16) According to another aspect of the disclosure, a method of controlling an electronic device comprising a mirror display may include based on a user on in front of the mirror display being sensed, obtaining information about a first area in which a first image corresponding to a reflection of the user is located on the mirror display; determining a second area for displaying content to be provided to the user based on the information about the first area; based on information about light being obtained through a second sensor, determining luminance of the second area based on the information about light; and displaying the content with the determined luminance on the second area.

(17) The information about the first area may include information about a size of the first area and information about a position of the first area. The determining the second area may include determining a position and a size of the second area based on the information about the size of the first area and the information about the position of the first area.

(18) The information about light may include information about a direction of light and information about an intensity of light. The determining the second area may include determining the position and the size of the second area based on the information about the first area and the information about the direction of the light. The determining luminance of the second area comprises determining luminance of the second area based on the information about the intensity of light.

(19) The method may further include obtaining a second image corresponding to the user; obtaining information about a pose of the user by inputting the second image to a trained neural network model; and determining the position and the size of the first area based on the information about the pose of the user.

(20) The content may include content including a plurality of objects, and the determining the second area further may include identifying types of the plurality of objects, respectively, by inputting data about the content to a trained neural network model; and determining luminance of areas corresponding to each of the plurality of objects in the second area based on the information about light and the types of each of the plurality of objects.

(21) According to yet another aspect of the disclosure, an electronic device may include a first sensor configured to sense a user; a second sensor configured to sense light incident from an external light source; a mirror display configured to provide a visible reflection of the user while also displaying content; a memory; and a processor configured to: based on the first sensor sensing the user in front of the mirror display, obtain information about a location of a reflection of the user from a perspective of the user, determine a displaying area for displaying content to be provided to the user based on information about the location of the reflection of the user, and control the mirror display to display the content on the displaying area.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will be more apparent from the following description taken in conjunction with the

accompanying drawings, in which:

- (2) FIG. 1 is a block diagram of a configuration of an electronic device, according to an embodiment of the disclosure;
- (3) FIGS. 2, 3, and 4 shown an operation of an electronic device, according to an embodiment of the disclosure;
- (4) FIG. 5 is a diagram of an operation of the electronic device for determining a second area, according to an embodiment of the disclosure;
- (5) FIG. 6 is a diagram of an operation of the electronic device for determining a first area according to an embodiment of the disclosure;
- (6) FIG. 7 is a diagram of an operation of the electronic device for determining brightness differently for each object included in the content, according to an embodiment of the disclosure;
- (7) FIG. 8 is a diagram of an operation of the electronic device for displaying a user interface for controlling content, according to an embodiment of the disclosure;
- (8) FIG. 9 is a block diagram illustrating details of an electronic device according to an embodiment of the disclosure; and
- (9) FIG. 10 is a flowchart of a method of controlling an electronic device, according to an embodiment of the disclosure.

DETAILED DESCRIPTION

(10) Hereinafter, embodiments of the disclosure will be described with reference to the accompanying drawings. However, it may be understood that the disclosure is not limited to the embodiments described hereinafter, but also includes various modifications, equivalents, and/or alternatives of the embodiments of the disclosure. In relation to explanation of the drawings, similar drawing reference numerals may be used for similar constituent elements.

(11) When it is decided that a detailed description for the known art related to the disclosure may unnecessarily obscure the gist of the disclosure, the detailed description may be omitted.

(12) In addition, the following embodiments may be modified in many different forms, and the scope of the technical spirit of the disclosure is not limited to the following examples. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the technical spirit to those skilled in the art.

(13) The terms used herein are to describe certain embodiments and are not intended to limit the scope of claims. A singular expression includes a plural expression unless otherwise specified.

(14) In this specification, the expressions “have,” “may have,” “include,” “may include,” or “comprise” or the like represent presence of a corresponding feature (for example: components such as numbers, functions, operations, or parts) and does not exclude the presence of additional feature.

(15) In this document, expressions such as “at least one of A [and/or] B,” or “one or more of A [and/or] B,” include all possible combinations of the listed items. For example, “at least one of A and B,” or “at least one of A or B” includes any of (1) at least one A, (2) at least one B, or (3) at least one A and at least one B.

(16) As used herein, the terms “first,” “second,” or the like may denote various components, regardless of order and/or importance, and may be used to distinguish one component from another, and does not limit the components.

(17) Description of a certain element (e.g., first element) being “operatively or communicatively coupled with/to” or being “connected to” another element (e.g., second element) should be understood to mean that the certain element may be connected to the other element directly or through still another element (e.g., third element).

(18) On the other hand, description of a certain element (e.g., first element) being “directly coupled to” or “directly connected to” another element (e.g., second element) may be understood to mean that there is no element (e.g., third element) between the certain element and the another element.

(19) Also, the expression “configured to” used in the disclosure may be interchangeably used with

other expressions such as “suitable for,” “having the capacity to,” “designed to,” “adapted to,” “made to,” and “capable of,” depending on cases. Meanwhile, the term “configured to” does not necessarily mean that a device is “specifically designed to” in terms of hardware.

(20) Instead, under some circumstances, the expression “a device configured to” may mean that the device “is capable of” performing an operation together with another device or component. For example, the phrase “a processor configured to perform A, B, and C” may mean a dedicated processor (e.g., an embedded processor) for performing the corresponding operations, or a generic-purpose processor (e.g., a central processing unit (CPU) or an application processor) that can perform the corresponding operations by executing one or more software programs stored in a memory device.

(21) Terms such as “module,” “unit,” “part,” and so on are used to refer to an element that performs at least one function or operation, and such element may be implemented as hardware or software, or a combination of hardware and software. Further, except for when each of a plurality of “modules,” “units,” “parts,” and the like needs to be provided in an individual hardware, the components may be integrated in at least one module or chip and be provided in at least one processor.

(22) Various elements and areas in the figures are shown out of scale. Accordingly, the scope of the disclosure is not limited by the relative sizes or spacing drawn from the accompanying drawings.

(23) Hereinafter, with reference to the attached drawings, embodiments will be described in detail so that those skilled in the art to which the disclosure belongs to can easily make and use the embodiments.

(24) FIG. 1 is a block diagram of a configuration of an electronic device according to an embodiment of the disclosure.

(25) As shown in FIG. 1, an electronic device **100** according to an embodiment may include a mirror display **110**, a sensor **120**, a memory **130**, and a processor **140**.

(26) The electronic device **100** may be implemented as a mirror display **110** having a shape such as a stand-type minor. However, the electronic device **100** is not limited to the type and shape of the electronic device **100** of the disclosed embodiments, and the electronic device **100** may be implemented as a TV or a smartphone.

(27) The minor display **110** may be configured to display content while performing a mirror function. That is, an image corresponding to an object disposed in front of the minor display **110** may be off of the minor display **110**, and content stored in the memory **130** may be displayed like a conventional display while an image corresponding to an object disposed on the front surface of the minor display **110** is displayed. The minor display **110** may include a display panel and a minor panel disposed on the display panel, and may further include a touch screen panel disposed on the minor panel.

(28) When the light incident from the external light source is reflected on the mirror display **110**, an image corresponding to an object positioned in front of the mirror display **110** may be reflected off of one area of the mirror display **110**. In other words, if the object is positioned in front of the mirror display **110**, a reflection of the object may be provided on one area on the mirror display **110**. When a user input for displaying content is received or an event for displaying content is generated, the minor display **110** may display content stored in the memory **130**. The content stored in the memory **130** may include not only content obtained by the electronic device **100** and stored in the memory **130**, but also content received from an external device and stored in the electronic device **100**.

(29) The sensor **120** may be configured to sense various information within or outside the electronic device **100**. The sensor **120** may include one or more sensors **120**, and may include a first sensor **120** for sensing a user and a second sensor **120** for sensing light incident from an external light source. The first sensor **120** may include at least one of an image sensor **120**, a proximity sensor **120**, and an infrared sensor **120**. The second sensor **120** may include at least one

of an illuminance sensor **120** and a color sensor **120**. The sensor **120** may include various types of sensors **120**, such as a global positioning system (GPS) sensor **120**, a gyro sensor **120**, an acceleration sensor **120**, a LiDAR sensor **120**, an inertial measurement unit (IMU) **120**, a motion sensor **120**, or the like.

(30) At least one instruction regarding the electronic device **100** may be stored in the memory **130**. In addition, an operating system (O/S) for driving the electronic device **100** may be stored in the memory **130**. The memory **130** may store various software programs or applications for operating the electronic device **100** according to various embodiments. The memory **130** may include a semiconductor memory such as a flash memory, a magnetic storage medium such as a hard disk, or the like.

(31) Specifically, the memory **130** may store various software modules for operating the electronic device **100**, and the processor **140** (e.g., at least one processor) may control the operation of the electronic device **100** by executing various software modules that are stored in the memory **130**. That is, the memory **130** may be accessed by the processor **140**, and may perform reading, recording, modifying, deleting, updating, or the like, of data by the processor **140**.

(32) The term memory **130** may be used to refer to any volatile or non-volatile memory, a ROM, RAM proximate to or in the processor **140** or a memory card (for example, a micro secure digital (SD) card, a memory stick) mounted to the electronic device **100**.

(33) In various embodiments, the memory **130** may store various information or data as described below. The memory **130** may store information about a user sensed through the first sensor **120**, information on the direction and intensity of the light sensed through the second sensor **120**, information on the position and size of the first area **21**, information on the position and size of the second area **22**, information on the luminance of the second area **22**, a plurality of content, or the like. The memory **130** may store various types of user data. Specific, non-limiting examples and embodiments of user data will be described in detail with reference to FIG. **9**.

(34) Various information required within a range for achieving the purpose of the disclosure may be stored in the memory **130**, and information stored in the memory **130** may be received from an external device or updated by being received by a user.

(35) The processor **140** may control overall operations of the electronic device **100**. Specifically, the processor **140** may be connected to a configuration of the electronic device **100** including the minor display **110**, the sensor **120**, and the memory **130** as described above, and may control overall operations of the electronic device **100** by executing at least one instruction stored in the memory **130** as described above.

(36) The processor **140** may be implemented in various ways. For example, the processor **140** may be implemented as at least one of an application specific integrated circuit (ASIC), an embedded processor, a microprocessor, a hardware control logic, a hardware finite state machine (FSM), a digital signal processor (DSP), or the like. Further, processor **140** may include at least one of a central processing unit (CPU), a graphic processing unit (GPU), a main processing unit (MPU), or the like.

(37) According to an embodiment, the processor **140** may sense the user in front of the minor display **110** through the first sensor **120**. The processor **140** may sense a user in front of the minor display **110** through at least one of the image sensor **120**, the proximity sensor **120**, and the infrared sensor **120** included in the first sensor **120**.

(38) As shown in FIGS. **3** through **8**, when the user is located in front of the mirror display **110**, the first image **11** corresponding to the user may be reflected off of one area of the mirror display **110** as the light incident from the external light source is reflected on the mirror display **110**.

Hereinafter, as the light incident from the external light source is reflected on the mirror display **110**, the user image reflected off of one area of the mirror display **110** is referred to as the “first image **11**.”

(39) When the user **10** in front of the minor display **110** is sensed, the processor **140** may obtain

information on a first area **21** on which a reflection of the user is reflected off of the mirror display **110**. The information on the first area **21** may include information on the size of the first area **21** and information on the position of the first area **21**. The location of the first area **21** may be based on a position of the user, such as a position of the user's eyes. That is, the first area **21** may be based on a perspective of a user.

(40) The processor **140** may determine a second area **22** for displaying content to be provided to the user **10** based on information about the first area **21**. The processor **140** may determine the position and size of the second area **22** for displaying the content on the basis of the information on the size of the first area **21** and the information on the position of the first area **21**. According to an embodiment, the second area **22** may be determined as an area among areas on the mirror display **110** that is not overlapped with the first area **21**.

(41) The processor **140** may obtain information on light incident from an external light source **30** through the second sensor **120**. The information on the light may include information on the direction of the light and information on the intensity of the light.

(42) When information about the light is obtained through the second sensor **120**, the processor **140** may determine the luminance of the second area **22** based on the information about the light and display the content on the second area **22**. According to an embodiment, the processor **140** may determine the luminance of the second area **22** so as to correspond to the intensity of light incident on the second area **22**, and display the content with determined luminance on the second area **22**.

(43) Various embodiments based on the control of the processor **140** will be further described with reference to FIGS. 2 to 9.

(44) FIGS. 2, 3, and 4 show an operation of an electronic device according to an embodiment of the disclosure.

(45) When the user **10** is not located in front of the mirror display **110**, the processor **140** may control the minor display **110** to display a standby screen **1** as shown in FIG. 2. For example, the standby screen **1** may include information about the current time, as shown in FIG. 2, and may include various information such as information on the current weather.

(46) When the user **10** approaches the front of the minor display **110** while the standby screen **1** is displayed, as shown in FIG. 3, the first image **11** corresponding to a reflection of the user **10** may be reflected off of one area of the mirror display **110** as the light incident from the external light source **30** is reflected on the mirror display **110**. When the first image **11** is displayed in one area of the minor display **110**, the processor **140** may stop displaying of the standby screen **1**, as shown in FIG. 3.

(47) The processor **140** may sense the user **10** in front of the mirror display **110** through the first sensor **120**. The processor **140** may obtain an image of a scene in front of the mirror display **110** through the image sensor **120** included in the first sensor **120**, perform object recognition on the obtained image, and sense the user **10** in front of the minor display **110**. The processor **140** may sense the user **10** in front of the minor display **110** through at least one of the proximity sensor **120** and the infrared sensor **120** included in the first sensor **120**.

(48) When the user **10** in front of the minor display **110** is sensed, the processor **140** may obtain information on the first area **21** of the mirror display **110**. The processor **140** may identify pixels of the mirror display **110** corresponding to the first image **11** and identify the position and size of the first area **21** including the identified pixels. As shown in FIG. 4, the first area **21** may be an area of the center of the mirror display **110**.

(49) The processor **140** may determine a second area **22** for displaying content to be provided to the user **10** based on information about the first area **21**. The processor **140** may determine the position and size of the second area **22** for displaying the content on the basis of the information on the size of the first area **21** and the information on the position of the first area **21**. As shown in FIG. 4, the content to be provided to the user **10** may include health-related data related to health of the user **10**, and the second area **22** may be determined as a right top area of the minor display **110**.

among the areas on the mirror display **110** that are not overlapped with the first area **21**.

(50) The processor **140** may obtain information on light incident from the external light source **30** through the second sensor **120**. The information on the light may include information on the direction of the light and information on the intensity of the light. When information about the light is obtained through the second sensor **120**, the processor **140** may determine the luminance of the second area **22** based on the information about the light and display the content on the second area **22** with the determined luminance.

(51) The visibility of the user **10** with respect to the content displayed on the second area **22** may vary depending on the direction and intensity of the light incident from the external light source **30**. For example, when a strong intensity of light is incident on the mirror display **110** from the external light source **30** disposed in the right upper direction of the electronic device **100**, the visibility of the user **10** with respect to the content displayed on the second area **22** at the right upper end of the mirror display **110** may be lowered.

(52) The processor **140** may adaptively determine the luminance of the second area **22** according to the direction and intensity of the light incident from the external light source **30**, thereby increasing the visibility of the user **10** with respect to the content displayed on the second area **22**. The processor **140** may determine the luminance of the second area **22** so as to correspond to the intensity of light incident on the second area **22**. According to an embodiment, the processor **140** may determine the brightness of the second area **22** to be proportional to the intensity of light incident on the second area **22**. According to another embodiment, data for a luminance level corresponding to each of a plurality of levels according to the intensity of light may be prestored in the memory **130**, and the processor **140** may determine the luminance of the second area **22** according to a luminance level corresponding to a level of the intensity of light incident on the second area **22**.

(53) According to the embodiment described above with reference to FIGS. 2 to 4, the electronic device **100** may determine an area for displaying content to be provided to the user **10** on the basis of the information on the area in which the user image is displayed according to the mirror function, and adjust the luminance of the area for displaying the content on the basis of the information on the light incident on the mirror display **110**, thereby improving visibility of the user **10** with respect to the content displayed on the mirror display **110**.

(54) FIG. 5 is a diagram showing an embodiment for determining a second area.

(55) Referring to FIGS. 2 to 4, the second area **22** is determined based on the information on the first area **21**, but this is merely exemplary and it is not necessary to use only the information about the first area **21** in determining the second area **22** according to the disclosure. According to another embodiment of the disclosure, the processor **140** may determine the second area **22** using information on light incident from the external light source **30** along with information about the first area **21**.

(56) As described above, when the user **10** approaches the front surface of the mirror display **110**, the first image **11** corresponding to the user **10** may be reflected off of one area of the mirror display **110**. When the user **10** in front of the mirror display **110** is sensed, the processor **140** may obtain information on the first area **21** of the mirror display **110**. The processor **140** may obtain information on light incident from the external light source **30** through the second sensor **120**.

(57) When the information about the first area **21** and the information about the light are obtained, the processor **140** may determine the position and size of the second area **22** based on the information about the first area **21** and the information about the light, and determine the luminance of the second area **22** based on the information about the light.

(58) For example, as shown in FIG. 5, when light of strong intensity is incident on the mirror display **110** from the external light source **30** disposed in the upper right direction of the electronic device **100**, in particular, the visibility of the user **10** with respect to the content displayed on the upper right area of the display **110** may be reduced, and the visibility of the user **10** with respect to

the content displayed on the lower left area of the minor display **110** may be relatively high.

Accordingly, the processor **140** may select one area of the lower left side of the minor display **110** instead of the upper right side of the mirror display **110** among the areas on the minor display **110** that do not overlap the first area **21** as the second area **22**.

(59) However, the embodiment of FIG. **5** is merely an embodiment, and the second area **22** may be determined as an area of a left upper end or a right lower end of the mirror display **110**, and at least a portion of the second area **22** may be determined to overlap at least a portion of the first area **21**. If at least a portion of the second area **22** is determined to overlap at least a portion of the first area **21**, the processor **140** may process the content such that the boundary area between the first image **11** reflected off of the first area **21** and the content displayed on the second area **22** is blended.

(60) The processor **140** may determine the second area **22** based on information on the gaze of the user **10**. The processor **140** may obtain information on the gaze of the user **10** through the sensor **120**, and determine one area including the position on the mirror display **110** corresponding to the gaze of the user **10** as the second area based on the information on the gaze of the user **10**.

(61) According to the embodiment described above with reference to FIG. **5**, the electronic device **100** may improve the visibility of the user **10** with respect to the content displayed on the mirror display **110** by determining the area for displaying the content to be provided to the user **10** using the information on the area in which the user image is displayed according to the mirror function and information about light incident on the mirror display **110**.

(62) FIG. **6** is a diagram showing an embodiment for determining a first area.

(63) Based on assumption that the motion of the user **10** in front of the minor display **110** is not large, a method of obtaining information about the first area **21** in which the first image **11** is reflected off of the mirror display **110** is described, but if a motion of the user **10** is large, an area on which content is displayed by the user image reflected off of the minor display **110** may be largely restricted. Accordingly, the processor **140** may determine a first area **21** for displaying content using information about the pose of the user **10**.

(64) In detail, the first sensor **120** may include the image sensor **120**, and the processor **140** may obtain a second image corresponding to the user **10** through the image sensor **120**. The image sensor **120** may refer to the sensor **120** capable of converting light entering through the lens of the camera into an electrical image signal, and may be included as one component of the camera. In the disclosure, obtaining the second image through the image sensor **120** may be replaced by obtaining a second image through the camera.

(65) The user image obtained through the image sensor **120** is referred to as “second image” by distinguishing from the term first image **11** which refers to a user image reflected off of an area of the mirror display **110** as the light incident from the external light source **30** is reflected on the mirror display **110**.

(66) Once the second image is obtained, the processor **140** may input the second image into a trained first neural network model to obtain information about the pose of the user **10**. The “first neural network model” refers to a model trained to obtain information about the pose of the user **10** included in the user image based on the inputted user image. Specifically, the processor **140** may detect the user **10** included in the second image through the first neural network model and obtain image data for an area including the user **10**. The processor **140** may obtain pose information for the user **10** based on information on a feature point or skeleton of the user **10** included in the image data.

(67) If information about the pose of the user **10** is obtained as described above, the processor **140** may determine the position and size of the first area **21** based on the information on the pose of the user **10**. The processor **140** may estimate an area in which the first image **11** is displayed according to the pose of the user **10** during a predetermined period on the basis of the information about the pose of the user **10**, and determine the estimated area as the first area **21**. For example, as shown in FIG. **6**, the processor **140** may estimate that the first image **11** may reach the upper portion of the

minor display **110** during a predetermined period based on information about the pose of the user **10**, thereby determining the area **21** as shown in FIG. **6** as the second area **22**. Here, the predetermined period may be changed by a developer or setting of the user **10**.

(68) As described above, if the first area **21** is determined based on the information on the pose of the user **10**, the processor **140** may determine the second area **22** for displaying the content based on the information about the first area **21**, determine the luminance of the second area **22** based on the information about the light, and display the content on the second area **22** with the determined luminance. For example, as shown in FIG. **6**, the second area **22** may be determined as the right top area of the mirror display **110** among the areas on the mirror display **110** that are not overlapped with the first area **21**.

(69) The processor **140** may identify the content to be provided to the user **10** based on information about the pose of the user **10**. The processor **140** may estimate an exercise motion of the user **10** based on information about the pose of the user **10** and identify content corresponding to the estimated motion. For example, as shown in FIG. **6**, if the user **10** is assumed to perform a “lunge” movement on the basis of the information about the pose of the user **10**, the processor **140** may identify recommended content for guiding the “lunge” movement and control the mirror display **110** to display the identified recommendation content on the second area **22**.

(70) Referring to FIG. **6**, the electronic device **100** may determine an area in which the user image is displayed according to a mirror function during a predetermined interval on the basis of the information about the pose of the user **10**, and in particular, when the movement of the user **10** is large, it is possible to prevent the area displayed on the minor display **110** from being restricted by the user image reflected off of the minor display **110**.

(71) FIG. **7** is a diagram showing an embodiment for determining brightness differently for each object included in the content.

(72) In the above, information on the light incident from the external light source **30** may be obtained through the second sensor **120**, and the content is displayed by determining the luminance of the second area **22** to correspond to the intensity of light incident on the second area **22**, more specifically, the luminance of the second area **22** may be determined differently depending on the object included in the content. Hereinafter, in the description of FIG. **7**, similarly to the description of FIG. **6**, the second area **22** is determined as an upper right area of the mirror display **110** among the areas on the mirror display **110** which is not overlapped with the first area **21**.

(73) Specifically, as shown in FIG. **7**, the content displayed on the second area **22** may include a plurality of objects. As an example, the plurality of objects may be divided into a “person” and a “background”. The processor **140** may input data on the content into the trained second neural network model to identify the types of each of the plurality of objects included in the content. Here, the “second neural network model” is a neural network trained to output information on the probability that a plurality of objects included in the content correspond to each of a plurality of predefined classes (or categories, domains) based on the data on the content.

(74) The processor **140** may determine the luminance of the second area **22** for each area corresponding to each of the plurality of objects included in the content based on the information about the light and the type of each of the plurality of objects. For example, as shown in FIG. **7**, when the external light source **30** is disposed on the right upper end of the electronic device **100**, the visibility of the user **10** with respect to the content displayed on the second area **22** on the right upper end of the minor display **110** may deteriorate. As shown in FIG. **7**, the processor **140** may determine the luminance of a “person” among the plurality of objects included in the content to be high, and determine the luminance of the “background” to be low.

(75) The processor **140** may determine the luminance of the second area **22** based on the information on the light, the information on the type of content, and the brightness of the content. The memory **130** may store information about the type of the content (or genre) and luminance corresponding to the brightness, and the processor **140** may determine the luminance of the second

area **22** by using the information on the luminance corresponding to the type and brightness of the content together with the information on the light. For example, if the content is “battle movie” and the average brightness of the image frame included in the content is less than a predetermined threshold value, the processor **140** may determine the luminance of the second area **22** relatively lower than when the luminance of the second area **22** is determined based on only information about the light.

(76) According to the embodiment described above with reference to FIG. 7, the electronic device **100** may substantially improve the user's **10** visibility of the content by differently determining the luminance of an area in which the content is displayed according to an object included in the content.

(77) FIG. 8 shown an operation of displaying a user interface for controlling content, according to an embodiment.

(78) In the above description, the first image **11** corresponding to the user **10** in front of the minor display **110** is reflected off of the first area **21** and the content to be provided to the user **10** is displayed on the second area **22**, but a user interface (UI) for controlling the content may be displayed on the minor display **110**. Hereinafter, as shown in FIG. 8, the first area **21** is determined as the center area of the mirror display **110** and the second area **22** is determined as the right upper area of the mirror display **110** among the areas on the mirror display **110**, which is not overlapped with the first area **21**.

(79) The processor **140** may control the mirror display **110** to determine the position of the user **10** interface for controlling the content based on the information about the first area **21** and the information about the second area **22**, and to display the user **10** interface at the determined position. For example, the processor **140** may control the mirror display **110** to display the user **10** interface on an area overlapping a portion of the first area **21** where the first image **11** corresponding to the user **10** is provided to facilitate the touch input of the user **10**.

(80) The user interface may include a plurality of UI items **23-1**, **23-2**, **23-3**, **23-4**, **23-5** for controlling the content displayed on the second area **22**.

(81) As shown in FIG. 8, the user interface may include a UI item **23-1** corresponding to a “rewind” function, a UI item **23-2** corresponding to a function of “moving to a previous content”, a UI item **23-3** corresponding to a function of “moving to the next content”, a UI item **23-4** corresponding to a “fast forward” function, and a UI item **23-5** corresponding to “play/pause” function. The UI item **23-2** corresponding to a function of “moving to the previous content” and the UI item **23-5** corresponding to the “play/pause” function may overlap a portion of the first area **21** on which the first image **11** is displayed. In this example, the processor **140** may process an image corresponding to the UI items **23-2** and **23-5** such that a boundary area between the UI items **23-2** and **23-5** is blended, thereby harmonizing the UI item with the first image **11**.

(82) The processor **140** may process an image corresponding to the UI items **23-2** and **23-5** such that the boundary area between the first image **11** and the UI items **23-2** and **23-5** may be blended, but may process the content to be blended with the boundary area between the first image **11** and the content. The processor **140** may process the content so that a boundary area between the first area **21** and the second area **22** is blended, and control the mirror display **110** to display the processed content on the second area **22**.

(83) According to the embodiment described above with reference to FIG. 8, the electronic device **100** may display a user image reflected off of the mirror display **110** according to a mirror function, and a user interface for controlling the content together with the content to be provided to the user **10**, thereby improving the convenience of the user **10**.

(84) FIG. 9 is a block diagram showing details of an electronic device according to an embodiment.

(85) As shown in FIG. 9, the electronic device **100** according to an embodiment may further include a communication interface **150**, a microphone **160**, and a speaker **170** as well as the mirror display **110**, the sensor **120**, the memory **130**, and the processor **140**. The mirror display **110**, the

sensor **120**, the memory **130**, and the processor **140** have been described above with reference to FIGS. **1** to **8**, and a duplicate description will be omitted. However, prior to describing the communication interface **150**, the microphone **160**, and the speaker **170**, the “user data” stored in the memory **130** and the embodiments related thereto will be described.

(86) As shown in FIG. **9**, the memory **130** may store user data according to the disclosure. Here, “user data” is used to collectively refer to various data related to the user **10** of the electronic device **100**. Specifically, the user data may include identification information, personal information, and health-related information of the user **10**.

(87) The “identification information” may include a face image, fingerprint data, iris data, and account information for identifying the user **10**. The “user personal information” may include information about the personal information of the user **10** and information about a schedule of the user **10**, or the like. The “health-related information” may include information on the heart rate of the user **10**, information on the body temperature of the user **10**, information on the weight of the user **10**, information on the body component of the user **10**, information on the sleep pattern of the user **10**, information on the stress of the user **10**, information on the hormone of the user, information on the emotion of the user **10**, information on the exercise history of the user **10**, information on the exercise history of the user **10**, and the like.

(88) The user data may be obtained through various types of sensors **120** included in the electronic device **100**, may be obtained through various types of sensors **120** included in the external device, and may be received from an external device through the communication interface **150** of the electronic device **100**. Here, the external device may be a user terminal, such as a smart phone, a smart watch, or the like, or may be a cloud server or an edge computing device configured to store/manage user data.

(89) According to an embodiment, the processor **140** may identify whether the user **10** in front of the minor display **110** is the pre-registered user **10** based on the user data. The processor **140** may identify whether the user **10** of the front surface of the mirror display **110** is the pre-registered user **10** depending on whether the identification information stored in the memory **130** is matched with the identification information (e.g., face image, fingerprint data, or iris data) obtained through the sensor **120**. In addition, the processor **140** may identify whether the user **10** is the pre-registered user **10** according to whether the account information stored in the memory **130** matches the account information input by the user **10**.

(90) When it is identified that the user **10** of the front surface of the mirror display **110** is not the pre-registered user **10**, the processor **140** may control the mirror display **110** to display a basic screen including information on the current time, the current weather, or the like.

(91) When the user **10** of the front surface of the minor display **110** is identified as the pre-registered user **10**, the processor **140** may output the greeting message based on the personal information of the user **10**. For example, the processor **140** may control the minor display **110** to display a greeting message, such as “Hello, Mr. Kim”, and may output a voice signal corresponding to the “Hello, Mr. Kim” through the speaker **170**.

(92) If the user **10** of the front surface of the mirror display **110** is the pre-registered user **10**, the processor **140** may control the minor display **110** to display health related data corresponding to the pre-registered user **10**. The processor **140** may control the mirror display **110** to display information on the heart rate of the user **10**, information on the body temperature of the user **10**, information on the weight of the user **10**, information on the body component of the user **10**, information on the sleep pattern of the user **10**, information on the stress of the user **10**, information on the hormone of the user, information on the emotion of the user **10**, information on the exercise history of the user **10**, information on the exercise history of the user **10**, and the like, who is identified as the pre-registered user **10**.

(93) If the user **10** on the front of the mirror display **110** is the pre-registered user **10**, the processor **140** may identify the content to be provided to the user **10** based on health-related data

corresponding to the pre-registered user **10** and control the mirror display **110** to display the identified content on the second area **22**. The processor **140** may identify content such as content that has been recently played by the user **10** that is identified as the pre-registered user **10** among the content stored in the memory **130**, content set to be preferred by the user **10**, recommendation content corresponding to at least some of the health-related information of the user **10**, and to display at least one content of the identified content on the second area **22**.

(94) The process of identifying the recommended content to be provided to the user **10** based on the user data may be performed through the trained third neural network model. The “third neural network model” is trained to identify content corresponding to the personal information and the health-related data of the user **10**, and the electronic device **100** may identify recommended content to be provided to the user **10** using the third neural network model.

(95) While the content provided to the user **10** is stored in the memory **130** of the electronic device **100**, the content provided to the user **10** may be stored in the external device, and the electronic device **100** may receive the content from the external device and may provide the received content to the user **10**.

(96) According to an embodiment as described above, when the user **10** of the front surface of the mirror display **110** is the pre-registered user **10**, the electronic device **100** may provide personalized health-related data and content to the user **10** of the front surface of the mirror display **110** based on the user data, thereby contributing to the health condition management/improvement of the user **10**.

(97) The communication interface **150** may include a circuit and may perform communication with an external device. The processor **140** may receive various data or information from an external device connected through the communication interface **150**, and may transmit various data or information to an external device.

(98) The communication interface **150** may include at least one of a Wi-Fi module, a Bluetooth module, a wireless communication module, and a near field communication (NFC) module. To be specific, the Wi-Fi module may communicate by a Wi-Fi method and the Bluetooth module may communicate by a Bluetooth method. When using the Wi-Fi module or the Bluetooth module, various connection information such as service set identifier (SSID) may be transmitted and received for communication connection and then various information may be transmitted and received.

(99) The wireless communication module may communicate according to various communication specifications such as IEEE, Zigbee, 3rd generation (3G), 3rd generation partnership project (3GPP), long term evolution (LTE), 5th generation (5G), or the like. The NFC module may communicate by the NFC method using a 13.56 MHz band among various RF-ID frequency bands such as 135 kHz, 13.56 MHz, 433 MHz, 860-960 MHz, 2.45 GHz, or the like.

(100) According to various embodiments, the processor **140** may receive user data as described above from an external device through the communication interface **150** and may store the received user data in the memory **130**.

(101) The microphone **160** may receive a voice signal and convert the received voice signal to an electrical signal. According to an embodiment, the processor **140** may receive a voice signal corresponding to a voice of the user **10**, input the received voice signal to a trained voice recognition model to obtain text information corresponding to the voice signal, and identify a control command corresponding to the obtained text information. For example, the user voice may correspond to a control command to change the position of the second area **22** or the size of the second area **22**, a control command to change the type of content displayed on the second area **22**, or a control command to control content displayed on the second area **22**.

(102) The speaker **170** may output audio data under the control of the processor **140**. According to an embodiment, the speaker **170** may output a voice signal corresponding to the content displayed on the second area **22**, a feedback voice signal corresponding to the voice of the user **10** received through the microphone **160**, or a greeting message for the pre-registered user **10**.

(103) Although various configurations of the electronic device **100** have been described above, the above-described configurations are merely exemplary, and in the practice of the disclosure, a new configuration may be added or some configuration may be omitted in addition to the configuration as shown in FIG. 9.

(104) FIG. 10 is a flowchart of a method of controlling an electronic device according to an embodiment.

(105) As shown in FIG. 10, the electronic device **100** may sense the user in front of the mirror display in operation **S1010**. When the user in front of the mirror display is not detected in operation **S1010**—N, the electronic device **100** may display a standby screen until a user of the front surface of the mirror display is sensed.

(106) If the user of the front surface of the mirror display is sensed in operation **S1010**—Y, the electronic device **100** may obtain information on the first area in which the first image corresponding to a reflection of a user is reflected off of the mirror display in operation **S1020**. The information on the first area may include information on the size of the first area and information on the position of the first area.

(107) The electronic device **100** may determine a second area for displaying the content to be provided to the user based on the information about the first area in operation **S1030**. The electronic device **100** may determine a position and a size of a second area for displaying content on the basis of information on the size of the first area and information on a position of the first area. According to an embodiment, the second area may be determined as one of the areas on the mirror display that is not overlapped with the first area.

(108) The electronic device **100** may obtain information on light incident from the external light source through the second sensor. The information on the light may include information on the direction of the light and information on the intensity of the light.

(109) When information about the light is obtained through the second sensor, the electronic device **100** may determine the luminance of the second area based on the information about the light in operation **S1040**. The electronic device **100** may display the content with the determined luminance on the second area in operation **S1050**. According to an embodiment, the processor may determine the luminance of the second area to correspond to the intensity of light incident on the second area, and display the content with the determined luminance on the second area.

(110) The controlling method of the electronic device **100** according to the aforementioned embodiment may be implemented as a program and provided to the electronic device **100**. In particular, a program including the controlling method of the electronic device **100** may be stored in a non-transitory computer readable medium and provided.

(111) Specifically, in a computer-readable recording medium including a program for executing a controlling method of the electronic device **100**, the controlling method of the electronic device **100** may include the steps of obtaining information on a first area on which a first image corresponding to a user is reflected off of a mirror display when a user of the front surface of the mirror display is sensed; determining a second area for displaying content to be provided to the user on the basis of the information on the first area; determining luminance of the second area on the basis of the information on the light when the information on the light incident from the external light source is obtained; and displaying the content with the determined luminance on the second area.

(112) As described above, the electronic device **100** may determine a second area using information on light incident from an external light source along with information about the first area, determine a first area for displaying the content using information about the pose of the user, and the luminance of the second area may be determined differently according to an object included in the content.

(113) The non-transitory computer readable medium refers to a medium that stores data semi-permanently rather than storing data for a very short time, such as a register, a cache, a memory,

etc., and is readable by an apparatus (i.e., executable by at least one processor). In detail, the aforementioned various applications or programs may be stored in the non-transitory computer readable medium, for example, a compact disc (CD), a digital versatile disc (DVD), a hard disc, a Blu-ray disc, a universal serial bus (USB), a memory card, a read only memory (ROM), and the like, and may be provided.

(114) A controlling method of the electronic device **100** and a computer-readable recordable medium including a program for executing the controlling method of the electronic device **100** are described, but this is to omit redundant description, and various embodiments of the electronic device **100** may be applied to the controlling method of the electronic device **100** and a computer-readable recordable medium including a program for executing the controlling method of the electronic device **100**.

(115) A function related to the foregoing may be performed by a memory and a processor.

(116) The processor may include one or a plurality of processors. At this time, one or a plurality of processors may be a general purpose processor, such as a central processing unit (CPU), an application processor (AP), or the like, a graphics-only processing unit such as a graphics processing unit (GPU), a visual processing unit (VPU), and/or an AI-dedicated processor such as a neural processing unit (NPU).

(117) The one or a plurality of processors control the processing of the input data in accordance with a predefined operating rule or artificial intelligence (AI) model stored in the non-volatile memory and the volatile memory. The predefined operating rule or artificial intelligence model is provided through training or learning.

(118) Being provided through learning may refer, for example, to, by applying a learning algorithm to a plurality of learning data, a predefined operating rule or AI model of a desired characteristic being made. The learning may be performed in a device itself in which AI according to an embodiment is performed, and/o may be implemented through a separate server/system.

(119) The AI model may include a plurality of neural network layers. Each layer has a plurality of weight values, and performs a layer operation through calculation of a previous layer and an operation of a plurality of weights. Examples of neural networks include, but are not limited to, convolutional neural network (CNN), deep neural network (DNN), recurrent neural network (RNN), restricted Boltzmann Machine (RBM), deep belief network (DBN), bidirectional recurrent deep neural network (BRDNN), generative adversarial networks (GAN), and deep Q-networks.

(120) The learning algorithm may include a method for training a predetermined target device (for example, a robot) using a plurality of learning data to cause, allow, or control the target device to make a determination or prediction. Examples of learning algorithms include, but are not limited to, supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning.

(121) The machine-readable storage medium may be provided in the form of a non-transitory storage medium. The, “non-transitory” storage medium may not include a signal (e.g., electromagnetic wave) and is tangible, but does not distinguish whether data is permanently or temporarily stored in a storage medium. For example, the “non-transitory storage medium” may include a buffer in which data is temporarily stored.

(122) According to various embodiments, a method disclosed herein may be provided in a computer program product. A computer program product may be traded between a seller and a purchaser as a commodity. A computer program product may be distributed in the form of a machine readable storage medium (e.g., compact disc ROM (CD-ROM)) or distributed online through an application store (e.g., PlayStore™) or distributed (e.g., download or upload) online between two user devices (e.g., smartphones) directly. In the case of on-line distribution, at least a portion of the computer program product (e.g., a downloadable app) may be stored temporarily or at least temporarily in a storage medium such as a manufacturer's server, a server in an application store, or a memory in a relay server.

(123) In addition, each of the components (e.g., modules or programs) according to various

embodiments may include a single entity or a plurality of entities, and some sub-components of the sub-components described above may be omitted, or other sub-components may be further included in the various embodiments. Alternatively or additionally, some components (e.g., modules or programs) may be integrated into one entity to perform the same or similar functions performed by the respective components prior to the integration.

(124) The operations performed by the module, the program, or other component, in accordance with various embodiments may be performed in a sequential, parallel, iterative, or heuristic manner, or at least some operations may be executed in a different order or omitted, or other operations may be added.

(125) The term “unit” or “module” used in the disclosure includes units consisting of hardware, software, or firmware, and is used interchangeably with terms such as, for example, logic, logic blocks, parts, or circuits. A “unit” or “module” may be an integrally constructed component or a minimum unit or part thereof that performs one or more functions. For example, the module may be configured as an application-specific integrated circuit (ASIC).

(126) Embodiments may be implemented as software that includes instructions stored in machine-readable storage media readable by a machine (e.g., a computer). A device may call instructions from a storage medium and that is operable in accordance with the called instructions, including an electronic device (e.g., the electronic device **100**).

(127) When the instruction is executed by a processor, the processor may perform the function corresponding to the instruction, either directly or under the control of the processor, using other components. The instructions may include a code generated or executed by the compiler or interpreter.

(128) While embodiments of the disclosure have been shown and described, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined at least by the appended claims and their equivalents.

Claims

1. An electronic device comprising: a camera; a first sensor configured to sense light incident from an external light source; a mirror display; and a processor configured to: obtain, through the camera, a first image corresponding to a user through the camera, obtain information regarding a pose of the user by inputting the first image into a trained first neural network model, identify, based on the information regarding the pose of the user, a first area in which the first image corresponding to a reflection of the user is to be located on the mirror display according to a movement of the user during a predetermined period, and obtain information regarding light through the first sensor, identify a second area for displaying content to be provided to the user based on information regarding the first area and the information regarding light, the second area being different from the first area, and control the mirror display to display the content on the second area.
2. The electronic device of claim 1, further comprising: a second sensor configured to sense the user; and wherein the processor is further configured to: based on the second sensor sensing the user in front of the mirror display, obtain information regarding a third area in which the first image corresponding to the reflection of the user is located on the mirror display, and identify the second area for displaying content to be provided to the user based on information regarding the first area, based on information regarding the third area and the information regarding light.
3. The electronic device of claim 2, wherein the processor is further configured to: based on information regarding light being obtained through the first sensor, identify luminance of the second area based on the information regarding the light, and control the mirror display to display the content with the identified luminance on the second area.

4. The electronic device of claim 3, wherein the information regarding the third area comprises information regarding a size of the third area and information regarding a position of the first area, and wherein the processor is further configured to identify a position and a size of the second area based on the information regarding the size of the second area and the information regarding the position of the second area.
5. The electronic device of claim 3, wherein the information regarding the light comprises information regarding a direction of the light and information regarding an intensity of the light, and wherein the processor is further configured to: identify a position and a size of the second area based on the information regarding the third area and the information regarding the direction of the light, and identify the luminance of the second area based on the information regarding the intensity of the light.
6. The electronic device of claim 3, wherein the processor is further configured to: identify types of a plurality of objects within the content, respectively, by inputting data regarding the content to a trained second neural network model, and identify luminance of areas corresponding to each of the plurality of objects in the second area based on the information regarding the light and the types of each of the plurality of objects.
7. The electronic device of claim 3, wherein the processor is further configured to identify the luminance of the second area based on the information regarding the light, the information regarding types of the content, and information regarding brightness of the content.
8. The electronic device of claim 3, wherein the processor is further configured to: identify a position of a user interface to control the content based on the information regarding the third area and the information regarding the second area, and control the mirror display to display the user interface at the identified position.
9. The electronic device of claim 3, further comprising: a memory, wherein the processor is further configured to: identify whether the user is a pre-registered user based on user data stored in the memory, based on the user being the pre-registered user, identify the content based on the user data corresponding to the pre-registered user, and control the mirror display to display the identified content on the second area.
10. The electronic device of claim 3, wherein the processor is further configured to: process the content so that a boundary area between the first area and the second area is blended, and control the mirror display to display the processed content on the second area.
11. A method of controlling an electronic device comprising a mirror display, the method comprising: obtaining, through a camera, a first image corresponding to a user through the camera, obtaining information regarding a pose of the user by inputting the first image into a trained first neural network model, identifying, based on the information regarding the pose of the user, a first area in which the first image corresponding to a reflection of the user is to be located on the mirror display according to a movement of the user during a predetermined period, obtaining information regarding light through a first sensor, identifying a second area for displaying content to be provided to the user based on information regarding the first area and the information regarding light, the second area being different from the first area, and controlling the mirror display to display the content on the second area.
12. The method of claim 11, further comprising: based on a second sensor sensing the user in front of the mirror display, obtaining information regarding a third area in which the first image corresponding to the reflection of the user is located on the mirror display, and identifying the second area for displaying content to be provided to the user based on information regarding the first area, based on information regarding the third area and the information regarding light.
13. The method of claim 12, further comprising: based on information regarding light being obtained through the first sensor, identifying luminance of the second area based on the information regarding the light, and controlling the mirror display to display the content with the identified luminance on the second area.

14. The method of claim 13, wherein the information regarding the third area comprises information regarding a size of the third area and information regarding a position of the first area, and wherein the method further comprises identifying a position and a size of the second area based on the information regarding the size of the second area and the information regarding the position of the second area.
15. The method of claim 13, wherein the information regarding the light comprises information regarding a direction of the light and information regarding an intensity of the light, and wherein the method further comprises: identifying a position and a size of the second area based on the information regarding the third area and the information regarding the direction of the light, and identifying the luminance of the second area based on the information regarding the intensity of the light.
16. The method of claim 13, wherein the method further comprises: identifying types of a plurality of objects within the content, respectively, by inputting data regarding the content to a trained second neural network model, and identifying luminance of areas corresponding to each of the plurality of objects in the second area based on the information regarding the light and the types of each of the plurality of objects.
17. The method of claim 13, wherein the method further comprises: identifying the luminance of the second area based on the information regarding the light, the information regarding types of the content, and information regarding brightness of the content.
18. The method of claim 13, wherein the method further comprises: identifying a position of a user interface to control the content based on the information regarding the third area and the information regarding the second area, and controlling the mirror display to display the user interface at the identified position.
19. The method of claim 13, further comprising: identifying whether the user is a pre-registered user based on user data stored in a memory of the electronic device, based on the user being the pre-registered user, identifying the content based on the user data corresponding to the pre-registered user, and controlling the mirror display to display the identified content on the second area.
20. The method of claim 13, wherein the method further comprises: processing the content so that a boundary area between the first area and the second area is blended, and controlling the mirror display to display the processed content on the second area.
-