

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406543
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Etou; Yoshiyuki et al.

Voting system and voting method

Abstract

A voting system and a voting method by which electronic voting can be securely conducted are provided. A voting system includes: a secret sharing unit that generates a plurality of shares from voting information by secret sharing; a plurality of share storage units that store the plurality of shares in a distributed manner; a first blockchain processing unit that transmits, to a node managing a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; and a secure computation unit that performs secure computation for analyzing the voting by using the shares stored in a distributed manner.

Inventors:	Etou; Yoshiyuki (Tokyo, JP), Itonaga; Wataru (Tokyo, JP), Matsuda; Daisuke (Tokyo, JP), Furukawa; Ryo (Tokyo, JP)
Applicant:	NEC Corporation (Tokyo, JP)
Family ID:	83322077
Assignee:	NEC CORPORATION (Tokyo, JP)
Appl. No.:	18/282016
Filed (or PCT Filed):	March 19, 2021
PCT No.:	PCT/JP2021/011441
PCT Pub. No.:	WO2022/195860
PCT Pub. Date:	September 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240153332 A1	May. 09, 2024

Publication Classification

Int. Cl.: G07C13/00 (20060101); H04L9/08 (20060101)

U.S. Cl.:

CPC G07C13/00 (20130101); H04L9/085 (20130101); H04L2209/463 (20130101)

Field of Classification Search

CPC: G07C (13/00); H04L (9/085); H04L (2209/463)

USPC: 235/51

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2019/0288846	12/2018	Zawierka	N/A	G06Q 30/00
2019/0384748	12/2018	Roennow	N/A	G06F 16/1837
2020/0351083	12/2019	Bartolucci	N/A	H04L 9/3247
2021/0049690	12/2020	Wright	N/A	H04L 9/3066
2021/0135855	12/2020	Sunkavally	N/A	H04L 9/0825
2022/0035932	12/2021	Baldi	N/A	G06F 21/602
2022/0158892	12/2021	Fedorov	N/A	G06F 11/1482
2022/0173917	12/2021	Basu	N/A	H04L 63/1458
2022/0253813	12/2021	Pospieszalski	N/A	H04L 9/50
2022/0271957	12/2021	Zamani	N/A	H04L 9/3239
2024/0007479	12/2023	Doney	N/A	H04L 63/12
2024/0153332	12/2023	Etou	N/A	G07C 13/00
2024/0338682	12/2023	Anton	N/A	H04L 9/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2003-099557	12/2002	JP	N/A
2004-13606	12/2003	JP	N/A
2004-192029	12/2003	JP	N/A
2011-248436	12/2010	JP	N/A
2018-101380	12/2017	JP	N/A
2020-0077366	12/2019	KR	N/A
2009/014215	12/2008	WO	N/A
2019/173519	12/2018	WO	N/A

OTHER PUBLICATIONS

JP Office Action for JP Application No. 2023-506675, mailed on Sep. 3, 2024 with English Translation. cited by applicant
International Search Report for PCT Application No. PCT/JP2021/011441, mailed on Jun. 22, 2021. cited by applicant

Background/Summary

(1) This application is a National Stage Entry of PCT/JP2021/011441 filed on Mar. 19, 2021, the contents of all of which are incorporated herein by reference, in their entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a voting system and a voting method.

BACKGROUND ART

(3) Technologies for conducting electronic voting are known. For example, Patent Literature 1 discloses a compilation system that allows disclosure of vote distributions in which the corresponding relations between candidates and their votes are concealed. This compilation system is configured to disclose, instead of disclosing a list of decrypted plaintexts, a list of conversion and decryption results, and further disclose information (conversion and decryption result proof data) that enables verification that the conversion and decryption results are correct without using the list of decrypted plaintexts.

CITATION LIST

Patent Literature

(4) Patent Literature 1: International Patent Publication No. WO 2009/014215

SUMMARY OF INVENTION

Technical Problem

(5) In recent years, there has been a growing increase in the use of Information and Communication Technology (ICT) for social activities, and hence there has been a demand that new systems for conducting electronic voting be provided.

(6) Therefore, one of the objects that are achieved by an example embodiment disclosed herein is to provide a voting system and a voting method by which electronic voting can be securely conducted.

Solution to Problem

(7) A voting system according to a first example aspect of the present disclosure includes: secret sharing means for generating a plurality of shares from voting information by secret sharing; a plurality of share storage means for storing the plurality of shares in a distributed manner; first blockchain processing means for transmitting, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; and secure computation means for performing secure computation for analyzing the voting by using the shares stored in a distributed manner.

(8) A voting method according to a second example aspect of the present disclosure includes: generating a plurality of shares from voting information by secret sharing; storing the plurality of shares in a distributed manner; transmitting, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; and performing secure computation for analyzing the voting by using the shares stored in a distributed manner.

Advantageous Effects of Invention

(9) According to the present disclosure, it is possible to provide a voting system and a voting method by which electronic voting can be securely conducted.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a block diagram showing an example of a configuration of a voting system according to an outline of an example embodiment;
- (2) FIG. 2 is a schematic diagram showing an example of a configuration of a voting system according to the example embodiment;
- (3) FIG. 3 is a block diagram showing an example of a functional configuration of a voter terminal;
- (4) FIG. 4 is a block diagram showing an example of a functional configuration of a computing server;
- (5) FIG. 5 is a block diagram showing an example of a functional configuration of an administrator terminal;
- (6) FIG. 6 is a sequence chart showing an example of a flow of operations performed by the voting system according to the example embodiment; and
- (7) FIG. 7 is a block diagram showing an example of a configuration of a computer.

EXAMPLE EMBODIMENT

Outline of Example Embodiment

- (8) Prior to describing an example embodiment in detail, an outline of the example embodiment will be given first. FIG. 1 is a block diagram showing an example of a configuration of a voting system 1 according to the outline of the example embodiment. As shown in FIG. 1, the voting system 1 includes a secret sharing unit 2, a share storage unit 3, a blockchain processing unit 4, and a secure computation unit 5.
- (9) The secret sharing unit 2 generates a plurality of shares (also refers to as distributed information) from voting information by secret sharing. That is, one piece of voting information is divided into N (N is an integer greater than or equal to two) shares (distributed information). Note that, although original voting information cannot be restored from one share, voting information can be restored by collecting M (M is an integer greater than or equal to two and less than or equal to N) shares out of N shares.
- (10) The voting system 1 includes a plurality of share storage units 3. The plurality of share storage units 3 store a plurality of shares generated by the secret sharing unit 2 in a distributed manner. When N shares are generated for one piece of voting information, the voting system 1 includes, for example, N share storage units 3. However, the shares may be stored in more than N share storage units 3, or in fewer than N share storage units 3.
- (11) The blockchain processing unit 4 transmits to the node that manages a blockchain transaction data of voting conducted using voting information in order to record the transaction data in the blockchain. This node is a node composing a blockchain network. By the above configuration, the node performs processing for recording transaction data in the blockchain. The transaction data recorded in the blockchain is any history of voting action based on voting information. For example, transaction data recorded in the blockchain may include data for identifying voters, data indicating the content of the voting, or data indicating the date and time of the conduction of the voting. The blockchain is an information group in which blocks, which compose a set of transaction data, are connected, and is ledger information managed on a network in a distributed manner. The blockchain having the above characteristics is typically tamper-resistant. By recording transaction data of voting in the blockchain, voting fraud can be prevented.
- (12) The secure computation unit 5 performs secure computation for analyzing voting by using the shares stored in a distributed manner. For example, the secure computation unit 5 performs secure computation by performing Multi-party computation (MPC).
- (13) According to the voting system 1 having the above configuration, voting fraud can be prevented and analysis of voting can be performed while keeping voting information secret. Therefore, according to the voting system 1, electronic voting can be securely conducted.
- (14) Next, details of the example embodiment will be described. FIG. 2 is a schematic diagram

showing an example of a configuration of a voting system **10** according to the example embodiment. The voting system **10** is a system that receives votes from voters and performs analysis of a result of the voting. As an example, the voting system **10** shown in FIG. 2 includes voter terminals **100_1**, **100_2**, . . . , and **100_N.sub.1**, a computing server group **200**, an administrator terminal **300**, and a blockchain network **400**. Note that, in FIG. 2, in order to aid the understanding thereof, voters **90_1**, **90_2**, . . . , and **90_N.sub.1** and an administrator **91** are also illustrated in addition to the voting system **10**. In the following description, the voter terminals **100_1**, **100_2**, . . . , and **100_N.sub.1** are referred to as the voter terminals **100** when they are referred to without being particularly distinguished from each other, and the voters **90_1**, **90_2**, . . . , and **90_N.sub.1** are referred to as the voters **90** when they are referred to without being particularly distinguished from each other.

(15) The blockchain network **400** is a network composed of nodes **401_1**, **401_2**, . . . , and **401_N.sub.2** that manage the blockchain, and may be provided, for example, as a cloud service. Note that, in the following description, the nodes **401_1**, **401_2**, . . . , and **401_N.sub.2** are referred to as the nodes **401** when they are referred to without being particularly distinguished from each other. Each of the nodes **401** is a node that composes the blockchain network **400**, and is a server that shares a blockchain, performs processing for recording transaction data in the blockchain, and so on. The node **401** receives transaction data to be written into the blockchain from another apparatus (e.g., the voter terminal **100** or the administrator terminal **300**) and performs processing for recording it in the blockchain.

(16) The voter terminal **100** is a terminal apparatus used by the voter **90** for voting, such as a smartphone, a tablet terminal, and a personal computer. The voters **90** uses the respective voter terminals **100** to vote. That is, the voter **90_i** (where $1 \leq i \leq N.sub.1$) uses the voter terminal **100_i** to vote. FIG. 3 is a block diagram showing an example of a functional configuration of the voter terminal **100**. As shown in FIG. 3, the voter terminal **100** includes an authentication unit **110**, a voting information generation unit **120**, a secret sharing unit **130**, a share storage processing unit **140**, and a blockchain processing unit **150**.

(17) The authentication unit **110** authenticates the voter **90** by using personal information of the voter **90**. The personal information is information input in the voter terminal **100**, and may be, for example, biometric information of the voter **90**. Note that, for example, the biometric information includes, but is not limited to, facial features, fingerprint features, and iris features of the voter **90**. Although authentication can be made more convenient by using biometric information, the authentication unit **110** may instead perform authentication by using personal information such as the ID and password of the voter **90**. The authentication unit **110** may also perform authentication by transmitting personal information to an authentication server (not shown) and receiving a result of the authentication from the authentication server.

(18) The voting information generation unit **120** generates voting information corresponding to an input operation performed by the voter **90**. For example, the voter **90** performs an input operation to select the content of the voting through an input apparatus included in the voter terminal **100**. By doing so, the content of the voting is determined. Note that the content of the voting is not limited to the selection of a specific person from among candidates such as heads or assembly members, and may instead be the selection of options (e.g., yes or no) in a predetermined public opinion poll. The voting information generation unit **120** generates data including the determined content of the voting as voting information. Note that the voting information generation unit **120** may generate voting information including not only the content of the voting but also various types of information. In this example embodiment, the voting information generation unit **120** generates voting information including, for example, the content of the voting and information indicating the attributes of the voter **90**. Note that the information indicating the attributes of the voter **90** may be, for example, information indicating the gender of the voter **90**, information indicating the age of the voter **90**, or information indicating the affiliation of the voter **90**. These pieces of information

are merely examples, and other information may be used as information indicating the attributes. Further, the voting information may include information indicating the date and time when the voting information was generated or information for identifying the voter **90**. In this example embodiment, the voting information generation unit **120** generates voting information when the authentication unit **110** successfully authenticates the voter **90**. Therefore, the voter **90** can be correctly identified.

(19) The secret sharing unit **130**, which corresponds to the secret sharing unit **2** shown in FIG. **1**, encrypts voting information generated by the voting information generation unit **120** using a secret sharing method. That is, the secret sharing unit **130** performs secret sharing processing on voting information in accordance with a predetermined secret sharing method, and generates a plurality of shares from this voting information. For example, the secret sharing unit **130** may use All or Nothing Transformation (AONT) as a secret sharing method. However, it is merely an example, and the secret sharing unit **130** may perform secret sharing processing by other secret sharing methods.

(20) In general, the secret sharing method cannot restore original data from one of the generated shares, but can restore original data by collecting a predetermined number of shares. Therefore, data can be prevented from being leaked by storing a plurality of generated shares in a distributed manner. In this example embodiment, the share storage processing unit **140** stores shares generated from one piece of voting information in three servers, namely, computing servers **201A**, **201B**, and **201C**, in a distributed manner, which servers will be described later. Therefore, the share storage processing unit **140** transmits the generated shares to the computing servers **201A**, **201B**, and **201C** in a distributed manner, and causes share storage units **210** included in the respective computing servers **201A**, **201B**, and **201C** to store them in a distributed manner. By doing so, voting information can be prevented from being leaked. Note that, in this example embodiment, as described above, processing of secret sharing is performed by the terminal apparatus used by the voter **90** to generate voting information. That is, secret sharing is performed before voting information is transmitted from the terminal apparatus (i.e., the voter terminal **100**) to another apparatus. Therefore, the occurrence of leakage of voting information during transmission can be prevented, and thus a system can be provided which is more secure than a system in which secret sharing is performed after transmission of voting information to another apparatus.

(21) The blockchain processing unit **150**, which corresponds to the blockchain processing unit **4** shown in FIG. **1**, transmits, to the node **401** that manages a blockchain, transaction data of voting in order to record the transaction data in the blockchain. Specifically, for example, the blockchain processing unit **150** generates transaction data of voting and broadcasts the generated transaction data to the blockchain network **400**. That is, the blockchain processing unit **150** transmits transaction data to each of the nodes **401** composing the blockchain network **400**. The broadcast transaction data is processed by the nodes **401** and then added to the blockchain as a block including one or a plurality of transaction data.

(22) The blockchain processing unit **150** may generate data including the following information as transaction data. For example, the blockchain processing unit **150** may generate transaction data including data for identifying the voter **90**, data indicating the content of the voting, and data indicating the date and time of the conduction of the voting. Note that the blockchain processing unit **150** may generate transaction data including only some of these pieces of data. For example, the blockchain processing unit **150** may generate transaction data including only data for identifying the voter **90** or transaction data including data identifying for the voter **90** and data indicating the date and time of the conduction of the voting. Note that the data for identifying the voter **90** may be data that enables the voter **90** to be identified, and it may be the name or the ID of the voter **90**. Further, the date and time of the conduction of the voting may be specifically the date and time of the generation of voting information or the date and time of the transmission of voting information to the blockchain network **400**.

(23) Further, when cancellation of an earlier voting is permitted, the blockchain processing unit **150** may generate transaction data including data related to the cancellation of the voting and transmit the transaction data to the blockchain network **400**. The data related to the cancellation of the voting may be, for example, one of data for identifying a person who performed the cancellation, data for specifying the voting to be cancelled, or data indicating the date and time when the cancellation was performed, or any combination thereof. Note that the blockchain processing unit **150** sets a user identified by authentication performed by the authentication unit **110** as the person who performed the cancellation. Further, when revoting is permitted, the blockchain processing unit **150** may generate transaction data for the revoting and transmit it to the blockchain network **400**.

(24) Note that the blockchain processing unit **150** may calculate a hash value of data to be recorded as transaction data and use the calculated hash value as transaction data. Further, although some examples of data to be included as transaction data have been described, these are merely examples and other data may be included in transaction data. For example, information indicating the attributes of the voter **90** may be included in transaction data.

(25) As described above, by generating transaction data including various types of data, it is possible to record various types of histories related to the voting in the blockchain.

(26) Next, the computing server group **200** will be described. The computing server group **200** is a server group that stores shares generated by secret sharing processing in a distributed manner and performs secure computation by using the shares stored in a distributed manner, and in this example embodiment, the computing server group **200** includes three computing servers **201A**, **201B**, and **201C**. The computing servers **201A**, **201B**, and **201C** may be servers managed by organizations (e.g., a municipality, an election administration commission, and a third-party organization) different from each other. In the following description, when the computing servers **201A**, **201B**, and **201C** are referred to as the computing servers **201** when they are referred to without being particularly distinguished from each other. FIG. **4** is a block diagram showing an example of a functional configuration of the computing server **201**. As shown in FIG. **4**, each of the computing servers **201** includes the share storage unit **210** and a secure computation unit **220**.

(27) The share storage unit **210**, which corresponds to the share storage unit **3** shown in FIG. **1**, is a storage that stores shares generated by the secret sharing unit **130** of the voter terminal **100**. As described above, a plurality of shares generated for one piece of voting information are stored in the share storage unit **210** of each of the computing servers **201** in a distributed manner.

(28) The secure computation unit **220**, which corresponds to the secure computation unit **5** shown in FIG. **1**, performs secure computation for analyzing voting by using the shares stored in the share storage unit **210**. In this example embodiment, the secure computation units **220** of the respective computing servers **201A**, **201B**, and **201C** perform multi-party calculation (MPC) in cooperation with the secure computation unit **220** of another computing server **201**. In this example embodiment, the secure computation unit **220** performs secure computation and transmits a result of the secure computation to the administrator terminal **300** in response to a request from the administrator terminal **300**. The result of the secure computation transmitted by each of the secure computation units **220** is a secrecy-shared result of the computation. Therefore, the final result of the computation can be obtained by collecting the results of the secure computation transmitted by the secure computation units **220** and then performing decryption processing.

(29) Next, the administrator terminal **300** will be described. The administrator terminal **300** is a terminal apparatus used by the administrator **91**, such as an election administrator, to acquire results of analysis of voting from a plurality of voters, and is, for example, a smartphone, a tablet terminal, or a personal computer. FIG. **5** is a block diagram showing an example of a functional configuration of the administrator terminal **300**. As shown in FIG. **5**, the administrator terminal **300** includes an authentication unit **310**, a computation instruction unit **320**, a computation result decrypting unit **330**, an output unit **340**, and a blockchain processing unit **350**.

(30) The authentication unit **310** authenticates the administrator **91** by using personal information of the administrator **91**. This personal information is information input to the administrator terminal **300** and may be, for example, biometric information of the administrator **91**. Note that, for example, the biometric information includes, but is not limited to, facial features, fingerprint features, and iris features of the administrator **91**. The authentication unit **310** may perform authentication by using personal information such as the ID and password of the administrator **91**. The authentication unit **310** may also perform authentication by transmitting personal information to an authentication server (not shown) and receiving a result of the authentication from the authentication server.

(31) In order to perform analysis specified by an input operation performed by the administrator **91**, the computation instruction unit **320** instructs the computing server **201** to execute secure computation according to the specified analysis. That is, the computation instruction unit **320** instructs the computing server **201** to perform secure computation for analyzing voting in response to an input operation performed by the administrator **91**. In other words, the computation instruction unit **320** transmits a request for the execution of secure computation to the computing server **201**. The secure computation for analyzing voting may be statistical processing using voting information. That is, the secure computation unit **220** of the computing server **201** may calculate a result of statistical processing using voting information as the result of the secure computation. For example, the number of votes for each option (each candidate) may be calculated. Further, in particular, when voting information includes information indicating the attributes of the voter **90**, the secure computation for analyzing voting may be statistical processing related to the attributes. That is, in this case, the secure computation unit **220** of the computing server **201** may calculate statistical data related to the attributes of the voter **90**. For example, the distribution of the ages, the age groups, or the genders of the voters **90** may be calculated for each option they voted for, or the distribution of the options for the voting destination may be calculated for each age, each age group, or each gender. In this example embodiment, the computation instruction unit **320** instructs the computing server **201** to execute secure computation when the authentication unit **310** successfully authenticates the administrator **91**. Therefore, a user who has instructed the execution of the secure computation can be correctly identified.

(32) The computation result decrypting unit **330** acquires the result of the secure computation performed based on an instruction provided by the computation instruction unit **320** from the computing servers **201** and performs decryption processing. The computation result decrypting unit **330** obtains the final result of the computation (the result of analysis of the voting) by performing decryption processing according to a predetermined secret sharing method (e.g., AONT) used by the secret sharing unit **130** of the voter terminal **100**.

(33) The output unit **340** outputs the final result of the computation obtained by the computation result decrypting unit **330**, that is, the result of analysis of the voting. For example, the output unit **340** may output the final result of the computation to a display connected to the administrator terminal **300** or may transmit it to another apparatus.

(34) The blockchain processing unit **350** transmits, to the node **401** that manages a blockchain, transaction data about the execution of the secure computation in order to record the transaction data in the blockchain. Specifically, for example, the blockchain processing unit **350** generates transaction data about the execution of the secure computation and broadcasts the generated transaction data to the blockchain network **400**. That is, the blockchain processing unit **350** transmits transaction data to each of the nodes **401** composing the blockchain network **400**. The broadcast transaction data is processed by the nodes **401** and then added to the blockchain as a block including one or a plurality of transaction data.

(35) The blockchain processing unit **350** may generate data including the following information as transaction data. For example, the blockchain processing unit **350** may generate transaction data including data for identifying the user (the administrator **91**) who has instructed the execution of

the secure computation, data indicating the content of analysis obtained by the execution of the secure computation, and data indicating the date and time of the execution of the secure computation. Note that the blockchain processing unit **350** may generate transaction data including only some of these pieces of data. For example, the blockchain processing unit **350** may generate transaction data including only data for identifying a user or transaction data including data for identifying a user and data indicating the date and time of the execution of the secure computation. Note that the data for identifying a user may be data that enables a user to be identified, and it may be the name or the ID of a user. Further, the date and time of the execution of the secure computation may be the date and time of the provision of the instruction by the computation instruction unit **320**, the date and time of the decryption by the computation result decrypting unit **330**, or the date and time of the output by the output unit **340**.

(36) Note that the blockchain processing unit **350** may calculate a hash value of data to be recorded as transaction data and use the calculated hash value as transaction data. Further, although some examples of data to be included as transaction data have been described, these are merely examples and other data may be included in transaction data. As described above, by generating transaction data including various types of data, it is possible to record various types of histories related to the execution of the analysis in the blockchain.

(37) Next, a flow of operations performed by the voting system **10** will be described. FIG. **6** is a sequence chart showing an example of the flow of the operations performed by the voting system **10**. The flow of the operations will be described below with reference to the sequence chart shown in FIG. **6**.

(38) In Step **S100**, the authentication unit **110** of the voter terminal **100** authenticates the voter **90**.

(39) When the voter **90** is successfully authenticated, the voting information generation unit **120** of the voter terminal **100** generates, in Step **S101**, voting information corresponding to an input operation performed by the voter **90**.

(40) Next, in Step **S102**, the secret sharing unit **130** of the voter terminal **100** generates a plurality of shares from the voting information generated in Step **101** by secret sharing.

(41) Next, in Step **S103**, the share storage processing unit **140** of the voter terminal **100** stores the plurality of shares generated in Step **S102** in three servers, namely, the computing servers **201A**, **201B**, and **201C**, in a distributed manner. Thus, in Step **S104**, the shares are stored in the share storage units **210** of the computing servers **201A**, **201B**, and **201C**.

(42) In Step **S105**, the blockchain processing unit **150** of the voter terminal **100** generates transaction data of voting and broadcasts the generated transaction data to the blockchain network **400**.

(43) The processes in Steps **S100** to **S105** are performed in the voter terminal **100** of each of the voters. As a result, the shares of the voting information transmitted from the voter terminals **100** of a plurality of voters are stored in the share storage units **210** of the computing servers **201**.

(44) Then, in Step **S106**, the authentication unit **310** of the administrator terminal **300** authenticates the administrator **91**.

(45) When the administrator **91** is successfully authenticated, the computation instruction unit **320** of the administrator terminal **300** instructs, in Step **S107**, the computing server **201** to perform secure computation for analyzing the voting in response to an input operation performed by the administrator **91**.

(46) In response to this instruction, in Step **S108**, the secure computation unit **220** of each of the computing servers **201** performs the secure computation by using the share stored in the share storage unit **210**.

(47) Then, in Step **S109**, the secure computation unit **220** of each of the computing servers **201** transmits a result of the secure computation to the administrator terminal **300**.

(48) Next, in Step **S110**, the computation result decrypting unit **330** of the administrator terminal **300** performs decryption processing on the acquired result of the secure computation, and obtains a

result of the analysis of the voting.

(49) Next, in Step **S111**, the output unit **340** of the administrator terminal **300** outputs the result of the analysis obtained in Step **S110**.

(50) Next, in Step **S112**, the blockchain processing unit **350** of the administrator terminal **300** generates transaction data about the execution of the secure computation and broadcasts the generated transaction data to the blockchain network **400**.

(51) The flow of the operations performed by the voting system **10** has been described above. These operations described above are merely examples and various changes can be made. For example, a timing at which transaction data is recorded in the blockchain is not limited to the timing shown in FIG. **6** and can be changed to any timing.

(52) The example embodiment has been described above. In the voting system according to this example embodiment, voting information is subjected to secret sharing processing and then stored in a distributed manner. Then, analysis of voting is performed by secure computation. Further, histories are recorded in the blockchain. Thus, according to the voting system **10**, voting fraud can be prevented and analysis of voting can be performed while keeping voting information secret. Therefore, according to the voting system **10**, electronic voting can be securely conducted. Note that various changes can be made to the above-described example embodiment. For example, each of the computing servers **201** may serve as the node **401** of the blockchain network **400**. That is, for example, the storage of the computing server **201** may store the blockchain and the computing server **201** may perform processing for recording transaction data in the blockchain. Further, when data regarding the shares stored in the share storage unit **210** is lost, the computing server **201** may perform data recovery in accordance with an algorithm of a predetermined secret sharing method (e.g., AONT). Further, in this example embodiment, although the voting system **10** includes three computing servers **201**, the number of computing servers **201** is not limited to three and may be any number as long as it is a plural number.

(53) Further, although the processing of the voter terminal **100**, the computing server **201**, the administrator terminal **300**, or the node **401** can be implemented by a hardware circuit, it can be implemented, for example, by causing a processor of a computer to execute a computer program.

(54) FIG. **7** is a block diagram showing an example of a configuration of a computer **500** that implements the processing of the voter terminal **100**, the computing server **201**, the administrator terminal **300**, or the node **401**. As shown in FIG. **7**, the computer **500** includes a network interface **501**, a memory **502**, and a processor **503**.

(55) The network interface **501** is used to communicate with any other apparatus.

(56) The memory **502** is composed of, for example, a combination of volatile memory and non-volatile memory. The memory **502** is used to store software (a computer program) including at least one instruction executed by the processor **503**, and the like.

(57) The processor **503** loads the software (the computer program) from the memory **502** and executes it, thereby performing the processing of the voter terminal **100**, the computing server **201**, the administrator terminal **300**, or the node **401**.

(58) The processor **503** may be, for example, a microprocessor, a Micro Processor Unit (MPU), or a Central Processing Unit (CPU). The processor **503** may include a plurality of processors.

(59) Note that the above-described program can be stored and provided to a computer using any type of non-transitory computer readable media. Non-transitory computer readable media include any type of tangible storage media.

(60) Examples of non-transitory computer readable media include magnetic storage media (such as floppy disks, magnetic tapes, hard disk drives, etc.), optical magnetic storage media (e.g., magneto-optical disks), CD-ROM (compact disc read only memory), CD-R (compact disc recordable), CD-R/W (compact disc rewritable), and semiconductor memories (such as mask ROM, PROM (programmable ROM), EPROM (erasable PROM), flash ROM, RAM (random access memory), etc.). The program may be provided to a computer using any type of transitory computer readable

media. Examples of transitory computer readable media include electric signals, optical signals, and electromagnetic waves. Transitory computer readable media can provide the program to a computer via a wired communication line (e.g., electric wires, and optical fibers) or a wireless communication line.

(61) Although the present invention has been described above with reference to an example embodiment, the present invention is not limited to the above-described example embodiment. Various changes that can be understood by those skilled in the art can be made to the configuration and details of the present invention within the scope of the invention.

(62) The whole or part of the example embodiment disclosed above can be described as, but not limited to, the following supplementary notes.

Supplementary Note 1

(63) A voting system comprising: secret sharing means for generating a plurality of shares from voting information by secret sharing; a plurality of share storage means for storing the plurality of shares in a distributed manner; first blockchain processing means for transmitting, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; and secure computation means for performing secure computation for analyzing the voting by using the shares stored in a distributed manner.

Supplementary Note 2

(64) The voting system according to supplementary note 1, wherein processing of the secret sharing means is performed by a terminal apparatus used by a voter to generate the voting information.

Supplementary Note 3

(65) The voting system according to supplementary note 1 or 2, further comprising: authentication means for authenticating a voter by using personal information of the voter; and voting information generation means for generating the voting information corresponding to an input operation performed by the voter when the voter is successfully authenticated.

Supplementary Note 4

(66) The voting system according to supplementary note 3, wherein the personal information is biometric information of the voter.

Supplementary Note 5

(67) The voting system according to any one of supplementary notes 1 to 4, wherein the transaction data recorded in the blockchain includes data for identifying the voter.

Supplementary Note 6

(68) The voting system according to supplementary note 5, wherein the transaction data recorded in the blockchain further includes data indicating a content of the voting.

Supplementary Note 7

(69) The voting system according to supplementary note 5 or 6, wherein the transaction data recorded in the blockchain further includes data indicating a date and time of execution of the voting.

Supplementary Note 8

(70) The voting system according to any one of supplementary notes 1 to 7, wherein the transaction data recorded in the blockchain includes data related to cancellation of the voting.

Supplementary Note 9

(71) The voting system according to any one of supplementary notes 1 to 8, further comprising second blockchain processing means for transmitting, to the node, transaction data about execution of the secure computation in order to record the transaction data in the blockchain.

Supplementary Note 10

(72) The voting system according to supplementary note 9, wherein the transaction data about the execution of the secure computation recorded in the blockchain includes data for identifying a user

who has instructed the execution of the secure computation.

Supplementary Note 11

(73) The voting system according to supplementary note 10, wherein the transaction data about the execution of the secure computation recorded in the blockchain further includes data indicating a content of analysis obtained by the execution of the secure computation.

Supplementary Note 12

(74) The voting system according to supplementary note 10 or 11, wherein the transaction data about the execution of the secure computation recorded in the blockchain further includes data indicating a date and time of the execution of the secure computation.

Supplementary Note 13

(75) The voting system according to any one of supplementary notes 1 to 12, wherein the voting information includes information indicating attributes of the voter, and the secure computation means calculates statistical data related to the attributes.

Supplementary Note 14

(76) A voting method comprising: generating a plurality of shares from voting information by secret sharing; storing the plurality of shares in a distributed manner; transmitting, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; and performing secure computation for analyzing the voting by using the shares stored in a distributed manner.

REFERENCE SIGNS LIST

(77) **1 VOTING SYSTEM 2 SECRET SHARING UNIT 3 SHARE STORAGE UNIT 4 BLOCKCHAIN PROCESSING UNIT 5 SECURE COMPUTATION UNIT 10 VOTING SYSTEM 90 VOTER 91 ADMINISTRATOR 100 VOTER TERMINAL 110 AUTHENTICATION UNIT 120 VOTING INFORMATION GENERATION UNIT 130 SECRET SHARING UNIT 140 SHARE STORAGE PROCESSING UNIT 150 BLOCKCHAIN PROCESSING UNIT 200 COMPUTING SERVER GROUP 201 COMPUTING SERVER 210 SHARE STORAGE UNIT 220 SECURE COMPUTATION UNIT 300 ADMINISTRATOR TERMINAL 310 AUTHENTICATION UNIT 320 COMPUTATION INSTRUCTION UNIT 330 COMPUTATION RESULT DECRYPTING UNIT 340 OUTPUT UNIT 350 BLOCKCHAIN PROCESSING UNIT 400 BLOCKCHAIN NETWORK 401 NODE 500 COMPUTER 501 NETWORK INTERFACE 502 MEMORY 503 PROCESSOR**

Claims

1. A voting system comprising: a plurality of storages; at least one memory storing instructions; and at least one processor configured to execute the instructions to: generate a plurality of shares from voting information using secret sharing; cause the storages to store the plurality of shares in a distributed manner; transmit, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; perform secure computation for analyzing the voting by using the shares stored in a distributed manner; and transmit, to the node, transaction data about execution of the secure computation in order to record the transaction data in the blockchain, wherein the transaction data about the execution of the secure computation recorded in the blockchain includes data for identifying a user who has instructed the execution of the secure computation.
2. The voting system according to claim 1, wherein processing for generating the plurality of shares is performed by a terminal apparatus used by a voter to generate the voting information.
3. The voting system according to claim 1, wherein the processor is further configured to execute the instructions to: authenticate a voter using personal information of the voter; and generate the voting information corresponding to an input operation performed by the voter when the voter is successfully authenticated.

4. The voting system according to claim 3, wherein the personal information is biometric information of the voter.

5. The voting system according to claim 1, wherein the transaction data of the voting recorded in the blockchain includes data for identifying a voter.

6. The voting system according to claim 5, wherein the transaction data of the voting recorded in the blockchain further includes data indicating content of the voting.

7. The voting system according to claim 5, wherein the transaction data of the voting recorded in the blockchain further includes data indicating a date and time of execution of the voting.

8. The voting system according to claim 1, wherein the transaction data of the voting recorded in the blockchain includes data related to cancellation of the voting.

9. The voting system according to claim 1, wherein the transaction data about the execution of the secure computation recorded in the blockchain further includes data indicating content of analysis obtained by the execution of the secure computation.

10. The voting system according to claim 1, wherein the transaction data about the execution of the secure computation recorded in the blockchain further includes data indicating a date and time of the execution of the secure computation.

11. The voting system according to claim 1, wherein the voting information includes information indicating attributes of a voter, and the processor is further configured to execute the instructions to calculate statistical data related to the attributes of the voter.

12. A voting method performed by a computer and comprising: generating a plurality of shares from voting information using secret sharing; storing the plurality of shares in a distributed manner; transmitting, to a node configured to manage a blockchain, transaction data of voting conducted using the voting information in order to record the transaction data in the blockchain; performing secure computation for analyzing the voting by using the shares stored in a distributed manner; and transmitting, to the node, transaction data about execution of the secure computation in order to record the transaction data in the blockchain, wherein the transaction data about the execution of the secure computation recorded in the blockchain includes data for identifying a user who has instructed the execution of the secure computation.
