

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12406581
B2
September 02, 2025
Noguchi; Kohei et al.

Position information output method, position information output system, and program

Abstract

Provided is a position information output method of causing a computer to acquire position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device mounted on a moving body at a first timing via a network from the moving body including at least one of a vehicle and a terminal device owned by an occupant of the vehicle, and output information, which indicates that the moving body is present at a position indicated by the position information, from an output part after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition.

Inventors:	Noguchi; Kohei (Tokyo, JP), Mukohara; Hodaka (Tokyo, JP)
Applicant:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Family ID:	83458216
Assignee:	HONDA MOTOR CO., LTD. (Tokyo, JP)
Appl. No.:	18/284559
Filed (or PCT Filed):	March 31, 2021
PCT No.:	PCT/JP2021/013850
PCT Pub. No.:	WO2022/208728
PCT Pub. Date:	October 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240177605 A1	May. 30, 2024

Publication Classification

Int. Cl.: G08G1/13 (20060101); G08G1/01 (20060101)

U.S. Cl.:

CPC G08G1/13 (20130101); G08G1/01 (20130101);

Field of Classification Search

CPC: G08G (1/13); G08G (1/01); G08G (1/0112); G08G (1/0133); G08G (1/0141); G08G (1/052); G08G (1/096716); G08G (1/096775); H04W (4/40); H04W (12/02); H04W (4/029)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2014/0195100	12/2013	Lundsgaard	701/29.6	G07C 5/008
2020/0184815	12/2019	Wakita	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106664507	12/2016	CN	N/A
2015-103025	12/2014	JP	N/A
2016-143232	12/2015	JP	N/A
2019-075747	12/2018	JP	N/A
2015/184055	12/2014	WO	N/A
2019/003399	12/2018	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for International Application No.

PCT/JP2021/013850 mailed on Jun. 15, 2021, 8 pages. cited by applicant

Extended European Search Report for European Patent Application No. 21934895.0 dated Apr. 5, 2024. cited by applicant

Ghinita, et al. "Protecting Against Velocity-Based, Proximity-Based, and External Event Attacks in Location-Centric Social Networks", ACM Transactions on Spatial Algorithms and Systems, vol. 2, No. 2, Jun. 21, 2016 (Jun. 21, 2016), pp. 1-36, XP058692223, ISSN: 2374-0353, DOI: 10.1145/2910580. cited by applicant

Gruteser et al. "Anonymous Usage of Location-Based Services Through Spatial and Temporal Cloaking", Proceedings of the 1st International Conference on Mobile Systems, Applications and Services, Mobisys '03, Jan. 1, 2003 (Jan. 1, 2003), pp. 31-42, XP055732558, New York, New York, USA, DOI: 10.1145/1066116.1189037. cited by applicant

India Office Action for India Patent Application No. 202317065242 mailed Feb. 28, 2025. cited by applicant

Primary Examiner: Goins; Davetta W

Assistant Examiner: Akhter; Sharmin

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a position information output method, a position information output system, and a program.

BACKGROUND ART

(2) In recent years, a system of transmitting traffic jam information and transmitting advertisement using movement information of moving bodies has become known. However, when positions of moving bodies are continuously notified, individuals may be able to be identified. Therefore, a technology that notifies the position of a moving body without identifying an individual is attracting attention.

(3) For example, as a general method for performing anonymization processing, there is a method of statistically processing a certain number or more of individuals as a group. However, if statistical processing is performed, since individual characteristics will be lost, it will be impossible to send advertisements that are aimed at individuals. In addition, information is lost for a small number of moving bodies that cannot be grouped together.

(4) In addition, in a communication device provided in a vehicle, after sending the current position information first, it is known to send only the position variation information at intervals of a predetermined time to prevent the current position of the vehicle from being leaked to a third party due to unauthorized access or the like (see Patent Document 1).

CITATION LIST

Patent Document

(5) [Patent Document 1]

(6) PCT International Publication No. 2019/003399

SUMMARY OF INVENTION

Technical Problem

(7) However, in the related art, during initial reference position transmission, anonymity could not be ensured in some cases because the current position of the vehicle was known.

(8) In consideration of the above-mentioned circumstances, the present invention is directed to providing a position information output method, a position information output system, and a program that are capable of securing anonymity of current positions of moving bodies.

Solution to Problem

(9) (1) A position information output method causes a computer to: acquire position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device (**113**, **260**) mounted on a moving body at a first timing via a network from the moving body including at least one of a vehicle (**100**) and a terminal device (**200**) owned by an occupant of the vehicle; and output information, which indicates that the moving body is present at a position indicated by the position information, from an output part (**330**) after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition.

(10) (2) In the above-mentioned (1), in a case the predetermined parameter is a distance, the computer may determine that the predetermined condition is satisfied when a movement distance of the vehicle from a position of the vehicle at the first timing is equal to or greater than a predetermined value.

(11) (3) In the above-mentioned (1) or (2), in a case the predetermined parameter is a time, the computer may determine that the predetermined condition is satisfied when an elapsed time from a

time in which the vehicle was at the first timing is equal to or greater than a predetermined value.

(12) (4) In any one of the above-mentioned (1) to (3), the computer may acquire a movement speed of the moving body on the basis of information detected by a detector mounted on the moving body or the position information, in a case the movement speed is smaller than a predetermined value, set the predetermined parameter as a distance and determine that the predetermined condition is satisfied when a movement distance from a position of the vehicle at the first timing is equal to or greater than a predetermined value, and in a case the movement speed is greater than the predetermined value, set the predetermined parameter as a time and determine that the predetermined condition is satisfied when an elapsed time from a time in which the vehicle was at the first timing is equal to or greater than a predetermined value.

(13) (5) In the above-mentioned (4), the computer may acquire an average value in a predetermined section as the movement speed of the moving body.

(14) (6) A position information output system (1) includes a moving body including at least one of a vehicle (100) and a terminal device (200) owned by an occupant of the vehicle, and an information management server (300) configured to communicate with the moving body via a network, wherein the moving body includes a communication part (111, 210) configured to transmit position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device (113, 260) mounted on the moving body at a first timing to the information management server via a network, and the information management server includes an output controller (353) configured to output information, which indicates that the moving body is present at a position indicated by the position information, from an output part (330) after a second timing which is when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition.

(15) (7) A program causes a computer to: acquire position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device (113, 260) mounted on a moving body at a first timing via a network from the moving body including at least one of a vehicle (100) and a terminal device (200) owned by an occupant of the vehicle; and output information, which indicates that the moving body is present at a position indicated by the position information, from an output part (330) after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition.

Advantageous Effects of Invention

(16) According to the above-mentioned (1) to (7), it is possible to secure anonymity of current positions of moving bodies.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic view of a position information output system 1 according to an embodiment.
- (2) FIG. 2 is a functional block diagram of a motorcycle 100.
- (3) FIG. 3 is a functional block diagram of a user terminal device 200.
- (4) FIG. 4 is a functional block diagram of an information management server 300.
- (5) FIG. 5 is a view showing an example of contents of a temporary DB 341 and a position information DB 342.
- (6) FIG. 6 is a view for describing an example of a second timing determination method (Part 1).
- (7) FIG. 7 is a view for describing an example of a second timing determination method (Part 2).
- (8) FIG. 8 is a sequence diagram showing an example of processing in the position information

output system **1**.

(9) FIG. **9** is a flowchart showing an example of processing of the information management server **300** by the second timing determination method (Part 1).

(10) FIG. **10** is a flowchart showing an example of processing of the information management server **300** by the second timing determination method (Part 2).

(11) FIG. **11** is a functional block diagram of a motorcycle **100A**.

(12) FIG. **12** is a functional block diagram of a user terminal device **200A**.

DESCRIPTION OF EMBODIMENTS

(13) Hereinafter, embodiments of a position information output method, a position information output system, and a program of the present invention will be described with reference to the accompanying drawings.

First Embodiment

(14) [Entire Configuration]

(15) FIG. **1** is a schematic view of a position information output system **1** according to an embodiment. The position information output system **1** is, for example, a motorcycle **100**, a user terminal device **200**, and an information management server **300**. The motorcycle **100**, the user terminal device **200**, and the information management server **300** are connected to each other via a network NW. Further, the network NW includes, for example, the Internet, a wide area network (WAN), a provider device, a radio base station, and the like. Further, the motorcycle **100** and the user terminal device **200** can be connected to each other using near field communication.

(16) The motorcycle **100** is, for example, a unit swing scooter type motorcycle. The user terminal device **200** is a communication terminal owned by an occupant in the motorcycle **100**, and a portable terminal device having at least a communication function and a display function, for example, a mobile phone such as a smartphone or the like, a tablet terminal, a personal digital assistant (PDA), or the like. The motorcycle **100** and the user terminal device **200** are examples of moving bodies.

(17) The information management server **300** manages information received from the motorcycle **100** or the user terminal device **200**, and notifies a manager of the information received from the motorcycle **100** or the user terminal device **200**. In the embodiment, while an example in which the information management server **300** notifies the manager of the information acquired by the motorcycle **100** will be described, the present invention is not limited thereto. For example, the information management server **300** may notify the manager of the information acquired by the user terminal device **200**, transmit the information acquired by the motorcycle **100** through short-distance wireless communication, and notify the manager of the information received from the motorcycle **100** by the user terminal device **200**.

(18) <Motorcycle>

(19) FIG. **2** is a functional block diagram of the motorcycle **100**. The motorcycle **100** includes, for example, a communication part **111**, a short-distance wireless communication part **112**, a GNSS receiver **113**, a speed detector **114**, a distance detector **115**, an accelerator grip **116**, a brake lever **117**, an engine **118**, a brake device **119**, a display device **120**, a controller **130**, and a storage **140**.

(20) The communication part **111** includes, for example, a communication interface such as an NIC or the like. The communication part **111** performs communication with the information management server **300** via a communication network such as the Internet or the like under control of the controller **130**. The short-distance wireless communication part **112** has the user terminal device **200**, an antenna and transmission/reception device that is a wireless module used for Bluetooth (registered trademark) or the like, and the like.

(21) The GNSS receiver **113** receives a signal from a global navigation satellite system (GNSS) satellite. The speed detector **114** includes, for example, a wheel speed sensor attached to a wheel, and a speed calculator, and integrates wheel speeds detected by the wheel speed sensor to derive a traveling speed (vehicle speed) of the motorcycle **100** and outputs the derived traveling speed to the

controller **130**. The distance detector **115** includes a wheel rotation sensor attached to a wheel, and a traveling distance calculator, and derives a traveling distance of the motorcycle **100** on the basis of the wheel rotational speed detected by the wheel rotation sensor and outputs the derived traveling distance to the controller **130**.

(22) The accelerator grip **116** is equipped with a sensor that detects an operation quantity or presence of an operation, and receives instructions for acceleration. The brake lever **117** is equipped with a sensor that detects an operation quantity or presence of an operation, and receives instruction for deceleration or stopping.

(23) The engine **118** outputs a traveling driving force (torque) for the motorcycle **100** to travel to the driving wheels. The engine **118** includes, for example, an internal combustion engine, an electric motor, a gearbox, and the like. The brake device **119** includes, for example, a brake caliper, a cylinder configured to transmit a hydraulic pressure to the brake caliper, and an electric motor configured to generate a hydraulic pressure in the cylinder. The display device **120** includes, for example, a liquid crystal display (LCD), an organic electroluminescence (EL) display, or the like. The display device **120** is installed at a position that is easily seen by a driver during driving.

(24) The controller **130** is, for example, an electronic control unit (ECU). The controller **130** is described as one block for the sake of simplicity of description, but it is not limited to this and may be divided into plurality of units.

(25) The controller **130** includes, for example, a communication controller **131**, a position specification part **132**, a movement speed acquisition part **133**, a movement distance acquisition part **134**, an engine controller **135**, a brake controller **136**, a transmission controller **137**, and a display controller **138**. Some or all of these functional units are realized by executing a program (software) stored in a storage thereof using a processor such as a central processing unit (CPU) or the like. In addition, some or all of the functions of these components may be realized by hardware (circuit unit: including circuitry) such as a large scale integration (LSI), an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or the like, or may be realized by cooperation of software and hardware. The program may be stored in a storage device such as a hard disk drive (HDD), a flash memory, or the like, in advance, may be stored in a detachable storage medium such as a DVD, a CD-ROM, or the like, or may be installed by mounting a storage medium in a drive device.

(26) The communication controller **131** controls the communication part **111** and performs communication with the information management server **300** via the network NW. In addition, the communication controller **131** controls the short-distance wireless communication part **112** and performs communication with the user terminal device **200**.

(27) The position specification part **132** specifies a position of the motorcycle **100** on the basis of the signal received by the GNSS receiver **113**. The position of the motorcycle **100** is expressed as a latitude and longitude. Further, the position specification part **132** generates information (hereinafter, referred to as position information) in which information indicating the specified position of the motorcycle **100** is associated with information indicating measurement date and time (date and time specifying the position of the motorcycle **100**).

(28) The movement speed acquisition part **133** acquires information (hereinafter, referred to as movement speed information) showing a movement speed of the motorcycle **100** on the basis of the output from the speed detector **114**. The “movement speed” may be a speed per hour at a certain time, or may be an average value of a speed per hour in a predetermined section. The predetermined section may be a predetermined period defined by time, or a predetermined length defined by a distance. By doing this, even if there is a temporary deceleration from high speed traveling, it can be prevented from notifying the location immediately. Further, not limited to this, the movement speed acquisition part **133** may acquire movement speed information based on the information indicating the speed acquired by the GNSS receiver **113**.

(29) The movement distance acquisition part **134** acquires information (hereinafter, referred to as

movement distance information) showing a movement distance of the motorcycle **100** from the distance detector **115**. The “movement distance” may be a total value of a traveling distance from a time when the motorcycle **100** turns on an ignition switch (for example, a time when the engine **118** is started with the accelerator grip **116**), or may be a traveling distance from a timing when the previous movement distance was acquired.

(30) The engine controller **135** controls the engine **118** on the basis of operation contents received via the accelerator grip **116**. The brake controller **136** controls the brake device **119** on the basis of the operation contents received via the brake lever **117**.

(31) The transmission controller **137** continuously transmits position information of the motorcycle **100** generated by the position specification part **132** to the information management server **300** using the communication part **111** when the ignition switch of the motorcycle **100** is turned on. Here, the transmission controller **137** may transmit the movement speed information acquired by the movement speed acquisition part **133** or the movement distance information acquired by the movement distance acquisition part **134** to the information management server **300** together with the position information. When the ignition switch is turned off, the transmission controller **137** stops transmission of the position information or the like. Hereinafter, the information transmitted by the transmission controller **137** may be referred to as vehicle information.

(32) The display controller **138** displays predetermined illustration or character information on the display device **120**. For example, the display controller **138** receives the information generated on the basis of the transmitted position information (for example, a traffic jam map showing traffic conditions, a request of requesting delivery to a delivery destination near a host vehicle, or the like) from the information management server **300** and displays the received information on the display device **120**.

(33) The storage **140** is realized by, for example, a random access memory (RAM), a read only memory (ROM), a hard disk drive (HDD), or the like. The storage **140** stores programs executed by the processor, and also stores log information **141** and the like. The log information **141** stores position information in which the information indicating measurement date and time is associated with the position acquired by the position specification part **132**. For example, the position specification part **132** periodically acquires position information at predetermined times (for example, several seconds, several microseconds) and stores the position information in the log information **141**. In the log information **141**, the position information may be automatically deleted when a predetermined time has elapsed.

(34) <User Terminal Device>

(35) FIG. 3 is a functional block diagram of the user terminal device **200**. The user terminal device **200** includes, for example, a communication part **210**, an input part **220**, a display part **230**, a short-distance wireless communication part **240**, a storage **250**, a GNSS receiver **260**, a sensor **270**, and an application execution part **280**.

(36) The communication part **210** includes, for example, a communication interface such as an NIC or the like. The communication part **210** performs communication with the information management server **300** via a communication network such as the Internet or the like under control by the application execution part **280**.

(37) The input part **220** includes, for example, some or all of a touch panel TP formed integrally with the display part **230**, various keys, buttons, a dial switch, a mouse, and the like. The display part **230** is, for example, a liquid crystal display (LCD), an organic electro luminescence (EL) display device, or the like. The short-distance wireless communication part **240** has, for example, an antenna and transmission/reception device, or the like, which is a wireless module used for Bluetooth (registered trademark) or the like.

(38) The storage **250** is realized by, for example, a random access memory (RAM), a read only memory (ROM), a flash memory, an SD card, a register, or the like. A position information report application **251** is stored in the storage **250**. The position information report application **251** is a

program that displays an interface configured to use the user terminal device **200** as a moving body notifying the position of the motorcycle **100** on the display part **230**, and executes processing in the user terminal device **200** based on the information input via an interface.

(39) The GNSS receiver **260** receives a signal from a GNSS satellite. The sensor **270** includes an acceleration sensor or the like, and detects information for measuring a movement speed, a movement distance, or the like of the user terminal device **200** and outputs the detected information to the application execution part **280**.

(40) The application execution part **280** is realized by executing the position information report application (program) **251** stored in the storage **250** using a processor such as a CPU or the like. The position information report application **251** may be downloaded from another device via, for example, the network NW, or may be previously installed in the user terminal device **200**.

(41) The application execution part **280** has the same functions as the communication controller **131**, the position specification part **132**, the movement speed acquisition part **133**, the movement distance acquisition part **134**, and the transmission controller **137** of the motorcycle **100**. For example, the application execution part **280** generates position information indicating the position of the user terminal device **200** specified by the position specification part **132** from the time when the application was turned on, and starts continuous transmission of the position information to the information management server **300** using the communication part **210**. Here, the application execution part **280** may acquire movement speed information indicating a movement speed of the user terminal device **200** or movement distance information indicating a movement distance of the user terminal device **200**, and transmit the acquired information to the information management server **300** together with the position information. When the application is turned off, the application execution part **280** stops transmission of the position information or the like.

(42) In addition, when the position information, movement speed information, movement distance information, and the like, are received from the motorcycle **100** through near field communication, the application execution part **280** may continuously transmit these pieces of received information to the information management server **300** via the network NW.

(43) <Information Management Server>

(44) FIG. **4** is a functional block diagram of the information management server **300**. The information management server **300** includes, for example, a communication part **310**, an input part **320**, an output part **330**, a storage **340**, and a processing part **350**.

(45) The communication part **310** includes, for example, a communication interface such as an NIC or the like. The communication part **310** performs communication with the motorcycle **100** or the user terminal device **200** via a communication network such as the Internet or the like under control by the processing part **350**.

(46) The input part **320** includes, for example, some or all of various keys, buttons, a dial switch, a mouse, and the like. The output part **330** includes, for example, an LCD, an organic EL display device, a speaker, a projector, or the like. The storage **340** is realized by, for example, a RAM, a ROM, an HDD, or the like. The storage **340** stores a program executed by the processor, as well as a temporary DB **341**, a position information DB **342**, a setting information DB **343**, a provision information DB **344**, and the like. Details of each piece of information will be described below.

(47) The processing part **350** includes, for example, a data management part **351**, an output information generating part **352**, an output controller **353**, a movement distance calculation part **354**, an elapsed time calculation part **355**, a movement speed estimation part **356**, and a provision information generating part **357**. For example, some or all of these functional units are realized by executing a program (software) stored in a storage thereof using a processor such as a CPU or the like. In addition, some or all of functions of these components may be realized by hardware (circuit unit: including circuitry) such as an LSI, an ASIC, an FPGA, or the like, or may be realized by cooperation of software and hardware. The program may be previously stored in a storage device such as an HDD, a flash memory, or the like, stored in a detachable storage medium such as a

DVD, a CD-ROM, or the like, or installed by mounting a storage medium in a drive device.

(48) The data management part **351** stores the information received from the motorcycle **100** or the user terminal device **200** via the communication part **310** in the storage **340** as a part of the temporary DB **341**. The temporary DB **341** is a database in which information received from the motorcycle **100** or the user terminal device **200** is saved.

(49) FIG. 5 is a view showing an example of contents of the temporary DB **341** and the position information DB **342**. The temporary DB **341** is, for example, information in which a vehicle ID, position information, a movement distance, and movement speed are associated with measurement date and time. The measurement date and time are information indicating date and time when the position of the motorcycle **100** is measured. The vehicle ID is information for identifying each of the motorcycles **100**. The movement distance and the movement speed are information acquired by the motorcycle **100**, and stored in the temporary DB **341** when transmitted from the motorcycle **100**.

(50) The output information generating part **352** generates information (hereinafter, referred to as output information) to be output to the output part **330** on the basis of the temporary DB **341**. For example, the output information generating part **352** generates output information for outputting the position information measured at a first timing to the output part **330** at a second timing slower than the first timing.

(51) The second timing is a timing when a predetermined parameter indicating a change from the state at the first timing has satisfied a predetermined condition. For example, a distance, a time, a speed, and the like, are included in the predetermined parameter. The second timing includes, for example, a timing when a movement distance (hereinafter, referred to as a movement distance M) from a position where the motorcycle **100** is at the first timing is a threshold Th_m or more, a timing when an elapsed time (hereinafter, referred to as an elapsed time T) from a time where the motorcycle **100** was at the first timing becomes a threshold Th_t or more, and the like, and details thereof will be described below.

(52) The movement distance M may be, for example, information indicating a movement distance received from the motorcycle **100** as the vehicle information, or information indicating a movement distance calculated by the movement distance calculation part **354**, which will be described below. The elapsed time T is, for example, information indicating an elapsed time calculated by the elapsed time calculation part **355**, which will be described below.

(53) In the embodiment, the output information generating part **352** saves a copy of information satisfying a condition at the second timing, among the information stored in the temporary DB **341**, in position information DB. That is, the position information DB is an example of the output information.

(54) As shown in FIG. 5, the position information DB **342** is, for example, information in which the vehicle ID and the position information are associated with the measurement date and time.

(55) The output controller **353** outputs information indicating a position of the motorcycle **100** measured at the first timing from the output part **330** after the second timing on the basis of the output information generated by the output information generating part **352**. For example, the output controller **353** outputs a map image, in which the latest position of the motorcycle **100** is displayed on a map, from the output part **330** on the basis of the position information DB **342**. Further, when the next latest position of the motorcycle **100** is added to the position information DB **342**, the output controller **353** updates the map image on the basis of the information indicating the next latest position of the motorcycle **100**.

(56) By doing this, the position measured at the first timing can be continuously output to the output part **330** after the second timing. Accordingly, since the current position of the motorcycle **100** cannot be output to the output part **330**, anonymity can be continuously secured. In addition, by setting the timing that notifies the position of the motorcycle **100** to the second timing that can be set in the condition using the threshold described above, it is possible to notify the approximate

current position.

(57) The movement distance calculation part **354** calculates a distance from a position P1 of the motorcycle **100** to a position P2 of the motorcycle **100** as the movement distance M with reference to the temporary DB **341**. The position P1 of the motorcycle **100** is the position shown by position information of an object to be determined whether or not the second timing has been reached, for example, the position information determined immediately before the second timing. The date and time when the position P1 of the motorcycle **100** is measured are a first timing.

(58) The elapsed time calculation part **355** calculates a time from date and time D1 when the position P1 of the motorcycle **100** is measured to date and time D2 when the position P2 of the motorcycle **100** is measured as the elapsed time T with reference to the temporary DB **341**.

(59) The movement speed estimation part **356** estimates a movement speed S of the motorcycle **100** by dividing the movement distance M, which is calculated by the movement distance calculation part **354**, by the elapsed time T which is calculated by the elapsed time calculation part **355**. Not limited to this, the movement speed estimation part **356** may estimate the movement speed S based on the information indicating the speed of the moving body acquired by the GNSS receiver.

(60) The provision information generating part **357** generates provision information to be provided to the motorcycle **100** or the user terminal device **200** on the basis of the position information DB **342**, stores the provision information in the provision information DB **344** and transmits the provision information read from the provision information DB **344** to the motorcycle **100** or the user terminal device **200** by using the communication part **310**. In this way, by setting the information referenced when the provision information is generated as the position information DB **342**, even when the provision information is generated, anonymity of the motorcycle **100** or the user terminal device **200** can be secured.

(61) Next, an example of the first timing and the second timing will be described. FIG. **6** is a view for describing an example of a second timing determination method (Part 1). The second timing determination method (Part 1) is an example of determination at the second timing when any one of a condition 1 of a distance and a condition 2 of time is satisfied.

(62) In the condition 1, the movement distance M from the position where the motorcycle **100** is at the first timing is the threshold Th_m or more, and the threshold Th_m is, for example, several hundred meters. In the condition 2, the elapsed time T from the time of the first timing is the threshold Th_t or more, and the threshold Th_t is, for example, several minutes. By doing this, the information management server **300** can output the information indicating the position of the motorcycle **100** measured at the first timing to the output part **330** at, not immediately after the first timing, but at the second timing when the condition 1 or the condition 2 is satisfied.

(63) FIG. **7** is a view for describing an example of a second timing determination method (Part 2). The second timing determination method (Part 2) is an example of determination at the second timing when the condition 1 of the distance is satisfied and a condition 3 of the speed is not satisfied and determination at the second timing when all the condition 1 of the distance, the condition 2 of the time and the condition 3 of the speed are satisfied.

(64) In the condition 3, the movement speed S of the motorcycle **100** at the first timing is higher than the threshold Th_s, and the threshold Th_s is, for example, an average speed per hour of about 30 km. By doing this, even though the movement distance M is equal to or greater than the threshold Th_m when the motorcycle **100** is traveling on an expressway or the like, if enough time has not passed after the first timing, it is not determined as the second timing, and it can be determined as the second timing after enough time has passed.

(65) Here, while the movement speed S is a speed of a motorcycle at a first timing detected by a sensor of the motorcycle, there is no limitation thereto. For example, the speed may be an average speed between the position P1 of the motorcycle **100** at the first timing and a position P0 of the motorcycle **100** at the previous measurement timing. Further, the information indicating the

condition 1 to the condition 3 is stored in the setting information DB **343**.

(66) <Sequence Diagram>

(67) FIG. **8** is a sequence diagram showing an example of processing in the position information output system **1**. As described above, an example of notifying a manager of information acquired by the motorcycle **100** will be described. First, the motorcycle **100** generates vehicle information including information indicating a position at the first timing (step **S1**), and transmits the vehicle information to the information management server **300** via the network NW (step **S2**). As described above, the vehicle information includes position information, movement speed information, movement distance information, and the like.

(68) Then, the information management server **300** stores the received vehicle information in the temporary DB **341** (step **S3**). Next, the information management server **300** determines whether the latest vehicle information saved in the temporary DB **341** satisfies a predetermined condition (step **S4**), and copies position information and saves the position information in the position information DB **342** when the predetermined condition is satisfied (step **S5**). Then, the information management server **300** outputs the information indicating the position of the motorcycle **100** from the output part **330** with reference to the position information DB **342** (step **S6**).

(69) <Flowchart>

(70) FIG. **9** is a flowchart showing an example of processing of the information management server **300** by the second timing determination method (Part 1). The data management part **351** determines whether the vehicle information is received from the motorcycle **100** (step **S101**), and saves the received vehicle information in the temporary DB **341** when the vehicle information is received (step **S102**). Then, the output information generating part **352** determines whether the condition 1 (the movement distance M is the threshold Th_m or more) or the condition 2 (the elapsed time T is the threshold Th_t or more) is satisfied (step **S103**). When the condition 1 or the condition 2 is satisfied, the output information generating part **352** copies the position information in which either the condition 1 or the condition 2 is satisfied, and saves the position information in the position information DB **342** (step **S104**). Next, the output controller **353** outputs the information indicating the position of the motorcycle **100** from the output part **330** with reference to the position information DB **342** (step **S105**).

(71) In this way, by notifying the position of the motorcycle **100** when the predetermined time or the predetermined distance has passed, real time position information can be concealed and the privacy of the motorcycle **100** and the occupant therein can be protected. In addition, since the notified position information is the information specified by the GNSS receiver **113** of the motorcycle **100**, it is possible to notify an accurate position that the motorcycle **100** has existed little bit before. Further, if it is not possible to notify the accurate position, in urban areas with complicated roads, etc., false information such as traveling on a different road on the map may be notified. According to the embodiment, it is possible to avoid such a situation.

(72) FIG. **10** is a flowchart showing an example of processing of the information management server **300** by the second timing determination method (Part 1). The data management part **351** determines whether the vehicle information is received from the motorcycle **100** (step **S201**), and saves the received vehicle information in the temporary DB **341** when the vehicle information is received (step **S202**). Then, the output information generating part **352** determines whether the condition 1 (the movement distance M of the motorcycle **100** is the threshold Th_m or more) is satisfied (step **S203**). When the condition 1 is satisfied, the output information generating part **352** determines whether the condition 3 (the movement speed S of the motorcycle **100** is higher than the threshold Th_s) is satisfied (step **S204**).

(73) When the condition 3 is not satisfied, the output information generating part **352** copies the position information that the condition 1 is satisfied and the condition 3 is not satisfied, and saves the position information in the position information DB **342** (step **S205**). Then, the output controller **353** outputs the information indicating the position of the motorcycle **100** from the

output part **330** with reference to the position information DB **342** (step **S206**).

(74) Meanwhile, when the condition 3 is satisfied in step **S204**, the output information generating part **352** determines whether the condition 2 (the elapsed time T is the threshold Th_t or more) is satisfied (step **S207**). When the condition 2 is not satisfied, the output information generating part **352** returns to step **S204** and repeats the processing. Meanwhile, in step **S207**, when the condition 2 is satisfied, the processing is shifted to processing **205**. Further, the condition 2 in step **S207** may have a shorter duration of the threshold Th_t than the condition 2 in step **S103**.

(75) Further, during high speed traveling, if the second timing is the timing when the movement distance is the threshold Th_m or more, the current position may be notified almost at real time. Here, as described above, at the high speed, by setting the timing when the elapsed time T from the time of the first timing is equal to or greater than the threshold Th_t as the second timing, the anonymity of the motorcycle **100** and the occupant therein can be maintained.

(76) Further, the processing of the information management server **300** by the second timing determination method (Part 2) is not limited thereto. For example, the output information generating part **352** may determine whether the condition 1 (the movement distance M of the motorcycle **100** is the threshold Th_m or more) is satisfied when the condition 3 (the movement speed S of the motorcycle **100** is higher than the threshold Th_s) is not satisfied, and may execute the processing of step **S205** when the condition 1 is satisfied. In addition, the output information generating part **352** may determine whether the condition 2 (the elapsed time T is the threshold Th_t or more) is satisfied when the condition 3 (the movement speed S of the motorcycle **100** is higher than the threshold Th_s) is satisfied, and may execute the processing of step **S205** when the condition 2 is satisfied.

(77) According to the above-mentioned first embodiment, a computer acquires position information, which is information showing a position of the moving body, indicating a position which is measured by a position measurement device (**113**, **260**) mounted on a moving body at a first timing via a network from the moving body including at least one of a vehicle (**100**) and a terminal device (**200**) owned by an occupant of the vehicle, and outputs information, which shows that the moving body is present at a position indicated by the position information, from an output part (**330**) after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition, thereby securing anonymity of a current position of the moving body.

(78) In addition, since the second timing is set as a timing when the movement distance M from the position of the motorcycle **100** at the first timing becomes equal to or greater than the threshold Th_m , or a timing when the elapsed time T from the time of the first timing of the motorcycle **100** becomes equal to or greater than the threshold Th_t , it is possible to set a predetermined distance not too close or too far from the current position, and it is possible to notify the approximate current position while protecting the privacy of the motorcycle **100** and the occupant therein.

Second Embodiment

(79) Hereinafter, a second embodiment will be described. In the first embodiment, the example in which the second timing determination processing is executed by the information management server **300** has been described. In the second embodiment, an example in which the second timing determination processing is executed by a motorcycle **100A** will be described. Hereinafter, description will be performed while focusing on the differences from the first embodiment.

(80) FIG. **11** is a functional block diagram of a motorcycle **100A** of the second embodiment. Here, differences from the motorcycle **100** of the first embodiment will be described. The motorcycle **100A** further stores a position information report application **142**, a temporary DB **143**, a position information DB **144**, and a setting information DB **145** in the storage **140**. These DBs are the same as the temporary DB **341**, the position information DB **342**, and the setting information DB **343** of the information management server **300**. Further, the position information report application **142** is a program that causes the motorcycle **100** to execute second timing determination processing by the

information management server **300**.

(81) The controller **130** further includes an application execution part **139**. The application execution part **139** is, for example, realized by executing a position information report application (program) **142** stored in the storage **140** using a processor such as a CPU or the like. For example, the application execution part **139** executes the second timing determination processing and transmits the position information that the condition of the second timing is satisfied to the information management server **300**. The information management server **300** saves the received position information in the position information DB **342**, and outputs the received position information from the output part **330** immediately.

Third Embodiment

(82) Hereinafter, a third embodiment will be described. In the first embodiment, the example in which the second timing determination processing is executed by the information management server **300** has been described. In the third embodiment, an example in which the second timing determination processing is executed by a user terminal device **200A** will be described. Hereinafter, description will be performed while focusing on differences from the first embodiment.

(83) FIG. **12** is a functional block diagram of the user terminal device **200A** of the third embodiment. Here, differences from the user terminal device **200** of the first embodiment will be described. The user terminal device **200A** further stores a temporary DB **252**, a position information DB **253**, and a setting information DB **254** in the storage **250**. These DBs are the same as the temporary DB **341**, the position information DB **342**, and the setting information DB **343** of the information management server **300**.

(84) The application execution part **280** includes the same function as the processing part **350** of the information management server **300**. For example, the application execution part **280** executes the second timing determination processing, and transmits the position information in which the condition of the second timing is satisfied to the information management server **300**. The information management server **300** saves the received position information in the position information DB **342**, and outputs the received position information from the output part **330** immediately.

(85) The above-mentioned embodiment can be expressed as follows.

(86) A position information output method comprising: a storage device; and a hardware processor configured to execute a program stored in the storage device, wherein the hardware processor executes the program to: acquire position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device mounted on a moving body at a first timing via a network from the moving body including at least one of a vehicle and a terminal device owned by an occupant of the vehicle; and outputs information, which indicates that the moving body is present at a position indicated by the position information, from an output part after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition.

(87) Hereinabove, while the mode for carrying out the present invention has been described using the embodiments, the present invention is by no means limited to these embodiments, and various modifications and replacements may be made without departing from the scope of the present invention.

(88) For example, a part of the position information notification processing by the information management server **300** in the first embodiment is executed by the moving body (the motorcycle **100** or the user terminal device **200**), and in cooperation with the moving body and the information management server **300**, position information notification processing may be executed. For example, in the second timing determination method (Part 1), the position information may be transmitted to the information management server **300** when it is determined that the position information satisfies the condition 1 or the condition 2 on the side of the moving body, and the received position information may be treated as output information and output from the output part

330 on the side of the information management server **300**. In the second timing determination method (Part 2), the position information may be transmitted to the information management server **300** when it is determined that the condition 1 is satisfied on the side of the moving body, whether the received position information satisfies the condition 3 may be determined on the side of the information management server **300**, and the position information received when the condition 3 is not satisfied may be treated as the output information and may be output from the output part **330**. Meanwhile, when the received position information satisfies the condition 3, whether the position information satisfies the condition 2 may be determined on the side of the information management server **300**, and the position information received when the condition 2 is satisfied may be treated as the output information and may be output from the output part **330**.

(89) Further, the present invention is not limited to the above embodiments, and for example, the present system is not limited to motorcycles but can be widely applied to saddle riding vehicles. The saddle riding vehicle includes all vehicles in which the driver straddles the vehicle body, not only motorcycles (including motorized bicycles and scooter type vehicles), but also three-wheeled vehicles (not only a vehicle with one front wheel and two rear wheels, but also a vehicle with two front wheels and one rear wheel) and also include a vehicle with one rear wheel) or a vehicle with four wheels. In addition, it also includes a vehicle whose prime mover is an electric motor. In addition, it may be applied to an automobile having a passenger compartment. In addition, it may be applied to various devices that require communication other than the vehicles. For example, it may be applied to devices such as storage boxes and bags with communication functions. In addition, this system is not limited to saddle riding vehicles, but can be applied to vehicles with four or more wheels, such as sedans, that can accommodate multiple people.

REFERENCE SIGNS LIST

(90) **1** Position information output system **100** Motorcycle **200** User terminal device **300**
Information management server **310** Communication part **320** Input part **330** Output part **340**
storage **350** Processing part **351** Data management part **352** Output information generating part **353**
Output controller **354** Movement distance calculation part **355** Elapsed time calculation part **356**
Movement speed estimation part **357** Provision information generating part

Claims

1. A position information output method of causing a computer to: acquire position information, which is information indicating a position of a moving body, indicating a position which is measured by a position measurement device mounted on the moving body at a first timing via a network from the moving body including at least one of a vehicle and a terminal device owned by an occupant of the vehicle; and output the position information, which is measured at the first timing without performing calculation using the position information, from an output part after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition, wherein the computer acquires a movement speed of the moving body on the basis of information detected by a detector mounted on the moving body or the position information, in a case the movement speed is smaller than a predetermined value, sets the predetermined parameter as a distance and determines that the predetermined condition is satisfied when a movement distance from a position of the vehicle at the first timing is equal to or greater than the predetermined value, and in a case the movement speed is greater than the predetermined value, sets the predetermined parameter as a time and determines that the predetermined condition is satisfied when an elapsed time from a time in which the vehicle was at the first timing is equal to or greater than the predetermined value.

2. The position information output method according to claim 1, wherein the computer acquires an average value in a predetermined section as the movement speed of the moving body.

3. A position information output system comprising a moving body including at least one of a

vehicle and a terminal device owned by an occupant of the vehicle, and an information management server configured to communicate with the moving body via a network, wherein the moving body includes a communication part configured to transmit position information, which is information indicating a position of the moving body, indicating a position which is measured by a position measurement device mounted on the moving body at a first timing to the information management server via the network, and the information management server includes an output controller configured to output information, which indicates that the moving body is present at a position indicated by the position information, from an output part after a second timing which is when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition, wherein the information management server acquires a movement speed of the moving body on the basis of information detected by a detector mounted on the moving body or the position information, in a case the movement speed is smaller than a predetermined value, sets the predetermined parameter as a distance and determines that the predetermined condition is satisfied when a movement distance from a position of the vehicle at the first timing is equal to or greater than the predetermined value, and in a case the movement speed is greater than the predetermined value, sets the predetermined parameter as a time and determines that the predetermined condition is satisfied when an elapsed time from a time in which the vehicle was at the first timing is equal to or greater than the predetermined value.

4. A non-transitory computer-readable storage medium comprising a program that causes a computer to: acquire position information, which is information indicating a position of a moving body, indicating a position which is measured by a position measurement device mounted on the moving body at a first timing via a network from the moving body including at least one of a vehicle and a terminal device owned by an occupant of the vehicle; and output the position information, which is measured at the first timing without performing calculation using the position information, from an output part after a second timing when a predetermined parameter indicating a change from a state at the first timing has satisfied a predetermined condition, wherein the computer acquires a movement speed of the moving body on the basis of information detected by a detector mounted on the moving body or the position information, in a case the movement speed is smaller than a predetermined value, sets the predetermined parameter as a distance and determines that the predetermined condition is satisfied when a movement distance from a position of the vehicle at the first timing is equal to or greater than the predetermined value, and in a case the movement speed is greater than the predetermined value, sets the predetermined parameter as a time and determines that the predetermined condition is satisfied when an elapsed time from a time in which the vehicle was at the first timing is equal to or greater than the predetermined value.
