

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12408051             |
| Kind Code            | B2                   |
| Date of Patent       | September 02, 2025   |
| Inventor(s)          | Aktas; Tugcan et al. |

---

### Receiver side sensing for sidelink inter-UE-coordination

---

#### Abstract

Apparatus, methods, and computer-readable media for facilitating a SL communication for mode 2 resource allocation are disclosed herein. An example method includes performing sensing on one or more SL resources to identify a first set of available resources. The example method further includes adjusting a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The example method further includes transmitting a sidelink message indicating a second set of available resources based on the second measurement threshold.

---

**Inventors:** Aktas; Tugcan (La Jolla, CA), Hosseini; Seyedkianoush (San Diego, CA), Nguyen; Tien Viet (Bridgewater, NJ), Sarkis; Gabi (San Diego, CA), Dutta; Sourjya (San Diego, CA)

**Applicant:** QUALCOMM Incorporated (San Diego, CA)

**Family ID:** 83508806

**Assignee:** QUALCOMM Incorporated (San Diego, CA)

**Appl. No.:** 17/450433

**Filed:** October 08, 2021

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20230114379 A1   | Apr. 13, 2023    |

---

#### Publication Classification

**Int. Cl.:** H04W24/08 (20090101); H04W24/02 (20090101); H04W72/1263 (20230101); H04W72/25 (20230101); H04W72/40 (20230101); H04W74/00 (20090101); H04W74/0808 (20240101); H04W92/18 (20090101)

## U.S. Cl.:

CPC     **H04W24/08** (20130101); **H04W72/1263** (20130101); **H04W74/0808** (20130101);

## Field of Classification Search

**CPC:**     H04W (24/08); H04W (72/1263); H04W (74/0808)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC          |
|--------------|-------------|---------------|----------|--------------|
| 10833932     | 12/2019     | Phillips      | N/A      | H04L 45/16   |
| 2015/0249998 | 12/2014     | Long          | 370/329  | H04L 5/001   |
| 2020/0154440 | 12/2019     | Gholmieh      | N/A      | H04W 28/0236 |
| 2020/0252910 | 12/2019     | Wu            | N/A      | H04B 17/318  |
| 2020/0267523 | 12/2019     | Tang          | N/A      | H04L 5/0064  |
| 2021/0051525 | 12/2020     | Cao           | N/A      | H04W 28/26   |
| 2021/0160817 | 12/2020     | Khoryaev      | N/A      | H04W 72/542  |
| 2022/0232585 | 12/2021     | Park          | N/A      | H04W 72/1263 |
| 2023/0123147 | 12/2022     | Hwang         | 370/329  | H04W 72/40   |
| 2023/0156669 | 12/2022     | Zhou          | 370/329  | H04W 72/02   |
| 2023/0262685 | 12/2022     | Panzner       | 370/329  | H04W 72/1263 |
| 2023/0300858 | 12/2022     | Zhou          | 370/329  | H04W 72/25   |
| 2023/0319878 | 12/2022     | Hui           | 370/329  | H04L 1/1854  |
| 2023/0389002 | 12/2022     | Hui           | N/A      | H04L 5/0064  |

### FOREIGN PATENT DOCUMENTS

| Patent No. | Application Date | Country | CPC |
|------------|------------------|---------|-----|
| 2020153998 | 12/2019          | WO      | N/A |
| 2021148046 | 12/2020          | WO      | N/A |

### OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2022/043236—ISA/EP—Dec. 15, 2022. cited by applicant

3GPP TS 38.214: “3rd Generation Partnership Project, Technical Specification Group Radio Access Network, NR, Physical Layer Procedures for Data (Release 16)”, 3GPP TS 38.214, V16.7.0, Sep. 2021, 6 Pages, Section 8.1.4. cited by applicant

---

*Primary Examiner:* Kim; Harry H

*Attorney, Agent or Firm:* Procopio, Cory, Hargreaves & Savitch LLP/QUALCOMM Incorporated

---

## Background/Summary

### INTRODUCTION

(1) The present disclosure relates generally to communication systems, and more particularly, to wireless communication utilizing sidelink (SL) communication between user equipments (UEs).

(2) Wireless communication systems are widely deployed to provide various telecommunication services such as telephony, video, data, messaging, and broadcasts. Typical wireless communication systems may employ multiple-access technologies capable of supporting communication with multiple users by sharing available system resources. Examples of such multiple-access technologies include code division multiple access (CDMA) systems, time division multiple access (TDMA) systems, frequency division multiple access (FDMA) systems, orthogonal frequency division multiple access (OFDMA) systems, single-carrier frequency division multiple access (SC-FDMA) systems, and time division synchronous code division multiple access (TD-SCDMA) systems.

(3) These multiple access technologies have been adopted in various telecommunication standards to provide a common protocol that enables different wireless devices to communicate on a municipal, national, regional, and even global level. An example telecommunication standard is 5G New Radio (NR). 5G NR is part of a continuous mobile broadband evolution promulgated by Third Generation Partnership Project (3GPP) to meet new requirements associated with latency, reliability, security, scalability (e.g., with Internet of Things (IOT)), and other requirements. 5G NR includes services associated with enhanced mobile broadband (eMBB), massive machine type communications (mMTC), and ultra-reliable low latency communications (URLLC). Some aspects of 5G NR may be based on the 4G Long Term Evolution (LTE) standard. Some aspects of wireless communication may include direct communication between devices based on sidelink. There exists a need for further improvements in sidelink technology. These improvements may also be applicable to other multi-access technologies and the telecommunication standards that employ these technologies.

#### BRIEF SUMMARY

(4) The following presents a simplified summary of one or more aspects in order to provide a basic understanding of such aspects. This summary is not an extensive overview of all contemplated aspects, and is intended to neither identify key or critical elements of all aspects nor delineate the scope of any or all aspects. Its sole purpose is to present some concepts of one or more aspects in a simplified form as a prelude to the more detailed description that is presented later.

(5) In an aspect of the disclosure, a method of wireless communication at a first UE is provided. The method may include performing sensing on one or more SL resources to identify a first set of available resources. The example method may also include adjusting a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The example method may also include transmitting a sidelink message indicating a second set of available resources based on the second measurement threshold.

(6) In another aspect of the disclosure, an apparatus for wireless communication is provided. The apparatus may be a UE that includes a memory and at least one processor coupled to the memory, the memory and the at least one processor configured to perform sensing on one or more SL resources to identify a first set of available resources. The memory and the at least one processor may also be configured to adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The memory and the at least one processor may also be configured to transmit a sidelink message indicating a second set of available resources based on the second measurement threshold.

(7) In another aspect of the disclosure, an apparatus for wireless communication at a wireless device is provided. The apparatus may include means for performing sensing on one or more SL resources to identify a first set of available resources. The example apparatus may also include means for adjusting a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The example apparatus may also include means for transmitting a sidelink message indicating a second set of available resources based on the second measurement threshold.

(8) In another aspect of the disclosure, a non-transitory computer-readable storage medium storing

computer executable code for wireless communication at a wireless device is provided. The code, when executed, may cause a processor to perform sensing on one or more SL resources to identify a first set of available resources. The example code, when executed, may also cause the processor to adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The example code, when executed, may also cause the processor to transmit a sidelink message indicating a second set of available resources based on the second measurement threshold.

(9) In an aspect of the disclosure, a method of wireless communication at a first UE is provided. The method may include performing a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. The example method may also include transmitting a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(10) In another aspect of the disclosure, an apparatus for wireless communication is provided. The apparatus may be a first UE that includes a memory and at least one processor coupled to the memory, the memory and the at least one processor configured to perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. The memory and the at least one processor may also be configured to transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(11) In another aspect of the disclosure, an apparatus for wireless communication at a first UE is provided. The apparatus may include means for performing a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. The example apparatus may also include means for transmitting a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(12) In another aspect of the disclosure, a non-transitory computer-readable storage medium storing computer executable code for wireless communication at a first UE is provided. The code, when executed, may cause a processor to perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. The example code, when executed, may also cause the processor to transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(13) To the accomplishment of the foregoing and related ends, the one or more aspects include the features hereinafter fully described and particularly pointed out in the claims. The following description and the annexed drawings set forth in detail certain illustrative features of the one or more aspects. These features are indicative, however, of but a few of the various ways in which the principles of various aspects may be employed, and this description is intended to include all such aspects and their equivalents.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network.

(2) FIG. 2 illustrates example aspects of a sidelink slot structure.

(3) FIG. 3 is a diagram illustrating an example of a first device and a second device involved in wireless communication based, e.g., on sidelink.

(4) FIG. 4 illustrates example aspects of sidelink communication between devices, in accordance with aspects presented herein.

(5) FIG. 5 illustrates examples of resource reservation for sidelink communication.

(6) FIG. 6 is a diagram illustrating a timing diagram for a UE employing a sensing mechanism.

(7) FIGS. 7A and 7B are diagrams illustrating inter UE coordination between UEs, in accordance with the teachings disclosed herein.

(8) FIG. 8 is a diagram illustrating communication flow between UEs, in accordance with the teachings disclosed herein.

(9) FIG. 9 is a flowchart of a method of wireless communication at a first UE, in accordance with the teachings disclosed herein.

(10) FIG. 10 is a flowchart of a method of wireless communication at a first UE, in accordance with the teachings disclosed herein.

(11) FIG. 11 is a flowchart of a method of wireless communication at a first UE, in accordance with the teachings disclosed herein.

(12) FIG. 12 is a flowchart of a method of wireless communication at a first UE, in accordance with the teachings disclosed herein.

(13) FIG. 13 is a diagram illustrating an example of a hardware implementation for an example apparatus, in accordance with the teachings disclosed herein.

#### DETAILED DESCRIPTION

(14) Sidelink communication enables a first UE to communicate with another UE directly. Sidelink communication may be based on different types or modes of resource allocation mechanisms. In a first resource allocation mode (which may be referred to herein as “Mode 1”), centralized resource allocation may be provided by a network entity. In a second resource allocation mode (which may be referred to herein as “Mode 2”), distributed resource allocation may be provided. In Mode 2 resource allocation, each UE may autonomously determine resources to use for sidelink transmission. In order to coordinate the selection of sidelink resources by individual UEs, each UE may use a sensing technique to monitor for resource reservations by other sidelink UEs and may select resources for sidelink transmissions from unreserved resources. Devices communicating based on sidelink may determine one or more radio resources in the time and frequency domain that are reserved, or used, by other devices in order to avoid a selection of colliding (e.g., overlapping in time and/or frequency) transmission resources.

(15) Thus, in the second mode (e.g., Mode 2), individual UEs may autonomously select resources for sidelink transmission, e.g., without a central entity such as a base station indicating the resources for the device. The UE may receive various types of information that may be used for sidelink resource selection. To reduce or avoid resource collisions under such instances, and to improve sidelink communication among UEs, the UEs may coordinate among themselves by generating and sharing inter-UE coordination information with other UEs. As an example, a first UE may generate inter-UE coordination information indicating preferred resources, non-preferred resources, or resource conflict information. A second UE may receive inter-UE coordination information from the first UE and may accordingly avoid using the non-preferred resources when communicating with the first UE. In some aspects, the second UE may include an inter-UE coordination information associated with the second UE based on reservation information (e.g., information indicating time and frequency resources reserved for a particular sidelink transmission) or inter-UE coordination information received from the first UE (or other UEs) when transmitting its own resource reservation.

(16) As an example, a receiving UE may perform sensing, then inform the transmitting UE (along with other UEs) about the resources that are available for transmission based on the sensing result. For example, the receiving UE may be a smartphone with a higher processing power and higher battery capacity than the transmitting UE, which may be a smartwatch with limited battery capacity and limited processing power. In such an example, it may be more efficient to have the higher processing power receiving UE with higher battery capacity perform the sensing for the transmitting UE.

(17) In some circumstances, based on the sensing, the receiving UE may identify a first set of available resources that may be smaller than a threshold amount of available resources (e.g., by

comparing a size of the available resources with an availability threshold) for a transmission by the transmitting UE. Aspects provided herein enable a receiving UE to adjust one or more parameters, such as a measurement threshold, when identifying a set of available resources that may be suitable for a transmission by the transmitting UE. By enabling the receiving UE to adjust the parameters for identifying available resources, e.g., by adjusting a measurement threshold, the receiving UE may indicate a more consistent amount of available resources for the transmitting UE. The added consistency in the amount of available resources reported by the receiving UE may provide the transmitting UE with information of a set of available resources that may be more suitable for the transmission.

(18) As used herein, the term “sensing” may refer to a procedure where a UE performs one or more measurements (which may be referred to as “sensing measurements”) to identify resources that are available for sidelink transmissions for the UE or another UE. By way of example, sensing measurements may include reference signal received power (RSRP) measurements, reference signal received quality (RSRQ) measurements, signal to interference ratio (SIR) measurements, or the like. A UE may compare sensing measurements associated with a resource with a threshold (which may be referred to as “measurement threshold”). If the sensing measurement associated with the resource is below the measurement threshold, the UE may determine that the resource is available. In another example, if the sensing measurement associated with the resource is above the measurement threshold, the UE may determine that the resource is available. As used herein, the term “inter-UE coordination information” may refer to information exchanged between sidelink UEs to facilitate sidelink communications under resource allocation Mode 2 where each UE may autonomously determine resources to use for sidelink transmission.

(19) The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known structures and components are shown in block diagram form in order to avoid obscuring such concepts.

(20) Several aspects of telecommunication systems will now be presented with reference to various apparatus and methods. These apparatus and methods will be described in the following detailed description and illustrated in the accompanying drawings by various blocks, components, circuits, processes, algorithms, etc. (collectively referred to as “elements”). These elements may be implemented using electronic hardware, computer software, or any combination thereof. Whether such elements are implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system.

(21) By way of example, an element, or any portion of an element, or any combination of elements may be implemented as a “processing system” that includes one or more processors. Examples of processors include microprocessors, microcontrollers, graphics processing units (GPUs), central processing units (CPUs), application processors, digital signal processors (DSPs), reduced instruction set computing (RISC) processors, systems on a chip (SoC), baseband processors, field programmable gate arrays (FPGAs), programmable logic devices (PLDs), state machines, gated logic, discrete hardware circuits, and other suitable hardware configured to perform the various functionality described throughout this disclosure. One or more processors in the processing system may execute software. Software shall be construed broadly to mean instructions, instruction sets, code, code segments, program code, programs, subprograms, software components, applications, software applications, software packages, routines, subroutines, objects, executables, threads of execution, procedures, functions, etc., whether referred to as software, firmware, middleware, microcode, hardware description language, or otherwise.

(22) Accordingly, in one or more examples, the functions described may be implemented in

hardware, software, or any combination thereof. If implemented in software, the functions may be stored on or encoded as one or more instructions or code on a computer-readable medium. Computer-readable media includes computer storage media. Storage media may be any available media that can be accessed by a computer. By way of example, and not limitation, such computer-readable media can comprise a random-access memory (RAM), a read-only memory (ROM), an electrically erasable programmable ROM (EEPROM), optical disk storage, magnetic disk storage, other magnetic storage devices, combinations of the types of computer-readable media, or any other medium that can be used to store computer executable code in the form of instructions or data structures that can be accessed by a computer.

(23) While aspects and implementations are described in this application by illustration to some examples, those skilled in the art will understand that additional implementations and use cases may come about in many different arrangements and scenarios. Aspects described herein may be implemented across many differing platform types, devices, systems, shapes, sizes, and packaging arrangements. For example, implementations and/or uses may come about via integrated chip implementations and other non-module-component based devices (e.g., end-user devices, vehicles, communication devices, computing devices, industrial equipment, retail/purchasing devices, medical devices, artificial intelligence (AI)-enabled devices, etc.). While some examples may or may not be specifically directed to use cases or applications, a wide assortment of applicability of described aspects may occur. Implementations may range a spectrum from chip-level or modular components to non-modular, non-chip-level implementations and further to aggregate, distributed, or original equipment manufacturer (OEM) devices or systems incorporating one or more aspects of the described aspects. In some practical settings, devices incorporating described aspects and features may also include additional components and features for implementation and practice of claimed and described aspect. For example, transmission and reception of wireless signals necessarily includes a number of components for analog and digital purposes (e.g., hardware components including antenna, RF-chains, power amplifiers, modulators, buffer, processor(s), interleaver, adders/summers, etc.). It is intended that aspects described herein may be practiced in a wide variety of devices, chip-level components, systems, distributed arrangements, end-user devices, etc. of varying sizes, shapes, and constitution.

(24) FIG. 1 is a diagram illustrating an example of a wireless communications system and an access network **100**. The wireless communications system (also referred to as a wireless wide area network (WWAN)) includes base stations **102**, UEs **104**, an Evolved Packet Core (EPC) **160**, and another core network **190** (e.g., a 5G Core (5GC)). The base stations **102** may include macrocells (high power cellular base station) and/or small cells (low power cellular base station). The macrocells include base stations. The small cells include femtocells, picocells, and microcells.

(25) A link between a UE **104** and a base station **102** or **180** may be established as an access link, e.g., using a Uu interface. Other communication may be exchanged between wireless devices based on sidelink. For example, some UEs **104** may communicate with each other directly using a device-to-device (D2D) communication link **158**. In some examples, the D2D communication link **158** may use the DL/UL WWAN spectrum. The D2D communication link **158** may use one or more sidelink channels, such as a physical sidelink broadcast channel (PSBCH), a physical sidelink discovery channel (PSDCH), a physical sidelink shared channel (PSSCH), and a physical sidelink control channel (PSCCH). D2D communication may be through a variety of wireless D2D communications systems, such as for example, WiMedia, Bluetooth, ZigBee, Wi-Fi based on the Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, LTE, or NR.

(26) Some examples of sidelink k communication may include vehicle-based communication devices that can communicate from vehicle-to-vehicle (V2V), vehicle-to-infrastructure (V2I) (e.g., from the vehicle-based communication device to road infrastructure nodes such as a Road Side Unit (RSU)), vehicle-to-network (V2N) (e.g., from the vehicle-based communication device to one or more network nodes, such as a base station), vehicle-to-pedestrian (V2P), cellular vehicle-to-

everything (C-V2X), and/or a combination thereof and/or with other devices, which can be collectively referred to as vehicle-to-anything (V2X) communications. Sidelink communication may be based on V2X or other D2D communication, such as Proximity Services (ProSe), etc. In addition to UEs, sidelink communication may also be transmitted and received by other transmitting and receiving devices, such as Road Side Unit (RSU) **107**, etc. Sidelink communication may be exchanged using a PC5 interface, such as described in connection with the example in FIG. 2. In some examples, an intermediary device (e.g., such as a base station **102** or **180**) may facilitate communication between an originating device (e.g., a first UE) and a target device (e.g., a second UE) using sidelink communication. For example, a base station may allocate resources for sidelink communication, in some examples. In other examples, the devices may communicate without assistance from an intermediary device.

(27) Although the following description, including the example slot structure of FIG. 2, may provide examples for sidelink communication in connection with 5G NR, the concepts described herein may be applicable to other similar areas, such as LTE, LTE-A, CDMA, GSM, and other wireless technologies.

(28) Referring again to FIG. 1, in some aspects, a sidelink communication device, such as the UE **104**, may be configured to manage one or more aspects of wireless communication by facilitating resource reservation for UEs applying a power saving mode. As an example, in FIG. 1, the UE **104** may include a SL component **198** configured to perform sensing on one or more SL resources to identify a first set of available resources. The SL component **198** may also be configured to adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. The SL component **198** may also be configured to transmit a sidelink message indicating a second set of available resources based on the second measurement threshold. The SL component **198** may also be configured to perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. The SL component **198** may also be configured to transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(29) Although the following description provides examples directed to 5G NR (and, in particular, to sidelink communications via 5G NR), the concepts described herein may be applicable to other similar areas, such as LTE, LTE-A, CDMA, GSM, and/or other wireless technologies, in which wireless communication devices may employ power saving modes and perform resource reservations.

(30) The base stations **102** configured for 4G LTE (collectively referred to as Evolved Universal Mobile Telecommunications System (UMTS) Terrestrial Radio Access Network (E-UTRAN)) may interface with the EPC **160** through first backhaul links **132** (e.g., SI interface). The base stations **102** configured for 5G NR (collectively referred to as Next Generation RAN (NG-RAN)) may interface with core network **190** through second backhaul links **184**. In addition to other functions, the base stations **102** may perform one or more of the following functions: transfer of user data, radio channel ciphering and deciphering, integrity protection, header compression, mobility control functions (e.g., handover, dual connectivity), inter-cell interference coordination, connection setup and release, load balancing, distribution for non-access stratum (NAS) messages, NAS node selection, synchronization, radio access network (RAN) sharing, multimedia broadcast multicast service (MBMS), subscriber and equipment trace, RAN information management (RIM), paging, positioning, and delivery of warning messages. The base stations **102** may communicate directly or indirectly (e.g., through the EPC **160** or core network **190**) with each other over third backhaul links **134** (e.g., X2 interface). The first backhaul links **132**, the second backhaul links **184** (e.g., an Xn interface), and the third backhaul links **134** may be wired or wireless.

(31) In some aspects, a base station **102** or **180** may be referred as a RAN and may include aggregated or disaggregated components. As an example of a disaggregated RAN, a base station

may include a central unit (CU) **106**, one or more distributed units (DU) **105**, and/or one or more remote units (RU) **109**, as illustrated in FIG. 1. A RAN may be disaggregated with a split between an RU **109** and an aggregated CU/DU. A RAN may be disaggregated with a split between the CU **106**, the DU **105**, and the RU **109**. A RAN may be disaggregated with a split between the CU **106** and an aggregated DU/RU. The CU **106** and the one or more DUs **105** may be connected via an F1 interface. A DU **105** and an RU **109** may be connected via a fronthaul interface. A connection between the CU **106** and a DU **105** may be referred to as a midhaul, and a connection between a DU **105** and an RU **109** may be referred to as a fronthaul. The connection between the CU **106** and the core network may be referred to as the backhaul. The RAN may be based on a functional split between various components of the RAN, e.g., between the CU **106**, the DU **105**, or the RU **109**. The CU may be configured to perform one or more aspects of a wireless communication protocol, e.g., handling one or more layers of a protocol stack, and the DU(s) may be configured to handle other aspects of the wireless communication protocol, e.g., other layers of the protocol stack. In different implementations, the split between the layers handled by the CU and the layers handled by the DU may occur at different layers of a protocol stack. As one, non-limiting example, a DU **105** may provide a logical node to host a radio link control (RLC) layer, a medium access control (MAC) layer, and at least a portion of a physical (PHY) layer based on the functional split. An RU may provide a logical node configured to host at least a portion of the PHY layer and radio frequency (RF) processing. A CU **106** may host higher layer functions, e.g., above the RLC layer, such as a service data adaptation protocol (SDAP) layer, a packet data convergence protocol (PDCP) layer. In other implementations, the split between the layer functions provided by the CU, DU, or RU may be different.

(32) An access network may include one or more integrated access and backhaul (IAB) nodes **111** that exchange wireless communication with a UE **104** or other IAB node **111** to provide access and backhaul to a core network. In an IAB network of multiple IAB nodes, an anchor node may be referred to as an IAB donor. The IAB donor may be a base station **102** or **180** that provides access to a core network **190** or EPC **160** and/or control to one or more IAB nodes **111**. The IAB donor may include a CU **106** and a DU **105**. IAB nodes **111** may include a DU **105** and a mobile termination (MT). The DU **105** of an IAB node **111** may operate as a parent node, and the MT may operate as a child node.

(33) The base stations **102** may wirelessly communicate with the UEs **104**. Each of the base stations **102** may provide communication coverage for a respective geographic coverage area **110**. There may be overlapping geographic coverage areas **110**. For example, the small cell **102'** may have a coverage area **110'** that overlaps the coverage area **110** of one or more macro base stations **102**. A network that includes both small cell and macrocells may be known as a heterogeneous network. A heterogeneous network may also include Home Evolved Node Bs (eNBs) (HeNBs), which may provide service to a restricted group known as a closed subscriber group (CSG). The communication links **120** between the base stations **102** and the UEs **104** may include uplink (UL) (also referred to as reverse link) transmissions from a UE **104** to a base station **102** and/or downlink (DL) (also referred to as forward link) transmissions from a base station **102** to a UE **104**. The communication links **120** may use multiple-input and multiple-output (MIMO) antenna technology, including spatial multiplexing, beamforming, and/or transmit diversity. The communication links may be through one or more carriers. The base stations **102**/UEs **104** may use spectrum up to Y MHz (e.g., 5, 10, 15, 20, 100, 400, etc. MHz) bandwidth per carrier allocated in a carrier aggregation of up to a total of Yx MHz (x component carriers) used for transmission in each direction. The carriers may or may not be adjacent to each other. Allocation of carriers may be asymmetric with respect to DL and UL (e.g., more or fewer carriers may be allocated for DL than for UL). The component carriers may include a primary component carrier and one or more secondary component carriers. A primary component carrier may be referred to as a primary cell (PCell) and a secondary component carrier may be referred to as a secondary cell (SCell).

(34) The wireless communications system may further include a Wi-Fi access point (AP) **150** in communication with Wi-Fi stations (STAs) **152** via communication links **154**, e.g., in a 5 GHz unlicensed frequency spectrum or the like. When communicating in an unlicensed frequency spectrum, the STAs **152**/AP **150** may perform a clear channel assessment (CCA) prior to communicating in order to determine whether the channel is available.

(35) The small cell **102'** may operate in a licensed and/or an unlicensed frequency spectrum. When operating in an unlicensed frequency spectrum, the small cell **102'** may employ NR and use the same unlicensed frequency spectrum (e.g., 5 GHz, or the like) as used by the Wi-Fi AP **150**. The small cell **102'**, employing NR in an unlicensed frequency spectrum, may boost coverage to and/or adjust capacity of the access network.

(36) The electromagnetic spectrum is often subdivided, based on frequency/wavelength, into various classes, bands, channels, etc. In 5G NR, two initial operating bands have been identified as frequency range designations FR1 (410 MHz-7.125 GHz) and FR2 (24.25 GHz-52.6 GHz). Although a portion of FR1 is greater than 6 GHz, FR1 is often referred to (interchangeably) as a “sub-6 GHz” band in various documents and articles. A similar nomenclature issue sometimes occurs with regard to FR2, which is often referred to (interchangeably) as a “millimeter wave” band in documents and articles, despite being different from the extremely high frequency (EHF) band (30 GHz-300 GHz) which is identified by the International Telecommunications Union (ITU) as a “millimeter wave” band.

(37) The frequencies between FR1 and FR2 are often referred to as mid-band frequencies. Recent 5G NR studies have identified an operating band for these mid-band frequencies as frequency range designation FR3 (7.125 GHz-24.25 GHz). Frequency bands falling within FR3 may inherit FR1 characteristics and/or FR2 characteristics, and thus may effectively extend features of FR1 and/or FR2 into mid-band frequencies. In addition, higher frequency bands are currently being explored to extend 5G NR operation beyond 52.6 GHz. For example, three higher operating bands have been identified as frequency range designations FR4a or FR4-1 (52.6 GHz-71 GHz), FR4 (52.6 GHz-114.25 GHz), and FR5 (114.25 GHz-300 GHz). Each of these higher frequency bands falls within the EHF band.

(38) With the above aspects in mind, unless specifically stated otherwise, it should be understood that the term “sub-6 GHz” or the like if used herein may broadly represent frequencies that may be less than 6 GHz, may be within FR1, or may include mid-band frequencies. Further, unless specifically stated otherwise, it should be understood that the term “millimeter wave” or the like if used herein may broadly represent frequencies that may include mid-band frequencies, may be within FR2, FR4, FR4-a or FR4-1, and/or FR5, or may be within the EHF band.

(39) A base station **102**, whether a small cell **102'** or a large cell (e.g., macro base station), may include and/or be referred to as an eNB, gNodeB (gNB), or another type of base station. Some base stations, such as gNB **180** may operate in a traditional sub 6 GHz spectrum, in millimeter wave frequencies, and/or near millimeter wave frequencies in communication with the UE **104**. When the gNB **180** operates in millimeter wave or near millimeter wave frequencies, the gNB **180** may be referred to as a millimeter wave base station. The millimeter wave base station **180** may utilize beamforming **182** with the UE **104** to compensate for the path loss and short range. The base station **180** and the UE **104** may each include a plurality of antennas, such as antenna elements, antenna panels, and/or antenna arrays to facilitate the beamforming. Similarly, beamforming may be applied for sidelink communication, e.g., between UEs.

(40) The base station **180** may transmit a beamformed signal to the UE **104** in one or more transmit directions **182'**. The UE **104** may receive the beamformed signal from the base station **180** in one or more receive directions **182''**. The UE **104** may also transmit a beamformed signal to the base station **180** in one or more transmit directions. The base station **180** may receive the beamformed signal from the UE **104** in one or more receive directions. The base station **180**/UE **104** may perform beam training to determine the best receive and transmit directions for each of the base

station **180**/UE **104**. The transmit and receive directions for the base station **180** may or may not be the same. The transmit and receive directions for the UE **104** may or may not be the same. Although this example is described for the base station **180** and UE **104**, the aspects may be similarly applied between a first and second device (e.g., a first and second UE) for sidelink communication.

(41) The EPC **160** may include a Mobility Management Entity (MME) **162**, other MMEs **164**, a Serving Gateway **166**, a Multimedia Broadcast Multicast Service (MBMS) Gateway **168**, a Broadcast Multicast Service Center (BM-SC) **170**, and a Packet Data Network (PDN) Gateway **172**. The MME **162** may be in communication with a Home Subscriber Server (HSS) **174**. The MME **162** is the control node that processes the signaling between the UEs **104** and the EPC **160**. Generally, the MME **162** provides bearer and connection management. All user Internet protocol (IP) packets are transferred through the Serving Gateway **166**, which itself is connected to the PDN Gateway **172**. The PDN Gateway **172** provides UE IP address allocation as well as other functions. The PDN Gateway **172** and the BM-SC **170** are connected to the IP Services **176**. The IP Services **176** may include the Internet, an intranet, an IP Multimedia Subsystem (IMS), a PS Streaming Service, and/or other IP services. The BM-SC **170** may provide functions for MBMS user service provisioning and delivery. The BM-SC **170** may serve as an entry point for content provider MBMS transmission, may be used to authorize and initiate MBMS Bearer Services within a public land mobile network (PLMN), and may be used to schedule MBMS transmissions. The MBMS Gateway **168** may be used to distribute MBMS traffic to the base stations **102** belonging to a Multicast Broadcast Single Frequency Network (MBSFN) area broadcasting a particular service, and may be responsible for session management (start/stop) and for collecting eMBMS related charging information.

(42) The core network **190** may include an Access and Mobility Management Function (AMF) **192**, other AMFs **193**, a Session Management Function (SMF) **194**, and a User Plane Function (UPF) **195**. The AMF **192** may be in communication with a Unified Data Management (UDM) **196**. The AMF **192** is the control node that processes the signaling between the UEs **104** and the core network **190**. Generally, the AMF **192** provides QoS flow and session management. All user Internet protocol (IP) packets are transferred through the UPF **195**. The UPF **195** provides UE IP address allocation as well as other functions. The UPF **195** is connected to the IP Services **197**. The IP Services **197** may include the Internet, an intranet, an IP Multimedia Subsystem (IMS), a Packet Switch (PS) Streaming (PSS) Service, and/or other IP services.

(43) The base station may include and/or be referred to as a gNB, Node B, eNB, an access point, a base transceiver station, a radio base station, a radio transceiver, a transceiver function, a basic service set (BSS), an extended service set (ESS), a transmit reception point (TRP), or some other suitable terminology. The base station **102** provides an access point to the EPC **160** or core network **190** for a UE **104**. Examples of UEs **104** include a cellular phone, a smart phone, a session initiation protocol (SIP) phone, a laptop, a personal digital assistant (PDA), a satellite radio, a global positioning system, a multimedia device, a video device, a digital audio player (e.g., MP3 player), a camera, a game console, a tablet, a smart device, a wearable device, a vehicle, an electric meter, a gas pump, a large or small kitchen appliance, a healthcare device, an implant, a sensor/actuator, a display, or any other similar functioning device. Some of the UEs **104** may be referred to as IoT devices (e.g., parking meter, gas pump, toaster, vehicles, heart monitor, etc.). The UE **104** may also be referred to as a station, a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology.

(44) FIG. 2 includes diagrams **200** and **210** illustrating example aspects of slot structures that may be used for sidelink communication (e.g., between UEs **104**, RSU **107**, etc.). The slot structure may

be within a 5G/NR frame structure in some examples. In other examples, the slot structure may be within an LTE frame structure. Although the following description may be focused on 5G NR, the concepts described herein may be applicable to other similar areas, such as LTE, LTE-A, CDMA, GSM, and other wireless technologies. The example slot structure in FIG. 2 is merely one example, and other sidelink communication may have a different frame structure and/or different channels for sidelink communication. A frame (10 ms) may be divided into 10 equally sized subframes (1 ms). Each subframe may include one or more time slots. Subframes may also include mini-slots, which may include 7, 4, or 2 symbols. Each slot may include 14 or 12 symbols, depending on whether the cyclic prefix (CP) is normal or extended. For normal CP, each slot may include 14 symbols, and for extended CP, each slot may include 12 symbols. The symbols may be CP orthogonal frequency division multiplexing (OFDM) (CP-OFDM) symbols. The symbols may be CP-OFDM symbols (for high throughput scenarios) or discrete Fourier transform (DFT) spread OFDM (DFT-s-OFDM) symbols (also referred to as single carrier frequency-division multiple access (SC-FDMA) symbols) (for power limited scenarios; limited to a single stream transmission). The number of slots within a subframe is based on the CP and the numerology. The numerology defines the subcarrier spacing (SCS) and, effectively, the symbol length/duration, which is equal to  $1/\text{SCS}$ .

(45) TABLE-US-00001 SCS  $\Delta f = 2^{\mu} \cdot 15 \text{ kHz}$  Cyclic prefix 0 15 Normal 1 30 Normal 2 60 Normal, Extended 3 120 Normal 4 240 Normal

(46) For normal CP (14 symbols/slot), different numerologies  $\mu$  “0” to 4 allow for 1, 2, 4, 8, and 16 slots, respectively, per subframe. For extended CP, the numerology 2 allows for 4 slots per subframe. Accordingly, for normal CP and numerology  $\mu$ , there are 14 symbols/slot and 2 slots/subframe. The subcarrier spacing may be equal to  $2^{\mu} \cdot 15 \text{ kHz}$ , where  $\mu$  is the numerology “0” to 4. As such, the numerology  $\mu=0$  has a subcarrier spacing of 15 kHz and the numerology  $\mu=4$  has a subcarrier spacing of 240 kHz. The symbol length/duration is inversely related to the subcarrier spacing. FIG. 2 provides an example of normal CP with 14 symbols per slot. Within a set of frames, there may be one or more different bandwidth parts (BWPs) that are frequency division multiplexed. Each BWP may have a particular numerology and CP (normal or extended).

(47) Diagram 200 illustrates a single resource block of a single slot transmission, e.g., which may correspond to a 0.5 ms transmission time interval (TTI). A physical sidelink control channel may be configured to occupy multiple physical resource blocks (PRBs), e.g., 10, 12, 15, 20, or 25 PRBs. The PSCCH may be limited to a single sub-channel. A PSCCH duration may be configured to be 2 symbols or 3 symbols, for example. A sub-channel may comprise 10, 15, 20, 25, 50, 75, or 100 PRBs, for example. The resources for a sidelink transmission may be selected from a resource pool including one or more subchannels. As a non-limiting example, the resource pool may include between 1-27 subchannels. A PSCCH size may be established for a resource pool, e.g., as between 10-100% of one subchannel for a duration of 2 symbols or 3 symbols. The diagram 210 in FIG. 2 illustrates an example in which the PSCCH occupies about 50% of a subchannel, as one example to illustrate the concept of PSCCH occupying a portion of a subchannel. The physical sidelink shared channel (PSSCH) occupies at least one subchannel. The PSCCH may include a first portion of sidelink control information (SCI), and the PSSCH may include a second portion of SCI in some examples.

(48) A resource grid may be used to represent the frame structure. Each time slot may include a resource block (RB) (also referred to as physical RBs (PRBs)) that extends 12 consecutive subcarriers. The resource grid is divided into multiple resource elements (REs). The number of bits carried by each RE depends on the modulation scheme. As illustrated in FIG. 2, some of the REs may include control information in PSCCH and some REs may include demodulation RS (DMRS). At least one symbol may be used for feedback. FIG. 2 illustrates examples with two symbols for a physical sidelink feedback channel (PSFCH) with adjacent gap symbols. A symbol prior to and/or after the feedback may be used for turnaround between reception of data and transmission of the

feedback. The gap enables a device to switch from operating as a transmitting device to prepare to operate as a receiving device, e.g., in the following slot. Data may be transmitted in the remaining REs, as illustrated. The data may comprise the data message described herein. The position of any of the data, DMRS, SCI, feedback, gap symbols, and/or LBT symbols may be different than the example illustrated in FIG. 2. Multiple slots may be aggregated together in some aspects.

(49) FIG. 3 is a block diagram 300 of a first wireless communication device 310 in communication with a second wireless communication device 350. The communication may be based on sidelink or an access link. In some examples, the wireless communication devices 310, 350 may communicate based on V2X or other D2D communication. In other aspects, the wireless communication devices 310, 350 may communicate over an access link based on uplink and downlink transmissions. The communication may be based on sidelink using a PC5 interface (e.g., between two UEs). The communication may be based on an access link using a Uu interface (e.g., between a base station and a UE). The wireless communication devices 310, 350 may comprise a UE, an RSU, a base station, etc. In some implementations, the first wireless communication device 310 may correspond to a base station and the second wireless communication device 350 may correspond to a UE.

(50) As shown in FIG. 3, the first wireless communication device 310 includes a transmit processor (TX processor 316), a transceiver 318 including a transmitter 318a and a receiver 318b, antennas 320, a receive processor (RX processor 370), a channel estimator 374, a controller/processor 375, and memory 376. The example second wireless communication device 350 includes antennas 352, a transceiver 354 including a transmitter 354a and a receiver 354b, an RX processor 356, a channel estimator 358, a controller/processor 359, memory 360, and a TX processor 368. In other examples, the first wireless communication device 310 and/or the second wireless communication device 350 may include additional or alternative components.

(51) Packets may be provided to the controller/processor 375 that implements layer 3 and layer 2 functionality. Layer 3 includes a radio resource control (RRC) layer, and layer 2 includes a packet data convergence protocol (PDCP) layer, a radio link control (RLC) layer, and a medium access control (MAC) layer.

(52) The TX processor 316 and the RX processor 370 implement layer “1” functionality associated with various signal processing functions. Layer 1, which includes a physical (PHY) layer, may include error detection on the transport channels, forward error correction (FEC) coding/decoding of the transport channels, interleaving, rate matching, mapping onto physical channels, modulation/demodulation of physical channels, and MIMO antenna processing. The TX processor 316 handles mapping to signal constellations based on various modulation schemes (e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), M-phase-shift keying (M-PSK), M-quadrature amplitude modulation (M-QAM)). The coded and modulated symbols may then be split into parallel streams. Each stream may then be mapped to an OFDM subcarrier, multiplexed with a reference signal (e.g., pilot) in the time and/or frequency domain, and then combined together using an Inverse Fast Fourier Transform (IFFT) to produce a physical channel carrying a time domain OFDM symbol stream. The OFDM stream is spatially precoded to produce multiple spatial streams. Channel estimates from the channel estimator 374 may be used to determine the coding and modulation scheme, as well as for spatial processing. The channel estimate may be derived from a reference signal and/or channel condition feedback transmitted by the second wireless communication device 350. Each spatial stream may then be provided to a different antenna 320 via a separate transmitter 318a. Each transmitter 318a may modulate a radio frequency (RF) carrier with a respective spatial stream for transmission.

(53) At the second wireless communication device 350, each receiver 354b receives a signal through its respective antenna 352. Each receiver 354b recovers information modulated onto an RF carrier and provides the information to the RX processor 356. The TX processor 368 and the RX processor 356 implement layer “1” functionality associated with various signal processing

functions. The RX processor **356** may perform spatial processing on the information to recover any spatial streams destined for the second wireless communication device **350**. If multiple spatial streams are destined for the second wireless communication device **350**, they may be combined by the RX processor **356** into a single OFDM symbol stream. The RX processor **356** then converts the OFDM symbol stream from the time-domain to the frequency domain using a Fast Fourier Transform (FFT). The frequency domain signal comprises a separate OFDM symbol stream for each subcarrier of the OFDM signal. The symbols on each subcarrier, and the reference signal, are recovered and demodulated by determining the most likely signal constellation points transmitted by the first wireless communication device **310**. These soft decisions may be based on channel estimates computed by the channel estimator **358**. The soft decisions are then decoded and deinterleaved to recover the data and control signals that were originally transmitted by the first wireless communication device **310** on the physical channel. The data and control signals are then provided to the controller/processor **359**, which implements layer **3** and layer **2** functionality.

(54) The controller/processor **359** can be associated with the memory **360** that stores program codes and data. The memory **360** may be referred to as a computer-readable medium. The controller/processor **359** may provide demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, and control signal processing. The controller/processor **359** is also responsible for error detection using an acknowledgment (ACK) and/or negative ACK (NACK) protocol to support hybrid automatic repeat request HARQ operations.

(55) Similar to the functionality described in connection with the transmission by the first wireless communication device **310**, the controller/processor **359** may provide RRC layer functionality associated with system information (e.g., MIB, SIBs) acquisition, RRC connections, and measurement reporting; PDCP layer functionality associated with header compression/decompression, and security (ciphering, deciphering, integrity protection, integrity verification); RLC layer functionality associated with the transfer of upper layer PDUs, error correction through ARQ, concatenation, segmentation, and reassembly of RLC SDUs, re-segmentation of RLC data PDUs, and reordering of RLC data PDUs; and MAC layer functionality associated with mapping between logical channels and transport channels, multiplexing of MAC SDUs onto TBs, demultiplexing of MAC SDUs from TBs, scheduling information reporting, error correction through HARQ, priority handling, and logical channel prioritization.

(56) Channel estimates derived by the channel estimator **358** from a reference signal or feedback transmitted by the first wireless communication device **310** may be used by the TX processor **368** to select the appropriate coding and modulation schemes, and to facilitate spatial processing. The spatial streams generated by the TX processor **368** may be provided to different antenna **352** via separate transmitters **354a**. Each transmitter **354a** may modulate an RF carrier with a respective spatial stream for transmission.

(57) The transmission is processed at the first wireless communication device **310** in a manner similar to that described in connection with the receiver function at the second wireless communication device **350**. Each receiver **318b** receives a signal through its respective antenna **320**. Each receiver **318b** recovers information modulated onto an RF carrier and provides the information to the RX processor **370**.

(58) The controller/processor **375** can be associated with the memory **376** that stores program codes and data. The memory **376** may be referred to as a computer-readable medium. The controller/processor **375** provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing. The controller/processor **375** is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

(59) At least one of the TX processor **368** or the TX processor **316**, the RX processor **356** or the RX processor **370**, and the controller/processor **359** or the controller/processor **375** may be configured

to perform aspects in connection with the SL component **198** of FIG. **1**.

(60) FIG. **4** illustrates an example **400** of sidelink communication between devices, as presented herein. The communication may be based on a slot structure including aspects described in connection with FIG. **2** or another sidelink structure. For example, a first UE **402** may transmit a sidelink transmission **410**, e.g., including a control channel (e.g., PSCCH) and/or a corresponding data channel (e.g., PSSCH), that may be received by a second UE **406** and/or a third UE **408**. The sidelink transmission **410** may be received directly from the first UE **402**, e.g., without being transmitting through a base station.

(61) The first UE **402**, the second UE **406**, and/or the third UE **408** may each be capable of operating as a transmitting device in addition to operating as a receiving device. Thus, the second UE **406** is illustrated as transmitting a sidelink transmission **412** that is received by the first UE **402**. One or more of the sidelink transmissions **410**, **412** may be broadcast or multicast to nearby devices. For example, the first UE **402** may transmit communications intended for receipt by other UEs within a range **401** of the first UE **402**. In other examples, one or more of the sidelink transmissions **410**, **412** may be groupcast to nearby devices that are a member of a group. In other examples, one or more of the sidelink transmissions **410**, **412** may be unicast from one UE to another UE.

(62) A sidelink transmission may provide sidelink control information (SCI) including information to facilitate decoding the corresponding data channel. For example, a transmitting device (sometimes referred to as an “originating device,” a “transmitting UE”, or an “originating UE”) may transmit SCI including information that a receiving device (sometimes referred to as a “target device,” a “receiving UE,” or a “target UE”) may use to avoid interference. For example, the SCI may indicate reserved time resources and/or reserved frequency resources that will be occupied by the data transmission, and may be indicated in a control message from the transmitting device. The number of TTIs, as well as the RBs that will be occupied by the data transmission, may be indicated in a control message from the first UE **402**. In some examples, the SCI may be used by a receiving device to avoid interference by refraining from transmitting on the occupied resources during a data transmission.

(63) One or more of the first UE **402**, the second UE **406**, and/or the third UE **408** may include an SL component, similar to the SL component **198** described in connection with FIG. **1**.

(64) Sidelink communication enables a first UE to communicate with another UE directly. For example, the first UE and the other UE may communicate without routing the communication through a base station. Sidelink may be beneficial for vehicle-based communications (e.g., V2V, V2I, V2N, V2P, C-V2X, etc.) that allows a vehicle UE to communicate directly with another UE or a pedestrian UE. When dealing with V2X communication, power consumption by the vehicle UE might not be a concern.

(65) However, it may be beneficial to implement power saving modes for some devices. Two examples of power saving modes include partial sensing or random selection and discontinuous reception (DRX). In either DRX or partial sensing, the UE may skip sensing for resource reservations for portions of time. The skipped sensing may save battery power at the UE, for example.

(66) Sidelink communication may be based on different types or modes of resource allocation mechanisms. In a first resource allocation mode (which may be referred to herein as “Mode 1”), centralized resource allocation may be provided by a network entity. For example, and referring to the example of FIG. **1**, a base station **102/180** may determine resources for sidelink communication and may allocate resources to different UEs to use for sidelink transmissions. In this first mode, a UE receives the allocation of sidelink resources from the base station **102/180**. In a second resource allocation mode (which may be referred to herein as “Mode 2”), distributed resource allocation may be provided. In Mode 2, each UE may autonomously determine resources to use for sidelink transmission. In order to coordinate the selection of sidelink resources by individual UEs, each UE

may use a sensing technique to monitor for resource reservations by other sidelink UEs and may select resources for sidelink transmissions from unreserved resources. Devices communicating based on sidelink may determine one or more radio resources in the time and frequency domain that are used by other devices in order to select transmission resources that avoid collisions with other devices. The sidelink transmission and/or the resource reservation may be periodic or aperiodic, where a UE may reserve resources for transmission in a current slot and up to two future slots.

(67) Thus, in the second mode (e.g., Mode 2), individual UEs may autonomously select resources for sidelink transmission, e.g., without a central entity such as a base station indicating the resources for the device. A first UE may reserve the selected resources in order to inform other UEs about the resources that the first UE intends to use for sidelink transmission(s).

(68) In some examples, the resource selection for sidelink communication may be based on a sensing-based mechanism. For instance, before selecting a resource for a data transmission, a UE may first determine whether resources have been reserved by other UEs.

(69) For example, as part of a sensing mechanism for resource allocation Mode 2, the UE may determine (e.g., sense) whether a selected sidelink resource has been reserved by other UE(s) before selecting the sidelink resource for a data transmission. If the UE determines that the sidelink resource has not been reserved by other UEs, the UE may use the selected sidelink resource for transmitting the data, e.g., in a PSSCH transmission. The UE may estimate or determine which radio resources (e.g., sidelink resources) may be in-use and/or reserved by others by detecting and decoding sidelink control information (SCI) transmitted by other UEs. The UE may use a sensing-based resource selection algorithm to estimate or determine which radio resources are in-use and/or reserved by others. The UE may receive SCI from another UE that includes reservation information based on a resource reservation field included in the SCI. The UE may continuously monitor for (e.g., sense) and decode SCI from peer UEs. The SCI may include reservation information, e.g., indicating slots and RBs that a particular UE has selected for a future transmission. The UE may exclude resources that are used and/or reserved by other UEs from a set of candidate resources for sidelink transmission by the UE, and the UE may select/reserve resources for a sidelink transmission from the resources that are unused and therefore form the set of candidate resources. The UE may continuously perform sensing for SCI with resource reservations in order to maintain a set of candidate resources from which the UE may select one or more resources for a sidelink transmission. Once the UE selects a candidate resource, the UE may transmit SCI indicating its own reservation of the resource for a sidelink transmission. The number of resources (e.g., sub-channels per subframe) reserved by the UE may depend on the size of data to be transmitted by the UE. Although the example is described for a UE receiving reservations from another UE, the reservations may also be received from an RSU or other device communicating based on sidelink.

(70) FIG. 5 is an example 500 of time and frequency resources showing reservations for sidelink transmissions, as presented herein. The resources may be included in a sidelink resource pool, for example. The resource allocation for each UE may be in units of one or more sub-channels in the frequency domain (e.g., sub-channels SC1 to SC 4), and may be based on one slot in the time domain (e.g., slots “1” to 8). The UE may also use resources in the current slot to perform an initial transmission, and may reserve resources in future slots for retransmissions. In the illustrated example of FIG. 5, two different future slots are being reserved by UE1 and UE2 for retransmissions. The resource reservation may be limited to a window of a pre-defined slots and sub-channels, such as an 8 time slots by 4 sub-channels window as shown in example 500, which provides 32 available resource blocks in total. This window may also be referred to as a resource selection window.

(71) A first UE (“UE1”) may reserve a sub-channel (e.g., SC 1) in a current slot (e.g., slot 1) for its initial data transmission 502, and may reserve additional future slots within the window for data retransmissions (e.g., a first data retransmission 504 and a second data retransmission 506). For

example, the first UE may reserve sub-channels SC 3 at slot 3 and SC 2 at slot 4 for future retransmissions as shown by FIG. 5. The first UE then transmits information regarding which resources are being used and/or reserved by it to other UE(s). The first UE may do so by including the reservation information in a reservation resource field of the SCI, e.g., a first stage SCI.

(72) FIG. 5 illustrates that a second UE (“UE2”) reserves resources in sub-channels SC 3 and SC 4 at slot “1” for a current data transmission 508, reserves a first data retransmission 510 at slot 4 using sub-channels SC 3 and SC 4, and reserves a second data retransmission 512 at slot 7 using sub-channels SC “1” and SC 2, as shown by FIG. 5. Similarly, the second UE may transmit the resource usage and reservation information to other UE(s), such as using the reservation resource field in SCI.

(73) A third UE may consider resources reserved by other UEs within the resource selection window to select resources to transmit its data. The third UE may first decode SCIs within a time period to identify which resources are available (e.g., candidate resources). For example, the third UE may exclude the resources reserved by UE1 and UE2 and may select other available sub-channels and time slots from the candidate resources for its transmission and retransmissions, which may be based on a number of adjacent sub-channels in which the data (e.g., packet) to be transmitted can fit.

(74) While FIG. 5 illustrates resources being reserved for an initial transmission and two retransmissions, the reservation may be for an initial transmission and a single transmission or only for an initial transmission.

(75) The UE may determine an associated signal measurement (such as RSRP) for each resource reservation received by another UE. The UE may consider resources reserved in a transmission for which the UE measures an RSRP below a threshold to be available for use by the UE. A UE may perform signal/channel measurement for a sidelink resource that has been reserved and/or used by other UE(s), such as by measuring the RSRP of the message (e.g., the SCI) that reserves the sidelink resource. Based at least in part on the signal/channel measurement, the UE may consider using/reusing the sidelink resource that has been reserved by other UE(s). For example, the UE may exclude the reserved resources from a candidate resource set if the measured RSRP meets or exceeds the threshold, and the UE may consider a reserved resource to be available if the measured RSRP for the message reserving the resource is below the threshold. The UE may include the resources in the candidate resources set and may use/reuse such reserved resources when the message reserving the resources has an RSRP below the threshold, because the low RSRP indicates that the other UE is distant and a reuse of the resources is less likely to cause interference to that UE. A higher RSRP indicates that the transmitting UE that reserved the resources is potentially closer to the UE and may experience higher levels of interference if the UE selected the same resources.

(76) For example, the UE may determine a set of candidate resources (e.g., by monitoring SCI from other UEs and removing resources from the set of candidate resources that are reserved by other UEs in a signal for which the UE measures an RSRP above a threshold value). The UE may also select N resources for transmissions and/or retransmissions of a TB. As an example, the UE may randomly select the N resources from the set of candidate resources previously determined. For each transmission, the UE may reserve future time and frequency resources for an initial transmission and up to two retransmissions. The UE may reserve the resources by transmitting SCI indicating the resource reservation. For example, in the example in FIG. 5, the second UE may transmit SCI reserving resources for the current data transmission 508, the first data retransmission 510, and the second data retransmission 512.

(77) There may be a timeline for a sensing-based resource selection. For example, the UE may sense and decode the SCI received from other UEs during a sensing window, e.g., a time duration prior to resource selection. Based on the sensing history during the sensing window, the UE may be able to maintain a set of available candidate resources by excluding resources that are reserved by

other UEs from the set of candidate resources. A UE may select resources from its set of available candidate resources and transmits SCI reserving the selected resources for sidelink transmission (e.g., a PSSCH transmission) by the UE. There may be a time gap between the UE's selection of the resources and the UE transmitting SCI reserving the resources.

(78) In the resource allocation Mode 2, a higher layer may request the UE **104** that includes the SL component **198** to determine a subset of resources from which the higher layer may select resources for PSSCH/PSCCH transmissions. FIG. 6 illustrates an example timing diagram **600** for a UE that may be triggered to select a resource for sidelink transmission in response to a resource selection trigger **650**. The timing diagram shows a timing for sensing for resource reservations from other UEs, such as the resource reservations described in connection with FIG. 5. As an example, the resource selection trigger **650** may include having data for transmission. Although FIG. 6 is described in connection with a UE, the resource selection may also be applied by other sidelink devices. In response to the resource selection trigger **650**, the UE may consider signals received within a sensing window **602** of duration  $T_{\text{0}}$  and determine information (e.g., SCI with resource reservations) received within the sensing window **602**. For example, the UE may determine which resources were used by other UE(s) or reserved by other UE(s) during the sensing window **602**. The UE may anticipate that the previously used resources may also be used by the other UE in the future. A signal received in the sensing window may include SCI indicating a resource reservation for a resource within the resource selection window **604** following the resource selection trigger **650**. Based on the past use of resources and/or the reservation of resources (e.g., the “sensing” of resources), the UE may determine which resources are scheduled for use and/or determine which resources are not scheduled for use. For example, based on the sensing of the resources during the sensing window **602**, the UE may determine that a first resource **606** and a second resource **608** may be reserved during the slot associated with the resource selection trigger **650** and/or during a future slot. The UE may exclude candidate resources that are reserved by other UEs from a candidate set of resources when selecting a sidelink transmission resource. In some examples, the UE may exclude candidate resources that are reserved by another UE and that meet one or more conditions, such as the reservation signal meeting an RSRP threshold. The UE may select resource **610** for a transmission.

(79) In some wireless communication systems, a receiving UE may perform sensing, then inform the transmitting UE (along with other UEs) about the resources that are available for transmission based on the sensing result. For example, the receiving UE may be a smartphone with a higher processing power and higher battery capacity than the transmitting UE, which may be a smartwatch with limited battery capacity and limited processing power. Therefore, it may be more efficient to have the higher processing power with higher battery capacity receiving UE to perform the sensing for the transmitting UE.

(80) In some instances, multiple UEs may transmit at the same time and may not receive the overlapping communication (e.g., SCI indicating resource reservations) from each other and/or from a base station. Such a UE may miss or be unaware of transmissions and sidelink reservations by other UEs. Therefore, two UEs may reserve the same resource block for a future sidelink transmission, which may result in a resource collision. A resource collision occurs for sidelink transmissions that overlap at least partially in time, and which may overlap, at least partially, in frequency.

(81) To reduce or avoid resource collisions under such instances, and to improve sidelink communication among UEs, the UEs may coordinate among themselves by generating and sharing inter-UE coordination information with other UEs. FIG. 7A is a diagram **700** illustrating the exchange of inter-UE coordination information, where a first UE (“UE-A”) **712** transmits inter-UE coordination information **716** to a second UE (“UE-B”) **714**. In some aspects, the transmission of inter-UE coordination information may include resource reservation forwarding by the UE-A.

(82) The inter-UE coordination information **716** may include information based on the UE's

sensing information (e.g., resource reservations of other UEs that are sensed by UE 712 (e.g., UE-A)), inter-UE coordination information from another UE, resources that are bad, undesirable, or non-preferred for the UE-A 712 (e.g., resources subject to high interference), resources which are preferred or better than other resources for the UE-A 712, etc.

(83) The inter-UE coordination information 716 may indicate candidate resources for sidelink transmission or preferred resources for transmissions by UE-B 714. In some aspects, the indication of preferred resources for UE-B's transmission may be referred to as "Type A" inter-UE coordination information. The UE-A 712 may use the inter-UE coordination information 716 to inform the UE-B 714 about which sub-channels and slots may be used for communicating with the UE-A 712 and/or which sub-channels and slots may not be used because they are occupied or reserved by the UE-A 712 and/or other UEs. The UE-A may indicate a set of resources that may be more suitable for UE-B's transmission based on UE-A's evaluation. The candidate resources may indicate a group of resources from which the UE-B 714 (e.g., UE-B) may select for the sidelink transmission 718. As illustrated, the sidelink transmission 718 may be for UE-A 712 or for one or more different UEs, e.g., UE-C 719. In some aspects, the UE-A may be a potential receiver of the UE-B's transmission, and the inter-UE coordination information may enable mode 2 resource allocation that is based on resource availability from a potential receiver's perspective, which may address reception challenges for a hidden node. In some aspects, the inter-UE coordination information 716 may indicate resources for a sidelink transmission, e.g., particular resources on which the UE-B 714 is to transmit the sidelink transmission 718 rather than candidate resources that the UE-B 714 may select.

(84) In some aspects, the inter-UE coordination information 716 may indicate a set of resources that may not be preferred for UE-B's transmission, such as resources that may not be available for UE-B to transmit a sidelink transmission based on the UE-A's evaluation. In some aspects, the indication of non-preferred resources for UE-B's transmission may be referred to as "Type B" inter-UE coordination information.

(85) In some aspects, the inter-UE coordination information 716 may indicate a half-duplex conflict. For example, the inter-UE coordination information 716 may indicate a collision in time and/or frequency for two transmitting UEs that are unable to receive the other, respective transmission in a half-duplex mode. In some aspects, the inter-UE coordination information 716 may indicate a collision of resources (e.g., reserved resources) in time and/or frequency. In some aspects, the indication of a collision/conflict in resources may be referred to as "Type C" inter-UE coordination information.

(86) Based at least in part on the inter-UE coordination information 716 from the UE-A 712, the UE-B 704 may make a better decision on which resources to use and/or reserve for its sidelink transmission 718 to avoid resource collisions. The UE-A 712 may share its inter-UE coordination information 716 with multiple UEs, and the UE-B 714 may receive the inter-UE coordination information 716 from multiple UEs. Inter-UE coordination information 716 may be transmitted in any of various ways.

(87) The UE-A 712 may transmit inter-UE coordination information 716 in a PSFCH, e.g., indicating a resource collision or a half-duplex conflict indication. The UE-A 712 may transmit inter-UE coordination information 716 in SCI. For example, the UE-A 712 may transmit shared sensing information, candidate resource information for a sidelink transmission, or particular resources for a sidelink transmission in SCI-2 transmitted in PSSCH. For example, a first portion of SCI (e.g., SCI-1) may be transmitted in PSCCH, and a second portion of SCI (e.g., SCI-2) may be transmitted in PSSCH. The UE-A 712 may transmit inter-UE coordination information 716 in a MAC-CE, e.g., on the PSSCH. The UE-A 712 may transmit the inter-UE coordination information 716 in a new physical channel (e.g., that is different than PSCCH, PSSCH, PSFCH, etc.). For example, the UE-A 712 may transmit the inter-UE coordination information 716 in a physical channel that is configured for or dedicated to inter-UE configuration information. The UE-A 712

may transmit the inter-UE coordination information **716** in RRC signaling.

(88) In some aspects, the UE-A **712** may transmit the inter-UE coordination information **716** periodically. In some aspects, the UE-A **712** may transmit aperiodic inter-UE coordination information **716** in response to a trigger. Among other examples, the trigger may be based on the occurrence of an event, such as the occurrence of/detection of a resource collision, the occurrence of/detection of a half-duplex conflict, etc. For example, if the UE-A **712** detects a resource collision, the UE-A **712** may respond by transmitting inter-UE coordination information **716**.

(89) The UE-B **714** may utilize the inter-UE coordination information **716** in various ways.

(90) If the inter-UE coordination information **716** includes information about resources that are preferred for transmissions of the UE-B **714** and/or resources that are not preferred for transmissions of the UE-B **714**, the UE-B **704** may select resource(s) to be used for its sidelink transmission resource selection, or resource re-selection, may be based on both UE-B's sensing result (if available) and the received inter-UE coordination information **716** according to a first option. In a second option, the UE-B **714** may select resource(s) to be used for its sidelink transmission resource selection, or resource re-selection, may be based on the received inter-UE coordination information **716** and not based on sensing. In a third option, the UE-B **714** may select resource(s) to be used for its sidelink transmission resource selection, or resource re-selection, may be based on the received inter-UE coordination information **716** (which may allow the UE-B to use or not use sensing in combination with the inter-UE coordination information **716**).

(91) FIG. 7B is a diagram **750** illustrating the exchange of inter UE coordination information that a UE **702** may provide to multiple UEs. As illustrated in FIG. 7B, the UE **702** may be more capable of performing sensing in comparison with the UE **704**, the UE **706**, or the UE **708**. For example, the UE **702**, which may be a receiving UE that receives a transmission from the UE **704**, the UE **706**, or the UE **708**) may have a higher processing power and/or higher battery capacity than the UE **704**, the UE **706**, or the UE **708**. Therefore, it may be more efficient for the higher battery capacity/processing power UE **702** to perform sensing and transmit (e.g., groupcast) resource availability information **722** to the UE **704**, the UE **706**, and the UE **708**. Moreover, the UE **702** may have information about the UE **704**, the UE **706**, and the UE **708** based on measuring RSRP of signals on incoming links. For example, the UE **702** may be able to measure RSRP on a link between the UE **702** and the UE **704**, a link between the UE **702** and the UE **706**, and a link between the UE **702** and the UE **708**. By measuring the different links, the UE **702** may be able to better identify resources that are available.

(92) In some circumstances, based on the sensing, the receiving UE **702** may identify a first set of available resources that may be smaller than a threshold amount of resources (e.g., determined to be unsuitably small by comparing a size of the available resources with an availability threshold) for the transmission **724** from the UE **704** to the UE **702**. Aspects provided herein enable a receiving UE to re-evaluate a set of available resources that may be suitable for a sidelink transmission by adjusting a measurement threshold, resulting in more consistent amount of available resources identified in inter-UE coordination information.

(93) FIG. 8 is an example diagram **800** illustrating a communication flow between UEs including the transmission of inter-UE coordination information, in accordance with the aspects presented herein. Both the UE **802** and the UE **804** in FIG. 8 may be operating under sidelink resource allocation Mode 2. The UE **802** in FIG. 8 may correspond with the UE-A **712** in FIG. 7A and/or the UE **702** in FIG. 7B and the UE **804** in FIG. 8 may correspond with the UE-B **714** in FIG. 7A and/or the UE **704** in FIG. 7B. In some aspects, the UE **802** may have a higher processing power and/or a higher battery capacity than the UE **804**. The UE **802** may perform sensing (e.g., as described in connection with FIGS. 5 and 6) to identify resources that are available for the UE **804**, at **810**. In some aspects, the UE **802** may generate a resource availability report **812** that the UE **802** transmits to other UEs. A resource availability report may refer to a set of information representing availability of each of one or more resources. As one example, each "0" represented in the resource

availability report **812** may indicate that a resource mapped to the “0” is unavailable for the UE **804** and each “1” represented in the resource availability report **812** may indicate that a resource mapped to the “1” is available for the UE **804**. Although the example is illustrated for a single UE receiving the availability report **812**, which may occur as a unicast, the UE **802** may similarly broadcast or groupcast the availability report **812** to multiple UEs, in some aspects. As part of the sensing, at **810**, the UE **802** may perform one or more sensing measurements, such as SIR measurements, RSRP measurements, RSRQ measurements, or the like. The UE **802** may compare a result of the sensing measurement on each of the resources to a measurement threshold. In some aspects, if the result of the sensing measurement on the resource is below than the measurement threshold, the UE **802** may determine that resource to be available for UE **804**. If the result of the sensing measurement on the resource is not below the measurement threshold, the UE **802** may determine that resource to be unavailable for UE **804**. In some aspects, if the result of the sensing measurement on the resource is above than the measurement threshold, the UE **802** may determine that resource to be available for UE **804**. If the result of the sensing measurement on the resource is not above the measurement threshold, the UE **802** may determine that resource to be unavailable for UE **804**.

(94) In some aspects, the measurement threshold may be associated with (e.g., may be a function of) one or more priorities of a packet associated with an associated transmission (such as the transmission **824**) of the UE **804**. In some aspects, the measurement threshold may be associated with (e.g., may be a function of) one or more modulation and coding scheme (MCS) associated with the UE **804**.

(95) In some aspects, the UE **802** may determine that the identified available resources identified at **810** (such as the resources indicated as available in the resource availability report **812**) may be unsuitably small for the UE **804**. For example, the UE **802** may determine that the identified available resources identified at **810** may be unsuitably small for the UE **804** by comparing a size of the available resources to an availability threshold. In some aspects, the size of the available resources and the availability threshold may be defined in terms of a total number of resources. In some aspects, the size of the available resources and the availability threshold may be defined in terms of a percentage compared with the resources that are being sensed. For example, the availability threshold may be 50%, and the UE **802** may determine the size of the available resources to be unsuitably small for UE **804** if the available resources are below 50% of the total amount of resources in the resource selection window. Upon determining the size of the available resources to be unsuitably small, the UE **802** may, at **814**, adjust a measurement threshold and re-identify available resources based on the adjusted measurement threshold. For example, the UE **802** may decrease a SIR threshold by a number of decibels (dBs), and then re-identify available resources based on the new SIR threshold by comparing SIR associated with the resources with the new SIR threshold. For each resource, if the SIR associated with the resource is above the SIR threshold, the resource may be determined by the UE **802** to be available for the UE **804**. In some aspects, the UE **802** may keep adjusting the measurement threshold and re-identify available resources based on the adjusted measurement threshold until a maximum allowed/minimum allowed measurement threshold is reached, or until the amount of available resources reach the availability threshold. As one example, the UE **802** may generate a resource availability report **816**. In some aspects, each “0” in the resource availability report **816** may indicate that a resource mapped to the “0” is unavailable for the UE **804** and each “1” in the resource availability report **816** may indicate that a resource mapped to the “1” is available for the UE **804**. As illustrated in FIG. 8, a size of the resources indicated as available in the resource availability report **816** may be above the availability threshold of 50% because more than 50% of the resources are available. In some aspects, the UE **802** may sort each of the available resources in a descending starting from the resource associated with a measurement furthest away from the measurement threshold. For example, the UE may sort all resources that have higher SIR than the SIR threshold in descending

order of SIR level.

(96) In some aspects, the UE **802** may provide a resource availability report **818** to the UE **804**. In some aspects, the resource availability report **818** may include the resource availability report **816**. In some aspects, the resource availability report **818** may include a report that sorts top X % available resources in a descending starting from the resource associated with a measurement furthest away from the measurement threshold. In some aspects, X may be defined based on an availability threshold or a different threshold. The UE may adjust the measurement threshold until a report that X % of available resources may be identified or until a maximum allowed/minimum allowed measurement threshold is reached.

(97) In some aspects, the UE **802** may also schedule one or more resources for the UE **804** by transmitting a resource reservation **820** to one or more UEs. In some aspects, the UE **802** may not schedule the one or more resources for the UE **804**. In some aspects, upon receiving the resource availability report **818**, the UE **804** may select one or more resources that are indicated as available in the resource availability report **818** for a transmission **824** to the UE **802**. In some aspects, as illustrated in 822 of FIG. **8**, the UE **804** may select (denoted by “S”) one or more resources indicated as being available in the resource availability report **818**. The UE **804** may use the one or more selected resources to transmit the transmission **824** to the UE **802**.

(98) FIG. **9** is a flowchart **900** of a method of wireless communication. The method may be performed by a UE (e.g., the UE **104**, the UE **702**, the UE **802**; the apparatus **1302**). The method may enable a receiving UE to re-identify a first set of available resources that may be suitable for the transmission of the transmitting UE by adjusting a measurement threshold, resulting in more efficient sidelink transmissions.

(99) At **902**, the UE may perform sensing on one or more SL resources to identify a first set of available resources. For example, the UE **802** may perform sensing on one or more SL resources to identify a first set of available resources at **810**. In some aspects, **902** may be performed by sensing component **1342** in FIG. **13**.

(100) At **904**, the UE may adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold. For example, the UE **802** may adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold at **814**. In some aspects, **904** may be performed by availability component **1344** in FIG. **13**. For example, the size may be defined based on a percentage relative to the one or more SL resources. As one example, if 50% of resources are available in the one or more SL resources, the size of the first set of available resources may be 50%.

(101) At **906**, the UE may transmit a sidelink message indicating a second set of available resources based on the second measurement threshold. For example, the UE **802** may transmit a sidelink message indicating a second set of available resources (e.g., the resource availability report **818**) that are available based on the second measurement threshold. In some aspects, **906** may be performed by SL component **1346** in FIG. **13**.

(102) FIG. **10** is a flowchart **1000** of a method of wireless communication. The method may be performed by a UE (e.g., the UE **104**, the UE **702**, the UE **802**; the apparatus **1302**). The method may enable a receiving UE to re-identify a first set of available resources that may be suitable for the transmission of the transmitting UE by adjusting a measurement threshold, resulting in more efficient sidelink transmissions.

(103) At **1002**, the UE may perform sensing on one or more SL resources to identify a first set of available resources. For example, the UE **802** may perform sensing on one or more SL resources to identify a first set of available resources at **810**. In some aspects, **1002** may be performed by sensing component **1342** in FIG. **13**.

(104) At **1004**, the UE may adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability

threshold. For example, the UE **802** may adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold at **814**. In some aspects, **1004** may be performed by availability component **1344** in FIG. **13**. In some aspects, the availability threshold may include a percentage of available resources from the one or more SL resources. For example, the size may be defined based on a percentage relative to the one or more SL resources. As one example, if 50% of resources are available in the one or more SL resources, the size of the first set of available resources may be 50%. In some aspects, the availability threshold may include a size of available resources from the one or more SL resources. In some aspects, the first measurement threshold is a first SIR ratio value, and the measurement second threshold is a second SIR ratio value. As one example, the first SIR ratio value may be lower or higher than the second SIR ratio value. In some aspects, the first SIR ratio value or the second SIR ratio value may be based on a function of one or more of a priority associated with a sidelink communication associated with a second UE based on the sensing or a MCS associated with the second UE. In some aspects, the first measurement threshold may be a first RSRQ threshold, and the second measurement threshold may be a second RSRQ threshold. The first RSRQ threshold may be lower or higher than the second RSRQ threshold. In some aspects, the second measurement threshold may be based on one or more of: a packet priority associated with a sidelink communication associated with a second UE, a MCS associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a HARQ ACK utilization status associated with the sidelink communication associated with the second UE, a channel busy ratio (CBR), or a distance between the UE and the second UE.

(105) At **1006**, the UE may transmit a sidelink message indicating a second set of available resources based on the second measurement threshold. For example, the UE **802** may transmit a sidelink message indicating a second set of available resources (e.g., the resource availability report **818**) that are available based on the second measurement threshold. In some aspects, **1006** may be performed by SL component **1346** in FIG. **13**. In some aspects, the second set of resources may be indicated in a resource availability report including a list of each resource in the second set of available resources based on the sensing. In some aspects, the second set of resources is indicated in a resource availability report including a top percentage of available resources based on the second measurement threshold.

(106) In some aspects, at **1008**, the UE may schedule at least one available resource of the second set of available resources for a second UE. For example, the UE **802** may schedule at least one available resource of the second set of available resources for a second UE **804** by transmitting a reservation **820**. The at least one available resource of the second set of available resources for a second UE may be used by the second UE to transmit a transmission to the UE, such as the transmission **824**. In some aspects, the UE may not schedule the at least one available resource of the second set of available resources for the second UE. In some aspects, **1008** may be performed by SL component **1346** in FIG. **13**.

(107) In some aspects, at **1010**, the UE may receive, from a second UE, a sidelink communication based on the sensing and carried by at least one available resource of the second set of available resources. For example, the UE **802** may receive, from a second UE **804**, a sidelink communication (e.g., the transmission **824**) based on the sensing and carried by at least one available resource of the second set of available resources.

(108) FIG. **11** is a flowchart **1100** of a method of wireless communication. The method may be performed by a UE (e.g., the UE **104**, the UE **702**, the UE **802**; the apparatus **1302**). The method may enable a receiving UE to re-identify a first set of available resources that may be suitable for the transmission of the transmitting UE by adjusting a measurement threshold, resulting in more efficient sidelink transmissions.

(109) At **1102**, the UE may perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. For example, the UE **802** may perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication at **810**. In some aspects, **1102** may be performed by sensing component **1342** in FIG. **13**.

(110) At **1104**, the UE may transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources. For example, the UE **802** may transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources (e.g., the resource availability report **818**). In some aspects, **1104** may be performed by SL component **1346** in FIG. **13**.

(111) FIG. **12** is a flowchart **1200** of a method of wireless communication. The method may be performed by a UE (e.g., the UE **104**, the UE **702**, the UE **802**; the apparatus **1302**). The method may enable a receiving UE to re-identify a first set of available resources that may be suitable for the transmission of the transmitting UE by adjusting a measurement threshold, resulting in more efficient sidelink transmissions.

(112) At **1202**, the UE may perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication. For example, the UE **802** may perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication at **810**. In some aspects, **1202** may be performed by sensing component **1342** in FIG. **13**.

(113) At **1204**, the UE may rank the one or more available resources based on the sensing measurement. The subset of the one or more available resources may correspond to a fraction of the one or more available resources having a lowest or highest sensing measurement. For example, the UE **802** may rank the one or more available resources based on the sensing measurement. In some aspects, **1204** may be performed by availability component **1344** in FIG. **13**.

(114) At **1206**, the UE may adjust a threshold for the sensing measurement based on a first set of available resources being below an availability threshold and further based on one or more of: a packet priority associated with a sidelink communication associated with a second UE, a MCS associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a HARQ ACK utilization status associated with the sidelink communication associated with the second UE, a CBR, or a distance between the UE and the second UE. For example, the UE **802** may adjust a measurement threshold at **814**. In some aspects, **1206** may be performed by availability component **1344** in FIG. **13**.

(115) At **1208**, the UE may transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources. For example, the UE **802** may transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources (e.g., the resource availability report **818**). In some aspects, **1208** may be performed by SL component **1346** in FIG. **13**. In some aspects, the subset corresponds to a percentage value of the one or more available resources of the one or more SL resources. In some aspects, the resource availability report indicates a ranking of each resource in the subset of the one or more available resources.

(116) FIG. **13** is a diagram **1300** illustrating an example of a hardware implementation for an apparatus **1302**. The apparatus **1302** may be a UE, a component of a UE, or may implement UE functionality. In some aspects, the apparatus **1302** may include a cellular baseband processor **1304** (also referred to as a modem) coupled to a cellular RF transceiver **1322**. In some aspects, the apparatus **1302** may further include one or more subscriber identity modules (SIM) cards **1320**, an application processor **1306** coupled to a secure digital (SD) card **1308** and a screen **1310**, a Bluetooth module **1312**, a wireless local area network (WLAN) module **1314**, a Global Positioning System (GPS) module **1316**, or a power supply **1318**. The cellular baseband processor **1304**

communicates through the cellular RF transceiver **1322** with the UE **104** and/or BS **102/180**. The cellular baseband processor **1304** may include a computer-readable medium/memory. The computer-readable medium/memory may be non-transitory. The cellular baseband processor **1304** is responsible for general processing, including the execution of software stored on the computer-readable medium/memory. The software, when executed by the cellular baseband processor **1304**, causes the cellular baseband processor **1304** to perform the various functions described supra. The computer-readable medium/memory may also be used for storing data that is manipulated by the cellular baseband processor **1304** when executing software. The cellular baseband processor **1304** further includes a reception component **1330**, a communication manager **1332**, and a transmission component **1334**. The communication manager **1332** includes the one or more illustrated components. The components within the communication manager **1332** may be stored in the computer-readable medium/memory and/or configured as hardware within the cellular baseband processor **1304**. The cellular baseband processor **1304** may be a component of the UE **350** and may include the memory **360** and/or at least one of the TX processor **368**, the RX processor **356**, and the controller/processor **359**. In one configuration, the apparatus **1302** may be a modem chip and include just the baseband processor **1304**, and in another configuration, the apparatus **1302** may be the entire UE (e.g., see **350** of FIG. 3) and include the additional modules of the apparatus **1302**.

(117) The communication manager **1332** may include a sensing component **1342** that is configured to perform sensing on one or more SL resources to identify a first set of available resources or perform a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication, e.g., as described in connection with **902** in FIG. 9, **1002** in FIG. 10, **1102** in FIG. 11, or **1202** in FIG. 12.

(118) The communication manager **1332** may further include an availability component **1344** that may be configured to adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold, rank the one or more available resources based on the sensing measurement, or adjust a measurement threshold, e.g., as described in connection with **904** in FIG. 9, **1004** in FIG. 10, or **1204** and **1206** in FIG. 12.

(119) The communication manager **1332** may further include an SL component **1346** that may be configured to transmit a sidelink message indicating a second set of available resources based on the second measurement threshold, schedule the at least one available resource of the second set of available resources for a second UE, receive, from a second UE, a sidelink communication based on the sensing and carried by at least one available resource of the second set of available resources, or transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources, e.g., as described in connection with **906** in FIG. 9, **1006**, **1008** or **1010** in FIG. 10, **1104** in FIG. 11, or **1208** in FIG. 12.

(120) The apparatus may include additional components that perform each of the blocks of the algorithm in the flowcharts of FIGS. 9-12. As such, each block in the flowcharts of FIGS. 9-12 may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

(121) As shown, the apparatus **1302** may include a variety of components configured for various functions. In one configuration, the apparatus **1302**, and in particular the cellular baseband processor **1304**, may include means for performing sensing on one or more of SL resources to identify a set of available resources, such as the sensing component **1342** or a transceiver. The cellular baseband processor **1304** may further include means for increasing a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold, such as the availability component **1344**. The cellular

baseband processor **1304** may further include means for transmitting a sidelink message indicating a second set of available resources based on the second measurement threshold, such as the SL component **1346** or a transceiver. The cellular baseband processor **1304** may further include means for receiving, from a second UE, a sidelink communication based on the sensing and carried by at least one available resource of the second set of available resources, such as the SL component **1346** or a transceiver. The cellular baseband processor **1304** may further include means for scheduling the at least one available resource of the second set of available resources for a second UE, such as the SL component **1346** or a transceiver. The cellular baseband processor **1304** may further include means for performing a sensing measurement on one or more SL resources to determine one or more available resources for sidelink communication, such as the sensing component **1342** or a transceiver. The cellular baseband processor **1304** may further include means for ranking the one or more available resources based on the sensing measurement, such as the availability component **1344**. The cellular baseband processor **1304** may further include means for adjusting a measurement threshold, such as the availability component **1344**. The cellular baseband processor **1304** may further include means for transmitting a sidelink message including a resource availability report indicating a subset of the one or more available resources, such as the SL component **1346** or a transceiver. The means may be one or more of the components of the apparatus **1302** configured to perform the functions recited by the means. As described supra, the apparatus **1302** may include the TX Processor **368**, the RX Processor **356**, and the controller/processor **359**. As such, in one configuration, the means may be the TX Processor **368**, the RX Processor **356**, and the controller/processor **359** configured to perform the functions recited by the means.

(122) It is understood that the specific order or hierarchy of blocks in the processes/flowcharts disclosed is an illustration of example approaches. Based upon design preferences, it is understood that the specific order or hierarchy of blocks in the processes/flowcharts may be rearranged. Further, some blocks may be combined or omitted. The accompanying method claims present elements of the various blocks in a sample order, and are not meant to be limited to the specific order or hierarchy presented.

(123) The previous description is provided to enable any person skilled in the art to practice the various aspects described herein. Various modifications to these aspects will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other aspects. Thus, the claims are not intended to be limited to the aspects shown herein, but is to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.” Terms such as “if,” “when,” and “while” should be interpreted to mean “under the condition that” rather than imply an immediate temporal relationship or reaction. That is, these phrases, e.g., “when,” do not imply an immediate action in response to or during the occurrence of an action, but simply imply that if a condition is met then an action will occur, but without requiring a specific or immediate time constraint for the action to occur. The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects. Unless specifically stated otherwise, the term “some” refers to one or more. Combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” include any combination of A, B, and/or C, and may include multiples of A, multiples of B, or multiples of C. Specifically, combinations such as “at least one of A, B, or C,” “one or more of A, B, or C,” “at least one of A, B, and C,” “one or more of A, B, and C,” and “A, B, C, or any combination thereof” may be A only, B only, C only, A and B, A and C, B and C, or A and B and C, where any such combinations may contain one or more member or members of A, B, or C. All structural and functional equivalents to the elements of the various aspects described throughout this disclosure that are known or later come to be known to those of

ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. The words “module,” “mechanism,” “element,” “device,” and the like may not be a substitute for the word “means.” As such, no claim element is to be construed as a means plus function unless the element is expressly recited using the phrase “means for.”

(124) The following aspects are illustrative only and may be combined with other aspects or teachings described herein, without limitation.

(125) Aspect 1 is an apparatus for wireless communication at a first UE, comprising: a memory; and at least one processor coupled to the memory, the memory and the at least one processor configured to: perform sensing on one or more SL resources to identify a first set of available resources; adjust a first measurement threshold to a second measurement threshold based on a size of the first set of available resources being below an availability threshold; and transmit a sidelink message indicating a second set of available resources based on the second measurement threshold.

(126) Aspect 2 is the apparatus of aspect 1, wherein the at least one processor and the memory are further configured to: receive, from a second UE, a sidelink communication and carried by at least one available resource of the second set of available resources.

(127) Aspect 3 is the apparatus of any of aspects 1-2, wherein the at least one processor coupled to the memory are further configured to: schedule the at least one available resource of the second set of available resources for the second UE.

(128) Aspect 4 is the apparatus of any of aspects 1-3, wherein the first measurement threshold is a first SIR ratio value, and wherein the second measurement threshold is a second SIR ratio value, the first SIR ratio value being higher than the second SIR ratio value.

(129) Aspect 5 is the apparatus of any of aspects 1-4, wherein the first SIR ratio value or the second SIR ratio value is based on a function of one or more of: a priority associated with a sidelink communication associated with a second UE or a MCS associated with the second UE.

(130) Aspect 6 is the apparatus of any of aspects 1-5, wherein the first measurement threshold is a first RSRQ threshold, and wherein the second measurement threshold is a second RSRQ threshold, the first RSRQ threshold being higher than the second RSRQ threshold.

(131) Aspect 7 is the apparatus of any of aspects 1-6, wherein the availability threshold comprises a percentage of available resources from the one or more SL resources.

(132) Aspect 8 is the apparatus of any of aspects 1-7, wherein the availability threshold comprises a threshold size of available resources from the one or more SL resources.

(133) Aspect 9 is the apparatus of any of aspects 1-8, wherein the second set of available resources is indicated in a resource availability report comprising a list of each resource in the second set of available resources.

(134) Aspect 10 is the apparatus of any of aspects 1-9, wherein the second set of available resources is indicated in a resource availability report comprising a top percentage of available resources based on the second measurement threshold.

(135) Aspect 11 is the apparatus of any of aspects 1-10, wherein the second measurement threshold is based on one or more of: a packet priority associated with a sidelink communication associated with a second UE, a MCS associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a HARQ ACK utilization status associated with the sidelink communication associated with the second UE, a CBR, or a distance between the first UE and the second UE.

(136) Aspect 12 is the apparatus of any of aspects 1-11, further comprising an antenna coupled to the at least one processor.

(137) Aspect 13 is an apparatus for wireless communication at a first UE, comprising: a memory; and at least one processor coupled to the memory and configured to: perform a sensing

measurement on one or more SL resources to determine one or more available resources for sidelink communication; and transmit a sidelink message including a resource availability report indicating a subset of the one or more available resources.

(138) Aspect 14 is the apparatus of aspect 13, wherein the subset corresponds to a percentage value of the one or more available resources of the one or more SL resources.

(139) Aspect 15 is the apparatus of any of aspects 13-14, wherein the at least one processor and the memory are further configured to: rank the one or more available resources based on the sensing measurement, wherein the subset of the one or more available resources correspond to a fraction of the one or more available resources having a lowest sensing measurement.

(140) Aspect 16 is the apparatus of any of aspects 13-15, wherein the resource availability report indicates a ranking of each resource in the subset of the one or more available resources.

(141) Aspect 17 is the apparatus of any of aspects 13-16, wherein the at least one processor coupled to the memory are further configured to: adjust a threshold for the sensing measurement based on a first set of available resources being below an availability threshold and further based on one or more of: a packet priority associated with the sidelink communication associated with a second UE, a MCS associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a HARQ ACK utilization status associated with the sidelink communication associated with the second UE, a CBR, or a distance between the first UE and the second UE.

(142) Aspect 18 is the apparatus of any of aspects 13-17, further comprising an antenna coupled to the at least one processor.

(143) Aspect 19 is a method of wireless communication for implementing any of aspects 1 to 12.

(144) Aspect 20 is an apparatus for wireless communication including means for implementing any of aspects 1 to 12.

(145) Aspect 21 is a computer-readable medium storing computer executable code, where the code when executed by a processor causes the processor to implement any of aspects 1 to 12.

(146) Aspect 22 is a method of wireless communication for implementing any of aspects 13 to 18.

(147) Aspect 23 is an apparatus for wireless communication including means for implementing any of aspects 13 to 18.

(148) Aspect 24 is a computer-readable medium storing computer executable code, where the code when executed by a processor causes the processor to implement any of aspects 13 to 18.

## Claims

1. An apparatus for wireless communication at a first user equipment (UE), comprising: memory; and one or more processors coupled to the memory and configured to cause the first UE to: perform sensing on one or more sidelink (SL) resources to identify a first set of one or more preferred resources or a first set of one or more non-preferred resources for a transmission from a second UE; adjust a first measurement threshold to a second measurement threshold based on a size of a first set of available resources that is below an availability threshold, the size of the first set of available resources associated with the first set of one or more preferred resources or the first set of one or more non-preferred resources for the transmission from the second UE; and transmit, to the second UE, inter-UE coordination information that indicates a second set of one or more preferred resources or a second set of one or more non-preferred resources based on the second measurement threshold, wherein the second set of one or more preferred resources or the second set of one or more non-preferred resources indicates at least one preferred resource for the transmission from the second UE or indicates at least one non-preferred resource for the transmission from the second UE.

2. The apparatus of claim 1, wherein the one or more processors are further configured to cause the

first UE to: receive, from the second UE, a sidelink communication carried by the at least one preferred resource.

3. The apparatus of claim 2, wherein the one or more processors are further configured to cause the first UE to: schedule the at least one preferred resource for the second UE.
4. The apparatus of claim 1, wherein the first measurement threshold is a first signal to interference (SIR) ratio value, wherein the second measurement threshold is a second SIR ratio value, and wherein the first SIR ratio value is higher than the second SIR ratio value.
5. The apparatus of claim 4, wherein the first SIR ratio value or the second SIR ratio value is based on a function of one or more of: a priority associated with a sidelink communication associated with the second UE or a modulation and coding scheme (MCS) associated with the second UE.
6. The apparatus of claim 1, wherein the first measurement threshold is a first reference signal received quality (RSRQ) threshold, wherein the second measurement threshold is a second RSRQ threshold, and wherein the first RSRQ threshold is higher than the second RSRQ threshold.
7. The apparatus of claim 1, wherein the availability threshold comprises a percentage of available resources from the one or more SL resources.
8. The apparatus of claim 1, wherein the availability threshold comprises a threshold size of available resources from the one or more SL resources.
9. The apparatus of claim 1, wherein the second set of one or more preferred resources is indicated in a resource availability report that comprises a list of each resource in the second set of one or more preferred resources.
10. The apparatus of claim 1, wherein the second set of one or more preferred resources is indicated in a resource availability report that comprises a top percentage of preferred resources based on the second measurement threshold.
11. The apparatus of claim 1, further comprising one or more antennas coupled to the one or more processors, and wherein the second measurement threshold is based on one or more of: a packet priority associated with a sidelink communication associated with the second UE, a modulation and coding scheme (MCS) associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a hybrid automatic repeat request (HARQ) acknowledgment (ACK) utilization status associated with the sidelink communication associated with the second UE, a channel busy ratio (CBR), or a distance between the first UE and the second UE.
12. The apparatus of claim 11, wherein the second measurement threshold is based on the packet priority associated with the sidelink communication associated with the second UE.
13. The apparatus of claim 11, wherein the second measurement threshold is based on the MCS associated with the second UE.
14. The apparatus of claim 11, wherein the second measurement threshold is based on the cast type associated with the second UE.
15. The apparatus of claim 11, wherein the second measurement threshold is based on the remaining packet delay budget associated with the sidelink communication associated with the second UE.
16. The apparatus of claim 11, wherein the second measurement threshold is based on the communication range specification associated with the second UE.
17. The apparatus of claim 11, wherein the second measurement threshold is based on the HARQ ACK utilization status associated with the sidelink communication associated with the second UE.
18. The apparatus of claim 11, wherein the second measurement threshold is based on the CBR.
19. The apparatus of claim 11, wherein the second measurement threshold is based on the distance between the first UE and the second UE.
20. The apparatus of claim 1, wherein the inter-UE coordination information indicates the second set of one or more preferred resources, wherein the second set of one or more preferred resources

includes a second set of available resources.

21. The apparatus of claim 1, wherein the one or more processors are coupled to a transceiver and individually or in combination configured to cause the first UE to perform the sensing on the one or more SL resources, adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources that is below the availability threshold, and transmit the inter-UE coordination information that indicates a second set of available resources.

22. The apparatus of claim 1, wherein the one or more processors are configured to cause the first UE to: increase the first measurement threshold to the second measurement threshold.

23. The apparatus of claim 1, wherein the first measurement threshold and the second measurement threshold are for a reference signal received power (RSRP) measurement.

24. The apparatus of claim 1, wherein to adjust the first measurement threshold to the second measurement threshold, the one or more processors are configured to cause the first UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more preferred resources that is below the availability threshold.

25. The apparatus of claim 1, wherein to adjust the first measurement threshold to the second measurement threshold, the one or more processors are configured to cause the first UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more non-preferred resources that is below the availability threshold.

26. The apparatus of claim 1, wherein to perform the sensing, the one or more processors are configured to cause the first UE to perform the sensing on the one or more SL resources to identify the first set of one or more preferred resources for the transmission from the second UE; wherein to adjust the first measurement threshold to the second measurement threshold, the one or more processors are configured to cause the first UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more preferred resources that is below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more preferred resources, and wherein the second set of one or more preferred resources indicates the at least one preferred resource for the transmission from the second UE.

27. The apparatus of claim 1, wherein to perform the sensing, the one or more processors are configured to cause the first UE to perform the sensing on the one or more SL resources to identify the first set of one or more non-preferred resources for the transmission from the second UE; wherein to adjust the first measurement threshold to the second measurement threshold, the one or more processors are configured to cause the first UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more non-preferred resources that is below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more non-preferred resources, and wherein the second set of one or more non-preferred resources indicates the at least one non-preferred resource for the transmission from the second UE.

28. A method for wireless communication at a first user equipment (UE), comprising: performing sensing on one or more sidelink (SL) resources to identify a first set of one or more preferred resources or a first set of one or more non-preferred resources for a transmission from a second UE; adjusting a first measurement threshold to a second measurement threshold based on a size of a first set of available resources that is below an availability threshold, the size of the first set of available resources associated with the first set of one or more preferred resources or the first set of one or more non-preferred resources for the transmission from the second UE; and transmitting, to the second UE, inter-UE coordination information that indicates a second set of one or more preferred resources or a second set of one or more non-preferred resources based on the second measurement threshold, wherein the second set of one or more preferred resources or the second set

of one or more non-preferred resources indicates at least one preferred resource for the transmission from the second UE or indicates at least one non-preferred resource for the transmission from the second UE.

29. The method of claim 28, further comprising: receive, from the second UE, a sidelink communication carried by the at least one preferred resource.

30. The method of claim 29, further comprising: scheduling the at least one preferred resource for the second UE.

31. The method of claim 28, wherein the first measurement threshold is a first signal to interference (SIR) ratio value, wherein the second measurement threshold is a second SIR ratio value, and wherein the first SIR ratio value is higher than the second SIR ratio value.

32. The method of claim 28, wherein the availability threshold comprises a percentage of available resources from the one or more SL resources.

33. The method of claim 28, wherein the availability threshold comprises a threshold size of available resources from the one or more SL resources.

34. The method of claim 28, wherein the second set of one or more preferred resources is indicated in a resource availability report comprising a list of each resource in the second set of one or more preferred resources.

35. The method of claim 28, wherein the second set of one or more preferred resources is indicated in a resource availability report comprising a top percentage of preferred resources based on the second measurement threshold.

36. The method of claim 28, wherein the second measurement threshold is based on one or more of: a packet priority associated with a sidelink communication associated with the second UE, a modulation and coding scheme (MCS) associated with the second UE, a cast type associated with the second UE, a remaining packet delay budget associated with the sidelink communication associated with the second UE, a communication range specification associated with the second UE, a hybrid automatic repeat request (HARQ) acknowledgment (ACK) utilization status associated with the sidelink communication associated with the second UE, a channel busy ratio (CBR), or a distance between the first UE and the second UE.

37. The method of claim 36, wherein the second measurement threshold is based on the packet priority associated with the sidelink communication associated with the second UE.

38. The method of claim 36, wherein the second measurement threshold is based on the MCS associated with the second UE.

39. The method of claim 36, wherein the second measurement threshold is based on the cast type associated with the second UE.

40. The method of claim 36, wherein the second measurement threshold is based on the remaining packet delay budget associated with the sidelink communication associated with the second UE.

41. The method of claim 36, wherein the second measurement threshold is based on the communication range specification associated with the second UE.

42. The method of claim 36, wherein the second measurement threshold is based on the HARQ ACK utilization status associated with the sidelink communication associated with the second UE.

43. The method of claim 36, wherein the second measurement threshold is based on the CBR.

44. The method of claim 36, wherein the second measurement threshold is based on the distance between the first UE and the second UE.

45. The method of claim 28, wherein the inter-UE coordination information indicates the second set of one or more preferred resources, wherein the second set of one or more preferred resources includes a second set of available resources.

46. The method of claim 28, wherein adjusting the first measurement threshold to the second measurement threshold comprises increasing the first measurement threshold to the second measurement threshold.

47. The method of claim 28, wherein the first measurement threshold and the second measurement

threshold are for a reference signal received power (RSRP) measurement.

48. The method of claim 28, wherein performing the sensing includes performing the sensing on the one or more SL resources to identify the first set of one or more preferred resources for the transmission from the second UE; wherein adjusting the first measurement threshold to the second measurement threshold includes adjusting the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more preferred resources being below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more preferred resources, and wherein the second set of one or more preferred resources indicates the at least one preferred resource for the transmission from the second UE.

49. The method of claim 28, wherein performing the sensing includes performing the sensing on the one or more SL resources to identify the first set of one or more non-preferred resources for the transmission from the second UE; wherein adjusting the first measurement threshold to the second measurement threshold includes adjusting the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more non-preferred resources being below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more non-preferred resources, and wherein the second set of one or more non-preferred resources indicates the at least one non-preferred resource for the transmission from the second UE.

50. An apparatus for wireless communication at a first user equipment (UE), comprising: means for performing sensing on one or more sidelink (SL) resources to identify a first set of one or more preferred resources or a first set of one or more non-preferred resources for a transmission from a second UE; means for adjusting a first measurement threshold to a second measurement threshold based on a size of a first set of available resources that is below an availability threshold, the size of the first set of available resources associated with the first set of one or more preferred resources or the first set of one or more non-preferred resources for the transmission from the second UE; and means for transmitting, to the second UE, inter-UE coordination information that indicates a second set of one or more preferred resources or a second set of one or more non-preferred resources based on the second measurement threshold, wherein the second set of one or more preferred resources or the second set of one or more non-preferred resources indicates at least one preferred resource for the transmission from the second UE or indicates at least one non-preferred resource for the transmission from the second UE.

51. The apparatus of claim 50, further comprising: means for receiving, from the second UE, a sidelink communication carried by the at least one preferred resource.

52. The apparatus of claim 50, wherein the inter-UE coordination information indicates the second set of one or more preferred resources, wherein the second set of one or more preferred resources includes a second set of available resources.

53. The apparatus of claim 50, wherein the means for performing the sensing includes means for performing the sensing on the one or more SL resources to identify the first set of one or more preferred resources for the transmission from the second UE; wherein the means for adjusting the first measurement threshold to the second measurement threshold includes means for adjusting the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more preferred resources that is below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more preferred resources, and wherein the second set of one or more preferred resources indicates the at least one preferred resource for the transmission from the second UE.

54. The apparatus of claim 50, wherein the means for performing the sensing includes means for performing the sensing on the one or more SL resources to identify the first set of one or more non-preferred resources for the transmission from the second UE; wherein the means for adjusting the first measurement threshold to the second measurement threshold includes means for adjusting the

first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more non-preferred resources that is below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more non-preferred resources, and wherein the second set of one or more non-preferred resources indicates the at least one non-preferred resource for the transmission from the second UE.

55. A non-transitory computer-readable medium storing computer executable code at a user equipment (UE), the code when executed by one or more processors causes the UE to: perform sensing on one or more sidelink (SL) resources to identify a first set of one or more preferred resources or a first set of one or more non-preferred resources for a transmission from a second UE; adjust a first measurement threshold to a second measurement threshold based on a size of a first set of available resources that is below an availability threshold, the size of the first set of available resources associated with the first set of one or more preferred resources or the first set of one or more non-preferred resources for the transmission from the second UE; and transmit, to the second UE, inter-UE coordination information that indicates a second set of one or more preferred resources or a second set of one or more non-preferred resources based on the second measurement threshold, wherein the second set of one or more preferred resources or the second set of one or more non-preferred resources indicates at least one preferred resource for the transmission from the second UE or indicates at least one non-preferred resource for the transmission from the second UE.

56. The non-transitory computer-readable medium of claim 55, further comprising: receive, from the second UE, a sidelink communication carried by the at least one preferred resource.

57. The non-transitory computer-readable medium of claim 55, wherein the inter-UE coordination information indicates the second set of one or more preferred resources, wherein the second set of one or more preferred resources includes a second set of available resources.

58. The non-transitory computer-readable medium of claim 55, wherein to adjust the first measurement threshold to the second measurement threshold, the code when executed by the one or more processors causes the UE to increase the first measurement threshold to the second measurement threshold.

59. The non-transitory computer-readable medium of claim 55, wherein the first measurement threshold and the second measurement threshold are for a reference signal received power (RSRP) measurement.

60. The non-transitory computer-readable medium of claim 55, wherein to perform the sensing, the code when executed by the one or more processors causes the UE to perform the sensing on the one or more SL resources to identify the first set of one or more preferred resources for the transmission from the second UE; wherein to adjust the first measurement threshold to the second measurement threshold, the code when executed by the one or more processors causes the UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more preferred resources that is below the availability threshold; and wherein the inter-UE coordination information indicates the second set of one or more preferred resources, and wherein the second set of one or more preferred resources indicates the at least one preferred resource for the transmission from the second UE.

61. The non-transitory computer-readable medium of claim 55, wherein to perform the sensing, the code when executed by the one or more processors causes the UE to perform the sensing on the one or more SL resources to identify the first set of one or more non-preferred resources for the transmission from the second UE; wherein to adjust the first measurement threshold to the second measurement threshold, the code when executed by the one or more processors causes the UE to adjust the first measurement threshold to the second measurement threshold based on the size of the first set of available resources associated with the first set of one or more non-preferred resources that is below the availability threshold; and wherein the inter-UE coordination

information indicates the second set of one or more non-preferred resources, and wherein the second set of one or more non-preferred resources indicates the at least one non-preferred resource for the transmission from the second UE.

---