

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396743
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Martin; Brian B. et al.

Retrieval systems and methods for use thereof

Abstract

The devices and methods described herein relate to improved structures for removing obstructions from body lumens. Such devices have applicability in through-out the body, including clearing of blockages within the vasculature, by addressing the frictional resistance on the obstruction prior to attempting to translate and/or mobilize the obstruction within the body lumen.

Inventors:	Martin; Brian B. (Felton, CA), Dieck; Martin S. (Campbell, CA)
Applicant:	Covidien LP (Mansfield, MA)
Family ID:	1000008777862
Assignee:	Covidien LP (Mansfield, MA)
Appl. No.:	18/056199
Filed:	November 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230074271 A1	Mar. 09, 2023

Related U.S. Application Data

continuation parent-doc US 16530101 20190802 US 11529155 child-doc US 18056199
continuation parent-doc US 15946466 20180405 US 11213307 20220104 child-doc US 16530101
continuation parent-doc US 15174016 20160606 US 9943323 20180417 child-doc US 15946466
continuation parent-doc US 14446755 20140730 US 9358094 20160607 child-doc US 15174016
continuation parent-doc US 13959433 20130805 US 8795305 20140805 child-doc US 14446755
continuation parent-doc WO PCT/US2012/039216 20120523 PENDING child-doc US 13959433
us-provisional-application US 61489254 20110524
us-provisional-application US 61489183 20110523

Publication Classification

Int. Cl.: **A61B17/221** (20060101); **A61B17/22** (20060101); **A61B17/3207** (20060101); **A61F2/01** (20060101); **A61F2/06** (20130101); **A61F2/95** (20130101); **A61F2/962** (20130101); **A61B17/34** (20060101)

U.S. Cl.:

CPC **A61B17/221** (20130101); **A61B17/22031** (20130101); **A61B17/3207** (20130101); **A61B17/320758** (20130101); **A61F2/01** (20130101); **A61F2/06** (20130101); **A61F2/95** (20130101); **A61F2/962** (20130101); **A61B2017/22034** (20130101); **A61B2017/3435** (20130101); **A61B2560/04** (20130101); **A61F2/011** (20200501); **A61F2230/0006** (20130101); **A61F2230/0093** (20130101); **A61F2250/0098** (20130101)

Field of Classification Search

CPC: **A61B** (17/221); **A61B** (2017/22034); **A61F** (2230/0006); **A61F** (2002/018); **A61F** (2/013); **A61F** (2230/008); **A61F** (2002/011); **A61F** (2/95); **A61F** (2230/0067); **A61F** (2/01); **A61F** (2/962); **A61F** (2230/0069); **A61F** (2230/0093); **A61F** (2002/015)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2918919	12/1958	Wallace	N/A	N/A
2943626	12/1959	Enrico	N/A	N/A
3996938	12/1975	Clark	N/A	N/A
4347846	12/1981	Dormia	N/A	N/A
4611594	12/1985	Grayhack et al.	N/A	N/A
4650466	12/1986	Luther	N/A	N/A
4657020	12/1986	Lifton	N/A	N/A
4699147	12/1986	Chilson et al.	N/A	N/A
4790812	12/1987	Hawkins et al.	N/A	N/A
4807626	12/1988	McGirr	N/A	N/A
4832055	12/1988	Palestrant	N/A	N/A
4873978	12/1988	Ginsburg	N/A	N/A
4969891	12/1989	Gewertz	N/A	N/A
4998539	12/1990	Delsanti	N/A	N/A
5034001	12/1990	Garrison et al.	N/A	N/A
5057114	12/1990	Wittich et al.	N/A	N/A
5059178	12/1990	Ya	N/A	N/A
5102415	12/1991	Guenther et al.	N/A	N/A
5147400	12/1991	Kaplan et al.	N/A	N/A
5152777	12/1991	Goldberg et al.	N/A	N/A
5192286	12/1992	Phan et al.	N/A	N/A
5300086	12/1993	Gory et al.	N/A	N/A
5329942	12/1993	Gunther et al.	N/A	N/A
5443478	12/1994	Purdy	N/A	N/A
5449372	12/1994	Schmaltz et al.	N/A	N/A

5458375	12/1994	Anspach et al.	N/A	N/A
5490859	12/1995	Mische et al.	N/A	N/A
5496330	12/1995	Bates et al.	N/A	N/A
5509900	12/1995	Kirkman	N/A	N/A
5653684	12/1996	Laptewicz et al.	N/A	N/A
5658296	12/1996	Bates et al.	N/A	N/A
5709704	12/1997	Nott et al.	N/A	N/A
5733302	12/1997	Myler et al.	N/A	N/A
5741325	12/1997	Chaikof et al.	N/A	N/A
5792156	12/1997	Perouse	N/A	N/A
5827324	12/1997	Cassell et al.	N/A	N/A
5846251	12/1997	Hart	N/A	N/A
5895398	12/1998	Wensel et al.	N/A	N/A
5941869	12/1998	Patterson et al.	N/A	N/A
5947995	12/1998	Samuels	N/A	N/A
5968090	12/1998	Ratcliff et al.	N/A	N/A
5971938	12/1998	Hart et al.	N/A	N/A
5972019	12/1998	Engelson et al.	N/A	N/A
5984957	12/1998	Laptewicz et al.	N/A	N/A
6001118	12/1998	Daniel et al.	N/A	N/A
6033394	12/1999	Vidlund et al.	N/A	N/A
6042598	12/1999	Tsugita et al.	N/A	N/A
6053932	12/1999	Daniel et al.	N/A	N/A
6066149	12/1999	Samson et al.	N/A	N/A
6066158	12/1999	Engelson et al.	N/A	N/A
6096053	12/1999	Bates	N/A	N/A
6099534	12/1999	Bates et al.	N/A	N/A
6146403	12/1999	St	N/A	N/A
6159220	12/1999	Gobron et al.	N/A	N/A
6165200	12/1999	Tsugita et al.	N/A	N/A
6168603	12/2000	Leslie et al.	N/A	N/A
6174318	12/2000	Bates et al.	N/A	N/A
6176873	12/2000	Ouchi	N/A	N/A
6190394	12/2000	Lind et al.	N/A	N/A
6217609	12/2000	Haverkost	N/A	N/A
6221006	12/2000	Dubrul et al.	N/A	N/A
6245088	12/2000	Lowery	N/A	N/A
6245089	12/2000	Daniel et al.	N/A	N/A
6248113	12/2000	Fina	N/A	N/A
6264664	12/2000	Avellanet	N/A	N/A
6302895	12/2000	Gobron et al.	N/A	N/A
6309399	12/2000	Barbut et al.	N/A	N/A
6348056	12/2001	Bates et al.	N/A	N/A
6350266	12/2001	White et al.	N/A	N/A
6364895	12/2001	Greenhalgh	N/A	N/A
6371971	12/2001	Tsugita et al.	N/A	N/A
6383195	12/2001	Richard	N/A	N/A
6383196	12/2001	Leslie et al.	N/A	N/A
6391044	12/2001	Yadav et al.	N/A	N/A
6402771	12/2001	Palmer et al.	N/A	N/A

6409750	12/2001	Hyodoh et al.	N/A	N/A
6416505	12/2001	Fleischman et al.	N/A	N/A
6425909	12/2001	Dieck et al.	N/A	N/A
6436112	12/2001	Wensel et al.	N/A	N/A
6443972	12/2001	Bosma et al.	N/A	N/A
6458139	12/2001	Palmer et al.	N/A	N/A
6485497	12/2001	Wensel et al.	N/A	N/A
6494884	12/2001	Gifford et al.	N/A	N/A
6506204	12/2002	Mazzocchi	N/A	N/A
6514273	12/2002	Voss et al.	N/A	N/A
6530935	12/2002	Wensel et al.	N/A	N/A
6540657	12/2002	Cross et al.	N/A	N/A
6540768	12/2002	Diaz et al.	N/A	N/A
6551342	12/2002	Shen et al.	N/A	N/A
6575997	12/2002	Palmer et al.	N/A	N/A
6585753	12/2002	Eder et al.	N/A	N/A
6592605	12/2002	Lenker et al.	N/A	N/A
6592607	12/2002	Palmer et al.	N/A	N/A
6602271	12/2002	Adams et al.	N/A	N/A
6605102	12/2002	Mazzocchi et al.	N/A	N/A
6610077	12/2002	Hancock et al.	N/A	N/A
6616679	12/2002	Khosravi et al.	N/A	N/A
6620148	12/2002	Tsugita	N/A	N/A
6635068	12/2002	Dubrul et al.	N/A	N/A
6636758	12/2002	Sanchez et al.	N/A	N/A
6638245	12/2002	Miller et al.	N/A	N/A
6638293	12/2002	Makower et al.	N/A	N/A
6641590	12/2002	Palmer et al.	N/A	N/A
6645199	12/2002	Jenkins et al.	N/A	N/A
6652505	12/2002	Tsugita	N/A	N/A
6652548	12/2002	Evans et al.	N/A	N/A
6660021	12/2002	Palmer et al.	N/A	N/A
6663650	12/2002	Sepetka et al.	N/A	N/A
6673042	12/2003	Samson et al.	N/A	N/A
6679893	12/2003	Tran	N/A	N/A
6685738	12/2003	Chouinard et al.	N/A	N/A
6692508	12/2003	Wensel et al.	N/A	N/A
6692509	12/2003	Wensel et al.	N/A	N/A
6695858	12/2003	Dubrul et al.	N/A	N/A
6702782	12/2003	Miller et al.	N/A	N/A
6730104	12/2003	Sepetka et al.	N/A	N/A
6745080	12/2003	Koblish	N/A	N/A
6746468	12/2003	Sepetka et al.	N/A	N/A
6749619	12/2003	Ouriel et al.	N/A	N/A
6755813	12/2003	Ouriel et al.	N/A	N/A
6800080	12/2003	Bates	N/A	N/A
6824545	12/2003	Sepetka et al.	N/A	N/A
6855155	12/2004	Denardo et al.	N/A	N/A
6872211	12/2004	White et al.	N/A	N/A
6872216	12/2004	Daniel et al.	N/A	N/A

6890341	12/2004	Dieck et al.	N/A	N/A
6893431	12/2004	Naimark et al.	N/A	N/A
6905503	12/2004	Gifford et al.	N/A	N/A
6913612	12/2004	Palmer et al.	N/A	N/A
6936059	12/2004	Belef	N/A	N/A
6939362	12/2004	Boyle et al.	N/A	N/A
6945977	12/2004	Demarais et al.	N/A	N/A
6953465	12/2004	Dieck et al.	N/A	N/A
6964672	12/2004	Brady et al.	N/A	N/A
7004955	12/2005	Shen et al.	N/A	N/A
7004956	12/2005	Palmer et al.	N/A	N/A
7037320	12/2005	Brady et al.	N/A	N/A
7041126	12/2005	Shin et al.	N/A	N/A
7048014	12/2005	Hyodoh et al.	N/A	N/A
7058456	12/2005	Pierce	N/A	N/A
7097653	12/2005	Freudenthal et al.	N/A	N/A
7101380	12/2005	Khachin et al.	N/A	N/A
7169165	12/2006	Belef et al.	N/A	N/A
7179273	12/2006	Palmer et al.	N/A	N/A
7182771	12/2006	Houser et al.	N/A	N/A
7235061	12/2006	Tsugita	N/A	N/A
7240516	12/2006	Pryor	N/A	N/A
7399308	12/2007	Borillo et al.	N/A	N/A
7534252	12/2008	Sepetka et al.	N/A	N/A
7578830	12/2008	Kusleika et al.	N/A	N/A
7621870	12/2008	Berrada et al.	N/A	N/A
7837702	12/2009	Bates	N/A	N/A
8070791	12/2010	Ferrera et al.	N/A	N/A
8088140	12/2011	Ferrera et al.	N/A	N/A
8105333	12/2011	Sepetka et al.	N/A	N/A
8197493	12/2011	Ferrera et al.	N/A	N/A
8603014	12/2012	Alleman et al.	N/A	N/A
8795305	12/2013	Martin et al.	N/A	N/A
8837800	12/2013	Bammer et al.	N/A	N/A
8932319	12/2014	Martin et al.	N/A	N/A
9119656	12/2014	Bose et al.	N/A	N/A
9126018	12/2014	Garrison	N/A	N/A
9211132	12/2014	Bowman	N/A	N/A
9241699	12/2015	Kume et al.	N/A	N/A
9265512	12/2015	Garrison et al.	N/A	N/A
9308007	12/2015	Cully et al.	N/A	N/A
9358094	12/2015	Martin et al.	N/A	N/A
9399118	12/2015	Kume et al.	N/A	N/A
9445828	12/2015	Turjman et al.	N/A	N/A
9445829	12/2015	Brady et al.	N/A	N/A
9492637	12/2015	Garrison et al.	N/A	N/A
9539022	12/2016	Bowman	N/A	N/A
9561345	12/2016	Garrison et al.	N/A	N/A
9579119	12/2016	Cully et al.	N/A	N/A

9585741	12/2016	Ma	N/A	N/A
9642635	12/2016	Vale et al.	N/A	N/A
9655633	12/2016	Leynov et al.	N/A	N/A
9737318	12/2016	Monstadt et al.	N/A	N/A
9770251	12/2016	Bowman et al.	N/A	N/A
9801643	12/2016	Hansen et al.	N/A	N/A
9861783	12/2017	Garrison et al.	N/A	N/A
9943323	12/2017	Martin et al.	N/A	N/A
9993257	12/2017	Losordo et al.	N/A	N/A
10028782	12/2017	Orion	N/A	N/A
10029008	12/2017	Creighton	N/A	N/A
10039906	12/2017	Kume et al.	N/A	N/A
11529155	12/2021	Martin et al.	N/A	N/A
2001/0041909	12/2000	Tsugita et al.	N/A	N/A
2001/0044632	12/2000	Daniel et al.	N/A	N/A
2001/0044634	12/2000	Don et al.	N/A	N/A
2001/0051810	12/2000	Dubrul et al.	N/A	N/A
2002/0002396	12/2001	Fulkerson	N/A	N/A
2002/0004667	12/2001	Adams et al.	N/A	N/A
2002/0026211	12/2001	Khosravi et al.	N/A	N/A
2002/0058904	12/2001	Boock et al.	N/A	N/A
2002/0062135	12/2001	Mazzocchi et al.	N/A	N/A
2002/0072764	12/2001	Sepetka et al.	N/A	N/A
2002/0082558	12/2001	Samson et al.	N/A	N/A
2002/0123765	12/2001	Sepetka et al.	N/A	N/A
2002/0138094	12/2001	Borillo et al.	N/A	N/A
2002/0151928	12/2001	Leslie et al.	N/A	N/A
2002/0169474	12/2001	Kusleika et al.	N/A	N/A
2002/0188314	12/2001	Anderson et al.	N/A	N/A
2002/0193825	12/2001	McGuckin et al.	N/A	N/A
2003/0004542	12/2002	Wensel et al.	N/A	N/A
2003/0023265	12/2002	Forber	N/A	N/A
2003/0040771	12/2002	Hyodoh et al.	N/A	N/A
2003/0050663	12/2002	Khachin et al.	N/A	N/A
2003/0060782	12/2002	Bose et al.	N/A	N/A
2003/0093087	12/2002	Jones et al.	N/A	N/A
2003/0144687	12/2002	Brady et al.	N/A	N/A
2003/0153935	12/2002	Mialhe	N/A	N/A
2003/0176884	12/2002	Berrada	606/200	A61F 2/0105
2003/0187495	12/2002	Cully	623/1.34	A61B 17/12109
2003/0195556	12/2002	Stack et al.	N/A	N/A
2003/0199921	12/2002	Palmer et al.	N/A	N/A
2004/0068288	12/2003	Palmer et al.	N/A	N/A
2004/0073243	12/2003	Sepetka et al.	N/A	N/A
2004/0079429	12/2003	Miller et al.	N/A	N/A
2004/0133232	12/2003	Rosenbluth et al.	N/A	N/A
2004/0138692	12/2003	Phung et al.	N/A	N/A
2004/0153025	12/2003	Seifert et al.	N/A	N/A
2004/0153118	12/2003	Clubb et al.	N/A	N/A

2004/0172056	12/2003	Guterman et al.	N/A	N/A
2004/0199201	12/2003	Kellett et al.	N/A	N/A
2004/0199243	12/2003	Yodfat	N/A	N/A
2004/0210116	12/2003	Nakao	N/A	N/A
2004/0267301	12/2003	Boylan et al.	N/A	N/A
2005/0004594	12/2004	Nool et al.	N/A	N/A
2005/0033348	12/2004	Sepetka et al.	N/A	N/A
2005/0038447	12/2004	Huffmaster	N/A	N/A
2005/0043680	12/2004	Segal et al.	N/A	N/A
2005/0043756	12/2004	Lavelle et al.	N/A	N/A
2005/0049619	12/2004	Sepetka et al.	N/A	N/A
2005/0055033	12/2004	Leslie et al.	N/A	N/A
2005/0055047	12/2004	Greenhalgh	N/A	N/A
2005/0059995	12/2004	Sepetka et al.	N/A	N/A
2005/0080356	12/2004	Dapolito et al.	N/A	N/A
2005/0085826	12/2004	Nair et al.	N/A	N/A
2005/0085847	12/2004	Galdonik et al.	N/A	N/A
2005/0085849	12/2004	Sepetka et al.	N/A	N/A
2005/0090857	12/2004	Kusleika et al.	N/A	N/A
2005/0090858	12/2004	Pavlovic	N/A	N/A
2005/0125024	12/2004	Sepetka et al.	N/A	N/A
2005/0131450	12/2004	Nicholson et al.	N/A	N/A
2005/0171566	12/2004	Kanamaru	N/A	N/A
2005/0203571	12/2004	Mazzocchi et al.	N/A	N/A
2005/0209609	12/2004	Wallace	N/A	N/A
2005/0216030	12/2004	Sepetka et al.	N/A	N/A
2005/0216050	12/2004	Sepetka et al.	N/A	N/A
2005/0234501	12/2004	Barone	N/A	N/A
2005/0234505	12/2004	Diaz et al.	N/A	N/A
2005/0277978	12/2004	Greenhalgh	N/A	N/A
2005/0283166	12/2004	Greenhalgh	N/A	N/A
2005/0283186	12/2004	Berrada et al.	N/A	N/A
2006/0004404	12/2005	Khachin et al.	N/A	N/A
2006/0009784	12/2005	Behl et al.	N/A	N/A
2006/0030925	12/2005	Pryor	N/A	N/A
2006/0047286	12/2005	West	N/A	N/A
2006/0058836	12/2005	Bose et al.	N/A	N/A
2006/0058837	12/2005	Bose et al.	N/A	N/A
2006/0058838	12/2005	Bose et al.	N/A	N/A
2006/0095070	12/2005	Gilson et al.	N/A	N/A
2006/0129166	12/2005	Lavelle	N/A	N/A
2006/0129180	12/2005	Tsugita et al.	N/A	N/A
2006/0155305	12/2005	Freudenthal et al.	N/A	N/A
2006/0190070	12/2005	Dieck et al.	N/A	N/A
2006/0195137	12/2005	Sepetka et al.	N/A	N/A
2006/0229638	12/2005	Abrams et al.	N/A	N/A
2006/0253145	12/2005	Lucas	N/A	N/A
2006/0271153	12/2005	Garcia et al.	N/A	N/A
2006/0276805	12/2005	Yu	N/A	N/A

2006/0282111	12/2005	Morsi	N/A	N/A
2006/0287668	12/2005	Fawzi	606/200	A61F 2/0105
2007/0112374	12/2006	Paul et al.	N/A	N/A
2007/0118165	12/2006	Demello et al.	N/A	N/A
2007/0149996	12/2006	Coughlin	N/A	N/A
2007/0185500	12/2006	Martin et al.	N/A	N/A
2007/0185501	12/2006	Martin et al.	N/A	N/A
2007/0197103	12/2006	Martin et al.	N/A	N/A
2007/0198029	12/2006	Martin et al.	N/A	N/A
2007/0198030	12/2006	Martin et al.	N/A	N/A
2007/0198051	12/2006	Clubb et al.	N/A	N/A
2007/0225749	12/2006	Martin et al.	N/A	N/A
2007/0233236	12/2006	Pryor	N/A	N/A
2007/0265656	12/2006	Amplatz et al.	N/A	N/A
2007/0299465	12/2006	Messal	606/200	A61F 2/011
2008/0103522	12/2007	Steingisser	606/200	A61F 2/01
2008/0109031	12/2007	Sepetka et al.	N/A	N/A
2008/0183198	12/2007	Sepetka et al.	N/A	N/A
2008/0188885	12/2007	Sepetka et al.	N/A	N/A
2008/0262528	12/2007	Martin	N/A	N/A
2008/0262532	12/2007	Martin	N/A	N/A
2009/0069828	12/2008	Martin et al.	N/A	N/A
2009/0105722	12/2008	Fulkerson et al.	N/A	N/A
2009/0105737	12/2008	Fulkerson et al.	N/A	N/A
2009/0125053	12/2008	Ferrera et al.	N/A	N/A
2009/0192518	12/2008	Leanna et al.	N/A	N/A
2009/0287291	12/2008	Becking et al.	N/A	N/A
2009/0299393	12/2008	Martin et al.	N/A	N/A
2010/0076452	12/2009	Sepetka et al.	N/A	N/A
2010/0100106	12/2009	Ferrera	N/A	N/A
2010/0174309	12/2009	Fulkerson et al.	N/A	N/A
2010/0185210	12/2009	Hauser et al.	N/A	N/A
2010/0217187	12/2009	Ferrera et al.	N/A	N/A
2010/0256600	12/2009	Ferrera	N/A	N/A
2010/0318097	12/2009	Cragg et al.	N/A	N/A
2011/0060359	12/2010	Hannes et al.	N/A	N/A
2011/0152920	12/2010	Eckhouse et al.	N/A	N/A
2011/0160742	12/2010	Ferrera et al.	N/A	N/A
2011/0160757	12/2010	Ferrera et al.	N/A	N/A
2011/0160760	12/2010	Ferrera et al.	N/A	N/A
2011/0160761	12/2010	Ferrera et al.	N/A	N/A
2011/0160763	12/2010	Ferrera et al.	N/A	N/A
2011/0166586	12/2010	Sepetka et al.	N/A	N/A
2011/0288572	12/2010	Martin	N/A	N/A
2011/0319917	12/2010	Ferrera et al.	N/A	N/A
2012/0143230	12/2011	Sepetka et al.	N/A	N/A
2012/0197285	12/2011	Martin et al.	N/A	N/A
2013/0030461	12/2012	Marks et al.	N/A	N/A
2013/0281788	12/2012	Garrison	N/A	N/A
2014/0276074	12/2013	Warner	N/A	N/A

2014/0343595	12/2013	Monstadt et al.	N/A	N/A
2015/0359547	12/2014	Vale et al.	N/A	N/A
2016/0015402	12/2015	Brady et al.	N/A	N/A
2016/0015935	12/2015	Chan et al.	N/A	N/A
2016/0106448	12/2015	Brady et al.	N/A	N/A
2016/0106449	12/2015	Brady et al.	N/A	N/A
2016/0113663	12/2015	Brady et al.	N/A	N/A
2016/0113665	12/2015	Brady et al.	N/A	N/A
2016/0151618	12/2015	Powers et al.	N/A	N/A
2016/0157985	12/2015	Vo et al.	N/A	N/A
2016/0199620	12/2015	Pokorney et al.	N/A	N/A
2016/0296690	12/2015	Kume et al.	N/A	N/A
2016/0302808	12/2015	Loganathan et al.	N/A	N/A
2016/0354098	12/2015	Martin et al.	N/A	N/A
2016/0375180	12/2015	Anzai	N/A	N/A
2017/0079766	12/2016	Wang et al.	N/A	N/A
2017/0079767	12/2016	Leon-Yip	N/A	N/A
2017/0086862	12/2016	Vale et al.	N/A	N/A
2017/0100143	12/2016	Grandfield	N/A	N/A
2017/0105743	12/2016	Vale et al.	N/A	N/A
2017/0164963	12/2016	Goyal	N/A	N/A
2017/0215902	12/2016	Leynov et al.	N/A	N/A
2017/0224953	12/2016	Tran et al.	N/A	N/A
2017/0281909	12/2016	Northrop et al.	N/A	N/A
2017/0290599	12/2016	Youn et al.	N/A	N/A
2018/0049762	12/2017	Seip et al.	N/A	N/A
2018/0084982	12/2017	Yamashita et al.	N/A	N/A
2018/0116717	12/2017	Taff et al.	N/A	N/A
2018/0132876	12/2017	Zaidat	N/A	N/A
2018/0140314	12/2017	Goyal et al.	N/A	N/A
2018/0140315	12/2017	Bowman et al.	N/A	N/A
2018/0140354	12/2017	Lam et al.	N/A	N/A
2018/0185614	12/2017	Garrison et al.	N/A	N/A
2019/0374239	12/2018	Martin et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1640505	12/2004	CN	N/A
102036611	12/2010	CN	N/A
3501707	12/1985	DE	N/A
60038501	12/2008	DE	N/A
0200668	12/1985	EP	N/A
1312314	12/2002	EP	N/A
2319575	12/2012	EP	N/A
2002537943	12/2001	JP	N/A
2007522881	12/2006	JP	N/A
2007252951	12/2006	JP	N/A
2008539958	12/2007	JP	N/A
2011508635	12/2010	JP	N/A

2014004219	12/2013	JP	N/A
2018118132	12/2017	JP	N/A
20180102877	12/2017	KR	N/A
9409845	12/1993	WO	N/A
9509586	12/1994	WO	N/A
9601591	12/1995	WO	N/A
9617634	12/1995	WO	N/A
9619941	12/1995	WO	N/A
9727808	12/1996	WO	N/A
9727893	12/1996	WO	N/A
9803120	12/1997	WO	N/A
0053120	12/1999	WO	N/A
0072909	12/1999	WO	N/A
0132254	12/2000	WO	N/A
0154622	12/2000	WO	N/A
0167967	12/2000	WO	N/A
0202162	12/2001	WO	N/A
0228291	12/2001	WO	N/A
03000334	12/2002	WO	N/A
03061730	12/2002	WO	N/A
03089039	12/2002	WO	N/A
WO 2005027751	12/2004	WO	N/A
WO-2005027751	12/2004	WO	A61B 17/221
2006031410	12/2005	WO	N/A
2006122076	12/2005	WO	N/A
2007092820	12/2006	WO	N/A
2008036156	12/2007	WO	N/A
2008131116	12/2007	WO	N/A
2009034456	12/2008	WO	N/A
2009086482	12/2008	WO	N/A
2011091383	12/2010	WO	N/A
2012009675	12/2011	WO	N/A
2012162437	12/2011	WO	N/A
2013106146	12/2012	WO	N/A
2015141317	12/2014	WO	N/A
2017192999	12/2016	WO	N/A
2018019829	12/2017	WO	N/A
2018033401	12/2017	WO	N/A
2018046408	12/2017	WO	N/A
2018137029	12/2017	WO	N/A
2018137030	12/2017	WO	N/A
2018145212	12/2017	WO	N/A
2018156813	12/2017	WO	N/A
2018172891	12/2017	WO	N/A
2018187776	12/2017	WO	N/A

Primary Examiner: Shi; Katherine M

Attorney, Agent or Firm: Fortem IP LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/530,101, filed Aug. 2, 2019, which is a continuation of U.S. patent application Ser. No. 15/946,466, filed Apr. 5, 2018, now U.S. Pat. No. 11,213,307, which is a continuation of U.S. patent application Ser. No. 15/174,016, filed Jun. 6, 2016, now U.S. Pat. No. 9,943,323, which is a continuation of U.S. patent application Ser. No. 14/446,755, filed Jul. 30, 2014, now U.S. Pat. No. 9,358,094, which is a continuation of U.S. patent application Ser. No. 13/959,433, filed Aug. 5, 2013, now U.S. Pat. No. 8,795,305, which is a continuation of PCT Application No. PCT/US2012/039216, filed May 23, 2012, which is a non-provisional of U.S. Provisional Application No. 61/489,183, filed May 23, 2011, and U.S. Provisional Application No. 61/489,254, filed May 24, 2011. The entirety of each of the above-mentioned prior applications is hereby incorporated by reference.

FIELD OF THE INVENTION

(1) The devices described herein are intended to retrieve obstructions from the body. Such devices have applicability throughout the body, including clearing of blockages within body lumens and providing passive protection of such, such as the vasculature, by providing a capturing portion that can translate and/or mobilize the obstruction within the body lumen.

BACKGROUND OF THE INVENTION

(2) A large number of medical procedures require the use of medical device(s) to remove an obstruction from a body lumen, vessel, or other organ. An inherent risk in such procedures is that mobilizing or otherwise disturbing the obstruction can potentially create further harm if the obstruction or a fragment thereof dislodges from the retrieval device. If a particle or the obstruction breaks free from the device and flows downstream, it is highly likely that the particle or obstruction will become trapped in smaller and more tortuous anatomy. In many cases, the physician will no longer be able to use the same retrieval device to again remove the obstruction because the size of the device may prevent advancing the device to the site of the new obstruction.

(3) Even in successful procedures, a physician must proceed with caution to prevent the walls of the vessel or body lumen from imparting undesired forces to shear or dislodge the obstruction as it is translated through the body during removal. These forces have the potential of breaking portions or fragments of the obstruction away. In some cases, the obstruction can simply break free from the retrieval device and can lodge in a new area causing more concern than the original blockage.

(4) Procedures for restoring flow within the cerebral vasculature as a result of ischemic stroke are one example of where these issues present a concern. The brain relies on its arteries and veins to supply oxygenated blood from the heart and lungs and to remove carbon dioxide and cellular waste from brain tissue. Blockages that interfere with this supply eventually cause the brain tissue to stop functioning. If the disruption in supply occurs for a sufficient amount of time, the continued lack of nutrients and oxygen causes irreversible cell death (infarction). Accordingly, immediate medical treatment of an ischemic stroke is critical for the recovery of a patient. To access the cerebral vasculature a physician typically advances a catheter from a remote part of the body (typically a leg) through the vasculature and into the cerebral region of the vasculature. Once within the cerebral region, the physician deploys a device for retrieval of the obstruction causing the blockage. Concerns about dislodged obstructions or the migration of dislodged fragments increases the duration of the procedure at time when restoration of blood flow is paramount. Furthermore, a physician might be unaware of one or more fragments that dislodge from the initial obstruction and cause blockage of smaller more distal vessels.

(5) Many physicians currently use stents to perform thrombectomy (i.e. clot removal) to resolve ischemic stroke. Typically, the physician deploys the stent into the clot, in an attempt to push the

clot to the side of the vessel and re-establish blood to flow. Tissue plasminogen activator (“Tpa”) is often injected into the bloodstream through an intravenous line. The TPA must travel in the blood stream until it reaches the clot that is causing the blockage. Once the Tpa contacts the clot, it begins to break up the clot with the hope of restoring blood flow to the affected areas. Tpa is also often administered to supplement the effectiveness of the stent. Yet, if attempts at clot dissolution are ineffective or incomplete, the physician can attempt to remove the stent while it is expanded against or enmeshed within the clot. In doing so, the physician must effectively drag the clot from the vessel, in a proximal direction, into a guide catheter located within vessels in the patient's neck (typically the carotid artery). While this procedure has been shown to be effective in the clinic and easy for the physician to perform, there remain some distinct disadvantages using this approach.

(6) The stent may not sufficiently hold onto the clot as it drags the clot to the catheter. In such a case, the clot might not move from the vessel. Another risk is that use of the stent might mobilize the clot from the original blockage site, but the clot might not adhere to the stent during translation toward the catheter. This is a particular risk when translating through bifurcations and tortuous anatomy. Furthermore, blood flow can migrate the clot (or fragments of the clot) into a branching vessel at a bifurcation. If the clot is successfully brought to the guide catheter in the carotid artery, yet another risk is that the clot may be “stripped” or “sheared” from the stent as the stent enters the guide catheter. Regardless, simply dragging an expanded stent (either fully or partially expanded) can result in undesired trauma to the vessel. In most cases, the stent is oversized compared to the vessel. Dragging a fixed metallic (or other) structure can pull the arteries and/or strip the cellular lining from the vessel, causing further trauma such as a hemorrhagic stroke (leakage of blood from a cerebral vessel). Also, the stent can become lodged on plaque on the vessel walls resulting in further vascular damage.

(7) In view of the above, there remains a need for improved devices and methods that can remove occlusions from body lumens and/or vessels. While the discussion focuses on applications in the cerebral vasculature, the improved devices and methods described below have applications outside of the area of ischemic stroke.

SUMMARY

(8) The examples discussed herein show the inventive device in a form that is suitable to retrieve obstructions or clots within the vasculature. The term obstructions may include blood clot, plaque, cholesterol, thrombus, naturally occurring foreign bodies (i.e., a part of the body that is lodged within the lumen), a non-naturally occurring foreign body (i.e., a portion of a medical device or other non-naturally occurring substance lodged within the lumen.) However, the devices are not limited to such applications and can apply to any number of medical applications where elimination or reduction of the number of connection points is desired.

(9) The devices discussed herein include interventional medical devices for retrieving and securing an obstruction within a vessel lumen. In one variation, the device includes a shaft having a flexibility to navigate through tortuous anatomy, the shaft having a distal portion and a proximal portion and a lumen extending therethrough; and an eversible cover having a fixed section affixed near an end of the distal portion of the shaft, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable against a vessel wall, the eversible cover being axially compliant such that when the interventional vascular device retrieval device is positioned through the shaft lumen and moved in a proximal direction, the friction of the eversible cover against the vessel wall causes the eversible cover to evert over the interventional vascular device allowing for the free section of the cover to be distal to the interventional vascular device.

(10) In another variation, the present disclosure includes a method of securing an obstruction within a vessel. For example, the method can include advancing a shaft having a retrieval device affixed thereto to the obstruction; advancing a protective device over the shaft, the protective device comprising a sheath having an eversible cover, where a fixed end of the eversible cover is

affixed to a distal portion of the sheath and a free end of the eversible cover is located proximal to the fixed end; positioning the fixed end of the eversible cover adjacent to the retrieval device and expanding at least a portion of the eversible cover against a portion of a wall of the vessel; proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.

(11) Another variation of the method include securing an obstruction within a vessel of a patient, by providing an interventional vascular device having a wire attached thereto, where the interventional vascular device is configured to remove the obstruction from the vessel; coupling a shaft to the wire of the interventional vascular device, the shaft having a distal portion and a proximal portion and a lumen extending therethrough and having a flexibility to navigate through tortuous anatomy, an eversible cover having a fixed section affixed near an end of the distal portion of the shaft, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable against a vessel wall, the eversible cover being axially compliant such that when the interventional vascular device retrieval device is positioned through the shaft lumen and moved in a proximal direction against the eversible cover, the friction of the eversible cover against the vessel wall causes the eversible cover to evert over the interventional vascular device allowing for the free section of the cover to be distal to the interventional vascular device; positioning the shaft and eversible cover over the wire of the interventional vascular device prior to insertion into the patient; and advancing the interventional vascular device, shaft and eversible cover into the vessel to the obstruction. The device can also be configured so that the fixed section of the eversible cover comprises a pre-set shape to reduce a force required to evert the evertable cover.

(12) The retrieval devices can comprise any number of capturing or retrieval device such as a filter, an atherectomy device, a rotational cutter, an aspiration device, stent based retrievers and retrieval baskets.

(13) The methods described herein can include methods of securing an obstruction within a vessel. In one example, the method can comprise: positioning a catheter within a vessel; advancing a shaft having a retrieval device affixed thereto out of the catheter; advancing an eversible cover out of the catheter such that a fixed end of the eversible cover is affixed adjacent to a proximal end of the retrieval device and a free end of the eversible cover is moveable relative to the shaft and retrieval device; expanding at least a portion of the eversible cover against a portion of a wall of the vessel; manipulating the retrieval device to become at least partially enmeshed with the obstruction; and proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.

(14) In another variation, the methods can include further withdrawing the shaft from the vessel such that during withdrawal the eversible cover forms a protective barrier over the obstruction to lessen shearing forces caused by the vessel and reduce dislodging portions of the obstruction from the retrieval device.

(15) Another variation of a method includes a method of preparing a retrieval device comprising: providing a retrieval device having been previously removed from a body of a patient where the retrieval device includes a protective cover where a fixed end of the protective cover is affixed adjacent to a proximal end of the retrieval device and where a free end is located distally to the fixed end covering the retrieval device and is moveable relative to the second end; reversing the protective cover by moving the free end proximally of the fixed while the fixed end remains affixed adjacent to the proximal end of the retrieval device; inserting the retrieval device and cover into a catheter where the free end of the cover is proximal to the fixed end of the cover and retrieval

device such that upon deployment from the catheter, the free end of the cover deploys proximally to the fixed end of the cover.

(16) In another example, the devices described herein can include medical device retrieval systems for securing an obstruction within a vessel lumen and for use with a catheter configured to be navigated through the vasculature. In one variation, the device comprises an elongated stent comprising a plurality of struts, the stent being collapsible for positioning in the catheter during delivery and having an expanded profile such that when expanded the struts are configured to engage the obstruction; a shaft fixedly attached to the elongated stent and having a flexibility to navigate through tortuous anatomy; a fluid permeable cover having a distal end coupled to a proximal end of the elongated stent a cover wall defining a cavity and extending along the shaft, and a proximal end being moveable relative to the shaft, where the fluid permeable cover is collapsible for positioning in the catheter during delivery and is expandable upon deployment from the catheter such that at least a portion of the fluid permeable cover is expandable; where the fluid permeable cover is axially pliable such that when the device is deployed in the vessel the frictional forces between the vessel and the fluid permeable cover permit proximal movement of the shaft and elongated stent to cause inversion of the fluid permeable cover wall such that the fluid permeable cover wall everts over the elongated stent.

(17) Another variation of a device includes an interventional medical device for use with a catheter configured for delivery through vasculature for securing an obstruction within a vessel lumen. For example, the device can comprise a shaft having a flexibility to navigate through tortuous anatomy, the shaft having a distal portion and a proximal portion; a capturing device comprising a sidewall, the capturing device fixedly located at a distal portion of the shaft and having a reduced profile for positioning in the catheter and an expanded profile, such that upon deployment from the catheter, the capturing device expands to force a portion of the sidewall into the obstruction to at least partially attach to the obstruction; a cover having a distal end coupled adjacent to a proximal end of the capturing structure, a proximal end and a cover wall extending therebetween, where the proximal end of the cover is slidable relative to the distal end, where the cover is expandable such that when located in the catheter the cover is in a reduced delivery state and upon advancement from the catheter the cover expands with the proximal end located proximally of the distal end, where the cover wall is compliant such that when deployed from the catheter and the shaft is pulled in a proximal direction frictional forces between the vessel and the cover wall or proximal end cause the cover to invert as the cover wall inverts over the capturing device to surround the capturing device.

(18) Another variation of the device includes an interventional medical device for securing a retrieval device having one or more obstructions located therein for removal from a body. In one such example the medical device includes a sheath having a flexibility to navigate through tortuous anatomy, the sheath a distal portion and a proximal portion and a lumen extending therethrough; an eversible cover having a fixed section affixed to the distal portion of the sheath, a free section extending in a proximal direction from the fixed section and a cover wall extending from the fixed section to the free section, where the eversible cover is expandable, the eversible cover being axially compliant such that when the retrieval device is positioned through the sheath lumen moved in a proximal direction against the eversible cover, the eversible cover everts over the retrieval device allowing for the free section of the cover to be distal to the retrieval device.

(19) Another variation of the method includes advancing a shaft having a retrieval device affixed thereto to the obstruction; advancing a protective device over the shaft, the protective device comprising a sheath having an eversible cover, where a fixed end of the eversible cover is affixed to a distal portion of the sheath and a free end of the eversible cover is located proximal to the fixed end; positioning the fixed end of the eversible cover adjacent to the retrieval device and expanding at least a portion of the eversible cover against a portion of a wall of the vessel; proximally translating the shaft and retrieval device with at least a portion of the obstruction affixed thereto

such that resistance of the eversible cover against the vessel resists movement of the eversible cover causing the free section of the eversible cover to evert over the proximally translated retrieval device.

(20) The capturing portions described herein can include a stent retrieval device for expanding against one or more occlusive bodies in a vasculature. In one example, the stent retrieval device includes an elongate shaft having a flexibility to navigate through tortuous anatomy, the elongate shaft having a distal portion and a proximal portion; a plurality of filaments that diverge from the distal portion of the elongate shaft to form an expandable elongated stent body having an open distal end and a fluid permeable closed proximal end and a cavity therebetween, where divergence of the filaments at the distal portion of the elongate shaft forms the fluid permeable closed proximal end; where the plurality of filaments extending along the shaft are free of any connection joints in the distal portion to permit increased flexibility of the distal portion as it navigates through tortuous anatomy; and one or more connection joints proximal to the distal portion where the connection joints secure the plurality of filaments to the shaft.

(21) The stent retrieval can also include at least one of the plurality of filaments that comprise at least two wires twisted together, the elongated stent body further comprising at least one intersection of filaments, where the wires of each filament are interwoven to provide increased outward radial strength of the elongated stent body and such that the wires slide relative to each other as the elongated stent body expands or compresses in diameter to reduce a force required to linearize the elongated stent body.

(22) The stent retrieval device can have an exterior surface of the elongated stent body that comprises an irregular surface formed by intersection of filaments.

(23) The stent retrieval device can also have intersection of filaments comprising a barb or knuckle and where a plurality of barbs or knuckles is radially spaced about the elongated stent body. The stent retrieval device can also have an intersection of filaments that comprises a barb or knuckle and where a plurality of barbs or knuckles is aligned with an axis of the elongated stent body.

(24) In one variation of the devices described herein, the device comprises a main bundle or group of wires that diverge to form a device having various shapes but few or no connection points or joints (where fabrication of such a construction is referred to as “jointless”). Clearly, the inventive devices described herein are not limited to such a jointless construction. Additional variation includes one or more leading wires that are attached to a capturing portion as described below.

(25) Devices of the present invention can incorporate any number of wires of different characteristics including, but not limited to, materials, shapes, sizes and/or diameters. Clearly, the number of permutations of device configurations is significant. Providing devices with such a composite construction allows for the manipulation of the device's properties to suit the intended application.

(26) As noted herein, the joint-less construction improves the flexibility and strength of the device by eliminating joints, connection points, or other attachment points. In addition, the joint-less construction improves the ability of the device to be delivered through a small microcatheter. As a result, the device and microcatheter are able to access remote regions of the vasculature.

(27) The devices may be fabricated to be self-expanding upon deployment from a catheter. Alternatively, the devices can be constructed from shape-memory alloys such that they automatically deploy upon reaching a pre-determined transition temperature.

(28) It should be noted that in some variations of the invention, all or some of the device can be designed to increase their ability to adhere to the obstruction. For example, the wires may be coupled to an energy source (e.g., RF, ultrasonic, or thermal energy) to “weld” to the obstruction. Application of energy to the device can allow the surrounding portion to deform into the obstruction and “embed” within the obstruction. Alternatively, the device can impart a positive charge to the obstruction to partially liquefy the obstruction sufficiently to allow for easier removal. In another variation, a negative charge could be applied to further build thrombus and nest the

device for better pulling force. The wires can be made stickier by use of a hydrophilic substance(s), or by chemicals that would generate a chemical bond to the surface of the obstruction. Alternatively, the filaments may reduce the temperature of the obstruction to congeal or adhere to the obstruction.

(29) Additional devices and methods for treating ischemic stroke are discussed in commonly assigned U.S. patent application Ser. No. 11/671,450 filed Feb. 5, 2007; Ser. No. 11/684,521 filed Mar. 9, 2007; Ser. No. 11/684,535 filed Mar. 9, 2007; Ser. No. 11/684,541 filed Mar. 9, 2007; Ser. No. 11/684,546 filed Mar. 9, 2007; Ser. No. 11/684,982 filed Mar. 12, 2007, Ser. No. 11/736,526 filed Apr. 17, 2007, Ser. No. 11/736,537 filed Apr. 17, 2007, Ser. No. 11/825,975 filed Sep. 10, 2007; Ser. No. 12/344,378 filed Dec. 26, 2008, Ser. No. 13/012,727 filed Jan. 24, 2011, and Ser. No. 13/226,222 filed Sep. 6, 2011; the entirety of each of which is incorporated by reference. The principles of the invention as discussed herein may be applied to the above referenced cases to produce devices useful in treating ischemic stroke. In other words, the wire-shaped construction of devices according to present invention may assume the shapes disclosed in the above-referenced cases when such a combination is not inconsistent with the features described herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Each of the following figures diagrammatically illustrates aspects of the invention. Variation of the invention from the aspects shown in the figures is contemplated.
- (2) FIG. 1 illustrates an example of a device according to the present invention when used in a system for removing obstructions from body lumens.
- (3) FIGS. 2A to 2C illustrate working ends of various coverable retrieval devices.
- (4) FIGS. 2D and 2E show variations of retrieval devices.
- (5) FIG. 2F shows an independent eversible cover on a delivery sheath.
- (6) FIGS. 3A to 3C illustrate an example of a coverable retrieval device where the cover everts about the retrieval structure.
- (7) FIG. 4A to 4I illustrates an example where an improved retrieval device with passive protection retrieves a clot from tortuous anatomy.
- (8) FIGS. 4J and 4K illustrate examples of an obstruction or other material captured within a retrieval device with a cover further protecting the loaded retrieval device.
- (9) FIG. 5A illustrates a retrieval device having a retrieval structure adjacent to a double layer cover.
- (10) FIG. 5B shows a funnel with a free end that tapers down about the delivery wire.
- (11) FIGS. 5C and 5D show a fixed end of a cover that is pre-shaped to reduce the force required to evert the cover wall.
- (12) FIG. 5E shows alternate variation of a passive cover integrated into a retrieval device.
- (13) FIG. 5F illustrates a cover having a pre-set flattened cover wall at a fixed end of the retrieval structure.
- (14) FIGS. 5G to 5I illustrate various layered covers.
- (15) FIG. 5J shows a cover that is constructed directly onto the retrieval structure rather than the delivery shaft.
- (16) FIGS. 5K and 5L show a variation of a cover and retrieval device where the cover is first mounted in a distal direction and then inverted in a proximal direction.
- (17) FIGS. 6A to 6L illustrate a variation of covers for use as describe herein.
- (18) FIGS. 7A to 7C show additional variations of covers.
- (19) FIG. 8 illustrates a variation of a proximal and distal end of an additional retrieval device.
- (20) FIGS. 9A to 9C illustrate wires of different constructions within a delivery wire or shaft.

(21) FIGS. **10A** to **10E** illustrate additional variations of covers for use as described above.

(22) FIGS. **11A** to **11C** illustrate additional variations of covers for use with the devices and methods described herein.

(23) FIGS. **12A** to **12F** illustrate various stent designs for increasing the ability of a stent to adhere to an occlusion within a vessel.

(24) FIG. **12G** illustrates a proximal end of the stent structure.

DETAILED DESCRIPTION

(25) It is understood that the examples below discuss uses in the cerebral vasculature (namely the arteries). However, unless specifically noted, variations of the device and method are not limited to use in the cerebral vasculature. Instead, the invention may have applicability in various parts of the body. Moreover, the invention may be used in various procedures where the benefits of the method and/or device are desired.

(26) FIG. **1** illustrates a system **10** for removing obstructions from body lumens as described herein.

(27) In the illustrated example, this variation of the system **10** is suited for removal of an obstruction in the cerebral vasculature. As stated herein, the present devices and methods are useful in other regions of the body including the vasculature and other body lumens or organs. For exemplary purposes, the discussion shall focus on uses of these devices and method in the vasculature.

(28) It is noted that any number of catheters or microcatheters may be used to locate the catheter/microcatheter **12** carrying the obstruction removal device **200** at the desired target site. Such techniques are well understood standard interventional catheterization techniques. Furthermore, the catheter **12** may be coupled to auxiliary or support components **14**, **16** (e.g., energy controllers, power supplies, actuators for movement of the device(s), vacuum sources, inflation sources, sources for therapeutic substances, pressure monitoring, flow monitoring, various bio-chemical sensors, bio-chemical substance, etc.) Again, such components are within the scope of the system **10** described herein.

(29) In addition, devices of the present invention may be packaged in kits including the components discussed above along with guiding catheters, various devices that assist in the stabilization or removal of the obstruction (e.g., proximal-assist devices that holds the proximal end of the obstruction in place preventing it from straying during removal or assisting in the removal of the obstruction), balloon-tipped guide catheters, dilators, etc.

(30) FIG. **2A** illustrates a working end of a coverable retrieval device **100**. Typically, the device includes a capturing or retrieval structure **200**. In the illustrated example, the retrieval structure **200** comprises an elongated stent structure. However, unless specifically noted, the capturing structure can comprise any number of devices, including but not limited to a filter, an atherectomy device, a rotational cutter, an aspiration catheter.

(31) The retrieval structure **200** is located at a distal end of a delivery wire **202**. In one variation, the retrieval structure **200** can be permanently affixed to the delivery wire **200** by such methods including, but not limited to adhesive bonding, soldering, welding, polymer joining, or any other conventional method. In some variations, the retrieval device **200** can be formed from one or more wires forming the delivery wire **202** or shaft **202**. The delivery wire **202** can have sufficient column strength such that it can axially advance and retract the device **100** within the vasculature as the physician manipulates a non-working end of the delivery wire **202** outside of the body.

Accordingly, the delivery wire **202** should have a length that is sufficient to extend from the target area, e.g., the cerebral vasculature, to the entry point on the body. Alternatively, additional variations of the device **100** can allow for the use of a support member or catheter that positions the retrieval structure **200** as needed. Additional features of the retrieval structure **200** can be found in the commonly assigned patents and applications cited herein and incorporated by reference.

(32) The coverable retrieval device **100** further includes a cover **300** (also referred to as a funnel or

sheath) affixed relative to a proximal end **206** of the retrieval structure **200**. By being affixed relative to a proximal end **206**, a distal end **204** of the retrieval structure **200** can move relative to the cover **300** so that the cover **300** everts over the proximal end **206** of the structure **200** when the cover **300** is expanded within a vessel and as the structure **200** is withdrawn into the distal end **302** of the cover **300**. This mechanism is discussed in detail below.

(33) FIGS. 2B and 2C illustrate alternative variations of a coverable retrieval device **100**. As shown in FIGS. 2B and 2C, the distal end **302** of the cover **300** can be spaced from the proximal end **206** of the retrieval structure **200**. Alternatively, the distal end **302** of the cover **300** can extend over a portion of the retrieval structure **200**. In some variations, at least a section of the cover **300** expands to a greater diameter than a diameter of the retrieval structure **200**. This allows the cover **300** to expand to a vessel wall where the vessel holds the cover stationary while the device is pulled proximally through the cover to evert the cover. In alternate variations, the cover **300** expands to the same or lesser diameter than the retrieval structure **200** or other device.

(34) FIG. 2D shows a retrieval device **100** with a catheter **112** (usually a microcatheter). The retrieval device **100** can comprise a single unitary device of a cover **300** and retrieval structure **200** (in this case the retrieval structure is an elongated stent structure). One benefit of a unitary device is that additional devices complicates the procedure and can increase the duration of what is ordinarily a time sensitive procedure. The retrieval device **100** can be positioned through the catheter **112** that includes a hub **114**. As a result, the physician only needs to manipulate the unitary retrieval device **100** and the catheter/microcatheter **112**. The retrieval device **100** is loaded into the catheter **112** for placement at the target site. In addition, the retrieval device can be reloaded if the procedure must be repeated. The cover **300** and retrieval structure **200** described herein can comprise any construction described herein or as known by those skilled in the art.

(35) FIG. 2E shows a retrieval device **100** with a cover **300** and retrieval device **200** with a radiopaque marker **305** therebetween. As shown, variations of the device **100** do not require a catheter or microcatheter.

(36) FIG. 2F illustrates an eversible cover **300** located on a sheath **330** having a lumen **332** extending therethrough. A separable retrieval device **200** can be coupled to the cover **300** and sheath **330** by inserting the wire **202** of the cover retrieval device **200** through the lumen **332** of the sheath **330**. In this variation, the eversible cover **300** can be used with any number of different interventional tools. The separate devices can be assembled prior to delivery into the patient. Alternatively, the devices can be positioned within the body and subsequently joined once the retrieval device **200** engages the target area.

(37) FIG. 3A illustrates an example of a coverable retrieval device **100** where the cover **300** is in the process of everting about the retrieval structure **200**. As shown, arrow **50** illustrates a force applied on the wire **202** in a proximal direction. Arrows **52** illustrate a resistance force applied by the friction of the expanded cover **300** against a vessel or similar wall. This friction force **52** prevents or resists proximal movement of the free end **304** of the cover **300** while the fixed end **302** moves in a proximal direction with the proximal end **206** of the retrieval structure **200**. This action causes a wall **306** of the cover **300** to evert over the retrieval structure **200**. Ultimately, and as shown in FIG. 3B, the free end **304** of the cover **300** ends up distally over the fixed end **302**. As shown, the wall of the everted cover **300** provides a safety type cover for the retrieval device **200**. In additional variations, the fixed end **302** of the cover can actually be slidable or moveable along the delivery wire **202**. However, the similar principle as discussed above shall apply to cause everting of the cover **300** over the retrieval structure **200**.

(38) FIG. 3C illustrates another variation of a coverable retrieval device **100** after the cover **300** is everted about the retrieval structure **200**. In this variation, the free end **304** of the cover **300** ends up distally of the fixed end **302** and tapers or collapses towards the free end **304**. The cover **300** can be shape set so that prior to eversion the cover is as shown above where the forces acting on the cover wall **306** expand outwards, but after eversion the forces on the cover wall **306** cause the tapering or

collapsing as shown in FIG. 3C.

(39) In accordance with the illustrations discussed above, the cover **300** can be made so that the cover wall **306** is atraumatic when dragged across a lumen wall. The cover can be manufactured from any number of materials including a fabric, a reinforced fabric, a braid, weave, or any such material that allows for expansion against a wall of the body lumen or vessel as well as to allow everting of a wall **306** of the cover over the retrieval device **200**. The cover wall **306** can also comprise combinations of these materials such as braids of polymer material with metal fibers, soft braids with coil reinforcements or various other combinations.

(40) The cover wall can comprise a mesh that can include any medically acceptable materials such as a Nitinol braid. Furthermore, the mesh allows for flow through the vessel or lumen while expanded. However, additional variations of the device can include a solid layer of material substituted for the mesh. Moreover the cover can comprise any number of configurations. For example, the cover can comprise a single layer wall or a multi layer wall, the open end of the cover could be made to have terminated ends such as by using continuous wire loops formed during the braiding process. Alternatively, the ends can be cut and then terminated by encasing in polymer, laser welds, or by folding inward for a discreet length and then terminating

(41) In one example, the cover **300** comprises a continuous wire construction as described in earlier commonly assigned patent applications incorporated by reference. In one variation the cover **300** comprises a finely braided wire, such as 48-96 wires of 0.0005" to 0.002" diameter fine Nitinol wire or similar. Additionally, the wire can comprise cobalt chromium, stainless steel, or similar, or drawn filled tube (dft) with platinum core. In additional variations, a flat wire or oval wire can be used. The wire does not need to be uniform. Instead, a number of different types of wires can be used. Some of the individual wires could be platinum alloys for added radiopacity.

(42) FIG. 4A to 4I illustrates an example where an improved retrieval device **100** with passive protection retrieves a clot **2** from tortuous anatomy. FIG. 4A illustrates a clot **2** that obstructs blood flow in a vessel **6**. As noted herein, the vessel **6** can comprise any vessel in cerebral vasculature, coronary or peripheral vasculature. Alternatively, the device and methods for use are not limited to use in the vasculature. Variations of the principles, concepts, method and devices described herein can be applicable wherever a retrieval device can be used. FIG. 4A also illustrates a guide sheath or access catheter **108** that is advanced within the vessel. During a procedure, the physician will advance the access catheter **108** as far distally as possible. However, due to the size of the access catheter **108**, a physician typically positions it a distance away from the obstruction **2**. As shown, there can be any number of bifurcations **8** in the vessel **6** located between the access catheter **108** and the obstruction **2**. As discussed herein, in some variations, the access catheter **108** can be used to remove the obstruction **2** from the body once the obstruction is captured by a retrieval device. However, the greater the distance between the initial location of the obstruction **2** and the location of the access catheter **108**, the greater the risk that the obstruction **2** can break free from the retrieval device or become dislodged due to anatomic or environmental features, including but not limited to bifurcations, the wall of the lumen, the tortuosity of the anatomy, vessel wall plaque, etc.

(43) FIG. 4B illustrates an optional catheter **112** that advances from the access catheter **108** to the site of the obstruction **2**. Once at the site, the catheter **112** can deploy a retrieval device (not shown in FIG. 4B) so that the retrieval device can engage the clot **2**. Alternatively, the catheter **112** can traverse the obstruction **2** as shown in FIG. 4C and deploy a portion of the retrieval device **100** distally to the obstruction **2**. The physician then manipulates the retrieval device **100** to secure the obstruction **2**. For example, the physician can deploy the retrieval structure **200** distally to the obstruction **6** and withdraw the retrieval structure **200** proximally to secure the obstruction **2**. In another variation, the physician can position the retrieval structure **200** within the catheter **2** while the catheter **112** is through or adjacent to the obstruction **2**. Then, the physician can withdraw the catheter **112** to expose the retrieval structure **200** so that it secures to the obstruction **2** after

expansion. In the illustrated example, the retrieval structure **200** comprises an elongated stent type structure that expands (or is expanded) to enmesh or secure to the obstruction. Although not illustrated, the system can include a distal capture filter or basket as described in any of the commonly assigned applications incorporated by reference herein.

(44) Next, as shown in FIG. 4E, the physician can further withdraw the catheter **112** to expose a cover **300** as described above. In many cases, the physician exposes the cove **300** once the retrieval structure **200** is engaged with the obstruction **2**. This sequential process allows for easier repositioning of the retrieval structure **200** if necessary. Alternatively, the cover **300** can be deployed prior to engaging the retrieval structure **200** with the obstruction **2**. If necessary, the physician can apply a proximal force on the delivery wire **202** while withdrawing the catheter **112** to prevent inadvertent movement of the obstruction **2** and retrieval device **200**.

(45) FIG. 4F illustrates the stage with a fully exposed the cover **300** and a catheter **112** moved closer towards the access sheath **108**. As shown, the free end **304** of the cover **300** is proximal to fixed end **302** of the cover **300**. As also noted above, the cover **300** can be a shape memory alloy that expands against the walls of the vessel **6** upon reaching body temperature. Alternatively, the cover **300** can be self expanding upon deployment into the vessel **6**. In some variations, the cover wall **306** comprises a porous material or construction that allows blood to continue to flow through the cover **300**.

(46) In addition, some variations of the retrieval device **100** include a cover **300** that has at least a section that expands to a greater diameter or dimension than the retrieval structure **200**. This allows for expansion of the cover **300** against the wall of the vessel **6**. In most variation, expansion of the cover **300** provides sufficient friction against the walls of the vessel to overcome column strength of the cover walls **306** allowing for everting of the cover walls **306** over the retrieval structure **200** and obstruction **2** as discussed herein. As noted above, in alternate variations the cover **300** can expand a diameter or dimension that is equal to or less than the retrieval structure **200**.

(47) FIG. 4G illustrates proximal movement of the delivery wire **202**, which causes proximal translation of the obstruction **2** and retrieval structure **200**. Because the cover **300** is expanded against the walls of the vessel **6** the free end **304** of the cover **300** does not move or moves less than the fixed end **306** of the cover **300**. The fixed end **306** moves with the obstruction **2** and retrieval structure **200** in a proximal direction causing the cover walls **306** to evert over the obstruction **2** and retrieval structure **200**. Unlike a conventional funnel, the everting cover functions similar to a conveyor belt type movement as the obstruction and retrieval structure move together. This action allows for a passive type of protection since cover **300** does not need to be actuated over the obstruction **2** and retrieval structure **200** and can be performed in a quick manner by simply withdrawing the deployed retrieval device **100**.

(48) FIG. 4H illustrates a stage where the fixed end **306** of the cover **300** is now proximal to the free end **304**. As shown, the everted cover **300** forms a protective sheath or cover over the obstruction **2** and the retrieval structure **200**. FIG. 4H also illustrates how the cover **300** protects the obstruction **2** and retrieval structure **200** as they are pulled along the vessel and navigate the tortuous anatomy, walls of the vessel, as well as bifurcations **8**. The cover **300** and cover wall **306** also protects the vasculature from the surface of the retrieval structure **200** and obstruction **2**.

(49) FIG. 4I shows the obstruction **2** and retrieval structure **200** protected by the cover **300** as the retrieval device **100** is positioned against or within the access catheter **108** in preparation for removal from the body. The retrieval device **100** can remain outside of the access catheter **108** as the physician removes both devices from the body. Alternatively, the cover **300** can assist in pulling the retrieval device **100** and obstruction **2** into the access catheter **108** by compressing the obstruction **2** as it is pulled into the access catheter **108**.

(50) FIGS. 4J and 4K illustrate examples of an obstruction or other material **2** captured within a retrieval device **2** with a cover **300** further protecting the loaded retrieval device **200**.

(51) FIGS. 5A to 5K show a variety of cover configurations. FIG. 5A illustrates a retrieval device

100 having a retrieval structure **200** adjacent to a double layer cover **300** with an exterior wall **306** and an interior wall **308**.

(52) FIG. 5B shows a cover **300** with a free end **304** that tapers down about the delivery wire **202** where the cover **300** will eventually form a double wall configuration when the cover **300** everts over the retrieval structure **200**. The tapered free end **304** limits the cover **304** from moving once the retrieval structure **200** reaches the free end **304** thereby forming double wall protection over the retrieval structure **200**.

(53) FIGS. 5C and 5D show how a fixed end **302** of a cover **300** can be pre-shaped to reduce the force required to evert the cover wall **306** or to lower the threshold to trigger passive covering of the retrieval structure by the cover. For example, as shown in FIG. 5C, the fixed end **302** of the cover **300** can include a distal recess or opening **307**.

(54) FIG. 5E shows alternate variation of a passive cover **300** integrated into a retrieval device **100**. In this variation, the retrieval device **100** includes a control shaft or wire **202** to manipulate the working end of the retrieval device **100**. The cover **300** floats along the shaft **202** between two fixed anchors or nodes **220**, **222**. The cover **300** can float or slide between the fixed nodes **220**, **222**. The nodes **220**, **222** can comprise radiopaque marker bands, glue joints, or any other mechanical obstructions capable of stopping the translation of cover **300**. When the device **100** advances through a microcatheter, the rear or proximal node **220** limits rearward movement of the cover **300**. When positioned appropriately, the microcatheter can be withdrawn to expose the retrieval device **200** and cover **300** as described herein. When the retrieval structure **200** engages the obstruction (not shown) the retrieval device **100** can be withdrawn by pulling on the delivery shaft **202**. While this occurs, the cover **300**, being expanded against the vessel remains stationary (or moves at a slower rate than the obstruction and retrieval structure **200** due to the friction against the vessel wall). The retrieval structure **200** and clot enter the cover **300**, causing the distal node **222** to make contact with the rear end **320** of the cover **300**. This contact causes the retrieval structure **200** and cover **300** to translate as an integrated unit. It should be appreciated that the cover could be a single layer or double layer cover, and could have any of the wire design variables and termination variables described herein.

(55) FIG. 5F illustrates a cover having a pre-set flattened cover wall **304** at a fixed end **302** that is spaced from a proximal end of the retrieval structure **200**. FIGS. 5G to 5I illustrate various layered covers **300**. The layered covers allow for shortening the axial length of the cover and therefore shortens the required translation length. Layering of the cover wall **306** allows for a shortened deployed length of the cover **300** when deployed in the vessel or body structure. As the cover **300** everts over the retrieval structure **200** the layered wall **306** extends. As a result, shortening the length reduces the length that the cover **300** extends into the proximal vessels and reduces the length of that the retrieval structure **200** must travel to become protected by the cover **300**. This also helps shorten the distance required to move the device **100** to complete eversion of the cover **300**.

(56) FIG. 5J shows a cover **300** that is constructed directly onto the retrieval structure **200** rather than the delivery shaft **202**. This construction also assists in reducing the distance necessary to complete passive protection of the retrieval structure by the cover.

(57) FIG. 5K show a variation of a cover **300** that is mounted in a distal direction over the retrieval device **200** and then everted in a proximal direction over the wires or shaft **202** as shown by arrows **230**. Once everted, as shown by FIG. 5L, the device **100** is ready for deployment as discussed herein.

(58) FIGS. 6A to 6B illustrate a variation of a cover **350** for use as describe herein. Additionally, the cover **350** can be used with any obstruction retrieval device not limited to the retrieval baskets and stents described herein. The covers **350** disclosed herein can be used where the physician desires to shield the obstruction being removed from the frictional effects of the arteries or from the local anatomy (e.g., branching vessels, tortuous anatomy, or other substances on the vessel walls).

In use, the covers can be sized for use with guide catheters, micro-catheters, and/or distal access catheters. The covers can include any number of radiopaque marker bands to allow non-invasive imaging of the device (see marker **390** affixed between cover **350** and shaft **212** in FIG. 7B as one example). In any case, once the retrieval device captures a clot or obstruction, as described above, the device and clot are protected by the cover so that the cover eliminates or reduces direct contact between the interior of the wall of the vessel and the clot.

(59) FIGS. **6A** to **6C** show a variation in which a cover is created from one or more mesh tubes **372**. FIG. **6B** illustrates inversion of the tube **372** so that a first end **374** is drawn over the tube **372** towards a second end **376**. As shown in FIG. **6C**, this creates a double walled cover having an exterior wall **378** separated from an interior wall **380**. In one example, such a spacing or gap could range between 0.001 inches to 0.100 inches. However, any range is contemplated within alternative variations of the device. In some variations the inverted cover **350** is heat set to maintain a separation between layers or walls **378 380** of the cover **350**. Typically, if the cover **350** is not created from a radiopaque material, a marker band will be placed on the proximal end **376** and adjacent to a shaft or catheter to which the cover **350** is attached. In some variations the construction of the mesh material is compliant to allow for movement of a first part of the mesh relative to a second part of the mesh through compression and expansion of the mesh material. In such a case, the individual strands forming the mesh are moveable relative to one another to cause the mesh to be naturally compliant. Accordingly, this construction permits the inner wall **380** to move or deflect with the retrieval device and/or obstruction as the device is withdrawn into the cover **350**. In some variations, both ends of the mesh **374** and **376** are affixed to the catheter, shaft or wire.

(60) In many variations, the cover mesh is selected to minimize friction when the interior layer **380** moves against the exterior layer **378**. For example, the braid pattern, wire, wire diameter, angle of the braid and or other features can be selected to reduce friction between the outer layer **378** and inner layer **380**. This permits the inner layer **380** to move proximally with a retrieval device while the outer layer remains stationary. Again, as discussed above, the construction of the mesh permits compression and expansion of the mesh layer to permit movement of the inner layer while the outer layer remains affixed when engaged against the vessel wall. In certain variations, the cover is heat set so that the inner layer has cushioning and the ability to deflect to assist in movement of the inner layer. FIG. **5C** also illustrates a cover **350** having a tapered design.

(61) FIGS. **6D** to **6L** illustrate additional variations of cover construction to produce covers having more than two walls. For example, a mesh tube **372** is everted or drawn over a second end **376** in the direction **420**. As shown in FIG. **6E** this produces a dual layer cover having a open ends **422** and **424** and a folded end **426**. The dual layer tube is then folded over again in the direction **420**. This creates a cover construction with an exterior layer **378** and an interior layer **380** as well as a first intermediate layer **381** and a second intermediate layer **383**. As shown in FIG. **6F**, the cover can be set to assume the tapered shape having an opening at the first end **374** that is flared with the ends of the mesh at the second end **372**, which are ultimately affixed to a shaft, wire or other catheter device as described herein.

(62) FIG. **6G** illustrates another example of a cover construction. As shown, a first mesh tube **372** is placed coaxially with a second tube **372**. The concentric tubes are then everted in direction **420** to produce a four layer cover. As shown in FIG. **6H**, the cover can comprise an interior mesh layer **380**, and exterior mesh layer **378** as well as any number of intermediate layers **381, 383** depending on the number of tubes that are initially used. The second end **372** of the cover **350** includes four unconnected ends of the mesh tubes that can be affixed to a shaft or tube as discussed herein, while the first end **374** of the cover **350** can be shape set to taper from the opening.

(63) FIGS. **6I** to **6L** illustrate another example of the construction of a multi-wall cover. As shown in FIG. **6I**, a first end **374** of a mesh tube **372** is everted over and beyond a second end **376** in direction **420** to produce the configuration of FIG. **6J**. Next, the first end **374** is everted or folded

back in direction **420** to produce the configuration of FIG. **6K**. Finally, the first end **374** is folded again in direction **420** so that the ends **374** and **376** are even to produce the cover configuration shown in FIG. **6K**. Again, one end of the cover **350** can be set to form the tapered shape while the other respective end can be affixed to a catheter or shaft.

(64) Although the covers of the present disclosure are presented without additional structures, it should be noted that these covers are coupled with a shaft or other member so that the cover can be advanced within the target anatomy to assist in removal of a device, structure, or debris from the site.

(65) FIGS. **7A** to **7C** show additional variations of covers **350**. FIG. **7A** illustrates a cover in which the cover wall as defined by the inner layer **380** and outer layer **378** is set in a shape that varies along a length of the cover. For example, the end adjacent to the cover opening **382** can be set to a bulbous shape. Such a configuration assists in maintaining separation of layers **378** and **380**, which aids in re-entry of the retrieval device. Additional configurations of cover walls that vary in thickness are within the scope of this disclosure.

(66) One of the benefits of using a cover **350** as described herein is that the cover reduces flow through the vessel when deployed so that the retrieval device can remove the obstruction without the full force of the flow of blood opposing the obstruction. Typically, conventional devices relied upon the use of an inflated balloon to obstruct flow. However, use of a cover eliminates the need for total occlusion of blood flow. FIG. **7B** illustrates a further improvement on a cover **350** that aids in flow reduction. As shown, the cover **350** includes a dense region **386** and a relatively less dense region **384**. This configuration permits greater blood flow through the region **385** while region **386** reduces or prevents blood flow. Furthermore, the distal section of the cover is more flexible and conformable. Additional mesh layers can be added to any of the cover designs to alter flow characteristics or even provide reinforcement to the cover. Alternatively, or in combination, the braid density can be altered to adjust the porosity of the braid at different sections. Furthermore, additional braid layers can also be used to affect porosity of portions of the cover or even the entire cover. Deployment of a cover can reduce blood flow by 30% to 40%. Adding additional layers or coatings can additionally reduce flow.

(67) FIG. **7C** shows another variation of a cover **350** in which the mesh partially or totally is obscured using a polymeric coating **388** that reduces the permeability of the mesh design. Furthermore, drugs or other substances can be placed within the cover wall of any of the covers or can be deposited on the cover using the polymeric coatings. In some examples, the covers described herein can range from a length of 10 mm up to 50 mm. The OD at the opening of the cover can range from 7 mm and could range between 4 mm to 10 mm. Again, any range of dimensions is contemplated within the disclosure.

(68) The covers described herein can further be stacked on a device. For example, two or more covers can be placed on a device to provide added protection.

(69) The cover/reentry devices described herein can be constructed of any material currently used in vascular applications, including those discussed above. Furthermore, fabrication of the cover from a DFT material can provide additional benefits as the entire cover remains radiopaque and can be imaged non-invasively. Furthermore, the covers can be provided with any type of medicament or bioactive substance either in a polymer that coats the mesh or in a delivery agent within the mesh or between layers. Such substances include tpa, urokinase, IIb/IIIa inhibitors, and other clot disruptors or inhibitors.

(70) FIG. **8** illustrates another variation of a retrieval device **400** including a distal capture portion **426** coupled to one or more leading wires in the form of a main bundle **402**. The main bundle extends through a sheath **106** that includes a proximal capture portion **460**. The configuration of the retrieval device **400** can incorporate the proximal and distal capture portions discussed herein as well as various other configurations discussed in the commonly assigned patent applications noted above.

(71) An end **464** of the proximal capture portion **460** is affixed to a distal end of the sheath **106**. However, as noted above, other variations are within the scope of the disclosure. The main bundle **402** can optionally terminate at a handle **442**. As noted above, in certain variations, the main bundle is joined to a stiffer wire or stiffer bundle of wires. This allows the device **400** to have a very flexible distal section with a relatively stiffer proximal section. The device **400** can have a proximal bundle **403** that comprises either the exposed wires or a covering/tube over the wires. In certain variations, the bundle or wire **402**, **403** can be encapsulated with a coating. The device also includes a cover **300** adjacent to the retrieval device.

(72) The proximal end of the sheath **106** includes a sheath handle **444**. As discussed herein, axial movement of the bundle **402** or proximal bundle **403** (typically at the handle **442**) results in movement **126**, or translation of the bundle within the sheath **106**. This action moves the distal capture portion **426** (as shown by arrows **126**). In certain variations, the device **400** is loaded into a microcatheter (not shown but discussed above) that is delivered to the site of the obstruction and crosses the obstruction.

(73) In some variations, the sheath hub **444** includes one or more locking hubs **446**. Where actuation (either axial or rotational) of the locking hub **446** locks the main bundle **402** relative to the sheath handle **444** and sheath **106**. It follows that such locking action also locks the distal capture portion **426** relative to the proximal capture portion **460**. A variety of methods can be employed to increase a frictional interference between the locking hub **446** and the proximal bundle **403**. As a result, when a physician determines a length of an obstruction, the physician can set a spacing between the capturing portions **426** **460** by locking the proximal bundle **403** relative to the sheath hub **444**. Accordingly, the proximal bundle **403** can include any type of incremental markings to allow the physician to readily determine a spacing of the capturing portions. As illustrated, the sheath hub **444** can include additional injection ports to deliver fluid or other substances through the sheath **106**.

(74) As noted above, the device **400** can be used with a micro-catheter. In those variations it is important that the device **400** is loaded without damaging the distal bundle **402**, capture portions **426** **460**, and/or sheath **106**. As a result, the device **400** can include an optional cover **486** that reduces the proximal capture portion **460** (and/or the distal capture portion **426**) for loading within the microcatheter and/or sheath **106**.

(75) Another variation of the device **400** includes an insertion tool **480** slidably affixed to the sheath **480**. Because variations of the device **400** can be extremely flexible, the insertion tool **480** can be used to provide column strength to the sheath **106**, bundle **402** or other components as the device **400** is pushed into the microcatheter. The insertion tool comprises a rigid section **482** and a frictional coupler **484**. The rigid section **282** has a column strength that supports the device **400** to prevent buckling. The frictional coupler **484** can be a flexible material that allows an operator to squeeze or grip the coupler **484** to create a temporary frictional interface between the loading tool **480** and the device **400** (typically the sheath **106**). Such an action allows axial advancement of the device **400** as the loading tool **480** is advanced into the microcatheter. Once the rigid section **482** is fully inserted into the microcatheter, the operator releases the frictional coupler **484** and can withdraw the loading tool **480** from the catheter without withdrawing the device **400**. The insertion tool **480** can also include an optional loading tube **486** slidably coupled to the rigid section **482**. When used, the cover **486** can withdraw the proximal and distal capturing portion **226** **260** within the loading tube **486**. The loading tube **486** then couples to a microcatheter allowing the capturing portions to advance therein as the rigid section **482** and frictional coupler **484** advance the device **400** relative to the loading tube **486**.

(76) FIGS. **9A** to **9C** show cross sectional views taken along the line **9A-9A** in FIG. **2A**. As shown, the wire form construction described herein allows for a number of configurations depending on the particular application. For example, the individual wires **254** (as discussed herein) may themselves comprise a bundle of smaller wires or filaments. In addition, the wires can be selected

from materials such as stainless steel, titanium, platinum, gold, iridium, tantalum, Nitinol, alloys, and/or polymeric strands. In addition, the wires used in a device may comprise a heterogeneous structure by using combinations of wires of different materials to produce a device having the particular desired properties. For example, one or more wires in the device may comprise a shape memory or superelastic alloy to impart predetermined shapes or resiliency to the device. In some variations, the mechanical properties of select wires can be altered. In such a case, the select wires can be treated to alter properties including: brittleness, ductility, elasticity, hardness, malleability, plasticity, strength, and toughness.

(77) The device may include a number of radiopaque wires, such as gold and platinum for improved visibility under fluoroscopic imaging. In other words, any combination of materials may be incorporated into the device. In addition to the materials, the size of the wires may vary as needed. For example, the diameters of the wires may be the same or may vary as needed.

(78) In addition, the individual wires may have cross-sectional shapes ranging from circular, oval, d-shaped, rectangular shape, etc. FIG. 9A illustrates one possible variation in which a number of circular wires **254** are included around another larger wire **256**. Moreover, the device is not limited to having wires having the same cross-sectional shape or size. Instead, the device can have wires having different cross-sectional shapes. For example, as shown in FIG. 9B, one or more wires **256** can have a different cross-sectional shape or size than a remainder of the wires **254**. Clearly, any number of variations is within the scope of this disclosure. This construction can apply to the retrieval portion, capturing portion and/or the covering portion of the device.

(79) To illustrate one such example, a device can have 8-12 wires made of 0.003" round superelastic material (e.g., Nitinol). The device may additionally have 2-4 wires made from 0.002" platinum for fluoroscopy. Of the 8-12 Nitinol wires, 1-4 of these wires can be made of a larger diameter or different cross-section to increase the overall strength of the device. Finally, a couple of polymer fibers can be added where the fibers have a desired surface property for clot adherence, etc. Such a combination of wires provides a composite device with properties not conventionally possible in view of other formation means (such as laser cutting or etching the shape from a tube or joining materials with welds, etc.). Clearly, any number of permutations is possible given the principles of the invention.

(80) In another example, the device may be fabricated from wires formed from a polymeric material or composite blend of polymeric materials. The polymeric composite can be selected such that it is very floppy until it is exposed to either the body fluids and or some other delivered activator that causes the polymer to further polymerize or stiffen for strength. Various coatings could protect the polymer from further polymerizing before the device is properly placed. The coatings could provide a specific duration for placement (e.g., 5 minutes) after which the covering degrades or is activated with an agent (that doesn't affect the surrounding tissues) allowing the device to increase in stiffness so that it doesn't stretch as the thrombus is pulled out. For example, shape memory polymers would allow the device to increase in stiffness.

(81) In another variation, one or more of the wires used in the device may comprise a Drawn Filled Tube (DFT) such as those provided by Fort Wayne Metals, Fort Wayne, Ind. As shown in FIG. 9C, such a DFT wire **252** comprises a first material or shell **258** over a second material **260** having properties different from the outer shell. While a variety of materials can be used, one variation under the present devices includes a DFT wire having a superelastic (e.g., Nitinol) outer tube with a radiopaque material within the super-elastic outer shell. For example, the radiopaque material can include any commercially used radiopaque material, including but not limited to platinum, iridium, gold, tantalum, or similar alloy. One benefit of making a capturing portion from the DFT wire noted above, is that rather than having one or more markers over the capturing portion, the entire capturing portion can be fabricated from a super-elastic material while, at the same time, the super-elastic capturing portion is made radiopaque given the core of radiopaque material within the super-elastic shell. Clearly, any composite DFT wire **252** can be incorporated into the system and

capturing portions described herein.

(82) Another aspect applicable to all variations of the devices is to configure the devices or portions thereof that engage the obstruction to improve adherence to the obstruction. One such mode includes the use of coatings that bond to certain clots (or other materials causing the obstruction.) For example, the wires may be coated with a hydrogel or adhesive that bonds to a thrombus. Accordingly, as the device secures about a clot, the combination of the additive and the mechanical structure of the device may improve the effectiveness of the device in removing the obstruction. Coatings may also be combined with the capturing portions or catheter to improve the ability of the device to encapsulate and remove the obstruction (e.g., a hydrophilic coating).

(83) Such improvements may also be mechanical or structural. Any portion of the capturing portion can have hooks, fibers, or barbs that grip into the obstruction as the device surrounds the obstruction. The hooks, fibers, or barbs **370** can be incorporated into any portion of the device. However, it will be important that such features do not hinder the ability of the practitioner to remove the device from the body.

(84) In addition to additives, the device can be coupled to an RF or other power source (such as **14** or **16** in FIG. **1**), to allow current, ultrasound or RF energy to transmit through the device and induce clotting or cause additional coagulation of a clot or other the obstruction.

(85) FIGS. **10A** to **10E** illustrate additional variations of covers **300** for use as described above. For example, as show in FIG. **10A**, a cover **300** can comprise a single wire, coil, or laser cut tube **351**. Alternatively, as shown in FIG. **10B**, the cover **300** can comprises two or more **351**, **352** wires or coils. FIG. **10C** shows a cover **300** comprising a coil **351** inside a mesh structure **354**. A variation of the device shown in FIG. **10C** can include a compliant atraumatic mesh **354** that is radially supported by the coil (whether interior or exterior to the mesh). The coil **351** provides the outward force against the vessel. FIG. **10D** illustrates a polymeric film or membrane **356** coupled to a coil **351**. The polymeric film **356** can be permeable to fluid flow or impermeable. FIG. **10E** illustrates a dual layer braid construction having an inner braid **358** and an outer braid **360**. The braids can be constructed to have unique properties. For example, the inner braid **358** can be composed of fewer wires or larger diameter wires, such that it provides an expansion force against the vessel wall. The outer braid **360** can comprise a softer construction and increased compliance. Accordingly, it can be comprised of a number of smaller diameter wires having a denser pattern to provide increased surface area to protect the obstruction as it is removed from the body. Alternatively, these two constructional elements (e.g., braids of varying diameters) can be combined into a single layer or even multiple layers for the cover.

(86) FIG. **11A** illustrates yet another variation of a device **100** having a retrieval structure **200** and cover **300** where the cover is simply fabricated from the same material as the retrieval structure so long as it functions as described herein. The variation can optionally include one or more barbs **370** to increase resistance against a vessel wall.

(87) FIGS. **11B** and **11C** illustrate a variation where the cover **300** comprises a balloon material. FIG. **11B** illustrates the balloon cover **370** prior to deployment. FIG. **11C** illustrates the balloon cover **370** once deployed.

(88) The retrieval devices described herein can optionally comprise elongated stents **400** as shown in FIGS. **12A** to **12E**. These stents **400** can include any number of features to better assist the stent **400** in becoming enmeshed into the obstruction. For example, FIG. **12A** illustrates a variation of a stent **400** affixed to a shaft **412**. As noted herein, the shaft **412** can include a lumen extending therethrough. Alternatively, the shaft **412** can include a solid member with the stent **400** affixed to a distal end thereof. The variation shown in FIG. **12A** includes a stent where a distal end **414** that is “closed off” by intersecting elements or wires **402** **403**. Accordingly, any of the variations of the stents disclosed herein can include an open lumen type stent or a closed lumen type stent as shown in FIG. **12A**. As noted herein, the wires forming the stent **400** can comprise a single wire that is wound from a first direction (e.g., from proximal to distal) and then wound back in a second

direction (e.g., from distal to proximal).

(89) FIG. 12A also illustrates a stent **400** comprised of twisted wires **402** or elements. For example, FIG. 12B shows a magnified view of the section **12B** in FIG. 12A. As illustrated, the elements **402 403** are twisted to increase the surface area at the exterior perimeter of the stent **400**. The twisting or spiraling of the elements **402 403** creates additional surface area to increase the ability of the stent **400** to capture debris, thrombus, foreign body, etc. as the stent is expanded against the debris. The twisting elements **402 403** can twist along the entire length of the stent **400** or along one or more portions of the stent. In certain variations, the twisting of the elements **402 403** is sufficiently loose such that as the stent expands into a clot or obstruction, the twisted pairs slightly separate to allow material to become trapped between the elements making up the pairs. The construction shown in FIGS. 12A and 12B also provide an additional benefit to a retrieval stent. In the illustrated variation, the twisted or spiraling elements interlock with crossing elements to form intersections **405** that provided added radial expansive force. As shown, a first twisted element **407** passes in between elements **402 403** of an intersecting element **409**. When in an expanded state, the element on the interior of the intersection **405** (in this case element **403**) provides an added outward radial force against the intersection **405**. However, since the elements are not affixed but instead are slidable at the intersection **405**, the force required to linearize and compress the stent **400** is reduced due to the fact that the intersections are not affixed but slidable over the adjacent elements. This reduced linearization force allows the stent to be compressed to a small diameter for positioning within a microcatheter but allow for a significant radial expansive force once removed from the microcatheter. This design allows for a reduction in radial force of the stent against the vessel wall when the stent is pulled and removed from the vessel. However, this design also provides a high degree of radial force due to the interweaving of elements when the stent is deployed in the vessel prior to withdrawal of the stent.

(90) FIGS. 12C to 12F illustrate another variation of types of stents **400** that have an irregular surface at an exterior of the stent **400** that is formed by an intersection of elements **402 403**. The intersection or crossing of the elements forms a type of barb or knuckle **416** that creates an irregular surface on the exterior of the stent **400**. FIG. 12C illustrates a variation of a stent **400** having a plurality of knuckles **52** that are radially spaced about an axis **390** of the stent **400**. FIG. 12E shows another variation of a stent **400** with knuckles **416** aligned with an axis **390** of the stent **400** as shown in FIG. 12D. Although the figures show the axial and radial aligned knuckles **416** on separate devices, both types of knuckles **416** can be incorporated into a single stent structure. Varying the alignment of knuckles can permit increased radial force as the stent expands into the obstruction or increased flexibility as the stent navigates through tortuous anatomy.

(91) FIG. 12G illustrates a proximal end of the stent structure **400** as shown, a plurality of elements **402** and **403** extend along the shaft **412** and diverge to form the fluid permeable closed proximal end of the stent structure **400**. The elements **402** and **403** that extend along the shaft **412** can be covered by a sheath, tube, spiral cut tube, or any structure **418** that prevents separation of the elements **402 403**. A variation of the stent structure **402** includes a construction where the elements **402 403** are not glued, welded, or have any similar type of joint in the distal portion **420** of the shaft **412**. Instead, the joint **411** is located proximal to the distal section of the shaft **412** in an intermediate section **422**. Because joints or other similar features reduce flexibility of the joined structure, positioning the joints **411** in a proximal area allows the distal portion **420** of the shaft to remain flexible.

(92) The methods described herein may also include treating the obstruction prior to attempting to remove the obstruction. Such a treatment can include applying a chemical or pharmaceutical agent with the goal of making the occlusion shrink or to make it more rigid for easier removal. Such agents include, but are not limited to chemotherapy drugs, or solutions, a mild formalin, or aldehyde solution.

(93) As for other details of the present invention, materials and manufacturing techniques may be

employed as within the level of those with skill in the relevant art. The same may hold true with respect to method-based aspects of the invention in terms of additional acts that are commonly or logically employed. In addition, though the invention has been described in reference to several examples, optionally incorporating various features, the invention is not to be limited to that which is described or indicated as contemplated with respect to each variation of the invention.

(94) Various changes may be made to the invention described and equivalents (whether recited herein or not included for the sake of some brevity) may be substituted without departing from the true spirit and scope of the invention. Also, any optional feature of the inventive variations may be set forth and claimed independently, or in combination with any one or more of the features described herein. Accordingly, the invention contemplates combinations of various aspects of the embodiments or combinations of the embodiments themselves, where possible. Reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in the appended claims, the singular forms “a,” “and,” “said,” and “the” include plural references unless the context clearly dictates otherwise.

(95) It is important to note that where possible, aspects of the various described embodiments, or the embodiments themselves can be combined. Where such combinations are intended to be within the scope of this disclosure.

Claims

1. A device for deployment within a blood vessel using a catheter, the device comprising: a shaft having a distal end and a proximal end; a braided cover having a free and open distal section and a proximal end coupled to the shaft at a location proximal to the distal end of the shaft, wherein the proximal end comprises at least one peak pointing in a proximal direction and at least one valley pointing in a distal direction, wherein the braided cover is configured to self-expand against the vessel wall when deployed from the catheter; and an expandable helical coils within the braided cover and configured to conform to a profile of the braided cover.
2. The device of claim 1, wherein the braided cover comprises a nitinol braid.
3. The device of claim 1, wherein the braided cover is formed from a mesh tube.
4. The device of claim 1, wherein the braided cover permits continued blood flow through the blood vessel when self-expanded against the vessel wall.
5. The device of claim 1, further comprising a node positioned on the shaft between the distal end and the proximal end.
6. The device of claim 5, wherein the node is configured to obstruct movement of the braided cover relative to the shaft.
7. The device of claim 5, wherein the node comprises a radiopaque marker band.
8. The device of claim 5, wherein the node is a first node, and the device further comprises a second node positioned on the shaft between the distal end and the proximal end, the second node being spaced apart from the first node.
9. The device of claim 1, further comprising a radiopaque marker at the proximal end of the braided cover.
10. The device of claim 1, wherein the helical coil is radiopaque.
11. The device of claim 1, wherein the helical coil is a single coil configured to provide radial support to the braided cover.
12. A device for deployment within a blood vessel using a catheter, the device comprising: a shaft having a distal end and a proximal end; and a cover configured to self-expand into contact with the vessel wall when deployed from the catheter, the cover including: a mesh structure having a free and open distal section and a proximal end coupled to the shaft at a location proximal to the distal end of the shaft, wherein the proximal end comprises at least one peak pointing in a proximal direction and at least one valley pointing in a distal direction, and an expandable helical coils inside

the mesh structure and configured to conform to a profile of the mesh structure.

13. The device of claim 12, wherein the mesh structure comprises a braid.

14. The device of claim 12, wherein the mesh structure comprises a tube.

15. The device of claim 12, wherein the cover permits continued blood flow through the blood vessel when self-expanded against the vessel wall.

16. The device of claim 12, further comprising at least one anchor coupled to the shaft between the distal end portion and the proximal end portion.

17. The device of claim 16, wherein the at least one anchor is configured to constrain translation of the cover along the shaft.

18. The device of claim 16, wherein the at least one anchor comprises a radiopaque marker band.

19. The device of claim 16, wherein the at least one anchor comprises a distal anchor and a proximal anchor.

20. The device of claim 12, further comprising a radiopaque marker at the proximal end of the cover.

21. The device of claim 12, wherein the helical coil is radiopaque.

22. The device of claim 12, wherein the helical coil is a single coil configured to provide radial support to the mesh structure.
