

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397768
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kim; Seo Hyoung et al.

Vehicle brake system

Abstract

Disclosed a vehicle brake system in which the structure required when transmitting a wake-up signal in response to a pedal input can be further simplified, the vehicle brake system comprising: a pedal travel sensor (PTS) which senses whether pressure is being applied to the pedal and the amount of pressure being applied; and a wake recognition circuit which is connected to the PTS such that electricity can flow directly in both directions, and which receives a signal from the PTS and wakes up an electronic control unit (ETU), wherein the PTS delivers the output signal to the wake recognition circuit if the output signal is at least a preset value.

Inventors:	Kim; Seo Hyoung (Gyeonggi-do, KR), Kim; Sang Woo (Gyeonggi-do, KR), Yang; Mo Ran (Gyeonggi-do, KR), Bae; Sang Won (Gyeonggi-do, KR), Jung; You Ri (Gyeonggi-do, KR), Kim; Sun Joo (Gyeonggi-do, KR)
Applicant:	HL MANDO CORPORATION (Gyeonggi-do, KR)
Family ID:	1000008777840
Assignee:	HL MANDO CORPORATION (Gyeonggi-do, KR)
Appl. No.:	18/027101
Filed (or PCT Filed):	September 24, 2021
PCT No.:	PCT/KR2021/013051
PCT Pub. No.:	WO2022/065920
PCT Pub. Date:	March 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230331209 A1	Oct. 19, 2023

Foreign Application Priority Data

KR	10-2020-0124823	Sep. 25, 2020
KR	10-2020-0124824	Sep. 25, 2020
KR	10-2020-0124826	Sep. 25, 2020
KR	10/2020/0124827	Sep. 25, 2020
KR	10-2021-0040524	Mar. 29, 2021

Publication Classification

Int. Cl.: B60T17/22 (20060101)

U.S. Cl.:

CPC B60T17/22 (20130101); B60T2220/04 (20130101); B60T2270/00 (20130101)

Field of Classification Search

CPC: B60T (1/10); B60T (3/586); B60T (7/042); B60T (8/00); B60T (8/172); B60T (8/3255); B60T (13/586); B60T (17/22); B60T (2220/04); B60T (2270/00); B60T (2270/06); B60W (10/18); B60W (30/18127); B60W (40/105); B60W (60/0001); B60Q (1/0076); B60Q (1/44); B60Q (1/441); B60Q (1/444); F16D (61/00)

USPC: 701/70; 701/71; 701/76; 701/77

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0219048	12/2005	Ueno	74/560	B60T 7/042
2006/0284481	12/2005	Yone	303/155	B60T 7/042
2007/0112473	12/2006	Ueno et al.	N/A	N/A
2008/0306667	12/2007	Karnjate	303/121	B60T 7/042
2014/0368027	12/2013	Bohm	303/14	B60T 8/4081
2019/0263382	12/2018	Parsels	N/A	B60W 30/20
2022/0185245	12/2021	Gabara	N/A	B60T 7/122

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2010-271298	12/2009	JP	N/A
2015-042526	12/2014	JP	N/A
2016-011833	12/2015	JP	N/A
10-1536196	12/2014	KR	N/A
10-2016-0032659	12/2015	KR	N/A
10-1904710	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report for PCT/KR2021/013051 mailed on Jan. 3, 2022 and its English Machine Translation by the WIPO (now published as WO 2022/065920). cited by applicant
Written Opinion of the International Searching Authority for PCT/KR2021/013051 mailed on Jan.

Primary Examiner: Huynh; Hai H

Assistant Examiner: Hoang; Johnny H

Attorney, Agent or Firm: WOMBLE BOND DICKINSON (US) LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the U.S. National Stage of International Patent Application No. PCT/KR2021/013051 filed on Sep. 24, 2021, which claims priority to and the benefit of Korean Patent Application No. 10-2020-0124823, filed on Sep. 25, 2020, Korean Patent Application No. 10-2020-0124826, filed on Sep. 25, 2020, Korean Patent Application No. 10-2020-0124827, filed on Sep. 25, 2020, Korean Patent Application No. 10-2020-0124824, filed on Sep. 25, 2020, and Korean Patent 10 Application No. 10-2021-0040524, filed on Mar. 29, 2021, the disclosures of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a vehicle brake system, and more specifically to a vehicle brake system in which the structure required when transmitting a wake-up signal in response to a pedal input can be further simplified.

BACKGROUND ART

(3) The vehicle braking system refers to a system for decelerating or stopping the speed of a driving vehicle. A typical vehicle braking system may be connected to a pedal, and driven based on whether and how much the pedal is pressed.

(4) The conventional vehicle braking system senses whether pressure is being applied to the pedal and the amount of pressure being applied by a pedal travel sensor (PTS), and an electronic control unit (ECU) receives an output signal from the PTS to brake the vehicle.

(5) In addition, the pedal may be connected to a separate circuit that is independent of the PTS and outputs a signal to the ECU requiring a wake-up signal by recognizing the application of the pedal. Accordingly, when the pedal is applied, a wake-up signal may be transmitted to the ECU of the vehicle braking system, and the ECU may be automatically started.

(6) However, this type of vehicle braking system requires a separate wiring for transmission/reception of a wake-up signal between the pedal and the ECU. That is, in addition to the existing circuit, additional installation of wiring between the pedal and the ECU is required. This may increase the overall weight of the vehicle braking system, which further increases the manufacturing cost.

(7) Accordingly, there will be a need to develop a vehicle braking system in which the structure required when transmitting a wake-up signal in response to a pedal input can be further simplified.

(8) Korean Registered Patent No. 10-1904710 discloses a braking control method of a smart booster for a vehicle. Specifically, the braking control method in which minimum power is supplied to an ECU of a vehicle braking system when a pedal is applied is disclosed.

(9) However, in this type of braking control method, since the wake-up signal transmission circuit according to a pedal input is formed independently of the PTS, transmission/reception wiring between the pedal and the ECU is additionally required.

(10) Korean Patent Application Laid-Open No. 10-2016-0032659 discloses a wake-up system of a

wake-up packet. Specifically, the wake-up system for generating a wake-up signal by receiving a signal from a pedal is disclosed.

(11) However, this type of wake-up system does not disclose a specific coupling relationship between the pedal and the wake-up system. Furthermore, the coupling relationship between the ECU or PTS of the vehicle braking system and the wake-up system is not disclosed. (Related Art Document 1) Korean Registered Patent No. 10-1904710 (Oct. 15, 2018) (Related Art Document 2) Korean Patent Application Laid-Open No. 10-2016-0032659 (Mar. 24, 2016)

DISCLOSURE

Technical Problem

(12) An object of the present disclosure is to provide a vehicle braking system in which the structure required when transmitting a wake-up signal in response to a pedal input can be further simplified.

(13) Another object of the present disclosure is to provide a vehicle braking system in which standby power can be further reduced.

(14) Still another object of the present disclosure is to provide a vehicle braking system in which the manufacturing cost can be further reduced.

Technical Solution

(15) In order to achieve the above objects, the vehicle brake system according to an exemplary embodiment of the present disclosure includes a pedal travel sensor (PTS) which senses whether pressure is being applied to the pedal and the amount of pressure being applied; and a wake recognition circuit which is connected to the PTS such that electricity can flow directly in both directions, and which receives a signal from the PTS and wakes up an electronic control unit (ETU), wherein the PTS delivers the output signal to the wake recognition circuit if the output signal is at least a preset value.

(16) In addition, the PTS may transmit the output signal to the wake recognition circuit, maintain the output signal for a preset time and transmit the output signal to the wake recognition circuit.

(17) In addition, the wake recognition circuit may be operated at all times by power.

(18) In addition, the PTS may be directly interconnected with the pedal.

(19) In addition, the PTS may be provided with a press switch for sensing whether pressure is being applied to the pedal and the amount of pressure being applied by coming into contact with the pedal, when the pedal is pressed and rotated.

(20) In addition, the PTS may be connected to the power of the ECU such that electricity can flow directly in both directions so as to receive power at all times.

(21) In addition, the PTS may be connected to a regulator of the ECU such that electricity can flow directly in both directions, and transmit the output signal to the regulator, if the output signal is at least a preset value, and wherein the regulator may wake up by receiving the output signal.

(22) In addition, the PTS may include a printed circuit board (PCB); a magnet whose magnetic strength is changed as the pedal is pressed; a sensor circuit disposed on one surface of the PCT and configured to sense whether pressure is being applied to the pedal and the amount of pressure being applied based on a change in the magnetic strength; and a switch circuit for outputting a signal to the wake recognition circuit, if the change in magnetic strength is at least a preset change amount.

(23) In addition, the switch circuit may be connected to a separate battery independent of the power of the ECU such that electricity can flow directly in both directions so as to receiver power at all times.

(24) In addition, the wake recognition circuit may be built in a central electronic module (CEM) independent of the ECU, and wherein the ECU may supply power to the PTS, when the wake recognition circuit receives the output signal from the PTS.

(25) In addition, the switch circuit may be disposed on the one surface of the PCB.

(26) In addition, the switch circuit may be disposed on the other surface opposite to the one surface of the PCB.

(27) In addition, the PTS may be spaced apart from the pedal.

(28) In addition, the PTS may include a printed circuit board (PCB); a magnet whose magnetic strength is changed as the pedal is pressed; a sensor circuit disposed on one surface of the PCT and configured to sense whether pressure is being applied to the pedal and the amount of pressure being applied based on a change in the magnetic strength; and a switch circuit for outputting a signal to the wake recognition circuit, if the change in magnetic strength is at least a preset change amount.

(29) In addition, the output signal of the PTS may be a pulse width modulation (PWM) signal, and wherein the wake recognition circuit may include a supervisor circuit for monitoring the PWM signal, and transmitting the PWM signal to the wake recognition circuit, when the PWM signal reaches a preset value.

Advantageous Effects

(30) Among the various effects of the present disclosure, effects that can be obtained through the above-described technical solution are as follows.

(31) First, the vehicle braking system includes a pedal travel sensor (PTS) for sensing whether pressure is being applied to the pedal and the amount of pressure being applied, and a wake recognition circuit which is connected to the PTS such that electricity can flow directly in both directions, and receives a signal from the PTS to wake up the electronic control unit (ECU).

(32) Accordingly, a wake-up signal is transmitted to the ECU when the pedal is applied without a separate circuit for recognizing a pedal input such that the ECU can be automatically started.

Accordingly, a separate wiring for transmitting and receiving a wake-up signal between the pedal and the ECU is not required. As a result, the overall weight of the vehicle braking system can be reduced, and the structure can be further simplified. Furthermore, the spatial freedom inside the vehicle braking system can also be improved.

(33) In addition, the PTS includes a switch circuit that outputs a signal to the wake recognition circuit when the pedal is applied. The switch circuit is connected to a separate battery independent of the ECU's power supply such that electricity can flow directly in both directions so as to receive power at all times.

(34) The wake recognition circuit is built in a central electronic module (CEM) independent of the ECU, and receives a wake-up signal from the PTS and sends it to the ECU. The ECU receives the wake-up signal from the CEM and supplies power to the PTS.

(35) Therefore, when the vehicle is in an OFF state, that is, in a parking state, the wake-up operation may be performed by a separate battery, and ECU power is not required. Accordingly, the standby power of the ECU can be further reduced. Furthermore, the efficiency of the ECU can be further improved.

(36) In addition, the switch circuit senses whether pressure is applied to the pedal based on the magnetic strength of a magnet provided in the existing PTS. That is, the switch circuit senses whether pressure is being applied to the pedal by using a magnet provided in the existing PTS.

(37) Accordingly, the cost required for structural replacement of the existing PTS can be further reduced. Furthermore, the manufacturing cost of the vehicle braking system can be further reduced.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a conceptual diagram illustrating the vehicle braking system according to an exemplary embodiment of the present disclosure.

(2) FIG. 2 is a conceptual diagram illustrating output results of a PTS and wake recognition circuit provided in the vehicle braking system of FIG. 1.

(3) FIGS. 3 to 4 are conceptual diagrams illustrating the coupling relationship between a PTS, an ECU and a battery provided in the vehicle braking system of FIG. 1.

(4) FIG. 5 is a conceptual diagram illustrating a PTS provided in the vehicle braking system of FIG. 1.

(5) FIG. 6 is a conceptual diagram illustrating the vehicle braking system according to another exemplary embodiment of the present disclosure.

(6) FIG. 7 is a conceptual diagram illustrating the coupling relationship between a PTS, an ECU, a battery and a CEM provided in the vehicle braking system of FIG. 6.

(7) FIG. 8 is a conceptual diagram illustrating the vehicle braking system according to still another embodiment of the present disclosure.

(8) FIG. 9 is a conceptual diagram illustrating the coupling relationship between a PTS and an ECU included in the vehicle braking system of FIG. 8.

(9) FIG. 10 is a conceptual diagram illustrating the wake-up sensing process according to a change in magnetic strength of the PTS of FIG. 9.

(10) FIG. 11 is a conceptual diagram illustrating another exemplary embodiment of a PTS and an ECU provided in the vehicle braking system of FIG. 8.

MODES OF THE INVENTION

(11) Hereinafter, the vehicle braking system 1 according to an exemplary embodiment of the present disclosure will be described in more detail with reference to the drawings.

(12) In the following description, in order to clarify the characteristics of the present disclosure, the descriptions of some components may be omitted.

(13) In the present specification, the same reference numerals are assigned to the same components even in different exemplary embodiments, and the overlapping descriptions thereof will be omitted.

(14) The accompanying drawings are only for easy understanding of the exemplary embodiments disclosed in the present specification, and the technical ideas disclosed in the present specification are not limited by the accompanying drawings.

(15) The singular expression includes the plural expression unless the context clearly dictates otherwise.

(16) Hereinafter, the vehicle braking system 1 according to an exemplary embodiment of the present disclosure will be described with reference to FIGS. 1 to 5.

(17) The vehicle braking system 1 refers to a system for decelerating or stopping the speed of the vehicle 2 in motion. The vehicle braking system 1 is connected to a pedal 10 and is driven based on whether pressure is applied to the pedal 10 and the amount of pressure being applied.

(18) In addition, the vehicle braking system 1 may be automatically started by generating a wake-up signal when the pedal 10 is applied.

(19) The vehicle braking system 1 according to the present exemplary embodiment includes a pedal 10, a pedal travel sensor (PTS) 20, an electronic control unit (ECU) 30, a wake recognition circuit 40 and a battery 50.

(20) The pedal 10 is applied by the user and serves to generate a driving signal to the vehicle braking system 1.

(21) The pedal 10 controls the driving and stopping of the vehicle braking system 1 according to whether it is applied. In addition, the braking force of the vehicle 2 may be determined according to the degree of application of the pedal 10.

(22) The PTS senses whether the pedal 10 is applied and the degree of application.

(23) The pedal travel sensor (PTS) 20 senses whether pressure is being applied to the pedal and the amount of pressure being applied, and transmits an output result based on the sensing result to the wake recognition circuit 40 to be described below.

(24) The PTS 20 may be classified into an external type or a built-in type depending on whether the PTS 20 is directly coupled to the pedal 10. In the exemplary embodiment illustrated in FIG. 1, the PTS 20 is formed as an external PTS 20 that is directly coupled to the pedal 10.

(25) However, the PTS 20 transmits the output signal to the wake recognition circuit 40 if the output signal is at least a preset value, and does not transmit it to the wake recognition circuit 40 if

the output signal is less than a preset value. The detailed description thereof will be provided below.

(26) A plurality of PTSs **20** may be provided. In an exemplary embodiment, the PTS **20** may be provided with a total of two, including a PDT channel and a PDF channel.

(27) The PTS **20** includes a circuit for receiving power from the ECU **30** and a circuit for transmitting an output signal according to the sensing result to the ECU **30**.

(28) The electronic control unit (ECU) **30** is in charge of controlling the driving state of the vehicle braking system **1**.

(29) The ECU **30** is electrically connected to the PTS **20**. The ECU **30** includes a circuit for supplying power to the PTS **20** and a circuit for receiving an output signal according to the sensing result of the PTS **20**.

(30) In the illustrated exemplary embodiment, the ECU **30** includes a first PTS controller **310** and a second PTS controller **320**.

(31) The first PTS controller **310** and the second PTS controller **320** are respectively connected to different PTSs **20** such that electricity can flow in both directions. In an exemplary embodiment, the first PTS controller **310** and the second PTS controller **320** may be connected to each other with the PTS **20** formed of different channels such that electricity can flow in both directions.

(32) The first PTS controller **310** and the second PTS controller **320** receive output signals sensed from the connected PTS **20**, respectively, and supply power to the connected PTS **20**.

(33) In the illustrated exemplary embodiment, the circuits transmitted from the PTS **20** to the ECU **30** are connected to the wake recognition circuit **40**, respectively, such that electricity can flow in both directions.

(34) The wake recognition circuit **40** is a recognition circuit for generating a wake-up signal to the ECU **30**.

(35) The wake recognition circuit **40** is connected to the PTS **20** such that electricity can directly flow in both directions. In addition, the wake recognition circuit **40** receives an output signal of the PTS **20** and outputs it to the outside.

(36) Accordingly, a wake-up signal is transmitted to the ECU **30** when the pedal **10** is applied without a separate circuit for recognizing the application of the pedal **10** such so that the ECU **30** may be automatically started. Accordingly, a separate wiring for transmission and reception of a wake-up signal between the pedal **10** and the ECU **30** is not required. As a result, the overall weight of the vehicle braking system **1** may be reduced and the structure may be further simplified. Furthermore, the spatial freedom inside the vehicle braking system **1** may also be improved.

(37) In the illustrated exemplary embodiment, the wake recognition circuit **40** is formed inside the ECU **30**. However, the wake recognition circuit **40** is not limited to the above exemplary embodiment, and may be formed in various structures connected to the PTS **20** such that electricity can directly flow in both directions.

(38) In the illustrated exemplary embodiment, the wake recognition circuit **40** is connected to a circuit for transmitting an output signal of the PTS **20** to the first PTS control unit **310**, and a circuit for transmitting it to the second PTS control unit **320**, respectively.

(39) However, the structure of the wake recognition circuit **40** is not limited to the illustrated exemplary embodiment, and may be formed in various structures capable of being connected to the PTS **20** such that electricity can directly flow in both directions. For example, the wake recognition circuit **40** may be connected to any one of a circuit for transmitting an output signal of the PTS **20** to the first PTS control unit **310** and a circuit for transmitting it to the second PTS control unit **320**.

(40) Hereinafter, the output of the wake recognition circuit **40** according to the output result of the PTS **20** will be described with reference to FIG. 2.

(41) FIGS. 2(a) and 2(b) illustrate the outputs of the PTS **20** and the wake recognition circuit **40** according to analog and digital signals, respectively.

(42) As described above, when the output signal of the PTS **20** is at least a preset value, the wake

recognition circuit **40** receives the output signal and outputs it to the outside. This may be implemented by, for example, an edge trigger circuit provided between the PTS **20** and the wake recognition circuit **40**.

(43) When the output signal of the PTS **20** reaches a preset value, the output signal is maintained for a preset time and transmitted to the wake recognition circuit **40**. This is to prevent a chattering phenomenon caused by a frequent wake-up signal.

(44) Hereinafter, an exemplary embodiment of the external PTS **20** will be described with reference to FIG. 3.

(45) In the exemplary embodiment illustrated in FIG. 3, the PTS **20** is provided with a press switch that contacts the pedal **10** when the pedal **10** is pressed and rotates to sense whether pressure is being applied the pedal **10** and the amount of pressure being applied to the pedal.

(46) The PTS **20** is connected to the battery **50** for supplying power to the ECU **30** such that electricity can directly flow in both directions, and receives power from the battery **50** at all times.

(47) The ECU **30** includes a regulator **330**.

(48) The regulator **330** is directly connected to the PTS **20** such that electricity can flow in both directions, and receives a wake-up signal from the PTS **20** to output power. Specifically, when the output signal of the PTS **20** is at least a preset value, the PTS **20** receives a wake-up signal to output power.

(49) In addition, the power output from the regulator **330** is supplied to the PTS **20**.

(50) Hereinafter, another exemplary embodiment of the external PTS **20** will be described with reference to FIGS. 4 to 5.

(51) In the exemplary embodiment illustrated in FIGS. 4 to 5, the PTS **20** includes a sensor circuit **210**, a switch circuit **220**, a printed circuit board (PCB) **230**, a magnet **240** and a magnetic flux concentration plate **250**.

(52) The sensor circuit **210** senses whether pressure is being applied to the pedal and the amount of pressure being applied through the magnet **240** to be described below. The magnet **240** is coupled to one end of the pedal **10**, rotates together with the pedal **10** when pressure is applied to the pedal **10**, and causes a change in magnetic strength. Accordingly, the sensor circuit **210** may sense whether pressure is being applied to the pedal and the amount of pressure being applied from the change in the magnetic strength of the magnet **240**.

(53) The switch circuit **220** outputs a signal to the wake recognition circuit **40** when the change in magnetic strength of the magnet **240** is at least a preset change amount. In this case, the switch circuit **220** measures a change in magnetic strength of the same magnet **240** as the sensor circuit **210**. Accordingly, the cost required for structural replacement of the existing PTS **20** may be further reduced. Furthermore, the manufacturing cost of the vehicle braking system **1** may be further reduced.

(54) In addition, the vehicle braking system **1** further includes a separate battery **50** independent of the power source of the ECU **30**. The switch circuit **220** is connected to a separate battery **50** such that electricity can flow in both directions, and receives constant power therefrom.

(55) A wake-up signal generation process of the ECU **30** when the pedal **10** is applied is as follows.

(56) (1) When the pedal **10** is pressed in the ignition OFF state of the vehicle **2**, the pedal **10** is rotated and the magnet **240** of the switch circuit **220** is rotated together. As the magnet **240** rotates, the magnetic strength in the switch circuit **220** changes. (2) The switch circuit **220** recognizes a change in magnetic strength of the magnet **240** and outputs a signal to the ECU **30**. (3)

Accordingly, a wake-up signal is generated in the ECU **30**, and the ECU **30** supplies power to the PTS **20**. (4) The PTS **20** supplied with power transmits operation and output signals to the ECU **30**.

(57) Hereinafter, various exemplary embodiments of the PTS **20** will be described in more detail with reference to FIG. 5.

(58) In the illustrated exemplary embodiment, the sensor circuit **210** and the switch circuit **220** of the PTS **20** are disposed on a PCB **230**.

(59) The printed circuit board (PCB) **230** forms the basis of the sensor circuit **210** and the switch circuit **220**. Positions of the sensor circuit **210** and the switch unit may be formed in various ways.

(60) In the exemplary embodiment illustrated in FIG. **5a**, the sensor circuit **210** and the switch circuit **220** may be disposed side by side on one surface of the PCB **230**. In the exemplary embodiment illustrated in FIG. **5b**, the sensor circuit **210** and the switch circuit **220** are disposed on one surface and the other surface of the PCB **230**, respectively. That is, the sensor circuit **210** and the switch circuit **220** are disposed to face each other with the PCB **230** interposed therebetween.

(61) The magnet **240** is disposed to be spaced apart from each other with the sensor circuit **210** and the switch unit circuit **220** and an air layer interposed therebetween.

(62) The magnet **240** is installed at one end of the pedal **10**, and rotates together with the pedal **10** when the pedal **10** is pressed and rotated. As the magnet **240** rotates, a change in magnetic strength is induced, and the sensor circuit **210** and the switch circuit **220** recognize the change in magnetic strength and output a signal to the ECU **30** or the wake recognition circuit **40**.

(63) In the illustrated exemplary embodiment, a magnetic flux concentration plate **250** is provided between the sensor circuit **210** and the switch circuit **220** and the magnet **240**.

(64) The magnetic flux concentration plate **250** serves to increase the precision of sensing by concentrating the magnetization direction of the magnet **240** to a specific area.

(65) Accordingly, the sensor circuit **210** and the switch circuit **220** may recognize a change in magnetic strength without changing the size and shape of the existing magnet **240**.

(66) In an exemplary embodiment, the magnetic flux concentration plate **250** may be formed of a metal material.

(67) As described above, the vehicle braking system **1** according to an exemplary embodiment of the present disclosure has been described. Hereinafter, the vehicle braking system **1** according to another exemplary embodiment of the present disclosure will be described with reference to FIGS. **6** to **7**.

(68) The function and structure of the vehicle braking system **1** according to the present exemplary embodiment corresponds to the vehicle braking system **1** according to the above-described exemplary embodiment. However, the vehicle braking system **1** according to the present exemplary embodiment is different from the vehicle braking system **1** according to the above-described exemplary embodiment in some components.

(69) Specifically, the vehicle braking system **1** according to the present exemplary embodiment is different from the vehicle braking system according to the above-described exemplary embodiment in that the wake recognition circuit **40** is built in a central electronic module (CEM) **60** independent of the ECU **30**.

(70) Hereinafter, the vehicle braking system **1** according to the present exemplary embodiment will be described with a focus on differences from the vehicle braking system **1** according to the above-described exemplary embodiment.

(71) The vehicle braking system **1** according to the present exemplary embodiment includes a pedal **10**, a PTS **20**, an ECU **30**, a wake recognition circuit **40**, a battery **50** and a CEM **60**. Among the above components, the pedal **10** and the battery **50** of the present exemplary embodiment have the same structures, functions and combination structures as those of the above-described exemplary embodiment.

(72) However, the PTS **20**, the ECU **30**, the wake recognition circuit **40** and the CEM **60** are different from the vehicle braking system **1** according to the above-described exemplary embodiment in some components.

(73) The wake recognition circuit **40** is built in a central electronic module (CEM) **60** independent of the ECU **30**. Accordingly, the switch circuit **220** of the PTS **20** is connected to the CEM **60** such that electricity can flow in both directions, rather than the ECU **30**, and outputs a signal to the CEM **60**.

(74) In the present exemplary embodiment, a wake-up signal generation process when the pedal **10**

is applied is as follows

(75) (1) When the pedal **10** is pressed in the ignition OFF state of the vehicle **2**, the pedal **10** is rotated and the magnet **240** of the switch circuit **220** is rotated together. As the magnet **240** rotates, the magnetic strength in the switch circuit **220** changes. (2) The switch circuit **220** recognizes a change in magnetic strength of the magnet **240**, and outputs a signal to the CEM **60**. (3) When the CEM **60** receives a wake-up signal, the ECU **30** supplies power to the PTS **20**. (4) The PTS **20** supplied with power transmits operation and output signals to the ECU **30**.

(76) In summary, after the wake recognition circuit **40** in the CEM **60** receives an output signal from the PTS **20**, power is supplied from the ECU **30** to the PTS **20**.

(77) Accordingly, when the ignition of the vehicle **2** is in the OFF state, that is, in the parking state, the wake-up operation may be performed by a separate battery **50**, and power to the ECU **30** is not required. Accordingly, the standby power of the ECU **30** may be further reduced. Furthermore, the efficiency of the ECU **30** may be further improved.

(78) As described above, the vehicle braking system **1** according to another exemplary embodiment of the present disclosure has been described. Hereinafter, the vehicle braking system **1** according to still another exemplary embodiment of the present disclosure will be described with reference to FIGS. **8** to **11**.

(79) The function and structure of the vehicle braking system **1** according to the present exemplary embodiment correspond to those of the vehicle braking system **1** according to the above-described exemplary embodiment. However, the vehicle braking system **1** according to the present exemplary embodiment is different from the vehicle braking system **1** according to the above-described exemplary embodiment in some components.

(80) Specifically, the vehicle braking system **1** according to the present exemplary embodiment is difference from the vehicle braking system **1** according to the above-described exemplary embodiment in that the PTS **20** and the pedal **10** are spaced apart from each other, that is, it is formed as a built-in type.

(81) Hereinafter, the vehicle braking system **1** according to the present exemplary embodiment will be described with a focus on differences from the vehicle braking system **1** according to the above-described exemplary embodiment.

(82) The vehicle braking system **1** according to the present exemplary embodiment includes a pedal **10**, a PTS **20**, an ECU **30** and awake recognition circuit **40**. Among the above components, the pedal **10** of the present exemplary embodiment has the same structure, function and combination structure as that of the above-described exemplary embodiment.

(83) However, the PTS **20**, the ECU **30** and the wake recognition circuit **40** are different from the vehicle braking system **1** according to the above-described exemplary embodiment in some components.

(84) The PTS **20** according to the present exemplary embodiment is spaced apart from the pedal **10**. That is, it is formed as a built-in type.

(85) In the exemplary embodiment illustrated in FIG. **9**, the PTS **20** includes a sensor circuit **210**, a switch circuit **220** and a magnet **240**. The switch circuit **220** detects a change in magnetic strength of the magnet **240**, and outputs a signal to the wake recognition circuit **40** when the magnetic strength of the magnet **240** is at least a preset magnetic strength.

(86) In the above exemplary embodiment, the ECU **30** further includes an internal power circuit **340** and a micro controller unit (MCU) **350**, in addition to the first PTS controller **310** and the second PTS controller **320**.

(87) In the above exemplary embodiment, a wake-up signal generation process when the pedal **10** is applied is as follows.

(88) (1) Power is always input to the internal power circuit **340** and the switch circuit **220** of the ECU **30**. (2) Accordingly, the switch circuit **220** is always driven. (3) When the pedal **10** is pressed while the vehicle **2** is in the ignition OFF state, the pedal **10** is rotated and the magnet **240** of the

PTS **20** is rotated together. As the magnet **240** rotates, the magnetic strength in the switch circuit **220** changes. (4) Through this, the switch circuit **220** recognizes a change in magnetic strength of the magnet **240**. (5) The switch circuit **220** outputs a signal to the wake recognition circuit **40** based thereon. (6) The wake recognition circuit **40** transmits a wake-up signal to the internal power supply circuit **340** of the ECU **30**. The internal power circuit **340** of the ECU **30** supplies power to the sensor circuit **210** of the MCU **350** and the PTS **20** after receiving the wake-up signal. The sensor circuit **210** supplied with power transmits operation and output signals to the ECU **30**.

(89) FIG. **10** illustrates a change in magnetic strength according to the amount of pressure being applied to the pedal **10**. Herein, it is assumed that the magnetic strength of the magnet **240** when the pedal **10** is pressed is a wake-up point. When the magnetic strength of the magnet **240** reaches the wake-up point, the switch circuit **220** detects this and outputs a signal to the wake recognition circuit **40**.

(90) As described above, the wake recognition circuit **40** receives a signal and generates a wake-up signal in the ECU **30**. In summary, when the magnetic strength of the magnet **240** increases above the wake-up point as the pedal **10** is pressed, the switch circuit **220** generates a wake-up signal to the ECU **30**.

(91) In the exemplary embodiment illustrated in FIG. **11**, the PTS **20** includes a sensor circuit **210** and a magnet **240**. The sensor circuit **210** senses whether pressure is being applied to the pedal and the amount of pressure being applied based on the change in magnetic strength of the magnet **240**. In addition, the sensor circuit **210** uses a pulse width modulation (PWM) signal as an output signal.

(92) In the above exemplary embodiment, the wake recognition circuit **40** is connected to a low-dropout regulator (LDO) **410** and a supervisor circuit **420** for maintaining a constant circuit voltage. The supervisor circuit **420** is connected to the sensor circuit **210** such that electricity can flow in both directions so as to receive an output signal according to the sensing result of the sensor circuit **210**. The supervisor circuit **420** monitors the output signal, and transmits it to the wake recognition circuit **40** when the output signal reaches a preset value.

(93) In the above exemplary embodiment, a wake-up signal generation process when the pedal **10** is applied is as follows.

(94) (1) Power is always input to the internal power circuit **340**, the sensor circuit **210** and the supervisor circuit **420** of the ECU **30**. (2) In this case, the power input to the sensor circuit **210** and the supervisor circuit **420** is input while maintaining a constant voltage by the LDO **410**. (3) Accordingly, the sensor circuit **210** is always driven. (4) When the pedal **10** is pressed while the vehicle **2** is in the ignition OFF state, the pedal **10** is rotated and the magnet **240** of the sensor circuit **210** is rotated together. (5) The sensor circuit **210** outputs a signal to the supervisor circuit **420** based on the magnetic strength of the magnet **240**, and the output signal is increased. (6) In this case, the supervisor circuit **420** recognizes an increase in the output signal of the sensor circuit **210**. (7) The supervisor circuit **420** outputs a signal to the wake recognition circuit **40** based thereon. (8) The wake recognition circuit **40** transmits a wake-up signal to the internal power circuit **340** of the ECU **30**. The internal power circuit **340** supplies power to the MCU **350** and the sensor circuit **210** after receiving the wake-up signal. The sensor circuit **210** supplied with power transmits operation and output signals to the supervisor circuit **420** and the ECU **30**.

(95) Although the above has been described with reference to the preferred exemplary embodiments of the present disclosure, the present disclosure is not limited to the configuration of the above-described exemplary embodiments.

(96) In addition, the present disclosure can be variously modified and changed by those of ordinary skill in the art to which the present disclosure pertains without departing from the spirit and scope of the present disclosure as set forth in the claims below.

(97) Furthermore, the exemplary embodiments may be configured by selectively combining all or part of each exemplary embodiment such that various modifications can be made. **1**: Vehicle braking system **10**: Pedal **20**: Pedal travel sensor (PTS) **210**: Sensor circuit **220**: Switch circuit **230**:

Printed circuit board (PCB) **240**: Magnet **250**: Magnetic flux density plate **30**: Electronic control unit (ECU) **310**: First PTS controller **320**: Second PTS controller **330**: Regulator **340**: Internal power circuit **350**: Micro controller unit (MCU) **40**: Wake recognition circuit **410**: Low-dropout regulator (LDO) **420**: Supervisor circuit **50**: Battery **60**: Central electronic module (CEM) **2**: Vehicle

Claims

1. A vehicle brake system, comprising: a pedal travel sensor (PTS) configured to sense whether pressure is being applied to a pedal and an amount of the pressure being applied; and an wake recognition circuit connected to the PTS such that electricity can flow directly in both directions, the wake recognition circuit configured to, in response to an output signal which is transmitted from the PTS to the wake recognition circuit if the output signal is greater than or equal to a preset value, wake up an electronic control unit, (ECU) if a vehicle is in an off state.
2. The vehicle brake system of claim 1, wherein the PTS transmits the output signal to the wake recognition circuit, maintains the output signal for a preset time and transmits the output signal to the wake recognition circuit.
3. The vehicle brake system of claim 1, wherein the wake recognition circuit is operated at all times by power.
4. The vehicle brake system of claim 1, wherein the PTS is directly interconnected with the pedal.
5. The vehicle brake system of claim 4, wherein the PTS is provided with a press switch for sensing whether pressure is being applied to the pedal and the amount of pressure being applied by coming into contact with the pedal, when the pedal is pressed and rotated.
6. The vehicle brake system of claim 5, wherein the PTS is connected to the power of the ECU such that electricity can flow directly in both directions so as to receive power at all times.
7. The vehicle brake system of claim 6, wherein the PTS is connected to a regulator of the ECU such that electricity can flow directly in both directions, and transmits the output signal to the regulator, if the output signal is at least a preset value, and wherein the regulator wakes up by receiving the output signal.
8. The vehicle brake system of claim 4, wherein the PTS comprises: a printed circuit board (PCB); a magnet whose magnetic strength is changed as the pedal is pressed; a sensor circuit disposed on one surface of the PCT and configured to sense whether pressure is being applied to the pedal and the amount of pressure being applied based on a change in the magnetic strength; and a switch circuit for outputting a signal to the wake recognition circuit, if the change in magnetic strength is at least a preset change amount.
9. The vehicle brake system of claim 8, wherein the switch circuit is connected to a separate battery independent of the power of the ECU such that electricity can flow directly in both directions so as to receiver power at all times.
10. The vehicle brake system of claim 9, wherein the wake recognition circuit is built in a central electronic module (CEM) independent of the ECU, and wherein the ECU supplies power to the PTS, when the wake recognition circuit receives the output signal from the PTS.
11. The vehicle brake system of claim 8, wherein the switch circuit is disposed on the one surface of the PCB.
12. The vehicle brake system of claim 8, wherein the switch circuit is disposed on the other surface opposite to the one surface of the PCB.
13. The vehicle brake system of claim 1, wherein the PTS is spaced apart from the pedal.
14. The vehicle brake system of claim 13, wherein the PTS comprises: a printed circuit board (PCB); a magnet whose magnetic strength is changed as the pedal is pressed; a sensor circuit disposed on one surface of the PCT and configured to sense whether pressure is being applied to the pedal and the amount of pressure being applied based on a change in the magnetic strength; and

a switch circuit for outputting a signal to the wake recognition circuit, if the change in magnetic strength is at least a preset change amount.

15. The vehicle brake system of claim 13, wherein the output signal of the PTS is a pulse width modulation (PWM) signal, and wherein the wake recognition circuit comprises a supervisor circuit for monitoring the PWM signal, and transmitting the PWM signal to the wake recognition circuit, when the PWM signal reaches a preset value.
