

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398672
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lawniczek; Baptiste Dorian et al.

Aeronautical propulsion system

Abstract

An aeronautical propulsion system includes: a drive shaft; a drive turbine; and a fan section. The drive turbine includes a drive turbine stator and a drive turbine rotor. The drive turbine rotor includes a plurality of shrouds, a plurality of turbine disks connected in pairs by a shroud of the plurality of shrouds, and a plurality of turbine blades. At least one shroud connects an upstream turbine disk to a downstream turbine disk of the plurality of turbine disks. The at least one shroud has an outer surface facing the drive turbine stator, and a shroud radius defined as a smallest distance between the longitudinal axis and the outer surface of the shroud. Each of the upstream turbine disk and of the downstream turbine disk is centered on the longitudinal axis and has an outer surface delimiting a plurality of slots distributed about the longitudinal axis.

Inventors: Lawniczek; Baptiste Dorian (Moissy-Cramayel, FR), Escure; Didier René André (Moissy-Cramayel, FR), Nguyen; Alexandre Thanh Nhan (Moissy-Cramayel, FR)

Applicant: SAFRAN AIRCRAFT ENGINES (Paris, FR)

Family ID: 1000008777715

Assignee: SAFRAN AIRCRAFT ENGINES (Paris, FR)

Appl. No.: 18/541234

Filed: December 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240209776 A1	Jun. 27, 2024

Foreign Application Priority Data

FR	2213628	Dec. 16, 2022
FR	2314122	Dec. 13, 2023

Publication Classification

Int. Cl.: **F02C6/20** (20060101); **F01D5/02** (20060101); **F01D5/06** (20060101); **F01D5/14** (20060101); **F01D5/30** (20060101); **F01D25/00** (20060101); **F02C3/107** (20060101)

U.S. Cl.:

CPC **F02C6/206** (20130101); **F01D5/066** (20130101); **F01D5/142** (20130101); **F01D5/3007** (20130101); **F01D25/00** (20130101); **F02C3/107** (20130101); F05D2230/60 (20130101)

Field of Classification Search

CPC: F02C (6/206); F02C (7/36); F02C (3/107); F05D (2220/32); F05D (2230/60); F05D (2260/40311); F05D (2220/323); F05D (2240/307); F05D (2220/36); F05D (2240/301); F05D (2240/24); F05D (2240/12); F05D (2240/303); F05D (2240/304); F05D (2240/80); F05D (2260/94); F01D (5/141); F01D (5/142); F01D (5/147); F01D (5/02); F01D (25/24); F01D (5/06); F01D (5/20); F01D (1/02); F01D (11/08); F01D (5/026); F01D (5/066); F01D (5/18); F01D (5/225); F01D (5/28); F01D (5/3007); F01D (5/12); F01D (25/00); F04D (29/324); F04D (29/325); F04D (19/02); F04D (29/384)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8720526	12/2013	Campbell	164/4.1	F01D 5/187
10260352	12/2018	Campbell	N/A	F01D 5/005
11396817	12/2021	Eshak	N/A	F01D 5/147
11608750	12/2022	McCaffrey	N/A	F02C 7/36
2013/0192266	12/2012	Houston	60/805	F02C 7/36
2015/0275675	12/2014	Ristau	60/726	F01D 5/147
2016/0238023	12/2015	Gallagher	N/A	F02C 3/04
2022/0259977	12/2021	Maar	N/A	F01D 5/147

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 591 191	12/2019	EP	N/A
3 708 819	12/2019	EP	N/A
4 026 986	12/2021	EP	N/A

OTHER PUBLICATIONS

Preliminary French Search Report for FR 2213628 dated Jun. 30, 2023. cited by applicant

Primary Examiner: Zamora Alvarez; Eric J

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure generally relates to the field of propulsion systems, and more particularly aeronautical propulsion systems.

STATE OF THE ART

(2) An aeronautical propulsion system generally includes, from upstream to downstream in the gas flow direction, a fan section, a compressor section which can comprise a low-pressure compressor and a high-pressure compressor, a combustion chamber and a turbine section which can comprise a high-pressure turbine and a low-pressure turbine. The high-pressure compressor is driven in rotation by the high-pressure turbine via a high-pressure shaft. The fan and, where applicable, the low-pressure compressor are driven in rotation by the low-pressure turbine via a low-pressure shaft.

(3) The technological research efforts have already made it possible to very significantly improve the environmental performances of the aircrafts. In particular, the relevant factors in all the design and development phases have been taken into account to obtain aeronautical components and products that are less energy-intensive, more respectful of the environment and whose integration and use in the civil aviation have moderate environmental consequences, with the aim of improving the energy efficiency of the aircrafts.

(4) For example, in order to improve the propulsive efficiency of an aeronautical propulsion system and reduce its specific consumption, it has been found that it is advantageous to seek to increase the rotation speed of the low-pressure shaft and/or of the high-pressure shaft. Likewise, in order to limit the drag and mass of the aircraft, and thus reduce its fuel consumption, it has been found that it is advantageous to seek to make its propulsion systems more compact, that is to say to reduce the bulk of all or part of their components.

(5) However, in doing so, it appears that the rotating components of the aeronautical propulsion systems, in particular those present within the compressor section and the turbine section, are subjected to centrifugal forces which become more significant, while having smaller dimensions, which is likely to alter their mechanical strength and/or limit their lifespan.

GENERAL DISCLOSURE

(6) One aim of the present disclosure is to reduce the fuel consumption of an aeronautical propulsion system without limiting the lifespan of its rotating components.

(7) For this purpose, according to one aspect of the present disclosure, an aeronautical propulsion system is proposed comprising: a drive shaft; a drive turbine comprising a drive turbine stator and a drive turbine rotor, the drive turbine rotor being connected to the drive shaft to drive it in rotation relative to the drive turbine stator about a longitudinal axis, the drive turbine rotor comprising a plurality of shrouds, a plurality of turbine disks connected in pairs by a shroud of the plurality of shrouds, and a plurality of turbine blades; a fan section comprising a fan rotor and a fan stator, the drive shaft being connected to the fan rotor to drive it in rotation relative to the fan stator about the longitudinal axis; wherein at least one shroud of the plurality of shrouds connects an upstream turbine disk to a downstream turbine disk of the plurality of turbine disks and has: an outer surface facing the drive turbine stator; and a shroud radius $R_{sub.v}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the shroud; wherein each of the upstream turbine disk and of the downstream turbine disk is centered on the longitudinal axis and has an outer surface delimiting a plurality of slots distributed about the longitudinal axis; wherein a first turbine blade of the plurality of turbine blades comprises: a root fixed to the upstream turbine disk in a respective slot of the plurality of slots of the upstream turbine disk; a stilt connected to the root and comprising a platform delimiting a first radially inner portion of a flowpath passing through the drive turbine; and an airfoil connected to the platform and extending within the flowpath, the airfoil having a leading edge, a trailing edge and an end opposite to the platform; wherein a second turbine blade of the plurality of turbine blades comprises: a root fixed to the downstream turbine disk in a respective slot of the plurality of slots of the downstream turbine disk; a stilt connected to the root

and comprising a platform delimiting a second radially inner portion of the flowpath passing through the drive turbine; and an airfoil connected to the platform and extending within the flowpath, the airfoil having a leading edge, a trailing edge and an end opposite to the platform; wherein the flowpath has: an upstream outer radius $R_{\text{sub.eam}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the first turbine blade and the leading edge of the airfoil of the first turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the first turbine blade and the trailing edge of the airfoil of the first turbine blade; an upstream inner radius $R_{\text{sub.iam}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the platform of the first turbine blade and the leading edge of the airfoil of the first turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the platform of the first turbine blade and the trailing edge of the airfoil of the first turbine blade; a downstream outer radius $R_{\text{sub.eav}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the second turbine blade and the leading edge of the airfoil of the second turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the second turbine blade and the trailing edge of the airfoil of the second turbine blade; and a downstream inner radius $R_{\text{sub.iav}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the platform of the second turbine blade and the leading edge of the airfoil of the second turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the platform of the second turbine blade and the trailing edge of the airfoil of the second turbine blade; wherein the drive shaft has a limit speed ω which is defined as the highest speed at which the drive shaft is capable of being driven in rotation about the longitudinal axis during the operation of the propulsion system; wherein the shroud radius $R_{\text{sub.v}}$, the upstream outer radius $R_{\text{sub.eam}}$, the upstream inner radius $R_{\text{sub.iam}}$, the downstream outer radius $R_{\text{sub.eav}}$, the downstream inner radius $R_{\text{sub.iav}}$ and the limit speed ω are such that:

$$(8) \quad \sigma_{\text{sub.1}} * \frac{N2S_{\text{sub.am}}}{100} + \chi_{\text{sub.1}} \leq \frac{R_{\text{sub.v}}}{R_m} \text{ with: } N2S_{\text{sub.am}} = \frac{(R_{\text{eam}}^2 - R_{\text{iam}}^2)}{2} * \omega^2 \text{ and: } R_m = \frac{\frac{R_{\text{eam}} + R_{\text{iam}}}{2} + \frac{R_{\text{eav}} + R_{\text{iav}}}{2}}{2} \text{ where:}$$

ω is expressed in revolutions per minute; $\sigma_{\text{sub.1}}$ is $-0.4 \text{ rpm.sup.-2.Math.m.sup.-2}$; $\chi_{\text{sub.1}}$ is 0.784; $R_{\text{sub.eam}}$, $R_{\text{sub.iam}}$, $R_{\text{sub.eav}}$, $R_{\text{sub.iav}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10.\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}$; wherein the ratio

$$(9) \quad \sigma_{\text{sub.2}} * \frac{N2S_{\text{sub.am}}}{100} + \chi_{\text{sub.2}} \leq \frac{R_{\text{sub.v}}}{R_m} \text{ is strictly positive and strictly less than 1; wherein the shroud radius}$$

$R_{\text{sub.v}}$ is comprised in a range from 0.05 to 0.8 meters inclusive, the upstream outer radius $R_{\text{sub.eam}}$ and the downstream outer radius $R_{\text{sub.eav}}$ are comprised in a range from 0.15 to 1.0 meters inclusive, the downstream inner radius $R_{\text{sub.iav}}$ and the upstream inner radius $R_{\text{sub.iam}}$ are comprised in a range from 0.1 to 0.8 meters inclusive, $R_{\text{sub.m}}$ is comprised in a range from 0.05 to 1.0 meters inclusive and $N2S_{\text{sub.am}}$ is comprised in a range from $30 * 10.\text{sup.6}$ rpm.sup.2.Math.m.sup.2 to $180 * 10.\text{sup.6}$ rpm.sup.2.Math.m.sup.2 inclusive.

(10) In one embodiment, the shroud radius $R_{\text{sub.v}}$, the upstream outer radius $R_{\text{sub.eam}}$, the upstream inner radius $R_{\text{sub.iam}}$, the downstream outer radius $R_{\text{sub.eav}}$, the downstream inner radius $R_{\text{sub.iav}}$ and the limit speed ω are such that:

$$(11) \quad \frac{R_{\text{sub.v}}}{R_m} \text{ where: } \sigma_{\text{sub.2}} \text{ is } -0.512 \text{ rpm.sup.-2.Math.m.sup.-2} \chi_{\text{sub.2}} \text{ is } 0.82; R_{\text{sub.m}} \text{ and } R_{\text{sub.v}} \text{ are expressed in meters; and } N2S_{\text{sub.am}} \text{ is expressed in } 10.\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}.$$

(12) In one embodiment, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the turbine disk and centered on the longitudinal axis; a bore radius $R_{\text{sub.a}}$ which is defined as a smallest distance between the longitudinal axis and the inner surface of the turbine disk; and a rim radius $R_{\text{sub.j}}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the turbine disk;

wherein the bore radius R.sub.a, the rim radius R.sub.j and the limit speed ω are such that:

$$(13) \quad *U_j + \frac{1}{1} \leq \frac{R_a}{R_j} \text{ with: } U_j = R_j *$$

where:

ω is expressed in radians per second;

α is $-0.0027 \text{ m.sup.-1.Math.s}$;

β .sub.1 is 0.4;

R.sub.a and R.sub.j are expressed in meters; and

U.sub.j is expressed in meters per second;

wherein the ratio

$$(14) \quad \frac{R_a}{R_j}$$

is strictly positive and strictly less than 1;

wherein the bore radius R.sub.a is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and U.sub.j is comprised in a range from 100 to 500 m.Math.s.sup.-1 inclusive.

(15) In one embodiment, the bore radius R.sub.a, the rim radius R.sub.j and the limit speed ω are such that:

$$(16) \quad *U_j + \frac{2}{2} \leq \frac{R_a}{R_j} \text{ where: } \alpha \text{ is } -0.0027 \text{ m.sup.-1.Math.s}; \beta \text{.sub.2 is } 1.2951; R \text{.sub.a and}$$

R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second.

(17) In one embodiment, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; a bore width L.sub.a which is defined as an axial distance between the upstream edge and the downstream edge of the inner surface; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the turbine disk;

wherein the bore width L.sub.a, the rim radius R.sub.j and the limit speed ω are such that:

$$(18) \quad \frac{100 * L_a}{R_j} \leq * \frac{U_j^2}{1,000} + \frac{1}{1} \text{ with: } U_j = R_j *$$

where:

ω is expressed in radians per second;

δ is $0.2424 \text{ s.sup.2.Math.m.sup.-2}$;

ζ .sub.1 is 10;

L.sub.a and R.sub.j are expressed in meters; and

U.sub.j is expressed in meters per second;

wherein the ratio

$$(19) \quad \frac{100 * L_a}{R_j}$$

is strictly positive;

wherein the bore width L.sub.a is comprised in a range from 0.005 to 0.1 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and U.sub.j is comprised in a range from 100 to 500 m.Math.s.sup.-1 inclusive.

(20) In one embodiment, the bore width L.sub.a, the rim radius R.sub.j and the limit speed ω are such that:

$$(21) \quad \frac{100 * L_a}{R_j} \leq * \frac{U_j^2}{1,000} + \frac{2}{2} \text{ where: } \delta \text{ is } 0.2424 \text{ s.sup.2.Math.m.sup.-2}; \zeta \text{.sub.2 is } -8; L \text{.sub.a and}$$

R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second.

(22) In one embodiment, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the upstream turbine disk and centered on the longitudinal axis; a bore radius R.sub.a which is defined as a smallest distance between the longitudinal axis and the inner surface of the upstream turbine disk; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the upstream turbine disk;

wherein the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, the outer radius $R_{\text{sub.e}}$, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

$$(23) \quad 0 \leq N2S + \frac{R_a}{R_j} \leq \frac{R_a}{R_j} \text{ with: } N2S = \frac{\omega^2}{2} (R_e^2 - R_i^2)$$

where:

ω is expressed in revolutions per minute;

κ is $-0.0091 \text{ rpm}^{\text{sup.}-2} \cdot \text{Math.m}^{\text{sup.}-2}$;

$\lambda_{\text{sub.1}}$ is 0.3;

$R_{\text{sub.a}}$, $R_{\text{sub.j}}$, $R_{\text{sub.e}}$ and $R_{\text{sub.i}}$ are expressed in meters; and

$N2S$ is expressed in $10^{\text{sup.6}} \text{Math.rpm}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.2}}$;

wherein the ratio

$$(24) \quad \frac{R_a}{R_j} + N2S \leq \frac{R_a}{R_j}$$

is strictly positive and strictly less than 1;

wherein the bore radius $R_{\text{sub.a}}$ is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius $R_{\text{sub.j}}$ is comprised in a range from 0.01 to 0.5 meters inclusive and $N2S$ is comprised in a range from $30 \cdot 10^{\text{sup.6}} \text{rpm}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.2}}$ to $180 \cdot 10^{\text{sup.6}} \text{rpm}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.2}}$ inclusive.

(25) In one embodiment, the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, the outer radius $R_{\text{sub.e}}$, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

(26) $\frac{R_a}{R_j}$ where: κ is $-0.0091 \text{ rpm}^{\text{sup.}-2} \cdot \text{Math.m}^{\text{sup.}-2}$; $\lambda_{\text{sub.2}}$ is 0.864; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $N2S$ is expressed in $10^{\text{sup.6}} \text{Math.rpm}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.2}}$.

(27) In one embodiment, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the upstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; and a bore width $L_{\text{sub.a}}$ which is defined as an axial distance between the upstream edge and the downstream edge of the inner surface;

wherein the bore width $L_{\text{sub.a}}$, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

$$(28) \quad \frac{100 \cdot L_a}{R_i} \leq \frac{\omega^2}{1,000} + \frac{U_i^2}{1} \text{ with: } U_i = R_i \cdot \omega$$

where:

ω is expressed in radians per second;

v is $0.079 \text{ s}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.}-2}$;

$\xi_{\text{sub.1}}$ is 2.28;

$L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and

$U_{\text{sub.i}}$ is expressed in meters per second;

wherein the ratio

$$(29) \quad \frac{100 \cdot L_a}{R_i}$$

is strictly positive;

wherein the bore width $L_{\text{sub.a}}$ is comprised in a range from 0.005 to 0.1 meters inclusive and $U_{\text{sub.i}}$ is comprised in a range from 100 to 500 $\text{m} \cdot \text{Math.s}^{\text{sup.}-1}$ inclusive.

(30) In one embodiment, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

(31) $\frac{100 \cdot L_a}{R_i} \leq v \cdot \frac{U_i^2}{1,000} + 2$ where: v is $0.079 \text{ s}^{\text{sup.2}} \cdot \text{Math.m}^{\text{sup.}-2}$; $\xi_{\text{sub.2}}$ is -1.41 ; $L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $U_{\text{sub.i}}$ is expressed in meters per second.

(32) According to another aspect of the present disclosure, a method for manufacturing a propulsion system is proposed, the propulsion system comprising: a drive shaft; a drive turbine comprising a drive turbine stator and a drive turbine rotor, the drive turbine rotor being connected to the drive shaft to drive it in rotation relative to the drive turbine stator about a longitudinal axis, the drive turbine rotor comprising a plurality of shrouds, a plurality of turbine disks connected in pairs by a shroud of the plurality of shrouds, and a plurality of turbine blades; a fan section comprising a fan rotor and a fan stator, the drive shaft being connected to the fan rotor to drive it in

rotation relative to the fan stator about the longitudinal axis; wherein at least one shroud of the plurality of shrouds connects an upstream turbine disk to a downstream turbine disk of the plurality of turbine disks and has: an outer surface extending facing the drive turbine stator; and a shroud radius $R_{\text{sub.v}}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the shroud; wherein each of the upstream turbine disk and of the downstream turbine disk is centered on the longitudinal axis and has an outer surface delimiting a plurality of slots distributed about the longitudinal axis; wherein a first turbine blade of the plurality of turbine blades comprises: a root fixed to the upstream turbine disk in a respective slot of the plurality of slots of the upstream turbine disk; a stilt connected to the root and comprising a platform delimiting a first radially inner portion of a flowpath passing through the drive turbine; and an airfoil connected to the platform and extending within the flowpath, the airfoil having a leading edge, a trailing edge and an end opposite to the platform; wherein a second turbine blade of the plurality of turbine blades comprises: a root fixed to the downstream turbine disk in a respective slot of the plurality of slots of the downstream turbine disk; a stilt connected to the root and comprising a platform delimiting a second radially inner portion of the flowpath passing through the drive turbine; and an airfoil connected to the platform and extending within the flowpath, the airfoil having a leading edge, a trailing edge and an end opposite to the platform; wherein the flowpath has: an upstream outer radius $R_{\text{sub.eam}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the first turbine blade and the leading edge of the airfoil of the first turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the first turbine blade and the trailing edge of the airfoil of the first turbine blade; an upstream inner radius $R_{\text{sub.iam}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the platform of the first turbine blade and the leading edge of the airfoil of the first turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the platform of the first turbine blade and the trailing edge of the airfoil of the first turbine blade; a downstream outer radius $R_{\text{sub.eav}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the second turbine blade and the leading edge of the airfoil of the second turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the end of the airfoil of the second turbine blade and the trailing edge of the airfoil of the second turbine blade; and a downstream inner radius $R_{\text{sub.iav}}$ which is defined as an average between, on the one hand, a distance between the longitudinal axis and a junction between the platform of the second turbine blade and the leading edge of the airfoil of the second turbine blade and, on the other hand, a distance between the longitudinal axis and a junction between the platform of the second turbine blade and the trailing edge of the airfoil of the second turbine blade; wherein the drive shaft has a limit speed ω which is defined as the highest speed at which the drive shaft is capable of being driven in rotation about the longitudinal axis during the operation of the propulsion system; wherein the method comprises a dimensioning of the at least one shroud, a dimensioning of the first turbine blade and a dimensioning of the second turbine blade implemented so that the shroud radius $R_{\text{sub.v}}$, the upstream outer radius $R_{\text{sub.eam}}$, the upstream inner radius $R_{\text{sub.iam}}$, the downstream outer radius $R_{\text{sub.eav}}$, the downstream inner radius $R_{\text{sub.iav}}$ and the limit speed ω are such that:

$$(33) \quad \sigma_{\text{sub.1}} * \frac{N2S_{\text{am}}}{R_m} + \chi_{\text{sub.1}} \leq \frac{R_v}{R_m} \text{ with: } N2S_{\text{am}} = \sigma_{\text{sub.1}} * (R_{\text{eam}}^2 - R_{\text{iam}}^2) * \omega^2 \text{ and: } R_m = \frac{\frac{R_{\text{eam}} + R_{\text{iam}}}{2} + \frac{R_{\text{eav}} + R_{\text{iav}}}{2}}{2}$$

where: ω is expressed in revolutions per minute; $\sigma_{\text{sub.1}}$ is $-0.4 \text{ rpm.sup.-2.Math.m.sup.-2}$; $\chi_{\text{sub.1}}$ is 0.784; $R_{\text{sub.eam}}$, $R_{\text{sub.iam}}$, $R_{\text{sub.eav}}$, $R_{\text{sub.iav}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10.\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}$; wherein the ratio

(34) $\frac{R_v}{R_m}$ is strictly positive and strictly less than 1; wherein the shroud radius $R_{\text{sub.v}}$ is comprised in a range from 0.05 to 0.8 meters inclusive, the upstream outer radius $R_{\text{sub.eam}}$ and

the downstream outer radius $R_{sub.eav}$ are comprised in a range from 0.15 to 1.0 meters inclusive, the downstream inner radius $R_{sub.iav}$ and the upstream inner radius $R_{sub.iam}$ are comprised in a range from 0.1 to 0.8 meters inclusive, $R_{sub.m}$ is comprised in a range from 0.05 to 1.0 meters inclusive and $N2S_{sub.am}$ is comprised in a range from $30 \cdot 10^{sup.6} \text{ rpm} \cdot sup.2 \cdot \text{Math.m} \cdot sup.2$ to $180 \cdot 10^{sup.6} \text{ rpm} \cdot sup.2 \cdot \text{Math.m} \cdot sup.2$ inclusive.

(35) In one mode of implementation, the dimensioning of the at least one shroud, the dimensioning of the first turbine blade and the dimensioning of the second turbine blade are implemented so that the shroud radius $R_{sub.v}$, the upstream outer radius $R_{sub.eam}$, the upstream inner radius $R_{sub.iam}$, the downstream outer radius $R_{sub.eav}$, the downstream inner radius $R_{sub.iav}$ and the limit speed ω are such that:

(36) $\sigma_{sub.2} \cdot \frac{N2S_{am}}{100} + \frac{R_v}{R_m} \leq \frac{R_v}{R_m}$ where: $\sigma_{sub.2}$ is $-0.512 \text{ rpm} \cdot sup.-2 \cdot \text{Math.m} \cdot sup.-2$ $\chi_{sub.2}$ is 0.82; $R_{sub.m}$ and $R_{sub.v}$ are expressed in meters; and $N2S_{sub.am}$ is expressed in $10^{sup.6} \cdot \text{Math.rpm} \cdot sup.2 \cdot \text{Math.m} \cdot sup.2$.

(37) In one mode of implementation, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the turbine disk and centered on the longitudinal axis; a bore radius $R_{sub.a}$ which is defined as a smallest distance between the longitudinal axis and the inner surface of the turbine disk; and a rim radius $R_{sub.j}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the turbine disk;

wherein the method further comprises a dimensioning of one of the upstream turbine disk and of the downstream turbine disk implemented so that the bore radius $R_{sub.a}$, the rim radius $R_{sub.j}$ and the limit speed ω are such that:

(38) $U_j + \frac{R_a}{R_j} \leq \frac{R_a}{R_j}$ with: $U_j = R_j \cdot$

where:

ω is expressed in radians per second;

α is $-0.0027 \text{ m} \cdot sup.-1 \cdot \text{Math.s}$;

$\beta_{sub.1}$ is 0.4;

$R_{sub.a}$ and $R_{sub.j}$ are expressed in meters; and

$U_{sub.j}$ is expressed in meters per second;

wherein the ratio

(39) $0 < \frac{R_a}{R_j}$

is strictly positive and strictly less than 1;

wherein the bore radius $R_{sub.a}$ is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius $R_{sub.j}$ is comprised in a range from 0.01 to 0.5 meters inclusive and $U_{sub.j}$ is comprised in a range from 100 to 500 $\text{m} \cdot \text{Math.s} \cdot sup.-1$ inclusive.

(40) In one mode of implementation, the dimensioning of one of the upstream turbine disk and of the downstream turbine disk is implemented so that the bore radius $R_{sub.a}$, the rim radius $R_{sub.j}$ and the limit speed ω are such that:

(41) $U_j + \frac{R_a}{R_j} \leq \frac{R_a}{R_j}$ where: α is $-0.0027 \text{ m} \cdot sup.-1 \cdot \text{Math.s}$; $\beta_{sub.2}$ is 1.2951; $R_{sub.a}$ and

$R_{sub.j}$ are expressed in meters; and $U_{sub.j}$ is expressed in meters per second.

(42) In one mode of implementation, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; a bore width $L_{sub.a}$ which is defined as an axial distance between the upstream edge and the downstream edge of the inner surface; and a rim radius $R_{sub.j}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the turbine disk;

wherein the method further comprises a dimensioning of one of the upstream turbine disk and of the downstream turbine disk implemented so that the bore width $L_{sub.a}$, the rim radius $R_{sub.j}$ and the limit speed ω are such that:

$$(43) \frac{100 * L_a}{R_j} \leq * \frac{U_j^2}{1,000} + {}_1 \text{ with: } U_j = R_j *$$

where:

ω is expressed in radians per second;

δ is 0.2424 s.sup.2.Math.m.sup.-2;

ζ .sub.1 is 10;

L.sub.a and R.sub.j are expressed in meters; and

U.sub.j is expressed in meters per second;

wherein the ratio

$$(44) \frac{100 * L_a}{R_j}$$

is strictly positive;

wherein the bore width L.sub.a is comprised in a range from 0.005 to 0.1 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and U.sub.j is comprised in a range from 100 to 500 m.Math.s.sup.-1 inclusive.

(45) In one mode of implementation, the dimensioning of one of the upstream turbine disk and of the downstream turbine disk is implemented so that the bore width L.sub.a, the rim radius R.sub.j and the limit speed ω are such that:

$$(46) \frac{100 * L_a}{R_j} \leq * \frac{U_j^2}{1,000} + {}_2 \text{ where: } \delta \text{ is } 0.2424 \text{ s.sup.2.Math.m.sup.-2; } \zeta \text{ is } -8; \text{ L.sub.a and R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second.}$$

(47) In one mode of implementation, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the upstream turbine disk and centered on the longitudinal axis; a bore radius R.sub.a which is defined as a smallest distance between the longitudinal axis and the inner surface of the upstream turbine disk; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the upstream turbine disk;

wherein the method further comprises a dimensioning of the at least one of the upstream turbine disk and of the downstream turbine disk and a dimensioning of at least one of the first turbine blade and of the second turbine blade implemented so that the bore radius R.sub.a, the rim radius R.sub.j, the outer radius R.sub.e, the inner radius R.sub.i and the limit speed ω are such that:

$$(48) * N2S + {}_1 \leq \frac{R_a}{R_j} \text{ with: } N2S = * (R_e^2 - R_i^2) * {}^2$$

where:

ω is expressed in revolutions per minute;

κ is -0.0091 rpm.sup.-2.Math.m.sup.-2;

λ .sub.1 is 0.3;

R.sub.a, R.sub.j, R.sub.e and R.sub.i are expressed in meters; and

N2S is expressed in 10.sup.6.Math.rpm.sup.2.Math.m.sup.2;

wherein the ratio

$$(49) \frac{R_a}{R_j}$$

is strictly positive and strictly less than 1;

wherein the bore radius R.sub.a is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and N2S is comprised in a range from 30*10.sup.6 rpm.sup.2.Math.m.sup.2 to 180*10.sup.6 rpm.sup.2.Math.m.sup.2 inclusive.

(50) In one mode of implementation, the dimensioning of the at least one of the upstream turbine disk and of the downstream turbine disk and the dimensioning of the at least one of the first turbine blade and of the second turbine blade are implemented so that the bore radius R.sub.a, the rim radius R.sub.j, the outer radius R.sub.e, the inner radius R.sub.i and the limit speed ω are such that:

$$(51) * N2S + {}_2 \leq \frac{R_a}{R_j} \text{ where: } \kappa \text{ is } -0.0091 \text{ rpm.sup.-2.Math.m.sup.-2; } \lambda \text{.sub.2 is } 0.864; \text{ R.sub.a and R.sub.j are expressed in meters; and N2S is expressed in}$$

10.sup.6.Math.rpm.sup.2.Math.m.sup.2.

(52) In one mode of implementation, at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the upstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; and a bore width $L_{\text{sub.a}}$ which is defined as an axial distance between the upstream edge and the downstream edge of the inner surface; wherein the method further comprises a dimensioning of the at least one of the upstream turbine disk and of the downstream turbine disk and a dimensioning of at least one of the first turbine blade and of the second turbine blade implemented so that the bore width $L_{\text{sub.a}}$, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

$$(53) \frac{100 * L_a}{R_i} \leq \frac{U_i^2}{1,000} + \xi_{\text{sub.1}} \text{ with: } U_i = R_i * \omega$$

where:

ω is expressed in radians per second;

v is 0.079 s.sup.2.Math.m.sup.-2;

$\xi_{\text{sub.1}}$ is 2.28;

$L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and

$U_{\text{sub.i}}$ is expressed in meters per second;

wherein the ratio

$$(54) \frac{100 * L_a}{R_i}$$

is strictly positive;

wherein the bore width $L_{\text{sub.a}}$ is comprised in a range from 0.005 to 0.1 meters inclusive and

$U_{\text{sub.i}}$ is comprised in a range from 100 to 500 m.Math.s.sup.-1 inclusive.

(55) In one mode of implementation, the dimensioning of the at least one of the upstream turbine disk and of the downstream turbine disk and the dimensioning of the at least one of the first turbine blade and of the second turbine blade are implemented so that the bore width $L_{\text{sub.a}}$, the inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

$$(56) 0 \leq \frac{100 * L_a}{R_i} \leq \frac{U_i^2}{1,000} + \xi_{\text{sub.2}} \text{ where: } v \text{ is } 0.079 \text{ s.sup.2.Math.m.sup.-2; } \xi_{\text{sub.2}} \text{ is } -1.41; L_{\text{sub.a}} \text{ and } R_{\text{sub.i}} \text{ are expressed in meters; and } U_{\text{sub.i}} \text{ is expressed in meters per second.}$$

Description

DESCRIPTION OF THE FIGURES

(1) Other characteristics, aims and advantages will emerge from the following description, which is purely illustrative and not limiting, and should be read in relation to the appended figures, in which:

(2) FIG. 1 illustrates an example of an aircraft that can comprise a propulsion system.

(3) FIG. 2 is a schematic, partial and sectional view of an example of a propulsion system in which the fan section is ducted.

(4) FIG. 3 is a schematic, partial and sectional view of an example of a propulsion system in which the fan section is unducted.

(5) FIG. 4 is a schematic sectional view of an example of a star gear reduction mechanism.

(6) FIG. 5 is a schematic sectional view of an example of a planetary gear reduction mechanism.

(7) FIG. 6 is a schematic perspective view of an example of a rotor stage of the turbine section of a propulsion system.

(8) FIG. 7 illustrates a schematic front view and a schematic sectional view of an example of a disk of a rotor stage of the turbine section of a propulsion system.

(9) FIG. 8A is a schematic perspective view of an example of a blade of a rotor stage of the turbine section of a propulsion system.

(10) FIG. 8B is a side view of FIG. 8A.

(11) FIG. 9 is a schematic sectional view of an example of a rotor stage of the turbine section of a propulsion system.

(12) FIG. 10 is a flowchart illustrating steps of one example of implementation of a method for manufacturing a propulsion system.

(13) In all the figures, similar elements bear identical references.

DETAILED DESCRIPTION

(14) A propulsion system **1** has a main direction extending along a longitudinal axis X and comprises, from upstream to downstream in the gas flow direction in the propulsion system **1** when it is in operation, a fan section **2** and a primary spool **3**, often called “gas generator”, including a compressor section **4, 5**, a combustion chamber **6** and a turbine section **7, 8**. The propulsion system **1** is here an aeronautical propulsion system **1** configured to be fixed to the airframe of an aircraft **100** via a pylon (or mast).

(15) The compressor section **4, 5** comprises a succession of stages each comprising a blade wheel (rotor) **4a, 5a** rotating in front of a vane wheel (stator) **4b, 5b**. The turbine section **7, 8** also comprises a succession of stages each comprising a vane wheel (stator) **7b, 8b** behind which a blade wheel (rotor) **7a, 8a** rotates.

(16) In the present disclosure, the axial direction corresponds to the direction of the longitudinal axis X, in correspondence with the rotation of the shafts **10, 11** of the primary spool **3**, and a radial direction is a direction perpendicular to this longitudinal axis X and passing therethrough.

Moreover, the circumferential (or lateral, or even tangential) direction corresponds to a direction perpendicular to the longitudinal axis X and not passing therethrough. Unless otherwise specified, inner (respectively, internal) and outer (respectively, external), respectively, are used with reference to a radial direction so that the inner part or face of an element is closer to the longitudinal axis X as the outer part or face of the same element.

(17) In operation, an air stream F entering the propulsion system **1** is divided between a primary air stream F1 and a secondary air stream F2, which circulate from upstream to downstream in the propulsion system **1**.

(18) The secondary air stream F2, also called “bypass air stream”, flows around the primary spool **3**. The secondary air stream F2 makes it possible to cool the periphery of the primary spool **3** and serves to generate most of the thrust provided by the propulsion system **1**.

(19) The primary air stream F1 flows in a primary flowpath **29** inside the primary spool **3**, passing successively through the compressor section **4, 5**, the combustion chamber **6** where it is mixed with fuel to serve as oxidizer, and the turbine section **7, 8**. The passage of the primary air stream F1 through the turbine section **7, 8** receiving energy from the combustion chamber **6** causes a rotation of the rotor stages **7a, 8a** of the turbine section **7, 8**, which in turn drive in rotation the rotor stages **4a, 5a** of the compressor section **4, 5** as well as a rotor **9** of the fan section **2**.

(20) In a two-spool propulsion system **1**, the compressor section **4, 5** can comprise a low-pressure compressor **4** and a high-pressure compressor **5**. The turbine section **7, 8** can comprise a high-pressure turbine **7** and a low-pressure turbine **8**. The rotor stages **5a** of the high-pressure compressor **5** are driven in rotation by the rotor stages **7a** of the high-pressure turbine **7** via a high-pressure shaft **10**. The rotor stages **4a** of the low-pressure compressor **4** and the rotor **9** of the fan section **2** are driven in rotation by the rotor stages **8a** of the low-pressure turbine **8** via a low-pressure shaft **11**. Thus, the primary spool **3** comprises a high-pressure spool comprising the high-pressure compressor **5**, the high-pressure turbine **7** and the high-pressure shaft **10**, and a low-pressure spool comprising the fan section **2**, the low-pressure compressor **4**, the low-pressure turbine **8** and the low-pressure shaft **11**. The rotation speed of the high-pressure spool is higher than the rotation speed of the low-pressure spool. In a triple-spool propulsion system **1**, the turbine section **7, 8** further comprises an intermediate turbine, positioned between the high-pressure turbine **7** and the low-pressure turbine **8** and whose rotor stages are configured to drive the rotor stages of

the low-pressure compressor **4** via an intermediate shaft. The rotor **9** of the fan section **2** and the rotor stages of the high-pressure compressor **5** remain driven by the low-pressure shaft **11** and the high-pressure shaft **10**, respectively.

(21) The low-pressure shaft **11** is generally housed, over a segment of its length, in the high-pressure shaft **10** and is coaxial with the high-pressure shaft **10**. The low-pressure shaft **11** and the high-pressure shaft **10** can be co-rotating, that is to say driven in the same direction about the longitudinal axis X. As a variant, the low-pressure shaft **11** and the high-pressure shaft **10** are counter-rotating that is to say they are driven in opposite directions about the longitudinal axis X. Where applicable, the intermediate shaft is housed between the high-pressure shaft **10** and the low-pressure shaft **11**. The intermediate shaft and the low-pressure shaft **11** can be co-rotating or counter-rotating.

(22) The fan section **2** comprises at least the rotor **9** capable of being driven in rotation relative to a stator part **19e** of the propulsion system **1** by at least one rotor part of the turbine section **7**, **8**. Each rotor **9** of the fan section fan **2** comprises a hub **13** and blades **14** extending radially from the hub **13**. The blades **14** of each rotor **9** can be stationary relative to the hub **13** or have a variable setting. In this case, the root of the blades **14** of each rotor **9** is pivotally mounted along a setting axis and is connected to a pitch change mechanism **15** mounted in the propulsion system **1**, the setting being adjusted according to the flight phases by the pitch change mechanism **15**. The rotor **9** of the fan section **2** moreover comprises at least fourteen blades **14** and at most twenty-four blades **14**, preferably at least sixteen blades **14** and at most twenty-two blades **14**.

(23) The fan section **2** can further comprise a stator **16**, or straightener, which comprises vanes **17** mounted on a hub of the stator **16** and have the function of straightening the secondary air stream F2 which flows at the outlet of the rotor **9**. The vanes **17** of the stator **16** can be stationary relative to the hub of the stator **16** or have a variable setting. Where applicable, and similarly to the rotor **9** blades **14**, the root of the stator **16** vanes **17** is pivotally mounted along a setting axis and is connected to a pitch change mechanism **15a**, which is generally distinct from that of the rotor **9**, the setting being adjusted according to the flight phases by the pitch change mechanism **15a**. The number of vanes **17** in the stator **16** depends on the acoustic criteria defined for the propulsion system **1** and is at least equal to the number of blades **14** in the rotor **9**.

(24) In order to improve the propulsive efficiency of the propulsion system **1** and to reduce its specific consumption as well as the noise emitted by the fan section **2**, the propulsion system **1** has a high bypass ratio. By “high” bypass ratio it is meant a bypass ratio greater than or equal to 10, for example comprised between 10 and 80 inclusive. To calculate the bypass ratio, the mass flow rate of the secondary air stream F2 and the mass flow rate of the primary air stream F1 are related to each other, by being measured when the propulsion system **1** is stationary, not installed, in take-off mode in a standard atmosphere (as defined by the International Civil Aviation Organization (ICAO) manual, Doc 7488/3, 3rd edition) and at sea level. In the present disclosure, the parameters (pressure, flow rate, thrust, speed, etc.) are systematically determined under these conditions. By “not installed”, it is meant that the measurements are performed when the propulsion system **1** is on a test bench (and not installed on an aircraft **100**), the measurements then being simpler to carry out. The distances, or dimensions (length, width, radius, diameter, etc.), are, for their part, measured at ambient temperature (approximately 20° C.) when the propulsion system **1** is cold, that is to say when the propulsion system **1** is stopped for a sufficient period in order for the parts of the propulsion system **1** to be at ambient temperature, it being understood that these dimensions vary little compared to the conditions in which the propulsion system **1** would be in take-off mode.

(25) The rotor **9** of the fan section **2** can be decoupled from the low-pressure shaft **11** using a reduction mechanism **19**, placed between an upstream end of the low-pressure shaft **11** and the rotor **9**, in order to independently optimize their respective rotation speed. In this case, the propulsion system **1** further comprises an additional shaft, called “fan shaft **20**”. The low-pressure shaft **11** connects the rotor stages **8a** of the low-pressure turbine **8** to an inlet of the reduction

mechanism **19** while the fan shaft **20** connects the outlet of the reduction mechanism **19** to the rotor **9** of the fan section **2**. The rotor **9** of the fan section **2** is therefore driven by the low-pressure shaft **11** via the reduction mechanism **19** and the fan shaft **20** at a rotation speed lower than the rotation speed of the low-pressure turbine **8**.

(26) This decoupling makes it possible to reduce the rotation speed and the pressure ratio of the rotor **9** of the fan section **2** and to increase the power extracted by the low-pressure turbine **8**. Indeed, the overall efficiency of the propulsion systems is conditioned to the first order by the propulsive efficiency, which is favorably influenced by minimization of the variation in the kinetic energy of the air when crossing the propulsion system **1**. In a propulsion system **1** with a high bypass ratio, most of the flow rate generating the propulsive force is made up of the secondary air stream F2 of the propulsion system **1**, the kinetic energy of the secondary air stream F2 being mainly affected by the compression that the secondary air stream F2 undergoes when crossing the fan section **2**. The propulsive efficiency and the pressure ratio of the fan section **2** are therefore linked: the lower the pressure ratio of the fan section **2**, the better the propulsive efficiency will be. In order to improve the propulsive efficiency of the propulsion system **1**, the pressure ratio of the fan section **2**, which corresponds to the ratio between the average pressure at the outlet of the stator **16** of the fan section **2** (or, in the absence of the stator **16**, at the outlet of the rotor **9**) and the average pressure at the inlet of the rotor **9** of the fan section **2**, is less than or equal to 1.70, preferably less than or equal to 1.50, for example comprised between 0.90 and 1.45. The average pressures are measured here over the height of at least one of the blades **14** of the rotor **9** that is to say of the surface which delimits radially inside the air flowpath at the inlet of the rotor **9** at the top **21** of the blade **14**.

(27) The rotor **9** of the fan section **1** can alternatively be directly coupled to the low-pressure shaft **11** (or direct-drive), that is to say without a reduction mechanism. The low-pressure shaft **11** is then coincident with the fan shaft **20** so that the rotor **9** is driven by the low-pressure shaft **11** at the same rotation speed as that of the rotor stages **8a** of the low-pressure turbine **8**.

(28) The propulsion system **1** is configured to provide a thrust comprised between 18,000 lbf (80,068 N) and 51,000 lbf (226,859 N), preferably between 20,000 lbf (88,964 N) and 35,000 lbf (155,688 N).

(29) The fan section **2** can be ducted or unducted.

(30) In the case of a ducted fan section **2**, the fan section **2** comprises a fan casing **12** and the rotor **9** is housed in the fan casing **12**. A ducted fan section **2** comprises a rotor **9** extending upstream of a stator **16**. The vanes **17** of the stator **16** are then generally referred to as “outlet vanes” (or OGV for Outlet Guide Vane) and have a fixed setting relative to the hub of the stator **16**. Moreover, the bypass ratio of the propulsion system **1** is preferably greater than or equal to 10, for example comprised between 10 and 35 inclusive, preferably between 10 and 18 inclusive. The peripheral speed at the top **21** of the blades **14** of the rotor **9** can moreover be comprised between 260 m.Math.s.sup.-1 and 400 m.Math.s.sup.-1 inclusive. The fan pressure ratio can then be comprised between 1.20 and 1.45.

(31) In an unducted fan section **2**, the fan section **2**, which can also be designated by the term “propeller”, is not surrounded by a fan casing. The fan section **2** being unducted, the blades **14** of the rotor **9** have a variable setting. Propulsion systems comprising at least one unducted rotor **9** are known under the terms “open rotor” or “unducted fan”. The propulsion system **1** can comprise two unducted and counter-rotating rotors **9**. Such a propulsion system **1** is known under the acronym “CROR” for “Contra-Rotating Open Rotor” or “UDF” for “Unducted Double Fan”. The rotors **9** can be placed at the rear of the primary spool **3** so as to be of the pusher type or at the front of the primary spool **3** so as to be of the puller type. As a variant, the propulsion system **1** can comprise a single unducted rotor **9** and an unducted stator **16** (straightener). Such a propulsion system **1** is known under the acronym “USF” for “Unducted Single Fan”. In the case of a propulsion system **1** of the USF type, the vanes **17** of the straightener **16** are fixed in rotation relative to the axis of

rotation X of the rotor **9** and, therefore, do not undergo centrifugal force. The vanes **17** of the straightener **16** are, moreover, variable setting vanes.

(32) The removal of the fairing around the fan section **2** makes it possible to increase the bypass ratio very significantly without the propulsion system **1** being penalized by the mass of the casings **12** or nacelles intended to surround the fan section **2**. The bypass ratio of the propulsion system **1** comprising an unducted fan section **2** is thus greater than or equal to 40, for example comprised between 40 and 80 inclusive. The peripheral speed at the top **21** of the blades **14** of the rotor(s) **9** can moreover be comprised between 210 m.Math.s.sup.-1 and 260 m.Math.s.sup.-1 inclusive. The fan pressure ratio can then be preferably comprised between 0.90 and 1.20 inclusive.

(33) The diameter D of the rotor **9** of the fan section **2** can be comprised between 80 inches (203.2 cm) and 185 inches (469.9 cm) inclusive. When the rotor **9** is ducted, the diameter D is preferably comprised between 85 inches (215.9 cm) and 120 inches (304.8 cm) inclusive, for example of the order of 90 inches (228.6 cm), which allows the integration of the propulsion system **1** in a conventional manner, particularly under a wing of the airframe of an aircraft **1**. When the rotor **9** is unducted, the diameter D is preferably greater than or equal to 100 inches (254 cm), for example between 120 inches (304.8 cm) and 156 inches (396.2 cm). The diameter of the rotor **9** is measured here in a plane normal to the axis of rotation X of the rotor **9**, at the level of an intersection between a top **21** and a leading edge **22** of the blades **14** of the rotor **9**. It should be noted that, FIG. 2 and FIG. 3 being partial views, the diameter D is only partially visible.

(34) The reduction mechanism **19** can comprise a planetary gear or star gear, single-stage or two-stage reduction mechanism. For example, the reduction mechanism **19** can be of the star gear (as visible in FIG. 4) type and comprise a sun pinion **19a** (inlet of the reduction mechanism **19**), centered on an axis of rotation of the reduction mechanism **19** generally coincident with the longitudinal axis X and configured to be driven in rotation by the low-pressure shaft **11**, a ring gear **19b** (outlet of the reduction mechanism **19**) coaxial with the sun pinion **19a** and configured to drive in rotation the fan shaft **20** about its axis of rotation X, and a series of planet gears **19c** distributed circumferentially about the axis of rotation X of the rotor **9** of the fan section **2**, between the sun pinion **19a** and the ring gear **19b**, each planet gear **19c** being meshed internally with the sun pinion **19a** and externally with the ring gear **19b**. The series of planet gears **19c** is mounted on a planet gear carrier **19d** which is stationary relative to the stator part **19e** of the propulsion system **1**, for example relative to a casing of the compressor section **4**, **5**. As a variant, the reduction mechanism **19** can be of the planetary gear (as visible in FIG. 5) type, in which case the ring gear **19b** is fixedly mounted on the stator part **19e** of the propulsion system **1** and the fan shaft **20** is driven in rotation by the planet gear carrier **19d**.

(35) Whatever the configuration of the reduction mechanism **19**, the diameter of the ring gear **19b** and of the planet gear carrier **19d** are greater than the diameter of the sun pinion **19a**, so that the rotation speed of the rotor **9** of the fan section **2** is lower than the rotation speed of the low-pressure shaft **11**.

(36) The reduction ratio of the reduction mechanism **19** is greater than or equal to 2.5 and less than or equal to 11. In the case of a propulsion system **1** comprising a rotor **9** of the fan section **2** which is ducted, the reduction ratio can be greater than or equal to 2.7 and less than or equal to 3.5, typically around 3.0. In the case of a propulsion system **1** comprising a rotor **9** of the fan section **2** which is unducted, the reduction ratio can be comprised between 9.0 and 11.0.

(37) The two-spool propulsion system **1** can in particular comprise a single-stage high-pressure turbine **7** that is to say comprising exactly one stage, or a two-stage high-pressure turbine that is to say comprising exactly two stages, a high-pressure compressor **5** comprising at least eight stages and at most eleven stages, a low-pressure turbine **8** comprising at least three stages and at most seven stages and a low-pressure compressor **4** comprising at least two stages and at most four stages.

(38) The limit speed ω (or redline speed) of the low-pressure shaft **11**, which corresponds to the

absolute maximum speed likely to be encountered by the low-pressure shaft **11**, and therefore by the rotor stages **4a**, **8a** of the low-pressure spool, during the entire flight (according to the European certification regulation EASA CS-E 740 or according to the American certification regulation 14-CFR Part 33.87), is comprised between 2,000 revolutions per minute (209 radians per second) and 30,000 revolutions per minute (3,142 radians per second) inclusive, for example between 8,500 revolutions per minute (890 radians per second) and 12,000 revolutions per minute (1,267 radians per second) inclusive, preferably between 9,000 revolutions per minute (942 radians per second) and 11,000 revolutions per minute inclusive (1,152 radians per second). The limit speed corresponds to the maximum rotation speed when the propulsion system **1** is sound, that is to say it is not at the end of its life. It is therefore likely to be reached by the low-pressure shaft **11** in flight conditions. This limit speed forms part of the data declared in the engine certification (or type certificate data sheet). Indeed, this rotation speed is commonly used as a reference speed for the dimensioning of the propulsion systems and in some certification tests, such as blade loss or rotor integrity tests. Of course, the high-pressure shaft **10**, and therefore the rotor stages **5a**, **7a** of the high-pressure spool, also has a limit speed, defined in the same way as for the low-pressure shaft **11**, but greater than that of the low-pressure shaft, for example comprised between 8,000 revolutions per minute and 30,000 revolutions per minute inclusive.

(39) The stator **16** of the fan section, the stator stages **4b**, **5b** of the compressor section **4**, **5**, the stator stages **7b**, **8b** of the turbine section **7**, **8** and the stator part **19e** of the propulsion system **1** are stationary relative to each other and relative to the mast making it possible to fix the propulsion system **1** to the airframe of the aircraft.

(40) In order to optimize the performances of the propulsion system **1**, and in particular to reduce its fuel consumption, without limiting its lifespan, it is advantageous to improve the dimensioning of at least one of the rotor stages **8a** of the low-pressure turbine **8**.

(41) Each rotor stage **8a** of the low-pressure turbine **8** comprises a disk **30** and a plurality of blades **31**. Furthermore, the rotor stages **8a** of the low-pressure turbine **8** are connected together by means of a plurality of shrouds **32** connecting in pairs the disks **30** of the rotor stages **8a**.

(42) The disk **30** is bored. More specifically, the disk **30** has an inner surface **33** delimiting a bore **34** passing axially through the disk **30**. The bore **34** is circular and centered on the longitudinal axis **X** when the disk **30** is mounted in the propulsion system **1**. A bore radius $R_{\text{sub.a}}$ of the disk **30** is then defined as a smallest distance between the longitudinal axis **X** and the inner surface **33** of the disk **30** that is to say as the distance separating the longitudinal axis **X** from the point of the inner surface **33** which is closest to the longitudinal axis **X**. The bore radius $R_{\text{sub.a}}$ can be comprised between 0.01 and 0.5 meters inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**. The inner surface **33** moreover has an upstream edge **35** and a downstream edge **36**, which form the axial ends of the bore **34**. A bore width $L_{\text{sub.a}}$ of the disk **30** is defined as an axial distance between the upstream edge **35** and the downstream edge **36** that is to say as the distance separating the upstream edge **35** from the point of the downstream edge **36** which is closest to the upstream edge **35** or, conversely, as the distance separating the downstream edge **36** from the point of the upstream edge **35** which is closest to the downstream edge **36**. The bore width $L_{\text{sub.a}}$ can be comprised between 0.005 and 0.1 meters inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**. The low-pressure shaft **11** extends through the bores **34** of the disks **30** of the low-pressure turbine **8** while being fixed to at least one of the disks **30** of the low-pressure turbine **8**, to be able to be driven in rotation by the rotor stages **8a** during the expansion of the hot gases circulating from the high-pressure turbine **7**.

(43) Furthermore, the disk **30** has an outer surface **37** delimiting a plurality of slots **38** distributed about the longitudinal axis **X** and extending axially. Each of the slots **38** is configured to ensure the fixing, in a removable or non-removable manner, of one of the blades **31** on the disk **30**. In this regard, each slot **38** is open on the primary flowpath **29** when the disk **30** is mounted in the propulsion system **1**, and can have any shape suitable for fixing the blades **31**, typically a dovetail

or fir tree shape, with at least one, or even several, lobe(s). A rim radius $R_{sub.j}$ of the disk **30** is defined as a smallest distance between the longitudinal axis X and the outer surface **37** of the disk **30** that is to say as the distance separating the longitudinal axis X from the point of the outer surface **37** which is closest to the longitudinal axis X, otherwise called the “rim” of the disk **30**. In other words, the rim radius $R_{sub.j}$ of the disk **30** corresponds to the radius of the slot bottom **38** that is to say the distance separating the deepest (innermost) point of the (radially) deepest of the slots **38** from the longitudinal axis X. The rim radius $R_{sub.j}$ can be comprised between 0.01 and 0.5 meters inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**. A tangential rim speed $U_{sub.j}$ of the disk **30** is defined as the rotation speed of the rim that is to say the rotation speed of the point of the outer surface **37** which is closest to the longitudinal axis X, about of the longitudinal axis X, when the low-pressure shaft **11** is at its limit speed ω . Thus, the tangential rim speed $U_{sub.j}$ of the disk **30** is $R_{sub.j} \cdot \omega$. The tangential rim speed $U_{sub.j}$ can be comprised between 100 and 500 m.Math.s.sup.-1 inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**.

(44) The portion of the disk **30** which extends from the rim to the bore **34** is sometimes called “web **39**” of the disk **30**. The web **39** contributes to transmitting the mechanical loads, in particular radial loads, within the rotor stage **8a** of the low-pressure turbine **8**, during the operation of the propulsion system **1**. A critical radius of the rotor stage **8a** is defined as the distance separating the longitudinal axis X from the position of a critical limit which separates the rotor stage **8a** in two radially distinct parts: a radially inner part and a radially outer part, the radially inner part retaining the radially outer part against the centrifugal forces, during the operation of the propulsion system **1**. The critical limit is generally positioned within the web **39** of the disk **30**. In any case, the performances of the web **39** to ensure the mechanical consistency of the rotor stage **8a** are directly correlated to the bore radius $R_{sub.a}$, to the bore width $L_{sub.a}$ and to the rim radius $R_{sub.j}$.

(45) Each of the blades **31** comprises a root **40** fixed to the disk **30** by cooperation with one of the slots **38**, a stilt **41** connected to the root **40** and comprising a platform **42** delimiting a radially inner portion of the primary flowpath **29**, an airfoil **43** connected to the platform **42** and extending within the primary flowpath **29**. The airfoil **43** has an aerodynamic profile and has, in this regard, a leading edge **44** on which the hot gases strike first, when they meet the stage rotor **8a**, a trailing edge **45** axially opposite to the leading edge **44**, and an end **46** radially opposite to the platform **42**. The airfoil **43** interacts with the hot gases flowing from the low-pressure turbine **7** to drive the disk **30** in rotation about the longitudinal axis X. To do so, the airfoil **43** extends within the primary flowpath **29** with a certain incidence relative to the main gas flow direction. The blade **31** can further comprise a shroud **47**, extending from the end **46** of the airfoil **43**, by being removably or non-removably fixed therein, or by being integral with the airfoil **43**. The shroud **47** ensures the sealing of the primary flowpath **29** by limiting the hot gas leaks at the interface between each rotor stage **8a** and the low-pressure turbine casing **8**, to which the stator stages **8b** are fixed. In this regard, the shroud **47** carries sealing lips intended to cooperate with an abradable material extending from the casing of the low-pressure turbine **8**.

(46) An outer radius $R_{sub.e}$ of the primary flowpath **29**, at the level of the disk **30**, is defined as an average between, on the one hand, a distance between the longitudinal axis X and a junction (or corner point) between the end **46** of the airfoil **43**, where applicable a junction between the end **46** of the airfoil **43** and the shroud **47**, and the leading edge **44** of the airfoil **43** and, on the other hand, a distance between the longitudinal axis X and a junction between the end **46** of the airfoil **43**, where applicable a junction between the end **46** of the airfoil **43** and the shroud **47**, and the trailing edge **45** of the airfoil **43**. The outer radius $R_{sub.e}$ of the primary flowpath **29** can be comprised between 0.15 and 1.0 meters inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**.

(47) An inner radius $R_{sub.i}$ of the primary flowpath **29**, at the level of the disk **30**, is defined as an average between, on the one hand, a distance between the longitudinal axis X and a junction

between the platform **42** and the leading edge **44** of the airfoil **43** and, on the other hand, a distance between the longitudinal axis X and a junction between the platform **42** and the trailing edge **45** of the airfoil **43**. The inner radius $R_{sub.i}$ of the primary flowpath **29** can be comprised between 0.1 and 0.8 meters inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**. A tangential inner flowpath speed $U_{sub.i}$ of the disk **30** is defined as the rotation speed of the junction between the platform **42** and the airfoil **43**, about the longitudinal axis X, when the low-pressure shaft **11** is at its limit speed ω . Thus, the tangential inner flowpath speed $U_{sub.i}$ of the disk **30** is $R_{sub.i} \cdot \omega$. The tangential inner flowpath speed $U_{sub.i}$ can be comprised between 100 and 500 m.s⁻¹ inclusive, depending, in particular, on the considered rotor stage **8a** of the low-pressure turbine **8**.

(48) Each rotor stage **8a** of the low-pressure turbine **8** has a mechanical difficulty N2S which is $\pi \cdot (R_{sub.e}^{sup.2} - R_{sub.i}^{sup.2}) \cdot \omega^{sup.2}$ and which can be comprised between $30 \cdot 10^{sup.6}$ rpm.s².Math.m.s² and $180 \cdot 10^{sup.6}$ rpm.s².Math.m.s² inclusive.

(49) Each of the shrouds **32** has an outer surface **48** facing the stator stage **8b** positioned between the two rotor stages **8a** that the shroud **32** connects. A shroud radius $R_{sub.v}$ is defined as a smallest distance between the longitudinal axis and the outer surface **48** of the shroud **32** that is to say as the distance separating the longitudinal axis X from the point of the outer surface **48** which is closest to the longitudinal axis X. The shroud radius $R_{sub.v}$ can be comprised between 0.05 and 0.8 meters inclusive, depending, in particular, on the considered shroud **32** of the low-pressure turbine **8**. An average radius $R_{sub.m}$ of the primary flowpath **29** at the level of the shroud **32** is defined as an average between, on the one hand, an average between the upstream outer radius $R_{sub.eam}$ and the upstream inner radius $R_{sub.iam}$ of the primary flowpath **29**, at the level of the disk **30** immediately upstream of the shroud **32** and, on the other hand, an average between the downstream outer radius $R_{sub.eav}$ and the downstream inner radius $R_{sub.iav}$ of the primary flowpath **29**, at the level of the disk **30** immediately downstream of the shroud **32**, the shroud **32** connecting the upstream disk **30** to the downstream disk **30**. The average radius $R_{sub.m}$ of the primary flowpath **29** at the level of the shroud **32** can be comprised between 0.05 and 1.0 meters inclusive, depending, in particular, on the considered shroud **32** of the low-pressure turbine **8**.

(50) When the rotor stages **8a** of the low-pressure turbine **8** are driven in rotation about the longitudinal axis X, following the expansion of the hot gases through the turbine section **7**, **8**, the disks **30** are subjected to centrifugal forces all the greater as the rotation speed of these rotor stages **8a** is high. The intensity of these forces is therefore directly correlated to the tangential rim speed $U_{sub.j}$ and/or to the tangential inner flowpath speed $U_{sub.i}$. These forces induce tangential and radial deformations of the disks **30**, due to their centrifugal expansion.

(51) The deformations of the disks **30** can be accentuated by the presence of the blades **31**, which are also subject to centrifugal forces passed on to the disks **30** by the cooperation of their root **40** with the corresponding slot **38** of the disk **30**. In this regard, the mechanical difficulty N2S is in particular representative of the stress exerted by the airfoil **43** on the stilt **41** and, therefore, on the disk **30**, both tangentially and radially.

(52) These deformations induce tangential and radial stresses within the rotor stages **8a** of the low-pressure turbine **8** which may, depending on the dimensions of the rotor stages **8a** and on the limits of admissibility of the materials which compose them, damage them, thus reducing their lifespan, but also the capacity of the disks **30** to retain the blades **31**.

(53) To reduce these stresses, it could be envisaged to increase the dimensions of the disks **30** and/or of the shrouds **32**, typically by reducing the bore radii $R_{sub.a}$, by increasing the bore widths $L_{sub.a}$, by increasing the rim radii $R_{sub.j}$ and/or by increasing the shroud radii $R_{sub.v}$. However, this would lead to an increase in the bulk of the low-pressure turbine **8**, which directly affects the compactness of the propulsion system **1** and, consequently, the fuel consumption of the aircraft **100**.

(54) To improve both the performances and the compactness of the propulsion system **1**, it is in

particular provided, within the framework of the present disclosure, a method E for manufacturing the propulsion system **1** which comprises steps E1, E2, E3, E3', E4, E4', E5, E5', E5'' of dimensioning the rotor stages **8a** of the low-pressure turbine **8**.

(55) During a step E1 of dimensioning at least one of the disks **30** of the rotor stages **8a** of the low-pressure turbine **8**, the bore radius $R_{\text{sub.a}}$ and the rim radius $R_{\text{sub.j}}$ are chosen such that the relation (1a) below is verified:

(56) $\omega * U_j + \frac{1}{2} \leq \frac{R_a}{R_j}$ with: $U_j = R_j * \omega$ where: ω is the speed of the low-pressure shaft **11** defined previously, expressed in radians per second; α is $-0.0027 \text{ m.sup.-1.Math.s}$; $\beta_{\text{sub.1}}$ is 0.4; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second.

(57) In this way, the radial bulk of the disk **30** and, consequently, of the rotor stage **8a** is reduced, without the centrifugal forces it undergoes due to the increase in the tangential rim speed $U_{\text{sub.j}}$, for improving the efficiency of the propulsion system **1**, significantly reducing its lifespan.

(58) Preferably, the bore radius $R_{\text{sub.a}}$ and the rim radius $R_{\text{sub.j}}$ are chosen such that the relation (1b) below is verified:

(59) $\omega * U_j + \frac{1}{2} \leq \frac{R_a}{R_j}$ where: α is $-0.0027 \text{ m.sup.-1.Math.s}$; $\beta_{\text{sub.2}}$ is 1.2951; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second.

(60) The ratio

$$(61) \frac{R_a}{R_j}$$

is strictly positive, since the rim radius $R_{\text{sub.j}}$ and the bore radius $R_{\text{sub.a}}$ are physical quantities whose measurement is strictly positive. Furthermore, the ratio

$$(62) \frac{R_a}{R_j}$$

is strictly less than 1, because the rim radius $R_{\text{sub.j}}$ is strictly greater than the bore radius $R_{\text{sub.a}}$.

(63) Moreover, during a step E2 of dimensioning at least one of the disks **30** of the rotor stages **8a** of the low-pressure turbine **8**, which may or may not be coincident with the step E1 of dimensioning the disk **30** during which the relation (1) is verified, the bore width $L_{\text{sub.a}}$ and the rim radius $R_{\text{sub.j}}$ are chosen such that the relation (2a) below is verified:

(64) $\frac{100 * L_a}{R_j} \leq \omega * \frac{U_j^2}{1,000} + \frac{1}{2}$ with: $U_j = R_j * \omega$ where: ω is the speed of the low-pressure shaft **11** defined previously, expressed in radians per second; δ is $0.2424 \text{ s.sup.2.Math.m.sup.-2}$; ζ is 10; $L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second.

(65) In this way, the axial bulk of the disk **30** and, consequently, of the rotor stage **8a** is reduced, without the centrifugal forces it undergoes due to the increase in the tangential rim speed $U_{\text{sub.j}}$, for improving the efficiency of the propulsion system **1**, significantly reducing its lifespan.

(66) Preferably, the bore width $L_{\text{sub.a}}$ and the rim radius $R_{\text{sub.j}}$ are chosen such that the relation (2b) below is verified:

(67) $\frac{100 * L_a}{R_j} \leq \omega * \frac{U_j^2}{1,000} + \frac{1}{2}$ where: δ is $0.2424 \text{ s.sup.2.Math.m.sup.-2}$; ζ is -8 ; $L_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second.

(68) The ratio

$$(69) \frac{100 * L_a}{R_j}$$

is strictly positive, since the rim radius $R_{\text{sub.j}}$ and the bore width $L_{\text{sub.a}}$ are physical quantities whose measurement is strictly positive.

(70) Furthermore, during a step E3 of dimensioning at least one of the disks **30** of the rotor stages **8a**, which may or may not be coincident with the step(s) E1, E2 of dimensioning the disk **30** during which the relation (1) and/or relation (2) is (are) verified, and during a step E3' of dimensioning at least one of the blades **31** of this disk **30**, the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, the outer radius $R_{\text{sub.e}}$ and the inner radius $R_{\text{sub.i}}$ are chosen such that the relation (3a) below is verified:

(71) $\kappa * N2S + \frac{1}{2} \leq \frac{R_a}{R_j}$ with: $N2S = \omega * (R_e^2 - R_i^2) * \frac{1}{2}$ where: ω is the speed of the low-pressure shaft **11** defined previously, expressed in revolutions per minute (rpm); κ is -0.0091

rpm.sup.-2.Math.m.sup.-2; $\lambda_{\text{sub.1}}$ is 0.3; $R_{\text{sub.a}}$, $R_{\text{sub.j}}$, $R_{\text{sub.e}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $N2S$ is expressed in $10^{\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}}$.

(72) In this way, the radial bulk of the rotor stage **8a** is reduced, without the centrifugal forces it undergoes due to the increase in the mechanical difficulty $N2S$, for improving the efficiency of the propulsion system **1**, significantly reducing its lifespan.

(73) Preferably, the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, the outer radius $R_{\text{sub.e}}$ and the inner radius $R_{\text{sub.i}}$ are chosen such that the relation (3b) below is verified:

(74) $\kappa N2S + \frac{R_a}{R_j} \leq \frac{R_a}{R_j}$ where: κ is $-0.0091 \text{ rpm.sup.-2.Math.m.sup.2}$; $\lambda_{\text{sub.2}}$ is 0.864; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $N2S$ is expressed in $10^{\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}}$.

(75) The ratio

$$(76) 0 < \frac{R_a}{R_j}$$

is strictly positive, since the rim radius $R_{\text{sub.j}}$ and the bore radius $R_{\text{sub.a}}$ are physical quantities whose measurement is strictly positive. Furthermore, the ratio

$$(77) \frac{R_a}{R_j}$$

is strictly less than 1, because the rim radius $R_{\text{sub.j}}$ is strictly greater than the bore radius $R_{\text{sub.a}}$.

(78) During a step E4 of dimensioning at least one of the disks **30** of the rotor stages **8a**, which may or may not be coincident with the step(s) E1, E2, E3, E3' of dimensioning the disk **30** during which the relation (1), the relation (2) and/or the relation (3) is (are) verified, and during a step E4' of dimensioning at least one of the blades **31** of this disk **30**, which may or may not be coincident with the step E3' of dimensioning the blade **31** during which the relation (3) is verified, the bore width $L_{\text{sub.a}}$ and the inner radius $R_{\text{sub.i}}$ are chosen such that relation (4a) below is verified:

(79) $\frac{100 * L_a}{R_i} \leq v * \frac{U_i^2}{1,000} + \frac{U_i^2}{1,000}$ with: $U_i = R_i * \omega$ where: ω is the speed of the low-pressure shaft **11** defined previously, expressed in radians per second; v is $0.079 \text{ s.sup.2.Math.m.sup.-2}$; $\xi_{\text{sub.1}}$ is 2.28; $L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $U_{\text{sub.i}}$ is expressed in meters per second.

(80) In this way, the axial bulk of the rotor stage **8a** is reduced without the centrifugal forces it undergoes due to the increase in the tangential inner flowpath speed $U_{\text{sub.i}}$, for improving the efficiency of the propulsion system **1**, significantly reducing its lifespan.

(81) Preferably, the bore width $L_{\text{sub.a}}$ and the inner radius $R_{\text{sub.i}}$ are chosen such that the relation (4b) below is verified:

(82) $\frac{100 * L_a}{R_i} \leq v * \frac{U_i^2}{1,000} + \frac{U_i^2}{1,000}$ where: v is $0.079 \text{ s.sup.2.Math.m.sup.-2}$; $\xi_{\text{sub.2}}$ is -1.41; $L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $U_{\text{sub.i}}$ is expressed in meters per second.

(83) The ratio

$$(84) \frac{100 * L_a}{R_i}$$

is strictly positive, since the inner radius $R_{\text{sub.i}}$ and the bore width $L_{\text{sub.a}}$ are physical quantities whose measurement is strictly positive.

(85) During a step E5 of dimensioning at least one of the shrouds **32** of the low-pressure turbine **8** connecting an upstream disk **30** to a downstream disk **30**, during a step E5' of dimensioning at least one of the first blades **31** of the upstream disk **30** and during a step E5'' of dimensioning at least one of the second blades **31** of the downstream disk **30**, the shroud radius $R_{\text{sub.v}}$ and the average radius $R_{\text{sub.m}}$ of the primary flowpath **29** are chosen such that the relation (5a) below is verified:

(86) $\frac{1}{100} * \frac{N2S_{\text{am}}}{100} + \frac{1}{100} \leq \frac{R_v}{R_m}$ with: $N2S_{\text{am}} = \frac{1}{2} * (R_{\text{eam}}^2 - R_{\text{iam}}^2) * \omega^2$ and: $R_m = \frac{R_{\text{eam}} + R_{\text{iam}}}{2} + \frac{R_{\text{eav}} + R_{\text{iav}}}{2}$

where: ω is the speed of the low-pressure shaft **11** defined previously, expressed in revolutions per minute (rpm); $\sigma_{\text{sub.1}}$ is $-0.4 \text{ rpm.sup.-2.Math.m.sup.2}$; $\chi_{\text{sub.1}}$ is 0.784; $R_{\text{sub.eam}}$, $R_{\text{sub.iam}}$, $R_{\text{sub.eav}}$, $R_{\text{sub.iav}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10^{\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}}$.

(87) In this way, the radial bulk of the shroud **32** and, consequently, of the rotor stages **8a** it connects, is reduced, without the centrifugal forces undergone by these rotor stages **8a** due to the

increase in the mechanical difficulty N2S, for improving the efficiency of the propulsion system **1**, significantly reducing its lifespan.

(88) Preferably, the shroud radius $R_{\text{sub.v}}$ and the average radius $R_{\text{sub.m}}$ of the primary flowpath **29** are chosen such that the relation (5b) below is verified:

(89) $2 * \frac{N2S_{\text{am}}}{100} + 2 \leq \frac{R_v}{R_m}$ where: $\sigma_{\text{sub.2}}$ is $-0.512 \text{ rpm.sup.-2.Math.m.sup.-2}$ $\chi_{\text{sub.2}}$ is 0.82; $R_{\text{sub.m}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10.\text{sup.6.Math.rpm.sup.2.Math.m.sup.2}$.

(90) The ratio

(91) $\frac{R_v}{R_m}$

is strictly positive, since the shroud radius $R_{\text{sub.v}}$ and the average radius $R_{\text{sub.m}}$ of the primary flowpath **29** are physical quantities whose measurement is strictly positive. Furthermore, the ratio

(92) $\frac{R_v}{R_m}$

is strictly less than 1, because the average radius $R_{\text{sub.m}}$ of the primary flowpath **29** is strictly greater than the shroud radius $R_{\text{sub.v}}$.

(93) Surprisingly, a propulsion system **1** obtained at the end of this manufacturing method E or a propulsion system **1** obtained by another manufacturing method, but whose low-pressure turbine **8** has dimensions conforming to at least one of the relations (1) to (5), has the advantage of being sufficiently compact to limit the fuel consumption of the aircraft **100** to which it is fixed, while allowing an improvement in its performances through the increase of the limit speed of its low-pressure shaft **11**.

(94) The relations (1) to (5) can therefore be used during the design of propulsion systems in order, in particular, to determine the feasibility of the rotor stages **8a** of the low-pressure turbine **8**. Indeed, these relations make it possible to improve both the compactness and the efficiency of the propulsion systems.

Claims

1. A propulsion system comprising: a drive shaft; a drive turbine comprising a drive turbine stator and a drive turbine rotor, the drive turbine rotor being connected to the drive shaft to drive the drive shaft in rotation relative to the drive turbine stator about a longitudinal axis, the drive turbine rotor comprising a plurality of shrouds, a plurality of turbine disks connected in pairs by a shroud of the plurality of shrouds, and a plurality of turbine blades; a fan section comprising a fan rotor and a fan stator, the drive shaft being connected to the fan rotor to drive the fan rotor in rotation relative to the fan stator about the longitudinal axis; wherein at least one shroud of the plurality of shrouds connects an upstream turbine disk to a downstream turbine disk of the plurality of turbine disks and has: an outer surface facing the drive turbine stator; and a shroud radius $R_{\text{sub.v}}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the shroud; wherein each of the upstream turbine disk and of the downstream turbine disk is centered on the longitudinal axis and has an outer surface delimiting a plurality of slots distributed about the longitudinal axis; wherein a first turbine blade of the plurality of turbine blades comprises: a first root fixed to the upstream turbine disk in a respective first slot of the plurality of slots of the upstream turbine disk; a first stilt connected to the first root and comprising a first platform delimiting a first radially inner portion of a flowpath passing through the drive turbine; and a first airfoil connected to the first platform and extending within the flowpath, the first airfoil having a first leading edge, a first trailing edge and a first end opposite to the first platform; wherein a second turbine blade of the plurality of turbine blades comprises: a second root fixed to the downstream turbine disk in a respective second slot of the plurality of slots of the downstream turbine disk; a second stilt connected to the second root and comprising a second platform delimiting a second radially inner portion of the flowpath passing through the drive turbine; and a second airfoil connected to the

second platform and extending within the flowpath the second airfoil having a second leading edge, a second trailing edge and a second end opposite to the second platform; wherein the flowpath has: an upstream outer radius $R_{\text{sub.eam}}$ which is defined as an average between a distance between the longitudinal axis and a junction between the first end and the first leading edge, and a distance between the longitudinal axis and a junction between the first end and the first trailing edge; an upstream inner radius $R_{\text{sub.iam}}$ which is defined as an average between a distance between the longitudinal axis and a junction between the first platform and the first leading edge, and a distance between the longitudinal axis and a junction between the first platform and the first trailing edge; a downstream outer radius $R_{\text{sub.eav}}$ which is defined as an average between a distance between the longitudinal axis and a junction between the second end and the second leading edge, and a distance between the longitudinal axis and a junction between the second end and the second trailing edge; and a downstream inner radius $R_{\text{sub.iav}}$ which is defined as an average between a distance between the longitudinal axis and a junction between the second platform and the second leading edge, and a distance between the longitudinal axis and a junction between the second platform and the second trailing edge; wherein the drive shaft has a limit speed ω which is defined as a highest speed at which the drive shaft is capable of being driven in rotation about the longitudinal axis during operation of the propulsion system; wherein the shroud radius $R_{\text{sub.v}}$, the upstream outer radius $R_{\text{sub.eam}}$, the upstream inner radius $R_{\text{sub.iam}}$, the downstream outer radius $R_{\text{sub.eav}}$, the downstream inner radius $R_{\text{sub.iav}}$ and the limit speed ω are such that:

$\sigma_{\text{sub.1}} * \frac{N2S_{\text{am}}}{100} + \chi_{\text{sub.1}} \leq \frac{R_v}{R_m}$ with: $N2S_{\text{am}} = \sigma_{\text{sub.1}} * (R_{\text{eam}}^2 - R_{\text{iam}}^2) * \omega^2$ and: $R_m = \frac{R_{\text{eam}} + R_{\text{iam}}}{2} + \frac{R_{\text{eav}} + R_{\text{iav}}}{2}$ where: ω is expressed in revolutions per minute (rpm); $\sigma_{\text{sub.1}}$ is $-0.4 \text{ rpm} \cdot \text{sup} \cdot -2 * \text{m} \cdot \text{sup} \cdot -2$; $\chi_{\text{sub.1}}$ is 0.784; $R_{\text{sub.eam}}$, $R_{\text{sub.iam}}$, $R_{\text{sub.eav}}$, $R_{\text{sub.iav}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10 \cdot \text{sup} \cdot 6 \text{ rpm} \cdot \text{sup} \cdot 2 * \text{m} \cdot \text{sup} \cdot 2$; wherein a ratio $\frac{R_v}{R_m}$ is strictly positive and strictly less than 1; wherein the shroud radius $R_{\text{sub.v}}$ is comprised in a range from 0.05 to 0.8 meters inclusive, the upstream outer radius $R_{\text{sub.eam}}$ and the downstream outer radius $R_{\text{sub.eav}}$ are comprised in a range from 0.15 to 1.0 meters inclusive, the downstream inner radius $R_{\text{sub.iav}}$ and the upstream inner radius $R_{\text{sub.iam}}$ are comprised in a range from 0.1 to 0.8 meters inclusive, $R_{\text{sub.m}}$ is comprised in a range from 0.05 to 1.0 meters inclusive and $N2S_{\text{sub.am}}$ is comprised in a range from $30 * 10 \cdot \text{sup} \cdot 6 \text{ rpm} \cdot \text{sup} \cdot 2 * \text{m} \cdot \text{sup} \cdot 2$ to $180 * 10 \cdot \text{sup} \cdot 6 \text{ rpm} \cdot \text{sup} \cdot 2 * \text{m} \cdot \text{sup} \cdot 2$ inclusive.

2. The propulsion system of claim 1, wherein the shroud radius $R_{\text{sub.v}}$, the upstream outer radius $R_{\text{sub.eam}}$, the upstream inner radius $R_{\text{sub.iam}}$, the downstream outer radius $R_{\text{sub.eav}}$, the downstream inner radius $R_{\text{sub.iav}}$ and the limit speed ω are such that: $\sigma_{\text{sub.2}} * \frac{N2S_{\text{am}}}{100} + \chi_{\text{sub.2}} \leq \frac{R_v}{R_m}$ where: $\sigma_{\text{sub.2}}$ is $-0.512 \text{ rpm} \cdot \text{sup} \cdot -2 * \text{m} \cdot \text{sup} \cdot -2$; $\chi_{\text{sub.2}}$ is 0.82; $R_{\text{sub.m}}$ and $R_{\text{sub.v}}$ are expressed in meters; and $N2S_{\text{sub.am}}$ is expressed in $10 \cdot \text{sup} \cdot 6 \text{ rpm} \cdot \text{sup} \cdot 2 * \text{m} \cdot \text{sup} \cdot 2$.

3. The propulsion system of claim 1, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis; a bore radius $R_{\text{sub.a}}$ which is defined as a smallest distance between the longitudinal axis and the inner surface of the at least one of the upstream turbine disk and of the downstream turbine disk; and a rim radius $R_{\text{sub.j}}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$ and the limit speed ω are such that: $\alpha * U_j + \beta_{\text{sub.1}} \leq \frac{R_a}{R_j}$ with: $U_j = R_j * \omega$ where: ω is expressed in radians per second; α is $-0.0027 \text{ m} \cdot \text{sup} \cdot -1 * \text{s}$; $\beta_{\text{sub.1}}$ is 0.4; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second; wherein a ratio $\frac{R_a}{R_j}$ is strictly positive and strictly less than 1; wherein the bore radius $R_{\text{sub.a}}$ is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius $R_{\text{sub.j}}$ is comprised in a range from 0.01 to 0.5 meters inclusive, and $U_{\text{sub.j}}$ is comprised in a range from 100 to 500 $\text{m} \cdot \text{s} \cdot \text{sup} \cdot -1$ inclusive.

4. The propulsion system of claim 3, wherein the bore radius R.sub.a, the rim radius R.sub.j and the limit speed ω are such that: $\frac{100 * U_j}{R_j} + \frac{U_j^2}{1,000} \leq \frac{R_a}{R_j}$ where: α is $-0.0027 \text{ m.sup.-1*s}$; β .sub.2 is 1.2951; R.sub.a and R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second.
5. The propulsion system of claim 1, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; a bore width L.sub.a which is defined as an axial distance between the upstream edge and the downstream edge; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the bore width L.sub.a, the rim radius R.sub.j and the limit speed w are such that: $\frac{100 * L_a}{R_j} \leq \frac{U_j^2}{1,000} + \frac{1}{\delta}$ with: $U_j = R_j * \omega$ where: ω is expressed in radians per second; δ is $0.2424 \text{ s.sup.2*m.sup.-2}$; ζ .sub.1 is 10; L.sub.a and R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second; wherein a ratio $\frac{100 * L_a}{R_j}$ is strictly positive; wherein the bore width L.sub.a is comprised in a range from 0.005 to 0.1 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and U.sub.j is comprised in a range from 100 to 500 m*s.sup.-1 inclusive.
6. The propulsion system of claim 5, wherein the bore width L.sub.a, the rim radius R.sub.j and the limit speed ω are such that: $\frac{100 * L_a}{R_j} \leq \frac{U_j^2}{1,000} + \frac{1}{\delta}$ where: δ is $0.2424 \text{ s.sup.2*m.sup.-2}$; ζ .sub.2 is -8 ; L.sub.a and R.sub.j are expressed in meters; and U.sub.j is expressed in meters per second.
7. The propulsion system of claim 1, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis; a bore radius R.sub.a which is defined as a smallest distance between the longitudinal axis and the inner surface of the at least one of the upstream turbine disk and of the downstream turbine disk; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the bore radius R.sub.a, the rim radius R.sub.j, a respective outer radius R.sub.e, a respective inner radius R.sub.i and the limit speed w are such that: $\frac{100 * N2S}{R_j} + \frac{1}{\kappa} \leq \frac{R_a}{R_j}$ with: $N2S = \frac{(R_e^2 - R_i^2) * \omega^2}{2}$ where: ω is expressed in revolutions per minute (rpm); κ is $-0.0091 \text{ rpm.sup.-2*m.sup.-2}$; λ .sub.1 is 0.3; R.sub.a, R.sub.j, R.sub.e and R.sub.i are expressed in meters; and N2S is expressed in $10 \text{ sup.6 rpm.sup.2*m.sup.2}$; wherein a ratio $\frac{R_a}{R_j}$ is strictly positive and strictly less than 1; wherein the bore radius R.sub.a is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius R.sub.j is comprised in a range from 0.01 to 0.5 meters inclusive and N2S is comprised in a range from $30 * 10 \text{ sup.6 rpm.sup.2*m.sup.2}$ to $180 * 10 \text{ sup.6 rpm.sup.2*m.sup.2}$ inclusive.
8. The propulsion system of claim 7, wherein the bore radius R.sub.a, the rim radius R.sub.j, the respective outer radius R.sub.e, the respective inner radius R.sub.i and the limit speed ω are such that: $\frac{100 * N2S}{R_j} + \frac{1}{\kappa} \leq \frac{R_a}{R_j}$ where: κ is $-0.0091 \text{ rpm.sup.-2*m.sup.-2}$; λ .sub.2 is 0.864; R.sub.a and R.sub.j are expressed in meters; and N2S is expressed in $10 \text{ sup.6 rpm.sup.2*m.sup.2}$.
9. The propulsion system of claim 1, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; and a bore width L.sub.a which is defined as an axial distance between the upstream edge and the downstream edge; wherein the bore width L.sub.a, a respective inner radius R.sub.i and the limit speed w are such that: $\frac{100 * L_a}{R_i} \leq \frac{U_i^2}{1,000} + \frac{1}{\nu}$ with: $U_i = R_i * \omega$ where: ω is expressed in radians per second; ν

is $0.079 \text{ s.sup.2} \cdot \text{m.sup.-2}$; $\xi.\text{sub.1}$ is 2.28; $L.\text{sub.a}$ and $R.\text{sub.i}$ are expressed in meters; and $U.\text{sub.i}$ is expressed in meters per second; wherein a ratio $\frac{100 \cdot L_a}{R_i}$ is strictly positive; wherein the bore width $L.\text{sub.a}$ is comprised in a range from 0.005 to 0.1 meters inclusive and $U.\text{sub.i}$ is comprised in a range from 100 to 500 $\text{m} \cdot \text{s.sup.-1}$ inclusive.

10. The propulsion system of claim 9, wherein the respective inner radius $R.\text{sub.i}$ and the limit speed ω are such that: $\frac{100 \cdot L_a}{R_i} \leq v \cdot \frac{U_i^2}{1,000} + \xi.\text{sub.2}$ where: v is $0.079 \text{ s.sup.2} \cdot \text{m.sup.-2}$; $\xi.\text{sub.2}$ is -1.41 ; $L.\text{sub.a}$ and $R.\text{sub.i}$ are expressed in meters; and $U.\text{sub.i}$ is expressed in meters per second.

11. A method for manufacturing a propulsion system, the propulsion system comprising: a drive shaft; a drive turbine comprising a drive turbine stator and a drive turbine rotor, the drive turbine rotor being connected to the drive shaft to drive the drive turbine rotor in rotation relative to the drive turbine stator about a longitudinal axis, the drive turbine rotor comprising a plurality of shrouds, a plurality of turbine disks connected in pairs by a shroud of the plurality of shrouds, and a plurality of turbine blades; a fan section comprising a fan rotor and a fan stator, the drive shaft being connected to the fan rotor to drive the fan rotor in rotation relative to the fan stator about the longitudinal axis; wherein at least one shroud of the plurality of shrouds connects an upstream turbine disk to a downstream turbine disk of the plurality of turbine disks and has: an outer surface facing the drive turbine stator; and a shroud radius $R.\text{sub.v}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the shroud; wherein each of the upstream turbine disk and of the downstream turbine disk is centered on the longitudinal axis and has an outer surface delimiting a plurality of slots distributed about the longitudinal axis; wherein a first turbine blade of the plurality of turbine blades comprises: a first root fixed to the upstream turbine disk in a respective first slot of the plurality of slots of the upstream turbine disk; a first stilt connected to the first root and comprising a first platform delimiting a first radially inner portion of a flowpath passing through the drive turbine; and a first airfoil connected to the first platform and extending within the flowpath, the first airfoil having a first leading edge, a first trailing edge and a first end opposite to the first platform; wherein a second turbine blade of the plurality of turbine blades comprises: a second root fixed to the downstream turbine disk in a respective second slot of the plurality of slots of the downstream turbine disk; a second stilt connected to the second root and comprising a second platform delimiting a second radially inner portion of the flowpath passing through the drive turbine; and a second airfoil connected to the second platform and extending within the flowpath, the second airfoil having a second leading edge, a second trailing edge and a second end opposite to the second platform; wherein the flowpath has: an upstream outer radius $R.\text{sub.eam}$ which is defined as an average between a distance between the longitudinal axis and a junction between the first end and the first leading edge, and a distance between the longitudinal axis and a junction between the first end and the first trailing edge; an upstream inner radius $R.\text{sub.iam}$ which is defined as an average between a distance between the longitudinal axis and a junction between the first platform and the first leading edge, and a distance between the longitudinal axis and a junction between the first platform and the first trailing edge; a downstream outer radius $R.\text{sub.eav}$ which is defined as an average between a distance between the longitudinal axis and a junction between the second end and the second leading edge, and a distance between the longitudinal axis and a junction between the second end and the second trailing edge; and a downstream inner radius $R.\text{sub.iav}$ which is defined as an average between a distance between the longitudinal axis and a junction between the second platform and the second leading edge, and a distance between the longitudinal axis and a junction between the second platform and the second trailing edge; wherein the drive shaft has a limit speed $@$ which is defined as a highest speed at which the drive shaft is capable of being driven in rotation about the longitudinal axis during operation of the propulsion system; wherein the method comprises dimensioning the at least one shroud, dimensioning the first turbine blade and dimensioning the second turbine blade such that the shroud radius $R.\text{sub.v}$, the upstream outer radius $R.\text{sub.eam}$, the upstream inner radius

R.sub.iam, the downstream outer radius R.sub.eav, the downstream inner radius R.sub.iav and the limit speed ω are such that:

$$\frac{1}{2} * \frac{N2S_{am}}{100} + \frac{1}{2} \leq \frac{R_v}{R_m} \text{ with: } N2S_{am} = \frac{1}{2} * (R_{eam}^2 - R_{iam}^2) * \omega^2 \text{ and: } R_m = \frac{R_{eam} + R_{iam}}{2} + \frac{R_{eav} + R_{iav}}{2} \text{ where: } \omega \text{ is}$$

expressed in revolutions per minute (rpm); $\sigma_{sub.1}$ is $-0.4 \text{ rpm} \cdot \text{sup.}^{-2} \cdot \text{m} \cdot \text{sup.}^{-2}$; $\chi_{sub.1}$ is 0.784; R.sub.eam, R.sub.iam, R.sub.eav, R.sub.iav and R.sub.v are expressed in meters; and N2S.sub.am is expressed in $10 \cdot \text{sup.}^6 \text{ rpm} \cdot \text{sup.}^2 \cdot \text{m} \cdot \text{sup.}^2$; wherein a ratio $\frac{R_v}{R_m}$ is strictly positive and strictly less than 1; wherein the shroud radius R.sub.v is comprised in a range from 0.05 to 0.8 meters inclusive, the upstream outer radius R.sub.eam and the downstream outer radius R.sub.eav are comprised in a range from 0.15 to 1.0 meters inclusive, the downstream inner radius R.sub.iav and the upstream inner radius R.sub.iam are comprised in a range from 0.1 to 0.8 meters inclusive, R.sub.m is comprised in a range from 0.05 to 1.0 meters inclusive and N2S.sub.am is comprised in a range from $30 \cdot 10 \cdot \text{sup.}^6 \text{ rpm} \cdot \text{sup.}^2 \cdot \text{m} \cdot \text{sup.}^2$ to $180 \cdot 10 \cdot \text{sup.}^6 \text{ rpm} \cdot \text{sup.}^2 \cdot \text{m} \cdot \text{sup.}^2$ inclusive.

12. The method of claim 11, wherein dimensioning the at least one shroud, dimensioning the first turbine blade and dimensioning the second turbine blade are such that the shroud radius R.sub.v, the upstream outer radius R.sub.eam, the upstream inner radius R.sub.iam, the downstream outer radius R.sub.eav, the downstream inner radius R.sub.iav and the limit speed w are such that:

$$\frac{2}{2} * \frac{N2S_{am}}{100} + \frac{2}{2} \leq \frac{R_v}{R_m} \text{ where: } \sigma_{sub.2} \text{ is } -0.512 \text{ rpm} \cdot \text{sup.}^{-2} \cdot \text{m} \cdot \text{sup.}^{-2}; \chi_{sub.2} \text{ is } 0.82; R_{sub.m} \text{ and } R_{sub.v} \text{ are expressed in meters; and } N2S_{sub.am} \text{ is expressed in } 10 \cdot \text{sup.}^6 \text{ rpm} \cdot \text{sup.}^2 \cdot \text{m} \cdot \text{sup.}^2.$$

13. The method of claim 11, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis; a bore radius R.sub.a which is defined as a smallest distance between the longitudinal axis and the inner surface of the at least one of the upstream turbine disk and of the downstream turbine disk; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the method further comprises dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk such that the bore radius R.sub.a, the rim radius R.sub.j and the limit speed ω are such that:
$$\frac{1}{2} * U_j + \frac{1}{2} \leq \frac{R_a}{R_j} \text{ with: } U_j = R_j * \omega^2 \text{ where: } \omega \text{ is expressed in radians per second; } \alpha \text{ is } -0.0027 \text{ m} \cdot \text{sup.}^{-1} \cdot \text{s}; \beta_{sub.1} \text{ is } 0.4; R_{sub.a} \text{ and } R_{sub.j} \text{ are expressed in meters; and } U_{sub.j} \text{ is expressed in meters per second; wherein a ratio } \frac{R_a}{R_j} \text{ is strictly positive and strictly less than 1; wherein the bore radius } R_{sub.a} \text{ is comprised in a range from } 0.01 \text{ to } 0.5 \text{ meters inclusive, the rim radius } R_{sub.j} \text{ is comprised in a range from } 0.01 \text{ to } 0.5 \text{ meters inclusive and } U_{sub.j} \text{ is comprised in a range from } 100 \text{ to } 500 \text{ m} \cdot \text{s} \cdot \text{sup.}^{-1} \text{ inclusive.}$$

14. The method of claim 13, wherein dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk is such that the bore radius R.sub.a, the rim radius R.sub.j and the limit speed ω are such that:
$$\frac{1}{2} * U_j + \frac{2}{2} \leq \frac{R_a}{R_j} \text{ where: } \alpha \text{ is } -0.0027 \text{ m} \cdot \text{sup.}^{-1} \cdot \text{s}; \beta_{sub.2} \text{ is } 1.2951; R_{sub.a} \text{ and } R_{sub.j} \text{ are expressed in meters; and } U_{sub.j} \text{ is expressed in meters per second.}$$

15. The method of claim 11, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; a bore width L.sub.a which is defined as an axial distance between the upstream edge and the downstream edge; and a rim radius R.sub.j which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the method further comprises dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk such that the bore width L.sub.a, the rim radius R.sub.j and the limit speed ω are such that:
$$\frac{100 * L_a}{R_j} \leq \frac{1}{2} * \frac{U_j^2}{1,000} + \frac{1}{2} \text{ with: } U_j = R_j * \omega^2 \text{ where: } \omega \text{ is expressed in radians per second; } \delta \text{ is } 0.2424 \text{ s} \cdot \text{sup.}^2 \cdot \text{m} \cdot \text{sup.}^{-2}; \zeta_{sub.1} \text{ is } 10; L_{sub.a} \text{ and } R_{sub.j}$$

are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second; wherein a ratio $\frac{100 * L_a}{R_j}$ is strictly positive; wherein the bore width $L_{\text{sub.a}}$ is comprised in a range from 0.005 to 0.1 meters inclusive, the rim radius $R_{\text{sub.j}}$ is comprised in a range from 0.01 to 0.5 meters inclusive and $U_{\text{sub.j}}$ is comprised in a range from 100 to 500 $\text{m} * \text{s}^{\text{sup.}-1}$ inclusive.

16. The method of claim 15, wherein dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk is such that the bore width $L_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$ and the limit speed w are such that: $\frac{100 * L_a}{R_j} \leq \delta * \frac{U_j^2}{1,000} + \zeta_{\text{sub.2}}$ where: δ is $0.2424 \text{ s}^{\text{sup.}2} * \text{m}^{\text{sup.}-2}$; $\zeta_{\text{sub.2}}$ is -8 ; $L_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $U_{\text{sub.j}}$ is expressed in meters per second.

17. The method of claim 11, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis; a bore radius $R_{\text{sub.a}}$ which is defined as a smallest distance between the longitudinal axis and the inner surface of the at least one of the upstream turbine disk and of the downstream turbine disk; and a rim radius $R_{\text{sub.j}}$ which is defined as a smallest distance between the longitudinal axis and the outer surface of the at least one of the upstream turbine disk and of the downstream turbine disk; wherein the method further comprises dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk and dimensioning at least one of the first turbine blade and of the second turbine blade such that the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, a respective outer radius $R_{\text{sub.e}}$, a respective inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that: $\kappa * N2S + \lambda_{\text{sub.1}} \leq \frac{R_a}{R_j}$ with: $N2S = \frac{\omega}{2\pi} * (R_e^2 - R_i^2) * \frac{1}{2}$ where: ω is expressed in revolutions per minute (rpm); κ is $-0.0091 \text{ rpm}^{\text{sup.}-2} * \text{m}^{\text{sup.}-2}$; $\lambda_{\text{sub.1}}$ is 0.3; $R_{\text{sub.a}}$, $R_{\text{sub.j}}$, $R_{\text{sub.e}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $N2S$ is expressed in $10^{\text{sup.}6} \text{ rpm}^{\text{sup.}2} * \text{m}^{\text{sup.}2}$; wherein a ratio $\frac{R_a}{R_j}$ is strictly positive and strictly less than 1; wherein the bore radius $R_{\text{sub.a}}$ is comprised in a range from 0.01 to 0.5 meters inclusive, the rim radius $R_{\text{sub.j}}$ is comprised in a range from 0.01 to 0.5 meters inclusive and $N2S$ is comprised in a range from $30 * 10^{\text{sup.}6} \text{ rpm}^{\text{sup.}2} * \text{m}^{\text{sup.}2}$ to $180 * 10^{\text{sup.}6} \text{ rpm}^{\text{sup.}2} * \text{m}^{\text{sup.}2}$ inclusive.

18. The method of claim 17, wherein dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk and dimensioning the at least one of the first turbine blade and of the second turbine blade are such that the bore radius $R_{\text{sub.a}}$, the rim radius $R_{\text{sub.j}}$, the respective outer radius $R_{\text{sub.e}}$, the respective inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that:

$\kappa * N2S + \lambda_{\text{sub.2}} \leq \frac{R_a}{R_j}$ where: κ is $-0.0091 \text{ rpm}^{\text{sup.}-2} * \text{m}^{\text{sup.}-2}$; $\lambda_{\text{sub.2}}$ is 0.864; $R_{\text{sub.a}}$ and $R_{\text{sub.j}}$ are expressed in meters; and $N2S$ is expressed in $10^{\text{sup.}6} \text{ rpm}^{\text{sup.}2} * \text{m}^{\text{sup.}2}$.

19. The method of claim 11, wherein at least one of the upstream turbine disk and of the downstream turbine disk further has: an inner surface delimiting a circular bore passing through the at least one of the upstream turbine disk and of the downstream turbine disk and centered on the longitudinal axis, the inner surface having an upstream edge and a downstream edge; and a bore width $L_{\text{sub.a}}$ which is defined as an axial distance between the upstream edge and the downstream edge; wherein the method further comprises dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk and dimensioning at least one of the first turbine blade and of the second turbine blade such that the bore width $L_{\text{sub.a}}$, a respective inner radius $R_{\text{sub.i}}$ and the limit speed ω are such that: $\frac{100 * L_a}{R_i} \leq v * \frac{U_i^2}{1,000} + \zeta_{\text{sub.1}}$ with: $U_i = R_i * \omega$ where: ω is expressed in radians per second; v is $0.079 \text{ s}^{\text{sup.}2} * \text{m}^{\text{sup.}-2}$; $\zeta_{\text{sub.1}}$ is 2.28; $L_{\text{sub.a}}$ and $R_{\text{sub.i}}$ are expressed in meters; and $U_{\text{sub.i}}$ is expressed in meters per second; wherein a ratio $\frac{100 * L_a}{R_i}$ is strictly positive; wherein the bore width $L_{\text{sub.a}}$ is comprised in a range from 0.005 to 0.1 meters inclusive and $U_{\text{sub.i}}$ is comprised in a range from 100 to 500 $\text{m} * \text{s}^{\text{sup.}-1}$ inclusive.

20. The method of claim 19, wherein dimensioning the at least one of the upstream turbine disk and of the downstream turbine disk and dimensioning the at least one of the first turbine blade and of the second turbine blade are such that the bore width $L_{\text{sub.a}}$, the respective inner radius $R_{\text{sub.i}}$

and the limit speed ω are such that: $\frac{100 * L_a}{R_i} \leq v * \frac{U_i^2}{1,000} + \xi_2$ where: v is 0.079 s²*m⁻², ξ_2 is -1.41; L_a and R_i are expressed in meters; and U_i is expressed in meters per second.
