

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399700
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Satoh; Ryuta

Information processing apparatus, information processing method, and information processing system to enable update of a software

Abstract

The present disclosure relates to an information processing apparatus, an information processing method, an information processing system, and a program that enable update of an SW to be quickly and safely implemented. When the software program (SW) is updated, the SW is updated at a timing at which the SW does not operate in a plurality of processing units constituting the SW, so that the SW is updated without stopping the entire operation of the SW. The present disclosure can be applied to an automated driving technology.

Inventors:	Satoh; Ryuta (Tokyo, JP)
Applicant:	SONY GROUP CORPORATION (Tokyo, JP)
Family ID:	1000008777792
Assignee:	SONY GROUP CORPORATION (Tokyo, JP)
Appl. No.:	18/003268
Filed (or PCT Filed):	June 21, 2021
PCT No.:	PCT/JP2021/023309
PCT Pub. No.:	WO2022/004447
PCT Pub. Date:	January 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230315425 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2020-115428	Jul. 03, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: G06F8/65 (20180101); B60W60/00 (20200101); G06F8/656 (20180101); G06T7/70 (20170101)

U.S. Cl.:

CPC G06F8/65 (20130101); B60W60/001 (20200201); G06T7/70 (20170101);

Field of Classification Search

CPC: G06F (8/65); G06F (8/656); B60W (60/001); G06T (7/70); G06N (20/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11555704	12/2022	Servos	N/A	G01C 21/206
2017/0134164	12/2016	Haga	N/A	G06F 21/445
2018/0084137	12/2017	Miyazaki	N/A	H04N 23/80
2019/0184916	12/2018	Troia	N/A	H04W 4/44
2019/0283761	12/2018	Bielby	N/A	G06F 8/65
2019/0324458	12/2018	Sadeghi	N/A	G05D 1/0276
2020/0160748	12/2019	Hans	N/A	G09B 21/008
2021/0011711	12/2020	Ogawa	N/A	G06F 8/62
2021/0150264	12/2020	Karanam	N/A	G06N 3/045
2021/0215496	12/2020	Sese	N/A	G01C 21/3697
2021/0349709	12/2020	Nakatsukasa	N/A	G06F 8/656

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011-081604	12/2010	JP	N/A
2019152948	12/2018	JP	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion of PCT Application No. PCT/JP2021/023309, issued on Aug. 24, 2021, 11 pages of ISRWO. cited by applicant

Primary Examiner: Wu; Daxin

Attorney, Agent or Firm: CHIP LAW GROUP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Phase of International Patent Application No. PCT/JP2021/023309 filed on Jun. 21, 2021, which claims priority benefit of Japanese Patent

Application No. JP 2020-115428 filed in the Japan Patent Office on Jul. 3, 2020. Each of the above-referenced applications is hereby incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to an information processing apparatus, an information processing method, an information processing system, and a program, and more particularly, to an information processing apparatus, an information processing method, an information processing system, and a program capable of quickly and safely implementing update of a software program (SW).

BACKGROUND ART

(3) Various problems occur in a software program (SW) mounted on hardware as use progresses, but development is progressed so as to solve the generated problems, an update SW for updating to the developed SW is repeatedly distributed, and the SW is updated by the update SW, thereby improving convenience.

(4) However, in a case where the update by the update SW is not appropriately performed, the function by the SW cannot be exhibited, and for example, there is a possibility of causing a serious accident in an SW or the like related to automated driving in a vehicle or the like.

(5) Therefore, in a case where the update by the update SW cannot be appropriately ended, a technology for ensuring safety by making the function related to the update SW unusable has been proposed (see Patent Document 1).

(6) Furthermore, there has been proposed a technology for ensuring safety by adjusting a timing at which the update can be safely performed so that the update by the update SW can be appropriately ended (see Patent Document 2).

CITATION LIST

Patent Document

(7) Patent Document 1: Japanese Patent Application Laid-Open No. 2011-081604 Patent Document 2: Japanese Patent Application Laid-Open No. 2013-148957

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(8) However, in the technology of Patent Document 1, even if it is possible to recognize whether or not the update of the update SW has been appropriately ended, or even if the update SW can be appropriately ended, it is not possible to recognize a case where the operating state becomes inappropriate due to a defect caused by the update.

(9) For this reason, since it is not possible to recognize a defect caused by performing an appropriate update by the update SW, there is a possibility that safety cannot be sufficiently ensured.

(10) Furthermore, it is conceivable to distribute the update SW after sufficiently developing the update SW until such a defect does not occur at all. However, in this case, it takes time to develop the update SW, the distribution of the update SW is delayed, and even if there is a defect in the SW before the update, improvement by the update cannot be implemented, and there is a possibility that the SW before the update has to be continuously used in a low safety state.

(11) Furthermore, in the technology of Patent Document 2, as the timing for safely implementing the update by the update SW, for example, in the case of an SW of a vehicle or the like, the timing at which the vehicle stops is searched and set as the update timing. However, in a vehicle or the like having a relatively high use frequency, which is used by car sharing, a carrier, or the like, since the frequency of the stop state is low, it is difficult to implement the update since the timing at which the SW can be safely updated is extremely little. Even if there is a defect in the SW before the update due to a delay in the update of the SW, it is difficult to implement the improvement by the update, and there is a possibility that the SW before the update has to be continuously used in a low safety state.

(12) The present disclosure has been made in view of such a situation, and in particular, enables

update by the update SW to be quickly and safely implemented.

Solutions to Problems

(13) An information processing apparatus, an information processing system, and a program according to one aspect of the present disclosure are an information processing apparatus, an information processing system, and a program including an update section that updates a software program (SW) of a moving apparatus for each processing unit constituting the SW.

(14) An information processing method according to one aspect of the present disclosure is an information processing method including a step of updating a software program (SW) of a moving apparatus for each processing unit constituting the SW.

(15) In one aspect of the present disclosure, a software program (SW) of a moving apparatus is updated for each processing unit constituting the SW.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating an overview of the present disclosure.

(2) FIG. 2 is a block diagram illustrating a configuration example of an SW management system of the present disclosure.

(3) FIG. 3 is a block diagram illustrating a configuration example of a vehicle control system.

(4) FIG. 4 is a diagram illustrating an example of sensing areas.

(5) FIG. 5 is a block diagram illustrating a configuration example of a server.

(6) FIG. 6 is a functional block diagram illustrating functions implemented by the vehicle control system of FIG. 3.

(7) FIG. 7 is a functional block diagram illustrating functions implemented by the server of FIG. 5.

(8) FIG. 8 is a diagram illustrating grouping of vehicles.

(9) FIG. 9 is a flowchart illustrating grouping processing.

(10) FIG. 10 is a flowchart illustrating relearning processing.

(11) FIG. 11 is a flowchart illustrating update processing.

(12) FIG. 12 is a flowchart illustrating update timing setting processing (part 1).

(13) FIG. 13 is a flowchart illustrating update timing setting processing (part 2).

(14) FIG. 14 is a diagram illustrating update processing using a component as a processing unit.

(15) FIG. 15 is a diagram illustrating update processing using a frame as a processing unit.

(16) FIG. 16 is a diagram illustrating update processing using a block as a processing unit.

(17) FIG. 17 is a diagram illustrating update processing using a layer as a processing unit.

(18) FIG. 18 is a flowchart illustrating update processing for each processing unit.

(19) FIG. 19 is a flowchart illustrating processing unit setting processing.

(20) FIG. 20 is a diagram illustrating a configuration example of a general-purpose computer.

MODE FOR CARRYING OUT THE INVENTION

(21) Hereinafter, preferred embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. Note that, in the present specification and the drawings, components having substantially the same functional configuration are denoted by the same reference numerals, and redundant description is omitted.

(22) Hereinafter, modes for carrying out the present technology will be described. The description will be given in the following order. 1. Overview of Present Disclosure 2. Configuration Example of Software (SW) Management System of Present Disclosure 3. Configuration Example of Vehicle Control System 4. Configuration Example of Server 5. Functions Implemented by Vehicle Control System of FIG. 3 6. Functions Implemented by Server of FIG. 4 7. Grouping of Vehicles 8. Grouping Processing 9. Relearning Processing 10. Update Processing 11. Update Timing Setting Processing (Part 1) 12. Update Timing Setting Processing (Part 2) 13. Update for Each Processing

1. Overview of Present Disclosure

(23) The present disclosure enables a software program (SW) to be updated quickly and safely.

(24) Note that, in the present specification, a case will be described as an example in which the SW is a recognition section that implements object recognition processing of recognizing an object present in the periphery on the basis of an image obtained by capturing the periphery of a vehicle capable of automated driving in order to implement automated driving. However, the SW applied to the present disclosure is not limited to the recognition section that implements the object recognition processing, and is only required to be an updatable SW.

(25) Furthermore, the recognition section that implements the object recognition processing as the SW applied to the present disclosure is configured by machine learning.

(26) It is known that an SW including a recognition section generated by machine learning can improve recognition accuracy by repeating further machine learning (relearning) with learning data collected for learning.

(27) For this reason, for the SW such as the recognition section, while executing the object recognition processing, information of an image and a recognition result associated with the execution is collected as learning data, and the recognition accuracy is continuously improved by relearning using the collected learning data.

(28) Therefore, in the following description, an SW management system that manages an SW as a recognition section mounted on a vehicle will be described as an example.

(29) The SW management system in FIG. 1 includes vehicles M1 to Mn each including an SW as a recognition section, and a server Sv for managing the SW.

(30) Each of the vehicles M1 to Mn includes cameras C1 to Cn and recognition sections R1 to Rn.

(31) Note that the vehicles M1 to Mn, the cameras C1 to Cn, and the recognition sections R1 to Rn are distinguished from each other by n as an identifier. However, the vehicles M1 to Mn, the cameras C1 to Cn, and the recognition sections R1 to Rn have basically the same configuration. Hereinafter, the vehicles M1 to Mn, the cameras C1 to Cn, and the recognition sections R1 to Rn are also simply referred to as the vehicle M, the camera C, and the recognition section R in a case where it is not particularly necessary to distinguish the vehicles M1 to Mn, the cameras C1 to Cn, and the recognition sections R1 to Rn.

(32) The camera C captures an image of the surroundings of the vehicle M required for implementing the automated driving of the vehicle M.

(33) The recognition section R executes object recognition processing on the basis of the image captured by the camera C, and recognizes an object present around the vehicle M.

(34) The vehicle M implements automated driving on the basis of the recognition result of the recognition section R.

(35) Furthermore, the vehicles M1 to Mn transmits vehicle accumulation information U1 to Un obtained by combining the images captured by the cameras C1 to Cn and the recognition results of the object recognition processing implemented by the recognition sections R1 to Rn to the server Sv via the network N.

(36) The server Sv accumulates, as a parameter P, the vehicle accumulation information U1 to Un obtained by combining the images captured by the cameras C1 to Cn and the recognition results of the recognition sections R1 to Rn transmitted from the vehicles M1 to Mn via the network N.

(37) Furthermore, the server Sv includes a relearning section L of the recognition section R.

(38) The relearning section L relearns the recognition section R by using the parameter P including the vehicle accumulation information U1 to Un as data for learning, generates an update SW for causing the current recognition section R to be updated to a relearned recognition section R, distributes the update SW to the vehicles M1 to Mn as distribution information D1 to Dn via the network N, and updates each of the recognition sections R1 to Rn.

(39) Here, there is a case where the recognition section R is not appropriately updated by the

update SW, and inappropriate object recognition processing is performed, and thus, there is a possibility that automated driving cannot be appropriately implemented.

(40) For this reason, the update SW for updating the recognition section R needs to be distributed after safety is confirmed by sufficient simulation.

(41) However, in order to generate the update SW such that the update processing for the recognition section R is in a complete state, the cost for the safety confirmation, in particular, the time required for the safety confirmation is enormous, and there is a possibility that the distribution of the update SW is delayed and the update of the recognition section R is delayed.

(42) Therefore, in the present disclosure, among the vehicles M1 to Mn, the update SW is first distributed to a vehicle M group with less danger in which safety is ensured even in a case where an appropriate operation cannot be implemented by updating the recognition section R by the update SW, to update the recognition section R, the operating state after the update is confirmed, and the update SW is distributed to other vehicles M in a case where it is confirmed that there is no defect with sufficient operation.

(43) More specifically, for example, in a case where the recognition section R is configured to recognize a pedestrian among objects, a recognition section Rm of a vehicle Mm traveling on a highway H among the vehicles M1 to Mn is updated by the update SW prior to the other vehicles M.

(44) That is, since it is unlikely that the vehicle Mm traveling on the highway H recognizes a pedestrian during traveling and requires an operation to avoid contact, even if the vehicle Mm cannot appropriately recognize a pedestrian due to the update of the recognition section Rm, a fatal problem is unlikely to occur.

(45) Furthermore, since there is a possibility that even the vehicle Mm traveling on the highway H recognizes a pedestrian present around the highway, it is possible to confirm whether or not the recognition section Rm after the update is properly operating.

(46) Therefore, in the present disclosure, the recognition section Rm of the vehicle Mm traveling on the highway H is updated by the update SW prior to the other vehicles M, and the recognition accuracy of pedestrians after the update is confirmed.

(47) Then, if there is no defect in the object recognition processing of the recognition section Rm of the vehicle Mm, the update SW is also distributed to the recognition sections R of the vehicles M other than the vehicle Mm traveling on the highway, and the update is performed.

(48) Furthermore, if there is a defect in the object recognition processing by the recognition section Rm updated by the update SW, the update by the update SW of the recognition sections R of the other vehicles M is stopped, and the processing of causing the relearning section L to relearn the update SW is repeated.

(49) As a result, it is possible to confirm the presence or absence of the defect by updating the recognition section R of the vehicle 1 in which safety is ensured by the update SW while suppressing the cost for reducing the occurrence of the defect related to the object recognition processing of the recognition section R updated by the update SW generated by the relearning of the recognition section R.

(50) Furthermore, since it is possible to suppress the time related to relearning for improving the perfection of the update SW, it is possible to quickly implement the distribution of the update SW.

(51) Moreover, even if there is a defect in the object recognition processing of the recognition section R updated by the update SW, the defect related to the object recognition processing by the updated recognition section R is confirmed in a vehicle Mm in which safety is ensured, and the distribution of the update SW is stopped. Therefore, recognition sections R of vehicles M in which safety is not ensured other than the vehicle Mm are not updated by the defective update SW, so that the safety related to the update by the update SW can be improved.

(52) As a result, it is possible to quickly and safely implement the update of the recognition section R of the vehicle M by the update SW.

2. Configuration Example of SW Management System of Present Disclosure

(53) Next, a configuration example of the SW management system of the present disclosure will be described with reference to FIG. 2.

(54) The SW management system **10** of the present disclosure includes vehicles **1-1** to **1-n**, a server **2**, and a network **3**. Note that, in a case where there is no particular need to distinguish the vehicles **1-1** to **1-n**, the vehicles **1-1** to **1-n** are simply referred to as a vehicle **1**, and other configurations are similarly referred to.

(55) The vehicles **1-1** to **1-n** have configurations corresponding to the vehicles **M1** to **Mn** in FIG. 1, and are vehicles capable of automated driving.

(56) The vehicles **1-1** to **1-n** include cameras **1a-1** to **1a-n** that capture images of the surroundings, and recognition sections **1b-1** to **1b-n** that recognize objects present in the surroundings on the basis of the images captured by the cameras **1a-1** to **1a-n**, and automated driving is implemented on the basis of the recognition results of the recognition sections **1b-1** to **1b-n**.

(57) Furthermore, each of the recognition sections **1b-1** to **1b-n** mounted on each of the vehicles **1-1** to **1-n** is a software program (SW), and the update is repeated by the update SW distributed from the server **2**.

(58) Note that the cameras **1a-1** to **1a-n** may not have the same structure, but the recognition sections **1b-1** to **1b-n** are the same since the update is repeated by the update SW distributed from the server **2**.

(59) Moreover, the vehicles **1-1** to **1-n** accumulates information obtained by combining the images captured by the cameras **1a-1** to **1a-n** and the recognition results of the recognition sections **1b-1** to **1b-n** as vehicle accumulation information, and transmit the accumulated information to the server **2** via the network **3**.

(60) The server **2** causes the recognition section **1b** to relearn by using the vehicle accumulation information transmitted from each of the vehicles **1-1** to **1-n** via the network **3** as learning data.

(61) Then, the server **2** generates the relearned recognition section **1b** as the update SW, distributes the update SW to the vehicles **1-1** to **1-n** via the network **3**, and updates each of the recognition sections **1b-1** to **1b-n**.

(62) When the update SW is distributed to update the recognition sections **1b-1** to **1b-n**, the server **2** distributes and updates the update SW from a vehicle **1** (group) having a small influence even if a defect occurs in the operating state due to the update of the recognition section **1b** among the vehicles **1-1** to **1-n**.

(63) Then, the server **2** confirms the operating state of the recognition section **1b** updated by the update SW, and when there is no defect in the operating state, the server **2** distributes the update SW to the other vehicles **1** and causes the other vehicles **1** to update.

(64) With this operation, when the recognition section **1b** is updated by the update SW, if the update cannot be appropriately completed, or if a defect occurs in which the recognition accuracy becomes lower than that of the recognition section **1b** before the update even if the update is appropriately performed, the update can be performed after the defect is improved by relearning.

(65) Furthermore, for the vehicle **1** (group) to which the SW is distributed first, even if there is a defect in the operating state of the recognition section **1b** updated by the update SW, only the recognition section **1b** of the vehicle **1** in which safety is ensured is updated, so that occurrence of a fatal problem can be suppressed.

(66) Moreover, by first confirming the operating state of the recognition section **1b** in the vehicle **1** in which the update SW has been updated, it is possible to confirm the presence or absence of a defect related to the update and then distribute the SW to other vehicles **1**, so that distribution to a vehicle **1** having a large influence in a case where a defect occurs in the recognition section **1b** updated by the update SW can be distributed after sufficient safety is ensured.

(67) As a result, even if the update SW is distributed to the vehicle **1** without being developed to a state where complete safety can be ensured, a serious problem does not occur. Therefore, at the

stage of a certain degree of completion, the update SW can be distributed to the vehicle **1** where safety is ensured, the recognition section **1b** can be updated, and the presence or absence of a defect can be confirmed. Therefore, it is possible to implement quick distribution of the update SW.

(68) Furthermore, since the SW can be distributed to the other vehicles **1** in a state in which the safety of the update SW is ensured to some extent, the update of the recognition section **1b** by the update SW can be safely implemented.

3. Configuration Example of Vehicle Control System

(69) FIG. **3** is a block diagram illustrating a configuration example of a vehicle control system **11** which is an example of a moving apparatus control system of the vehicle **1** to which the present technology is applied.

(70) The vehicle control system **11** is provided in the vehicle **1** and performs processing related to travel assistance and automated driving of the vehicle **1**.

(71) The vehicle control system **11** includes a processor **21**, a communication section **22**, a map information accumulation section **23**, a global navigation satellite system (GNSS) reception section **24**, an external recognition sensor **25**, an in-vehicle sensor **26**, a vehicle sensor **27**, a recording section **28**, a travel assistance/automated driving control section **29**, a driver monitoring system (DMS) **30**, a human machine interface (HMI) **31**, and a vehicle control section **32**.

(72) The processor **21**, the communication section **22**, the map information accumulation section **23**, the GNSS reception section **24**, the external recognition sensor **25**, the in-vehicle sensor **26**, the vehicle sensor **27**, the recording section **28**, the travel assistance/automated driving control section **29**, the driver monitoring system (DMS) **30**, the human machine interface (HMI) **31**, and the vehicle control section **32** are connected to one another via a communication network **41**. The communication network **41** includes, for example, an in-vehicle communication network, a bus, or the like conforming to an arbitrary standard such as a controller area network (CAN), a local interconnect network (LIN), a local area network (LAN), FlexRay (registered trademark), Ethernet (registered trademark), or the like. Note that each section of the vehicle control system **11** may be directly connected by, for example, near field communication (NFC), Bluetooth (registered trademark), or the like without passing through the communication network **41**.

(73) Note that, hereinafter, in a case where each section of the vehicle control system **11** performs communication via the communication network **41**, description of the communication network **41** will be omitted. For example, in a case where the processor **21** and the communication section **22** perform communication via the communication network **41**, it is simply described that the processor **21** and the communication section **22** perform communication.

(74) The processor **21** includes various processors such as a central processing unit (CPU), a micro processing unit (MPU), an electronic control unit (ECU), or the like, for example. The processor **21** controls the entire vehicle control system **11**.

(75) The communication section **22** communicates with various devices inside and outside the vehicle, other vehicles, servers, base stations, and the like, and transmits and receives various data. As the communication with the outside of the vehicle, for example, the communication section **22** receives a program for updating software for controlling the operation of the vehicle control system **11**, map information, traffic information, information around the vehicle **1**, and the like from the outside. For example, the communication section **22** transmits information regarding the vehicle **1** (for example, data indicating the state of the vehicle **1**, a recognition result by the recognition section **73**, and the like), information around the vehicle **1**, and the like to the outside. For example, the communication section **22** performs communication corresponding to a vehicle emergency call system such as an eCall or the like.

(76) Note that a communication method of the communication section **22** is not particularly limited. Furthermore, a plurality of communication methods may be used.

(77) As communication with the inside of the vehicle, for example, the communication section **22** performs wireless communication with a device in the vehicle by a communication method such as

wireless LAN, Bluetooth, NFC, wireless USB (WUSB), or the like. For example, the communication section **22** performs wired communication with a device in the vehicle by a communication method such as a universal serial bus (USB), a high-definition multimedia interface (HDMI, registered trademark), a mobile high-definition link (MHL), or the like via a connection terminal (and, if necessary, a cable) not illustrated.

(78) Here, the in-vehicle device is, for example, a device that is not connected to the communication network **41** in the vehicle. For example, a mobile device or a wearable device carried by an occupant such as a driver or the like, an information device brought into the vehicle and temporarily installed, or the like is assumed.

(79) For example, the communication section **22** communicates with a server or the like present on an external network (for example, the Internet, a cloud network, or a company-specific network) via a base station or an access point by a wireless communication method such as fourth generation mobile communication system (4G), fifth generation mobile communication system (5G), long term evolution (LTE), dedicated short range communications (DSRC), or the like.

(80) For example, the communication section **22** communicates with a terminal (for example, a terminal of a pedestrian or a store, or a machine type communication (MTC) terminal) present in the vicinity of the host vehicle using a peer to peer (P2P) technology. For example, the communication section **22** performs V2X communication. The V2X communication is, for example, vehicle to vehicle communication with another vehicle, vehicle to infrastructure communication with a roadside device or the like, vehicle to home communication, vehicle to pedestrian communication with a terminal or the like possessed by a pedestrian, or the like.

(81) For example, the communication section **22** receives an electromagnetic wave transmitted by a road traffic information communication system (vehicle information and communication system (VICS), registered trademark) such as a radio wave beacon, an optical beacon, FM multiplex broadcasting, or the like.

(82) The map information accumulation section **23** accumulates a map acquired from the outside and a map created by the vehicle **1**. For example, the map information accumulation section **23** accumulates a three-dimensional high-precision map, a global map having lower accuracy than the highly accurate map but covering a wide area, and the like.

(83) The high-precision map is, for example, a dynamic map, a point cloud map, a vector map (also referred to as an advanced driver assistance system (ADAS) map), or the like. The dynamic map is, for example, a map including four layers of dynamic information, semi-dynamic information, semi-static information, and static information, and is provided from an external server or the like. The point cloud map is a map including point clouds (point cloud data). The vector map is a map in which information such as a lane, a position of a signal, and the like is associated with the point cloud map. The point cloud map and the vector map may be provided from, for example, an external server or the like, or may be created by the vehicle **1** as a map for performing matching with a local map to be described later on the basis of a sensing result by a radar **52**, a LiDAR **53**, or the like, and may be accumulated in the map information accumulation section **23**. Furthermore, in a case where a high-precision map is provided from an external server or the like, for example, map data of several hundred meters square regarding a planned route on which the vehicle **1** travels from now is acquired from the server or the like in order to reduce the communication capacity.

(84) The GNSS reception section **24** receives a GNSS signal from a GNSS satellite, and supplies the GNSS signal to the travel assistance/automated driving control section **29**.

(85) The external recognition sensor **25** includes various sensors used for recognizing a situation outside the vehicle **1**, and supplies sensor data from each sensor to each section of the vehicle control system **11**. The type and number of sensors included in the external recognition sensor **25** are arbitrary.

(86) For example, the external recognition sensor **25** includes a camera **51**, a radar **52**, a light detection and ranging or laser imaging detection and ranging (LiDAR) **53**, and an ultrasonic sensor

54. The number of the cameras **51**, the radars **52**, the LiDARs **53**, and the ultrasonic sensors **54** is arbitrary, and an example of a sensing area of each sensor will be described later.

(87) Note that, as the camera **51**, for example, a camera of an arbitrary imaging method such as a time of flight (ToF) camera, a stereo camera, a monocular camera, an infrared camera, or the like is used as necessary.

(88) Furthermore, for example, the external recognition sensor **25** includes an environment sensor for detecting weather, climate, brightness, and the like. The environment sensor includes, for example, a raindrop sensor, a fog sensor, a sunshine sensor, a snow sensor, an illuminance sensor, and the like.

(89) Moreover, for example, the external recognition sensor **25** includes a microphone used for detecting a sound around the vehicle **1**, a position of a sound source, and the like.

(90) The in-vehicle sensor **26** includes various sensors for detecting information inside the vehicle, and supplies sensor data from each sensor to each section of the vehicle control system **11**. The type and number of sensors included in the in-vehicle sensor **26** are arbitrary.

(91) For example, the in-vehicle sensor **26** includes a camera, a radar, a seating sensor, a steering wheel sensor, a microphone, a biometric sensor, and the like. As the camera, for example, a camera of any imaging method such as a ToF camera, a stereo camera, a monocular camera, an infrared camera, or the like can be used. The biometric sensor is provided, for example, on a seat, a steering wheel, or the like, and detects various types of biometric information of an occupant such as a driver and the like.

(92) The vehicle sensor **27** includes various sensors for detecting the state of the vehicle **1**, and supplies sensor data from each sensor to each section of the vehicle control system **11**. The type and number of sensors included in the vehicle sensor **27** are arbitrary.

(93) For example, the vehicle sensor **27** includes a speed sensor, an acceleration sensor, an angular velocity sensor (gyro sensor), and an inertial measurement unit (IMU). For example, the vehicle sensor **27** includes a steering angle sensor that detects a steering angle of a steering wheel, a yaw rate sensor, an accelerator sensor that detects an operation amount of an accelerator pedal, and a brake sensor that detects an operation amount of a brake pedal. For example, the vehicle sensor **27** includes a rotation sensor that detects the number of rotations of the engine or the motor, an air pressure sensor that detects the air pressure of the tire, a slip rate sensor that detects the slip rate of the tire, and a wheel speed sensor that detects the rotation speed of the wheel. For example, the vehicle sensor **27** includes a battery sensor that detects the remaining amount and temperature of the battery, and an impact sensor that detects an external impact.

(94) The recording section **28** includes, for example, a read only memory (ROM), a random access memory (RAM), a magnetic storage device such as a hard disc drive (HDD) or the like, a semiconductor storage device, an optical storage device, a magneto-optical storage device, and the like. The recording section **28** records various programs, data, and the like used by each section of the vehicle control system **11**. For example, the recording section **28** records a rosbag file including a message transmitted and received by a robot operating system (ROS) in which an application program related to automated driving operates. For example, the recording section **28** includes an event data recorder (EDR) and a data storage system for automated driving (DSSAD), and records information of the vehicle **1** before and after an event such as an accident or the like.

(95) The travel assistance/automated driving control section **29** controls travel assistance and automated driving of the vehicle **1**. For example, the travel assistance/automated driving control section **29** includes an analysis section **61**, an action planning section **62**, and an operation control section **63**.

(96) The analysis section **61** performs analysis processing of the situation of the vehicle **1** and the surroundings. The analysis section **61** includes a self-position estimation section **71**, a sensor fusion section **72**, and a recognition section **73**.

(97) The self-position estimation section **71** estimates the self-position of the vehicle **1** on the basis

of the sensor data from the external recognition sensor **25** and the high-precision map accumulated in the map information accumulation section **23**. For example, the self-position estimation section **71** generates a local map on the basis of sensor data from the external recognition sensor **25**, and estimates the self-position of the vehicle **1** by matching the local map with the high-precision map. The position of the vehicle **1** is based on, for example, the center of the rear wheel pair axle.

(98) The local map is, for example, a three-dimensional high-precision map created using a technology such as simultaneous localization and mapping (SLAM), or the like, an occupancy grid map, or the like. The three-dimensional high-precision map is, for example, the above-described point cloud map or the like. The occupancy grid map is a map in which a three-dimensional or two-dimensional space around the vehicle **1** is divided into grids of a predetermined size, and an occupancy state of an object is indicated in units of grids. The occupancy state of the object is indicated by, for example, the presence or absence or existence probability of the object. The local map is also used for detection processing and recognition processing of a situation outside the vehicle **1** by the recognition section **73**, for example.

(99) Note that the self-position estimation section **71** may estimate the self-position of the vehicle **1** on the basis of the GNSS signal and the sensor data from the vehicle sensor **27**.

(100) The sensor fusion section **72** performs sensor fusion processing of combining a plurality of different types of sensor data (for example, image data supplied from the camera **51** and sensor data supplied from the radar **52**) to obtain new information. Methods for combining different types of sensor data include integration, fusion, association, and the like.

(101) The recognition section **73** performs detection processing and recognition processing of a situation outside the vehicle **1**.

(102) For example, the recognition section **73** performs detection processing and recognition processing of a situation outside the vehicle **1** on the basis of information from the external recognition sensor **25**, information from the self-position estimation section **71**, information from the sensor fusion section **72**, and the like.

(103) Specifically, for example, the recognition section **73** performs detection processing, recognition processing, and the like of an object around the vehicle **1**. The object detection processing is, for example, processing of detecting the presence or absence, size, shape, position, movement, and the like of an object. The object recognition processing is, for example, processing of recognizing an attribute such as a type of an object or the like or identifying a specific object. However, the detection processing and the recognition processing are not necessarily clearly divided, and may overlap.

(104) For example, the recognition section **73** detects an object around the vehicle **1** by performing clustering for classifying point clouds based on sensor data such as LiDAR, radar, or the like for each cluster of point clouds. As a result, the presence or absence, size, shape, and position of an object around the vehicle **1** are detected.

(105) For example, the recognition section **73** detects the motion of the object around the vehicle **1** by performing tracking that follows the motion of the cluster of the point cloud classified by clustering. As a result, the speed and the traveling direction (movement vector) of the object around the vehicle **1** are detected.

(106) For example, the recognition section **73** recognizes the type of the object around the vehicle **1** by performing object recognition processing such as semantic segmentation or the like on the image data supplied from the camera **51**.

(107) Note that, as the object to be detected or recognized, for example, a vehicle, a person, a bicycle, an obstacle, a structure, a road, a traffic light, a traffic sign, a road sign, and the like are assumed.

(108) For example, the recognition section **73** performs recognition processing of traffic rules around the vehicle **1** on the basis of the map accumulated in the map information accumulation section **23**, the estimation result of the self-position, and the recognition result of the object around

the vehicle **1**. By this processing, for example, the position and the state of the signal, the contents of the traffic sign and the road sign, the contents of the traffic regulation, the travelable lane, and the like are recognized.

(109) For example, the recognition section **73** performs recognition processing of the environment around the vehicle **1**. As the surrounding environment to be recognized, for example, weather, temperature, humidity, brightness, a state of a road surface, and the like are assumed.

(110) The action planning section **62** creates an action plan of the vehicle **1**. For example, the action planning section **62** creates an action plan by performing processing of route planning and route following.

(111) Note that the route planning (global path planning) is a process of planning a rough route from the start to the goal. This route planning is called a track planning, and includes processing of track generation (local path planning) that enables safe and smooth traveling in the vicinity of the vehicle **1** in consideration of the motion characteristics of the vehicle **1** in the route planned by the route planning.

(112) Route following is a process of planning an operation for safely and accurately traveling a route planned by route planning within a planned time. For example, the target speed and the target angular velocity of the vehicle **1** are calculated.

(113) The operation control section **63** controls the operation of the vehicle **1** in order to implement the action plan created by the action planning section **62**.

(114) For example, the operation control section **63** controls a steering control section **81**, a brake control section **82**, and a drive control section **83** to perform acceleration/deceleration control and direction control such that the vehicle **1** travels on the track calculated by the track planning. For example, the operation control section **63** performs cooperative control for the purpose of implementing the functions of the ADAS such as collision avoidance or impact mitigation, follow-up traveling, vehicle speed maintaining traveling, collision warning of the host vehicle, lane deviation warning of the host vehicle, and the like. For example, the operation control section **63** performs cooperative control for the purpose of automated driving or the like in which the vehicle automatically travels without depending on the operation of the driver.

(115) The DMS **30** performs a driver authentication processing, a driver state recognition processing, and the like on the basis of sensor data from the in-vehicle sensor **26**, input data input to the HMI **31**, and the like. As the state of the driver to be recognized, for example, a physical condition, a wakefulness level, a concentration level, a fatigue level, a line-of-sight direction, a drunkenness level, a driving operation, a posture, and the like are assumed.

(116) Note that the DMS **30** may perform authentication processing of an occupant other than the driver and recognition processing of the state of the occupant. Furthermore, for example, the DMS **30** may perform recognition processing of the situation inside the vehicle on the basis of sensor data from the in-vehicle sensor **26**. As the situation inside the vehicle to be recognized, for example, temperature, humidity, brightness, odor, and the like are assumed.

(117) The HMI **31** is used for inputting various data, instructions, and the like, generates a signal input on the basis of the input data, instructions, and the like, and supplies the input signal to each section of the vehicle control system **11**. For example, the HMI **31** includes an operation device such as a touch panel, a button, a microphone, a switch, a lever, and the like, an operation device that can input by a method other than manual operation such as voice, gesture, or the like, and the like. Note that the HMI **31** may be, for example, a remote control device using infrared rays or other radio waves, or an external connection device such as a mobile device, a wearable device, or the like compatible with the operation of the vehicle control system **11**.

(118) Furthermore, the HMI **31** performs output control to control generation and output of visual information, auditory information, and tactile information on the occupant or the outside of the vehicle, output content, output timing, an output method, and the like. The visual information is, for example, information indicated by an image or light such as an operation screen, a state display

of the vehicle **1**, a warning display, a monitor image indicating a situation around the vehicle **1**, or the like. The auditory information is, for example, information indicated by sound such as guidance, a warning sound, a warning message, or the like. The tactile information is, for example, information given to the tactile sense of the occupant by force, vibration, motion, or the like.

(119) As a device that outputs visual information, for example, a display device, a projector, a navigation device, an instrument panel, a camera monitoring system (CMS), an electronic mirror, a lamp, and the like are assumed. The display device may be, for example, a device that displays visual information in the field of view of the occupant, such as a head-up display, a transmissive display, a wearable device having an augmented reality (AR) function, or the like, in addition to a device having a normal display.

(120) As a device that outputs auditory information, for example, an audio speaker, a headphone, an earphone, or the like is assumed.

(121) As a device that outputs tactile information, for example, a haptics element using haptics technology or the like is assumed. The haptics element is provided, for example, on a steering wheel, a seat, or the like.

(122) The vehicle control section **32** controls each section of the vehicle **1**. The vehicle control section **32** includes a steering control section **81**, a brake control section **82**, a drive control section **83**, a body system control section **84**, a light control section **85**, and a horn control section **86**.

(123) The steering control section **81** detects and controls the state of the steering system of the vehicle **1** or the like. The steering system includes, for example, a steering mechanism including a steering wheel and the like, an electric power steering, and the like. The steering control section **81** includes, for example, a control unit such as an ECU or the like that controls the steering system, an actuator that drives the steering system, and the like.

(124) The brake control section **82** detects and controls the state of the brake system of the vehicle **1** or the like. The brake system includes, for example, a brake mechanism including a brake pedal, an antilock brake system (ABS), and the like. The brake control section **82** includes, for example, a control unit such as an ECU or the like that controls a brake system, an actuator that drives the brake system, and the like.

(125) The drive control section **83** detects and controls the state of the drive system of the vehicle **1** or the like. The drive system includes, for example, a driving force generation device for generating a driving force such as an accelerator pedal, an internal combustion engine, a driving motor, or the like, a driving force transmission mechanism for transmitting the driving force to wheels, and the like. The drive control section **83** includes, for example, a control unit such as an ECU or the like that controls the drive system, an actuator that drives the drive system, and the like.

(126) The body system control section **84** detects and controls the state of the body system of the vehicle **1** or the like. The body system includes, for example, a keyless entry system, a smart key system, a power window device, a power seat, an air conditioner, an airbag, a seat belt, a shift lever, and the like. The body system control section **84** includes, for example, a control unit such as an ECU or the like that controls the body system, an actuator that drives the body system, and the like.

(127) The light control section **85** detects and controls states of various lights of the vehicle **1** or the like. As the light to be controlled, for example, a headlight, a backlight, a fog light, a turn signal, a brake light, a projection, a display of a bumper, and the like are assumed. The light control section **85** includes a control unit such as an ECU or the like that controls light, an actuator that drives light, and the like.

(128) The horn control section **86** detects and controls the state of the car horn of the vehicle **1** or the like. The horn control section **86** includes, for example, a control unit such as an ECU or the like that controls the car horn, an actuator that drives the car horn, and the like.

(129) FIG. **4** is a diagram illustrating an example of sensing areas by the camera **51**, the radar **52**, the LiDAR **53**, and the ultrasonic sensor **54** of the external recognition sensor **25** in FIG. **3**.

(130) The sensing area **101F** and the sensing area **101B** illustrate examples of sensing areas of the

ultrasonic sensor **54**. The sensing area **101F** covers the periphery of the front end of the vehicle **1**.

The sensing area **101B** covers the periphery of the rear end of the vehicle **1**.

(131) The sensing results in the sensing area **101F** and the sensing area **101B** are used, for example, for parking assistance of the vehicle **1** or the like.

(132) The sensing areas **102F** to **102B** illustrate examples of sensing areas of the radar **52** for a short distance or a middle distance. The sensing area **102F** covers a position farther than the sensing area **101F** in front of the vehicle **1**. The sensing area **102B** covers a position farther than the sensing area **101B** behind the vehicle **1**. The sensing area **102L** covers the rear periphery of the left side surface of the vehicle **1**. The sensing area **102R** covers the rear periphery of the right side surface of the vehicle **1**.

(133) The sensing result in the sensing area **102F** is used, for example, to detect a vehicle, a pedestrian, or the like present in front of the vehicle **1**. The sensing result in the sensing area **102B** is used, for example, for a collision prevention function or the like behind the vehicle **1**. The sensing results in the sensing area **102L** and the sensing area **102R** are used, for example, for detecting an object in a blind spot on the sides of the vehicle **1** or the like.

(134) The sensing areas **103F** to **103B** illustrate examples of sensing areas by the camera **51**. The sensing area **103F** covers a position farther than the sensing area **102F** in front of the vehicle **1**. The sensing area **103B** covers a position farther than the sensing area **102B** behind the vehicle **1**. The sensing area **103L** covers the periphery of the left side surface of the vehicle **1**. The sensing area **103R** covers the periphery of the right side surface of the vehicle **1**.

(135) The sensing result in the sensing area **103F** is used for, for example, recognition of a traffic light or a traffic sign, a lane departure prevention assist system, and the like. The sensing result in the sensing area **103B** is used for, for example, parking assistance, a surround view system, and the like. The sensing results in the sensing area **103L** and the sensing area **103R** are used, for example, in a surround view system or the like.

(136) The sensing area **104** illustrates an example of a sensing area of the LiDAR **53**. The sensing area **104** covers a position farther than the sensing area **103F** in front of the vehicle **1**. Meanwhile, the sensing area **104** has a narrower range in the left-right direction than the sensing area **103F**.

(137) The sensing result in the sensing area **104** is used for, for example, emergency braking, collision avoidance, pedestrian detection, and the like.

(138) The sensing area **105** illustrates an example of a sensing area of the long-range radar **52**. The sensing area **105** covers a position farther than the sensing area **104** in front of the vehicle **1**. Meanwhile, the sensing area **105** has a narrower range in the left-right direction than the sensing area **104**.

(139) The sensing result in the sensing area **105** is used for, for example, adaptive cruise control (ACC) or the like.

(140) Note that the sensing area of each sensor may have various configurations other than those in FIG. 4. Specifically, the ultrasonic sensor **54** may also sense the sides of the vehicle **1**, or the LiDAR **53** may sense the rear of the vehicle **1**.

(141) Note that the camera **51** and the recognition section **73** in FIG. 3 have configurations corresponding to the camera **1a** and the recognition section **1b** in FIG. 2.

4. Configuration Example of Server

(142) Next, a configuration example of the server **2** will be described with reference to FIG. 5.

(143) The server **2** includes a processor **111**, an input section **112**, an output section **113**, a storage section **114**, a communication section **115**, a drive **116**, and a removable storage medium **117**, and is connected to each other via a bus **118**, and can transmit and receive data and programs.

(144) The processor **111** controls the entire operation of the server **2**. Furthermore, the processor **111** manages update of the recognition section **73** as the SW. Moreover, the processor **111** recognizes the operation state of the recognition section **73** as the SW and transmits the operation state to the server **2**.

(145) The input section **112** includes an input device such as a keyboard, a mouse, and the like with which the user inputs an operation command, and supplies various input signals to the processor **111**.

(146) The output section **113** is controlled by the processor **111**, and outputs an image of a supplied operation screen and a processing result to a display device including a liquid crystal display (LCD), an organic electro luminescence (EL), or the like to display.

(147) The storage section **114** includes a hard disk drive (HDD), a solid state drive (SSD), a semiconductor memory, or the like, is controlled by the processor **111**, and writes or reads various data and programs including content data.

(148) The communication section **115** is controlled by the processor **111**, and transmits and receives various data and programs to and from various devices via a communication network represented by a local area network (LAN) or the like in a wired (or wireless (not illustrated)) manner.

(149) The drive **116** reads and writes data from and to the removable storage medium **117** such as a magnetic disk (including a flexible disk), an optical disk (including a compact disc-read only memory (CD-ROM) and a digital versatile disc (DVD)), a magneto-optical disk (including a mini disc (MD)), a semiconductor memory, or the like.

5. Functions Implemented by Vehicle Control System of FIG. 3

(150) Next, functions implemented by the vehicle **1** of FIG. **3** will be described with reference to a functional block diagram of FIG. **6**.

(151) The processor **21** of the vehicle **1** implements functions as a control section **201**, an operation status recognition section **202**, an operation status reporting section **203**, and an update section **204**.

(152) The control section **201** controls the entire operation of the vehicle control system **11**, and outputs various control signals.

(153) Furthermore, the control section **201** outputs a control signal for controlling various operations of the vehicle **1** to the vehicle control section **32** on the basis of the object recognition result by the recognition section **73** based on the image captured by the camera **51**.

(154) Moreover, the control section **201** controls the operation of the operation status recognition section **202** to recognize the operation status of the recognition section **73**.

(155) Furthermore, when vehicle information required for grouping the vehicles **1** is requested by the server **2**, the control section **201** controls the communication section **22** to transmit the vehicle information. Note that the vehicle information required for grouping the vehicles **1** will be described later when the configuration of the server **2** is described.

(156) The operation status recognition section **202** recognizes the operation status of the recognition section **73** on the basis of the image captured by the camera **51** and the object recognition result of the recognition section **73** corresponding to the image captured by the camera **51**.

(157) More specifically, for example, the operation status recognition section **202** specifies an object that can be recognized from the map information corresponding to the current position information on the basis of the map information of the map information accumulation section **23** and the position information based on the signals from the GNSS reception section **24** and the external recognition sensor **25**, in addition to the image captured by the camera **51** and the object recognition result of the recognition section **73** based on the image captured by the camera **51**, determines whether or not the recognition section **73** is appropriately operating by comparison with the object recognition result, recognizes the determination result as the operation status, and outputs the operation status reporting section **203**.

(158) For example, the operation status recognition section **202** reads, from the map information, a position specified on the basis of the GNSS signal of the GNSS reception section **24** and the signal of the external recognition sensor **25** and information on an object present within the angle of view of the camera **51** based on the direction of the vehicle **1** at the specified position, compares the

information with the recognition result of the recognition section **73**, and recognizes the comparison result as the operation status.

(159) That is, in a case where, for example, a specific sign, a specific building, or the like is read as an object present in the vicinity read from the map information at the position specified on the basis of the GNSS signal, the operation status recognition section **202** determines that the operation status is appropriate if the recognition result of the recognition section **73** at that time matches the specific sign, the specific building, or the like read from the map information, and determines that the operation status is not appropriate if the recognition result does not match the specific sign, the specific building, or the like read from the map information.

(160) The object to be compared with the recognition result may be an object specified from map information such as a specific sign, a specific building or the like, or may be a dedicated marker or the like for confirming the operation status of the recognition section **73**.

(161) Furthermore, the object to be compared with the recognition result may be an object that can be recognized along with a phenomenon that is expected to occur from a position, a time zone, and the like, and may be, for example, a vehicle, a pedestrian, or the like in a traffic jam that is expected to occur from a position, a time zone, and the like. In this case, whether or not it is possible to recognize that the vehicle or the pedestrian is moving may also be used for determining the operation status of the recognition section **73**.

(162) Moreover, the object to be compared with the recognition result may be a sensitive signal that operates with V2X communication or approach of the vehicle **1**, a gate bar of a parking lot, or the like. In this case, whether or not the sensitive signal changes from red to green as the vehicle **1** approaches, or whether or not a change in operation such as opening or closing of the gate bar is recognized as a recognition result may also be used for the determination of the operation status.

(163) Furthermore, the operation status recognition section **202** may back up the recognition section **73** before the update, compare the recognition rate of the recognition section **73** before the update with the recognition rate of the recognition section **73** after the update, and regard the comparison result as the operation status. In this case, when the recognition rate of the recognition section **73** after the update is not lower than the recognition rate of the recognition section **73** before the update and there is no deterioration, it may be considered that appropriate update has been performed, and conversely, when the recognition rate is lowered and there is deterioration, it may be considered that inappropriate update has been performed.

(164) The operation status reporting section **203** determines whether or not reporting to the server **2** is necessary on the basis of the information of the operation status supplied from the operation status recognition section **202**, and controls the communication section **22** to transmit the image captured by the camera **51** and the recognition result together to the server **2** when determining that reporting to the server **2** is necessary. For example, when the operation status is inappropriate, the operation status reporting section **203** reports the image captured by the camera **51** and the recognition result together to the server **2**.

(165) Note that, for example, when the operation status is appropriate, the operation status reporting section **203** may report the image captured by the camera **51** and the recognition result together to the server **2**.

(166) Furthermore, the operation status reporting section **203** may report the operation status together with the image captured by the camera **51** and the recognition result to the server **2** regardless of whether or not the operation status is appropriate, for example.

(167) The update section **204** controls the communication section **22** to update the recognition section **73** from the server **2**, receive the update SW, develop information as necessary, or the like, thereby updating the recognition section **73** to a state relearned by the server **2**.

6. Functions Implemented by Server of FIG. 4

(168) Next, functions implemented by the server **2** of FIG. 4 will be described with reference to the functional block diagram of FIG. 7.

(169) The processor **111** of the server **2** implements functions as a vehicle information collection section **231**, a grouping section **232**, a distribution order decision section **233**, a distribution status confirmation section **234**, a distribution planning section **235**, a distribution section **236**, a relearning section **237**, and an update SW release section **238**.

(170) The vehicle information collection section **231** controls the communication section **115** to request vehicle information for grouping the vehicles **1**, collects the vehicle information, and outputs the collected vehicle information to the grouping section **232**.

(171) Here, the vehicle information is various types of information required for grouping the vehicles **1** by the grouping section **232** to be described later, and is, for example, information such as a vehicle type, position information, a detection history of the external recognition sensor **25** and a travel history including a route or the like traveled in the past, a total travel distance, weather information corresponding to the current position information of the vehicle **1**, and the like.

(172) The grouping section **232** groups the vehicles **1-1** to **1-n** on the basis of the vehicle information collected from each of the vehicles **1**, and outputs the grouping result to the distribution order decision section **233**.

(173) The grouping performed here is to group the vehicles **1-1** to **1-n** into at least two groups or more for setting the order when the update SW for updating the recognition section **73** is distributed.

(174) At the time of updating the recognition section **73**, the distribution of the update SW is performed in order from a group of vehicles **1** that are not to be in a dangerous state, have a high possibility of being safe, and have ensured safety to a group with lower safety even in a state where an appropriate operation cannot be performed.

(175) Note that the grouping will be described later in detail with reference to FIG. **8**.

(176) On the basis of the grouping result supplied from the grouping section **232**, the distribution order decision section **233** decides the order of distributing the update SW in order from the group having a high possibility of being safe (safety is ensured), and outputs information on the distribution order with respect to the decided grouping result to the distribution planning section **235**.

(177) The distribution status confirmation section **234** controls the communication section **115** to confirm the distribution status indicating to which group of vehicles **1** the update SW is distributed, and outputs information of the confirmed distribution status to the distribution planning section **235**.

(178) Furthermore, the distribution status confirmation section **234** controls the communication section **115** to confirm, as the distribution status, information indicating whether or not the object recognition processing by the recognition section **73** updated by the distributed update SW is appropriate, the information being transmitted from the vehicle **1**, and outputs the information to the distribution planning section **235**.

(179) The distribution planning section **235** plans the order and timing for distributing the update SW from the information on the distribution order supplied from the distribution order decision section **233** and the information on the distribution status supplied from the distribution status confirmation section **234**, and outputs the order and timing to the distribution section **236** as a distribution plan.

(180) The relearning section **237** accumulates vehicle accumulation information constituting a parameter used as relearning data including the image captured by the camera **51** and the object recognition result by the recognition section **73**, supplied from the vehicle **1**, relearns the corresponding recognition section **73** by using the accumulated vehicle accumulation information as relearning data, generates an update SW as a relearning result, and outputs the update SW to the update SW release section **238**.

(181) The update SW release section **238** confirms, by simulation, the operation of the recognition section **73** updated by the update SW generated by the relearning of the recognition section **73** by

the releasing section **237**, determines whether or not it is distributable, and outputs the distributable update SW to the distribution section **236**.

(182) The distribution section **236** controls the communication section **115** to distribute the update SW supplied from the update SW release section **238** to the vehicle **1** according to the distribution plan supplied from the distribution planning section **235**, and causes the recognition section **73** to be updated.

7. Grouping of Vehicles

(183) Next, grouping of the vehicles **1-1** to **1-n** will be described with reference to FIG. **8**.

(184) The grouping of the vehicles **1-1** to **1-n** by the grouping section **232** is processing for grouping a vehicle group for confirming a state of a case where the recognition section **73** is actually updated by the update SW to be distributed.

(185) Therefore, the vehicles **1-1** to **1-n** are desirably grouped as illustrated in FIG. **8**, for example.

(186) That is, in FIG. **8**, the vehicles **1-1** to **1-n** are grouped into groups **G1** to **Gx** in order from the top.

(187) Here, the group **G1** includes vehicles **1-11** to **1-X** among the vehicles **1-1** to **1-n**, the group **G2** includes vehicles **1-21** to **1-Y** among the vehicles **1-1** to **1-n**, and the group **Gx** includes vehicles **1-31** to **1-Z** among the vehicles **1-1** to **1-n**.

(188) Furthermore, in the groups **G1** to **Gx** in FIG. **8**, the risk in a case where some defect occurs by updating the recognition section **73** by the update SW is assumed to be smaller in the upper part and larger in the lower part in the drawing.

(189) In other words, the safest group even in a case where some defect occurs by updating the recognition section **73** the update SW is the group **G1**, the next safest group is the group **G2**, and the most dangerous group is the group **Gx**.

(190) For this reason, in a case where grouping is performed as in the groups **G1** to **Gx** as illustrated in FIG. **8**, the distribution order decision section **233** decides the order of distribution of the update SW as in the groups **G1**, **G2**, . . . , **Gx**.

(191) Therefore, the grouping section **232** scores the risk in a case where some defect occurs by updating the recognition section **73** by the update SW in the vehicles **1-1** to **1-n**, and groups according to the score.

(192) Hereinafter, a risk that occurs in a case where some defect occurs by updating the recognition section **73** by the update SW is referred to as an update risk.

(193) That is, the grouping is to group the vehicles **1-1** to **1-n** into a plurality of groups according to the update risk.

(194) Therefore, in FIG. **8**, an example of being divided into three or more groups is described, but ideally, it is considered that a predetermined effect can be obtained if at least two groups are obtained, that is, a group including the number of vehicles **1** in which complete safety is ensured and the influence of the update risk is likely to be stochastically obtained with a predetermined accuracy and the other groups.

(195) That is, the update SW is first distributed to the first group including the number of vehicles **1** in which complete safety is ensured and the influence of the update risk is likely to be stochastically obtained with a predetermined accuracy, and the presence or absence of a defect when traveling using the recognition result of the recognition section **73** updated by the update SW is confirmed.

(196) Then, when it is confirmed that there is no defect in the first group, the update SW is also distributed to the remaining groups.

(197) Furthermore, in a case where the vehicles **1-1** to **1-n** are divided into three or more groups by grouping, the update SW is distributed sequentially from the upper group, and when it is confirmed that there is no defect, the update SW is distributed sequentially to the upper group of the update risk.

(198) In the case of being divided into three or more groups, the update SW is distributed to the

group to which the update SW is distributed last in a state in which the operation status of the recognition section **73** updated by the update SW is sufficiently verified in the vehicles **1** in the groups to which the update SW is distributed so far immediately before. Therefore, vehicles **1** in a group to which the update SW is distributed later can update the recognition section **73** more safely. (199) For example, the grouping section **232** may regard that the update risk of encountering an accident is higher as the number of accidents or the number of automobiles in each region is larger according to the position information of the vehicles **1-1** to **1-n** and the number of accidents in each region or the number of automobiles in each region.

(200) In this case, the grouping section **232** may set scores such that the vehicle **1** in a region having a larger number of accidents or a larger number of automobiles for each region is lower, set ranks according to the scores set in this manner, and set the groups **G1** to **Gx** from the top.

(201) Furthermore, the grouping section **232** may set the score lower for the vehicle **1** present in a region where the recognition accuracy by object recognition is likely to deteriorate, for example, in a region where the weather is stormy, and conversely, set the score higher for the vehicle **1** present in a region where the recognition accuracy is considered to be less deteriorated, for example, in a region where the weather is fine, according to the position information of each vehicle **1** and the weather of the current location of each region, and group the vehicles **1**.

(202) Moreover, the grouping section **232** may perform grouping such that, for example, the smaller the travel distance, the lower the probability of encountering an accident and the lower the update risk, and thus the higher the score is set, and conversely, the larger the travel distance, the higher the probability of encountering an accident and the higher the update risk, and thus the higher the score is set, according to the travel distance from the operation history or the like of each vehicle **1**.

(203) Furthermore, the grouping section **232** may acquire a tendency of acceleration/deceleration, a speed range, and a driving situation of a road or the like to be used from an operation history (sensing result of the external recognition sensor **25**) of each vehicle **1**, and the like, and may perform grouping such that, for example, when a change in acceleration/deceleration is large, a speed range is a high speed range, or a use frequency of a road having a high accident occurrence frequency is high, the score is set low assuming that an update risk is high, and conversely, when a change in acceleration/deceleration is small, a speed range is a low speed range, or a use frequency of a road having a high accident occurrence frequency is low, the score is set high assuming that an update risk is low.

(204) Moreover, according to the vehicle type of the vehicle **1**, for example, the grouping section **232** may regard a vehicle type for which it is known that a purchaser group who prefers slow traveling purchases more than a predetermined number of vehicles, a vehicle type having a size smaller than a predetermined size, a vehicle type having traveling performance higher than a predetermined traveling performance, a vehicle type equipped with safety equipment more than a predetermined number, a commercial vehicle or the like that is traveling for commercial purposes and is known not to travel recklessly, as having a low update risk, and set the score high so as to perform grouping.

(205) Conversely, the grouping section **232** may regard a vehicle type for which it is known that a purchaser group who prefers slow traveling purchases less than a predetermined number of vehicles, a vehicle type having a size larger than a predetermined size, a vehicle type not having traveling performance higher than a predetermined traveling performance, a vehicle type not equipped with safety equipment more than a predetermined number, a private car that may drive recklessly compared to a commercial vehicle, and the like, as having a high update risk, and set the score low so as to perform grouping. Furthermore, the grouping section **232** may group the vehicles **1** by a combination of scores in consideration of the above-described elements.

(206) For grouping, the grouping section **232** first sets scores for the vehicles **1**, then obtains ranks, and sets groups from the top with a predetermined number of divisions.

(207) At this time, the number of vehicles **1** belonging to each group may not be equal. For example, the number of vehicles **1** belonging to a higher group may be smaller, and the number of vehicles **1** belonging to a lower group may be larger. Furthermore, the number of vehicles **1** belonging to each group may not be fixed, and for example, the width of the score belonging to each group may be determined, and the group may be set according to the score.

(208) However, the smaller the number of vehicles **1** belonging to the group to which the update SW is first distributed, the smaller the influence of the update risk, and the easier the confirmation of the update risk.

(209) Furthermore, since the grouping may be performed according to the level of safety, the grouping may be performed on the basis of other criteria. For example, since safety is high for vehicles for mobility as a service (MaaS), vehicles traveling in a limited area, and the like, the update SW may be distributed from these groups, and may be distributed to general vehicles after safety is confirmed.

(210) Moreover, in a case where a passenger car is compared with a bus or the like, the bus has a larger number of occupants than the passenger car, and has a larger influence in a case where an accident occurs. Therefore, the update SW may be distributed from the passenger car, and may be distributed to the bus or the like after safety is confirmed.

(211) Furthermore, as for the automated driving, since the driver intervenes in the driving in the case of level **2** as compared with levels **3** and **4**, it is considered that a defect can be handled even if there is a defect in the update of the recognition section **73**. Therefore, the update may be distributed from the vehicles **1** of level **2**, and may be sequentially distributed to the vehicles of level **3** and level **4** after safety is confirmed.

8. Grouping Processing

(212) Next, the grouping processing will be described with reference to the flowchart of FIG. **9**.

(213) In step **S11**, the vehicle information collection section **231** controls the communication section **115** to request the vehicle information from the vehicles **1-1** to **1-n**.

(214) In step **S31**, the control section **201** controls the communication section **22** to determine whether or not vehicle information has been requested from the server **2**, and repeats the similar processing until requested.

(215) In a case where vehicle information is requested from the server **2** in step **S31**, in step **S32**, the control section **201** controls the communication section **22** to transmit, to the server **2**, vehicle information required for grouping the vehicles **1** such as, for example, vehicle types, position information based on a GNSS signal, a detection history of the external recognition sensor **25** and a travel history including a route or the like traveled in the past, a total travel distance, weather information corresponding to current position information of the vehicle **1**, and the like.

(216) In step **S33**, the control section **201** determines whether or not the end of the process has been instructed, and in a case where the end of the process has not been instructed, the process returns to step **S31**.

(217) That is, the processing of steps **S31** to **S33** is repeated until the end of the process is instructed.

(218) Then, in step **S33**, when the end of the process is instructed, the process ends.

(219) Meanwhile, when the vehicle information is transmitted to the server **2** by the processing in step **S32**, the vehicle information collection section **231** of the server **2** controls the communication section **115** to acquire and collect the vehicle information transmitted from the vehicle **1** in step **S12**.

(220) At this time, the vehicle information collection section **231** may continuously collect each piece of the vehicle information of the vehicles **1** as a database in association with information for individually identifying the vehicles **1**, for example.

(221) Note that, here, the description will be given assuming that all the vehicle information of the vehicles **1-1** to **1-n** is stored into a database by the processing of steps **S12** and **S32**, but only some

of the vehicles **1** may be compiled into a database.

(222) In step **S13**, the grouping section **232** sets any unprocessed vehicle **1** among the vehicles **1-1** to **1-n** stored in the database in the vehicle information collection section **231** as the processing target vehicle.

(223) In step **S14**, the grouping section **232** sets a score for implementing the grouping on the basis of the vehicle information of the processing target vehicle.

(224) That is, the grouping section **232** sets the score for each vehicle **1** on the basis of the vehicle information such that a higher score is set as the update risk (risk in a case where a defect occurs by updating the recognition section **73** by the update SW) is smaller.

(225) In step **S15**, it is determined whether or not there is an unprocessed vehicle **1** for which a score necessary for grouping is not set, and in a case where there is an unprocessed vehicle **1**, the process returns to step **S13**.

(226) That is, the processing of steps **S13** to **15** is repeated until scores for grouping are set for all the vehicles **1** for which the vehicle information is stored in the database in the vehicle information collection section **231**.

(227) Then, in step **S15**, in a case where it is determined that scores for grouping are set for all the vehicles **1** in which the vehicle information is stored in the database in the vehicle information collection section **231** and there is no unprocessed vehicle **1** for which a score necessary for grouping is not set, the process proceeds to step **S16**.

(228) In step **S16**, the grouping section **232** obtains (sorts) the ranks of the vehicles **1-1** to **1-n** on the basis of the obtained scores.

(229) In step **S17**, the grouping section **232** sets the number of groups. Note that the number of groups may be set to a fixed value or may be dynamically set.

(230) In step **S18**, the grouping section **232** groups the vehicles **1-1** to **1-n** so as to have a set number of groups on the basis of the ranks according to the scores, and outputs the result to the distribution order decision section **233**.

(231) In step **S19**, the distribution order decision section **233** decides the distribution order in units of groups according to the scores of the groups supplied from the grouping section **232**.

(232) In step **S20**, the vehicle information collection section **231** determines whether or not the end of the process has been instructed, and in a case where the end of the process has not been instructed, the process proceeds to step **S21**.

(233) In step **S21**, the vehicle information collection section **231** determines whether or not a predetermined time has elapsed, and repeats similar processing until the predetermined time has elapsed.

(234) Then, in a case where it is determined in step **S21** that the predetermined time has elapsed, the process returns to step **S11**, and the subsequent processing is repeated.

(235) That is, every time a predetermined time elapses, the vehicle information is acquired from each vehicle **1**, and the grouping based on the vehicle information is repeated, whereby the grouping based on fixed information such as the vehicle type of the vehicle **1** and the like and changing information around the vehicle **1** such as the position information, the weather, and the like is continuously set while changing in real time.

(236) Then, in step **S20**, when the end of the process is instructed, the process ends.

(237) That is, by the above processing, in the server **2**, the grouping is repeated on the basis of the vehicle information including the fixed information of the vehicles **1** and the changing information, and the processing in which the order in which the update SW is distributed is set in units of groups of the vehicles **1** is repeated.

(238) As a result, the vehicles **1** are grouped according to the update risk by the update SW, and the distribution order of the update SW is set for each group of the vehicles **1**.

9. Relearning Processing

(239) Next, relearning processing of the recognition section **73** will be described with reference to a

flowchart of FIG. 10.

(240) In step S51, the recognition section 73 of the vehicle 1 recognizes an object on the basis of the image captured by the camera 51, and outputs the object recognition result to the control section 201 together with the image.

(241) In step S52, the control section 201 controls the vehicle control section 32 on the basis of the object recognition result to control the operation of the vehicle 1. For example, in a case where it is recognized that a pedestrian is present in front of traveling on the basis of the object recognition result, the control section 201 supplies a control signal to the vehicle control section 32 to perform control so as to perform an operation of avoiding contact with the pedestrian.

(242) In step S53, the control section 201 controls the communication section 22 to accumulate the object recognition result of the recognition section 73 and the image of the camera 51 at that time together as vehicle accumulation information and transmit the accumulated information to the server 2. At this time, for example, the control section 201 may transmit an identifier for identifying the vehicle 1 and other vehicle information to the server 2.

(243) In step S71, the relearning section 237 of the server 2 controls the communication section 115 to determine whether or not the vehicle accumulation information in which the object recognition result of the recognition section 73 and the image of the camera 51 at that time are combined has been transmitted.

(244) In a case where it is determined in step S71 that the vehicle accumulation information in which the object recognition result of the recognition section 73 and the image of the camera 51 at that time are combined has not been transmitted, the process proceeds to step S75.

(245) Meanwhile, in a case where it is determined in step S71 that the vehicle accumulation information in which the object recognition result of the recognition section 73 and the image of the camera 51 at that time are combined has been transmitted, the process proceeds to step S72.

(246) In step S72, the relearning section 237 receives and accumulates the transmitted object recognition result of the recognition section 73 and the image of the camera 51 at that time together as vehicle accumulation information for relearning.

(247) At this time, in a case where an identifier for identifying the vehicle 1 or other vehicle accumulation information is transmitted, the relearning section 237 receives and accumulates the identifier and the other vehicle accumulation information together.

(248) Note that, here, the description will proceed on the assumption that the vehicle accumulation information for relearning is received and accumulated from all the vehicles 1 by the processing of steps S71 and S72, but the vehicle accumulation information may be partially provided.

(249) In step S73, the relearning section 237 relearns the recognition section 73 by using the accumulated vehicle accumulation information for relearning, and supplies a relearning result to the update SW release section 238.

(250) In step S74, the update SW release section 238 executes a simulation using the relearned recognition section 73 to verify the recognition accuracy.

(251) In step S75, the relearning section 237 determines whether or not the end of the process has been instructed, and in a case where the end of the process has not been instructed, the process returns to step S71, and the subsequent processing is repeated.

(252) That is, until the end of the process is instructed, the vehicle accumulation information for relearning including the recognition result of the recognition section 73 and the image is collected from the vehicle 1, the relearning is repeated, and the processing in which the recognition accuracy of the recognition section 73 subjected to the relearning is obtained by simulation is repeated.

(253) Then, in step S75, when the end of the process is instructed, the process ends.

(254) With the above processing, the vehicle accumulation information for relearning including the recognition result of the recognition section 73 and the image is collected from the vehicle 1, the relearning is repeated, and the processing in which the recognition accuracy of the recognition section 73 subjected to the relearning is obtained by simulation can be repeated.

10. Update Processing

(255) Next, update processing will be described with reference to the flowchart of FIG. 11.

(256) In step **S91**, the update SW release section **238** determines whether or not to distribute the update SW and set that there is an update on the basis of whether or not the relearned recognition section **73** obtained by the relearning processing described above is in the state to be distributed, and repeats the similar processing until it is determined that there is an update.

(257) For example, in a case where the recognition accuracy of the relearned recognition section **73** is improved by a predetermined ratio from the recognition accuracy of the recognition section **73** before relearning, the update SW release section **238** may determine that it is in the state to be updated.

(258) In step **S91**, in a case where the update SW release section **238** determines that it is in the state to be updated by the relearned recognition section **73**, the process proceeds to step **S92**.

(259) In step **S92**, the distribution planning section **235** initializes a counter *i* of an identifier for identifying the grouped group to 1.

(260) In step **S93**, the distribution planning section **235** acquires the vehicle information of the vehicles **1** belonging to the group *i* among the information of the distribution order in units of groups decided by the distribution order decision section **233**.

(261) For example, in the case of the first processing in which the counter *i*=1, even if there is a defect in the update of the recognition sections **73** belonging to the group **G1** to which the update SW is first distributed, described with reference to FIG. 8, the vehicle information of the group of vehicles **1** in which the safety is ensured is acquired.

(262) In step **S94**, the distribution planning section **235** sets an unprocessed vehicle **1** among the vehicles **1** belonging to the group *i* as the processing target vehicle.

(263) In step **S95**, the distribution planning section **235** executes distribution timing setting processing, and sets the update timing of the recognition section **73** of the processing target vehicle by the update SW.

(264) In updating the recognition section **73** by distributing the update SW, since the operation of the recognition section **73** being updated is stopped, the timing at which the movement of the vehicle **1** is stopped or the timing at which the recognition processing by the recognition section **73** related to the update is unnecessary is set as the timing at which the update SW is distributed.

(265) Note that details of the distribution timing setting processing will be described later with reference to the flowcharts of FIGS. 12 and 13.

(266) In step **S96**, the distribution planning section **235** determines whether or not there is an unprocessed vehicle **1** in which the distribution timing is not set among the vehicles **1** belonging to the group *i*, and in a case where there is an unprocessed vehicle **1**, the process returns to step **S94**.

(267) That is, the processing of steps **S94** to **S96** is repeated until the distribution timing is set for all the vehicles **1** belonging to the group *i*.

(268) Then, in a case where it is determined in step **S96** that the distribution timing has been set for all the vehicles **1** belonging to the group *i*, the process proceeds to step **S97**.

(269) That is, at this time point, all the distribution timings of the vehicles **1** belonging to the group *i* are planned, whereby the distribution plan of the update SW is completed.

(270) In step **S97**, the distribution planning section **235** determines whether or not the distribution timing of any vehicle **1** belonging to the group *i* has come on the basis of the distribution plan.

(271) In a case where it is determined in step **S97** that the distribution timing of any vehicle **1** belonging to the group *i* has come on the basis of the distribution plan, the process proceeds to step **S98**. Note that, in step **S97**, in a case where it is not any distribution timing of the vehicles **1** belonging to the group *i*, the process proceeds to step **S103**.

(272) In step **S98**, the distribution planning section **235** controls the distribution section **236** to acquire the update SW supplied from the update SW release section **238** to update the recognition section **73** generated by relearning, and causes the communication section **115** to distribute the

update SW to the vehicle **1** at the distribution timing.

(273) At this time, the distribution status confirmation section **234** controls the communication section **115** to acquire the distributed version of the update SW and the information of the vehicle **1** to be the distribution destination as the distribution status.

(274) In step **S121**, the update section **204** of the vehicle **1** controls the communication section **22** to determine whether or not the update SW is transmitted from the server **2**.

(275) In the case of the vehicle **1** belonging to the group **i** at the distribution timing, it is determined in step **S121** that the update SW is transmitted from the server **2**, and the process proceeds to step **S122**.

(276) In step **S122**, the update section **204** stops at least one of the operation related to the object recognition processing of the recognition section **73** or the operation control based on the recognition result of the recognition section **73** in the control section **201**.

(277) In step **S123**, the update section **204** controls the communication section **22** to acquire the transmitted update SW and updates the recognition section **73**. At this time, before performing the update by the update SW, the update section **204** holds the recognition section **73** before the update for backup.

(278) In step **S124**, the update section **204** operates the recognition section **73** on a trial basis, confirms the operating state, and confirms that the update by the update SW has been appropriately completed.

(279) Here, in a case where the update by the update SW is not completed, the update section **204** repeats the update by the update SW until the update is appropriately completed, and completes the update in an appropriate state.

(280) At this time point, in a case where the update cannot be appropriately completed, the update section **204** ends the update processing and operates the recognition section **73** before the update held as a backup again.

(281) In step **S125**, after the update by the update SW is completed, the recognition section **73** recognizes an object on the basis of the image captured by the camera **51**, and outputs the recognition result to the operation status recognition section **202**.

(282) In step **S126**, the operation status recognition section **202** acquires the image captured by the camera **51** and the object recognition result of the recognition section **73** corresponding to the image captured by the camera **51**.

(283) In step **S127**, the operation status recognition section **202** determines whether or not the operation status of the recognition section **73** is appropriate on the basis of the acquired object recognition result, and outputs the determination result to the operation status reporting section **203** in association with the object recognition result and the image.

(284) That is, for example, the operation status recognition section **202** specifies an object that can be recognized from the map information corresponding to the current position information on the basis of the map information of the map information accumulation section **23** and the position information based on the signals from the GNSS reception section **24** and the external recognition sensor **25**, in addition to the image captured by the camera **51** and the object recognition result of the recognition section **73** based on the image captured by the camera **51**, and determines whether or not the recognition section **73** is appropriately operating by comparison with the object recognition result.

(285) In step **S128**, the operation status reporting section **203** determines whether or not reporting of the operation status is necessary. That is, the necessity of the reporting of the operation status is, for example, a case where the operation state is inappropriate. However, the necessity of the reporting of the operation status may be any case where the operation status is required regardless of whether or not the operation status is appropriate.

(286) In a case where it is determined in step **S128** that the reporting of the operation status is necessary, the process proceeds to step **S129**.

(287) In step **S129**, the operation status reporting section **203** controls the communication section **22** to report the operation status to the server **2**.

(288) Note that, in a case where it is determined in step **S128** that reporting of the operation status is unnecessary, the processing of step **S129** is skipped.

(289) In step **S130**, the operation status recognition section **202** determines whether or not the determination of the operation status of the recognition section **73** after the update is sufficient, and in a case where it is determined that the determination is not sufficient, the process returns to step **S124**.

(290) That is, the processing of steps **S125** to **S130** is repeated until it is determined that the determination of the operation status of the recognition section **73** after the update is sufficient.

(291) Note that the determination as to whether or not the determination of the operation status of the recognition section **73** after the update is sufficient may be made, for example, by determining whether or not the operation status has been recognized a predetermined number of times or more.

(292) In a case where it is determined in step **S130** that the determination of the operation status of the recognition section **73** after the update is sufficient, the process proceeds to step **S131**.

(293) In step **S131**, the update section **204** determines whether or not the update of the recognition section **73** by the update SW is appropriate.

(294) That is, since it is the timing after it is determined that the determination of the operation status of the recognition section **73** after the update is sufficient in the immediately preceding processing, the update section **204** may determine whether or not the update of the recognition section **73** by the update SW is appropriate on the basis of, for example, whether or not the ratio of the number of times the operation status is recognized to be inappropriate is higher than a predetermined ratio with respect to the predetermined number of times the operation status of the operation status recognition section **202** is recognized.

(295) In a case where it is determined in step **S131** that the update of the recognition section **73** by the update SW is appropriate, the process proceeds to step **S132**.

(296) In step **S132**, the update section **204** resumes the operation related to the object recognition processing of the recognition section **73** after the update and the operation control based on the recognition result of the recognition section **73** after the update in the control section **201**. At this time, the update section **204** discards the recognition section **73** before update held for backup.

(297) In a case where it is determined in step **S131** that the update of the recognition section **73** by the update SW is not appropriate, the process proceeds to step **S133**.

(298) In step **S133**, the update section **204** returns the operation to the state of the recognition section **73** before update held for backup, and resumes the operation related to the object recognition processing of the recognition section **73** before update and the operation control based on the recognition result of the recognition section **73** before update in the control section **201**. That is, in this case, the recognition section **73** is not updated, and the operation in the state before the update is continued.

(299) That is, in this case, since the update by the update SW of the recognition section **73** is not appropriate, it is considered that the reliability of the recognition result of the recognition section **73** after the update is low. For this reason, if the processing based on the recognition result of the recognition section **73** after the update is performed, there is a possibility that erroneous processing based on erroneous detection is performed and dangerous operation is caused. Therefore, the operation is returned to the operation based on the recognition result of the recognition section **73** before the update.

(300) Furthermore, in a case where it is determined that the update of the recognition section **73** by the update SW is not appropriate, instead of the processing of step **S133**, a state may be made in which the processing based on the recognition result of the recognition section **73** after the update by the update SW is not performed in the control section **201**.

(301) At this time, since the update of the recognition section **73** by the update SW is in an

inappropriate state and the reliability of the operation control based on the recognition result is low, the driver who is the user may be allowed to recognize that the operation such as the automated driving or the like using the recognition result of the recognition section 73 is stopped.

(302) In step S134, it is determined whether or not the end of the process has been instructed, and in a case where the end of the process has not been instructed, the process returns to step S121.

(303) That is, when the processing of steps S121 to S134 is repeated and the update SW is distributed until the end of the process is instructed, the stop of the operation by the recognition section 73, the update of the recognition section 73, and the recognition of the operation status of the recognition section 73 are repeated, and the process of reporting the operation status to the server 2 is repeated as necessary.

(304) Meanwhile, in step S99, the distribution status confirmation section 234 of the server 2 controls the communication section 115 to determine whether or not there is a report of the operation status of the recognition section 73 updated by the update SW from any one of the vehicles 1, and in a case where there is the report of the operation status, the process proceeds to step S100. Note that, in a case where there is no report of the operation status of the recognition section 73 updated by the update SW from any vehicle 1 in step S99, the process proceeds to step S103.

(305) In step S100, the distribution status confirmation section 234 acquires information on the operation status of the recognition section 73 updated by the reported update SW.

(306) In step S101, the distribution status confirmation section 234 aggregates the information of the operation status of the recognition section 73 updated by the reported update SW. More specifically, the distribution status confirmation section 234 aggregates, for example, the rate at which the recognition processing of the recognition section 73 updated by the update SW is regarded as inappropriate.

(307) In step S102, the distribution status confirmation section 234 determines whether or not the update of the recognition section 73 by the update SW is inappropriate on the basis of the aggregated result.

(308) More specifically, for example, the distribution status confirmation section 234 determines whether or not the update of the recognition section 73 by the update SW is inappropriate according to whether or not the rate at which the recognition processing of the recognition section 73 updated by the update SW is regarded as inappropriate is higher than a predetermined rate.

(309) In a case where it is not determined in step S102 that the update of the recognition section 73 by the update SW is inappropriate, the process proceeds to step S103.

(310) In step S103, the distribution status confirmation section 234 determines whether or not the update SW is distributed and the recognition section 73 is updated in all the vehicles 1 of the group i.

(311) In step S103, in a case where the update SW is not distributed and the recognition section 73 is not updated in all the vehicles 1 in the group i, the process returns to step S97.

(312) That is, the processing of steps S97 to S103 is repeated until the update SW is distributed and the recognition section 73 is updated in all the vehicles 1 in the group i.

(313) Then, in step S103, in a case where it is determined that the update SW is distributed and the recognition section 73 is updated in all the vehicles 1 in the group i, the process proceeds to step S104.

(314) In step S104, the distribution planning section 235 increments the counter i by 1.

(315) In step S105, the distribution planning section 235 determines whether or not the counter i is larger than the maximum value which is the number of groups, and the update processing has been completed for all the groups.

(316) In step S105, in a case where it is determined that the counter i is equal to or less than the maximum value which is the number of groups, and the update processing is not completed for all the groups, the process returns to step S93, and the subsequent processing is repeated.

(317) That is, the processing of distributing the update SW in units of groups and updating the recognition section **73** is repeated in order from each vehicle **1** in the group with high safety in a case where there is a defect in the updated recognition section **73**, and the processing of steps **S93** to **S105** is repeated until the recognition section **73** is updated by the update SW for the vehicles **1** in the all groups.

(318) Then, in step **S105**, in a case where it is determined that the counter *i* is larger than the maximum value which is the number of groups and the processing has been completed for all the groups, the process proceeds to step **S106**.

(319) In step **S106**, it is determined whether or not the end of the process has been instructed, and in a case where the end of the process has not been instructed, the process returns to step **S91**, and the subsequent processing is repeated.

(320) Then, in a case where the end of the process is instructed in step **S106**, the process ends.

(321) Furthermore, in step **S102**, in a case where it is determined that the update of the recognition section **73** by the update SW is inappropriate, the process proceeds to step **S107**.

(322) In step **S107**, since it has been confirmed that a defect occurs in the update of the recognition section **73** by the current update SW, the distribution status confirmation section **234** notifies the distribution planning section **235** that the subsequent distribution of the update SW is stopped.

(323) As a result, the distribution planning section **235** discards the distribution plan and stops the subsequent distribution of the update SW of the group *i*.

(324) According to the above processing, when it is regarded that the recognition section **73** needs to be updated by the update SW obtained by relearning, the update SW is distributed in order from the group having a lower update risk for each group of vehicles **1**, and the operation status is confirmed. When it is regarded that the recognition processing is appropriate by the recognition section **73** after the update on the basis of the operation status, it is possible to sequentially and stepwise distribute the update SW to the vehicles **1** of the group having a higher update risk to update the recognition section **73**.

(325) As a result, since the distribution of the update SW of the recognition section **73** is sequentially performed from the group of the vehicles **1** having a lower update risk, even if a defect is recognized from the operation status of the recognition section **73** after the update, it is possible to safely update the recognition section **73** while suppressing occurrence of a fatal problem due to erroneous recognition.

(326) Furthermore, even in a state where complete relearning is not performed, the recognition section **73** is updated by the update SW in order from the vehicle **1** having a lower update risk, and the distribution of the update SW can be gradually spread to the vehicle **1** of the group having a higher update risk while confirming the operation status. As a result, it is possible to reduce the temporal cost related to relearning, and it is possible to quickly distribute the update SW.

(327) As a result, it is possible to quickly and safely update the SW such as the recognition section **73** by the update SW or the like.

11. Update Timing Setting Processing (Part 1)

(328) Next, update timing setting processing (part 1) of FIG. **11** will be described with reference to the flowchart of FIG. **12**.

(329) In step **S151**, the distribution planning section **235** reads the vehicle information of the vehicle **1** included in the information of the distribution order decided by the distribution order decision section **233**, and reads the operation record of the processing target vehicle. The operation record here is, for example, a daily operation time zone of the vehicle **1** or the like.

(330) In step **S152**, the distribution planning section **235** estimates a time zone during which the processing target vehicle is stopped on the basis of the read operation record of the processing target vehicle.

(331) In step **S153**, the distribution planning section **235** sets, as the distribution timing, the timing at which the processing target vehicle is most likely to be stopped in the time zone in which the

processing target vehicle is stopped.

(332) That is, according to the above processing, it is possible to set, as the update timing of the recognition section **73** by the update SW, the safe timing in which the recognition section **73** is most likely to be stopped from the operation record even if it gets in a state of being unable to function with the update.

(333) Note that, in addition to this, a time zone in which the vehicle is likely to be in the stop state such as night or the like may be set.

12. Update Timing Setting Processing (Part 2)

(334) Next, the update timing setting processing (part 2) of FIG. **11** will be described with reference to the flowchart of FIG. **13**.

(335) In the above, an example has been described in which the timing at which the vehicle **1** is most likely to be stopped from the operation record is set as the update timing. However, since the users of the vehicles **1** used for car sharing and the like are not the same, there is a possibility that the timing at which the vehicle **1** is stopped is difficult to estimate from the operation record and the update timing cannot be appropriately set. Furthermore, in the case of the vehicle **1** used for delivery or the like, there is a possibility that the stop timing is originally little.

(336) Therefore, by setting a timing at which a recognition target of the recognition section **73** is unlikely to be recognized as the update timing, the timing at which the influence is smaller even if the recognition section **73** does not function during the update processing may be set as the update timing.

(337) For example, when the recognition target of the recognition section **73** is only a pedestrian and a pedestrian is to be recognized, for example, a pedestrian is not recognized, for example, during traveling on a highway or the like when the control section **201** controls the operation so as to avoid contact with a pedestrian. Therefore, the operation to avoid contact with a pedestrian is not required.

(338) Therefore, on the basis of the operation record or the driving route planning, a timing at which it is estimated that a recognition target to be recognized by the recognition section **73** is not to be detected and at which there is no problem even if the recognition function by the recognition section **73** is stopped may be set as the update timing.

(339) Therefore, in the update timing setting processing (part 2), processing will be described in which, in a case where the recognition target of the recognition section **73** is only a pedestrian, a timing at which there is a low possibility that a pedestrian is to be detected by the recognition section **73** such as on a highway or the like on the basis of the driving route planning and there is no problem even if the recognition function of the recognition section **73** is stopped is set as the update timing.

(340) In step **S171**, the distribution planning section **235** acquires information on the driving route planned by the action planning section **62**.

(341) In step **S172**, the distribution planning section **235** estimates a variation in data to be recognized on the driving route on the basis of the acquired information of the driving route.

(342) That is, for example, in a case where the recognition target is a pedestrian, when the processing target vehicle moves on the planned driving route, the distribution planning section **235** estimates a position on the driving route where (there is a high possibility that) there is no data recognized as a pedestrian by the recognition section **73** on the basis of the image captured by the camera **51**.

(343) In step **S173**, the distribution planning section **235** specifies a section on the driving route where (there is a high possibility that) there is no data to be recognized on the basis of the information on the variation of the data to be recognized on the estimated driving route.

(344) That is, in a case where the recognition target is a pedestrian, the distribution planning section **235** specifies a section in which (there is a high possibility that) there is no data of a pedestrian on the planned driving route. On the planned driving route, a section in which there is no

data of a pedestrian is, for example, on a highway, an automobile exclusive road, or the like.

(345) In step **S174**, the distribution planning section **235** sets, as the update timing, a timing at which the vehicle passes through a section in which (there is a high possibility that) there is no data to be recognized on the estimated driving route.

(346) That is, in this case, a timing at which the vehicle passes through a section in which (there is a high possibility that) there is no data of a pedestrian on the planned driving route, for example, a timing at which the vehicle travels on a highway or the like is set as the update timing.

(347) By setting the update timing in this manner, when the recognition section **73** is updated by the update SW is a timing at which a pedestrian is not to be recognized since the vehicle is traveling on the highway during the update, and a state in which a malfunction caused by erroneous recognition such as recognition of a pedestrian does not occur even if the operation based on the recognition result of the recognition section **73** is stopped, that is, even if the function of recognizing a pedestrian is stopped. Therefore, it is possible to safely implement the update of the recognition section **73**.

(348) Note that, regarding the update of the recognition section **73** that executes the object recognition processing on the basis of the image captured by the rear camera, there is no problem even if the object recognition processing is stopped as long as it is the timing of forward travel, and thus, the update timing may be set during forward travel.

(349) Furthermore, in the above description, the example in which the server **2** sets the update timing has been described, but the update timing may be set by the vehicle **1**.

(350) That is, in this case, the update section **204** of the vehicle **1** executes the update timing setting processing described with reference to the flowcharts of FIGS. **12** and **13** on the basis of the operation status, and sets the update timing between steps **S31** and **S32** in the grouping processing described with reference to the flowchart of FIG. **9**, for example. Then, in the processing of step **S32**, the control section **201** controls the communication section **22** to include the information of the update timing in the vehicle information and transmit the information to the server **2**.

(351) Furthermore, in the update processing described with reference to the flowchart of FIG. **11**, since the update timing has already been set on the vehicle **1** side in the grouping processing, the processing of steps **S94** to **S96** is skipped, and the update SW is distributed from the server **2** at the update timing set on the vehicle **1** side.

13. Update for Each Processing Unit

(352) <Update in Component Unit>

(353) In the above description, regarding the update of the recognition section **73**, an example has been described in which the operation by the recognition section **73** is stopped and the recognition section is updated by the update SW. However, the recognition section **73** may be updated by the update SW during the operation in which the recognition processing is performed.

(354) The recognition processing by the recognition section **73** is processed in time series in units of components. The component indicates, for example, recognition processing for each recognition target, and is set, for example, for each recognition target such as recognizing a railroad crossing, recognizing a signal, and recognizing a pedestrian. Therefore, in the object recognition processing by the recognition section **73**, it can be considered that the object recognition processing in units of components having different recognition targets is sequentially executed in time series.

(355) That is, for example, as illustrated in FIG. **14**, a case where the components **C1** and **C2** are executed in time series will be considered. In FIG. **14**, the processing of the component **C1** is performed at times **t11** to **t15**, and the processing of the component **C2** is performed at times **t15** to **t19**.

(356) Furthermore, the processing of each component is performed in units of frames of an image captured by the camera **51**.

(357) That is, in the processing of the component **C1** in FIG. **14**, it is illustrated that the processing of the frame **F1** is performed at times **t11** to **t12**, the processing of the frame **F2** is performed at

times **t12** to **t13**, the processing of the frame **F3** is performed at times **t13** to **t14**, and the processing of the frame **F4** is performed at times **t14** to **t15**.

(358) Furthermore, in the processing of the component **C2** in FIG. **14**, it is illustrated that the processing of the frame **F5** is performed at times **t15** to **t16**, the processing of the frame **F6** is performed at times **t16** to **t17**, the processing of the frame **F7** is performed at times **t17** to **t18**, and the processing of the frame **F8** is performed at times **t18** to **t19**.

(359) Note that, in FIG. **14**, an example of processing for four frames is illustrated in each of the components **C1** and **C2**, but processing for other number of frames may be performed, or the number of frames may not be the same for each component.

(360) In a case where the component **C1** is object recognition processing for recognizing a railroad crossing, for example, when the vehicle is traveling on a highway, there is no railroad crossing, and no railroad crossing is detected as a recognition result. Therefore, the object recognition processing of the component **C1** is substantially unnecessary.

(361) For this reason, even if the accuracy of the recognition result of the component **C1** is extremely lowered, a malfunction due to the recognition result does not occur.

(362) Therefore, for the component **C1** that recognizes a railroad crossing, there is no problem even if the update processing of the recognition section **73** by the update SW is performed without stopping the operation of the object recognition processing of the component **C1** (or the operation control of the control section **201** based on the recognition result of the recognition section **73**) as long as the vehicle is traveling on a highway where there is no railroad crossing.

(363) For this reason, at the timing when the recognition target is not recognized (the possibility of recognition is extremely low), the recognition section **73** may be updated by the update SW in units of components without stopping the operation of the recognition section **73**.

(364) <Update Between Frames>

(365) Moreover, in each frame, imaging processing, transfer processing, and recognition processing are performed in time series.

(366) That is, for example, in the frames **F1** and **F2**, as illustrated in FIG. **15**, imaging processing is performed by the camera **51** at times **t11** to **t31**, transfer processing of imaging data is performed by the camera **51** at times **t31** to **t32**, and recognition processing is performed by the recognition section **73** at times **t32** to **t33**.

(367) Furthermore, in the frame **F2**, imaging processing is performed by the camera **51** at times **t12** to **t34**, transfer processing of imaging data is performed by the camera **51** at times **t34** to **t35**, and recognition processing is performed by the recognition section **73** at times **t35** to **t36**.

(368) For this reason, in the series of recognition processing, since the operation is substantially stopped at the timing when the recognition processing by the recognition section **73** is not actually performed, the operation control based on the recognition result is not affected even if the recognition section **73** is updated by the update SW.

(369) Therefore, as illustrated in FIG. **15**, since the processing of the recognition section **73** is not performed in a period **T11** from the timing of time **t33** at which the recognition processing of the recognition section **73** of the frame **F1** ends to the timing of time **t35** at which the recognition processing of the recognition section **73** of the frame **F2** starts, the period is a timing at which the update can be performed.

(370) As described above, while the series of recognition processing is continued, the update timing may be set such that the recognition section **73** is updated by the update SW at the timing between the frames in which the recognition section **73** does not actually function.

(371) <Update in Processing Block Unit>

(372) Furthermore, since the recognition processing by the recognition section **73** includes a plurality of processing blocks, the update may be performed in units of processing blocks by the update SW at a timing between blocks where the processing is not performed in units of processing blocks.

(373) That is, for example, as illustrated in FIG. 16, in a case where the recognition processing of the frame F1 by the recognition section 73 includes processing blocks B1 to B4, processing of the processing block B1 is performed at times t32 to t51, processing of the processing block B2 is performed at times t52 to t53, processing of the processing block B3 is performed at times t54 to t55, and processing of the processing block B4 is performed at times t56 to t33.

(374) Furthermore, in the recognition processing of the frame F2 by the recognition section 73, the processing of the processing block B1 is performed at times t35 to t57, the processing of the processing block B2 is performed at times t58 to t59, the processing of the processing block B3 is performed at times t60 to t61, and the processing of the processing block B4 is performed at times t62 to t36.

(375) In this case, since the processing of the processing block B1 is not performed in a period T31 from time t51 when the processing of the processing block B1 of the frame F1 ends to when the processing of the processing block B1 of the frame F2 starts, the operation of the processing block B1 is substantially stopped, and thus, the period is a timing at which the update can be performed.

(376) As described above, while the series of recognition processing is continued, the recognition section 73 may be updated in units of processing blocks by the update SW at the timing between the processing blocks in which the recognition section 73 does not actually function.

(377) <Update in Layer Unit>

(378) In a case where each of the processing blocks constituting the recognition processing of the recognition section 73 is constituted by a neural network, updating may be performed in units of specific layers in the processing block.

(379) That is, as illustrated in FIG. 17, update of the processing block B1 is considered in a case where each of the processing blocks B1 to B4 is constituted by, for example, a neural network including layers L1 to Lx.

(380) In this case, in the case of the processing block B1, as illustrated in FIG. 17, the layer Lx of the processing block B1 may be updated in units of layers at the first timing in the period T31 similar to the updatable timing between the processing blocks, and thereafter, may be sequentially updated in units of layers, such as the layers Lx-1, Lx-2, . . . , L1, at similar timing. Note that, although FIG. 17 illustrates an example in which the update by the update SW is performed in units of one layer, the update by the update SW may be performed in units of a plurality of layers.

(381) In the case of the processing block constituted by the neural network, the update by the update SW may be further performed in units of channels in the layer. In this case, the update may be performed in units of one channel or in units of a plurality of channels.

(382) Furthermore, in this case, since the update is performed in units of layers or in units of channels, layers or channels having different versions may be mixed in the same processing block.

14. Update Processing for Each Processing Unit

(383) Next, update processing for each processing unit in the application example will be described with reference to the flowchart of FIG. 18.

(384) Note that the processing of steps S201 to S204, S206, S207, and S209 to S217 and steps S234 to S240 and S242 in the flowchart of FIG. 18 is similar to the processing of steps S91 to S94, S96, S97, and S99 to S107 and steps S125 to S131 and S134 in the flowchart of FIG. 11, and thus description thereof is omitted.

(385) That is, in step S204, when an unprocessed vehicle among the vehicles 1 of the group i is set as the processing target vehicle, in step S205, the distribution planning section 235 executes the processing unit setting processing, sets the update unit for updating the recognition section 73 by the update SW of the processing target vehicle, and sets the update timing according to the update unit.

(386) <Processing Unit Decision Processing>

(387) Here, the processing unit decision processing will be described with reference to the flowchart of FIG. 19.

(388) In step **S271**, the distribution planning section **235** determines whether or not the processing is the update processing in which the processing unit updated by the update SW is a channel unit.

(389) In step **S271**, in a case where the processing is the update processing in which the processing unit updated by the update SW is a channel unit, the process proceeds to step **S272**.

(390) In step **S272**, the distribution planning section **235** sets the update timing when the processing unit is a channel unit.

(391) In step **S271**, in a case where the processing is not the update processing in which the processing unit updated by the update SW is a channel unit, the process proceeds to step **S273**.

(392) In step **S273**, the distribution planning section **235** determines whether or not the processing is the update processing in which the processing unit updated by the update SW is a layer unit.

(393) In step **S273**, in a case where the processing is the update processing in which the processing unit updated by the update SW is a layer unit, the process proceeds to step **S274**.

(394) In step **S274**, the distribution planning section **235** sets the update timing when the processing unit is a layer unit, as described with reference to FIG. **17**.

(395) In step **S273**, in a case where the processing is not the update processing in which the processing unit updated by the update SW is a layer unit, the process proceeds to step **S275**.

(396) In step **S275**, the distribution planning section **235** determines whether or not the processing is the update processing in which the processing unit updated by the update SW is a block unit.

(397) In step **S275**, in a case where the processing is the update processing in which the processing unit updated by the update SW is a block unit, the process proceeds to step **S276**.

(398) In step **S276**, the distribution planning section **235** sets the update timing when the processing unit is a block unit, as described with reference to FIG. **16**.

(399) In step **S275**, in a case where the processing is not the update processing in which the processing unit updated by the update SW is a block unit, the process proceeds to step **S277**.

(400) In step **S277**, the distribution planning section **235** determines whether or not the processing is the update processing in which the processing unit updated by the update SW is between frames.

(401) In step **S277**, in a case where the processing is the update processing in which the processing unit updated by the update SW is a frame unit, the process proceeds to step **S278**.

(402) In step **S278**, the distribution planning section **235** sets the update timing when the processing unit is between frames, as described with reference to FIG. **15**.

(403) In step **S277**, in a case where the processing is not the update processing in which the processing unit updated by the update SW is between frames, the process proceeds to step **S279**.

(404) In step **S279**, the distribution planning section **235** determines whether or not the processing is the update processing in which the processing unit updated by the update SW is a component unit.

(405) In step **S279**, in a case where the processing is the update processing in which the processing unit updated by the update SW is a component unit, the process proceeds to step **S280**.

(406) In step **S280**, the distribution planning section **235** sets the update timing when the processing unit is a component unit, as described with reference to FIG. **14**.

(407) In step **S279**, in a case where the processing is not the update processing in which the processing unit updated by the update SW is a component unit, the process proceeds to step **S281**.

(408) Since the processing in step **S281** is not the update in any processing unit of a channel unit, a layer unit, a block unit, between frames, and a component unit, the processing is processing assuming a state in which the recognition section **73** is stopped with the entire recognition section **73** as a unit. Therefore, the distribution planning section **235** sets the update timing by executing the update timing setting processing similar to step **S99** in the flowchart of FIG. **11**.

(409) Here, the description returns to the flowchart of FIG. **18**.

(410) Then, at the timing at which the update processing by the update SW set for each processing unit is performed in step **S207**, the update SW for executing the update of the recognition section **73** in each processing unit is transmitted to the vehicle **1** in the processing of step **S208**.

(411) When it is determined in step S231 that the update SW is transmitted, in step S232, the update section 204 controls the communication section 22 to acquire the update SW corresponding to the transmitted processing unit, and updates the recognition section 73. At this time, before performing the update by the update SW, the update section 204 holds the recognition section 73 before the update for backup.

(412) Note that, in the update processing of FIG. 18, as in the processing of step S122 in the update processing of FIG. 11, both the operation related to the object recognition processing of the recognition section 73 and the operation control based on the recognition result of the recognition section 73 in the control section 201 are not stopped, and the operation is continued.

(413) In step S233, the update section 204 confirms that the recognition section 73 has been reliably updated.

(414) At this time, for example, in a case where the update processing is performed in units of components, between frames, in units of blocks, in units of layers, or in units of channels, the update section 204 may compare the recognition result of the recognition section 73 before the update with the recognition result of the recognition section 73 after the update to determine whether or not there is a change of a predetermined level or more, thereby determining whether or not the update has been appropriately performed.

(415) Furthermore, when the operation status of the recognition section 73 after the update is recognized, the operation status is transmitted to the server 2 as necessary, and it is determined that the determination of the operation status is sufficient, the process proceeds to step S240.

(416) In step S240, the update section 204 determines whether or not the update of the recognition section 73 by the update SW is appropriate.

(417) In a case where it is determined in step S240 that the update of the recognition section 73 by the update SW is not appropriate, the process proceeds to step S241.

(418) In step S241, the update section 204 returns to the operation to the state of the recognition section 73 before update held for backup, and brings the operation related to the object recognition processing of the recognition section 73 before update and the operation control based on the recognition result of the recognition section 73 before update in the control section 201 to the state before update. That is, in this case, the recognition section 73 is not updated, and the operation in the state before the update is continued.

(419) That is, in this case, since the update by the update SW of the recognition section 73 is not appropriate, it is considered that the reliability of the recognition result of the recognition section 73 after the update is low. For this reason, if the processing based on the recognition result of the recognition section 73 after the update is performed, there is a possibility that erroneous processing based on erroneous detection is performed and dangerous operation is caused. Therefore, the operation is returned to the operation based on the recognition result of the recognition section 73 before the update.

(420) Furthermore, in a case where it is determined that the update of the recognition section 73 by the update SW is not appropriate, instead of the processing of step S241, a state may be made in which the processing based on the recognition result of the recognition section 73 after the update by the update SW is not performed in the control section 201.

(421) Meanwhile, in a case where it is determined in step S240 that the update of the recognition section 73 by the update SW is appropriate, the processing of step S241 is skipped.

(422) That is, since the operation of the recognition section 73 is updated without being stopped and the update is appropriately performed, the operation is continued as it is.

(423) With the series of processing described above, the update processing of the recognition section 73 by the update SW can be executed with the timing set for each processing unit, so that the operation of the object recognition processing in the recognition section 73 can be appropriately updated without being stopped.

(424) Note that, in the above description, the update processing (hereinafter, also referred to as

non-operation update processing) for implementing the update processing by the update SW in a state where the object recognition processing in the recognition section **73** is stopped, which has been described with reference to the flowchart of FIG. **11**, and the update processing (hereinafter, also referred to as operation update processing) for implementing the update processing by the update SW in a state where the object recognition processing in the recognition section **73** is stopped, which has been described with reference to the flowchart of FIG. **18**, have been described.

(425) Regarding the non-operation update processing and the operation update processing, it is generally considered that the non-operation update processing is safer, but the operation update processing can update almost at any time. Therefore, the non-operation update processing and the operation update processing may be switched.

(426) For example, the non-operation update processing may be performed within a predetermined period after the distribution of the update SW is started, and the operation update processing may be performed in a case where the update cannot be performed within the predetermined period.

(427) Furthermore, for example, a score indicating urgency or priority according to the update content of the recognition section **73** by the update SW may be set, and the non-operation update processing may be performed in a case of an update with urgency or priority lower than a predetermined score, and the operation update processing may be performed in a case of an update with urgency or priority higher than a predetermined score.

(428) Moreover, the score indicating urgency or priority may be changed according to the automated driving plan or the like. For example, the non-operation update processing may be performed by setting the score indicating urgency or priority lower for the update processing of the recognition section **73** related to the function that is not scheduled to be used in the automated driving plan, and the operation update processing may be performed by setting the score indicating urgency or priority higher for the update processing of the recognition section **73** related to the function that is scheduled to be used in the automated driving plan.

(429) Moreover, as the plan made in the automated driving plan is changed, for example, the non-operation update processing may be performed by changing the setting so that the score indicating urgency or priority becomes lower for the update processing of the recognition section **73** related to the function that is not scheduled to be used in accordance with the change of the automated driving plan, and the operation update processing may be performed by changing the setting so that the score indicating urgency or priority becomes higher for the update processing of the recognition section **73** related to the function that is scheduled to be used in accordance with the change of the automated driving plan.

(430) Note that, in the above, an example has been described in which the managed software program (SW) is the recognition section **73** that executes the object recognition processing and recognizes an object. However, as long as the SW is generated by machine learning or the like, the SW may execute other processing. For example, the SW may be an SW that executes a route search formed by machine learning or an SW that implements battery management.

15. Example Executed by Software

(431) Meanwhile, the above-described series of processing can be executed by hardware, but can also be executed by software. In a case where the series of processing is executed by software, a program constituting the software is installed from a recording medium to a computer incorporated in dedicated hardware or, for example, a general-purpose computer or the like capable of executing various functions by installing various programs.

(432) FIG. **20** illustrates a configuration example of a general-purpose computer. The personal computer includes a central processing unit (CPU) **1001**. An input/output interface **1005** is connected to the CPU **1001** via a bus **1004**. A read only memory (ROM) **1002** and a random access memory (RAM) **1003** are connected to the bus **1004**.

(433) The input/output interface **1005** is connected with an input section **1006** including an input device such as a keyboard, a mouse, or the like with which a user inputs an operation command, an

output section **1007** that outputs an image of a processing operation screen or a processing result to a display device, a storage section **1008** including a hard disk drive or the like that stores programs or various data, and a communication section **1009** including a local area network (LAN) adapter or the like that executes communication processing via a network represented by the Internet. Furthermore, a drive **1010** that reads and writes data from and to a removable storage medium **1011** such as a magnetic disk (including a flexible disk), an optical disk (including a compact disc-read only memory (CD-ROM) and a digital versatile disc (DVD)), a magneto-optical disk (including a mini disc (MD)), a semiconductor memory, or the like is connected.

(434) The CPU **1001** executes various processes according to programs stored in the ROM **1002** or programs read from the removable storage medium **1011** such as a magnetic disk, an optical disk, a magneto-optical disk, a semiconductor memory, or the like installed in the storage section **1008**, and loaded from the storage section **1008** to the RAM **1003**. The RAM **1003** also appropriately stores data and the like necessary for the CPU **1001** to execute various processes.

(435) In the computer configured as described above, for example, the CPU **1001** loads a program stored in the storage section **1008** into the RAM **1003** via the input/output interface **1005** and the bus **1004** and executes the program, whereby the above-described series of processing is performed.

(436) The program executed by the computer (CPU **1001**) can be provided by being recorded in the removable storage medium **1011** as a package medium or the like, for example. Furthermore, the program can be provided via a wired or wireless transmission medium such as a local area network, the Internet, or digital satellite broadcasting.

(437) In the computer, the program can be installed in the storage section **1008** via the input/output interface **1005** by attaching the removable storage medium **1011** to the drive **1010**. Furthermore, the program can be received by the communication section **1009** via a wired or wireless transmission medium and installed in the storage section **1008**. In addition, the program can be installed in the ROM **1002** or the storage section **1008** in advance.

(438) Note that the program executed by the computer may be a program in which processing is performed in time series in the order described in the present specification, or may be a program in which processing is performed in parallel or at necessary timing such as when a call is made or the like.

(439) Note that the CPU **1001** in FIG. **20** implements the functions of the processor **21** in FIG. **3** and the processor **111** in FIG. **5**.

(440) Furthermore, in the present specification, a system means a set of a plurality of components (devices, modules (parts), or the like), and it does not matter whether or not all the components are in the same housing. Therefore, a plurality of devices housed in separate housings and connected via a network and one device in which a plurality of modules is housed in one housing are both systems.

(441) Note that the embodiments of the present disclosure are not limited to the above-described embodiments, and various modifications can be made without departing from the gist of the present disclosure.

(442) For example, the present disclosure can have a configuration of cloud computing in which one function is shared and processed in cooperation by a plurality of devices via a network.

(443) Furthermore, each step described in the above-described flowchart can be executed by one device or can be shared and executed by a plurality of devices.

(444) Moreover, in a case where a plurality of processes is included in one step, the plurality of processes included in the one step can be executed by one device or can be shared and executed by a plurality of devices.

(445) Note that the present disclosure can also have the following configurations.

(446) <1> An information processing apparatus including an update section that updates a software program (SW) of a moving apparatus for each processing unit constituting the SW.

(447) <2> The information processing apparatus according to <1>, in which the SW is formed by machine learning, and the update section updates the SW using an update SW for updating the SW to the SW relearned by the machine learning.

(448) <3> The information processing apparatus according to <2>, in which the SW is an SW that is formed by machine learning and functions as an object recognition section that executes object recognition processing based on an image.

(449) <4> The information processing apparatus according to <3>, in which the update section updates the SW in units of components constituting the SW.

(450) <5> The information processing apparatus according to <4>, in which the update section updates the SW of a component in which a predetermined object is not to be recognized by the object recognition processing among components constituting the SW.

(451) <6> The information processing apparatus according to <3>, in which the update section updates the SW at a predetermined timing between frames of the image captured.

(452) <7> The information processing apparatus according to <6>, in which the update section updates the SW at a timing at which the SW does not operate between frames of the image captured.

(453) <8> The information processing apparatus according to <6>, in which the SW includes a plurality of processing blocks, and the update section updates a predetermined processing block of the SW at a timing at which the predetermined processing block does not operate between frames of the image captured.

(454) <9> The information processing apparatus according to <8>, in which the processing block includes a neural network, and the update section updates a predetermined layer in the predetermined processing block of the SW at a timing at which the predetermined processing block does not operate between frames of the image captured.

(455) <10> The information processing apparatus according to <9>, in which the update section updates a predetermined channel in the predetermined layer in the predetermined processing block of the SW at a timing at which the predetermined processing block does not operate between frames of the image captured.

(456) <11> The information processing apparatus according to <3> to <10>, further including a control section that controls an operation on the basis of an object recognition result of the SW, in which the control section stops control of the operation based on the object recognition result of the updated SW that functions as the object recognition section on the basis of an operation status of the SW.

(457) <12> The information processing apparatus according to <11>, in which the control section controls the operation on the basis of the object recognition result of the SW that functions as the object recognition section before update on the basis of the operation status of the SW.

(458) <13> The information processing apparatus according to <11>, in which the moving apparatus is a vehicle, and the control section controls automated driving of the vehicle on the basis of the object recognition result of the SW that functions as the object recognition section.

(459) <14> The information processing apparatus according to <13>, in which the update section acquires the update SW for updating the SW distributed from a server, and updates the SW on the basis of the update SW.

(460) <15> The information processing apparatus according to <14>, in which the server groups the information processing apparatus that distribute the update SW on the basis of safety related to control of the automated driving of the vehicle based on the object recognition result of the SW in a case where the SW is not appropriately updated by the update SW, and sequentially and stepwise distributes the update SW in units of groups from the information processing apparatuses of a safest group.

(461) <16> The information processing apparatus according to <15>, in which the server generates a distribution plan that is a timing of distributing the update SW to the information processing

apparatus in units of groups grouped on the basis of the safety.

(462) <17> The information processing apparatus according to <14>, in which the server distributes the update SW for updating the SW to the relearned state when the SW relearned reaches predetermined recognition accuracy on the basis of the image and the corresponding object recognition result.

(463) <18> An information processing method including the step of updating a software program (SW) of a moving apparatus for each processing unit constituting the SW.

(464) <19> A program for causing a computer to function as an update section that updates a software program (SW) of a moving apparatus for each processing unit constituting the SW.

(465) <20> An information processing system including an update section that updates a software program (SW) of a moving apparatus for each processing unit constituting the SW.

REFERENCE SIGNS LIST

(466) **1** Vehicle **2** Server **21** Processor **22** Communication section **23** Map information accumulation section **24** GNSS reception section **25** External recognition sensor **32** Vehicle control section **51** Camera **73** Recognition section **201** Control section **202** Operation status recognition section **203** Operation status reporting section **204** Update section **231** Vehicle information collection section **232** Grouping section **233** Distribution order decision section **234** Distribution status confirmation section **235** Distribution planning section **236** Distribution section **237** Relearning section **238** Update SW release section

Claims

1. An information processing apparatus, comprising: a central processing unit (CPU) configured to: recognize a first object based on a specific image, wherein each of the first object and the specific image is associated with a moving apparatus; control an automated driving of the moving apparatus based on the recognized first object; acquire an update software program (SW) from a server; update, based on the update SW, a first SW for each of a plurality of components in time-series, wherein the first SW is associated with the moving apparatus, the plurality of components includes the first SW, the server classifies a plurality of information processing apparatuses into groups based on a safety of the moving apparatus and the control of the automated driving of the moving apparatus, and the plurality of information processing apparatuses includes the information processing apparatus; and update a first component of the plurality of components at a first timing based on an operation on the moving apparatus, wherein the first component includes the first SW, and the first timing is a timing at which the first component is not executed.

2. The information processing apparatus according to claim 1, wherein the first SW is based on machine learning, the CPU is further configured to update the first SW to a second SW based on the update SW, and the second SW corresponds to the first SW relearned by the machine learning.

3. The information processing apparatus according to claim 2, wherein the CPU is further configured to recognize the first object based on the second SW and the specific image.

4. The information processing apparatus according to claim 3, wherein the CPU is further configured to update a third SW associated with a second component of the plurality of components, the second component includes the third SW, and the second component is associated with a second object that is not to be recognized.

5. The information processing apparatus according to claim 3, wherein the CPU is further configured to update the first SW at a second timing, and the second timing is between frames of the specific image.

6. The information processing apparatus according to claim 5, wherein the CPU is further configured to update the first SW at a third timing at which the first component does not operate between the frames of the specific image.

7. The information processing apparatus according to claim 5, wherein the first SW includes a

plurality of processing blocks, the CPU is further configured to update a specific processing block of the plurality of processing blocks at a third timing, and the specific processing block does not operate between the frames of the specific image at the third timing.

8. The information processing apparatus according to claim 7, wherein the specific processing block includes a neural network, and the CPU is further configured to update a specific layer in the specific processing block at the third timing.

9. The information processing apparatus according to claim 8, wherein the CPU is further configured to update a specific channel in the specific layer at the third timing.

10. The information processing apparatus according to claim 3, wherein the CPU is further configured to: control the operation based on the recognized first object; determine, based on the specific image, an operation status associated with the recognized first object; stop the control of the operation based on the recognized first object associated with the updated first SW; and recognize the first object based on the operation status of the first SW.

11. The information processing apparatus according to claim 10, wherein the CPU is further configured to: control the operation based on the recognized first object associated with the first SW; and recognize the first object before the determination of the operation status.

12. The information processing apparatus according to claim 10, wherein the moving apparatus is a vehicle.

13. The information processing apparatus according to claim 12, wherein the control of the automated driving of the vehicle is based on the first SW not appropriately updated by the update SW, and the update SW is sequentially and stepwise distributed to a safest group of the groups.

14. The information processing apparatus according to claim 13, wherein the safest group comprises a set of information processing apparatuses of the plurality of information processing apparatuses, the update SW is distributed based on a distribution plan, the distribution plan is associated with a second timing, and the second timing is associated with the distribution of the update SW to the set of information processing apparatuses.

15. The information processing apparatus according to claim 1, wherein the update SW is distributed based on a specific recognition accuracy associated with the first SW, and the specific recognition accuracy is based on the specific image and the recognized first object.

16. An information processing method, comprising: recognizing an object based on a specific image, wherein each of the object and the specific image is associated with a moving apparatus; controlling an automated driving of the moving apparatus based on the recognized object; acquiring an update software program (SW) from a server; updating, based on the update SW, a specific SW for each of a plurality of components in time-series, wherein the specific SW is associated with the moving apparatus, the plurality of components includes the specific SW, and the server classifies a plurality of information processing apparatuses into groups based on a safety of the moving apparatus and the control of the automated driving of the moving apparatus; and updating a specific component of the plurality of components at a specific timing based on an operation on the moving apparatus, wherein the specific component includes the specific SW, and the specific timing is a timing at which the specific component is not executed.

17. A non-transitory computer-readable medium having stored thereon, computer-executable instructions which, when executed by a computer, cause the computer to execute operations, the operations: recognizing an object based on a specific image, wherein each of the object and the specific image is associated with a moving apparatus; controlling an automated driving of the moving apparatus based on the recognized object; acquiring an update software program (SW) from a server; updating, based on the update SW, a specific SW for each of a plurality of components in time-series, wherein the specific SW is associated with the moving apparatus, the plurality of components includes the specific SW, and the server classifies a plurality of information processing apparatuses into groups based on a safety of the moving apparatus and the control of the automated driving of the moving apparatus; and updating a specific component of the

plurality of components at a specific timing based on an operation on the moving apparatus, wherein the specific component includes the specific SW, and the specific timing is a timing at which the specific component is not executed.

18. An information processing system, comprising a server; and an information processing apparatus that includes a central processing unit (CPU), wherein the CPU is configured to: recognize an object based on a specific image, wherein each of the object and the specific image is associated with a moving apparatus; control an automated driving of the moving apparatus based on the recognized object; acquire an update software program (SW) from the server; update, based on the update SW, a specific SW for each of a plurality of components in time-series, wherein the specific SW is associated with the moving apparatus, and the plurality of components includes the specific SW; and update a specific component of the plurality of components at a specific timing based on an operation on the moving apparatus, wherein the specific component includes the specific SW, the specific timing is a timing at which the specific component is not executed, the server is configured to classify a plurality of information processing apparatuses into groups based on a safety of the moving apparatus and the control of the automated driving of the moving apparatus, and the plurality of information processing apparatuses includes the information processing apparatus.

19. The information processing apparatus according to claim 1, wherein the control of the automated driving of the moving apparatus is based on the first SW not appropriately updated by the update SW, and the update SW is sequentially and stepwise distributed to a safest group of the groups.

20. The information processing apparatus according to claim 19, wherein the safest group comprises a set of information processing apparatuses of the plurality of information processing apparatuses, the update SW is distributed based on a distribution plan, the distribution plan is associated with a second timing, and the second timing is associated with the distribution of the update SW to the set of information processing apparatuses.
