

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400159
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Donovan; William Randall et al.

Delegation of tasks in an enterprise environment

Abstract

Disclosed are various embodiments for delegating tasks in an enterprise service. A user can associate an action or task within the enterprise service with a delegate. The user can also specify temporal restrictions with the delegation of the task. The temporal restrictions specified time limitations on the authority of the delegate.

Inventors: Donovan; William Randall (Brooklyn, NY), Heasman; Nicholas (Sarasota, FL), Palanikumar; Prasannakumar (New York, NY)

Applicant: ADP, Inc. (Roseland, NJ)

Family ID: 1000008777869

Assignee: ADP, Inc. (Roseland, NJ)

Appl. No.: 18/057046

Filed: November 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240169289 A1	May. 23, 2024

Publication Classification

Int. Cl.: G06Q10/00 (20230101); G06Q10/0631 (20230101); G06Q10/1057 (20230101)

U.S. Cl.:

CPC G06Q10/06312 (20130101); G06Q10/1057 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0064280	12/2008	Babeanu	726/3	G06Q 10/06
2015/0220649	12/2014	Papa	707/722	G06F 16/9535
2015/0269854	12/2014	Maharaj	434/353	G09B 5/08
2016/0155135	12/2015	Papa	726/28	G06Q 40/04
2016/0292601	12/2015	Pakanathi	N/A	H04L 63/101
2018/0075413	12/2017	Culver	N/A	G06Q 10/103
2018/0129995	12/2017	Fowler	N/A	G06F 3/0482
2019/0213528	12/2018	Gupta	N/A	G06Q 10/10
2019/0259038	12/2018	Papa	N/A	G06F 21/62
2020/0394595	12/2019	Fowler	N/A	G06Q 10/06312
2020/0410133	12/2019	Barday	N/A	H04L 63/20
2023/0071115	12/2022	Matsuoka	N/A	G06Q 10/06316
2023/0090862	12/2022	Cupersmith	701/2	B25J 11/008
2023/0169440	12/2022	VanBuskirk	705/7.42	H04L 12/4625
2024/0086859	12/2023	Gillam	N/A	G06Q 10/1095

OTHER PUBLICATIONS

Managing App Approval for Your Workspace, Sep. 8, 2016, Slack,
<https://slack.com/help/articles/222386767-Manage-app-approval-for-your-workspace>, p. 1-5. (Year: 2016). cited by examiner

Primary Examiner: Waesco; Joseph M

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

BACKGROUND

(1) In an enterprise environment, certain users can be tasked with approving or denying requests of various types. For example, a user in a managerial or supervisory role can be tasked with approving or denying requests for vacation from workers associated with the enterprise. As another example, a user can be tasked with approving or denying requests for changes to the compensation of workers in the enterprise. As yet another example, a user can be tasked with approving or denying requests for reimbursement of expense report for workers associated with the enterprise.

Accordingly, certain users associated with an enterprise can be tasked with all manner of requests for approval or denial of requests from or on behalf of other users in the enterprise. If a user in this role is unavailable to approve or deny requests, these requests can cause delays or other issues within the organization.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Many aspects of the present disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, with emphasis instead being placed upon clearly illustrating the principles of the disclosure. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

(2) FIGS. 1A-1B illustrate example user interfaces for client devices, according to various embodiments of the present disclosure.

(3) FIG. 2 is a drawing of a networked environment according to various embodiments of the present disclosure.

(4) FIG. 3A-3D illustrate example user interfaces according to various embodiments of the present disclosure.

(5) FIG. 4 is a flowchart illustrating one example of functionality implemented as portions of a delegation service executed in a computing environment in the networked environment of FIG. 2 according to various embodiments of the present disclosure.

DETAILED DESCRIPTION

(6) The present disclosure relates to delegating tasks among users in an enterprise. Delegation of tasks can be discretely defined to link a particular action in an enterprise system with a set of temporal restrictions and one or more delegates of a user. Additionally, according to examples of the disclosure, the act of delegating a task to another user can be performed for any action in an enterprise system where a decision is sought from a primary deciding user. In this way, delegation logic need not be built into the logic or process that defines the action. Instead, any action can leverage the generalized delegation logic according to examples of the disclosure to delegate a decision or action in an enterprise application or service.

(7) In many cases, employers have human resources (HR) systems that enable various features. For example, an HR system can allow employees, contractors, or other users associated with an enterprise to perform various HR-related tasks and receive HR services. The HR system can operate as a portal for compensation, vacation, employee benefits, time or attendance tracking, and other services associated with employees and/or contractors of an enterprise.

(8) The HR system can allow to managers or supervisory users to interact with employees and contractors as well as to service various requests on behalf of other users in an organization. For example, the HR system can allow for employees to submit requests for vacation or sick leave. Such a request might be required to be approved or denied by the employee's supervisor or manager. In some cases, a supervisory or managerial user might have a large number of requests that require review and approval or denial. Additionally, the supervisory or managerial user might be unavailable to review the requests. In this scenario, a delegation framework can be desirable that allows delegates of the supervisory user to approve or deny requests on behalf of the user.

(9) Examples of the disclosure provide a delegation framework in which supervisory users can delegate a task requiring a decision to one or more other users in the HR system. The delegation can also include temporal limitations that define a time period during which the other users are authorized to make a decision on behalf of the delegating user. The delegation framework does not allow the other users to log into the HR system as the delegating user. Instead, the delegation framework only permits delegates to make a decision regarding a task but do so under their own respective identifies within the HR system.

(10) Accordingly, the delegating user can define a delegation that identifies one or more delegates as well as the task or action that the delegate is authorized to act upon on behalf of the delegating user. The delegating user can also define a time period during which the delegates are authorized to act on behalf of the delegating user. Examples of the disclosure can provide various user interfaces through which the delegating user and the delegate can access the HR system to setup delegation of a task as well as act upon a delegated task. In the following discussion, a general description of the

system and its components is provided, followed by a discussion of the operation of the same.

(11) FIG. 1A is an example of a management user interface **100** for viewing employee profiles. Presently, the management user interface **100** illustrates a user profile for a user, illustrated as the user “Jane Doe.” The management user interface **100** can represent a view into an HR system that can be accessed by the user. The user can be associated with a user account within the HR system. (12) The management user interface **100** can display one or more tasks in a task section **103** and potentially other suitable elements which are not shown and are not necessary for an understanding of examples of the disclosure. The task section **103** can list or categorize the tasks requiring approval or grant by the user. For example, as shown in the example of FIG. 1A, the HR system can generate a user interface that shows the approval tasks that are in a task queue associated with a user account. The task queue can contain the various tasks within the HR system that require review or approval by a user. The task queue can be presented in various ways. In one example, as shown in FIG. 1A, the task queue can be categorized by the type of request. In another example, the task queue can be presented chronologically.

(13) The task section **103** can also provide a visual indicator of how many tasks require review and/or approval by the user. The visual indicator can show a quantity of each category of task that requires action by the user, as shown in the example of FIG. 1A. The user can select one of the categories of tasks from the task section **103** to view the tasks requiring review and approval. (14) Continuing the example of FIG. 1A, reference is made to FIG. 1B. In the management user interface **100** shown in FIG. 1B, the user has selected one of the categories of tasks from the task section **103** of FIG. 1A. Accordingly, in FIG. 1B, a task list user interface **109** can be shown, which lists the requests that require action by the user. The user can then select a request, review the request, and either approve or deny the request based upon the data within the request.

(15) Accordingly, managing a potentially constant inflow of requests that require review and/or approval by a user can result in a backlog of requests that do not get handled in a timely manner. Therefore, examples of the disclosure can provide a framework for delegation of tasks in an HR system so that users can delegate the authority to approve or deny requests to one or more other users of the HR system. Additionally, examples of the disclosure can allow for temporal restrictions to be placed on the delegation of the authority to approve or deny requests.

(16) With reference to FIG. 2, shown is a networked environment **200** according to various embodiments. The networked environment **200** includes a computing environment **203**, and one or more client devices **206**, which are in data communication with each other via a network **215**. The network **215** includes, for example, the Internet, intranets, extranets, wide area networks (WANs), local area networks (LANs), wired networks, wireless networks, or other suitable networks, etc., or any combination of two or more such networks. For example, such networks may comprise satellite networks, cable networks, Ethernet networks, and other types of networks.

(17) The computing environment **203** may include, for example, a server computer or any other system providing computing capability. Alternatively, the computing environment **203** may employ a plurality of computing devices that may be arranged, for example, in one or more server banks or computer banks or other arrangements. Such computing devices may be located in a single installation or may be distributed among many different geographical locations. For example, the computing environment **203** may include a plurality of computing devices that together may comprise a hosted computing resource, a grid computing resource and/or any other distributed computing arrangement. In some cases, the computing environment **203** may correspond to an elastic computing resource where the allotted capacity of processing, network, storage, or other computing-related resources may vary over time.

(18) Various applications and/or other functionality may be executed in the computing environment **203** according to various embodiments. The components executed on the computing environment **203**, for example, may include a delegation service **221**, an enterprise service **223**, and other applications, services, processes, systems, engines, or functionality not discussed in detail herein.

The enterprise service **223** can include, for example, an HR service. The enterprise service **223** can also include other types of network accessible services that can service multiple users over a network **215**. For example, the enterprise service **223** can include an email service, an enterprise resource planning (ERP) service, a customer relationship management (CRM) service, or any other type of service that can serve multiple users.

(19) The delegation service **221** can be executed to facilitate delegation of tasks between users of the enterprise service **223**. In some examples, the delegation service **221** can represent a standalone service that is separate from the enterprise service **223** or as a module or functionality that is integrated into the enterprise service **223**. The delegation service **221** can allow users to define tasks that can be delegated to other users or user groups who are also users of the enterprise service **223**. The delegation service **221** can also allow users to specify temporal limitations on the delegation of tasks to other users. In some examples, the delegation service **221** can automatically discover tasks that can be delegated to other users based upon whether a given user is out-of-office or is failing to respond to requests in a timely manner.

(20) Various data is stored in a data store **225** that is accessible to the computing environment **203**. The data store **225** may be representative of a plurality of data stores **225** as can be appreciated. The data stored in the data store **225**, for example, is associated with the operation of the various applications and/or functional entities described below. In some embodiments, the data store **225** can also represent a search index database for identifying user profiles **228** based at least in part on a search query. For example, the search query can include items (e.g., search criteria) for identifying a user profile stored in the data store **225**. The search index data can include an index that associates the user profile **228** with the data associated with the user profile **228**. The data stored in the data store **225** includes, for example, user profiles **228**, and potentially other data. The user profile **228** can represent a user account for a user at a company. The user profile **228** can include profile data **233**, a task queue **236**, delegate data **239**, a user identifier **230**, and other suitable data.

(21) The user identifier **230** can represent a unique identifier for each user profile **228**. In some examples, the user identifier **230** can be an alphanumeric character string, a data signature, a device signature, or other suitable identifiers. In some embodiments, the data signature can include a set of unique data for the user (e.g., hire data, social security number, employee number or identifier, residence location, etc.). The device signature for a user can include one or more of an internet protocol (IP) address, a device identifier of a client device **206**, a device type, an operating system version, a set of installed applications, and other suitable unique data for a user.

(22) The profile data **233** can represent background information, such as the user's name, title, hiring date, company department, and other suitable information. The profile data **233** can also include a role of a user within an organization or enterprise. The profile data **233** can also include privileges or authorizations associated with the user, such as what applications or services to which the user has access as well as what actions or requests within the profile data **233** that should be sent to the user for review and/or approval.

(23) For example, the profile data **233** can identify a group of users for whom a given user is a manager or supervisor and for whom certain requests should be sent to review. The requests can include vacation requests, requests to edit compensation, a working schedule, a change in employee or contractor status, a change to a role within an organization, or any other request that can be made by or on behalf of another user. In some examples, the enterprise service **223** can rely upon data from a user directory, such as Microsoft ActiveDirectory® in addition to information that can be stored in a user profile **228** to determine a relationship of a given user account to other users within an organization.

(24) In some examples, a profile data **233** can include authentication tokens, credentials, password information, password reset data, certificate data, encryption key data, and other security or authentication-related data that is utilized by the user to access the enterprise service **223** or secure

communications between a client device **206** or the user and the enterprise service **223**.

(25) The task queue **236** can represent a list or queue of tasks that require action by a given user associated with a user account. In the context of this disclosure, tasks in a task queue **236** can represent requests that are made by or on behalf of other users that require review and approval or denial by a user. For example, a user can submit a request time off to the enterprise service **223**. The enterprise service **223** can identify that the request requires approval by one or more other users, such as the user's supervisors or managers. The enterprise service **223** can then create a task that is placed into a task queue **236** or one or more supervisors or managers of the requesting user. The enterprise service **223** can subsequently remove the task from the task queue **236** of the supervisors or managers once the request is either approved or denied.

(26) Delegate data **239** represents information about delegates that are linked to a user account. A delegate of a user is authorized to act upon certain tasks in the task queue **236** of the user. A user can delegate authority to a delegate using user interfaces provided by the enterprise service **223** or the delegation service **221**. The delegating user can identify one or more actions or tasks that are delegated to the delegate. The delegating user can also identify temporal data **241** that specifies time restrictions associated with the delegation of an action or task to the delegate. For example, if a delegating user is scheduled to be on vacation during a time period, the delegating user can specify a delegate for a particular task during the time period. In some cases, the temporal data **241** can merely specify a beginning date but not ending date for the delegation of the task. In this scenario, delegation of the task to the delegate can have an indefinite time period.

(27) Task data **243** represents information about a task that can be delegated using the delegation service **221**. The task data **243** can include a particular action within the **223**. In one scenario, the action can be specified with an API call, a callback uniform resource locator (URL), or any other mechanism by which an action can be programmatically identified by the delegation service **221**. The task data **243** can also include one or more arguments or options to approve or deny a request associated with the action so that the delegation service **221** determine how to programmatically approve or deny the request. The task data **243** can further include information about how a task can be displayed to a user in a user interface so that the delegation service **221** can facilitate creating a user interface in which a delegate can review and act upon a delegated task.

(28) The client device **206** is representative of one or more client devices **206** that may be coupled to the network **215**. The client device **206** may be representative of a client device used by the user and/or a corresponding client devices **206** used by project users. The client device **206** can include any computer system. Examples of computer systems can include a desktop computer, a laptop computer, personal digital assistants, cellular telephones, smartphones, set-top boxes, music players, web pads, tablet computer systems, game consoles, electronic book readers, or other devices with like capability. The client device **206** may include a display **248**. The display **248** may comprise, for example, one or more devices such as liquid crystal display (LCD) displays, gas plasma-based flat panel displays, organic light emitting diode (OLED) displays, electrophoretic ink (E ink) displays, LCD projectors, or other types of display devices, etc.

(29) The client device **206** may be configured to execute various applications such as a client application **251** and/or other applications. The client application **251** is executed to facilitate identifying data for storage in the user profile **228** (e.g., task queue **236** and delegate data **239**). Additionally, the client application **251** may be executed in a client device **206**, for example, to access network content served up by the computing environment **203** and/or other servers, thereby rendering a user interface **253** on the display **248**. To this end, the client application **251** may include a browser, a dedicated application, etc., and the user interface may comprise a network page, an application screen, etc. The client device **206** may be configured to execute applications beyond the client application **251** such as, for example, email applications, social networking applications, word processors, spreadsheets, and/or other applications.

(30) A user can authenticate his or her identity with the enterprise service **223** using the client

application **251**. The enterprise service **223** can provide content to the client application **251**, which can include user interfaces through which the user can review, approve, or deny requests in the task queue **236** of the user. Additionally, the enterprise service **223** can transmit notifications to the client device **206** of a user. Notifications can comprise mobile application notifications provided to the client application **251**, emails, text messages sent via messaging services, push notifications, or other notifications. Notifications can inform a user that tasks are awaiting to the user in their respective task queue **236** or that a request submitted by or on behalf of a user, such as a vacation request, has been approved or denied by another user with the appropriate authority to do so.

(31) Next, a general description of the operation of the various components of the networked environment **200** is provided. To begin, a user of the enterprise service **223** can utilize client application **251** to access the enterprise service **223** to view tasks in a task queue **236** of the user. The user can be a managerial or supervisory user that accesses an HR system to view requests submitted by or on behalf of other users. The requests should be either approved or denied by the user. In one aspect, the user can review or approve these requests on their own. The user can utilize various user interface workflows provided by the enterprise service **223** to do so.

(32) For example, the user can view a task section **103** of a user interface that shows a task list to identify tasks in the task queue **236** of the user. The user can select one or more tasks to review the details associated with a task. The user can then review and either approve or deny a request associated with a task.

(33) In some examples, the user can also set up delegation of a task to one or more other users. A task can be delegated to a user or a user group. A user can be identified using a user identifier within the enterprise service **223** such as an email address, user ID, or other identifier. A user group can also be identified within the enterprise service **223** using a group email address, group identifier, multiple user identifiers, or other identifier that can be used to identify a user group.

(34) The user can also specify temporal data **241** that can be associated with delegation of a task. The temporal data **241** specifies time restrictions associated with the delegation of an action or task to the delegate. For example, if a delegating user is scheduled to be on vacation during a time period, the delegating user can specify a delegate for a particular task during the time period. In some cases, the temporal data **241** can merely specify a beginning date but not ending date for the delegation of the task. In this scenario, delegation of the task to the delegate can have an indefinite time period. Specifying temporal data **241** can be considered optional if a user wishes to indefinitely delegate a task to another user.

(35) Once delegation of a task is setup by a user, the delegation service **221** can add tasks associated with a request submitted by or on behalf of a requesting user to a task queue **236** of the delegating user as well as the delegates specified by the delegating user. As the task is acted upon by the delegating user or the delegates, the task can be removed from the task queue **236** of the delegates and the delegating user.

(36) Additionally, the delegation service **221** or enterprise service **223** can generate notifications that can be sent to the delegates, as well as the delegating user, when a request submitted by or on behalf of a requesting user is received by the enterprise service **223**. Notifications can comprise mobile application notifications provided to the client application **251**, emails, text messages sent via messaging services, push notifications, or other notifications. Notifications can inform a user that tasks are awaiting to the user in their respective task queue **236** or that a request submitted by or on behalf of a user, such as a vacation request, has been approved or denied by another user with the appropriate authority to do so.

(37) Turning now to FIG. 3A, shown is a delegation user interface **301** in which a user can view, edit, and add delegates for various types of tasks. As shown in the delegation user interface **301**, a user can define another user as a delegate. The delegate user can be identified by a user identifier within the enterprise service **223**, such as an email address of the delegate user. The delegating user can further specify temporal restrictions associated with the delegate. The temporal restrictions can

include a start date and an end date of delegation of a specified action. In some examples, the temporal data **241** can specify a particular time of the day in addition to the dates.

(38) Finally, as shown in FIG. 3A, the delegating user can identify one or more actions that can be delegated to the user. The actions can be selected by the user using the delegation user interface **301** generated by the enterprise service **223** or delegation service **221**. In the example shown, multiple actions can be delegated to the delegate by the delegating user. The actions can both be associated with the temporal data **241** specified by the delegating user. In one implementation, multiple entries for each delegated action can be created within the delegate data **239**. In another example, a single entry specifying multiple actions can be created within the delegate data **239**.

(39) In some examples, delegations can be automatically created by obtaining an out of office status of a user. For example, if a user can designate an out of office status, the delegation service **221** can automatically select a delegate for one or more tasks associated with the user based upon a previous delegation of the one or more tasks. In this scenario, if a user has previously delegated a task to another user or user group, the delegation service **221** can automatically create a delegation of the task to the same other user or user group if the user is designated as out of office or unavailable. The out of office or unavailability status of the user can be detected from a user directory service or from another data point from the enterprise service **223**, such as in an HR system directory. In another scenario, the other user or user group to whom a task is delegated can be selected by navigating a user directory to locate a supervisor of the user or a subordinate of the user.

(40) Moving on to FIG. 3B, shown is a delegate user interface **303** that can be rendered on the client device **206**. The delegate user interface **303** can be generated by the delegation service **221** or enterprise service **223** to display delegations that have been given to a delegate. As shown in the delegate user interface **303**, the enterprise service **223** or delegation service **221** can indicate an identity of a delegating user who has delegated one or more tasks to the delegate. Additionally, the delegate user interface **303** can display temporal restrictions associated with each delegation. The temporal restrictions can include a start date and an end date of delegation of a specified action. Finally, as shown in FIG. 3B, the delegate user interface **303** can display the one or more actions that have been delegated to the user. The actions can be selected by the user using the delegation user interface **301** of FIG. 3A.

(41) Moving on to FIG. 3C, shown is a delegate history user interface **305** that can be rendered on the client device **206**. The delegate history user interface **305** can be generated by the delegation service **221** or enterprise service **223** to display an activity history of a user as a delegate. As shown in the delegate history user interface **305**, the enterprise service **223** or delegation service **221** can display a history of previous approvals or denials made on behalf of a delegating user.

(42) Moving on to FIG. 3D, shown is a request result user interface **307** that can be rendered on the client device **206**. The request result user interface **307** can be generated by the delegation service **221** or enterprise service **223** to display a result of a request that was handled by a supervisory user or manager of a requesting user. In some examples, the request can be handled by a delegate of the supervisory user or manager. Accordingly, the request result user interface **307** can indicate that the request was handled by a delegate of the supervisory user or manager.

(43) Referring next to FIG. 4, shown is a flowchart that provides one example of the operation of a portion of the delegation service **221** according to various embodiments. It is understood that the flowchart of FIG. 4 provides merely an example of the many different types of functional arrangements that may be employed to implement the operation of the portion of the delegation service **221** as described herein. As an alternative, the flowchart of FIG. 4 may be viewed as depicting an example of elements of a method implemented in the computing environment **203** (FIG. 2) according to one or more embodiments. The functionality shown in FIG. 4 can also be performed by the enterprise service **223** in some examples.

(44) Beginning with box **401**, the delegation service **221** can identify a task associated with a user

of the enterprise service **223**. The task can be associated with a request made by another user that requires approval or denial by the user. The task can be obtained from a task queue **236** of the user by the delegation service **221**. For example, the task can be associated with a request for vacation, a change in compensation, a change to a working schedule, or any other request that can be made using the enterprise service **223**.

(45) At step **404**, the delegation service **221** can determine that the user account has delegated the task to one or more delegate users. The delegation service **221** can make this determination by consulting delegate data **239** associated with the user account. The delegate data **239** can indicate which tasks of a user have been delegated and to which other users of the enterprise service **223**. Accordingly, the delegation service **221** can determine whether the characteristics of the request associated with the task, including a request type, are consistent with the delegate data **239** associated with the user account.

(46) At step **407**, the delegation service **221** can determine that a timestamp associated with the request linked to the task falls within a start date and end date specified in the temporal data **241**. The temporal data **241** specifies whether the task is delegated during a timestamp associated with the request.

(47) At step **410**, the delegation service **221** can generate a notification that can be transmitted to the delegates identified by the delegate data **239**. The notification can inform the delegates that a delegated task requires action by the delegate. The notification can be sent via email, messaging, a mobile app notification, or through any suitable notification framework.

(48) At step **413**, the delegation service **221** can authenticate a delegate user that has responded to the notification by attempting to take action on the request. The delegation service **221** can verify that the delegate user is authenticated with the delegation service **221** as well as verify that the delegate user is a delegate for the task.

(49) At step **416**, the delegation service **221** can obtain an approval or denial of the request associated with the task. The approval or denial can be obtained through a user interface provided by the delegation service **221** to the delegate user.

(50) At step **419**, once the delegate user approves or denies the request associated with the task, the delegation service **221** can generate a notification informing the subject user associated with the request. The notification can include an indication of whether the request was approved or denied. The notification can also include an indication of the identity of the delegate user that approved or denied the request. Thereafter, the process can proceed to completion.

(51) A number of software components are stored in the memory and are executable by the processor. In this respect, the term “executable” means a program file that is in a form that can ultimately be run by the processor. Examples of executable programs may be, for example, a compiled program that can be translated into machine code in a format that can be loaded into a random access portion of the memory and run by the processor, source code that may be expressed in proper format such as object code that is capable of being loaded into a random access portion of the memory and executed by the processor, or source code that may be interpreted by another executable program to generate instructions in a random access portion of the memory to be executed by the processor, etc. An executable program may be stored in any portion or component of the memory including, for example, random access memory (RAM), read-only memory (ROM), hard drive, solid-state drive, USB flash drive, memory card, optical disc such as compact disc (CD) or digital versatile disc (DVD), floppy disk, magnetic tape, or other memory components.

(52) The memory is defined herein as including both volatile and nonvolatile memory and data storage components. Volatile components are those that do not retain data values upon loss of power. Nonvolatile components are those that retain data upon a loss of power. Thus, the memory may comprise, for example, random access memory (RAM), read-only memory (ROM), hard disk drives, solid-state drives, USB flash drives, memory cards accessed via a memory card reader, floppy disks accessed via an associated floppy disk drive, optical discs accessed via an optical disc

drive, magnetic tapes accessed via an appropriate tape drive, and/or other memory components, or a combination of any two or more of these memory components. In addition, the RAM may comprise, for example, static random access memory (SRAM), dynamic random access memory (DRAM), or magnetic random access memory (MRAM) and other such devices. The ROM may comprise, for example, a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), or other like memory device.

(53) Also, the processor may represent multiple processors and/or multiple processor cores and the memory may represent multiple memories that operate in parallel processing circuits, respectively. In such a case, the local interface may be an appropriate network that facilitates communication between any two of the multiple processors, between any processor and any of the memories, or between any two of the memories, etc. The local interface may comprise additional systems designed to coordinate this communication, including, for example, performing load balancing. The processor may be of electrical or of some other available construction.

(54) Although the applications described herein may be embodied in software or code executed by general purpose hardware as discussed above, as an alternative the same may also be embodied in dedicated hardware or a combination of software/general purpose hardware and dedicated hardware. If embodied in dedicated hardware, each can be implemented as a circuit or state machine that employs any one of or a combination of a number of technologies. These technologies may include, but are not limited to, discrete logic circuits having logic gates for implementing various logic functions upon an application of one or more data signals, application specific integrated circuits (ASICs) having appropriate logic gates, field-programmable gate arrays (FPGAs), or other components, etc. Such technologies are generally well known by those skilled in the art and, consequently, are not described in detail herein.

(55) The flowchart of FIG. 4 shows the functionality and operation of an implementation of portions of various embodiments of the present disclosure. If embodied in software, each block may represent a module, segment, or portion of code that comprises program instructions to implement the specified logical function(s). The program instructions may be embodied in the form of source code that comprises human-readable statements written in a programming language or machine code that comprises numerical instructions recognizable by a suitable execution system such as a processor in a computer system or other system. The machine code may be converted from the source code, etc. If embodied in hardware, each block may represent a circuit or a number of interconnected circuits to implement the specified logical function(s).

(56) Although the flowchart of FIG. 4 shows a specific order of execution, it is understood that the order of execution may differ from that which is depicted. For example, the order of execution of two or more blocks may be scrambled relative to the order shown. Also, two or more blocks shown in succession in FIG. 4 may be executed concurrently or with partial concurrence. Further, in some embodiments, one or more of the blocks shown in FIG. 4 may be skipped or omitted. In addition, any number of counters, state variables, warning semaphores, or messages might be added to the logical flow described herein, for purposes of enhanced utility, accounting, performance measurement, or providing troubleshooting aids, etc. It is understood that all such variations are within the scope of the present disclosure.

(57) Also, any logic or application described herein that comprises software or code can be embodied in any non-transitory computer-readable medium for use by or in connection with an instruction execution system such as, for example, a processor in a computer system or other system. In this sense, the logic may comprise, for example, statements including instructions and declarations that can be fetched from the computer-readable medium and executed by the instruction execution system. In the context of the present disclosure, a “computer-readable medium” can be any medium that can contain, store, or maintain the logic or application described herein for use by or in connection with the instruction execution system.

(58) The computer-readable medium can comprise any one of many physical media such as, for example, magnetic, optical, or semiconductor media. More specific examples of a suitable computer-readable medium would include, but are not limited to, magnetic tapes, magnetic floppy diskettes, magnetic hard drives, memory cards, solid-state drives, USB flash drives, or optical discs. Also, the computer-readable medium may be a random access memory (RAM) including, for example, static random access memory (SRAM) and dynamic random access memory (DRAM), or magnetic random access memory (MRAM). In addition, the computer-readable medium may be a read-only memory (ROM), a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), or other type of memory device.

(59) Further, any logic or application described herein may be implemented and structured in a variety of ways. For example, one or more applications described may be implemented as modules or components of a single application. Further, one or more applications described herein may be executed in shared or separate computing devices or a combination thereof. For example, a plurality of the applications described herein may execute in the same computing device, or in multiple computing devices in the same computing environment **203**. Additionally, it is understood that terms such as “application,” “service,” “system,” “engine,” “module,” and so on may be interchangeable and are not intended to be limiting.

(60) Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, etc., may be either X, Y, or Z, or any combination thereof (e.g., X; Y; Z; X and/or Y; X and/or Z; Y and/or Z; X, Y, and/or Z; etc.). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

(61) It should be emphasized that the above-described embodiments of the present disclosure are merely possible examples of implementations set forth for a clear understanding of the principles of the disclosure. Many variations and modifications may be made to the above-described embodiment(s) without departing substantially from the spirit and principles of the disclosure. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims.

Claims

1. A system, comprising: a computing device comprising a processor and a memory; and machine-readable instructions stored in the memory that, when executed by the processor, cause the computing device to at least: receive, from a first device remote from the computing device, via a network using a secure communication channel, a first request to approve a task associated with a first account identifier; determine, based on an account profile for the first account identifier, that the first account identifier is associated with a second account identifier; retrieve, from a database, data associated with the second account identifier, the data including one or more tasks linked with the second account identifier; append, responsive to retrieval of the data, the task to the data such that the task is included in the one or more tasks; cause a second device, associated with the second account identifier, to generate a first graphical user interface that includes a first notification of the task; receive, from the second device, information that includes (1) a device signature associated with the second device and (2) an authentication token of the second account identifier; authenticate the second device in response to receipt of the information; cause, responsive to authentication of the second device, the second device to generate a second graphical user interface that includes a second notification with a second request for approval of the task; control, responsive to receipt of the approval of the task, execution of an application stored on the second device to cause the second device to perform one or more actions associated with implementation

of the task; and truncate, responsive to performance of the one or more actions, the data to remove the task from the one or more tasks.

2. The system of claim 1, wherein the second notification includes an indication to delegate the task, wherein the indication is associated with temporal data, and wherein the temporal data indicates a time period during which the task is delegated to at least one other account identifier.

3. The system of claim 2, wherein the machine-readable instructions, when executed by the processor, further cause the computing device to: generate a third graphical user interface for the first device to define the temporal data associated with the task.

4. The system of claim 3, wherein the third graphical user interface comprises a selection component configured to receive a selection of the at least one other account identifier.

5. The system of claim 1, wherein the machine-readable instructions, when executed by the processor, further cause the computing device to: generate a third graphical user interface for a third device associated with at least one other account identifier.

6. The system of claim 1, wherein the machine-readable instructions, when executed by the processor, cause the computing device to: define a delegation of the task by identifying the one or more actions associated with implementation of the task; obtain a selection of at least one other account identifier for which the task is delegated to; and associate the delegation of the task with the at least one other account identifier.

7. A method, comprising: receiving, by a computing device, from a first device remote from the computing device, via a network using a secure communication channel, a first request for approval of a task associated with a first account identifier; determining, by the computing device, based on an account profile for the first account identifier, that the first account identifier is associated with a second account identifier; retrieving, by the computing device, from a database, data associated with the second account identifier, the data including one or more tasks linked with the second account identifier; appending, by the computing device, responsive to retrieval of the data, the task to the data such that the task is included in the one or more tasks; causing, by the computing device, a second device, associated with the second account identifier, to generate a first graphical user interface that includes a first notification of the task; receiving, by the computing device, from the second device, information that includes (1) a device signature associated with the second device and (2) an authentication token of the second account identifier; authenticating, by the computing device, the second device in response to receiving the information; causing, by the computing device, responsive to authentication of the second device, the second device to generate a second graphical user interface that includes a second notification with a second request for approval of the task; controlling, by the computing device, responsive to receiving the approval of the task, execution of an application stored on the second device to cause the second device to perform one or more actions associated with implementation of the task; and truncating, by the computing device, responsive to performance of the one or more actions, the data to remove the task from the one or more tasks.

8. The method of claim 7, wherein the second notification includes an indication to delegate the task, wherein the indication is associated with temporal data, and wherein the temporal data indicates a time period during which the task is delegated to at least one other account identifier.

9. The method of claim 8, further comprising: generating, by the computing device, a third graphical user interface for the first device to define the temporal data associated with the task.

10. The method of claim 9, wherein the third graphical user interface comprises a selection component configured to receive a selection of the at least one other account identifier.

11. The method of claim 7, further comprising: generating, by the computing device, a third graphical user interface for a third device associated with at least one other account identifier.

12. The method of claim 7, further comprising: defining, by the computing device, a delegation of the task by identifying the one or more actions associated with implementation of the task; obtaining, by the computing device, a selection of at least one other account identifier for which the

task is delegated to; and associating, by the computing device, the delegation of the task with the at least one other account identifier.

13. One or more non-transitory storage media storing instructions thereon that, when executed by one or more processors, cause the one or more processors to perform operations comprising: receiving, from a first device, via a network, using a secure communication channel, a first request for approval of a task associated with a first account identifier; determining, based on an account profile for the first account identifier, that the first account identifier is associated with a second account identifier; retrieving, from a database, data associated with the second account identifier, the data including one or more tasks linked with the second account identifier; appending, responsive to retrieving the data, the task to the data such that the task is included in the one or more tasks; causing a second device, associated with the second account identifier, to generate a first graphical user interface that includes a first notification of the task; receiving, from the second device, information that includes (1) a device signature associated with the second device and (2) an authentication token of the second account identifier; authenticating the second device in response to receiving the information; causing, responsive to authenticating the second device, the second device to generate a second graphical user interface that includes a second notification with a second request for approval of the task; controlling, responsive to receiving the approval of the task, execution of an application stored on the second device to cause the second device to perform one or more actions associated with implementation of the task; and truncating, responsive to performance of the one or more actions, the data to remove the task from the one or more tasks.

14. The one or more non-transitory storage media of claim 13, wherein the second notification includes an indication to delegate the task, wherein the indication is associated with temporal data, and wherein the temporal data indicates a time period during which the task is delegated to at least one other account identifier.

15. The one or more non-transitory storage media of claim 14, wherein the instructions, further cause the one or more processors to perform operations comprising: generating a third graphical user interface for the first device to define the temporal data associated with the task.

16. The one or more non-transitory storage media of claim 13, wherein the instructions, further cause the one or more processors to perform operations comprising: generating a third graphical user interface for a third device associated with at least one other account identifier.

17. The one or more non-transitory storage media of claim 13, wherein the instructions, further cause the one or more processors to perform operations comprising: defining a delegation of the task by identifying the one or more actions associated with implementation of the task; obtaining a selection of at least one other account identifier for which the task is delegated to; and associating the delegation of the task with the at least one other account identifier.
