

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12402302

Kind Code

B2

Date of Patent

August 26, 2025

Inventor(s)

Cho; Seongkeun et al.

Semiconductor memory device and method for manufacturing the same

Abstract

A semiconductor memory device includes a substrate including a cell area and a peripheral area defined by a periphery of the cell area, the cell area including a dummy cell area and a normal cell area, and an active area defined by a cell element isolation film. The device includes a cell area separation film defining the cell area in the substrate, the dummy cell area defining a boundary with the cell area separation film between the normal cell area and the cell area separation film. The device includes a normal bit-line on the normal cell area and extending in a first direction, a dummy bit-line group on the dummy cell area, the dummy bit-line group including a plurality of dummy bit-lines extending in the first direction, and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction.

Inventors: Cho; Seongkeun (Suwon-si, KR), Park; Jae Seong (Seoul, KR), Kim; Youngseok (Seoul, KR), Kim; Young Sin (Hwaseong-si, KR), Moon; Daeyoung (Seoul, KR), Lee; Keum Joo (Hwaseong-si, KR), Jung; Sung-Wook (Seoul, KR), Hong; Sungduk (Yongin-si, KR), Hwang; Suhwan (Seongnam-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008777860

Assignee: Samsung Electronics Co., Ltd. (Suwon-Si, KR)

Appl. No.: 18/056085

Filed: November 16, 2022

Prior Publication Data

Document Identifier

Publication Date

US 20230247823 A1

Aug. 03, 2023

Foreign Application Priority Data

Publication Classification**Int. Cl.:** H10B12/00 (20230101); G11C5/06 (20060101)**U.S. Cl.:****CPC** H10B12/315 (20230201); G11C5/063 (20130101); H10B12/50 (20230201);**Field of Classification Search****USPC:** None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5773844	12/1997	Kawamura et al.	N/A	N/A
6635588	12/2002	Hawryluk et al.	N/A	N/A
6916690	12/2004	Chang	N/A	N/A
7943936	12/2010	Hiramatsu et al.	N/A	N/A
8441850	12/2012	Lee et al.	N/A	N/A
9349870	12/2015	Wang et al.	N/A	N/A
2013/0099298	12/2012	Kim	N/A	N/A
2021/0082924	12/2020	Seong	N/A	H10B 12/315

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
5756692	12/2014	JP	N/A
2012/0004774	12/2011	KR	N/A

Primary Examiner: Page; Steven M*Attorney, Agent or Firm:* Fish & Richardson P.C.

Background/Summary**CROSS-REFERENCE TO RELATED APPLICATION**

(1) This application claims priority from Korean Patent Application No. 10-2022-0012906 filed on Jan. 28, 2022, in the Korean Intellectual Property Office, and all the benefits accruing therefrom under 35 U.S.C. 119, the contents of which in its entirety are herein incorporated by reference.

FIELD

(2) The present inventive concepts relate to a semiconductor memory device and/or a method for manufacturing the same, and more specifically, to a semiconductor memory device having a plurality of wire lines intersecting with each other and buried contacts, and/or a method for manufacturing the same.

BACKGROUND

- (3) A semiconductor device has an increasingly higher integration level. Thus, in order to implement more semiconductor elements in the same area, individual circuit patterns are increasingly smaller. In other words, as the integration level of the semiconductor memory device increases, a design rule for components of the semiconductor memory device is decreasing.
- (4) In a highly scaled semiconductor device, a process of forming a plurality of wire lines and a plurality of buried contacts (BC) interposed between the lines is becoming increasingly complex and difficult.

SUMMARY

- (5) Aspects of the present inventive concepts provide a semiconductor memory device that may have improved reliability and performance.
- (6) Another aspect of the present inventive concepts is to provide a method for manufacturing a semiconductor memory device that may have improved reliability and performance.
- (7) Example embodiments of the present inventive concepts are not limited to the above-mentioned aspects. Other aspects and advantages in accordance with the present inventive concepts as not mentioned above may be understood from following descriptions and more clearly understood from example embodiments in accordance with the present inventive concepts. Further, it will be readily appreciated that aspects and advantages in accordance with the present inventive concepts may be realized by features and combinations thereof as disclosed in the claims.
- (8) According to an aspect of the present inventive concepts, a semiconductor memory device includes a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film, a cell area separation film defining the cell area in the substrate, wherein the dummy cell area defines a boundary with the cell area separation film between the normal cell area and the cell area separation film, and a normal bit-line on the normal cell area and extending in a first direction. The device includes a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in the first direction, and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction, wherein a width in the second direction of the dummy cell area is greater than or equal to 50 nm and less than or equal to 200 nm, wherein the normal bit-line has a first width in the second direction, and wherein a ratio of a width in the second direction of each of the dummy bit-lines to the first width is greater than or equal to 1 and less than or equal to 2.
- (9) According to another aspect of the present inventive concepts, a semiconductor memory device includes a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film, a cell area separation film defining the cell area in the substrate, wherein the dummy cell area forms a boundary with the cell area separation film between the normal cell area and the cell area separation film, and a normal bit-line group on the normal cell area. The device includes a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in a first direction, and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction. The dummy cell area forms a boundary with the cell area separation film between the normal cell area and the cell area separation film, the normal bit-line group includes a plurality of normal bit-lines extending in the first direction, the plurality of normal bit-lines are spaced from each other by a bit-line pitch in the second direction, a width in the second direction of the dummy cell area is greater than the bit-line pitch and is less than or equal to 5 times the bit-line pitch, each of the normal bit-lines has a first width in the second direction, and a ratio of a width in the second direction of each of the dummy bit-lines to the first width is greater than or equal to 1 and less than or equal to 2.

(10) According to an aspect of the present inventive concepts, a semiconductor memory device includes a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film, a cell area separation film defining the cell area in the substrate, wherein the dummy cell area forms a boundary with the cell area separation film between the normal cell area and the cell area separation film, and a normal bit-line on the normal cell area and extending in a first direction. The device includes a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in the first direction, and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction, wherein a width in the second direction of the dummy cell area is greater than or equal to 50 nm and less than or equal to 200 nm, wherein a width in the second direction of the normal bit-line is greater than or equal to 5 nm and less than or equal to 25 nm, and wherein a width in the second direction of each of the dummy bit-lines is greater than or equal to 5 nm and less than or equal to 30 nm.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The above and other aspects and features of the present inventive concepts will become more apparent by describing in detail example embodiments thereof with reference to the attached drawings, in which:
- (2) FIG. 1 is a schematic layout of a semiconductor memory device according to some example embodiments.
- (3) FIG. 2 is an enlarged schematic layout of a R1 portion of FIG. 1.
- (4) FIG. 3 is a layout showing only a word-line and an active area of FIG. 2.
- (5) FIG. 4 is a schematic layout diagram of a R2 area of FIG. 1.
- (6) FIG. 5 is a schematic layout diagram of a R3 area of FIG. 1.
- (7) FIG. 6 is an illustrative cross-sectional view taken along A-A of FIG. 4.
- (8) FIG. 7 is an illustrative cross-sectional view taken along B-B of FIG. 4.
- (9) FIG. 8 is an illustrative cross-sectional view taken along C-C of FIG. 5.
- (10) FIG. 9 is an illustrative cross-sectional view taken along D-D of FIG. 5.
- (11) FIG. 10 is a diagram for illustrating a semiconductor memory device according to some example embodiments.
- (12) FIG. 11 is a diagram for illustrating a semiconductor memory device according to some example embodiments.
- (13) FIG. 12 is a schematic layout diagram of a semiconductor memory device according to some example embodiments.
- (14) FIG. 13 is an illustrative cross-sectional view taken along A-A of FIG. 12.
- (15) FIG. 14 is a schematic layout diagram of a semiconductor memory device according to some example embodiments.
- (16) FIG. 15, 16, 17, 18, 19, 20 and FIG. 21 are diagrams of intermediate structures of steps for illustrating a method for manufacturing a semiconductor memory device according to some example embodiments.
- (17) FIG. 22 and FIG. 23 are diagrams to illustrate an effect of a thickness of the semiconductor material film formed on the substrate on intensity of laser energy absorbed by the semiconductor material film.
- (18) FIG. 24, 25, 26 and FIG. 27 are diagrams to illustrate an effect of an arrangement of structures on the substrate on intensity of laser energy absorbed by the semiconductor material film.
- (19) FIG. 28, 29, 30, 31, and FIG. 32 are diagrams of intermediate structures of steps for

illustrating a method for manufacturing a semiconductor memory device according to some example embodiments.

(20) FIG. 33 is a diagram showing reflectance of laser based on a thickness of an anti-reflective film.

DETAILED DESCRIPTION

(21) For simplicity and clarity of illustration, elements in the figures are not necessarily drawn to scale. The same reference numbers in different figures represent the same or similar elements, and as such perform similar functionality. Further, descriptions and details of well-known steps and elements are omitted for simplicity of the description. Furthermore, in the following detailed description of the present inventive concepts, numerous specific details are set forth in order to provide a thorough understanding of the present inventive concepts. However, it will be understood that the present inventive concepts may be practiced without these specific details. In other instances, some methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present inventive concepts.

(22) Examples of various example embodiments are illustrated and described further below. It will be understood that the description herein is not intended to limit the claims to the specific example embodiments described. On the contrary, it is intended to cover alternatives, modifications, and equivalents as may be included within the scope of the present inventive concepts.

(23) A shape, a size, a ratio, an angle, a number, etc. disclosed in the drawings for illustrating example embodiments of the present inventive concepts are illustrative, and the present inventive concepts are not limited thereto. The same reference numerals refer to the same elements herein. Further, descriptions and details of some steps and elements may be omitted for simplicity of the description. Furthermore, in the following detailed description of the present inventive concepts, numerous specific details are set forth in order to provide a thorough understanding of the present inventive concepts. However, it will be understood that the present inventive concepts may be practiced without these specific details. In other instances, some methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present inventive concepts.

(24) The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to limit the present inventive concepts. As used herein, the singular forms “a” and “an” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises”, “comprising”, “includes”, and “including” when used in this specification, specify the presence of the stated features, integers, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, operations, elements, components, and/or portions thereof. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expression such as “at least one of” when preceding a list of elements may modify the entirety of list of elements and may not modify the individual elements of the list. When referring to “C to D”, this means C inclusive to D inclusive unless otherwise specified.

(25) It will be understood that, although the terms “first”, “second”, “third”, and so on may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms are used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer or section described below could be termed a second element, component, region, layer or section, without departing from the scope of the present inventive concepts.

(26) In addition, it will also be understood that when a first element or layer is referred to as being present “on” or “beneath” a second element or layer, the first element may be disposed directly on or beneath the second element or may be disposed indirectly on or beneath the second element with a third element or layer being disposed between the first and second elements or layers.

(27) It will be understood that when an element or layer is referred to as being “connected to”, or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer, or one or more intervening elements or layers may be present. In addition, it will also be understood that when an element or layer is referred to as being “between” two elements or layers, it may be the only element or layer between the two elements or layers, or one or more intervening elements or layers may also be present.

(28) Further, as used herein, when a layer, film, region, plate, or the like is disposed “on” or “on a top” of another layer, film, region, plate, or the like, the former may directly contact the latter or still another layer, film, region, plate, or the like may be disposed between the former and the latter. As used herein, when a layer, film, region, plate, or the like is directly disposed “on” or “on a top” of another layer, film, region, plate, or the like, the former directly contacts the latter and still another layer, film, region, plate, or the like is not disposed between the former and the latter. Further, as used herein, when a layer, film, region, plate, or the like is disposed “below” or “under” another layer, film, region, plate, or the like, the former may directly contact the latter or still another layer, film, region, plate, or the like may be disposed between the former and the latter. As used herein, when a layer, film, region, plate, or the like is directly disposed “below” or “under” another layer, film, region, plate, or the like, the former directly contacts the latter and still another layer, film, region, plate, or the like is not disposed between the former and the latter.

(29) Unless otherwise defined, all terms including technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the inventive concepts belong. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(30) In one example, when a certain example embodiment may be implemented differently, a function or operation specified in a specific block may occur in a sequence different from that specified in a flowchart. For example, two consecutive blocks may actually be executed at the same time. Depending on a related function or operation, the blocks may be executed in a reverse sequence.

(31) In descriptions of temporal relationships, for example, temporal precedent relationships between two events such as “after”, “subsequent to”, “before”, etc., another event may occur therebetween unless “directly after”, “directly subsequent” or “directly before” is not indicated.

(32) The features of the various example embodiments of the present inventive concepts may be partially or entirely combined with each other, and may be technically associated with each other or operate with each other. The example embodiments may be implemented independently of each other and may be implemented together in an association relationship.

(33) Spatially relative terms, such as “beneath,” “below,” “lower,” “under,” “above,” “upper,” and the like, may be used herein for ease of explanation to describe one element or feature's relationship to another element or feature as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or in operation, in addition to the orientation depicted in the figures. For example, when the device in the figures is turned over, elements described as “below” or “beneath” or “under” other elements or features would then be oriented “above” the other elements or features. Thus, the example terms “below” and “under” may encompass both an orientation of above and below. The device may be otherwise oriented for example, rotated 90 degrees or at other orientations, and the spatially relative descriptors used herein should be interpreted accordingly.

(34) “D1 direction” and “D2 axis direction” should not be interpreted only to have a geometric relationship in which the D1 direction, and the D2 direction are perpendicular to each other. “D1 direction” and “D2 direction” may be interpreted to have a broader direction within a range in which components herein may work functionally.

(35) FIG. 1 is a schematic layout of a semiconductor memory device according to some example embodiments. FIG. 2 is an enlarged schematic layout of a R1 portion of FIG. 1. FIG. 3 is a layout showing a word-line and an active area of FIG. 2. FIG. 4 is a schematic layout diagram of a R2 area of FIG. 1. FIG. 5 is a schematic layout diagram of a R3 area of FIG. 1. FIG. 6 is an illustrative cross-sectional view taken along A-A of FIG. 4. FIG. 7 is an illustrative cross-sectional view taken along B-B of FIG. 4. FIG. 8 is an illustrative cross-sectional view taken along C-C of FIG. 5. FIG. 9 is an illustrative cross-sectional view taken along D-D of FIG. 5.

(36) In a diagram of a semiconductor memory device according to some example embodiments, DRAM (Dynamic Random Access Memory) is illustrated by way of example. However, the present inventive concepts are not limited thereto.

(37) Referring to FIG. 1 to FIG. 5, a semiconductor memory device according to some example embodiments may include a cell area **20**, a cell area separation film **22**, and a peripheral area **24**.

(38) The cell area separation film **22** may be formed along an outer edge of the cell area **20**. The cell area separation film **22** may separate the cell area **20** and the peripheral area **24** from each other. The cell area separation film **22** defines the cell area **20**. The peripheral area **24** may be defined as a periphery around the cell area **20**.

(39) The cell area **20** may include a plurality of cell active areas ACT. The cell active area ACT may be defined by a cell element isolation film (**105** in FIG. 6 to FIG. 9) formed in a substrate (**100** in FIG. 6). As the design rule of the semiconductor memory device decreases, the cell active area ACT may have a bar shape extending in a diagonal line or an oblique line as shown in FIG. 2. For example, the cell active area ACT may extend in a third direction D3.

(40) Each of a plurality of gate electrodes may extend in a first direction D1 and across the cell active area ACT. The plurality of gate electrodes may extend parallel or substantially parallel to each other. Each of the plurality of gate electrodes may be embodied as, for example, each of a plurality of word-lines WL. The word-lines WL may be spaced from each other by an equal or substantially equal spacing. A width of the word-line WL or a spacing between word-lines WL may be determined according to the design rule.

(41) The cell area **20** may include a dummy cell area **20_DCR** and a normal cell area **20_NCR**. The dummy cell area **20_DCR** may be disposed on each of both opposing sides in the first direction D1 of the normal cell area **20_NCR**.

(42) A boundary extending in the second direction D2 may be formed between the dummy cell area **20_DCR** and the cell area separation film **22**. That is, the boundary between the dummy cell area **20_DCR** and the cell area separation film **22** may extend in an elongate manner in the second direction D2. The dummy cell area **20_DCR** is located between the normal cell area **20_NCR** and the cell area separation film **22**.

(43) The word-line WL may extend to the cell area separation film **22**. A portion of the word-line WL may overlap the cell area separation film **22** in a fourth direction D4.

(44) The two word-lines WLs extending in the first direction D1 may allow each cell active area ACT to be divided into three portions. The cell active area ACT may include a storage connection area **103b** and a bit-line connection area **103a**. The bit-line connection area **103a** may be located at a middle portion of the cell active area ACT, while the storage connection area **103b** may be located at an end of the cell active area ACT.

(45) A plurality of bit-lines BL extending in a second direction D2 perpendicular or substantially perpendicular to the extension direction of the word-line WL may be disposed on the word-lines WL. The plurality of bit-line BL may extend parallel or substantially parallel to each other. The bit-lines BL may be arranged to be spaced from each other by the same spacing. A width of the bit-line BL or a spacing between bit-lines BLs may be determined according to the design rule.

(46) The bit-line BL may extend to the cell area separation film **22**. A portion of the bit-line BL may overlap the cell area separation film **22** in the fourth direction D4. The fourth direction D4 may be orthogonal to the first direction D1, the second direction D2, and the third direction D3.

The fourth direction D4 may be a thickness direction of the substrate **100**.

(47) The plurality of bit-lines BL may include a normal bit-line group BL_NG and a dummy bit-line group BL_DG. The dummy bit-line group BL_DG may be disposed in the dummy cell area **20_DCR**. The normal bit-line group BL_NG may be disposed in the normal cell area **20_NCR**.

(48) The dummy bit-line group BL_DG may be disposed at a boundary of the cell area **20**. The dummy bit-line group BL_DG may be disposed at the boundary of the cell area **20** extending in the second direction D2. Because the dummy bit-line groups BL_DG are respectively disposed at the boundaries of the cell area **20** extending in the second direction D2, the normal bit-line group BL_NG may be disposed between the dummy bit-line groups BLDG.

(49) The normal bit-line group BL_NG may include a plurality of normal bit-lines BL_N extending in the second direction D2. The normal bit-line BL_N may act as a bit-line used for operation of a memory cell included in the semiconductor memory device.

(50) The normal bit-lines BL_N may be spaced apart from each other in the first direction D1. For example, the normal bit-lines BL_N may be spaced from each other by a bit-line pitch BL_P. That is, a spacing between the normal bit-lines BL_N adjacent to the first direction D1 may be the bit-line pitch BL_P.

(51) The dummy bit-line group BL_DG may include a plurality of dummy bit-lines BL_DA and BL_DB extending in the second direction D2. Each of the plurality of dummy bit-lines BL_DA and BL_DB may act as a bit-line that is not used for operation of the memory cell included in the semiconductor memory device. For example, because a voltage source or a current source is not connected to the plurality of dummy bit-lines BL_DA and BL_DB, each of the plurality of dummy bit-lines BL_DA and BL_DB may be in an electrically floating state.

(52) The dummy bit-line group BL_DG may include an outermost dummy bit-line BL_DA that is closest to the peripheral area **24** in the first direction D1. The dummy bit-line group BL_DG may include an inner dummy bit-line BL_DB disposed between the outermost dummy bit-line BL_DA and the normal bit-line BL_N.

(53) The outermost dummy bit-line BL_DA may extend in the second direction D2 and in parallel with the inner dummy bit-line BL_DB. The outermost dummy bit-line BL_DA is spaced apart from the inner dummy bit-line BL_DB in the first direction D1. Although the outermost dummy bit-line BL_DA may not overlap with the cell area separation film **22** in the first direction D1, the present inventive concepts are not limited thereto.

(54) The dummy bit-line group BL_DG may include, for example, 2 to 6 dummy bit-lines (or more or less). For example, the inner dummy bit-line BL_DB may include 1 to 5 dummy bit-lines (or more).

(55) In FIG. 4, the dummy bit-line group BL_DG may include two dummy bit-lines. The dummy bit-line group BL_DG disposed on one side of the normal bit-line group BL_NG may include, for example, the outermost dummy bit-line BL_DA and one inner dummy bit-line BL_DB.

(56) A width of the dummy cell area **20_DCR** in the first direction D1 may be, for example, in a range from 50 nm to 200 nm (or more or less). For example, the width of the dummy cell area **20_DCR** may refer to a distance from the boundary of the cell area **20** and the cell area separation film **22** to a sidewall of the inner dummy bit-line BL_DB closest to the normal bit-line BL_N.

(57) The width of the dummy cell area **20_DCR** in the first direction D1 may be greater than the bit-line pitch BL_P. The width of the dummy cell area **20_DCR** in the first direction D1 may be smaller than or equal to 5 times of the bit-line pitch BL_P.

(58) The width of the dummy cell area **20_DCR** in the first direction D1 may vary based on the number of the dummy bit-lines included in the dummy bit-line group BL_DG.

(59) A boundary peripheral gate PR_GE may extend in the second direction D2 and in parallel with the outermost dummy bit-line BL_DA. The boundary peripheral gate PR_GE may be disposed at a boundary between the cell area separation film **22** and the peripheral area **24**. Unlike the drawings, in the semiconductor memory device according to some example embodiments, the boundary

peripheral gate PR_GE may extend in the first direction D1. Further, the semiconductor memory device according to some embodiments may not include the boundary peripheral gate PR_GE.

(60) A semiconductor memory device according to some example embodiments may include various contact arrangements formed on the cell active area ACT. The various contact arrangements may include, for example, a direct contact DC, a buried contact BC, and a landing pad LP, etc.

(61) In this regard, the direct contact DC may mean a contact that electrically connects the cell active area ACT to the bit-line BL. The buried contact BC may mean a contact connecting the cell active area ACT to a lower electrode (e.g., **191** in FIG. **6** and FIG. **9**) of a capacitor. In terms of an arrangement structure, a contact area between the buried contact BC and the cell active area ACT may be small. Accordingly, a conductive landing pad LP may be introduced to expand the contact area between the cell active area ACT and the buried contact BC, and to expand the contact area between the buried contact BC and the lower electrode (**191** in FIG. **6** and FIG. **9**) of the capacitor.

(62) The landing pad LP may be disposed between the cell active area ACT and the buried contact BC and may be disposed between the buried contact BC and the lower electrode (**191** in FIG. **6** and FIG. **9**) of the capacitor. In the semiconductor memory device according to some example embodiments, the landing pad LP may be disposed between the buried contact BC and the lower electrode of the capacitor. Expanding the contact area via the introduction of the landing pad LP may allow a contact resistance between the cell active area ACT and the lower electrode of the capacitor to be reduced.

(63) The direct contact DC may be connected to the bit-line connection area **103a**. The buried contact BC may be connected to the storage connection area **103b**. As the buried contact BC is disposed in each of both opposing ends of the cell active area ACT, the landing pad LP may be disposed adjacent to each of both opposing ends of the cell active area ACT and partially overlap with the buried contact BC. In other words, the buried contact BC may be formed to overlap the cell active area ACT and the cell element isolation film (e.g., **105** in FIG. **6**) between adjacent word-lines WL and between adjacent bit-lines BL.

(64) The word-line WL may be formed as a structure buried in the substrate **100**. The word-line WL may extend across the cell active area ACT between the direct contacts DC or between the buried contacts BC. As shown, two word-lines WL may extend through one cell active area ACT. As the cell active area ACT extends along the third direction D3, the extension direction of the word-line WL may have an angle smaller than 90 degrees with respect to the extension direction of the cell active area ACT.

(65) The direct contacts DC and the buried contacts BC may be arranged in a symmetrical or substantially symmetrical manner. Accordingly, the direct contacts DC and the buried contacts BC may be arranged in a straight or substantially straight line along the first direction D1 and the second direction D2. Unlike the direct contact DC and the buried contact BC, the landing pads LP may be arranged in a zigzag manner in the second direction D2 which the bit-line BL extends. Further, the landing pads LP may overlap with the same portion of a side face of each bit-line BL in the first direction D1 in which the word-line WL extends. For example, each of landing pads LP in a first line may overlap the left side face of a corresponding bit-line BL, while each of the landing pads LP in a second line may overlap with a right side face of the corresponding bit-line BL.

(66) Referring to FIG. **1** to FIG. **9**, the semiconductor memory device according to some example embodiments may include a plurality of cell gate structures **110**, a plurality of cell conductive lines **140N**, **140DA**, and **140DB**, a plurality of storage pads **160**, information storage **190**, and a peripheral gate conductive film **240**.

(67) The substrate **100** may include the cell area **20**, the cell area separation film **22**, and the peripheral area **24**. The substrate **100** may be a silicon substrate, an SOI (silicon-on-insulator), etc. Alternatively, the substrate **100** may include silicon germanium, SGOI (silicon germanium on insulator), indium antimonide, lead tellurium compound, indium arsenic, indium phosphide,

gallium arsenide or gallium antimonide. However, the present inventive concepts are not limited thereto.

(68) The plurality of cell gate structures **110**, the plurality of cell conductive lines **140N**, **140DA**, and **140DB**, the plurality of storage pads **160**, and the information storage **190** may be disposed in the cell area **20**. The peripheral gate structure **240** may be disposed in the peripheral area **24**.

(69) A cell element isolation film **105** may be formed in the substrate **100** and in the cell area **20**. The cell element isolation film **105** may have an STI (shallow trench isolation) structure with excellent element isolation ability. The cell element isolation film **105** may define the cell active area ACT within the cell area **20**. The cell active area ACT defined by the cell element isolation film **105** may have an elongate island shape including a minor axis and a major axis as shown in FIG. 2 to FIG. 5. The cell active area ACT may have a diagonally extension shape to have an angle of smaller than 90 degrees with respect to the extension direction of the word-line WL horizontally flush with the cell element isolation film **105**. Further, the cell active area ACT may have a diagonally extension shape to have an angle of smaller than 90 degrees with respect to an extension direction of the bit-line BL formed on the cell element isolation film **105**.

(70) The cell area separation film **22** may be embodied as a cell boundary separation film having an STI structure. The cell area **20** may be defined by the cell area separation film **22**.

(71) Each of the cell element isolation film **105** and the cell area separation film **22** may include, for example, at least one of a silicon oxide film, a silicon nitride film, and a silicon oxynitride film. However, the present inventive concepts are not limited thereto. In FIG. 6 to FIG. 9, each of the cell element isolation film **105** and the cell area separation film **22** is shown to be formed as a single insulating film. However, this is only for convenience of illustration, and the present inventive concepts are not limited thereto. Depending on a width of each of the cell element isolation film **105** and the cell area separation film **22**, each of the cell element isolation film **105** and the cell area separation film **22** may be formed as a single insulating film, or as a stack of a plurality of insulating films.

(72) In FIG. 6 and FIG. 8, a top face of the cell element isolation film **105**, a top face of the substrate **100**, and a top face of the cell area separation film **22** are shown to be horizontally flush with each other. However, this is only for convenience of illustration, and the present inventive concepts are not limited thereto.

(73) The cell gate structure **110** may be formed in the substrate **100** and the cell element isolation film **105**. The cell gate structure **110** may be formed along the cell element isolation film **105** and the cell active area ACT defined by the cell element isolation film **105**.

(74) The cell gate structure **110** may include a cell gate trench **115** formed in the substrate **100** and the cell element isolation film **105**, a cell gate insulating film **111**, a cell gate electrode **112**, a cell gate capping pattern **113**, and a cell gate capping conductive film **114**. In this regard, the cell gate electrode **112** may act as the word-line WL. Unlike a configuration as shown, the cell gate structure **110** may not include the cell gate capping conductive film **114**.

(75) The cell gate insulating film **111** may extend along a side wall and a bottom face of the cell gate trench **115**. The cell gate insulating film **111** may extend along a profile of at least a portion of the cell gate trench **115**. The cell gate insulating film **111** may include, for example, at least one of silicon oxide, silicon nitride, silicon oxynitride, or high dielectric constant materials having a higher dielectric constant than that of silicon oxide. The high dielectric constant material may include, for example, hafnium oxide, hafnium silicon oxide, hafnium aluminum oxide, lanthanum oxide, lanthanum aluminum oxide, zirconium oxide, zirconium silicon oxide, tantalum oxide, titanium oxide, barium strontium titanium oxide, barium titanium oxide, strontium titanium oxide, yttrium oxide, aluminum oxide, lead scandium tantalum oxide, lead zinc niobate, and combinations thereof, but example embodiments are not limited thereto.

(76) The cell gate electrode **112** may be formed on the cell gate insulating film **111**. The cell gate electrode **112** may fill a portion of the cell gate trench **115**. The cell gate capping conductive film

114 may extend along a top face of the cell gate electrode **112**.

(77) The cell gate electrode **112** may include at least one of metal, metal alloy, conductive metal carbonitride, conductive metal carbide, metal silicide, doped semiconductor material, conductive metal oxynitride, and conductive metal oxide but example embodiments are not limited thereto. The cell gate electrode **112** may include at least one of, for example, TiN, TaC, TaN, TiSiN, TaSiN, TaTiN, TiAlN, TaAlN, WN, Ru, TiAl, TiAlC—N, TiAlC, TiC, TaCN, W, Al, Cu, Co, Ti, Ta, Ni, Pt, Ni—Pt, Nb, NbN, NbC, Mo, MoN, MoC, WC, Rh, Pd, Ir, Ag, Au, Zn, V, RuTiN, TiSi, TaSi, NiSi, CoSi, IrOx, RuOx, and combinations thereof. However, the present inventive concepts are not limited thereto. The cell gate capping conductive film **114** may include, for example, polysilicon or polysilicon germanium. However, the present inventive concepts are not limited thereto.

(78) The cell gate capping pattern **113** may be disposed on the cell gate electrode **112** and the cell gate capping conductive film **114**. The cell gate capping pattern **113** may fill a remaining portion of the cell gate trench **115** except for the cell gate electrode **112** and the cell gate capping conductive film **114**. The cell gate insulating film **111** is shown to extend along a side wall of the cell gate capping pattern **113**. However, the present inventive concepts are not limited thereto. The cell gate capping pattern **113** may include, for example, at least one of silicon nitride SiN, silicon oxynitride SiON, silicon oxide SiO₂, silicon carbonitride SiCN, silicon oxycarbonitride SiOCN, and combinations thereof.

(79) Although not shown, an impurity doped area may be formed on at least one side of the cell gate structure **110**. The impurity doped area may act as a source/drain area of the transistor. The impurity doped area may be formed in the storage connection area **103b** and the bit-line connection area **103a** of FIG. 3.

(80) The bit-line structure may include cell conductive lines **140N**, **140DA**, and **140DB** and a cell line capping film **144**. The cell conductive lines **140N**, **140DA**, and **140DB** may be formed on the substrate **100** including the cell gate structure **110**, and on the cell element isolation film **105** formed in the substrate **100**. The cell conductive lines **140N**, **140DA**, and **140DB** may intersect a cell element isolation film **105**, and the cell active area ACT defined by the cell element isolation film **105**. The cell conductive lines **140N**, **140DA**, and **140DB** may be formed to intersect with the cell gate structure **110**. In this regard, the cell conductive lines **140N**, **140DA**, and **140DB** may act as the bit-lines BL.

(81) The cell conductive lines **140N**, **140DA**, and **140DB** may include a normal cell conductive line **140N** and dummy cell conductive lines **140DA** and **140DB**. The dummy cell conductive lines **140DA** and **140DB** may include a first outermost dummy cell conductive line **140DA** and an inner dummy cell conductive line **140DB**. The normal cell conductive line **140N** may act as the normal bit-line BL_N. The first outermost dummy cell conductive line **140DA** may act as the outermost dummy bit-line BL_{DA}. The inner dummy cell conductive line **140DB** may act as the inner dummy bit-line BL_{DB}.

(82) Each of the cell conductive lines **140N**, **140DA**, and **140DB** may include a stack of multiple films. Each of the cell conductive lines **140N**, **140DA**, and **140DB** may include, for example, a first cell conductive film **141**, a second cell conductive film **142**, and a third cell conductive film **143**. The first to third cell conductive films **141**, **142**, and **143** may be sequentially stacked on the substrate **100** and the cell element isolation film **105**. Although each of the cell conductive lines **140N**, **140DA**, and **140DB** is shown to be composed of the three films, the present inventive concepts are not limited thereto.

(83) Each of the first to third cell conductive films **141**, **142**, and **143** may include, for example, at least one of a semiconductor material doped with impurities, a conductive silicide compound, a conductive metal nitride metal, and a metal alloy, but example embodiments are not limited thereto. For example, the first cell conductive film **141** may include a doped semiconductor material. The first cell conductive film **141** may be a semiconductor conductive line. The second cell conductive film **142** may include at least one of the conductive silicide compound and the

conductive metal nitride. The third cell conductive film **143** may include at least one of metal and metal alloy. However, the present inventive concepts are not limited thereto. Each of the second and third cell conductive films **142** and **143** may be a metallic conductive line.

(84) The normal cell conductive line **140N** may have a first width $W1$ in the first direction $D1$. The first outermost dummy cell conductive line **140DA** may have a second width $W21$ in the first direction $D1$. The inner dummy cell conductive line **140DB** may have a third width $W22$ in the first direction $D1$.

(85) In this regard, the width $W1$ of the normal cell conductive line **140N**, the width $W21$ of the first outermost dummy cell conductive line **140DA**, and the width $W22$ of the inner dummy cell conductive line **140DB** may respectively refer to widths of bottom faces of the normal cell conductive line **140N**, the first outermost dummy cell conductive line **140DA**, and the inner dummy cell conductive line **140DB**. That is, the width $W1$ of the normal cell conductive line **140N**, the width $W21$ of the first outermost dummy cell conductive line **140DA**, and the width $W22$ of the inner dummy cell conductive line **140DB** may be a width of a bottom face of the first cell conductive film **141** facing the substrate **100**.

(86) The width $W1$ of the normal cell conductive line **140N** may be a width of the normal bit-line BL_N . The width $W21$ of the first outermost dummy cell conductive line **140DA** may be a width of the outermost dummy bit-line BL_DA . The width $W22$ of the inner dummy cell conductive line **140DB** may be a width of the inner dummy bit-line BL_DB .

(87) For example, the width $W22$ of the inner dummy cell conductive line **140DB** is equal or substantially equal to the width $W1$ of the normal cell conductive line **140N**. In the semiconductor memory device according to some example embodiments, the width $W21$ of the first outermost dummy cell conductive line **140DA** may be equal or substantially equal to the width $W22$ of the inner dummy cell conductive line **140DB**. Each of the widths $W21$ and $W22$ of the dummy cell conductive lines **140DA** and **140DB** may be equal or substantially equal to the width $W1$ of the normal cell conductive line **140N**.

(88) A ratio of each of the widths $W21$ and $W22$ of the dummy cell conductive lines **140DA** and **140DB** to the width $W1$ of the normal cell conductive line **140N** may be 1. That is, a ratio $W21/W1$ of the width $W21$ of the first outermost dummy cell conductive line **140DA** to the width $W1$ of the normal cell conductive line **140N** may be 1. A ratio $W22/W1$ of the width $W22$ of the inner dummy cell conductive line **140DB** to the width $W1$ of the normal cell conductive line **140N** may be 1.

(89) For example, the width $W1$ of the normal cell conductive line **140N** may be in a range from 5 nm to 25 nm. Similarly, each of the widths $W21$ and $W22$ of the dummy cell conductive lines **140DA** and **140DB** may be in a range from 5 nm to 25 nm.

(90) A bit-line contact **146** may be formed between the cell conductive lines **140N**, **140DA**, and **140DB** and the substrate **100**. That is, the cell conductive lines **140N**, **140DA**, and **140DB** may be formed on the bit-line contact **146**. For example, the bit-line contact **146** may be formed at a point where each of the cell conductive lines **140N**, **140DA**, and **140DB** intersects a center portion of the cell active area **ACT** having an elongate island shape. The bit-line contact **146** may be formed between the bit-line connection area **103a** of the cell active area **ACT** and the cell conductive lines **140N**, **140DA**, and **140DB**. The bit-line contact **146** may be connected to the bit-line connection area **103a**.

(91) The plurality of bit-line contacts **146** may extend along the second direction $D2$. Each of the cell conductive lines **140N**, **140DA**, and **140DB** may be disposed on the plurality of bit-line contacts **146** and extend along the second direction $D2$.

(92) The bit-line contact **146** may electrically connect the cell conductive lines **140N**, **140DA**, and **140DB** to the substrate **100**. In this regard, the bit-line contact **146** may act as the direct contact **DC**. The bit-line contact **146** may include, for example, at least one of a semiconductor material doped with impurities, a conductive silicide compound, a conductive metal nitride, and a metal, but example embodiments are not limited thereto. In the semiconductor memory device according to

some example embodiments, the bit-line contact **146** may include a semiconductor material doped with impurities.

(93) In FIG. **8** in which the normal cell conductive line **140N** is shown, in an area overlapping a top face **146US** of the bit-line contact, the normal cell conductive line **140N** may include the second cell conductive film **142** and the third cell conductive film **143**. In an area that does not overlap with the top face **146US** of the bit-line contact, the normal cell conductive line **140N** may include the first to third cell conductive films **141**, **142**, and **143**.

(94) Although not shown, the dummy cell conductive line **140DA** and **140DB** may have the same or substantially the same structure as that of the normal cell conductive line **140N**.

(95) The second cell conductive film **142** may extend along a top face **141US** of the first cell conductive film and a top face **146US** of the bit-line contact. A bottom face **142BS** of the second cell conductive film may face toward the top face **141US** of the first cell conductive film and the top face **146US** of the bit-line contact.

(96) The bottom face **142BS** of the second cell conductive film may directly contact the top face **141US** of the first cell conductive film and the top face **146US** of the bit-line contact. A vertical dimension from a top face of the substrate **100** to the bottom face **142BS** of the second cell conductive film may be the same or substantially the same as a vertical dimension from the top face of the substrate **100** to the top face **146US** of the bit-line contact. For example, the vertical dimension from the top face of the substrate **100** to the top face **141US** of the first cell conductive film may be the same or substantially the same as the vertical dimension from the top face of the substrate **100** of the top face **146US** of the bit-line contact.

(97) The plurality of bit-line contacts **146** may include a first bit-line contact, a second bit-line contact and a third bit-line contact under one cell conductive line **140N**, **140DA**, or **140DB**. The first to third bit-line contacts may be sequentially arranged from the cell area separation film **22** in the second direction **D2**. The second bit-line contact may be disposed between the first bit-line contact and the third bit-line contact. In the semiconductor memory device according to some embodiments, the bottom face **142BS** of the second cell conductive film may directly contact a top face **146US** of the first bit-line contact, a top face **146US** of the second bit-line contact, and a top face **146US** of the third bit-line contact.

(98) In FIG. **8**, it is illustrated that the bit-line contact **146** is not disposed between the substrate **100** and the normal cell conductive line **140N** closest to the cell area separation film **22**. The present inventive concepts are not limited thereto. Unlike the illustration, the bit-line contact **146** may be disposed between the substrate **100** and the normal cell conductive line **140N** closest to the cell area separation film **22**.

(99) The cell line capping film **144** may be disposed on the cell conductive lines **140N**, **140DA**, and **140DB**. The cell line capping film **144** may extend in the second direction **D2** and along the top faces of the cell conductive lines **140N**, **140DA**, and **140DB**. In this case, the cell line capping film **144** may include, for example, at least one of a silicon nitride, a silicon oxynitride, a silicon carbonitride, and a silicon oxycarbonitride, but example embodiments are not limited thereto. In the semiconductor memory device according to some example embodiments, the cell line capping film **144** may include, for example, a silicon nitride film. Although the cell line capping film **144** is shown to be a single film, the present inventive concepts are not limited thereto.

(100) A cell insulating film **130** may be formed on the substrate **100** and the cell element isolation film **105**. More specifically, the cell insulating film **130** may be disposed on a portion of the substrate **100** and a portion of the cell element isolation film **105** on which the bit-line contact **146** has not been formed. The cell insulating film **130** may be disposed between the substrate **100** and the cell conductive line **140** and between the cell element isolation film **105** and the cell conductive lines **140N**, **140DA**, and **140DB**.

(101) The cell insulating film **130** may be a single film. However, as illustrated, the cell insulating film **130** may be a stack of multi-films including the first cell insulating film **131** and the second

cell insulating film **132**. For example, the first cell insulating film **131** may include a silicon oxide film, and the second cell insulating film **132** may include a silicon nitride film. The present inventive concepts are not limited thereto. Unlike the configuration as shown, the cell insulating film **130** may include three or more insulating films.

(102) A cell buffer film **101** may be disposed between the cell insulating film **130** and the cell area separation film **22**. Although cell buffer film **101** may include, for example, a silicon oxide film, the present inventive concepts are not limited thereto.

(103) A cell line spacer **150** may be disposed on sidewalls of the cell conductive lines **140N**, **140DA**, and **140DB**, and the cell line capping film **144**. In portions of the cell conductive lines **140N**, **140DA**, and **140DB** where the bit-line contact **146** is formed, the cell line spacer **150** may be formed on the substrate **100** and the cell element isolation film **105**. The cell line spacer **150** may be disposed on sidewalls of the cell conductive lines **140N**, **140DA**, and **140DB**, the cell line capping film **144** and the bit-line contact **146**.

(104) In remaining portions of the cell conductive lines **140N**, **140DA**, and **140DB** where the bit-line contact **146** is not formed, the cell line spacer **150** may be disposed on the cell insulating film **130**. The cell line spacer **150** may be disposed on the sidewalls of the cell conductive lines **140N**, **140DA**, and **140DB**, and the cell line capping film **144**.

(105) The cell line spacer **150** may be a single layer. However, as illustrated, the cell line spacer **150** may be a stack of multi-films including the first to fourth cell line spacers **151**, **152**, **153**, and **154**. For example, each of the first to fourth cell line spacers **151**, **152**, **153**, and **154** may include one of a silicon oxide film, a silicon nitride film, a silicon oxynitride film (SiON), a silicon oxycarbonitride film (SiOCN), air, and combinations thereof. However, the present inventive concepts are not limited thereto.

(106) For example, the second cell line spacer **152** may not be disposed on the cell insulating film **130**, but may be disposed on a sidewall of the bit-line contact **146**. The cell line spacer **150** may be disposed on a long sidewall extending in the second direction D2 among sidewalls of the cell conductive lines **140N**, **140DA**, and **140DB**.

(107) A fence pattern **170** may be disposed on the substrate **100** and the cell element isolation film **105**. The fence pattern **170** may be formed to overlap the cell gate structure **110** formed in the substrate **100** and the cell element isolation film **105**. The fence pattern **170** may be disposed between the cell conductive lines **140N**, **140DA**, and **140DB** extending in the second direction D2. The fence pattern **170** may include, for example, at least one of silicon oxide, silicon nitride, silicon oxynitride, and a combination thereof, but example embodiments are not limited thereto.

(108) A plurality of storage contacts **120** may be disposed between the cell conductive lines **140N**, **140DA**, and **140DB** adjacent to each other in the first direction D1. The storage contact **120** may be disposed between the fence patterns **170** adjacent to each other in the second direction D2. The storage contact **120** may overlap portions of the substrate **100** and the cell element isolation film **105** between the adjacent cell conductive lines **140N**, **140DA**, and **140DB**. The storage contact **120** may be connected to the storage connection area **103b** of the cell active area ACT. In this regard, the storage contact **120** may act as the buried contact BC.

(109) The plurality of storage contacts **120** may be arranged along the first direction D 1. In the semiconductor memory device according to some example embodiments, the plurality of storage contacts **120** may not include an air gap.

(110) The storage contact **120** may include, for example, at least one of a semiconductor material doped with impurities, a conductive silicide compound, a conductive metal nitride, and a metal, but example embodiments are not limited thereto. In the semiconductor memory device according to some example embodiments, the storage contact **120** may include a semiconductor material doped with impurities.

(111) The storage pad **160** may be disposed on each storage contact **120**. The storage pad **160** may be electrically connected to the storage contact **120**. The storage pad **160** may be connected to the

storage connection area **103b** of the cell active area ACT. In this regard, the storage pad **160** may act as the landing pad LP.

(112) The storage pad **160** may overlap a portion of a top face of each of the cell conductive lines **140N**, **140DA**, and **140DB**. The storage pad **160** may include, for example, at least one of a semiconductor material doped with impurities, a conductive silicide compound, a conductive metal nitride, a conductive metal carbide, a metal, and a metal alloy, but example embodiments are not limited thereto.

(113) A pad separation insulating film **180** may be formed on the storage pad **160** and the cell conductive lines **140N**, **140DA**, and **140DB**. For example, the pad separation insulating film **180** may be disposed on the cell line capping film **144**. The pad separation insulating film **180** may separate the storage pads **160** constituting a plurality of isolated areas from each other. The pad separation insulating film **180** may not cover a top face **160US** of the storage pad. The pad separation insulating film **180** may fill a pad separation recess. The pad separation recess may separate adjacent storage pads **160** from each other.

(114) The pad separation insulating film **180** may include an insulating material, and may electrically separate the plurality of storage pads **160** from each other. For example, the pad separation insulating film **180** may include, for example, at least one of a silicon oxide film, a silicon nitride film, a silicon oxynitride film, a silicon oxycarbonitride film, and a silicon carbonitride film. The present inventive concepts are not limited thereto.

(115) The peripheral gate structure may be disposed on the substrate **100** and in the peripheral area **24**. The peripheral gate structure may be disposed on a peripheral active area defined by a peripheral element isolation film. The peripheral gate structure may be formed in the peripheral area **24**, and may be included in a peripheral circuit for controlling a memory cell formed in the cell area **20**.

(116) The peripheral gate structure may include a peripheral gate insulating film **230**, a peripheral gate conductive film **240**, and a peripheral capping film **244** sequentially stacked on the substrate **100**. The peripheral gate structure may include a peripheral spacer **245** disposed on a sidewall of the peripheral gate conductive film **240** and a sidewall of the peripheral capping film **244**.

(117) The boundary peripheral gate PR_GE shown in FIG. 4 may include the peripheral gate conductive film **240**. That is, the peripheral gate structure of the peripheral area **24** may include the peripheral gate insulating film **230**, the peripheral gate conductive film **240**, the peripheral capping film **244**, and the peripheral spacer **245** as shown in FIG. 6.

(118) The peripheral gate conductive film **240** may include first to third peripheral conductive films **241**, **242**, and **243** sequentially stacked on the peripheral gate insulating film **230**. In one example, an additional conductive film may not be disposed between the peripheral gate conductive film **240** and the peripheral gate insulating film **230**. In another example, unlike a configuration as shown, an additional conductive film such as a work function conductive film may be disposed between the peripheral gate conductive film **240** and the peripheral gate insulating film **230**.

(119) The peripheral gate conductive film **240** may have the same or substantially the same stack structure as that of each of the cell conductive lines **140N**, **140DA**, and **140DB**. The first peripheral conductive film **241** may include the same or substantially the same material as that of the first cell conductive film **141**. The second peripheral conductive film **242** may include the same or substantially the same material as that of the second cell conductive film **142**. The third peripheral conductive film **243** may include the same or substantially the same material as that of the third cell conductive film **143**.

(120) The peripheral gate insulating film **230** may include, for example, silicon oxide, silicon nitride, silicon oxynitride, or a high dielectric constant material having a higher dielectric constant than that of silicon oxide. The peripheral spacer **245** may include, for example, at least one of silicon nitride, silicon oxynitride, silicon oxide, silicon carbonitride, silicon oxycarbonitride, and combinations thereof. The peripheral capping film **244** may include, for example, at least one of a

silicon nitride film, a silicon oxynitride, and a silicon oxide. However, example embodiments are not limited to these materials.

(121) A lower etch stop film **250** may be disposed on the substrate **100**. The lower etch stop film **250** may be formed along a profile of the peripheral gate structure. The lower etch stop film **250** may be disposed on the sidewalls of the cell conductive lines **140N**, **140DA**, and **140DB** extending in the first direction D1. The lower etch stop film **250** may extend along a long sidewall of the first outermost dummy cell conductive line **140DA** extending in the second direction D2. The lower etch stop film **250** may include, for example, at least one of a silicon nitride, a silicon oxynitride, a silicon carbonitride, and a silicon oxycarbonitride, but example embodiments are not limited thereto.

(122) The lower peripheral interlayer insulating film **290** may be disposed on the lower etch stop film **250**. The lower peripheral interlayer insulating film **290** may be disposed on the cell area separation film **22** and between the first outermost dummy cell conductive line **140DA** and the peripheral gate conductive film **240**.

(123) The lower peripheral interlayer insulating film **290** may include an oxide-based insulating material. A top face of the lower peripheral interlayer insulating film **290** may be coplanar with the lower etch stop film **250** extending along a top face of the peripheral capping film **244**.

(124) An upper peripheral interlayer insulating film **291** is disposed on the peripheral gate conductive film **240** and a lower peripheral interlayer insulating film **290**. The upper peripheral interlayer insulating film **291** may cover the lower etch stop film **250** and the lower peripheral interlayer insulating film **290**.

(125) The upper peripheral interlayer insulating film **291** may include a material different from that of the lower peripheral interlayer insulating film **290**. The upper peripheral interlayer insulating film **291** may include, for example, a nitride-based insulating material. For example, the upper peripheral interlayer insulating film **291** may include silicon nitride.

(126) A peripheral wire line **265** may be disposed on the upper peripheral interlayer insulating film **291**. The peripheral wire line **265** may connect a peripheral circuit formed in the peripheral area **24** and a memory cell formed in the cell area **20** to each other.

(127) A bit-line contact plug **261** may extend through the upper peripheral interlayer insulating film **291** and the cell line capping film **144** and may be connected to the normal cell conductive line **140N**. The bit-line contact plug **261** may be connected to a peripheral circuit formed in the peripheral area **24**.

(128) In one example, the bit-line contact plug **261** may not be connected to the dummy cell conductive lines **140DA** and **140DB**. That is, the bit-line contact plug **261** connected to the dummy cell conductive lines **140DA** and **140DB** may not be formed on the dummy cell conductive lines **140DA** and **140DB**. In another example, the bit-line contact plug **261** may be connected to the dummy cell conductive lines **140DA** and **140DB**. However, the bit-line contact plug **261** connected to the dummy cell conductive lines **140DA** and **140DB** may not be connected to the peripheral circuit formed in the peripheral area **24**. Alternatively, the bit-line contact plug **261** connected to the dummy cell conductive lines **140DA** and **140DB** may not be connected to a voltage source or a current source.

(129) The peripheral wire line **265** and the bit-line contact plug **261** may include the same or substantially the same material as that of the storage pad **160**. However, the present inventive concepts are not limited thereto. The peripheral wire line **265** and the bit-line contact plug **261** may be formed at the same vertical level at which the storage pad **160** is formed. However, the present inventive concepts are not limited thereto. In this regard, the phrase “being formed at the same vertical level as” may mean being manufactured in the same or substantially the same manufacturing process. A top face **265US** of the peripheral wire line and a top face of the bit-line contact plug **261** may be coplanar or substantially coplanar with the top face **160US** of the storage pad.

(130) An upper etch stop film **295** may be disposed on the storage pad **160**, the pad separation insulating film **180**, the peripheral wire line **265**, and the bit-line contact plug **261**. The upper etch stop film **195** may extend to the cell area **20** and also to the peripheral area **24**. The upper etch stop film **195** may include at least one of a silicon nitride film, a silicon carbonitride film, a silicon boron nitride film (SiBN), a silicon oxynitride film, and a silicon oxycarbide film, but example embodiments are not limited thereto.

(131) The information storage **190** may be disposed on the storage pad **160**. The information storage **190** may be electrically connected to the storage pad **160**. A portion of the information storage **190** may be disposed in the upper etch stop film **295**. Although the information storage **190** may include, for example, a capacitor, the present inventive concepts are not limited thereto. The information storage **190** includes a lower electrode **191** and a capacitor dielectric film **192**, and an upper electrode **193**. For example, the upper electrode **193** may be a plate upper electrode having a plate shape. Although the upper electrode **193** is illustrated as being composed of a single film, it is only for convenience of illustration. The present inventive concepts are not limited thereto.

(132) The lower electrode **191** may be disposed on the storage pad **160**. Although the lower electrode **191** is shown to have a pillar shape, the present inventive concepts are not limited thereto. In another example, the lower electrode **191** may have a cylindrical shape. The capacitor dielectric film **192** is formed on the lower electrode **191**. The capacitor dielectric film **192** may be formed along a profile of the lower electrode **191**. The upper electrode **193** is formed on the capacitor dielectric film **192**. The upper electrode **193** may surround an outer sidewall of the lower electrode **191**.

(133) In one example, the capacitor dielectric film **192** may be disposed at a portion overlapping the upper electrode **193** in the fourth direction D4. In another example, unlike a configuration as illustrated, the capacitor dielectric film **192** may include a first portion overlapping the upper electrode **193** in the fourth direction D4, and a second portion not overlapping the upper electrode **193** in the fourth direction D4. That is, the second portion of the capacitor dielectric film **192** is not covered with the upper electrode **193**.

(134) Each of the lower electrode **191** and the upper electrode **193** may include, for example, a doped semiconductor material, a conductive metal nitride (such as titanium nitride, tantalum nitride, niobium nitride, or tungsten nitride), a metal (such as ruthenium, iridium, or titanium, or tantalum, etc.), and a conductive metal oxide (such as iridium oxide or niobium oxide, etc.). The present inventive concepts are not limited thereto.

(135) Although the capacitor dielectric film **192** may include, for example, one of silicon oxide, silicon nitride, silicon oxynitride and high dielectric constant material and combinations thereof, the present inventive concepts are not limited thereto. In the semiconductor memory device according to some example embodiments, the capacitor dielectric film **192** may include a stack structure in which layers made of zirconium oxide, aluminum oxide, and zirconium oxide are sequentially stacked. In the semiconductor memory device according to some example embodiments, the capacitor dielectric film **192** may include a dielectric film including hafnium (Hf). In the semiconductor memory device according to some example embodiments, the capacitor dielectric film **192** may have a stack structure of a ferroelectric material film and a paraelectric material film.

(136) An interlayer insulating film **292** may be disposed on the upper etch stop film **295**. The interlayer insulating film **292** may cover a sidewall of the upper electrode **193**. The interlayer insulating film **292** may include an insulating material.

(137) FIG. **10** is a diagram for illustrating a semiconductor memory device according to some example embodiments. FIG. **11** is a diagram for illustrating a semiconductor memory device according to some example embodiments. For convenience of description, following description is based on differences thereof from those as described with reference to FIG. **1** to FIG. **9**.

(138) For reference, FIG. **10** is a cross-sectional view taken along A-A of FIG. **4**, and FIG. **11** is a

cross-sectional view taken along C-C of FIG. 5.

(139) Referring to FIG. 10, in the semiconductor memory device according to some example embodiments, the storage contacts **120** respectively including first air gaps AG_BC may be arranged in a discrete manner.

(140) For example, the plurality of storage contacts **120** may include a first storage contact, a second storage contact, and a third storage contact. The first storage contact, the second storage contact and the third storage contact may be sequentially arranged from the cell area separation film **22** and in the first direction D1. The second storage contact may be disposed between the first storage contact and the third storage contact.

(141) For example, each of the first storage contact and the third storage contact may include the first airgap AG_BC. The second storage contact does not include the first airgap AG_BC. The second storage contact not including the first airgap AG_BC may be disposed between the first storage contact including the first airgap AG_BC and the third storage contact including the first airgap AG_BC.

(142) The storage contacts **120** including the first airgap AG_BC may be arranged to be spaced from each other by a regular spacing. However, the present inventive concepts are not limited thereto.

(143) It is shown that two second storage contacts that do not include the first airgap AG_BC are disposed between the first storage contact including the first airgap AG_BC and the third storage contact including the first airgap AG_BC. However, this is only for convenience of the description. The inventive concepts are not limited thereto.

(144) Further, although it is illustrated that two storage contacts **120** including the first air gap AG_BC are arranged in a non-discrete manner, the present inventive concepts are not limited thereto.

(145) Referring to FIG. 11, the semiconductor memory device according to some example embodiments may further include a second airgap AG_DC disposed between each of the cell conductive lines **140N**, **140DA**, and **140DB** and the bit-line contact **146**.

(146) One of the cell conductive lines **140N**, **140DA**, and **140DB** may be disposed on the plurality of bit-line contacts **146** arranged in the first direction D1. The plurality of bit-line contacts **146** may include the first bit-line contact, the second bit-line contact and the third bit-line contact under one of the cell conductive lines **140N**, **140DA**, and **140DB**.

(147) The first to third bit-line contacts may be sequentially arranged from the cell area separation film **22** in the second direction D2.

(148) In FIG. 11 in which the normal cell conductive line **140N** is shown, the second airgap AG_DC may be disposed between the first bit-line contact and the normal cell conductive line **140N**, and between the third bit-line contact and the normal cell conductive line **140N**. The second airgap AG_DC is not disposed between the second bit-line contact and the normal cell conductive line **140N**.

(149) The second airgaps AG_DC may be arranged in a discrete manner between one normal cell conductive line **140N** and the plurality of bit-line contacts **146**. Although it is illustrated that one second bit-line contact is disposed between the second airgaps AG_DC, this is only for convenience of description. The inventive concepts are not limited thereto.

(150) A vertical level of each of a top face **146US** of the first bit-line contact in which the second airgap AG_DC is disposed and a top face **146US** of the third bit-line contact in which the second airgap AG_DC is disposed may be lower than that of a top face **146US** of the second bit-line contact in which the second airgap AG_DC is not disposed. Each of a vertical dimension from the top face of substrate **100** to the top face **146US** of the first bit-line contact in which the second airgap AG_DC is disposed and a vertical dimension from the top face of substrate **100** to the top face **146US** of the third bit-line contact in which the second airgap AG_DC is disposed may be smaller than a vertical dimension from the top face of substrate **100** to a bottom face **142BS** of the

second cell conductive film. Each of a vertical level of the top face **146US** of the first bit-line contact in which the second airgap AG_DC is disposed and a vertical level of the top face **146US** of the third bit-line contact in which the second airgap AG_DC is disposed may be lower than a vertical level of the top face **141US** of the first cell conductive film.

(151) In one example, the top face **146US** of the first bit-line contact in which the second airgap AG_DC is disposed and the top face **146US** of the third bit-line contact in which the second airgap AG_DC is disposed may not contact the bottom face **142BS** of the second cell conductive film. Unlike a configuration shown, in another example, a portion of the top face **146US** of the first bit-line contact in which the second airgap AG_DC is disposed, and a portion of the top face **146US** of the third bit-line contact in which the second airgap AG_DC is disposed may contact the bottom face **142BS** of the second cell conductive film.

(152) In one example, the plurality of storage contacts **120** arranged along the first direction D1 may not include the first airgap (e.g., AG_BC in FIG. 10).

(153) FIG. 12 is a schematic layout diagram of a semiconductor memory device according to some example embodiments. FIG. 13 is an illustrative cross-sectional view taken along A-A of FIG. 12. For convenience of description, following descriptions are based on differences thereof from those described with reference to FIG. 1 to FIG. 9.

(154) For reference, FIG. 12 is a schematic layout diagram of a R2 area in FIG. 1.

(155) Referring to FIG. 12 and FIG. 13, in the semiconductor memory device according to some example embodiments, the width W21 of the first outermost dummy cell conductive line **140DA** may be greater than the width W22 of the inner dummy cell conductive line **140DB**.

(156) The width W22 of the inner dummy cell conductive line **140DB** may be equal or substantially equal to the width W1 of the normal cell conductive line **140N**.

(157) The ratio of each of the widths W21 and W22 of the dummy cell conductive lines **140DA** and **140DB** to the width W1 of the normal cell conductive line **140N** may be in a range from 1 to 2.

(158) For example, the ratio W21/W1 of the width W21 of the first outermost dummy cell conductive line **140DA** to the width W1 of the normal cell conductive line **140N** may be in a range from 1 exclusive to 2 inclusive. The ratio W22/W1 of the width W22 of the inner dummy cell conductive line **140DB** to the width W1 of the normal cell conductive line **140N** may be 1. The ratio W21/W22 of the width W21 of the first outermost dummy cell conductive line **140DA** to the width W22 of the inner dummy cell conductive line **140DB** may be in a range from 1 exclusive to 2 inclusive.

(159) For example, the width W1 of the normal cell conductive line **140N** may be in a range from 5 nm to 25 nm. Each of the widths W21 and W22 of the dummy cell conductive lines **140DA** and **140DB** may be smaller than or equal to 30 nm.

(160) For example, each of the widths W21 and W22 of the dummy cell conductive lines **140DA** and **140DB** may be in a range from 5 nm to 30 nm. The width W22 of the inner dummy cell conductive line **140DB** may be in a range from 5 nm to 25 nm. The width W21 of the first outermost dummy cell conductive line **140DA** may be in a range from 5 nm to 30 nm.

(161) In another example, a ratio of each of the widths W21 and W22 of the dummy cell conductive lines **140DA** and **140DB** to the width W1 of the normal cell conductive line **140N** may be in a range from 1 inclusive to 1.7 inclusive. The ratio W21/W22 of the width W21 of the first outermost dummy cell conductive line **140DA** to the width W22 of the inner dummy cell conductive line **140DB** may be in a range from 1 exclusive to 1.7 inclusive.

(162) In another example, the ratio of each of the widths W21 and W22 of the dummy cell conductive lines **140DA** and **140DB** to the width W1 of the normal cell conductive line **140N** may be in a range from 1 inclusive to 1.5 inclusive. The ratio W21/W22 of the width W21 of the first outermost dummy cell conductive line **140DA** to the width W22 of the inner dummy cell conductive line **140DB** may be in a range from 1 exclusive to 1.5 inclusive. Description thereof will be described later with reference to FIG. 24 to FIG. 27.

(163) FIG. **14** is a schematic layout diagram of a semiconductor memory device according to some example embodiments. For convenience of description, the description is based on differences thereof from those described with reference to FIG. **1** to FIG. **9**.

(164) For reference, FIG. **14** is a schematic layout diagram of a R2 area in FIG. **1**.

(165) Referring to FIG. **14**, in the semiconductor device according to some example embodiments, the dummy bit-line group BL_DG includes six dummy bit-lines.

(166) The dummy bit-line group BL_DG includes 5 inner dummy bit-lines BL_DB and one outermost dummy bit-line BL_DA.

(167) A width W21 of the outermost dummy bit-line BL_DA and each of widths W22 and W23 of the inner dummy bit-lines BL_DB in the first direction D1 are illustrated as being equal to each other. However, the present inventive concepts are not limited thereto.

(168) The inner dummy bit-line BL_DB may include a first inner dummy bit-line BL_DB and a second inner dummy bit-line BL_DB. The first inner dummy bit-line BL_DB may be disposed between the second inner dummy bit-line BL_DB and the outermost dummy bit-line BL_DA. The first inner dummy bit-line BL_DB may be or may not be a dummy bit-line closest to the outermost dummy bit-line BL_DA.

(169) A width of the first inner dummy bit-line BL_DB in the first direction D1 may be W22. A width of the second inner dummy bit-line BL_DB in the first direction D1 may be W23.

(170) In one example, the width W21 of the outermost dummy bit-line BL_DA may be greater than each of the widths W22 and W23 of the inner dummy bit-lines BL_DB in the first direction D1. The width W22 of the first inner dummy bit-line BL_DB may be equal or substantially equal to the width W23 of the second inner dummy bit-line BL_DB. Each of the widths W22 and W23 of the inner dummy bit-lines BL_DB may be equal to the width W1 of the normal bit-line BL_N.

(171) In another example, the width W22 of the first inner dummy bit-line BL_DB may be greater than the width W23 of the second inner dummy bit-line BL_DB. The width W21 of the outermost dummy bit-line BL_DA may be smaller than or equal to the width W22 of the first inner dummy bit-line BL_DB. The width W23 of the second inner dummy bit-line BL_DB may be equal or substantially equal to the width W1 of the normal bit-line BL_N.

(172) FIG. **15** to FIG. **21** are diagrams of intermediate structures of steps for illustrating a method for manufacturing a semiconductor memory device according to some example embodiments. Those of descriptions of the manufacturing method that are duplicate with those described using FIG. **1** to FIG. **14** are briefly described or omitted. Further, the description of the manufacturing method is made using a cross section cut along the lines A-A and B-B of FIG. **4**.

(173) Referring to FIG. **1** to FIG. **5**, FIG. **15** to FIG. **17**, the substrate **100** including the cell area **20**, the peripheral area **24**, and the cell area separation film **22** is provided.

(174) In the cell area **20**, the cell element isolation film **105** separation the cell active area ACT may be formed.

(175) The cell gate structure **110** may be formed in the substrate **100** and in the cell area **20**. The cell gate structure **110** may extend in an elongate manner in the first direction D1. The cell gate structure **110** may include the cell gate trench **115**, the cell gate insulating film **111**, the cell gate electrode **112**, the cell gate capping pattern **113**, and the cell gate capping conductive film **114**.

(176) Subsequently, the cell insulating film **130** may be formed on the cell area **20**. The cell insulating film **130** may expose a portion of the substrate **100** in the peripheral area **24**.

(177) Subsequently, the cell conductive lines **140N**, **140DA**, **140DB**, and the cell line capping film **144** may be formed on the substrate **100** and in the cell area **20**. That is, a plurality of bit-lines BL extending in the second direction D2 may be formed on the substrate **100** and in the cell area **20**. The outermost dummy cell conductive line **140DA** and the inner dummy cell conductive line **140DB** are disposed in the dummy cell area **20_DCR**, while the normal cell conductive line **140N** is disposed in the normal cell area **20_NCR**.

(178) While the cell conductive lines **140N**, **140DA**, and **140DB** and the cell line capping film **144**

are being formed, the peripheral gate conductive film **240** and the peripheral capping film **244** may be formed. The insulating material film including the peripheral capping film **244**, the lower etch stop film **250**, and the upper peripheral interlayer insulating film **291** may be patterned such that the cell line capping film **144** may be formed.

(179) The peripheral structure PR_ST is formed in the peripheral area **24**. The peripheral structure PR_ST may include the peripheral gate conductive film **240**, the peripheral capping film **244**, the peripheral gate insulating film **230**, the peripheral spacer **245**, the lower peripheral interlayer insulating film **290**, and the upper peripheral interlayer insulating film **291**.

(180) While the cell conductive lines **140N**, **140DA**, and **140DB** and the cell line capping film **144** are being formed, the bit-line contact **146** may be formed.

(181) In FIG. **15**, a ratio of the width of the first outermost dummy cell conductive line **140DA** in the first direction D1 to the width of the inner dummy cell conductive line **140DB** in the first direction D1 may be in a range from 1 inclusive to 2 inclusive.

(182) In FIG. **16**, a ratio of the width of the second outermost dummy cell conductive line **140DAA** in the first direction D1 to the width of the inner dummy cell conductive line **140DB** in the first direction D1 may be greater than or equal to 3. The second outermost dummy cell conductive line **140DAA** may correspond to the outermost dummy bit-line BL_DA.

(183) Following description is made with reference to FIG. **15**.

(184) Subsequently, the cell line spacer **150** may be formed. While the fourth cell line spacer **154** is formed, a storage contact recess **120R** may be formed between the cell conductive lines **140N**, **140DA**, and **140DB** adjacent to each other in the first direction D1.

(185) A vertical level of the top face PR_STUS of the peripheral structure based on a top face of the substrate **100** is shown to be the same or substantially the same as a vertical level of the top face of the cell line capping film **144** based on the top face of the substrate **100**. However, this is only for convenience of illustration. The present inventive concepts are not limited thereto.

(186) Subsequently, the first semiconductor material film **121** may be formed on the substrate **100**. The first semiconductor material film **121** may include a semiconductor material containing impurities therein. For example, the first semiconductor material film **121** may include, but is not limited to, amorphous silicon including the impurities therein.

(187) The first semiconductor material film **121** may cover the cell conductive lines **140N**, **140DA**, **140DB** and the peripheral structure PR_ST. The first semiconductor material film **121** may cover the top face of the cell line capping film **144** and the top face PR_STUS of the peripheral structure. The first semiconductor material film **121** may cover the top face of the cell gate capping pattern **113**.

(188) The first semiconductor material film **121** may fill or substantially fill the storage contact recess **120R**. The first semiconductor material film **121** may fill or substantially fill a space between the cell conductive lines **140N**, **140DA**, and **140DB** adjacent to each other in the first direction D1.

(189) A thickness **t1** of the first semiconductor material film **121** may satisfy a following Relationship 1. The thickness **t1** of the first semiconductor material film **121** may be a distance from the top face PR_STUS of the peripheral structure to the top face **121US** of the first semiconductor material film.

$$(190) \left(\frac{N}{2} + \frac{1}{8} + \right) n_{a-Si} \leq t_{a-Si} \leq \left(\frac{N}{2} + \frac{3}{8} + \right) n_{a-Si} \quad (\text{Relationship 1})$$

(191) In the Relationship 1, $t_{\text{sub.a-Si}}$ may denote the thickness **t1** of the first semiconductor material film **121**. λ denotes a wavelength of laser used in a laser annealing process (e.g., **60** in FIG. **18**). $n_{\text{sub.a-Si}}$ denotes a refractive index of the first semiconductor material film **121**. N is one of 1, 2, and 3. Δ denotes an optical path correction factor. Δ may be in a range from $-\frac{1}{8}$ inclusive to $\frac{1}{8}$ inclusive.

(192) Alternatively, N may be a natural number of 4 or greater. When N is a natural number greater

than 4, the thickness **t1** of the first semiconductor material film **121** may be larger than desired or necessary. In this case, efficiency of the manufacturing process may be deteriorated, and a process unit cost may increase.

(193) For example, when the first semiconductor material film **121** includes amorphous silicon, $n_{\text{sub.a-Si}}$ may refer to a refractive index of the amorphous silicon. The optical path correction factor may be affected by a difference between the vertical level of the top face PR_STUS of the peripheral structure disposed on the substrate **100** and the vertical level of the top face of the cell line capping film **144**. Further, the optical path correction factor may be affected by a shape of the peripheral structure PR_ST disposed in the peripheral area **24**, and the width of and a spacing between the cell conductive lines **140N**, **140DA**, and **140DB** disposed in the cell area **20**.

(194) Referring to FIG. **18** and FIG. **19**, the laser may be irradiated onto the first semiconductor material film **121**. The laser annealing process **60** may be performed.

(195) Under the laser annealing process **60**, a second semiconductor material film **122** may be formed on the substrate **100**. The second semiconductor material film **122** may be formed by recrystallizing the first semiconductor material film **121**. When the laser is irradiated onto the first semiconductor material film **121**, the first semiconductor material film **121** is heated and melts, so that the first semiconductor material film **121** may be recrystallized.

(196) Although not shown, the first air gap (e.g., AG_BC of FIG. **10**) may be formed in the second semiconductor material film **122**. Alternatively, the second air gap (AG_DC of FIG. **11**) may be formed between each of the cell conductive lines **140N**, **140DA**, and **140DB** and the bit-line contact **146**.

(197) Referring to FIG. **20** and FIG. **21**, a portion of the second semiconductor material film **122** on a top face of the cell line capping film **144** and the top face PR_STUS of the peripheral structure may be removed.

(198) The second semiconductor material film **122** may be patterned such that the storage contact **120** may be formed on the substrate **100** and in the cell area **20**. The storage contact **120** may be connected to the active area ACT of the cell area **20**.

(199) The fence pattern **170** may be formed on the cell gate structure **110**. The fence pattern **170** may fill or substantially fill a space in which a portion of the second semiconductor material film **122** has been removed.

(200) Although not shown, a portion of the storage contact **120** may be removed after the second semiconductor material film **122** has been patterned. A vertical level of a top face of the storage contact **120** may be lower than that of a top face of the cell line capping film **144**.

(201) Then, referring to FIG. **6** and FIG. **7**, the storage pad **160** may be formed on the storage contact **120**. Further, the information storage element **190** connected to the storage pad **160** may be formed.

(202) FIG. **22** and FIG. **23** are diagrams to illustrate an effect of a thickness of the semiconductor material film formed on the substrate on intensity of laser energy absorbed by the semiconductor material film.

(203) The first cell structure C_ST1, the second cell structure C_ST2 and the peripheral structure PR_ST may be disposed on the substrate **100** including the cell area **20**, the cell area separation film **22**, and the peripheral area **24**. The second cell structure C_ST2 may refer to a structure disposed at the outermost portion of the cell area **20** among the first and second cell structures C_ST1 and C_ST2.

(204) The first semiconductor material film **121** may cover the first cell structure C_ST1, the second cell structure C_ST2, and the peripheral structure PR_ST.

(205) When the thickness **t1** of the first semiconductor material film **121** does not satisfy the Relationship 1, the intensity of laser energy absorbed by the first semiconductor material film **121** may correspond to (1) in FIG. **23**.

(206) When the laser annealing process **60** is performed while the thickness **t1** of the first

semiconductor material film **121** does not satisfy the Relationship 1, excessive heat may be generated near the cell area separation film **22**. The heat generated from the laser annealing process **60** may flow to the cell area **20** which contacts the cell area separation film **22** such that a boundary is defined therebetween. That is, inside the first semiconductor material film **121**, the heat flow from the peripheral area **24** to the cell area **20** may occur. Thus, the heat flow may affect the bit-line contact **146** made of a semiconductor material near the boundary of the cell area **20**. That is, a defect may occur between the normal cell conductive line **140N** and the bit-line contact **146** disposed near the boundary of the cell area **20**.

(207) When the thickness t_1 of the first semiconductor material film **121** satisfies the above Relationship 1, the intensity of laser energy absorbed by the first semiconductor material film **121** may correspond to (2) of FIG. **23**.

(208) When the laser annealing process **60** is performed while the thickness t_1 of the first semiconductor material film **121** does not satisfy the Relationship 1, excessive heat may not be generated near the cell area separation film **22**.

(209) FIG. **24** to FIG. **27** are diagrams to illustrate an effect of an arrangement of structures on the substrate on intensity of laser energy absorbed by the semiconductor material film.

(210) In FIG. **24** to FIG. **27**, the first cell structure C_ST1, the second cell structure C_ST2, and the peripheral structure PR_ST may be disposed on the substrate **100**.

(211) The first cell structure C_ST1 may have a fourth width W_{31} . The second cell structure C_ST2 may have a fifth width W_{32} . The cell structures C_ST1 and C_ST2 may include one second cell structure C_ST2 and at least one first cell structure C_ST1.

(212) The first cell structure C_ST1 may correspond to the inner dummy cell conductive line **140DB** and the normal cell conductive line **140N** as described with reference to FIG. **1** to FIG. **14**. The second cell structure C_ST2 may correspond to the first outermost dummy cell conductive line **140DA**.

(213) FIG. **25** and FIG. **27** are graphs showing the intensity of laser energy absorbed by the first semiconductor material film **121** on the cell area **20** under the laser annealing process **60**. FIG. **25** is a graph showing the intensity of laser energy absorbed by the first semiconductor material film **121** when the cell structures C_ST1 and C_ST2 are arranged as shown in FIG. **24**. FIG. **27** is a graph showing the intensity of laser energy absorbed by the first semiconductor material film **121** when the cell structures C_ST1 and C_ST2 are arranged as shown in FIG. **26**.

(214) In FIG. **25** and FIG. **27**, the cell area **20** may include the dummy cell area **20_DCR** and the normal cell area **20_NCR**. The intensity of laser energy absorbed by the first semiconductor material film **121** on the cell area **20** may be located between an upper limit U.L. of absorption intensity and a lower limit L.L. of absorption intensity.

(215) A ratio W_{32}/W_{31} of the width W_{32} of the second cell structure C_ST2 to the width W_{31} of the first cell structure C_ST1 in FIG. **24** is greater than a ratio W_{32}/W_{31} of the width W_{32} of the second cell structure C_ST2 to the width W_{31} of the first cell structure C_ST1 in FIG. **26**. In FIG. **26**, the ratio W_{32}/W_{31} of the width W_{32} of the second cell structure C_ST2 to the width W_{31} of the first cell structure C_ST1 may be greater than or equal to 1.

(216) In the normal cell area **20_NCR** of FIG. **25**, a difference between a maximum value and a minimum value of the intensity of laser energy absorbed by the first semiconductor material film **121** may be a first energy gap **GAP1**. In the normal cell area **20_NCR** of FIG. **27**, the difference between the maximum value and the minimum value of the intensity of laser energy absorbed by the first semiconductor material film **121** may be a second energy gap **GAP2**.

(217) The second energy gap **GAP2** in the normal cell area **20_NCR** of FIG. **27** is smaller than the first energy gap **GAP1** in the normal cell area **20_NCR** of FIG. **25**. In other words, as the ratio W_{32}/W_{31} of the width W_{32} of the second cell structure C_ST2 to the width W_{31} of the first cell structure C_ST1 decreases, the energy gap in the normal cell area **20_NCR** may decrease.

(218) When a process condition of the laser annealing process **60** varies, a probability at which the

intensity of laser energy absorbed by the first semiconductor material film **121** deviates out of the upper limit U.L. of absorption intensity or the lower limit L.L. of absorption intensity in FIG. **25** is higher than that in FIG. **27**. That is, reducing the ratio W32/W31 of the width W32 of the second cell structure C_ST2 to the width W31 of the first cell structure C_ST1 may allow stability and reliability of the manufacturing process to be improved.

(219) The ratio W32/W31 of the width W32 of the second cell structure C_ST2 to the width W31 of the first cell structure C_ST1 may be in a range from 1 inclusive to 2 inclusive. Preferably, the ratio W32/W31 of the width W32 of the second cell structure C_ST2 to the width W31 of the first cell structure C_ST1 may be in a range from 1 inclusive to 1.7 inclusive. More preferably, the ratio W32/W31 of the width W32 of the second cell structure C_ST2 to the width W31 of the first cell structure C_ST1 may be in a range from 1 inclusive to 1.5 inclusive.

(220) FIG. **28** to FIG. **32** are diagrams of intermediate structures of steps for illustrating a method for manufacturing a semiconductor memory device according to some example embodiments. FIG. **33** is a diagram showing reflectance of laser based on a thickness of an anti-reflective film.

(221) For reference, FIG. **28** to FIG. **30** may be directed to a manufacturing process performed after FIG. **15** to FIG. **17**.

(222) Referring to FIG. **1** to FIG. **9** and FIG. **28** to FIG. **30**, an anti-reflective film **70** may be formed on the first semiconductor material film **121**.

(223) The anti-reflective film **70** may be made of an insulating material. The anti-reflective film **70** may be formed of, for example, a single film. A refractive index of the anti-reflective film **70** is lower than that of the first semiconductor material film **121**. The anti-reflective film **70** may include, for example, silicon oxide. The inventive concepts are not limited thereto.

(224) A thickness t2 of the anti-reflective film **70** may satisfy a following Relationship 2.

(225) $0 \leq t_{\text{ox}} \leq \frac{\lambda}{2n_{\text{ox}}}$ (Relationship2)

(226) In the above Relationship 2, t.sub.ox may denote the thickness t2 of the anti-reflective film **70**. λ denotes the wavelength of the laser used in the laser annealing process (e.g., **60** in FIG. **31**). n.sub.ox denotes the refractive index of the anti-reflective film **70**. When the anti-reflective film **70** includes silicon oxide, n.sub.ox may denote a refractive index of silicon oxide.

(227) In FIG. **33**, as the thickness of the anti-reflective film increases, the reflectance of the laser decreases and then increases. In other words, as the thickness of the anti-reflective film increases, the intensity of laser energy absorbed by the first semiconductor material film **121** increases and then decreases.

(228) When a specific reflectance Rc desired or required for the manufacturing process is set, the thickness t2 of the anti-reflection layer **70** may be set to t.sub.2a and t.sub.2b. The specific reflectance Rc may vary depending on an amount of energy required for recrystallization of the first semiconductor material film **121**.

(229) In FIG. **28**, the anti-reflective film **70** may be formed on the cell area **20**, the cell area separation film **22**, and the peripheral area **24**. That is, the anti-reflective film **70** may be formed over an entirety or substantially all of a top face of the substrate **100**.

(230) In FIG. **29**, the anti-reflective film **70** may be formed on the cell area **20**. The anti-reflective film **70** may overlap the cell area **20** in a fourth direction D4. The anti-reflective film **70** may overlap at least a portion of the cell area separation film **22** in the fourth direction D4. The anti-reflective film **70** may not overlap the peripheral area **24** in the fourth direction D4. Contrary to what is shown, in one example, the anti-reflective film **70** may not overlap the cell area separation film **22** in the fourth direction D4. In another example, the anti-reflective film **70** may not overlap a portion of the cell area **20** in the fourth direction D4. In still another example, at least a portion of the peripheral area **24** does not overlap the anti-reflective film **70** in the fourth direction D4. A portion of the peripheral area **24** may not overlap the anti-reflective film **70** in the fourth direction D4, and the remainder of the peripheral area **24** may overlap the anti-reflective film **70** in the fourth

direction D4.

(231) Following description is made with reference to FIG. 28.

(232) Referring to FIG. 31 and FIG. 32, the laser may be irradiated onto the first semiconductor material film 121 on which the anti-reflective film 70 has been formed. The laser annealing process 60 using the anti-reflective film 70 may be performed.

(233) Under the laser annealing process 60, the first semiconductor material film 121 may be recrystallized, such that the second semiconductor material film 122 may be formed on the substrate 100.

(234) Although not shown, the first air gap (e.g., AG_BC of FIG. 10) may be formed in the second semiconductor material film 122. Alternatively, the second air gap (e.g., AG_DC of FIG. 11) may be formed between each of the cell conductive lines 140N, 140DA, and 140DB and the bit-line contact 146.

(235) Then, the anti-reflective film 70 on the second semiconductor material film 122 may be removed. Subsequently, the second semiconductor material film 122 may be patterned such that the storage contact 120 may be formed on the substrate 100 and in the cell area 20.

(236) One or more of the elements disclosed above may include or be implemented in one or more processing circuitries such as hardware including logic circuits; a hardware/software combination such as a processor executing software; or a combination thereof. For example, the processing circuitries more specifically may include, but is not limited to, a central processing unit (CPU), an arithmetic logic unit (ALU), a digital signal processor, a microcomputer, a field programmable gate array (FPGA), a System-on-Chip (SoC), a programmable logic unit, a microprocessor, application-specific integrated circuit (ASIC), etc.

(237) It will be understood that elements and/or properties thereof described herein as being “substantially” the same and/or identical encompasses elements and/or properties thereof that have a relative difference in magnitude that is equal to or less than 10%. Further, regardless of whether elements and/or properties thereof are modified as “substantially,” it will be understood that these elements and/or properties thereof should be construed as including a manufacturing or operational tolerance (e.g., $\pm 10\%$) around the stated elements and/or properties thereof.

(238) Although example embodiments of the present inventive concepts have been described in more detail with reference to the accompanying drawings, the present inventive concepts are not necessarily limited to these example embodiments. The present inventive concepts may be implemented in various modified manners within the scope not departing from the present inventive concepts. Accordingly, the example embodiments disclosed herein are not intended to limit the present inventive concepts. Therefore, it should be understood that the example embodiments as described above are illustrative and non-limiting in all respects.

Claims

1. A semiconductor memory device comprising: a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film; a cell area separation film defining the cell area in the substrate, wherein the dummy cell area defines a boundary with the cell area separation film between the normal cell area and the cell area separation film; a normal bit-line on the normal cell area and extending in a first direction; a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in the first direction; and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction, wherein a width in the second direction of the dummy cell area is greater than or equal to 50 nm and less than or equal to 200 nm, wherein the normal bit-line has a first width in the second direction, and wherein a ratio of a width in the second direction of each of the dummy bit-lines to

the first width is greater than or equal to 1 and less than or equal to 2.

2. The semiconductor memory device of claim 1, wherein the dummy bit-line group includes a first dummy bit-line closest to the peripheral area in the second direction, and a second dummy bit-line between the first dummy bit-line and the normal bit-line, wherein the first dummy bit-line has a second width in the second direction, wherein the second dummy bit-line has a third width in the second direction, and wherein the second width is greater than or equal to the third width.

3. The semiconductor memory device of claim 2, wherein each of the second width and the third width is equal to the first width.

4. The semiconductor memory device of claim 2, wherein the third width is equal to the first width, and wherein a ratio of the second width to the third width is greater than 1 and less than or equal to 2.

5. The semiconductor memory device of claim 1, wherein the first width is greater than or equal to 5 nm and less than or equal to 25 nm.

6. The semiconductor memory device of claim 5, wherein a width in the second direction of at least one of the plurality of dummy bit-lines is less than or equal to 30 nm.

7. The semiconductor memory device of claim 1, wherein the ratio of the width in the second direction of each of the dummy bit-lines to the first width is greater than or equal to 1 and less than or equal to 1.7.

8. The semiconductor memory device of claim 7, wherein the ratio of the width in the second direction of each of the dummy bit-lines to the first width is greater than or equal to 1 and less than or equal to 1.5.

9. The semiconductor memory device of claim 1, wherein a number of the dummy bit-lines included in the dummy bit-line group is greater than or equal to 2 and less than or equal to 6.

10. The semiconductor memory device of claim 1, wherein the plurality of storage contacts includes a first storage contact, a second storage contact, and a third storage contact, wherein the second storage contact is between the first storage contact and the third storage contact, wherein each of the first storage contact and the second storage contact defines an air gap therein, and wherein the third storage contact does not define an air gap.

11. The semiconductor memory device of claim 1, further comprising a plurality of bit-line contacts between the normal bit-line and the substrate, the plurality of bit-line contacts located along the first direction, wherein the plurality of bit-line contacts include a first bit-line contact, a second bit-line contact, and a third bit-line contact, wherein the second bit-line contact is between the first bit-line contact and the third bit-line contact, wherein an air gap is defined between the first bit-line contact and the normal bit-line, and an air gap is defined between the third bit-line contact and the normal bit-line; wherein an air gap not defined between the second bit-line contact and the normal bit-line.

12. The semiconductor memory device of claim 1, further comprising an information storage element connected to each of the storage contacts, wherein the information storage element includes a lower electrode connected to a storage pad, a capacitor dielectric film on the lower electrode, and a plate upper electrode on the capacitor dielectric film.

13. A semiconductor memory device comprising: a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film; a cell area separation film defining the cell area in the substrate, wherein the dummy cell area forms a boundary with the cell area separation film between the normal cell area and the cell area separation film; a normal bit-line group on the normal cell area; a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in a first direction; and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction, wherein the normal bit-line group includes a plurality of normal bit-lines extending in the first direction, wherein the plurality

of normal bit-lines are spaced from each other by a bit-line pitch in the second direction, wherein a width in the second direction of the dummy cell area is greater than the bit-line pitch and is less than or equal to 5 times the bit-line pitch, wherein each of the normal bit-lines has a first width in the second direction, and wherein a ratio of a width in the second direction of each of the dummy bit-lines to the first width is greater than or equal to 1 and less than or equal to 2.

14. The semiconductor memory device of claim 13, wherein the dummy bit-line group includes a first dummy bit-line closest to the peripheral area in the second direction, and a second dummy bit-line between the first dummy bit-line and at least one of the plurality of normal bit-lines, wherein a width in the second direction of the first dummy bit-line is a second width greater than the first width, and wherein a width in the second direction of the second dummy bit-line is equal to the first width.

15. The semiconductor memory device of claim 13, wherein the width in the second direction of each of the dummy bit-lines is equal to the first width.

16. The semiconductor memory device of claim 13, wherein the first width is greater than or equal to 5 nm and less than or equal to 25 nm.

17. The semiconductor memory device of claim 16, wherein the width in the second direction of each of the dummy bit-lines is less than or equal to 30 nm.

18. A semiconductor memory device comprising: a substrate including a cell area and a peripheral area defined by a periphery of the cell area, wherein the cell area includes a dummy cell area and a normal cell area, wherein the cell area includes an active area defined by a cell element isolation film; a cell area separation film defining the cell area in the substrate, wherein the dummy cell area forms a boundary with the cell area separation film between the normal cell area and the cell area separation film; a normal bit-line on the normal cell area and extending in a first direction; a dummy bit-line group on the dummy cell area, wherein the dummy bit-line group includes a plurality of dummy bit-lines extending in the first direction; and a plurality of storage contacts connected to the active area and located along a second direction perpendicular to the first direction, wherein a width in the second direction of the dummy cell area is greater than or equal to 50 nm and less than or equal to 200 nm, wherein a width in the second direction of the normal bit-line is greater than or equal to 5 nm and less than or equal to 25 nm, wherein a width in the second direction of each of the dummy bit-lines is greater than or equal to 5 nm and less than or equal to 30 nm.

19. The semiconductor memory device of claim 18, wherein the dummy bit-line group includes a first dummy bit-line closest to the peripheral area in the second direction, and a second dummy bit-line between the first dummy bit-line and the normal bit-line, wherein a width in the second direction of the first dummy bit-line is greater than a width in the second direction of the second dummy bit-line.

20. The semiconductor memory device of claim 18, wherein the dummy bit-line group includes a first dummy bit-line closest to the peripheral area in the second direction, and a second dummy bit-line between the first dummy bit-line and the normal bit-line, wherein a width in the second direction of the first dummy bit-line is equal to a width in the second direction of the second dummy bit-line.
