

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396736
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Clark; Timothy W. I.

Adhesive pad and hemostasis system

Abstract

An adhesive pad for use with a hemostasis device comprising a footplate having a top surface and a receiving device positioned on the footplate, the adhesive pad comprising: (1) a flexible backing layer having a bottom surface, a central portion having an opening, a first side portion, and a second side portion; (2) an adhesive layer applied to the bottom surface of the backing layer; and (3) a release layer removably secured to the adhesive layer. The opening in the central portion of the backing layer is sized to fit the receiving device of the hemostasis device, and the adhesive layer applied to the bottom surface of the first and second side portions of the backing layer is configured to adhere to and extend beyond the top surface of the footplate.

Inventors:	Clark; Timothy W. I. (Philadelphia, PA)
Applicant:	Forge Medical, Inc. (Morrisville, NC)
Family ID:	1000008781770
Assignee:	Forge Medical, Inc. (Morrisville, NC)
Appl. No.:	18/075061
Filed:	December 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230103229 A1	Mar. 30, 2023

Related U.S. Application Data

continuation parent-doc US 15203049 20160706 US 11517323 child-doc US 18075061

Publication Classification

Int. Cl.: A61B17/132 (20060101); **A61B17/00** (20060101); **A61B17/08** (20060101); **A61B17/12** (20060101)

U.S. Cl.:

CPC **A61B17/132** (20130101); **A61B17/0057** (20130101); **A61B17/085** (20130101);
A61B2017/0065 (20130101); A61B2017/12004 (20130101)

Field of Classification Search

CPC: A61B (17/132); A61B (17/0057); A61B (17/085); A61B (2017/0065); A61B
(2017/12004)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3086530	12/1962	Groom	N/A	N/A
5263965	12/1992	Roth	N/A	N/A
5728120	12/1997	Shani et al.	N/A	N/A
6068646	12/1999	Lam	N/A	N/A
6316686	12/2000	Byrd	N/A	N/A
6332879	12/2000	Nielsen et al.	N/A	N/A
7780612	12/2009	Ross	N/A	N/A
11517323	12/2021	Clark	N/A	A61B 17/132
2002/0058893	12/2001	Vesey	N/A	N/A
2003/0028214	12/2002	Benz et al.	N/A	N/A
2004/0068290	12/2003	Bates et al.	N/A	N/A
2005/0085757	12/2004	Santanello	N/A	N/A
2007/0282239	12/2006	Bates et al.	N/A	N/A
2008/0269659	12/2007	Bergin et al.	N/A	N/A
2009/0171192	12/2008	Patrick et al.	N/A	N/A
2009/0281565	12/2008	Mcneese	N/A	N/A
2010/0152770	12/2009	Spencer	N/A	N/A
2010/0217202	12/2009	Clark	N/A	N/A
2011/0196417	12/2010	Clark	606/201	A61F 5/32
2012/0191128	12/2011	Teeslink et al.	N/A	N/A
2013/0237943	12/2012	Erland	N/A	N/A
2018/0008280	12/2017	Clark	N/A	A61B 17/132

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
67622	12/1981	EP	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 15/203,049, filed Jul. 6, 2016, Pending, U.S. Pat. No. 11,517,323, Dec. 6, 2022.
cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 15/203,049, filed Jul. 6, 2016, the entirety of which is incorporated herein by reference.

BACKGROUND

(1) The present disclosure relates to an improved adhesive attachment system for devices that adhere to a patient's skin at a vascular access site and apply a compressive force to the puncture site to achieve hemostasis.

(2) There are many devices and procedures currently employed in the medical field for achieving hemostasis at a percutaneous vascular access site resulting, for example, from a transradial cardiac catheterization procedure.

(3) Among such prior art devices and procedures are, for example: a non-woven sponge manually applied directly to the site of the bleeding at the puncture site; band-type devices tightened around the arm of the patient and possessing an inflatable balloon over the blood vessel; and notch-shaped compression pad tightened around the arm of the patient much like an electrical tie.

(4) Each of these prior art devices and procedures require extensive interaction with a patient by a clinician. For example, a non-woven sponge requires the clinician apply pressure to the puncture site until hemostasis is achieved. Similarly, band-shaped compression device requires the clinician to use both hands to wrap the device around the arm (or leg) of a patient and inflate the compressive balloon using an air-filled syringe such that the pressure is applied appropriately to the puncture site. None of these prior art devices provides the clinician with a device that can be applied with a single hand in a manner that allows the clinician to simultaneously remove the vascular access sheath so that hemostasis is achieved.

(5) Improving on these prior art devices and procedures, the VasoStat™ hemostasis device has been developed. The VasoStat™ hemostasis device is configured to apply a compressive force to a patient's skin at the site of a percutaneous vascular access. This device comprises a footplate, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough, and motion restricting means interposed between the receiving device and the plunger, the motion restricting means configured such that as the plunger moves toward the skin movement of the plunger away from the skin is restricted until the restricting means are released. So configured, this hemostasis device permits single-handed operation allowing the clinician to quickly and efficiently apply the hemostasis device to the puncture site.

(6) The VasoStat™ hemostasis device employs adhesive pads that are applied to the bottom of the footplate. In operation, these pads secure the device to the patient's skin and enable precise alignment of the device over the intended area of vascular compression. In order for the device to achieve a secure adhesion, the pads must have an adhesive force greater than the compressive force applied on the puncture site by the plunger. Thus, the compressive force that may be applied to a puncture site is limited by the surface area of the bottom of the footplate and by the strength of the adhesive used on the pads. If adhesive pads cover the entire surface area of the bottom of the footplate, the application of higher compressive forces can only be achieved by using stronger adhesives. The use of stronger adhesives, however, increases the likelihood that the removal of the device may cause injury or undue discomfort to the patient. Accordingly, there is a need for an attachment system for such hemostasis devices that permits the application of a wider range of

compressive forces at a puncture site.

SUMMARY

(7) One aspect of the present invention is an adhesive pad for a hemostasis device that has a footplate, a receiving device positioned in the footplate, and a plunger positioned within the receiving device and configured to move therethrough and apply a compressive force to a patient's skin at a puncture site to assist in hemostasis. The adhesive pad comprises a flexible backing layer, an adhesive layer, and a release liner. The flexible backing layer has a bottom surface, a central portion having an opening, a first side portion, and a second side portion. The adhesive layer is applied to the bottom surface of the backing layer, and the release liner is removably secured to the adhesive layer. The opening in the central portion of the backing layer is sized to fit the receiving device of the hemostasis device. The first and second side portions of the backing layer are configured to overlie and adhere to the footplate of the hemostasis device and to the patient's skin about the footplate.

(8) Another aspect of the present invention is a hemostasis system for adhering to a patient's skin and applying a compressive force to a puncture site, the system comprising a hemostasis device and an adhesive pad. The hemostasis device has a footplate, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough, and a plurality of motion restricting components interposed between the receiving device and the plunger. The adhesive pad has a flexible backing layer with a bottom surface, a top surface, a first side portion, and a second side portion, and a central portion, an adhesive layer applied to the bottom surface of the backing layer, and a release liner removably secured to the adhesive layer. The central portion of the backing layer of the adhesive pad has an opening sized to fit the receiving device of the hemostasis device, and the first side portion and the second side portion of the backing layer of the adhesive pad are configured to overlie and adhere to the footplate of the hemostasis device and to the patient's skin about the footplate.

(9) Another aspect of the present invention is a method for applying a compressive force to a patient's skin at a puncture site, the method comprising the steps of placing a hemostasis device on the patient's skin at the puncture site, adhesively anchoring an adhesive pad to the hemostasis device and to the patient's skin proximal to the puncture site, and applying a compressive force to the puncture site.

(10) The hemostasis device employed in the present method comprises a footplate, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough, and a plurality of motion restricting components interposed between the receiving device and the plunger. In practicing the present method, the such hemostasis device is placed on a patient's skin proximal to the puncture site, the plunger is advanced through the receiving device until it applies a compressive force to the puncture site, and the plurality of motion restricting components are engaged to restrict reverse movement of the plunger through the receiving device.

(11) The adhesive pad employed in the present method comprises a flexible backing layer with a bottom surface having an adhesive layer applied thereto, a first side portion, and a second side portion, and a central portion having an opening sized to fit the receiving device of the hemostasis device, wherein at least the first side portion and the second side portion of the backing layer of the adhesive pad overlie and adhere to the footplate of the hemostasis device and to the patient's skin about the footplate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Referring now to the drawings, in which like numerals represent like parts in the several views:

(2) FIG. 1 illustrates a top view of an exemplary embodiment of an adhesive pad for a hemostasis device.

(3) FIG. 2 illustrates a perspective view of the adhesive pad of FIG. 1.

(4) FIG. 3 illustrates a bottom view of the adhesive pad of FIG. 1.

(5) FIG. 4 illustrates a side view of the adhesive pad of FIG. 1.

(6) FIG. 5 illustrates an exemplary embodiment of a hemostasis device for use with an adhesive pad according to the present invention.

(7) FIG. 6 illustrates the hemostasis device of FIG. 5 showing a plunger in an internally ratcheted cylinder prior to use.

(8) FIG. 7 illustrates the hemostasis device of FIG. 5, showing the plunger fully advanced in the cylinder against a puncture site.

(9) FIG. 8 illustrates a second exemplary embodiment of a hemostasis device for use with an adhesive pad according to the present invention.

(10) FIG. 9 illustrates a third exemplary embodiment of a hemostasis device for use with an adhesive pad according to the present invention.

(11) FIG. 10 illustrates a fourth exemplary embodiment of a hemostasis device for use with an adhesive pad according to the present invention.

(12) FIGS. 11A and 11B illustrate an exemplary plunger for use in the hemostasis device of FIG. 10.

(13) FIG. 12 illustrates a perspective view of an exemplary embodiment of a hemostasis system for adhering to a patient's skin and applying a compressive force to a puncture site.

(14) FIG. 13 illustrates a side perspective view of the hemostasis system of FIG. 12.

(15) FIG. 14 illustrates a bottom view of the hemostasis system of FIG. 12.

(16) FIG. 15 illustrates a side view of the hemostasis system of FIG. 12.

DETAILED DESCRIPTION

(17) One aspect of the present invention relates to an adhesive pad for a hemostasis device configured to apply a compressive force to a puncture site on a patient's skin. The hemostasis device is configured such that a clinician may adhere the device to a patient's skin, apply pressure directly to the puncture site using a mechanical plunger, and leave the hemostasis device adhered to the patient's skin until hemostasis is achieved. The hemostasis device may be sized and configured such that it may be used on a patient's forearm, upper arm, head, chest, back, thigh, lower leg, or any other body part. As discussed herein, the hemostasis device is applied to a puncture site resulting from a medical procedure such as, for example, a cardiac catheterization procedure performed through the radial artery; however, the hemostasis device as discussed herein may be applied to any type of puncture site where hemostasis is desired. For example, the hemostasis device described herein may be applied to a wound resulting from an abrasion, incision, laceration, avulsion, amputation, or any other wound where hemostasis is desired. It should be understood that use of the term "puncture site" herein includes punctures resulting from a medical procedure as well as all such types of wounds.

(18) As shown in the embodiment illustrated in FIGS. 1-4, the adhesive pad **100** comprises a flexible backing layer **102**, an adhesive layer **104**, and a release layer **106**. The flexible backing layer **102** has a bottom surface **108**, a central portion **110** having an opening **112**, a first side portion **114**, and a second side portion **116**. The adhesive layer **104** is applied to the bottom surface **108** of the backing layer **102**, and the release layer **106** is removably secured to the adhesive layer **104**. The opening **112** in the central portion **110** of the backing layer **102** is sized to fit over a hemostasis device configured similarly to the hemostasis devices shown in FIGS. 5-10. Such hemostasis devices have a footplate, a receiving device positioned in the footplate, and a plunger positioned within the receiving device and configured to move therethrough and apply a compressive force to a patient's skin at a puncture site. The first and second side portions **114** and **116** of the backing layer **102** are configured to overlie and adhere to the footplate of such hemostasis devices and to

the patient's skin about the footplate.

(19) The backing layer **102** is the main structural component of adhesive pad **100**. The backing layer **102** may comprise paper, woven or unwoven fibers, flexible foam, or plastic film. In embodiments in which the backing layer **102** is flexible foam, the foam may be formed from various elastomer materials such as polyester or polyether polyurethane foams, styrene-butadiene foams, and certain rubber-based foams. In embodiments in which the backing layer **102** is a plastic film, the film may be formed from various polymers including polyethylene, polypropylene, polyurethane, polyester, poly(ethylene-vinyl acetate), and poly(vinyl chloride). The backing layer **102** may comprise a unitary layer or a combination of layers of materials. For multilayer backing layers, the layers may comprise the same or different materials.

(20) The backing layer **102** bears the adhesive layer **104** on its bottom surface **108** and, in operation, is overlaid on the VasoStat™ hemostasis device or similarly configured hemostasis devices, and is adhesively secured to both the top of the footplate of such devices and to the patient's skin about the footplate. The adhesive pad **100** is sized to provide greater contact area with a patient's skin as compared with the adhesive pads disposed on the footplate of the hemostasis device. As a result, the adhesive pad **100** provides greater adhesive strength for a given adhesive than the adhesive pads disposed on the footplate of the hemostasis device. Thus, for applications in which high compressive forces are required, or if only a weak adhesive is appropriate for the patient or the puncture site, the adhesive system of the present invention—the combination of the adhesive pad of the present invention with the VasoStat™ hemostasis device or a similarly configured hemostasis device—provides enhanced adhesion to the patient's skin that cannot be achieved by the hemostasis device alone. Further, use of the adhesive pad of the present invention permits the application of hemostasis devices without adhesive pads disposed on the bottom surface of the footplate.

(21) The backing layer **102** may also be provided in a variety of shapes. In one embodiment, the backing layer **102** comprises an elongated strip in which the central portion **110** is wider than the two side portions **114** and **116**. In another embodiment, the backing layer **102** comprises an elongated strip in which the central portion **110** and the two side portions **114** and **116** have approximately equal widths. In yet another embodiment, the backing layer **102** comprises an elongated strip in which the central portion **110** is narrower than the two side portions **114** and **116**. In still other embodiments, the backing layer **102** has an elliptical or circular shape. For embodiments in which the backing layer **102** has an elliptical or circular shape, the first and second side portions **114** and **116** can be regarded as any pair of complimentary semi-elliptical or semi-circular portions.

(22) The adhesive layer **104** provides the adhesion between the backing layer **102** of the adhesive pad **100** and both the top surface of the footplate of the hemostasis device and the patient's skin about the footplate. Any pharmaceutically acceptable adhesive which provides adhesion to a patient's skin that is releasable without significant injury to the patient may be used as the adhesive layer **104**. Examples of such suitable adhesives include pressure-sensitive adhesives which do not require solvent, water, or heat to activate the adhesive. Such pressure-sensitive adhesives may comprise acrylates, butyl rubber, ethylene-vinyl acetate, natural rubber, nitriles, silicone rubbers, dimethylsiloxane, isobutylene, urethanes, styrene block copolymers, styrene-butadiene-styrene, styrene-ethylene/butylene-styrene, styrene-ethylene/propylene, styrene-isoprene-styrene, and vinyl ethers.

(23) The release layer **106** covers the adhesive layer **104** and is removed prior to use to expose the adhesive layer **104** prior to application to a patient's skin. Materials suitable for use as the release layer **106** are well-known in the art and include paper and plastic films. In embodiments utilizing a paper release layer, the paper may be coated. In one embodiment, the release layer **106** may comprise a unitary structure. In another embodiment, the release layer **106** may comprise plurality of discrete sections. The release layer **106** may also have an opening coincident with the opening

112 in the central portion **110** of the adhesive pad **100**. Alternatively, the release layer **106** may cover a portion or all of the opening **112** in the central portion **110** of the adhesive pad **100**.

(24) Exemplary hemostasis devices suitable for use with the adhesive pad of the present invention are shown in FIGS. 5-11B. As shown in FIGS. 5-9, an exemplary hemostasis device suitable for use with the adhesive pad of the present invention may comprise a footplate **2**, a receiving device such as cylinder **3** positioned on the footplate **2**, a plunger **4** and, optionally, one or more stabilizing means such as one or more curved arms **5** on the footplate **2**. The footplate **2** may be made from a flexible material such that the contour of the footplate is capable of adjusting to various areas of the body of a patient having different curvatures. Also, it should be noted that the receiving device is shown as cylindrical by way of example only. Additional cross-sectional shapes may be used such as a rectangle, square, oval, or other geometric shape that allows the receiving device to accept the plunger **4** and permit movement therethrough.

(25) The engagement of the plunger **4** within the cylinder **3** provides for one-directional movement of the plunger **4** with respect to the cylinder **3** such as, for example, by use of a ratcheting mechanism. In one embodiment, one or more racks **6** positioned on the plunger **4** may engage a pawl **15** positioned in cylinder **3** in such manner as to limit plunger **4** to movement downwardly in cylinder **3**. In other words, plunger **4** may be forced downwardly toward the puncture site, but is restrained from upward movement in the cylinder **3** by the combination and position of the one or more racks **6** and the internally positioned pawl **15** resulting in a ratcheting in the cylinder **3**. In another embodiment, one or more racks **6** on the cylinder **3** may engage a pawl positioned on plunger **4** in such manner as to limit plunger **4** to movement downwardly in cylinder **3**. In yet another embodiment, one or more racks **6** on the plunger **4** may engage corresponding racks **16** positioned in cylinder **3** in such manner as to limit plunger **4** to movement downwardly in cylinder **3**.

(26) As shown in the embodiments represented in FIGS. 5-9, an upper portion of the plunger **4** may be bifurcated whereby, due to the resilience of the material from which the plunger **4** is made, to force the bifurcations **7** and **8** outwardly against the interior of the cylinder **3**, thereby to force the external ratchets **6** on plunger **4** into engagement with the internal ratchets in cylinder **3**. As discussed above, this arrangement restrains the plunger **4** from upward movement through the cylinder **3**.

(27) The bifurcated portions **7** and **8** at the top of the plunger **4** may be, at their extreme upper ends, arcuate shaped **9**, and are adapted to be engaged by a clinician when the hemostasis device **1** is operated. For example, the clinician may engage the top of the plunger **4** with their finger, thumb, palm, or other body part that allows the clinician to assert a downward pressure on the plunger.

(28) The bottom of the plunger **4** may include a compression surface **10** having a compression pad **11** adhered thereto. The compression pad **11** may have a pro-coagulant coating such as calcium alginate, oxidized regenerated cellulose, seaweed extracts, a pro-coagulant polymer, another pro-coagulant coating, or combinations of two or more of these. The compression pad **11** may also have an antimicrobial coating such as silver or chlorhexidine.

(29) One or more pads **12**, with adhesive surfaces on both faces thereof, may be applied to the bottom of the footplate **2** such that, during operation, the pads adhere to the skin **13** of the patient when the hemostasis device **1** is in use thereby assisting in securing the footplate **2** to the patient's skin when in use. The size of the pads **12** may be determined relative to the pressure being applied by the hemostasis device **1** to puncture site and/or the part of the body to which the hemostasis device **1** is being applied. The size of the pads **12** may also be determined relative to the type of adhesive used on the pads **12**. For example, the adhesive force of the pads **12** should be greater than the compressive force applied to the puncture site by the plunger **4**. Typical temporary medical adhesives may be used such that when hemostasis is achieved, the hemostasis device **1** is easily removed.

(30) As shown in FIGS. 5-7, additional features such as curved arms **5** may be included on

footplate **2**. For example, the curved arms **5** may be engaged by the thumb and middle finger of the clinician when the hemostasis device **1** is in use. Alternatively, the curved arms **5** may be engaged by the index and middle fingers of the clinician when the hemostasis device **1** is in use. Either method of operation provides a single-handed operation style allowing the clinician to quickly and efficiently apply the hemostasis device **1**.

(31) As shown in FIGS. **5-9**, the footplate **2** may also be provided with apertures **14** configured and positioned to allow the clinician to observe the position of the rounded portion **10** of the plunger **4** and the compression pad **11** relative to the puncture site to assure that the hemostasis device **1** is properly positioned over the puncture site.

(32) FIGS. **10**, **11A** and **11B** illustrate another embodiment of the hemostasis device. Like hemostasis device **1** shown in FIGS. **5-9**, the hemostasis device **21** may comprise a footplate **22**, a cylinder **23** centrally positioned on footplate **22**, and a plunger **24**. Though not shown in FIGS. **10**, **11A** and **11B**, the footplate **22** may further include stabilizing means such as curved arms **5** as discussed above.

(33) The engagement of the plunger **24** within the cylinder **23** provides for one-directional movement of the plunger **24** with respect to the cylinder **23** by use of a ratcheting mechanism. In the embodiment shown in FIGS. **10**, **11A** and **11B**, a plurality of racks **26** attached to the plunger **24** may engage a corresponding pawl or rack (not shown) in the cylinder **23** in such manner as to limit the plunger **24** to movement downwardly in the cylinder **23**. In other words, the plunger **24** may be forced downwardly toward the puncture site, but is restrained from movement upwardly in the cylinder **23** by the combination and position of racks **26** and the corresponding pawls or racks in the cylinder **23**. In another embodiment, a single rack **26** is attached to the plunger **24** and may engage a corresponding pawl or rack in the cylinder **23**. In yet another embodiment, one or more racks **26** positioned on the cylinder **23** may engage a pawl positioned on plunger **24** in such manner as to limit plunger **24** to movement downwardly in cylinder **23**.

(34) As shown in FIGS. **11A** and **11B**, the plunger **24** may include various components. For example, the plunger **24** may be designed and configured such that the plunger includes a central plunger portion **34** and wings **35a** and **35b**. The central plunger portion **34** may be configured to receive applied downward force as provided by the clinician. The wings **35a** and **35b** may include the racks **26** such that as the clinician applies force to the central plunger portion **34**, the wings **35a** and **35b** ratchet downward against the racks **26** of the cylinder **23**. The wings **35a** and **35b** may also provide a means for releasing the pressure being applied to the puncture site by the plunger **24**. The wings **35a** and **35b** may be squeezed toward the central plunger portion **34**, thereby disengaging the racks **26**, allowing the plunger **24** to move away from the puncture site. This may be done when hemostasis is achieved or if too much pressure has been applied to the puncture site. Further, this embodiment permits one-handed movement of the plunger **24** from the puncture site by compression of wings **35a** and **35b** and movement of the plunger **24** through the cylinder **23** and away from the puncture site.

(35) Similarly, the bottom of the plunger **24** may include a compression surface **30** having a compression pad **31** adhered thereto. The compression pad **31** may have a pro-coagulant coating such as calcium alginate, oxidized regenerated cellulose, seaweed extracts, a pro-coagulant polymer, another pro-coagulant coating, or combinations of two or more of these. The compression pad **31** may also have an antimicrobial coating such as silver or chlorhexidine.

(36) One or more adhesive pads **32** having adhesive surfaces may be applied to the bottom of the footplate **22** such that, during operation, the pads **32** may adhere to the skin of the patient when the hemostasis device **21** is in use, thereby assisting in securing the footplate **22** to the patient's skin to prevent the hemostasis device from shifting position on the skin when in use. The size of the pads **32** may be determined relative to the pressure being applied by the hemostasis device **21** to the puncture site and/or the part of the body to which the hemostasis device **21** is being applied. The size of the pads may also be determined relative to the type of adhesive being used on the pads. For

example, the pulling force exerted on the patient's skin by the one or more pads **32** should be greater than the compressive force applied on the puncture site by the plunger **24**. Higher compressive forces applied on the puncture site may be achieved by increasing the surface area of the pads **32** that are in contact with the skin, either by increasing the size and/or number of pads **32**, using an adhesive having greater adhesive strength, or a combination of the two. Typical temporary medical adhesives may be used such that when hemostasis is achieved, the hemostasis device **21** is easily removed.

(37) It should be noted that the hemostasis devices as shown in FIGS. **5-11B** are shown by way of example only. Additional design features may be incorporated. For example, although only a ratcheting mechanism is disclosed herein to permit only unidirectional movement of plunger, additional locking mechanisms such as a screw machine (not shown herein) or other similar mechanisms may be employed.

(38) The method for applying a compressive force to a patient's skin at a puncture site using the hemostasis devices as shown in FIGS. **5-9** will now be described. In practice, after the removal of the needle from the puncture site in a patient's arm, the hemostasis device **1** may be positioned over the puncture site, the apertures **14** in the footplate **2** permitting visual observance by the medical technician to insure that the compression surface **10** of the plunger **4** and compression pad **11** adhered thereto are placed over the puncture site. In practice, after the removal of the needle from the puncture site in a patient's arm, the hemostasis device **1** may be positioned over the puncture site. In certain embodiments, adhesive pads **12** are positioned on the bottom surface of the footplate **2**. There may also be one or more apertures **14** in the footplate **2** permitting visual observance by the clinician to insure the proper positioning of the compression surface **10** of the plunger **4** (and, optionally, a compression pad **11**) over the puncture site. A compressive force is then applied to the puncture site by advancing the plunger **4** through the receiving device **3**, and the motion restricting components are engaged to prevent reverse movement of the plunger **4**.

(39) The adhesive pads **12** may securely hold the hemostasis device in position on the skin. A finger of the clinician may be placed on the arcuate elements **9** of the plunger **4**. A second finger of the clinician may be placed in engagement with one of the curved arms **5** as a third finger of the clinician may be placed in engagement with the other of the curved arms **5**. The first finger may be used to force down the plunger **4** until the compression surface **10** (and, optionally, the compression pad **11**) firmly bears against the puncture site, the second and third fingers of the clinician in clamping engagement with the curved arms **5** holding the hemostasis device **1** firmly in position until hemostasis is achieved. Because the plunger **4** is prevented from moving away from the puncture site due to the ratcheting effect between the cylinder **3** and the plunger **4**, the first finger of the clinician may be removed from the arcuate elements **9** of the plunger **4**. Similarly, as adhesive pads **12** may hold the hemostasis device **1** to the skin of the patient, the clinician may remove their second and third fingers as well, leaving the hemostasis device **1** temporarily adhered to the patient's skin such that the plunger **4** maintains pressure on the puncture site.

(40) After hemostasis has been achieved, the hemostasis device **1** may be removed from the skin of the patient, and a surgical dressing may then be applied to the site of the puncture site.

(41) In the embodiment shown in FIG. **8**, the curved arms have been dispensed with. Two fingers, for example the thumb and middle finger of the clinician, may engage the cylinder **3** on opposite sides thereof and function just as they did in the embodiment of FIGS. **5-7**.

(42) In the embodiment of the hemostasis device shown in FIG. **9**, only one curved arm **5** is employed. Two fingers, for example the thumb and middle finger of the clinician, may engage curved arm **5** and the side of cylinder **3** opposite the curved arm **5**. In this embodiment, the thumb and middle finger of the clinician function just as they did in the embodiment shown in FIGS. **5-7**.

(43) The method as discussed above for operating hemostasis device **1** is applicable as well to hemostasis device **21** as shown in FIGS. **10**, **11A**, and **11B**. The hemostasis device **21** is placed on the skin of a patient about a puncture site and adhered to the skin via one or more adhesive pads **32**.

The plunger **24** is then pressed downward through the cylinder **23** toward the puncture site until appropriate pressure has been applied to the puncture site by the compression pad **31**. The hemostasis device **21** is then left in position, thereby allowing the medical technician operating the device to perform other tasks until hemostasis is achieved.

(44) In another aspect of the invention, one embodiment of the hemostasis system of the present invention is shown in FIGS. **12-15**. As shown in FIGS. **12-15**, the adhesive pad **100** overlies the hemostasis device **21** so that the opening **112** in the central portion **110** of the adhesive pad **100** is positioned coincident with the cylinder **23** of the hemostasis device **21** and the first and second side portions **114** and **116** are adhered to the top surface of the footplate **22** and to the patient's skin proximal to the footplate **22**.

(45) In embodiments of the hemostasis system employing hemostasis devices such as shown in FIGS. **5-7**, the hemostasis device is operated as described above. The adhesive pad **100** overlies the hemostasis device so that the opening **112** in the central portion **110** of the adhesive pad **100** is positioned coincident with the cylinder of the hemostasis device and the first and second side portions **114** and **116** are adhered to the top surface of the footplate and to the patient's skin proximal to the footplate. As the adhesive pad **100** secures the hemostasis device to the skin of the patient, the clinician may remove their second and third fingers as well, leaving the device temporarily adhered to the patient's skin such that the plunger maintains pressure on the puncture site. After hemostasis has been achieved, the hemostasis system may be removed from the skin of the patient, and a surgical dressing may then be applied to the site of the puncture.

(46) In embodiments of the hemostasis system employing a hemostasis device such as shown in FIG. **8**, the curved arms have been dispensed with. Two fingers, for example the thumb and middle finger of the clinician, may engage the cylinder on opposite sides thereof and function just as they did in the embodiment of FIGS. **5-7**.

(47) In embodiments of the hemostasis system employing a hemostasis device as shown in FIGS. **10, 11a** and **11b**, the hemostasis device is operated as described above. As shown in FIGS. **12-15**, the adhesive pad **100** overlies the hemostasis device **21** so that the opening **112** in the central portion **110** of the adhesive pad **100** is positioned coincident with the cylinder **23** of the hemostasis device **21** and the first and second side portions **114** and **116** are adhered to and extend beyond the top surface of the footplate **22**.

(48) The method as discussed above for applying a compressive force to a patient's skin at a puncture site may employ the hemostasis system such as shown in FIGS. **12-15**. The hemostasis device **21** is placed on the patient's skin at a puncture site. The release layer **106** of the adhesive pad **100** is removed, and the adhesive pad **100** is then placed over the hemostasis device **21** so that the opening **112** in the central portion **110** of the adhesive pad **100** is positioned coincident with the cylinder **23**, and the first and second side portions **114** and **116** are adhered to the top surface of the footplate **22** and to the patient's skin proximal to the footplate. The plunger **24** is then pressed downward through the cylinder **23** toward the puncture site until appropriate pressure has been applied to the puncture site. The hemostasis device **21** is then left in position, thereby allowing the clinician operating the device to perform other tasks until hemostasis is achieved. After hemostasis has been achieved, the hemostasis system may be removed from the skin of the patient, and a surgical dressing may then be applied to the site of the puncture.

(49) It should be noted that the configurations and mechanisms discussed above are shown by way of example only. Additional configurations and mechanisms may be used to implement a hemostasis system. For example, a compressive force may be applied directly to the footplate. As above, the footplate may be adhered directly to a patient's skin proximal a puncture site. An inflatable bladder or other mechanical expander may be positioned between the footplate and the puncture site or between the footplate and a second plate positioned on the side of the footplate distal to the puncture site and attached to the footplate only at each end such that the bladder is positioned between the footplate and the second plate. The bladder or other mechanical expander

may then be inflated, exerting a force against the footplate and thus providing a compressive force against the puncture site. Once hemostasis is achieved, the bladder or other mechanical expander may be deactivated and the footplate removed from the patient's skin. Examples of alternative mechanical expanders that may also be used include spring-loaded and threaded expanding devices.

(50) Various of the above-disclosed and other features and functions, or alternatives thereof, may be combined into many other different systems or applications. Various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art, each of which is also intended to be encompassed by the disclosed embodiments. Thus, this disclosure is not limited to the particular systems, devices, and methods described, as these may vary.

(51) The terminology used in the description is for the purpose of describing the particular versions or embodiments only, and is not intended to limit the scope. As used in this document, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Unless defined otherwise, all terms used herein have the same meanings as commonly understood by one of ordinary skill in the art.

(52) As various changes could be made in the above articles and methods without departing from the scope of the invention, it is intended that all matter contained in the above description shall be interpreted as illustrative and not in a limiting sense. Other embodiments within the scope of the claims herein will be apparent to one skilled in the art from consideration of the specification or practice of the invention as disclosed herein. It is intended that the specification be considered exemplary only, with the scope and spirit of the invention being indicated by the claims. The appended claims are intended to be construed to include all such embodiments and equivalent variations.

Claims

1. A hemostasis system for adhering to a patient's skin and applying a compressive force to a puncture site, the hemostasis system comprising: (a) a hemostasis device comprising: a footplate having a top surface and a bottom surface, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough and apply a compressive force to the patient's skin at the puncture site, and a plurality of motion restricting components interposed between the receiving device and the plunger to restrict reverse movement of the plunger through the receiving device; and (b) an anchoring adhesive pad comprising a flexible backing layer with a bottom surface, a first side portion, a second side portion, and a central portion; an adhesive layer on the bottom surface of the backing layer; and a release liner removably secured to the adhesive layer; wherein the central portion defines a hole sized to receive the receiving device, and wherein the first side portion and the second side portion of the backing layer overlay and adhere to the top surface of the footplate of the hemostasis device and extend beyond the footplate to the patient's skin.
2. The hemostasis system of claim 1, wherein the backing layer of the anchoring adhesive pad comprises paper, woven fabric, or non-woven plastic film.
3. The hemostasis system of claim 1, wherein the backing layer of the anchoring adhesive pad comprises a non-woven plastic film.
4. The hemostasis system of claim 3, wherein the non-woven plastic film is selected from the group consisting of polyethylene, polypropylene, polyurethane, polyester, poly(ethylene-vinyl acetate), and poly(vinyl chloride).
5. The hemostasis system of claim 1, wherein the release liner of the anchoring adhesive pad has an opening coincident with the opening in the central portion of the backing layer.
6. The hemostasis system of claim 1, wherein the release liner of the anchoring adhesive pad

comprises a plurality of separate sections.

7. The hemostasis system of claim 1, wherein the release liner of the anchoring adhesive pad is paper.

8. The hemostasis system of claim 1, wherein the plunger of the hemostasis device further comprises a compression pad.

9. A method for applying a compressive force to a patient's skin at the site of a puncture site, the method comprising the steps of: providing an anchoring adhesive pad configured to be received by a hemostasis device comprising a footplate having a top surface and a bottom surface, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough, and a plurality of motion restricting components interposed between the receiving device and the plunger to restrict reverse movement of the plunger through the receiving device wherein the anchoring adhesive pad comprises a flexible backing layer having a bottom surface, a first side portion, a second side portion, a central portion positioned between the first side portion and the second side portion, defining an opening to receive the receiving device, and an adhesive layer applied to the bottom surface of the flexible backing layer, wherein the first side portion and the second side portion of the backing layer overlay and adhere to the top surface of the footplate of the hemostasis device and extend beyond the footplate to the patient's skin proximal to the puncture site; and improving securement of the hemostasis device at a puncture site.

10. The method of claim 9, further comprising improving a compression force of the hemostasis device at the puncture site.

11. A kit comprising: (a) a hemostasis system comprising: a hemostasis device comprising a footplate having a top surface and a bottom surface, a receiving device positioned on the footplate, a plunger positioned within the receiving device and configured to move therethrough and apply a compressive force to the patient's skin at the puncture site, and a plurality of motion restricting components interposed between the receiving device and the plunger to restrict reverse movement of the plunger through the receiving device; and (b) an anchoring adhesive pad comprising a flexible backing layer with a bottom surface, first side portion, a second side portion, a central portion positioned between the first side portion and the second side portion, defining an opening to receive the receiving device; an adhesive layer applied to the bottom surface of the backing layer; and a release liner removably secured to the adhesive layer; wherein the first side portion and the second side portion of the backing layer overlay and adhere to the top surface of the footplate of the hemostasis device and extend beyond the footplate to the patient's skin proximal to the puncture site.
