

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12397464
B2
August 26, 2025
Liu; Shelly et al.

Device for mounting a tooling board in a flat bed die-cutting, stripping or blanking machine

Abstract

A mounting device (12) for mounting a tooling board (14) in a flat bed die-cutting, stripping or blanking machine comprises at least one first clamping jaw (38) which is moveable from an unlocked position, in which a tooling board (14) may be removed from or inserted into the machine, to a locked position, in which a tooling board (14) may be fixed in the machine, at least one actuator (18) which comprises a moveable piston (54) and a piston rod (56) coupled to the piston (54), wherein the actuator (18) is configured to transfer the at least one first clamping jaw (38) from the locked position to the unlocked position, and wherein the actuator (18) is coupled to the at least one clamping jaw (38) via an attachment point (60) which has a fixed position relative to the first clamping jaw (38). Furthermore, a mounting assembly (10) comprising a mounting device (12) is provided.

Inventors:	Liu; Shelly (Shanghai, CN), Jaquet; Bernard (Rue, CH)
Applicant:	BOBST MEX SA (Mex, CH)
Family ID:	1000008781804
Assignee:	BOBST MEX SA (Mex, CH)
Appl. No.:	17/760226
Filed (or PCT Filed):	January 22, 2021
PCT No.:	PCT/EP2021/051509
PCT Pub. No.:	WO2021/160410
PCT Pub. Date:	August 19, 2021

Prior Publication Data

Document Identifier

US 20230021706 A1

Publication Date

Jan. 26, 2023

Foreign Application Priority Data

EP

20020068

Feb. 13, 2020

Publication Classification

Int. Cl.: B26D7/26 (20060101); B25B5/06 (20060101)

U.S. Cl.:

CPC B26D7/2614 (20130101); B25B5/067 (20130101); B25B5/061 (20130101); B26D2007/2607 (20130101)

Field of Classification Search

CPC: B25B (1/18); B25B (5/02-04); B25B (5/061); B25B (5/087); B25B (5/122); B25B (5/067); B25B (5/142); B25J (15/0253); B25J (15/0293); B26D (7/2614); B26D (7/26); B26D (2007/26); B26D (2007/2607); B26D (2007/2614)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2096574	12/1936	Denny	269/25	B21D 7/06
2747535	12/1955	Curry	269/238	B21D 7/14
2776854	12/1956	Billstrom	292/96	B25B 5/061
4541828	12/1984	Polic	493/473	B30B 15/026
5114394	12/1991	Madsen	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201471829	12/2009	CN	N/A
204136117	12/2014	CN	N/A
206551091	12/2016	CN	N/A
206899258	12/2017	CN	N/A
207283364	12/2017	CN	N/A
207843490	12/2017	CN	N/A
208034802	12/2017	CN	N/A
209175891	12/2018	CN	N/A
110340968	12/2018	CN	N/A
209666546	12/2018	CN	N/A
209851025	12/2018	CN	N/A
10252549	12/2003	DE	N/A
1418030	12/2003	EP	N/A

663501	12/1950	GB	N/A
S62130894	12/1986	JP	N/A
H01-37920	12/1988	JP	N/A
H01148295	12/1988	JP	N/A
S63043880	12/1988	JP	N/A
2004036729	12/2003	JP	N/A
2004269125	12/2003	JP	N/A
5507719	12/2013	JP	N/A
2008044027	12/2013	JP	N/A
20080072816	12/2007	KR	N/A
1020110101925	12/2010	KR	N/A
101389549	12/2013	KR	N/A
101509219	12/2014	KR	N/A
20170063770	12/2016	KR	N/A
20180002238	12/2017	KR	N/A
I519458	12/2015	TW	N/A

OTHER PUBLICATIONS

European Patent Office, International Search Report, PCT/EP2021/051509, Apr. 20, 2021, 3 pages, Europe. cited by applicant

Primary Examiner: Hall, Jr.; Tyrone V

Attorney, Agent or Firm: Bookoff McAndrews, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This patent application is a National Stage Application under 35 U.S.C § 371 of International Patent Application No. PCT/EP2021/051509, filed on Jan. 22, 2021, which claims priority to European Patent Application No. 20020068.1, filed on Feb. 13, 2020, the entireties of which are incorporated herein by reference.

(2) The invention relates to a mounting device for mounting a tooling board in a flat bed die-cutting, stripping or blanking machine and to a mounting assembly comprising a mounting device.

(3) Flat bed die-cutting machines, flat bed stripping machines or part separation machines may be part of a production line in which paper, cardboard, corrugated board or plastic are processed, in particular for packaging. For example, a plurality of blanks on the same sheet are die-cut and subsequently separated in a flat bed die-cutting machine with an adjoining flat bed stripping device.

(4) In order to enable the processing of different packaging, an exchangeable tooling board which is specific for a kind of packaging to be processed is mounted in the respective machine. For flat bed die-cutting machines these tooling boards may be for example pressure plates which have cutting knives or pressure pads attached thereto. The tooling boards are usually inserted into the machine from the side with respect to the transport direction of the workpiece. Tooling boards may further be so called universal tools.

(5) It is essential that the machines work with very high precision. The exchangeable tooling board must therefore be exactly aligned with the edges of cut in the preceding station and held in a stable position in order to remain exactly aligned. If upper and lower exchange tools are provided, as it is the case in the die-cutting or stripping machines, these tools further need to be precisely aligned

with each other.

(6) For mounting an exchangeable tooling board in flat bed die-cutting, stripping or blanking machines, these machines usually comprise clamping and adjustment mechanisms. However, the known mechanisms are usually complicated, comprise a large number of parts and are thus expensive with regard to material input and mounting time.

(7) It is thus an object of the present invention to provide a mounting assembly for a flat bed die-cutting, stripping or blanking machine which is cost effective and easy to assemble.

(8) This object is achieved by a mounting device for mounting a tooling board in a flat bed die-cutting, stripping or blanking machine, comprising at least one first clamping jaw which is moveable from an unlocked position, in which a tooling board may be removed from or inserted into the machine, to a locked position, in which a tooling board may be fixed in the machine, at least one actuator which comprises a moveable piston and a piston rod coupled to the piston, wherein the actuator is configured to transfer the at least one first clamping jaw from the locked position to the unlocked position, and wherein the actuator is coupled to the at least one first clamping jaw via an attachment point which has a fixed position relative to the first clamping jaw.

(9) By means of the actuator being coupled to the at least one clamping jaw via an attachment point which has a fixed position relative to the clamping jaw, the assembly of the mounting device is particularly simple and only a little number of separate parts has to be handled. In contrast to previous mounting devices, there is no gear present connecting the actuator with the clamping jaw. That means, after assembling the mounting device, the position of the actuator relative to the clamping jaw is fixed and cannot be adjusted. This allows keeping the production costs low and the mounting device can be assembled quickly.

(10) Preferably, the attachment point is provided directly at the clamping jaw or at a coupling element which is fixed to the clamping jaw, i. e. the actuator may be directly coupled to the clamping jaw or via a coupling element. The coupling element may be a distance piece which serves to overcome a gap between the actuator and the clamping jaw, if necessary.

(11) When the actuator is actuated, its length may be increased compared to its length in the non-actuated state.

(12) According to one embodiment, the actuator is coupled to the first clamping jaw via a swivel joint. Due to the swivel joint, the actuator can buckle out in order to overcome geometric and positional tolerances.

(13) The rotation axis of the swivel joint may be transverse to the moving direction of the clamping jaw.

(14) The mounting device for example comprises at least one closing spring which is arranged so as to move the first clamping jaw towards its locked position.

(15) Thereby, the mounting device may be operated particularly energy-efficient. In particular, the clamping jaw can be reliably held in the locked position by the closing spring when the actuator is not actuated. Thus, no electric energy has to be provided to hold the first clamping jaw in its locked position.

(16) The actuator only needs to be actuated for a short time to move the first clamping jaw from the locked position to the unlocked position when a tooling board needs to be exchanged.

(17) For example, the closing spring is compressed when the actuator is actuated, thereby storing elastic energy which can be used to move the first clamping jaw from the unlocked position in the locked position.

(18) According to one embodiment, the closing spring is clamped between a first abutment surface at the piston rod and a second abutment surface which has a fixed position in the mounting device. Thereby, the closing spring is held in a defined position. Due to the first abutment surface being comprised by the piston rod, a compact design is achieved.

(19) The closing spring may be arranged coaxial with the piston rod and in particular surrounds the piston rod. Thus, the piston rod serves as a guide for the closing spring such that the spring does

not buckle when it is compressed by the actuator.

(20) The mounting device has for example a linear guide for support and movement of the clamping jaw. Consequently, the clamping jaw is moved with high precision.

(21) In particular, the clamping jaw comprises at least one guiding portion which is made of sheet metal, wherein the actuator is coupled to the guiding portion. Sheet metal parts can be produced very easy and cheap. By using sheet metal parts, the total costs for the mounting device may be particularly low.

(22) According to one embodiment, the guiding portion has at least one elongated slit which extends in the moving direction of the clamping jaw and wherein the mounting device has at least one protrusion which extends through the slit and thereby guides the clamping jaw. Thereby, a simple and effective linear guide is provided.

(23) In order to provide a particularly stable mounting for the tooling board, the mounting device may further comprise a clamping profile which is fastened to the clamping jaw and which is configured to engage the tooling board. The clamping jaw is therefore not in direct engagement with the tooling board. The profile allows the clamping force applied by the clamping jaw to be distributed more evenly on the tooling board such that the tooling board is held in its mounting position particularly stable.

(24) The clamping profile preferably engages the tooling board along its entire length.

(25) For example, the clamping jaw and the clamping profile are connected to each other by screwing, welding etc.

(26) However, according to an alternative embodiment, the clamping profile may be omitted and the clamping jaw may directly engage the tooling board.

(27) According to one embodiment, the mounting device comprises at least one second clamping jaw which constitutes a counter bearing to the at least one first clamping jaw, wherein the first and the second clamping jaws are configured to clamp a tooling board between each other, in particular either directly or via the clamping profile. This also contributes to the tooling board being held in its mounting position stable. In particular, due to the second jaw constituting a counter bearing, a sufficient holding force is exerted on the tooling board to inhibit an unwanted shifting of the tooling board during an operation of the machine.

(28) Preferably, the first clamping jaw and the second clamping jaw are existing in duplicate, in order to provide a sufficient bearing for the tooling board.

(29) In this case, the clamping profile connects the two first clamping jaws and a further clamping profile connects the two second clamping jaws.

(30) The actuator may be fixed to the second clamping jaw, either directly or via a coupling element. Consequently, due to the actuator being coupled to the first clamping jaw and being fixed to the second clamping jaw, the distance between the first and the second clamping jaws is increased by an actuation of the actuator in order to insert a tooling board in the mounting device. Thereby, a simple opening mechanism for the mounting device is provided.

(31) The mounting device may further comprise at least one adjustment device which is configured to adjust the position of the tooling board in the machine. Thereby, the position of the tooling board can be fine-tuned with high precision.

(32) For example, the adjustment device comprises a setting screw which can be operated by a user in order to adjust the position of the tooling board. Thus, the operation of the adjustment device is very simple.

(33) In particular, by means of the adjustment device the at least one second clamping jaw can be displaced along a direction of movement of the clamping jaws. Preferably, the displacement of the second clamping jaw is a linear displacement. The direction of movement of the clamping jaws thus corresponds to board travel direction. By means of a displacement of the at least one second clamping jaw, the position of the tooling board in the machine is shifted.

(34) According to one embodiment, at least one bridge is provided having opposite end portions,

wherein the first clamping jaw is displaceably mounted to a first end portion of the bridge and the second jaw is displaceably mounted to the opposite, second end portion of the bridge. Thus, the bridge serves as a mount for the clamping jaws and additionally gives the mounting device sufficient stability. In particular, the bridge extends from one side of the mounting device to the opposite side of the mounting device.

(35) The object is further achieved by a mounting assembly comprising a mounting device as previously described and a frame and/or a tooling board which can be removably displaceably mounted in the mounting device by the at least one first clamping jaw, wherein a tooling board is attachable to the frame. The frame serves as an adapter for differently sized tooling boards. This allows to keep the mounting device particularly simple because there is no need to provide complicated adjustment means which allow an adjustment of the mounting device to differently sized tooling boards.

(36) Tooling boards which have a size fitting into the mounting device can be directly mounted in the mounting device and be fixed by means of the clamping jaws. In this case, there is no need of a frame. If the tooling board is smaller or larger than a size fitting into the mounting device, the frame may be releasably attached to the tooling board, for example by screwing, and the frame can be mounted in the mounting device with the attached tooling board. In this case, the frame is clamped in the mounting device and not the tooling board.

Description

(1) Further features and advantages of the invention can be derived from the following description and from the enclosed Figures. In the drawings:

(2) FIG. 1 shows a longitudinal section through an inventive mounting assembly comprising an inventive mounting device, wherein the mounting device is in a locked condition,

(3) FIG. 2 shows a longitudinal section through the mounting assembly of FIG. 1, wherein the mounting device is in an unlocked condition.

(4) FIG. 3 shows an inventive mounting device in a perspective view,

(5) FIG. 4 shows the mounting device of FIG. 3 in a further perspective view,

(6) FIG. 5 shows the mounting device of FIG. 3 in a further perspective view,

(7) FIG. 6 shows the mounting device of FIG. 3 in a further perspective view,

(8) FIG. 7 shows the mounting device of FIG. 3 in a side view,

(9) FIG. 8 shows the mounting device of FIG. 3 in a front view,

(10) FIG. 9 shows the mounting device of FIG. 3 in a back view,

(11) FIG. 10 shows the mounting device of FIG. 3 in a top view,

(12) FIG. 11 shows a section through an adjustment device of the mounting device according to the invention, and

(13) FIG. 12 shows a section through an alternative adjustment device of the mounting device according to the invention.

(14) FIGS. 1 and 2 each show a longitudinal section through an inventive mounting assembly 10.

(15) The mounting assembly 10 comprises a mounting device 12 for mounting a tooling board 14 in a flat bed die-cutting, stripping or blanking machine. In FIG. 1 the mounting device 12 is shown in a locked condition while in FIG. 2 the mounting device is shown in an unlocked condition.

(16) The mounting device 12 may hold the tooling board 14 or the tooling board 14 and a frame 16, wherein the frame 16 is attached to the tooling board 14 and serves as an adapter to mount the tooling board 14 in the mounting device 12, since the tooling board 14 which is illustrated in FIG. 1 is too broad to fit in the mounting device 12. In particular, by means of the frame 16, tooling boards 14 of different sizes can be mounted in a flat bed die-cutting, stripping or blanking machine.

- (17) However, if a tooling board **14** has the right dimensions, it can be mounted in the mounting device **12** without the need of a frame **16**.
- (18) In the following, the mounting device **12** is further described with reference to FIGS. **1** to **10**, wherein FIGS. **3** to **10** show the mounting device in more detail and in different views.
- (19) The mounting device **12** comprises at least one actuator **18** for shifting the mounting device **12** from a locked condition to an unlocked condition and at least one closing spring **20**, which keeps the mounting device **12** in the locked condition when the actuator **18** is not actuated.
- (20) A bearing **21** is provided to guide the actuator **18**. In the illustrated embodiment, the bearing **21** comprises two guide elements **22**.
- (21) Moreover, in order to allow a fine adjustment of the tooling board **14** in a flat bed die-cutting, stripping or blanking machine, the mounting device **12** comprises at least one adjustment device **24** (see FIGS. **1** and **2**).
- (22) Furthermore, the mounting device **12** comprises a centring device **26**, which is configured to centre a tooling board **14** in the machine (see FIGS. **3** to **6**).
- (23) The mounting device **12** comprises two C-shaped beams **25** with a central bridge **28** and arms **29** at the opposite ends of the bridge which protrude downwardly and carry clamping profiles **50**. Between the clamping profiles **50** the board **14** can be clamped.
- (24) In the illustrated embodiment, each bridge **28** comprises two sheet metal parts **30** which are congruent. The sheet metal parts **30** may be fixed to each other by screws, rivets etc. Additionally, at least two spacers **27** are provided per bridge **28**. Each bridge **28** has opposite end portions **32**, **34**.
- (25) One actuator **18** and one closing spring **20** is provided for each bridge **28**.
- (26) A crossbar **36** connects the bridges **28** on one side of the bridges **28**. By means of the crossbar **36**, the mounting device **12** may be fixed in a flat bed die-cutting, stripping or blanking machine, for example by screwing.
- (27) The bridges **28** and the crossbar **36** respectively the clamping profiles **50** are preferably aligned perpendicular to each other.
- (28) The arms **29** are defined by clamping jaws. A first clamping jaw **38** and a second clamping jaw **40** are mounted on each bridge **28**. The second clamping jaw **40** constitutes a counter bearing for the first clamping jaw **38**.
- (29) The first clamping jaw **38** is displaceably mounted to the first end portion **32** of the bridge **28** and the second clamping jaw **40** is displaceably mounted to the opposite, second end portion **34** of the bridge **28**. Thereby, the first clamping jaw **38** and the second clamping jaw **40** are configured to clamp the tooling board **14** or a frame **16** between each other.
- (30) The first clamping jaws **38** are moveable from an unlocked position, in which a tooling board **14** respectively a frame **16** may be removed from or inserted into the machine, to a locked position, in which a tooling board **14** or a frame **16** may be fixed in the machine.
- (31) In particular, actuator **18** is configured to transfer the at least one first clamping jaw **38** from the locked position to the unlocked position.
- (32) The second clamping jaws **40** are also moveable for means of fine adjustment, only. However, clamping jaw **40** is not actuated by actuator **18**.
- (33) For example, each clamping jaw **38**, **40** is moveable in the moving direction by about 5 mm to 10 mm.
- (34) The mounting device **12** further comprises a linear guide **42** for support and movement of the clamping jaws **38**, **40**.
- (35) As can be best seen in FIGS. **1** and **2**, each clamping jaw **38**, **40** comprises a guiding portion **44** which is made of sheet metal, in particular of two sheet metal parts which are preferably congruent to each other. However, other materials are also possible.
- (36) Each guiding portion **44** has two elongated slits **46** which extend in the moving direction of the clamping jaws **38**, **40**.
- (37) The mounting device **12** has several protrusions **48** which extend through the slits **46** and

thereby guide the clamping jaws **38**, **40**. In the shown embodiment, the protrusions **48** are cuboid chunks which are fastened to the bridge **28**.

(38) The guiding portion **44** with the slits **46** and the protrusions **48** together form the linear guide **42**.

(39) Furthermore, the clamping profiles **50** are provided which are fastened to the guiding portions **44** of each clamping jaw **38**, **40** and which are configured to engage the tooling board **14** or the frame **16**, preferably along its entire length. The clamping profiles **50** connect the two first clamping jaws **38** respectively the two second clamping jaws **40** (see FIG. 3).

(40) The clamping jaws **38**, **40** each comprise a solid part **52** which is fixed between the two sheet metal parts and thereby holds the sheet metal parts in a fixed position relative to each other. Thus, the solid part **52** ensures a sufficient stability of the clamping jaws **38**, **40**. The solid part **52** also serves to fasten the clamping profiles **50** to the clamping jaws **38**, **40**.

(41) The actuator **18** comprises a moveable piston **54** and a piston rod **56** coupled to the piston **54**. The moveable piston **54** is contained in a cylinder **58**.

(42) The closing spring **20** is arranged coaxial by with the piston rod **56** and in particular surrounds the piston rod **56**. Thereby, the piston rod **56** supports and guides the closing spring **20**.

(43) The closing spring **20** is arranged so as to move the clamping jaw **38** towards its locked position. In other words, the closing spring **20** pushes the first clamping jaw **38** towards the second clamping jaw **40**.

(44) In order to hold the closing spring **20** in a defined position, the closing spring **20** is clamped between a first abutment surface **64** and a second abutment surface **66** (see FIGS. 1 and 2).

(45) In the depicted embodiment, the first abutment surface **64** is comprised by the actuator **18**, in particular by the piston rod **56**, and the second abutment surface **66** has a fixed position in the mounting device **12**. In particular, the second abutment surface is provided at one of the guide elements **22**.

(46) However, the abutment surfaces **64**, **66** can also be located somewhere else in the machine and the closing spring **20** may be mounted independently from the piston rod **56**.

(47) In the depicted embodiment, the actuator **18** is coupled to the first clamping jaw **38** via an attachment point **60** (see FIGS. 1 and 2) which has a fixed position relative to the first clamping jaw **38**. Thus, a distance of the actuator **18** to the first clamping jaw **38** is fixed after the mounting device **12** has been assembled. In particular, the actuator **18** is coupled to the guiding portion **44** of the first clamping jaw **38**.

(48) The attachment point **60** is provided directly at the first clamping jaw **38**. However, it is also possible to provide the attachment point **60** at an additional coupling element which is fixed to the first clamping jaw **38**, for example, when a greater distance has to be overcome between the clamping jaw **38** and the actuator **18**.

(49) The piston rod **56** is coupled to the first clamping jaw **38** and the cylinder **58** containing the piston **54** is coupled to the second clamping jaw **40**. However, the arrangement of parts can also be the other way round.

(50) As can be seen in FIG. 10, the actuator **18** is coupled to the clamping jaw **38** via a swivel joint **62**.

(51) FIG. 11 shows a detailed sectional view through the adjustment device **24** shown in FIGS. 1 and 2.

(52) For each of the second clamping jaws **40**, one adjustment device **24** is provided.

(53) The adjustment device **24** comprises a setting screw **68** which is fixed to the second clamping jaw **40**, in particular such that the setting screw **68** may be rotated with respect to the second clamping jaw **40**, but not linearly moved or otherwise shifted with respect to the second clamping jaw **40**. More precisely, the setting screw **68** extends through and is fixed to the solid part **52** of the second clamping jaw **40**.

(54) This is achieved by two bearings **70**, **72** which clamp the second clamping jaw **40** between

them. Optionally, one of the two bearings **70**, **72** is formed integrally with the setting screw **68**, wherein the other bearing **70**, **72** is fastened to the setting screw **68**.

(55) At one end, the setting screw **68** is provided with a knob **74** which may be grabbed and rotated by a user.

(56) At the other end, the setting screw **68** has a thread **76** which engages a respective internal thread **78** of a nut **80** which is rotationally and linearly fixed in the mounting device **12**, for example in the crossbar **36**.

(57) Upon rotation of the setting screw **68**, the setting screw **68** is screwed into or out of the thread **76** of the nut **80**. Thereby, since the nut **80** is fixed, the second clamping jaw **40** is linearly moved in the moving direction of the clamping jaws **38**, **40**.

(58) FIG. **12** shows a sectional view through an adjustment device **24** according to an alternative embodiment.

(59) This adjustment device is based on the same mechanism as the adjustment device **24** shown in FIG. **11**.

(60) However, instead of a nut **80**, the adjustment device **24** according to FIG. **12** comprises a bolt **82** with an internal thread, into which the setting screw **68** is threaded.

(61) Upon rotation of the setting screw **68**, the setting screw **68** is screwed into the bolt **82** or out of the bolt **82**.

(62) The bolt **82** is supported by the crossbar **36**, in particular it abuts the crossbar **36** or another element coupled to the crossbar **36** without being firmly fixed to the crossbar **36**.

(63) In the following, the handling and functioning of the mounting device **12** is described with reference to the previously described Figures.

(64) If a tooling board **14** needs to be inserted or exchanged, the actuators **18** are actuated. In particular, the actuators **18** are only used to open the mounting device **12**, but not for closing the mounting device **12**.

(65) The actuation of each actuator **18** takes place by applying pressurized air to the piston **54**, in particular by filling the cylinder **58** with pressurized air. Thereby, the piston **54** is moved such that the actuator **18** is extended and the first clamping jaw **38** connected to the actuator **18** is moved from its locked position to its unlocked position. This movement is visualized by FIGS. **1** and **2**.

(66) In particular, the first clamping jaw **38** is moved against the force of the closing spring **20**.

(67) When the first clamping jaw **38** is moved, the closing spring **20** is compressed, because the abutment surfaces **64**, **66** are moved towards each other. Thereby, the closing spring **20** stores elastic energy.

(68) The same movements are simultaneously taking place in the parallel, second bridge **28** and its actuator **18**.

(69) In this condition, when the actuators **18** are actuated and the closing springs **20** are compressed, a tooling board **14** or a frame **16** may be inserted into the mounting device **12**.

(70) During insertion of a tooling board **14** or a frame **16**, the clamping profiles **50** facilitate an easy exchange of the tooling board **14** or the frame **16** because the tooling board **14** or the frame **16** are supported by the clamping profiles **50**, even if the mounting device **12** is still in the unlocked condition.

(71) Upon insertion, the centring device **26** engages with the tooling board **14** or the frame **16** and thereby centres the tooling board **14** in the mounting device **12** in a direction perpendicular to the movement direction of the paper or cardboard.

(72) After insertion of a tooling board **14**, the actuators **18** may be deactivated, in particular by stopping the supply of pressurized air.

(73) When the air pressure in the cylinder **58** is lowered again, the first clamping jaw **38** is moved back to its locked position due to the spring force of the closing spring **20**.

(74) If a fine adjustment of the position of the tooling board **14** is necessary, the second clamping jaws **40** can be displaced along a direction of movement of the clamping jaws **38**, **40** by means of

the adjustment device **24**.

(75) In particular, a user may rotate the knob **74** and thereby move the respective second clamping jaw **40**. In particular, upon rotation of the knob **74** respectively the setting screw **68**, the second clamping jaw **40** is linearly moved.

Claims

1. A mounting device for mounting a tooling board in a machine, the mounting device comprising: a first clamping jaw which is moveable from an unlocked position, in which the tooling board may be removed from or inserted into the machine, to a locked position, in which the tooling board may be fixed in the machine; and an actuator which comprises a moveable piston and a piston rod coupled to the piston, wherein the actuator is configured to transfer the first clamping jaw from the locked position to the unlocked position, and wherein the actuator is coupled to the first clamping jaw via an attachment point which has a fixed position relative to the first clamping jaw, wherein the actuator is coupled to the first clamping jaw via a swivel joint, wherein the mounting device comprises a closing spring which is arranged to move the first clamping jaw towards the locked position, and wherein the closing spring is clamped between a first abutment surface of the piston rod and a second abutment surface which has a fixed position in the mounting device.
2. The mounting device according to claim 1, wherein the closing spring is arranged coaxial with the piston rod.
3. The mounting device according to claim 1, wherein the mounting device has a linear guide for support and movement of the first clamping jaw.
4. The mounting device according to claim 1, wherein the first clamping jaw comprises a guiding portion made of sheet metal, wherein the actuator is coupled to the guiding portion.
5. The mounting device according to claim 4, wherein the guiding portion has a slit which extends in a moving direction of the first clamping jaw, and wherein the mounting device has a protrusion which extends through the slit and thereby guides the first clamping jaw.
6. The mounting device according to claim 1, wherein the mounting device comprises a clamping profile which is fastened to the first clamping jaw and which is configured to engage the tooling board.
7. The mounting device according to claim 1, wherein the mounting device comprises a second clamping jaw which constitutes a counter bearing to the first clamping jaw, wherein the first and the second clamping jaws are configured to clamp a tooling board between each other.
8. The mounting device according to claim 7, wherein the actuator is fixed to the second clamping jaw.
9. The mounting device according to claim 7, further comprising a bridge having a first end portion and a second end portion opposite to the first end portion, wherein the first clamping jaw is displaceably mounted to the first end portion of the bridge and the second clamping jaw is displaceably mounted to the second end portion of the bridge.
10. A mounting device for mounting a tooling board in a machine, the mounting device comprising: a first clamping jaw which is moveable from an unlocked position, in which the tooling board may be removed from or inserted into the machine, to a locked position, in which the tooling board may be fixed in the machine; an actuator which comprises a moveable piston and a piston rod coupled to the piston; a second clamping jaw which constitutes a counter bearing to the first clamping jaw; and an adjustment device which is configured to adjust a position of the tooling board in the machine, wherein the actuator is configured to transfer the first clamping jaw from the locked position to the unlocked position, wherein the actuator is coupled to the first clamping jaw via an attachment point which has a fixed position relative to the first clamping jaw, wherein the first and the second clamping jaws are configured to clamp a tooling board between each other, wherein the actuator is fixed to the second clamping jaw.

11. The mounting device according to claim 10, wherein the second clamping jaw is displaceable by the adjustment device along a direction of movement of the first clamping jaw.

12. A mounting assembly comprising: a mounting device for mounting a tooling board in a machine, the mounting device including: a first clamping jaw which is moveable from an unlocked position, in which the tooling board may be removed from or inserted into the machine, to a locked position, in which the tooling board may be fixed in the machine; an actuator which comprises a moveable piston and a piston rod coupled to the piston; and a frame, wherein the frame and/or the tooling board are removably mounted in the mounting device by the first clamping jaw, wherein the tooling board is attachable to the frame, wherein the actuator is configured to transfer the first clamping jaw from the locked position to the unlocked position, wherein the actuator is coupled to the first clamping jaw via an attachment point which has a fixed position relative to the first clamping jaw, and wherein the actuator is coupled to the first clamping jaw via a swivel joint.
