

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397476
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Childers; Doug

Nested elliptic reflector for curing optical fibers

Abstract

Methods and systems are provided for ultra-violet curing, and in particular, for ultra-violet curing of optical fiber surface coatings. In one example, a curing device includes a first elliptic cylindrical reflector, with a second elliptic cylindrical reflector housed within the first elliptic cylindrical reflector. The first elliptic cylindrical reflector and second elliptic cylindrical reflector have a co-located focus, and a workpiece to be cured by the curing device may be arranged at the co-located focus.

Inventors:	Childers; Doug (Portland, OR)
Applicant:	Excelitas Technologies Corp. (Waltham, MA)
Family ID:	1000008781764
Assignee:	Excelitas Technologies Corp. (Waltham, MA)
Appl. No.:	18/065578
Filed:	December 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230114938 A1	Apr. 13, 2023

Related U.S. Application Data

division parent-doc US 17119974 20201211 US 11548190 20230110 child-doc US 18065578

Publication Classification

Int. Cl.: **B29C35/08** (20060101); **B01J19/12** (20060101); **B29C35/02** (20060101); **B29C35/10** (20060101); **B29C35/16** (20060101); **G02B5/08** (20060101)

U.S. Cl.:

CPC **B29C35/0805** (20130101); **B01J19/123** (20130101); **B29C35/0288** (20130101);
B29C35/10 (20130101); **B29C35/16** (20130101); **G02B5/0891** (20130101);
B29C2035/0838 (20130101)

Field of Classification Search

CPC: B29C (35/0805); B29C (2035/0827); B29C (64/277); B29C (65/1441); B29C (65/1641);
B29C (66/81268); G02B (2006/12104); G02B (23/105)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4591724	12/1985	Fuse et al.	N/A	N/A
5301249	12/1993	Hamblen et al.	N/A	N/A
5418369	12/1994	Moore et al.	N/A	N/A
6626561	12/2002	Carter et al.	N/A	N/A
7265365	12/2006	Arvin et al.	N/A	N/A
7291846	12/2006	Cekic et al.	N/A	N/A
7923706	12/2010	Brassell et al.	N/A	N/A
9370046	12/2015	Childers	N/A	N/A
10328457	12/2018	Childers	N/A	N/A
11529646	12/2021	Childers	N/A	N/A
11548190	12/2022	Childers	N/A	N/A
2003/0095623	12/2002	Singer	378/34	B82Y 10/00
2011/0002058	12/2010	Leonhardt	N/A	N/A
2013/0068969	12/2012	Childers	N/A	N/A
2015/0028020	12/2014	Childers	N/A	N/A
2016/0271647	12/2015	Childers	N/A	N/A
2017/0050166	12/2016	Karlicek, Jr.	N/A	G02B 5/08
2019/0262860	12/2018	Childers	N/A	N/A
2022/0184858	12/2021	Childers	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201741507	12/2010	CN	N/A
102171526	12/2010	CN	N/A
0660148	12/1994	EP	N/A
H05-229855	12/1992	JP	N/A
H06-104217	12/1993	JP	N/A
2012-504853	12/2011	JP	N/A
2011094947	12/2010	WO	N/A

OTHER PUBLICATIONS

Chinese Office Action dated Jan. 9, 2018 in connection with Chinese Application No. 201480040096.2. cited by applicant

International Search Report and Written Opinion mailed Nov. 25, 2014 in connection with International Application No. PCT/US2014/047666. cited by applicant

Japanese Office Action dated Jul. 24, 2018 in connection with Japanese Application No. 2016-529833. cited by applicant
Taiwanese Office Action dated Jun. 26, 2018 in connection with Taiwanese Application No. 103120807. cited by applicant

Primary Examiner: Yi; Stella K

Attorney, Agent or Firm: Wolf, Greenfield & Sacks, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. Non-Provisional patent application Ser. No. 17/119,974, entitled “NESTED ELIPTIC REFLECTOR FOR CURING OPTICAL FIBERS” and filed on Dec. 11, 2020. The entire contents of the above-referenced application are hereby incorporated by reference for all purposes.

FIELD

(1) The present description relates generally to methods and systems for ultra-violet curing, and in particular, for ultra-violet curing of optical fiber surface coatings.

BACKGROUND/SUMMARY

(2) Optical fibers are used ubiquitously in lighting and imaging applications, as well as in the telecommunication industry, where they provide higher data transmission rates over longer distances as compared to electric wiring. In addition, optical fibers are more flexible, lighter, and can be drawn into thinner diameters than metal wiring, allowing for higher-capacity bundling of fibers into cables. Surface coatings, applied via an ultra-violet (UV) curing process, are employed to protect optical fibers from physical damage and moisture intrusion, and to maintain their long-term durability in performance. As a uniformity of curing of the surface coatings increases, a durability of the optical fibers may also increase. However, it is often difficult to provide sufficiently uniform curing of the surface coatings. One approach is to arrange a workpiece, such as an optical fiber, proximate to a UV light source, with the surface coatings being cured via UV light emitted by the UV light source. To increase an efficiency of the curing, a reflector may be used to direct a portion of the UV light back toward the workpiece. However, the UV light may be dispersed by the reflector in directions away from the workpiece, which may result in efficiency losses. Additionally, as a size of the reflector is increased, a distance of the workpiece from the UV light source may also increase, resulting in a reduction of UV light absorbed by the workpiece.

(3) In one example, the issues described above may be addressed by a curing device, comprising: a larger, first elliptic cylindrical reflector and a smaller, second elliptic cylindrical reflector, with the second elliptic cylindrical reflector nested within an interior of the first elliptic cylindrical reflector, and with the first elliptic cylindrical reflector and the second elliptic cylindrical reflector arranged to have a co-located first focus. In this way, the first elliptic cylindrical reflector and the second elliptic cylindrical reflector nested within the first elliptic cylindrical reflector may each reflect light from a light source to a workpiece arranged at the co-located first focus.

(4) As one example, an entirety of the second elliptic cylindrical reflector may be seated within the interior of the first elliptic cylindrical reflector, with the co-located first focus arranged at a first opening of the second elliptic cylindrical reflector, between a closed end of the first elliptic cylindrical reflector and an opposing, second opening of the second elliptic cylindrical reflector. As a result, the workpiece arranged at the co-located first focus may be positioned closer to the light source, and a size of the curing device may be decreased.

(5) It should be understood that the summary above is provided to introduce in simplified form a

selection of concepts that are further described in the detailed description. It is not meant to identify key or essential features of the claimed subject matter, the scope of which is defined uniquely by the claims that follow the detailed description. Furthermore, the claimed subject matter is not limited to implementations that solve any disadvantages noted above or in any part of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows an example of a photoreactive system, comprising a power source, a controller, and a light-emitting subsystem.
- (2) FIG. 2 shows a cross-section of an elliptic cylindrical reflector for a UV curing device with a single light source.
- (3) FIG. 3 shows a cross section of a first UV curing device including nested elliptic reflectors with a co-located focus.
- (4) FIG. 4 shows a graph illustrating an incoherent irradiance versus position relationship of the UV curing device of FIG. 3.
- (5) FIG. 5 shows a cross section of a second UV curing device including nested elliptic reflectors with a co-located focus.
- (6) FIG. 6 shows a graph illustrating an incoherent irradiance versus position relationship of the UV curing device of FIG. 5.
- (7) FIG. 7 illustrates a cross-section of an example photoreactive system including a UV curing device with nested elliptic reflectors having a co-located focus.
- (8) FIG. 8 illustrates a perspective cross-section of an example photoreactive system.
- (9) FIG. 9 illustrates a perspective view of a nested elliptic reflector for a photoreactive system.
- (10) FIG. 10 illustrates an end cross-section of the nested elliptic reflector of FIG. 9.
- (11) FIG. 11 illustrates a flowchart of an example method for curing a workpiece such as an optical fiber using a UV curing device including nested elliptic reflectors having a co-located focus.
- (12) FIGS. 3, 5, and 7-10 are shown to scale, although other relative dimensions may be used, if desired.

DETAILED DESCRIPTION

(13) The following description relates to systems and methods for a UV curing device, and in particular, a UV curing device for ultra-violet curing of optical fiber surface coatings. The UV curing device may be included within a photoreactive system, such as the photoreactive system shown by FIG. 1. Conventionally, UV curing devices include a single elliptic reflector, as shown by FIG. 2. However, the UV curing devices according to the present disclosure include nested elliptic reflectors, as shown by FIGS. 3 and 5. The nested elliptic reflectors include an outer, first elliptic reflector housing an inner, second elliptic reflector. The first elliptic reflector and the second elliptic reflector are configured such that a first focus of the first elliptic reflector and a first focus of the second elliptic reflector are each arranged at a same location. A light source positioned at a second focus of the first elliptic reflector directs UV light rays toward a workpiece, such as an optical fiber, arranged at the first focus. The UV light rays may be reflected toward the workpiece by reflective surfaces of the first elliptic reflector and second elliptic reflector, resulting in an increased UV light irradiance at the location of the workpiece, as illustrated by the graphs of FIGS. 4 and 6. The elliptic reflectors may be arranged within a housing of the UV curing device, as illustrated by FIGS. 7-8, and one or both of the elliptic reflectors may be formed from separate pieces, as illustrated by FIGS. 9-10. The workpiece may be cured via the UV curing device according to the example method illustrated by the flowchart of FIG. 11. By configuring the UV curing device to include the nested elliptic reflectors, the UV irradiance at the location of the workpiece is increased

relative to conventional UV curing devices. The increased irradiance may reduce a curing time of the workpiece, which may increase production efficiency and reduce costs. Additionally, due to the increased irradiance provided by the nested reflectors, an amount of power consumed by the light source to generate the UV radiation for curing the workpiece may be reduced and a size and/or complexity of the light source may be decreased as a result, which may additionally lower an operating cost and/or manufacturing cost of the UV curing device.

(14) Referring to FIG. 1, a block diagram for an example configuration of a photoreactive system, such as curing device **10** (which may be referred to herein as a UV curing device), is shown.

Curing device **10** comprises a light-emitting subsystem **12**, a controller **14**, a power source **16** and a cooling subsystem **18**. The light-emitting subsystem **12** may comprise a plurality of semiconductor devices **19**. The plurality of semiconductor devices **19** may be an array **20** of light-emitting elements such as a linear array of LED devices, for example. Array **20** of light-emitting elements may also comprise a two-dimensional array of LED devices, or an array of LED arrays, for example. Semiconductor devices may provide radiant output **24**. The radiant output **24** may be directed to a workpiece **26** located at a fixed plane from curing device **10**. Returned radiation **28** may be directed back to the light-emitting subsystem **12** from the workpiece **26** (e.g., via reflection of the radiant output **24**).

(15) The radiant output **24** may be directed to the workpiece **26** via coupling optics **30**. The coupling optics **30** may be variously implemented. As an example, the coupling optics may include one or more layers, materials or other structures interposed between the semiconductor devices **19** and window **64**, and providing radiant output **24** to surfaces of the workpiece **26**. As an example, the coupling optics **30** may include a micro-lens array to enhance collection, condensing, collimation or otherwise the quality or effective quantity of the radiant output **24**. As another example, the coupling optics **30** may include a micro-reflector array. In employing such a micro-reflector array, each semiconductor device providing radiant output **24** may be disposed in a respective micro-reflector, on a one-to-one basis. As another example, array **20** of light-emitting elements providing radiant output **24** may be disposed in macro-reflectors, on a many-to-one basis. In this manner, coupling optics **30** may include both micro-reflector arrays, wherein each semiconductor device is disposed on a one-to-one basis in a respective micro-reflector, and macro-reflectors wherein the quantity and/or quality of the radiant output **24** from the semiconductor devices is further enhanced by macro-reflectors. For example, macro-reflectors may comprise elliptic cylindrical reflectors, parabolic reflectors, nested elliptic cylindrical reflectors, and the like.

(16) Each of the layers, materials or other structure of coupling optics **30** may have a selected index of refraction. By properly selecting each index of refraction, reflection at interfaces between layers, materials and other structures in the path of the radiant output **24** (and/or returned radiation **28**) may be selectively controlled. As an example, by controlling differences in such indexes of refraction at a selected interface, for example window **64**, disposed between the semiconductor devices and the workpiece **26**, reflection at that interface may be reduced or increased so as to enhance the transmission of radiant output at that interface for ultimate delivery to the workpiece **26**. For example, the coupling optics may include a dichroic reflector where certain wavelengths of incident light are absorbed, while others are reflected and focused to the surface of workpiece **26**.

(17) The coupling optics **30** may be employed for various purposes. Example purposes include, among others, to reduce a likelihood of degradation of the semiconductor devices **19**, to retain cooling fluid associated with the cooling subsystem **18**, to collect, condense, and/or collimate the radiant output **24**, to collect, direct, or reject returned radiation **28**, or for other purposes, alone or in combination. As a further example, the curing device **10** may employ coupling optics **30** so as to enhance the effective quality, uniformity, or quantity of the radiant output **24**, particularly as delivered to the workpiece **26**.

(18) The plurality of semiconductor devices **19** may be coupled to the controller **14** via coupling electronics **22**, so as to provide data to the controller **14**. As described further below, the controller

14 may also be implemented to control such data-providing semiconductor devices (e.g., via the coupling electronics **22**). The controller **14** may be connected to, and may be implemented to control, the power source **16**, and the cooling subsystem **18**. For example, the controller may supply a larger drive current to light-emitting elements distributed in the middle portion of array **20** and a smaller drive current to light-emitting elements distributed in the end portions of array **20** in order to increase the usable area of light irradiated at workpiece **26**. Moreover, the controller **14** may receive data from power source **16** and cooling subsystem **18**. In one example, the irradiance at one or more locations at the workpiece **26** surface may be detected by sensors and transmitted to controller **14** in a feedback control scheme. In a further example, controller **14** may communicate with a controller of another lighting system (not shown in FIG. **1**) to coordinate control of both lighting systems. For example, controllers **14** of multiple lighting systems may operate in a master-slave cascading control algorithm, where the setpoint of one of the controllers is set by the output of the other controller. Other control strategies for operation of curing device **10** in conjunction with another lighting system may also be used. As another example, controllers **14** for multiple lighting systems arranged side by side may control lighting systems in an identical manner for increasing uniformity of irradiated light across multiple lighting systems.

(19) In addition to the power source **16**, cooling subsystem **18**, and light-emitting subsystem **12**, the controller **14** may also be connected to, and implemented to control internal element **32**, and external element **34**. Internal element **32**, as shown, may be internal to the curing device **10**, while external element **34**, as shown, may be external to the curing device **10**, but may be associated with the workpiece **26** (e.g., handling, cooling or other external equipment) or may be otherwise related to a photoreaction (e.g. curing) that curing device **10** supports.

(20) The data received by the controller **14** from one or more of the power source **16**, the cooling subsystem **18**, the light-emitting subsystem **12**, and/or internal element **32** and external element **34**, may be of various types. As an example, the data may be representative of one or more characteristics associated with coupled semiconductor devices **19**. As another example, the data may be representative of one or more characteristics associated with the respective light-emitting subsystem **12**, power source **16**, cooling subsystem **18**, internal element **32**, and external element **34** providing the data. As still another example, the data may be representative of one or more characteristics associated with the workpiece **26** (e.g., representative of the radiant output energy or spectral component(s) directed to the workpiece). Moreover, the data may be representative of some combination of these characteristics.

(21) The controller **14**, in receipt of any such data, may be implemented to respond to that data. For example, responsive to such data from any such component, the controller **14** may be implemented to control one or more of the power source **16**, cooling subsystem **18**, light-emitting subsystem **12** (including one or more such coupled semiconductor devices), and/or the internal element **32** and external element **34**. As an example, responsive to data from the light-emitting subsystem indicating that the light energy is lower than a threshold amount of light energy at one or more points associated with the workpiece (e.g., where the threshold amount of light energy corresponds to an amount of light energy desirable for curing of the workpiece **26**), the controller **14** may be implemented to either (a) increase the power source's supply of power to one or more of the semiconductor devices, (b) increase cooling of the light-emitting subsystem via the cooling subsystem **18** (e.g., certain light-emitting devices, if cooled, provide greater radiant output), (c) increase the time during which the power is supplied to such devices, or (d) a combination of any of the above.

(22) Individual semiconductor devices **19** (e.g., LED devices) of the light-emitting subsystem **12** may be controlled independently by controller **14**. For example, controller **14** may control a first group of one or more individual LED devices to emit light of a first intensity, wavelength, and the like, while controlling a second group of one or more individual LED devices to emit light of a different intensity, wavelength, and the like. The first group of one or more individual LED devices

may be within the same array **20** of light-emitting elements, or may be from more than one array **20** of light-emitting elements from multiple lighting systems. Array **20** of light-emitting elements may also be controlled independently by controller **14** from other arrays of light-emitting elements (e.g., semiconductor devices **19**) in other lighting systems. For example, the semiconductor devices of a first array may be controlled to emit light of a first intensity, wavelength, and the like, while those of a second array in another curing device may be controlled to emit light of a second intensity, wavelength, and the like.

(23) As a further example, under a first set of conditions (e.g. for a specific workpiece, photoreaction, and/or set of operating conditions) controller **14** may operate curing device **10** to implement a first control strategy, whereas under a second set of conditions (e.g. for a specific workpiece, photoreaction, and/or set of operating conditions) controller **14** may operate curing device **10** to implement a second control strategy. As described above, the first control strategy may include operating a first group of one or more individual semiconductor devices (e.g., LED devices) to emit light of a first intensity, wavelength, and the like, while the second control strategy may include operating a second group of one or more individual LED devices to emit light of a second intensity, wavelength, and the like. The first group of LED devices may be the same group of LED devices as the second group, and may span one or more arrays of LED devices, or may be a different group of LED devices from the second group, but the different group of LED devices may include a subset of one or more LED devices from the second group.

(24) The cooling subsystem **18** may be implemented to manage the thermal behavior of the light-emitting subsystem **12**. For example, the cooling subsystem **18** may provide for cooling of light-emitting subsystem **12**, and more specifically, the semiconductor devices **19**. The cooling subsystem **18** may also be implemented to cool the workpiece **26** and/or the space between the workpiece **26** and the curing device **10** (e.g., the light-emitting subsystem **12**). For example, cooling subsystem **18** may comprise an air or other fluid (e.g., water) cooling system. Cooling subsystem **18** may also include cooling elements such as cooling fins attached to the semiconductor devices **19**, or array **20** thereof, or to the coupling optics **30**. For example, cooling subsystem may include blowing cooling air over the coupling optics **30**, wherein the coupling optics **30** are equipped with external fins to enhance heat transfer.

(25) The curing device **10** may be used for various applications. Examples include, without limitation, curing applications for fiber optics, ink printing, the fabrication of DVDs and lithography, etc. The applications in which the curing device **10** may be employed can have associated operating parameters. That is, an application may have associated operating parameters as follows: provision of one or more levels of radiant power, at one or more wavelengths, applied over one or more periods of time. In order to properly accomplish the photoreaction associated with the application, optical power may be delivered at or near the workpiece **26** at or above one or more predetermined levels of one or a plurality of these parameters (and/or for a certain time, times or range of times).

(26) In order to follow an intended application's parameters, the semiconductor devices **19** providing radiant output **24** may be operated in accordance with various characteristics associated with the application's parameters (e.g., temperature, spectral distribution and radiant power). At the same time, the semiconductor devices **19** may have certain operating specifications, which may be associated with the semiconductor devices' fabrication and, among other things, may be followed in order to reduce a likelihood of degradation of the devices. Other components of the curing device **10** may also have associated operating specifications. These specifications may include ranges (e.g., maximum and minimum) for operating temperatures and applied electrical power, among other parameter specifications.

(27) Accordingly, the curing device **10** may support monitoring of the application's parameters. In addition, the curing device **10** may provide for monitoring of semiconductor devices **19**, including their respective characteristics and specifications. Moreover, the curing device **10** may also provide

for monitoring of selected other components of the curing device **10**, including its characteristics and specifications.

(28) Providing such monitoring may enable verification of the system's proper operation so that operation of curing device **10** may be reliably evaluated. For example, curing device **10** may be operating undesirably with respect to one or more of the application's parameters (e.g. temperature, spectral distribution, radiant power, and the like), any component's characteristics associated with such parameters, and/or any component's respective operating specifications. The provision of monitoring may be responsive and carried out in accordance with the data received by the controller **14** from one or more of the system's components.

(29) Monitoring may also support control of the system's operation. For example, a control strategy may be implemented via the controller **14**, the controller **14** receiving and being responsive to data from one or more system components. This control strategy, as described above, may be implemented directly (e.g., by controlling a component through control signals directed to the component, based on data respecting that component's operation) or indirectly (e.g., by controlling a component's operation through control signals directed to adjust operation of other components). As an example, a semiconductor device's radiant output may be adjusted indirectly through control signals directed to the power source **16** that adjust power applied to the light-emitting subsystem **12** and/or through control signals directed to the cooling subsystem **18** that adjust cooling applied to the light-emitting subsystem **12**.

(30) Control strategies may be employed to enable and/or enhance the system's proper operation and/or performance of the application. In a more specific example, control may also be employed to enable and/or enhance balance between the array's radiant output and its operating temperature (e.g., to reduce a likelihood of heating the semiconductor devices **19** above a desired threshold operating temperature while also directing sufficient radiant energy to the workpiece **26**), so as to carry out a photoreaction of the application.

(31) In some applications, high radiant power may be delivered to the workpiece **26**. Accordingly, the light-emitting subsystem **12** may be implemented using an array **20** of light-emitting elements (e.g., semiconductor devices **19**). For example, the light-emitting subsystem **12** may be implemented using a high-density, light-emitting diode (LED) array. Although LED arrays may be used and are described in detail herein, it is understood that the semiconductor devices **19**, and arrays thereof (e.g., array **20**), may be implemented using other light-emitting technologies without departing from the principles of the invention; examples of other light-emitting technologies include, without limitation, organic LEDs, laser diodes, other semiconductor lasers.

(32) Continuing with FIG. **1**, the plurality of semiconductor devices **19** may be provided in the form of arrays (e.g., array **20**), or an array of arrays (e.g., as shown in FIG. **1**). The array may be implemented so that one or more, or most of the semiconductor devices **19** are configured to provide radiant output. At the same time, however, one or more of the array's semiconductor devices **19** may be implemented so as to provide for monitoring of a selection of the array's characteristics. For example, monitoring devices **36** may be selected from among the devices in the array and, for example, may have the same structure as the other, emitting devices. A difference between emitting devices and monitoring devices may be determined by the coupling electronics **22** associated with the particular semiconductor device (e.g., in a basic form, an LED array may have monitoring LED devices where the coupling electronics provides a reverse current, and emitting LED devices where the coupling electronics provides a forward current).

(33) Furthermore, based on coupling electronics, the semiconductor devices in the array may be either/both multifunction devices and/or multimode devices, where (a) multifunction devices may be capable of detecting more than one characteristic (e.g., either radiant output, temperature, magnetic fields, vibration, pressure, acceleration, and other mechanical forces or deformations) and may be switched among these detection functions in accordance with the application parameters or other determinative factors and (b) multimode devices may be capable of emission, detection and

some other mode (e.g., off) and may be switched among modes in accordance with the application parameters or other determinative factors.

(34) As described above, curing device **10** may be configured to receive workpiece **26**. As an example, workpiece **26** may be a UV-curable optical fiber, ribbon, or cable. Furthermore, workpiece **26** may be positioned at or near a focus of coupling optics **30** of curing device **10**. In this manner, UV light irradiated from curing device **10** may be directed via coupling optics to the surface of the workpiece for UV curing and driving the photoreactions thereat. Coupling optics **30** of curing device **10** may be configured to have a co-located focus, as will be further described below.

(35) Turning now to FIG. 2, it illustrates an example of coupling optics comprising a single elliptic reflector **200**. Single elliptic reflectors are used in conventional UV curing devices for curing coatings of optical fiber workpieces.

(36) An ellipse, as described herein, is a plane curve that results from the intersection of a cone by a plane in a way that produces a closed curve, and is defined as the locus of all points of the plane whose distances to two fixed points (the foci of the ellipse) add to the same constant. The distance between antipodal points on the ellipse, or pairs of points whose midpoint is at the center of the ellipse, is maximum along its major axis or transverse diameter, and a minimum along its perpendicular minor axis or conjugate diameter. An ellipse is symmetric about its major and minor axes. The foci of the ellipse are two special points on the ellipse's major axis and are equidistant from the center point of the ellipse (where the major and minor axes intersect). The sum of the distances from any point on the ellipse to those two foci is constant and equal to the major axis. Each of these two points is called a focus of the ellipse. An elliptic cylinder is a cylinder having an elliptic cross section.

(37) Elliptic reflector **200** comprises an elliptic cylinder having an elliptic cross section. Elliptic reflector **200** thus has two foci, wherein light irradiated from one focus along the axial length of the elliptic cylinder is concentrated at the second focus along the axial length of the cylinder. Elliptic reflector surface **210** is an example of a light control device having an elliptic cylindrical shape and elliptic cross section, such that light rays **250** emanating from a single light source **230** at a first focal point (e.g., a focal point along an axis of the elliptic cylinder) of the elliptic reflector are directed to a second focal point **240** of the elliptic reflector (e.g., a focal point along a second axis of the elliptic cylinder). For UV curing, the interior surface of the elliptic reflector may be UV-reflective, to direct UV light substantially onto the surface of a workpiece located at the second focal point **240**.

(38) In single elliptic reflector devices with a single light source, the near-field workpiece surfaces (e.g., workpiece surfaces facing toward the light source) may receive light at higher intensities than the far-field workpiece surfaces (e.g., workpiece surfaces facing away from the light source). As such, single elliptic reflectors may also include a cylindrical back auxiliary reflector **260** in order to help in focusing UV light rays **264** emanating from light source **230** and being directed onto the far-field surface of the workpiece. Use of back auxiliary reflectors may be used thereby to provide for more uniform irradiation of a workpiece.

(39) As described above, a conventional single elliptic reflector (e.g., elliptic reflector **200**) has two foci, wherein light initiating from a light source (e.g., light source **230**) at a first focal point may be substantially concentrated at a second focal point (e.g., second focal point **240**).

(40) Referring to FIG. 3, a curing device **300** is shown. The curing device **300** (which may be referred to herein as a UV curing device, UV curing system, and/or photoreactive system) is shown with stipple shading in FIG. 3 to indicate an irradiance of portions of the curing device **300** during operation of the curing device **300**, as described further below. Curing device **300** includes a first elliptic reflector **302** and a second elliptic reflector **304** in a nested arrangement. First elliptic reflector **302** and second elliptic reflector **304** may also be referred to as nested elliptic reflectors. The first elliptic reflector **302** may be referred to herein as a first elliptic cylindrical reflector, and

the second elliptic reflector **304** may be referred to herein as a second elliptic cylindrical reflector. In particular, the second elliptic reflector **304** is housed within an interior **303** of the first elliptic reflector **302**. Minor axis **308** of the first elliptic reflector **302** is arranged coaxially with minor axis **306** of the second elliptic reflector **304**, and major axis **310** of the first elliptic reflector **302** is arranged coaxially with major axis **312** of the second elliptic reflector **304**. The second elliptic reflector **304** is smaller than the first elliptic reflector **302**, with the minor axis **306** of the second elliptic reflector **304** having a smaller amount of length relative to the minor axis **308** of the first elliptic reflector.

(41) The first elliptic reflector **302** and the second elliptic reflector **304** are arranged such that they substantially share a co-located focus **314**. The co-located focus **314** represents a first focus of the first elliptic reflector **302** and a first focus of the second elliptic reflector **304**, with the first focus of the first elliptic reflector **302** and the first focus of the second elliptic reflector **304** being arranged at substantially the same spatial location and being referred to herein collectively as the co-located focus **314**. The first elliptic reflector **302** includes reflective interior surfaces **316**, and the second elliptic reflector **304** includes reflective interior surfaces **318**. Additionally, the second focus **322** may be a focus of each of the first elliptic reflector **302** and the second elliptic reflector **304**, where second focus **322** is arranged opposite to the co-located focus **314**. The co-located focus **314** is arranged closer to a closed, first end **311** of the first elliptic reflector **302** than an open, second end **313** of the first elliptic reflector **302**, while the second focus **322** is arranged closer to the open, second end **313** of the first elliptic reflector **302** than the closed, first end **311** of the first elliptic reflector **302**.

(42) A light source **320** may be positioned at or in the vicinity or encompassing a second focus **322** located opposite to the co-located focus **314** along the major axis **312** and major axis **310**. The light source **320** may, for example, be an individual LED device comprising an array of LEDs, or an array of LED arrays. In this arrangement, the nested elliptic surfaces can substantially concentrate light irradiated from the light source **320** positioned at, or in the vicinity, of the second focus **322** of the nested elliptic reflectors onto the surfaces of workpiece **324** positioned at the co-located focus **314**. The workpiece **324** may be arranged within a sample tube **326**, where a material of the sample tube **326** (e.g., glass, quartz, etc.) is substantially transparent to light emitted by the light source **320**. Additionally, the material of the sample tube may have a suitably low index of refraction so as to direct a larger amount of light rays generated by the light source **320** to the workpiece **324** within the sample tube **326**. The sample tube **326** is arranged within the curing device **300**, with a central axis of the sample tube **326** substantially centered about the co-located focus **314**. In the example shown by FIG. 3, the sample tube **326** may have a diameter of 22 millimeters. However, in other examples (e.g., the example shown by FIG. 5 and described further below), the sample tube may have a different diameter. In yet other examples, the workpiece **324** may be arranged at the co-located focus **314** within the interior of the curing device **300** without the sample tube **326**. For example, the workpiece **324** may extend within the curing device **300** and may be centered at the co-located focus **314** without being enclosed by the sample tube **326** (e.g., the sample tube **326** may be omitted from the interior of the curing device **300**).

(43) In this configuration, due to the reflection of the light rays generated by the light source **320** via the reflective interior surfaces **316** and reflective interior surfaces **318**, an amount of illumination of the workpiece **324** may be maintained at a desired amount of illumination more easily, and the curing device **300** may be manufactured or assembled without back reflectors. As a result, a cost and/or complexity of the curing device **300** may be reduced. In this manner, the configuration exemplified in FIG. 3 can also potentially achieve higher irradiation intensity and more uniform irradiation intensity across the workpiece surfaces relative to single elliptic reflector UV curing devices. Achieving higher and more uniform irradiation intensity may potentially allow for increased production rates and/or shorter curing times, thereby reducing product manufacturing costs.

(44) With regard to the nested elliptic reflectors, UV light can be concentrated more uniformly across all surfaces of the workpiece relative to configurations with single elliptic reflectors, while maintaining high intensity as compared to single elliptic UV curing devices. Furthermore, because nested elliptic reflectors are utilized, light irradiated from the light source can substantially be directed to the surface of the workpiece, even when there may be slight misalignment of the workpiece from the co-located focus, or slight misalignment of one or more light sources from one of the foci. Furthermore, in cases where the cross section of the workpiece may be irregularly shaped or asymmetrical, or in cases where the workpiece cross section may be large, light irradiated from the light sources can be substantially directed to the surface of the workpiece, when nested elliptic reflectors are utilized.

(45) The nested elliptic reflector configuration of the curing device **300** may additionally reduce a size of the curing device **300** relative to curing devices that do not include the nested configuration. For example, a size of the curing device **300** may be reduced relative to curing devices that include dual elliptic reflectors in a non-nested configuration (e.g., configurations in which a minor axis of a first elliptic reflector is not arranged coaxially with a minor axis of a second elliptic reflector). The reduced size of the curing device **300** may increase an ease of handling and/or transportation of the curing device **300**, and with the reduced size of the curing device **300** the light source **320** may be positioned closer to the workpiece **324**, which may increase an amount of light absorbed by the workpiece **324** and may increase a rate of curing of the workpiece **324**. Additionally, because the second elliptic reflector **304** is nested within the first elliptic reflector **302**, a likelihood of degradation of the second elliptic reflector **304** may be reduced (e.g., while transporting the curing device **300**). Further still, the nested configuration of the first elliptic reflector **302** and second elliptic reflector **304** may reduce a manufacturing complexity of the curing device **300** (e.g., a molding and/or casting complexity, reflective surface coating complexity, etc.) relative to curing devices that do not include elliptic reflectors in the nested configuration (e.g., curing devices that include dual elliptic reflectors in axially offset or non-concentric configurations).

(46) Reflective interior surfaces **316** and reflective interior surfaces **318** may be substantially elliptic, or at least partially elliptic. The first elliptic reflector **302** and second elliptic reflector **304** are each formed as substantially elliptic cylinders, with light irradiated from the light source **320** arranged at second focus **322** being reflected by the reflective interior surfaces **316** and reflective interior surfaces **318** toward the co-located focus **314**. For example, the shapes of reflective interior surfaces **316** and reflective interior surfaces **318** may depart slightly from perfectly elliptic without substantially compromising the convergence of light irradiated by light source **320** at co-located focus **314**. As a further example, shapes of surfaces reflective interior surfaces **316** and reflective interior surfaces **318** departing slightly from perfectly elliptic can include faceted elliptic surfaces, wherein the general shape of the first elliptic reflector **302** and second elliptic reflector **304** may be elliptic, but with individual sections faceted to slightly depart from an ellipse. Faceted or partially faceted elliptic surfaces may potentially allow for control of reflected light in a manner that enhances light uniformity or intensity at the workpiece surface for a given light source. For example, the facets may be flat or curved, smooth or continuous in nature, to approximate an elliptic shape, and may deviate slightly from an elliptic shape to account for the emission shape of the light source, thereby improving irradiance at a workpiece surface. Each of the facets may be flat, with corners connecting a plurality of the flat facets to form the elliptic surface. Alternatively, the facets may have a curved surface.

(47) The curing device **300** includes an opening **328** formed the first elliptic reflector **302**. The opening **328** is arranged opposite to the co-located focus **314** and workpiece **324**, and the opening **328** is symmetric about the major axis **310** and major axis **312**. The opening **328** may aid in mounting, positioning and/or aligning, and integrating the first elliptic reflector **302** and second elliptic reflector **304** with other components of UV curing device **300**, such as light source **320**. Edges **332** of opening **328** are positioned such that opening **328** is not larger than a length **334**

between opposing sides of the first elliptic reflector **302** at the second focus **322** in a direction parallel to the minor axis **308** of the first elliptic reflector **302**. Further, the second elliptic reflector **304** includes a first aperture **340** arranged toward the opening **328** (e.g., at a first end of the second elliptic reflector **304**) and a second aperture **342** arranged away from the opening **328** (e.g., at an opposing, second end of the second elliptic reflector **304**). The first aperture **340** may provide access to the interior portions of the second elliptic reflector **304**, while light rays **336** emitted by the light source **320** may pass through the second aperture **342** to intercept the workpiece **324** arranged at the co-located focus **314** (e.g., passing directly from the light source **320** to the workpiece **324** and/or reflecting via reflective interior surfaces **316** toward the workpiece **324**).

(48) As described above, curing device **300** is configured to receive workpiece **324** at sample tube **326**, where the workpiece **324** may pass inside the sample tube **326**, so that the central axis of the workpiece **324** and the central axis of the sample tube **326** are each parallel and each intercept the co-located focus **314**. In this configuration, with the first elliptic reflector **302** and second elliptic reflector **304** arranged in the nested configuration, curing device **300** can substantially focus and direct light rays **336** irradiated from the light source **320** onto surfaces of the workpiece **324** in a substantially uniform manner and with high intensity. Herein, irradiating the workpiece in a substantially uniform manner may refer to irradiating all of the workpiece surfaces arranged within the curing device **300** with essentially the same irradiance (e.g., power per unit area). For example, workpiece **324** may comprise an optical fiber, and arranging the light source **320** substantially at the second focus **322** may facilitate irradiating the optical fiber with a beam of constant irradiance within a threshold distance surrounding the optical fiber. As an example, the threshold distance may comprise a constant beam of 1 mm surrounding the optical fiber. As a further example, the threshold distance may comprise a constant beam of 3 mm surrounding the optical fiber.

(49) Furthermore, because the first elliptic reflector **302** and second elliptic reflector **304** are arranged in the nested configuration, the surfaces of the workpiece **324** can be uniformly irradiated, precluding using back reflectors or reflective surfaces other than the interior surfaces of the nested elliptic reflectors to direct the light onto the workpiece **324**. Further still, for cases where the workpiece **324** passes within sample tube **326**, the size of the sample tube **326** can be determined at least in part based on the size of elliptic reflectors to reduce a likelihood of contact of the sample tube **326** with the reflective interior surfaces **316** of the first elliptic reflector **302** and the reflective interior surfaces **318** of the second elliptic reflector **304**. As described above, due to the nested configuration of the elliptic reflectors, the size of the curing device **300** may be reduced relative to curing devices that do not include the nested elliptic reflectors. Reducing the size of the curing device **300** may additionally aid in positioning the light source **320** closer to the workpiece **324** (e.g., configuring the size of the first elliptic reflector **302** and second elliptic reflector **304** such that a length between the co-located focus **314** and the second focus **322** in a direction of the major axis **310** and major axis **312** is reduced).

(50) As shown, light irradiated from light source **320** may comprise light rays **336** which are reflected from reflective interior surfaces **316** of first elliptic reflector **302** and reflective interior surfaces **318** of second elliptic reflector **304** onto the surfaces of the workpiece **324**. Light irradiated from light source **320** may further comprise light rays irradiated directly onto the surfaces of the workpiece **324** from light source **320**.

(51) The reflective interior surfaces **316** and reflective interior surfaces **318** may reflect visible and/or UV and/or IR light rays with minimal absorption or refraction of light. Alternately, the reflective interior surfaces **316** and reflective interior surfaces **318** may be dichroic such that a certain range of wavelengths of light may be reflected, whereas light of wavelengths outside a certain range may be absorbed at the reflective interior surfaces **316** and reflective interior surfaces **318**. For example, the reflective interior surfaces **316** and reflective interior surfaces **318** may be designed to reflect UV and visible light rays, but absorb IR light rays. Such a reflective interior surface may be potentially useful for heat sensitive coatings or workpieces, or to moderate the rate

and uniformity of the curing reaction at the surface of workpiece **324**. On the other hand, the reflective interior surfaces **316** and reflective interior surfaces **318** may preferentially reflect both UV and IR since curing reactions can proceed more rapidly at higher temperatures.

(52) As described above, workpiece **324** can include optical fibers. Workpiece **324** may additionally and/or alternatively include ribbons or cables having a range of sizes and dimensions. Workpiece **324** may also include a UV-curable cladding and/or surface coating, as well as UV-curable ink printed on its surface. UV-curable cladding can include one or more UV-curable polymer systems, and may also include more than one UV-curable layer, that may be UV-curable in one or more curing stages. UV-curable surface coatings may include a thin film, or an ink that is curable on the surface of the optical fiber or optical fiber cladding. For example, the workpiece may be an optical fiber comprising a core and cladding layer, and the cladding may include a coating comprising a UV-curable polymer such as a polyimide or acrylate polymer, or another one or more UV-curable polymers. As another example, a nested-layer coating may also be used, wherein the workpiece may be coated with an inner layer that may have a soft and rubbery quality when cured for minimizing attenuation by microbending, and an outer layer, which may be stiffer and suited for protecting the workpiece (e.g. optical fiber) from abrasion and exposure to the environment (e.g., moisture, UV). The inner and outer layers may comprise a polymer system, for example an epoxy system, comprising initiators, monomers, oligomers, and other additives.

(53) During curing, the workpiece **324** may be pulled or drawn through the curing device **300** in the axial direction, inside the sample tube **326**, wherein the workpiece **324** is axially centered substantially about the co-located focus **314**. Furthermore, the sample tube **326** may be axially centered about the co-located focus **314**, and may concentrically surround the workpiece **324**. Sample tube **326** may be constructed of glass, or quartz or another optically and/or UV and/or IR transparent material, and may not be overly thick in dimension, such that the sample tube **326** does not block or substantially interfere with the light rays irradiated from light source **320**, including light rays reflected from the reflective interior surfaces **316** of the first elliptic reflector **302** and reflective interior surfaces **318** of the second elliptic reflector **304** through the sample tube **326** onto the surfaces of workpiece **324**. Sample tube **326** may have a circular cross-section, or sample tube **326** may possess another suitably shaped cross-section. Sample tube **326** may also contain an inerting gas such as nitrogen, carbon dioxide, helium, and the like, in order to sustain an inert atmosphere around the workpiece **324** and to reduce oxygen inhibition, which may slow the UV curing reaction.

(54) Light source **320** may include one or more of semiconductor devices or arrays of semiconductor devices such as LED light sources, LED array light sources, or microwave-powered, or halogen arc light sources, or arrays thereof. For example, light source **320** may include a plurality of semiconductor devices similar to the semiconductor devices **19** described above with reference to FIG. **1**. Furthermore, light source **320** substantially located at second focus **322**, may extend along an axial length of the second focus **322**, so as to extend along a length (e.g., axial length) of the first elliptic reflector **302** and a length (e.g., axial length) of the second elliptic reflector **304** of the curing device **300**. Light source **320**, particularly arrays of light sources, or arrays of arrays of light sources, may further encompass or extend beyond second focus **322** along or at points along the length of the first elliptic reflector **302** and the length of the second elliptic reflector **304**. In this manner, light irradiated from light source **320** along the length of first elliptic reflector **302** and the length of the second elliptic reflector **304** is substantially redirected to the surfaces of the workpiece **324** along the entire length of the workpiece **324**.

(55) Furthermore, light source **320** may emit one or more of visible, UV, or IR light. As another example, light source **320** may irradiate UV light of a first spectrum during a first time period, and then may irradiate UV light of a second spectrum during a second time period. The first and second spectrums emitted by light source **320** may or may not overlap. For example, if the light source **320** comprises a first LED array with a first type of LED light source and a second LED array with a

second type of LED light source, then their emission spectra may or may not overlap. Furthermore, the intensities of light irradiated by light source **320** from the first LED array and the second LED array may be identical or they may be different, and their intensities can be independently controlled by an operator via a controller **14** or coupling electronics **22**. In this manner, both the light intensity and wavelengths of light source **320** can be flexibly and independently controlled for achieving uniform UV irradiation and UV cure of a workpiece. For instance, if the workpiece **324** is irregularly shaped, and/or is not symmetrical about the co-located focus **314** of the first elliptic reflector **302** and second elliptic reflector **304**, the curing device **300** may irradiate one portion of the workpiece **324** differentially from another portion to achieve uniform cure. As another example, if different coatings or inks are applied to the surface of the workpiece **324**, the curing device **300** may irradiate one portion of the workpiece **324** differentially from another portion in order to provide a complete curing of each of the different coatings or inks applied to the workpiece **324**.

(56) By configuring the curing device **300** to include the second elliptic reflector **304** in the nested configuration with the first elliptic reflector **302**, a curing rate associated with the curing device **300** may be increased, and a uniformity of the curing of the workpiece **324** via the curing device **300** may be increased. For example, workpiece **324** may include a coating configured to be cured via exposure to UV light. If the coating is non-uniform or unevenly applied to the workpiece, the workpiece may experience non-uniform forces while the coating expands or contracts. If the workpiece is an optical fiber, the uneven coating may result in an increased likelihood of signal attenuation. Achieving a more uniform curing of the coating may include providing a higher percent conversion of reactive monomer and oligomer, and higher degree of cross-linking in the polymer system, in addition to achieving concentric coatings around the workpiece that have an approximately constant thickness and are continuous over the application length of the workpiece (e.g., an optical fiber).

(57) Achieving faster curing rates in a continuous or batch manufacturing process of optical fibers, cables, ribbons, or the like, may potentially reduce the manufacturing time and costs. Furthermore, achieving more uniform cure may potentially impart higher durability and strength to the workpiece. In the case of an optical fiber coating, increased coating uniformity may potentially preserve the fiber strength, thereby potentially increasing the durability of the optical fiber with respect to preventing attenuation of signal transmission due to phenomena such as microbending deformations, stress corrosion, or other mechanical damage in the optical fiber. Higher degrees of cross-linking may also potentially increase the chemical resistance of the coating, preventing chemical penetration and chemical corrosion or degradation of the optical fiber. Optical fibers may be severely degraded by surface defects. With conventional UV curing devices, curing rates may be increased at the expense of reduced cure uniformity; similarly, cure uniformity may be increased, but at the expense of lowering curing rates.

(58) As described above, the curing device **300** is shown with stipple shading to indicate the irradiance of various portions of the interior **303** of the curing device **300** during operation of the curing device **300**. In particular, the stipple shading indicating portions of the interior **303** of the curing device **300** that have a higher irradiance is illustrated with a larger stipple size, while the stipple shading indicating portions of the interior **303** of the curing device **300** that have a lower irradiance is illustrated with a smaller stipple size. Portions of the interior **303** of the curing device **300** proximate to the second focus **322** and the co-located focus **314** each have a higher irradiance relative to portions of the interior **303** that are located away from the second focus **322** and co-located focus **314**, with the irradiance at the co-located focus **314** being higher than the irradiance at the second focus **322**. For example, light rays **336** emitted by the light source **320** may intercept the workpiece **324** and be absorbed by surfaces of the workpiece **324** for curing of the workpiece **324**, as described above. A portion of the light rays **336** may reflect back to the light source **320**, but the portion of the light rays **336** reflecting back to the light source **320** may be smaller than the portion of the light rays **336** absorbed by the workpiece **324** (e.g., the workpiece **324** may absorb a

majority of the light emitted by the light source **320** due to the reflection of the light rays **336** toward the co-located focus **314** by the reflective interior surfaces **316** of the first elliptic reflector **302** and the reflective interior surfaces **318** of the second elliptic reflector **304**).

(59) Referring to FIG. **4**, a graph **400** including a plot **402** is shown indicating the irradiance at different locations within the interior **303** of the curing device **300** shown by FIG. **3** and described above. In particular, the vertical axis of graph **400** indicates incoherent irradiance, and the horizontal axis of graph **400** indicates position within the interior **303** of the curing device **300**. The position labeled “0” along the horizontal axis may correspond to the location of the co-located focus **314** shown by FIG. **3** and described above, with positive values along the horizontal axis indicating locations arranged at the right-hand side of the co-located focus **314** as illustrated by FIG. **3** (e.g., toward the opening **328**), and with negative values along the horizontal axis indicating locations arranged at the left-hand side of the co-located focus **314** as illustrated by FIG. **3** (e.g., away from the opening **328**). The portion of the plot **402** arranged between the “30” and “40” values of the x-axis of graph **400** may correspond to the location of the second focus **322** shown by FIG. **3** and described above.

(60) As shown by plot **402**, the irradiance at the location of the co-located focus **314** has a higher peak value relative to the irradiance at other portions of the interior **303** of the curing device **300**. As a result, the curing rate and curing uniformity of a workpiece arranged at the co-located focus **314**, such as workpiece **324** shown by FIG. **3** and described above, may be increased. In some examples, the peak irradiance at the location of the co-located focus **314** may be 66.452 Watts per centimeter squared, and the total power output by the light source may be 109.53 Watts. In other examples, the peak irradiance and/or total power may have different values. However, in each example, the peak irradiance within the interior **303** of the curing device **300** occurs at the location of the co-located focus **314**.

(61) Referring now to FIG. **5**, another example of a curing device **500** is shown. Curing device **500** may include several components configured similarly to those described above with reference to curing device **300** shown by FIG. **3** and described above. In particular, the curing device **500** includes a first elliptic reflector **502** and a second elliptic reflector **504**, with the second elliptic reflector **504** housed within the first elliptic reflector **502** in a nested configuration. The first elliptic reflector **502** may be referred to herein as a first elliptic cylindrical reflector, and the second elliptic reflector **504** may be referred to herein as a second elliptic cylindrical reflector. The configuration of first elliptic reflector **502** may be similar to the first elliptic reflector **302** described above with reference to FIG. **3**, and the configuration of the second elliptic reflector **504** may be similar to the second elliptic reflector **304** described above with reference to FIG. **3**. The first elliptic reflector **502** and second elliptic reflector **504** each have a co-located focus **514**, similar to the co-located focus **314** described above. In particular, the co-located focus **514** is a focus of each of the first elliptic reflector **502** and the second elliptic reflector **504**. Reflective interior surfaces **516** of the first elliptic reflector **502** and reflective interior surfaces **518** of the second elliptic reflector **504** are configured to reflect light rays **536** emitted by light source **520** arranged at second focus **522** to workpiece **524** arranged at the co-located focus **514** within sample tube **526**, similar to the example described above with reference to FIG. **3**. The second focus **522** may be a focus of each of the first elliptic reflector **502** and the second elliptic reflector **504**, where second focus **522** is arranged opposite to the co-located focus **514**. The co-located focus **514** is arranged closer to a closed, first end **511** of the first elliptic reflector **502** than an open, second end **513** of the first elliptic reflector **502**, while the second focus **522** is arranged closer to the open, second end **513** of the first elliptic reflector **502** than the closed, first end **511** of the first elliptic reflector **502**. A material of the sample tube **526** (e.g., glass, quartz, etc.) is substantially transparent to light emitted by the light source **520** (e.g., at least 95% of light emitted by the light source **520** and incident to surfaces of the sample tube **526** may pass through the sample tube **526** without reflection by the sample tube **526**, in some examples). The curing device **500** further includes an opening **528** disposed between edges

532, where the opening 528 may aid in mounting, positioning and/or aligning, and integrating the first elliptic reflector 502 and second elliptic reflector 504 with other components of curing device 500, such as light source 520. Second elliptic reflector 504 includes first aperture 540 and second aperture 542, where the first aperture 540 may provide access to interior portions of the second elliptic reflector 504, and light rays 536 emitted by the light source 520 may pass through the second aperture 542 to intercept the workpiece 524 arranged at the co-located focus 514.

(62) The relative dimensions of the first elliptic reflector 502 and the second elliptic reflector 504 may be different compared to the relative dimensions of the first elliptic reflector 302 and second elliptic reflector 304 described above with reference to FIG. 3. In particular, a length 534 between opposing sides of the first elliptic reflector 502 at the second focus 522 may be larger than the length 334 described above with reference to FIG. 3. Additionally, a length of first elliptic reflector 502 along major axis 510 and/or minor axis 508 may be greater than the corresponding respective lengths of first elliptic reflector 302 shown by FIG. 3 and described above, and a length of second elliptic reflector 504 along major axis 512 and/or minor axis 506 may be greater than the corresponding respective lengths of second elliptic reflector 304 shown by FIG. 3 and described above. The enlarged size of one or each of first elliptic reflector 502 and second elliptic reflector 504 may provide additional interior space for accommodating the workpiece 524 and sample tube 526 relative to the curing device 300 described above with reference to FIG. 3. As one example, the sample tube 526 may have a diameter of 28 millimeters, as compared to the diameter of 22 millimeters provided as one example of the diameter of the sample tube 326 shown by FIG. 3 and described above. The larger sample tube 526 may accommodate larger workpieces relative to the sample tube 326, in some examples. In yet other examples, the workpiece 524 may be arranged at the co-located focus 514 within the interior of the curing device 500 without the sample tube 526. For example, the workpiece 524 may extend within the curing device 500 and may be centered at the co-located focus 514 without being enclosed by the sample tube 526 (e.g., the sample tube 526 may be omitted from the interior of the curing device 500).

(63) Similar to the example described above with reference to FIG. 3, the curing device 500 shown by FIG. 5 is shown with stipple shading to indicate the irradiance of various portions of the interior 503 of the curing device 500 during operation of the curing device 500. The portions of the interior 503 that have a higher irradiance are illustrated with larger stipple size, while the portions of the interior that have a lower irradiance are illustrated with smaller stipple size. As indicated by the stipple shading, the irradiance at the co-located focus 514 is higher than the irradiance at the second focus 522.

(64) Referring to FIG. 6, a graph 600 including a plot 602 is shown indicating the irradiance at different locations within the interior 503 of the curing device 500 shown by FIG. 5 and described above. In particular, the vertical axis of graph 600 indicates incoherent irradiance, and the horizontal axis of graph 600 indicates position within the interior 503 of the curing device 500. The position labeled “0” along the horizontal axis may correspond to the location of the co-located focus 514 shown by FIG. 5 and described above, with positive values along the horizontal axis indicating locations arranged at the right-hand side of the co-located focus 514 as illustrated by FIG. 5 (e.g., toward the opening 528), and with negative values along the horizontal axis indicating locations arranged at the left-hand side of the co-located focus 514 as illustrated by FIG. 5 (e.g., away from the opening 528). The portion of the plot 602 arranged between the “30” and “40” values of the x-axis of graph 600 may correspond to the location of the second focus 522 shown by FIG. 5 and described above.

(65) As shown by plot 602, the irradiance at the location of the co-located focus 514 has a higher peak value relative to the irradiance at other portions of the interior 503 of the curing device 500. As a result, the curing rate and curing uniformity of a workpiece arranged at the co-located focus 514, such as workpiece 524 shown by FIG. 5 and described above, may be increased. In some examples, the peak irradiance at the location of the co-located focus 514 may be 53.494 Watts per

centimeter squared, and the total power output by the light source may be 116.47 Watts. In other examples, the peak irradiance and/or total power may have different values. However, in each example, the peak irradiance within the interior **503** of the curing device **500** occurs at the location of the co-located focus **514**.

(66) Turning now to FIG. 7, a cross-sectional view of a curing device **700** is shown. The curing device **700** may be referred to herein as a photoreactive system, UV curing device, and/or a UV curing system. Curing device **700** is shown comprising a nested elliptic cylindrical reflector **775** comprising a cylindrical, first elliptic reflector **780** and a cylindrical, second elliptic reflector **790**. The first elliptic reflector **780** may be similar to, or the same as, the first elliptic reflector **302** or first elliptic reflector **502** described above, and the second elliptic reflector **790** may be similar to, or the same as, the second elliptic reflector **304** or second elliptic reflector **504** described above. The curing device **700** may be similar to, or the same as, the curing device **300** or curing device **500** described above. The second elliptic reflector **790** is housed within the first elliptic reflector **780** (e.g., arranged within an interior space enclosed by the first elliptic reflector **780**), such that the first elliptic reflector **780** and second elliptic reflector **790** are in a nested configuration. The first elliptic reflector **780** and second elliptic reflector **790** have a co-located focus **760**, similar to co-located focus **314** and co-located focus **514** described above, with second focus **792** being similar to second focus **322** and second focus **522** described above. In particular, co-located focus **760** is a focus of each of the first elliptic reflector **780** and the second elliptic reflector **790**. Additionally, second focus **792** may be a focus of each of the first elliptic reflector **780** and the second elliptic reflector **790**, where second focus **792** is arranged opposite to the co-located focus **760**. The co-located focus **760** is arranged closer to a closed, first end **791** of the first elliptic reflector **780** than an open, second end **793** of the first elliptic reflector **780**, while the second focus **792** is arranged closer to the open, second end **793** of the first elliptic reflector **780** than the closed, first end **791** of the first elliptic reflector **780**.

(67) A light source **710** arranged at the second focus **792** may be at least partially housed within a housing **716**, with the housing **716** including inlet and outlet piping connections **714** through which cooling fluid may circulate. Light source **710** may comprise one or more arrays of UV LED's positioned substantially along the second focus **792**. Curing device **700** may further comprise mounting brackets **718** by which the housing **716** may attach to a reflector assembly baseplate **720**. Curing device **700** may also include a sample tube **770** and a workpiece (not shown), for example an optical fiber, that is pulled or drawn within the sample tube **770** and positioned substantially about the central longitudinal axis of the sample tube **770**. Longitudinal axis of sample tube **770** may be positioned substantially along the co-located focus **760** of the nested elliptic cylindrical reflector **775**, wherein UV light originating from light source **710** may be substantially directed through the sample tube **770** to surfaces of the workpiece by the first elliptic reflector **780** and second elliptic reflector **790**. Sample tube **770** may be constructed of quartz, glass or other material, and may have a cylindrical or other geometry, wherein UV light directed onto the external surface of the sample tube **770** may pass through the sample tube **770** without substantial refraction, reflection or absorption.

(68) Reflector assembly baseplate **720** may be connected to reflector assembly faceplates **724**, which may be mechanically fastened to either axial end of nested elliptic cylindrical reflector **775**. Sample tube **770** may also be mechanically fastened to reflector assembly faceplates **724**. In this manner, mounting brackets **718**, reflector assembly faceplates **724** and reflector assembly baseplate **720** may serve to aid in aligning the light source **710**, nested elliptic cylindrical reflector **775** and sample tube **770**, wherein the light originating from light source **710** is substantially positioned about a second focus **792** of elliptic cylindrical reflector **790**, wherein the sample tube is substantially positioned about a co-located focus of nested elliptic cylindrical reflector **775**, and wherein UV light originating from light source **710** may be substantially directed through the sample tube **770** to surfaces of the workpiece by nested elliptic cylindrical reflector **775**. Reflector

assembly faceplate **724** may also include an alignment mechanism (not shown), where the alignment and/or position of the sample tube **770** may be adjusted after the reflector assembly faceplates **724**, reflector assembly baseplate **720**, first elliptic reflector **780**, second elliptic reflector **790**, and sample tube **770** have been assembled together. Reflector assembly baseplate **720** may also be connected along one side to a reflector assembly mounting plate **740**. Reflector assembly mounting plate **740** may further be provided with one or more mounting slots **744** (see FIG. **8**) and one or more mounting holes **748** (see FIG. **8**) by which curing device **700** can be mounted. Curing device **700** may also include further connection ports **722** and **750** for other purposes such as for connecting electrical wiring conduits, mounting sensors, and the like. Furthermore, curing device **700** may comprise a reflector housing **712**, and a cooling fan **715** mounted on the reflector housing **712** for removing heat from the curing device **700**. In some examples, the second elliptic reflector **790** may be fixedly coupled to the first elliptic reflector **780** via one or more thin posts, such as posts **794**. In some examples, the light source **710** may be arranged at the location of the second focus **792** via one or more thin posts, such as thin post **796**.

(69) Turning now to FIG. **8**, a perspective cross-sectional view of the curing device **700** of FIG. **7** is shown, with reflector assembly faceplates **724** removed for illustrative purposes. In addition to the elements described above for FIG. **7**, curing device **700** further comprises an opening or cavity **840** in reflector assembly baseplate **720** through which light irradiated from light source **710** (shown by FIG. **7**) is transmitted. As shown in FIG. **8**, cavity **840** may substantially span an axial length of the nested elliptic reflector **775**. Light from light source **710** is irradiated along the entire length of the nested elliptic reflector **775**. In addition to cooling fan **715** and inlet and outlet piping connections **714** for cooling fluid, reflector housing **712** may also comprise finned surfaces **820** for aiding in heat dissipation away from the curing device **700**.

(70) In the curing device **700** of FIG. **7** and FIG. **8**, the nested elliptic reflector **775** is shown as having a thin rounded sheet construction. In one example, the nested elliptic reflector may comprise shaped thin sheets of polished aluminum that may be cleanable, reusable, and replaceable. In another example, fins may be added to the external surface (e.g. external relative to the irradiated surface from light source **710**) to increase heat transfer surface area from the nested elliptic reflector **775**.

(71) Turning now to FIGS. **9** and **10**, perspective and end cross-sectional views of another embodiment of a curing device **901** including a nested elliptic reflector **900** are shown. Nested elliptic reflector **900** includes a first elliptic reflector **950** and a second elliptic reflector **952** each having a co-located focus **982** (e.g., the co-located focus **982** is a focus of both of the first elliptic reflector **950** and second elliptic reflector **952**). Nested elliptic reflector **900** comprises reflective interior surfaces **984** of first elliptic reflector **950** and reflective interior surfaces **994** of second elliptic reflector. Nested elliptic reflector **900** may be machined or cast metal, and polished to form reflective interior surfaces **984** and reflective interior surfaces **994**. Alternately, nested elliptic reflector may be machined, molded, cast or extruded of glass, ceramic, or plastic and treated with a high reflectance coating to form reflective interior surfaces **984** and reflective interior surfaces **994**. Further still, nested elliptic reflector may be fabricated in two halves, including a first half **900A** and a second half **900B**, with the two halves fit and/or joined together during assembly of the curing device **901**. Nested elliptic reflector **900** further comprises finned surfaces **918** to increase heat transfer surface area. Mounting holes **966** may be provided on an underside **964** of the nested elliptic reflector **900** to facilitate mounting and positioning of the nested elliptic reflector **900** to other components of the curing device **901**, such as a light source, light source housing, etc. Nested elliptic reflector **900** further comprises an opening or cavity **968** along its entire axial length. Cavity **968** is positioned along the major axis of the nested elliptic reflector **900** so that cavity **968** extends along second focus **992** of the nested elliptic reflector **900**.

(72) In this manner, a curing device may comprise a first elliptic cylindrical reflector housing a second elliptic cylindrical reflector, the first elliptic cylindrical reflector and the second elliptic

cylindrical reflector arranged to have a co-located focus, and a light source located at a second focus, wherein light emitted from the light source is reflected to the co-located focus from the second elliptic cylindrical reflector and retro-reflected to the co-located focus from the first elliptic cylindrical reflector. Further still, a first elliptic cylindrical reflector major axis may be greater than a second elliptic cylindrical reflector major axis, and a first elliptic cylindrical reflector minor axis may be greater than a second elliptic cylindrical reflector minor axis.

(73) The first elliptic cylindrical reflector and the second elliptic cylindrical reflector may be configured to receive a workpiece. Furthermore, the light source may comprise a power source, a controller, a cooling subsystem, and a light-emitting subsystem, the light-emitting subsystem including coupling electronics, coupling optics and a plurality of semiconductor devices, and the housing may contain the light source and include inlets and outlets for cooling subsystem fluid.

(74) At least one of the first elliptic cylindrical reflector and the second elliptic cylindrical reflectors may be a dichroic reflector, and the plurality of semiconductor devices of the light source may comprise an LED array. The LED array may comprise a first LED and a second LED, the first LED and the second LED emitting UV light with different peak wavelengths. The curing device may further comprise a quartz tube axially centered around the co-located focus and concentrically surrounding the workpiece inside the curing device.

(75) In another embodiment, a photoreactive system for UV curing, may comprise a power supply, a cooling subsystem, a light-emitting subsystem, and a UV light source. The light-emitting subsystem may comprise coupling optics, including a first elliptic cylindrical reflector housing a second elliptic cylindrical reflector, the first elliptic cylindrical reflector and the second elliptic cylindrical reflector having a co-located focus and arranged in a nested configuration. The photoreactive system may further comprise a controller, including instructions stored in memory executable to irradiate UV light from the UV light source, wherein the irradiated UV light is reflected by at least one of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector and focused on to a surface of the workpiece. The controller may further comprise instructions executable to dynamically vary an intensity of the irradiated UV light, and the photoreactive system may further comprise the UV light source located substantially at the second focus, wherein the irradiated UV light comprises a beam of spatially constant intensity surrounding the workpiece.

(76) Turning now to FIG. **11**, a method **1100** of curing a workpiece is shown. In some examples, the workpiece may be an optical fiber, optical fiber coating, or another type of workpiece. Method **1100** begins at **1110**, where a workpiece may be drawn, in the case of an optical fiber, from a preform, in a workpiece drawing step. Method **1100** then continues at **1120** where the workpiece is coated with a UV-curable coating or UV-curable polymer system using a predetermined coating process.

(77) Next, method **1100** proceeds with **1130**, wherein the workpiece may be UV-cured. During the UV curing at **1130**, the workpiece may be pulled or drawn through a sample tube of one or a plurality UV curing devices at **1132**. For example, the one or plurality of UV curing devices may include one or more of curing device **10**, curing device **300**, curing device **500**, or curing device **901**, arranged linearly in series. Furthermore, the workpiece may be positioned along a co-located focus of a nested elliptic reflector of the UV curing device, for example, a co-located focus of a first elliptic cylindrical reflector and a second elliptic cylindrical reflector (e.g., co-located focus **314** of first elliptic reflector **302** and second elliptic reflector **304** shown by FIG. **3** and described above). UV curing the workpiece may further include irradiating UV light from at least one LED array light source positioned at a second focus of the nested elliptic reflector at **1134**. The irradiated UV light may be reflected by the second elliptic cylindrical reflector onto the surface of the workpiece at **1136**, and retro-reflected onto the surface of the workpiece by the first elliptic cylindrical reflector at **1138**. Accordingly irradiated UV light may be uniformly directed onto a surface of the workpiece.

(78) In the case of drawing and UV curing optical fibers, the linear speed at which the optical fiber may be pulled or drawn can be very fast, and may exceed 20 m/s, for example. Arranging a plurality of UV curing devices in series may thus allow the coated length of optical fiber to receive a long enough UV exposure residence time in order to substantially complete curing of the optical fiber coating. In some examples, the effective length of the UV curing stage (for example, the number of UV curing devices arranged in series) is determined by taking into account the manufacturing rate, or draw or linear speed of the optical fiber or workpiece. Thus if the optical fiber linear speed is slower, the length or number of the UV curing system stage may be shorter than for cases where the optical fiber linear speed is faster. In particular, using UV curing devices including a first elliptic cylindrical reflector housing a second elliptic cylindrical reflector with a co-located focus may potentially provide higher intensity and more uniform UV light irradiated and directed onto the surface of the workpiece, thereby providing both faster and more uniform cure of the workpiece. In this manner, optical fiber coatings and/or inks may be UV-cured at higher production rates, thereby lowering manufacturing costs.

(79) Complete UV curing of the optical fiber coating may impart physical and chemical properties such as strength, durability, chemical resistance, fatigue strength, and the like. Incomplete or inadequate curing may degrade product performance qualities and other properties that can potentially cause premature failure and loss of performance of the optical fiber. In some examples, the effective length of the UV curing stage (for example, the number of UV curing devices arranged in series) is determined by taking into account the manufacturing rate, or draw or linear speed of the optical fiber or workpiece. Thus if the optical fiber linear speed is slower, the length or number of the UV curing system stage may be shorter than for cases where the optical fiber linear speed is faster.

(80) Next, method **1100** continues at **1140**, where it is determined if additional coating stages are required. In some examples, dual or multi-layer coatings may be applied to the surface of the workpiece, for example an optical fiber. As discussed above, optical fibers can be manufactured to include two protective concentric coating layers. For example, a dual-layer coating may also be used, wherein the workpiece may be coated with an inner layer that may have a soft and rubbery quality when cured for minimizing attenuation by microbending, and an outer layer, which may be stiffer and suited for protecting the workpiece (e.g. optical fiber) from abrasion and exposure to the environment (e.g., moisture, UV). The inner and outer layers may comprise a polymer system comprising initiators, monomers, oligomers, and other additives. If an additional coating step is to be performed, then method **1100** returns to **1120** where the optical fiber or other workpiece (now coated with a UV-cured first layer) is coated via an additional coating step followed by an additional UV curing. In FIG. **11**, each coating step is shown as the coating step **1120** for simple illustrative purposes, however, each coating step may not be identical such that each coating step may apply different types of coatings, different coating compositions, different coating thicknesses, and impart different coating properties to the workpiece. In addition the coating step **1120** may use different processing conditions (e.g., temperature, coating viscosity, coating method). Similarly, UV curing the workpiece at **1130** for different coating layers or steps can involve a range of processing conditions. For example, in different UV cure steps, processing conditions such as UV light intensity, UV exposure time, UV light wavelength spectra, UV light source, and the like may be changed depending on the type of coating and/or coating properties.

(81) Additional coating stages may also comprise printing or coating a UV curable ink or lacquer onto the surface of the workpiece, for example, for coloring or identification purposes. The printing may be carried out using a predetermined printing process, and may involve one or more multiple printing stages or steps. As such, UV curing at **1130** may comprise UV-curing a printed ink or lacquer on the surface of the workpiece. Similar to the UV curing step of the one or more optical fiber coatings, the printed ink or lacquer is UV-cured by pulling the workpiece positioned at the co-located focus of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector of

one or a plurality of UV curing devices arranged linearly in series, during which UV light is irradiated from the LED array light sources of the UV curing device(s) and directed by the nested elliptic cylindrical reflectors onto the surface of the optical fiber at the co-located focus.

(82) If there are no additional coating stages, method **1100** continues at **1180** where any post-UV curing process steps are performed. As an example, for the case where the workpiece includes an optical fiber, post-UV curing process steps may include cable or ribbon construction, where a plurality of coated and printed and UV-cured optical fibers are combined into a flat ribbon, or a larger diameter cable composed of multiple fibers or ribbons. Other post-UV curing process steps may include co-extrusion of external cladding or sheathing of cables and ribbons.

(83) In this manner, a method of curing a workpiece may comprise drawing the workpiece along a co-located focus of a first elliptic cylindrical reflector housing a second elliptic cylindrical reflector, irradiating UV light from a light source positioned at a second focus, reflecting the irradiated UV light from the second elliptic cylindrical reflector on to a surface of the workpiece, and retro-reflecting the irradiated UV light from the first elliptic cylindrical reflector onto the surface of the workpiece. Furthermore, drawing the workpiece along the co-located focus may comprise drawing at least one of an optical fiber, ribbon, or cable with at least one of a UV-curable coating, polymer, or ink. Further still, the LED array comprises a first LED and a second LED, wherein the first LED and the second LED emit UV light with different peak wavelengths.

(84) The method may comprise dynamically varying an intensity of the irradiated UV light, and positioning the UV light source substantially at the second focus, wherein the irradiated UV light comprises a beam of spatially constant intensity surrounding the workpiece.

(85) It will be appreciated that the configurations disclosed herein are exemplary in nature, and that these specific embodiments are not to be considered in a limiting sense, because numerous variations are possible. For example, the above embodiments can be applied to workpieces other than optical fibers, cables, and ribbons. Furthermore, the UV curing devices and systems described above may be integrated with existing manufacturing equipment and are not designed for a specific light source. As described above, any suitable light engine may be used such as a microwave-powered lamp, LED's, LED arrays, and mercury arc lamps. The subject matter of the present disclosure includes all novel and non-obvious combinations and subcombinations of the various configurations, and other features, functions, and/or properties disclosed herein.

(86) Note that the example process flows described herein can be used with various UV curing devices and UV curing system configurations. The process flows described herein may represent one or more of any number of processing strategies such as continuous, batch, semi-batch, and semi-continuous processing, and the like. As such, various acts, operations, or functions illustrated may be performed in the sequence illustrated, in parallel, or in some cases omitted. Likewise, the order of processing is not necessarily called for to achieve the features and advantages of the example embodiments described herein, but is provided for ease of illustration and description. One or more of the illustrated acts or functions may be repeatedly performed depending on the particular strategy being used. It will be appreciated that the configurations and routines disclosed herein are exemplary in nature, and that these specific embodiments are not to be considered in a limiting sense, because numerous variations are possible. The subject matter of the present disclosure includes all novel and non-obvious combinations and subcombinations of the various systems and configurations, and other features, functions, and/or properties disclosed herein.

(87) In one embodiment, a curing device comprises: a larger, first elliptic cylindrical reflector and a smaller, second elliptic cylindrical reflector, with the second elliptic cylindrical reflector nested within an interior of the first elliptic cylindrical reflector, and with the first elliptic cylindrical reflector and the second elliptic cylindrical reflector arranged to have a co-located first focus. In a first example of the curing device, the curing device further comprises a light source located at a second focus of the first elliptic cylindrical reflector, wherein light emitted from the light source is reflected to the co-located first focus from the second elliptic cylindrical reflector and retro-

reflected to the co-located first focus from the first elliptic cylindrical reflector, and wherein an entirety of the second elliptic cylindrical reflector is seated within the interior of the first elliptic cylindrical reflector, with the co-located first focus arranged at a first opening of the second elliptic cylindrical reflector, between a closed end of the first elliptic cylindrical reflector and an opposing, second opening of the second elliptic cylindrical reflector. A second example of the curing device optionally includes the first example, and further includes wherein a length of the first elliptic cylindrical reflector along a major axis of the first elliptic cylindrical reflector is greater than a length of the second elliptic cylindrical reflector along a major axis of the second elliptic cylindrical reflector, with the major axis of the first elliptic cylindrical reflector being coaxial with the major axis of the second elliptic cylindrical reflector. A third example of the curing device optionally includes one or both of the first and second examples, and further includes wherein a length of the first elliptic cylindrical reflector along a minor axis of the first elliptic cylindrical reflector is greater than a length of the second elliptic cylindrical reflector along a minor axis of the second elliptic cylindrical reflector, with the minor axis of the first elliptic cylindrical reflector being coaxial with the minor axis of the second elliptic cylindrical reflector. A fourth example of the curing device optionally includes one or more or each of the first through third examples, and further includes wherein a difference between the length of the first elliptic cylindrical reflector along the major axis of the first elliptic cylindrical reflector and the length of the second elliptic cylindrical reflector along the major axis of the second elliptic cylindrical reflector is equal to a difference between the length of the first elliptic cylindrical reflector along the minor axis of the first elliptic cylindrical reflector and the length of the second elliptic cylindrical reflector along the minor axis of the second elliptic cylindrical reflector. A fifth example of the curing device optionally includes one or more or each of the first through fourth examples, and further includes wherein the first elliptic cylindrical reflector and the second elliptic cylindrical reflector are configured to receive a workpiece, with the second elliptic cylindrical reflector disposed between the workpiece and the first elliptic cylindrical reflector. A sixth example of the curing device optionally includes one or more or each of the first through fifth examples, and further includes wherein: reflective surfaces of the first elliptic cylindrical reflector are spaced apart from reflective surfaces of the second elliptic cylindrical reflector in a direction along a minor axis of the first elliptic cylindrical reflector and a minor axis of the second elliptic cylindrical reflector; the light source comprises a power source, a controller, a cooling subsystem, and a light-emitting subsystem, the light-emitting subsystem including coupling electronics, coupling optics and a plurality of semiconductor devices; and a housing of the light source includes inlets and outlets for cooling subsystem fluid. A seventh example of the curing device optionally includes one or more or each of the first through sixth examples, and further includes a quartz tube axially centered around the co-located first focus and concentrically surrounding the workpiece inside the curing device between the first elliptic cylindrical reflector and the second elliptic cylindrical reflector. An eighth example of the curing device optionally includes one or more or each of the first through seventh examples, and further includes wherein the plurality of semiconductor devices of the light source comprises an LED array. A ninth example of the curing device optionally includes one or more or each of the first through eighth examples, and further includes wherein the LED array comprises a first LED and a second LED, the first LED and the second LED emitting UV light with different peak wavelengths. A tenth example of the curing device optionally includes one or more or each of the first through ninth examples, and further includes wherein at least one of the first elliptic cylindrical reflector and the second elliptic cylindrical reflectors is a dichroic reflector.

(88) In one embodiment, a photoreactive system for UV curing comprises: a power supply; a cooling subsystem; a light-emitting subsystem comprising: coupling optics, including a first elliptic cylindrical reflector and a second elliptic cylindrical reflector sharing a co-located focus, the second elliptic cylindrical reflector housed within the first elliptic cylindrical reflector; a workpiece disposed within an interior of each of the first elliptic cylindrical reflector and the second elliptic

cylindrical reflector; and a UV light source located substantially at a second focus of the first elliptic cylindrical reflector; and a controller, including instructions stored in memory that when executed, cause the controller to: irradiate UV light from the UV light source, wherein the irradiated UV light is reflected by reflective surfaces of the first elliptic cylindrical reflector and reflective surfaces of the second elliptic cylindrical reflector, where the irradiated UV light reflected by the reflective surfaces first elliptic cylindrical reflector is reflected through an opening of the second elliptic cylindrical reflector and focused on to the workpiece. In a first example of the photoreactive system for UV curing, the controller further comprises instructions stored in memory that when executed, cause the controller to: dynamically vary an intensity of the irradiated UV light. A second example of the photoreactive system for UV curing optionally includes the first example, and further includes wherein the irradiated UV light reflected by the reflective surfaces of the first elliptic cylindrical reflector through the opening of the second elliptic cylindrical reflector and the irradiated UV light reflected by the reflective surfaces of the second elliptic cylindrical reflector forms a beam of spatially constant intensity surrounding the workpiece.

(89) In one embodiment, a method comprises: positioning a workpiece along a major axis of a first elliptic cylindrical reflector and a coaxial major axis of a second elliptic cylindrical reflector, the second elliptic cylindrical reflector nested within the first elliptic cylindrical reflector; positioning a light source within an interior of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector; and emitting light from the light source, wherein the emitted light is reflected onto the workpiece by reflective surfaces of the second elliptic cylindrical reflector and by reflective surfaces of the first elliptic cylindrical reflector through an opening of the second elliptic cylindrical reflector. In a first example of the method, the method further includes the workpiece arranged at a co-located focus of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector. A second example of the method optionally includes the first example, and further includes wherein the emitted light reflected onto the workpiece by the reflective surfaces of the second elliptic cylindrical reflector through the opening of the second elliptic cylindrical reflector is emitted through the opening in a first direction toward the first elliptic cylindrical reflector and reflected in a second direction toward the workpiece. A third example of the method optionally includes one or both of the first and second examples, and further includes wherein the emitted light is singly reflected from the reflective surfaces of the first elliptic cylindrical reflector prior to reaching the workpiece. A fourth example of the method optionally includes one or more or each of the first through third examples, and further includes wherein the emitted light is multiply reflected from the reflective surfaces of the second elliptic cylindrical reflector prior to reaching workpiece. A fifth example of the method optionally includes one or more or each of the first through fourth examples, and further includes wherein the light source comprises an LED array including a first LED and a second LED, wherein light is emitted from the first LED with a first peak wavelength and from the second LED with a second peak wavelength.

(90) FIGS. 3, 5, and 7-10 show example configurations with relative positioning of the various components. If shown directly contacting each other, or directly coupled, then such elements may be referred to as directly contacting or directly coupled, respectively, at least in one example. Similarly, elements shown contiguous or adjacent to one another may be contiguous or adjacent to each other, respectively, at least in one example. As an example, components laying in face-sharing contact with each other may be referred to as in face-sharing contact. As another example, elements positioned apart from each other with only a space there-between and no other components may be referred to as such, in at least one example. As yet another example, elements shown above/below one another, at opposite sides to one another, or to the left/right of one another may be referred to as such, relative to one another. Further, as shown in the figures, a topmost element or point of element may be referred to as a “top” of the component and a bottommost element or point of the element may be referred to as a “bottom” of the component, in at least one example. As used herein, top/bottom, upper/lower, above/below, may be relative to a vertical axis of the figures and

used to describe positioning of elements of the figures relative to one another. As such, elements shown above other elements are positioned vertically above the other elements, in one example. As yet another example, shapes of the elements depicted within the figures may be referred to as having those shapes (e.g., such as being circular, straight, planar, curved, rounded, chamfered, angled, or the like). Further, elements shown intersecting one another may be referred to as intersecting elements or intersecting one another, in at least one example. Further still, an element shown within another element or shown outside of another element may be referred to as such, in one example.

(91) Note that the example control and estimation routines included herein can be used with various system configurations. The control methods and routines disclosed herein may be stored as executable instructions in non-transitory memory and may be carried out by the control system including the controller in combination with the various sensors, actuators, and other hardware. The specific routines described herein may represent one or more of any number of processing strategies such as event-driven, interrupt-driven, multi-tasking, multi-threading, and the like. As such, various actions, operations, and/or functions illustrated may be performed in the sequence illustrated, in parallel, or in some cases omitted. Likewise, the order of processing is not necessarily required to achieve the features and advantages of the example embodiments described herein, but is provided for ease of illustration and description. One or more of the illustrated actions, operations, and/or functions may be repeatedly performed depending on the particular strategy being used. Further, the described actions, operations, and/or functions may graphically represent code to be programmed into non-transitory memory of the computer readable storage medium in the control system, where the described actions are carried out by executing the instructions in a system including the various hardware components in combination with the electronic controller.

(92) It will be appreciated that the configurations and routines disclosed herein are exemplary in nature, and that these specific embodiments are not to be considered in a limiting sense, because numerous variations are possible. Moreover, unless explicitly stated to the contrary, the terms “first,” “second,” “third,” and the like are not intended to denote any order, position, quantity, or importance, but rather are used merely as labels to distinguish one element from another. The subject matter of the present disclosure includes all novel and non-obvious combinations and sub-combinations of the various systems and configurations, and other features, functions, and/or properties disclosed herein.

(93) As used herein, the term “approximately” is construed to mean plus or minus five percent of the range unless otherwise specified.

(94) The following claims particularly point out certain combinations and sub-combinations regarded as novel and non-obvious. These claims may refer to “an” element or “a first” element or the equivalent thereof. Such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements. Other combinations and sub-combinations of the disclosed features, functions, elements, and/or properties may be claimed through amendment of the present claims or through presentation of new claims in this or a related application. Such claims, whether broader, narrower, equal, or different in scope to the original claims, also are regarded as included within the subject matter of the present disclosure.

Claims

1. A method, comprising: positioning a workpiece along a major axis of a first elliptic cylindrical reflector and a coaxial major axis of a second elliptic cylindrical reflector, the second elliptic cylindrical reflector nested within the first elliptic cylindrical reflector; positioning a light source within an interior of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector; and emitting light from the light source, wherein the emitted light is reflected onto the workpiece by reflective surfaces of the second elliptic cylindrical reflector and by reflective

surfaces of the first elliptic cylindrical reflector through an opening of the second elliptic cylindrical reflector.

2. The method of claim 1, wherein the workpiece is arranged at a co-located focus of the first elliptic cylindrical reflector and the second elliptic cylindrical reflector.

3. The method of claim 2, wherein the emitted light reflected onto the workpiece by the reflective surfaces of the second elliptic cylindrical reflector through the opening of the second elliptic cylindrical reflector is emitted through the opening in a first direction toward the first elliptic cylindrical reflector and reflected in a second direction toward the workpiece.

4. The method of claim 3, wherein the emitted light is singly reflected from the reflective surfaces of the first elliptic cylindrical reflector prior to reaching the workpiece.

5. The method of claim 4, wherein the emitted light is multiply reflected from the reflective surfaces of the second elliptic cylindrical reflector prior to reaching workpiece.

6. The method of claim 5, wherein the light source comprises an LED array including a first LED and a second LED, wherein light is emitted from the first LED with a first peak wavelength and from the second LED with a second peak wavelength.
