

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398007
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Abe; Nobuhira

Electrode stacking apparatus

Abstract

An electrode stacking apparatus provided with a planar motor device (B) comprised of a flat plate-shaped stator (50) and a plurality of movers (40) able to move on a flat surface (51) of the stator in any direction along the flat surface (51) and able to rotate about a perpendicular axis of the flat surface (51) in a state magnetically floating from the flat surface (51). When stacking a new sheet-shaped electrode (1) held by an electrode conveyor device (A) arranged above the planar motor device (B) on a stacked electrode holder (60) of a mover (40), the mover (40) is made to move in synchronization with movement of the new sheet-shaped electrode (1) so that the new sheet-shaped electrode (1) continues to face the sheet-shaped electrode stacking position on the stacked electrode holder (60).

Inventors:	Abe; Nobuhira (Toyota, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	1000008781801
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	17/736598
Filed:	May 04, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220363499 A1	Nov. 17, 2022

Foreign Application Priority Data

JP	2021-081038	May. 12, 2021
----	-------------	---------------

Publication Classification

Int. Cl.: B65H7/06 (20060101); B65H7/20 (20060101); B65H9/20 (20060101)

U.S. Cl.:

CPC B65H7/06 (20130101); B65H7/20 (20130101); B65H9/20 (20130101); B65H2301/421 (20130101); B65H2553/42 (20130101)

Field of Classification Search

CPC: H01M (10/0404); H01M (10/0413); H01M (10/0525); H01M (10/0585); B65G (54/02); B65H (7/06); B65H (7/20); B65H (9/20); B65H (31/20); B65H (31/24); B65H (31/28); B65H (31/34); B65H (29/005)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3832610	12/1973	Shimizu et al.	N/A	N/A
10581108	12/2019	Sakurai	N/A	H01M 10/0404
10910664	12/2020	Abe	N/A	H01M 10/0585
11241872	12/2021	Abe	N/A	H01M 10/0404
11274002	12/2021	Abe	N/A	B65H 3/48
11469437	12/2021	Abe	N/A	H01M 10/0404
2020/0044273	12/2019	Abe	N/A	N/A
2021/0257653	12/2020	Ono	N/A	B65H 31/10
2025/0074736	12/2024	Abe	N/A	H02K 41/031

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110808420	12/2019	CN	N/A
111564953	12/2019	CN	N/A
2345424	12/1973	DE	N/A
102017216138	12/2018	DE	N/A
2010-212165	12/2009	JP	N/A
2016-157586	12/2015	JP	N/A
2020-24816	12/2019	JP	N/A

Primary Examiner: Mackey; Patrick H

Attorney, Agent or Firm: Oliff PLC

Background/Summary

FIELD

(1) The present invention relates to an electrode stacking apparatus.

BACKGROUND

(2) Known in the art is an electrode stacking apparatus in which a sheet-shaped electrode conveyor device comprised of a linear motor having a plurality of movers running on an elliptically shaped

running rail and a stacking jig conveyor device comprised of a linear motor having a plurality of movers running on an elliptically shaped running rail are used and in which the elliptically shaped running rail of the sheet-shaped electrode conveyor device is arranged in a vertical plane and the elliptically shaped running rail of the stacking jig conveyor device is arranged inside a horizontal plane so that the straight parts of the elliptically shaped running rail of the stacking jig conveyor device extend in the same direction below the straight parts of the sheet-shaped electrode conveyor device (for example, see Japanese Unexamined Patent Publication No. 2020-024816).

(3) In this electrode stacking apparatus, at the straight rail parts, the stacking jig supported by the mover of the stacking jig conveyor device is made to move in synchronization with the movement of the sheet-shaped electrode held by the mover of the sheet-shaped electrode conveyor device. While the sheet-shaped electrode and the stacking jig are made to move in synchronization, the sheet-shaped electrode held by the mover of the sheet-shaped electrode conveyor device is stacked inside the stacking jig.

SUMMARY

(4) In this regard, however, in a conveyor device comprised of such linear motors, the holding position of the sheet-shaped electrode held by the mover of the sheet electrode conveyor device cannot be adjusted. As a result, if the holding position of the sheet-shaped electrode held by the mover of the sheet electrode conveyor device deviate from position aligned with and stackable on the sheet-shaped electrode already stacked inside the stacking jig, there is the problem that it is not possible align and stack the sheet-shaped electrode held by the mover of the sheet electrode conveyor device on the sheet-shaped electrode already stacked inside the stacking jig. Such a problem is difficult to solve so long as using a pair of conveyor devices comprised of the above such linear motors. A change in thinking is required to solve such a problem.

(5) To solve the above problem, according to the present invention, there is provided an electrode stacking apparatus for stacking a sheet-shaped electrode, comprising: a planar motor device comprised of a flat plate shaped stator and a plurality of movers able to move on a flat surface of the stator in any direction along the flat surface and able to rotate about a perpendicular axis of the flat surface in a state magnetically floating from the flat surface, an electrode conveyor device arranged above the planar motor device and conveying the sheet-shaped electrode along a conveyance path while holding the sheet-shaped electrode, and a control device for controlling the planar motor device and the electrode conveyor device, wherein a stacked electrode holder for holding stacked sheet-shaped electrodes being attached on each mover of the planar motor device and a successively stacked sheet-shaped electrode being held at a sheet-shaped electrode stacking position on the stacked electrode holder by the stacked electrode holder, when stacking a new sheet-shaped electrode held by the electrode conveyor device on the stacked electrode holder of the mover, the control device making the mover move in synchronization with movement of the new sheet-shaped electrode so that the new sheet-shaped electrode continues to face the sheet-shaped electrode stacking position on the stacked electrode holder.

(6) According to the present invention, when the holding position of the sheet-shaped electrode held by the mover of the sheet-shaped electrode conveyor device deviates from a position aligned with and stackable on the already stacked sheet-shaped electrode, by adjusting the position of the already stacked sheet-shaped electrode rather than adjusting the holding position of the sheet-shaped electrode held by the mover of the sheet-shaped electrode conveyor device, it becomes possible to make the sheet-shaped electrode held by the mover of the sheet-shaped electrode conveyor device be aligned with and stacked on the already stacked sheet-shaped electrode. In this case, the adjustment of the position of the already stacked sheet-shaped electrode becomes possible by using the planar motor device provided with a plurality of the movers able to move in any direction along the flat surface of the stator and able to rotate about a perpendicular axis of the flat surface in a state magnetically floating from the flat surface.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is an overall view of an electrode stacking apparatus.
- (2) FIGS. 2A, 2B, and 2C are views for explaining a sheet-shaped electrode.
- (3) FIG. 3 is an enlarged side view of part of the electrode conveyor device shown in FIG. 1.
- (4) FIG. 4 is a cross-sectional view of a mover.
- (5) FIG. 5 is a side view of a mover.
- (6) FIG. 6 is a perspective view of a planar motor device.
- (7) FIG. 7A, FIG. 7B, and FIG. 7C are views for explaining the structure of a mover of the planar motor device.
- (8) FIG. 8A, FIG. 8B, and FIG. 8C are views for explaining the structure of a stator of the planar motor device.
- (9) FIG. 9 is a view for explaining a method of control of a mover of the planar motor device.
- (10) FIG. 10A and FIG. 10B are perspective views of separate examples of a stacked electrode holder.
- (11) FIGS. 11A, 11B, and 11C are views for explaining an operation of a clamp of a stacked electrode holder.
- (12) FIG. 12 is a view for explaining a method of control of a mover of the planar motor device.
- (13) FIGS. 13A, 13B, 13C, 13D, and 13E are views for explaining stacking work of a sheet-shaped electrode.
- (14) FIG. 14A and FIG. 14B are views for explaining an amount of deviation of the holding position of a sheet-shaped electrode and a method of adjustment of the amount of deviation.
- (15) FIG. 15A and FIG. 15B are views for explaining amounts of deviation of the holding position of a sheet-shaped electrode and a method of adjustment of the amount of deviation.
- (16) FIG. 16 is a flow chart for control of a mover.
- (17) FIG. 17 is a flow chart for detection of positional deviation.
- (18) FIG. 18 is a flow chart for stacking processing.
- (19) FIG. 19 is an overall view of another embodiment of an electrode stacking apparatus.
- (20) FIG. 20A, FIG. 20B, FIG. 20C, and FIG. 20D are respectively a cross-sectional view of a mover and a view for explaining operation of a clamp.
- (21) FIG. 21A and FIG. 21B are respectively a perspective view of a stacked electrode holder and a view for explaining a link mechanism.
- (22) FIG. 22 is a view showing a state of arrangement of movers of a planar motor device.
- (23) FIG. 23A and FIG. 23B are respectively views showing a state of arrangement of movers of a planar motor device.
- (24) FIGS. 24A, 24B, 24C, 24D, 24E, 24F, 24G, and 24H are views for explaining stacking work of a sheet electrode.
- (25) FIG. 25 is a flow chart for control of movers.
- (26) FIG. 26 is a flow chart for stacking processing.
- (27) FIG. 27 is a flow chart for stacking processing.

DESCRIPTION OF EMBODIMENTS

(28) The present invention is an electrode stacking apparatus for stacking a sheet-shaped electrode. In an embodiment of the present invention, an electrode stack is formed by the sheet-shaped electrodes stacked by this electrode stacking apparatus. A plurality of the thus formed electrode stacks are electrically connected serially or in parallel to thereby, for example, form a battery for mounting in a vehicle. Therefore, first, a sheet-shaped electrode to be stacked in this electrode stacking apparatus will be explained. FIG. 2A is a plan view of a sheet-shaped electrode 1 used in the embodiment of the present invention, while FIG. 2B and FIG. 2C schematically show cross-

sections of two representative examples of the sheet-shaped electrode **1** seen along the X-X line of FIG. 2A. Note that, the thickness of the sheet-shaped electrode **1** is 1 mm or less. Therefore, in FIG. 2B and FIG. 2C, the thicknesses of the different layers are shown considerably exaggerated. (29) In the embodiment of the present invention, as the sheet-shaped electrode **1**, it is possible to use a sheet-shaped electrode **1** for an all-solid-state lithium-ion secondary battery and possible to use a sheet-shaped electrode **1** for a lithium-ion secondary battery using an electrolyte solution or gel polymer electrolyte. If as the sheet electrode **1** a sheet electrode **1** for an all-solid-state lithium-ion secondary battery is used, the sheet electrode **1**, as shown in FIG. 2B, has a positive electrode current collector layer **2**, positive electrode active substance layer **3**, solid-state electrolyte layer **4**, negative electrode active substance layer **5**, and negative electrode current collector layer **6**. In this case, the positive electrode current collector layer **2** is formed from a conductive material. In the embodiment of the present invention, this positive electrode current collector layer **2** is formed from a current collector-use metal foil, for example, aluminum foil. Further, the positive electrode active substance layer **3** is formed from a positive electrode active substance able to store lithium ions, sodium ions, calcium ions, and other metal ions at the time of discharge and release them at the time of charging. Further, the solid-state electrolyte layer **4** is formed from a material which has conductivity with respect to lithium ions, sodium ions, calcium ions, and other metal ions and can be utilized as the material of an all solid-state battery.

(30) On the other hand, the negative electrode active substance layer **5** is formed from a negative electrode active substance able to release lithium ions, sodium ions, calcium ions, and other metal ions at the time of discharge and store them at the time of charging. Further, the negative electrode current collector layer **6** is formed from a conductive material. In the embodiment of the present invention, this negative electrode current collector layer **2** is formed from a current collector-use metal foil, for example, copper foil. On the other hand, in the example shown in FIG. 2C, the sheet electrode **1** is comprised of an eight-layer structure of, in order from the top, a positive electrode current collector layer **2**, positive electrode active substance layer **3**, solid-state electrolyte layer **4**, negative electrode active substance layer **5**, negative electrode current collector layer **6**, negative electrode active substance layer **5**, solid-state electrolyte layer **4**, and positive electrode active substance layer **3**.

(31) On the other hand, if as the sheet electrode **1** a sheet electrode **1** for a lithium ion secondary battery using an electrolyte solution or gel polymer electrolyte is used, in FIG. 2B and FIG. 2C, instead of the solid-state electrolyte layer **4**, a separator **4** is used. In this case, for example, after the stacking work of the sheet-shaped electrode by the electrode stacking apparatus according to the present invention is completed, the electrolyte solution or gel polymer electrolyte is injected into the positive electrode active substance layer **3**, separator **4**, and electrode active substance layer **5** of the stacked sheet electrode. Note that, above, a typical sheet electrode **1** was explained, but various other types of the sheet electrode **1** can also be used.

(32) Referring to FIG. 1, FIG. 1 shows an electrode conveyor device A, planar motor device B, and control device C for control of these electrode conveyor device A and planar motor device B. First, this electrode conveyor device A will be explained. FIG. 3 shows an enlarged side view of part of the electrode conveyor device A shown in FIG. 1. Referring to FIG. 1 and FIG. 3, the electrode conveyor device A is provided with an elliptically shaped rail **10** comprised of horizontal straight parts **10a** separated by a distance in the up-down direction in a perpendicular plane and a pair of semicircular parts **10b** and a plurality of movers **12** able to run on this rail **10**. FIG. 4 shows a cross-sectional view of the mover **12** seen along the Y-Y line of FIG. 3. As shown in FIG. 4, this mover **12** is provided with a pair of guide rollers **13** attached to the mover **12** to be able to rotate about an axis **13a** and rolling on the rail **10** (arranged at the front and back with respect to an advancing direction), a pair of guide rollers **14** attached to the mover **12** to be able to rotate about an axis **14a** and rolling on the rail **10** (arranged at the front and back with respect to an advancing direction), a guide roller **15** attached to the mover **12** to be able to rotate about an axis **15a** and

rolling on the rail **10**, and a guide roller **16** attached to the mover **12** to be able to rotate about an axis **16a** and rolling on the rail **10**.

(33) On the other hand, this mover **12** is provided with a pair of permanent magnets **17** and **18**. Sandwiched between these permanent magnets **17** and **18** inside the electrode conveyor device A, a stator **11** around which a coil is wound is arranged. Due to this stator **11** and the permanent magnets **17** and **18**, that is, due to the stator **11** and the mover **12**, a linear motor is formed. Therefore, in the electrode conveyor device A, the mover **12** of the linear motor is made to run on the rail **10** in the conveyance direction shown in FIG. 3. The running speed of this mover **12** etc. are controlled by the control device C.

(34) Referring to FIG. 3, FIG. 4, and FIG. 5 showing a side view of FIG. 4, a conveyor plate **20** forming a rectangular shape is attached onto the mover **12** and, in the embodiment shown in FIG. 1, the sheet-shaped electrode **1** is held on this conveyor plate **20**. A plurality of clamps **21** and **22** for holding the sheet electrode **1** on the conveyor plate **20** are attached to the conveyor plate **20**. In the embodiment shown in FIG. 4 and FIG. 5, a pair of the clamps **21** are attached separated by a distance at the front end part of the conveyor plate **20** positioned at the front in the advancing direction and a pair of the clamps **22** are attached separated by a distance at the rear end part of the conveyor plate **20** positioned at the rear in the advancing direction. Note that, in addition to these clamps **21** and **22**, it is possible to attach further clamps to the conveyor plate **20**.

(35) The clamp **21** of FIG. 5 is shown when positioned at a sheet-shaped electrode holding position for holding the sheet-shaped electrode **1** on the conveyor plate **20**, while the clamp **22** of FIG. 5 is shown when positioned at a release position for releasing the holding action on the sheet electrode **1**. These clamps **21** and **22** have the same structures, so if explaining the structure of only the clamp **21**, the clamp **21** roughly speaking is provided with a clamp arm **23** forming an L-shape. The center part of this clamp arm **23** is attached by a support pin **24** to a support plate **25** fixed to the conveyor plate **20** to be able to turn. At one end of the clamp arm **23**, a hold down part **23a** extending up to the surface of the conveyor plate **20** is formed. At the other end of the clamp arm **23**, a roller **26** is attached. The clamp arm **23** is biased constantly in the counter clockwise direction by a tension spring **27** attached between the clamp arm **23** and support plate **25**.

(36) On the running path of the mover **12**, a fixed cam (not shown) able to engage with the roller **26** of the clamp arm **23** is provided. The roller **26** of the clamp arm **23** is usually not engaged with this fixed cam. At this time, the clamps **21** and **22** are positioned at the sheet-shaped electrode holding positions such as shown by the clamp **21** of FIG. 5 by the spring forces of the tension springs **27**. On the other hand, if the roller **26** of the clamp arm **23** is engaged with the fixed cam, the clamps **21** and **22** are made to turn until the release positions such as shown by the clamp **22** of FIG. 5.

(37) In the embodiment of the present invention, the sheet-shaped electrode **1** is prepared by cutting a long strip shaped electrode manufactured in advance in a prior process and having a cross-sectional structure shown in FIG. 2B or FIG. 2C into a set length. FIG. 1 and FIG. 3 schematically show this long strip shaped electrode sheet **30** and a cutting device **31**. As shown by the arrow mark F in FIG. 3, the electrode sheet **30** is continuously supplied facing slightly below the lower horizontal straight part **10a** of the rail **10** of the electrode conveyor device A. This electrode sheet **30** is cut into a set length by the cutting device **31**. Due to this, the sheet-shaped electrode **1** is prepared. In this case, for example, if the front end part of the electrode sheet **30** in the advancing direction proceeds to the front beyond the cutting device **31**, the mover **12** is controlled to run in synchronization with the movement of the front end part of the electrode sheet **30** in the advancing direction so that the position of the front end part of the electrode sheet **30** in the advancing direction is maintained at a position able to be held by the clamp **21**.

(38) That is, the mover **12** descends along the semicircular part **10b** of the rail **10** of the electrode conveyor device A in the state where the clamps **21** and **22** are rendered the release positions such as shown by the clamp **22** of FIG. 5. When the position of the front end part of the electrode sheet

30 in the advancing direction reaches a position able to be held by the clamp **21**, the clamp **21** is made to turn to the sheet-shaped electrode holding position and the front end part of the electrode sheet **30** in the advancing direction is held by the clamp **21**. If the position of the front end part of the electrode sheet **30** in the advancing direction is held by the clamp **21**, the electrode sheet **30** is cut into the set length by the cutting device **31** whereby the sheet-shaped electrode **1** is prepared. Next, the clamp **22** is made to turn to the sheet-shaped electrode holding position and the rear end part of the sheet-shaped electrode **1** is held by the clamp **22**. By doing this, this sheet-shaped electrode **1** is held by the clamps **21** and **22** on the conveyor plate **20**. Note that, guide rollers **32** guiding the sheet-shaped electrode **1** may be arranged so that the sheet-shaped electrode **1** is kept from falling off while the sheet-shaped electrode **1** is held by the clamps **21** and **22** on the conveyor plate **20**. In this case, the guide rollers **32**, for example, are configured by a plurality of rollers separated in distance, and the clamps **21** and **22** are made able to pass between the rollers. Note that, as will be understood from FIG. **3**, in the embodiment of the present invention, the direction of the arrow mark F is referred to as the “conveyance direction”.

(39) Next, an outline of the planar motor device B shown in FIG. **1** will be explained while referring to FIG. **6** to FIG. **9**. FIG. **6** schematically shows the planar motor device B as a whole. Referring to FIG. **6**, the planar motor device B is comprised of a flat plate shaped stator **50** and a mover **40** able to move on the flat surface **51** of the stator **50** in any direction along the flat surface **51** and able to rotate about a perpendicular axis of the flat surface **51** in the state magnetically floating from the flat surface **51**. As shown in FIG. **6**, this mover **40** forms a flat plate shape. Further, as shown in FIG. **6**, the stator **50** is formed by a set of a plurality of split stator elements **52**.

(40) FIG. **7A** is a rear view of the mover **40** shown in FIG. **6**, while FIG. **7B** is a vertical cross-sectional view of the mover **40** seen along the Z-Z line of FIG. **7A**. In FIG. **7A** and FIG. **7B**, **41** shows elongated permanent magnet pieces with rectangular cross-sections, and **42A** to **42D** respectively show magnet regions where these plurality of permanent magnet pieces **41** are arranged in parallel. As will be understood from FIG. **7A**, the magnet regions **42A** to **42D** are arranged point symmetrically about the center of the mover **40**. FIG. **7C** shows the typical magnetization directions inside the permanent magnet pieces **41** arranged in parallel in the magnet regions **42A** to **42D** (arrow marks show direction from S pole to N pole). On the other hand, as shown in FIG. **7A** and FIG. **7B**, a conductor **43** is arranged at the center part of the mover **40** surrounded by the magnet regions **42A** to **42D**.

(41) On the other hand, FIG. **8A** shows a vertical cross-sectional view of the stator elements **52** of the stator **50**. In the example shown in FIG. **8A**, inside each stator element **52**, a coil layer **53A** interacting with the magnetic field by the permanent magnet pieces **41** of the magnet region **42A** of the mover **40**, a coil layer **53B** interacting with the magnetic field by the permanent magnet pieces **41** of the magnet region **42B** of the mover **40**, a coil layer **53C** interacting with the magnetic field by the permanent magnet pieces **41** of the magnet region **42C** of the mover **40**, and a coil layer **53D** interacting with the magnetic field by the permanent magnet pieces **41** of the magnet region **42D** of the mover **40** are formed. Further, FIG. **8B** shows a plan view of the coil layer **53B** and the coil layer **53D**, while FIG. **8C** shows a plan view of the coil layer **53A** and the coil layer **53C**. In the example shown in FIG. **8B** and FIG. **8C**, the three coils **54A**, **54B**, and **54C** arranged slightly offset and partially superposed are made a single coil group. Inside the coil layers **53A**, **53B**, **53C**, and **53D**, such coil groups are arranged in parallel.

(42) Current is supplied to the coils **54A**, **54B**, and **54C** of the coil groups, and the amounts of current supplied to the coils **54A**, **54B**, and **54C** are controlled by the control device C. If current is supplied to the coils **54A**, **54B**, and **54C**, a magnetic field is generated. Due to the interaction of this magnetic field and the magnetic fields of the permanent magnet pieces **41** of the mover **40**, a force acting on the mover **40** is generated. In this case, in the example shown from FIG. **8A** to FIG. **8C**, the interaction of the magnetic field generated by the coils **54A**, **54B**, and **54C** of the coil layer

53A and the magnetic field generated by the permanent magnet pieces 41 of the magnet region 42A of the mover 40 causes a force acting on the magnet region 42A of the mover 40 to be generated, the interaction of the magnetic field generated by the coils 54A, 54B, and 54C of the coil layer 53B and the magnetic field generated by the permanent magnet pieces 41 of the magnet region 42B of the mover 40 causes a force acting on the magnet region 42B of the mover 40 to be generated, the interaction of the magnetic field generated by the coils 54A, 54B, and 54C of the coil layer 53C and the magnetic field generated by the permanent magnet pieces 41 of the magnet region 42C of the mover 40 causes a force acting on the magnet region 42C of the mover 40 to be generated, and the interaction of the magnetic field generated by the coils 54A, 54B, and 54C of the coil layer 53D and the magnetic field generated by the permanent magnet pieces 41 of the magnet region 42D of the mover 40 causes a force acting on the magnet region 42D of the mover 40 to be generated.

(43) In this case, by controlling the amounts of current supplied to the coils 54A, 54B, and 54C inside the coil layers 53A, 53B, 53C, and 53D to adjust the forces acting on the magnet regions 42A, 42B, 42C, and 42D of the mover 40, the mover 40 can be made to move on the flat surface 51 of the stator 50 in any direction along the flat surface 51 in a state magnetically floating from the flat surface 51, the mover 40 can be made to rotate on the flat surface 51 of the stator 50 about a perpendicular axis of the flat surface 51 in a state magnetically floating from the flat surface 51, and the mover 40 can be held on the flat surface 51 of the stator 50 at any position on the flat surface 51 targeted in a state magnetically floating from the flat surface 51.

(44) On the other hand, in the example shown from FIG. 6 to FIG. 8C, in the flat surface 51 of the stator 50, a large number of magnetic sensors are arranged dispersed over the flat surface 51 as a whole. Based on the outputs of these magnetic sensors, the position of the mover 40 is detected. That is, if the conductor 43 is arranged at the bottom surface of the mover 40, a magnetic circuit is formed inside this conductor 43 and the magnetic field greatly changes below the conductor 43. The change of the magnetic field appears in the outputs of the magnetic sensors. Therefore, in the example shown in FIG. 6 to FIG. 8C, the position of the mover 40 is detected based on the outputs of the magnetic sensors. Note that, there are various methods for detecting the position of the mover 40. For example, it is possible to detect the position of the mover 40 by attaching a light emitter to the bottom surface of the mover 40 and arranging a large number of optical sensors dispersed in the flat surface 51 of the stator 50.

(45) Now then, in the planar motor device B, the mover 40 can be held on the flat surface 51 of the stator 50 at any target planar position by any target angular position. In this case, the amounts of current which should be supplied to the coils 54A, 54B, and 54C in the coil layers 53A, 53B, 53C, and 53D so as to hold the mover 40 at the target planar position by the target angular position are known in advance. Therefore, if the target angular position and the target planar position of the mover 40 on the flat surface 51 of the stator 50 are determined, if controlling the amounts of current to be supplied to the coils 54A, 54B, and 54C inside the coil layers 53A, 53B, 53C, and 53D to the amounts of current necessary for holding the mover 40 at the target planar position by the target angular position, it becomes possible to hold the mover 40 at the target planar position by the target angular position.

(46) In the embodiment of the present invention, this is utilized to control movement and rotation of the mover 40. Next, the control of movement and rotation of the mover 40 will be explained while referring to FIG. 9. Note that, as shown in FIG. 9, a position P on the flat surface 51 of the stator 50 is set by x-y coordinates while the rotational angle θ of the mover 40 is set with reference to the x-axis. In FIG. 9, if assuming that the initial position of the mover 40 was P.sub.1 (x.sub.1, y.sub.1), first, the target planar positions P.sub.1 (x.sub.1, y.sub.1), P.sub.2 (x.sub.2, y.sub.2), P.sub.3 (x.sub.3, y.sub.3), P.sub.4 (x.sub.4, y.sub.4), and P.sub.5 (x.sub.5, y.sub.5) along the target path of movement for every time period and the target rotational angle positions Θ .sub.1, Θ .sub.2, Θ .sub.3, Θ .sub.4, and Θ .sub.5 at the target planar positions P.sub.1 (x.sub.1, y.sub.1), P.sub.2 (x.sub.2, y.sub.2), P.sub.3 (x.sub.3, y.sub.3), P.sub.4 (x.sub.4, y.sub.4), and P.sub.5 (x.sub.5, y.sub.5),

y.sub.5) are set. If these target planar positions P.sub.1, P.sub.2, P.sub.3, P.sub.4, and P.sub.5 and target rotational angle positions Θ .sub.1, Θ .sub.2, Θ .sub.3, Θ .sub.4, and Θ .sub.5 are set, based on the set target planar positions P.sub.1, P.sub.2, P.sub.3, P.sub.4, and P.sub.5 and target rotational angle positions Θ .sub.1, Θ .sub.2, Θ .sub.3, Θ .sub.4, and Θ .sub.5, the amounts of current supplied to the coils **54A**, **54B**, and **54C** inside the coil layers **53A**, **53B**, **53C**, and **53D** are controlled so that the mover **40** is held at the target planar positions P.sub.1, P.sub.2, P.sub.3, P.sub.4, and P.sub.5 by the target rotational angle positions Θ .sub.1, Θ .sub.2, Θ .sub.3, Θ .sub.4, and Θ .sub.5 every constant time period. If the amounts of current supplied to the coils **54A**, **54B**, and **54C** inside the coil layers **53A**, **53B**, **53C**, and **53D** are controlled in this way, the mover **40** is made to move along the target planar positions P.sub.1, P.sub.2, P.sub.3, P.sub.4, and P.sub.5 while rotating to the target rotational angle positions Θ .sub.1, Θ .sub.2, Θ .sub.3, Θ .sub.4, and Θ .sub.5.

(47) On the mover **40** of the planar motor device **B**, a stacked electrode holder **60** for holding a stacked sheet electrode **1** is carried. Therefore, next, this stacked electrode holder **60** will be explained while referring to FIG. **10A** and FIG. **10B**. FIG. **10A** shows a perspective view of the schematically illustrated stacked electrode holder **60**. Referring to FIG. **10A**, the stacked electrode holder **60** is provided with a base **61**, a pantograph type elevator mechanism **62** attached to the base **61**, a bottom plate **63** supported by the pantograph type elevator mechanism **62**, a clamp mechanism **65** for operating a clamp **64** provided at one side of the bottom plate **63**, and a clamp mechanism **67** for operating a clamp **66** provided at the other side of the bottom plate **63**. The pantograph type elevator mechanism **62** is provided with a spring (not shown) for pushing the bottom plate **63** upward. Due to the spring force of the spring of this pantograph type elevator mechanism **62**, the bottom plate **63** is constantly biased upward. The sheet-shaped electrode **1** is stacked on the bottom plate **63**.

(48) On the other hand, the clamp mechanism **65** and the clamp mechanism **67** have symmetric shapes about the short axis of the bottom plate **63**. Therefore, below, while referring to FIG. **10A** and FIGS. **11A**, **11B**, and **11C**, only the structure of the clamp mechanism **65** for operating the clamp **64** will be explained. The explanation of the structure of the clamp mechanism **67** for operating the clamp **66** will be omitted. Note that, FIGS. **11A-C** schematically show the operation of the clamp mechanism **65** for operating the clamp **64**. In FIGS. **11A**, **11B**, and **11C**, part of the bottom plate **63** and part of a plurality of the sheet-shaped electrodes **1** stacked on the bottom plate **63** are illustrated.

(49) Referring to FIG. **11A**, the clamp mechanism **65** of the stacked electrode holder **60** has a tilt mechanism **68** for tilting the clamp **64** and a slide mechanism **69** for making the tilt mechanism **68** move up and down. The slide mechanism **69** is provided with a slider **70** supported to be able to slide in the up-down direction inside the stacked electrode holder **60**, a roller **71** attached to the bottom end part of the slider **70** to be able to rotate, a compression spring **72** biasing the slider **70** upward, a camshaft **73** supported inside the stacked electrode holder **60** to be able to turn, a cam **74** fixed to the camshaft **73** and engaging with the roller **71**, an arm **75** fixed to the outside end part of the camshaft **73**, and a roller **76** attached to the front end part of the arm **75** to be able to rotate. The camshaft **73** is constantly biased counterclockwise by the spring force of a coil spring (not shown). If the camshaft **73** is made to turn clockwise in FIG. **11A**, as shown in FIG. **11B**, the slider **70** will rise due to the spring force of the compression spring **72**. That is, in the slide mechanism **69**, the slider **70** is made to move up and down by making the camshaft **73** turn.

(50) On the other hand, as shown in FIG. **11A**, the tilt mechanism **68** is provided with a tilt head **78** supporting the clamp **64** and attached by a rotating shaft **77** to the slider **70** to be able to turn, a roller **79** attached to the tilt head **78** to be able to rotate, a camshaft **80** supported at the slider **70** to be able to turn, a cam **81** fixed to the camshaft **80** and engaging with the roller **79**, an arm **82** fixed to the outside end part of the camshaft **80**, a roller **83** attached to the front end part of the arm **82** to be able to rotate, and a coil spring **84** biasing the tilt head **78** counterclockwise. The camshaft **80** is constantly biased clockwise by the spring force of a coil spring (not shown). Note that, as shown in

FIG. 11A or FIG. 11C, the position of the tilt head **78** when the clamp **64** is positioned above the sheet electrode **1** placed on the bottom plate **63** will be referred to below as the “upright position”. If in FIG. 11A, the camshaft **80** is made to turn counterclockwise, as shown in FIG. 11B, the tilt head **78** is tilted in a direction where the clamp **64** leaves the region above the sheet-shaped electrode **1** placed on the bottom plate **63**.

(51) FIG. 11A shows when the tilt head **78** is in the upright position and the sheet-shaped electrodes **1** stacked on the bottom plate **63** are held down by the clamp **64**. That is, at this time, the sheet-shaped electrodes **1** stacked on the bottom plate **63** are biased upward by the pantograph type elevator mechanism **62**, and the sheet-shaped electrodes **1** trying to rise at this time are held down by the clamp **64**. When releasing the hold down action by the clamp **64** on the sheet-shaped electrodes **1** stacked on the bottom plate **63**, the camshaft **73** is turned clockwise and the camshaft **80** is turned counterclockwise due to which, as shown in FIG. 11B, the tilt head **78** is made to rise and the tilt head **78** is tilted in a direction in which the clamp **64** leaves the region above the sheet-shaped electrodes **1** stacked on the bottom plate **63** (at this time, a new sheet-shaped electrode **1** is stacked on the sheet-shaped electrodes **1** stacked on the bottom plate **83**). Next, as shown in FIG. 11C, the tilt head **78** is returned to the upright position, then the tilt head **78** is made to descend, whereby the sheet-shaped electrodes **1** stacked on the bottom plate **83** are held down by the clamp **64**. The work of turning the camshaft **73** and the camshaft **80** is performed by the roller **76** and the roller **83** engaging with the fixed cams when the mover **12** is made to move.

(52) FIG. 10B shows a modification of the stacked electrode holder **60**. In this modification, only the clamp mechanism **65** for operating the clamp **64** is provided. The clamp mechanism **67** for operating the clamp **66** shown in FIG. 10A is not provided. In this modification as well, the clamp mechanism **65** performs the operation shown in FIGS. 11A-C the same as the clamp mechanism **65** shown in FIG. 10A.

(53) Next, referring to FIG. 12, the method of control of the mover **40** of the planar motor device B performed in the first embodiment of the present invention will be explained. FIG. 12 shows a plan view of the electrode stacking apparatus shown in FIG. 1 seen from above. In FIG. 12, a plurality of the movers **40** moving on the flat surface **51** of the stator **50**, the stacked electrode holders **60** shown in FIG. 10A fixed on the movers **40**, and the sheet-shaped electrodes **1** held by the stacked electrode holders **60** are shown. Furthermore, in FIG. 12, the position of the electrode conveyor device A is shown by the dash and dot lines. As shown in FIG. 12, in this first embodiment, the sheet-shaped electrodes **1** are held by pairs of the stacked electrode holders **60** fixed on pairs of the movers **40** arranged in parallel.

(54) In this first embodiment, new sheet-shaped electrodes **1** held by the electrode conveyor device A are stacked on pairs of the stacked electrode holders **60** fixed on pairs of the movers **40** moving in a parallel arranged state in the conveyance direction right under the electrode conveyor device A (in FIG. 12, direction from above to below). Note that, below, the control for movement of the movers **40** will be explained with reference to an example where the long direction axis of the electrode conveyor device A is made the y-axis direction of the positional coordinates at the flat surface **51** of the stator **50** and the short direction axis of the electrode conveyor device A is made the x-axis direction of the positional coordinates on the flat surface **51** of the stator **50**. In this case, when the new sheet-shaped electrodes **1** held by the electrode conveyor device A are stacked on the pairs of the stacked electrode holders **60** below the electrode conveyor device A, the pairs of the movers **40** move in the minus direction of the y-axis.

(55) Now then, in this embodiment of the present invention, the running path of the mover **40** used as the reference on the flat surface **51** of the stator **50** is set in advance by x-y coordinates. The running path of the mover **40** used as the reference set in advance will be called a “reference running path”. In this embodiment of the invention, this reference running path is set with respect to the center of the mover **40**. Each mover **40** is controlled by the control device C so that the center of the mover **40** moves along this reference running path. In FIG. 12, a plurality of the

reference running paths are shown by the dash and dot lines.

(56) Referring to FIG. 12, a pair of stacking reference running paths K1 and K2 forming loop shapes and separated by a constant distance in the x-axis direction and a pair of ejection reference running paths K3 and K4 respectively branched from these stacking reference running paths K1 and K2 and extending straight are illustrated. When performing stacking work for stacking new sheet-shaped electrodes 1 on the pairs of stacked electrode holders 60, paired movers 40 carrying the stacked electrode holders 60 and arranged in parallel are made to move along the stacking reference running paths K1 and K2 in the paired state without the movers 40 turning. In this case, at the region below the electrode conveyor device A where the stacking work is performed, the stacking reference running paths K1 and K2 are set so as to extend straight in the y-axis direction separated by equal distances at opposite sides to each other from the long axis of the electrode conveyor device A. When stacking work is performed, the paired movers 40 are made to move in synchronization with the movement of the new sheet-shaped electrodes 1 held by the electrode conveyor device A so that the new sheet-shaped electrodes 1 continue to face the sheet-shaped electrode stacking positions on the stacked electrode holders 60.

(57) At the region below the electrode conveyor device A where the stacking work is performed, a plurality of paired movers 40 are made to move in the y-axis direction separated by equal distances, and the work of stacking new sheet-shaped electrodes 1 on the stacked electrode holders 60 is successively performed. The paired movers 40 carrying the stacked electrode holders 60 on which the stacking work of the new sheet-shaped electrodes 1 has been completed are made to move at a high speed along the stacking reference running paths K1 and K2 until arriving behind the paired movers 40 running in front so as to perform the stacking work of the next new sheet-shaped electrodes 1. When the paired movers 40 reach behind the paired movers running in front, after that, the paired movers 40 are made to move while following the paired movers 40 running in front.

(58) If the stacking work of a preset number of new sheet-shaped electrodes 1 is completed, the paired movers 40 carrying the stacked electrode holders 60 holding the preset number of stacked sheet-shaped electrodes 1 are ejected from the electrode conveyor device A along the corresponding ejection reference running paths K3 and K4 from the region below the electrode conveyor device A where the stacking work is performed. In case where the sheet-shaped electrodes 1 for an all-solid-state lithium-ion secondary battery are used as the sheet-shaped electrodes 1, if the stacked sheet-shaped electrodes 1 are ejected from the electrode conveyor device A, at the next process, the stacked sheet-shaped electrodes 1 held by the stacked electrode holders 60 are pressed by a press device and single side surfaces of the pressed stacked sheet-shaped electrodes 1 are bonded by a resin. Next, after other processes, stacks of the sheet-shaped electrodes 1 are prepared. If the stacks of the sheet-shaped electrodes 1 are prepared, the stacks of the sheet-shaped electrodes 1 are taken out from the stacked electrode holders 60 and the paired movers 40 carrying the emptied stacked electrode holders 60 are made to move to a standby region Q.

(59) On the other hand, in case where the sheet-shaped electrodes 1 for a lithium-ion secondary battery using an electrolyte solution or gel polymer are used as the sheet-shaped electrodes 1, if the stacked sheet-shaped electrodes 1 are ejected from the electrode conveyor device A, at the next process, single side surfaces of the pressed stacked sheet-shaped electrodes 1 are bonded by a resin, then the electrolyte solution or gel polymer electrolyte is injected into the positive electrode active substance layers 3, separators 4 and electrode active substance layers 5 from the peripheral parts of the stacked sheet-shaped electrodes 1 not bonded by the resin. Next, after other processes, stacks of the sheet-shaped electrodes 1 are prepared. If the stacks of the sheet-shaped electrodes 1 are prepared, the stacks of the sheet-shaped electrodes 1 are taken out from the stacked electrode holders 60 and the paired movers 40 carrying the emptied stacked electrode holders 60 are made to move to a standby region Q.

(60) On the other hand, if the stacked sheet-shaped electrodes 1 are ejected from the electrode

conveyor device A, the paired movers **40** carrying the empty stacked electrode holders **60** standing by at the standby region Q are made to move at a high speed to behind the front paired movers **40** running along the stacking reference running paths K1 and K2. Next, if the paired movers **40** carrying the emptied stacked electrode holders **60** reach behind the paired movers **40** running in front, after that the paired movers **40** carrying the emptied stacked electrode holders **60** are made to move following the paired movers **40** running in front.

(61) In this way, in the first embodiment, the movers **40** are made to move along the preset stacking reference running paths K1 and K2 and ejection reference running paths K3 and K4. In this case, in this embodiment of the present invention, the x-y coordinates for each time period on the stacking reference running paths K1 and K2 and ejection reference running paths K3 and K4 corresponding to the requests for movement of the movers **40** are set as the target planar positions of the movers **40** while the rotational angle positions of the movers **40** with respect to the x-axis of the x-y coordinates are set as the target rotational angle positions. In this case, the amounts of current supplied to the coils **54A**, **54B**, and **54C** inside the coil layers **53A**, **53B**, and **53C** **53D** are controlled by the control device C every constant time period so that the movers **40** are held at the target planar positions by the target rotational angle positions.

(62) Next, referring to FIGS. **13A-E**, the stacking work of a new sheet-shaped electrode **1** on the stacked electrode holder **60** performed at the region below the electrode conveyor device A will be explained. Note that, in FIGS. **13A-E**, the clamping action of the sheet-shaped electrodes **1** by the clamps **21** and **22** attached to the conveyor plate **20** of the electrode conveyor device A and the clamping action of the sheet-shaped electrodes **1** by the clamps **64** and **66** of the stacked electrode holder **60** carried by the mover **40** of the planar motor device B are schematically shown. Further, in FIGS. **13A-E**, the pantograph type elevator mechanism **62** for biasing the bottom plate **63** of the stacked electrode holder **60** upward is illustrated by a spring. Note that, FIGS. **13A-E** show the case where sheet-shaped electrodes **1** are already stacked on the bottom plate **63**.

(63) When the stacking work is performed, paired movers **40** are made to move in synchronization with the movement of the new sheet-shaped electrode **1** so that the new sheet-shaped electrode **1** held by the electrode conveyor device A continues to face the sheet-shaped electrode stacking positions on the stacked electrode holders **60**. FIG. **13A** shows the time of start of the stacking work. At this time, the new sheet-shaped electrode **1** is held by the clamps **21** and **22** on the conveyor plate **20** while the stacked sheet-shaped electrodes **1** are held by the clamps **64** and **66** on the bottom plate **63**. Next, as shown in FIG. **13B**, the holding actions of the clamp **21** and the clamp **64** are released in the state holding the peripheral part of one side of the new sheet-shaped electrode **1** on the conveyor plate **20** by the clamp **22** and holding the end parts of single sides of the stacked sheet-shaped electrodes **1** on the bottom plate **63** by the clamp **66** of the paired movers **40**. At this time, the end part of the other side of the new sheet-shaped electrode **1** drops onto the stacked sheet-shaped electrodes **1**.

(64) Next, as shown in FIG. **13C**, the end part at the other side of the new sheet-shaped electrode **1** dropping onto the stacked sheet-shaped electrodes **1** is held by the clamp **64** on the stacked sheet-shaped electrodes **1**. Next, as shown in FIG. **13D**, the holding actions of the clamps **22** and the clamps **65** are released in the state where the end part of the other side of the new sheet-shaped electrode **1** dropping onto the stacked sheet-shaped electrodes **1** is held on the stacked sheet-shaped electrodes **1** by the clamp **64**. At this time, the new sheet-shaped electrode **1** as a whole drops onto the stacked sheet-shaped electrodes **1**. Next, as shown in FIG. **13E**, the stacked sheet-shaped electrodes **1** are held by the clamps **64** and **66** on the bottom plate **63**. Note that, in FIGS. **13A-E**, the clamping actions by the clamps **21** and **22** attached to the conveyor plate **20** and the releasing actions of the clamps are performed by the roller **26** engaging with fixed cams during movement of the conveyor plate **20** while the clamping actions by the clamps **64** and **66** of the stacked electrode holder **60** and the releasing actions of the clamps are performed by the rollers **76** and **83** of the stacked electrode holder **60** engaging with fixed cams during movement of the mover **40**.

(65) In this way, in this embodiment of the present invention, it will be understood that during stacking work of the sheet-shaped electrodes **1**, the new sheet-shaped electrode **1** is held by at least one clamp among the clamps **21** and **22** attached to the conveyor plate **20** or the clamps **64** and **66** of the stacked electrode holder **60** until it is stacked on the stacked electrode holder **60**.

(66) In this regard, if the new sheet-shaped electrode **1** is not held on the conveyor plate **20** by the clamps **21** and **22** at the regular holding position, when stacking the new sheet-shaped electrode **1** on the stacked sheet-shaped electrodes **1** held by the stacked electrode holder **60**, the stacking position of the new sheet-shaped electrode **1** will deviate from the stacking position of the stacked sheet-shaped electrodes **1** and the new sheet-shaped electrode **1** will no longer be able to be stacked aligned on the stacked sheet-shaped electrodes **1**. Therefore, in this embodiment of the present invention, when stacking the new sheet-shaped electrode **1** on stacked sheet-shaped electrodes **1** held by the stacked electrode holder **60**, if the stacking position of the new sheet-shaped electrode **1** deviates from the stacking position of the stacked sheet-shaped electrodes **1**, the movement position and rotational angle position of the mover **40** of the planar motor device B are controlled so as to enable the new sheet-shaped electrode **1** to be stacked aligned on the stacked sheet-shaped electrodes **1**.

(67) Next, the control of the movement position and rotational angle position of the mover **40** of the planar motor device B will be explained while referring to FIG. **14A** to FIG. **15B**. FIG. **14A** shows a bottom view of the conveyor plate **20** when the mover **12** of the electrode conveyor device A is positioned on the lower horizontal straight part **10a** of the rail **10**. In FIG. **14A**, the new sheet-shaped electrode **1** held on the conveyor plate **20** by the clamps **21** and **22** is shown. Further, in FIG. **14A**, the arrow mark direction shows the advancing direction of the conveyor plate **20**. On the other hand, FIG. **14B** shows a plan view of the paired movers **40** made to move in synchronization with movement of the conveyor plate **20** shown in FIG. **14A**. In FIG. **14B**, the stacked sheet-shaped electrodes **1** held by the clamps **64** and **66** at the sheet-shaped electrode stacking position on the stacked electrode holder **60** carried by the movers **40** is shown.

(68) On the other hand, in FIG. **14A**, the regular holding position required for aligning the new sheet-shaped electrode **1** with the sheet-shaped electrode stacking position on the stacked electrode holder **60** is shown by the dash and dot line R. If the new sheet-shaped electrode **1** is held on the conveyor plate **20** at this regular holding position R, when stacking the new sheet-shaped electrode **1** on the stacked sheet-shaped electrodes **1** held by the stacked electrode holder **60**, the new sheet-shaped electrode **1** is stacked aligned with the stacked sheet-shaped electrodes **1** held by the stacked electrode holder **60**. In this embodiment of the present invention, this regular holding position R is preset.

(69) Now then, FIG. **14A** shows the case where the center of the new sheet-shaped electrode **1** held on the conveyor plate **20** deviates from the center O.sub.0 of the regular holding position R as shown by the arrow to O.sub.c and where the rotational angle position of the new sheet-shaped electrode **1** deviates from the regular holding position by exactly the angle α . Note that, these amounts of deviation are shown exaggerated so as to facilitate understanding. In this case, in this embodiment of the present invention, as shown in FIG. **14B**, the position of one mover **40** is changed from the set position O.sub.1 on the stacking reference running path K1 to the position O.sub.d and one mover **40** is rotated from the reference rotational angle position by exactly the angle α while the position of the other mover **40** is changed from the set position O.sub.2 on the stacking reference running path K2 to the position O.sub.e and the other mover **40** is rotated from the reference rotational angle position by exactly the angle α so that the new sheet-shaped electrode **1** is stacked aligned on the stacked sheet-shaped electrodes **1** held by the stacked electrode holder **60**.

(70) The method of calculation of the changed coordinates (x.sub.d, y.sub.d) of the set position O.sub.d of the one mover **40** in this case and the method of calculation of the changed coordinates (x.sub.e, y.sub.e) of the set position O.sub.e of the other mover **40** in this case are shown in FIG.

15A and FIG. 15B. That is, if the amounts of deviation in the x-axis direction and the y-axis direction when the center of the new sheet-shaped electrode **1** held on the conveyor plate **20** deviates from the center O.sub.0 of the regular holding position R to Oc as shown in FIG. 15A are made Δx and Δy , and if the coordinates of the reference position O.sub.1 set on the stacking reference running path K1 of one mover **40** as shown in FIG. 15B are made (x.sub.1, y.sub.1), and the coordinates of the reference position O.sub.2 set on the stacking reference running path K2 of the other mover **40** are made (x.sub.2, y.sub.2), as shown at the bottom of FIG. 15B, it is possible to calculate the changed coordinates (x.sub.d, y.sub.d) of the set position O.sub.d of the one mover **40** and the changed coordinates (x.sub.e, y.sub.e) of the set position O.sub.e of the other mover **40** by using the amounts of deviation Δx , Δy , the rotational angle α , the values of the coordinates x.sub.1, y.sub.1 of the reference position O.sub.1, and the values of the coordinates x.sub.2, y.sub.2 of the reference position O.sub.2. Note that, in FIG. 15B, the coordinates (x.sub.0, y.sub.0) of O.sub.m show a median point of the reference position O.sub.1 (x.sub.1, y.sub.1) and the reference position O.sub.2 (x.sub.2, y.sub.2), that is, the center of the stacked sheet electrode **1**, while S shows the distance from the center coordinates O.sub.m (x.sub.0, y.sub.0) to the reference position O.sub.1 (x.sub.1, y.sub.1) and reference position O.sub.2 (x.sub.2, y.sub.2).

(71) In the first embodiment shown in FIG. 1, to detect the occurrence of deviation of the new sheet-shaped electrode **1** on the conveyor plate **20** with respect to the regular holding position R such as shown in FIG. 14A, a camera **33** is set for capturing the new sheet-shaped electrode **1** held on the conveyor plate **20** and the amounts of deviation Δx , Δy , and α such as shown in FIG. 15A are detected based on the images captured by the camera **33**. If these amounts of deviation Δx , Δy , and α are detected, the changed coordinates (x.sub.d, y.sub.d) of the set position O.sub.d of the one mover **40** and the changed coordinates (x.sub.e, y.sub.e) of the set position O.sub.e of the other mover **40** are calculated from these amounts of deviation Δx , Δy , and α using the calculation formula shown at the bottom of FIG. 15B. If these coordinates (x.sub.d, y.sub.d) and coordinates (x.sub.e, y.sub.e) are calculated, movement of the movers **40** is controlled by the control device C so that the movers **40** pass through these coordinates (x.sub.d, y.sub.d) and coordinates (x.sub.e, y.sub.e).

(72) FIG. 16 shows a mover control routine for control of movement of the paired movers in the first embodiment. Control of movement of all of the movers **40** present inside the electrode stacking apparatus is repeatedly performed for each mover by this mover control routine.

(73) Referring to FIG. 16, at step **100**, it is judged if the stacking processing for stacking the new sheet-shaped electrode **1** held on the conveyor plate **20** onto the stacked electrode holders **60** of the movers **40** being controlled at the current processing cycle is underway. When it is judged that the stacking processing for stacking the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the movers **40** being controlled is underway, the routine proceeds to step **101** where the stacking processing is continued. This stacking processing is performed by the stacking processing routine shown in FIG. 18.

(74) Next, at step **102**, it is judged if the stacking processing for stacking the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the movers **40** being controlled has been completed. When it is judged that the stacking processing for stacking the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the movers **40** being controlled has not been completed, the routine proceeds to step **103** where return processing is performed for returning the movers **40** being controlled along the stacking reference running paths K1 and K2 to the stacking start positions. On the other hand, when at step **102** it is judged that the stacking processing for stacking the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the movers **40** being controlled has been completed, the routine proceeds to step **104** where the ejection processing is performed for making the movers **40** being controlled advance along the ejection reference running paths K3 and K4 to the next process.

(75) On the other hand, when at step **100** it is judged that the stacking processing for stacking the

new sheet-shaped electrode **1** on the stacked electrode holders **60** of the movers **40** being controlled is not underway, the routine proceeds to step **105** where it is judged if the movers **40** being controlled are in the middle of a following operation following a pair of the movers **40** moving in front on the stacking reference running paths K1 and K2. When it is judged that the movers **40** being controlled are in the middle of following a pair of the movers **40** moving in front, the routine proceeds to step **106** where it is judged if the movers **40** being controlled reaches the stacking start positions. When it is judged that the movers **40** being controlled reaches the stacking start positions, the routine proceeds to step **107** where the stacking processing for stacking the new sheet-shaped electrode **1** on the stacked electrode holders **60** on the movers **40** being controlled is started.

(76) On the other hand, when at step **105** it is judged that the movers **40** being controlled are not following a pair of the movers **40** moving in the front, the routine proceeds to step **108** where the movers **40** being controlled are made to move at a high speed toward the pair of the movers **40** moving in front until approaching the rear of the pair of movers **40** moving in front. This high speed running of the movers **40** is performed when the return processing is started at step **103** and when a pair of the movers **40** carrying emptied stacked electrode holders **60** are sent inside the stacking reference running paths K1 and K2. Next, at step **109**, it is judged if the movers **40** being controlled reaches following positions of constant distances to a pair of the movers **40** moving in front on the stacking reference running paths K1 and K2. When it is judged that the movers **40** being controlled reaches the following positions, the routine proceeds to step **110** where the following processing is performed for making the movers **40** being controlled move to follow a pair of the movers **40** moving in front.

(77) FIG. **17** shows a position deviation detection routine for detecting the occurrence of deviation of the new sheet electrode **1** on the conveyor plate **20** from the regular holding position. This detection routine is repeatedly performed.

(78) Referring to FIG. **17**, at step **120**, it is judged if it is the detection timing. When it is judged that it is the detection timing, the routine proceeds to step **121** where an image of the new sheet-shaped electrode **1** held on the conveyor plate **20** is captured by the camera **33**. Next, at step **122**, from this captured image, the image processing for recognizing the shape of the sheet-shaped electrode **1** and the holding position of the sheet-shaped electrode **1** is performed by using, for example, an object detection technique.

(79) Next, at step **123**, it is judged based on the results of the image processing if the new sheet-shaped electrode **1** on the conveyor plate **20** deviates from the regular holding position R. When it is judged that the new sheet-shaped electrode **1** on the conveyor plate **20** deviates from the regular holding position R, the routine proceeds to step **124** where amounts of deviation Δx , Δy , and α such as shown in FIG. **15A**, that is, correction values Δx , Δy , and α used for correction of the set positions of the movers **40**, are calculated. Next, at step **125**, the correction values Δx , Δy , and α are stored in the control device C. Next, at step **126**, a correction request showing that the set positions of the movers **40** should be corrected is issued.

(80) FIG. **18** shows a stacking processing routine performed at step **101** of the mover control routine shown in FIG. **16**. This stacking processing routine is repeatedly performed.

(81) Referring to FIG. **18**, at step **140**, the values of the coordinates of the next reference position O.sub.1 ($x_{sub.1}$, $y_{sub.1}$) on the stacking reference running path K1 for one of the movers **40** being controlled and the values of the coordinates of the next reference position O.sub.2 ($x_{sub.2}$, $y_{sub.2}$) on the stacking reference running path K2 with respect to the other of the movers **40** being controlled are calculated. Next, at step **141**, it is judged if the correction request is made in the position deviation detection routine shown in FIG. **17**. When it is judged that the correction request is made, the routine proceeds to step **142**.

(82) At step **142**, the correction values Δx , Δy , and α stored in the control device C are read. Next, at step **143**, as shown in FIG. **15B**, based on these correction values Δx , Δy , and α , the values of the

changed coordinates of the set position O.sub.d (x.sub.d, y.sub.d) of one of the movers **40** and the values of the changed coordinates of the set position O.sub.e (x.sub.e, y.sub.e) of the other of the movers **40** are calculated. Next, the routine proceeds to step **144**. On the other hand, when at step **141** it is judged that the correction request is not made, the routine jumps to step **144**. When at step **144** the correction request is not been made, the amounts of current supplied to the coils **54A**, **54B**, and **54C** in the coil layers **53A**, **53B**, **53C**, and **53D** of the stator **50** are controlled by the control device C so that the movement positions of the movers **40** respectively become the next reference position O.sub.1 (x.sub.1, y.sub.1) on the stacking reference running path K1 and the next reference position O.sub.2 (x.sub.2, y.sub.2) on the stacking reference running path K2, while when the correction request is made, the amounts of current supplied to the coils **54A**, **54B**, and **54C** in the coil layers **53A**, **53B**, **53C**, and **53D** of the stator **50** are controlled by the control device C so that the movement positions of the movers **40** respectively become the changed set position O.sub.d (x.sub.d, y.sub.d) and changed set position O.sub.e (x.sub.e, y.sub.e).

(83) Next, at step **145**, the routine waits until the preset constant time elapses. If the constant time elapses, the routine proceeds to step **146** where it is judged of the stacking work of one new sheet-shaped electrode **1** has ended. When it is judged that the stacking work of one new sheet-shaped electrode **1** has not ended, the routine returns to step **140** where control of movement of the movers **40** is continued. On the other hand, when at step **146** it is judged that the stacking work of one new sheet-shaped electrode **1** has ended, the routine proceeds to step **147** where the stacking work of the new sheet-shaped electrode **1** is ended. Next, the routine proceeds to step **102** of the mover control routine shown in FIG. **16**.

(84) In this way, in the first embodiment according to the present invention, the electrode stacking apparatus for stacking the sheet-shaped electrode **1** comprises the planar motor device B comprised of the flat plate shaped stator **50** and a plurality of the movers **40** able to move on the flat surface **51** of the stator **50** in any direction along the flat surface **51** and able to rotate about a perpendicular axis of the flat surface **51** in a state magnetically floating from the flat surface **51**, the electrode conveyor device A arranged above the planar motor device B and conveying the sheet-shaped electrode **1** along the conveyance path while holding the sheet-shaped electrode **1**, and the control device C for controlling the planar motor device B and electrode conveyor device A. The stacked electrode holder **60** for holding stacked sheet-shaped electrodes **1** is attached on each mover **40** of the planar motor device B and successively stacked sheet-shaped electrodes **1** are held at a sheet electrode stacking position on the stacked electrode holder **60** by the stacked electrode holder **60**. When stacking the new sheet-shaped electrode **1** held by the electrode conveyor device A on the stacked electrode holder **60** of the mover **40**, the control device C makes the mover **40** move in synchronization with movement of the new sheet-shaped electrode **1** so that the new sheet-shaped electrode **1** continues to face the sheet-shaped electrode stacking position on the stacked electrode holder **60**.

(85) In this case, in the embodiment of the present invention, as the holding position of the new sheet-shaped electrode **1** by the electrode conveyor device A, a regular holding position R required for making the new sheet-shaped electrode **1** align with the sheet-shaped electrode stacking position on the stacked electrode holder **60** is set in advance, a deviation detection device is provided for detecting an amounts of deviation of the holding position of the new sheet-shaped electrode **1** from the regular holding position R, and the control device controls the movement position and rotational angle position of each mover **60** based on the amounts of deviation so that the new sheet-shaped electrode **1** is stacked on the stacked electrode holder **60** aligned with the sheet-shaped electrode stacking position of the stacked electrode holder **60**. In this case, in the embodiment of the present invention, the above-mentioned deviation detection device is provided with a camera **33** for capturing the new sheet-shaped electrode **1** held by the electrode conveyor device A, and the amounts of deviation are detected based on images captured by the camera **33**.

(86) On the other hand, in the embodiment of the present invention, the electrode conveyor device

A is comprised of a linear motor having a plurality of movers **12** made to move along the conveyance path, and a new sheet-shaped electrode **1** is held by the clamps **21** and **22** on conveyor plates **20** attached to the movers **12** of the linear motor. In this case, in the embodiment of the present invention, the stacked electrode holders **60** of the movers **40** of the planar motor device B are provided with clamps **64** and **66**, and when the movers **40** of the planar motor device B are made to move in synchronization with movement of the new sheet-shaped electrodes **1**, the new sheet-shaped electrode **1** held on the conveyor plates **20** is stacked on the stacked electrode holders **60** while being held at the peripheral part of the new sheet shaped electrode **1** by either the clamps of the clamps **21** and **22** of the conveyor plate and the clamps **66** of the stacked electrode holders. (87) Furthermore, in the embodiment of the present invention, the sheet-shaped electrode **1** is held by a plurality of the movers **40** of the planar motor device B. Further, in the embodiment of the present invention, when the movers **40** of the planar motor device B holding the sheet-shaped electrodes **1** are made to run along curved running paths, the control device controls the movement positions and rotational positions of the movers **40** so that the movers **40** of the planar motor device B do not rotate.

(88) Next, referring to FIG. **19** to FIG. **27**, a second embodiment according to the present invention will be explained. This second embodiment is suitable for the case where as the sheet-shaped electrode **1** the sheet-shaped electrode **1** for a lithium ion secondary battery using an electrolyte solution or gel polymer electrolyte is used and the size of the stacked sheet-shaped electrode **1** is large. Note that, in this second embodiment, constituent elements similar to the first embodiment will use the same reference notations as the first embodiment and explanations will be omitted.

(89) Referring to FIG. **19**, in this second embodiment, unlike the first embodiment, a pair of electrode conveyor devices, that is, a first electrode conveyor device **A1** and a second electrode conveyor device **A2**, are used. These first electrode conveyor device **A1** and second electrode conveyor device **A2** are arranged in parallel symmetrically about a symmetric axis I-I while separated by a distance from each other. Therefore, in this second embodiment, compared with the first embodiment, the flat surface **51** of the planar motor device B is made larger in size. Further, in this second embodiment, compared with the first embodiment, the sheet-shaped electrode **1** is larger in size. Therefore, the horizontal width of the long strip-shaped electrode sheet **30** and the horizontal width of the cutting device **31** also become larger. Further, in this second embodiment as well, the control device C and the camera **33** are provided. However, in this second embodiment, the camera **33** is arranged above the sheet electrode **1**.

(90) The first electrode conveyor device **A1** and the second electrode conveyor device **A2** have overall shapes the same as the electrode conveyor device A of FIG. **1**. In the same way as the electrode conveyor device A of FIG. **1**, they are comprised of linear motors having stators **11** and movers **12**. FIG. **20A** shows a cross-sectional view of the mover **12** of the first electrode conveyor device **A1** seen along the XX-XX line of FIG. **19**. From FIG. **20A**, it will be understood that the mover **12** has the same structure as the mover **12** of the first embodiment. On the other hand, as shown in FIG. **20A**, in this second embodiment, unlike the first embodiment, the conveyor plate **20** attached to the mover **12** is comprised of a lower plate **20a** fixed on the mover **12** and an upper plate **20b** slidably supported on the lower plate **20a**. At the outside end part of the upper plate **20b**, a thick part **20c** able to engage with the outside end face of the lower plate **20a** is formed.

(91) As shown in FIG. **20A**, at the outside end part of the upper plate **20b**, a clamp **19** is attached. This clamp **19** is provided with a clamp arm **23** roughly speaking forming an L-shape. The center part of this clamp arm **23** is attached to a support plate **25** fixed to the upper plate **20b** by a support pin **24** to be able to turn. At one end of the clamp arm **23**, a hold down part **23a** extending up to the surface of the conveyor plate **20** is formed. At the other end of the clamp arm **23**, a roller **26** is attached. The clamp arm **23** is constantly biased clockwise by the spring force of a compression spring **29** attached between the support plate **28** fixed to the lower plate **20a** and the clamp arm **23**. Note that, at the running path of the mover **12**, a cam able to engage with the roller **26** of the clamp

arm **23** is arranged.

(92) In FIG. **20A**, if the roller **26** is pushed by the cam rightward, the thick part **20c** of the upper plate **20b** engages with the outside end face of the lower plate **20a** and the clamp arm **23** turns counterclockwise such as shown in FIG. **20B** whereby the clamp **19** is released in state. Next, the sheet-shaped electrode **1** is placed on the upper plate **20b**. If, in this state, the roller **26** and the cam are disengaged, the clamp arm **23** is turned clockwise by the spring force of the compression spring **29**. At this time, first, as shown by FIG. **20C**, the sheet-shaped electrode **1** is held down by the clamp arm **23** on the upper plate **20b**. Next, in such a state, at the sheet-shaped electrode **1**, as shown by FIG. **20D**, a force acts trying to make it move leftward in FIG. **20A** together with the upper plate **20b**.

(93) On the other hand, the conveyor plate **20** attached on the mover **12** of the second electrode conveyor device **A2** is also comprised of the lower plate **20a** and the upper plate **20b** as shown in FIG. **20A**, and the clamp **19** such as shown in FIG. **20A** is attached to the outside end part of the upper plate **20b** (in FIG. **19**, end part at right side). That is, the overall structure of the conveyor plate **20** of the first electrode conveyor device **A1** having the clamp **19** and the overall structure of the conveyor plate **20** of the second electrode conveyor device **A2** having the clamp **19** are made symmetric structures about the symmetric axis I-I.

(94) On the other hand, in this second embodiment as well, the planar motor device **B** has a plurality of the movers **40** able to move on the flat surface **51** of the stator **50** in any direction along the flat surface **51** and able to rotate about a perpendicular axis of the flat surface **51** in a state magnetically floating from the flat surface **51**. FIG. **21A** shows a perspective view of a stacked electrode holder **60** attached to the mover **40** in this second embodiment. As will be understood by comparing FIG. **21A** and FIG. **10B**, the stacked electrode holder **60** shown in FIG. **21A** and the stacked electrode holder **60** shown in FIG. **10B** have substantially similar structures. The stacked electrode holder **60** shown in FIG. **21A** and the stacked electrode holder **60** shown in FIG. **10B** differ only in that, in the stacked electrode holder **60** shown in FIG. **21A**, the arm **75** and the roller **76** for driving rotation of the camshaft **73**, and the arm **82** and the roller **83** for driving rotation of the camshaft **80** are arranged on the end plate **85** of the clamp **64** side and that the camshaft **73** and the arm **75** and the camshaft **80** and the arm **82** are linked through link mechanisms.

(95) FIG. **21B** schematically shows one example of a link mechanism linking the camshaft **80** and the arm **82**. In this example, the arm **82** is fixed to one end part of an arm shaft **86** supported inside the end plate **85** to be able to rotate. A link arm **87** fixed to the other end part of the arm shaft **86** and a link arm **88** fixed to the camshaft **80** are linked with each other through a link rod **89**. Therefore, if the arm shaft **86** is made to turn in the arrow direction, the camshaft **80** will be made to turn in the arrow direction. The link mechanism linking the camshaft **73** and the arm **75** also has a structure similar to the link mechanism shown in FIG. **21B**. If the camshaft **73** and the camshaft **80** are made to turn, the clamp **64** is made to operate as shown in FIGS. **11A-C**. Note that, in the stacked electrode holder **60** shown in FIG. **21A**, the turning work of the camshaft **73** and the camshaft **80** is performed the roller **76** and the roller **83** engaging with the cams when the mover **40** is made to move.

(96) In this second embodiment as well, the sheet-shaped electrode **1** is prepared by cutting a long strip shaped electrode sheet **30** having a cross-sectional structure shown in FIG. **2B** or FIG. **2C**, manufactured in advance in a previous process, into a set length by a cutting device **31**. In FIG. **19**, this long strip shaped electrode sheet **30** and the cutting device **31** are schematically shown. In this second embodiment as well, the electrode sheet **30** is continuously sent slightly below the lower horizontal straight parts **10a** of the rails **10** of the first electrode conveyor device **A1** and the second electrode conveyor device **A2**. This electrode sheet **30** is cut to a set length by the cutting device **31**, whereby the sheet-shaped electrode **1** is prepared. In this case, for example, if the front end part of the electrode sheet **30** in the advancing direction advances to the front beyond the cutting device **31**, the movers **12** of the conveyor device **A1** and the movers **12** of the second electrode conveyor

device A2 are controlled in running in synchronization with the movement of the front end part of the electrode sheet 30 in the advancing direction so that the position of the front end part of the electrode sheet 30 in the advancing direction is maintained at a position able to be held by the clamps 19. Note that, at this time, the movers 12 of the conveyor device A1 and the movers 12 of the second electrode conveyor device A2 are made to run in a parallel state.

(97) That is, the movers 12 of the conveyor device A1 and the movers 12 of the second electrode conveyor device A2 descend over the semicircular parts 10b of the rails 10 of the first electrode conveyor device A1 and the second electrode conveyor device A2 in the state with the clamps 19 rendered the release positions such as shown in FIG. 20B. When the position of the front end part of the electrode sheet 30 in the advancing direction reaches a position able to be held by the clamps 19, the clamps 19 are made to turn up to the sheet electrode holding positions shown in FIG. 20C and the both side parts of the front end part of the electrode sheet 30 in the advancing direction are held by the clamps 19. If the both side parts of the front end part of the electrode sheet 30 in the advancing direction are held by the clamps 19, as shown in FIG. 20D, forces act on the clamps 19 making the clamps 19 move outward by the spring forces of the compression springs 29. As a result, forces are generated at the front end part of the electrode sheet 30 in the advancing direction pulling the electrode sheet 30 in the lateral direction. Due to this, the center part of the front end part of the electrode sheet 30 in the advancing direction is prevented from sagging down.

(98) Next, the both side parts of the electrode sheet 30 somewhat to the rear from the front end part of the electrode sheet 30 in the advancing direction are held by the clamps 19 which follow behind. In this way, the both side parts of the electrode sheet 30 are held by pluralities of clamps 19 moving in the advancing direction separated by equal distances. In the example shown in FIG. 19, the both side parts of the electrode sheet 30 are finally held by the clamps 19 supported by five movers 12 of the first electrode conveyor device A1 and the clamps 19 of five movers 12 of the second electrode conveyor device A2. If the both side parts of the electrode sheet 30 are held by the clamps 19 supported by five movers 12 of the first electrode conveyor device A1 and the clamps 19 of five movers 12 of the second electrode conveyor device A2, the electrode sheet 30 is cut to a length set by the cutting device 31. Due to this, the sheet-shaped electrode 1 is prepared. Therefore, in the example shown in FIG. 19, the both side parts of the prepared sheet-shaped electrode 1 are held by the clamps 19 supported by the five movers 12 of the first electrode conveyor device A1 and the clamps 19 supported by the five movers 12 of the second electrode conveyor device A2.

(99) On the other hand, in this second embodiment, below the first electrode conveyor device A1, the same number of the first movers 40 as the movers 12 used for holding the prepared sheet-shaped electrode 1 are arranged aligned in the conveyance direction, while below the second electrode conveyor device A2, the same number of the second movers 40 as the movers 12 used for holding the prepared sheet-shaped electrode 1 are arranged aligned in the conveyance direction. On these first movers 40 and second movers 40, the stacked electrode holders 60 shown in FIG. 21A are respectively fixed. The new sheet-shaped electrode 1 held by the clamps 19 of the first electrode conveyor device A1 and the clamps 19 of the second electrode conveyor device A2 is stacked on the stacked electrode holders 60 fixed on the first movers 40 and the second movers 40 arranged aligned below the first electrode conveyor device A1 and below the second electrode conveyor device A2. FIG. 19 shows the state where the new sheet-shaped electrode 1 is stacked on the stacked electrode holders 60 fixed on the first movers 40 and the second movers 40.

(100) FIG. 22 shows the state when removing the first electrode conveyor device A1 and the second electrode conveyor device A2 in FIG. 19. As will be understood from FIG. 22, if the new sheet-shaped electrode 1 is stacked on the stacked electrode holders 60, one side of the sheet-shaped electrode 1 is held by the stacked electrode holders 60 on five first movers 40 arranged aligned, while the other side of the sheet-shaped electrode 1 is held by the stacked electrode holders 60 on five second movers 40 arranged aligned. To hold the sheet electrode 1 by the clamps 19 in this way, the movers 40 are arranged so that the clamps 19 are positioned at the outsides.

(101) Next, referring to FIG. 19 and FIG. 22, control of movement of the movers 40 will be explained taking as an example the case where, in the same way as the first embodiment, the long direction axes of the electrode conveyor devices A1 and A2 are made the y-axis directions of the position coordinates on the flat surface 51 of the stator 50 and the short direction axes of the electrode conveyor devices A1 and A2 are made the x-axis directions of the position coordinates on the flat surface 51 of the stator 50. In this case as well, when the new sheet electrode 1 held by the first electrode conveyor device A1 and the second electrode conveyor device A2 is stacked on the stacked electrode holders 60, the first movers 40 and the second movers 40 move in the minus direction of the y-axis.

(102) Now then, in this second embodiment as well, the reference running paths of the first movers 40 and the second movers 40 made the reference on the flat surface 51 of the stator 50 are set in advance by x-y coordinates. In this case, in the second embodiment as well, the reference running paths are set with respect to the centers of the first movers 40 and the second movers 40. The movers 40 are controlled by the control device C so that the centers of the movers 40 move along the reference running paths. In FIG. 22, the plurality of reference running paths are shown by the dash and dot lines.

(103) Referring to FIG. 22, a pair of stacking reference running paths K5 and K6 forming U-shapes and separated by a distance in the x-axis direction and a stacking auxiliary reference running path K7 extending straight between these stacking reference running paths K5 and K6 are illustrated. When performing stacking work for stacking the new sheet-shaped electrode 1 on the stacked electrode holders 60, at the region below the first electrode conveyor device A1, the first movers 40 carrying the stacked electrode holders 60 are made to move along the inside stacking reference running path K5 separated at an equal distance in the y-axis direction and at the region below the second electrode conveyor device A2, the second movers 40 carrying the stacked electrode holders 60 are made to move along the inside stacking reference running path K6 separated at an equal distance in the y-axis direction. In this case, when stacking work is performed, the first movers 40 and the second movers 40 are made to move in synchronization with the new sheet-shaped electrode 1 so that the new sheet-shaped electrode 1 held by the first electrode conveyor device A1 and the second electrode conveyor device A2 continues to face the sheet-shaped electrode stacking positions on the stacked electrode holders 60.

(104) In this second embodiment, the stacking work of sheet-shaped electrodes 1 is, as explained later, performed by making the first movers 40 carrying the stacked electrode holders 60 move back and forth below the first electrode conveyor device A1 in an aligned state along the inside stacking reference running path K5 and by making the second movers 40 carrying the stacked electrode holders 60 move back and forth below the second electrode conveyor device A2 in an aligned state along the inside stacking reference running path K6. If the stacking work of a preset number of new sheet-shaped electrodes 1 is completed, the first movers 40 and the second movers 40 carrying the stacked electrode holders 60 holding the preset number of stacked sheet-shaped electrodes 1 are ejected from the region below the first electrode conveyor device A1 and the second electrode conveyor device A2 along the respective inside stacking reference running paths K5 and K6 and the next process is proceeded to. At the next process, for example, single side surface parts of the pressed stacked sheet-shaped electrodes 1 are bonded by a resin, then an electrolyte solution or gel polymer electrolyte is injected from the peripheral parts of the stacked sheet-shaped electrodes 1 not bonded by the resin into the positive electrode active substance layer 3, separator 4, and electrode active substance layer 5. Next, after other processes, the stack of the sheet-shaped electrodes 1 is prepared.

(105) If the stack of the sheet-shaped electrodes 1 is prepared, the stack of the sheet-shaped electrodes 1 is taken out from the stacked electrode holders 60. The movers 40 carrying the emptied stacked electrode holders 60 are made to move to the standby region Q along the outside stacking reference running paths K5 and K6. On the other hand, if the stacking work of the preset

number of the new sheet-shaped electrodes **1** is completed and the movers **40** carrying the stacked electrode holders **60** holding the preset number of stacked sheet-shaped electrodes **1** are ejected from the region below the first electrode conveyor device **A1** and the second electrode conveyor device **A2**, as shown in FIG. **19**, the movers **40** carrying the empty stacked electrode holders **60** standing by at the standby region **Q** are made to move to the region below the first electrode conveyor device **A1** and the second electrode conveyor device **A2** for performing the stacking work of the sheet-shaped electrodes **1**.

(106) On the other hand, in this second embodiment, as shown in FIG. **22**, to keep the sheet-shaped electrode **1** from sagging, a plurality of support bases **90** supporting the sheet-shaped electrode **1** from below are provided between the first movers **40** and the second movers **40**. These support bases **90** are carried on movers **40**. The movers **40** carrying the support bases **90** are made to move in synchronization with movement of the sheet-shaped electrode **1** along the stacking auxiliary reference running path **K7**. The movers **40** carrying the support bases **90** will be referred to as “support movers **40**”.

(107) Next, referring to FIG. **23A**, the method of preventing sagging of the sheet-shaped electrode performed in the second embodiment so as to further keep the sheet-shaped electrode **1** from sagging down will be explained. FIG. **23A** shows a perspective view similar to FIG. **22**. Note that, in the following explanation, in accordance with need, as shown in FIG. **23A**, the first movers **40** arranged aligned below the first electrode conveyor device **A1** will be referred to as the “mover A.sub.1”, “mover A.sub.2”, “mover A.sub.3”, “mover A.sub.4”, and “mover A.sub.5”, in order from the front end part of the sheet-shaped electrode **1** in the conveyance direction, that is, the front end part of the sheet-shaped electrode **1** in the moving forward direction at the time of stacking work, while the second movers **40** arranged aligned below the second electrode conveyor device **A2** will be referred to as the “mover B.sub.1”, “mover B.sub.2”, “mover B.sub.3”, “mover B.sub.4”, and “mover B.sub.5” in order from the front end part of the sheet electrode **1** in the conveyance direction, that is, the front end part of the sheet electrode **1** in the moving forward direction at the time of stacking work.

(108) If referred to in this way, as denoted in FIG. **23A**, in the clamping forces of the sheet-shaped electrode **1** by the clamps **64** of the stacked electrode holders **60** carried on the movers A.sub.1, A.sub.2, A.sub.3, A.sub.4, A.sub.5, B.sub.1, B.sub.2, B.sub.3, B.sub.4, and B.sub.5, the clamping force at the mover A.sub.1 or the mover B.sub.1 at the front end part of the sheet-shaped electrode **1** in the conveyance direction is made the maximum. Note that, in this case, in the example shown in FIG. **23A**, the clamping force at the mover B.sub.1 at the front end part of the sheet electrode **1** in the conveyance direction is made the maximum. Further, in this case, in the example shown in FIG. **23A**, among the second movers **40**, the clamping forces of the other mover B.sub.2, mover B.sub.3, mover B.sub.4, mover B.sub.5 besides the mover B.sub.1 are made lower than the maximum clamping force, and the clamping forces of the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, and mover A.sub.5 are made further lower. Note that, the clamping forces of the movers are adjusted by adjusting the spring forces of the springs which the pantograph type elevator mechanisms **62** are provided with for pushing the bottom plates **63** upward in the stacked electrode holders **60**.

(109) Further, the arrow marks “f” in FIG. **23A** show the directions in which the other mover B.sub.2, mover B.sub.3, mover B.sub.4, mover B.sub.5 besides the mover B.sub.1 and mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, and mover A.sub.5 are made to move slightly from the reference positions set on the inside stacking reference running paths **K5** and **K6** to apply tension to the sheet-shaped electrode **1** and thereby prevent the sheet electrode **1** from sagging down. At this time, the adjusted amounts of movement in the x-axis and y-axis directions from the reference positions required for keeping the sheet electrode **1** from sagging down are preset for the other mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 besides the mover B.sub.1 and mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, and mover

A.sub.5.

(110) In this way, it is possible to prevent the sheet-shaped electrode **1** from sagging down by making the clamping force of the second mover **40** positioned at the front end part in the conveyance direction the maximum among the second movers **40**, by making the clamping force of the remaining second movers **40** lower than the maximum clamping force, by making the clamping force of the first movers **40** further lower, and by controlling the movement positions of the first movers **40** and the second movers **40** to positions necessary for keeping the sheet-shaped electrode **1** from sagging down.

(111) Next, referring to FIG. 23B, moving cam devices for making cams engage with the rollers **76** and **83** for driving the camshafts **73** and **80** of the stacked electrode holders **60** carried on the first movers **40** and the second movers **40** and for making cams engage with the rollers **26** of the clamps **19** attached to the conveyor plates **20** of the first electrode conveyor device A1 and the second electrode conveyor device A2 will be explained. Note that, FIG. 23B shows a perspective view similar to FIG. 22. In this second embodiment, the moving cam devices **91** are comprised of the cam movers **40** provided with cams **92**. In the example shown in FIG. 23B, two moving cam devices **91** are provided. In FIG. 23B, a pair of loop-shaped cam reference paths K8 and K9 for these moving cam devices **91** are shown. The inside path of the cam reference running path K8 extends straight along the outside of the first movers **40** in FIG. 23B so that the cam **92** engages with the rollers **76** and **83** of the stacked electrode holders **60** carried on the first movers **40** and the rollers **26** of the clamps **19** attached to the conveyor plates **20** of the first electrode conveyor device A1. The inside path of the cam reference running path K9 extends straight along the outside of the second movers **40** in FIG. 23B so that the cam **92** engages with the rollers **76** and **83** of the stacked electrode holders **60** carried on the second movers **40** and the rollers **26** of the clamps **19** attached to the conveyor plates **20** of the second electrode conveyor device A2. On the other hand, the outside paths of the cam reference running paths K8 and K9 are return paths of the moving cam devices **91** for preventing engagement with these rollers **76**, **83**, and **26**.

(112) In this second embodiment as well, x-y coordinates of every constant time on the stacking reference running paths K5 and K6, stacking auxiliary reference running path K7, and cam reference running paths K8 and K9 corresponding to movement requests of the movers **40** are set as the target planar positions of the movers **40**, while rotational angle positions of the movers **40** with respect to the x-axis of the x-y coordinates are set as target rotational angle positions. In this case, in this second embodiment as well, the amounts of current supplied to the coils **54A**, **54B**, and **54C** in the coil layers **53A**, **53B**, **53C**, and **53D** of the stator **50** are controlled by the control device C so that every constant time interval, the movers **40** are held at the target planar positions at the target rotational angle positions.

(113) FIGS. 24A-H is a view for explaining the stacking work of the sheet-shaped electrode **1** in the second embodiment. In FIGS. 24A-H, the conveyor plates **20** of the electrode conveyor device A1 and electrode conveyor device A2, the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 shown in FIG. 23A, the moving cam devices **91**, the cutting device **31**, the long strip shaped electrode sheet **30**, and the sheet-shaped electrode **1** are schematically shown. Note that, when the electrode sheet **30** or the sheet-shaped electrode **1** is held on the conveyor plates **20** by the clamps **19**, in FIGS. 24A-H, the electrode sheet **30** or the sheet-shaped electrode **1** is shown as if contacting the conveyor plates **20**, while when the sheet-shaped electrode **1** is held on the stacked electrode holders **60** fixed on the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 by the clamps **64**, in FIGS. 24A-H, the sheet-shaped electrode **1** is shown as being carried on the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5.

(114) FIG. 24A shows the time of start of the stacking work of the sheet-shaped electrode **1**. At this

time, the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 are stopped at the stacking start positions, while the moving cam devices **91** are stopped at the standby positions. If an electrode sheet **30** is sent in the conveyance direction, the electrode sheet **30** is successively held by clamps **19** on the conveyor plates **20** separated by equal distances in the conveyance direction. If a preset length of the electrode sheet **30** passes through the cutting device **31**, the electrode sheet **30** is cut by the cutting device **31**. Due to this, the sheet-shaped electrode **1** is produced. Next, as shown in FIG. **24B**, the plurality of the conveyor plates **20** holding the produced sheet-shaped electrode **1** are moved to positions aligned with the respectively corresponding movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.1 and B.sub.5 in the perpendicular direction.

(115) Next, as shown in FIGS. **24B-E**, the plurality of the conveyor plates **20** holding the sheet-shaped electrode **1** move in the conveyance direction separated by equal distances. At this time, the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 are aligned with the corresponding conveyor plates **20** in the perpendicular direction while making them move in synchronization with movement of the conveyor plates **20**. That is, the first movers **40** and the second movers **40** are made to move in synchronization with movement of the sheet-shaped electrode **1** so that the sheet-shaped electrode **1** continues to face the sheet-shaped electrode stacking positions on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40**. During this time, the moving cam devices **91** are made to move in the opposite direction from the conveyance direction, and the sheet-shaped electrode **1** is transferred between the mover **40** which the moving cam device **91** reaches and the conveyor plate **20** aligned in the vertical direction from this mover **40**.

(116) In this case, the transfer of the sheet-shaped electrode **1** from the conveyor plates **20** to the corresponding stacked electrode holders **60** is performed in the following way. That is, first, the holding actions of the sheet-shaped electrode **1** by the clamps **19** of the conveyor plates **20** are released by the moving cam devices **91** and the clamps **64** of the stacked electrode holders **60** carried by the movers **40** aligned with the conveyor plates **20** in the perpendicular direction are made to move by the moving cam devices **91** to the release positions. At this time, the part of the sheet-shaped electrode **1** which had been held by the clamps **19** drops onto the stacked electrode holders **60** carried by the movers **40**. If the part of the sheet-shaped electrode **1** held by the clamps **19** drops onto the stacked electrode holders **60** carried by the movers **40**, the clamps **64** of the stacked electrode holders **60** are turned on the dropped sheet-shaped electrode **1** and the dropped sheet-shaped electrode **1** is held by the clamps **64** on the stacked electrode holders **60**.

(117) Such work of transfer of the sheet-shaped electrode **1** is performed in order each time the moving cam devices **91** reach the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5. That is, first, transfer work of the sheet-shaped electrode **1** from the conveyor plates **20** aligned with the movers A.sub.1 and B.sub.1 to the stacked electrode holders **60** of the movers A.sub.1 and B.sub.1 is performed, next, transfer work of the sheet-shaped electrode **1** from the conveyor plates **20** aligned with the movers A.sub.2 and B.sub.2 to the stacked electrode holders **60** of the movers A.sub.2 and B.sub.2 is performed, next, transfer work of the sheet-shaped electrode **1** from the conveyor plates **20** aligned with the movers A.sub.3 and B.sub.3 to the stacked electrode holders **60** of the movers A.sub.3 and B.sub.3 is performed, next, transfer work of the sheet-shaped electrode **1** from the conveyor plates **20** aligned with the movers A.sub.4 and B.sub.4 to the stacked electrode holders **60** of the movers A.sub.4 and B.sub.4 is performed, and, next, transfer work of the sheet-shaped electrode **1** from the conveyor plates **20** aligned with the movers A.sub.5 and B.sub.5 to the stacked electrode holders **60** of the movers A.sub.5 and B.sub.5 is performed. While such transfer work of the sheet-shaped electrode **1** is being performed as well, the electrode sheet **30** continues to

be supplied in the conveyance direction and is held by the clamps **19** of the successively moving conveyor plates **20** on the conveyor plates **20** separated by equal distances.

(118) FIG. **24E** shows when the sheet-shaped electrode **1** which had been held by the conveyor plates **20** is transferred overall to the stacked electrode holders **60** of the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5. If the sheet-shaped electrode **1** which had been held by the conveyor plates **20** is transferred overall to the stacked electrode holders **60** of the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5, to enable the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 holding the sheet-shaped electrode **1** on the stacked electrode holders **60** to stack a new sheet-shaped electrode **1** on the held sheet-shaped electrodes **1**, as shown by FIGS. **24E-H**, they are returned to the stacking start positions shown at FIG. **24A** in the opposite direction to the conveyance direction, At this time, the moving cam devices **91** are returned to the standby positions.

(119) In this way, in the second embodiment, the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 are made to move back and forth to perform the stacking work of the sheet-shaped electrodes **1**. In this case, if using the moving cam devices **91** as the cams for engaging with the rollers **76** and **83** of the stacked electrode holders **60** and the rollers **26** of the clamps attached to the conveyor plates **20**, compared with when using fixed cams, the distances over which the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 have to return become shorter and therefore the time required for the stacking work of the sheet-shaped electrodes **1** can be made shorter. Further, in this second embodiment as well, the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 are adjusted in position based on images captured by the camera **33**.

(120) FIG. **25** shows the mover control routine for controlling the movers **40** in the second embodiment. Due to this mover control routine, control of movement of all of the movers **40** present in the electrode stacking apparatus is repeatedly performed for every mover **40**.

(121) Referring to FIG. **25**, at step **200**, it is judged if it is the time for start of stacking processing for stacking a new sheet-shaped electrode **1** carried on the conveyor plates **20** on stacked electrode holders **60** carried on the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5. When it is judged it is the time for start of stacking processing for stacking at stacked electrode holders **60** carried on the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5, the routine proceeds to step **201** where the movers **40** carrying empty stacked electrode holders **60** are made to move from the standby positions to the stacking start positions. In this case, in the second embodiment, five pairs of the movers **40** carrying empty stacked electrode holders **60** are made to move from the standby positions to the stacking start positions. The movers **40** at this time are, in FIG. **24A**, shown by the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5.

(122) Next, at step **202**, the other movers **40** carrying empty stacked electrode holders **60** are made to move to the standby positions. Next, at step **203**, stacking processing is performed for stacking a new sheet-shaped electrode **1** held on the conveyor plates **20** on the stacked electrode holders **60** carried on the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5. On the other hand, when at step **200** it is judged that it is not the time for start of the stacking processing of the sheet electrode **1**, the routine jumps to step **203** where the stacking processing of the sheet electrode **1** is

performed. This stacking processing is performed by the stacking processing routine shown in FIG. 16 and FIG. 27.

(123) Next, at step 204, it is judged if the stacking processing of the sheet electrode 1 has been completed. When it is judged that the stacking processing of the sheet electrode 1 has been completed, the routine proceeds to step 205 where ejection processing is performed for making the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 advance to the next process. Next, at step 204, the next stacking processing of a new sheet-shaped electrode 1 is started.

(124) On the other hand, in the second embodiment as well, the position deviation detection routine shown in FIG. 17 is used. If, based on the images captured by the camera 33, it is judged that the new sheet-shaped electrode 1 on the conveyor plates 20 deviates from the regular holding position R, the correction values Δx , Δy , and α used for correction of the set positions of the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 are calculated. Next, these correction values Δx , Δy , and α are stored in the control device C, and the correction request is made showing that the set positions of the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 should be corrected.

(125) FIG. 26 and FIG. 27 show a stacking processing routine performed at step 203 of the mover control routine shown in FIG. 25. This mover control routine is repeatedly performed.

(126) Referring to FIG. 26 and FIG. 27, at step 220, it is judged if a return processing for returning the movers A.sub.1 and B.sub.1, movers A.sub.2 and B.sub.2, movers A.sub.3 and B.sub.3, movers A.sub.4 and B.sub.4, and movers A.sub.5 and B.sub.5 to the stacking start positions shown in FIG. 24A in an opposite direction to the conveyance direction as shown in FIGS. 24E-H to stack a new sheet-shaped electrode 1 on the held sheet-shaped electrodes 1, is being performed. When it is judged that the return processing is not being performed, the routine proceeds to step 221 where the values of the x-y coordinates of the next reference positions on the stacking reference running path K5 for the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, and mover A.sub.5 being controlled are calculated and the values of the x-y coordinates of the next reference positions on the stacking reference running path K6 for the mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 being controlled are calculated.

(127) Next, at step 222, it is judged if the correction request has been made in the position deviation detection routine shown in FIG. 17. When it is judged that the correction request has been made, the routine proceeds to step 223 where the correction values Δx , Δy , and α stored in the control device C are read. Next, at step 224, among the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5, the electrode holding movers holding the sheet-shaped electrode by the clamps 64 of the stacked electrode holders 60 are extracted. Next, at step 225, to keep the sheet-shaped electrode 1 from sagging down, among the adjusted amounts of movement in the x-axis and y-axis directions set in advance for the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5, the adjusted amounts of movement in the x-axis and y-axis directions of the electrode holding movers extracted at step 224 are read.

(128) Next, at step 226, the values of the x-y coordinates of the changed set positions of the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 for holding an electrode are calculated based on the correction values Δx , Δy , and α and the adjusted amounts of movement in the x-axis and y-axis directions. At this time, for example, by adding the adjusted amount of movement in the x-axis direction to the correction value Δx , the value of the x-coordinate of the changed set position is calculated, while by adding the adjusted amount of movement in the y-axis direction to the correction value Δy , the value of the y-coordinate of the changed set position is calculated. Next, at

step 227, the values of the x-y coordinates of the next reference positions on the cam-use reference running paths K8 and K9 for the pair of the cam movers 40 and the values of the x-y coordinates of the next reference positions on the auxiliary stacking-use reference running path K7 for the support movers 40 are calculated.

(129) Next, at step 228, control of movement of the movers 40 is performed. At this time, for the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 for holding an electrode, the amounts of current supplied to the coils 54A, 54B, and 54C in the coil layers 53A, 53B, 53C, and 53D of the stator 50 are controlled by the control device C so that the movement positions of the movers 40 respectively become the changed set positions, while for the cam movers 40 and support movers 40, the amounts of current supplied to the coils 54A, 54B, and 54C in the coil layers 53A, 53B, 53C, and 53D of the stator 50 are controlled by the control device C so that the movement positions of the movers 40 respectively become the set reference positions. Note that, in this case, it is possible to change the set positions of the cam movers 40 from the reference positions based on the above-mentioned correction values Δx , Δy , and a and the adjusted amounts of movement in the x-axis and y-axis directions and make the cam movers 40 move along the changed set positions.

(130) Next, at step 229, the routine waits until a preset constant time has elapsed. If the constant time has elapsed, the routine proceeds to step 230 where it is judged if the stacking work of one new sheet-shaped electrode 1 has ended. When it is judged that the stacking work of one new sheet-shaped electrode 1 has not ended, the routine returns to step 220 where control of movement of the movers 40 is continued. Next, when at step 230 it is judged that the stacking work of one new sheet-shaped electrode 1 has ended, the routine proceeds to step 231 where it is judged if the stacking work of the set total number of new sheet-shaped electrodes 1 has ended. When it is judged that the stacking work of the set total number of new sheet-shaped electrodes 1 has not ended, the routine proceeds to step 232 where the return processing is started. On the other hand, when it is judged that the stacking work of the set total number of new sheet-shaped electrodes 1 has ended, at step 233, the stacking work of the sheet-shaped electrodes 1 is completed.

(131) If the return processing is performed, the routine proceeds from step 220 to step 234 where the values of the x-y coordinates of the next set positions of the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 for holding an electrode, the cam movers 40, and the support movers 40 at the time of the return processing are calculated. Next, at step 235, the amounts of current supplied to the coils 54A, 54B, and 54C in the coil layers 53A, 53B, 53C, and 53D of the stator 50 are controlled by the control device C so that the movement positions of the movers 40 respectively become the set positions.

(132) Next, at step 236, the routine waits until a preset constant time elapses. If the constant time elapses, the routine proceeds to step 237 where it is judged if all of the mover A.sub.1, mover A.sub.2, mover A.sub.3, mover A.sub.4, mover A.sub.5, mover B.sub.1, mover B.sub.2, mover B.sub.3, mover B.sub.4, and mover B.sub.5 for holding an electrode have returned to the stacking start positions. When it is judged that not all of the movers for holding an electrode have returned to the stacking start positions, the routine returns to step 234. As opposed to this, when it is judged that all of the movers for holding an electrode have returned to the stacking start positions, the routine proceeds to step 238 where movement of all of the movers for holding an electrode is stopped. Next, at step 239, the return processing is ended. If the return processing is ended, the next stacking work is started.

(133) In this way, in the second embodiment according to the present invention as well, the electrode stacking apparatus for stacking the sheet-shaped electrode 1 comprises the planar motor device B comprised of the flat plate shaped stator 50 and a plurality of the movers 40 able to move on the flat surface 51 of the stator 50 in any direction along the flat surface 51 and able to rotate about a perpendicular axis of the flat surface 51 in a state magnetically floating from the flat

surface **51**, the electrode conveyor devices **A1** and **A2** arranged above the planar motor device **B** and conveying the sheet-shaped electrode **1** along a conveyance path while holding the sheet-shaped electrode **1**, and the control device **C** for controlling the planar motor device **B** and the electrode conveyor devices **A1** and **A2**. The stacked electrode holders **60** for holding the stacked sheet-shaped electrode **1** is attached on each mover **40** of the planar motor device **B** so that the successively stacked sheet-shaped electrode **1** is held by the stacked electrode holders **60** at the sheet-shaped electrode stacking positions on the stacked electrode holders **60**. When the stacking the new sheet-shaped electrode **1** held by the electrode conveyor devices **A1** and **A2** on the stacked electrode holders **60** of the movers **40**, the control device **C** makes the movers **40** move in synchronization with movement of the new sheet-shaped electrode **1** so that the new sheet-shaped electrode **1** continues to face the sheet-shaped electrode stacking positions on the stacked electrode holders **60**.

(134) In this case, in this second embodiment, the electrode conveyor device is comprised of the first electrode conveyor device **A1** and the second electrode conveyor device **A2** arranged separated by a distance from each other at the both sides in the conveyance direction. The both end parts of the new sheet-shaped electrode **1** positioned at the both sides in the conveyance direction are respectively held by the first electrode conveyor device **A1** and the second electrode conveyor device **A2**. Below the first electrode conveyor device **A1**, a plurality of the first movers **40** of the planar motor device **B** are arranged aligned in the conveyance direction so as to hold one end part of the sheet-shaped electrode **1** while a plurality of the second movers **40** of the planar motor device **B** are arranged aligned in the conveyance direction so as to hold the other end part of the sheet-shaped electrode **1**. The successively stacked sheet-shaped electrode **1** is held by the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** at the sheet-shaped electrode stacking positions of the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40**. When stacking the new sheet-shaped electrode **1** held by the first electrode conveyor device **A1** and the second electrode conveyor device **A2** on the stacked electrode holders **60** of the first movers **40** and stacked electrode holders **60** of the second movers **40**, the control device **C** makes the first movers **40** and the second movers **40** move in synchronization with the movement of the new sheet-shaped electrode **1** so that the new sheet-shaped electrode **1** continues to face the sheet-shaped electrode stacking positions on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40**.

(135) Further, in this second embodiment, if the stacking work of the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** ends, the control device **C** returns the first movers **40** and the second movers **40** to the stacking start positions in the opposite direction from the conveyance direction so as to stack a next new sheet-shaped electrode **1** on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40**. Further, in this second embodiment, support movers **40** provided with support bases for supporting the sheet-shaped electrode **1** held by the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** from below between the first movers **40** and the second movers **40** are provided. The control device **C** makes the support movers **40** move in synchronization with movement of the sheet-shaped electrode **1** stacked on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** at the time of stacking.

(136) Further, in this second embodiment, the first electrode conveyor device **A1** and the second electrode conveyor device **A2** are comprised of linear motors having pluralities of movers **12** made to move along the conveyance paths. Each mover **12** of the linear motors are provided with clamps **19** for holding the new sheet-shaped electrode **1**, while the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** of the planar motor device **B** are provided with clamps **64**. When the first movers **40** and the second movers **40** of the planar

motor device B are made to move in synchronization with movement of the new sheet-shaped electrode, the holding actions of the sheet-shaped electrode **1** by the clamps **19** of the movers **12** of the linear motor are released in order from the movers **12** of the linear motors positioned in the front in the conveyance direction and the holding actions of the sheet-shaped electrode **1** by the clamps **64** of the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** corresponding to the movers **12** of the linear motors are initiated, thereby the new sheet-shaped electrode **1** is stacked on the stacked electrode holders **60** of the first movers **40** and on the stacked electrode holders **60** of the second movers **40**.

(137) Furthermore, in the second embodiment, the first electrode conveyor device A1 and the second electrode conveyor device A2 are provided with clamps **19** for holding the sheet-shaped electrode **1** and the stacked electrode holders **60** of the first movers **40** and the second movers **40** are provided with clamps **64** for holding the sheet-shaped electrode **1**. The holding actions of the sheet-shaped electrode **1** by these clamps **19** and **64** are initiated by cams and released by cams. The control device C makes the cam movers **40** provided with the cams **92** which engage with these clamps **19** and **64** move in an opposite direction to the conveyance direction when stacking work of the new sheet-shaped electrode **1** on the stacked electrode holders **60** of the first movers **40** and the stacked electrode holders **60** of the second movers **40** is performed. Further, in the second embodiment, the clamps **19** which the movers **12** of the linear motors are provided with cause tension at the new sheet-shaped electrode **1** when holding the new sheet-shaped electrode **1** so as to keep the new sheet-shaped electrode **1** from sagging down.

(138) Further, in this second embodiment, as the holding position of the new sheet-shaped electrode **1** by the first electrode conveyor device A1 and the second electrode conveyor device A2, the regular holding position R required for making the new sheet-shaped electrode **1** align with the sheet-shaped electrode stacking position on the stacked electrode holders **60** is set in advance. A deviation detection device is provided for detecting the amounts of deviation of the holding position of the new sheet-shaped electrode **1** with respect to the regular holding position R. The control device C controls the movement positions and rotational angle positions of the first movers **40** and the second movers **40** based on the amounts of deviation so that the new sheet-shaped electrode **1** is stacked on the stacked electrode holders **60** aligned with the sheet-shaped electrode stacking position on the stacked electrode holders **60**. In this case, the deviation detection device is provided with a camera **33** for capturing the new sheet-shaped electrode **1** held by the electrode conveyor devices A1 and A2, and the amounts of deviation are detected by images captured by the camera **33**.

(139) Further, in this second embodiment, the stacked electrode holders **60** of the first movers **40** and the second movers **40** are provided with the clamps **64**, and the sheet-shaped electrode **1** is held by the clamps **64** of the stacked electrode holders **60** of the first movers **40** and the clamps **64** of the stacked electrode holders **60** of the second movers **40**. The control device C controls the movement positions of the first movers **40** and the second movers **40** to positions required for keeping the sheet-shaped electrode **1** from sagging down. In this case, the clamping force of the first mover **40** positioned at the front end part in the conveyance direction among the first movers **40** is made the maximum, the clamping forces of the remaining first movers **40** are made lower than the maximum clamping force, and the clamping forces of the second movers **40** are made further lower.

Claims

1. An electrode stacking apparatus for stacking a sheet-shaped electrode, comprising: a planar motor device comprised of a flat plate shaped stator and a plurality of movers able to move on a flat surface of the stator in any direction along the flat surface and able to rotate about a perpendicular axis of the flat surface in a state magnetically floating from the flat surface, an electrode conveyor device arranged above the planar motor device and conveying the sheet-shaped

electrode along a conveyance path while holding the sheet-shaped electrode, and a control device for controlling the planar motor device and the electrode conveyor device, wherein a stacked electrode holder for holding stacked sheet-shaped electrodes being attached on each mover of the planar motor device and a successively stacked sheet-shaped electrode being held at a sheet-shaped electrode stacking position on the stacked electrode holder by the stacked electrode holder, when stacking a new sheet-shaped electrode held by the electrode conveyor device on the stacked electrode holder of the mover, said control device making the mover move in synchronization with movement of the new sheet-shaped electrode so that the new sheet-shaped electrode continues to face the sheet-shaped electrode stacking position on the stacked electrode holder.

2. The electrode stacking apparatus according to claim 1, wherein as a holding position of the new sheet-shaped electrode by the electrode conveyor device, a regular holding position required for making the new sheet-shaped electrode align with the sheet-shaped electrode stacking position on the stacked electrode holder is set in advance, a deviation detection device is provided for detecting an amount of deviation of the holding position of the new sheet-shaped electrode from the regular holding position, and said control device controls a movement position and rotational angle position of each mover based on the amount of deviation so that the new sheet-shaped electrode is stacked on the stacked electrode holder aligned with the sheet-shaped electrode stacking position on the stacked electrode holder.

3. The electrode stacking apparatus according to claim 2, wherein the deviation detection device is provided with a camera for capturing the new sheet-shaped electrode held by the electrode conveyor device, and the amount of deviation is detected based on images captured by the camera.

4. The electrode stacking apparatus according to claim 1, wherein the electrode conveyor device is comprised of a linear motor having a plurality of movers made to move along the conveyance path, and the new sheet-shaped electrode is held by clamps on a conveyor plate attached to the mover of the linear motor.

5. The electrode stacking apparatus according to claim 4, wherein the stacked electrode holders of the movers of the planar motor device are provided with clamps, when the movers of the planar motor device are made to move in synchronization with movement of the new sheet-shaped electrode, the new sheet-shaped electrode held on the conveyor plate being stacked on the stacked electrode holder while being held at a peripheral part of the new sheet-shaped electrode by either clamps of the clamps of the conveyor plate and the clamps of the stacked electrode holders.

6. The electrode stacking apparatus according to claim 1, wherein the sheet-shaped electrode is held by a plurality of the movers of the planar motor device.

7. The electrode stacking apparatus according to claim 1, wherein said control device controls a movement position and rotational angle position of the mover of the planar motor device holding the sheet-shaped electrode so that the mover does not rotate when making the mover move along a curved running path.

8. The electrode stacking apparatus according to claim 1, wherein the electrode conveyor device is comprised of a first electrode conveyor device and a second electrode conveyor device arranged separated by a distance from each other at both sides in a conveyance direction, both end parts of the new sheet-shaped electrode positioned at the both sides in the conveyance direction are respectively held by the first electrode conveyor device and the second electrode conveyor device, a plurality of first movers of the planar motor device are arranged aligned in the conveyance direction below the first electrode conveyor device so as to each hold one end part of the new sheet-shaped electrode, a plurality of second movers of the planar motor device are arranged aligned in the conveyance direction below the second electrode conveyor device so as to each hold the other end part of the new sheet-shaped electrode, successively stacked sheet-shaped electrodes are held at the sheet-shaped electrode stacking positions on the stacked electrode holders of the first movers and on the stacked electrode holders of the second movers by the stacked electrode holders of the first movers and the stacked electrode holders of the second movers, and said control device

makes the first movers and the second movers move in synchronization with movement of the new sheet-shaped electrode so that, when stacking the new sheet-shaped electrode held by the first electrode conveyor device and the second electrode conveyor device on the stacked electrode holder of the first mover and on the stacked electrode holder of the second mover, the new sheet-shaped electrode continues to face the sheet-shaped electrode stacking positions on the stacked electrode holder of the first mover and on the stacked electrode holder of the second mover.

9. The electrode stacking apparatus according to claim 8, wherein when stacking work of the new sheet-shaped electrode on the stacked electrode holder of the first mover and the stacked electrode holder of the second mover ends, said control device returns the first mover and the second mover to stacking start positions in a direction opposite to the conveyance direction so as to stack a next new sheet-shaped electrode on the stacked electrode holder of the first mover and the stacked electrode holder of the second mover.

10. The electrode stacking apparatus according to claim 8, wherein a support mover provided with a support base for supporting the sheet-shaped electrode held by the stacked electrode holder of the first mover and the stacked electrode holder of the second mover from below between the first mover and the second mover is provided, and said control device makes the support mover move in synchronization with movement of the sheet-shaped electrode stacked on the stacked electrode holder of the first mover and the stacked electrode holder of the second mover at the time of stacking.

11. The electrode stacking apparatus according to claim 8, wherein the first electrode conveyor device and the second electrode conveyor device are comprised of linear motor having pluralities of movers made to move along conveyance paths, each mover of the linear motor is provided with clamps for holding the new sheet-shaped electrode, the stacked electrode holders of the first movers and the stacked electrode holders of the second movers of the planar motor device are provided with clamps, and, when the first movers and the second movers of the planar motor device are made to move in synchronization with movement of the new sheet-shaped electrode, holding actions of the sheet-shaped electrode by the clamps of the movers of the linear motor are released in order from the movers of the linear motor positioned at a front in the conveyance direction and holding actions of the sheet-shaped electrode by the clamps of the stacked electrode holders of the first movers and the stacked electrode holders of the second movers corresponding to the movers of the linear motor are initiated, whereby the new sheet-shaped electrode is stacked on the stacked electrode holder of the first mover and the stacked electrode holder of the second mover.

12. The electrode stacking apparatus according to claim 8, wherein the first electrode conveyor device and the second electrode conveyor device are provided with clamps for holding the sheet-shaped electrode, the stacked electrode holders of the first movers and the second movers are provided with clamps for holding the sheet-shaped electrode, the holding actions of the sheet-shaped electrode by these clamps are initiated by cams and released by cams, and, said control device makes cam movers provided with the cams which engage with these clamps move in a direction opposite to the conveyance direction when stacking work of the new sheet-shaped electrode on the stacked electrode holder of the first mover and the stacked electrode holder of the second mover is performed.

13. The electrode stacking apparatus according to claim 8, wherein: the electrode conveyor device is comprised of a linear motor having a plurality of movers made to move along the conveyance path, and the new sheet-shaped electrode is held by clamps on a conveyor plate attached to the mover of the linear motor; and the clamps which the movers of the linear motor are provided with cause tension at the new sheet-shaped electrode when holding the new sheet-shaped electrode so as to keep the new sheet-shaped electrode from sagging down.

14. The electrode stacking apparatus according to claim 8, wherein as a holding position of the new sheet-shaped electrode by the first electrode conveyor device and the second electrode conveyor

device, a regular holding position required for making the new sheet-shaped electrode align with the sheet-shaped electrode stacking position on the stacked electrode holders is set in advance, a deviation detection device is provided for detecting amounts of deviation of the holding position of the new sheet-shaped electrode from the regular holding position, and said control device controls the movement positions and the rotational angle positions of the first mover and the second mover based on the amounts of deviation so that the new sheet-shaped electrode is stacked on the stacked electrode holders aligned with the sheet-shaped electrode stacking position on the stacked electrode holders.

15. The electrode stacking apparatus according to claim 14, wherein the deviation detection device is provided with a camera for capturing the new sheet-shaped electrode held by the electrode conveyor devices, and the amounts of deviation are detected based on images captured by the camera.

16. The electrode stacking apparatus according to claim 8, wherein the stacked electrode holders of the first movers and the second movers are provided with clamps, the sheet-shaped electrode is held by the clamps of the stacked electrode holders of the first movers and the clamps of the stacked electrode holders of the second movers, and said control device controls the movement positions of the first movers and the second movers to positions required for keeping the sheet-shaped electrode from sagging down.

17. The electrode stacking apparatus according to claim 16, wherein clamping force of the first mover positioned at a front end part in the conveyance direction among the first movers is made the maximum, the clamping forces of the remaining first movers are made lower compared with the maximum clamping force, and the clamping forces of the second movers are made further lower.
