



US012399347B2

(12) **United States Patent**
Hsueh et al.

(10) **Patent No.:** **US 12,399,347 B2**

(45) **Date of Patent:** **Aug. 26, 2025**

(54) **IMAGE CAPTURING OPTICAL LENS ASSEMBLY, IMAGE CAPTURING DEVICE AND ELECTRONIC DEVICE**

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **LARGAN PRECISION CO., LTD.**,
Taichung (TW)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,681,594 A 6/1954 Ito
5,200,861 A 4/1993 Moskovich
(Continued)

(72) Inventors: **Chun-Che Hsueh**, Taichung (TW);
Wei-Yu Chen, Taichung (TW)

(73) Assignee: **LARGAN PRECISION CO., LTD.**,
Taichung (TW)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 99 days.

CN 203882004 U 10/2014
CN 203981955 U 12/2014
(Continued)

(21) Appl. No.: **18/513,806**

Primary Examiner — Darryl J Collins

(22) Filed: **Nov. 20, 2023**

(74) *Attorney, Agent, or Firm* — Troutman Pepper Locke LLP; Tim Tingkang Xia, Esq.

(65) **Prior Publication Data**

US 2024/0085666 A1 Mar. 14, 2024

Related U.S. Application Data

(60) Continuation of application No. 17/569,917, filed on Jan. 6, 2022, now Pat. No. 11,860,448, which is a (Continued)

(30) **Foreign Application Priority Data**

Dec. 5, 2014 (TW) 103142323

(51) **Int. Cl.**

G02B 9/62 (2006.01)

G02B 5/20 (2006.01)

G02B 13/00 (2006.01)


(52) **U.S. Cl.**

CPC **G02B 9/62** (2013.01); **G02B 5/208** (2013.01); **G02B 13/0045** (2013.01)

(57) **ABSTRACT**

This disclosure provides an image capturing optical lens assembly including, in order from an object side to an image side: a first lens element with refractive power having an object-side surface being convex in a paraxial region thereof; a second lens element having positive refractive power; a third lens element with refractive power having an image-side surface being concave in a paraxial region thereof; a fourth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein both surfaces thereof being aspheric; a fifth lens element with refractive power having an object-side surface being concave in a paraxial region thereof and a sixth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein both surfaces thereof being aspheric, and the image-side surface having at least one convex shape in an off-axis region thereof.

25 Claims, 21 Drawing Sheets



Related U.S. Application Data

division of application No. 16/856,148, filed on Apr. 23, 2020, now Pat. No. 11,256,070, which is a continuation of application No. 16/135,167, filed on Sep. 19, 2018, now Pat. No. 10,670,838, which is a continuation of application No. 15/497,385, filed on Apr. 26, 2017, now Pat. No. 10,107,991, which is a continuation of application No. 14/671,426, filed on Mar. 27, 2015, now Pat. No. 9,671,588.

(56)

References Cited**U.S. PATENT DOCUMENTS**

5,475,536	A	12/1995	Kikutani	
6,028,717	A	2/2000	Kohno et al.	
8,310,767	B2	11/2012	Huang et al.	
8,477,431	B2	7/2013	Huang	
8,724,237	B2	5/2014	Hsu et al.	
8,743,483	B2	6/2014	Hsu et al.	
8,908,295	B1	12/2014	Tsai et al.	
9,103,962	B2	8/2015	Liao et al.	
9,170,400	B2	10/2015	Huang	
9,176,300	B2	11/2015	Chen et al.	
9,602,731	B2	3/2017	Lin et al.	
2013/0010375	A1	1/2013	Chen et al.	
2014/0043695	A1	2/2014	Hsu et al.	
2014/0063323	A1	3/2014	Yamazaki et al.	
2014/0185141	A1	7/2014	Lee et al.	
2014/0293458	A1	10/2014	Nabeta	
2014/0347745	A1 *	11/2014	Shinohara	G02B 13/0045 359/713
2014/0376107	A1	12/2014	Son	
2015/0022905	A1	1/2015	Shinohara et al.	
2015/0055229	A1	2/2015	Park et al.	
2015/0070578	A1	3/2015	Chen et al.	
2015/0070579	A1	3/2015	Chen et al.	
2015/0070784	A1	3/2015	Chen et al.	
2015/0098135	A1	4/2015	Chung et al.	
2015/0109684	A1	4/2015	Son	
2015/0177483	A1 *	6/2015	You	G02B 9/62 359/757
2015/0177485	A1	6/2015	Hsu et al.	

2015/0338614	A1 *	11/2015	Tang	G02B 9/62 359/713
2015/0362702	A1	12/2015	Tang et al.	
2015/0362709	A1	12/2015	Wang	
2016/0124185	A1	5/2016	Tang et al.	
2016/0124186	A1 *	5/2016	Tang	G02B 13/0045 359/713
2016/0131870	A1	5/2016	Tang et al.	
2016/0131871	A1	5/2016	Tang et al.	
2016/0131872	A1	5/2016	Tang et al.	
2016/0131873	A1	5/2016	Tang et al.	
2016/0131899	A1 *	5/2016	Jo	G02B 13/0045 359/713
2016/0139366	A1 *	5/2016	Jung	G02B 13/0045 359/713
2016/0147044	A1	5/2016	Kondo	
2016/0161719	A1	6/2016	Son	
2016/0282585	A1	9/2016	Shih et al.	

FOREIGN PATENT DOCUMENTS

CN	105093497	A	11/2015
JP	1979116220	A	9/1979
JP	06230277	A	8/1994
JP	1994230277	A	8/1994
JP	1999002762	A	1/1999
JP	2006119368	A	5/2006
JP	2011085733	A	4/2011
JP	2012220741	A	11/2012
JP	2014010400	A	1/2014
JP	2014010401	A	1/2014
JP	2014044250	A	3/2014
JP	2015121649	A	7/2015
TW	201344237	A	11/2013
TW	201411182	A	3/2014
TW	201418764	A	5/2014
TW	201500758	A	1/2015
TW	201541116	A	11/2015
TW	201602629	A	1/2016
WO	2010024214	A1	3/2010
WO	2012008357	A1	9/2013
WO	2013157249	A1	12/2015
WO	2015060166	A1	3/2017

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 5A




Fig. 5B




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 8A




Fig. 8B




Fig. 9A




Fig. 9B




Fig. 10A




Fig. 10B




Fig. 10C

1

IMAGE CAPTURING OPTICAL LENS ASSEMBLY, IMAGE CAPTURING DEVICE AND ELECTRONIC DEVICE

RELATED APPLICATIONS

This application is a continuation application of U.S. application Ser. No. 17/569,917 filed on Jan. 6, 2022, now approved, which is a divisional application of U.S. application Ser. No. 16/856,148 filed on Apr. 23, 2020, now U.S. Pat. No. 11,256,070, which is a continuation application of U.S. application Ser. No. 16/135,167 filed on Sep. 19, 2018, now U.S. Pat. No. 10,670,838, which is a continuation application of U.S. application Ser. No. 15/497,385 filed on Apr. 26, 2017, now U.S. Pat. No. 10,107,991, which is a continuation application of U.S. application Ser. No. 14/671,426 filed on Mar. 27, 2015, now U.S. Pat. No. 9,671,588 and claims priority to Taiwan Application Serial Number 103142323, filed Dec. 5, 2014, which is incorporated by reference herein in its entirety.

BACKGROUND

Technical Field

The present disclosure relates to an image capturing optical lens assembly and an image capturing device, and more particularly, to an image capturing optical lens assembly and an image capturing device applicable to electronic devices.

Description of Related Art

As personal electronic products have been becoming more and more compact, the internal components of the electronic products are also required to be smaller in size than before, resulting in an increasing demand for compact optical systems. In addition to the demand of miniaturization, the reduction of the pixel size of sensors in the advanced semiconductor manufacturing technologies has enabled optical systems to evolve toward the field of higher megapixels. Meanwhile, the popularity of smart phones and tablet computers greatly boost the need for compact optical systems featuring high image quality.

A conventional compact optical system is usually configured to have a positive first lens element and a negative second lens element. However, the arrangement of greater refractive power for the first two lens elements at the light incident side usually increases the sensitivity of the system and adversely affects the manufacturing yield rate.

Therefore, a need exists in the art for an optical system that features compact size, high image quality, improved manufacturing yield rate and appropriate sensitivity.

SUMMARY

According to one aspect of the present disclosure, an image capturing optical lens assembly includes, in order from an object side to an image side: a first lens element with refractive power having an object-side surface being convex in a paraxial region thereof; a second lens element having positive refractive power; a third lens element with refractive power having an image-side surface being concave in a paraxial region thereof; a fourth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein an object-side surface and the image-side surface thereof being aspheric; a fifth lens

2

element with refractive power having an object-side surface being concave in a paraxial region thereof; and a sixth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, and an object-side surface and the image-side surface thereof being aspheric, wherein the image-side surface having at least one convex shape in an off-axis region thereof; wherein the image capturing optical lens assembly has a total of six lens elements with refractive power and further includes a stop between an imaged object and the third lens element; wherein a focal length of the image capturing optical lens assembly is f , a focal length of the fifth lens element is f_5 , a focal length of the sixth lens element is f_6 , a focal length of the second lens element is f_2 , a focal length of the third lens element is f_3 , a curvature radius of the object-side surface of the first lens element is R_1 , and the following conditions are satisfied:

$$1.50 < |f/f_5| + |f/f_6|;$$

$$2.20 < |f/f_2| + |f/f_3|; \text{ and}$$

$$|R_1/f| < 1.50.$$

According to another aspect of the present disclosure, an image capturing optical lens assembly includes, in order from an object side to an image side: a first lens element with negative refractive power having an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof; a second lens element having positive refractive power; a third lens element with negative refractive power having an image-side surface being concave in a paraxial region thereof; a fourth lens element with refractive power having an object-side surface and an image-side surface thereof being aspheric; a fifth lens element having refractive power; and a sixth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein an object-side surface and the image-side surface thereof being aspheric, and the image-side surface having at least one convex shape in an off-axis region thereof; wherein the image capturing optical lens assembly has a total of six lens elements with refractive power and further includes a stop between an imaged object and the third lens element; wherein a focal length of the image capturing optical lens assembly is f , a focal length of the fifth lens element is f_5 , a focal length of the sixth lens element is f_6 , a curvature radius of the object-side surface of the first lens element is R_1 , and the following conditions are satisfied:

$$1.50 < |f/f_5| + |f/f_6|; \text{ and}$$

$$|R_1/f| < 1.50.$$

According to another aspect of the present disclosure, an image capturing optical lens assembly includes, in order from an object side to an image side: a first lens element with positive refractive power having an object-side surface being convex in a paraxial region thereof; a second lens element having positive refractive power; a third lens element having refractive power; a fourth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein an object-side surface and the image-side surface thereof being aspheric; a fifth lens element with refractive power having an object-side surface being concave in a paraxial region thereof; and a sixth lens element with refractive power having an image-side surface being concave in a paraxial region thereof, wherein an object-side surface and the image-side surface thereof being aspheric, and the image-side surface having at

3

least one convex shape in an off-axis region thereof; wherein the image capturing optical lens assembly has a total of six lens elements with refractive power and further includes a stop between an imaged object and the third lens element; wherein a focal length of the image capturing optical lens assembly is f , a focal length of the second lens element is f_2 , a focal length of the third lens element is f_3 , and the following condition is satisfied:

$$2.20 < |f/f_2| + |f/f_3|.$$

According to another aspect of the present disclosure, an image capturing device includes the aforementioned image capturing optical lens assembly and an image sensor.

According to another aspect of the present disclosure, an electronic device includes the aforementioned image capturing device.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a schematic view of an image capturing device according to the 1st embodiment of the present disclosure;

FIG. 1B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 1st embodiment;

FIG. 2A is a schematic view of an image capturing device according to the 2nd embodiment of the present disclosure;

FIG. 2B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 2nd embodiment;

FIG. 3A is a schematic view of an image capturing device according to the 3rd embodiment of the present disclosure;

FIG. 3B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 3rd embodiment;

FIG. 4A is a schematic view of an image capturing device according to the 4th embodiment of the present disclosure;

FIG. 4B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 4th embodiment;

FIG. 5A is a schematic view of an image capturing device according to the 5th embodiment of the present disclosure;

FIG. 5B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 5th embodiment;

FIG. 6A is a schematic view of an image capturing device according to the 6th embodiment of the present disclosure;

FIG. 6B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 6th embodiment;

FIG. 7A is a schematic view of an image capturing device according to the 7th embodiment of the present disclosure;

FIG. 7B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 7th embodiment;

FIG. 8A is a schematic view of an image capturing device according to the 8th embodiment of the present disclosure;

FIG. 8B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 8th embodiment;

FIG. 9A is a schematic view of an image capturing device according to the 9th embodiment of the present disclosure;

FIG. 9B shows longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 9th embodiment;

FIG. 10A shows a smart phone with an image capturing device of the present disclosure installed therein;

4

FIG. 10B shows a tablet personal computer with an image capturing device of the present disclosure installed therein; and

FIG. 10C shows a wearable device with an image capturing device of the present disclosure installed therein.

DETAILED DESCRIPTION

The present disclosure provides an image capturing optical lens assembly including, in order from an object side to an image side, a first lens element, a second lens element, a third lens element, a fourth lens element, a fifth lens element, and a sixth lens element, wherein the image capturing optical lens assembly has a total of six lens elements with refractive power and further includes a stop, such as an aperture stop. The stop is between an imaged object and the third lens element.

The first lens element may have negative refractive power so as to favorably enlarge the field of view of the image capturing optical lens assembly. Alternatively, the first lens element may have positive refractive power, so that it provides the image capturing optical lens assembly with part of refractive power as it needs to be so as to favorably reduce the total track length of the image capturing optical lens assembly. The object-side surface of the first lens element is convex in a paraxial region thereof, and the image-side surface of the first lens element is concave in a paraxial region thereof so as to correct the astigmatism of the image capturing optical lens assembly.

The second lens element may have positive refractive power, so that it is favorable for distributing the refractive power of the first lens element and thereby to favorably reduce the photosensitivity of the image capturing optical lens assembly. The object-side surface of the second lens element may be convex in a paraxial region thereof so as to enhance the capability of correcting the astigmatism.

The third lens element may have negative refractive power, which together with the positive refractive power of the second lens element can mitigate the deflection of light incident to the image capturing optical lens assembly to control the aberration and to reduce the sensitivity of the image capturing optical lens assembly, thereby improving the manufacturing yield rate. The object-side surface of the third lens element may be concave in a paraxial region thereof, and the image-side surface of the third lens element is concave in a paraxial region thereof so as to favorably correct the aberration of the image capturing optical lens assembly. The object-side surface of the third lens element may have at least one inflection point so as to effectively correct the aberration of the off-axis field.

The object-side surface of the fourth lens element may be convex in a paraxial region thereof, and the image-side surface of the fourth lens element is concave in a paraxial region thereof so as to effectively correct the astigmatism of the image capturing optical lens assembly and to effectively mitigate the variation in the shape of the fourth lens element, thereby facilitating the formation of the fourth lens element. The image-side surface of the fourth lens element has at least one convex shape in an off-axis region thereof so as to favorably correct the aberration of the off-axis field.

The fifth lens element may have positive refractive power, so that it is favorable for balancing the distribution of the positive refractive power. The object-side surface of the fifth lens element may be concave in a paraxial region thereof, and the image-side surface of the fifth lens element may be convex in a paraxial region thereof so that the capability of correcting the astigmatism is enhanced.

The sixth lens element may have negative refractive power, so that it is favorable for the distribution of the negative refractive power of the image capturing optical lens assembly. The image-side surface of the sixth lens element is concave in a paraxial region thereof; this allows the principal point of the image capturing optical lens assembly to be placed away from the image surface, thereby reducing the total track length of the image capturing optical lens assembly. The image-side surface of the sixth lens element has at least one convex shape in an off-axis region thereof so as to effectively correct the aberration of the off-axis field.

When a focal length of the image capturing optical lens assembly is f , a focal length of the fifth lens element is $f5$, a focal length of the sixth lens element is $f6$, and the following condition is satisfied: $1.50 < |f/f5| + |f/f6|$, the distribution of the refractive power of the image capturing optical lens assembly is more balanced and thereby to reduce the sensitivity of the image capturing optical lens assembly. Preferably, the following condition is satisfied: $2.50 < |f/f5| + |f/f6| < 5.0$.

When the focal length of the image capturing optical lens assembly is f , a focal length of the second lens element is $f2$, a focal length of the third lens element is $f3$, and the following condition is satisfied: $2.20 < |f/f2| + |f/f3|$, the deflection of light incident to the image capturing optical lens assembly can be mitigated to control the aberration and reduce the sensitivity of the image capturing optical lens assembly, thereby improving the manufacturing yield rate.

When a curvature radius of the object-side surface of the first lens element is $R1$, the focal length of the image capturing optical lens assembly is f , and the following condition is satisfied: $|R1/f| < 1.50$, it is favorable for reducing the sensitivity of the image capturing optical lens assembly. Preferably, the following condition is satisfied: $|R1/f| < 0.75$.

When a central thickness of the second lens element is $CT2$, an axial distance between the first lens element and the second lens element is $T12$, an axial distance between the second lens element and the third lens element is $T23$, and the following condition is satisfied: $2.4 < CT2/(T12+T23) < 5.0$, the thickness of the second lens element and the axial distances between the first lens element, the second lens element and the third lens element will be more appropriate. Such an arrangement facilitates controlling the thickness of the second lens element and preventing the total track length of the image capturing optical lens assembly from being too long, and this is favorable for assembling and manufacturing lens elements.

When the focal length of the image capturing optical lens assembly is f , a curvature radius of the object-side surface of the second lens element is $R3$, and the following condition is satisfied: $1.40 < |f/R3|$, the sensitivity of the image capturing optical lens assembly can be effectively corrected and this is favorable for manufacturing yield rate.

When the focal length of the image capturing optical lens assembly is f , a curvature radius of the image-side surface of the sixth lens element is $R12$, and the following condition is satisfied: $0 < R12/f < 0.40$, the incident angle of the light projecting onto an image sensor from the image capturing optical lens assembly can be favorably suppressed to increase the photosensitivity of the image capturing optical lens assembly.

When an Abbe number of the fifth lens element is $V5$, an Abbe number of the third lens element is $V3$, an Abbe number of the fourth lens element is $V4$, and the following

condition is satisfied: $1.0 < V5/(V3+V4) < 1.5$, the chromatic aberration in the image capturing optical lens assembly can be effectively corrected.

When an f-number of the image capturing optical lens assembly is Fno , and the following condition is satisfied: $1.6 < Fno < 2.5$, the ambient illuminance of the image capturing optical lens assembly can be favorably increased.

When a central thickness of the first lens element is $CT1$, a distance in parallel with an optical axis from an axial vertex on the image-side surface of the first lens element to a maximum effective radius position on the image-side surface of the first lens element is $Sag12$, and the following condition is satisfied: $CT1/|Sag12| < 2.5$, it is favorable for the reduction of the sensitivity of the image capturing optical lens assembly and the manufacturing yield rate.

When a central thickness of the fifth lens element is $CT5$, a central thickness of the sixth lens element is $CT6$, and the following condition is satisfied: $0.80 < CT5/CT6$, the thickness of the lens elements is more appropriate, and this is favorable for manufacturing and assembling lens elements.

According to the image capturing optical lens assembly of the present disclosure, the lens elements thereof can be made of glass or plastic material. When the lens elements are made of glass material, the distribution of the refractive power of the image capturing optical lens assembly may be more flexible to design. When the lens elements are made of plastic material, the manufacturing cost can be effectively reduced. Furthermore, surfaces of each lens element can be arranged to be aspheric (ASP), since the aspheric surface of the lens element is easy to form a shape other than spherical surfaces so as to have more controllable variables for eliminating the aberration thereof and to further decrease the required number of the lens elements, the total track length of the image capturing optical lens assembly can be effectively reduced.

According to the image capturing optical lens assembly of the present disclosure, the image capturing optical lens assembly can include at least one stop, such as an aperture stop, a glare stop or a field stop.

According to the image capturing optical lens assembly of the present disclosure, a stop can be configured as a front stop or a middle stop. A front stop disposed between an imaged object and the first lens element can provide a longer distance between an exit pupil of the image capturing optical lens assembly and the image surface and thereby to improve the image-sensing efficiency of an image sensor, such as a CCD or CMOS sensor. A middle stop disposed between the first lens element and the image surface is favorable for enlarging the field of view of the image capturing optical lens assembly and thereby to provide a wider field of view for the same.

According to the image capturing optical lens assembly of the present disclosure, when the lens element has a convex surface and the region of convex shape is not defined, it indicates that the surface is convex in the paraxial region thereof; when the lens element has a concave surface and the region of concave shape is not defined, it indicates that the surface is concave in the paraxial region thereof. Likewise, when the region of refractive power or focal length of a lens element is not defined, it indicates that the region of refractive power or focal length of the lens element is in the paraxial region thereof.

According to the image capturing optical lens assembly of the present disclosure, an image surface of the image capturing optical lens assembly, based on the corresponding

image sensor, can be a plane or a curved surface with any curvature, especially a curved surface being concave facing towards the object side.

The image capturing optical lens assembly of the present disclosure can be optionally applied to moving focus optical systems. According to the image capturing optical lens assembly of the present disclosure, the image capturing optical lens assembly features good correction capability and high image quality, and can be applied to 3D (three-dimensional) image capturing applications and electronic devices, such as digital cameras, mobile devices, digital tablets, smart TV, wireless monitoring device, motion sensing input device, driving recording system, rear view camera system, and wearable devices.

According to the present disclosure, an image capturing device includes the aforementioned image capturing optical lens assembly and an image sensor, wherein the image sensor is disposed on or near an image surface of the image capturing optical lens assembly. Therefore, the design of the image capturing optical lens assembly enables the image capturing device to achieve the best image quality. Preferably, the image capturing device can further include a barrel member, a holding member or a combination thereof.

Referring to FIG. 10A, FIG. 10B and FIG. 10C, an image capturing device **1001** may be installed in an electronic device, including, but not limited to, a smart phone **1010**, a tablet personal computer **1020** or a wearable device **1030**. The three exemplary figures of different kinds of electronic devices are only exemplary for showing the image capturing device of present disclosure installed in an electronic device and are not limited thereto. Preferably, the electronic device can further include a control unit, a display unit, a storage unit, a random access memory unit (RAM) or a combination thereof.

According to the above description of the present disclosure, the following 1st-9th specific embodiments are provided for further explanation.

1st Embodiment

FIG. 1A is a schematic view of an image capturing device according to the 1st embodiment of the present disclosure. FIG. 1B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 1st embodiment.

In FIG. 1A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor **190**. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element **110**, a second lens element **120**, a third lens element **130**, a fourth lens element **140**, a fifth lens element **150**, and a sixth lens element **160**, wherein the image capturing optical lens assembly has a total of six lens elements (**110-160**) with refractive power.

The first lens element **110** with positive refractive power has an object-side surface **111** being convex in a paraxial region thereof and an image-side surface **112** being concave in a paraxial region thereof, which are both aspheric, and the first lens element **110** is made of plastic material.

The second lens element **120** with positive refractive power has an object-side surface **121** being convex in a paraxial region thereof and an image-side surface **122** being convex in a paraxial region thereof, which are both aspheric, and the second lens element **120** is made of plastic material.

The third lens element **130** with negative refractive power has an object-side surface **131** being concave in a paraxial region thereof and an image-side surface **132** being concave in a paraxial region thereof, which are both aspheric, and the third lens element **130** is made of plastic material. Furthermore, the object-side surface **131** of the third lens element **130** has at least one inflection point.

The fourth lens element **140** with negative refractive power has an object-side surface **141** being convex in a paraxial region thereof and an image-side surface **142** being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element **140** is made of plastic material. Furthermore, the image-side surface **142** of the fourth lens element **140** has at least one convex shape in an off-axis region thereof.

The fifth lens element **150** with positive refractive power has an object-side surface **151** being concave in a paraxial region thereof and an image-side surface **152** being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element **150** is made of plastic material.

The sixth lens element **160** with negative refractive power has an object-side surface **161** being convex in a paraxial region thereof and an image-side surface **162** being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element **160** is made of plastic material. Furthermore, the image-side surface **162** of the sixth lens element **160** has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop **100** and an IR-cut filter **170**. The aperture stop **100** is disposed between an imaged object and the first lens element **110**. The IR-cut filter **170** is made of glass and located between the sixth lens element **160** and an image surface **180**, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor **190** is disposed on or near the image surface **180** of the image capturing optical lens assembly.

The equation of the aspheric surface profiles is expressed as follows:

$$X(Y) = (Y^2/R) / (1 + \sqrt{1 - (1 + k) * (Y/R)^2}) + \sum_i (Ai * Y^i),$$

where,

X is the relative distance between a point on the aspheric surface spaced at a distance Y from the optical axis and the tangential plane at the aspheric surface vertex on the optical axis;

Y is the vertical distance from the point on the aspheric surface to the optical axis;

R is the curvature radius;

k is the conic coefficient; and

Ai is the i-th aspheric coefficient.

In the first embodiment, a focal length of the image capturing optical lens assembly is f, an f-number of the image capturing optical lens assembly is Fno, half of maximal field of view of the image capturing optical lens assembly is HFOV, and these parameters have the following values: f=3.78 mm; Fno=1.90; and HFOV=38.5 degrees.

In the first embodiment, an Abbe number of the fifth lens element **150** is V5, an Abbe number of the third lens element **130** is V3, an Abbe number of the fourth lens element **140** is V4, and they satisfy the condition: V5/(V3+V4)=1.19.

In the first embodiment, a central thickness of the second lens element **120** is CT2, an axial distance between the first

lens element **110** and the second lens element **120** is T12, an axial distance between the second lens element **120** and the third lens element **130** is T23, and they satisfy the condition: $CT2/(T12+T23)=2.70$.

In the first embodiment, a central thickness of the fifth lens element **150** is CT5, a central thickness of the sixth lens element **160** is CT6, and they satisfy the condition: $CT5/CT6=1.99$.

In the first embodiment, a central thickness of the first lens element **110** is CT1, a distance in parallel with an optical axis from an axial vertex on the image-side surface **112** of the first lens element **110** to a maximum effective radius position on the image-side surface **112** of the first lens element **110** is Sag12, and they satisfy the condition: $CT1/|Sag12|=1.47$.

In the first embodiment, a curvature radius of the object-side surface **111** of the first lens element **110** is R1, a focal length of the image capturing optical lens assembly is f, and they satisfy the condition: $|R1/f|=0.46$.

In the first embodiment, the focal length of the image capturing optical lens assembly is f, a curvature radius of the

object-side surface **121** of the second lens element **120** is R3, and they satisfy the condition: $f/R3=1.77$.

In the first embodiment, a curvature radius of the image-side surface **162** of the sixth lens element **160** is R12, the focal length of the image capturing optical lens assembly is f, and they satisfy the condition: $R12/f=0.20$.

In the first embodiment, the focal length of the image capturing optical lens assembly is f, a focal length of the second lens element **120** is f2, a focal length of the third lens element **130** is f3, and they satisfy the condition: $|f/f2|+|f/f3|=2.28$.

In the first embodiment, the focal length of the image capturing optical lens assembly is f, a focal length of the fifth lens element **150** is f5, a focal length of the sixth lens element **160** is f6, and they satisfy the condition: $|f/f5|+|f/f6|=3.61$.

The detailed optical data of the first embodiment are shown in TABLE 1, and the aspheric surface data are shown in TABLE 2, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 1

(Embodiment 1)								
f = 3.78 mm, Fno = 1.90, HFOV = 38.5 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe#	Focal Length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.247					
2	Lens 1	1.755 ASP	0.300	Plastic	1.544	55.9	419.65	
3		1.662 ASP	0.151					
4	Lens 2	2.133 ASP	0.594	Plastic	1.544	55.9	2.78	
5		-4.662 ASP	0.069					
6	Lens 3	-38.635 ASP	0.265	Plastic	1.639	23.5	-4.12	
7		2.830 ASP	0.293					
8	Lens 4	3.671 ASP	0.310	Plastic	1.633	23.4	-843.52	
9		3.527 ASP	0.330					
10	Lens 5	-12.309 ASP	0.899	Plastic	1.544	55.9	2.02	
11		-1.035 ASP	0.050					
12	Lens 6	2.468 ASP	0.451	Plastic	1.544	55.9	-2.18	
13		0.750 ASP	0.800					
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2		
15		Plano	0.470					
16	Image Surface	Plano	—					

Note:

Reference Wavelength is d-line 587.6 nm

TABLE 2

Aspheric Coefficients							
Surface #	2	3	4	5	6	7	
k=	-5.8403E-01	-1.7275E+00	-7.6830E+00	-9.0000E+01	8.9992E+01	3.1605E+00	
A4=	-4.1244E-02	-8.7529E-02	1.2639E-02	-2.1623E-03	1.3639E-01	3.8318E-03	
A6=	8.8742E-03	4.0028E-02	-5.2013E-02	-1.9764E-01	-4.2352E-01	-1.1664E-01	
A8=	6.8214E-03	-3.6180E-02	-1.4139E-02	1.7852E-01	4.5265E-01	1.0855E-01	
A10=	-1.5515E-02		9.2136E-03	-5.4540E-02	-2.1953E-01	-5.8999E-02	
A12=					4.0773E-02	1.1469E-02	
Surface #	8	9	10	11	12	13	
k=	-5.9209E+01	-1.8336E+01	-3.3470E+00	-5.5845E+00	-2.4679E-01	-4.3394E+00	
A4=	-2.1805E-02	-7.9011E-02	7.7778E-02	-5.0173E-02	-2.1999E-01	-9.0041E-02	
A6=	-3.2370E-02	3.1538E-02	-1.2567E-01	1.4292E-02	6.7649E-02	3.2227E-02	
A8=	4.3459E-03	-2.1342E-02	1.3643E-01	9.6967E-03	-1.0551E-02	-8.5109E-03	
A10=	1.3091E-02	-1.4490E-02	-9.6542E-02	-9.4547E-04	9.7036E-04	1.3883E-03	
A12=	-5.2554E-03	2.1447E-02	3.6315E-02	-1.0958E-03	-7.6596E-05	-1.3093E-04	
A14=		-5.3783E-03	-5.4872E-03	1.8051E-04	4.1836E-06	5.5499E-06	

11

2nd Embodiment

FIG. 2A is a schematic view of an image capturing device according to the 2nd embodiment of the present disclosure. FIG. 2B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 2nd embodiment.

In FIG. 2A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 290. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 210, a second lens element 220, a third lens element 230, a fourth lens element 240, a fifth lens element 250, and a sixth lens element 260, wherein the image capturing optical lens assembly has a total of six lens elements (210-260) with refractive power.

The first lens element 210 with negative refractive power has an object-side surface 211 being convex in a paraxial region thereof and an image-side surface 212 being concave in a paraxial region thereof, which are both aspheric, and the first lens element 210 is made of plastic material.

The second lens element 220 with positive refractive power has an object-side surface 221 being convex in a paraxial region thereof and an image-side surface 222 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 220 is made of plastic material.

The third lens element 230 with negative refractive power has an object-side surface 231 being concave in a paraxial region thereof and an image-side surface 232 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 230 is made of plastic material. Furthermore, the object-side surface 231 of the third lens element 230 has at least one inflection point.

12

The fourth lens element 240 with positive refractive power has an object-side surface 241 being convex in a paraxial region thereof and an image-side surface 242 being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element 240 is made of plastic material. Furthermore, the image-side surface 242 of the fourth lens element 240 has at least one convex shape in an off-axis region thereof.

The fifth lens element 250 with positive refractive power has an object-side surface 251 being convex in a paraxial region thereof and an image-side surface 252 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 250 is made of plastic material.

The sixth lens element 260 with negative refractive power has an object-side surface 261 being convex in a paraxial region thereof and an image-side surface 262 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 260 is made of plastic material. Furthermore, the image-side surface 262 of the sixth lens element 260 has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop 200 and an IR-cut filter 270. The aperture stop 200 is disposed between an imaged object and the first lens element 210. The IR-cut filter 270 is made of glass and located between the sixth lens element 260 and an image surface 280, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 290 is disposed on or near the image surface 280 of the image capturing optical lens assembly.

The detailed optical data of the second embodiment are shown in TABLE 3, and the aspheric surface data are shown in TABLE 4, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 3

(Embodiment 2)								
f = 3.85 mm, Fno = 2.03, HFOV = 38.0 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length	
0	Object	Plano	Infinity					
1	Ape. Stop	Plano	-0.205					
2	Lens 1	1.865	ASP	0.300	Plastic	1.639	23.5	-17.00
3		1.492	ASP	0.125				
4	Lens 2	1.946	ASP	0.746	Plastic	1.544	55.9	2.58
5		-4.338	ASP	0.082				
6	Lens 3	-43.214	ASP	0.257	Plastic	1.639	23.5	-4.50
7		3.089	ASP	0.286				
8	Lens 4	4.419	ASP	0.294	Plastic	1.639	23.5	43.61
9		5.115	ASP	0.576				
10	Lens 5	23.394	ASP	0.631	Plastic	1.544	55.9	2.32
11		-1.323	ASP	0.050				
12	Lens 6	2.113	ASP	0.437	Plastic	1.535	55.7	-2.42
13		0.744	ASP	0.800				
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2		
15		Plano	0.468					
16	Image Surface	Plano	—					

Note:

Reference wavelength is d-line 587.6 nm

TABLE 4

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-9.5006E-01	-1.4696E+00	-5.1972E+00	-9.0000E+01	1.8649E+01	2.8260E+00
A4=	-4.8463E-02	-7.9417E-02	2.6637E-02	-1.8368E-02	1.1132E-01	-1.1792E-02
A6=	1.7148E-02	3.7001E-02	-3.8254E-02	-1.7579E-01	-4.3697E-01	-1.2813E-01
A8=	-5.3900E-03	-1.5693E-02	9.7414E-03	1.6829E-01	4.4501E-01	1.2110E-01
A10=	-3.0618E-03		-3.9222E-03	-5.1187E-02	-1.8095E-01	-4.9657E-02
A12=					2.5264E-02	6.5309E-03
Surface #	8	9	10	11	12	13
k=	-5.9209E+01	-1.8336E+01	-3.3470E+00	-8.3516E+00	-2.6657E-01	-3.7283E+00
A4=	-8.4909E-02	-1.5264E-01	9.4160E-02	4.6088E-02	-2.4725E-01	-1.2284E-01
A6=	5.6241E-02	8.3547E-02	-1.2263E-02	-8.1544E-02	5.4175E-03	4.7993E-02
A8=	-9.6690E-02	-6.4550E-02	9.9072E-02	7.2034E-02	5.1453E-02	-1.2048E-02
A10=	7.3382E-02	1.3063E-02	-5.3443E-02	-2.5383E-02	-2.0237E-02	1.8540E-03
A12=	-1.7548E-02	1.6176E-02	1.5774E-02	3.5764E-03	3.0896E-03	-1.6330E-04
A14=		-5.6694E-03	-2.0349E-03	-1.5400E-04	-1.7312E-04	6.2775E-06

In the 2nd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 5 below are the same as those stated in the 1st embodiment with corresponding values for the 2nd embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 3 and Table 4 and satisfy the conditions stated in Table 5.

TABLE 5

2 nd Embodiment	
f [mm]	3.85
Fno	2.03
HFOV [deg.]	38.0
V5/(V3 + V4)	1.19
CT2/(T12 + T23)	3.60
CT5/CT6	1.44
CT1/(Sag12)	1.11
R1/f	0.48
f/R3	1.98
R12/f	0.19
f/f2 + f/f3	2.35
f/f5 + f/f6	3.25

3rd Embodiment

FIG. 3A is a schematic view of an image capturing device according to the 3rd embodiment of the present disclosure. FIG. 3B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 3rd embodiment.

In FIG. 3A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 390. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 310, a second lens element 320, a third lens element 330, a fourth lens element 340, a fifth lens element 350, and a sixth lens element 360, wherein the image capturing optical lens assembly has a total of six lens elements (310-360) with refractive power.

The first lens element 310 with positive refractive power has an object-side surface 311 being convex in a paraxial region thereof and an image-side surface 312 being concave

in a paraxial region thereof, which are both aspheric, and the first lens element 310 is made of plastic material.

The second lens element 320 with positive refractive power has an object-side surface 321 being convex in a paraxial region thereof and an image-side surface 322 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 320 is made of glass.

The third lens element 330 with negative refractive power has an object-side surface 331 being concave in a paraxial region thereof and an image-side surface 332 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 330 is made of plastic material. Furthermore, the object-side surface 331 of the third lens element 330 has at least one inflection point.

The fourth lens element 340 with negative refractive power has an object-side surface 341 being convex in a paraxial region thereof and an image-side surface 342 being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element 340 is made of plastic material. Furthermore, the image-side surface 342 of the fourth lens element 340 has at least one convex shape in an off-axis region thereof.

The fifth lens element 350 with positive refractive power has an object-side surface 351 being concave in a paraxial region thereof and an image-side surface 352 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 350 is made of plastic material.

The sixth lens element 360 with negative refractive power has an object-side surface 361 being convex in a paraxial region thereof and an image-side surface 362 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 360 is made of plastic material. Furthermore, the image-side surface 362 of the sixth lens element 360 has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop 300 and an IR-cut filter 370. The aperture stop 300 is disposed between an imaged object and the first lens element 310. The IR-cut filter 370 is made of glass and located between the sixth lens element 360 and an image surface 380, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 390 is disposed on or near the image surface 380 of the image capturing optical lens assembly.

The detailed optical data of the third embodiment are shown in TABLE 6, and the aspheric surface data are shown

in TABLE 7, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 6

(Embodiment 3)							
f = 4.00 mm, Fno = 2.20, HFOV = 37.0 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.234				
2	Lens 1	1.641 ASP	0.364	Plastic	1.544	55.9	220.35
3		1.533 ASP	0.171				
4	Lens 2	2.242 ASP	0.632	Glass	1.592	60.6	2.59
5		-4.344 ASP	0.072				
6	Lens 3	-97.807 ASP	0.265	Plastic	1.650	21.5	-4.59
7		3.084 ASP	0.510				
8	Lens 4	8.562 ASP	0.310	Plastic	1.650	21.5	-51.98
9		6.735 ASP	0.319				
10	Lens 5	-3.775 ASP	0.562	Plastic	1.544	55.9	1.95
11		-0.870 ASP	0.050				
12	Lens 6	20.329 ASP	0.498	Plastic	1.544	55.9	-1.92
13		0.987 ASP	0.800				
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2	
15		Plano	0.330				
16	Image Surface	Plano	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 7

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-2.3625E-01	-5.1323E-01	-6.3496E+00	-8.5546E+01	9.0000E+01	4.7426E+00
A4=	-2.9819E-02	-4.2192E-02	4.4302E-02	9.0303E-04	1.4707E-01	4.7795E-03
A6=	-1.9524E-02	-3.7052E-02	-5.3859E-02	-1.9805E-01	-4.2318E-01	-1.1289E-01
A8=	1.1402E-02	3.0115E-03	-2.6940E-02	1.9648E-01	4.9123E-01	1.1398E-01
A10=	-9.6681E-03		2.0339E-02	-7.0527E-02	-2.2873E-01	-3.9910E-02
A12=					2.8300E-02	-4.5156E-03
Surface #	8	9	10	11	12	13
k=	-9.0000E+01	-1.8336E+01	4.1711E-01	-3.1586E+00	3.1571E+00	-6.1836E+00
A4=	-1.1006E-01	-2.1050E-01	-2.7733E-01	-8.8569E-02	-2.8139E-02	-6.3400E-02
A6=	3.7911E-02	2.1305E-01	1.4087E-01	-1.1462E-01	1.9850E-02	2.4929E-02
A8=	-2.5110E-02	-2.2483E-01	1.9670E-01	3.0457E-01	-1.2431E-02	-6.9183E-03
A10=	-3.2822E-02	1.6220E-01	-2.2965E-01	-2.0229E-01	3.6192E-03	1.0336E-03
A12=	1.7673E-02	-7.9151E-02	8.3773E-02	5.6359E-02	-4.7701E-04	-8.1559E-05
A14=		1.7180E-02	-1.1045E-02	-5.8255E-03	2.3696E-05	2.8318E-06

In the 3rd embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 8 below are the same as those stated in the 1st embodiment with corresponding values for the 3rd embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 6 and Table 7 and satisfy the conditions stated in Table 8.

TABLE 8

3 rd Embodiment	
f [mm]	4.00
Fno	2.20
HFOV [deg.]	37.0
V5/(V3 + V4)	1.30
CT2/(T12 + T23)	2.60
CT5/CT6	1.13

TABLE 8-continued

3 rd Embodiment	
CT1/(Sag12)	1.40
R1/f	0.41
f/R3	1.78
R12/f	0.25
f/f2 + f/f3	2.42
f/f5 + f/f6	4.13

4th Embodiment

FIG. 4A is a schematic view of an image capturing device according to the 4th embodiment of the present disclosure. FIG. 4B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 4th embodiment.

In FIG. 4A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 490. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 410, a second lens element 420, a third lens element 430, a fourth lens element 440, a fifth lens element 450, and a sixth lens element 460, wherein the image capturing optical lens assembly has a total of six lens elements (410-460) with refractive power.

The first lens element 410 with negative refractive power has an object-side surface 411 being convex in a paraxial region thereof and an image-side surface 412 being concave in a paraxial region thereof, which are both aspheric, and the first lens element 410 is made of plastic material.

The second lens element 420 with positive refractive power has an object-side surface 421 being convex in a paraxial region thereof and an image-side surface 422 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 420 is made of plastic material.

The third lens element 430 with negative refractive power has an object-side surface 431 being concave in a paraxial region thereof and an image-side surface 432 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 430 is made of plastic material. Furthermore, the object-side surface 431 of the third lens element 430 has at least one inflection point.

The fourth lens element 440 with positive refractive power has an object-side surface 441 being concave in a

paraxial region thereof and an image-side surface 442 being convex in a paraxial region thereof, which are both aspheric, and the fourth lens element 440 is made of plastic material.

The fifth lens element 450 with positive refractive power has an object-side surface 451 being concave in a paraxial region thereof and an image-side surface 452 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 450 is made of plastic material.

The sixth lens element 460 with negative refractive power has an object-side surface 461 being concave in a paraxial region thereof and an image-side surface 462 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 460 is made of plastic material. Furthermore, the image-side surface 462 of the sixth lens element 460 has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop 400 and an IR-cut filter 470. The aperture stop 400 is disposed between the first lens element 410 and the second lens element 420. The IR-cut filter 470 is made of glass and located between the sixth lens element 460 and an image surface 480, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 490 is disposed on or near the image surface 480 of the image capturing optical lens assembly.

The detailed optical data of the fourth embodiment are shown in TABLE 9, and the aspheric surface data are shown in TABLE 10, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 9

(Embodiment 4)							
f = 4.05 mm, Fno = 2.35, HFOV = 37.4 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Lens 1	1.983 ASP	0.483	Plastic	1.639	23.5	-28.07
2		1.616 ASP	0.216				
3	Ape. Stop	Plano	-0.054				
4	Lens 2	1.603 ASP	0.635	Plastic	1.544	55.9	2.16
5		-3.774 ASP	0.050				
6	Lens 3	-8.904 ASP	0.265	Plastic	1.639	23.5	-3.79
7		3.364 ASP	0.476				
8	Lens 4	-76.136 ASP	0.549	Plastic	1.639	23.5	19.86
9		-10.908 ASP	0.232				
10	Lens 5	-3.216 ASP	0.450	Plastic	1.560	48.0	2.21
11		-0.939 ASP	0.110				
12	Lens 6	-10.240 ASP	0.457	Plastic	1.535	55.7	-1.87
13		1.128 ASP	0.700				
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2	
15		Plano	0.385				
16	Image Surface	Plano	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 10

Aspheric Coefficients						
Surface #	1	2	4	5	6	7
k=	-5.7523E-01	-2.1481E+00	-5.1057E+00	-2.0516E+00	-7.1165E+01	3.7642E+00
A4=	-3.7779E-02	-8.5995E-02	3.7763E-02	6.4233E-02	6.5837E-02	-9.9342E-03
A6=	9.2238E-03	2.3775E-02	-7.6710E-02	-3.5241E-01	-3.2167E-01	-9.6870E-03
A8=	-1.2136E-02	-3.6991E-02	-8.6875E-02	2.6822E-01	4.1527E-01	-1.8667E-02
A10=	1.0602E-02	3.6436E-02	3.9520E-02	-7.1191E-02	-1.5582E-01	2.2647E-01
A12=	-3.5836E-03	4.6081E-07	-1.7005E-07	-3.7222E-05	9.5053E-03	-3.7548E-01

TABLE 10-continued

Aspheric Coefficients						
A14	-1.6420E-06	9.3737E-10	-2.4239E-08	2.6821E-08	3.5253E-05	2.4673E-01
A16	-5.0985E-07	3.2671E-10	-3.5042E-09	5.0416E-09	6.9823E-09	-5.7653E-02
Surface #	8	9	10	11	12	13
k=	8.9919E+01	-2.0465E+01	2.9303E+00	-2.7882E+00	1.0183E+01	-5.4912E+00
A4=	1.5752E-02	5.1742E-02	-1.5154E-01	-1.0657E-01	-3.9771E-02	-1.0047E-01
A6=	-3.5756E-01	-3.6773E-01	1.1369E-01	6.2159E-02	7.8334E-02	6.2075E-02
A8=	9.4123E-01	5.9434E-01	-1.4877E-01	3.7236E-02	-7.7804E-02	-2.8959E-02
A10=	-1.5526E+00	-6.0723E-01	2.3795E-01	-4.4330E-02	3.5295E-02	8.2981E-03
A12=	1.4931E+00	4.0608E-01	-1.5071E-01	1.8291E-02	-8.0761E-03	-1.4363E-03
A14=	-7.7570E-01	-1.5902E-01	3.3077E-02	-3.7920E-03	9.2581E-04	1.3625E-04
A16=	1.6501E-01	2.6042E-02	-9.6229E-04	3.2310E-04	-4.2687E-05	-5.3431E-06

In the 4th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 11 below are the same as those stated in the 1st embodiment with corresponding values for the 4th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 9 and Table 10 and satisfy the conditions stated in Table 11.

TABLE 11

4 th Embodiment	
f [mm]	4.05
Fno	2.35
HFOV [deg.]	37.4
V5/(V3 + V4)	1.02
CT2/(T12 + T23)	3.00
CT5/CT6	0.98
CT1/ Sag12	2.91
R1/f	0.49
f/R3	2.53
R12/f	0.28
f/f2 + f/f3	2.94
f/f5 + f/f6	4.00

5th Embodiment

FIG. 5A is a schematic view of an image capturing device according to the 5th embodiment of the present disclosure. FIG. 5B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 5th embodiment.

In FIG. 5A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 590. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 510, a second lens element 520, a third lens element 530, a fourth lens element 540, a fifth lens element 550, and a sixth lens element 560, wherein the image capturing optical lens assembly has a total of six lens elements (510-560) with refractive power.

The first lens element 510 with negative refractive power has an object-side surface 511 being convex in a paraxial region thereof and an image-side surface 512 being concave in a paraxial region thereof, which are both aspheric, and the first lens element 510 is made of plastic material.

The second lens element 520 with positive refractive power has an object-side surface 521 being convex in a paraxial region thereof and an image-side surface 522 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 520 is made of plastic material.

The third lens element 530 with negative refractive power has an object-side surface 531 being concave in a paraxial region thereof and an image-side surface 532 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 530 is made of plastic material. Furthermore, the object-side surface 531 of the third lens element 530 has at least one inflection point.

The fourth lens element 540 with positive refractive power has an object-side surface 541 being convex in a paraxial region thereof and an image-side surface 542 being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element 540 is made of plastic material. Furthermore, the image-side surface 542 of the fourth lens element 540 has at least one convex shape in an off-axis region thereof.

The fifth lens element 550 with positive refractive power has an object-side surface 551 being concave in a paraxial region thereof and an image-side surface 552 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 550 is made of plastic material.

The sixth lens element 560 with negative refractive power has an object-side surface 561 being convex in a paraxial region thereof and an image-side surface 562 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 560 is made of plastic material. Furthermore, the image-side surface 562 of the sixth lens element 560 has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop 500 and an IR-cut filter 570. The aperture stop 500 is disposed between an imaged object and the first lens element 510. The IR-cut filter 570 is made of glass and located between the sixth lens element 560 and an image surface 580, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 590 is disposed on or near the image surface 580 of the image capturing optical lens assembly.

The detailed optical data of the fifth embodiment are shown in TABLE 12, and the aspheric surface data are shown in TABLE 13, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 12

(Embodiment 5)							
f = 4.13 mm, Fno = 2.20, HFOV = 36.4 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.255				
2	Lens 1	1.500 ASP	0.300	Plastic	1.544	55.9	-166.89
3		1.371 ASP	0.151				
4	Lens 2	1.865 ASP	0.612	Plastic	1.544	55.9	2.35
5		-3.576 ASP	0.050				
6	Lens 3	-8.368 ASP	0.265	Plastic	1.639	23.5	-3.62
7		3.231 ASP	0.426				
8	Lens 4	2.892 ASP	0.319	Plastic	1.639	23.5	27.68
9		3.308 ASP	0.450				
10	Lens 5	-1.768 ASP	0.565	Plastic	1.544	55.9	2.15
11		-0.784 ASP	0.050				
12	Lens 6	5.648 ASP	0.445	Plastic	1.544	55.9	-2.15
13		0.942 ASP	0.800				
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2	
15		Plano	0.457				
16	Image Surface	Plano	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 13

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-5.5896E-01	-1.4494E+00	-6.3163E+00	-5.6354E+01	-4.3569E+01	5.3797E+00
A4=	-4.7192E-02	-7.0688E-02	3.9453E-02	-2.0570E-02	1.8352E-01	3.3300E-02
A6=	1.3599E-02	6.7547E-02	-4.7790E-02	-1.9058E-01	-4.1269E-01	-7.7319E-02
A8=	-1.8138E-02	-9.4969E-02	-1.5747E-02	2.3811E-01	5.0227E-01	8.0864E-02
A10=	-1.7872E-02		2.6867E-03	-9.1459E-02	-2.4357E-01	-3.4197E-02
A12=					2.7318E-02	3.8233E-04
Surface #	8	9	10	11	12	13
k=	-9.0249E+00	-1.8336E+01	-3.9819E+00	-3.0957E+00	1.9367E+00	-6.9866E+00
A4=	-9.8090E-02	-1.0549E-01	-2.6887E-01	-1.1386E-01	-5.3755E-02	-6.2835E-02
A6=	3.2554E-02	5.8699E-02	1.3592E-01	-9.7432E-02	2.7217E-02	2.6537E-02
A8=	-3.1922E-02	-5.4107E-02	1.9802E-01	3.0547E-01	-1.1348E-02	-8.0041E-03
A10=	-3.2857E-02	4.0901E-03	-2.2670E-01	-2.0319E-01	2.1500E-03	1.3291E-03
A12=	1.7673E-02	7.7777E-03	8.5227E-02	5.6128E-02	-1.5555E-04	-1.2193E-04
A14=		-1.3520E-03	-1.1376E-02	-5.7523E-03	2.0108E-06	5.0552E-06

In the 5th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 14 below are the same as those stated in the 1st embodiment with corresponding values for the 5th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 12 and Table 13 and satisfy the conditions stated in Table 14.

TABLE 14

Embodiment 5	
f [mm]	4.13
Fno	2.20
HFOV [deg.]	36.4
V5/(V3 + V4)	1.19
CT2/(T12 + T23)	3.04
CT5/CT6	1.27
CT1/(Sag12)	1.21
R1/f	0.36
f/R3	2.21
R12/f	0.23

TABLE 14-continued

Embodiment 5	
f/f2 + f/f3	2.90
f/f5 + f/f6	3.84

6th Embodiment

FIG. 6A is a schematic view of an image capturing device according to the 6th embodiment of the present disclosure. FIG. 6B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 6th embodiment.

In FIG. 6A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 690. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 610, a second lens element 620, a third lens element 630, a fourth lens element 640, a fifth lens element 650, and a sixth lens

23

element **660**, wherein the image capturing optical lens assembly has a total of six lens elements (**610-660**) with refractive power.

The first lens element **610** with positive refractive power has an object-side surface **611** being convex in a paraxial region thereof and an image-side surface **612** being concave in a paraxial region thereof, which are both aspheric, and the first lens element **610** is made of plastic material.

The second lens element **620** with positive refractive power has an object-side surface **621** being convex in a paraxial region thereof and an image-side surface **622** being convex in a paraxial region thereof, which are both aspheric, and the second lens element **620** is made of plastic material.

The third lens element **630** with negative refractive power has an object-side surface **631** being convex in a paraxial region thereof and an image-side surface **632** being concave in a paraxial region thereof, which are both aspheric, and the third lens element **630** is made of plastic material. Furthermore, the object-side surface **631** of the third lens element **630** has at least one inflection point.

The fourth lens element **640** with positive refractive power has an object-side surface **641** being convex in a paraxial region thereof and an image-side surface **642** being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element **640** is made of plastic material. Furthermore, the image-side surface **642** of the fourth lens element **640** has at least one convex shape in an off-axis region thereof.

24

The fifth lens element **650** with positive refractive power has an object-side surface **651** being concave in a paraxial region thereof and an image-side surface **652** being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element **650** is made of plastic material.

The sixth lens element **660** with negative refractive power has an object-side surface **661** being concave in a paraxial region thereof and an image-side surface **662** being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element **660** is made of plastic material. Furthermore, the image-side surface **662** of the sixth lens element **660** has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop **600** and an IR-cut filter **670**. The aperture stop **600** is disposed between the first lens element **610** and the second lens element **620**. The IR-cut filter **670** is made of glass and located between the sixth lens element **660** and an image surface **680**, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor **690** is disposed on or near the image surface **680** of the image capturing optical lens assembly.

The detailed optical data of the sixth embodiment are shown in TABLE 15, and the aspheric surface data are shown in TABLE 16, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 15

(Embodiment 6)								
f = 4.03 mm, Fno = 2.15, HFOV = 37.5 deg.								
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length	
0	Object	Plano	Infinity					
1	Lens 1	1.700 ASP	0.335	Plastic	1.544	55.9	20.58	
2		1.865 ASP	0.303					
3	Ape. Stop	Plano	-0.047					
4	Lens 2	1.901 ASP	0.534	Plastic	1.544	55.9	2.90	
5		-8.295 ASP	0.050					
6	Lens 3	102.239 ASP	0.265	Plastic	1.639	23.5	-4.00	
7		2.492 ASP	0.403					
8	Lens 4	4.782 ASP	0.333	Plastic	1.639	23.5	33.21	
9		6.004 ASP	0.314					
10	Lens 5	-3.233 ASP	0.678	Plastic	1.544	55.9	1.98	
11		-0.866 ASP	0.050					
12	Lens 6	-8.125 ASP	0.611	Plastic	1.544	55.9	-1.88	
13		1.199 ASP	0.750					
14	IR-cut filter	Plano	0.300	Glass	1.517	64.2		
15		Plano	0.311					
16	Image Surface	Plano	—					

Note:

Reference wavelength is d-line 587.6 nm

TABLE 16

Aspheric Coefficients						
Surface #	1	2	4	5	6	7
k=	-3.2057E-01	-5.8285E-01	-4.5187E+00	-9.0000E+01	-9.0000E+01	2.9881E+00
A4=	-2.6126E-02	-5.5272E-02	4.9583E-02	9.0479E-02	9.2170E-02	-2.3305E-02
A6=	-6.0019E-03	-3.1834E-02	-4.9241E-02	-3.0985E-01	-3.0386E-01	-4.1487E-02
A8=	-1.2882E-02	3.1790E-03	-1.8385E-02	3.3010E-01	3.9526E-01	6.9733E-02
A10=	6.7825E-03		1.6460E-02	-1.3335E-01	-1.7932E-01	-4.0368E-02
A12=	-3.9320E-03				5.2719E-03	-1.1145E-03

TABLE 16-continued

Aspheric Coefficients						
Surface #	8	9	10	11	12	13
k=	1.1940E+01	-2.0465E+01	-1.6368E+00	-2.5106E+00	9.2904E+00	-8.8205E+00
A4=	-7.1430E-02	-5.6625E-02	-1.0770E-01	2.4797E-02	-1.4956E-02	-5.4797E-02
A6=	-8.5848E-03	3.2675E-02	-1.3003E-02	-1.9988E-01	3.9582E-02	2.2760E-02
A8=	-1.5609E-02	-5.6250E-02	1.7688E-01	2.7655E-01	-2.2307E-02	-7.0516E-03
A10=	-3.1221E-03	3.9067E-02	-1.3908E-01	-1.4230E-01	5.6135E-03	1.2827E-03
A12=	4.7077E-04	-1.7340E-02	4.3536E-02	3.2856E-02	-6.5853E-04	-1.4239E-04
A14=		3.5450E-03	-5.1505E-03	-2.8977E-03	3.0064E-05	7.2813E-06

In the 6th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 17 below are the same as those stated in the 1st embodiment with corresponding values for the 6th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 15 and Table 16 and satisfy the conditions stated in Table 17.

TABLE 17

6 th Embodiment	
f [mm]	4.03
Fno	2.15
HFOV [deg.]	37.5
V5/(V3 + V4)	1.19
CT2/(T12 + T23)	1.75
CT5/CT6	1.11
CT1/ Sag12	1.76
R1/f	0.42
f/R3	2.12
R12/f	0.30
f/f2 + f/f3	2.40
f/f5 + f/f6	4.18

7th Embodiment

FIG. 7A is a schematic view of an image capturing device according to the 7th embodiment of the present disclosure. FIG. 7B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 7th embodiment.

In FIG. 7A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 790. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 710, a second lens element 720, a third lens element 730, a fourth lens element 740, a fifth lens element 750, and a sixth lens element 760, wherein the image capturing optical lens assembly has a total of six lens elements (710-760) with refractive power.

The first lens element 710 with positive refractive power has an object-side surface 711 being convex in a paraxial region thereof and an image-side surface 712 being concave

in a paraxial region thereof, which are both aspheric, and the first lens element 710 is made of plastic material.

The second lens element 720 with positive refractive power has an object-side surface 721 being convex in a paraxial region thereof and an image-side surface 722 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 720 is made of plastic material.

The third lens element 730 with negative refractive power has an object-side surface 731 being concave in a paraxial region thereof and an image-side surface 732 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 730 is made of plastic material. Furthermore, the object-side surface 731 of the third lens element 730 has at least one inflection point.

The fourth lens element 740 with positive refractive power has an object-side surface 741 being convex in a paraxial region thereof and an image-side surface 742 being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element 740 is made of plastic material. Furthermore, the image-side surface 742 of the fourth lens element 740 has at least one convex shape in an off-axis region thereof.

The fifth lens element 750 with positive refractive power has an object-side surface 751 being concave in a paraxial region thereof and an image-side surface 752 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 750 is made of plastic material.

The sixth lens element 760 with negative refractive power has an object-side surface 761 being convex in a paraxial region thereof and an image-side surface 762 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 760 is made of plastic material.

The image capturing optical lens assembly further includes an aperture stop 700 and an IR-cut filter 770. The aperture stop 700 is disposed between an imaged object and the first lens element 710. The IR-cut filter 770 is made of glass and located between the sixth lens element 760 and an image surface 780, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 790 is disposed on or near the image surface 780 of the image capturing optical lens assembly.

The detailed optical data of the seventh embodiment are shown in TABLE 18, and the aspheric surface data are shown in TABLE 19, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 18

(Embodiment 7)							
f = 3.68 mm, Fno = 2.08, HFOV = 39.3 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.173				
2	Lens 1	1.899 ASP	0.300	Plastic	1.544	55.9	122.76
3		1.846 ASP	0.116				
4	Lens 2	2.300 ASP	0.554	Plastic	1.544	55.9	2.78
5		-4.035 ASP	0.081				
6	Lens 3	-38.337 ASP	0.240	Plastic	1.633	23.4	-4.10
7		2.790 ASP	0.286				
8	Lens 4	3.425 ASP	0.258	Plastic	1.633	23.4	1256.25
9		3.340 ASP	0.364				
10	Lens 5	-9.692 ASP	0.867	Plastic	1.544	55.9	1.85
11		-0.942 ASP	0.050				
12	Lens 6	2.933 ASP	0.458	Plastic	1.530	55.8	-1.94
13		0.720 ASP	0.750				
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	
15		Plano	0.517				
16	Image Surface	Plano	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 19

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-9.5669E-01	-2.2189E+00	-9.9136E+00	-5.9386E+01	9.0000E+01	3.4245E+00
A4=	-3.9422E-02	-9.3177E-02	1.0236E-02	-1.3459E-02	1.2391E-01	-8.7816E-03
A6=	3.6432E-03	2.3632E-02	-6.0008E-02	-1.9883E-01	-4.3066E-01	-1.2269E-01
A8=	-5.6239E-03	-6.4246E-02	-3.4128E-02	1.7984E-01	4.4249E-01	1.0769E-01
A10=	-1.5854E-02	1.5019E-02	1.8394E-02	-5.9817E-02	-2.0518E-01	-5.6384E-02
A12=	1.5100E-04	-7.1739E-04	-3.5962E-04	3.8510E-04	4.0032E-02	1.0816E-02
A14=	-2.9618E-12	4.2165E-12	-8.4906E-04	3.1939E-04	5.3024E-05	5.6840E-06
A16=	-3.0325E-13	5.8639E-13	-1.3039E-12	2.4245E-12	1.5149E-04	-2.1479E-05
Surface #	8	9	10	11	12	13
k=	-4.7361E+01	-2.0709E+01	-4.6097E+00	-5.6391E+00	1.4561E-01	-4.5463E+00
A4=	-5.3418E-02	-9.5577E-02	7.8529E-02	-1.0613E-01	-2.1438E-01	-8.9370E-02
A6=	-2.5685E-02	2.3691E-02	-1.2547E-01	1.2850E-01	7.8166E-02	3.4161E-02
A8=	6.2631E-03	-1.9846E-02	1.3612E-01	-1.2213E-01	-2.2919E-02	-1.0138E-02
A10=	1.1778E-02	-1.2449E-02	-9.6794E-02	9.4158E-02	8.2159E-03	1.9611E-03
A12=	-5.2422E-03	2.2092E-02	3.6505E-02	-4.0036E-02	-2.2675E-03	-2.3819E-04
A14=	-2.5121E-06	-5.6189E-03	-5.4061E-03	8.2931E-03	3.2862E-04	1.6232E-05
A16=	-6.5874E-06	-9.2016E-06	-1.4484E-04	-6.6813E-04	-1.8730E-05	-4.4817E-07

In the 7th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 20 below are the same as those stated in the 1st embodiment with corresponding values for the 7th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 18 and Table 19 and satisfy the conditions stated in Table 20.

TABLE 20

7 th Embodiment	
f [mm]	3.68
Fno	2.08
HFOV [deg.]	39.3
V5/(V3 + V4)	1.19
CT2/(T12 + T23)	2.81
CT5/CT6	1.89
CT1/Sag12	2.23

TABLE 20-continued

7 th Embodiment	
R1/f	0.52
f/R3	1.60
R12/f	0.20
f/f2 + f/f3	2.22
f/f5 + f/f6	3.89

8th Embodiment

FIG. 8A is a schematic view of an image capturing device according to the 8th embodiment of the present disclosure. FIG. 8B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 8th embodiment.

In FIG. 8A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein

labeled) of the present disclosure and an image sensor **890**. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element **810**, a second lens element **820**, a third lens element **830**, a fourth lens element **840**, a fifth lens element **850**, and a sixth lens element **860**, wherein the image capturing optical lens assembly has a total of six lens elements (**810-860**) with refractive power.

The first lens element **810** with negative refractive power has an object-side surface **811** being convex in a paraxial region thereof and an image-side surface **812** being concave in a paraxial region thereof, which are both aspheric, and the first lens element **810** is made of plastic material.

The second lens element **820** with positive refractive power has an object-side surface **821** being convex in a paraxial region thereof and an image-side surface **822** being concave in a paraxial region thereof, which are both aspheric, and the second lens element **820** is made of plastic material.

The third lens element **830** with negative refractive power has an object-side surface **831** being concave in a paraxial region thereof and an image-side surface **832** being concave in a paraxial region thereof, which are both aspheric, and the third lens element **830** is made of plastic material. Furthermore, the object-side surface **831** of the third lens element **830** has at least one inflection point.

The fourth lens element **840** with positive refractive power has an object-side surface **841** being convex in a paraxial region thereof and an image-side surface **842** being concave in a paraxial region thereof, which are both

aspheric, and the fourth lens element **840** is made of plastic material. Furthermore, the image-side surface **842** of the fourth lens element **840** has at least one convex shape in an off-axis region thereof.

The fifth lens element **850** with positive refractive power has an object-side surface **851** being concave in a paraxial region thereof and an image-side surface **852** being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element **850** is made of plastic material.

The sixth lens element **860** with negative refractive power has an object-side surface **861** being convex in a paraxial region thereof and an image-side surface **862** being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element **860** is made of plastic material. Furthermore, the image-side surface **862** of the sixth lens element **860** has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop **800** and an IR-cut filter **870**. The aperture stop **800** is disposed between an imaged object and the first lens element **810**. The IR-cut filter **870** is made of glass and located between the sixth lens element **860** and an image surface **880**, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor **890** is disposed on or near the image surface **880** of the image capturing optical lens assembly.

The detailed optical data of the eighth embodiment are shown in TABLE 21, and the aspheric surface data are shown in TABLE 22, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 21

(Embodiment 8)							
f = 3.92 mm, Fno = 2.28, HFOV = 38.2 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.145				
2	Lens 1	2.105 ASP	0.300	Plastic	1.544	55.9	-37.93
3		1.814 ASP	0.078				
4	Lens 2	1.550 ASP	0.437	Plastic	1.544	55.9	2.89
5		100.000 ASP	0.114				
6	Lens 3	-17.344 ASP	0.240	Plastic	1.640	23.5	-4.67
7		3.634 ASP	0.228				
8	Lens 4	3.479 ASP	0.422	Plastic	1.544	55.9	17.79
9		5.198 ASP	0.348				
10	Lens 5	-39.154 ASP	1.084	Plastic	1.544	55.9	2.32
11		-1.235 ASP	0.050				
12	Lens 6	3.049 ASP	0.457	Plastic	1.544	55.9	-2.25
13		0.828 ASP	0.500				
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	
15		Plano	0.724				
16	Image Surface	-66.000	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 22

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-1.4899E+00	-9.8839E+00	-6.8085E+00	9.0000E+01	-9.0000E+01	6.1144E+00
A4=	-4.5205E-02	-1.2247E-01	-3.2748E-02	4.9659E-02	1.3790E-01	5.3820E-02
A6=	5.1197E-02	6.0345E-02	-7.3451E-02	-2.4952E-01	-3.3291E-01	-1.0592E-01
A8=	-4.0943E-02	-6.6411E-02	1.2284E-03	2.1260E-01	4.2570E-01	1.1785E-01

TABLE 22-continued

Aspheric Coefficients						
A10=	-8.6014E-03	-5.0626E-03	-3.0791E-02	-8.5375E-02	-2.3612E-01	-5.9685E-02
A12=	1.5100E-04	-7.1739E-04	-3.5962E-04	3.8509E-04	4.7718E-02	1.1319E-02
A14=	-1.2201E-12	7.0003E-12	-8.4906E-04	3.1939E-04	5.3133E-05	5.2256E-06
A16=	-2.2709E-13	9.4712E-13	-2.7109E-12	4.6755E-12	1.5149E-04	-2.1479E-05
Surface #	8	9	10	11	12	13
k=	-4.6730E+01	-1.5373E+01	9.0000E+01	-7.1106E+00	4.9048E-01	-4.5643E+00
A4=	-5.4516E-03	-1.0078E-01	4.2271E-02	-2.3773E-02	-2.2898E-01	-1.1128E-01
A6=	-3.1108E-02	3.0750E-02	-1.2529E-01	-1.9586E-02	6.3251E-02	5.3012E-02
A8=	6.8351E-03	-1.5314E-02	1.3527E-01	3.1412E-02	2.0475E-03	-1.9274E-02
A10=	1.7495E-02	-1.4654E-02	-9.7150E-02	-9.8738E-03	-5.6386E-03	4.7017E-03
A12=	-5.2383E-03	2.1011E-02	3.6467E-02	2.4407E-04	1.4705E-03	-7.3304E-04
A14=	-2.7941E-06	-5.2369E-03	-5.2777E-03	3.4269E-04	-1.6603E-04	6.4713E-05
A16=	-6.5874E-06	-1.0560E-05	-1.6489E-04	-4.3067E-05	6.9222E-06	-2.4059E-06

In the 8th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 23 below are the same as those stated in the 1st embodiment with corresponding values for the 8th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 21 and Table 22 and satisfy the conditions stated in Table 23.

TABLE 23

8 th Embodiment	
f [mm]	3.92
Fno	2.28
HFOV [deg.]	38.2
V5/(V3 + V4)	0.70
CT2/(T12 + T23)	2.28
CT5/CT6	2.37
CT1/(Sag12)	3.96
R1/f	0.54
f/R3	2.53
R12/f	0.21
f/f2 + f/f3	2.20
f/f5 + f/f6	3.43

9th Embodiment

FIG. 9A is a schematic view of an image capturing device according to the 9th embodiment of the present disclosure. FIG. 9B shows, in order from left to right, longitudinal spherical aberration curves, astigmatic field curves and a distortion curve of the image capturing device according to the 9th embodiment.

In FIG. 9A, the image capturing device includes an image capturing optical lens assembly (not otherwise herein labeled) of the present disclosure and an image sensor 990. The image capturing optical lens assembly includes, in order from an object side to an image side, a first lens element 910, a second lens element 920, a third lens element 930, a fourth lens element 940, a fifth lens element 950, and a sixth lens element 960, wherein the image capturing optical lens assembly has a total of six lens elements (910-960) with refractive power.

The first lens element 910 with negative refractive power has an object-side surface 911 being convex in a paraxial region thereof and an image-side surface 912 being concave in a paraxial region thereof, which are both aspheric, and the first lens element 910 is made of plastic material.

The second lens element 920 with positive refractive power has an object-side surface 921 being convex in a paraxial region thereof and an image-side surface 922 being convex in a paraxial region thereof, which are both aspheric, and the second lens element 920 is made of plastic material.

The third lens element 930 with negative refractive power has an object-side surface 931 being convex in a paraxial region thereof and an image-side surface 932 being concave in a paraxial region thereof, which are both aspheric, and the third lens element 930 is made of plastic material. Furthermore, the object-side surface 931 of the third lens element 930 has at least one inflection point.

The fourth lens element 940 with negative refractive power has an object-side surface 941 being convex in a paraxial region thereof and an image-side surface 942 being concave in a paraxial region thereof, which are both aspheric, and the fourth lens element 940 is made of plastic material. Furthermore, the image-side surface 942 of the fourth lens element 940 has at least one convex shape in an off-axis region thereof.

The fifth lens element 950 with positive refractive power has an object-side surface 951 being plano in a paraxial region thereof and an image-side surface 952 being convex in a paraxial region thereof, which are both aspheric, and the fifth lens element 950 is made of plastic material.

The sixth lens element 960 with negative refractive power has an object-side surface 961 being convex in a paraxial region thereof and an image-side surface 962 being concave in a paraxial region thereof, which are both aspheric, and the sixth lens element 960 is made of plastic material. Furthermore, the image-side surface 962 of the sixth lens element 960 has at least one convex shape in an off-axis region thereof.

The image capturing optical lens assembly further includes an aperture stop 900 and an IR-cut filter 970. The aperture stop 900 is disposed between an imaged object and the first lens element 910. The IR-cut filter 970 is made of glass and located between the sixth lens element 960 and an image surface 980, and will not affect the focal length of the image capturing optical lens assembly.

The image sensor 990 is disposed on or near the image surface 980 of the image capturing optical lens assembly.

The detailed optical data of the ninth embodiment are shown in TABLE 24, and the aspheric surface data are shown in TABLE 25, wherein the units of the curvature radius, the thickness and the focal length are expressed in mm, and HFOV is half of the maximal field of view.

TABLE 24

(Embodiment 9)							
f = 3.62 mm, Fno = 1.98, HFOV = 40.2 deg.							
Surface #		Curvature Radius	Thickness	Material	Index	Abbe #	Focal Length
0	Object	Plano	Infinity				
1	Ape. Stop	Plano	-0.180				
2	Lens 1	1.747 ASP	0.260	Plastic	1.633	23.4	-17.23
3		1.419 ASP	0.117				
4	Lens 2	2.225 ASP	0.622	Plastic	1.544	55.9	2.86
5		-4.663 ASP	0.088				
6	Lens 3	4.938 ASP	0.250	Plastic	1.633	23.4	-7.00
7		2.289 ASP	0.306				
8	Lens 4	5.050 ASP	0.325	Plastic	1.583	30.2	-22.24
9		3.549 ASP	0.389				
10	Lens 5	∞ ASP	0.729	Plastic	1.544	55.9	2.13
11		-1.157 ASP	0.053				
12	Lens 6	1.924 ASP	0.449	Plastic	1.544	55.9	-2.51
13		0.733 ASP	0.800				
14	IR-cut filter	Plano	0.210	Glass	1.517	64.2	
15		Plano	0.485				
16	Image Surface	Plano	—				

Note:

Reference wavelength is d-line 587.6 nm

TABLE 25

Aspheric Coefficients						
Surface #	2	3	4	5	6	7
k=	-1.5406E+00	-1.4741E+00	-6.9574E+00	-9.0000E+01	-7.7354E+01	1.4291E+00
A4=	-5.9518E-02	-8.4009E-02	3.8285E-02	-7.5145E-02	1.0508E-01	-2.5999E-02
A6=	5.0380E-03	1.3010E-04	-7.6756E-02	-1.0269E-01	-4.1895E-01	-1.4113E-01
A8=	-2.9733E-03	1.3313E-02	4.9236E-02	1.3593E-01	4.4191E-01	1.2966E-01
A10=	-1.3711E-02	-2.4812E-02	-8.7498E-03	-3.4919E-02	-1.8266E-01	-4.2303E-02
A12=	-4.7003E-06	-1.8784E-06	-7.1207E-07	1.4858E-06	2.0534E-02	8.0679E-04
A14=	-4.8754E-07	-1.2373E-06	4.9004E-07	2.0374E-06	-3.2960E-07	-1.5009E-04
A16=	-3.8986E-08	-2.5634E-08	-2.4542E-07	5.7090E-07	-6.8212E-07	4.5550E-07
Surface #	8	9	10	11	12	13
k=	-9.0000E+01	-7.7593E+00	0.0000E+00	-5.9615E+00	-4.6525E-01	-3.6454E+00
A4=	-7.7485E-02	-1.4523E-01	9.3359E-02	-9.2801E-03	-2.5153E-01	-1.1884E-01
A6=	-2.2953E-02	2.1720E-02	-8.8561E-02	2.0840E-02	6.2415E-02	5.1561E-02
A8=	1.1669E-01	5.1752E-02	4.2159E-02	-1.7276E-02	-5.0257E-03	-1.6872E-02
A10=	-1.6451E-01	-1.0054E-01	-4.9625E-03	2.2422E-02	2.1098E-03	3.8037E-03
A12=	1.3794E-01	7.7829E-02	-8.1567E-03	-1.1801E-02	-1.3193E-03	-5.5778E-04
A14=	-5.4488E-02	-2.4154E-02	4.6838E-03	2.4895E-03	2.6217E-04	4.6576E-05
A16=	7.4997E-03	2.3888E-03	-8.5860E-04	-1.8221E-04	-1.7122E-05	-1.6371E-06

In the 9th embodiment, the equation of the aspheric surface profiles of the aforementioned lens elements is the same as the equation of the 1st embodiment. Also, the definitions of these parameters shown in Table 26 below are the same as those stated in the 1st embodiment with corresponding values for the 9th embodiment, so an explanation in this regard will not be provided again.

Moreover, these parameters can be calculated from Table 24 and Table 25 and satisfy the conditions stated in Table 26.

TABLE 26

9 th Embodiment	
f [mm]	3.62
Fno	1.98
HFOV [deg.]	40.2
V5/(V3 + V4)	1.04
CT2/(T12 + T23)	3.03
CT5/CT6	1.62
CT1/Sag12	1.08

TABLE 26-continued

9 th Embodiment	
R1/f	0.48
f/R3	1.63
R12/f	0.20
f/f2 + f/f3	1.78
f/f5 + f/f6	3.14

The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. It is to be noted that TABLES 1-26 show different data of the different embodiments; however, the data of the different embodiments are obtained from experiments. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, to thereby enable others skilled in the art to best utilize the disclosure and various embodiments with various modifications as are suited to the particular use contemplated. The embodiments depicted above and the appended drawings are

35

exemplary and are not intended to be exhaustive or to limit the scope of the present disclosure to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings.

What is claimed is:

1. An image capturing optical lens assembly comprising in order from an object side to an image side:

- a first lens element having an image-side surface being concave in a paraxial region thereof;
- a second lens element;
- a third lens element;
- a fourth lens element having an image-side surface being concave in a paraxial region thereof;
- a fifth lens element with positive refractive power; and
- a sixth lens element having an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof, a curvature radius of an object-side surface of the first lens element and a curvature radius of an image-side surface of the third lens element have the same sign, an absolute value of a curvature radius of an object-side surface of the second lens element is smaller than an absolute value of a curvature radius of an object-side surface of the fourth lens element, an axial distance between the fifth lens element and the sixth lens element is smaller than an axial distance between the first lens element and the second lens element;

wherein a total number of lens elements having refractive power of the image capturing optical lens assembly is six, an f-number of the image capturing optical lens assembly is F_{no} , a central thickness of the fifth lens element is $CT5$, a central thickness of the sixth lens element is $CT6$, and the following conditions are satisfied:

$$1.6 < F_{no} \leq 2.28; \text{ and}$$

$$1.62 \leq CT5/CT6.$$

2. The image capturing optical lens assembly of claim 1, wherein the second lens element has positive refractive power and an object-side surface being convex in a paraxial region thereof, the fifth lens element has an image-side surface being convex in a paraxial region thereof, and an aperture stop is positioned disposed between an imaged object and the third lens element.

3. The image capturing optical lens assembly of claim 1, wherein the first lens element has negative refractive power and the sixth lens element has negative refractive power.

4. The image capturing optical lens assembly of claim 1, wherein a focal length of the image capturing optical lens assembly is f , a focal length of the fifth lens element is $f5$, a focal length of the sixth lens element is $f6$, and the following condition is satisfied:

$$1.50 < |f/f5| + |f/f6|.$$

5. The image capturing optical lens assembly of claim 1, wherein a curvature radius of the image-side surface of the sixth lens element is $R12$, a focal length of the image capturing optical lens assembly is f , and the following condition is satisfied:

$$0 < R12/f < 0.40.$$

6. The image capturing optical lens assembly of claim 1, wherein a central thickness of the first lens element is $CT1$, a distance in parallel with an optical axis from an axial vertex on the image-side surface of the first lens element to a maximum effective radius position on the image-side

36

surface of the first lens element is $Sag12$, the central thickness of the fifth lens element is $CT5$, the central thickness of the sixth lens element is $CT6$, and the following conditions are satisfied:

$$CT1/|Sag12| < 2.5; \text{ and}$$

$$1.89 \leq CT5/CT6.$$

7. The image capturing optical lens assembly of claim 1, wherein an absolute value of a focal length of the third lens element is smaller than an absolute value of a focal length of the fourth lens element.

8. The image capturing optical lens assembly of claim 1, wherein an axial distance between the first lens element and the second lens element is smaller than a central thickness of the first lens element.

9. The image capturing optical lens assembly of claim 1, wherein an absolute value of a curvature radius of the object-side surface of the sixth lens element is smaller than an absolute value of a curvature radius of an image-side surface of the second lens element.

10. The image capturing optical lens assembly of claim 1, wherein a focal length of the first lens element and a focal length of the third lens element have different signs.

11. The image capturing optical lens assembly of claim 1, wherein the axial distance between the fifth lens element and the sixth lens element is smaller than an axial distance between the second lens element and the third lens element.

12. An image capturing device, comprising the image capturing optical lens assembly of claim 1; and an image sensor, wherein the image sensor is disposed on an image surface of the image capturing optical lens assembly.

13. An electronic device, comprising the image capturing device of claim 12.

14. An image capturing optical lens assembly comprising in order from an object side to an image side:

- a first lens element having negative refractive power and an image-side surface being concave in a paraxial region thereof;
- a second lens element;
- a third lens element;
- a fourth lens element;
- a fifth lens element; and
- a sixth lens element having an object-side surface being convex in a paraxial region thereof and an image-side surface being concave in a paraxial region thereof, an absolute value of a focal length of the third lens element is smaller than an absolute value of a focal length of the fourth lens element, an absolute value of a curvature radius of an image-side surface of the third lens element is smaller than an absolute value of a curvature radius of an object-side surface of the third lens element, an axial distance between the fifth lens element and the sixth lens element is smaller than an axial distance between the first lens element and the second lens element;

wherein a total number of lens elements having refractive power of the image capturing optical lens assembly is six, an f-number of the image capturing optical lens assembly is F_{no} , a focal length of the image capturing optical lens assembly is f , a focal length of the fifth lens element is $f5$, a focal length of the sixth lens element is $f6$, and the following conditions are satisfied:

$$1.6 < F_{no} \leq 2.28; \text{ and}$$

$$1.50 < |f/f5| + |f/f6|.$$

37

15. The image capturing optical lens assembly of claim 14, wherein the second lens element has positive refractive power, the fifth lens element has positive refractive power, the sixth lens element has negative refractive power, and an aperture stop is disposed between an imaged object and the third lens element.

16. The image capturing optical lens assembly of claim 14, wherein the second lens element has an object-side surface being convex in a paraxial region thereof and the fifth lens element has an image-side surface being convex in a paraxial region thereof.

17. The image capturing optical lens assembly of claim 14, wherein a curvature radius of the image-side surface of the sixth lens element is R_{12} , the focal length of the image capturing optical lens assembly is f , and the following condition is satisfied:

$$0 < R_{12}/f < 0.40.$$

18. The image capturing optical lens assembly of claim 14, wherein a central thickness of the fifth lens element is CT_5 , a central thickness of the sixth lens element is CT_6 , and the following condition is satisfied:

$$0.80 < CT_5/CT_6.$$

19. The image capturing optical lens assembly of claim 18, wherein the central thickness of the fifth lens element is CT_5 , the central thickness of the sixth lens element is CT_6 , and the following condition is satisfied:

$$1.27 \leq CT_5/CT_6.$$

20. The image capturing optical lens assembly of claim 14, wherein a central thickness of the first lens element is

38

CT_1 , a distance in parallel with an optical axis from an axial vertex on the image-side surface of the first lens element to a maximum effective radius position on the image-side surface of the first lens element is Sag_{12} , and the following condition is satisfied:

$$CT_1/|Sag_{12}| < 2.5.$$

21. The image capturing optical lens assembly of claim 14, wherein the axial distance between the first lens element and the second lens element is smaller than a central thickness of the first lens element.

22. The image capturing optical lens assembly of claim 14, wherein an absolute value of a curvature radius of an object-side surface of the second lens element is smaller than an absolute value of a curvature radius of an object-side surface of the fourth lens element, and an absolute value of a curvature radius of the object-side surface of the sixth lens element is smaller than an absolute value of a curvature radius of an image-side surface of the second lens element.

23. The image capturing optical lens assembly of claim 14, wherein the fourth lens element has an image-side surface being concave in a paraxial region thereof.

24. An image capturing device, comprising the image capturing optical lens assembly of claim 14; and an image sensor, wherein the image sensor is disposed on an image surface of the image capturing optical lens assembly.

25. An electronic device, comprising the image capturing device of claim 24.

* * * * *