

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399462
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Monferrer; Bernat et al.

Remote control device for a horological movement of a watch and watch comprising said control device

Abstract

A remote control device for a horological movement of a watch wherein the remote control device includes an input control member intended to be acted on by a user and kinematically connected, with a connecting member, to an output control member intended to act on the horological movement of the watch, the connecting member being intended to be arranged such that it can rotate about the horological movement, and being configured such that it is driven in rotation by the input control member when the latter is acted upon, and such that it causes the output control member to move during this rotation.

Inventors:	Monferrer; Bernat (St-Prex, CH), Denoreaz; Steven (Bellefontaine, FR)
Applicant:	Harry Winston SA (Plan-les-Ouates, CH)
Family ID:	1000008781858
Assignee:	Harry Winston SA (Plan-les-Ouates, CH)
Appl. No.:	18/177282
Filed:	March 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230315016 A1	Oct. 05, 2023

Foreign Application Priority Data

EP	22165358	Mar. 30, 2022
----	----------	---------------

Publication Classification

Int. Cl.: G04B3/04 (20060101)

U.S. Cl.:

CPC G04B3/046 (20130101);

Field of Classification Search

CPC: G04B (3/046); G04B (37/066); G04B (27/001); G04B (27/00); G04B (3/12); G04B (27/08); G04B (3/048); G04B (37/064); G04B (27/06); G04C (13/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4555185	12/1984	Vuilleumier	368/185	G04B 27/00
2007/0025191	12/2006	Pittet	368/319	G04B 27/04
2011/0216631	12/2010	Pittet	368/190	G04B 37/066
2018/0095425	12/2017	Vuille	N/A	N/A
2018/0314211	12/2017	Hurni	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
689 570	12/1998	CH	N/A
1 710 635	12/2005	EP	N/A
3 306 421	12/2017	EP	N/A
3 396 469	12/2017	EP	N/A
2018-189629	12/2017	JP	N/A

OTHER PUBLICATIONS

European Search Report issued Aug. 16, 2022 in European Application 22165358.7 filed on Mar. 30, 2022, 3 pages (with English Translation of Categories of cited documents). cited by applicant
Japanese Office Action issued Apr. 2, 2024 in Japanese Patent Application No. 2023-036216 (with English Translation), 10 pages. cited by applicant

Primary Examiner: Leon; Edwin A.

Attorney, Agent or Firm: Oblon, McClelland, Maier & Neustadt, L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to European Patent Application No. 22165358.7 filed on Mar. 30, 2022, the entire disclosure of which is hereby incorporated herein by reference.

TECHNICAL FIELD OF THE INVENTION

(2) The invention relates to the horological field, and concerns in particular a remote control device for a horological movement of a watch and a watch comprising said control device.

TECHNOLOGICAL BACKGROUND

- (3) A control member, such as a push-piece, a corrector, or a crown, etc., is arranged in a middle of a watch, typically facing a horological movement mechanism which it is intended to actuate once acted on by a user.
- (4) By way of example, the control members for a chronograph, striking mechanism, time zone change, or date correction, etc., are frequently arranged in the immediate vicinity of the mechanisms of the horological movement that they are intended to actuate.
- (5) Thus, the architecture of the horological movements is often determined by the layout of the one or more control members in the middle, or vice-versa.
- (6) However, in some cases, the arrangement of the control members remotely from the mechanisms they are intended to actuate can be sought. For example, in order to reduce the development and production costs of a watch, it can be of particular interest to design a watch with a horological movement that has already been produced and with a middle that has also already been produced.
- (7) One of the solutions developed to meet this need is described in the Swiss patent document No. 689570. This solution takes the form of a control device including a set of levers for arranging the control member remotely from the mechanism to be actuated.
- (8) However, this solution has the drawback of significantly increasing the dimensions of the watch case in which it is applied. Moreover, it only allows the control member to be offset from the mechanism it is intended to actuate within limits.
- (9) Another drawback of the existing solutions is that the design thereof must be significantly adapted for each scenario, in particular as a function of the dimensions and geometry of the middle, and as a function of the distance between the control member and the mechanism it is intended to actuate.

SUMMARY OF THE INVENTION

- (10) The invention overcomes the aforementioned drawbacks by providing a remote control device for a horological movement allowing a control member to actuate a mechanism of the horological movement without their position relative to one another being a constraint.
- (11) More specifically, the present invention allows a control member to be kinematically connected with a mechanism of a horological movement to be actuated, regardless of the respective positions thereof, relative to one another, and regardless of the dimensions and geometry of the middle.
- (12) To this end, the present invention relates to a remote control device for a horological movement of a watch including an input control member intended to be acted on by a user and kinematically connected, by means of a connecting member, to an output control member intended to act on the horological movement of said watch. The connecting member is intended to be arranged such that it can rotate about the horological movement and being configured such that it can be driven in rotation by the input control member when the latter is acted upon, and to cause the output control member to move during this rotation.
- (13) In specific embodiments, the invention can further include one or more of the following features, which must be considered singly or according to any combination technically possible.
- (14) In specific embodiments, the control device includes a support structure with which the input and output control members are integral, said support structure forming an annular recess receiving the connecting member.
- (15) In specific embodiments, the connecting member forms a ring.
- (16) In specific embodiments, the input control member includes an engagement profile configured to engage with a driven engagement element of the connecting member, so as to drive said connecting member such that it rotates when said input control member is acted upon.
- (17) In specific embodiments, the engagement profile and the driven engagement element are respectively shaped as complementary bevels.
- (18) In specific embodiments, the input control member is formed by a lever extending between a

first end by which it is attached to the support structure such that it can rotate, at a first end, said lever including, at a second end, the engagement profile.

(19) In specific embodiments, the input control member is arranged such that it can slide relative to the support structure and is configured to engage, via the engagement profile, with a transmission element attached to the support structure such that it can rotate and engaging with the connecting member, such that the sliding of said input control member causes the connecting member to rotate.

(20) In specific embodiments, the output control member includes an engagement profile configured to engage with a driving engagement element of the connecting member, such that the rotation of said connecting member causes said output control member to move.

(21) In specific embodiments, the output control member is formed by a lever attached to the support structure such that it can rotate, at a first end, said lever including a bevel at a second end, constituting the engagement profile, said output control member being intended to act on the horological movement via an internal flank opposite the engagement profile.

(22) In specific embodiments, the output control member is connected by a pivot link, on the one hand to the connecting member, and on the other hand to the support structure, said output control member including a bearing arm intended to be arranged such that it bears against a balance of the horological movement in order to perform a balance stop function when the input control member is acted upon.

(23) In specific embodiments, the driving engagement element is constituted by a catch.

(24) In specific embodiments, the control device comprises a spring connected to the connecting member and biased to move it into a rest position in which said connecting member is capable of engaging with the input control member.

(25) In specific embodiments, the control device includes a second input control member and a second output control member kinematically connected to one another via the connecting member and respectively configured to engage with a driven engagement member and with a driving engagement member, the input control members being configured such that, depending on which one is acted upon, the connecting member is driven in a different direction of rotation and causes one or the other output control member respectively to move.

(26) In specific embodiments, the connecting member comprises a locking element arranged to constitute a banking preventing one of the input control members from making any movement when the other is acted upon.

(27) In specific embodiments, the locking element is formed by a tooth extending between two bevelled radial flanks each constituting a driven engagement element, the tooth further comprising an outer flank connecting the radial flanks together and being arranged so as to constitute a banking preventing one of the input control members from making any movement, when the other is acted upon.

(28) According to another aspect, the present invention relates to a watch comprising a horological movement and a control device as described hereinabove.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Other features and advantages of the invention will become apparent upon reading the following detailed description given by way of a non-limiting example, and with reference to the accompanying drawings, in which:

(2) FIG. 1 diagrammatically shows a front view of a remote control device for a horological movement of a watch according to a preferred example embodiment of the invention;

(3) FIGS. 2 and 3 respectively diagrammatically show the control device of FIG. 1 in which an input control member is acted upon;

(4) FIG. 4 shows another example embodiment of the control device according to the invention;
(5) FIG. 5 shows the control device of FIG. 4 in which the control member is acted upon.

DETAILED DESCRIPTION OF THE INVENTION

(6) The present invention relates to a remote control device **10** for a horological movement **100** of a watch, as shown in FIGS. 1 to 5. It should be noted that the horological movement **100** is shown as a dashed line in the figures, and that only part of the watch is shown.

(7) The control device **10** includes at least one input control member **11** to be acted on by a user.

(8) As shown in FIGS. 1 to 5, the input control member **11** is kinematically connected, via a connecting member **13**, to an output control member **12** intended to act on the horological movement **100** of said watch.

(9) In the example embodiment shown in FIGS. 1 to 3, the control device **10** includes two input control members **11** and two output control members **12**, each of said input control members **11** being kinematically connected to an output control member **12**.

(10) Alternatively, in the example embodiment shown in FIGS. 4 and 5, the control device **10** includes a single input control member **11** and a single output control member **12**.

(11) For ease of reading, the invention is described hereinbelow in general terms, with a single input control member **11** and a single output control member **12**.

(12) As shown in FIGS. 1 to 3, the output control member **12** can be intended to engage with a horological component of the horological movement **100** via an actuator **101** of the horological movement **100**, such as a corrector, a push-piece, a lever, a yoke, or a wheel, etc., of the movement for performing a function of said horological movement **100**.

(13) In the example embodiment of the invention shown in FIGS. 4 and 5, the output control member **12** is intended to engage directly with a horological component of the horological movement **100**, such as a balance **102**. Such a function is thus a balance stop function, also referred to as a “stop-seconds” or “stop-balance”.

(14) In alternative embodiments of the invention, such a function can be a function of a chronograph, a date correction, a moon phase correction, or a tourbillon carriage or karussell stop function, etc.

(15) The output control member **12** is thus intended to be sandwiched between the horological movement **100** and the connecting member **13**, as shown in FIGS. 1 to 5.

(16) The connecting member **13** is intended to be arranged such that it can rotate about the horological movement **100** in a support structure, for example in a middle of a watch case (not visible in the figures). More specifically, the support structure forms an annular recess, such as a groove, intended to receive the connecting member **13**.

(17) The connecting member **13** preferably forms a closed ring. However, in other alternative embodiments of the invention, the connecting member **13** can form an open ring extending over an angular sector that depends on the angular distance between the input control member **11** and the output control member **12**.

(18) Advantageously, the connecting member **13** is configured so as to be driven in rotation by the input control member **11** when the latter is acted upon, and to cause the output control member **12** to move during this rotation.

(19) The connecting member **13** is defined between an inner peripheral wall **130** and an outer peripheral wall **131**, the output control member **12** being arranged at the inner peripheral wall **130**, within the connecting member **13**. All or part of the input control member **11** is arranged outside the connecting member **13**, as shown in FIGS. 1 to 5.

(20) The input control member **11** and output control member **12** are integral with the support structure.

(21) In particular, in the example embodiment shown in FIG. 1, the input control member **11** is formed by a lever attached to the support structure such that it can rotate, at a first end, said lever including, at a second end, an engagement profile **110**.

(22) The engagement profile **110** of the input control member **11** is bevel-shaped and is configured to directly engage with a driven engagement element **132** of the connecting member **13**, so as to drive said connecting member **13** such that it rotates when said input control member **11** is acted upon.

(23) In particular, as shown in FIG. 2 or FIG. 3, during the movement of the input control member **11**, when the latter is acted upon by a user, the engagement profile **110** thereof applies pressure to the driven engagement element **132** of the connecting member **13**, causing said connecting member **13** to pivot.

(24) The driven engagement element **132** of the connecting member **13** is constituted by a bevel with a shape complementary to that of the bevel shape of the input control member **11**.

(25) Moreover, the output control member **12** further includes an engagement profile **120** configured to engage with the connecting member **13**, and more particularly with a driving engagement element **133** thereof, such that the rotation of said connecting member **13** causes said output control member **12** to move.

(26) In particular, as shown in FIGS. 1 to 3, the engagement profile **120** of the output control member **12** is bevelled.

(27) In the example embodiment shown in FIGS. 1 to 3, the output control member **12** is formed by a lever attached to the support structure such that it can rotate, at a first end, said lever including, at a second end, the engagement profile **120**. Advantageously, the output control member **12** is intended to act on the horological movement **100** via an internal flank opposite the engagement profile **120**.

(28) Moreover, in the example embodiment of the invention shown in FIGS. 1 to 3, the driving engagement element **133** is constituted by a catch, for example formed by a catch driven into the connecting member **13**.

(29) In other alternative embodiments of the invention not shown in the figures, the driven engagement element **132** and the driving engagement element **133** can be formed either by hollows made in the inner peripheral wall **130** and/or outer peripheral wall **131** of the connecting member **13**, or by catches, bevels or any other protrusion extending from the connecting member **13**. It goes without saying that, depending on the alternative embodiment of the driven engagement element **132** or driving engagement element **133** considered, the input control member **11** or respectively the output control member **12** are arranged in planes which are parallel or coincident with the plane in which the connecting member **13** extends.

(30) Advantageously, the control device **10** can comprise a spring (not shown in the figures) connected to the connecting member **13** and biased to move it into a rest position in which said connecting member **13** is capable of engaging with the input control member **11**. The term 'spring' is understood to mean any component that is capable of undergoing elastic deformation.

(31) In particular, when the connecting member **13** is in the rest position, the input control member **11** is also in a rest position, i.e. it is not acted on by a user and is unmoving, and consequently, the output control member **12** is also in a rest position, as seen in FIG. 1.

(32) In order to hold it in its rest position, the input control member **11** can advantageously be stressed by a spring **111**, for example constituted by a resilient strip extending from the first end of said input control member **11** and arranged such that it abuts against the support structure.

(33) In the example embodiment shown in FIGS. 1 to 3, the input control members **11** are configured such that, depending on which one is acted upon, the connecting member **13** is driven in a different direction of rotation and causes one or the other output control member **12** to move respectively, as shown in FIGS. 2 and 3 respectively.

(34) The two input control members **11** are as described for the input control member **11** hereinabove and are preferably identical, as shown in FIGS. 1 to 3. Moreover, the input control members **11** are preferably arranged symmetrically to one another, along a diametrical plane of the connecting member **13**.

(35) Similarly, the two output control members **12** are as described for the output control member **12** hereinabove and are preferably identical, as shown in FIGS. **1** to **3**. Moreover, the output control members **12** are preferably arranged symmetrically to one another, along a diametrical plane of the connecting member **13**.

(36) In the example embodiment of the invention shown in FIGS. **1** to **3**, the connecting member **13** includes two driven engagement elements **132**, each intended to engage with one of the input control members **11**, and includes two driving engagement elements **133**, each intended to engage with one of the output control members **12**.

(37) As shown in FIGS. **1** to **3** in an example embodiment of the invention, the connecting member **13** preferably further comprises a locking element **134** arranged to constitute a banking preventing one of the input control members **11** from making any movement when the other is acted upon.

(38) In particular, the locking element **134** can advantageously be formed by a tooth extending between two bevelled radial flanks, each constituting a driven engagement element **132** intended to engage with one of the input control members **11**. The tooth further comprises an inner flank opposite an outer flank connecting the radial flanks together. The outer flank has a curved shape, as does the inner flank, and is arranged so as to constitute a banking preventing one of the input control members **11** from making any movement when the other is acted upon, as shown in FIGS. **2** and **3**.

(39) As can be seen in FIGS. **1** to **3**, with the bevelled radial flanks constituting the driven engagement elements **132**, the outer flank extends over an angular sector that is smaller than that over which the inner flank extends.

(40) In the example embodiment of the invention shown in FIGS. **4** and **5**, the input control member **11** is formed by a stem, in particular a setting stem, arranged such that it can slide relative to the support structure. The input control member **11** is arranged such that it extends through the connecting member **13** and opens out from the inner peripheral wall **130** via an inner portion and from the outer peripheral wall **131** via an outer portion, as shown in FIGS. **4** and **5**.

(41) The input control member **11** is intended to be acted on by a pulling force exerted by a user along the longitudinal axis thereof, from its outer portion, and is configured to engage from its inner portion, via a transmission element, with a driven engagement element **132** of the connecting member **13**.

(42) More particularly, the input control member **11** is configured to engage, via an engagement profile **110**, with a transmission yoke **14**. The transmission yoke **14** is attached to the support structure such that it can rotate and engages with the connecting member **13**, such that the sliding of said input control member **11** causes said transmission yoke **14** to rotate, which causes the connecting member **13** to rotate.

(43) Preferably, the engagement profile **110** has the form of a radial groove with which a first end of the transmission yoke **14** engages in the form of a finger. Moreover, the driven engagement element **132** engages in a pivotal connection with a second end of the transmission yoke **14**.

(44) In the example embodiment shown in FIGS. **4** and **5**, the output control member **12** further includes an engagement profile **120** configured to engage with a driving engagement element **133** of the connecting member **13**, such that the rotation of said connecting member **13** causes said output control member **12** to move.

(45) The output control member **12** is, in this example embodiment of the invention, formed by a lever that is attached, such that it can rotate, on the one hand, to the support structure and, on the other hand, to the connecting member **13**.

(46) In particular, as shown in FIGS. **4** and **5**, the engagement profile **120** and the driving engagement element **133** can be formed indifferently by a pin and a bore respectively. The pivot link between the output control member **12** and the support structure can advantageously be produced in a similar manner.

(47) In this example embodiment of the invention, the output control member **12** includes a bearing

arm **121** intended to be arranged such that it bears against the balance of the horological movement **100** in order to perform the balance stop function, when the input control member **11** is acted upon, as seen in FIG. 5.

(48) More generally, it should be noted that the implementations and embodiments considered above have been described by way of non-limiting examples, and that other alternatives are thus possible.

(49) In particular, the input control member **11** and/or the output control member **12** are formed by yokes in the present description, but can be formed by any type of control, such as pull-out pieces, push buttons, a crown, or a wheel, etc.

(50) Furthermore, the engagement profiles **110** and **120** can be formed by toothed portions meshing with the driven engagement element **132** and driving engagement element **133** respectively.

Claims

1. A remote control device for a horological movement of a watch comprising: an input control member intended to be acted on by a user and kinematically connected, with a connecting member, to an output control member intended to act on the horological movement of said watch, the connecting member being intended to be arranged such that the connecting member can rotate about the horological movement, and to cause the output control member to move during said rotation, wherein the input control member includes an engagement profile configured to engage with a driven engagement element of the connecting member, so as to drive said connecting member such that said connecting member rotates when said input control member is acted upon, the engagement profile and the driven engagement element being respectively shaped as complementary bevels, wherein the output control member comprises an engagement profile configured to engage with a driving engagement element of the connecting member, such that the rotation of said connecting member causes said output control member to move, and wherein the driven engagement element is disposed on a first portion of the connecting member and the driving engagement element is disposed on a second portion of the connecting member different than the first portion of the connecting member such that the driven engagement element and the driving engagement element both move with the connecting member when the connecting member rotates.
2. The control device according to claim 1, comprising a support structure with which the input control member and output control member are integral, said support structure forming an annular recess receiving the connecting member.
3. The control device according to claim 1, wherein the connecting member forms a ring.
4. The control device according to claim 1, wherein the input control member is formed by a lever extending between a first end by which said lever is attached to the support structure such that said lever can rotate, at a first end, said lever including, at a second end, the engagement profile.
5. The control device according to claim 1, comprising a support structure with which the input control member and output control member are integral, said support structure forming an annular recess receiving the connecting member, and wherein the input control member is arranged such that said input control member can slide relative to the support structure and is configured to engage, via the engagement profile, with a transmission element attached to the support structure such that said transmission element can rotate and engaging with the connecting member, such that the sliding of said input control member causes the connecting member to rotate.
6. The control device according to claim 2, wherein the output control member is formed by a lever attached to the support structure such that said lever can rotate, at a first end, said lever including a bevel at a second end, constituting the engagement profile, said output control member being intended to act on the horological movement via an internal flank opposite the engagement profile.
7. The control device according to claim 2, wherein the output control member is connected by a pivot link to the connecting member, and wherein said output control member is further connected

- to the support structure, said output control member comprising a bearing arm intended to be arranged such that said bearing arm bears against a balance of the horological movement in order to perform a balance stop function when the input control member is acted upon.
8. The control device according to claim 2, wherein the driving engagement element is constituted by a catch.
9. The control device according to claim 1, comprising a spring connected to the connecting member and biased to move said connecting member into a rest position wherein said connecting member is capable of engaging with the input control member.
10. The control device according to claim 1, comprising a second input control member and a second output control member kinematically connected to one another via the connecting member and respectively configured to engage with another driven engagement member and with another driving engagement member, the input control members being configured such that, depending on which one is acted upon, the connecting member is driven in a different direction of rotation and causes one or the other output control member respectively to move.
11. The control device according to claim 10, wherein the connecting member comprises a locking element arranged to constitute a banking preventing one of the input control members from making any movement when the other is acted upon.
12. The control device according to claim 10, wherein the connecting member comprises a locking element arranged to constitute a banking preventing one of the input control members from making any movement when the other is acted upon and wherein the locking element is formed by a tooth extending between two bevelled radial flanks each constituting one of the driven engagement elements, the tooth further comprising an outer flank connecting the radial flanks together and being arranged so as to constitute the banking preventing one of the input control members from making any movement, when the other is acted upon.
13. A watch comprising: a horological movement; and the remote control device according to claim 1.
-