

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401813
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kuo; Che-Wei et al.

Coding enhancement in cross-component sample adaptive offset

Abstract

An electronic apparatus performs a method of decoding video data. The method includes: receiving, from the video signal, a picture frame that includes a first component and a second component; determining a classifier for the second component from a set of one or more samples of the first component associated with a respective sample of the second component; determining whether to modify a value of the respective sample of the second component within a region of the picture frame according to the classifier; in response to the determination to modify the value of the respective sample of the second component within the region according to the classifier, determining a sample offset for the respective sample of the second component according to the classifier; and modifying the value of the respective sample of the second component based on the determined sample offset.

Inventors: Kuo; Che-Wei (Beijing, CN), Xiu; Xiaoyu (Beijing, CN), Chen; Wei (Beijing, CN), Wang; Xianglin (Beijing, CN), Chen; Yi-Wen (Beijing, CN), Jhu; Hong-Jheng (Beijing, CN), Yu; Bing (Beijing, CN)

Applicant: BEIJING DAJIA INTERNET INFORMATION TECHNOLOGY CO., LTD.
(Beijing, CN)

Family ID: 1000008781781

Assignee: BEIJING DAJIA INTERNET INFORMATION TECHNOLOGY CO., LTD.
(Beijing, CN)

Appl. No.: 18/469409

Filed: September 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240007652 A1	Jan. 04, 2024

Related U.S. Application Data

continuation parent-doc WO PCT/US2022/020538 20220316 PENDING child-doc US 18469409
us-provisional-application US 63164459 20210322
us-provisional-application US 63200626 20210318

Publication Classification

Int. Cl.: H04N19/167 (20140101); H04N19/119 (20140101); H04N19/132 (20140101);
H04N19/186 (20140101); H04N19/44 (20140101); H04N19/60 (20140101); H04N19/96
(20140101)

U.S. Cl.:

CPC H04N19/44 (20141101); H04N19/119 (20141101); H04N19/132 (20141101);
H04N19/167 (20141101); H04N19/186 (20141101); H04N19/60 (20141101);
H04N19/96 (20141101);

Field of Classification Search

CPC: H04N (19/44); H04N (19/119); H04N (19/132); H04N (19/167); H04N (19/186); H04N
(19/60); H04N (19/96)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2004/0037361	12/2003	Gudis	375/E7.193	H04N 19/895
2007/0297511	12/2006	Chiu	375/E7.262	H04N 19/112
2014/0092999	12/2013	Dong et al.	N/A	N/A
2014/0301480	12/2013	Francois et al.	N/A	N/A
2015/0215631	12/2014	Zhou	375/240.02	H04N 19/436
2016/0173881	12/2015	Alshina	375/240.08	H04N 19/186
2018/0063527	12/2017	Chen et al.	N/A	N/A
2020/0120341	12/2019	Park et al.	N/A	N/A
2020/0288127	12/2019	Tourapis	N/A	N/A
2020/0404341	12/2019	Dong	N/A	H04N 19/70
2021/0076032	12/2020	Hu	N/A	H04N 19/159
2021/0105506	12/2020	Misra	N/A	H04N 19/186
2022/0217354	12/2021	Sim	N/A	H04N 19/103

2022/0337848	12/2021	Francois	N/A	H04N 19/70
2023/0247215	12/2022	Xu	375/240.12	H04N 19/50

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3503556	12/2018	EP	H04N 19/117
2014534762	12/2013	JP	N/A
2019525679	12/2018	JP	N/A
202036353	12/2019	JP	N/A
2014023207	12/2013	WO	N/A
2018182377	12/2017	WO	N/A
2020262396	12/2019	WO	N/A
2021013178	12/2020	WO	N/A
2022093992	12/2021	WO	N/A
2022125151	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report issued in Application No. PCT/US2022/020538, mailed on Jun. 23, 2022 (3 pages). cited by applicant

Written Opinion issued in Application No. PCT/US2022/020538, mailed on Jun. 23, 2022 (5 pages). cited by applicant

First Office Action issued in corresponding Japanese Patent Application 2023-557382 with English translation mailed on Oct. 15, 2024 (9 pages). cited by applicant

C-W Kuo et al., AHG12:Cross-component Sample Adaptive offset, JVET Meeting, JVET-V0153, Apr. 22, 2021 (4 pages). cited by applicant

Extended European Search Report issued on Jan. 30, 2025 for counterpart European patent application No. 22772120.6 (11 pages). cited by applicant

Primary Examiner: Jiang; Zaihan

Attorney, Agent or Firm: Osha Bergman Watanabe & Burton LLP

Background/Summary

RELATED APPLICATIONS (1) The present application claims priority to U.S. Provisional Patent Application No. 63/200,626, entitled “Cross-component Sample Adaptive Offset” filed Mar. 18, 2021, and U.S. Provisional Patent Application No. 63/164,459, entitled “Cross-component Sample Adaptive Offset” filed Mar. 22, 2021, which are incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present application generally relates to video coding and compression, and more specifically, to methods and apparatus on improving both the luma and the chroma coding efficiency.

BACKGROUND

(2) Digital video is supported by a variety of electronic devices, such as digital televisions, laptop or desktop computers, tablet computers, digital cameras, digital recording devices, digital media players, video gaming consoles, smart phones, video teleconferencing devices, video streaming devices, etc. The electronic devices transmit, receive, encode, decode, and/or store digital video data by implementing video compression/decompression standards. Some well-known video coding standards include Versatile Video Coding (VVC), High Efficiency Video Coding (HEVC,

also known as H.265 or MPEG-H Part 2) and Advanced Video Coding (AVC, also known as H.264 or MPEG-4 Part 10), which are jointly developed by ISO/IEC MPEG and ITU-T VCEG. AOMedia Video 1 (AV1) was developed by Alliance for Open Media (AOM) as a successor to its preceding standard VP9. Audio Video Coding (AVS), which refers to digital audio and digital video compression standard, is another video compression standard series developed by the Audio and Video Coding Standard Workgroup.

(3) Video compression typically includes performing spatial (intra frame) prediction and/or temporal (inter frame) prediction to reduce or remove redundancy inherent in the video data. For block-based video coding, a video frame is partitioned into one or more slices, each slice having multiple video blocks, which may also be referred to as coding tree units (CTUs). Each CTU may contain one coding unit (CU) or recursively split into smaller CUs until the predefined minimum CU size is reached. Each CU (also named leaf CU) contains one or multiple transform units (TUs) and each CU also contains one or multiple prediction units (PUs). Each CU can be coded in either intra, inter or IBC modes. Video blocks in an intra coded (I) slice of a video frame are encoded using spatial prediction with respect to reference samples in neighboring blocks within the same video frame. Video blocks in an inter coded (P or B) slice of a video frame may use spatial prediction with respect to reference samples in neighboring blocks within the same video frame or temporal prediction with respect to reference samples in other previous and/or future reference video frames.

(4) Spatial or temporal prediction based on a reference block that has been previously encoded, e.g., a neighboring block, results in a predictive block for a current video block to be coded. The process of finding the reference block may be accomplished by block matching algorithm. Residual data representing pixel differences between the current block to be coded and the predictive block is referred to as a residual block or prediction errors. An inter-coded block is encoded according to a motion vector that points to a reference block in a reference frame forming the predictive block, and the residual block. The process of determining the motion vector is typically referred to as motion estimation. An intra coded block is encoded according to an intra prediction mode and the residual block. For further compression, the residual block is transformed from the pixel domain to a transform domain, e.g., frequency domain, resulting in residual transform coefficients, which may then be quantized. The quantized transform coefficients, initially arranged in a two-dimensional array, may be scanned to produce a one-dimensional vector of transform coefficients, and then entropy encoded into a video bitstream to achieve even more compression.

(5) The encoded video bitstream is then saved in a computer-readable storage medium (e.g., flash memory) to be accessed by another electronic device with digital video capability or directly transmitted to the electronic device wired or wirelessly. The electronic device then performs video decompression (which is an opposite process to the video compression described above) by, e.g., parsing the encoded video bitstream to obtain syntax elements from the bitstream and reconstructing the digital video data to its original format from the encoded video bitstream based at least in part on the syntax elements obtained from the bitstream, and renders the reconstructed digital video data on a display of the electronic device.

(6) With digital video quality going from high definition, to 4K×2K or even 8K×4K, the amount of video data to be encoded/decoded grows exponentially. It is a constant challenge in terms of how the video data can be encoded/decoded more efficiently while maintaining the image quality of the decoded video data.

SUMMARY

(7) The present application describes implementations related to video data encoding and decoding and, more particularly, to methods and apparatus on improving the coding efficiency of both luma and chroma components, including improving the coding efficiency by exploring cross-component relationship between luma component and chroma component.

(8) According to a first aspect of the present application, a method of decoding video signal

comprises: receiving, from the video signal, a picture frame that includes a first component and a second component; determining a classifier for the second component from a set of one or more samples of the first component associated with a respective sample of the second component; determining whether to modify a value of the respective sample of the second component within a region of the picture frame according to the classifier; in response to the determination to modify the value of the respective sample of the second component within the region according to the classifier, determining a sample offset for the respective sample of the second component according to the classifier; and modifying the value of the respective sample of the second component based on the determined sample offset. In some embodiments, the region is formed by dividing the picture frame.

(9) According to a second aspect of the present application, an electronic apparatus includes one or more processing units, memory and a plurality of programs stored in the memory. The programs, when executed by the one or more processing units, cause the electronic apparatus to perform the method of coding video signal as described above.

(10) According to a third aspect of the present application, a non-transitory computer readable storage medium stores a plurality of programs for execution by an electronic apparatus having one or more processing units. The programs, when executed by the one or more processing units, cause the electronic apparatus to perform the method of coding video signal as described above.

(11) According to a fourth aspect of the present application, a computer readable storage medium stores therein a bitstream comprising video information generated by the method for video coding as described above.

(12) It is to be understood that both the foregoing general description and the following detailed description are examples only and are not restrictive of the present disclosure.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The accompanying drawings, which are included to provide a further understanding of the implementations and are incorporated herein and constitute a part of the specification, illustrate the described implementations and together with the description serve to explain the underlying principles. Like reference numerals refer to corresponding parts.

(2) FIG. 1 is a block diagram illustrating an exemplary video encoding and decoding system in accordance with some implementations of the present disclosure.

(3) FIG. 2 is a block diagram illustrating an exemplary video encoder in accordance with some implementations of the present disclosure.

(4) FIG. 3 is a block diagram illustrating an exemplary video decoder in accordance with some implementations of the present disclosure.

(5) FIGS. 4A through 4E are block diagrams illustrating how a frame is recursively partitioned into multiple video blocks of different sizes and shapes in accordance with some implementations of the present disclosure.

(6) FIG. 5 is a block diagram depicting the four gradient patterns used in Sample Adaptive Offset (SAO) in accordance with some implementations of the present disclosure.

(7) FIG. 6A is a block diagram illustrating that the system and process of CCSAO that are applied on chroma samples, and use DBF Y as the input according to some implementations of the present disclosure.

(8) FIG. 6B is a block diagram illustrating the system and process of CCSAO that are applied on luma and chroma samples, and use DBF Y/Cb/Cr as input according to some implementations of the present disclosure.

(9) FIG. 6C is a block diagram illustrating the system and process of CCSAO that can work

independently according to some implementations of the present disclosure.

(10) FIG. 6D is a block diagram illustrating the system and process of CCSAO that can be applied recursively (2 or N times) with same or different offsets according to some implementations of the present disclosure.

(11) FIG. 6E is a block diagram illustrating the system and process of CCSAO applied in parallel with Enhanced Sample Adaptive Offset (ESAO) in the AVS standard according to some implementations of the present disclosure.

(12) FIG. 6F is a block diagram illustrating the system and process of CCSAO applied after SAO according to some implementations of the present disclosure.

(13) FIG. 6G is a block diagram illustrating that the system and process of CCSAO can work independently without CCALF according to some implementations of the present disclosure.

(14) FIG. 6H is a block diagram illustrating the system and process of CCSAO applied in parallel with Cross-Component Adaptive Loop Filter (CCALF) according to some implementations of the present disclosure.

(15) FIG. 7 is a block diagram illustrating a sample process using CCSAO in accordance with some implementations of the present disclosure.

(16) FIG. 8 is a block diagram illustrating that CCSAO process is interleaved to vertical and horizontal deblocking filter (DBF) in accordance with some implementations of the present disclosure.

(17) FIG. 9 is a flowchart illustrating an exemplary process of decoding video signal using cross-component correlation in accordance with some implementations of the present disclosure.

(18) FIG. 10A is a block diagram showing a classifier using different luma (or chroma) sample position for C0 classification in accordance with some implementations of the present disclosure.

(19) FIG. 10B illustrates some examples of different shapes for luma candidates, in accordance with some implementations of the present disclosure.

(20) FIG. 11 is a block diagram of a sample process illustrating that all collocated and neighbouring luma/chroma samples can be fed into CCSAO classification in accordance with some implementations of the present disclosure

(21) FIG. 12 illustrates exemplary classifiers by replacing the collocated luma sample value with a value obtained by weighing collocated and neighboring luma samples in accordance with some implementations of the present disclosure.

(22) FIG. 13A is a block diagram illustrating CCSAO is not applied on the current chroma (luma) sample if any of the collocated and neighboring luma (chroma) samples used for classification is outside the current picture in accordance with some implementations of the present disclosure.

(23) FIG. 13B is a block diagram illustrating CCSAO is applied on the current luma or chroma sample if any of the collocated and neighboring luma or chroma samples used for classification is outside the current picture in accordance with some implementations of the present disclosure.

(24) FIG. 14 is a block diagram illustrating CCSAO is not applied on the current chroma sample if a corresponding selected collocated or neighboring luma sample used for classification is outside a virtual space defined by a virtual boundary (VB) in accordance with some implementations of the present disclosure.

(25) FIG. 15 shows repetitive or mirror padding is applied on the luma samples that are outside the virtual boundary in accordance with some implementations of the present disclosure.

(26) FIG. 16 shows additional 1 luma line buffer is required if all 9 collocated neighboring luma samples are used for classification in accordance with some implementations of the present disclosure.

(27) FIG. 17 shows an illustration in AVS that 9 luma candidates CCSAO crossing VB may increase 2 additional luma line buffers in accordance with some implementations of the present disclosure.

(28) FIG. 18A shows an illustration in VVC that 9 luma candidates CCSAO crossing VB may

increase 1 additional luma line buffer in accordance with some implementations of the present disclosure.

(29) FIG. 18B shows an illustration when collocated or neighbouring chroma samples are used to classify the current luma samples, the selected chroma candidate may be across VB and need additional chroma line buffer in accordance with some implementations of the present disclosure.

(30) FIGS. 19A-19C show in AVS and VVC, CCSAO is disabled for a chroma sample if any of the chroma sample's luma candidates is across VB (outside the current chroma sample VB) in accordance with some implementations of the present disclosure.

(31) FIGS. 20A-20C show in AVS and VVC, CCSAO is enabled using repetitive padding for a chroma sample if any of the chroma sample's luma candidates is across VB (outside the current chroma sample VB) in accordance with some implementations of the present disclosure.

(32) FIGS. 21A-21C show in AVS and VVC, CCSAO is enabled using mirror padding for a chroma sample if any of the chroma sample's luma candidates is across VB (outside the current chroma sample VB) in accordance with some implementations of the present disclosure.

(33) FIGS. 22A-22B show that CCSAO is enabled using double sided symmetric padding for different CCSAO sample shapes in accordance with some implementations of the present disclosure.

(34) FIG. 23 shows the restrictions of using a limited number of luma candidates for classification in accordance with some implementations of the present disclosure.

(35) FIG. 24 shows the CCSAO applied region is not aligned to the coding tree block (CTB)/coding tree unit (CTU) boundary in accordance with some implementations of the present disclosure.

(36) FIG. 25 shows that the CCSAO applied region frame partition can be fixed with CCSAO parameters in accordance with some implementations of the present disclosure.

(37) FIG. 26 shows that the CCSAO applied region can be Binary-tree (BT)/Quad-tree (QT)/Ternary-tree (TT) split from frame/slice/CTB level in accordance with some implementations of the present disclosure.

(38) FIG. 27 is a block diagram illustrating a plurality of classifiers used and switched at different levels within a picture frame in accordance with some implementations of the present disclosure.

(39) FIG. 28 is a block diagram illustrating that the CCSAO applied region partition can be dynamic and switched in picture level, in accordance with some implementations of the present disclosure.

(40) FIG. 29 is a diagram illustrating the CCSAO classifiers can take current or cross component coding information into account, in accordance with some implementations of the present disclosure.

(41) FIG. 30 is a block diagram illustrating that the SAO classification methods disclosed in the present disclosure serve as a post prediction filter in accordance with some implementations of the present disclosure.

(42) FIG. 31 is a block diagram illustrating that for post prediction SAO filter, each component can use the current and neighboring samples for classification in accordance with some implementations of the present disclosure.

(43) FIG. 32 is a flowchart illustrating an exemplary process of decoding video signal using cross-component correlation in accordance with some implementations of the present disclosure.

(44) FIG. 33 is a diagram illustrating a computing environment coupled with a user interface in accordance with some implementations of the present disclosure.

DETAILED DESCRIPTION

(45) Reference will now be made in detail to specific implementations, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous non-limiting specific details are set forth in order to assist in understanding the subject matter presented herein. But it will be apparent to one of ordinary skill in the art that various alternatives may be

used without departing from the scope of claims and the subject matter may be practiced without these specific details. For example, it will be apparent to one of ordinary skill in the art that the subject matter presented herein can be implemented on many types of electronic devices with digital video capabilities.

(46) The first generation AVS standard includes Chinese national standard “Information Technology, Advanced Audio Video Coding, Part 2: Video” (known as AVS1) and “Information Technology, Advanced Audio Video Coding Part 16: Radio Television Video” (known as AVS+). It can offer around 50% bit-rate saving at the same perceptual quality compared to MPEG-2 standard. The second generation AVS standard includes the series of Chinese national standard “Information Technology, Efficient Multimedia Coding” (known as AVS2), which is mainly targeted at the transmission of extra HD TV programs. The coding efficiency of the AVS2 is double of that of the AVS+. Meanwhile, the AVS2 standard video part was submitted by Institute of Electrical and Electronics Engineers (IEEE) as one international standard for applications. The AVS3 standard is one new generation video coding standard for UHD video application aiming at surpassing the coding efficiency of the latest international standard HEVC, which provides approximately 30% bit-rate savings over the HEVC standard. In March 2019, at the 68-th AVS meeting, the AVS3-P2 baseline was finished, which provides approximately 30% bit-rate savings over the HEVC standard. Currently, one reference software, called high performance model (HPM), is maintained by the AVS group to demonstrate a reference implementation of the AVS3 standard. Like the HEVC, the AVS3 standard is built upon the block-based hybrid video coding framework.

(47) FIG. 1 is a block diagram illustrating an exemplary system **10** for encoding and decoding video blocks in parallel in accordance with some implementations of the present disclosure. As shown in FIG. 1, system **10** includes a source device **12** that generates and encodes video data to be decoded at a later time by a destination device **14**. Source device **12** and destination device **14** may comprise any of a wide variety of electronic devices, including desktop or laptop computers, tablet computers, smart phones, set-top boxes, digital televisions, cameras, display devices, digital media players, video gaming consoles, video streaming device, or the like. In some implementations, source device **12** and destination device **14** are equipped with wireless communication capabilities.

(48) In some implementations, destination device **14** may receive the encoded video data to be decoded via a link **16**. Link **16** may comprise any type of communication medium or device capable of moving the encoded video data from source device **12** to destination device **14**. In one example, link **16** may comprise a communication medium to enable source device **12** to transmit the encoded video data directly to destination device **14** in real-time. The encoded video data may be modulated according to a communication standard, such as a wireless communication protocol, and transmitted to destination device **14**. The communication medium may comprise any wireless or wired communication medium, such as a radio frequency (RF) spectrum or one or more physical transmission lines. The communication medium may form part of a packet-based network, such as a local area network, a wide-area network, or a global network such as the Internet. The communication medium may include routers, switches, base stations, or any other equipment that may be useful to facilitate communication from source device **12** to destination device **14**.

(49) In some other implementations, the encoded video data may be transmitted from output interface **22** to a storage device **32**. Subsequently, the encoded video data in storage device **32** may be accessed by destination device **14** via input interface **28**. Storage device **32** may include any of a variety of distributed or locally accessed data storage media such as a hard drive, Blu-ray discs, DVDs, CD-ROMs, flash memory, volatile or non-volatile memory, or any other suitable digital storage media for storing encoded video data. In a further example, storage device **32** may correspond to a file server or another intermediate storage device that may hold the encoded video data generated by source device **12**. Destination device **14** may access the stored video data from storage device **32** via streaming or downloading. The file server may be any type of computer capable of storing encoded video data and transmitting the encoded video data to destination device

14. Exemplary file servers include a web server (e.g., for a website), an FTP server, network attached storage (NAS) devices, or a local disk drive. Destination device **14** may access the encoded video data through any standard data connection, including a wireless channel (e.g., a Wi-Fi connection), a wired connection (e.g., DSL, cable modem, etc.), or a combination of both that is suitable for accessing encoded video data stored on a file server. The transmission of encoded video data from storage device **32** may be a streaming transmission, a download transmission, or a combination of both.

(50) As shown in FIG. **1**, source device **12** includes a video source **18**, a video encoder **20** and an output interface **22**. Video source **18** may include a source such as a video capture device, e.g., a video camera, a video archive containing previously captured video, a video feed interface to receive video from a video content provider, and/or a computer graphics system for generating computer graphics data as the source video, or a combination of such sources. As one example, if video source **18** is a video camera of a security surveillance system, source device **12** and destination device **14** may form camera phones or video phones. However, the implementations described in the present application may be applicable to video coding in general, and may be applied to wireless and/or wired applications.

(51) The captured, pre-captured, or computer-generated video may be encoded by video encoder **20**. The encoded video data may be transmitted directly to destination device **14** via output interface **22** of source device **12**. The encoded video data may also (or alternatively) be stored onto storage device **32** for later access by destination device **14** or other devices, for decoding and/or playback. Output interface **22** may further include a modem and/or a transmitter.

(52) Destination device **14** includes an input interface **28**, a video decoder **30**, and a display device **34**. Input interface **28** may include a receiver and/or a modem and receive the encoded video data over link **16**. The encoded video data communicated over link **16**, or provided on storage device **32**, may include a variety of syntax elements generated by video encoder **20** for use by video decoder **30** in decoding the video data. Such syntax elements may be included within the encoded video data transmitted on a communication medium, stored on a storage medium, or stored a file server.

(53) In some implementations, destination device **14** may include a display device **34**, which can be an integrated display device and an external display device that is configured to communicate with destination device **14**. Display device **34** displays the decoded video data to a user, and may comprise any of a variety of display devices such as a liquid crystal display (LCD), a plasma display, an organic light emitting diode (OLED) display, or another type of display device.

(54) Video encoder **20** and video decoder **30** may operate according to proprietary or industry standards, such as VVC, HEVC, MPEG-4, Part 10, Advanced Video Coding (AVC), AVS, or extensions of such standards. It should be understood that the present application is not limited to a specific video coding/decoding standard and may be applicable to other video coding/decoding standards. It is generally contemplated that video encoder **20** of source device **12** may be configured to encode video data according to any of these current or future standards. Similarly, it is also generally contemplated that video decoder **30** of destination device **14** may be configured to decode video data according to any of these current or future standards.

(55) Video encoder **20** and video decoder **30** each may be implemented as any of a variety of suitable encoder circuitry, such as one or more microprocessors, digital signal processors (DSPs), application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), discrete logic, software, hardware, firmware or any combinations thereof. When implemented partially in software, an electronic device may store instructions for the software in a suitable, non-transitory computer-readable medium and execute the instructions in hardware using one or more processors to perform the video coding/decoding operations disclosed in the present disclosure. Each of video encoder **20** and video decoder **30** may be included in one or more encoders or decoders, either of which may be integrated as part of a combined encoder/decoder (CODEC) in a respective device.

(56) FIG. 2 is a block diagram illustrating an exemplary video encoder **20** in accordance with some implementations described in the present application. Video encoder **20** may perform intra and inter predictive coding of video blocks within video frames. Intra predictive coding relies on spatial prediction to reduce or remove spatial redundancy in video data within a given video frame or picture. Inter predictive coding relies on temporal prediction to reduce or remove temporal redundancy in video data within adjacent video frames or pictures of a video sequence.

(57) As shown in FIG. 2, video encoder **20** includes video data memory **40**, prediction processing unit **41**, decoded picture buffer (DPB) **64**, summer **50**, transform processing unit **52**, quantization unit **54**, and entropy encoding unit **56**. Prediction processing unit **41** further includes motion estimation unit **42**, motion compensation unit **44**, partition unit **45**, intra prediction processing unit **46**, and intra block copy (BC) unit **48**. In some implementations, video encoder **20** also includes inverse quantization unit **58**, inverse transform processing unit **60**, and summer **62** for video block reconstruction. An in-loop filter **63**, such as a deblocking filter may be positioned between summer **62** and DPB **64** to filter block boundaries to remove blocky artifacts from reconstructed video. Another in-loop filter **63** may also be used in addition to the deblocking filter to filter the output of summer **62**. Further in-loop filtering **63**, such as sample adaptive offset (SAO) and adaptive in-loop filter (ALF) may be applied on the reconstructed CU before it is put in the reference picture store and used as reference to code future video blocks. Video encoder **20** may take the form of a fixed or programmable hardware unit or may be divided among one or more of the illustrated fixed or programmable hardware units.

(58) Video data memory **40** may store video data to be encoded by the components of video encoder **20**. The video data in video data memory **40** may be obtained, for example, from video source **18**. DPB **64** is a buffer that stores reference video data for use in encoding video data by video encoder **20** (e.g., in intra or inter predictive coding modes). Video data memory **40** and DPB **64** may be formed by any of a variety of memory devices. In various examples, video data memory **40** may be on-chip with other components of video encoder **20**, or off-chip relative to those components.

(59) As shown in FIG. 2, after receiving video data, partition unit **45** within prediction processing unit **41** partitions the video data into video blocks. This partitioning may also include partitioning a video frame into slices, tiles, or other larger coding units (CUs) according to a predefined splitting structures such as quad-tree structure associated with the video data. The video frame may be divided into multiple video blocks (or sets of video blocks referred to as tiles). Prediction processing unit **41** may select one of a plurality of possible predictive coding modes, such as one of a plurality of intra predictive coding modes or one of a plurality of inter predictive coding modes, for the current video block based on error results (e.g., coding rate and the level of distortion). Prediction processing unit **41** may provide the resulting intra or inter prediction coded block to summer **50** to generate a residual block and to summer **62** to reconstruct the encoded block for use as part of a reference frame subsequently. Prediction processing unit **41** also provides syntax elements, such as motion vectors, intra-mode indicators, partition information, and other such syntax information, to entropy encoding unit **56**.

(60) In order to select an appropriate intra predictive coding mode for the current video block, intra prediction processing unit **46** within prediction processing unit **41** may perform intra predictive coding of the current video block relative to one or more neighboring blocks in the same frame as the current block to be coded to provide spatial prediction. Motion estimation unit **42** and motion compensation unit **44** within prediction processing unit **41** perform inter predictive coding of the current video block relative to one or more predictive blocks in one or more reference frames to provide temporal prediction. Video encoder **20** may perform multiple coding passes, e.g., to select an appropriate coding mode for each block of video data.

(61) In some implementations, motion estimation unit **42** determines the inter prediction mode for a current video frame by generating a motion vector, which indicates the displacement of a prediction

unit (PU) of a video block within the current video frame relative to a predictive block within a reference video frame, according to a predetermined pattern within a sequence of video frames. Motion estimation, performed by motion estimation unit **42**, is the process of generating motion vectors, which estimate motion for video blocks. A motion vector, for example, may indicate the displacement of a PU of a video block within a current video frame or picture relative to a predictive block within a reference frame (or other coded unit) relative to the current block being coded within the current frame (or other coded unit). The predetermined pattern may designate video frames in the sequence as P frames or B frames. Intra BC unit **48** may determine vectors, e.g., block vectors, for intra BC coding in a manner similar to the determination of motion vectors by motion estimation unit **42** for inter prediction, or may utilize motion estimation unit **42** to determine the block vector.

(62) A predictive block is a block of a reference frame that is deemed as closely matching the PU of the video block to be coded in terms of pixel difference, which may be determined by sum of absolute difference (SAD), sum of square difference (SSD), or other difference metrics. In some implementations, video encoder **20** may calculate values for sub-integer pixel positions of reference frames stored in DPB **64**. For example, video encoder **20** may interpolate values of one-quarter pixel positions, one-eighth pixel positions, or other fractional pixel positions of the reference frame. Therefore, motion estimation unit **42** may perform a motion search relative to the full pixel positions and fractional pixel positions and output a motion vector with fractional pixel precision.

(63) Motion estimation unit **42** calculates a motion vector for a PU of a video block in an inter prediction coded frame by comparing the position of the PU to the position of a predictive block of a reference frame selected from a first reference frame list (List **0**) or a second reference frame list (List **1**), each of which identifies one or more reference frames stored in DPB **64**. Motion estimation unit **42** sends the calculated motion vector to motion compensation unit **44** and then to entropy encoding unit **56**.

(64) Motion compensation, performed by motion compensation unit **44**, may involve fetching or generating the predictive block based on the motion vector determined by motion estimation unit **42**. Upon receiving the motion vector for the PU of the current video block, motion compensation unit **44** may locate a predictive block to which the motion vector points in one of the reference frame lists, retrieve the predictive block from DPB **64**, and forward the predictive block to summer **50**. Summer **50** then forms a residual video block of pixel difference values by subtracting pixel values of the predictive block provided by motion compensation unit **44** from the pixel values of the current video block being coded. The pixel difference values forming the residual video block may include luma or chroma difference components or both. Motion compensation unit **44** may also generate syntax elements associated with the video blocks of a video frame for use by video decoder **30** in decoding the video blocks of the video frame. The syntax elements may include, for example, syntax elements defining the motion vector used to identify the predictive block, any flags indicating the prediction mode, or any other syntax information described herein. Note that motion estimation unit **42** and motion compensation unit **44** may be highly integrated, but are illustrated separately for conceptual purposes.

(65) In some implementations, intra BC unit **48** may generate vectors and fetch predictive blocks in a manner similar to that described above in connection with motion estimation unit **42** and motion compensation unit **44**, but with the predictive blocks being in the same frame as the current block being coded and with the vectors being referred to as block vectors as opposed to motion vectors. In particular, intra BC unit **48** may determine an intra-prediction mode to use to encode a current block. In some examples, intra BC unit **48** may encode a current block using various intra-prediction modes, e.g., during separate encoding passes, and test their performance through rate-distortion analysis. Next, intra BC unit **48** may select, among the various tested intra-prediction modes, an appropriate intra-prediction mode to use and generate an intra-mode indicator

accordingly. For example, intra BC unit **48** may calculate rate-distortion values using a rate-distortion analysis for the various tested intra-prediction modes, and select the intra-prediction mode having the best rate-distortion characteristics among the tested modes as the appropriate intra-prediction mode to use. Rate-distortion analysis generally determines an amount of distortion (or error) between an encoded block and an original, unencoded block that was encoded to produce the encoded block, as well as a bitrate (i.e., a number of bits) used to produce the encoded block. Intra BC unit **48** may calculate ratios from the distortions and rates for the various encoded blocks to determine which intra-prediction mode exhibits the best rate-distortion value for the block.

(66) In other examples, intra BC unit **48** may use motion estimation unit **42** and motion compensation unit **44**, in whole or in part, to perform such functions for Intra BC prediction according to the implementations described herein. In either case, for Intra block copy, a predictive block may be a block that is deemed as closely matching the block to be coded, in terms of pixel difference, which may be determined by sum of absolute difference (SAD), sum of squared difference (SSD), or other difference metrics, and identification of the predictive block may include calculation of values for sub-integer pixel positions.

(67) Whether the predictive block is from the same frame according to intra prediction, or a different frame according to inter prediction, video encoder **20** may form a residual video block by subtracting pixel values of the predictive block from the pixel values of the current video block being coded, forming pixel difference values. The pixel difference values forming the residual video block may include both luma and chroma component differences.

(68) Intra prediction processing unit **46** may intra-predict a current video block, as an alternative to the inter-prediction performed by motion estimation unit **42** and motion compensation unit **44**, or the intra block copy prediction performed by intra BC unit **48**, as described above. In particular, intra prediction processing unit **46** may determine an intra prediction mode to use to encode a current block. To do so, intra prediction processing unit **46** may encode a current block using various intra prediction modes, e.g., during separate encoding passes, and intra prediction processing unit **46** (or a mode select unit, in some examples) may select an appropriate intra prediction mode to use from the tested intra prediction modes. Intra prediction processing unit **46** may provide information indicative of the selected intra-prediction mode for the block to entropy encoding unit **56**. Entropy encoding unit **56** may encode the information indicating the selected intra-prediction mode in the bitstream.

(69) After prediction processing unit **41** determines the predictive block for the current video block via either inter prediction or intra prediction, summer **50** forms a residual video block by subtracting the predictive block from the current video block. The residual video data in the residual block may be included in one or more transform units (TUs) and is provided to transform processing unit **52**. Transform processing unit **52** transforms the residual video data into residual transform coefficients using a transform, such as a discrete cosine transform (DCT) or a conceptually similar transform.

(70) Transform processing unit **52** may send the resulting transform coefficients to quantization unit **54**. Quantization unit **54** quantizes the transform coefficients to further reduce bit rate. The quantization process may also reduce the bit depth associated with some or all of the coefficients. The degree of quantization may be modified by adjusting a quantization parameter. In some examples, quantization unit **54** may then perform a scan of a matrix including the quantized transform coefficients. Alternatively, entropy encoding unit **56** may perform the scan.

(71) Following quantization, entropy encoding unit **56** entropy encodes the quantized transform coefficients into a video bitstream using, e.g., context adaptive variable length coding (CAVLC), context adaptive binary arithmetic coding (CABAC), syntax-based context-adaptive binary arithmetic coding (SBAC), probability interval partitioning entropy (PIPE) coding or another entropy encoding methodology or technique. The encoded bitstream may then be transmitted to video decoder **30**, or archived in storage device **32** for later transmission to or retrieval by video

decoder **30**. Entropy encoding unit **56** may also entropy encode the motion vectors and the other syntax elements for the current video frame being coded.

(72) Inverse quantization unit **58** and inverse transform processing unit **60** apply inverse quantization and inverse transformation, respectively, to reconstruct the residual video block in the pixel domain for generating a reference block for prediction of other video blocks. As noted above, motion compensation unit **44** may generate a motion compensated predictive block from one or more reference blocks of the frames stored in DPB **64**. Motion compensation unit **44** may also apply one or more interpolation filters to the predictive block to calculate sub-integer pixel values for use in motion estimation.

(73) Summer **62** adds the reconstructed residual block to the motion compensated predictive block produced by motion compensation unit **44** to produce a reference block for storage in DPB **64**. The reference block may then be used by intra BC unit **48**, motion estimation unit **42** and motion compensation unit **44** as a predictive block to inter predict another video block in a subsequent video frame.

(74) FIG. **3** is a block diagram illustrating an exemplary video decoder **30** in accordance with some implementations of the present application. Video decoder **30** includes video data memory **79**, entropy decoding unit **80**, prediction processing unit **81**, inverse quantization unit **86**, inverse transform processing unit **88**, summer **90**, and DPB **92**. Prediction processing unit **81** further includes motion compensation unit **82**, intra prediction processing unit **84**, and intra BC unit **85**. Video decoder **30** may perform a decoding process generally reciprocal to the encoding process described above with respect to video encoder in connection with FIG. **2**. For example, motion compensation unit **82** may generate prediction data based on motion vectors received from entropy decoding unit **80**, while intra-prediction unit **84** may generate prediction data based on intra-prediction mode indicators received from entropy decoding unit **80**.

(75) In some examples, a unit of video decoder **30** may be tasked to perform the implementations of the present application. Also, in some examples, the implementations of the present disclosure may be divided among one or more of the units of video decoder **30**. For example, intra BC unit **85** may perform the implementations of the present application, alone, or in combination with other units of video decoder **30**, such as motion compensation unit **82**, intra prediction processing unit **84**, and entropy decoding unit **80**. In some examples, video decoder **30** may not include intra BC unit **85** and the functionality of intra BC unit **85** may be performed by other components of prediction processing unit **81**, such as motion compensation unit **82**.

(76) Video data memory **79** may store video data, such as an encoded video bitstream, to be decoded by the other components of video decoder **30**. The video data stored in video data memory **79** may be obtained, for example, from storage device **32**, from a local video source, such as a camera, via wired or wireless network communication of video data, or by accessing physical data storage media (e.g., a flash drive or hard disk). Video data memory **79** may include a coded picture buffer (CPB) that stores encoded video data from an encoded video bitstream. Decoded picture buffer (DPB) **92** of video decoder **30** stores reference video data for use in decoding video data by video decoder **30** (e.g., in intra or inter predictive coding modes). Video data memory **79** and DPB **92** may be formed by any of a variety of memory devices, such as dynamic random access memory (DRAM), including synchronous DRAM (SDRAM), magneto-resistive RAM (MRAM), resistive RAM (RRAM), or other types of memory devices. For illustrative purpose, video data memory **79** and DPB **92** are depicted as two distinct components of video decoder **30** in FIG. **3**. But it will be apparent to one skilled in the art that video data memory **79** and DPB **92** may be provided by the same memory device or separate memory devices. In some examples, video data memory **79** may be on-chip with other components of video decoder **30**, or off-chip relative to those components.

(77) During the decoding process, video decoder **30** receives an encoded video bitstream that represents video blocks of an encoded video frame and associated syntax elements. Video decoder **30** may receive the syntax elements at the video frame level and/or the video block level. Entropy

decoding unit **80** of video decoder **30** entropy decodes the bitstream to generate quantized coefficients, motion vectors or intra-prediction mode indicators, and other syntax elements. Entropy decoding unit **80** then forwards the motion vectors and other syntax elements to prediction processing unit **81**.

(78) When the video frame is coded as an intra predictive coded (I) frame or for intra coded predictive blocks in other types of frames, intra prediction processing unit **84** of prediction processing unit **81** may generate prediction data for a video block of the current video frame based on a signaled intra prediction mode and reference data from previously decoded blocks of the current frame.

(79) When the video frame is coded as an inter-predictive coded (i.e., B or P) frame, motion compensation unit **82** of prediction processing unit **81** produces one or more predictive blocks for a video block of the current video frame based on the motion vectors and other syntax elements received from entropy decoding unit **80**. Each of the predictive blocks may be produced from a reference frame within one of the reference frame lists. Video decoder **30** may construct the reference frame lists, List **0** and List **1**, using default construction techniques based on reference frames stored in DPB **92**.

(80) In some examples, when the video block is coded according to the intra BC mode described herein, intra BC unit **85** of prediction processing unit **81** produces predictive blocks for the current video block based on block vectors and other syntax elements received from entropy decoding unit **80**. The predictive blocks may be within a reconstructed region of the same picture as the current video block defined by video encoder **20**.

(81) Motion compensation unit **82** and/or intra BC unit **85** determines prediction information for a video block of the current video frame by parsing the motion vectors and other syntax elements, and then uses the prediction information to produce the predictive blocks for the current video block being decoded. For example, motion compensation unit **82** uses some of the received syntax elements to determine a prediction mode (e.g., intra or inter prediction) used to code video blocks of the video frame, an inter prediction frame type (e.g., B or P), construction information for one or more of the reference frame lists for the frame, motion vectors for each inter predictive encoded video block of the frame, inter prediction status for each inter predictive coded video block of the frame, and other information to decode the video blocks in the current video frame.

(82) Similarly, intra BC unit **85** may use some of the received syntax elements, e.g., a flag, to determine that the current video block was predicted using the intra BC mode, construction information of which video blocks of the frame are within the reconstructed region and should be stored in DPB **92**, block vectors for each intra BC predicted video block of the frame, intra BC prediction status for each intra BC predicted video block of the frame, and other information to decode the video blocks in the current video frame.

(83) Motion compensation unit **82** may also perform interpolation using the interpolation filters as used by video encoder **20** during encoding of the video blocks to calculate interpolated values for sub-integer pixels of reference blocks. In this case, motion compensation unit **82** may determine the interpolation filters used by video encoder **20** from the received syntax elements and use the interpolation filters to produce predictive blocks.

(84) Inverse quantization unit **86** inverse quantizes the quantized transform coefficients provided in the bitstream and entropy decoded by entropy decoding unit **80** using the same quantization parameter calculated by video encoder **20** for each video block in the video frame to determine a degree of quantization. Inverse transform processing unit **88** applies an inverse transform, e.g., an inverse DCT, an inverse integer transform, or a conceptually similar inverse transform process, to the transform coefficients in order to reconstruct the residual blocks in the pixel domain.

(85) After motion compensation unit **82** or intra BC unit **85** generates the predictive block for the current video block based on the vectors and other syntax elements, summer **90** reconstructs decoded video block for the current video block by summing the residual block from inverse

transform processing unit **88** and a corresponding predictive block generated by motion compensation unit **82** and intra BC unit **85**. An in-loop filter **91** may be positioned between summer **90** and DPB **92** to further process the decoded video block. The in-loop filtering **91**, such as deblocking filter, sample adaptive offset (SAO) and adaptive in-loop filter (ALF) may be applied on the reconstructed CU before it is put in the reference picture store. The decoded video blocks in a given frame are then stored in DPB **92**, which stores reference frames used for subsequent motion compensation of next video blocks. DPB **92**, or a memory device separate from DPB **92**, may also store decoded video for later presentation on a display device, such as display device **34** of FIG. 1.

(86) In a typical video coding process, a video sequence typically includes an ordered set of frames or pictures. Each frame may include three sample arrays, denoted SL, SCb, and SCr. SL is a two-dimensional array of luma samples. SCb is a two-dimensional array of Cb chroma samples. SCr is a two-dimensional array of Cr chroma samples. In other instances, a frame may be monochrome and therefore includes only one two-dimensional array of luma samples.

(87) Like the HEVC, the AVS3 standard is built upon the block-based hybrid video coding framework. The input video signal is processed block by block (called coding units (CUs)). Different from the HEVC which partitions blocks only based on quad-trees, in the AVS3, one coding tree unit (CTU) is split into CUs to adapt to varying local characteristics based on quad/binary/extended-quad-tree. Additionally, the concept of multiple partition unit type in the HEVC is removed, i.e., the separation of CU, prediction unit (PU) and transform unit (TU) does not exist in the AVS3. Instead, each CU is always used as the basic unit for both prediction and transform without further partitions. In the tree partition structure of the AVS3, one CTU is firstly partitioned based on a quad-tree structure. Then, each quad-tree leaf node can be further partitioned based on a binary and extended-quad-tree structure.

(88) As shown in FIG. 4A, video encoder **20** (or more specifically partition unit **45**) generates an encoded representation of a frame by first partitioning the frame into a set of coding tree units (CTUs). A video frame may include an integer number of CTUs ordered consecutively in a raster scan order from left to right and from top to bottom. Each CTU is a largest logical coding unit and the width and height of the CTU are signaled by the video encoder **20** in a sequence parameter set, such that all the CTUs in a video sequence have the same size being one of 128×128 , 64×64 , 32×32 , and 16×16 . But it should be noted that the present application is not necessarily limited to a particular size. As shown in FIG. 4B, each CTU may comprise one coding tree block (CTB) of luma samples, two corresponding coding tree blocks of chroma samples, and syntax elements used to code the samples of the coding tree blocks. The syntax elements describe properties of different types of units of a coded block of pixels and how the video sequence can be reconstructed at the video decoder **30**, including inter or intra prediction, intra prediction mode, motion vectors, and other parameters. In monochrome pictures or pictures having three separate color planes, a CTU may comprise a single coding tree block and syntax elements used to code the samples of the coding tree block. A coding tree block may be an $N \times N$ block of samples.

(89) To achieve a better performance, video encoder **20** may recursively perform tree partitioning such as binary-tree partitioning, ternary-tree partitioning, quad-tree partitioning or a combination of both on the coding tree blocks of the CTU and divide the CTU into smaller coding units (CUs). As depicted in FIG. 4C, the 64×64 CTU **400** is first divided into four smaller CU, each having a block size of 32×32 . Among the four smaller CUs, CU **410** and CU **420** are each divided into four CUs of 16×16 by block size. The two 16×16 CUs **430** and **440** are each further divided into four CUs of 8×8 by block size. FIG. 4D depicts a quad-tree data structure illustrating the end result of the partition process of the CTU **400** as depicted in FIG. 4C, each leaf node of the quad-tree corresponding to one CU of a respective size ranging from 32×32 to 8×8 . Like the CTU depicted in FIG. 4B, each CU may comprise a coding block (CB) of luma samples and two corresponding coding blocks of chroma samples of a frame of the same size, and syntax elements used to code the samples of the coding blocks. In monochrome pictures or pictures having three separate color

planes, a CU may comprise a single coding block and syntax structures used to code the samples of the coding block. It should be noted that the quad-tree partitioning depicted in FIGS. 4C and 4D is only for illustrative purposes and one CTU can be split into CUs to adapt to varying local characteristics based on quad/ternary/binary-tree partitions. In the multi-type tree structure, one CTU is partitioned by a quad-tree structure and each quad-tree leaf CU can be further partitioned by a binary and ternary tree structure. As shown in FIG. 4E, there are five splitting/partitioning types in the AVS3, i.e., quaternary partitioning, horizontal binary partitioning, vertical binary partitioning, horizontal extended quad-tree partitioning, and vertical extended quad-tree partitioning.

(90) In some implementations, video encoder **20** may further partition a coding block of a CU into one or more $M \times N$ prediction blocks (PB). A prediction block is a rectangular (square or non-square) block of samples on which the same prediction, inter or intra, is applied. A prediction unit (PU) of a CU may comprise a prediction block of luma samples, two corresponding prediction blocks of chroma samples, and syntax elements used to predict the prediction blocks. In monochrome pictures or pictures having three separate color planes, a PU may comprise a single prediction block and syntax structures used to predict the prediction block. Video encoder **20** may generate predictive luma, Cb, and Cr blocks for luma, Cb, and Cr prediction blocks of each PU of the CU.

(91) Video encoder **20** may use intra prediction or inter prediction to generate the predictive blocks for a PU. If video encoder **20** uses intra prediction to generate the predictive blocks of a PU, video encoder **20** may generate the predictive blocks of the PU based on decoded samples of the frame associated with the PU. If video encoder **20** uses inter prediction to generate the predictive blocks of a PU, video encoder **20** may generate the predictive blocks of the PU based on decoded samples of one or more frames other than the frame associated with the PU.

(92) After video encoder **20** generates predictive luma, Cb, and Cr blocks for one or more PUs of a CU, video encoder **20** may generate a luma residual block for the CU by subtracting the CU's predictive luma blocks from its original luma coding block such that each sample in the CU's luma residual block indicates a difference between a luma sample in one of the CU's predictive luma blocks and a corresponding sample in the CU's original luma coding block. Similarly, video encoder **20** may generate a Cb residual block and a Cr residual block for the CU, respectively, such that each sample in the CU's Cb residual block indicates a difference between a Cb sample in one of the CU's predictive Cb blocks and a corresponding sample in the CU's original Cb coding block and each sample in the CU's Cr residual block may indicate a difference between a Cr sample in one of the CU's predictive Cr blocks and a corresponding sample in the CU's original Cr coding block.

(93) Furthermore, as illustrated in FIG. 4C, video encoder **20** may use quad-tree partitioning to decompose the luma, Cb, and Cr residual blocks of a CU into one or more luma, Cb, and Cr transform blocks. A transform block is a rectangular (square or non-square) block of samples on which the same transform is applied. A transform unit (TU) of a CU may comprise a transform block of luma samples, two corresponding transform blocks of chroma samples, and syntax elements used to transform the transform block samples. Thus, each TU of a CU may be associated with a luma transform block, a Cb transform block, and a Cr transform block. In some examples, the luma transform block associated with the TU may be a sub-block of the CU's luma residual block. The Cb transform block may be a sub-block of the CU's Cb residual block. The Cr transform block may be a sub-block of the CU's Cr residual block. In monochrome pictures or pictures having three separate color planes, a TU may comprise a single transform block and syntax structures used to transform the samples of the transform block.

(94) Video encoder **20** may apply one or more transforms to a luma transform block of a TU to generate a luma coefficient block for the TU. A coefficient block may be a two-dimensional array of transform coefficients. A transform coefficient may be a scalar quantity. Video encoder **20** may

apply one or more transforms to a Cb transform block of a TU to generate a Cb coefficient block for the TU. Video encoder **20** may apply one or more transforms to a Cr transform block of a TU to generate a Cr coefficient block for the TU.

(95) After generating a coefficient block (e.g., a luma coefficient block, a Cb coefficient block or a Cr coefficient block), video encoder **20** may quantize the coefficient block. Quantization generally refers to a process in which transform coefficients are quantized to possibly reduce the amount of data used to represent the transform coefficients, providing further compression. After video encoder **20** quantizes a coefficient block, video encoder **20** may entropy encode syntax elements indicating the quantized transform coefficients. For example, video encoder **20** may perform Context-Adaptive Binary Arithmetic Coding (CABAC) on the syntax elements indicating the quantized transform coefficients. Finally, video encoder **20** may output a bitstream that includes a sequence of bits that forms a representation of coded frames and associated data, which is either saved in storage device **32** or transmitted to destination device **14**.

(96) After receiving a bitstream generated by video encoder **20**, video decoder **30** may parse the bitstream to obtain syntax elements from the bitstream. Video decoder **30** may reconstruct the frames of the video data based at least in part on the syntax elements obtained from the bitstream. The process of reconstructing the video data is generally reciprocal to the encoding process performed by video encoder **20**. For example, video decoder **30** may perform inverse transforms on the coefficient blocks associated with TUs of a current CU to reconstruct residual blocks associated with the TUs of the current CU. Video decoder **30** also reconstructs the coding blocks of the current CU by adding the samples of the predictive blocks for PUs of the current CU to corresponding samples of the transform blocks of the TUs of the current CU. After reconstructing the coding blocks for each CU of a frame, video decoder **30** may reconstruct the frame.

(97) SAO is a process that modifies the decoded samples by conditionally adding an offset value to each sample after the application of the deblocking filter, based on values in look-up tables transmitted by the encoder. SAO filtering is performed on a region basis, based on a filtering type selected per CTB by a syntax element `sao-type-idx`. A value of 0 for `sao-type-idx` indicates that the SAO filter is not applied to the CTB, and the values 1 and 2 signal the use of the band offset and edge offset filtering types, respectively. In the band offset mode specified by `sao-type-idx` equal to 1, the selected offset value directly depends on the sample amplitude. In this mode, the full sample amplitude range is uniformly split into 32 segments called bands, and the sample values belonging to four of these bands (which are consecutive within the 32 bands) are modified by adding transmitted values denoted as band offsets, which can be positive or negative. The main reason for using four consecutive bands is that in the smooth areas where banding artifacts can appear, the sample amplitudes in a CTB tend to be concentrated in only few of the bands. In addition, the design choice of using four offsets is unified with the edge offset mode of operation which also uses four offset values. In the edge offset mode specified by `sao-type-idx` equal to 2, a syntax element `sao-eo-class` with values from 0 to 3 signals whether a horizontal, vertical or one of two diagonal gradient directions is used for the edge offset classification in the CTB.

(98) FIG. 5 is a block diagram depicting the four gradient patterns used in SAO in accordance with some implementations of the present disclosure. The four gradient patterns **502**, **504**, **506**, and **508** are for the respective `sao-eo-class` in the edge offset mode. Sample labelled “p” indicates a center sample to be considered. Two samples labelled “n0” and “n1” specify two neighboring samples along the (a) horizontal (`sao-eo-class`=0), (b) vertical (`sao-eo-class`=1), (c) 135° diagonal (`sao-eo-class`=2), and (d) 45° (`sao-eo-class`=3) gradient patterns. Each sample in the CTB is classified into one of five `EdgeIdx` categories by comparing the sample value p located at some position with the values n0 and n1 of two samples located at neighboring positions as shown in FIG. 5. This classification is done for each sample based on decoded sample values, so no additional signaling is required for the `EdgeIdx` classification. Depending on the `EdgeIdx` category at the sample position, for `EdgeIdx` categories from 1 to 4, an offset value from a transmitted look-up table is added to the

sample value. The offset values are always positive for categories 1 and 2 and negative for categories 3 and 4. Thus the filter generally has a smoothing effect in the edge offset mode. Table 1 below illustrates a sample EdgeIdx categories in SAO edge classes.

(99) TABLE-US-00001 TABLE 1 A sample EdgeIdx categories in SAO edge classes. EdgeIdx Condition Meaning 0 Cases not listed below Monotonic area 1 $p < n_{sub.0}$ and $p < n_{sub.1}$ Local min 2 $p < n_{sub.0}$ and $p = n_{sub.1}$ or $p < n_{sub.1}$ and $p = n_{sub.0}$ Edge 3 $p > n_{sub.0}$ and $p = n_{sub.1}$ or $p > n_{sub.1}$ and $p = n_{sub.0}$ Edge 4 $p > n_{sub.0}$ and $p > n_{sub.1}$ Local max

(100) For SAO types 1 and 2, a total of four amplitude offset values are transmitted to the decoder for each CTB. For type 1, the sign is also encoded. The offset values and related syntax elements such as sao-type-idx and sao-eo-class are determined by the encoder—typically using criteria that optimize rate-distortion performance. The SAO parameters can be indicated to be inherited from the left or above CTB using a merge flag to make the signaling efficient. In summary, SAO is a nonlinear filtering operation which allows additional refinement of the reconstructed signal, and it can enhance the signal representation in both smooth areas and around edges.

(101) In some embodiments, methods and systems are disclosed herein to improve the coding efficiency or reduce the complexity of Sample Adaptive Offset (SAO) by introducing cross-component information. SAO is used in the HEVC, VVC, AVS2 and AVS3 standards. Although the existing SAO design in the HEVC, VVC, AVS2 and AVS3 standards is used as the basic SAO method in the following descriptions, to a person skilled in the art of video coding, the cross-component methods described in the disclosure can also be applied to other loop filter designs or other coding tools with the similar design spirits. For example, in the AVS3 standard, SAO is replaced by a coding tool called Enhanced Sample Adaptive Offset (ESAO). However, the CCSAO disclosed herein can also be applied in parallel with ESAO. In another example, CCSAO can be applied in parallel with Constrained Directional Enhancement Filter (CDEF) in the AV1 standard.

(102) For the existing SAO design in the HEVC, VVC, AVS2 and AVS3 standards, the luma Y, chroma Cb and chroma Cr sample offset values are decided independently. That is, for example, the current chroma sample offset is decided by only the current and neighboring chroma sample values, without taking collocated or neighboring luma samples into consideration. However, luma samples preserve more original picture detail information than chroma samples, and they can benefit the decision of the current chroma sample offset. Furthermore, since chroma samples usually lose high frequency details after color conversion from RGB to YCbCr, or after quantization and deblocking filter, introducing luma samples with high frequency detail preserved for chroma offset decision can benefit the chroma sample reconstruction. Hence, further gain can be expected by exploring cross-component correlation, for example, by using the methods and systems of Cross-Component Sample Adaptive Offset (CCSAO). In some embodiments, the correlation here not only includes cross-component sample values but also includes picture/coding information such as prediction/residual coding modes, transformation types, and quantization/deblocking/SAO/ALF parameters from cross-components.

(103) Another example is for SAO, the luma sample offsets are decided only by the luma samples. However, for example, a luma sample with the same band offset (BO) classification can be further classified by its collocated and neighboring chroma samples, which may lead to a more effective classification. SAO classification can be taken as a shortcut to compensate the sample difference between the original picture and the reconstructed picture. Therefore, an effective classification is desired.

(104) FIG. 6A is a block diagram illustrating that the system and process of CCSAO that are applied on chroma samples, and use DBF Y as the input according to some implementations of the present disclosure. The luma samples after luma deblocking filter (DBF Y) is used to determine additional offsets for chroma Cb and Cr after SAO Cb and SAO Cr. For example, the current chroma sample **602** is first classified using collocated **604** and neighboring (white) luma samples **606**, and the corresponding CCSAO offset value of the corresponding class is added to the current

chroma sample value. FIG. 6B is a block diagram illustrating the system and process of CCSAO that are applied on luma and chroma samples, and use DBF Y/Cb/Cr as input according to some implementations of the present disclosure. FIG. 6C is a block diagram illustrating the system and process of CCSAO that can work independently according to some implementations of the present disclosure. FIG. 6D is a block diagram illustrating the system and process of CCSAO that can be applied recursively (2 or N times) with same or different offsets in the same codec stage or repeated in the different stages, according to some implementations of the present disclosure. In summary, in some embodiments, for classifying the current luma sample, the information of current and neighboring luma samples, the information of collocated and neighboring chroma samples (Cb and Cr), can be used. In some embodiments, for classifying the current chroma sample (Cb or Cr), collocated and neighboring luma samples, collocated and neighboring cross-chroma samples, and current and neighboring chroma samples can be used. In some embodiments, CCSAO can be cascaded after (1) DBF Y/Cb/Cr, (2) reconstructed image Y/Cb/Cr before DBF, or (3) after SAO Y/Cb/Cr, or (4) after ALF Y/Cb/Cr.

(105) In some embodiments, CCSAO can also be applied in parallel with other coding tools, for example, ESAO in the AVS standard, or CDEF in the AV1 standard. FIG. 6E is a block diagram illustrating the system and process of CCSAO applied in parallel with ESAO in the AVS standard according to some implementations of the present disclosure.

(106) FIG. 6F is a block diagram illustrating the system and process of CCSAO applied after SAO according to some implementations of the present disclosure. In some embodiments, FIG. 6F shows that the location of CCSAO can be after SAO, i.e., the location of Cross-Component Adaptive Loop Filter (CCALF) in the VVC standard. FIG. 6G is a block diagram illustrating that the system and process of CCSAO can work independently without CCALF, according to some implementations of the present disclosure. In some embodiments, the SAO Y/Cb/Cr can be replaced by ESAO, for example, in the AVS3 standard.

(107) FIG. 6H is a block diagram illustrating the system and process of CCSAO applied in parallel with CCALF according to some implementations of the present disclosure. In some embodiments, FIG. 6H shows that CCSAO can be applied in parallel with CCALF. In some embodiments, in FIG. 6H, the locations of CCALF and CCSAO can be switched. In some embodiments, in FIG. 6A to FIG. 6H, or throughout the present disclosure, the SAO Y/Cb/Cr blocks can be replaced by ESAO Y/Cb/Cr (in AVS3) or CDEF (in AV1). Note Y/Cb/Cr also can be denoted as Y/U/V in video coding area.

(108) In some embodiments, the current chroma sample classification is reusing the SAO type (edge offset (EO) or BO), class, and category of the collocated luma sample. The corresponding CCSAO offset can be signaled or derived from the decoder itself. For example, let h_Y be the collocated luma SAO offset, h_{Cb} and h_{Cr} be the CCSAO Cb and Cr offset, respectively. h_{Cb} (or h_{Cr}) = $w \cdot h_Y$ where w can be selected in a limited table. For example, $+1/4, +1/2, 0, +1, +2, +4 \dots$ etc., where $|w|$ only includes the power-of-2 values.

(109) In some embodiments, the comparison score $[-8, 8]$ of the collocated luma samples (Y_0) and neighboring 8 luma samples are used, which yields 17 classes in total. Initial Class=0 Loop over neighboring 8 luma samples ($Y_i, i=1$ to 8) if $Y_0 > Y_i$ Class+=1 else if $Y_0 < Y_i$ Class-=1

(110) In some embodiments, the abovementioned classification methods can be combined. For example, comparison score combined with SAO BO (32 bands classification) is used to increase diversity, which yields $17 \cdot 32$ classes in total. In some embodiments, the Cb and Cr can use the same class to reduce the complexity or saving bits.

(111) FIG. 7 is a block diagram illustrating a sample process using CCSAO in accordance with some implementations of the present disclosure. Specifically, FIG. 7 shows the input of CCSAO can introduce the input of vertical and horizontal DBF, to simplify the class determination, or increase flexibility. For example, let $Y_0_DBF_V, Y_0_DBF_H$, and Y_0 be collocated luma samples at the input of DBF_V, DBF_H, and SAO, respectively. $Y_i_DBF_V, Y_i_DBF_H$, and Y_i are

neighboring 8 luma samples at the input of DBF_V, DBF_H, and SAO, respectively, where $i=1$ to 8.

$\text{Max } Y0 = \max(Y0_DBF_V, Y0_DBF_H, Y0_DBF)$

$\text{Max } Yi = \max(Yi_DBF_V, Yi_DBF_H, Yi_DBF)$

And feed max Y0 and max Yi to CCSAO classification.

(112) FIG. 8 is a block diagram illustrating that CCSAO process is interleaved to vertical and horizontal DBF in accordance with some implementations of the present disclosure. In some embodiments, CCSAO blocks in FIGS. 6, 7 and 8 can be selective. For example, using Y0_DBF_V and Yi_DBF_V for the first CCSAO_V, which applies the same sample processing as in FIG. 6, while using the input of DBF_V luma samples as CCSAO input.

(113) In some embodiments, CCSAO syntax implemented is shown in Table 2 below.

(114) TABLE-US-00002 TABLE 2 An example of CCSAO syntax

Level	Syntax element	Meaning
SPS	cc_sao_enabled_flag	whether CCSAO is enabled in the sequence
SH	slice_cc_sao_cb_flag	whether CCSAO is enabled for Cb
slice	cc_sao_cr_flag	whether CCSAO is enabled for Cr
CTU	cc_sao_merge_left_flag	whether CCSAO offset is merged from the left
CTU	cc_sao_merge_up_flag	whether CCSAO offset is merged from the up
CTU	cc_sao_class_idx	CCSAO class index of this CTU
CTU	cc_sao_offset_sign_flag	CCSAO Cb and Cr offset values of cc_sao_offset_abs this CTU class

(115) In some embodiments, for signaling CCSAO Cb and Cr offset values, if one additional chroma offset is signaled, the other chroma component offset can be derived by plus or minus sign, or weighting to save bits overhead. For example, let h_Cb and h_Cr be the offset of CCSAO Cb and Cr, respectively. With explicit signaling w , wherein $w = + - |w|$ with limited $|w|$ candidates, h_Cr can be derived from h_Cb without explicit signaling h_Cr itself.

$h_Cr = w * h_Cb$

(116) FIG. 9 is a flowchart illustrating an exemplary process 900 of decoding video signal using cross-component correlation in accordance with some implementations of the present disclosure.

(117) The video decoder 30, receives the video signal that includes a first component and a second component (910). In some embodiments, the first component is a luma component, and the second component is a chroma component of the video signal.

(118) The video decoder 30 also receives a plurality of offsets associated with the second component (920).

(119) The video decoder 30 then utilizes a characteristic measurement of the first component to obtain a classification category associated with the second component (930). For example, in FIG. 6, the current chroma sample 602 is first classified using collocated 604 and neighboring (white) luma samples 606, and the corresponding CCSAO offset value is added to the current chroma sample.

(120) The video decoder 30 further selects a first offset from the plurality of offsets for the second component according to the classification category (940).

(121) The video decoder 30 additionally modifies the second component based on the selected first offset (950).

(122) In some embodiments, utilizing the characteristic measurement of the first component to obtain the classification category associated with the second component (930) includes: utilizing a respective sample of the first component to obtain a respective classification category of a respective each sample of the second component, wherein the respective sample of the first component is a respective collocated sample of the first component to the respective each sample of the second component. For example, the current chroma sample classification is reusing the SAO type (EO or BO), class, and category of the collocated luma sample.

(123) In some embodiments, utilizing the characteristic measurement of the first component to obtain the classification category associated with the second component (930) includes: utilizing a respective sample of the first component to obtain a respective classification category of a respective each sample of the second component, wherein the respective sample of the first

component is reconstructed before being deblocked or is reconstructed after being deblocked. In some embodiment, the first component is being deblocked at a deblocking filter (DBF). In some embodiment, the first component is being deblocked at a luma deblocking filter (DBF Y). For example, alternative to FIG. 6 or 7, the CCSAO input can also be before DBF Y.

(124) In some embodiments, the characteristic measurement is derived by dividing the range of sample values of the first component into several bands and selecting a band based on the intensity value of a sample in the first component. In some embodiments, the characteristic measurement is derived from Band Offset (BO).

(125) In some embodiments, the characteristic measurement is derived based on the direction and strength of the edge information of a sample in the first component. In some embodiments, the characteristic measurement is derived from Edge Offset (E0).

(126) In some embodiments, modifying the second component (950) comprises directly adding the selected first offset to the second component. For example, the corresponding CCSAO offset value is added to the current chroma component sample.

(127) In some embodiments, modifying the second component (950) comprises mapping the selected first offset to a second offset and adding the mapped second offset to the second component. For example, for signaling CCSAO Cb and Cr offset values, if one additional chroma offset is signaled, the other chroma component offset can be derived by using a plus or minus sign, or weighting to save bits overhead.

(128) In some embodiments, receiving the video signal (910) comprises receiving a syntax element that indicates whether the method of decoding video signal using CCSAO is enabled for the video signal in the Sequence Parameter Set (SPS). In some embodiments, `cc_sao_enabled_flag` indicates whether CCSAO is enabled in the sequence level.

(129) In some embodiments, receiving the video signal (910) comprises receiving a syntax element that indicates whether the method of decoding video signal using CCSAO is enabled for the second component on the slice level. In some embodiments, `slice_cc_sao_cb_flag` or `slice_cc_sao_cr_flag` indicates whether CCSAO is enabled in the respective slice for Cb or Cr.

(130) In some embodiments, receiving the plurality of offsets associated with the second component (920) comprises receiving different offsets for different Coding Tree Units (CTUs). In some embodiments, for a CTU, `cc_sao_offset_sign_flag` indicates a sign for an offset, and `cc_sao_offset_abs` indicates the CCSAO Cb and Cr offset values of the current CTU.

(131) In some embodiments, receiving the plurality of offsets associated with the second component (920) comprises receiving a syntax element that indicates whether the received offsets of a CTU are the same as that of one of a neighboring CTU of the CTU, wherein the neighboring CTU is either a left or a top neighboring CTU. For example, `cc_sao_merge_up_flag` indicates whether CCSAO offset is merged from the left or up CTU.

(132) In some embodiments, the video signal further includes a third component and the method of decoding the video signal using CCSAO further includes: receiving a second plurality of offsets associated with a third component; utilizing the characteristic measurement of the first component to obtain a second classification category associated with the third component; selecting a third offset from the second plurality of offsets for the third component according to the second classification category; and modifying the third component based on the selected third offset.

(133) FIG. 11 is a block diagram of a sample process illustrating that all collocated and neighbouring (white) luma/chroma samples can be fed into CCSAO classification in accordance with some implementations of the present disclosure. FIG. 6A, 6B and FIG. 11 show the input of CCSAO classification. In FIG. 11, current chroma sample is 1104, the cross-component collocated chroma sample is 1102, and the collocated luma sample is 1106.

(134) In some embodiments, a classifier example (C0) uses the collocated luma or chroma sample value (Y0) in FIG. 12 below (Y4/U4/V4 in FIG. 6B, and FIG. 6C) for classification. Let `band_num` be the number of equally divided bands of luma or chroma dynamic range, and `bit_depth` be the

sequence bit depth, an example of the class index for the current chroma sample is:

$\text{Class}(C0) = (Y0 * \text{band_num}) \gg \text{bit_depth}$

(135) In some embodiments, the classification takes rounding into account, for example:

$\text{Class}(C0) = ((Y0 * \text{band_num}) + (1 \ll \text{bit_depth})) \gg \text{bit_depth}$

(136) Some band_num and bit_depth examples are listed below in Table 3. Table 3 shows three classification examples when the number of bands is different for each of the classification examples.

(137) TABLE-US-00003 TABLE 3 Exemplary band_num and bit_depth for each class index.

band_num	16	band_num	7	band_num	7	bit_depth	10	bit_depth	10	bit_depth	8	Class	Y0	Class	Y0															
Class	Y0	0	0	63	0	0	145	0	0	36	1	64	127	1	146	292	1	37	72	2	128	191	2	293	438	2	73	109	3	192
255	3	439	584	3	110	145	4	256	319	4	585	730	4	146	182	5	320	383	5	731	877	5	183	218	6	384	447			
6	878	1023	6	219	255	7	448	511	8	512	575	9	576	639	10	640	703	11	704	767	12	768	831	13	832					
895	14	896	959	15	960	1023																								

(138) In some embodiments, a classifier uses different luma sample position for C0 classification. FIG. 10A is a block diagram showing a classifier using different luma (or chroma) sample position for C0 classification in accordance with some implementations of the present disclosure, for example, using the neighboring Y7 but not Y0 for C0 classification.

(139) In some embodiments, different classifiers can be switched in Sequence Parameter Set (SPS)/Adaptation parameter set (APS)/Picture parameter set (PPS)/Picture header (PH)/Slice header (SH)/Region/Coding tree unit (CTU)/Coding unit (CU)/Subblock/Sample levels. For example, in FIG. 10, using Y0 for POC0 but using Y7 for POC1, as shown in Table 4 below.

(140) TABLE-US-00004 TABLE 4 Different classifiers are applied to different pictures POC

Classifier	C0	band_num	Total classes	0	C0 using Y0 position	8	8	1	C0 using Y7 position	8	8
------------	----	----------	---------------	---	----------------------	---	---	---	----------------------	---	---

(141) In some embodiments, FIG. 10B illustrates some examples of different shapes for luma candidates, in accordance with some implementations of the present disclosure. For example, a constraint can be applied to the shapes. In some instances, the total number of luma candidates must be the power of 2, as shown in FIG. 10B (b) (c) (d). In some instances, the number of luma candidates must be horizontal and vertical symmetric relative to the chroma sample (in the center), as shown in FIG. 10B (a) (c) (d) (e). In some embodiments, the power of 2 constraint and the symmetric constraint can also be applied for chroma candidates. The U/V part of FIG. 6B and FIG. 6C shows an example for symmetric constraint. In some embodiments, different color format can have different classifier “constraints”. For example, 420 color format uses luma/chroma candidate selection (one candidate selected from 3×3 shape) as shown in FIG. 6B and FIG. 6C, but 444 color format uses FIG. 10B(f) for luma and chroma candidate selection, 422 color format uses FIG. 10B(g) for luma (2 chroma samples share 4 luma candidates), FIG. 10B(f) for chroma candidates.

(142) In some embodiments, the C0 position and C0 band_num can be combined and switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. Different combinations can be different classifiers as shown in Table 5 below.

(143) TABLE-US-00005 TABLE 5 Different classifier and band number combinations are applied to different pictures POC

Classifier	C0	band_num	Total classes	0	C0 using Y0 position	16	16	1	C0 using Y7 position	8	8
------------	----	----------	---------------	---	----------------------	----	----	---	----------------------	---	---

(144) In some embodiments, the collocated luma sample value (Y0) is replaced by a value (Yp) obtained by weighing collocated and neighboring luma samples. FIG. 12 illustrates exemplary classifiers by replacing the collocated luma sample value with a value obtained by weighing collocated and neighboring luma samples in accordance with some implementations of the present disclosure. The collocated luma sample value (Y0) can be replaced by a phase corrected value (Yp) obtained by weighing neighboring luma samples. Different Yp can be a different classifier.

(145) In some embodiments, different Yp is applied on different chroma format. For example, in FIG. 12, the Yp of (a) is used for the 420 chroma format, the Yp of (b) is used for the 422 chroma format, and Y0 is used for the 444 chroma format.

(146) In some embodiments, another classifier (C1) is the comparison score $[-8, 8]$ of the collocated luma samples (Y_0) and neighboring 8 luma samples, which yields 17 classes in total as shown below. Initial Class (C_1)=0, Loop over neighboring 8 luma samples (Y_i , $i=1$ to 8) if $Y_0 > Y_i$ Class+=1 else if $Y_0 < Y_i$ Class-=1

(147) In some embodiments, the C_1 example is equal to the following function with threshold th being 0. $ClassIdx = Index2ClassTable(f(C, P_1) + f(C, P_2) + \dots + f(C, P_8))$ if $x - y > th$, $f(x, y) = 1$; if $x - y = th$, $f(x, y) = 0$; if $x - y < th$, $f(x, y) = -1$ wherein $Index2ClassTable$ is a look up table (LUT), C is the current or collocated sample, and P_1 to P_8 are neighboring samples.

(148) In some embodiments, similar to the C_4 classifier, one or more thresholds can be predefined (e.g., kept in a LUT) or signaled in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels to help classify (quantize) the difference.

(149) In some embodiments, a variation (C_1') only counts comparison score $[0, 8]$, and this yields 8 classes. (C_1, C_1') is a classifier group and a PH/SH level flag can be signaled to switch between C_1 and C_1' .

(150) Initial Class (C_1')=0, Loop over neighboring 8 luma samples (Y_i , $i=1$ to 8) if $Y_0 > Y_i$ Class+=1

(151) In some embodiments, a variation (C_1s) is selectively using neighboring N out of M neighboring samples to count the comparison score. An M -bit bitmask can be signaled at SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels to indicate which neighboring samples are selected to count the comparison score. Using FIG. 6B as an example for a luma classifier: 8 neighboring luma samples are candidates, and a 8-bit bitmask (01111110) is signaled at PH, indicating Y_1 to Y_6 6 samples are selected, so the comparison score is in $[-6, 6]$, which yields 13 offsets. The selective classifier C_1s gives encoder more choices to trade-off between offsets signaling overhead and classification granularity.

(152) Similar to C_1s , a variation ($C_1's$) is only counting comparison score $[0, +N]$, the previous bitmask 01111110 example gives comparison score in $[0, 6]$, which yields 7 offsets.

(153) In some embodiments, different classifiers are combined to yield a general classifier. For example, for different pictures (different POC values), different classifiers are applied as shown in Table 6-1 below.

(154) TABLE-US-00006 TABLE 6-1 Different general classifiers are applied to different pictures

POC	Classifier	C0 band_num	Total classes
0	combine C_0 and C_1	16	$16 * 17$
1	combine C_0 and C_1'	16	$16 * 9$
2	combine C_0 and C_1	7	$7 * 17$

(155) In some embodiments, another classifier example (C_3) is using a bitmask for classification as shown in Table 6-2. A 10-bit bitmask is signaled in

SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels to indicate the classifier. For example, bitmask 11 1100 0000 means that for a given 10-bit luma sample value, only most significant bit (MSB): 4 bits are used for classification, and that yields 16 classes in total. Another example bitmask 10 0100 0001 means that only 3 bits are used for classification, and that yields 8 classes in total.

(156) In some embodiments, the bitmask length (N) can be fixed or switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. For example, for a 10-bit sequence, a 4-bit bitmask 1110 is signaled in PH in a picture, and MSB 3 bits b_9, b_8, b_7 are used for classification. Another example is a 4-bit bitmask 0011 on LSB, and b_0, b_1 are used for classification. The bitmask classifier can apply on luma or chroma classification. Whether to use MSB or LSB for bitmask N can be fixed or switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels.

(157) In some embodiments, the luma position and C_3 bitmask can be combined and switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. Different combinations can be different classifiers.

(158) In some embodiments, a “max number of is” of the bitmask restriction can be applied to

restrict the corresponding number of offsets. For example, restricting “max number of 1s” of the bitmask to 4 in SPS, and that yields the max offsets in the sequence to be 16. The bitmask in different POC can be different, but the “max number of 1s” shall not exceed 4 (total classes shall not exceed 16). The “max number of 1s” value can be signaled and switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels.

(159) TABLE-US-00007 TABLE 6-2 Classifier example uses a bitmask for classification (bit mask position is underscored) POC Classifier C3 10-bit bitmask Total classes 0 C3 using Y0 11 1100 0000 16 position Luma sample value Class index 00 0000 1111 0 (0000) 10 1011 0011 9 (1010) 11 1100 1001 15 (1111) POC Classifier C3 10-bit bitmask Total classes 1 C3 using Y4 10 0100 0001 8 position Luma sample value Class index 00 0000 1111 1 (001) 10 1011 0011 5 (101) 11 1100 1001 7 (111)

(160) In some embodiments, as shown in FIG. 11, the other cross-component chroma samples, for example, chroma sample **1102** and its neighboring samples. can be also fed into the CCSAO classification, e.g., for the current chroma sample **1104**. For example, Cr chroma samples can be fed into the CCSAO Cb classification. Cb chroma samples can be fed into the CCSAO Cr classification. The classifier of cross-component chroma samples can be the same as luma cross-component classifier or can have its own classifier as described in this disclosure. The two classifiers can be combined to form a joint classifier to classify the current chroma sample. For example, a joint classifier combining cross-component luma and chroma samples, yields total 16 classes as shown in Table 6-3 below.

(161) TABLE-US-00008 TABLE 6-3 Classifier example using a joint classifier combining cross-component luma and chroma samples (bit mask position is underscored) POC Classifier classes Total classes 0 Combine C3 using Y4 position Bitmask: 8 1001000001 C0 using cross chroma C0 2 collocated position band_num: 2 16

(162) All abovementioned classifies (C0, C1, C1', C2, C3) can be combined. For example, see Table 6-4 below.

(163) TABLE-US-00009 TABLE 6-4 Different classifiers are combined POC Classifier Total classes 0 Combine C0, C0 C2 4*17*4 C1 and C2 band_num: 4 band_num: 4 1 Combine C0, C0 C2 6*9*4 C1' and C2 band_num: 6 band_num: 4 2 Combine C1 C3 Number 16*17 and C3 of 1s: 4

(164) In some embodiments, a classifier example (C2) uses the difference (Yn) of collocated and neighboring luma samples. FIG. 12 (c) shows an example of Yn, which has a dynamic range of [-1024, 1023] when bit depth is 10. Let C2 band_num be the number of equally divided bands of Yn dynamic range, Class (C2)=(Yn+(1<<bit_depth)*band_num)>>(bit_depth+1).

(165) In some embodiments, C0 and C2 are combined to yield a general classifier. For example, for different pictures (different POC), different classifiers are applied as shown in Table 7 below.

(166) TABLE-US-00010 TABLE 7 Different general classifiers are applied to different pictures Total POC Classifier C0 band_num C2 band_num classes 0 combine C0 and C2 16 16 16*17 1 combine C0 and C2 8 7 8*7

(167) In some embodiments, all above mentioned classifiers (C0, C1, C1', C2) are combined. For example, for different pictures (different POCs), different classifiers are applied as shown in Table 8-1 below.

(168) TABLE-US-00011 TABLE 8-1 Different general classifiers are applied to different pictures Total POC Classifier C0 band_num C2 band_num classes 0 combine C0, 4 4 4*17*4 C1 and C2 1 combine C0, 6 4 6*9*4 C1' and C2

(169) In some embodiments, a classifier example (C4) uses the difference of CCSAO input values and to-be-compensated sample values for classification as shown in Table 8-2 below. For example, if CCSAO is applied in the ALF stage, the difference of the current component pre-ALF and post-ALF sample values are used for classification. One or more thresholds can be predefined (e.g., kept in a look up table (LUT)) or signalled in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels to help classify (quantize) the difference. The C4 classifier can be combined with C0 Y/U/V

bandNum to form a joint classifier (for example, POC1 example as shown in Table 8-2).

(170) TABLE-US-00012 TABLE 8-2 a classifier example uses the difference of CCSAO input values and to-be-compensated sample values for classification Difference threshold Total POC Classifier (Th) bandNum classes 0 C4 with diff <= Th? < 0? < Th = 3 4 Th? Else 1 Combine C4/C0 using Y0 Th = 3 16 48 2 C4 with diff < Th1? < Th2? Th1 = 4, 3 Else Th2 = 5 3 C4 with diff <= Th? < Th? Th = 1 3 Else

(171) In some embodiments, a classifier example (C5) uses “coding information” to help subblock classification since different coding mode may introduce different distortion statistics in the reconstruction image. A CCSAO sample is classified by its sample previous coding information and the combination of the coding information can form a classifier, for example, as shown in Table 8-3 below. FIG. 30 below shows another example of different stages of the coding information for C5.

(172) TABLE-US-00013 TABLE 8-3 A CCSAO sample is classified by its sample previous coding information and the combination of the coding information can form a classifier POC 0 Comp Y U V Set 0 1 0 0 Pred info 3: 2: Skip? 2: intra 2: CCLM? inter/intra/else inherit luma? transform 2: LFNST? 2: MTS? 2: (local) 2: CTB > info dual tree? 32 × 32? quant info 2: dep quant? 2: dep quant 3: CU 2: slice odd? QP > 37/27? QP < 27? residual 2: all res 0? 3: all 3: JCCR CCP used? coding info res > 2/3/ow sign = 1/1/ow LMCS info 2: LMCS 3: map 2: is CRS 2: is CRS applied? slope > 0.5/0.7? applied? applied? DBF info 2: is long tap 3: inter/intra 3: DBF 2: tC DBF used bdry/ow H/Vow? value != 0? SAO info 2: is BO? 3: EO/BO/ow 5: 4 EO 2: BO start Types/ow from band 0? ALF info 2: is temporal 4: transpose 2: is CCALF 2: any 1 (APS) selected? idx applied? coeff = 0? Offsets num 384 1728 1080 256

(173) In some embodiments, a classifier example (C6) uses the YUV color transformed value for classification. For example, to classify the current Y component, 1/1/1 collocated or neighboring Y/U/V samples are selected to be color transformed to RGB, and using C3 bandNum to quantize the R value to be the current Y component classifier.

(174) In some embodiments, other classifier examples, which use only current component information for current component classification, can be used as cross-component classification. For example, as shown in FIG. 5 and Table 1, luma sample information and eo-class are used to derive an EdgeIdx, and classify the current chroma sample. Other “non-cross-component” classifiers which can also be used as cross-component classifiers include edge direction, pixel intensity, pixel variation, pixel variance, pixel sum-of-Laplacian, sobel operator, compass operator, high-pass filtered value, low-pass filtered value, etc.

(175) In some embodiments, plural classifiers are used in the same POC. The current frame is divided by several regions, and each region uses the same classifier. For example, 3 different classifiers are used in POC0, and which classifier (0, 1, or 2) is used is signaled in CTU level as shown in Table 9 below.

(176) TABLE-US-00014 TABLE 9 Different general classifiers are applied to different regions in the same picture POC Classifier C0 band_num Region 0 C0 using Y0 position 16 0 0 C0 using Y0 position 8 1 0 C0 using Y1 position 8 2

(177) In some embodiments, the maximum number of plural classifiers (plural classifiers can also be called alternative offset sets) can be fixed or signaled in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. In one example, the fixed (pre-defined) maximum number of plural classifiers is 4. In that case, 4 different classifiers are used in POC0, and which classifier (0, 1, or 2) is used is signaled in the CTU level. Truncated-unary (TU) code can be used to indicate the classifier used for each luma or chroma CTB. For example, as shown in Table 10 below, when TU code is 0: CCSAO is not applied; when TU code is 10: set 0 is applied; when TU code is 110, set 1 is applied; when TU code is 1110: set 2 is applied; when TU code is 1111: set 3 is applied. Fixed-length code, golomb-rice code, and exponential-golomb code can also be used to indicate the classifier (offset set index) for CTB. 3 different classifiers are used

in POC1.

(178) TABLE-US-00015 TABLE 10 Truncated-unary (TU) code is used to indicate the classifier used for each chroma CTB POC Classifier C0 band_num Region TU code 0 C0 using Y3 position 6 0 10 0 C0 using Y3 position 7 1 110 0 C0 using Y1 position 3 2 1110 0 C0 using Y6 position 6 3 1111 1 C0 using Y0 position 16 0 10 1 C0 using Y0 position 8 1 110 1 C0 using Y1 position 8 2 1110

(179) An example of Cb and Cr CTB offset set indices is given for 1280×720 sequence POC0 (number of CTUs in a frame is 10×6 if the CTU size is 128×128). POC0 Cb uses 4 offset sets and Cr uses 1 offset set. As shown in Table 11-1 below, when the offset set index is 0: CCSAO is not applied; when the offset set index is 1: set 0 is applied; when the offset set index is 2: set 1 is applied; when the offset set index is 3: set 2 is applied; when the offset set index is 4: set 3 is applied. Type means the position of the chosen collocated luma sample (Yi). Different offset sets can have different types, band_num and corresponding offsets.

(180) TABLE-US-00016 TABLE 11-1 An example of Cb and Cr CTB offset set indices is given for 1280 × 720 sequence POC0 (number of CTUs in a frame is 10 × 6 if the CTU size is 128 × 128)

ccsao_on_frame	POC:	0,	TID:	0,	comp:	0,	on:	1,	1cu_ctrl:	1,	set_num:	4,	set:	0,	type:	3,	band_num:	6			
ccsao_on_frame	POC:	0,	TID:	0,	comp:	0,	on:	1,	1cu_ctrl:	1,	set_num:	4,	set:	1,	type:	3,	band_num:	7			
ccsao_on_frame	POC:	0,	TID:	0,	comp:	0,	on:	1,	1cu_ctrl:	1,	set_num:	4,	set:	2,	type:	1,	band_num:	3			
ccsao_on_frame	POC:	0,	TID:	0,	comp:	0,	on:	1,	1cu_ctrl:	1,	set_num:	4,	set:	3,	type:	6,	band_num:	6			
ccsao_on_frame	POC:	0,	TID:	0,	comp:	1,	on:	1,	1cu_ctrl:	0,	set_num:	1,	set:	0,	type:	8,	band_num:	10			
1 0 2 2 0 0 1 2 0 0											1 1 1 1 1 1 1 1 1 0 0 0 0 1 1 1 1 2 4					1 1 1 1 1 1 1 1 1 1 1 1 4 1 3					
1 1 2 2 1											1 1 1 1 1 1 1 1 1 1 4 3 1 1 4 2 1 1 1 4					1 1 1 1 1 1 1 1 1 1 0 0 3 1 1 1 1 2 1 3					
											1 1 1 1 1 1 1 1 1 1 0 0 3 3 3 1 1 3 4 1					1 1 1 1 1 1 1 1 1 1 1 1 offset[0]	U: 6				
0 -1	2 V: -2	offset[1]									U: 2						1 -7	0 V: 0	offset[2]	U: 0	-1
-6 -2	V: 0	offset[3]									U: -2						2 0 -1	V: 0	offset[4]	U: -3	2 -0
-1 V: 0	offset[5]										U: -4						1 0 -7	V: 1	offset[6]	U:	
V: 1	offset[7]										U:						V: 0	offset[8]	U:		V: 0
	offset[9]										U:						V: 0	offset[10]	U:		V: -4
offset[11]											U:						V:	offset[12]	U:		V:
offset[13]											U:						V:	offset[14]	U:		V:
offset[15]											U:						V:				

(181) In some embodiments, an example of jointly using collocated/current and neighboring Y/U/V samples for classification is listed (3 component joint bandNum classification for each Y/U/V component) in Table 11-2 below. In POC0, {2,4,1} offset sets are used for {Y, U, V}, respectively. Each offset set can be adaptively switched in

SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. Different offset sets can have different classifiers. For example, as candidate position (candPos) indicating in FIGS. 6B and 6C, for classifying current Y4 luma sample, Y set0 selects {current Y4, collocated U4, collocated V4} as candidates, with different bandNum {Y, U, V}={16,1,2}, respectively. With {candY, candU, candV} as the sample values of selected {Y, U, V} candidates, the number of total classes is 32, and the class index derivation can be shown as:

```
bandY=(candY*bandNumY)>>BitDepth;
bandU=(candU*bandNumU)>>BitDepth;
bandV=(candV*bandNumV)>>BitDepth;
classIdx=bandY*bandNumU*bandNumV
+bandU*bandNumV
+bandV;
```

(182) Another example is in POC1 component V set1 classification. In that example, candPos={neighboring Y8, neighboring U3, neighboring VO} with bandNum={4,1,2} are used, which yields 8 classes.

(183) TABLE-US-00017 TABLE 11-2 An example of jointly using collocated/current and neighboring Y/U/V samples for classification Current offset Classifier: candPos(Y, U, V) Total classes POC Comp set with bandNum(Y, U, V) (offsets number) 0 Y 0 (Y4, U4, V4), (16, 1, 2) $16*1*2 = 32$ 1 (Y4, U0, V2), (15, 4, 1) $15*4*1 = 60$ U 0 (Y8, U3, V0), (1, 1, 2) 2 1 (Y4, U1, V0), (15, 2, 2) 60 2 (Y6, U6, V6), (4, 4, 1) 16 3 (Y2, U0, V5), (1, 1, 1) 1 V 0 (Y2, U0, V5), (1, 1, 1) 1 1 Y 0 (Y4, U1, V0), (15, 2, 2) 60 U 0 (Y6, U2, V1), (7, 1, 2) 14 V 0 (Y8, U3, V0), (1, 1, 2) 2 1 (Y8, U3, V0), (4, 1, 2) 8

(184) In some embodiments, an example of jointly using collocated and neighbouring Y/U/V samples for the current Y/U/V sample classification is listed (3 components joint edgeNum (C1s) and bandNum classification for each Y/U/V component), for example, as shown in Table 11-3 below. Edge CandPos is the centered position used for C1s classifier, edge bitMask is the CIs neighbouring samples activation indicator, and edgeNum is corresponding number of CIs classes. In this example, CIs is only applied on Y classifier (so edgeNum equals to edgeNumY) with edge candPos is always Y4 (current/collocated sample position). However, C1s can be applied on Y/U/V classifiers with edge candPos as the neighbouring sample position.

(185) With diff denoting Y C1s's comparison score, the classIdx derivation can be

```
bandY=(candY*bandNumY)>>BitDepth;
bandU=(candU*bandNumU)>>BitDepth;
bandV=(candV*bandNumV)>>BitDepth;
edgeIdx=diff+(edgeNum>>1);
bandIdx=bandY*bandNumU*bandNumV
+bandU*bandNumV
+bandV;
```

```
classIdx=bandIdx*edgeNum+edgeIdx;
```

(186) TABLE-US-00018 TABLE 11-3 An example of jointly using collocated/current and neighboring Y/U/V samples for classification (part 1) POC 0 Current Component Y U Set 0 1 2 0 edge candPos(y) (Y4) (Y4) (Y4) (Y4) edge bitmask(Y) 10000001 00010000 01111110 10000000 edgeNum 5, [-2, 2] 3, [-1, 1] 13, [-6, 6] 3, [-1, 1] band candPos(Y, U, V) (Y4, U4, V4) (Y4, U0, V2) (Y4, U1, V2) (Y8, U3, V0) bandNum(Y, U, V) (16, 1, 2) (15, 4, 1) (2, 1, 1) (1, 1, 2) Total classes $5*16*1*2 = 160$ $3*15*4*1 = 180$ $13*2*1*1* = 26$ $3*1*1*1*2 = 6$ Signaled offsets 160 offsets values: 180 offsets 26 offsets 6 offset (3, 3, 2, -1 . . .) values values values Sorted set idx 0 1 2 0 Component Y Y Y U (part 2) POC 1 Current Component V Y Set 1 2 3 0 0 edge candPos(y) (Y4) (Y4) (Y4) (Y4) reuse edge bitmask(Y) 00000000 00000000 10000001 00000000 reuse edgeNum 1, [0] 1, [0] 5, [-2, 2] 1, [0] reuse band candPos(Y, U, V) (Y4, U1, V0) (Y6, U6, V6) (Y2, U0, V5) (Y2, U0, V5) reuse bandNum(Y, U, V) (15, 2, 2) (4, 1, 1) (1, 1, 1) (1, 1, 1) reuse Total classes 60 4 1 1 160 Signaled offsets 60 offsets 4 offsets 1 offsets 1 offsets signal values values values idxY = 0, (1, 2, 0, 1) reuse params & offsets (3, 3, 2, -1 . . .) Sorted set idx 1 2 3 0 Component U U U V Y (part 3) POC Current Component U V Set 1 0 0 1 edge candPos(y) (Y4) reuse (Y4) (Y4) edge bitmask(Y) 11111111 reuse 00000000 00000000 edgeNum 17, [-8, 8] reuse 1, [0] 1, [0] band candPos(Y, U, V) (Y4, U1, V2) reuse (Y8, U3, V0) (Y8, U3, V0) bandNum(Y, U, V) (4, 1, 1) reuse (1, 1, 2) (4, 1, 2) Total classes $17*4*1*1 = 68$ 4 2 8 Signaled offsets 68 offsets signal 2 offsets 8 offsets values idxU = 2, values values reuse params & offsets (1, 2, 0, 1) Sorted set idx 3 Component Y U V V

(187) In some embodiments, the maximum band_num (bandNumY, bandNumU, or bandNumV) can be fixed or signaled in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/S ample levels. For example, fixing max band_num=16 in the decoder and for each frame, 4 bits are signaled to indicate the C0 band_num in a frame. Some other maximum band_num examples are listed below in Table 12.

(188) TABLE-US-00019 TABLE 12 Maximum band_num and band_num bit examples

Band_num_min Band_num_max Band_num bit 1 1 0 1 2 1 1 4 2 1 8 3 1 16 4 1 32 5 1 64 6 1 128 7 1 256 8

(189) In some embodiments, the max number of classes or offsets (combinations of jointly using multiple classifiers, for example, C1s edgeNum*C1 bandNumY*bandNumU*bandNumV) for each set (or all set added) can be fixed or signaled in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. For example, max is fixed for all sets added class_num=256*4, and an encoder conformance check or a decoder normative check can be used to check the constraint.

(190) In some embodiments, a restriction can be applied on the C0 classification, for example, restricting band_num (bandNumY, bandNumU, or bandNumV) to be only power of 2 values. Instead of explicitly signaling band_num, a syntax band_num_shift is signaled. Decoder can use shift operation to avoid multiplication. Different band_num_shift can be used for different component.

Class(C0)=(Y0>>band_num_shift)>>bit_depth

(191) Another operation example is taking rounding into account to reduce error.

Class(C0)=((Y0+(1<<(band_num_shift-1)))>>band_num_shift)>>bit_depth

(192) For example, if band_num_max (Y, U, or V) is 16, the possible band_num_shift candidates are 0, 1, 2, 3, 4, corresponding to band_num=1, 2, 4, 8, 16, as shown in Table 13.

(193) TABLE-US-00020 TABLE 13 Band_num and corresponding band_num_shift candidates

POC Classifier	C0 band_num_shift	C0 band_num	Total classes
0 C0 using Y0	4	16	16 position 1
C0 using Y7	3	8	8 position
Band_num_max	Valid band_num	Band_num_shift candidates	1 1 0 2 1, 2 0, 1 4 1, 2, 4 0, 1, 2 8 1, 2, 4, 8 0, 1, 2, 3 16 1, 2, 4, 8, 16 0, 1, 2, 3, 4 32 1, 2, 4, 8, 16, 32 0, 1, 2, 3, 4, 5 64 1, 2, 4, 8, 16, 32, 64 0, 1, 2, 3, 4, 5, 6 128 1, 2, 4, 8, 16, 32, 64, 128 0, 1, 2, 3, 4, 5, 6, 7 256 1, 2, 4, 8, 16, 32, 64, 128, 256 0, 1, 2, 3, 4, 5, 6, 7, 8

(194) In some embodiments, the classifiers applied to Cb and Cr are different. The Cb and Cr offsets for all classes can be signaled separately. For example, different signaled offsets are applied to different chroma components as shown in Table 14 below.

(195) TABLE-US-00021 TABLE 14 The Cb and Cr offsets for all classes can be signaled separately

Com-	Clas-	C0 Total	Signaled POC	ponent	sifier	band_num	classes	offsets
0	Cb	C0	16	16	0	Cr	C0	5 5 5

(196) In some embodiments, the max offset value is fixed or signaled in Sequence Parameter Set (SPS)/Adaptation parameter set (APS)/Picture parameter set (PPS)/Picture header (PH)/Slice header (SH)/Region/CTU/CU/Subblock/Sample levels. For example, the max offset is between [-15, 15]. Different component can have different max offset value.

(197) In some embodiments, the offset signaling can use Differential pulse-code modulation (DPCM). For example, offsets {3, 3, 2, 1, -1} can be signaled as {3, 0, -1, -1, -2}.

(198) In some embodiments, the offsets can be stored in APS or a memory buffer for the next picture/slice reuse. An index can be signaled to indicate which stored previous frame offsets are used for the current picture.

(199) In some embodiments, the classifiers of Cb and Cr are the same. The Cb and Cr offsets for all classes can be signaled jointly, for example, as shown in Table 15 below.

(200) TABLE-US-00022 TABLE 15 The Cb and Cr offsets for all classes can be signaled jointly

Com-	Clas-	Total	Signaled POC	ponent	sifier	C0 band_num	classes	offsets
0	Cb and Cr	C0	8	8	8			

(201) In some embodiments, the classifier of Cb and Cr can be the same. The Cb and Cr offsets for all classes can be signaled jointly, with a sign flag difference, for example, as shown in Table 16 below. According to Table 16, when Cb offsets are (3, 3, 2, -1), the derived Cr offsets are (-3, -3, -2, 1).

(202) TABLE-US-00023 TABLE 16 The Cb and Cr offsets for all classes can be signaled jointly with a sign flag difference

C0 Total	Signaled	Signaled POC	Component	Classifier	band_num	classes	offsets	sign flag
0	Cb and Cr	C0	4	4	4:	(3, 3, 2, -1)	1:	(-)

(203) In some embodiments, the sign flag can be signaled for each class. for example, as shown in Table 17 below. According to Table 17, when Cb offsets are (3, 3, 2, -1), the derived Cr offsets are (-3, 3, 2, 1) according to the respective signed flag.

(204) TABLE-US-00024 TABLE 17 The Cb and Cr offsets for all classes can be signaled jointly with a sign flag signaled for each class C0 Total Signaled Signaled POC Component Classifier band_num classes offsets sign flag 0 Cb and Cr C0 4 4 4: (3, 3, 2, -1) 1: (-, +, +, -)

(205) In some embodiments, the classifiers of Cb and Cr can be the same. The Cb and Cr offsets for all classes can be signaled jointly, with a weight difference, for example, as shown in Table 18 below. The weight (w) can be selected in a limited table, for example, $+\frac{1}{4}$, $+\frac{1}{2}$, 0, $-\frac{1}{2}$, $-\frac{1}{4}$, $-\frac{1}{2}$, $-\frac{3}{4}$, -1 , -2 , -4 . . . etc., where $|w|$ only includes the power-of-2 values. According to Table 18, when Cb offsets are (3, 3, 2, -1), the derived Cr offsets are (-6, -6, -4, 2) according to the respective signed flag.

(206) TABLE-US-00025 TABLE 18 The Cb and Cr offsets for all classes can be signaled jointly with a weight difference C0 Total Signaled Signaled POC Component Classifier band_num classes offsets weight 0 Cb and Cr C0 4 4 4: (3, 3, 2, -1) -2

(207) In some embodiments, the weight can be signaled for each class, for example, as shown in Table 19 below. According to Table 19, when Cb offsets are (3, 3, 2, -1), the derived Cr offsets are (-6, 12, 0, -1) according to the respective signed flag

(208) TABLE-US-00026 TABLE 19 The Cb and Cr offsets for all classes can be signaled jointly with a weight signaled for each class C0 Total Signaled Signaled POC Component Classifier band_num classes offsets weight 0 Cb and Cr C0 4 4 4: (3, 3, 2, -1) 4: (-2, 4, 0, 1)

(209) In some embodiments, if plural classifiers are used in the same POC, different offset sets are signaled separately or jointly.

(210) In some embodiments, the previously decoded offsets can be stored for use of future frames. An index can be signaled to indicate which previously decoded offsets set is used for the current frame, to reduce offsets signaling overhead. For example, POC0 offsets can be reused by POC2 with signaling offsets set idx=0 as shown in Table 20 below.

(211) TABLE-US-00027 TABLE 20 An index can be signaled to indicate which previously decoded offsets set is used for the current frame C0 Total Stored offset POC Component Classifier band_num classes Signaled offsets set idx 0 Cb C0 4 4 4: (3, 3, 2, -1) 0 0 Cr C0 4 4 4: (-2, 1, 0, 1) 0 1 Cb C0 4 4 4: (0, 0, 1, -1) 1 1 Cr C0 4 4 4: (1, 2, 0, 1) 1 2 Cb C0 4 4 Reuse offsets Signal (3, 3, 2, -1) idx = 0 2 Cr C0 4 4 Reuse offsets Signal (-2, 1, 0, 1) idx = 0

(212) In some embodiments, the reuse offsets set idx for Cb and Cr can be different, for example, as shown in Table 21 below.

(213) TABLE-US-00028 TABLE 21 An index can be signaled to indicate which previously decoded offsets set is used for the current frame, and the index can be different for Cb and Cr components. C0 Total Stored offset POC Component Classifier band_num classes Signaled offsets set idx 0 Cb C0 4 4 4: (3, 3, 2, -1) 0 0 Cr C0 4 4 4: (-2, 1, 0, 1) 0 1 Cb C0 4 4 4: (0, 0, 1, -1) 1 1 Cr C0 4 4 4: (1, 2, 0, 1) 1 2 Cb C0 4 4 Reuse offsets Signal (3, 3, 2, -1) idx = 0 2 Cr C0 4 4 Reuse offsets Signal (1, 2, 0, 1) idx = 1

(214) In some embodiments, the offset signaling can use additional syntax including start and length, to reduce signaling overhead. For example, when band_num=256, only offsets of band_idx=37-44 are signaled. In the example below in Table 22-1, the syntax of start and length both are 8 bits fixed-length coded that should match band_num bits.

(215) TABLE-US-00029 TABLE 22-1 the offset signaling uses additional syntax including start and length band_idx offset band_num_max band_num bits, start, length 1 0 1 0 2 0 2 1 3 0 4 2 . . . 8 3 37 start = 37 offset[0] 16 4 38 offset[1] 32 5 39 offset[2] 64 6 40 offset[3] 128 7 41 offset[4] 256 8 42 offset[5] 43 offset[6] 44 length = 8 offset[7] . . . 255 0 256 0

(216) In some embodiments, if CCSAO is applied to all YUV 3 components, collocated and neighbouring YUV samples can be jointly used for classification, and all abovementioned offsets signaling method for Cb/Cr can be extended to Y/Cb/Cr. In some embodiments, different

component offset set can be stored and used separately (each component has its own stored sets) or jointly (each component shares/reuses the same stored). A separate set example is shown in Table 22-2 below.

(217) TABLE-US-00030 TABLE 22-2 an example showing that different component offset set can be stored and used separately (each component has its own stored sets) or jointly (each component shares/reuses the same stored) Classifier: candPos(Y, Total U, V) with classes Sorted Current Offset bandNum (offsets offsets POC Component set (Y, U, V) number) Signaled offsets set idx 0 Y 0 (Y4, U4, V4), 16 * 1 * 2 = 32 offsets values 0 Y (16, 1, 2) 32 (3, 3, 2, 1, . . .) 1 (Y4, U0, V2), 15 * 4 * 1 = 60 offsets values 0 Y (14, 4, 1) 60 U 0 (Y8, U3, V0), 2 2 offsets values 0 U (1, 1, 2) 1 (Y4, U1, V0), 60 60 offsets values 1 U (15, 2, 2) 2 (Y6, U6, V6), 4 4 offsets values 2 U (4, 1, 1) 3 (Y2, U0, V5), 1 1 offsets values 3 U (1, 1, 1) V 0 (Y2, U0, V5), 1 1 offsets values 0 V (1, 1, 1) 1 Y 0 Reuse Y stored 32 Signal idx = 0 Y offset set idx 0 and reuse offsets (3, 3, 2, -1, . . .) U 0 Reuse U stored 4 Signal idx = 2 U offset set idx 2 and reuse offsets (1, 2, 0, 1) V 0 (Y8, U3, V0), 2 2 offsets values V (1, 1, 2) 1 (Y8, U3, V0), 8 8 offsets values V (4, 1, 2)

(218) In some embodiments, if a sequence bit depth is higher than 10 (or a certain bit depth), the offset can be quantized before signaling. On the decoder side, the decoded offset is dequantized before applying it as shown in Table 23 below. For example, for a 12-bit sequence, the decoded offsets are left shifted (dequantized) by 2.

(219) TABLE-US-00031 TABLE 23 The decoded offset is dequantized before applying it Signaled offset Dequantized and applied offset 0 0 1 4 2 8 3 12 . . . 14 56 15 60

(220) In some embodiments, the offset can be calculated as $CcSaoOffsetVal =$

$(1 - 2 * ccsao_offset_sign_flag) * (ccsao_offset_abs << (BitDepth - Min(10, BitDepth)))$

(221) In some embodiments, a sample processing is described below. Let $R(x, y)$ be the input luma or chroma sample value before CCSAO, $R'(x, y)$ be the output luma or chroma sample value after CCSAO:

$offset = ccsao_offset[class_index\ of\ R(x, y)]$

$R'(x, y) = Clip3(0, (1 << bit_depth) - 1, R(x, y) + offset)$

(222) According the above equations, each luma or chroma sample value $R(x, y)$ is classified using the indicated classifier of the current picture and/or current offset set idx. The corresponding offset of the derived class index is added to each luma or chroma sample value $R(x, y)$. A clip function Clip 3 is applied to the $(R(x, y) + offset)$ to make the output luma or chroma sample value $R'(x, y)$ within the bit depth dynamic range, for example, range 0 to $(1 << bit_depth) - 1$.

(223) In some embodiments, a boundary processing is described below. If any of the collocated and neighboring luma (chroma) samples used for classification is outside the current picture, CCSAO is not applied on the current chroma (luma) sample. FIG. 13A is a block diagram illustrating CCSAO is not applied on the current chroma (luma) sample if any of the collocated and neighboring luma (chroma) samples used for classification is outside the current picture in accordance with some implementations of the present disclosure. For example, in FIG. 13A(a), if a classifier is used, CCSAO is not applied on the left 1 column chroma components of the current picture. For example, if C1' is used, CCSAO is not applied on the left 1 column and the top 1 row chroma components of the current picture, as shown in FIG. 13A(b).

(224) FIG. 13B is a block diagram illustrating CCSAO is applied on the current luma or chroma sample if any of the collocated and neighboring luma or chroma samples used for classification is outside the current picture in accordance with some implementations of the present disclosure. In some embodiments, a variation is, if any of the collocated and neighboring luma or chroma samples used for classification is outside the current picture, the missed samples are used repetitively as shown in FIG. 13B(a), or the missed samples are mirror padded to create samples for classification as shown in FIG. 13B(b), and CCSAO can be applied on the current luma or chroma samples. In some embodiments, disabled/repetitive/mirror picture boundary processing method disclosed herein can also be applied on the subpicture/slice/tile/CTU/360 virtual boundary

if any of the collocated and neighboring luma (chroma) samples used for classification is outside the current subpicture/slice/tile/patch/CTU/360 virtual boundary.

(225) For example, a picture is divided into one or more tile rows and one or more tile columns. A tile is a sequence of CTUs that covers a rectangular region of a picture.

(226) A slice consists of an integer number of complete tiles or an integer number of consecutive complete CTU rows within a tile of a picture.

(227) A subpicture contains one or more slices that collectively cover a rectangular region of a picture.

(228) In some embodiments, a 360-degree video is captured on a sphere and inherently has no “boundary,” the reference samples that are out of the boundaries of a reference picture in the projected domain can always be obtained from neighboring samples in the spherical domain. For projection formats composed of a plurality of faces, no matter what kind of compact frame packing arrangement is used, discontinuities appear between two or more adjacent faces in the frame packed picture. In VVC, vertical and/or horizontal virtual boundaries, across which the in-loop filtering operations are disabled, are introduced and the positions of those boundaries are signalled in either SPS or Picture Header. Compared to using two tiles, one for each set of continuous faces, the use of 360 virtual boundary is more flexible as it does not require the face size to be a multiple of the CTU size. In some embodiments, the maximum number of vertical 360 virtual boundaries is 3 and the maximum number of horizontal 360 virtual boundaries is also 3. In some embodiments, The distance between two virtual boundaries is greater than or equal to the CTU size and the virtual boundary granularity is 8 luma samples, for example, an 8×8 sample grid.

(229) FIG. 14 is a block diagram illustrating CCSAO is not applied on the current chroma sample if a corresponding selected collocated or neighboring luma sample used for classification is outside a virtual space defined by a virtual boundary in accordance with some implementations of the present disclosure. In some embodiments, a virtual boundary (VB) is a virtual line that separates the space within a picture frame. In some embodiments, if a virtual boundary (VB) is applied in the current frame, CCSAO is not applied on the chroma samples that have selected corresponding luma position outside a virtual space defined by the virtual boundary. FIG. 14 shows an example with a virtual boundary for C0 classifier with 9 luma position candidates. For each CTU, CCSAO is not applied on the chroma samples for which the corresponding selected luma position is outside a virtual space surrounded by the virtual boundary. For example, in FIG. 14(a), CCSAO is not applied to the chroma sample 1402 when the selected Y7 luma sample position is on the other side of the horizontal virtual boundary 1406 which is located 4 pixel lines from the bottom side of the frame. For example, in FIG. 14(b), CCSAO is not applied to the chroma sample 1404 when the selected Y5 luma sample position is located on the other side of the vertical virtual boundary 1408 which is located y pixel lines from the right side of the frame.

(230) FIG. 15 shows repetitive or mirror padding can be applied on the luma samples that are outside the virtual boundary in accordance with some implementations of the present disclosure. FIG. 15 (a) shows an example of repetitive padding. If the original Y7 is chosen to be the classifier which is located on the bottom side of the VB 1502, the Y4 luma sample value is used for classification (copied to the Y7 position), instead of the original Y7 luma sample value. FIG. 15 (b) shows an example of mirror padding. If Y7 is chosen to be the classifier which is located on the bottom side of the VB 1504, the Y1 luma sample value which is symmetric to the Y7 value relative to the Y0 luma sample is used for classification, instead of the original Y7 luma sample value. The padding methods give more chroma samples possibility to apply CCSAO so more coding gain can be achieved.

(231) In some embodiments, a restriction can be applied to reduce the CCSAO required line buffer, and to simplify the boundary processing condition check. FIG. 16 shows additional 1 luma line buffer, i.e., the whole line luma samples of line -5 above the current VB 1602, may be required if all 9 collocated neighboring luma samples are used for classification in accordance with some

implementations of the present disclosure. FIG. 10B (a) shows an example using only 6 luma candidates for classification, which reduces the line buffer and does not need any additional boundary check in FIG. 13 A and FIG. 13 B.

(232) In some embodiments, using luma samples for CCSAO classification may increase the luma line buffer and hence increase the decoder hardware implementation cost. FIG. 17 shows an illustration in AVS that 9 luma candidates CCSAO crossing VB 1702 may increase 2 additional luma line buffers in accordance with some implementations of the present disclosure. For luma and chroma samples above Virtual Boundary (VB) 1702, DBF/SAO/ALF are processed at the current CTU row. For luma and chroma samples below VB 1702, DBF/SAO/ALF are processed at the next CTU row. In AVS decoder hardware design, luma line -4 to -1 pre DBF samples, line -5 pre SAO samples, and chroma line -3 to -1 pre DBF samples, line -4 pre SAO samples are stored as line buffers for next CTU row DBF/SAO/ALF processing. When processing the next CTU row, luma and chroma samples not in the line buffer are not available. However, for example, at chroma line -3 (b) position, the chroma sample is processed at the next CTU row, but CCSAO requires pre SAO luma sample lines -7, -6, and -5 for classification. Pre SAO luma sample lines -7, -6 are not in the line buffer so they are not available. And adding pre SAO luma samples line -7 and -6 to the line buffer will increase the decoder hardware implementation cost. In some examples, luma VB (line -4) and chroma VB (line -3) can be different (not aligned).

(233) Similar as FIG. 17, FIG. 18A shows an illustration in VVC that 9 luma candidates CCSAO crossing VB 1802 may increase 1 additional luma line buffer in accordance with some implementations of the present disclosure. VB can be different in different standard. In VVC, luma VB is line -4 and chroma VB is line -2, so 9 candidate CCSAO may increase 1 luma line buffer.

(234) In some embodiments, in a first solution, CCSAO is disabled for a chroma sample if any of the chroma sample's luma candidates is across VB (outside the current chroma sample VB). FIGS. 19A-19C show in AVS and VVC, CCSAO is disabled for a chroma sample if any of the chroma sample's luma candidates is across VB 1902 (outside the current chroma sample VB) in accordance with some implementations of the present disclosure. FIG. 14 also shows some examples of this implementation.

(235) In some embodiments, in a second solution, repetitive padding is used for CCSAO from a luma line close to and on the other side of the VB, for example, the luma line -4, for “cross VB” luma candidates. In some embodiments, repetitive padding from luma nearest neighbor below VB is implemented for “cross VB” chroma candidates. FIGS. 20A-20C show in AVS and VVC, CCSAO is enabled using repetitive padding for a chroma sample if any of the chroma sample's luma candidates is across VB 2002 (outside the current chroma sample VB) in accordance with some implementations of the present disclosure. FIG. 14 (a) also shows some examples of this implementation.

(236) In some embodiments, in a third solution, mirror padding is used for CCSAO from below luma VB for “cross VB” luma candidates. FIGS. 21A-21C show in AVS and VVC, CCSAO is enabled using mirror padding for a chroma sample if any of the chroma sample's luma candidates is across VB 2102 (outside the current chroma sample VB) in accordance with some implementations of the present disclosure. FIGS. 14 (b) and 13B (b) also show some examples of this implementation. In some embodiments, in a fourth solution, “double sided symmetric padding” is used for applying CCSAO. FIGS. 22A-22B show that CCSAO is enabled using double sided symmetric padding for some examples of different CCSAO shapes (for example, 9 luma candidates (FIG. 22A) and 8 luma candidates (FIG. 22B)) in accordance with some implementations of the present disclosure. For a luma sample set with a collocated centered luma sample of a chroma sample, if one side of the luma sample set is outside the VB 2202, double-sided symmetric padding is applied for both sides of the luma sample set. For example, in FIG. 22A, luma samples Y0, Y1, and Y2 are outside of the VB 2202, so both Y0, Y1, Y2 and Y6, Y7, Y8 are padded using Y3, Y4, Y5. For example, in FIG. 22B, luma sample Y0 is outside of the VB 2202, so Y0 is padded using

Y2, and Y7 is padded using Y5.

(237) FIG. **18B** shows an illustration when the collocated or neighbouring chroma samples are used to classify the current luma samples, the selected chroma candidate may be across VB and need additional chroma line buffer in accordance with some implementations of the present disclosure. Similar solutions 1 to 4 as described above can be applied to handle the issue.

(238) Solution 1 is to disable CCSAO for a luma sample when any of its chroma candidates may be across VB.

(239) Solution 2 is to use repetitive padding from chroma nearest neighbor below VB for “cross VB” chroma candidates.

(240) Solution 3 is to use mirror padding from below chroma VB for “cross VB” chroma candidates.

(241) Solution 4 is to use “double sided symmetric padding”. For a candidate set centered at CCSAO collocated chroma sample, if one side of the candidate set is outside VB, double-sided symmetric padding is applied for both sides.

(242) The padding methods give more luma or chroma samples possibility to apply CCSAO so more coding gain can be achieved.

(243) In some embodiments, at the bottom picture (or slice, tile, brick) boundary CTU row, the samples below VB are processed at the current CTU row, so the above special handling (Solution 1, 2, 3, 4) is not applied at the bottom picture (or slice, tile, brick) boundary CTU row. For example, a frame of 1920×1080 is divided by CTUs of 128×128. A frame contains 15×9 CTUs (round up). The bottom CTU row is the 15th CTU row. The decoding process is CTU row by CTU row, and CTU by CTU for each CTU row. Deblocking needs to be applied along horizontal CTU boundaries between the current and next CTU row. CTB VB is applied for each CTU row since inside one CTU, at the bottom 4/2 luma/chroma line, DBF samples (VVC case) are processed at the next CTU row and are not available for CCSAO at the current CTU row. However, at the bottom CTU row of the picture frame, the bottom 4/2 luma/chroma line DBF samples are available at the current CTU row since there is no next CTU row left and they are DBF processed at the current CTU row.

(244) In some embodiments, the VB displayed in FIGS. **13** to **22** can be replaced by a boundary of subpicture/slice/tile/patch/CTU/360 virtual boundary. In some embodiments, the positions of the chroma and luma samples in FIGS. **13** to **22** can be switched. In some embodiments, the positions of the chroma and luma samples in FIGS. **13** to **22** can be replaced by positions of a first chroma sample and a second chroma sample. In some embodiments, an ALF VB inside CTU may be commonly horizontal. In some embodiments, a boundary of subpicture/slice/tile/patch/CTU/360 virtual boundary may be horizontal or vertical.

(245) In some embodiments, a restriction can be applied to reduce the CCSAO required line buffer, and to simplify boundary processing condition check as explained in FIG. **16**. FIG. **23** shows the restrictions of using a limited number of luma candidates for classification in accordance with some implementations of the present disclosure. FIG. **23** (a) shows the restriction of using only 6 luma candidates for classification. FIG. **23** (b) shows the restriction of using only 4 luma candidates for classification.

(246) In some embodiments, applied region is implemented. The CCSAO applied region unit can be CTB based. That is, the on/off control, CCSAO parameters (offsets, luma candidate positions, band_num, bitmask . . . etc. used for classification, offset set index) are the same in one CTB.

(247) In some embodiments, the applied region can be not aligned to the CTB boundary. For example, the applied region is not aligned to chroma CTB boundary but shifted. The syntaxes (on/off control, CCSAO parameters) are still signaled for each CTB, but the truly applied region is not aligned to the CTB boundary. FIG. **24** shows the CCSAO applied region is not aligned to the CTB/CTU boundary **2406** in accordance with some implementations of the present disclosure. For example, the applied region is not aligned to chroma CTB/CTU boundary **2406** but top-left shifted

(4, 4) samples to VB 2408. This not-aligned CTB boundary design benefits the deblocking process since the same deblocking parameters are used for each 8×8 deblocking process region.

(248) In some embodiments, the CCSAO applied region unit (mask size) can be variant (larger or smaller than CTB size) as shown in Table 24. The mask size can be different for different components. The mask size can be switched in

SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. For example, in PH, a series of mask on/off flags and offset set indices are signaled to indicate each CCSAO region information.

(249) TABLE-US-00032 TABLE 24 CCSAO applied region unit (mask size) can be variant POC Component CTB size Mask size 0 Cb 64 × 64 128 × 128 0 Cr 64 × 64 32 × 32 1 Cb 64 × 64 16 × 16 1 Cr 64 × 64 256 × 256

(250) In some embodiments, the CCSAO applied region frame partition can be fixed. For example, partition the frame into N regions. FIG. 25 shows that the CCSAO applied region frame partition can be fixed with CCSAO parameters in accordance with some implementations of the present disclosure.

(251) In some embodiments, each region can have its own region on/off control flag and CCSAO parameters. Also, if the region size is larger than CTB size, it can have both CTB on/off control flags and region on/off control flag. FIGS. 25 (a) and (b) show some examples of partitioning the frame into N regions. FIG. 25 (a) shows vertical partitioning of 4 regions. FIG. 25 (b) shows square partitioning of 4 regions. In some embodiments, similar to picture level CTB all on control flag (ph_cc_sao_cb_ctb_control_flag/ph_cc_sao_cr_ctb_control_flag), if the region on/off control flag is off, CTB on/off flags can be further signaled. Otherwise CCSAO is applied for all CTBs in this region without further signaling CTB flags.

(252) In some embodiments, different CCSAO applied region can share the same region on/off control and CCSAO parameters. For example, in FIG. 25 (c), region 0~2 shares the same parameters and region 3~15 shares the same parameters. FIG. 25 (c) also shows the region on/off control flag and CCSAO parameters can be signaled in a Hilbert scan order.

(253) In some embodiments, the CCSAO applied region unit can be quad-tree/binary-tree/ternary-tree split from picture/slice/CTB level. Similar to the CTB split, a series of split flags are signaled to indicate the CCSAO applied region partition. FIG. 26 shows that the CCSAO applied region can be Binary-tree (BT)/Quad-tree (QT)/Ternary-tree (TT) split from frame/slice/CTB level in accordance with some implementations of the present disclosure.

(254) FIG. 27 is a block diagram illustrating a plurality of classifiers used and switched at different levels within a picture frame in accordance with some implementations of the present disclosure. In some embodiments, if plural classifiers are used in one frame, the method of how to apply the classifier set index can be switched in SPS/APS/PPS/PH/SH/Region/CTU/CU/Subblock/Sample levels. For example, four sets of classifiers are used in a frame, switched in PH as shown in Table 25 below. FIGS. 27 (a) and (c) show default fixed region classifier. FIG. 27 (b) shows classifier set index is signaled in mask/CTB level where 0 means CCSAO off for this CTB and 1~4 means set index.

(255) TABLE-US-00033 TABLE 25 Four sets of classifiers are used in a frame, switched in PH POC 0 Square partition 4 regions (same as frame QT split to max depth 1) (a) 1 CTB level switch classifier (b) 2 Vertical partition 4 regions (c) 3 Frame QT split to max depth 2

(256) In some embodiments, for default region case, a region level flag can be signaled if CTBs in this region do not use the default set index (for example, the region level flag is 0), but use other classifier set in this frame. For instance, if the default set index is used, the region level flag is 1. For example, in a square partition 4 regions, the following classifier sets are used as shown in Table 26 below,

(257) TABLE-US-00034 TABLE 26 A region level flag can be signaled to show if CTBs in this region do not use the default set index POC Region Flag Use default set index 0 1 1 Use default set: 1 2 1 Use default set: 2 3 1 Use default set: 3 4 0 CTB switch set 1 to 4

(258) FIG. 28 is a block diagram illustrating that the CCSAO applied region partition can be dynamic and switched in picture level, in accordance with some implementations of the present disclosure. For example, FIG. 28 (a) shows that 3 CCSAO offset sets are used in this POC (set_num=3), so the picture frame is vertically partitioned into 3 regions. FIG. 28 (b) shows that 4 CCSAO offset sets are used in this POC (set_num=4), so the picture frame is horizontally partitioned into 4 regions. FIG. 28 (c) shows that 3 CCSAO offset sets are used in this POC (set_num=3), so the picture frame is raster partitioned into 3 regions. Each region can have its own region all on flag to save per CTB on/off control bits. The number of regions is dependent on signaled picture set_num.

(259) The CCSAO applied region can be a specific area according to the coding information (sample position, sample coded modes, loop filter parameters, etc.) inside a block. For example, 1) the CCSAO applied region can be applied only when samples are skip mode coded, or 2) the CCSAO applied region only contains N samples along CTU boundaries, or 3) the CCSAO applied region only contains samples on an 8×8 grid in the frame, or 4) the CCSAO applied region only contains DBF-filtered samples, or 5) the CCSAO applied region only contains top M and left N rows in a CU. Different applied regions can use different classifiers. Different applied regions can use different classifiers. For example, in a CTU, the skip mode uses C1, an 8×8 grid uses C2, the skip mode and 8×8 grid uses C3. For example, in a CTU, skip mode coded samples use C1, samples at CU center use C2, samples that are skip mode coded at CU center use C3. FIG. 29 is a diagram illustrating the CCSAO classifiers can take current or cross component coding information into account, in accordance with some implementations of the present disclosure. For example, different coding modes/parameters/sample positions can form different classifiers. Different coding information can be combined to form a joint classifier. Different areas can use different classifiers. FIG. 29 also shows another example of applied region.

(260) In some embodiments, CCSAO syntax implemented is shown in Table 27 below. In some examples, the binarization of each syntax element can be changed. In AVS3, the term patch is similar with slice, and patch header is similar with the slice header. FLC stands for fixed length code. TU stands for truncated unary code. EGk stands for exponential-golomb code with order k, where k can be fixed. SVLC stands for signed EG0. UVLC stands for unsigned EG0.

(261) TABLE-US-00035 TABLE 27 A exemplary CCSAO syntax Level Syntax element
Binarization Meaning SPS cc_sao_enabled_flag FLC whether CCSAO is enabled in the sequence, can be inferred as off (disable state) when chromaFormat is CHROMA_400 PH/SH

ph_cc_sao_y_flag FLC whether CCSAO is enabled ph_cc_sao_cb_flag in this picture/slice for

ph_cc_sao_cr_flag Y/Cb/Cr, can be inferred as off (disable state) when chromaFormat is

CHROMA_400 PH/SH ph_cc_sao_stored_offsets_set_idx FLC which previously decoded offsets set is used, Y/U/V offset set can be separate or shared PH/SH ph_cc_sao_y_ctb_control_flag FLC

whether to enable Y/Cb/Cr ph_cc_sao_cb_ctb_control_flag on/off control at CTB level

ph_cc_sao_cr_ctb_control_flag PH/SH Ph_cc_sao_y_set_num_minus1 UVLC the number of alternative ph_cc_sao_cb_set_num_minus1 sets used in the picture/slice.

ph_cc_sao_cb_set_num_minus1 SPS/APS/ ph_cc_sao_y_class_y_enabled_flag FLC whether current component PPS/PH/ ph_cc_sao_y_class_u_enabled_flag can use other components SH/CTU ph_cc_sao_y_class_v_enabled_flag for classification

ph_cc_sao_cb_class_y_enabled_flag e.g., if ph_cc_sao_cb_class_u_enabled_flag

ph_cc_sao_y_class_u_enabled_flag = 0 ph_cc_sao_cb_class_v_enabled_flag component Y cannot use ph_cc_sao_cr_class_y_enabled_flag Cb sample for ph_cc_sao_cr_class_u_enabled_flag

classification, and a ph_cc_sao_cr_class_v_enabled_flag classification parameter such as

bandNumU does not need to be signalled. Otherwise if the flag is 1, Cb can be used to classify the

current Y. SPS/APS/ ph_cc_sao_y_band_num_y_minus1 FLC adaptively changed band PPS/PH/

ph_cc_sao_y_band_num_u_minus1 numbers for classification. SH/CTU

ph_cc_sao_y_band_num_v_minus1 e.g., ph_cc_sao_cb_band_num_y_minus1

ph_cc_sao_cb_band_num_y_minus1 ph_cc_sao_cb_band_num_u_minus1
 ph_cc_sao_cb_band_num_u_minus1 ph_cc_sao_cb_band_num_v_minus1
 ph_cc_sao_cb_band_num_v_minus1 ph_cc_sao_cr_band_num_y_minus1 indicates for component
 Cb ph_cc_sao_cr_band_num_u_minus1 classification, bandNum of
 ph_cc_sao_cr_band_num_v_minus1 Y/U/V used for 3 component joint bandNum classification
 SPS/APS/ ph_cc_sao_y_cand_pos_y FLC Indicating classifier PPS/PH/ ph_cc_sao_y_cand_pos_u
 candidate position. e.g., SH/CTU ph_cc_sao_y_cand_pos_v ph_cc_sao_y_cand_pos_y
 ph_cc_sao_cb_cand_pos_y ph_cc_sao_y_cand_pos_u ph_cc_sao_cb_cand_pos_u
 ph_cc_sao_y_cand_pos_v ph_cc_sao_cb_cand_pos_v indicates for component Y
 ph_cc_sao_cr_cand_pos_y classification, positions of ph_cc_sao_cr_cand_pos_u Y/U/V candidate
 are ph_cc_sao_cr_cand_pos_v selected as 3 component joint bandNum classification SPS/APS/
 cc_sao_y_offset_sign_flag FLC CCSAO Y, Cb and Cr offset PPS/PH/ cc_sao_y_offset_abs TU or
 EGk values of each class SH/CTU cc_sao_cb_offset_sign_flag FLC cc_sao_cb_offset_abs TU or
 EGk cc_sao_cr_offset_sign_flag cc_sao_cr_offset_abs CTU ctb_cc_sao_y_flag CABAC, 1
 whether CCSAO is enabled ctb_cc_sao_cb_flag or 2 (up & for the current Y, Cb or Cr
 ctb_cc_sao_cr_flag left) CTB contexts CTU ctb_cc_sao_y_set_idx TU or EGk which CCSAO
 offset set is ctb_cc_sao_cb_set_idx used for the current Y, Cb or ctb_cc_sao_cr_set_idx Cr CTB (if
 CCSAO is enabled) CTU cc_sao_y_merge_left_flag CABAC whether CCSAO offset is
 cc_sao_y_merge_up_flag merged from the left or up cc_sao_cb_merge_left_flag CTU
 cc_sao_cb_merge_up_flag cc_sao_cr_merge_left_flag cc_sao_cr_merge_up_flag
 (262) If a higher-level flag is off, the lower level flags can be inferred from the off state of the flag
 and do not need to be signaled. For example, if ph_cc_sao_cb_flag is false in this picture,
 ph_ccsao_cb_band_num_minus1, ph_cc_sao_cb_luma_type, cc_sao_cb_offset_sign_flag,
 cc_sao_cb_offset_abs ctb_cc_sao_cb(ag, cc_sao_cb_merge_left_flag, and cc_sao_cb_merge_up_flag
 are not present and inferred to be false.

(263) In some embodiments, the SPS ccsao_enabled_flag is conditioned on the SPS
 SAO_enabled_flag as shown in Table 28 below.

(264) TABLE-US-00036 TABLE 28 the SPS ccsao_enabled_flag is conditioned on the SPS SAO
 enabled flag sps_sao_enabled_flag u(1) if(sps_sao_enabled_flag && ChromaArrayType != 0)
 sps_ccsao_enabled_flag u(1) sps_alf_enabled_flag u(1) if(sps_alf_enabled_flag &&
 ChromaArrayType != 0) sps_ccalf_enabled_flag u(1)

(265) In some embodiments, ph_cc_sao_cb_ctb_control_flag, ph_cc_sao_cr_ctb_control_flag
 indicate whether to enable Cb/Cr CTB on/off control granularity. If
 ph_cc_sao_cb_ctb_control_flag, and ph_cc_sao_cr_ctb_control_flag are enabled,
 ctb_cc_sao_cb_flag and ctb_cc_sao_cr_flag can be further signaled. Otherwise, whether CCSAO is
 applied in the current picture depends on ph_cc_sao_cb_flag, ph_cc_sao_cr_flag, without further
 signaling ctb_cc_sao_cb_flag and ctb_cc_sao_cr_flag at CTB level.

(266) In some embodiments, for ph_cc_sao_cb_type and ph_cc_sao_cr_type, a flag can be further
 signaled to distinguish if the center collocated luma position is used (Y0 position in FIG. 10) for
 classification for a chroma sample, to reduce bit overhead. Similarly, if cc_sao_cb_type and
 cc_sao_cr_type are signaled in CTB level, a flag can be further signaled with the same mechanism.
 For example, if the number of the C0 luma position candidates is 9, cc_sao_cb_type0_flag is
 further signaled to distinguish if the center collocated luma position is used as shown in Table 29
 below. If the center collocated luma position is not used, cc_sao_cb_type_idc is used to indicate
 which of the remaining 8 neighboring luma positions is used.

(267) TABLE-US-00037 TABLE 29 cc_sao_cb_type0_flag is signaled to distinguish if the center
 collocated luma position is used ctb_cc_sao_cb_flag u(1) if(ctb_cc_sao_cb_flag)
 cc_sao_cb_type0_flag u(1), can be context coded if(!cc_sao_cb_type0_flag)
 cc_sao_cb_type_idc u(3), can be context coded

(268) The following Table 30 shows an example in AVS that single (set_num=1) or plural

(set_num>1) classifiers are used in the frame. Note the syntax notation can be mapped to the notation used above.

(269) TABLE-US-00038 TABLE 30 An example in AVS that single (set_num = 1) or plural (set_num > 1) classifiers are used in the picture frame ccsao_parameter_picture_header_set() {
for (compIdx=0;compIdx<2;compIdx++) { picture_ccsao_enable_flag[compIdx] u(1)
if (PictureCcSaoEnableFlag[compIdx]) {
picture_ccsao_lcu_control_flag[compIdx] u(1) if
(PictureCcSaoLcuControlFlag[compIdx]) { picture_ccsao_set_num_minus1[compIdx]
u(2) } for (setIdx=0; setIdx<PictureCcSaoSetNum[compIdx]; setIdx++) {
picture_ccsao_type[compIdx][setIdx] u(4)
picture_ccsao_band_num_minus1[compIdx][setIdx] u(4) } } }
ccsao_parameter_set() { for (compIdx=0;compIdx<2;compIdx++) { if
(PictureCcSaoEnableFlag[compIdx]) { if (PictureCcSaoLcuControlFlag[compIdx]) {
for (LcuIndex=0; LcuIndex<PictureWidthInLcu*PictureHeightInLcu) {
ccsao_lcu_enable_flag[compIdx][LcuIndex] ae(v) if (CcSaoLcuEnableFlag[compIdx]
[LcuIndex] && PictureCcSaoSetNum[comp] > 1) { ccsao_lcu_set_idx[compIdx]
[LcuIndex] ae(v) } } } for (setIdx=0;
setIdx<PictureCcSaoSetNum[comp]; setIdx++) { for (i=0;
i<PictureCcSaoBandNum[compIdx][setIdx]; i++){ ccsao_offset_abs[compIdx][setIdx]
[i] ae(v) if (CcSaoOffsetAbs[compIdx][setIdx][i]) {
ccsao_offset_sign[compIdx][setIdx][i] u(1) } } } } } }
(270) If combined with FIG. 25 or FIG. 27 in which each region has its own set, the syntax example can include region on/off control flag (picture_ccsao_lcu_control_flag[compIdx][setIdx]) as shown in Table 31 below.

(271) TABLE-US-00039 TABLE 31 Each region has its own set and the syntax example can include region on/off control flag (picture_ccsao_lcu_control_flag[compIdx][setIdx])

ccsao_parameter_picture_header_set() { for (compIdx=0;compIdx<2;compIdx++) {
picture_ccsao_enable_flag[compIdx] u(1) if (PictureCcSaoEnableFlag[compIdx]) {
picture_ccsao_set_num_minus1[compIdx] u(2) for (setIdx=0;
setIdx<PictureCcSaoSetNum[compIdx]; setIdx++) {
picture_ccsao_lcu_control_flag[compIdx][setIdx] u(1) picture_ccsao_type[compIdx]
[setIdx] u(4) picture_ccsao_band_num_minus1[compIdx][setIdx] u(4) } }
} }

(272) In some embodiments, an extension to the intra and inter post prediction SAO filter is illustrated further below. In some embodiments, the SAO classification methods disclosed in the present disclosure can serve as a post prediction filter, and the prediction can be intra, inter, or other prediction tools such as Intra Block Copy. FIG. 30 is a block diagram illustrating that the SAO classification methods disclosed in the present disclosure serve as a post prediction filter in accordance with some implementations of the present disclosure.

(273) In some embodiments, for each Y, U, and V component, a corresponding classifier is chosen. And for each component prediction sample, it is first classified, and a corresponding offset is added. For example, each component can use the current and neighboring samples for classification. Y uses the current Y and neighboring Y samples, and U/V uses the current U/V samples for classification as shown in Table 32 below. FIG. 31 is a block diagram illustrating that for post prediction SAO filter, each component can use the current and neighboring samples for classification in accordance with some implementations of the present disclosure.

(274) TABLE-US-00040 TABLE 32 A corresponding classifier is chosen for each Y, U, and V component Offset derived C0 Total from the current POC Component Classifier band_num classes component 0 Y combine C0 and C1 16 16*17 h_Y[i] 0 U C0 using U0 position 8 8 h_U[i] 0 V C0 using V0 position 32 32 h_V[i]

(275) In some embodiments, the refined prediction samples (Ypred', Upred', Vpred') are updated by adding the corresponding class offset and are used for intra, inter, or other prediction thereafter.

$Y_{pred}' = \text{clip3}(0, (1 << \text{bit_depth}) - 1, Y_{pred} + h_Y[i])$

$U_{pred}' = \text{clip3}(0, (1 << \text{bit_depth}) - 1, U_{pred} + h_U[i])$

$V_{pred}' = \text{clip3}(0, (1 << \text{bit_depth}) - 1, V_{pred} + h_V[i])$

(276) In some embodiments, for chroma U and V components, besides the current chroma component, the cross-component (Y) can be used for further offset classification. The additional cross-component offset (h'_U, h'_V) can be added on the current component offset (h_U, h_V), for example, as shown in Table 33 below.

(277) TABLE-US-00041 TABLE 33 For chroma U and V components, besides the current chroma component, the cross-component (Y) can be used for further offset classification Offset derived C0 Total from the current POC Component Classifier band_num classes component 0 U C0 using Y4 position 16 16 h'_U[i] 0 V C0 using Y1 position 7 7 h'_V[i]

(278) In some embodiments, the refined prediction samples (Upred'', Vpred'') are updated by adding the corresponding class offset and are used for intra, inter, or other prediction thereafter.

$U_{pred}'' = \text{clip3}(0, (1 << \text{bit_depth}) - 1, U_{pred}' + h'_U[i])$

$V_{pred}'' = \text{clip3}(0, (1 << \text{bit_depth}) - 1, V_{pred}' + h'_V[i])$

(279) In some embodiments, the intra and inter prediction can use different SAO filter offsets.

(280) FIG. 32 is a flowchart illustrating an exemplary process 3200 of decoding video signal using cross-component correlation in accordance with some implementations of the present disclosure.

(281) The video decoder 30 (as shown in FIG. 3), receives, from the video signal, a picture frame that includes a first component and a second component (3210).

(282) The video decoder 30, determines a classifier for the second component from a set of one or more samples of the first component associated with a respective sample of the second component (3220).

(283) The video decoder 30, determines whether to modify a value of the respective sample of the second component within a region of the picture frame according to the classifier (3230). In some embodiments, the region is formed by dividing the picture frame.

(284) The video decoder 30, in response to the determination to modify the value of the respective sample of the second component within the region according to the classifier, determines a sample offset for the respective sample of the second component according to the classifier (3240).

(285) The video decoder 30, modifies the value of the respective sample of the second component based on the determined sample offset (3250).

(286) In some embodiments, the first component is a luma component and the second component is a first chroma component, the first component is a first chroma component and the second component is a luma component, or the first component is a first chroma component and the second component is a second chroma component.

(287) In some embodiments, the region is one selected from the group consisting of subpicture, slice, tile, patch, coding tree unit (CTU), and 360 virtual boundary.

(288) In some embodiments, a boundary of the region is aligned with a CTU boundary.

(289) In some embodiments, a boundary of the region is aligned to a boundary of an 8×8 sample grid in the picture frame.

(290) In some embodiments, the region includes a region boundary including a first boundary of the first component and a second boundary of the second component.

(291) In some embodiments, the first boundary is not aligned with the second boundary.

(292) In some embodiments, the first boundary is aligned with the second boundary.

(293) In some embodiments, determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier (3230) includes: in accordance with a determination that any one sample of the set of one or more samples of the first component associated with the respective sample of the second component is located on

a different side of the region boundary relative to the respective sample of the second component, determining not to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

(294) In some embodiments, determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier (3230) includes: in accordance with a determination that: a first subset of the set of one or more samples of the first component associated with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, and a remaining subset of the set of one or more samples of the first component associated with the respective sample of the second component is located on a same side of the region boundary relative to the respective sample of the second component, replacing the first subset with a second subset from the remaining subset of the set of one or more samples of the first component to replace the first subset; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

(295) In some embodiments, the second subset from the remaining subset of the set of one or more samples of the first component is from a closest row or column of samples of the first component in the remaining subset to the first subset.

(296) In some embodiments, the second subset from the remaining subset of the set of one or more samples of the first component is located in a symmetric location of the region boundary or the respective sample of the second component to the first subset.

(297) In some embodiments, determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier (3230) comprises: in accordance with a determination that the set of one or more samples of the first component associated with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, replacing the set of one or more samples of the first component with a second set of samples of the first component on a same side of the region boundary relative to the respective sample of the second component to replace the set of one or more samples of the first component; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

(298) In some embodiments, the second set of samples on the same side of the region boundary relative to the respective sample of the second component is from a closest row or column of samples of the first component on the same side of the region boundary relative to the respective sample of the second component to the set of one or more samples of the first component.

(299) In some embodiments, the second set of samples on the same side of the region boundary relative to the respective sample of the second component is located in a symmetric location of the region boundary or the respective sample of the second component to the set of one or more samples of the first component.

(300) In some embodiments, determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier (3230) includes: in accordance with a determination that a first subset of the set of one or more samples of the first component associated with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, and a remaining subset of the set of one or more samples of the first component associated with the respective sample of the second component is located on a same side of the region boundary relative to the respective sample of the second component, replacing the first subset by with a second subset of one or more central subsets from the remaining subset of the set of one or more samples of the first component, and replacing a third subset in the remaining subset at a boundary position of the set of one or more samples of the first component with the second subset or a fourth subset of the one or more central subsets from the remaining subset of the set of one or more

samples of the first component; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

(301) In some embodiments, the third subset and the first subset are symmetrically located within the set of one or more samples of the first component.

(302) In some embodiments, determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier (3230) includes: in accordance with a determination that a chroma format of the video signal is 4:0:0, determining not to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

(303) FIG. 33 shows a computing environment 3310 coupled with a user interface 3350. The computing environment 3310 can be part of a data processing server. The computing environment 3310 includes a processor 3320, a memory 3330, and an Input/Output (I/O) interface 3340.

(304) The processor 3320 typically controls overall operations of the computing environment 3310, such as the operations associated with display, data acquisition, data communications, and image processing. The processor 3320 may include one or more processors to execute instructions to perform all or some of the steps in the above-described methods. Moreover, the processor 3320 may include one or more modules that facilitate the interaction between the processor 3320 and other components. The processor may be a Central Processing Unit (CPU), a microprocessor, a single chip machine, a Graphical Processing Unit (GPU), or the like.

(305) The memory 3330 is configured to store various types of data to support the operation of the computing environment 3310. The memory 3330 may include predetermined software 3332. Examples of such data includes instructions for any applications or methods operated on the computing environment 3310, video datasets, image data, etc. The memory 3330 may be implemented by using any type of volatile or non-volatile memory devices, or a combination thereof, such as a Static Random Access Memory (SRAM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), an Erasable Programmable Read-Only Memory (EPROM), a Programmable Read-Only Memory (PROM), a Read-Only Memory (ROM), a magnetic memory, a flash memory, a magnetic or optical disk.

(306) The I/O interface 3340 provides an interface between the processor 3320 and peripheral interface modules, such as a keyboard, a click wheel, buttons, and the like. The buttons may include but are not limited to, a home button, a start scan button, and a stop scan button. The I/O interface 3340 can be coupled with an encoder and decoder.

(307) In an embodiment, there is also provided a non-transitory computer-readable storage medium comprising a plurality of programs, for example, in the memory 3330, executable by the processor 3320 in the computing environment 3310, for performing the above-described methods.

Alternatively, the non-transitory computer-readable storage medium may have stored therein a bitstream or a data stream comprising encoded video information (for example, video information comprising one or more syntax elements) generated by an encoder (for example, the video encoder 20 in FIG. 2) using, for example, the encoding method described above for use by a decoder (for example, the video decoder 30 in FIG. 3) in decoding video data. The non-transitory computer-readable storage medium may be, for example, a ROM, a Random Access Memory (RAM), a CD-ROM, a magnetic tape, a floppy disc, an optical data storage device or the like.

(308) In an embodiment, there is also provided a computing device comprising one or more processors (for example, the processor 3320); and the non-transitory computer-readable storage medium or the memory 3330 having stored therein a plurality of programs executable by the one or more processors, wherein the one or more processors, upon execution of the plurality of programs, are configured to perform the above-described methods.

(309) In an embodiment, there is also provided a computer program product comprising a plurality of programs, for example, in the memory 3330, executable by the processor 3320 in the computing environment 3310, for performing the above-described methods. For example, the computer

program product may include the non-transitory computer-readable storage medium.

(310) In an embodiment, the computing environment **3310** may be implemented with one or more ASICs, DSPs, Digital Signal Processing Devices (DSPDs), Programmable Logic Devices (PLDs), FPGAs, GPUs, controllers, micro-controllers, microprocessors, or other electronic components, for performing the above methods.

(311) Further embodiments also include various subsets of the above embodiments combined or otherwise re-arranged in various other embodiments.

(312) In one or more examples, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored on or transmitted over, as one or more instructions or code, a computer-readable medium and executed by a hardware-based processing unit. Computer-readable media may include computer-readable storage media, which corresponds to a tangible medium such as data storage media, or communication media including any medium that facilitates transfer of a computer program from one place to another, e.g., according to a communication protocol. In this manner, computer-readable media generally may correspond to (1) tangible computer-readable storage media which is non-transitory or (2) a communication medium such as a signal or carrier wave. Data storage media may be any available media that can be accessed by one or more computers or one or more processors to retrieve instructions, code and/or data structures for implementation of the implementations described in the present application. A computer program product may include a computer-readable medium.

(313) The terminology used in the description of the implementations herein is for the purpose of describing particular implementations only and is not intended to limit the scope of claims. As used in the description of the implementations and the appended claims, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, elements, and/or components, but do not preclude the presence or addition of one or more other features, elements, components, and/or groups thereof.

(314) It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first electrode could be termed a second electrode, and, similarly, a second electrode could be termed a first electrode, without departing from the scope of the implementations. The first electrode and the second electrode are both electrodes, but they are not the same electrode.

(315) Reference throughout this specification to “one example,” “an example,” “exemplary example,” or the like in the singular or plural means that one or more particular features, structures, or characteristics described in connection with an example is included in at least one example of the present disclosure. Thus, the appearances of the phrases “in one example” or “in an example,” “in an exemplary example,” or the like in the singular or plural in various places throughout this specification are not necessarily all referring to the same example. Furthermore, the particular features, structures, or characteristics in one or more examples may include combined in any suitable manner.

(316) The description of the present application has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications, variations, and alternative implementations will be apparent to those of ordinary skill in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others skilled in the art to

understand the invention for various implementations and to best utilize the underlying principles and various implementations with various modifications as are suited to the particular use contemplated. Therefore, it is to be understood that the scope of claims is not to be limited to the specific examples of the implementations disclosed and that modifications and other implementations are intended to be included within the scope of the appended claims.

Claims

1. A method of decoding a video signal, comprising: receiving, from the video signal, a region of a picture frame that includes a first component and a second component, wherein the region is formed by dividing the picture frame; determining a classifier for the second component based on characteristic measurement of a set of one or more samples of the first component collocated or neighboring with a respective sample of the second component; determining whether to modify a value of the respective sample of the second component within the region of the picture frame according to the classifier; in response to the determination to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier, determining a sample offset for the respective sample of the second component according to the classifier; and modifying the value of the respective sample of the second component based on the determined sample offset.
2. The method of claim 1, wherein the first component is a luma component and the second component is a first chroma component, or the first component is a first chroma component and the second component is a luma component, or the first component is a first chroma component and the second component is a second chroma component.
3. The method of claim 1, wherein the region is one selected from a group consisting of subpicture, slice, tile, patch, coding tree unit (CTU), and 360 virtual boundary.
4. The method of claim 3, wherein a boundary of the region is aligned with a CTU boundary.
5. The method of claim 3, wherein a boundary of the region is aligned with a boundary of an 8×8 sample grid in the picture frame.
6. The method of claim 1, wherein the region includes a region boundary including a first boundary of the first component and a second boundary of the second component.
7. The method of claim 6, wherein the first boundary is not aligned with the second boundary; or the first boundary is aligned with the second boundary.
8. The method of claim 6, wherein determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier comprises: in accordance with a determination that any one sample of the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, determining not to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.
9. The method of claim 6, wherein determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier comprises: in accordance with a determination that: a first subset of the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, and a remaining subset of the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a same side of the region boundary relative to the respective sample of the second component, replacing the first subset with a second subset from the remaining subset of the set of one or more samples of the first component; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.

10. The method of claim 9, wherein the second subset from the remaining subset of the set of one or more samples of the first component is from a closest row or column of samples of the first component in the remaining subset to the first subset.
11. The method of claim 9, wherein the second subset from the remaining subset of the set of one or more samples of the first component is located in a symmetric location of the region boundary or the respective sample of the second component to the first subset.
12. The method of claim 6, wherein determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier comprises: in accordance with a determination that the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, replacing the set of one or more samples of the first component with a second set of samples of the first component on a same side of the region boundary relative to the respective sample of the second component; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.
13. The method of claim 12, wherein the second set of samples on the same side of the region boundary relative to the respective sample of the second component is from a closest row or column of samples of the first component on the same side of the region boundary relative to the respective sample of the second component to the set of one or more samples of the first component.
14. The method of claim 12, wherein the second set of samples on the same side of the region boundary relative to the respective sample of the second component is located in a symmetric location of the region boundary or the respective sample of the second component to the set of one or more samples of the first component.
15. The method of claim 6, wherein determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier comprises: in accordance with a determination that a first subset of the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a different side of the region boundary relative to the respective sample of the second component, and a remaining subset of the set of one or more samples of the first component collocated or neighboring with the respective sample of the second component is located on a same side of the region boundary relative to the respective sample of the second component, replacing the first subset with a second subset of one or more central subsets from the remaining subset of the set of one or more samples of the first component, and replacing a third subset in the remaining subset at a boundary position of the set of one or more samples of the first component with the second subset or a fourth subset of the one or more central subsets from the remaining subset of the set of one or more samples of the first component; and determining to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.
16. The method of claim 15, wherein the third subset and the first subset are symmetrically located within the set of one or more samples of the first component.
17. The method of claim 1, wherein determining whether to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier comprises: in accordance with a determination that a chroma format of the video signal is 4:0:0, determining not to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier.
18. An electronic apparatus for decoding a video signal comprising: one or more processors; a non-transitory computer-readable memory configured to store instructions executable by the one or more processors, wherein the one or more processors, upon execution of the instructions, are configured to: receive, from the video signal, a region of a picture frame that includes a first

component and a second component, wherein the region is formed by dividing the picture frame; determine a classifier for the second component based on characteristic measurement of a set of one or more samples of the first component collocated or neighboring with a respective sample of the second component; determine whether to modify a value of the respective sample of the second component within the region of the picture frame according to the classifier; in response to the determination to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier, determine a sample offset for the respective sample of the second component according to the classifier; and modify the value of the respective sample of the second component based on the determined sample offset.

19. A method for storing a bitstream, comprising: performing an encoding method to generate a bitstream; storing the bitstream; wherein the encoding method comprising: obtaining a region of a picture frame that includes a first component and a second component, wherein the region is formed by dividing the picture frame; determining a classifier for the second component based on characteristic measurement of a set of one or more samples of the first component collocated or neighboring with a respective sample of the second component; determining whether to modify a value of the respective sample of the second component within the region of the picture frame according to the classifier; in response to the determination to modify the value of the respective sample of the second component within the region of the picture frame according to the classifier, determining a sample offset for the respective sample of the second component according to the classifier; and modifying the value of the respective sample of the second component based on the determined sample offset.
