

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397185
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Multer; Thomas

Flexible dry sprinkler having a differential pressure controller

Abstract

A dry fire protection sprinkler in which, when a ratio of a pressure P1 of a pressurized fluid in a flexible tube to a pressure P3 of the fluid in a fluid supply line is less than a predetermined ratio of at least 3 to 1, a differential pressure controller sends a signal to a control valve to open, in order to allow the pressurized fluid in a pressurized fluid source at a pressure of P2 to enter the flexible tube, and, when the ratio of the pressure P1 of the pressurized fluid in the flexible tube to the pressure P3 of the fluid in the fluid supply line equals the predetermined ratio, the differential pressure controller sends a signal to the control valve to close.

Inventors:	Multer; Thomas (Liberty, SC)
Applicant:	The Reliable Automatic Sprinkler Co. Inc. (Liberty, SC)
Family ID:	1000008780984
Assignee:	The Reliable Automatic Sprinkler Co. Inc. (Liberty, SC)
Appl. No.:	18/633704
Filed:	April 12, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240252863 A1	Aug. 01, 2024

Related U.S. Application Data

continuation parent-doc US 18340095 20230623 US 11998781 child-doc US 18633704
continuation parent-doc US 17341662 20210608 US 11730990 20230822 child-doc US 18340095
continuation parent-doc US 15989316 20180525 US 11083920 20210810 child-doc US 17341662
continuation parent-doc US 13757448 20130201 US 9999793 20180619 child-doc US 15989316
us-provisional-application US 61594972 20120203

Publication Classification

Int. Cl.: **A62C37/11** (20060101); **A62C3/00** (20060101); **A62C35/60** (20060101); **A62C35/68** (20060101); A62C35/62 (20060101)

U.S. Cl.:

CPC **A62C37/11** (20130101); **A62C3/004** (20130101); **A62C35/68** (20130101); A62C35/60 (20130101); A62C35/62 (20130101)

Field of Classification Search

CPC: A62C (35/68); A62C (35/60); A62C (35/62); A62C (35/64); A62C (37/10); A62C (37/11); A62C (37/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1405411	12/1921	Hamilton	169/5	A62C 35/605
3329215	12/1966	Kane	N/A	N/A
4311198	12/1981	Vasquez	169/11	A62C 27/00
6488097	12/2001	MacDonald, III et al.	N/A	N/A
7389824	12/2007	Jackson	239/69	A62C 35/58
7802628	12/2009	Silva, Jr.	169/17	A62C 37/14
11083920	12/2020	Multer	N/A	N/A
11730990	12/2022	Multer	169/37	A61P 19/00
11998781	12/2023	Multer	N/A	A61P 43/00
2003/0075343	12/2002	Ballard	169/37	A62C 3/004
2009/0254315	12/2008	Golinveaux	N/A	N/A
2010/0038099	12/2009	Thompson et al.	N/A	N/A
2011/0127049	12/2010	Long	N/A	N/A
2012/0031630	12/2011	Stephens	N/A	N/A
2012/0298383	12/2011	Shipman	169/37	A62C 35/68

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012/166636	12/2011	WO	N/A
2012/166644	12/2011	WO	N/A

Primary Examiner: Dandridge; Christopher R

Attorney, Agent or Firm: Venable LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/340,095, filed Jun. 23, 2023, now U.S. Pat. No. 11,998,781,

issued Jun. 4, 2024, which is a continuation of U.S. patent application Ser. No. 17/341,662, filed Jun. 8, 2021, now U.S. Pat. No. 11,730,990, issued Aug. 22, 2023, which is a continuation of U.S. patent application Ser. No. 15/989,316, filed May 25, 2018, now U.S. Pat. No. 11,083,920, issued on Aug. 10, 2021, which is a continuation of U.S. patent application Ser. No. 13/757,448, filed Feb. 1, 2013, now U.S. Pat. No. 9,999,793, issued on Jun. 19, 2018, and which claims priority to U.S. Provisional Patent Application No. 61/594,972, filed Feb. 3, 2012, each of which is incorporated herein by reference.

FIELD OF THE INVENTION

(1) My invention relates to a dry fire protection sprinkler. In particular, my invention relates to a dry fire protection sprinkler for use in an area that is exposed to freezing conditions. In addition, my invention relates to a dry fire protection sprinkler having a differential pressure controller.

BACKGROUND OF THE INVENTION

(2) Dry sprinklers are used in areas that are exposed to freezing conditions, such as in freezers or outdoor walkways. In some dry-pipe systems, fluid supply conduits are positioned in a space in which the fluid in the fluid supply conduit is not subject to freezing. A dry sprinkler is attached to the fluid supply conduit and extends into a space in which the fluid would otherwise be subject to freezing.

(3) A typical dry sprinkler comprises a sprinkler head, a tube, a pipe connector at an inlet end of the tube that connects the inlet end to a pipe network of a fire suppression system, a plug seal at the inlet end to prevent water from entering the tube, and an actuating mechanism to maintain the plug seal at the inlet end. Typically, the sprinkler head is attached to an end of the tube that is opposite to the inlet end of the tube. Also, the tube section is conventionally vented to the atmosphere to allow drainage of any condensate that may form in the tube.

(4) Examples of dry sprinklers are generally disclosed in U.S. Pat. No. 5,775,431 to Ondracek, and in U.S. Pat. No. 5,967,240 to Ondracek. As shown generally in these patents, the actuating mechanism of a dry sprinkler can be a rod or another similar structure that extends through the tube between the sprinkler head and the inlet end to maintain the plug seal at the inlet end. The actuating mechanism includes a thermally responsive support element at the sprinkler head that supports the rod and, therefore, the plug seal at the inlet end. In some dry sprinklers, the tube is also sealed at the sprinkler head end of the tube and the actuating mechanism is supported at the sprinkler head end by a seal cap that is supported by the thermally responsive support element. In such arrangements, the space in the tube between the seal cap and the plug seal can be filled with a pressurized gas, such as dry air or nitrogen, or with a liquid, such as an antifreeze solution. When an elevated temperature occurs, the thermally responsive support element fails, releasing the plug seal (and also any lower seal at the sprinkler head end of the tube) to allow water from the fluid supply conduit to flow into and through the tube to the sprinkler head, whereupon the fluid is distributed by the sprinkler head.

(5) Conventional dry sprinklers are fabricated using a rigid tube having a seal at the inlet that is separated from the thermally responsive support element of the sprinkler, which is intended to be positioned in an area exposed to freezing conditions, such as an area that is not heated. The rigid tube extends into the unheated area from a wet pipe system (located in a heated area) and must be precisely aligned and installed while avoiding various architectural, structural, and mechanical obstructions typically found in commercial or industrial buildings.

SUMMARY OF THE INVENTION

(6) To remedy the problems and difficulties noted above, in one aspect, the invention provides a dry sprinkler having a flexible tube section that has a first end having an inlet opening, and a second end having an outlet opening. The flexible tube section is configured to contain a pressurized fluid between the first end and the second end. The pressurized fluid includes a liquid anti-freeze solution that is not susceptible to freezing at the freezing point of water. The dry

sprinkler includes a supply line connection having a first end connected to the inlet opening of the first end of the flexible tube section and having an opening, and a second end configured to connect to a supply line to receive a supply fluid from the supply line. A first seal is configured to seal the opening at the first end of the supply line connection to prevent the supply fluid from the supply line from entering the flexible tube section. The first seal is maintained in a sealed position by a pressure of the pressurized fluid so as to seal the opening at the first end of the supply line connection. A sprinkler head is coupled to the second end of the flexible tube section. The sprinkler head has a frame connected to the second end of the flexible tube section, an output orifice centrally located within the frame, a deflector connected to the frame, a second seal configured to seal the output orifice of the sprinkler head, and a thermally responsive element between the frame and the second seal. The thermally responsive element is configured to maintain the second seal in a sealed position when the thermally responsive element is in a non-responsive state. A differential pressure controller is connected to the flexible tube section between the first seal and the second seal, and is connected to the supply line connection. The differential pressure controller is configured to supply the pressurized fluid to the flexible tube section in order to maintain a ratio between the pressure of the pressurized fluid in the flexible tube section and a pressure of the supply fluid in the supply line to at least a certain ratio. The pressure of the pressurized fluid in the flexible tube section is not equal to the pressure of the supply fluid in the supply line. The thermally responsive element is configured to switch from the non-responsive state to a responsive state to release the second seal in response to an elevated temperature condition, and to permit the release of the pressurized fluid in the flexible tube section. The release of the pressurized fluid in the flexible tube section releases the first seal from the seal position.

Description

BRIEF DESCRIPTION OF THE DRAWING

(1) FIG. 1 shows a flexible dry sprinkler in accordance with an embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(2) As shown in FIG. 1, a flexible dry sprinkler arrangement comprises a generally flexible tube **1** that is connected at one end to a sprinkler head **2** and connected at another end to a fitting **3** constructed to be coupled to a wet pipe, a dry pipe, or a pre-action fire sprinkler system. The fitting **3** includes an inlet seal assembly having a first seal **4** that is normally in a closed or sealed position for preventing the flow of fluid from the fitting **3** through the flexible tube **1** and the sprinkler head **2**. The flexible tube **1** is also sealed at the sprinkler head **2** by an outlet seal assembly having a second seal **5** (e.g., a sealing cap) that is supported by a thermal release element **6** compressed between the second seal **5** and a frame **7** of the sprinkler head **2**. The first seal **4** is generally formed as an annular plug having a grooved outer edge that sits against an annular spring washer **9** of the inlet seal assembly, such as a Belleville washer. The annular spring washer **9** is configured to seal with an annular flange **10** extending from an inner wall of the fitting **3**. The second seal **5** is formed similarly to the first seal **4**, and also is generally formed as an annular disk **11** having an outer annular groove that receives a spring washer **12** of the outlet seal assembly. The spring washer **12** is constructed to seal against a sealing flange **13** formed in an output orifice **14** of the sprinkler head **2**.

(3) The flexible tube **1** can be formed from a metallic or a non-metallic material. For example, in one embodiment, the flexible tube **1** is formed from a corrugated metal hose, and, in another embodiment, the flexible tube **1** is formed from a corrugated plastic hose. The outer surface of the flexible tube **1** can be covered, such as with a braided jacket, to protect the flexible tube **1**. As shown in the preferred embodiment, the sprinkler head **2** has male threads that engage with female threads on the output end of the flexible tube **1**. The female threaded connection of the flexible tube

1 can have a nominal diameter that is between $\frac{1}{2}$ inch and 1 inch. While a specific configuration of the sprinkler head **2** is shown in FIG. **1**, the present disclosure is broader than this configuration, and it is contemplated that substantially any present or future approved or listed fire sprinkler head can be attached to the flexible tube **1** in place of the sprinkler head **2** shown in FIG. **1**.

(4) When the flexible dry sprinkler is in a sealed state, as shown in FIG. **1**, the flexible dry sprinkler is filled with a fluid that is pressurized to keep the first seal **4** sealed. The fluid is a freeze resistant gas, such as nitrogen, or a liquid, such as a water/glycol mixture or other conventional “antifreeze” liquids.

(5) The connection to the fire sprinkler system utilizes a differential pressure device **16** to ensure the pressure in the flexible tube **1** is greater than the pressure in the fluid supply so as to prevent the introduction of water or air from the fire sprinkler system into the flexible tube **1**. This differential pressure device **16** is configured to maintain a ratio of 3 to 1 or greater between the pressure **P1** in the flexible tube **1** and the fluid supply pressure **P3** in the fluid supply. It is believed that the ratio of 3 to 1 is sufficient to prevent leakage into the flexible tube **1** caused by pressure surges in the fluid supply of the fire sprinkler system. In one embodiment, the differential pressure device **16** is configured as a differential pressure controller in communication with a pressure sensor that monitors the fluid supply pressure **P3** and in communication with a pressure sensor that monitors the pressure **P1**. The differential pressure controller **16** is in communication with a control valve **17** positioned between the flexible tube **1** and a source of pressurized fluid **18** that is maintained at a pressure **P2** that is greater than the fluid supply pressure **P3**. In the event that the pressure ratio drops below 3 to 1, a signal is sent from the differential pressure controller **16** to the control valve **17** to open the control valve **17** to introduce the pressurized fluid from the source of pressurized fluid **18** into the flexible tube **1** until the 3 to 1 ratio is achieved, at which time the control valve **17** is instructed to close. Thus, the differential pressure controller **16** and the control valve **17** operate according to a conventional feedback control arrangement to maintain the desired pressure ratio, e.g., of 3 to 1. It will be appreciated that the differential pressure controller **16** may include a computer constructed to execute a computer readable program stored in a tangible computer-readable medium or in another type of memory, and including instructions for operating the differential pressure controller **16** to maintain the pressure ratio between **P1** and **P3**. While one embodiment of a control arrangement has been described with reference to the preferred embodiment, other control arrangements can be employed to maintain the desired pressure ratio, and are within the scope of this disclosure.

(6) Moreover, the various pressure sensors that monitor the pressures **P1**, **P2**, and **P3** can be constructed to communicate with an alarm system to notify an operator regarding operation of the fire sprinkler system. For example, an alarm may be provided to notify an operator if the pressure **P1** decreases to a certain pressure value, which may alert the operator of the possibility that the sprinkler head **2** may be leaking. Alternatively, notifications can be provided by various methods, including, but not limited to, a telephone message, an e-mail, a visual display, and a facsimile message. Optionally, a visual pressure indicator, such as an analog or digital pressure gauge, located proximate to the flexible dry sprinkler, can be installed for indication that the pressure **P1** of the fluid sealed in the flexible tube **1** has been maintained within tolerances permitted by the design of the flexible dry sprinkler. Such an indicator may simply be a binary status indicator, such as a color indicator, e.g., an indicator that displays green, indicating acceptable operating status, and that displays red, indicating an unacceptable operating status. Of course, other pressure indicators are within the scope of this disclosure.

(7) An optional flexible linkage **15** is shown in FIG. **1** connecting the first seal **4** to the second seal **5**. The flexible linkage **15** is formed of a material that will not corrode in the presence of the fluid contained in the flexible tube **1**. The flexible linkage **15** can be formed as a chain or a cable. In one exemplary embodiment, the flexible linkage **15** is constructed of stainless steel. By virtue of the flexible linkage **15**, when the flexible tube **1** of the flexible dry sprinkler is bent, as shown by the

broken lines, the flexible linkage 15 in the flexible tube 1 will conform to the inner wall of the flexible tube 1 and will not limit the range of motion of the flexible tube 1. Also, by physically coupling the first seal 4 and the second seal 5 together with the flexible linkage 15, the first seal 4 can be pulled out of the flexible tube 1 by virtue of the release and discharge of the second seal 5. It is expected that the flexible linkage 15 will positively ensure that the first seal 4 is indeed removed from the path of flow in the flexible tube 1 without being obstructed by other structures in the flexible tube 1. Also, the flexible linkage 15 allows the first seal 4 to pass out of the flexible tube 1 regardless of any kinks or sharp corners in the inner surface of the flexible tube 1 caused by corrugations in the flexible tube 1 or flexing of the flexible tube 1.

(8) The flexibility in the flexible tube 1 of the flexible dry sprinkler facilitates installation of the sprinkler system because the flexible dry sprinkler can be moved around building obstructions that would ordinarily require additional plumbing work. Moreover, the flexibility of the flexible dry sprinkler eliminates the need for installers of the fluid supply to precisely align the sprinkler drops (i.e., the connections for each flexible dry sprinkler) in the ceiling of a structure because any variance can be adjusted by movement of the flexible tube 1.

(9) While the present invention has been described with respect to what are, at present, considered to be the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. To the contrary, the invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

INDUSTRIAL APPLICABILITY

(10) My invention can be used to provide fire protection, particularly in areas subject to freezing conditions. Thus, the invention is applicable to the fire protection industry.

Claims

1. A dry fire protection sprinkler comprising: a flexible tube having an inlet end, an outlet end, and a valve opening, the flexible tube configured to contain a pressurized fluid supplied from a fluid supply line; an outlet seal assembly having a sealing cap configured to seal an outlet orifice of a sprinkler frame, wherein the flexible tube contains the pressurized fluid between an inlet seal assembly and the sealing cap of the outlet seal assembly; a thermally responsive element configured to fail when ambient temperature reaches a predetermined temperature, and to hold the sealing cap of the outlet seal assembly in an outlet orifice until the thermally responsive element fails; a flexible tube pressure sensor configured to measure a pressure P1 of the pressurized fluid in the flexible tube; a control valve connected to the valve opening of the flexible tube, and configured to open and to close; a pressurized fluid source connected to the control valve and configured to supply the pressurized fluid from the fluid supply line to the flexible tube when the control valve opens, the pressurized fluid in the pressurized fluid source being at a pressure P2; a fluid supply pressure sensor configured to measure a pressure P3 of the pressurized fluid in the fluid supply line, the pressure P2 of the pressurized fluid in the pressurized fluid source being greater than the pressure P3 of the fluid in the supply line; and a differential pressure controller connected to the control valve, to the flexible tube pressure sensor, and to the fluid supply pressure sensor, and, when a ratio of the pressure P1 of the pressurized fluid in the flexible tube to the pressure P3 of the fluid in the fluid supply line is less than a predetermined ratio of at least three to one, the differential pressure controller sends a signal to the control valve to open, in order to allow the pressurized fluid in the pressurized fluid source at the pressure of P2 to enter the flexible tube, and, when the ratio of the pressure P1 of the pressurized fluid in the flexible tube to the pressure P3 of the fluid in the fluid supply line equals the predetermined ratio, the differential pressure controller sends a signal to the control valve to close.

2. The dry fire protection sprinkler according to claim 1, wherein the sprinkler frame has frame arms that form a hub that is spaced from the outlet orifice.

3. The dry fire protection sprinkler according to claim 2, further comprising a deflector connected to the hub of the sprinkler frame.
4. The dry fire protection sprinkler according to claim 1, wherein the outlet end of the flexible tube is threadably connected to the sprinkler frame.
5. The dry fire protection sprinkler according to claim 1, further comprising a pressure indicator connected to the flexible tube, the pressure indicator being configured to indicate the pressure of the pressurized fluid in the flexible tube.
6. The dry fire protection sprinkler according to claim 5, wherein the pressure indicator is at least one of an analog pressure monitor and a digital pressure monitor.
7. The dry sprinkler according to claim 5, wherein the pressure indicator communicates with an alarm system.
8. The dry fire protection sprinkler according to claim 7, wherein the alarm system notifies an operator if the pressure of the pressurized fluid in the flexible tube decreases to a certain pressure value.
9. The dry fire protection sprinkler according to claim 1, further comprising a flexible connector provided in the flexible tube and connected to the sealing cap of the outlet seal assembly.
10. The dry fire protection sprinkler according to claim 9, wherein the flexible connector is one of a chain and a cable.
11. The dry fire protection sprinkler according to claim 1, wherein the flexible tube is a corrugated metal hose.
12. The dry fire protection sprinkler according to claim 1, wherein the flexible tube is a corrugated plastic hose.
13. The dry fire protection sprinkler according to claim 1, wherein, when the thermally responsive element fails, the sealing cap of the outlet seal assembly is released, permitting the pressurized fluid in the flexible tube to flow through the outlet orifice.
14. The dry fire protection sprinkler according to claim 1, wherein the outlet seal assembly includes a spring washer provided in the outlet orifice of the sprinkler frame, and the sealing cap of the outlet seal assembly is an annular disk that sits in the spring washer of the outlet seal assembly.
15. A dry fire protection sprinkler comprising: an inlet seal assembly having an inlet plug; a flexible tube having an inlet end, an outlet end, and a valve opening, the flexible tube having a circular inner cross section and being configured to contain a pressurized fluid supplied from a fluid supply line; an outlet seal assembly having a sealing cap configured to seal an outlet orifice of a sprinkler frame, wherein the flexible tube contains the pressurized fluid between the inlet seal assembly and the sealing cap of the outlet seal assembly; a thermally responsive element configured to fail when ambient temperature reaches a predetermined temperature, and to hold the sealing cap of the outlet seal assembly in the outlet orifice until the thermally responsive element fails; a flexible tube pressure sensor configured to measure a pressure P_1 of the pressurized fluid in the flexible tube; a control valve connected to the valve opening of the flexible tube, and configured to open and to close; a pressurized fluid source connected to the control valve and configured to supply the pressurized fluid from the fluid supply line to the flexible tube when the control valve opens, the pressurized fluid in the pressurized fluid source being at a pressure P_2 ; a fluid supply pressure sensor configured to measure a pressure P_3 of the pressurized fluid in the fluid supply line, the pressure P_2 of the pressurized fluid in the pressurized fluid source being greater than the pressure P_3 of the fluid in the supply line; and a differential pressure controller connected to the control valve, to the flexible tube pressure sensor, and to the fluid supply pressure sensor, and, when a ratio of the pressure P_1 of the pressurized fluid in the flexible tube to the pressure P_3 of the fluid in the fluid supply line is less than a predetermined ratio of at least three to one, the differential pressure controller sends a signal to the control valve to open, in order to allow the pressurized fluid in the pressurized fluid source at the pressure of P_2 to enter the flexible tube, and, when the ratio of the pressure P_1 of the pressurized fluid in the flexible tube to the pressure P_3

of the fluid in the fluid supply line equals the predetermined ratio, the differential pressure controller sends a signal to the control valve to close.

16. The dry fire protection sprinkler according to claim 15, wherein the sprinkler frame has frame arms that form a hub that is spaced from the outlet orifice.

17. The dry fire protection sprinkler according to claim 16, further comprising a deflector connected to the hub of the sprinkler frame.

18. The dry fire protection sprinkler according to claim 15, wherein the outlet end of the flexible tube is threadably connected to the sprinkler frame.

19. The dry fire protection sprinkler according to claim 15, further comprising a pressure indicator connected to the flexible tube, the pressure indicator being configured to indicate the pressure of the pressurized fluid in the flexible tube.

20. The dry fire protection sprinkler according to claim 19, wherein the pressure indicator is at least one of an analog pressure monitor and a digital pressure monitor.

21. The dry sprinkler according to claim 19, wherein the pressure indicator communicates with an alarm system.

22. The dry fire protection sprinkler according to claim 21, wherein the alarm system notifies an operator if the pressure of the pressurized fluid in the flexible tube decreases to a certain pressure value.

23. The dry fire protection sprinkler according to claim 15, further comprising a flexible connector provided in the flexible tube and connected to the inlet plug of the inlet seal assembly and the sealing cap of the outlet seal assembly.

24. The dry fire protection sprinkler according to claim 23, wherein the flexible connector is one of a chain and a cable.

25. The dry fire protection sprinkler according to claim 15, wherein the flexible tube is a corrugated metal hose.

26. The dry fire protection sprinkler according to claim 15, wherein the flexible tube is a corrugated plastic hose.

27. The dry fire protection sprinkler according to claim 15, wherein, when the thermally responsive element fails, the sealing cap of the outlet seal assembly is released, releasing the inlet plug of the inlet seal assembly from the inlet orifice, and permitting the pressurized fluid in the flexible tube to flow through the outlet orifice.

28. The dry fire protection sprinkler according to claim 15, wherein the outlet seal assembly includes a spring washer provided in the outlet orifice of the sprinkler frame, and the sealing cap of the outlet seal assembly is an annular disk that sits in the spring washer of the outlet seal assembly.

29. A dry fire protection sprinkler for use in an area that is exposed to freezing conditions, the dry fire protection sprinkler comprising: a flexible tube having an inlet end, an outlet end, and a valve opening, the flexible tube configured to contain a pressurized fluid supplied from a fluid supply line, the pressurized fluid being a liquid anti-freeze solution that is not susceptible to freezing at the freezing point of water; an outlet seal assembly having a sealing cap configured to seal an outlet orifice of a sprinkler frame, wherein the flexible tube contains the pressurized fluid between an inlet seal assembly and the sealing cap of the outlet seal assembly; a thermally responsive element configured to fail when ambient temperature reaches a predetermined temperature, and to hold the sealing cap of the outlet seal assembly in the outlet orifice until the thermally responsive element fails; a flexible tube pressure sensor configured to measure a pressure P_1 of the pressurized fluid in the flexible tube; a control valve connected to the valve opening of the flexible tube, and configured to open and to close; a pressurized fluid source connected to the control valve and configured to supply the pressurized fluid from the fluid supply line to the flexible tube when the control valve opens, the pressurized fluid in the pressurized fluid source being at a pressure P_2 ; a fluid supply pressure sensor configured to measure a pressure P_3 of the pressurized fluid in the fluid supply line, the pressure P_2 of the pressurized fluid in the pressurized fluid source being

greater than the pressure P3 of the fluid in the supply line; and a differential pressure controller connected to the control valve, to the flexible tube pressure sensor, and to the fluid supply pressure sensor, and, when a ratio of the pressure P1 of the pressurized fluid in the flexible tube to the pressure P3 of the fluid in the fluid supply line is less than a predetermined ratio of at least three to one, the differential pressure controller sends a signal to the control valve to open, in order to allow the pressurized fluid in the pressurized fluid source at the pressure of P2 to enter the flexible tube, and, when the ratio of the pressure P1 of the pressurized fluid in the flexible tube to the pressure P3 of the fluid in the fluid supply line equals the predetermined ratio, the differential pressure controller sends a signal to the control valve to close.

30. The dry fire protection sprinkler according to claim 29, wherein the sprinkler frame has frame arms that form a hub that is spaced from the outlet orifice.

31. The dry fire protection sprinkler according to claim 30, further comprising a deflector connected to the hub of the sprinkler frame.

32. The dry fire protection sprinkler according to claim 29, wherein the outlet end of the flexible tube is threadably connected to the sprinkler frame.

33. The dry fire protection sprinkler according to claim 29, further comprising a pressure indicator connected to the flexible tube, the pressure indicator being configured to indicate the pressure of the pressurized fluid in the flexible tube.

34. The dry fire protection sprinkler according to claim 33, wherein the pressure indicator is at least one of an analog pressure monitor and a digital pressure monitor.

35. The dry sprinkler according to claim 33, wherein the pressure indicator communicates with an alarm system.

36. The dry fire protection sprinkler according to claim 35, wherein the alarm system notifies an operator if the pressure of the pressurized fluid in the flexible tube decreases to a certain pressure value.

37. The dry fire protection sprinkler according to claim 29, further comprising a flexible connector provided in the flexible tube and connected to the sealing cap of the outlet seal assembly.

38. The dry fire protection sprinkler according to claim 37, wherein the flexible connector is one of a chain and a cable.

39. The dry fire protection sprinkler according to claim 29, wherein the flexible tube is a corrugated metal hose.

40. The dry fire protection sprinkler according to claim 29, wherein the flexible tube is a corrugated plastic hose.

41. The dry fire protection sprinkler according to claim 29, wherein, when the thermally responsive element fails, the sealing cap of the outlet seal assembly is released, permitting the pressurized fluid in the flexible tube to flow through the outlet orifice.

42. The dry fire protection sprinkler according to claim 29, wherein the spring washer of the outlet seal assembly is provided in the outlet orifice of the sprinkler frame, and the sealing cap of the outlet seal assembly is an annular disk that sits in the spring washer of the outlet seal assembly.

43. The dry fire protection sprinkler according to claim 1, wherein the sprinkler is for use in an area that is exposed to freezing conditions.

44. The dry fire protection sprinkler according to claim 43, wherein the pressurized fluid is a liquid anti-freeze solution that is not susceptible to freezing at the freezing point of water.

45. The dry fire protection sprinkler according to claim 15, wherein the sprinkler is for use in an area that is exposed to freezing conditions.

46. The dry fire protection sprinkler according to claim 45, wherein the pressurized fluid is a liquid anti-freeze solution that is not susceptible to freezing at the freezing point of water.
