

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400891
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Antoniolli; Francesca et al.

Deposition apparatus, method of deposition on a substrate, substrate structure and substrate support

Abstract

A deposition apparatus includes a first substrate support for supporting a substrate in a substantially vertical orientation. The substrate has a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface. The deposition apparatus includes a first deposition device for depositing a first conductive pattern or a first resist mask on the side surface of the substrate while the substrate is supported in the substantially vertical orientation by the first substrate support.

Inventors:	Antoniolli; Francesca (Oderzo, IT), D'Acunzo; Marco (Quinto Di Treviso, IT), Galiazzo; Marco (Quinto Di Treviso, IT), Hada; Daniel (Cupertino, CA)
Applicant:	APPLIED MATERIALS ITALIA S.R.L. (San Biagio di Callalta, IT)
Family ID:	1000008781026
Assignee:	APPLIED MATERIALS ITALIA S.R.L. (San Biagio di Callalta, IT)
Appl. No.:	17/440149
Filed (or PCT Filed):	March 19, 2019
PCT No.:	PCT/EP2019/056836
PCT Pub. No.:	WO2020/187399
PCT Pub. Date:	September 24, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220157629 A1	May. 19, 2022

Publication Classification

Int. Cl.: **H01L21/677** (20060101); **C23C14/04** (20060101); **C23C14/50** (20060101);
H01L21/027 (20060101); **H01L21/768** (20060101); **H05K3/12** (20060101); **H05K3/18**
(20060101)

U.S. Cl.:

CPC **H01L21/67712** (20130101); **C23C14/042** (20130101); **C23C14/50** (20130101);
H01L21/027 (20130101); **H01L21/768** (20130101); **H05K3/1216** (20130101);
H05K3/184 (20130101); H05K2203/1518 (20130101)

Field of Classification Search

CPC: C23C (14/042); C23C (14/50); H01L (21/027); H05K (3/1216); H05K (3/184); H05K
(2203/1518)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6156967	12/1999	Ralph et al.	N/A	N/A
6232655	12/2000	Sugimura	257/E23.012	H01L 23/482
2005/0168960	12/2004	Asahi et al.	N/A	N/A
2010/0182375	12/2009	Ciampini et al.	N/A	N/A
2012/0064728	12/2011	Yi	438/758	C23C 14/50
2017/0244070	12/2016	Bangert et al.	N/A	N/A
2017/0347461	12/2016	Zwiers et al.	N/A	N/A
2018/0166324	12/2017	Schaeffer	N/A	H01L 29/0804
2019/0078211	12/2018	Kuenle	N/A	C23C 16/4584

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106435477	12/2016	CN	N/A
109055898	12/2017	CN	N/A
2104147	12/2008	EP	N/A
S55117185	12/1979	JP	N/A
S58058796	12/1982	JP	N/A
S58219751	12/1982	JP	N/A
S59149086	12/1983	JP	N/A
H0521302	12/1992	JP	N/A
H05301334	12/1992	JP	N/A
H07134559	12/1994	JP	N/A
H09115958	12/1996	JP	N/A
H10199887	12/1997	JP	N/A
20130045200	12/2012	KR	N/A

201827641	12/2017	TW	N/A
2010044257	12/2009	WO	N/A
2018197007	12/2017	WO	N/A

OTHER PUBLICATIONS

Japanese Office Action dated Oct. 25, 2022 for Application No. 2021-555611. cited by applicant
Taiwan Office Action issued to Application No. 109107897 on Nov. 18, 2021. cited by applicant
International Search Report, PCT/EP2019/056836, Nov. 14, 2019. cited by applicant
Taiwan Office Action dated Dec. 2, 2022 for Application No. 109107897. cited by applicant
Chinese Office Action dated Nov. 24, 2023 for Application No. 201980094304.X. cited by applicant
Korean Office Action dated Dec. 28, 2023 for Application No. 10-2021-7033603. cited by applicant

Primary Examiner: Miller; Michael G

Attorney, Agent or Firm: Patterson + Sheridan, LLP

Background/Summary

FIELD

(1) Embodiments of the present disclosure relate to a deposition apparatus and a method for depositing a material on a substrate, more specifically for depositing a conductive pattern or a mask on a substrate. More specifically, embodiments of the present disclosure relate to a printing apparatus, such as a screen printing apparatus, for printing a material on a substrate.

BACKGROUND

(2) Many technological applications involve the deposition of a material on various kinds of substrates. For example, a substrate may be a substrate used in display technology, a semiconductor substrate, or a printed circuit board substrate. A substrate may be an inflexible substrate such as glass substrate, or a flexible substrate. A substrate may have a variety of possible dimensions, ranging from smartwatch dimension to large area substrates for display manufacturing.

(3) A layer of material can be deposited on a substrate, wherein the deposited layer forms a pattern of deposited material. Several deposition techniques can be used to deposit a pattern on a substrate, such as screen printing, physical vapor deposition or chemical vapor deposition. In some implementations, a patterned layer is formed by using a mask covering a portion of the substrate.

(4) Several applications involve substrates on which conductive patterns are deposited. Such conductive patterns may include conductive materials deposited on different regions of the substrate. Conductive patterns may include a plurality of conductive portions having different shapes and sizes. Some conductive portions of a pattern may be connected to other conductive portions of the pattern by yet further conductive portions, which can result in conductive patterns having a complex structure.

(5) In light of the above, there is a need for improving the deposition of patterned structures on substrates.

SUMMARY

(6) According to an embodiment, a deposition apparatus is provided. The deposition apparatus includes a first substrate support for supporting a substrate in a substantially vertical orientation. The substrate has a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface. The deposition apparatus

includes a first deposition device for depositing a first conductive pattern or a first resist mask on the side surface of the substrate while the substrate is supported in the substantially vertical orientation by the first substrate support.

(7) According to a further embodiment, a deposition apparatus is provided. The deposition apparatus includes a first printing device. The deposition apparatus includes a first orientation-changing device downstream of the first printing device. The deposition apparatus includes a second printing device downstream of the first orientation-changing device. The deposition apparatus includes a second orientation-changing device downstream of the second printing device. The deposition apparatus includes a third printing device downstream of the second orientation-changing device.

(8) According to a further embodiment, a method of deposition on a substrate is provided. The method includes providing a substrate in a substantially vertical orientation. The substrate has a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface. The method includes depositing a first conductive pattern or a first resist mask on the side surface of the substrate while the substrate is in the substantially vertical orientation.

(9) According to a further embodiment, a substrate structure is provided. The substrate structure includes a substrate having a first surface, a second surface opposite the first surface and a side surface between the first surface and the second surface. The substrate structure includes a plurality of electrical connections connecting the first surface with the second surface. Each electrical connection includes a conductive line on the first surface, a conductive line on the side surface, and a conductive line on the second surface. The conductive line on the side surface contacts the conductive line on the first surface and the conductive line on the second surface.

(10) According to a further embodiment, a substrate structure is provided. The substrate structure includes a substrate having a first surface, a second surface opposite the first surface and a side surface between the first surface and the second surface. The substrate surface includes a resist mask. The resist mask includes a first resist mask portion covering a portion of the side surface, the first resist mask portion having a first plurality of line-like openings. The resist mask includes a second resist mask portion covering a portion of the first surface, the second resist mask portion having a second plurality of line-like openings. The resist mask includes a third resist mask portion covering a portion of the second surface, the third resist mask portion having a third plurality of line-like openings. Each line-like opening of the first plurality of line-like openings is adjacent to a line-like opening of the second plurality of line-like openings and to a line-like opening of the third plurality of line-like openings.

(11) According to a further embodiment, a substrate support for supporting a substrate in a substantially vertical orientation is provided. The substrate support includes a first surface, the first surface being a stationary surface which is substantially vertical or a movable surface which is movable between a first position and a second position, wherein in the second position the first surface is substantially vertical. The substrate support includes a substrate attraction device adjacent to the first surface.

(12) According to a further embodiment, a substrate support for a deposition apparatus is provided. The substrate support includes a housing comprising a slit to receive a substrate in a substantially vertical orientation.

(13) According to a further embodiment, a substrate support is provided. The substrate support includes a first surface, the first surface being a stationary surface which is substantially vertical or a movable surface which is movable between a first position and a second position, wherein in the second position the first surface is substantially vertical. The substrate support includes a biasing device for biasing a substrate against the first surface, the substrate having a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface. The substrate support is configured for holding the substrate

in a substantially vertical orientation in a manner such that the side surface of the substrate is exposed for deposition of a material on the side surface.

(14) Embodiments are also directed at apparatuses for carrying out the disclosed methods and include apparatus parts for performing each described method aspect. These method aspects may be performed by way of hardware components, a computer programmed by appropriate software, by any combination of the two or in any other manner. Furthermore, embodiments according to the disclosure are also directed at methods for operating the described apparatus. The methods for operating the described apparatus include method aspects for carrying out every function of the apparatus.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) So that the manner in which the above recited features of the present disclosure can be understood in detail, a more particular description of the disclosure, briefly summarized above, may be had by reference to embodiments. The accompanying drawings relate to embodiments of the disclosure and are described in the following:
- (2) FIG. 1 shows a side view of a deposition apparatus according to embodiments described herein;
- (3) FIG. 2a shows an example of a substrate having a first conductive pattern on the side surface of the substrate;
- (4) FIG. 2b shows an example of a substrate having a first resist mask on the side surface of the substrate;
- (5) FIGS. 3a-c show a deposition apparatus according to embodiments described herein, the deposition apparatus including a first deposition device, a second deposition device and a third deposition device;
- (6) FIG. 4a shows an example of a substrate having a second conductive pattern on the first main surface of the substrate;
- (7) FIG. 4b shows an example of a substrate having a second resist mask on the first main surface of the substrate;
- (8) FIG. 5a shows an example of a substrate having a third conductive pattern on the second main surface of the substrate;
- (9) FIG. 5b shows an example of a substrate having a third resist mask on the second main surface of the substrate;
- (10) FIGS. 6-7 show examples of a substrate having a first, second and third conductive pattern;
- (11) FIG. 8 shows a substrate structure according to embodiments described herein;
- (12) FIG. 9 shows a deposition apparatus according to embodiments described herein;
- (13) FIG. 10 shows a deposition apparatus according to embodiments described herein;
- (14) FIGS. 11a-b show a top view of a stack of substrates;
- (15) FIG. 12 shows a deposition apparatus according to embodiments described herein;
- (16) FIG. 13 shows a substrate support according to embodiments described herein;
- (17) FIGS. 14a-c show a substrate support according to embodiments described herein;
- (18) FIGS. 15a-b show a substrate support according to embodiments described herein;
- (19) FIGS. 16a-b show a substrate support according to embodiments described herein;
- (20) FIG. 17 shows a deposition apparatus according to embodiments described herein;
- (21) FIG. 18 shows a substrate including alignment marks;
- (22) FIG. 19 shows a deposition apparatus according to embodiments described herein; and
- (23) FIGS. 20a-b shows a deposition apparatus according to embodiments described herein.

DETAILED DESCRIPTION

- (24) Reference will now be made in detail to the various embodiments of the disclosure, one or

more examples of which are illustrated in the figures. Within the following description of the drawings, the same reference numbers refer to same components. Generally, only the differences with respect to individual embodiments are described. Each example is provided by way of explanation of the disclosure and is not meant as a limitation of the disclosure. Further, features illustrated or described as part of one embodiment can be used on or in conjunction with other embodiments to yield yet a further embodiment. It is intended that the description includes such modifications and variations.

(25) FIG. 1 shows a side view of a deposition apparatus **10** according to embodiments described herein.

(26) According to an embodiment, a deposition apparatus **10** is provided. The deposition apparatus **10** includes a first substrate support **180**. The first substrate support **180** may be for supporting a substrate **100** in a substantially vertical orientation. The vertical direction is indicated in FIG. 1 by the arrow **1**. The substrate **100** has a first main surface **120**, a second main surface **130** opposite the first main surface **120** and a side surface **110** between the first main surface **120** and the second main surface **130**. The deposition apparatus **10** includes a first deposition device **190**. The first deposition device **190** may be for depositing a first conductive pattern **250** or a first resist mask **260** on the side surface **110** of the substrate **100** while the substrate **100** is supported in the substantially vertical orientation by the first substrate support **180**.

(27) FIGS. 2a-b show a top view of the side surface **110** of an exemplary substrate **100** as described herein. A first conductive pattern **250** is deposited on the side surface **110** of the substrate **100** shown in FIG. 2a. As shown, the first conductive pattern **250**, indicated by the hashed portions in FIG. 2a, can include a plurality of conductive lines **252**. A first resist mask **260** as described herein is deposited on the side surface **110** of the substrate **100** shown in FIG. 2b. As shown, the first resist mask **260**, indicated by the hashed portions in FIG. 2b, can include a plurality of line-like openings **262**. If the side surface **110** including the first resist mask **260** is coated with a conductive material, e.g. by sputtering or plating, conductive lines similar to the conductive lines **252** are formed in the line-like openings **262** of the first resist mask **260**.

(28) A substrate as described herein, such as e.g. the substrate **100**, may be provided in a substantially vertical orientation. A substantially vertical orientation of the substrate includes small deviations from an exact vertical orientation, e.g. deviations of 5% or less or 10% or less, possibly even up to 15%.

(29) A substrate as described herein may be a substantially planar or sheet-like substrate. For example, a substrate may be a substrate used in display technology, a semiconductor substrate, a printed circuit board substrate, or any kind of circuit for which it is beneficial to provide an electrical connection between two surfaces of the substrate.

(30) The substrate may, e.g., be an inflexible substrate such as a glass substrate, or a flexible substrate. The substrate may have a variety of possible dimensions, ranging from smartwatch dimension to large area substrates for display manufacturing.

(31) A substrate as described herein may have a first main surface. The substrate may have a second main surface opposite the first main surface. The terms “first main surface” and the “second main surface” can be understood in a manner such that a total area of the substrate is substantially the same as the area of at least one of the first main surface and the second surface.

(32) The substrate may have a side surface between the first main surface and the second main surface. The side surface may connect the first main surface with the second main surface. The area of the side surface is much smaller than the area of the first main surface and the area of the second main surface. The side surface may be a thin strip-like surface between the first major surface and the second major surface.

(33) The substrate may have a thickness, e.g. a thickness of 20 mm or less, particularly 5 mm or less, more particularly 1 mm or less, such as e.g. about 0.5 mm. The thickness may be as small as e.g. 0.1 mm. The distance between the first main surface and the second main surface may

correspond to the thickness of the substrate. The side surface may have a length and a width. The length is larger than the width. The width of the side surface may correspond to the thickness of the substrate. For example, the width of the side surface may be 5 mm or less, more particularly 1 mm or less, such as e.g. about 0.5 mm.

(34) The first deposition device **190**, or at least a portion thereof, may be arranged above the first substrate support **180**. While the substrate **100** is supported by the first substrate support **180**, the side surface **110** may be located at a top portion of the substrate **100**. The first deposition device **190** may be arranged to deposit the first conductive pattern **250** onto the side surface **110** from above.

(35) A conductive pattern as described herein, such as e.g. the first conductive pattern **250**, the second conductive line pattern **450** or the third conductive line pattern **550**, may include a plurality of conductive lines. The plurality of conductive lines may include, e.g., 10 or more lines per mm. The plurality of conductive lines may include a first conductive line. The plurality of conductive lines may include a second conductive line.

(36) The first conductive line may be substantially parallel to the second conductive line. The term “substantially parallel” includes conductive lines having an angle from 0 degrees to 15 degrees with respect to each other. The plurality of conductive lines may be a plurality of substantially parallel lines. In other implementations, the conductive lines may not be substantially parallel. A conductive pattern can include conductive lines having an angle relative to each other, e.g., an angle of 20 degrees or more.

(37) According to embodiments described herein, a conductive pattern may be printed on the substrate. Printing results in thicker conductive patterns as compared to other deposition techniques such as e.g. sputtering. Thicker conductive patterns provide the advantage that a more reliable, i.e. electrically and mechanically more stable electrical connection can be formed. In order to further increase thickness, multiple passes can be applied. A conductive pattern as described herein may have a thickness of 20 μm or less and/or 0.5 μm or more. For example, the thickness can be 3 μm or more.

(38) Further, printing provides the advantage that the printed patterns have a good adhesion to the substrate.

(39) The first conductive pattern **250** as described herein may include a conductive line **252**. The conductive line **252** may extend from a first edge region of the side surface **110** to a second edge region of the side surface **110**. The first edge region may be adjacent to the first main surface **120**. The first edge region may be a region where the side surface **110** meets the first main surface **120**. The second edge region may be opposite the first edge region. The second edge region may be adjacent to the second main surface **130**. The second edge region may be a region where the side surface **110** meets the second main surface **130**.

(40) In some implementations, the conductive line **252** may be substantially perpendicular to at least one of the first main surface **120** and the second main surface **130**. The term “substantially perpendicular” includes an angle of 90 degrees and small deviations therefrom, e.g. angles from 75 degrees to 105 degrees. In other implementations, the conductive line **252** may be at an angle with respect to at least one of the first main surface and the second main surface, e.g. an angle of 70 degrees or less. The first conductive pattern **250** as described herein may include a plurality of conductive lines. Each conductive line **252** of the plurality of conductive lines may extend from the first edge region of the side surface **110** to the second edge region of the side surface **110**. Each conductive line **252** may, for example, be substantially perpendicular to at least one of the first main surface **120** and the second main surface **130**.

(41) A conductive line as described herein, e.g. a conductive line of the first conductive pattern **250**, the second conductive pattern **450** or the third conductive pattern **550**, may have a line width of 200 μm or less and/or 5 μm or more. For example, the line width may be from 20 to 80 μm . A conductive line may have a line length of 500 μm or less and/or 50 μm or more, such as e.g. a line

length of about 100 μm .

(42) A resist mask, such as the first resist mask **260**, the second resist mask **460** or the third resist mask **560** as described herein, may cover one or more portion(s) of the substrate. One or more other portions of the substrate may not be covered by the resist mask. The resist mask may be shaped in the form of a pattern. The pattern may be a “negative image” of a target pattern of conductive material that is to be deposited on the substrate. For example, the resist mask may have a plurality of openings shaped in the form of a plurality of lines. The plurality of lines may correspond to a target pattern that is to be deposited on the substrate. After the resist mask is deposited on the substrate, the substrate including the resist mask may be coated, e.g. in a sputtering or plating process, to deposit a conductive material on the substrate. The conductive material is deposited on the resist mask and on the portion(s) of the substrate not covered by the resist mask. No conductive material is deposited on the portion(s) of the substrate covered by the resist mask. In light thereof, the conductive material may be deposited on the substrate in the form of a target pattern determined by the shape of the resist mask. After the deposition process, the resist mask may be removed from the substrate, e.g. in a chemical removal process. A substrate having a target pattern of conductive material formed thereon is provided.

(43) A resist mask as described herein may include a plurality of line-like openings, e.g. openings having the shape of a thin strip or slits, in the resist mask. The plurality of line-like openings of the resist mask may correspond to a plurality of lines of a conductive pattern to be deposited on the substrate using the resist mask. The plurality of line-like openings may include, e.g. 10 or more line-like openings per mm. The plurality of line-like openings may include a first line-like opening or slit. The plurality of line-like openings may include a second line-like opening or slit. The first line-like opening may be substantially parallel to the second line-like opening. The plurality of line-like openings may be a plurality of substantially parallel line-like openings. Alternatively, the line-like openings may be at an angle relative to each other, e.g. an angle of 20 degrees or more.

(44) The first resist mask **260** as described herein may include a line-like opening **262** or slit. The line-like opening **262** may extend from a first edge region, as described herein, of the side surface **110** to a second edge region, as described herein, of the side surface **110**. The line-like opening **262** may be substantially perpendicular to at least one of the first main surface **120** and the second main surface **130**. Alternatively, the line-like opening **262** may be at an angle with respect to at least one of the first main surface **120** and the second main surface **130**, e.g. an angle of 70 degrees or less.

(45) The first resist mask **260** as described herein may include a plurality of line-like openings. Each line-like opening **262** of the plurality of line-like openings may extend from the first edge region of the side surface **110** to the second edge region of the side surface **110**. Each line-like opening **262** may be substantially perpendicular to at least one of the first main surface and the second main surface.

(46) The first deposition device **190** may include or be a printing device. The first deposition device **190** may be configured to print the first conductive pattern **250** and/or the first resist mask **260** on the side surface **110** of the substrate. The first deposition device may be a screen printing device. The first deposition device may include a screen for screen printing. The screen may be arranged above the first substrate support **180**. The first deposition device **190** may be configured to print the first conductive pattern **250** and/or the first resist mask **260** on the side surface **110** of the substrate **100** by urging a printing material through the screen. For printing the first conductive pattern **250** (or the second conductive pattern **450** or the third conductive pattern **550**, or any other conductive pattern described herein), the printing material urged through the screen may be a conductive material, e.g. a conductive ink or paste, such as a silver or copper ink, or any other kind of conductive screen printing material. For printing the first resist mask **260** (or the second resist mask **460** or the third resist mask **560** as described herein), the printing material urged through the screen may be an insulating material, e.g. a polymer.

(47) A deposition apparatus **10** according to embodiments described herein may include a layer

deposition device for depositing a conductive material on the substrate. The layer deposition device may be configured to deposit the conductive material on at least the side surface **110** of the substrate **100** including the first resist mask **260**. The layer deposition device may be, e.g., a sputtering device or a plating device.

(48) FIGS. **3a-c** show a deposition apparatus **10** according to embodiments described herein. The deposition apparatus **10** includes a first deposition device **190**, a second deposition device **330** and a third deposition device **370**. The deposition apparatus **10** includes a first substrate support **180**, a second substrate support **320** and a third substrate support **360**. As shown in FIG. **3a**, the substrate **100** can be supported by the second substrate support **320** in a substantially horizontal orientation. The first main surface **120** of the substrate **100** can face upward. The second deposition device **330** can deposit a second conductive pattern or a second resist mask on the first main surface **120** of the substrate **100**. The substrate **100** can be moved from the second substrate support **320** to the third substrate support **360**. As shown in FIG. **3b**, the substrate **100** can be supported by the third substrate support **360** in a substantially horizontal orientation. The second main surface **130** of the substrate **100** can face upward. The third deposition device **370** can deposit a third conductive pattern or a third resist mask on the second main surface **130** of the substrate **100**. The substrate **100** can be moved from the third substrate support **360** to the first substrate support **180**. The first deposition device **190** can deposit the first conductive pattern **250** on the side surface **110** of the substrate **100**.

(49) FIGS. **4a-b** show a top view of the first main surface **120** of an exemplary substrate **100**. A second conductive pattern **450** as described herein is deposited on the first main surface **120** shown in FIG. **4a**. As shown, the second conductive pattern **450**, indicated by the hashed portions in FIG. **4a**, can include a plurality of conductive lines **452**. A second resist mask **460** as described herein is deposited on the first main surface **120** shown in FIG. **4b**. As shown, the second resist mask **460**, indicated by the hashed portions in FIG. **4b**, can include a plurality of line-like openings **462**.

(50) FIGS. **5a-b** show a top view of the second main surface **130** of an exemplary substrate **100**. A third conductive pattern **550** including a plurality of conductive lines **552** is deposited on the second main surface **130** shown in FIG. **5a**. A third resist mask **560** including a plurality of line-like openings **562** is deposited on the second main surface **130** shown in FIG. **5b**.

(51) A deposition apparatus **10** according to embodiments described herein may include a second deposition device **330** for depositing a second conductive pattern **450** or a second resist mask **460** on the first main surface **120** of the substrate **100**. A portion of the second conductive pattern **450** may contact a portion of the first conductive pattern **250**. A portion of the second resist mask **460** may contact a portion of the first resist mask **260**.

(52) The second deposition device **330** may include or be a printing device, particularly a screen printing device. The second deposition device **330** may be configured to print the second conductive pattern **450** and/or the second resist mask **460** on the first main surface **120** of the substrate **100**.

(53) A deposition apparatus **10** according to embodiments described herein may include a second substrate support **320**. The second substrate support **320** may be configured for supporting the substrate **100** in a substantially horizontal orientation. The second deposition device **330** may be arranged for depositing the second conductive pattern **450** or the second resist mask **460** on the first main surface **120** of the substrate **100** while the substrate **100** is supported by the second substrate support **320**.

(54) The second conductive pattern **450** as described herein may include a conductive line **452**. The conductive line **452** may extend from a first end of the conductive line **452** to a second end of the conductive line **452**. The first end of the conductive line **452** may be located at, or adjacent to, a region where the first main surface **120** meets the side surface **110**. The conductive line **452** of the second conductive pattern **450** may contact a conductive line **252** of the first conductive pattern **250**. An electric current can flow from the conductive line **452** to the conductive line **252** or vice

versa. The conductive line **452** together with the conductive line **252** may form an electrical connection from the first main surface **120** to the side surface **110**. The second conductive pattern **450** may include a plurality of conductive lines. The plurality of conductive lines may be substantially parallel conductive lines or conductive lines at an angle relative to each other. Each conductive line **452** of the plurality of conductive lines may extend from a first end of the conductive line **452** to a second end of the conductive line **452**. The first end of each conductive line **452** may be located at, or adjacent to, a region where the first main surface **120** meets the side surface **110**. Each conductive line **452** of the plurality of conductive lines may contact a corresponding conductive line **252** of the first conductive pattern **250**. A plurality of electrical connections between the side surface **110** and the first main surface **120** may be formed.

(55) The second resist mask **460** as described herein may include a line-like opening **462** or slit. The line-like opening **462** may extend from a first end of the line-like opening **462** to a second end of the line-like opening **462**. The first end of the line-like opening **462** may be located at, or adjacent to, a region where the first main surface **120** meets the side surface **110**. The first end of the line-like opening **462** of the second resist mask **460** may be adjacent to an end of a line-like opening **262** of the first resist mask **260**. After the side surface **110** including the first resist mask **260** and the first main surface **120** including the second resist mask **460** are coated with a conductive material, a conductive line is formed in the line-like opening **262** of the first resist mask **260** and a conductive line is formed in the line-like opening **462** of the second resist mask **460**, wherein the two conductive lines contact each other so that a current can flow between the two conductive lines. The second resist mask **460** may include a plurality of line-like openings. The plurality of line-like openings may be substantially parallel to each other or may be at an angle relative to each other. Each line-like opening **462** of the plurality of line-like openings may extend from a first end of the line-like opening **462** to a second end of the line-like opening **462**. The first end of each line-like opening **462** may be located at, or adjacent to, a region where the first main surface **120** meets the side surface **110**. The first end of each line-like opening **462** of the second resist mask **460** may be adjacent to, or in communication with, an end of a corresponding line-like opening **262** of the first resist mask **260**.

(56) A deposition apparatus **10** according to embodiments described herein may include a third deposition device **370** for depositing a third conductive pattern **550** or a third resist mask **560** on the second main surface **130** of the substrate **100**. A portion of the third conductive pattern **550** may contact a portion of the first conductive pattern **250**. A portion of the third resist mask **560** may contact a portion of the first resist mask **260**.

(57) The third deposition device **370** may include or be a printing device, particularly a screen printing device. The third deposition device **370** may be configured to print the third conductive pattern **550** and/or the third resist mask **560** on the second main surface **130** of the substrate **100**.

(58) A deposition apparatus **10** according to embodiments described herein may include a third substrate support **360**. The third substrate support **360** may be configured for supporting the substrate **100** in a substantially horizontal orientation. The third deposition device **370** may be arranged for depositing the third conductive pattern **550** or the third resist mask **560** on the second main surface **130** of the substrate **100** while the substrate **100** is supported by the third substrate support **360**.

(59) The third conductive pattern **550** as described herein may include a conductive line **552**. The conductive line **552** may extend from a first end of the conductive line **552** to a second end of the conductive line **552**. The first end of the conductive line **552** may be located at, or adjacent to, a region where the second main surface **130** meets the side surface **110**.

(60) The conductive line **552** of the third conductive pattern **550** may contact a conductive line **252** of the first conductive pattern **250**. The conductive line **252** of the first conductive pattern **250** may contact a conductive line **452** of the second conductive pattern **450**, as described herein. The conductive line **452** together with the conductive line **252** and the conductive line **552** may form an

electrical connection from the first main surface **120** to the second main surface **130** via the side surface **110**. In light thereof, embodiments described herein provide the advantage that an electrical connection can be formed between the first main surface **120** and the second main surface **130** without the need for a through-hole or via in the substrate **100** to establish the electrical connection.

(61) The first conductive pattern **250** as described herein may include a first plurality of conductive lines. The second conductive pattern **450** may include a second plurality of conductive lines. The third conductive pattern **550** may include a third plurality of conductive lines. Each conductive line **252** of the first plurality of conductive lines may contact a conductive line **452** of the second plurality of conductive lines and a conductive line **552** of the third plurality of conductive lines to form an electrical connection from the first main surface **120** to the second main surface **130**. In light thereof, embodiments described herein provide the advantage that a plurality of electrical connections can be formed between the first main surface **120** and the second main surface **130** without the need for through-holes or via in the substrate **100** to establish the electrical connections.

(62) The third resist mask **560** as described herein may include a line-like opening **562** or slit. The line-like opening **562** may extend from a first end of the line-like opening **562** to a second end of the line-like opening **562**. The first end of the line-like opening **562** may be located at, or adjacent to, a region where the second main surface **130** meets the side surface **110**. The first end of the line-like opening **562** of the third resist mask **560** may be adjacent to an end of a line-like opening **262** of the first resist mask **260**. The line-like opening **262** of the first resist mask **260** may be adjacent to a line-like opening **462** of the second resist mask **460**, as described herein. After the side surface **110** including the first resist mask **260**, the first main surface **120** including the second resist mask **460** and the second main surface **130** including the third resist mask **560** are coated with a conductive material, a conductive line is formed in the line-like opening **262** of the first resist mask **260**, a conductive line is formed in the line-like opening **462** of the second resist mask **460** and a conductive line is formed in the line-like opening **562** of the third resist mask **560**. The three conductive lines form an electrical connection from the first main surface **120** to the second main surface **130** via the side surface **110**.

(63) The first resist mask **260** as described herein may include a first plurality of line-like openings. The second resist mask **460** may include a second plurality of line-like openings. The third resist mask **560** may include a third plurality of line-like openings. Each line-like opening **262** of the first plurality of line-like openings may be adjacent to, or in communication with, a line-like opening **462** of the second plurality of line-like openings and a line-like opening **562** of the third plurality of line-like openings. When a conductive material is deposited in the line-like opening **262** and in the adjacent line-like openings **462** and **562**, an electrical connection from the first main surface **120** to the second main surface **130** via the side surface **110** is formed. In light thereof, by coating the side surface **110** including the first resist mask **260**, the first main surface **120** including the second resist mask **460** and the second main surface **130** including the third resist mask **560** with a conductive material, a plurality of electrical connections from the first main surface **120** to the second main surface **130** are formed.

(64) FIGS. **6-7** show a substrate structure **600** according to embodiments described herein. FIG. **6** shows an example of a substrate structure **600** resulting from depositing the first conductive pattern **250** on the side surface **110** after depositing the second conductive pattern **450** on the first main surface **120** and the third conductive pattern **550** on the second main surface **130**. FIG. **7** shows an example of a substrate structure **600** resulting from depositing the first conductive pattern **250** before depositing the second conductive pattern **450** and the third conductive pattern **550**. As shown in FIGS. **6-7**, a conductive line **252** of the first conductive pattern **250** is deposited on the side surface **110**. A conductive line **452** of the second conductive pattern **450** is deposited on the first main surface **120**. A conductive line **552** of the third conductive pattern **550** is deposited on the second main surface **130**. The conductive line **252** contacts the conductive line **452** and the conductive line **552**. The conductive line **252** together with the conductive line **452** and the

conductive line **552** provide an electrical connection from the first main surface **120** to the second main surface **130** via the side surface **110**. In light thereof, embodiments described herein provide the advantage that an electrical connection from the first main surface **120** to the second main surface **130** can be provided while avoiding the formation of a through-hole through the substrate **100**.

(65) FIG. **8** shows a substrate structure **600** according to embodiments described herein. The substrate structure **600** includes a plurality of electrical connections between the first main surface **120** and the second main surface **130**. Each electrical connection includes a conductive line **452** on the first main surface **120**, a conductive line **252** on the side surface **110**, and a conductive line **552** on the second main surface **130**. The conductive line **252** on the side surface **110** contacts the conductive line **452** on the first main surface **120** and the conductive line **552** on the second main surface **130**.

(66) FIG. **9** shows a deposition apparatus **10** according to embodiments described herein. In FIG. **9**, substrates are processed from left to right. The deposition apparatus **10** includes a storing unit **910**, e.g. a cassette, for storing a plurality of substrates. The deposition apparatus **10** includes the second deposition device **330** as described herein, e.g. for depositing the second conductive pattern **450** or the second resist mask **460** on the first main surface **120** of the substrate **100**. The deposition apparatus **10** includes an inspection device **912**, e.g. an optical inspection device, for inspecting the second conductive pattern **450** or the second resist mask **460**. The deposition apparatus **10** includes a drying device **914** for drying the second conductive pattern **450** or the second resist mask **460**. The deposition apparatus **10** includes an orientation-changing device **916**, e.g. for flipping the substrate **100** by about 180 degrees from a first horizontal orientation to a second horizontal orientation.

(67) The deposition apparatus **10** shown in FIG. **9** includes the third deposition device **370** as described herein, e.g. for depositing the third conductive pattern **550** or the third resist mask **560** on the second main surface **130** of the substrate **100**. The deposition apparatus **10** includes an inspection device **922**, e.g. an optical inspection device, for inspecting the third conductive pattern **550** or the third resist mask **560**. The deposition apparatus **10** includes a drying device **924** for drying the third conductive pattern **550** or the third resist mask **560**. The deposition apparatus **10** includes an orientation-changing device **926**, e.g. for flipping the substrate **100** by about 90 degrees from a horizontal orientation to a vertical orientation.

(68) The deposition apparatus **10** shown in FIG. **9** includes the first deposition device **190** as described herein, e.g. for depositing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100**. The deposition apparatus **10** includes an inspection device **932**, e.g. an optical inspection device, for inspecting the first conductive pattern **250** or the first resist mask **260**. The deposition apparatus **10** includes a drying device **934** for drying the first conductive pattern **250** or the first resist mask **260**.

(69) The deposition apparatus **10** shown in FIG. **9** is an exemplary embodiment shown for the purpose of illustration. Several of the components shown in FIG. **9** can be omitted. For example, the storing unit **910**, the inspection devices **912**, **922** and **932**, and the drying devices **914**, **924** and **934** are optional components and can be omitted. Further, the deposition apparatus **10** can include additional components not shown in FIG. **9**, such as an unloading unit for unloading the substrates. Further, the order of processing the surfaces of the substrates is also exemplary and can be changed, e.g. by performing printing on the side surface first and then on the two main surfaces, or any other order depending on the application.

(70) A deposition apparatus **10** as described herein may include a first orientation-changing device, e.g. the orientation-changing device **926** shown in FIG. **9**, for changing the orientation of the substrate **100** from a first orientation of the substrate to a second orientation of the substrate. The first orientation-changing device may be configured for changing the orientation of the substrate **100** by an angle of about 90 degrees. The first orientation-changing device may be configured for

changing the orientation of the substrate **100** from a substantially vertical orientation to a substantially horizontal orientation and/or from a substantially horizontal orientation to a substantially vertical orientation. The term “substantially horizontal” includes a substrate orientation which can deviate from exact horizontality by an angle of 5 degrees or less, 10 degrees or less, or in some cases even up to 15 degrees.

(71) A deposition apparatus **10** as described herein may include a second orientation-changing device, e.g. orientation-changing device **916** shown in FIG. **9**, for changing the orientation of the substrate **100**. The second orientation-changing device may be configured for changing the orientation of the substrate **100** by an angle of about 180 degrees. The second orientation-changing device may be configured for changing the orientation of the substrate **100** from a first substantially horizontal orientation to a second substantially horizontal orientation. In the first substantially horizontal orientation, the first main surface **120** of the substrate **100** may face upward. In the second substantially horizontal orientation, the second main surface **130** of the substrate **100** may face upward.

(72) The first orientation-changing device may be arranged upstream of the first deposition device **190**. The second orientation-changing device may be arranged upstream of the first orientation-changing device.

(73) The terms “upstream” and “downstream” are defined relative to a processing direction, or processing flow, of the deposition apparatus **10**.

(74) In some implementations, the two main surfaces of the substrate are provided with a conductive pattern first, followed by patterning the side surface of the substrate. The substrate **100** may be processed by depositing a conductive pattern on the first main surface **120** in a first substantially horizontal orientation of the substrate **100**, followed by flipping the substrate **100**, followed by depositing a conductive pattern on the second main surface **130** in a second substantially horizontal orientation of the substrate **100**, followed by changing the orientation of the substrate **100** by about 90 degrees, followed by depositing a conductive pattern on the side surface **110** in a substantially vertical orientation of the substrate **100**.

(75) In other implementations, the surfaces of the substrate may be processed in a different order. For example, the substrate **100** may be processed by depositing a conductive pattern on the first main surface **120** in a first substantially horizontal orientation of the substrate **100**, followed by changing the orientation of the substrate **100** by about 90 degrees, followed by depositing a conductive pattern on the side surface **110** in a substantially vertical orientation of the substrate **100**, followed by changing the orientation of the substrate **100** by another 90 degrees, followed by depositing a conductive pattern on the second main surface **130** in a second substantially horizontal orientation of the substrate **100**. Any other order of processing the surfaces of the substrate is also possible. The same applies to the order for depositing the resist masks on the surfaces of the substrate.

(76) FIG. **10** shows a deposition apparatus **10** according to embodiments described herein.

(77) The first substrate support **180** as described herein may be configured for supporting a stack of substrates **1010** in a substantially vertical orientation. The stack of substrates **1010** in the substantially vertical orientation may have a top portion **1012**. The first deposition device **190** may be configured for depositing, particularly printing, a conductive pattern **1150** or a resist mask **1160** on the top portion **1012** of the stack of substrates **1010** while the stack of substrates **1010** is supported in the substantially vertical orientation by the first substrate support **180**.

(78) FIG. **11a**, showing a top view of a stack of substrates **1010**, shows an example of a conductive pattern **1150** (hashed) on the top portion **1012** of the stack of substrates **1010**. FIG. **11b** shows an example of a resist mask **1160** (hashed) on the top portion **1012** of the stack of substrates **1010**.

(79) The stack of substrates **1010** as described herein may include two, three, four, five or more substrates. The stack of substrates **1010** may include the substrate **100** as described herein. The stack of substrates can be held together, e.g., by a clamping device.

(80) The stack of substrates **1010** can include a plurality of separators. Each separator can be arranged between two adjacent substrates of the stack of substrates **1010**. Each separator can be a sheet-like separator. For example, each separator can be a sheet of paper. Providing the separators between the substrates in the stack has several advantages. For example, the number of fully printed lines can be increased, a sliding of the substrates can be facilitated so that alignment of the substrates is easier, the separators can act as soft layers between the substrates so that particle generation is reduced, and the separators facilitate substrate detachment after drying or curing of the printed material.

(81) Each substrate of the stack of substrates **1010** may have a first main surface, a second main surface and a side surface between the first main surface and the second main surface. While the stack of substrates **1010** is supported in the substantially vertical orientation by the first substrate support, the side surface of each substrate in the stack of substrates **1010** may be at the top portion of the stack of substrates **1010**. The top portion **1012** of the stack of substrates **1010** may include, or be formed by, the side surfaces of the substrates in the stack of substrates **1010**.

(82) The conductive pattern **1150** or resist mask **1160** may be deposited on the side surfaces of a plurality of substrates, or even all substrates, of the stack of substrates **1010**. The stack of substrates **1010** may include the substrate **100** as described herein. The stack of substrates **1010** may include a second substrate. A first portion of the conductive pattern **1150** or of the resist mask **1160** may be deposited on the side surface **110** of the substrate **100**. For example, the first portion of the conductive pattern **1150** may be the first conductive pattern **250** as described herein, or the first portion of the resist mask **1160** may be the first resist mask **260** as described herein. A second portion of the conductive pattern **1150** or of the resist mask **1160** may be deposited on a side surface of the second substrate. In light thereof, embodiments described herein provide the advantage that the side surfaces of multiple substrates can be provided with a conductive pattern or resist mask in a single processing cycle. The throughput of the deposition apparatus can be increased.

(83) The conductive pattern **1150** may include a plurality of conductive lines **1152**. Each conductive line **1152** of the plurality of conductive lines may extend across multiple side surfaces of substrates of the stack of substrates **1010**. The resist mask **1160** may include a plurality of line-like openings **1162**. Each line-like opening **1162** of the plurality of line-like openings may extend across multiple side surfaces of substrates of the stack of substrates **1010**.

(84) After depositing the conductive pattern **1150** or the resist mask **1160** on the stack of substrates **1010**, the substrates of the stack of substrates **1010** can be further processed one by one. For example, the substrate **100** can be taken as a single substrate from the stack of substrates **1010**. Therein, the substrate **100** includes the first conductive pattern **250** or the first resist mask **260** resulting from the deposition of the conductive pattern **1150** or the resist mask **1160** on the stack of substrates **1010**. After the substrate **100** is taken from the stack of substrates **1010**, the first main surface **120** of the substrate **100** can be provided with the second conductive pattern **450** or the second resist mask **460** as described herein. The second main surface **130** of the substrate **100** can be provided with the third conductive pattern **550** or the third resist mask **560** as described herein.

(85) FIG. 12 shows a deposition apparatus **10** according to embodiments described herein.

(86) According to a further embodiment, a deposition apparatus **10** is provided. The deposition apparatus includes a first printing device **1210**. The deposition apparatus **10** includes a first orientation-changing device **1220** downstream of the first printing device. The deposition apparatus **10** includes a second printing device **1230** downstream of the first orientation-changing device. The deposition apparatus **10** includes a second orientation-changing device **1240** downstream of the second printing device. The deposition apparatus **10** includes a third printing device **1250** downstream of the second orientation-changing device.

(87) The terms “upstream” and “downstream” are defined relative to a processing direction, or processing flow, of the deposition apparatus **10**. For example, that the first orientation-changing

device **1220** is downstream of the first printing device **1210** can be understood in the sense that the first orientation-changing device **1220** is arranged relative to the first printing device **1210** in a manner such that substrates are processed by the first printing device **1210** and thereafter transferred to the first orientation-changing device **1220** and processed by the first orientation-changing device **1220**.

(88) As described herein, the first main surface **120**, the second main surface **130** and the side surface **110** of a substrate **100** may be processed in different orders. For example, in an implementation where the two main surfaces of the substrate are provided with a conductive pattern before the side surface is provided with a conductive pattern, the first printing device **1210** may be the second deposition device **330** as described herein, the second printing device **1230** may be the third deposition device **370** as described herein, and the third printing device **1250** may be the first deposition device **190** as described herein. In another implementation, the side surface **110** may be processed in between processing of the first main surface **120** and the second main surface **130**. In such an implementation, the first printing device **1210** may be the second deposition device **330** as described herein, the second printing device **1230** may be the first deposition device **190** as described herein, and the third printing device **1250** may be the third deposition device **370** as described herein.

(89) Depending on the order in which the surfaces of the substrate are processed, the first orientation-changing device may be configured to change the orientation of the substrate by about 90 degrees or by about 180 degrees. The first orientation-changing device may be configured for changing the orientation of the substrate **100** from a substantially vertical orientation to a substantially horizontal orientation or from a substantially horizontal orientation to a substantially vertical orientation, as described herein. The first orientation-changing device may be configured for changing the orientation of the substrate **100** from a first substantially horizontal orientation to a second substantially horizontal orientation, as described herein.

(90) Likewise, depending on the order in which the surfaces of the substrate are processed, the second orientation-changing device may be configured to change the orientation of the substrate by about 90 degrees or by about 180 degrees. The second orientation-changing device may be configured for changing the orientation of the substrate **100** from a substantially vertical orientation to a substantially horizontal orientation or from a substantially horizontal orientation to a substantially vertical orientation, as described herein. The second orientation-changing device may be configured for changing the orientation of the substrate **100** from a first substantially horizontal orientation to a second substantially horizontal orientation, as described herein.

(91) At least one of the first orientation-changing device and the second orientation-changing device may be configured for changing the orientation of the substrate **100** from a substantially vertical orientation to a substantially horizontal orientation or from a substantially horizontal orientation to a substantially vertical orientation.

(92) The first printing device, the second printing device and/or the third pattern deposition device may be a screen printing device.

(93) A deposition apparatus **10** according to embodiments described herein may include a substrate support associated with the first printing device **1210**. The deposition apparatus **10** may include a substrate support associated with the second printing device **1230**. The deposition apparatus **10** may include a substrate support associated with the third printing device **1250**.

(94) A deposition apparatus **10** according to embodiments described herein may include a vertically oriented substrate support. The term “vertically oriented substrate support” refers to a substrate support configured for supporting a substrate in a substantially vertical orientation, as described herein. At least one of the substrate support associated with the first printing device **1210**, the substrate support associated with the second printing device **1230** and the substrate support associated with the third printing device **1250** may be a vertically oriented substrate support.

(95) The deposition apparatus **10** may include at least one horizontally oriented substrate support,

e.g. one horizontally oriented substrate support or two horizontally oriented substrate supports. The term “horizontally oriented substrate support” refers to a substrate support configured for supporting a substrate in a substantially horizontal orientation, as described herein. At least one of the substrate support associated with the first printing device **1210**, the substrate support associated with the second printing device **1230** and the substrate support associated with the third printing device **1250** may be a horizontally oriented substrate support.

(96) According to a further embodiment, a method of deposition on a substrate is provided. The method includes providing a substrate **100** in a substantially vertical orientation. The first substrate has a first main surface **120**, a second main surface **130** opposite the first main surface **120** and a side surface **110** between the first main surface **120** and the second main surface **130**. The method includes depositing a first conductive pattern **250** or a first resist mask **260** on the side surface **110** of the substrate **100** while the first substrate is in the substantially vertical orientation.

(97) The first conductive pattern **250** and/or the first resist mask **260** may be deposited on the side surface **110** by a first deposition device **190** as described herein.

(98) The substrate **100** may be provided, or supported, in the substantially vertical orientation by the first substrate support **180** as described herein.

(99) Depositing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100** may include printing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100**.

(100) A method according to embodiments described herein may include depositing, e.g. printing, a second conductive pattern **450** or a second resist mask **460** on the first main surface **120**, wherein a portion of the second conductive pattern **450** contacts a portion of the first conductive pattern **250** or a portion of the second resist mask **460** contacts a portion of the first resist mask **260**. The second conductive pattern **450** may be deposited by a second deposition device **330** as described herein. The second conductive pattern **450** may be deposited while the substrate **100** is held in a substantially horizontal orientation, e.g. by the second substrate support **320** as described herein.

(101) A method according to embodiments described herein may include depositing, e.g. printing, a third conductive pattern **550** or a third resist mask **560** on the second main surface **130**, wherein a portion of the third conductive pattern **550** contacts a portion of the first conductive pattern **250** or a portion of the third resist mask **560** contacts a portion of the first resist mask **260**. The third conductive pattern **550** may be deposited on the second main surface **130** by a third deposition device **370** as described herein. The third conductive pattern **550** may be deposited while the substrate **100** is held in a substantially horizontal orientation, e.g. by the third substrate support **360** as described herein.

(102) The method according to embodiments described herein may include changing the orientation of the substrate **100** from the substantially vertical orientation to a substantially horizontal orientation or from a substantially horizontal orientation to the substantially vertical orientation.

(103) The method according to embodiments described herein may include changing the orientation of the substrate **100** from a first orientation to a second orientation. The method may include changing the orientation of the substrate **100** from the second orientation to a third orientation. At least one of the first orientation, the second orientation and the third orientation may be a substantially vertical orientation. At least one of the first orientation, the second orientation and the third orientation may be a substantially horizontal orientation.

(104) The method according to embodiments described herein may include providing a stack of substrates **1010** in a substantially vertical orientation. The stack of substrates **1010** may include the substrate **100**. The stack of substrates **1010** in the substantially vertical orientation may have a top portion **1012**. The method may include depositing a conductive pattern **1150** or a resist mask **1160** on the top portion **1012** of the stack while the stack of substrates **1010** is supported in the substantially vertical orientation.

(105) According to a further embodiment, a substrate structure **600** is provided. The substrate structure **600** includes a substrate **100** having a first surface and a second surface opposite the first surface. The first surface of the substrate **100** may be the first main surface **120** as described herein. The second surface may be the second main surface **130** as described herein. The substrate has a side surface **110** between the first surface and the second surface. The substrate structure **600** further includes a plurality of electrical connections between the first surface and the second surface. Each electrical connection includes a conductive line **452** on the first surface, a conductive line **252** on the side surface, and a conductive line **552** on the second surface. The conductive line **252** on the side surface contacts the conductive line **452** on the first surface and the conductive line **552** on the second surface.

(106) According to a further embodiment, a substrate structure is provided. The substrate structure includes a substrate **100** having a first surface, a second surface opposite the first surface and a side surface **110** between the first surface and the second surface. The substrate structure includes a resist mask. The resist mask includes a first resist mask portion covering a portion of the side surface, the first resist mask portion having a first plurality of line-like openings. The first resist mask portion may be the first resist mask **260** as described herein. The resist mask includes a second resist mask portion covering a portion of the first surface, the second resist mask portion having a second plurality of line-like openings. The second resist mask portion may be the second resist mask **460** as described herein. The resist mask includes a third resist mask portion covering a portion of the second surface, the third resist mask portion having a third plurality of line-like openings. The third resist mask portion may be the third resist mask **560** as described herein. Each line-like opening **262** of the first plurality of line-like openings is adjacent to a line-like opening **462** of the second plurality of line-like openings and to a line-like opening **562** of the third plurality of line-like openings.

(107) FIG. **13** shows a substrate support **1300** according to embodiments described herein.

(108) According to a further embodiment, a substrate support **1300** is provided. The substrate support **1300** may be for supporting a substrate **100** in a substantially vertical orientation. The substrate support **1300** includes a first surface **1310**, the first surface **1310** being a stationary surface which is substantially vertical or a movable surface which is movable between a first position and a second position, wherein in the second position the first surface **1310** is substantially vertical. The substrate support **1300** includes a substrate attraction device **1320** adjacent to the first surface **1310**.

(109) The substrate **100** may have a first main surface **120**, a second main surface **130** and a side surface **110** as described herein. A substrate support **1300** according to embodiments described herein may be configured for holding the substrate **100** in a substantially vertical orientation in a manner such that the side surface **110** of the substrate **100** is exposed for deposition of a material on the side surface **110**, e.g. by the first deposition device **190** as described herein. In particular, no holding elements (such as clamps or the like) for holding the substrate **100** may be provided at or on the side surface **110**. In light thereof, the side surface **110** may be free for deposition of, e.g., a first conductive pattern **250** or a first resist mask **260** on the side surface **110**.

(110) A substrate support **1300** according to embodiments described herein may include a support member **1330**. The first surface **1310** may be a surface, particularly a side surface, of the support member **1330**.

(111) The substrate attraction device **1320** is configured to attract the substrate **100**. The substrate attraction device **1320** may be a substrate suctioning device. The substrate attraction device **1320** may be for suctioning the substrate **100** against the first surface **1310**. The substrate attraction device may be, for example, a vacuum chuck, an electronic chuck, or the like. The substrate attraction device **1320** and the substrate **100** may be arranged at opposite sides of the first surface **1310**.

(112) The first surface **1310** may include a plurality of openings **1312**. The plurality of openings

1312 may allow air to pass through the first surface **1310**. The plurality of openings **1312** may allow the substrate attraction device **1320**, e.g. a substrate suctioning device, to suction the substrate **100** against the first surface **1310**. The substrate attraction device **1320** may be a vacuum suctioning device.

(113) The substrate attraction device **1320** may be arranged in or at the support member **1330** of the substrate support **1300**.

(114) The first surface **1310** may be a stationary surface, the stationary surface being a substantially vertical surface. The first surface **1310** may be fixed in a vertical orientation.

(115) Alternatively, the first surface **1310** may be movable from a first position to a second position. In the first position, the first surface **1310** may be a substantially horizontal surface. In the second position, the first surface **1310** may be a substantially vertical surface.

(116) FIGS. **14a-c** show a substrate support **1300** according to embodiments described herein.

FIGS. **14a-b** show the first surface **1310** in the first position as described herein. FIG. **14c** shows the first surface **1310** in the second position as described herein.

(117) As shown for example in FIGS. **14a-b**, the substrate **100** may be loaded onto the first surface **1310** while the first surface **1310** is in the first position. As shown in FIG. **14c**, the first surface **1310** may be moved from the first position to the second position by moving the first surface **1310** by an angle, e.g. an angle of about 90 degrees. When the first surface **1310** is in the second position, the substrate **100** is supported in a substantially vertical orientation. A first conductive pattern **250** or a first resist mask **260**, as described herein, may be deposited on the side surface **110** while the first surface **1310** is in the second position.

(118) The substrate support **1300** may include an actuator for moving the first surface **1310** from the first position to the second position. For example, the first surface **1310** may be a surface of the support member **1330**, wherein the support member **1330** is movable over an angle, e.g. an angle of about 90 degrees, by the actuator.

(119) Embodiments wherein the first surface **1310** is movable from a first position to a second position allow for receiving a horizontally oriented substrate, e.g. a substrate **100** on which in a previous stage a material was deposited while the substrate **100** was in a horizontal orientation. The substrate **100** can be received in the horizontal orientation and be rotated into a vertical orientation by the substrate support **1300**, so that a material can be deposited on the side surface **110** of the substrate **100**. Embodiments described herein thus facilitate switching between a horizontal orientation and a vertical orientation of the substrate **100**. Particularly, where the first surface **1310** is moved between the first position and the second position by an actuator, embodiments described herein allow for switching between a horizontal orientation and a vertical orientation of the substrate **100** in a fully automated manner.

(120) A substrate support **1300** according to embodiments described herein may include a force member **1450** for pressing the substrate **100** against the first surface **1310**. FIG. **14c** shows an example of a force member **1450**.

(121) For example, the force member **1450** may be a piston. The force member **1450** may be for holding the substrate **100** in the substantially vertical orientation. The force member **1450** may be configured to apply a force to the substrate, e.g. to the first main surface **120** or second main surface **130** as described herein. The force member may include a plate-like element for pressing against the substrate **100**. The force member may be configured for applying a substantially horizontal force to the substrate **100**. The force member **1450** may be movable in a substantially horizontal direction, as indicated by the arrow **1452** in FIG. **14c**. The force member **1450** and the substrate attraction device **1320** may be arranged on opposite sides of the substrate **100**.

(122) A separator, e.g. a sheet of paper, may be arranged between the substrate **100** and the first surface **1310**.

(123) A substrate support **1300** according to embodiments described herein may be configured for supporting a stack of substrates **1010**, as described herein, in a substantially vertical orientation.

For example, a stack of substrates **1010** may be attracted against the first surface **1310** by the substrate attraction device **1320** and/or may be pressed against the first surface **1310** by the force member **1450**.

(124) FIGS. **15a-b** shows a substrate support **1300** according to embodiments described herein. FIG. **15b** shows a top view.

(125) According to a further embodiment, a substrate support **1300** for a deposition apparatus, particularly a printing apparatus, is provided. The substrate support **1300** may be for supporting a substrate **100** in a substantially vertical orientation. The substrate support **1300** includes a housing **1520** comprising a slit **1510** to receive the substrate **100** in the substantially vertical orientation. The slit **1510** may have a bottom surface. The slit **1510** may have a first surface **1310**, e.g. a surface of a first side wall of the slit. The slit **1510** may have a second surface **1512**, e.g. a surface of a second side wall of the slit. The second surface **1512** may face the first surface **1310**. The bottom surface may connect the first surface **1310** with the second surface **1512**. The first surface **1310** and the second surface **1512** may be substantially vertical surfaces. The bottom surface may be a substantially horizontal surface. The slit **1510** may be configured for receiving the substrate **100** between the first surface **1310** and the second surface **1512**.

(126) The slit **1510** may be configured for receiving the substrate **100** in a manner such that the side surface **110** of the substrate **100** is exposed for depositing a material, e.g. a first conductive pattern or a first resist mask as described herein, on the side surface **110**.

(127) The slit **1510** may have a top side. The housing **1520** may have a top side. The top side of the slit **1510** may be at the top side of the housing **1520**. The top side of the slit **1510** may be an open side for receiving the substrate **100**.

(128) The slit **1510** may have a bottom side. The bottom side of the slit **1510** may be opposite the top side of the slit **1510**. The slit **1510** may include a substrate supporting surface **1550** for supporting the substrate **100** from below. The substrate supporting surface **1550** may be a substantially horizontal surface. The substrate supporting surface **1550** may be at the bottom side of the slit **1510**. The substrate supporting surface **1550** may be the bottom surface of the slit **1510**.

(129) The slit **1510** may be configured for receiving a stack of substrates **1010**, as described herein, in a substantially vertical orientation. For example, a stack of substrates including two or three or more substrates can be inserted in the slit **1510**. The substrate supporting surface **1550** may be for supporting the stack of substrates **1010** in a substantially vertical orientation. FIG. **15b** shows a stack of two substrates received in the slit **1510**.

(130) The substrate support **1300** may include a force member **1450** for holding the substrate **100** in the slit **1510**. FIG. **15b** shows an example of a force member **1450**. For example, the force member **1450** may be an arrangement including a plate pressing against the substrate **100** in the slit **1510**, possibly including one or more screws for adjusting the position of the plate.

(131) The force member **1450** may be at least partially arranged in the slit **1510**. The force member **1450** may be configured to apply a force to the substrate **100**, e.g. to the first main surface **120** or second main surface **130** as described herein. The force member **1450** may include a plate-like element for pressing against the substrate **100**. The force member **1450** may be configured for applying a substantially horizontal force to the substrate **100**. The force member **1450** may be movable in a substantially horizontal direction, as indicated by the arrow **1580** in FIG. **15b**. The force member **1450** may be configured for pressing the substrate **100** against the first surface **1310** of the slit **1510**. A separator, e.g. a sheet of paper, may be arranged between the substrate **100** and the first surface **1310** of the slit **1510**.

(132) The housing **1520** may surround the slit **1510**. The housing **1520** may, e.g., include or be made of aluminum. The housing **1520** may be shaped as a box.

(133) The first substrate support **180** as described herein may be a substrate support **1300** according to embodiments described herein, e.g. a substrate support **1300** as shown in FIGS. **13**, **14a-c** or **15a-b**.

(134) According to a further embodiment, a substrate support **1300** for supporting a substrate **100** is provided. The substrate support **1300** includes a first surface, the first surface being a stationary surface which is substantially vertical or a movable surface which is movable between a first position and a second position, wherein in the second position the first surface is substantially vertical. The substrate support **1300** includes a biasing device for biasing a substrate **100** against the first surface, the substrate **100** having a first main surface **120**, a second main surface **130** opposite the first main surface **120** and a side surface **110** between the first main surface **120** and the second main surface **130**. The substrate support **1300** may be configured for holding the substrate **100** in a substantially vertical orientation in a manner such that the side surface **110** of the substrate **100** is exposed for deposition of a material on the side surface **110**. The first surface may be the first surface **1310** as described herein, e.g. the first surface **1310** shown in FIG. **13** or **14a-c** or the first surface **1310** shown in FIG. **15b**. The biasing device may include or be at least one of a substrate attraction device **1320** and a force member **1450** as described herein.

(135) A substrate support **1300** according to embodiments described herein may be a substrate support for a deposition apparatus, particularly a printing apparatus. The substrate support may be included in the deposition apparatus. The deposition apparatus may include a deposition device, particularly a printing device. The deposition device may be for depositing a material on a substrate supported by the substrate support.

(136) FIGS. **16a-b** shows a substrate support **1600** according to embodiments described herein.

(137) According to a further embodiment, a substrate support **1600** for supporting a substrate **100** is provided. The substrate support **1600** includes a substrate receiving area **1610**. The substrate support **1600** includes a first recess **1630** at or near a first edge **1620** of the substrate receiving area **1610**.

(138) The substrate support **1600** may be a substrate support for a deposition apparatus **10**, particularly a printing apparatus. The substrate support **1600** may be a nest, particularly a printing nest.

(139) The substrate support **1600** may be configured for supporting the substrate **100** in a substantially horizontal orientation. The substrate receiving area **1610** may be a substantially horizontally oriented area. The second substrate support **320** and/or the third substrate support **360**, as described herein, may be a substrate support **1600** according to embodiments described herein.

(140) The substrate receiving area **1610** may be configured for receiving the substrate **100**. The dimensions (e.g. length and width) of the substrate receiving area **1610** may correspond to the dimensions of the substrate **100** supported by the substrate support **1600**. The first edge **1620** of the substrate receiving area **1610** may correspond to, e.g. be aligned with, a first edge of the substrate **100** supported in the substrate receiving area **1610**.

(141) The substrate support **1600** may have a substrate receiving surface **1650**. The substrate receiving area **1610** may be a region on the substrate receiving surface **1650**. The first recess **1630** may be a recess formed in the substrate receiving surface **1650**.

(142) The first edge **1620** of the substrate receiving area **1610** may have a length in a first direction, e.g. direction **1602** shown in FIG. **16b**. The first recess **1630** may have a length in the first direction.

(143) The first direction may be a horizontal direction. The first recess **1630** may be a strip-like recess having a length in the first direction. The length of the first recess **1630** in the first direction may be at least as long as, or longer than, the length of the first edge **1620** of the substrate receiving area **1610** in the first direction.

(144) The first recess **1630** may have a width **1632** in a second direction, e.g. direction **1604** shown in FIGS. **16a-b**. The width **1632** of the first recess **1630** may be smaller than the length of the first recess **1630**. The second direction may be a horizontal direction. The second direction may be perpendicular to the first direction.

(145) The first recess **1630** may have a width **1632** in the second direction from a first side of the

first recess **1630** to a second side of the first recess **1630**. At least a portion of the first edge **1620** of the substrate receiving area **1610** may be located between the first side and the second side of the first recess **1630**.

(146) A portion of the substrate receiving area **1610**, particularly an edge portion of the substrate receiving area **1610**, may overlap with the first recess **1630**, as shown for example in FIG. **16b**. The first side of the first recess **1630** may be outside a periphery of the substrate receiving area **1610**. At least a portion of the second side of the first recess may be inside the periphery of the substrate receiving area.

(147) The first recess **1630** may have a depth in a vertical direction.

(148) The first recess **1630** may be configured for receiving deposition material **1680**. Particularly, the first recess **1630** may be configured for receiving deposition material **1680** resulting from depositing a layer or pattern **1690** on an edge region of the substrate **100** near the first edge **1620** of the substrate receiving area **1610**, such as e.g. deposition of a second/third conductive pattern or a second/third resist mask as described herein. By receiving the deposition material **1680** in the first recess **1630**, the deposition material **1680** does not accumulate on the substrate receiving surface **1650** of the substrate support **1600**, but is received in the first recess **1630**. In light thereof, the substrate receiving surface **1650** of the substrate support **1600** does not become dirty through an accumulation of deposition material thereon. Further, the presence of the first recess **1630** allows for usage of a screen with a bigger pattern for performing screen printing on the edge region of the substrate without making the substrate support dirty, since the deposition material urged through the screen at the periphery of the screen will be received in the first recess **1630**. Accordingly, an improved coverage of the edge region of the substrate **100** by the layer or pattern **1690** can be provided.

(149) The substrate support **1600** according to embodiments described herein may include one or more further recesses like the first recess **1630**. For example, the substrate receiving area **1610** may have a second edge. The substrate support **1600** may have a second recess at or near the second edge. Like the first recess **1630**, the second recess may be configured to receive deposition material.

(150) A substrate support **1600** according to embodiments described herein may be a substrate support for a deposition apparatus, particularly a printing apparatus. The substrate support may be included in the deposition apparatus. The deposition apparatus may include a deposition device, particularly a printing device. The deposition device may be for depositing a material on a substrate supported by the substrate support.

(151) FIG. **17** shows a deposition apparatus **10** according to embodiments described herein.

(152) According to a further embodiment, a deposition apparatus **10** is provided. The deposition apparatus **10** includes a first substrate support **180** for supporting a substrate **100**. The substrate has a first main surface **120**, a second main surface **130** opposite the first main surface **120** and a side surface **110** between the first main surface **120** and the second main surface **130**. The deposition apparatus **10** includes a first deposition device **190**. The first deposition device **190** may be for depositing a first conductive pattern **250** or a first resist mask **260** on the side surface **110** of the substrate **100**. The deposition apparatus **10** includes an observation device **1710**. The observation device may be for observing at least a portion of the first main surface **120**. The deposition apparatus **10** includes one or more alignment actuators **1720** connected to the observation device **1710**. The one or more alignment actuators **1720** may be configured to align the first deposition device **190** and the side surface **110** of the substrate **100** relative to each other.

(153) The deposition apparatus **10** including the one or more alignment actuators **1720** may include any feature, or any feature combination, described herein within the context of other embodiments of the deposition apparatus **10**. For example, the deposition apparatus **10** may include a second deposition device **330**, a third deposition device **370**, a first orientation-changing device, a second orientation-changing device, and so on, or any combination thereof.

(154) The first deposition device **190** may be arranged for depositing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100** while the substrate **100** is supported by the first substrate support **180**. The observation device **1710** may be configured for observing the at least a portion of the first main surface **120** while the substrate **100** is supported by the first substrate support **180**. The one or more alignment actuators **1720** may be configured for aligning the first deposition device **190** and the side surface **110** relative to each other while the substrate **100** is supported by the first substrate support **180**. The first substrate support **180** may be configured to support the substrate **100** in a substantially vertical orientation.

(155) That the one or more alignment actuators **1720** are connected to the observation device **1710** can be understood in the sense that the observation device **1710** is in communication with the one or more alignment actuators **1720**. The one or more alignment actuators **1720** may be connected to the observation device **1710** in a manner such that data obtained by observing the first main surface **120** of the substrate **100** can be provided from the observation device **1710** to the one or more alignment actuators **1720**, possibly via a controller as described herein.

(156) That the first deposition device **190** and the side surface **110** of the substrate **100** are aligned relative to each other does not necessarily mean that the entire first deposition device **190** and the side surface **110** are aligned relative to each other. For example, a portion of the first deposition device **190**, such as e.g. a deposition head or printing head, may be displaced to align the portion relative to the side surface **110**, while a remaining portion of the first deposition device **190** may remain stationary.

(157) In some implementations, the one or more alignment actuators **1720** may be part of the first deposition device **190**. Alternatively, the one or more alignment actuators **1720** and the first deposition device **190** may be different components of the deposition apparatus. The first deposition device **190** may be mounted to the one or more alignment actuators **1720** or vice versa. A portion of the first deposition device **190**, e.g. a deposition head or printing head, may be mounted to the one or more alignment actuators **1720**, or vice versa.

(158) In some implementations, the one or more alignment actuators **1720** may be part of the first substrate support **180**, e.g. a printing nest. Alternatively, the one or more alignment actuators **1720** and the first substrate support **180** may be different components of the deposition apparatus. The first substrate support **180** may be mounted to the one or more alignment actuators **1720** or vice versa.

(159) The observation device **1710** may be configured to provide data obtained by observing at least a portion of the first main surface **120** to the one or more alignment actuators **1720**. The data may be data regarding the position of the at least a portion of the first main surface **120**. The one or more alignment actuators **1720** may be configured to align the first deposition device **190** and the side surface **110** of the substrate **100** relative to each other based at least on the data.

(160) The first deposition device **190** may be configured for depositing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100** after the first deposition device **190** and the side surface **110** of the substrate have been aligned with respect to each other by the one or more alignment actuators **1720**.

(161) The first substrate support **180** may be configured for supporting the substrate **100** in a substantially vertical orientation. The first deposition device **190** may be configured for depositing the first conductive pattern **250** or the first resist mask **260** on the side surface **110** of the substrate **100** while the substrate **100** is supported in the substantially vertical orientation by the first substrate support **180**. The observation device **1710** may be configured for observing the at least a portion of the first main surface **120** while the substrate **100** is supported in the substantially vertical orientation by the first substrate support **180**.

(162) The substrate **100** may have an alignment mark **1810** on the first main surface **120**, as shown for example in FIG. **18**. The observation device **1710** may be configured to observe the alignment mark **1810**. The observation device **1710** may be configured to provide data obtained by observing

the alignment mark **1810** to the one or more alignment actuators **1720**. The data may be data regarding the position of the alignment mark **1810**. The one or more alignment actuators **1720** may be configured to align the first deposition device **190** and the side surface **110** of the substrate relative to each other based at least on the data.

(163) The first main surface **120** may include a plurality of alignment marks. For example, in the case of a rectangular substrate, an alignment mark can be provided in the two upper corners of the first main surface **120**. The observation device **1710** may be configured for observing the plurality of alignment marks. The one or more alignment actuators **1720** may be configured for aligning the side surface **110** and the first deposition device **190** relative to each other at least based on data obtained by observing the plurality of alignment marks.

(164) The alignment mark(s) on the first main surface **120** of the substrate **100** may be already available, e.g. pre-formed, for aligning the first main surface **120**, e.g., for a deposition process in which a material is deposited on the first main surface **120**. Embodiments described herein make use of the alignment mark(s) on the first main surface **120** to align a different surface of the substrate **100**, namely the side surface **110**, with respect to a deposition device for depositing a material on the side surface **110**.

(165) The observation device **1710** may be an inspection device for inspecting at least a portion of the first main surface **120** of the substrate **100**. The observation device **1710** may be or include an imaging device, particularly an optical imaging device such as e.g. a camera, configured to make an image of the at least a portion of the first main surface **120**. The observation device **1710** may be configured to make an image of the alignment mark **1810**.

(166) The alignment performed by the one or more alignment actuators **1720** as described herein is a relative alignment of the first deposition device **190** and the side surface **110** of the substrate **100** with respect to each other. The one or more alignment actuators **1720** may be configured for moving the first deposition device **190** (as illustrated e.g. in FIG. 17), for moving the substrate **100** or for moving both the first deposition device **190** and the substrate **100** to align the first deposition device **190** and the side surface **110** of the substrate relative to each other.

(167) The one or more alignment actuators **1720** may be configured for providing a translational alignment and/or an angular alignment of the first deposition device **190** and the side surface **110** of the substrate relative to each other.

(168) The one or more alignment actuators **1720** may be configured for translating the first deposition device **190**, or at least a portion thereof, such as e.g. a deposition head or printing head of the first deposition device **190**. The first deposition device **190** or the portion thereof may be moved, e.g. translated, by the one or more alignment actuators **1720** in a substantially vertical direction and/or in a substantially horizontal direction. Additionally or alternatively, the one or more alignment actuators **1720** may be configured for changing an angle of the first deposition device **190**, or at least a portion thereof, such as a deposition head or printing head. The angle may be an angle with respect to a substantially horizontal axis.

(169) The one or more alignment actuators **1720** may be configured for translating the substrate **100**. The substrate **100** may be translated in a substantially vertical direction and/or in a substantially horizontal direction. The one or more alignment actuators **1720** may be configured for changing an angle of the substrate **100**. The angle may be an angle with respect to a substantially horizontal axis.

(170) A deposition apparatus **10** according to embodiments described herein may include a controller. The controller may be connected to the observation device **1710**. Additionally or alternatively, the controller may be connected to the one or more alignment actuators **1720**. The controller may be configured to determine a target relative position for the first deposition device **190** with respect to the side surface **110** of the substrate **100** based on data provided by the observation device **1710**. The data may be data regarding the position of the at least a portion of the first main surface **120** or data regarding the position of the alignment mark **1810**. The controller

may be configured for issuing an instruction to the one or more alignment actuators **1720**. The controller may be configured to instruct the one or more alignment actuators to move the first deposition device **190**, or a portion thereof, and/or to move the substrate **100**, to provide the first deposition device **190** and the substrate **100** in the target relative position. In the target relative position, the first deposition device **190** and the substrate **100** are well-aligned relative to each other.

(171) FIG. **19** shows a deposition apparatus **10** according to embodiments described herein.

(172) The observation device **1710**, e.g. a camera, may be connected to the first deposition device **190**. The observation device may be mounted to the first deposition device **190**, as shown for example in FIG. **19**. For example, the observation device **1710** may be connected or mounted to a deposition head, e.g. a printing head, of the first deposition device **190**.

(173) A deposition apparatus according to embodiments described herein may include a reflective surface **1912**. The reflective surface **1912** may be a reflective surface of a reflective member **1910**, e.g. a mirror. The observation device **1710**, e.g. a camera, may be configured for observing at least a portion of the first main surface **120** via the reflective surface **1912**. The observation device **1710** may be arranged at an elevated position with respect to the reflective surface **1912**. For example, the observation device **1710** may be attached or mounted to the first deposition device **190**, particularly to a printing head of the first deposition device **190**. The reflective surface **1912** may face the substrate **100** supported by the first substrate support **180**. In particular, the reflective surface **1912** may face the vertically oriented substrate **100**. The reflective surface **1912** may be arranged to reflect light emanating from a region near the first main surface **120** to the observation device **1710**, as e.g. indicated in FIG. **19** by the dashed lines.

(174) A deposition apparatus according to embodiments described herein may include a light source **1920**. The light source **1920** may be for illuminating the first main surface **120**. The light source **1920** may be arranged in a region near a substrate receiving area of the first substrate support **180** or near the substrate **100** supported by the first substrate support **180**. The light source **1920** and the reflective surface **1912** may be arranged on the same side of the substrate **100** or substrate receiving area (as shown e.g. in FIG. **19**), or on different sides of the substrate **100** or substrate receiving area (e.g. if the substrate **100** is transparent). Light from the light source **1920** may travel to the reflective surface **1912** and be reflected by the reflective surface to the observation device. The observation device **1710** may be configured for observing at least a portion of the first main surface **120** via the reflective surface **1912**.

(175) Whereas some embodiments described herein use a light source **1920** and a reflective surface **1912** to facilitate the observation of the substrate **100** by the observation device **1710**, neither the light source **1920** nor the reflective surface **1912** is necessary for observing the substrate **100**. For example, the observation device **1710** may be arranged to face the substrate **100** supported by the first substrate support **180**. In such a set-up, a reflective surface **1912** is not needed. Further, depending on the lighting conditions of the deposition apparatus **10**, a light source **1920** for illuminating the first main surface **120** may not be necessary.

(176) In the above description of the deposition apparatus **10**, the observation device **1710** is arranged for observing at least a portion of the first main surface **120**, as shown for example in FIG. **17**. Alternatively, the observation device **1710** can be arranged for observing at least a portion of the second main surface **130**.

(177) FIGS. **20a-b** show a deposition apparatus **10** according to embodiments described herein.

(178) A deposition apparatus **10** according to embodiments described herein may include one or more inspection units **2010** for determining an alignment of the side surface **110** with respect to a substantially horizontal direction, e.g. direction **2030** shown in FIGS. **20a-b**. The one or more inspection units **2010** can be combined with any embodiment of a deposition apparatus **10** as described herein.

(179) The one or more inspection units **2010** may be arranged above a substrate receiving area of

the first substrate support **180** or above the substrate **100** supported by the first substrate support **180**, particularly a vertically oriented substrate or substrate receiving area. The one or more inspection units **2010** may be two or more inspection units, e.g. two cameras or distance sensors. The two or more inspection units may include a first inspection unit and a second inspection unit spaced apart from each other by a horizontal distance, as shown for example in FIGS. **20a-b**.

(180) The one or more inspection units **2010** may be configured to inspect the side surface **110** of the substrate **100** supported by the first substrate support **180**. The one or more inspection units **2010** may be configured to inspect an upper edge **2020** of the substrate **100** supported by the first substrate support **180**. The upper edge **2020** may be an edge of the side surface **110**. The upper edge **2020** may be a substantially horizontal edge of the substrate **100** supported by the first substrate support **180**.

(181) The one or more inspection units **2010** may be part of the observation device **1710** as described herein, may be the observation device **1710**, or may be separate from the observation device **1710**.

(182) The one or more inspection units **2010** may be configured for determining a height of the substrate **100**, particularly a vertically oriented substrate, supported by the first substrate support **180**. In light thereof, embodiments described herein allow for dynamically changing the snap-off according to the height of the substrate **100** and the difference of substrate size can be compensated for on a substrate-by-substrate basis.

(183) Additionally or alternatively, the one or more inspection units may be for determining a horizontal alignment of the upper edge **2020**, particularly for determining whether the upper edge **2020** is aligned with a substantially horizontal direction, e.g. direction **2030** shown in FIGS. **20a-b**. The one or more inspection units may be for determining whether an angle exists between the upper edge **2020** and the substantially horizontal direction. If no angle or an angle below a small threshold angle exists, the upper edge **2020** may be well aligned, as shown for example in FIG. **20a**. If an angle above the threshold value exists, the upper edge **2020** may not be well aligned, as shown for example in FIG. **20b**. The angle between the upper edge **2020** and the direction **2030** is drawn in an exaggerated manner in FIG. **20b**.

(184) By having the one or more inspection units **2010**, embodiments described herein provide the advantage that the deposition process, e.g. a screen printing process, can be interrupted or stopped if the tilting angle of the substrate **100**, i.e. the angle between the upper edge **2020** and the substantially horizontal direction **2030**, is too large. In light thereof, damage to e.g. the screen of the first deposition device, which can arise if the tilting angle of the substrate is too large, can be avoided.

(185) According to a further embodiment, a method of alignment is provided. The method includes providing a substrate **100** having a first main surface **120**, a second main surface **130** opposite the first main surface **120** and a side surface **110** between the first main surface **120** and the second main surface **130**. The method includes aligning a first deposition device **190** and the side surface **110** of the substrate relative to each other, the aligning being based at least on data obtained by observing at least a portion of the first main surface **120**.

(186) The aligning of the first deposition device **190** and the side surface **110** relative to each other may be performed by one or more alignment actuators **1720** as described herein.

(187) The method may include depositing a first conductive pattern **250** or a first resist mask **260**, as described herein, on the side surface **110** of the substrate **100** using the first deposition device **190**. The first conductive pattern **250** or the first resist mask **260** may be deposited on the side surface **110** after the first deposition device **190** and the side surface **110** of the substrate have been aligned with respect to each other based on the data obtained by observing the first main surface **120**.

(188) The method may include supporting the substrate **100** in a substantially vertical orientation, e.g. using a first substrate support **180** as described herein. The method may include observing the

at least a portion of the first main surface **120** while the substrate **100** is supported in the substantially vertical orientation. The first deposition device **190** and the side surface **110** of the substrate **100** may be aligned relative to each other while the substrate **100** is supported in the substantially vertical orientation. The first conductive pattern **250** or the first resist mask **260** may be deposited on the side surface **110** of the substrate **100** while the substrate **100** is supported in the substantially vertical orientation.

(189) The substrate **100** may have an alignment mark **1810**, as described herein, on the first main surface **120**. Particularly, the at least a portion of the first main surface **120** may include the alignment mark **1810**. The method may include observing the alignment mark **1810**, particularly observing a position of the alignment mark **1810**. The data obtained by observing at least a portion of the first main surface **120** may be data obtained by observing the alignment mark **1810**. The method may include aligning the first deposition device **190** and the side surface **110** of the substrate relative to each other based at least on the data obtained by observing the alignment mark **1810**.

(190) Observing at least a portion of the first main surface **120** or observing the alignment mark **1810** may include making one or more images of the at least a portion or of the alignment mark **1810**, e.g. using a camera.

(191) The method may include determining an alignment of the side surface **110** with respect to a substantially horizontal direction, as described herein. The alignment may be determined using one or more inspection units **2010** as described herein.

(192) While the foregoing is directed to embodiments of the disclosure, other and further embodiments of the disclosure may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

Claims

1. A deposition apparatus, comprising: a first substrate support for supporting a substrate in a substantially vertical orientation, the substrate having a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface; and a first deposition device for depositing a first conductive pattern or a first resist mask on the side surface of the substrate while the substrate is supported in the substantially vertical orientation by the first substrate support.
2. The deposition apparatus according to claim 1, wherein the first substrate support is configured for supporting a stack of substrates in a substantially vertical orientation, the stack of substrates in the substantially vertical orientation having a top portion, wherein the first deposition device is configured for depositing a conductive pattern or a resist mask on the top portion of the stack while the stack is supported in the substantially vertical orientation by the first substrate support.
3. A method of deposition on a substrate, comprising: providing a substrate in a substantially vertical orientation, the substrate having a first main surface, a second main surface opposite the first main surface and a side surface between the first main surface and the second main surface, the side surface being a surface at a top portion of the substrate and having a width corresponding to a thickness of the substrate; and printing a first conductive pattern or a first resist mask on the side surface of the substrate while the substrate is in the substantially vertical orientation.
4. The method according to claim 3, further comprising at least one of: depositing a second conductive pattern or a second resist mask on the first main surface, wherein a portion of the second conductive pattern contacts a portion of the first conductive pattern or a portion of the second resist mask contacts a portion of the first resist mask; and depositing a third conductive pattern or a third resist mask on the second main surface, wherein a portion of the third conductive pattern contacts a portion of the first conductive pattern or a portion of the third resist mask contacts a portion of the first resist mask.

5. The method according to claim 4, wherein: the first conductive pattern includes a first plurality of conductive lines, the second conductive pattern includes a second plurality of conductive lines, and the third conductive pattern includes a third plurality of conductive lines, each conductive line of the first plurality of conductive lines contacting a conductive line of the second plurality of conductive lines and a conductive line of the third plurality of conductive lines to form an electrical connection from the first main surface to the second main surface, or the first resist mask includes a first plurality of line-like openings, the second resist mask includes a second plurality of line-like openings, and the third resist mask includes a third plurality of line-like openings, each line-like opening of the first plurality of line-like openings being adjacent to a line-like opening of the second plurality of line-like openings and to a line-like opening of the third plurality of line-like openings.

6. The method of claim 3, wherein the substrate is provided in the substantially vertical orientation by a first substrate support and the first conductive pattern or the first resist mask is deposited on the side surface of the substrate by a first deposition device, the method further comprising: supporting the substrate in a substantially horizontal orientation by a second substrate support; and depositing a second conductive pattern or a second resist mask on the first main surface of the substrate by a second deposition device while the substrate is supported by the second substrate support.

7. The method of claim 6, further comprising: supporting the substrate in a substantially horizontal orientation by a third substrate support; and depositing a third conductive pattern or a third resist mask on the second main surface of the substrate by a third deposition device while the substrate is supported by the third substrate support.

8. The method of claim 3, further comprising: changing the orientation of the substrate from a first orientation of the substrate to a second orientation of the substrate.

9. The method of claim 3, further comprising: supporting a stack of substrates in a substantially vertical orientation, the stack of substrates including the substrate, the stack of substrates in the substantially vertical orientation having a top portion; and depositing a conductive pattern or a resist mask on the top portion of the stack while the stack is supported in the substantially vertical orientation.
