

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402420
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Guo; Zhiqiu et al.

Photovoltaic module and method for manufacturing photovoltaic module

Abstract

A photovoltaic module and a method for manufacturing the photovoltaic module are provided. The photovoltaic module includes a battery module including multiple cell string groups and multiple first connection structures. Each cell string group includes multiple cell strings arranged along a first direction. Each cell string includes multiple solar cells and multiple second connection structures. Each solar cell includes multiple first grid lines and multiple second grid lines. There is a distance L between a first grid line and a second grid line adjacent to the first grid line in the first direction. A second connection structure connected to an end of a respective middle first connection structure is spaced apart by a distance S in the first direction from an adjacent second connection structure connected to an end of another middle first connection structure adjacent to the respective middle first connection structure and the distance S is greater than the distance L .

Inventors: Guo; Zhiqiu (Jiaxing, CN), Huang; Shiliang (Jiaxing, CN), Guan; Yingli (Jiaxing, CN)

Applicant: JINKO SOLAR (HAINING) CO., LTD. (Haining, CN)

Family ID: 1000008780969

Assignee: JINKO SOLAR (HAINING) CO., LTD. (Haining, CN)

Appl. No.: 17/898259

Filed: August 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230307565 A1	Sep. 28, 2023

Foreign Application Priority Data

CN	202210309343.0	Mar. 28, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: H10F19/90 (20250101); H10F71/00 (20250101)

U.S. Cl.:

CPC H10F19/908 (20250101); H10F71/137 (20250101);

Field of Classification Search

CPC: H01L (31/022441); H01L (31/05); H01L (31/0504); H01L (31/0508); H01L (31/0516);
H01L (31/1876); H10F (19/902); H10F (19/908); H10F (71/137)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0146128	12/2012	Yang	136/251	H01L 31/0516
2015/0171484	12/2014	Lenardic	429/50	H02J 7/35
2016/0308082	12/2015	Ishii	N/A	H02S 40/34
2017/0222082	12/2016	Lin et al.	N/A	N/A
2017/0323988	12/2016	Kim	N/A	H02S 40/22
2018/0198008	12/2017	Tripp et al.	N/A	N/A
2020/0105954	12/2019	Maki	N/A	H01L 31/02013

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103208547	12/2012	CN	N/A
104952888	12/2014	CN	N/A
105122459	12/2014	CN	N/A
105576055	12/2015	CN	N/A
206259375	12/2016	CN	N/A
107170841	12/2016	CN	N/A
107851673	12/2017	CN	N/A
108649089	12/2017	CN	N/A
208422933	12/2018	CN	N/A
208580754	12/2018	CN	N/A
209843730	12/2018	CN	N/A
110838527	12/2019	CN	N/A
210110811	12/2019	CN	N/A
210136884	12/2019	CN	N/A
210379080	12/2019	CN	N/A
111613685	12/2019	CN	N/A
2020216912	12/2019	CN	N/A
112086520	12/2019	CN	N/A
212113733	12/2019	CN	N/A
112186059	12/2020	CN	N/A

112542527	12/2020	CN	N/A
212695156	12/2020	CN	N/A
212848423	12/2020	CN	N/A
214505504	12/2020	CN	N/A
214505507	12/2020	CN	N/A
214505517	12/2020	CN	N/A
113611766	12/2020	CN	N/A
215183991	12/2020	CN	N/A
215183994	12/2020	CN	N/A
215342629	12/2020	CN	N/A
215451430	12/2021	CN	N/A
102011056632	12/2012	DE	N/A
S63278279	12/1987	JP	N/A
2008218578	12/2007	JP	N/A
2013243358	12/2012	JP	N/A
2016082025	12/2015	JP	N/A
2018046112	12/2017	JP	N/A
6312761	12/2017	JP	N/A
2019519942	12/2018	JP	N/A
2020057652	12/2019	JP	N/A
2011011855	12/2010	WO	N/A
2021051862	12/2020	WO	N/A
2021051929	12/2020	WO	N/A

OTHER PUBLICATIONS

Machine translation of CN-105576055-A, Lin et al. (Year: 2016). cited by examiner
Jinko Solar (Haining) Co., Ltd., AU Notice of acceptance for your patent application, AU 2022218482, Aug. 7, 2023, 4 pgs. cited by applicant
Jinko Solar (Haining) Co., Ltd., Extended European Search Report, EP 22191924.4, May 15, 2023, 11 pgs. cited by applicant
Jinko Solar Co., Ltd., et al., CN First Office Action with English translation, CN 2022106516511, Jun. 28, 2024, 13 pgs. cited by applicant
Jinko Solar (Haining) Co., Ltd., JP Notice of Reasons for Refusal with English translation, JP 2023-012488, Jul. 2, 2024, 27 pgs. cited by applicant
Jinko Solar Co., Ltd et al., Chinese Notice of Rejection with English Translation, CN 202210651651.1, Mar. 5, 2025, 12 pgs. cited by applicant

Primary Examiner: Gonzalez Ramos; Mayla

Attorney, Agent or Firm: USCH Law, PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) The present application claims the benefit of priority under the Paris Convention to Chinese Patent Application No. 202210309343.0 filed on Mar. 28, 2022 and Chinese Patent Application No. 202210651651.1 filed on Jun. 9, 2022, which are incorporated herein by reference in their entireties.

TECHNIC FIELD

(2) Embodiments of the disclosure relate to the field of photovoltaic, and more particularly to a photovoltaic module and a method for manufacturing the photovoltaic module.

BACKGROUND

(3) The interdigitated back contact (IBC) solar cell refers to a back contact solar cell in which positive and negative metal electrodes are arranged on the back of the cell in an interdigitated manner. The PN junction and electrodes of the IBC solar cell are disposed on the back of the cell, that is, electrodes in an emitting region and a base region of the IBC solar cell are all disposed on the back of the IBC solar cell, so that the front of the solar cell is not shielded by grid lines, which can improve photoelectric conversion performance of the cell.

(4) Generally, lead lines are used to lead out current converged by grid lines of the cell to the outside of the photovoltaic module. One end of the lead line is connected with an end of a bus bar of the battery, the lead line is perpendicular to a surface of the photovoltaic module or a surface of the solar cell, and then the other end of the lead line is connected with a junction box, such that lead line is connected with an external element through the junction box. With the development of solar cells, the lead lines are susceptible to short circuit.

SUMMARY

(5) Embodiments of the disclosure provide a photovoltaic module and a method for manufacturing the photovoltaic module.

(6) Some embodiments of the disclosure provide a photovoltaic module. The photovoltaic module includes a battery module. The battery module includes multiple cell string groups and multiple first connection structures. Each of the multiple cell string groups includes multiple cell strings that are arranged along a first direction and are electrically connected in a first electrical connection mode. The multiple cell string groups include at least one first cell string group and at least one second cell string group, and a respective cell string group of the at least one first cell string group and a corresponding cell string group of the at least one second cell string group are arranged along a second direction and electrically connected in a second electrical connection mode. The multiple first connection structures extend in the first direction. Each of the multiple first connection structures is configured to connect corresponding cell strings. The multiple first connection structures include at least one middle first connection structure. Each of the at least one middle first connection structure is configured to connect at least one cell string of a corresponding first cell string group and at least one cell string of a corresponding second cell string group. Each of the multiple cell strings includes multiple second connection structures and multiple solar cells, where the multiple solar cells are electrically connected in the first electrical connection mode, and each of the multiple second connection structures is configured to connect corresponding grid lines. Each solar cell of the multiple solar cells includes multiple first grid lines of a first conductivity type interleaved with multiple second grid lines of a second conductivity type, and there is a distance L , in the first direction, between a first grid line and a second grid line adjacent to the first grid line of the solar cell. Each of at least one second connection structure in a solar cell at an end of a respective cell string is connected with a corresponding middle first connection structure. A second connection structure connected to an end of a respective middle first connection structure is spaced apart by a distance S in the first direction from an adjacent second connection structure connected to an end of another middle first connection structure adjacent to the respective middle first connection structure, and the distance S is greater than the distance L .

(7) In some embodiments, each of the multiple cell strings includes an even number of solar cells, and the even number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. Each of the at least one first cell string group includes

multiple first cell strings and multiple first cell strings rotated by 180° that are alternately arranged in the first direction. Each of the multiple first cell strings includes the multiple first solar cells and multiple second solar cells rotated by 180° that are alternately arranged in the second direction.

(8) In some embodiments, each of the multiple cell strings includes an even number of solar cells, and the even number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. Each of the at least one second cell string group includes multiple first cell strings rotated by 180° and multiple first cell strings that are alternately arranged in the first direction. Each of the multiple first cell strings includes multiple second solar cells rotated by 180° and the multiple first solar cells that are alternately arranged in the second direction.

(9) In some embodiments, each of the multiple cell strings includes an odd number of solar cells, and the odd number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. A respective cell string group of the multiple cell string groups includes multiple first cell strings and multiple second cell strings rotated by 180° that are alternately arranged in the first direction, where each of the multiple first cell strings includes the multiple first solar cells and multiple second solar cells rotated by 180° that are alternately arranged in the second direction, and each of multiple second cell strings includes the multiple second solar cells rotated by 180° and the multiple first solar cells that are alternately arranged in the second direction.

(10) In some embodiments, in the second direction, each of the multiple first grid lines having the first conductivity type in a respective first solar cell of the multiple first solar cells and a corresponding second grid line having the second conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure. The each of the multiple first grid lines having the first conductivity type directly faces the corresponding second grid line having the second conductivity type; and each of the multiple second grid lines having the second conductivity type in a respective first solar cell of the multiple first solar cells and a corresponding first grid line having the first conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure. The each of the multiple second grid lines having the second conductivity type directly faces the corresponding first grid line having the first conductivity type.

(11) In some embodiments, in the second direction, in the second direction: a respective first grid line of each of at least one solar cell, of the corresponding first cell string group, adjacent to the respective middle first connection structure is on an extension line of a corresponding first grid line of each of at least one solar cell, of the corresponding second cell string group, adjacent to the respective middle first connection structure; and a respective second grid line of each of the at least one solar cell, of the corresponding first cell string group, adjacent to the respective middle first connection structure is on an extension line of a corresponding second grid line of each of the at least one solar cell, of the corresponding second cell string group, adjacent to the respective middle first connection structure.

(12) In some embodiments, the multiple first connection structures further include at least one end first connection structure, where another end of the respective cell string away from the corresponding middle first connection structure is connected with a corresponding end first connection structure. Each of the multiple cell strings includes an odd number of solar cells. In the first direction, a second connection structure connected to an end of a respective end first

connection structure is spaced apart by a distance M in the first direction from an adjacent second connection structure connected to an end of another end first connection structure adjacent to the respective end first connection structure, and the distance M is greater than twice the distance L .

(13) In some embodiments, the multiple first connection structures further include at least one end first connection structure. Another end of the respective cell string away from the corresponding middle first connection structure is connected with a corresponding end first connection structure. Each of the multiple cell strings includes an even number of solar cells. In the first direction, a second connection structure connected to an end of a respective end first connection structure is spaced apart by a distance N in the first direction from an adjacent second connection structure connected to an end of another end first connection structure adjacent to the respective end first connection structure, and the distance N is less than twice the distance L .

(14) In some embodiments, a respective solar cell of the multiple solar cells is a slice cell and includes an even number of grid lines.

(15) In some embodiments, a respective solar cell of the multiple solar cells is a back contact solar cell.

(16) In some embodiments, the distance S is greater than twice the distance L .

(17) In some embodiments, the distance L ranges from 3.5 mm to 20 mm; and/or the distance S is in the range of 8 mm to 50 mm.

(18) In some embodiments, for the multiple cell strings of each of the multiple cell string groups, a grid line on an edge of each of the multiple solar cells of a respective cell string of the multiple cell strings and a grid line on an edge of a corresponding solar cell on another cell string adjacent to the respective cell string are adjacent to each other and have opposite conductivity types.

(19) In some embodiments, each of the multiple first grid lines and the multiple second grid lines has a width ranging from 40 μm to 80 μm , and each of the multiple solar cells has a thickness in a range of 100 μm to 300 μm .

(20) Some embodiments of the disclosure further provide a method for manufacturing a photovoltaic module. The method includes the following. A battery module is formed. The battery module is formed as follows. Multiple cell string groups are formed. Corresponding cell strings are connected using the multiple first connection structures extending in the first direction. Specifically, the corresponding cell strings are connected as follows. At least one cell string of a respective first cell string group and at least one cell string of a corresponding second cell string group are connected with a corresponding middle first connection structure. The multiple cell string groups are formed as follows. For the each cell string group of the multiple cell string groups, the multiple cell strings are formed, including forming the each of the plurality of cell strings by electrically connecting the plurality of solar cells in the first electrical connection mode. The each of the at least one second connection structure in the solar cell at the end of the respective cell string is connected with the corresponding middle first connection structure such that the distance S is greater than the distance L .

(21) In some embodiments, each of the multiple cell strings includes an even number of solar cells, and the even number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. A respective first cell string group of the at least one first cell string group is formed as follows. Multiple first cell strings are formed. Each of the multiple first cell strings includes the multiple first solar cells and multiple second solar cells rotated by 180° that are alternately arranged in the second direction. The respective first cell string group is formed by alternately arranging, in the first direction, several first cell strings of the multiple third cell strings and several first cell strings rotated by 180° of the multiple first cell strings.

(22) In some embodiments, each of the multiple cell strings includes an even number of solar cells,

and the even number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. A respective second cell string group of the at least one second cell string group is formed as follows. Multiple first cell strings are formed. Each of the multiple first cell strings includes multiple second solar cells rotated by 180° and the multiple first solar cells that are alternately arranged in the second direction. The respective second cell string group is formed by alternately arranging, in the first direction, several first cell strings of the multiple first cell strings and several first cell strings rotated by 180° of the multiple first cell strings.

(23) In some embodiments, each of the multiple cell strings includes an odd number of solar cells, and the odd number of solar cells include multiple first solar cells and multiple second solar cells. A respective first solar cell of the multiple first solar cells and a respective second solar cell of the multiple second solar cells are obtained by slicing a respective initial cell of multiple initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell. A respective cell string group of the multiple cell string groups is formed as follows. Multiple first cell strings and multiple second cell strings are formed. Each of the multiple first cell strings includes the multiple first solar cells and multiple second solar cells rotated by 180° that are alternately arranged in the second direction, and each of multiple second cell strings includes the multiple second solar cells rotated by 180° and the multiple first solar cells that are alternately arranged in the second direction. The respective cell string group is formed by alternately arranging, in the first direction, the multiple first cell strings and the multiple second cell strings rotated by 180° .

(24) In some embodiments, in the second direction: each of the multiple first grid lines having the first conductivity type in a respective first solar cell of the multiple first solar cells and a corresponding second grid line having the second conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure, where the each of the multiple first grid lines having the first conductivity type directly faces the corresponding second grid line having the second conductivity type; and each of the multiple second grid lines having the second conductivity type in a respective first solar cell of the multiple first solar cells and a corresponding first grid line having the first conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure, where the each of the multiple second grid lines having the second conductivity type directly faces the corresponding first grid line having the first conductivity type.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) One or more embodiments are described as examples with reference to the corresponding figures in the accompanying drawings, and the examples do not constitute a limitation to the embodiments. The figures in the accompanying drawings do not constitute a proportion limitation unless otherwise stated. To describe the technical solutions of the implementations of the disclosure or the related art more clearly, the following will give a brief description of accompanying drawings used for describing the implementations of the disclosure or the related art. Apparently, the accompanying drawings described in the following are merely some implementations of the disclosure. Those of ordinary skill in the art can also obtain other accompanying drawings based on the accompanying drawings described below without creative efforts.

(2) FIG. 1 is a circuit connection diagram illustrating a battery module according to an embodiment

of the disclosure.

(3) FIG. 2 is a schematic structural diagram illustrating a photovoltaic module according to an embodiment of the disclosure.

(4) FIG. 3 is a schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure.

(5) FIG. 4 is another schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure.

(6) FIG. 5 is a schematic diagram illustrating another partial structure of the photovoltaic module according to an embodiment of the disclosure.

(7) FIG. 6 is a schematic structural diagram illustrating a photovoltaic module according to another embodiment of the disclosure.

(8) FIG. 7 is a schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure.

(9) FIG. 8 is a schematic diagram illustrating another partial structure of the photovoltaic module according to an embodiment of the disclosure.

(10) FIG. 9 is a sectional structural diagram illustrating the photovoltaic module according to an embodiment of the disclosure.

(11) FIG. 10 is a schematic structural diagram of forming an initial cell in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(12) FIG. 11 is a schematic structural diagram of forming a solar cell in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(13) FIG. 12 is a schematic structural diagram of forming a third cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(14) FIG. 13 is a schematic structural diagram of forming a fourth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(15) FIG. 14 is a schematic structural diagram of forming a cell string group in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(16) FIG. 15 is a schematic structural diagram of forming a fifth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(17) FIG. 16 is a schematic structural diagram of forming a sixth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(18) FIG. 17 is a schematic structural diagram of forming a cell string group in a method for manufacturing a photovoltaic module according to another embodiment of the disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(19) As stated above, existing photovoltaic modules are susceptible to short circuit caused by a relatively small spacing of lead lines.

(20) One of reasons for the small spacing of the lead lines is as follows. The preparation and arrangement of cell strings including IBC solar cells are basically consistent with those of conventional solar cells (i.e., non-back contact solar cells). Since positive and negative electrodes of the IBC solar cells are generally alternatively arranged and in parallel to each other, when the conventional preparation and arrangement process of cell strings is adopted, a spacing between of lead lines of adjacent cell strings is relatively small, which may lead to short circuit caused by the relatively small spacing of the lead lines.

(21) Embodiments of the disclosure aim to change a structure of the cell string and arrangement of cell strings in a cell string group, and ensure that a second connection structure connected to an end of a respective middle first connection structure is adjacent to another second connection structure connected to an end of another middle first connection structure adjacent to the respective middle first connection structure, and a distance S , in the first direction, between the second connection structure connected to the end of the respective middle first connection structure and the another second connection structure connected to the end of the another middle first connection structure is

greater than the distance L between the first grid line and the second grid line adjacent to the first grid line of the solar cell. Therefore, the spacing between adjacent lead lines connected with the middle first connection structures is relatively large, thereby avoiding short circuit. Moreover, since the spacing between the adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, so that the adjacent lead lines do not need to be insulated by isolation materials, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost.

(22) Various embodiments of the disclosure will be described in detail below with reference to the accompanying drawings. However, those of ordinary skill in the art should appreciate that many technical details have been proposed in various embodiments of the disclosure for better understanding of the disclosure. The technical solutions claimed in the disclosure is able to be realized even without these technical details as well as various changes and modifications based on the following embodiments.

(23) The terms “first”, “second”, “third”, and “fourth”, “fifth”, and “sixth”, and so on used in the specification, the claims, and the accompany drawings of the disclosure are merely used for description and cannot be understood as explicitly or implicitly indicating relative importance or the number of technical features referred to herein, or cannot be understood as a limitation of elements or components sequentially defined.

(24) The following will describe the technical solutions of the disclosure in detail with reference to the accompany drawings.

(25) FIG. 1 is a circuit connection diagram illustrating a battery module according to an embodiment of the disclosure. FIG. 2 is a schematic structural diagram illustrating a photovoltaic module according to an embodiment of the disclosure. FIG. 3 is a schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure. FIG. 4 is another schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure. FIG. 5 is a schematic diagram illustrating another partial structure of the photovoltaic module according to an embodiment of the disclosure. FIG. 6 is a schematic structural diagram illustrating a photovoltaic module according to another embodiment of the disclosure. FIG. 7 is a schematic diagram illustrating a partial structure of the photovoltaic module according to an embodiment of the disclosure. FIG. 8 is a schematic diagram illustrating another partial structure of the photovoltaic module according to an embodiment of the disclosure. FIG. 9 is a sectional structural diagram illustrating the photovoltaic module according to an embodiment of the disclosure. It is to be noted that in the figure, a difference between a first grid line and a second grid line is reflected by a thickness of the lines, where a thin line represents the first grid line and a thick line represents the second grid line. The “middle” in the middle first connection structure refers to the middle of a distance between two cell string groups that are connected in a second electrical connection mode or the middle of the battery module along a second direction Y. The “end” in an end first connection structure refers to an end of the battery module or an end of a cell string group close an edge of the battery module along the second direction Y.

(26) Referring to FIGS. 1 to 8, a photovoltaic module includes a battery module 10. The battery module 10 includes multiple cell string groups and multiple first connection structures. Each cell string group includes multiple cell strings 20 alternatively arranged along a first direction X, and the multiple cell strings 20 in the cell string group are connected in a first electrical connection mode. Each cell string 20 includes multiple solar cells 200 that are connected in the first electrical connection mode and multiple second connection structures 40. Each solar cell 200 has multiple first grid lines 201 of a first conductivity type interleaved with multiple second grid lines 202 of a second conductivity type, and in the first direction X, there is a distance L between a first grid line 201 and a second grid line 202 adjacent to the first grid line of the solar cell 200. The multiple cell string groups include one or more first cell string groups 11 and one or more second cell string

groups **12**. The one or more first cell string groups **11** and the one or more second cell string groups **12** are connected in a second electrical connection mode in a second direction Y. The multiple first connection structures extend in the first direction X, and the first connection structure is configured to connect cell strings **20**. The second connection structure **40** is configured to connect grid lines **210** (including first grid lines **201** and second grid line **202**), and each of at least one second connection structure **40** located at any end of a respective cell string is connected with a corresponding first connection structure. The multiple first connection structures include at least one middle first connection structure **31**. Each of the at least one middle first connection structure **31** is configured to connect at least one cell string **20** of a corresponding first cell string group **11** and at least one cell string **20** of a corresponding second cell string group **12**. A second connection structure **40** connected to an end of a respective middle first connection structure **31** is adjacent to another second connection structure **40** connected to an end of another adjacent middle first connection structure **31** adjacent to the respective middle first connection structure **31** and a distance S, in the first direction X, between the second connection structure **40** connected to the end of the respective middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure is greater than a distance L between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201** of the solar cell. By changing the structure of the cell string **20** and the arrangement of the cell strings **20** in the cell string group, it is ensured that the second connection structure **40** connected to the end of the middle first connection structure **31** is adjacent to the another second connection structure **40** connected to the end of the another middle first connection structure **31** and the distance S, in the first direction X, between the second connection structure **40** connected to the end of the middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure **31** is greater than the distance L between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201** of the solar cell. Therefore, the spacing between adjacent lead lines connected with the middle first connection structures is relatively large, thereby avoiding short circuit. Moreover, since the spacing between the adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, so that the adjacent lead lines do not need to be insulated by isolation materials, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost.

(27) The solar cell **200** is a slice cell. In some embodiments, the slice cell is a half-piece cell, which can also be understood as a half-cut cell or a two-split cell. In other embodiments, the slice cell may be a three-split cell, a four-split cell, an eight-split cell, or the like. The solar cell **200** is a back contact solar cell and the solar cell **200** includes grid lines **210**. The grid lines **210** are main grid lines of the solar cell **200** or electrodes of the solar cell **200**. The grid lines **210** may be divided into first grid lines **201** of the first conductivity type and second grid lines **202** of the second conductivity type in terms of conductivity types. The first grid lines **201** and the second grid lines **202** are alternatively arranged in the first direction X. There may be any number of the grid lines **210** (generally 8 to 30 grid lines **210**), and only the number of the first grid lines **201** and the number of the second grid lines **202** being equal is needed to be ensured. Preferably, the number of the grid lines **210** ranges from 14 to 22, such as, 8, 10, 12, 14, 16, 18, or 20. Each grid line **210** has a width ranging from 40 μm to 80 μm , such as, 40 μm , 50 μm , 60 μm , 70 μm , or 80 μm . Preferably, the width of the grid line **210** ranges from 50 μm to 60 μm , such as, 50 μm , 53 μm , 56 μm , or 60 μm . In other embodiments, the number of the first grid lines **201** and the number of the second grid lines **202** are not equal. For example, the number of the grid lines **210** may be 7, 9, 11, 13, 15, 17, or 19, and the number of the first grid lines **201** is 4 and the number of the second grid lines **202** is 3. In one example, it is assumed that the solar cell **200** has eight grid lines **210**, and the eight grid lines **210** includes four first grid lines **201** and four second grid lines **202**. The first conductivity type is a positive polarity and the second conductivity type is a negative polarity. The first electrical

connection mode is series connection, and a second electrical connection mode is parallel connection.

(28) In some embodiments, the solar cell **200** further includes secondary grid lines, and there may be any number of secondary grid lines. Generally, the number of the secondary grid lines ranges from 100 to 250, such as, 100, 110, 120, 130, 140, 150, 160, 170, or 180. Preferably, the number of the secondary grid lines is in a range of 140 to 180, such as, 148, 150, 156, 166, 171, 178, or 180. The secondary grid line has a width ranging from 20 μm to 60 μm , such as, 20 μm , 30 μm , 40 μm , 50 μm , or 60 μm . Preferably, the width of the secondary grid line is in the range of 20 μm to 40 μm , such as, 23 μm , 26 μm , 34 μm , or 39 μm . There may be 8 to 20 welding sections on the grid lines **210**, and the welding sections have a same area. In other embodiments, the welding sections may have different areas, for example, an area of the welding section on the grid line **210** of either of both ends of the cell string is larger than that of a welding section on the grid line **210** of the middle of the cell string. It will be understood that the welding section is a contact section where the grid line **210** is in contact with the second connection structure **40**.

(29) In some embodiments, the back contact solar cell includes a silicon substrate, a front surface field (FSF) layer (which has the same conductivity type as the silicon substrate) located on a first surface of the silicon substrate, and a first passivation layer located on a surface of the FSF layer, a first doped semiconductor layer and a second doped semiconductor layer that are located on a second surface of the silicon substrate, a second passivation layer, a first electrode, and second electrode. The second passivation layer is located on the surface of the first doped semiconductor layer, the second doped semiconductor layer, and the surface of the silicon substrate. The first electrode penetrates the second passivation layer and is connected with the first doped semiconductor layer. The second electrode penetrates the second passivation layer and is connected with the second doped semiconductor layer. In other embodiments, the back contact solar cell includes a silicon substrate, a first passivation layer, a first doped semiconductor layer, a tunneling oxide layer, a doped polysilicon layer, a second passivation layer, a first electrode, and a second electrode. The first passivation layer is disposed on a first surface of the silicon substrate. The first doped semiconductor layer is disposed on a second surface of the silicon substrate, where the first doped semiconductor layer may have the same conductivity type as the silicon substrate or may have a different conductivity type from the silicon substrate. The tunneling oxide layer and the doped polysilicon layer are sequentially disposed on the second surface of the silicon substrate. The second passivation layer is disposed on a surface of the first doping semiconductor layer and the doped polysilicon layer. The first electrode penetrates the second passivation layer and is then connected with the doped polysilicon layer. The second electrode penetrates the second passivation layer and is then connected with the first doped semiconductor layer. In other embodiments, the back contact solar cell includes a silicon substrate, a first passivation layer, a tunneling oxide layer, a first doped polysilicon layer, a second doped polysilicon layer, a second passivation layer, a first electrode, and a second electrode. The first passivation layer is disposed on a first surface of the silicon substrate. The tunneling oxide layer, the first doped polysilicon layer, and the second doped polysilicon layer are arranged on a second surface of the silicon substrate. The second passivation layer is disposed on a surface of the first doped polysilicon layer, the second doped polysilicon layer, and the silicon substrate. The first electrode penetrates the second passivation layer and is then connected with the first doped polysilicon layer. The second electrode penetrates the second passivation layer and is connected with the second doped polysilicon layer. It can be understood that the first surface is a front surface of the silicon substrate, the second surface is a back surface of the silicon substrate, the first doped semiconductor layer is one of a N-type doped semiconductor layer and a P-type doped semiconductor layer, and the second doped semiconductor layer is the other of the N-type doped semiconductor layer and the P-type doped semiconductor layer.

(30) In some embodiments, a thickness of the solar cell may be in a range of 100 μm to 300 μm , such as, 100 μm , 180 μm , 220 μm , or 300 μm . Preferably, the thickness of the solar cell may be in

the range of 120 to 180 μm , such as, 120 μm , 134 μm , 153 μm , or 179 μm . In other embodiments, a size of the solar cell **200** may be in a range of 150 mm to 300 mm, such as, 156.75 mm, 158.75 mm, 166 mm, 182 mm, or 210 mm. The solar cell **200** may be in the shape of a rectangle, a circle, a square, an approximately rectangle, or the like. In other embodiments, a ratio of the thickness to the width of the solar cell may be in the range of 0.5×10^3 to 2×10^3 , such as, 0.5×10^3 , 0.8×10^3 , 1.6×10^3 , or 1.89×10^3 . Preferably, a ratio of the thickness to the width of the solar cell may be ranging from 1×10^3 to 1.8×10^3 , such as, 1.1×10^3 , 1.32×10^3 , 1.65×10^3 , or 1.79×10^3 . In other embodiments, the solar cell **200** may be a monocrystalline silicon solar cell, a polysilicon solar cell, an amorphous silicon solar cell, or a multicomponent compound solar cell. The multicomponent compound solar cell may be a cadmium sulfide solar cell, a gallium arsenide solar cell, a copper indium selenium solar cell, or a perovskite solar cell. In one example, the ratio of the thickness to the width of the solar cell **200** is 1×10^3 , the thickness of the solar cell is 166 μm , the size of the entire solar cell **200** is 166 mm, the solar cell **200** may have a rectangular shape, and the solar cell **200** is a monocrystalline silicon solar cell.

(31) In some embodiments, the cell string group includes multiple first cell strings **21** and multiple second cell strings **22**, where the multiple first cell strings **21** and the multiple second cell strings **22** are alternately arranged. A grid line **210** on an edge of each of the multiple solar cells **200** of a respective first cell string **21** and a grid line **210** on an edge of a corresponding solar cell **200** on a second cell string **22** adjacent to the respective first cell string are adjacent to each other and have opposite conductivity types. The second connection structure **40** connected to the end of the respective middle first connection structure **31** is adjacent to the another second connection structure **40** connected to the end of the another middle first connection structure **31** adjacent to the respective middle first connection structure and the distance S, in the first direction X, between the second connection structure **40** connected to the end of the respective middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure **31** is greater than twice the distance L between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201** of the solar cell.

(32) In some embodiments, the cell string group sequentially includes a first cell string **21** and a second cell string **22** in the first direction X. Multiple first cell strings **21** and multiple second cell strings **22** are alternatively arranged and in parallel to one another in the first direction X. Electrode directions in the first cell string **21** and the second cell string **22** are opposite to each other, or current transmission directions in the first cell string **21** and the second cell string **22** are opposite to each other. A cell string group substantially having a rectangular shape is formed in a connection manner in which a positive electrode of a first cell string **21** is connected to a negative electrode of a second cell string **22** adjacent to the first cell string **21** and a positive electrode of the second cell string **22** is connected to a negative electrode of another first cell string **21** adjacent to the second cell string **22**.

(33) In some embodiments, in the second direction Y, a first respective first grid line **201** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** directly faces a corresponding first grid line **201** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. A respective second grid line **202** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** directly faces a corresponding second grid line **202** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. Therefore, in the second direction Y, each of at least one second connection structure **40** that is located on an upper side of the respective middle first connection structure **31** and connected with a corresponding first grid line **201** directly faces a corresponding second connection structure **40** located on a lower side of the respective middle first connection structure **31**. Compared with a scenario where the second connection structure **40**

located on the upper side of the middle first connection structure **31** does not directly face the second connection structure **40** located on the lower side of the middle first connection structure **31**, in this case, a length of the middle first connection structure **31** can be reduced, that is, the use of raw materials can be reduced, thereby reducing the manufacturing cost.

(34) In some embodiments, in the second direction Y, a first respective first grid line **201** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** is on an extension line of a corresponding first grid line **201** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. A respective second grid line **202** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** is on an extension line of a corresponding second grid line **202** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. In other embodiments, referring to FIG. 4, in the second direction Y, a first respective first grid line **201** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** is close to an extension line of a corresponding first grid line **201** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. A distance W, in the first direction X, between the respective first grid line **201** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** and the extension line of the corresponding first grid line **201** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31** is less than 0.5 times the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**. In the second direction Y, a respective second grid line **202** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** is close to an extension line of a corresponding second grid line **202** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31**. A distance U, in the first direction, between the respective second grid line **202** of each of the at least one solar cell **200**, of the corresponding first cell string group **11**, adjacent to the respective middle first connection structure **31** and the extension line of the corresponding second grid line **202** of each of the at least one solar cell **200**, of the corresponding second cell string group **12**, adjacent to the respective middle first connection structure **31** is less than 0.5 times the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**.

(35) In some embodiments, the middle first connection structure **31** is used for preventing the number of cell strings that are connected in parallel through an end first connection structure **32** from being too large to exceed a cell reverse bias limit, thereby avoiding damaging the photovoltaic module. The first connection structures further include multiple end first connection structures **32**. The end first connection structure **32** is an end bus bar. The other end of the respective cell string away from the corresponding middle first connection structure is connected with a corresponding end first connection structure. The end first connection structures **32** are respectively arranged on both ends of the battery module.

(36) In some embodiments, referring to FIG. 2 and FIG. 5, each cell string includes an odd number of solar cells **200**. In the first direction X, a second connection structure **40** connected to an end of a respective end first connection structure **32** is adjacent to another second connection structure **40** connected to an end of another end first connection structure **32** adjacent to the respective end first connection structure **32**. A distance M, in the first direction X, between the second connection structure **40** connected to the end of the respective end first connection structure **32** and the another second connection structure **40** connected to the end of the another end first connection structure **32** is greater than twice the distance L between the first grid line **201** and the second grid line **202** of

the solar cell **200**. In other embodiments, referring to FIG. 6 and FIG. 8, each cell string includes an even number of solar cells **200**. In the first direction X, a second connection structure **40** connected to an end of a respective end first connection structure **32** is adjacent to another second connection structure **40** connected to an end of another end first connection structure **32** adjacent to the respective end first connection structure **32**. A distance N, in the first direction X, between the second connection structure **40** connected to the end of the respective end first connection structure **32** and the another second connection structure **40** connected to the end of the another end first connection structure **32** is greater than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** is less than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**. In some embodiments, the photovoltaic module further includes: lead lines (not illustrated) and a junction box (not illustrated). The lead lines are connected to the middle first connection structures **31**, one of adjacent lead lines is connected to a positive output of a cell string and the other of the adjacent lead lines is connected to a negative output of another cell string **20** adjacent to the cell string. The junction box is provided with a diode, and both ends of the diode are connected in reverse parallel with the cell string through the lead lines, so as to avoid exceeding the cell reverse bias limit and further avoid damaging the photovoltaic module.

(37) In some embodiments, the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** ranges from 3.5 mm to 20 mm, for example, the distance L may be 4 mm, 8 mm, 12 mm, 16mm, or 19mm. Preferably, the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** ranges from 4 mm to 10 mm, such as, 4.3 mm, 5.6 mm, 6.3 mm, 8.2 mm, or 9.9 mm. The second connection structure **40** connected to the end of the respective middle first connection structure **31** is adjacent to the another second connection structure **40** connected to the end of the another middle first connection structure **31** adjacent to the respective middle first connection structure **31**, and the distance S, in the first direction X, between the second connection structure **40** connected to the end of the respective middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure **31** adjacent to the respective middle first connection structure **31** ranges from 8 mm to 50 mm, such as, 9 mm, 20 mm, 30 mm, 40 mm, or 45 mm. Preferably, the distance S, in the first direction X, between the second connection structure **40** and the another second connection structure **40** ranges from 10 mm to 25 mm, such as, 12 mm, 15 mm, 16.9 mm, 19 mm, or 23.9 mm. In one example, the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** is 4.3 mm, and the distance S, in the first direction X, between the second connection structure **40** and the another second connection structure **40** is 12 mm, such that the distance S is greater than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**. Therefore, the spacing between adjacent lead lines connected with the middle first connection structures is relatively large, thereby avoiding short circuit. Moreover, since the spacing between the adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, so that the adjacent lead lines do not need to be insulated by isolation materials, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost.

(38) In some embodiments, referring to FIG. 9, the photovoltaic module further includes a cover plate **51** and an encapsulation layer **52**. The encapsulation layer **52** may be an organic encapsulation film, such as, a Polyethylene vinylacetate (EVA) film or a Polyolefin elastomer (POE) film. The encapsulation layer **52** covers a surface of a cell string for sealing the cell string. The cover plate **51** may be a glass cover plate or a plastic cover plate, or the like. The cover plate **51** covers a surface of the encapsulation layer away from the cell string. The cover plate **51** is provided with a light trapping structure to increase the utilization rate of the incident light. The photovoltaic module has a relatively high current collection capacity and a relatively low carrier recombination rate, which can achieve relatively high photoelectric conversion efficiency.

(39) The embodiment of the disclosure provide a photovoltaic module, by changing the structure of the cell string **20** and the arrangement of the cell strings **20** in the cell string group, it is ensured that the second connection structure **40** connected to the end of the middle first connection structure **31** is adjacent to the another second connection structure **40** connected to the end of the another middle first connection structure **31** and the distance S, in the first direction X, between the second connection structure **40** connected to the end of the middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure **31** is greater than the distance L between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201** of the solar cell. Therefore, the spacing between adjacent lead lines connected with the middle first connection structures is relatively large, thereby avoiding short circuit. Moreover, since the spacing between the adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, so that the adjacent lead lines do not need to be insulated by isolation materials, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost.

(40) According to some embodiments of the disclosure, another aspect of the embodiment of the disclosure provides a method for manufacturing a photovoltaic module, to manufacture the photovoltaic module described in the above embodiments.

(41) FIG. **10** is a schematic structural diagram of forming an initial cell in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. Referring to FIG. **10**, multiple initial cells **220** are provided. The initial cell **220** is a back contact solar cell and the initial cell **220** has an even number of grid lines **210**. The grid line **210** is a main grid line or an electrode of the initial cell **220**. The grid lines **210** may be divided into first grid lines **201** of a first conductivity type and second grid lines **202** of a second conductivity type according to conductivity types. The first grid lines **201** and the second grid lines **202** are alternatively arranged at intervals in the first direction X, and there is a distance L, in the first direction X, between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201**. There may be any number of the grid lines **210** (generally 8 to 30 grid lines **210**), and only the number of the first grid lines **201** and the number of the second grid lines **202** being equal is needed to be ensured.

Preferably, the number of the grid lines **210** may range from 14 to 22, such as, 8, 10, 12, 14, 16, 18, or 20. Each grid line **210** has a width ranging from 40 μm to 80 μm . Preferably, the width of the grid line **210** ranges from 50 μm to 60 μm , such as, 50 μm , 53 μm , 56 μm , or 60 μm . In other embodiments, the number of the first grid lines **201** is not equal to the number of the second grid lines **202**, for example, the number of the first grid lines **201** is 4 and the number of the second grid lines **202** is 3. Specifically, it is assumed that each initial cell **220** has eight grid lines **210**, the first conductivity type is a positive polarity, and the second conductivity type is a negative polarity.

(42) FIG. **11** is a schematic structural diagram of forming a solar cell in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. Referring to FIG. **11**, an initial cell **220** is sliced to form two solar cells, where the two solar cells include a first solar cell **221** and a second solar cell **222**. The initial cell **220** is sliced to form the first solar cell **221** and the second solar cell **222**, and the first solar cell **221** and the second solar cell **222** are symmetrical relative to a cutting line A1-A2 (referring to FIG. **10**) of the initial cell. The first solar cell **221** has four first grid lines **201** and four second grid lines **202**. The first grid lines **201** and the second grid lines **202** are alternatively arranged at intervals. Similarly, the second solar cell **222** has four first grid lines **201** and four second grid lines **202**, and the first grid lines **201** and the second grid lines **202** are alternatively arranged at intervals.

(43) In other embodiments, the solar cells include a first solar cell, a second solar cell, and a third solar cell, i.e., the solar cell is a three-split cell. In still other embodiments, the solar cell is a four-split cell or an eight-split cell.

(44) FIG. **12** is a schematic structural diagram of forming a third cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. FIG. **13** is a

schematic structural diagram of forming a fourth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. FIG. 15 is a schematic structural diagram of forming a fifth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. FIG. 16 is a schematic structural diagram of forming a sixth cell string in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure.

(45) Referring to FIGS. 12, 13, 15, and 16, cell strings are formed. The cell strings include a third cell string 23, a fourth cell string 24, a fifth cell string 25, and a sixth cell string 26. The third cell string 23 or the fifth cell string 25 is formed by alternatively arranging, in the second direction Y, the first solar cells 221 and the second solar cells 222 rotated by 180°. The fourth cell string 24 or the sixth cell string 26 is formed by alternatively arranging, in the second direction Y, the second solar cells 222 rotated by 180° and the first solar cells 221.

(46) In some embodiments, the third cell string 23 and the fifth cell string 25 are formed as follows.

(47) At S1, the second connection structure 40 is electrically connected with the first grid line 201 of a first solar cell 221 by welding, bonding, or the like, and the second connection structure 40 extends in an extension direction of the grid line 210 and beyond an edge of a side of the first solar cell 221.

(48) At S2, the second solar cell 222 is rotated by 180°, to ensure that a polarity of each grid line 210 of the second solar cell 222 along the extension direction of the grid line 210 is reversed to that of a corresponding grid line 210 of the first solar cell 221, and an extension line of each grid line 210 of the second solar cell 222 and an extension line of the corresponding grid line 210 of the first solar cell 221 are on a same vertical line (i.e., the second direction Y) or overlapped. That is, each second grid line 202 of the second solar cell 222 directly faces a corresponding first grid line 201 of the first solar cell 221. The second connection structure 40 connects the second main grid line of the first solar cell 221 and the first grid line 201 of the second solar cell 222, respectively.

(49) At S3, another first solar cell 221 is placed after the second solar cell 222, and each of the second grid lines 202 of the second solar cell 222 that are not welded with second connection structures 40 is electrically connected with a corresponding first grid line of first grid lines 201 of the another first solar cell 221 through one second connection structure 40.

(50) Operations at S2 and S3 are continued to be performed until the last solar cell of the cell string is welded, where second connection structures 40 are respectively welded with grid lines 210 of the last solar cell of the cell string, and the second connection structure 40 extends in an extension direction of the grid line 210 and beyond an edge of a side of the last solar cell.

(51) Referring to FIG. 12, when the cell string includes an even number of solar cells, the last solar cell of the cell string is the second solar cell 222, and each of the second connection structures 40 located at one end of the cell string directly face a corresponding second connection structure 40 located at the other end of the cell string, or each of the second connection structures 40 connected to the first solar cell 221 of the cell string is on an extension line of the corresponding second connection structure 40 connected to the last solar cell of the cell string. The cell string formed is the third cell string 23.

(52) Referring to FIG. 15, when the cell string includes an odd number of solar cells, the last solar cell of the cell string is the first solar cell 221. In the first direction X, a distance between each of the second connection structures 40 located at one end of the cell string and the corresponding second connection structure 40 located at the other end of the cell string is the distance L between the first grid line 201 and the second grid line 202 adjacent to the first grid line 201. That is, the distance between each of the second connection structures 40 connected to the first of the solar cells of the cell string and the extension line of the corresponding second connection structure 40 connected to the last solar cell of the cell string is the distance L between the first grid line 201 and the second grid line 202 (referring to FIG. 11). The cell string formed is the fifth cell string 25.

(53) In some embodiments, the fourth cell string 24 and the sixth cell string 26 are formed as

follows.

(54) At S1, the second solar cell **222** is rotated by 180° , and each of second connection structures **40** is electrically connected with a corresponding first grid line **201** of the second solar cell **222** by welding, bonding, etc. The second connection structure **40** extends in an extension direction of the grid line **210** and beyond an edge of a side of the second solar cell **222**.

(55) At S2, a first solar cell **221** is placed on a side of the second solar cell **222** away from the second connection structure **40**, to ensure that a polarity of each of grid lines **210** of the second solar cell **222** along the extension direction of the grid line **210** is reversed to that of a corresponding grid line **210** of the first solar cell **221**, and an extension line of each grid line **210** of the second solar cell **222** and an extension line of the corresponding grid line **210** of the first solar cell **221** are on a same vertical line or overlapped. That is, each second grid line **202** of the second solar cell **222** directly faces the corresponding first grid line **201** of the first solar cell **221**. The second connection structure **40** connects the first main grid line of the first solar cell **221** and the second grid line **202** of the second solar cell **222**, respectively.

(56) At S3, another second solar cell **222** is rotated by 180° and then placed after the first solar cell **221**, and each of the second grid lines **202** of the first solar cell **221** that are not welded with the second connection structures **40** is electrically connected with a corresponding first grid lines **201** of the another second solar cell **222** through one second connection structure **40**.

(57) Operations at S2 and S3 are continued to be performed until the welding of the last solar cell of each cell string is completed, where the second connection structures **40** are respectively welded with grid lines **210** of the last solar cell of the cell string, and the second connection structure **40** extends in the extension direction of the grid line **210** and beyond an edge of a side of the last solar cell.

(58) Referring to FIG. 13, when the cell string includes an even number of solar cells, the last solar cell of the cell string is the first solar cell **221**, each of the second connection structures **40** located at one end of the cell string directly face a corresponding second connection structure **40** located at the other end of cell string, or each of the second connection structures **40** connected to the first solar cell of the cell string is on an extension line of the corresponding second connection structure **40** connected to the last solar cell of the cell string. The cell string formed is the fourth cell string **24**.

(59) Referring to FIG. 16, when the cell string includes an odd number of solar cells, the last solar cell of the cell string is the second solar cell. In the first direction X, a distance between each of the second connection structures **40** located at one end of the cell string and the corresponding second connection structure **40** located at the other end of the cell string is the distance L between the first grid line **201** and the second grid line **202**. That is, the distance between each of the second connection structures **40** connected to the first of the solar cells of the cell string and the extension line of the corresponding second connection structure **40** connected to the last solar cell of the cell string is the distance L between the first grid line **201** and the second grid line **202** (referring to FIG. 11). The cell string formed is the sixth cell string **26**.

(60) It can be understood that the first solar cell **221** and the second solar cell **222** are symmetrical relative to the cutting line A1-A2 (referring to FIG. 10) of the initial cell **220**. The first solar cell **221** and the second solar cell **222** illustrated are illustrative only, and the first of solar cells may be the first solar cell **221** or the second solar cell **222**.

(61) FIG. 14 is a schematic structural diagram of forming a cell string group in a method for manufacturing a photovoltaic module according to an embodiment of the disclosure. FIG. 17 is a schematic structural diagram of forming cell string group in a method for manufacturing a photovoltaic module according to another embodiment of the disclosure.

(62) Referring to FIGS. 14 and 17, multiple cell string groups are formed. Multiple cell strings are connected in a first electrical connection mode to form a cell string group, and the multiple cell strings **20** are alternatively arranged in the first direction X. The cell string group includes multiple

first cell strings and multiple second cell strings, where the multiple first cell strings and the multiple second cell strings are alternatively arranged. A grid line **210** on an edge of each of the solar cells **200** of a respective first cell string **21** and a grid line **210** on an edge of a corresponding solar cell **200** of a second cell string **22** adjacent to the respective first cell string are adjacent to each other and have opposite conductivity types. The cell string groups includes at least one first cell string group **11** and at least one second cell string group **12**. The first cell string group **11** and the second cell string group **12** are connected in a second electrical connection mode in the second direction Y. Specifically, the first electrical connection mode is series connection, and the second electrical connection mode is parallel connection.

(63) In some embodiments, referring to FIG. **14**, each cell string includes an even number of solar cells **200**. The first cell string group **11** and the second cell string group **12** are formed as follows. In the first direction X, multiple third cell strings and multiple third cell strings rotated by 180° are alternatively arranged to form the first cell string group **11**, and multiple fourth cell strings rotated by 180° and multiple fourth cell strings are alternatively arranged to form the second cell string group **12**. In other embodiments, referring to FIG. **17**, a cell string group is formed as follows. Multiple fifth cell strings and multiple sixth cell string rotated by 180° are alternatively arranged in the first direction X to form the cell string group.

(64) Continuing to refer to FIGS. **14** and **17**, a battery module is formed, where multiple cell string groups form the battery module.

(65) In some embodiments, the method for manufacturing the photovoltaic module further includes the following. Multiple first connection structure and multiple second connection structures **40** are provided. The first connection structure extends in the first direction X, and each first connection structure is configured to connect cell strings. Each second connection structure **40** is configured to connect grid lines **210**. The first connection structures include at least one middle first connection structure **31**. Each middle first connection structure **31** connects at least one cell string of a corresponding first cell string group **11** and at least one cell string of a corresponding second cell string group **12**. Each of at least one second connection structure **40** located at an end of a respective cell string is connected to a corresponding middle first connection structure **31**. A second connection structure **40** connected to an end of a respective middle first connection structure **31** and another second connection structure **40** connected to an end of another middle first connection structure **31** adjacent to the respective middle first connection structure **31** are adjacent to each other and have a distance S along the first direction X therebetween, where the distance S is greater than the distance L between the first grid line **201** and the second grid line **202** adjacent to the first grid line **201** of the solar cell. Therefore, the spacing between adjacent lead lines connected with the middle first connection structures is relatively large, thereby avoiding short circuit. Moreover, since the spacing between the adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, so that the adjacent lead lines do not need to be insulated by isolation materials, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost. In other embodiments, the second connection structure **40** connected to the end of the respective middle first connection structure **31** and the another second connection structure **40** connected to the end of the another middle first connection structure **31** are adjacent to each other and have a distance S in the first direction X therebetween, where the distance S is greater than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell.

(66) In some embodiments, the first connection structures further include at least one end first connection structure **32**. The end first connection structure **32** is an end bus bar. each end first connection structure **32** is connected with the other end of a corresponding cell string away from a corresponding middle first connection structure **31**. The end first connection structures **32** are respectively disposed on both ends of the battery module.

(67) In some embodiments, referring to FIG. **17**, each cell string includes an odd number of solar

cells **200**. In the first direction X, a second connection structure **40** connected to an end of a respective end first connection structure **32** is adjacent to another second connection structure **40** connected to an end of another end first connection structure **32** adjacent to the respective second connection structure **40**, and a distance M between the second connection structure **40** connected to the end of the respective end first connection structure **32** and the another second connection structure **40** connected to the end of the another end first connection structure **32** adjacent to the respective second connection structure **40** is greater than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**. In other embodiments, referring to FIG. **12**, the cell string includes an even number of solar cells **200**. In the first direction X, the second connection structure **40** connected to the end of the respective end first connection structure **32** is adjacent to the another second connection structure **40** connected to the end of the another end first connection structure **32** adjacent to the respective end first connection structure **32**, and the distance N between the second connection structure **40** connected to the end of the respective end first connection structure **32** and the another second connection structure **40** connected to the end of the another end first connection structure **32** adjacent to the respective end first connection structure **32** is less than twice the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200**.

(68) In some embodiments, for each second connection structure **40** of the multiple second connection structures, in the second direction, the second connection structure **40** connects a first grid line **201** having a first conductivity type in a corresponding first solar cell **221** and a second grid line **202** having a second conductivity type in a second solar cell **222** adjacent to the corresponding first solar cell **221**, where the first grid line **201** in the first solar cell **221** directly faces the second grid line **202** in the second solar cell **222**. Alternatively, in the second direction, the second connection structure **40** connects the second grid line **202** having the second conductivity type in the corresponding first solar cell **221** and a first grid line **201** having the first conductivity type in the second solar cell **222** adjacent to the corresponding first solar cell, where the second grid line **202** in the corresponding first solar cell **221** directly faces the first grid line **201** in the second solar cell **222**.

(69) In some embodiments, after the battery module is formed, the following can be further conducted. Lead lines and a junction box are formed. The lead line is connected to the middle first connection structure **31**, one of adjacent lead lines is connected to a positive output of a cell string and the other of the adjacent lead lines is connected to a negative output of another cell string **20** adjacent to the cell string. The junction box is provided with diodes, and both ends of the diode are connected in reverse parallel with the cell string through the lead lines, so as to avoid exceeding the cell reverse bias limit and further avoid damaging the photovoltaic module.

(70) In some embodiments, the distance L between the first grid line **201** and the second grid line **202** of the solar cell ranges from 3.5 mm to 20 mm. Preferably, the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** ranges from 4 mm to 10 mm, such as, 4.3 mm, 5.6 mm, 6.3 mm, 8.2 mm, or 9.9 mm. The second connection structure **40** connected to the end of the middle first connection structure **31** is adjacent to the another second connection structure **40** connected to the end of the another adjacent middle first connection structure **31** and the distance S, in the first direction X, between the second connection structure **40** connected to the end of the middle first connection structure **31** and the another second connection structure **40** connected to the end of the another adjacent middle first connection structure **31** ranges from 8 mm to 50 mm. Preferably, the distance S, in the first direction X, between the second connection structure **40** and the another second connection structure **40** ranges from 10 mm to 25 mm, such as, 12 mm, 15 mm, 16.9 mm, 19 mm, or 23.9 mm. In one example, the distance L between the first grid line **201** and the second grid line **202** of the solar cell **200** is 4.3 mm, and the distance S, in the first direction X, between the second connection structure **40** and the another second connection structure **40** is 12 mm, such that the distance S is greater than twice the distance L between the first

grid line **201** and the second grid line **202** of the solar cell **200**. Therefore, the spacing between the adjacent lead lines connected to the middle first connection structures **31** is relatively large, and short circuit may be avoided. Moreover, since the distance between adjacent lead lines is relatively large, that is, there is no contact between the adjacent lead lines, and isolation materials are not needed for insulation, which not only simplifies the process, improves the processing efficiency, but also reduces the use of raw materials and reduces the manufacturing cost.

(71) Those of ordinary skill in the art should appreciate that the embodiments described above are specific embodiments of the disclosure, and in practical application, various changes may be made thereto in form and detail without departing from the scope of the disclosure. Any one of those skilled in the art may make their own changes and modifications without departing from the scope of the present disclosure. Therefore, the protection scope of the disclosure shall be subject to the scope defined in the claims.

Claims

1. A photovoltaic module, comprising a battery module, wherein the battery module comprises: a plurality of cell string groups, wherein each cell string group of the plurality of cell string groups includes a plurality of cell strings arranged along a first direction and electrically connected in a first electrical connection mode, wherein the plurality of cell string groups include at least one first cell string group and at least one second cell string group, and wherein a respective cell string group of the at least one first cell string group and a corresponding cell string group of the at least one second cell string group are arranged along a second direction and electrically connected in a second electrical connection mode; and a plurality of first connection structures extending in the first direction, wherein each of the plurality of first connection structures is configured to connect corresponding cell strings, and wherein the plurality of first connection structures include at least one middle first connection structure, and each middle first connection structure is configured to connect at least one cell string of a corresponding first cell string group and at least one cell string of a corresponding second cell string group; wherein each of the plurality of cell strings comprises: a plurality of solar cells electrically connected in the first electrical connection mode, wherein each solar cell of the plurality of solar cells comprises a plurality of first grid lines of a first conductivity type interleaved with a plurality of second grid lines of a second conductivity type, and each first grid line is spaced from an adjacent second grid line by a distance L in the first direction, wherein a respective solar cell of the plurality of solar cells is a back contact solar cell; and a plurality of second connection structures, wherein each of the plurality of second connection structures is configured to connect corresponding grid lines; wherein: each of at least one second connection structure in a solar cell at an end of a respective cell string is connected with a corresponding first connection structure; and a second connection structure connected to an end of a respective middle first connection structure is spaced apart by a distance S in the first direction from an adjacent second connection structure connected to an end of another middle first connection structure adjacent to the respective middle first connection structure, and the distance S is greater than the distance L ; wherein the plurality of first connection structures further comprise at least one end first connection structure, wherein another end of the respective cell string away from the corresponding middle first connection structure is connected with a corresponding end first connection structure; wherein each of the plurality of cell strings comprises an even number of solar cells, wherein in the first direction, a second connection structure connected to an end of a respective end first connection structure is spaced apart by a distance N in the first direction from an adjacent second connection structure connected to an end of another end first connection structure adjacent to the respective end first connection structure, and the distance N is less than twice the distance L .

2. The photovoltaic module of claim 1, wherein each of the plurality of cell strings comprises an even number of solar cells, and the even number of solar cells comprise a plurality of first solar

cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein each of the at least one first cell string group comprises a plurality of first cell strings and a plurality of first cell strings rotated by 180° that are alternately arranged in the first direction, wherein each of the plurality of first cell strings comprises the plurality of first solar cells and the plurality of second solar cells rotated by 180° that are alternately arranged in the second direction.

3. The photovoltaic module of claim 1, wherein each of the plurality of cell strings comprises an even number of solar cells, and the even number of solar cells comprise a plurality of first solar cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein each of the at least one second cell string group comprises a plurality of first cell strings rotated by 180° and a plurality of first cell strings that are alternately arranged in the first direction, wherein each of the plurality of first cell strings comprises the plurality of second solar cells rotated by 180° and the plurality of first solar cells that are alternately arranged in the second direction.

4. The photovoltaic module of claim 1, wherein each of the plurality of cell strings comprises an odd number of solar cells, and the odd number of solar cells comprise a plurality of first solar cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein a respective cell string group of the plurality of cell string groups comprises a plurality of first cell strings and a plurality of second cell strings rotated by 180° that are alternately arranged in the first direction, wherein each of the plurality of first cell strings comprises the plurality of first solar cells and the plurality of second solar cells rotated by 180° that are alternately arranged in the second direction, and each of plurality of second cell strings comprises the plurality of second solar cells rotated by 180° and the plurality of first solar cells that are alternately arranged in the second direction.

5. The photovoltaic module of claim 4, wherein in the second direction, each of the plurality of first grid lines having the first conductivity type in a respective first solar cell of the plurality of first solar cells and a corresponding second grid line having the second conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure, wherein the each of the plurality of first grid lines having the first conductivity type directly faces the corresponding second grid line having the second conductivity type; and each of the plurality of second grid lines having the second conductivity type in a respective first solar cell of the plurality of first solar cells and a corresponding first grid line having the first conductivity type in a second solar cell adjacent to the respective first solar cell are connected through a corresponding second connection structure, wherein the each of the plurality of second grid lines having the second conductivity type directly faces the corresponding first grid line having the first conductivity type.

6. The photovoltaic module of claim 1, wherein in the second direction: a respective first grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding first cell string group adjacent to the respective middle first connection structure is on an extension line of a corresponding first grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding second cell string group adjacent to the respective middle first connection structure; and a respective second grid line of the solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding first cell string

group adjacent to the respective middle first connection structure is on an extension line of a corresponding second grid line of the solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding second cell string group adjacent to the respective middle first connection structure.

7. The photovoltaic module of claim 1, wherein a respective solar cell of the plurality of solar cells is a slice cell and comprises an even number of grid lines.

8. The photovoltaic module of claim 1, wherein the distance S is greater than twice the distance L .

9. The photovoltaic module of claim 1, wherein the distance L ranges from 3.5 mm to 20 mm.

10. The photovoltaic module of claim 1, wherein the distance S is in the range of 8 mm to 50 mm.

11. The photovoltaic module of claim 1, wherein for the plurality of cell strings of each of the plurality of cell string groups, a grid line on an edge of each of the plurality of solar cells of a respective cell string of the plurality of cell strings and a grid line on an edge of a corresponding solar cell on another cell string adjacent to the respective cell string are spaced apart from each other and have opposite conductivity types.

12. The photovoltaic module of claim 1, wherein each of the plurality of first grid lines and the plurality of second grid lines has a width ranging from 40 μm to 80 μm , and each of the plurality of solar cells has a thickness in a range of 100 μm to 300 μm .

13. A method for manufacturing the photovoltaic module of claim 1, comprising: forming the battery module, including: forming the plurality of cell string groups; and connecting corresponding cell strings using the plurality of first connection structures extending in the first direction, including connecting at least one cell string of a respective first cell string group and at least one cell string of a corresponding second cell string group with a corresponding middle first connection structure; wherein forming the plurality of cell string groups comprises, for the each cell string group of the plurality of cell string groups: forming the plurality of cell strings, including forming the each of the plurality of cell strings by electrically connecting the plurality of solar cells in the first electrical connection mode; and connecting the each of the at least one second connection structure in the solar cell at the end of the respective cell string with the corresponding middle-first connection structure such that the distance S is greater than the distance L .

14. The method of claim 13, wherein each of the plurality of cell strings comprises an even number of solar cells, and the even number of solar cells comprise a plurality of first solar cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein forming a respective first cell string group of the at least one first cell string group comprises: forming a plurality of first cell strings; wherein each of the plurality of first cell strings comprises the plurality of first solar cells and a plurality of second solar cells rotated by 180° that are alternately arranged in the second direction; and forming the respective first cell string group by alternately arranging, in the first direction, several first cell strings of the plurality of first cell strings and several first cell strings rotated by 180° of the plurality of first cell strings.

15. The method of claim 13, wherein each of the plurality of cell strings comprises an even number of solar cells, and the even number of solar cells comprise a plurality of first solar cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein forming a respective second cell string group of the at least one second cell string group comprises: forming a plurality of first cell strings, wherein each of the plurality of first cell strings comprises a plurality of second solar cells rotated by 180° and the plurality of first solar cells that are alternately arranged in the second direction; and forming the respective second cell string group

by alternately arranging, in the first direction, several first cell strings of the plurality of first cell strings and several first cell strings rotated by 180° of the plurality of first cell strings.

16. The method of claim 13, wherein each of the plurality of cell strings comprises an odd number of solar cells, and the odd number of solar cells comprise a plurality of first solar cells and a plurality of second solar cells, wherein a respective first solar cell of the plurality of first solar cells and a respective second solar cell of the plurality of second solar cells are obtained by slicing a respective initial cell of a plurality of initial cells, and the respective first solar cell and the respective second solar cell are symmetrical relative to a cutting line of the respective initial cell, wherein forming a respective cell string group of the plurality of cell string groups comprises: forming a plurality of first cell strings and a plurality of second cell strings, wherein each of the plurality of first cell strings comprises the plurality of first solar cells and a plurality of second solar cells rotated by 180° that are alternately arranged in the second direction, and each of plurality of second cell strings comprises the plurality of second solar cells rotated by 180° and the plurality of first solar cells that are alternately arranged in the second direction; and forming the cell string group by alternately arranging, in the first direction, the plurality of first cell strings and the plurality of second cell strings rotated by 180° .

17. The method of claim 16, wherein in the second direction, connecting each of the plurality of first grid lines having the first conductivity type in a respective first solar cell of the plurality of first solar cells and a corresponding second grid line having the second conductivity type in a second solar cell adjacent to the respective first solar cell through a corresponding second connection structure, wherein the each of the plurality of first grid lines having the first conductivity type directly faces the corresponding second grid line having the second conductivity type; and connecting each of the plurality of second grid lines having the second conductivity type in a respective first solar cell of the plurality of first solar cells and a corresponding first grid line having the first conductivity type in a second solar cell adjacent to the respective first solar cell through a corresponding second connection structure, wherein the each of the plurality of second grid lines having the second conductivity type directly faces the corresponding first grid line having the first conductivity type.

18. The photovoltaic module of claim 1, wherein in the second direction: a respective first grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding first cell string group adjacent to the respective middle first connection structure is spaced apart by a distance W in the first direction from an extension line of a corresponding first grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding second cell string group adjacent to the respective middle first connection structure, and the distance W is less than 0.5 times the distance L.

19. The photovoltaic module of claim 1, wherein in the second direction: a respective second grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding first cell string group adjacent to the respective middle first connection structure is spaced apart by a distance U in the first direction from an extension line of a corresponding second grid line of a solar cell of the plurality of solar cells of each of the at least one cell string of the corresponding second cell string group adjacent to the respective middle first connection structure, and the distance U is less than 0.5 times the distance L.
